



US 20130180526A1

(19) **United States**

(12) **Patent Application Publication**
Ronen et al.

(10) **Pub. No.: US 2013/0180526 A1**
(43) **Pub. Date: Jul. 18, 2013**

(54) **WEANING FROM VENTILATION USING CAPNOGRAPHY**

Publication Classification

(75) Inventors: **Michal Ronen**, Givat-Brenner (IL);
Sharon Einav, Zur Hadassah (IL);
Keren Davidpur,
Modi'in-Maccabim-Reut (IL)

(51) **Int. Cl.**
A61B 5/00 (2006.01)
A61B 5/08 (2006.01)
(52) **U.S. Cl.**
CPC *A61B 5/4836* (2013.01); *A61B 5/082*
(2013.01)
USPC **128/204.23**; 600/532

(73) Assignee: **Oridion Medical 1987 Ltd.**, Jerusalem (IL)

(21) Appl. No.: **13/703,162**

(57) **ABSTRACT**

(22) PCT Filed: **Jun. 9, 2011**


(86) PCT No.: **PCT/IL2011/000453**


§ 371 (c)(1),
(2), (4) Date: **Apr. 4, 2013**

There is provided herein a method for monitoring weaning of a subject from a respiratory ventilator, the method comprising characterizing distinct patterns in a series of CO₂ waveforms obtained from expired breath of a subject undergoing respiratory ventilation weaning, wherein said distinct patterns are indicative to the effectiveness of a weaning process and wherein said distinct patterns are selected from a group consisting of "sigh events", "spike events" and "pools"; and providing an indication relating to the effectiveness of the weaning process.

Related U.S. Application Data

(60) Provisional application No. 61/353,243, filed on Jun. 10, 2010.





TIME (min)

FIG.1A

WEANING FROM VENTILATION USING CAPNOGRAPHY

FIELD OF THE INVENTION

[0001] Embodiments of the invention are related to the use of capnography in weaning a patient from a ventilator.

BACKGROUND

[0002] Mechanical ventilatory support is widely accepted as an effective form of therapy and means for treating patients with respiratory failure. The early generation of mechanical ventilators, prior to the mid-1960s, were designed to support alveolar ventilation and to provide supplemental oxygen for those patients who were unable to breathe on their own. Since that time, mechanical ventilators have become more sophisticated and complicated in response to increasing understanding of lung pathophysiology. For example, CPAP (Continuous Positive Airway Pressure), BiPAP (Bilevel Positive Airway Pressure) and SIMV (Synchronized Intermittent Mandatory Ventilation) are effective in preventing need for intubation and also decreasing mortality in patients with acute respiratory failure.

[0003] Even though the ventilator technology is constantly improving, ventilator dependence is still a serious medical and economic problem. It is well known that severe and sometimes lethal complications may develop the longer a patient is on ventilator support. In addition, as ventilator therapy is provided in specialized and very expensive Intensive Care Unit environments, there is a need to minimize ventilator dependency. Weaning the patients from artificial ventilation is among the most difficult challenges of the regarding intensive care ventilation.

[0004] Prior art ventilator weaning monitoring methods are not efficient enough and are often depending on subjective impressions of clinical fatigue or distress and/or arterial blood gas derangements that of necessity measure failure after the failure has already developed. More modern monitoring techniques such as the ratio of Tidal Volume to Respiratory Rate are still relatively crude indices of weaning performance. Weaning from ventilator dependency is potentially hazardous due to unexpected precipitous ventilatory failure, and early warning by appropriate monitoring means is imperative for patient safety. Further, controlled stress of weakened respiratory muscles is imperative in order to recondition these muscles, but in addition to not over-stress these recovering muscles and therefore cause further damage. It is often difficult to safely define the proper degree of weaning stress clinically.

[0005] There is thus a need in the art for systems, devices and methods that would allow monitoring the constantly changing condition of a patient undergoing weaning from ventilation.

[0006] The foregoing examples of the related art and limitations related therewith are intended to be illustrative and not exclusive. Other limitations of the related art will become apparent to those of skill in the art upon a reading of the specification and a study of the figures.

SUMMARY

[0007] The following embodiments and aspects thereof are described and illustrated in conjunction with systems, tools and methods which are meant to be exemplary and illustrative, not limiting in scope.

[0008] In accordance with some aspects of the invention, systems, devices, and methods are provided, which facilitate the monitoring the effectiveness and progression of a weaning process using data related to the level of CO₂ in the expired breath of a ventilated patient.

[0009] In accordance with some embodiments of the invention, it was surprisingly found that certain characteristics or combination of characteristics relating to CO₂ waveform(s) of the expired breath of a patient are indicative to how well the weaning process is progressing. Characteristics related to CO₂ waveform(s) may include, for example, CO₂ waveform characteristics, characteristics or behavior of groups of CO₂ waveforms, time dependent behavior of the CO₂ waveforms, the frequency of appearance of certain characteristics, the ratios between certain characteristics or any combination thereof.

[0010] In accordance with some embodiments of the invention, there is provided a method for monitoring a respiratory patient to evaluate respiratory ventilator weaning (and/or train the patient for respiratory ventilator weaning), the method comprising characterizing one or more CO₂ waveforms obtained from expired breath of the respiratory patient (for example, detecting distinct patterns such as “sigh events”, “spike events” and “pools” among “regular” CO₂ waveforms, see FIG. 1-3 and the “Detailed Description section) and evaluating respiratory ventilator weaning of the patient. The method may further include providing a signal to the ventilator at least partially based on the characterized one or more CO₂ waveforms and thus inducing a change of one or more parameters of the ventilator (for example, changing the level of support to the ventilation, allowing the patient to rest from the weaning attempts, changing the mode/program of weaning, etc.).

[0011] In accordance with some embodiments of the invention, there is provided a device for monitoring a respiratory patient to evaluate respiratory ventilator weaning (and/or train the patient for respiratory ventilator weaning), the device comprising:

[0012] a capnograph configured to provide one or more CO₂ waveforms;

[0013] processing logic configured to: (a) characterize the one or more CO₂ waveforms obtained by the capnograph (for example, detecting distinct patterns in the CO₂ waveforms, such as, “sigh events”, “spike events” and “pools” among “regular” CO₂ waveforms, see FIG. 1-3 and the “Detailed Description section); and (b) provide a signal to the ventilator at least partially based on the characterized one or more CO₂ waveforms thereby induce a change of one or more parameters of the ventilator (for example, changing the level of support to the ventilation, allowing the patient to rest from the weaning attempts, changing the mode/program of weaning, etc.).

[0014] The prevalence and frequency of the waveforms characteristics, such as the above mentioned events as an indicator may be different for different ventilator modes. In other words, depending on the ventilator mode the event (for example, “sigh event”) frequency may have a different meaning. One could also perform coordinated changes in the ventilator parameters/modes (for example, reductions of pressure support) and evaluate the consequent change in event pattern and accordingly continue or stop the process.

[0015] The processing logic may be further configured to provide the signal to the ventilator based on other parameters, in addition to the characteristics of the CO₂ waveforms. Such

parameters may include general patient parameters, such as age, medical condition, medical history, medications or any other parameter. The parameters may also include respiratory related parameters such as respiration rate, tidal volumes, minute ventilation (the total lung ventilation per minute), inspiration rate and expiration rate at ambient pressure in the absence of ventilator assistance, ventilator mode, ventilator setup parameters or any other parameter.

[0016] In accordance with some embodiments of the invention, there is provided a method for monitoring weaning of a subject from a respiratory ventilator, the method comprising characterizing distinct patterns in a series of CO₂ waveforms obtained from expired breath of a subject undergoing respiratory ventilation weaning, wherein said distinct patterns are indicative to the effectiveness of a weaning process and wherein said distinct patterns are selected from a group consisting of “sigh events”, “spike events” and “pools” and providing an indication relating to the effectiveness of the weaning process.

[0017] The method may further include providing a signal to a ventilator at least partially based on the characterized distinct patterns in the series of CO₂ waveforms and thus inducing a change in one or more parameters of the ventilator.

[0018] In accordance with some embodiments of the invention, there is provided a device for monitoring weaning of a subject from a respiratory ventilator, the device comprising: processing logic configured to characterize distinct patterns in the series of CO₂ waveforms, wherein said distinct patterns are indicative to the effectiveness of a weaning process and wherein said distinct patterns are selected from a group consisting of “sigh events”, “spike events” and “pools”, wherein said processing logic is further configured to provide an indication relating to the effectiveness of the weaning process.

[0019] In accordance with some embodiments of the invention, there is provided a system for monitoring weaning of a subject from a respiratory ventilator, the system comprising: a capnograph configured to provide a series of CO₂ waveforms obtained from expired breath of a subject undergoing respiratory ventilation weaning; and processing logic configured to characterize distinct patterns in the series of CO₂ waveforms, wherein said distinct patterns are indicative to the effectiveness of a weaning process and wherein said distinct patterns are selected from a group consisting of “sigh events”, “spike events” and “pools”, wherein said processing logic is further configured to provide an indication relating to the effectiveness of the weaning process.

[0020] The change in one or more parameters of the ventilator may include a change in the level of support to the ventilation, allowing the patient to rest from weaning attempts, changing a mode/program of weaning or any combination thereof.

[0021] Providing a signal to the ventilator may further be based on one or more additional parameters selected from the group consisting of: age of the subject, medical condition of the subject, medical history of the subject and medications administered to the subject.

[0022] Providing a signal to the ventilator may further be based on one or more additional parameters selected from the group consisting of: respiration rate, tidal volumes, minute ventilation (the total lung ventilation per minute), inspiration rate and expiration rate at ambient pressure in the absence of ventilator assistance, ventilator mode and ventilator setup parameters.

[0023] Characterizing distinct patterns in a series of CO₂ waveforms may include segmenting the series of CO₂ waveforms into breaths (waveforms), and calculating for each breath one or more features.

[0024] The one or more features may include: area under the curve (AUC), breath duration (inhalation, expiration or both), I to E ratio, maximal CO₂ value, minimal CO₂ value or any combination thereof.

[0025] Characterizing distinct patterns in the series of CO₂ waveforms may include determining the extent and/or frequency of appearance of said distinct patterns. Characterizing distinct patterns in the series of CO₂ waveforms may include determining the ratios between the distinct patterns.

[0026] The processing logic may further be configured to provide a signal to a ventilator at least partially based on the characterized distinct patterns in the series of CO₂ waveforms and thus inducing a change in one or more parameters of the ventilator.

[0027] In addition to the exemplary aspects and embodiments described above, further aspects and embodiments will become apparent by reference to the figures and by study of the following detailed description.

BRIEF DESCRIPTION OF THE FIGURES

[0028] Exemplary embodiments are illustrated in referenced figures. Dimensions of components and features shown in the figures are generally chosen for convenience and clarity of presentation and are not necessarily shown to scale. It is intended that the embodiments and figures disclosed herein are to be considered illustrative rather than restrictive. The figures are listed below.

[0029] FIGS. 1 A and B show series of CO₂ waveforms in a weaning patient, according to some embodiments of the invention;

[0030] FIG. 2 shows a series of CO₂ waveforms in a weaning patient, according to some embodiments of the invention;

[0031] FIGS. 3 A and B show series of CO₂ waveforms in a weaning patient, according to some embodiments of the invention;

[0032] FIG. 4 shows a series of CO₂ waveforms in different ventilation modes (CPAP, SIMV and VS), according to some embodiments of the invention;

[0033] FIG. 5 shows a “zoom-in” series of CO₂ waveforms taken from the CPAP section of FIG. 4, according to some embodiments of the invention;

[0034] FIG. 6 shows a “zoom-in” series of CO₂ waveforms taken a few minutes after starting the VS section of FIG. 4, according to some embodiments of the invention; and

[0035] FIG. 7 shows a “zoom-in” series of CO₂ waveforms taken from the VS section of FIG. 4, according to some embodiments of the invention.

DETAILED DESCRIPTION

[0036] In accordance with some embodiments of the invention, certain types of distinct breathing patterns (characteristics) in data obtained from ventilated patients during weaning process were found and evaluated.

[0037] According to some embodiments, the CO₂ signal obtained from expired air of a subject was segmented into breaths (waveforms), and one or more features for each breath were calculated. Example of such features include area under the curve (AUC), breath duration (inhalation, expiration or both), I to E ratio (the ratio between inhalation to expiration in

a breath), maximal CO₂ value, minimal CO₂ value, presence of small “dip(s)” in the waveform plateau or in the inhalation part of the breath (a dip in a waveform may be due to breathing effort that the ventilation does not capture), and other features.

[0038] The extent and/or frequency of appearance of these features may, over time, create certain patterns. According to some embodiments, these patterns may be indicative to the effectiveness of a weaning process. Three patterns were determined by their relative value of a feature or values of a set of features (as discussed herein according to some embodiments) compared to a pre-defined base-line or to an average or median feature value before weaning started (for example, when full ventilation was still applied) or to an average or median feature value obtained during a specific time period (for example the last X hours, such as 2-10, 12 to 24). The following three patterns were determined:

[0039] 1) Sigh Events: breaths with relatively large AUC (for example, compared to an average or median AUC value before weaning started or to the average or median AUC value obtained during a specific time period) or relatively high breath duration (for example, compared to an average or median breath duration value before weaning started or to an average or median breath duration value obtained during a specific time period) or any other typical feature.

[0040] 2) Spike Events: breaths with very small AUC (for example, compared to an average or median AUC value before weaning started or to the average or median AUC value obtained during a specific time period) or relatively small breath duration and/or relatively low maximal CO₂ or any other typical feature (for example, compared to the respective feature value before weaning started or to an average or median respective feature value obtained during a specific time period).

[0041] 3) Pools: group of breaths with relatively low AUC (for example, compared to an average or median AUC value before weaning started or to the average or median AUC value obtained during a specific time period) or low maximal CO₂ or low breath duration or any other typical feature (for example, compared to the respective feature value before weaning started or to an average or median respective feature value obtained during a specific time period).

[0042] FIGS. 1-3 show series of CO₂ waveforms of weaning patients, according to some embodiments of the invention. In each one of FIGS. 1-3 the distinct patterns (FIG. 1: “sigh events”, FIG. 2: “spike events” and FIG. 3 “pools”) are marked by arrows and can easily be observed among the “regular” breaths.

[0043] The patterns appear in different frequencies during weaning, at different modes of ventilation (CPAP, SIMV and VS), as shown in FIG. 4. The arrows indicate the ventilation mode at that time.

[0044] FIG. 5 shows a “zoom-in” series of CO₂ waveforms taken from the CPAP section of FIG. 4, according to some embodiments of the invention. The deterioration of the patient’s condition with time, during CPAP ventilation can clearly be seen by the higher frequency of “pools” (see arrow).

[0045] FIG. 6 shows a “zoom-in” series of CO₂ waveforms taken a few minutes after starting the VS section of FIG. 4, according to some embodiments of the invention. The “sigh events” are marked by arrows.

[0046] FIG. 7 shows a “zoom-in” series of CO₂ waveforms taken from the VS section of FIG. 4, according to some

embodiments of the invention. The deterioration of the patient’s condition with time, during VS can clearly be seen by the higher frequency of “pools” (marked by horizontal arrows) in addition to the “sigh events” (marked by arrows).

[0047] It is also noted that some of the characteristics (for example, the pooling effect) occurred together with changes in the Respiration Rate.

[0048] The appearance of the distinct patterns (for example, the “sigh events”, “spike events” and “pools”), their frequencies and extent, could serve as indicators for progress of the weaning process. Of course, the three distinct patterns disclosed herein are merely examples and other distinct patterns (characteristics) that appear in the CO₂ waveforms or waveforms series may also be indicative to the progress and effectiveness of the weaning process.

[0049] According to some embodiments, the appearance of CO₂ distinct patterns their frequencies and/or extent, optionally together with additional ventilator parameter (such as ventilation modes, tidal volume, minute ventilation, and PEEP (Positive End-Expiratory Pressure)) may serve as indicators to the progress and effectiveness of the weaning process.

[0050] The appearance of the CO₂ distinct patterns, their frequencies and/or extent, together with additional ventilator parameter (such as ventilation modes, tidal volume, minute ventilation and PEEP) may also serve as indicators for ventilation related conditions such as air-leaks, a-synchrony, rebreathing, changes in compliance, obstruction and triggering effort.

[0051] Referring to the term “a-synchrony”: During weaning the patient breaths spontaneously and the ventilator “helps” by “filling in” and adding flow, for example, or in other ways (depending on the ventilator mode). A-synchrony is when the settings of the ventilator are such that it interferes with the spontaneous breathing. For example, the patient tries to start a new breath in the middle of a ventilator breath.

[0052] Referring to the term “Rebreathing”: breathing a new breath without finishing the previous breath.

What we claim is:

1. A method for monitoring weaning of a subject from a respiratory ventilator, the method comprising:
 - characterizing distinct patterns in a series of CO₂ waveforms obtained from expired breath of a subject undergoing respiratory ventilation weaning, wherein said distinct patterns are indicative to the effectiveness of a weaning process and wherein said distinct patterns are selected from a group consisting of “sigh events”, “spike events” and “pools”; and
 - providing an indication relating to the effectiveness of the weaning process.
2. The method of claim 1, further comprising providing a signal to a ventilator at least partially based on the characterized distinct patterns in the series of CO₂ waveforms and thus inducing a change in one or more parameters of the ventilator.
3. The method of claim 2, wherein said change in one or more parameters of the ventilator comprises a change in the level of support to the ventilation, allowing the patient to rest from weaning attempts, changing a mode/program of weaning or any combination thereof.
4. The method of claim 2, wherein providing a signal to the ventilator is further based on one or more additional parameters selected from the group consisting of: age of the subject, medical condition of the subject, medical history of the subject and medications administered to the subject.

5. The method of claim 2, wherein providing a signal to the ventilator is further based on one or more additional parameters selected from the group consisting of: respiration rate, tidal volumes, minute ventilation (the total lung ventilation per minute), inspiration rate and expiration rate at ambient pressure in the absence of ventilator assistance, ventilator mode and ventilator setup parameters.

6. The method of claim 1, wherein characterizing distinct patterns in a series of CO₂ waveforms comprises segmenting the series of CO₂ waveforms into breaths (waveforms), and calculating for each breath one or more features.

7. The method of claim 1, wherein the one or more features comprise: area under the curve (AUC), breath duration (inhalation, expiration or both), I to E ratio, maximal CO₂ value, minimal CO₂ value or any combination thereof.

8. The method of claim 1, wherein characterizing distinct patterns in the series of CO₂ waveforms comprises determining the extent and/or frequency of appearance of said distinct patterns.

9. The method of claim 1, wherein characterizing distinct patterns in the series of CO₂ waveforms comprises determining the ratios between the distinct patterns.

10. A device for monitoring weaning of a subject from a respiratory ventilator, the device comprising:

processing logic configured to characterize distinct patterns in the series of CO₂ waveforms, wherein said distinct patterns are indicative to the effectiveness of a weaning process and wherein said distinct patterns are selected from a group consisting of "sigh events", "spike events" and "pools", wherein said processing logic is further configured to provide an indication relating to the effectiveness of the weaning process.

11. The device of claim 10, wherein said processing logic is further configured to provide a signal to a ventilator at least partially based on the characterized distinct patterns in the series of CO₂ waveforms and thus inducing a change in one or more parameters of the ventilator.

12. The device of claim 11, wherein said change in one or more parameters of the ventilator comprises a change in the level of support to the ventilation, allowing the patient to rest from weaning attempts, changing a mode/program of weaning or any combination thereof.

13. The device of claim 11, wherein providing a signal to the ventilator is further based on one or more additional parameters selected from the group consisting of: age of the subject, medical condition of the subject, medical history of the subject and medications administered to the subject.

14. The device of claim 11, wherein providing a signal to the ventilator is further based on one or more additional parameters selected from the group consisting of: respiration rate, tidal volumes, minute ventilation (the total lung ventilation per minute), inspiration rate and expiration rate at ambient pressure in the absence of ventilator assistance, ventilator mode and ventilator setup parameters.

15. The device of claim 10, wherein characterizing distinct patterns in a series of CO₂ waveforms comprises segmenting the series of CO₂ waveforms into breaths (waveforms), and calculating for each breath one or more features.

16. The device of claim 10, wherein the one or more features comprise: area under the curve (AUC), breath duration (inhalation, expiration or both), I to E ratio, maximal CO₂ value, minimal CO₂ value or any combination thereof.

17. The device of claim 10, wherein characterizing distinct patterns in the series of CO₂ waveforms comprises determining the extent and/or frequency of appearance of said distinct patterns.


18. The device of claim 10, wherein characterizing distinct patterns in the series of CO₂ waveforms comprises determining the ratios between the distinct patterns.

19. A system for monitoring weaning of a subject from a respiratory ventilator, the system comprising:

a capnograph configured to provide a series of CO₂ waveforms obtained from expired breath of a subject undergoing respiratory ventilation weaning; and


processing logic configured to characterize distinct patterns in the series of CO₂ waveforms, wherein said distinct patterns are indicative to the effectiveness of a weaning process and wherein said distinct patterns are selected from a group consisting of "sigh events", "spike events" and "pools", wherein said processing logic is further configured to provide an indication relating to the effectiveness of the weaning process.

* * * * *




TIME (sec)

FIG.1B




TIME (min)

FIG.2




TIME (min)

FIG.3A



TIME (sec)

FIG.3B



TIME (min)
FIG.4






FIG.5



TIME (min)

FIG.6



TIME (sec)

FIG. 7

专利名称(译)	使用二氧化碳图进行通气断奶		
公开(公告)号	US20130180526A1	公开(公告)日	2013-07-18
申请号	US13/703162	申请日	2011-06-09
[标]申请(专利权)人(译)	RONEN MICHAL EINAV SHARON DAVIDPUR KEREN		
申请(专利权)人(译)	RONEN , MICHAL EINAV , SHARON DAVIDPUR , KEREN		
当前申请(专利权)人(译)	ORIDION MEDICAL 1987年LTD.		
[标]发明人	RONEN MICHAL EINAV SHARON DAVIDPUR KEREN		
发明人	RONEN, MICHAL EINAV, SHARON DAVIDPUR, KEREN		
IPC分类号	A61B5/00 A61B5/08		
CPC分类号	A61B5/0836 A61M16/0051 A61M2230/432 A61B5/082 A61B5/4836 A61M16/085 A61B5/4848 A61B5/7264 A61B5/7275 A61B5/7282 A61M16/0069 A61B5/7278 A61B5/7235 A61M16/0057 A61M16/021 A61M2230/005 A61M2230/42		
优先权	61/353243 2010-06-10 US		
其他公开文献	US8695596		
外部链接	Espacenet USPTO		

摘要(译)

本文提供了一种用于监测来自呼吸呼吸机的受试者断奶的方法，该方法包括表征从进行呼吸通气断奶的受试者的呼气呼吸获得的一系列CO₂波形中的不同模式，其中所述不同模式指示有效性。断奶过程中，所述不同的模式选自“叹息事件”，“尖峰事件”和“池”；并提供有关断奶过程有效性的指示。

