



US008852099B2

(12) **United States Patent**  
**Von Arx et al.**

(10) **Patent No.:** **US 8,852,099 B2**  
(45) **Date of Patent:** **\*Oct. 7, 2014**

(54) **SYSTEMS AND METHODS FOR DERIVING  
RELATIVE PHYSIOLOGIC  
MEASUREMENTS**

(75) Inventors: **Jeffrey A. Von Arx**, Minneapolis, MN  
(US); **Scott T. Mazar**, Woodbury, MN  
(US); **Abhi Chavan**, Maple Grove, MN  
(US)

(73) Assignee: **Cardiac Pacemakers, Inc.**, St. Paul,  
MN (US)

(\* ) Notice: Subject to any disclaimer, the term of this  
patent is extended or adjusted under 35  
U.S.C. 154(b) by 8 days.

This patent is subject to a terminal dis-  
claimer.

(21) Appl. No.: **13/564,332**

(22) Filed: **Aug. 1, 2012**

(65) **Prior Publication Data**

US 2012/0296177 A1 Nov. 22, 2012

**Related U.S. Application Data**

(63) Continuation of application No. 10/943,627, filed on  
Sep. 17, 2004, now Pat. No. 8,271,093.

(51) **Int. Cl.**

**A61B 5/00** (2006.01)  
**A61M 5/142** (2006.01)  
**A61N 1/372** (2006.01)  
**A61M 5/172** (2006.01)

(52) **U.S. Cl.**

CPC ..... **A61N 1/37252** (2013.01); **A61N 1/37223**  
(2013.01); **A61M 2230/30** (2013.01); **A61B**  
**5/0031** (2013.01); **A61M 5/1723** (2013.01);  
**A61N 1/37217** (2013.01); **A61M 2205/3523**  
(2013.01); **A61M 5/14276** (2013.01); **A61M**  
**2205/52** (2013.01)

USPC ..... **600/301**

(58) **Field of Classification Search**

USPC ..... 607/60; 600/301, 485, 49  
See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

2,786,899 A 3/1957 Carlisle  
3,310,885 A 3/1967 Alderson  
(Continued)

FOREIGN PATENT DOCUMENTS

EP 0897690 2/1999  
EP 0928598 7/1999  
(Continued)

OTHER PUBLICATIONS

B. C. Penney et al., "Simplified electrode array for impedance cardi-  
ography," *Medical & Biological Engineering & Computing*, 1985,  
23, p. 1-7.

(Continued)


*Primary Examiner* — Alyssa M Alter

(74) *Attorney, Agent, or Firm* — Faegre Baker Daniels LLP

(57) **ABSTRACT**

One embodiment of the present invention relates to a system for deriving physiologic measurement values that are relative to ambient conditions. In one embodiment, the system comprises an implantable medical device ("IMD"), an external computing device, and a backend computing system. The IMD determines a physiologic parameter value within a patient's body, and communicates the physiologic parameter value outside the patient's body, for example, to the external computing device. Further, the external computing device receives the physiologic parameter from the IMD and communicates it to the backend computing system. The backend computing system receives the physiologic parameter value and obtains an ambient condition value outside the body. The backend computing system then calculates a relative physiologic parameter value from the ambient condition value and the physiologic parameter value, and in some embodiments, stores the relative physiologic parameter value in a storage location, such as a memory or database.

**23 Claims, 12 Drawing Sheets**



(56)

## References Cited

## U.S. PATENT DOCUMENTS

3,320,946 A	5/1967	Dethloff et al.	5,279,309 A	1/1994	Taylor et al.
3,536,836 A	10/1970	Pfeiffer	5,279,607 A	1/1994	Schentag et al.
3,568,661 A	3/1971	Franklin	5,289,821 A	3/1994	Swartz
3,672,352 A	6/1972	Summers	5,300,092 A	4/1994	Schaldach
3,692,027 A	9/1972	Ellinwood	5,314,457 A	5/1994	Jeutter et al.
3,757,770 A	9/1973	Brayshaw et al.	5,329,459 A	7/1994	Kaufman et al.
3,794,840 A	2/1974	Scott	5,330,505 A	7/1994	Cohen
3,943,915 A	3/1976	Severson	5,339,051 A	8/1994	Koehler et al.
4,003,379 A	1/1977	Ellinwood	5,368,040 A	11/1994	Carney
4,041,954 A	8/1977	Ohara	5,375,603 A	12/1994	Feiler
4,099,530 A	7/1978	Chen et al.	5,394,457 A	2/1995	Leibinger et al.
4,127,110 A	11/1978	Bullara	5,397,329 A	3/1995	Allen
4,146,029 A	3/1979	Ellinwood	5,411,535 A	5/1995	Fujii et al.
4,223,801 A	9/1980	Carlson	5,411,551 A	5/1995	Winston et al.
4,227,407 A	10/1980	Drost	5,417,717 A	5/1995	Salo et al.
4,237,900 A	12/1980	Schulman et al.	5,423,334 A	6/1995	Jordan
4,281,664 A	8/1981	Duggen	5,438,990 A	8/1995	Wahlstrand et al.
4,360,019 A	11/1982	Portner et al.	5,445,608 A	8/1995	Chen et al.
4,407,296 A	10/1983	Anderson	5,454,838 A	10/1995	Vallana et al.
4,450,527 A	5/1984	Sramek	5,469,859 A	11/1995	Tsoglin et al.
4,480,483 A	11/1984	McShane	5,476,488 A	12/1995	Morgan et al.
4,519,401 A	5/1985	Ko et al.	5,488,954 A	2/1996	Sleva et al.
4,541,431 A	9/1985	Ibrahim et al.	5,490,962 A	2/1996	Cima et al.
4,543,955 A	10/1985	Schroepfel	5,509,424 A	4/1996	Al-Ali
4,550,370 A	10/1985	Baker	5,528,067 A	6/1996	Farb
4,585,004 A	4/1986	Brownlee	5,535,752 A	7/1996	Halperin et al.
4,593,703 A	6/1986	Cosman	5,558,091 A	9/1996	Acker et al.
4,600,855 A	7/1986	Strachan	5,562,714 A	10/1996	Greivous
4,616,640 A	10/1986	Kaali et al.	5,564,434 A	10/1996	Halperin et al.
4,651,740 A	3/1987	Schroepfel	5,571,152 A	11/1996	Chen et al.
4,653,508 A	3/1987	Cosman	5,604,531 A	2/1997	Iddan et al.
4,660,568 A	4/1987	Cosman	5,619,997 A	4/1997	Kaplan
4,676,255 A	6/1987	Cosman	5,626,630 A	5/1997	Markowitz et al.
4,677,985 A	7/1987	Bro et al.	5,628,782 A	5/1997	Myers
4,680,957 A	7/1987	Dodd	5,642,731 A	7/1997	Kehr
4,686,987 A	8/1987	Salo et al.	5,643,327 A	7/1997	Dawson et al.
4,697,595 A	10/1987	Breyer et al.	5,650,770 A	7/1997	Schlager et al.
4,768,176 A	8/1988	Kehr et al.	5,656,428 A	8/1997	McAllister et al.
4,768,177 A	8/1988	Kehr et al.	5,704,352 A	1/1998	Tremblay et al.
4,781,715 A	11/1988	Wurzel	5,705,753 A	1/1998	Hastings et al.
4,791,936 A	12/1988	Snell et al.	5,728,281 A	3/1998	Holmstrom et al.
4,793,825 A	12/1988	Benjamin et al.	5,729,129 A	3/1998	Acker
4,809,697 A	3/1989	Causey, III et al.	5,733,313 A	3/1998	Barreras, Sr. et al.
4,845,503 A	7/1989	Adam et al.	5,735,887 A	4/1998	Barreras, Sr. et al.
4,846,191 A	7/1989	Brockway et al.	5,741,316 A	4/1998	Chen et al.
4,854,327 A	8/1989	Kunig	5,749,909 A	5/1998	Schroepfel et al.
4,886,064 A	12/1989	Strandberg	5,752,235 A	5/1998	Kehr et al.
4,899,752 A	2/1990	Cohen	5,752,976 A	5/1998	Duffin et al.
4,909,259 A	3/1990	Tehrani	5,755,766 A	5/1998	Chastain et al.
4,918,736 A	4/1990	Bordewijk	5,769,877 A	6/1998	Barreras, Sr.
4,945,914 A	8/1990	Allen	5,776,324 A	7/1998	Usala
4,967,749 A	11/1990	Cohen	5,792,195 A	8/1998	Carlson et al.
4,986,270 A	1/1991	Cohen	5,796,827 A	8/1998	Coppersmith et al.
4,991,579 A	2/1991	Allen	5,800,478 A	9/1998	Chen et al.
4,995,068 A	2/1991	Chou et al.	5,807,258 A	9/1998	Cimochowski et al.
4,995,398 A	2/1991	Turnidge	5,807,395 A	9/1998	Mulier et al.
5,003,976 A	4/1991	Alt	5,807,397 A	9/1998	Barreras
5,024,224 A	6/1991	Engebretson	5,810,009 A	9/1998	Mine et al.
5,025,795 A	6/1991	Kunig	5,810,735 A	9/1998	Halperin et al.
5,029,582 A	7/1991	Lekholm	5,832,924 A	11/1998	Archibald et al.
5,040,536 A	8/1991	Riff	5,833,603 A	11/1998	Kovacs et al.
5,040,538 A	8/1991	Mortazavi	5,835,455 A	11/1998	Hanson et al.
5,113,859 A	5/1992	Funke	5,836,300 A	11/1998	Mault
5,154,171 A	10/1992	Chirife	5,843,135 A	12/1998	Weijand et al.
5,161,536 A	11/1992	Vilkomerson et al.	5,855,609 A	1/1999	Knapp
5,163,429 A	11/1992	Cohen	5,856,722 A	1/1999	Haronian et al.
5,178,151 A	1/1993	Sackner	5,868,673 A	2/1999	Vesely
5,178,153 A	1/1993	Einzig	5,873,835 A	2/1999	Hastings et al.
5,190,035 A	3/1993	Salo et al.	5,886,267 A	3/1999	Ortiz
5,199,428 A	4/1993	Obel et al.	5,891,180 A	4/1999	Greeninger et al.
5,200,891 A	4/1993	Kehr et al.	5,904,708 A	5/1999	Goedeke et al.
5,213,098 A	5/1993	Bennett et al.	5,911,685 A	6/1999	Siess et al.
5,246,008 A	9/1993	Mueller	5,919,221 A	7/1999	Miesel
5,267,174 A	11/1993	Kaufman et al.	5,941,249 A	8/1999	Maynard
5,277,191 A	1/1994	Hughes	5,954,641 A	9/1999	Kehr et al.
			5,957,950 A	9/1999	Mockros et al.
			5,967,986 A	10/1999	Cimochowski et al.
			5,979,898 A	11/1999	Pan
			6,002,963 A	12/1999	Mouchawar et al.

(56)

## References Cited

## U.S. PATENT DOCUMENTS

6,023,641	A	2/2000	Thompson	6,783,499	B2	8/2004	Schwartz
6,024,704	A	2/2000	Meador et al.	6,792,308	B2	9/2004	Corbucci
6,053,873	A	4/2000	Govari et al.	6,792,311	B2	9/2004	Fox et al.
6,083,248	A	7/2000	Thompson	6,805,667	B2	10/2004	Christopherson et al.
6,112,116	A	8/2000	Fischell et al.	6,809,507	B2	10/2004	Morgan et al.
6,123,861	A	9/2000	Santini, Jr. et al.	6,824,512	B2	11/2004	Warkentin et al.
6,140,740	A	10/2000	Porat et al.	6,840,956	B1	1/2005	Wolinsky et al.
6,141,588	A	10/2000	Cox et al.	6,855,115	B2	2/2005	Fonseca et al.
6,152,885	A	11/2000	Taepke	6,859,665	B2	2/2005	Ding et al.
6,155,267	A	12/2000	Nelson	6,865,419	B2	3/2005	Mulligan et al.
6,161,032	A	12/2000	Acker	6,868,346	B2	3/2005	Larson et al.
6,162,238	A	12/2000	Kaplan et al.	6,869,404	B2	3/2005	Schulhauser et al.
6,171,252	B1	1/2001	Roberts	6,871,088	B2	3/2005	Chinchoy
6,179,767	B1	1/2001	Ziegler et al.	6,885,889	B2	4/2005	Chinchoy
6,185,452	B1	2/2001	Schulman et al.	6,889,086	B2	5/2005	Mass et al.
6,198,965	B1	3/2001	Penner et al.	6,895,265	B2	5/2005	Silver
6,200,265	B1	3/2001	Walsh et al.	6,907,285	B2	6/2005	Denker et al.
6,234,973	B1	5/2001	Meador et al.	6,915,162	B2	7/2005	Noren et al.
6,236,889	B1	5/2001	Soykan et al.	6,926,670	B2	8/2005	Rich et al.
6,237,398	B1	5/2001	Porat et al.	6,937,900	B1	8/2005	Pianca et al.
6,239,724	B1	5/2001	Doron et al.	6,949,075	B2	9/2005	Hatlesad et al.
6,248,080	B1	6/2001	Miesel et al.	6,961,448	B2	11/2005	Nichols et al.
6,256,538	B1	7/2001	Ekwall	6,970,742	B2	11/2005	Mann et al.
6,266,567	B1	7/2001	Ishikawa et al.	6,978,182	B2	12/2005	Mazar et al.
6,273,904	B1	8/2001	Chen et al.	6,985,773	B2	1/2006	Von Arx et al.
6,277,078	B1	8/2001	Porat et al.	6,993,393	B2	1/2006	Von Arx et al.
6,278,894	B1	8/2001	Salo et al.	7,003,350	B2	2/2006	Denker et al.
6,305,381	B1	10/2001	Weijand et al.	7,018,336	B2	3/2006	Enegren et al.
6,308,099	B1	10/2001	Fox et al.	7,024,248	B2	4/2006	Penner et al.
6,330,957	B1	12/2001	Bell-Greenstreet	7,033,322	B2	4/2006	Silver
6,331,163	B1	12/2001	Kaplan	7,035,684	B2	4/2006	Lee
6,368,275	B1	4/2002	Sliwa et al.	7,047,065	B2	5/2006	Kalgren et al.
6,397,661	B1	6/2002	Grimes et al.	7,060,030	B2	6/2006	Von Arx et al.
6,409,674	B1	6/2002	Brockway et al.	7,061,381	B2	6/2006	Forcier et al.
6,409,675	B1	6/2002	Turcott	7,088,254	B2	8/2006	Liebenow
6,411,850	B1	6/2002	Kay et al.	7,127,290	B2	10/2006	Girouard et al.
6,416,474	B1	7/2002	Penner et al.	7,134,999	B2	11/2006	Brauker et al.
6,431,175	B1	8/2002	Penner et al.	7,136,703	B1	11/2006	Cappa et al.
6,432,050	B1	8/2002	Porat et al.	7,160,252	B2	1/2007	Cho et al.
6,438,408	B1	8/2002	Mulligan et al.	7,195,594	B2	3/2007	Eigler et al.
6,441,747	B1	8/2002	Khair et al.	7,198,603	B2	4/2007	Penner et al.
6,442,413	B1	8/2002	Silver	7,200,439	B2	4/2007	Zdeblick et al.
6,445,953	B1	9/2002	Bulkes et al.	7,203,545	B2	4/2007	Schmitt et al.
6,456,883	B1	9/2002	Torgerson et al.	7,204,798	B2	4/2007	Zdeblick et al.
6,471,645	B1	10/2002	Warkentin et al.	7,212,861	B1	5/2007	Park et al.
6,472,991	B1	10/2002	Schulman et al.	7,214,189	B2	5/2007	Zdeblick
6,475,170	B1	11/2002	Doron et al.	7,236,821	B2	6/2007	Cates et al.
6,486,588	B2	11/2002	Doron et al.	7,248,923	B2	7/2007	Maile et al.
6,504,286	B1	1/2003	Porat et al.	7,273,457	B2	9/2007	Penner
6,522,914	B1	2/2003	Huvelle et al.	7,294,105	B1	11/2007	Islam
6,567,700	B1	5/2003	Turcott et al.	7,335,161	B2	2/2008	Von Arx et al.
6,574,510	B2	6/2003	Von Arx et al.	7,399,313	B2	7/2008	Brown et al.
6,580,946	B2	6/2003	Struble	7,425,200	B2	9/2008	Brockway et al.
6,604,000	B2	8/2003	Lu	7,452,334	B2	11/2008	Gianchandani et al.
6,607,485	B2	8/2003	Bardy	7,481,771	B2	1/2009	Fonseca et al.
6,609,023	B1	8/2003	Fischell et al.	7,641,619	B2	1/2010	Penner
6,615,083	B2	9/2003	Kupper	8,271,093	B2*	9/2012	Von Arx et al. .... 607/60
6,622,049	B2	9/2003	Penner et al.	2002/0023123	A1	2/2002	Madison
6,628,989	B1	9/2003	Penner et al.	2002/0042561	A1	4/2002	Schulman et al.
6,638,231	B2	10/2003	Govari et al.	2002/0045804	A1*	4/2002	Christopherson et al. .... 600/300
6,644,322	B2	11/2003	Webb	2002/0045812	A1	4/2002	Ben-Haim et al.
6,654,638	B1	11/2003	Sweeney	2002/0045836	A1	4/2002	Alkawwas
6,675,049	B2	1/2004	Thompson et al.	2002/0147406	A1	10/2002	von Segesser
6,699,186	B1	3/2004	Wolinsky et al.	2002/0151770	A1	10/2002	Noll, III et al.
6,702,847	B2	3/2004	DiCarlo	2002/0183628	A1	12/2002	Reich et al.
6,708,061	B2	3/2004	Salo et al.	2002/0188323	A1	12/2002	Penner et al.
6,708,065	B2	3/2004	Von Arx et al.	2003/0009204	A1	1/2003	Amundson et al.
6,712,772	B2	3/2004	Cohen et al.	2003/0114897	A1	6/2003	Von Arx et al.
6,720,709	B2	4/2004	Porat et al.	2003/0136417	A1	7/2003	Fonseca et al.
6,720,887	B1	4/2004	Zunti	2003/0181794	A1	9/2003	Rini et al.
6,733,447	B2	5/2004	Lai et al.	2003/0191383	A1	10/2003	Ben-Haim et al.
6,738,671	B2	5/2004	Christophersom et al.	2004/0032187	A1	2/2004	Penner et al.
6,743,173	B2	6/2004	Penner et al.	2004/0044393	A1	3/2004	Yarden et al.
6,764,446	B2	7/2004	Wolinsky et al.	2004/0064133	A1	4/2004	Miller et al.
6,782,810	B2	8/2004	Vilo	2004/0077937	A1	4/2004	Yarden
				2004/0122484	A1	6/2004	Hatlestad et al.
				2004/0122486	A1*	6/2004	Stahmann et al. .... 607/60
				2004/0152999	A1	8/2004	Cohen et al.
				2004/0172081	A1	9/2004	Wang

(56)

## References Cited

## U.S. PATENT DOCUMENTS

2005/0056539 A1 3/2005 Morgan et al.  
 2005/0102002 A1 5/2005 Salo et al.  
 2005/0137490 A1 6/2005 Scheiner et al.  
 2005/0149143 A1 7/2005 Libbus et al.  
 2005/0154321 A1 7/2005 Wolinsky et al.  
 2005/0159789 A1 7/2005 Brockway et al.  
 2005/0182330 A1 8/2005 Brockway et al.  
 2005/0187482 A1 8/2005 O'Brien et al.  
 2005/0192637 A1 9/2005 Girouard et al.  
 2005/0192844 A1 9/2005 Esler et al.  
 2005/0197585 A1 9/2005 Brockway et al.  
 2005/0215887 A1 9/2005 Ben-Haim et al.  
 2005/0242479 A1 11/2005 Petisce et al.  
 2005/0288727 A1 12/2005 Penner  
 2006/0031378 A1 2/2006 Vallapureddy et al.  
 2006/0064133 A1 3/2006 Von Arx et al.  
 2006/0064134 A1 3/2006 Mazar et al.  
 2006/0064142 A1 3/2006 Chavan et al.  
 2006/0064143 A1 3/2006 Von Arx et al.  
 2006/0085039 A1 4/2006 Hastings et al.  
 2006/0085041 A1 4/2006 Hastings et al.  
 2006/0085042 A1 4/2006 Hastings et al.  
 2006/0089694 A1 4/2006 Zhang et al.  
 2006/0136004 A1 6/2006 Cowan et al.  
 2006/0142651 A1 6/2006 Brister et al.  
 2007/0043394 A1 2/2007 Zhang et al.  
 2007/0049977 A1 3/2007 Von Arx et al.  
 2007/0060959 A1 3/2007 Salo et al.  
 2007/0129765 A1 6/2007 Gilkerson et al.  
 2007/0142727 A1 6/2007 Zhang et al.  
 2008/0015421 A1 1/2008 Penner  
 2008/0021333 A1 1/2008 Huelskamp  
 2008/0021972 A1 1/2008 Huelskamp et al.  
 2008/0071178 A1 3/2008 Greenland et al.  
 2008/0077440 A1 3/2008 Doron  
 2008/0312553 A1 12/2008 Timmons

## FOREIGN PATENT DOCUMENTS

EP 1266606 12/2002  
 EP 1169085 8/2004  
 JP 2002224053 8/2002  
 WO WO83/03345 10/1983  
 WO WO97/01986 1/1997  
 WO WO97/32519 9/1997  
 WO WO97/33513 9/1997  
 WO WO97/47236 12/1997  
 WO WO98/26716 6/1998  
 WO WO98/29030 7/1998  
 WO WO99/17095 4/1999  
 WO WO99/26530 6/1999  
 WO WO99/34453 7/1999  
 WO WO99/47205 9/1999  
 WO WO99/55223 11/1999  
 WO WO99/55225 11/1999  
 WO WO99/59460 11/1999  
 WO WO99/66988 12/1999  
 WO WO00/16686 3/2000  
 WO WO00/47109 8/2000  
 WO WO00/58744 10/2000  
 WO WO01/28627 4/2001  
 WO WO01/56467 8/2001  
 WO WO01/074278 10/2001  
 WO WO02/03347 1/2002  
 WO WO02/32502 4/2002  
 WO WO03/002243 1/2003  
 WO WO03/096889 11/2003  
 WO WO2004/056301 7/2004  
 WO WO2004/060043 7/2004  
 WO WO2004/073513 A2 9/2004  
 WO WO2005/118056 12/2005  
 WO WO2006/033812 3/2006  
 WO WO2006/034183 3/2006  
 WO WO2006/045073 4/2006

WO WO2006/045074 4/2006  
 WO WO2006/045075 4/2006  
 WO WO2006/069215 6/2006  
 WO WO2007/030474 3/2007  
 WO WO2007/047287 4/2007  
 WO WO2007/047288 A1 4/2007  
 WO WO2007/070794 6/2007  
 WO WO2008/011592 1/2008  
 WO WO2008/011593 1/2008  
 WO WO2008/154145 12/2008

## OTHER PUBLICATIONS

Henderson et al., "Interaction of Photodynamic Therapy and Hyperthermia: Tumor Response and Cell Survival after Treatment of Mice in Vivo," *Cancer Research*, vol. 45, 6071 (Dec. 1985).  
 Bennett et al., "Subcutaneous pressure measurement as a surrogate for an external pressure reference for chronic implantable pressure monitoring," *Journal of Cardiac Failure*, Churchill Livingstone, vol. 9, No. 5, p. S51, Oct. 1, 2003, abstract only.  
 Bonnefoy E, Ninet J, Robin J, Leroux F, Boissonat P, Brule P, Champsaur G., 1994, Bipolar intramyocardial electrogram from an implanted telemetric pacemaker for the diagnosis of cardiac allograft rejection, *Pacing Clin Electrophysiol*, 17(11 Pt 2):2052-6.  
 C. Hierold et al. (Germany, 1998) "Implantable Low Power Integrated Pressure Sensor System for Minimal Invasive Telemetric Patient Monitoring" *IEEE*, pp. 568-573.  
 Dipl.-Ing. Torsten Eggert et al. (Germany) "Implantable Telemetric Endosystem (ITES)" *IMSAS Institut Fur Mikrosensoren-Aktuatoren Und-Systeme*, 1998. 2 pp.  
 E R. Cosman et al. (Massachusetts, Apr. 1979) "A Telemetric Pressure Sensor for Ventricular Shunt Systems" *Surgical Neurology* vol. 11, No. 4, pp. 287-294.  
 G.W.H. Schurink et al. (1998) "Late Endoleak After Endovascular Therapy for Abdominal Aortic Aneurysm" *Eur. J. Vasc. Endovasc. Surg.* vol. 17, pp. 448-450.  
 Gerhauser A, Reichel T, Neukomm P A, Bolz A, Hugel J, Schaldach M, 1997, Diagnosis of rejection after kidney transplantation by impedance spectroscopy with an implantable measuring system, *Biomed Tech (Berl)*, 42 Suppl. 160-1.  
 GH White et al. (1997) "Endoleak Following Endoluminal Repair of AAA: Management Options and Patient Outcomes", *J. Endovasc Surg*, pp. 1-45.  
 Graichen et al., "Patient Monitoring System for Load Measurement with Spinal Fixation Devices," *Med. Eng. Phys.* 18, (1996), pp. 167-174.  
 Haas et al., "Photodynamic Effects of Dyes on Bacteria," *Published in Mutation Research*, 1979, vol. 60, pp. 1-11.  
 Hashima et al., "Nonhomogenous Analysis of Epicardial Strain Distributions During Acute Myocardial Ischemia in the Dog," *J Biomech* 1993, Jan. 26: 19-35.  
 Hetzer R. et al., 1998, Daily non-invasive rejection monitoring improves long-term survival in pediatric heart transplantation, *Ann. Thorac. Surg.* (66):1343-1349.  
 J.A. Parrish, "Photobiologic Consideration on Photoradiation Therapy," pp. 91-108, *Porphyryn Photosensitization*, Plenum Press, (1983).  
 K.E. Uhrich et al., "Synthesis and characterization of degradable poly(anhydride-co-imides)", *Macromolecules*, 1995, 28, 2184-93.  
 Karl E. Richard et al. (Germany, Jan. 1999) "First clinical results with a telemetric shunt-integrated ICP-sensor" *Neurological Research* vol. 21, pp. 117-120.  
 Labrousse and Satre, "Photodynamic Killing of Dictyostelium Discoideum Amoebae Mediated by 4',5'-Diiodofluorescein Isothiocyanate Dextran. A strategy for the isolation of Thermoconditional Endocytosis Mutants," published in *Photochemistry and Photobiology*.  
 Mackay et al., "Bio-medical Telemetry: Sensing and Transmitting Biological Information from Animals and Man," *John Wiley & Sons, Inc. New York* (1970) pp. 244-245.  
 Pfitzmann R, Muller J, Grauhan O. Cohnert T, Hetzer R, Z Kardiol, 1998, Measuring bioelectric myocardial impedance as a non invasive method for diagnosis of graft rejection after heart transplantation, *87(4):258-266*.

(56)

**References Cited**

OTHER PUBLICATIONS

Pirolò J S, Shuman T S, Brunt E M, Liptay M J, Cox J L, Ferguson T B Jr., J Thoracic Cardiovasc Surg, 1992, Noninvasive detection of cardiac allograft rejection by prospective telemetric monitoring, 103(5):969-79.

Prof. Dr. Johannes Zacheja et al. (Germany, Sep. 1996) "An Implantable Microsystem for Biomedical Applications" Micro System Technologies 96, pp. 717-722.

S.K. Gupta et al. (1999) "Use of a Piezoelectric Film Sensor for Monitoring Vascular Grafts", The American Journal of Surgery, vol. 160, pp. 182-186.

T. Chuter et al. (Sweden, Jan. 1997) "Aneurysm Pressure Following Endovascular Exclusion" Eur. J. Vasc. Endovasc. Surg. vol. 13, pp. 85-87.

T.A. Cochran et al. (1990) "Aortic Aneurysm Abdominal", Current Therapy in Adult Medicine, Fourth Edition.

Z. Tang et al. (May 1995) "Data Transmission from an Implantable Biotelemeter by Load-Shift Keying Using Circuit Configuration Modulator" IEEE Transactions on Biomedical Engineering. vol. 42, No. 5, pp. 524-528.

Extended European Search Report issued in EP 10184174, mailed Dec. 7, 2010.

Non-Final Office Action issued in U.S. Appl. No. 10/943,627, mailed Oct. 2, 2008, 10 pages.

Non-Final Office Action issued in U.S. Appl. No. 09/943,627, mailed Oct. 7, 2009, 9 pages.

\* cited by examiner




FIG.1




FIG.2




FIG.4




FIG.3




FIG.5




FIG.6a




FIG.6b




FIG.6c




FIG.6d




FIG.7




FIG.8a




FIG.8b




FIG.8c




FIG.8d




FIG.9




FIG. 10a




FIG. 10b




FIG. 10c





FIG. 10d








FIG.11






FIG.12d




FIG.12e




FIG.12f

## SYSTEMS AND METHODS FOR DERIVING RELATIVE PHYSIOLOGIC MEASUREMENTS

### CROSS-REFERENCE TO RELATED APPLICATION

This application is a continuation of U.S. application Ser. No. 10/943,627, filed on Sep. 17, 2004, entitled "SYSTEMS AND METHODS FOR DERIVING RELATIVE PHYSIOLOGIC MEASUREMENTS USING A BACKEND COMPUTING SYSTEM," the entirety of which is incorporated herein by reference.

### BACKGROUND

The present invention relates generally to measuring physiologic parameters of a patient, and more particularly, to systems, methods and devices for measuring and deriving physiologic parameters relative to various environmental parameters.

Medical devices are known that can be implanted within a patient's body for monitoring one or more physiological parameters and/or to provide therapeutic functions. For example, sensors or transducers can be placed in the body for monitoring a variety of properties, such as temperature, blood pressure, strain, fluid flow, chemical properties, electrical properties, magnetic properties, and the like. In addition, medical devices can be implanted that perform one or more therapeutic functions, such as drug delivery, cardiac pacing, defibrillation, electrical stimulation, and the like.

In many cases, the implanted medical devices ("IMDs") are configured or adapted to communicate with external controllers or programmers, for example, to communicate data between the IMD and the external programmers, and/or to activate or otherwise control the IMDs. Typically, the IMDs can communicate with the external programmers via a wireless communication link, such as an RF communication link, or the like.

As mentioned above, IMDs can be configured to measure or sense a number of different parameters in the body. One parameter of particular interest is blood pressure. The implantable biosensors that measure pressure deep within anatomical structures, however, typically can only communicate the absolute pressure associated with the immediate anatomical environment. These devices are not capable of communicating gauge pressure because they are confined and sealed away from the ambient pressure external the body. In most cases, it is gauge pressure and not absolute pressure that is sought to be known, since the body regulates its activities based on the ambient pressure. Gauge pressure may be determined by correlating the absolute pressure with the ambient pressure. Similar situations exist for other parameters, as well, such as temperature.

Thus, a need exists for systems, methods, and/or devices for adjusting measured physiologic parameters, such as pressure, temperature and others, based on ambient or other environmental conditions.

### SUMMARY

One embodiment of the present invention relates to a system for deriving physiologic measurement values that are relative to ambient conditions. In one embodiment, the system comprises an implantable medical device ("IMD"), an external computing device, and a backend computing system. The IMD determines a physiologic parameter value within a

patient's body, and communicates the physiologic parameter value outside the patient's body, for example, to the external computing device. Further, the external computing device receives the physiologic parameter from the IMD and communicates it to the backend computing system. The backend computing system receives the physiologic parameter value and obtains an ambient condition value outside the body. The backend computing system then calculates a relative physiologic parameter value from the ambient condition value and the physiologic parameter value, and in some embodiments, stores the relative physiologic parameter value in a storage location, such as a memory or database.

In one embodiment, the physiologic parameter value and/or the ambient condition value can be marked with a time stamp. Thus, because time stamps are used, the backend computing system can select an ambient condition value that is obtained or measured at a time reasonably close to the time when the physiologic parameter value is measured to calculate the relative physiologic parameter value.

Further, in another embodiment, the backend computing system can communicate the relative physiologic parameter value to the external computing device, which also can communicate the relative physiologic parameter value to the IMD. The IMD then can receive the relative physiologic parameter value and store it in a memory.

In some embodiments, the backend computing system can be a database accessible by one or more health care providers. Thus, the one or more health care providers can obtain the relative physiologic parameter value from the database and use the relative physiologic parameter value to provide a service to the patient, such as diagnosing the patient, prescribing medication to the patient, providing a therapy to the patient, modifying one or more settings of the IMD, or the like.

In addition, in other embodiment, the external computing device can include a sensor for measuring the ambient condition value. In this embodiment, the external computing device communicates the ambient condition value to the backend computing system. Further, in other embodiments, the backend computing system can receive the ambient condition value from an ambient condition source, such as an external monitor or other source. If an external monitor is used to obtain the ambient condition value, it can communicate the ambient condition value to the external computing device, which communicates the ambient condition value to the backend computing system. In some embodiments, the external monitor can be a wireless communication device carried on or near the patient's body. For example, the external monitor can be a device adapted to be worn around a patient's body part, a device that can be connected to a belt, a device that can be worn as a patch, a personal digital assistant (PDA), a device that can be carried in a pocket or a personal carry bag, a customized cell phone or pager, or any other suitable device that can perform the functions of the external monitor.

In some embodiments, the external computing device can be an IMD programmer, or a repeater device in communication with the backend computing system. In addition, in some embodiments, the IMD and the external computing device can communicate via a wireless communication connection, such as, for example, a radio frequency communication connection, an acoustic communication connection, a magnetic field communication connection, an optical communication connection, or any other suitable wireless communication connection.

The IMD can be any suitable implantable medical device. For example, in some embodiments, the IMD can be a physi-

ologic parameter sensor, a pacemaker, a defibrillator, a bi-ventricular pacer, a ventricular assist blood pump, a drug delivery pump, a drug infusion device, a neurostimulating device, an intra-ocular shunt, an intra-cranial shunt, or any other suitable IMD. Also, the IMD can be adapted to provide therapy to a patient. In accordance with this embodiment, the IMD can be configured to use the relative physiologic parameter value to determine the proper therapy to provide to the patient. For example, in some embodiments, the IMD can use the relative physiologic parameter value to determine and provide therapies, such as, cardiac pacing therapy, anti-tachycardia therapy, drug delivery therapy, neurostimulation therapy, blood pump therapy, or any other suitable therapy provided by IMDs.

In still other embodiments, the IMD can include a processor that can be adapted to generate patient therapy information based at least in part on the relative physiologic parameter value. In accordance with this embodiment, the implantable medical device can be configured to communicate the patient therapy information to the external computing device, and the external computing device can include a patient communication interface adapted to provide the patient therapy information to the patient. In other embodiments, the external computing device can communicate the patient therapy information to the backend computing system for access by one or more health care providers.

In yet another embodiment, the backend computing system can determine a proper therapy to provide to a patient. In the embodiment, the backend computing system can use the relative physiologic parameter value to determine the therapy, and it can store the therapy information for access by one or more health care providers.

In yet other embodiments, the present invention can include methods performed by the IMD, the external computing device, and/or the backend computing system, and the present invention can include the IMDs and/or the external computing devices individually.

While multiple embodiments are disclosed, still other embodiments of the present invention will become apparent to those skilled in the art from the following detailed description, which shows and describes illustrative embodiments of the invention. Accordingly, the drawings and detailed description are to be regarded as illustrative in nature and not restrictive.

#### BRIEF DESCRIPTION OF THE DRAWINGS

In the Figures, similar components and/or features may have the same reference label. Further, various components of the same type may be distinguished by following the reference label with a second label that distinguishes among the similar components. If only the first reference label is used in the specification, the description is applicable to any one of the similar components having the same first reference label irrespective of the second reference label.

FIG. 1 is a diagram showing one embodiment of a system of the present invention;

FIG. 2 is a block diagram showing one embodiment of an implantable medical device;

FIG. 3 is a block diagram showing one embodiment of a remote sensor system of an implantable medical device;

FIG. 4 is a block diagram of one embodiment of an external monitor; and

FIGS. 5-12 are flow charts illustrating various embodiments of methods of the present invention.

While the invention is amenable to various modifications and alternative forms, specific embodiments have been

shown by way of example in the drawings and are described in detail below. The intention, however, is not to limit the invention to the particular embodiments described. On the contrary, the invention is intended to cover all modifications, equivalents, and alternatives falling within the scope of the invention as defined by the appended claims.

#### DETAILED DESCRIPTION

The present invention relates generally to measuring physiological parameters of a patient, and more particularly, to systems, methods and devices for measuring and deriving physiological parameters relative to various environmental parameters. In contrast to prior art systems and methods, the present invention utilizes a backend computing system to obtain ambient measurement values, and then the backend computing system use the ambient values along with the measured physiologic parameters to calculate relative physiologic parameter values.

As discussed herein, the present invention relates to systems and methods for obtaining relative physiologic parameter values. The physiologic parameter values obtained can be any physiologic measurement, such as, blood pressure, temperature, blood or fluid flow, strain, electrical, chemical or magnetic properties within the body, or the like. As one skilled in the art will appreciate, the type of measurement being taken may determine whether the measurement will need to be adjusted for ambient or other environmental conditions that may affect the measurements within the body. For example, it is known that ambient pressure will affect intravascular blood pressure. Further, outside temperature may affect the internal body temperature of a person or other animal, depending, in part, on the severity of the outside temperature. Also, other environmental conditions, such as, altitude, humidity, electric or magnetic fields, or chemical compositions may affect other physiologic measurements of interest. Accordingly, the present invention can be used to adjust any internal physiologic measurements relative to environmental conditions, and thus, is not limited in scope to any particular measurement. Of course, as one skilled in the art will appreciate, adjusting measured internal blood pressure relative to ambient pressure (which also can be derived from or affected by temperature, humidity, altitude, etc.) is of particular interest for many clinical and therapeutic applications, and the present invention is well suited to obtain relative pressure values.

Referring now to FIG. 1, one embodiment of a system 100 for deriving relative physiologic measurement values is shown. In accordance with the illustrated embodiment, system 100 includes an implantable medical device ("IMD") 102, an external monitoring device 104, an external computing device 106, and a backend computing system 108.

IMD 102 can be any type of implantable medical device that is configured to obtain physiologic measurements of a patient and/or provide therapy to the patient. For example, IMD 102 can be a pacemaker, an implantable cardioverter defibrillator ("ICD"), a cardiac resynchronization device, a bi-ventricular pacer, a ventricular assist blood pump, a drug delivery pump, a drug infusion device, a neurostimulating device, an intra-ocular shunt, an intra-cranial shunt, or any other suitable implantable device, which can obtain or measure physiologic parameter values. In the embodiment illustrated in FIG. 1, IMD 102 is a cardiac device, such as a pacemaker or ICD, which has one or more leads 110 that can include sensors or sensor circuitry 112 for obtaining physi-

ologic measurements (e.g., blood pressure or the like) and therapy delivery systems (also **112**) for providing cardiac therapy to the patient.

In addition, in alternative embodiments, sensors and/or therapy delivery systems **112** can be located separate from leads **110**, and the sensor data can be transmitted to IMD **102** via other communication medium, such as a coupled communication connection, or a wireless communication connection. If a wireless communication connection is used, the wireless connection can be a radio frequency (RF) connection, an acoustic connection (e.g., ultrasound), an optical connection, an electric field connection, or any other suitable communication connection. For example, in one embodiment, sensors and/or therapy delivery systems **112** can be configured in one or more satellite devices (e.g., chronically implanted stent devices) as is disclosed in Published U.S. Patent Application No. 2003/0158584 A1, published on Aug. 21, 2003, and entitled "Chronically-Implanted Device For Sensing and Therapy," the entirety of which is incorporated by reference herein for all purposes.

In addition, in some embodiments, IMD **102** is operable to communicate with external monitoring device **104** and external computing device **106** via wireless connections **114** and **116**, respectively. Similarly, in some embodiments, external monitoring device **104** is operable to communicate with external computing device **106** via wireless connection **118**. Further, in other embodiments, external monitor **104** and external computing device **106** can be in wireless communication with sensor circuitry **112** via wireless connections **120** and **122**, respectively. Each of these different embodiments will be discussed in more detail below. Wireless connections **114**, **116**, **118**, **120** and **122** all can be uni-directional or bi-directional communication links, depending on the IMD and the data being transferred. As such, IMD **102** and/or sensor circuitry **112** can send information to and receive information from external monitoring device **104** and external computing device **106** via the communication connections. Similarly, external monitoring device **104** can communicate bi-directionally with external computing device **106**.

Referring now to FIG. 2, one embodiment of an IMD **102** is illustrated. In accordance with the illustrated embodiment, IMD **102** comprises a processor **202**, a memory **204**, communication circuitry **206**, therapy circuitry **208** and sensor circuitry **210**. Memory **204**, communication circuitry **206**, therapy circuitry **208** and sensor circuitry **210** all are in electrical communication with processor **202**, as is illustrated by arrows **212**.

As one skilled in the art will appreciate, processors and memory devices are well known in the art, and the specific type and/or style of processor or memory device that can be used in IMD **102** is not limited. Accordingly, processor **202** can be any suitable processing device currently known or hereinafter developed, and memory device **204** can be any suitable memory device currently known or hereinafter developed.

Communication circuitry **206** is circuitry that allows IMD **102** to communicate with other devices, such as external computing device **106**, external monitoring device **104**, other IMDs, or other external devices. As discussed above, IMD **102** communicates with other devices via a wireless connection. The wireless connection can be, for example, a near field radio frequency (RF) communication connection, a far field RF communication connection, an acoustic communication connection (e.g., an ultrasound connection), an optical communication connection, or any other suitable wireless communication connection.

In one embodiment, communication circuitry **206** can include circuitry for both near field RF telemetry and far field RF telemetry. For example, one embodiment of communication circuitry that can be used in IMD **102** is disclosed in Published U.S. Patent App. No. US 2003/0114897 A1, published on Jun. 19, 2003, and entitled "Implantable Medical Device with Two or More Telemetry Systems," and Published U.S. Patent App. No. U.S. 2003/0114898 A1, published on Jun. 19, 2003, and entitled "Telemetry Duty Cycle Management System for an Implantable Medical Device," both of which are incorporated by reference herein for all purposes.

In addition, in other embodiments, power saving wireless communication circuitry and methods can be used. For example, the IMD communication circuitry **206** can be configured to reside in a power-saving, sleep mode for a majority of the time. In accordance with this embodiment, communication circuitry **206** can be configured to "wake-up" on a periodic basis to communicate with an external device. Upon "wake-up" the external device will monitor for RF activity, and if the external device locates it, communication between the IMD and the external device can be initiated. There are a number of different ways IMD power-saving modes can be implemented, and the present invention is not limited to any particular one. Indeed, the aforementioned Published U.S. Patent App. Nos. US 2003/0114897 A1 and US 2003/0114898 A1 disclose different ways of implementing IMD power-saving modes, which, as discussed above, are incorporated herein by reference for all purposes. In addition, additional power management systems and methods are disclosed in Published U.S. Patent App. No. US 2003/0149459 A1, published on Aug. 7, 2003, and entitled "Methods and Apparatuses for Implantable Medical Device Telemetry Power Management," the entirety of which is incorporated by reference herein for all purposes.

Further, in accordance with other embodiments, communication circuitry **206** can be configured to communicate with an intermediary telemetry device, which, in turn, can facilitate communication with the external monitoring device **104** and/or external computing device **106**. One example of this type of configuration is disclosed in Published U.S. Patent App. No. US 2003/0130708, published on Jul. 10, 2003, and entitled "Two-Hop Telemetry Interface for Medical Device," the entirety of which is incorporated by reference herein for all purposes. In addition, other configurations for RF telemetry are known, and communication circuitry **206** can embody those configurations, as well. Thus, as one skilled in the art will appreciate, communication circuitry **206** is not limited by any particular configuration or communication means.

Therapy circuitry **208** comprises circuitry for providing one or more therapeutic functions to a patient. For example, therapy circuitry **208** can include circuitry for providing heart pacing therapy, cardiac defibrillation therapy, cardiac resynchronization therapy, drug delivery therapy, or any other therapy associated with a suitable IMD. In the case of cardiac therapy (e.g., pacing, defibrillation, etc.), therapy circuitry **208** can include cardiac leads for delivering the therapy to particular locations in the heart. In other embodiments, the therapy circuitry and/or therapy delivery mechanisms can reside in a satellite device wirelessly coupled to the IMD body **102**, as discussed below.

Finally, sensor circuitry **210** comprises the sensors and circuitry needed to obtain or measure the physiologic parameters. For example, to obtain a blood pressure (e.g., intravascular or intracardiac blood pressure), sensor circuitry **210** comprises one or more pressure sensors and associated circuitry for recording the pressure accurately. Pressure sensors

and the associated circuitry are well known in the art, and therefore, will not be disclosed in detail herein. In addition, in other embodiments, sensor circuitry **210** can be configured to obtain other physiologic parameters, such as temperature, electrical impedance, position, strain, pH, fluid flow, blood oxygen levels, and the like. In these cases, sensor circuitry **210** will include suitable bio-sensors for obtaining the corresponding physiologic parameters.

Also, as one skilled in the art will appreciate, the sensors and/or sensor circuitry can be, and many times are, electrically coupled to IMD **102**, but placed remotely from the IMD; e.g., at the end of a lead or in a satellite device in wireless communication with IMD **102**. FIG. **1** illustrates an embodiment in which the sensors and/or therapy delivery mechanisms **112** are connected to IMD **102** via leads **110**.

In an alternative embodiment, IMD **102** can comprise a planet/satellite configuration, in which the satellite portion of the IMD includes sensor and/or therapy delivery circuits and mechanisms. Such a configuration is disclosed in Published U.S. Patent Application No. US 2003/0158584 A1, published on Aug. 21, 2003, and entitled "Chronically-Implanted Device for Sensing and Therapy," the entirety of which is incorporated herein by reference for all purposes. In this system, the planet or main body of the IMD communicates with one or more satellite sensor/therapy devices either by an electrical wire connection or wirelessly. In some embodiments, the planet or main body can command each satellite to provide sensing functions and therapy functions, such as delivering cardiac electrical pulses, drug delivery, or other functions, as discussed above. In other embodiments, the satellite devices can function autonomously, and then communicate with the planet device at their own direction, at the planet's direction, or at timed intervals. The relationships between the planet device and the satellite device(s) are discussed in more detail in the incorporated reference.

In accordance with one embodiment of the invention, the satellite sensor/therapy devices can be configured as stent-like, intravenous, chronically-implanted devices. The configuration of embodiments of stent-like devices is disclosed in more detail in the incorporated Published U.S. Patent Application No. US 2003/0158584. FIG. **3**, however, illustrates one embodiment of sensing and/or therapy circuitry **300** of a satellite device. In accordance with the illustrated embodiment, the circuitry **300** comprises a pair of electrodes **302**, a stimulus storage unit **304**, a sensing amplifier and comparator logic **306**, a sense event state storage and interface **308**, a data processor **310**, a transceiver **312**, an antenna **314**, a pump-rectifier **316**, and a pump-regulator **318**. According to various embodiments, the satellite is designed for mechanical, electrical and/or chemical sensing, and for mechanical, electrical and/or drug-eluting therapies.

The operation of circuitry **300** is described in greater detail in the incorporated Published U.S. Patent Application No. US 2003/0158584. However, in accordance with one embodiment, antenna **314** and transceiver **312** can be configured to communicate with the planet or main body of the IMD **102**, with external monitor **104**, or with external computing device **106**. Such communication connections can be RF connections, acoustic connections (e.g., ultrasound), optical connections, or other suitable communication connections. In addition, antenna **314** and transceiver **312** can be configured to communicate with the multiple devices using one or more different connection types.

As discussed in more detail below, in some embodiments, sensor/therapy circuitry **300** is operable to receive ambient condition values, for example, from the main body of the IMD **102**, external monitor **104** or external computing device

**106** and calculate a relative physiologic parameter value using the ambient condition value. In accordance with these embodiments of the invention, data processor **310** can be configured to calculate the relative physiologic parameter values using measured values and the received ambient condition values. In addition, data processor **310** is operable to format data received by circuitry **300**, as well as format data being transmitted by the satellite device. Again, a more complete description of the operation and configuration of the satellite device and associated circuitry is set forth in the incorporated reference.

Referring again to FIG. **1**, external monitoring device **104** comprises a device that is adapted to obtain an ambient condition value or other environmental condition value outside the body that can affect the measured physiologic parameter value, and then, in some embodiments, calculate a relative physiologic parameter value using the measured physiologic parameter value and the ambient condition value. For example, as discussed in more detail below, when determining intravascular blood pressure, external monitoring device **104** can calculate a gauge blood pressure by adjusting the measured blood pressure value with an atmospheric or barometric pressure value.

External monitoring device **104** can comprise any type of processor-based device that can be carried on or near a patient's body. For example, external monitoring device **104** can be a device that is adapted to worn around a part of a patient's body, such as a wrist watch, a device connected to a belt, or some other device adapted to be worn around an ankle, leg, arm, neck, chest, stomach, etc. In addition, in other embodiments, external monitoring device can be a computing device worn as a patch, or a computing device that can be carried in a pocket, on a belt clip, or in a personal carry bag, such as a PDA, or a customized cellular phone or pager. One skilled in the art will appreciate that other device can be used as well.

Referring now to FIG. **4**, one embodiment of an external monitoring device **104** is shown. In the illustrated embodiment, external monitoring device **104** comprises a processor **402**, a memory **404**, communication circuitry **406** and a patient interface **408**. Memory **404**, communication circuitry **406**, and patient interface **408** all are in electrical communication with processor **402**, as is illustrated by arrows **412**.

As one skilled in the art will appreciate, and as discussed above with reference to IMD **102**, processors and memory devices are well known in the art, and the specific type and/or style of processor or memory device that can be used in external monitoring device **104** is not limited. Accordingly, processor **402** can be any suitable processing device currently known or hereinafter developed, and memory device **404** can be any suitable memory device currently known or hereinafter developed. In addition, communication circuitry **406** is circuitry that allows external monitoring device **104** to communicate with IMD **102** and other devices, such as external computing device **106**, and/or sensor/therapy circuitry **112**. Thus, if IMD **102** and the other devices are communicating via an RF connection, communication circuitry **406** comprises RF communication circuitry, as well. Similarly, if optical or acoustic communication connections are used, communication circuitry **406** is adapted to facilitate such connections. Further, in some embodiments, IMD **102** might be communicating with external monitor **104** via one type of communication connection, while other devices, such as external computing device **106** or sensor/therapy circuitry **112** might be communicating with external monitor **104** via other types of connections. Thus, communication circuitry **406** can be any circuitry adapted to facilitate the communi-

cations with IMD 102, external computing device 106, and sensor/therapy circuitry 112, and communication circuitry 406 can facilitate multiple types of communications at the same time. As one skilled in the art will appreciate, such circuitry is known in the art, and therefore, will not be discussed in detail herein.

In one embodiment, external monitoring device 104 also can include a patient interface 408 adapted to communicate information, such as therapy or diagnostic information, to the patient. In accordance with this embodiment, patient interface 408 may comprise a visually readable screen that allows the patient to read information, an audible or sound interface that can broadcast or transmit audible or sound information to the patient, or some other communication means.

Finally, referring again to FIG. 1, external computing device 106 can be any suitable computing device adapted to communicate with IMD 102, external monitoring device 104, and/or sensor/therapy circuitry 112, and process data from those devices. For example, in the case of a cardiac rhythm management (“CRM”) IMD (e.g., pacemaker, ICD, etc.), external computing device 106 might be a programmer used by physicians, specialists, or other health care providers to extract data from the cardiac IMDs. Programmers are well known in the art. In addition, in other embodiments, external computing device 106 can be a repeater device associate with a patient. Examples of one or more repeater-type devices are disclosed in U.S. Pat. No. 6,607,485, issued on Aug. 9, 2003, and entitled “Computer Readable Storage Medium Containing Code for Automated Collection and Analysis of Patient Information Retrieved from an Implantable Medical Device for Remote Patient Care,” the entirety of which is incorporated by reference herein for all purposes. In still other embodiments, external computing device 106 can be any other computing device for receiving, processing and/or storing medical data, including a workstation or appliance on a network, a server on a network, or a computer network as a whole. The present invention is not limited to any particular type of computing device.

Backend computing system 108 can be any type of computing system. In one embodiment, backend computing system is a networked system with a database operable to receive information regarding patients and their IMDs. The information then can be accessed by third parties, such as physicians, specialists, IMD manufacturers, insurance companies, pharmaceutical companies, or any other health care provider. As discussed in more detail below, backend computing system 108 can be configured to receive relative physiologic parameter values for patients and IMDs, other IMD information, and/or patient therapy information. In addition, backend computing system 108 can be configured to receive physiologic measurements and calculate relative measurements using ambient condition values. Further, backend computing system can determine patient therapy information based on data received from IMD 102, external monitor 104, and/or external computing device 106. Examples of embodiments of a one or more backend computing systems that can be used with the present invention are disclosed in U.S. Pat. No. 6,607,485 discussed above, and U.S. patent application Ser. No. 10/789,964, filed on Feb. 27, 2004, and entitled “Systems and Methods for Automatically Collecting, Formatting and Storing Medical Device Data in a Database,” both of which are incorporated by reference herein for all purposes.

Referring now to FIG. 5, flow chart 500 illustrates a method for obtaining and using relative physiologic parameter values in accordance with one embodiment of the present invention. In accordance with the method illustrated in flow chart 500, an IMD (e.g., IMD 102 in FIG. 1) determines an absolute

physiologic parameter value (block 502). As discussed above, the physiologic parameter values obtained can be any physiologic measurement, such as, blood pressure, temperature, blood or fluid flow, strain, electrical, chemical or magnetic properties within the body, or the like. In one particular embodiment, the physiologic parameter value obtained is blood pressure (e.g., intravascular or intracardiac blood pressure), and one or more pressure sensors are used to obtain the absolute blood pressure value. As one skilled in the art will appreciate, the absolute pressure measured by a pressure sensor typically is not a true absolute pressure. The measured pressure typically is adjusted for internal temperatures and/or a built-in backing pressure and/or temperature coefficients of the pressure sensor. Thus, an absolute blood pressure value can be calculated according to the following formula:

$$P_{ABP} = P_{MBP} - P_{Re f}(T_{Blood}) \text{ where:}$$

$P_{ABP}$  is the absolute blood pressure;

$P_{MBP}$  is the measured blood pressure; and

$P_{Re f}(T_{Blood})$  is the sensor reference/backing pressure, which is a function of blood temperature ( $T_{Blood}$ ).

As one skilled in the art will appreciate, most pressure sensors are configured to perform these adjustments automatically, and thus, special processing within the IMD typically is not needed to obtain the absolute blood pressure value.

After the IMD obtains the absolute physiologic parameter (e.g., absolute blood pressure), the IMD communicates the absolute physiologic parameter value to an external monitor (e.g., external monitor 104 in FIG. 1) (block 504). In one embodiment, the IMD and the external monitor can implement a data transmission check (e.g., a cyclic redundancy code (“CRC”) check) to ensure the data is transmitted properly.

The external monitor receives the absolute physiologic parameter value and obtains an ambient condition value (block 506). In some embodiments, the external monitor can obtain the ambient condition value either prior to or after receiving the absolute physiologic parameter value. In one embodiment, the external monitor includes a sensor for measuring the ambient condition value. Alternatively, in another embodiment, the external monitor could receive the ambient condition value from another source, such as another computing device in communication with the external monitor, the Internet, or some other source. The means by which the external monitor obtains the ambient condition value is not critical, and thus, the present invention is not limited to any particular method or system for obtaining the ambient condition value.

In some embodiments, the step of determining the absolute physiologic parameter value and the step of obtaining the ambient condition value may not occur at the same time or even close to the same time. For example, the external monitor may only measure or obtain the ambient condition value a few times a day, or there may be a delay between when the external monitor receives the ambient condition value and the absolute physiologic parameter value. As one skilled in the art will appreciate, ambient condition values can change relatively quickly, and thus, if an ambient condition value is not obtained at a time relatively close to when the absolute physiologic parameter value is obtained, the calculated relative value may be inaccurate. Therefore, the absolute physiologic parameter value and/or the ambient condition value can include a time stamp, so that values measured or obtained at about the same time can be used to calculate the relative physiologic parameter value. In some embodiments, if there

is a gap between when ambient condition values are measured or obtained, averaged or prorated ambient values can be used.

As discussed above, in one embodiment, the systems and methods of the present invention can be used to obtain blood pressure. In accordance with this embodiment, the ambient condition value is atmospheric or barometric pressure (and/or other parameters, such as temperature, humidity, altitude, etc. that can affect barometric pressure), which can be measured by one or more sensors in the external monitor, or which can be passed to the external monitor from an outside source. As with the pressure sensor associated with the IMD, a pressure sensor in the external monitor also typically is adjusted for temperature and a built-in backing pressure. Thus, in one embodiment, the atmospheric pressure obtained by the external monitor can be calculated according to the following formula:

$$P_{ATM} = P_{MATM} - P_{ATM Re}(T_{ATM}) \text{ where:}$$

$P_{ATM}$  is the adjusted atmospheric pressure;

$P_{MATM}$  is the measured atmospheric pressure; and

$P_{ATM Re}(T_{ATM})$  is the sensor reference/backing pressure, which is a function of the temperature where the external monitor is placed ( $T_{ATM}$ ).

As discussed above, most pressure sensors are configured to perform these adjustments automatically, and thus, special processing within the external monitor typically is not needed to obtain the adjusted atmospheric pressure.

After the external monitor obtains the ambient condition value and the absolute physiologic parameter value, the external monitor calculates a relative physiologic parameter value (block 508). For example, for intravascular blood pressure, a gauge blood pressure can be calculated by subtracting the atmospheric pressure from the absolute pressure value. When pressure sensor adjustments are taken into account, the following formula will apply:

$$P_{Gauge} = (P_{MBP} - P_{Re}(T_{Blood})) - (P_{MATM} - P_{ATM Re}(T_{ATM})).$$

In other embodiments, the relative physiologic parameter values can be calculated using other mathematical operations or models. For example, in one embodiment, some vascular abnormalities, which can be precursors to some cardiac problems, can be diagnosed by measuring physiologic parameters in two or more locations within the body, using two or more separate sensors. The data from the multiple sensors then might undergo mathematical manipulation, which then can be reconciled with the external ambient condition measurements. Thus, the present invention is not limited to a pure subtraction operation. Further, as one skilled in the art will appreciate, the calculations needed to obtain relative physiologic parameter values from other types of physiologic measurements (e.g., temperature, pH, etc.) may be different depending on the measurements being taken. Also, as discussed briefly above, if the physiologic parameter value and/or the ambient condition value include time stamps, the external monitor will values that are similar in time (or averaged or prorated values), so that the relative value is accurate.

In one embodiment, after the external monitor calculates the relative physiologic parameter value, it communicates the relative value to the IMD (block 510), which, in turn, stores the relative physiologic parameter value in a memory (block 512). Again, the IMD and the external monitor can implement a data transmission check, such as a CRC check, to ensure the data is transmitted properly. After the relative physiologic parameter value is stored in the IMD memory, the IMD and/or the external monitor can perform a number of different operations with the relative value. This is illustrated by continuation block 514 in FIG. 5.

Referring now to FIGS. 6a-6d, additional embodiments of the present invention will be described with reference to flow charts 600, 610, 620 and 630, respectively. In FIGS. 6a-6d, continuation blocks 602, 612, 622 and 632 are continuations from block 514 in FIG. 5. Thus, in accordance with the embodiment illustrated in FIG. 5a, after the IMD stores the relative physiologic parameter value in memory, the IMD can be configured to communicate the relative physiologic parameter value to an external computing device, such as external computing device 106 discussed above with reference to FIG. 1 (block 604). For example, in the case in which the IMD is a CRM device, such as a pacemaker or an ICD, the IMD can communicate the relative physiologic measurements to an external programmer or repeater device along with other IMD data, which is well known. A physician or other health care provider can analyze the relative physiologic measurements to determine trends and provide diagnosis and treatment based on those trends. In addition, the data can be uploaded to one or more backend systems (e.g., backend system 108) for later processing, access, and/or analysis by one or more health care providers, such as physicians, specialists, IMD manufacturers, insurance companies, pharmaceutical companies, or any other suitable health care provider (block 606).

Referring now to FIG. 6b, in this particular embodiment, the IMD can be configured to calculate or determine a therapy based on the relative physiologic parameter value (block 614), and then administer the therapy to the patient (block 616). For example, if the IMD is a cardiac pacemaker, the pacemaker may be configured to change pacing modes or parameters based on the obtained relative physiologic value. Similarly, if the IMD is a drug delivery device, the device might deliver a drug dosage when certain relative physiologic parameter values are measured. As one skilled in the art will appreciate, the type of therapy administered to the patient will be dependent upon the type of IMD used and the physiologic measurements taken. Thus, as discussed above, the present invention is not limited to any particular IMD or therapy system.

Referring now to FIG. 6c, in this particular embodiment, the IMD can be configured to calculate or determine a therapy or therapy information based on the relative physiologic parameter value (block 624). The IMD then is configured to communicate the therapy information to the external monitor (e.g., external monitor 104) (block 626), which in turn can be configured to provide or communicate the therapy information to the patient (block 628). For example, in the case of a CRM IMD, which is configured to detect blood pressure, when the IMD detects a consistent rise in blood pressure for a congestive heart failure patient, the IMD can be configured to communicate information to the patient on how to deal with the situation. For example, the IMD might communicate a message to the external monitor, instructing the patient to change a medication dosage, or perhaps take a medication. As discussed above, the external monitor can include a communication interface, such as a visual screen or audible interface, to communicate the information to the patient.

Referring now to FIG. 6d, in this particular embodiment, the IMD again can be configured to calculate or determine a therapy or therapy information based on the relative physiologic parameter value (block 634). Then, instead of, or in addition to administering the therapy to the patient, the IMD is configured to communicate the therapy information to an external computing device, such as computing device 106 (block 636). A physician or other health care provider then can analyze the therapy information and provide it to the patient if the physician determines that it is appropriate, or the

physician can provide different or additional therapy to the patient if the physician determines that an alternative therapy would be better. In addition, the therapy information can be uploaded to a backend computing system (e.g., backend computing system **108**) for later processing, access and/or analysis.

In an alternative embodiment, instead of the external monitor communicating the relative physiologic parameter value to the IMD, it can be configured to communicate the relative physiologic parameter value to the external computing device without first communicating it to the IMD. The external computing device then can communicate it to a backend computing system, or it can display it to the patient or another health care provider. In addition, instead of the IMD determining the therapy information, the external monitor or the external computing device can be configured to determine the therapy information based on, in part, the calculated relative physiologic parameter value. In this embodiment, the processor within the external monitor or the external computing device will include the therapy logic, not the processor within the IMD. In addition, as one skilled in the art will appreciate, the therapy and/or diagnosis information that the IMD, the external monitor, and/or the external computing device provide to the patient will depend upon the type of IMD and the type of physiologic parameters being measured. As discussed above, the present invention is not limited to any particular IMD or physiologic parameter value measurement.

Referring now to FIG. 7, an alternative embodiment of a method of deriving and using relative physiologic parameter values is shown. In accordance with the method illustrated in flow chart **700**, an IMD (e.g., IMD **102** in FIG. 1) determines an absolute physiologic parameter value (block **702**). As discussed above, the physiologic parameter values obtained can be any physiologic measurement, such as, blood pressure, temperature, blood or fluid flow, strain, electrical, chemical or magnetic properties within the body, or the like. In one particular embodiment, the physiologic parameter value obtained is blood pressure (e.g., intravascular or intracardiac blood pressure), and one or more pressure sensors are used to obtain the absolute blood pressure value. As discussed above, the absolute pressure measured by a pressure sensor can be adjusted for internal temperatures and/or a built-in backing pressure and/or temperature coefficients of the pressure sensor.

After the IMD obtains the absolute physiologic parameter (e.g., absolute blood pressure), the IMD communicates the absolute physiologic parameter value to an external computing device (e.g., external computing device **106** in FIG. 1) (block **704**). In one embodiment, the IMD and the external computing device can implement a data transmission check (e.g., a cyclic redundancy code (“CRC”) check) to ensure the data is transmitted properly.

The external computing device receives the absolute physiologic parameter value and obtains an ambient condition value (block **706**). In one embodiment, the external computing device includes one or more sensors for measuring the ambient condition value. Alternatively, in another embodiment, the external computing device can receive the ambient condition value from another source, such as another computing device in communication with the external computing device, the Internet, or some other source. For example, as discussed above, an external monitor (e.g., external monitor **104** in FIG. 1) can include a sensor for measuring the ambient condition value, and the external monitor can pass the ambient condition value to the external computing device via a wired or wireless communication connection. The means by which the external computing device obtains the ambient

condition value is not critical, and thus, the present invention is not limited to any particular method or system for obtaining the ambient condition value.

In one embodiment, the systems and methods of the present invention can be used to obtain blood pressure. In accordance with this embodiment, the ambient condition value is atmospheric or barometric pressure, which can be measured by one or more sensors in the external computing device, or which can be passed to the external computing device from an outside source (e.g., from an external monitor). As with the pressure sensor associated with the IMD, a pressure sensor in the external computing device or the external monitor also typically is adjusted for temperature and a built-in backing pressure. As mentioned above, most pressure sensors are configured to perform these adjustments automatically, and thus, special processing within the external computing device or the external monitor typically is not needed to obtain the adjusted atmospheric pressure.

After the external computing device obtains the ambient condition value, the external computing device calculates a relative physiologic parameter value (block **708**). In one embodiment, for blood pressure, a gauge blood pressure can be calculated by subtracting the atmospheric pressure from the absolute pressure value, or as discussed above, other mathematical calculations can be used. In addition, the calculations needed to obtain relative physiologic parameter values from other types of physiologic measurements (e.g., temperature, pH, etc.) may be different depending on the measurements being taken. Further, as discussed above, the physiologic parameter value and/or the ambient condition value can include time stamps, so that the relative physiologic parameter value is calculated using values that are similar in time.

In one embodiment, after the external computing device calculates the relative physiologic parameter value, it communicates the relative value to a backend computing system (e.g., backend computing system **108** in FIG. 1) (block **710**). Further, the external computing device can display or provide the relative physiologic measurement values to a health care provider or other entity for review. For example, in the case in which the IMD is a CRM device, such as a pacemaker or an ICD, the external computing device might be an external programmer with print-out or display capabilities. Thus, a physician or other health care provider can view and analyze the relative physiologic measurements to determine trends and provide diagnosis and treatment based on those trends.

After the relative physiologic parameter value is communicated to the backend computing system, additional processing can occur in a number of different devices in the system. This is illustrated by continuation block **712** in FIG. 7.

Referring now to FIGS. **8a-8d**, additional embodiments of the present invention will be described with reference to flow charts **800**, **810**, **820** and **830**, respectively. In FIGS. **8a-8b**, continuation blocks **802** and **812** are continuations from block **712** in FIG. 7. Thus, in accordance with the embodiment illustrated in FIG. **8a**, after the external computing device communicates the relative physiologic parameter value to the backend computing system, the backend computing system stores the relative physiologic parameter values, for example, in a database (block **804**). The data then can be made available for later processing, access, and/or analysis by one or more health care providers, such as physicians, specialists, IMD manufacturers, insurance companies, pharmaceutical companies, or any other suitable health care provider (block **806**).

As illustrated by flow chart **810** in FIG. **8b**, the external computing device also can communicate the relative physi-

ologic parameter value to the IMD (block **814**), which then stores the relative physiologic parameter value in memory (block **816**). When the IMD receives the relative physiologic parameter value, the IMD then can use the value for additional processing, as illustrated by continuation block **818**. Continuation blocks **822** and **832** in FIGS. **8c** and **8d**, respectively, continue from block **818**. Also, even though the drawings illustrate that the relative physiologic parameter value is communicated to the backend computing system and then to the IMD, the present invention is not limited to this embodiment. In some embodiments, the external computing device can display the relative physiologic parameter value to a physician or other user, or it can determine therapy information using the relative physiologic parameter value without first communicating the relative value to the backend computing system. Further, the external computing device can communicate the relative physiologic parameter value to the IMD without first communicating it to the backend computing system. Thus, as one skilled in the art will appreciate, the present invention is not limited to the illustrated embodiments.

Referring now to FIG. **8c**, in this particular embodiment, the IMD can be configured to calculate or determine a therapy based on the relative physiologic parameter value (block **824**). In one embodiment, the IMD can be configured to administer the therapy to the patient (block **826**), as discussed above.

Referring now to FIG. **8d**, in this particular embodiment, the IMD again can be configured to calculate or determine a therapy or therapy information based on the relative physiologic parameter value (block **834**). Then, instead of, or in addition to administering the therapy to the patient, the IMD is configured to communicate the therapy information to the external computing device (e.g., external computing device **106**), or alternatively, the external monitor (e.g., external monitor **104**) (block **836**). In one embodiment, the external computing device (and/or external monitor) can be configured to provide or communicate the therapy information to the patient via a user or patient interface, as discussed above (block **838**).

In an alternative embodiment, after the external computing device (or external monitor) receives the therapy information from the IMD, a physician or other health care provider then can analyze the therapy information and provide it to the patient if the physician determines that it is appropriate, or the physician could provide different or additional therapy to the patient if the physician determines that an alternative therapy would be better. In addition, the therapy information can be uploaded to a backend computing system (e.g., backend computing system **108**) (block **840**) for later processing, access and/or analysis. Also, instead of the IMD determining the therapy information, the external computing device, the external monitor, and/or the backend computing system can be configured to determine the therapy information based on the relative physiologic parameter value. The present invention is not limited to the IMD determining the therapy.

Referring now to FIG. **9**, yet another embodiment of a method of deriving and using relative physiologic parameter values is shown. In accordance with the method illustrated in flow chart **900**, an IMD (e.g., IMD **102** in FIG. **1**) determines an absolute physiologic parameter value (block **902**). As discussed above, the physiologic parameter values obtained can be any physiologic measurement, such as, blood pressure, temperature, blood or fluid flow, strain, electrical, chemical or magnetic properties within the body, or the like.

After the IMD obtains the absolute physiologic parameter value (e.g., absolute blood pressure), the IMD communicates the

absolute physiologic parameter value to an external computing device (e.g., external computing device **106** in FIG. **1**) (block **904**). Again, the IMD and the external computing device can implement a data transmission check (e.g., a cyclic redundancy code (“CRC”) check) to ensure the data is transmitted properly.

The external computing device receives the absolute physiologic parameter value and communicates it to a backend computing system (e.g., backend computing system **108** in FIG. **1**) (block **906**). The backend computing then obtains an ambient condition value (block **908**), for example, from the external computing device or from an external monitor, as discussed above. Alternatively, the backend computing system can receive the ambient condition value from another source, such as another computing device in communication with the backend computing system, the Internet, or some other source. The means by which the backend computing system obtains the ambient condition value is not critical, and thus, the present invention is not limited to any particular method or system for obtaining the ambient condition value. Also, as one skilled in the art will appreciate, backend computing system can obtain the ambient condition value prior to receiving the absolute physiologic parameter value. In addition, as discussed above, the physiologic parameter value and/or the ambient condition value can include time stamps, so that the relative physiologic parameter value is calculated using values that are similar in time.

After the backend computing system obtains the ambient condition value and the absolute physiologic parameter value, the backend computing system calculates a relative physiologic parameter value (block **910**), and then the backend computing system stores the relative physiologic parameter value, for example, in a database or other similar storage area (block **912**). The data then can be made available for later processing, access, and/or analysis by one or more health care providers, such as physicians, specialists, IMD manufacturers, insurance companies, pharmaceutical companies, or any other suitable health care provider.

After the relative physiologic parameter value is calculated at the backend computing system, additional processing can occur in a number of different devices in the system. This is illustrated by continuation block **914** in FIG. **9**.

Referring now to FIGS. **10a-10d**, additional embodiments of the present invention will be described with reference to flow charts **1000**, **1010**, **1020** and **1030**, respectively. In FIGS. **10a-10b**, continuation blocks **1002** and **1032** are continuations from block **914** in FIG. **9**. Thus, in accordance with the embodiment illustrated in FIG. **10a**, after the backend computing system calculates the relative physiologic parameter value, it communicates the relative physiologic parameter value to the external computing device. As discussed above, the external computing device then can display or provide the relative physiologic measurement values to a health care provider or other entity for review.

In addition, as illustrated by flow chart **1000** in FIG. **10a**, the external computing device also can communicate the relative physiologic parameter value to the IMD (block **1006**), which then can store the relative physiologic parameter value, for example, in a memory. When the IMD receives the relative physiologic parameter value, the IMD then can use the value for additional processing, as illustrated by continuation block **1008**. Continuation blocks **1012** and **1022** in FIGS. **10b** and **10c**, respectively, continue from block **1008**.

Referring now to FIG. **10b**, in this particular embodiment, the IMD can be configured to calculate or determine a therapy based on the relative physiologic parameter value (block

1014). As discussed above, the IMD can be configured to administer the therapy to the patient (block 1016).

In an alternative embodiment illustrated in FIG. 10c, the IMD again can be configured to calculate or determine a therapy or therapy information based on the relative physiologic parameter value (block 1024), but instead of, or in addition to administering the therapy to the patient, the IMD is configured to communicate the therapy information to the external computing device or external monitor (block 1026), which can be configured to provide or communicate the therapy information to the patient (block 1028).

Further, as discussed above, after the external computing device (and/or the external monitor) receives the therapy information from the IMD, a physician or other health care provider then can analyze the therapy information and provide it to the patient if the physician determines that it is appropriate, or the physician could provide different or additional therapy to the patient if the physician determines that an alternative therapy would be better. The therapy information also can be uploaded to a backend computing system (e.g., backend computing system 108) (block 1029) for later processing, access and/or analysis. In addition, in an alternative embodiment, instead of the IMD determining the therapy information, the external computing device and/or the external monitor can be configured to calculate or determine the therapy information.

Referring now to FIG. 10d, flowchart 1030 illustrates another embodiment of the present invention. In accordance with this particular embodiment, after the backend computing system calculates the relative physiologic parameter value, the backend computing system then can use that value to determine a therapy or therapy information for the patient (block 1034). The backend system then can store the therapy information in the database for later access by a health care provider (block 1036). In addition, the backend system can communicate the therapy information to the external computing device and/or the external monitor, which can display or provide the therapy information to a health care provider, as discussed above.

Referring now to FIG. 11, still another embodiment of a method of deriving and using relative physiologic parameter values is shown. In accordance with the method illustrated in flow chart 1100, a remote sensor system of an IMD (e.g., remote sensor system 112 in FIG. 1) measures an absolute physiologic parameter value (block 1102). As discussed above, the remote sensor system can comprise satellite sensors, which can measure any physiologic measurement, such as, blood pressure, temperature, blood or fluid flow, strain, electrical, chemical or magnetic properties within the body, or the like. In one particular embodiment, the physiologic parameter value obtained is blood pressure (e.g., intravascular or intracardiac blood pressure), and one or more pressure sensors associated with the remote sensor system are used to obtain the absolute blood pressure value. Again, the absolute pressure measured by a pressure sensor can be adjusted for internal temperatures and/or a built-in backing pressure and/or temperature coefficients of the pressure sensor.

After the remote sensor system of the IMD obtains the absolute physiologic parameter (e.g., absolute blood pressure), an external device obtains an ambient condition value (block 1104). In one embodiment, the external device is an external monitor (e.g., external monitor 104 in FIG. 1), which includes one or more sensors for measuring the ambient condition value. In another embodiment, the external device is an external computing device (e.g., external computing device 106 in FIG. 1), which can either measure the ambient condition value, or obtain the ambient condition value from another

source, such as a backend computing system, other sensors in communication with the external computing device, or the Internet.

After the external device obtains the ambient condition value, it communicates the ambient condition value to the remote sensor system (block 1106), which then calculates a relative physiologic parameter value from the absolute physiologic parameter value and the ambient condition value (block 1108). As with other communication connections, the external device and the remote sensor system can implement a data transmission check (e.g., a cyclic redundancy code ("CRC") check) to ensure the data is transmitted properly. Further, as discussed above, the physiologic parameter value and/or the ambient condition value can include time stamps, so that the relative physiologic parameter value is calculated using values that are similar in time. After the remote sensor system calculates the relative physiologic parameter value, additional processing can occur in a number of different devices in the system. This is illustrated by continuation block 1110 in FIG. 11.

Referring now to FIGS. 12a-12f, additional embodiments of the present invention will be described with reference to flow charts 1200-1250. In accordance with the embodiment illustrated in FIG. 12a, after the remote sensor system calculates the relative physiologic parameter value, it communicates the relative physiologic parameter value to the main body of the IMD (e.g., IMD 102) (block 1204), which then can store the relative physiologic parameter value, for example, in a memory (block 1206).

In addition, after the IMD receives the relative physiologic parameter value, it can communicate it to the external device (block 1214 in FIG. 12b). As discussed in previous embodiments, the external device can provide the relative physiologic parameter value to the patient or a health care provider, or it can communicate the relative physiologic parameter value to a backend computing system (block 1216).

In another embodiment, instead of the main body of the IMD communicating the relative physiologic parameter value to the external device, the remote sensor system can be configured to communicate the relative physiologic parameter value to the external device directly (block 1224 in FIG. 12c). Then, as with the embodiment of FIG. 12b, the external device can display the relative physiologic parameter value, and/or it can communicate the value to a backend computing system (block 1226).

Upon receiving the relative physiologic parameter value, the backend computing system then can store the value in a database for access by health care providers. In addition, as discussed above, the backend computing system can use the relative physiologic parameter value to determine a therapy for the patient (block 1254 in FIG. 120). The backend computing system then can store the therapy information in a database (block 1256), and/or the backend system can communicate the therapy information to the external device, which can display or provide the therapy information to relevant parties.

Referring now to FIGS. 12d and 12e, in accordance with other embodiments of the invention, after the IMD stores the relative physiologic parameter value (block 1206 in FIG. 12a), the IMD can be configured to calculate or determine a therapy based on the relative physiologic parameter value (blocks 1234 and 1244 in FIGS. 12d and 12e, respectively). As discussed above, the IMD can be configured to administer the therapy to the patient (block 1236), and/or the IMD can communicate the therapy information to the external device (block 1246). The external device then can provide or communicate the therapy information to the patient, a physician

or other health care provider (block 1248). In addition, the therapy information can be uploaded to a backend computing system (block 1249) for later processing, access and/or analysis. In still other embodiments, instead of the backend computing system or the IMD determining the therapy information, the external device can be configured to calculate or determine the therapy.

Various modifications and additions can be made to the exemplary embodiments discussed without departing from the scope of the present invention. For example, while the embodiments described above refer to particular features, the scope of this invention also includes embodiments having different combinations of features and embodiments that do not include all of the described features. Accordingly, the scope of the present invention is intended to embrace all such alternatives, modifications, and variations as fall within the scope of the claims, together with all equivalents thereof

We claim:

1. A system for deriving relative physiologic measurement values, comprising:

an implantable medical device (“IMD”) operable to determine a physiologic parameter value within a patient’s body and communicate the physiologic parameter value outside the patient’s body, the IMD including a sensor operable to obtain a measured physiologic parameter value, wherein the measured physiologic parameter value comprises a value of a parameter measured within the patient’s body, and including a transmitter adapted to communicate the physiologic parameter value outside the patient’s body, wherein the physiologic parameter value comprises the measured physiologic parameter value or an absolute physiologic parameter value, wherein the absolute physiologic parameter value is based on the measured physiologic parameter value;

an external computing device including communication circuitry configured to wirelessly receive the physiologic parameter value and an integral sensor configured to sense an ambient condition value, wherein the ambient condition value comprises a value of the parameter measured outside the patient’s body, the external computing device comprising a single device operable to both:

wirelessly receive the physiologic parameter value from the IMD; and

sense the ambient condition value;

the external computing device or a backend computing system operable to calculate a relative physiologic parameter value from the ambient condition value and the physiologic parameter value; and

the external computing device or the backend computing system operable to store the calculated relative physiologic parameter value.

2. The system of claim 1, the IMD comprising a main body, the main body including a receiver in communication with the sensor, wherein the sensor comprises a remote sensor, the remote sensor operable to obtain the measured physiologic parameter value within the patient’s body and including a transmitter adapted to communicate the physiologic parameter value to the receiver.

3. The system of claim 1, wherein the external computing device is operable to communicate the relative physiologic parameter value to the IMD, and wherein the IMD is further operable to receive the relative physiologic parameter value and store it in a memory.

4. The system of claim 1, wherein the backend computing system comprises a database accessible by one or more health care providers, and wherein the one or more health care

providers can obtain the relative physiologic parameter value from the database and use the relative physiologic parameter value to provide a service to the patient selected from the group consisting of diagnosing the patient, prescribing medication to the patient, providing a therapy to the patient, or modifying one or more settings of the IMD.

5. The system of claim 1, wherein the physiologic parameter value comprises at least one of a blood pressure, a temperature, a fluid flow, a strain, an electrical property, a chemical property, and a magnetic property.

6. The system of claim 1, wherein the external computing device comprises at least one of an IMD programmer and a repeater device in communication with the backend computing system.

7. The system of claim 1, wherein the IMD and the external computing device are operable to communicate via a wireless communication connection selected from the group consisting of: a radio frequency communication connection; an acoustic communication connection; an electrical field communication connection; and an optical communication connection.

8. The system of claim 1, wherein the IMD is selected from the group consisting of a physiologic parameter sensor, a pacemaker, a defibrillator, a bi-ventricular pacer, a ventricular assist blood pump, a drug delivery pump, a drug infusion device, a neurostimulating device, an intra-ocular shunt, and an intra-cranial shunt.

9. The system of claim 1, wherein the IMD is operable to provide therapy to a patient, and wherein at least one of the IMD, the external computing device, and the backend computing system uses the relative physiologic parameter value to determine a therapy to provide to the patient.

10. The system of claim 3, wherein:

the IMD comprises a processor operable to generate patient therapy information based at least in part on the relative physiologic parameter value;

the IMD is further operable to communicate the patient therapy information to the external computing device; and

the external computing device is operable to communicate the patient therapy information to the backend computing system for access by one or more health care providers.

11. A method for deriving relative physiologic measurement values, comprising:

determining a physiologic parameter value with an implantable medical device (“IMD”), the IMD including an implantable sensor and a transmitter, wherein the physiologic parameter value comprises a measured physiologic parameter value or an absolute physiologic parameter value, wherein the measured physiologic parameter value comprises a value of a parameter measured within the patient’s body, and wherein the absolute physiological parameter value is based on the measured physiologic parameter value;

obtaining the measured physiologic parameter value with the implantable sensor;

communicating the physiologic parameter value to an external computing device outside the patient’s body, the external computing device comprising communication circuitry configured to wirelessly receive the physiologic parameter value and an integral sensor configured to sense an ambient condition value, wherein the ambient condition value comprises a value of the parameter measured outside of the patient’s body, the external computing device comprising a single device operable to both:

21

wirelessly receive the physiologic parameter value from the IMD; and sense the ambient condition value; sensing, via the integral sensor, the ambient condition value; communicating the physiologic parameter value and the ambient condition value from the external computing device to a backend computing system; calculating a relative physiologic parameter value from the ambient condition value and the physiologic parameter value and storing the relative physiologic parameter value in a memory.

12. The method of claim 11, wherein the IMD comprises a main body with a receiver in acoustic communication with a remote sensor system, the remote sensor system including a transmitter adapted to acoustically communicate the physiologic parameter value to the receiver.

13. The method of claim 11, further comprising storing the relative physiologic parameter value in a database of the backend computing system accessible by one or more health care providers.

14. The method of claim 11, wherein the physiologic parameter value comprises at least one of a blood pressure, a temperature, a fluid flow, a strain, an electrical property, a chemical property, and a magnetic property.

15. The method of claim 11, wherein the external computing device comprises at least one of an IMD programmer and a repeater device in communication with the backend computing system.

16. The method of claim 11, wherein communicating the physiologic parameter value to the external computing device comprises communicating via a wireless communication connection selected from the group consisting of a radio frequency communication connection; an acoustic communication connection; an electric field communication connection; and an optical communication connection.

17. The method of claim 11, wherein the IMD is selected from the group consisting of a physiologic parameter sensor, a pacemaker, a defibrillator, a bi-ventricular pacer, a ventricular assist blood pump, a drug delivery pump, a drug infusion device, a neurostimulating device, an intra-ocular shunt, and an intra-cranial shunt.

18. The method of claim 17, further comprising: determining a therapy to provide to the patient using the relative physiologic parameter value; providing the therapy to the patient with the IMD; and storing the therapy information for access by one or more health care providers using the backend computing system.

19. A system for deriving relative physiologic parameter values, comprising: an implantable medical device (“IMD”) including: a remote sensor system adapted to be implanted in a patient’s body and operable to obtain a physiologic parameter value, the remote sensor system including a transmitter, wherein the physiologic parameter value

22

comprises a measured physiologic parameter value or an absolute physiologic parameter value, wherein the measured physiologic parameter value comprises a value of a parameter measured within the patient’s body, and wherein the absolute physiologic parameter value is based on the measured physiologic parameter value;

a main body adapted to be implanted in the patient’s body, the main body including a receiver in communication with the transmitter of the remote sensor system and operable to receive the physiologic parameter value from the remote sensor system, the main body operable to communicate the physiologic parameter value outside the patient’s body;

an external computing device comprising a single device operable to: wirelessly receive the physiologic parameter value from the IMD; sense an ambient condition value, wherein the ambient condition value comprises a value of the parameter measured outside the patient’s body; and communicate the physiologic parameter value to a backend computing system; and the backend computing system operable to: receive the physiologic parameter value from the external computing device; obtain the ambient condition value from the external computing device; calculate a relative physiologic parameter value from the ambient condition value and the physiologic parameter value; and store the calculated relative physiologic parameter value in a database accessible by one or more health care providers.

20. The system of claim 19, wherein the physiologic parameter value comprises at least one of a blood pressure, a temperature, a fluid flow, a strain, an electrical property, a chemical property, and a magnetic property.

21. The system of claim 19, wherein the external computing device comprises at least one of an IMD programmer and a repeater device in communication with the backend computing system.

22. The system of claim 19, wherein the IMD and the external computing device are operable to communicate via a wireless communication connection selected from the group consisting of: a radio frequency communication connection; an acoustic communication connection; an electrical field communication connection; and an optical communication connection.

23. The system of claim 19, wherein the IMD is selected from the group consisting of a physiologic parameter sensor, a pacemaker, a defibrillator, a bi-ventricular pacer, a ventricular assist blood pump, a drug delivery pump, a drug infusion device, a neurostimulating device, an intra-ocular shunt, and an intra-cranial shunt.

\* \* \* \* \*

专利名称(译)	用于导出相对生理测量的系统和方法		
公开(公告)号	<a href="#">US8852099</a>	公开(公告)日	2014-10-07
申请号	US13/564332	申请日	2012-08-01
[标]申请(专利权)人(译)	VON ARX JEFFREY 一个 MAZAR SCOTT† 恰范ABHI		
申请(专利权)人(译)	VON ARX JEFFREY A. MAZAR SCOTT T. 恰范ABHI		
当前申请(专利权)人(译)	心脏起搏器, INC.		
[标]发明人	VON ARX JEFFREY A MAZAR SCOTT T CHAVAN ABHI		
发明人	VON ARX, JEFFREY A. MAZAR, SCOTT T. CHAVAN, ABHI		
IPC分类号	A61B5/00 A61M5/142 A61M5/172 A61N1/372		
CPC分类号	A61N1/37252 A61B5/0031 A61M5/14276 A61N1/37223 A61M2230/30 A61M5/1723 A61N1/37217 A61M2205/3523 A61M2205/52		
代理机构(译)	FAEGRE BAKER丹尼尔斯律师事务所		
其他公开文献	US20120296177A1		
外部链接	<a href="#">Espacenet</a> <a href="#">USPTO</a>		

摘要(译)

本发明的一个实施例涉及一种用于导出相对于环境条件的生理测量值的系统。在一个实施例中，该系统包括可植入医疗设备 (“IMD”)，外部计算设备和后端计算系统。IMD确定患者体内的生理参数值，并将例如患者体外的生理参数值传送到外部计算设备。此外，外部计算设备从IMD接收生理参数并将其传送到后端计算系统。后端计算系统接收生理参数值并获得身体外的环境条件值。然后，后端计算系统根据环境条件值和生理参数值计算相对生理参数值，并且在一些实施例中，将相对生理参数值存储在存储位置，例如存储器或数据库中。

