



US008923960B2

(12) **United States Patent**
Goto

(10) **Patent No.:** **US 8,923,960 B2**
(45) **Date of Patent:** **Dec. 30, 2014**

- (54) **CARDIAC ARREST MONITORING DEVICE**
- (71) Applicant: **Empire Technology Development LLC**,
Wilmington, DE (US)
- (72) Inventor: **Hiroshi Goto**, Ushiku (JP)
- (73) Assignee: **Empire Technology Development LLC**,
Wilmington, DE (US)
- (*) Notice: Subject to any disclaimer, the term of this
patent is extended or adjusted under 35
U.S.C. 154(b) by 0 days.

(21) Appl. No.: **13/682,669**

(22) Filed: **Nov. 20, 2012**

(65) **Prior Publication Data**
US 2013/0076508 A1 Mar. 28, 2013

Related U.S. Application Data

(62) Division of application No. 12/645,309, filed on Dec.
22, 2009, now Pat. No. 8,423,128.

- (51) **Int. Cl.**
A61B 5/04 (2006.01)
A61B 5/00 (2006.01)
A61B 5/11 (2006.01)
G06F 19/00 (2011.01)
G08B 21/02 (2006.01)
A61N 1/39 (2006.01)
A61B 5/0402 (2006.01)

- (52) **U.S. Cl.**
CPC *G08B 21/02* (2013.01); *A61B 5/0006*
(2013.01); *A61B 5/1112* (2013.01); *A61N*
1/3993 (2013.01); *G06F 19/3418* (2013.01);
A61B 5/0402 (2013.01); *A61N 1/3925*
(2013.01)
USPC **600/523**; 600/509; 600/515; 600/522

(58) **Field of Classification Search**
USPC 600/509, 513, 522, 525
See application file for complete search history.

- (56) **References Cited**
U.S. PATENT DOCUMENTS
6,292,687 B1 * 9/2001 Lowell et al. 600/515
6,493,581 B2 12/2002 Russell
6,985,771 B2 1/2006 Fischell et al.
2002/0069885 A1 * 6/2002 Boies et al. 128/899
2005/0065445 A1 3/2005 Arzbaecher et al.
2007/0218869 A1 * 9/2007 Thijs et al. 455/404.2
2011/0152702 A1 6/2011 Goto


- FOREIGN PATENT DOCUMENTS
JP 2001-327472 A 11/2001
JP 2004-129980 A 4/2004
JP 2008-161641 A 7/2008
JP 2009-224967 A 1/2009
JP 2011-066861 A 3/2011
WO WO03/082102 10/2003
WO 2008-149467 A1 11/2008

OTHER PUBLICATIONS
“Heart Attack Also called: MI, Myocardial infarction,” Accessed at
<http://web.archive.org/web/20140606045722/http://www.nlm.nih.gov/medlineplus/heartattack.html>, Accessed on Jun. 18, 2014.

* cited by examiner
Primary Examiner — Christopher D Koharski
Assistant Examiner — Natasha Patel
(74) *Attorney, Agent, or Firm* — Turk IP Law, LLC

(57) **ABSTRACT**
The present disclosure relates to devices, implementations
and techniques for health monitoring. Embodiments of the
present disclosure relate to cardiac arrest monitoring devices.

8 Claims, 11 Drawing Sheets






FIG. 1




FIG. 2




FIG. 3




FIG. 4




FIG. 5




FIG. 6




FIG. 7




FIG. 8




FIG. 9




FIG. 10




FIG. 11




FIG. 12

CARDIAC ARREST MONITORING DEVICECROSS-REFERENCE TO RELATED
APPLICATION

This application is a divisional of and claims priority to U.S. patent application Ser. No. 12/645,309 filed Dec. 22, 2009 entitled "Cardiac Arrest Monitoring Device", the entire contents of which are incorporated herein by reference.

BACKGROUND

Unless otherwise indicated herein, the approaches described in this section are not prior art to the claims in this application and are not admitted to be prior art by inclusion in this section.

An effective way to treat cardiac arrest may be with a defibrillator. A defibrillator is a medical device that delivers an electric current, or "shock" to the chest of a cardiac arrest victim, which delivers that electric current to the victim's heart. The shock can interrupt the erratic electrical pulse of ventricular fibrillation of the heart during the cardiac arrest, which can give the victim's heart a chance to begin beating at its normal rhythm.

During the first 10 minutes after a person suffers a cardiac arrest, every minute saved before defibrillation may mean about a 10 percent increase in relative survival rate. Therefore, as time is critical, there has been an increase in the availability of automated external defibrillators, or AEDs. AEDs are portable medical devices designed primarily for use by "first responders" (first to arrive at the scene of a medical emergency), such as police and fire departments. An AED generally has a built-in computer that evaluates a victim's heart rhythm to determine whether a shock is required. AEDs are also relatively easy to use as they typically include voice instructions and screen messages to assist in its operation, and thus, can be used by an average citizen with little or no training.

As the AEDs have become more simple to use, they are being installed in a variety of public and private settings, including but not limited to, schools, sports facilities, transportation hubs, office buildings, elder care facilities, government buildings, and the like.

BRIEF DESCRIPTION OF THE DRAWINGS

The subject matter of the present disclosure is particularly pointed out and distinctly claimed in the concluding portion of the specification. The foregoing and other features of the present disclosure will become more fully apparent from the following description and appended claims, taken in conjunction with the accompanying drawings. Understanding that these drawings depict only several embodiments in accordance with the disclosure and are, therefore, not to be considered limiting of its scope, the disclosure will be described with additional specificity and detail through use of the accompanying drawings.

In the drawings:

FIG. 1 illustrates a cardiac arrest monitoring system, according to one embodiment of the present disclosure;

FIG. 2 illustrates a cardiac arrest monitoring device, according to one embodiment of the present disclosure;

FIG. 3 illustrates a map displayed on a monitor, according to one embodiment of the present disclosure;

FIG. 4 illustrates a cardiac rhythm on a monitor, according to one embodiment of the present disclosure;

FIG. 5 illustrates a paramedical device, according to one embodiment of the present disclosure;

FIG. 6 illustrates a mobile terminal device, according to one embodiment of the present disclosure;

FIGS. 7-10 are block diagrams illustrating process flows for the cardiac arrest monitoring system, according to one embodiment of the present disclosure;

FIG. 11 is a schematic illustrating an example computer program product that is arranged in accordance with the present disclosure; and

FIG. 12 is a schematic illustrating an exemplary computing device, according to one embodiment of the present disclosure.

DETAILED DESCRIPTION

The following description sets forth various examples along with specific details to provide a thorough understanding of claimed subject matter. It will be understood by those skilled in the art, however, that claimed subject matter may be practiced without some or more of the specific details disclosed herein. Further, in some circumstances, well-known methods, procedures, systems, components and/or circuits have not been described in detail in order to avoid unnecessarily obscuring claimed subject matter. In the following detailed description, reference is made to the accompanying drawings, which form a part hereof. In the drawings, similar symbols typically identify similar components, unless context dictates otherwise. The illustrative embodiments described in the detailed description, drawings, and claims are not meant to be limiting. Other embodiments may be utilized, and other changes may be made, without departing from the spirit or scope of the subject matter presented here. It will be readily understood that the aspects of the present disclosure, as generally described herein, and illustrated in the Figures, can be arranged, substituted, combined, and designed in a wide variety of different configurations, all of which are explicitly contemplated and make part of this disclosure.

This disclosure is drawn, inter alia, to methods, apparatus, systems, and/or computer program products related to health monitoring, such as a cardiac arrest monitoring systems.

The subject matter described herein provides a cardiac arrest monitoring system, which may include:

- a. Cardiac Arrest Monitoring Device, which monitors a user's cardiac rhythm, detects anomalies, locates nearby paramedical equipment, and outputs the location information of the paramedical equipment. This device may generate an audio and/or visual alarm to notify passersby of the cardiac victim/user's distress;
- b. Paramedical Device, connected to paramedical equipment, such as automated external defibrillator (hereinafter "AED"), which may be configured to output the location information of a patient who wears the cardiac arrest monitoring device. Further, this device may be configured to generate an audio and/or visual alarm to notify passersby of the existence of a victim/user who needs the paramedical equipment connected to the paramedical device; and
- c. Mobile Terminal Device, which is for use by a passerby who encounters a victim of a cardiac arrest. The mobile terminal device searches nearby paramedical equipment and outputs the location information of the paramedical equipment to the passerby.

Referring to FIG. 1, one embodiment of a cardiac arrest monitoring system **100** may include a cardiac arrest monitoring device **110**, which may be worn by a patient/user **115**. The

cardiac arrest monitoring device **110** may communicate with at least one paramedical device (illustrated as **120a** and **120b**). Although illustrated as **120a** and **120b**, the paramedical devices will be referred to collectively as **120**, as there may be any number of paramedical devices. The communication with the paramedical devices **120** may be wireless as illustrated by wireless communication line **112**. The cardiac arrest monitoring device **110** may communicate with a server **130**, which contains the location information of the paramedical devices **120a** and **120b**. The communication with the server **130** may be wireless, as illustrated by wireless communication line **114**. The cardiac arrest monitoring system **100** may also include a mobile terminal device **140** which may be carried by a user **135**. The mobile terminal device **140** may communicate with at least one paramedical device **120**. The communication may be wireless, as illustrated by wireless communication line **116**. The mobile terminal device **140** may communicate with the server **130**, which contains the location information of the paramedical devices **120a** and **120b**. The communication with the paramedical devices **120** may be wireless, as illustrated by wireless communication line **118**.

Thus, when an anomaly in a cardiac rhythm is detected by the cardiac arrest monitoring device **110**, the device searches for nearby paramedical equipment **120** (either through a server **130** or the paramedical equipment **120** itself), and outputs the location information of the paramedical equipment **120**.

Referring to FIGS. **1** and **2**, one embodiment of the cardiac arrest monitoring device **110** of FIG. **1** may include an electronic monitor **206** coupled to a sensor **202**. The electronic monitor **206** monitors the cardiac rhythm of the patient/user **115** through the sensor **202**, which may be adapted to attach to the patient/user **115**. The sensor **202** may be adapted to detect a user's cardiac rhythm and store such data continuously as an electrical signal, such as an electrocardiograph or ECG, as will be understood to those skilled in the art.

The electronic monitor **206** may include an anomaly detection circuit **208**. The anomaly detection circuit **208** may comprise a logic circuit that analyzes data received from the sensor **202** to detect anomalies in cardiac rhythm. The anomaly detection circuit **208** may include a comparison circuit **210**. The comparison circuit **210** may be adapted to compare the received cardiac rhythm data by the anomaly detection circuit **208** with preprogrammed data. The examples of "preprogrammed data" may included, but is not limited to, previous data of the user, average populous data (e.g. 60-100 beats per minute), average data of a specific demographic (age, sex, location, etc.), and the like. The anomaly detection circuit **208** in conjunction with its comparison circuit **210** may determine whether an anomaly of cardiac rhythm is occurring, e.g., a lack of a heartbeat for a certain period or a substantial difference from the preprogrammed data.

The electronic monitor **206** may further include a paramedical equipment locator **212**. The paramedical equipment locator **212** may be adapted to identify the location of the paramedical device **120**. The paramedical equipment locator **212** may wirelessly broadcast a message to request the location information of the paramedical device **120**, and may receive the location information from the paramedical device **120** itself, as will be discussed. In response to receiving the location information, the paramedical equipment locator **212** may select one or more nearby paramedical devices **120** by calculating the distance between the cardiac arrest monitoring device **110** and each paramedical device **120**. Alternately, the paramedical device **120** may broadcast its location information

periodically, regardless whether or not the cardiac arrest monitoring device **110** requests the location information, as will be discussed. Thus, the cardiac arrest monitoring device **110** can receive the location information for each paramedical device **120**, without sending a request of the location information.

Referring to FIGS. **1** and **2**, in another embodiment, the cardiac arrest monitoring device **110** through its paramedical equipment locator **212** may request the location information for the paramedical device **120** from the server **130**, which may manage the location information of paramedical device **120**. The cardiac arrest monitoring device **110** may also send the server **130** its location information to obtain the location information for nearby paramedical device **120**. A self-location acquisition unit **214** such as a GPS receiver may be coupled or installed in the cardiac arrest monitoring device **110**, which can determine the location of the cardiac arrest monitoring device **110** or a user **115** (victim). The paramedical equipment locator **212** may use this location information to calculate the distance between a user (i.e., the cardiac arrest monitoring device **110**) and the paramedical device **120**.

The electronic monitor **206** may also have an alarm unit **216**. The alarm unit **216** may generate an alarm, e.g. audible and/or visual, to notify a passerby of a cardiac anomaly that is occurring with the patient/user **115**, in responding to the anomaly detection circuit **208** detecting the anomaly in the cardiac rhythm.

The electronic monitor **206** may further include a communication interface **218**. The communication interface **218** may control the communication between the electronic monitor **206** and the paramedical device **120** and/or the server **130**. The communication interface **218** may include, but is not limited to, a wireless communication device.

The electronic monitor **206** may also have an output unit **220**. The output unit **220** may be, for example, a video display, audio speaker, and the like. The output unit **220** may output information of the location of the paramedical device **120**. For example, as shown in FIG. **3**, the location of the electronic monitor **206** (e.g. location of the user **115**) and the location of nearby paramedical devices **120a** and **120b** may be displayed on a map **304** on a video display or monitor **302**. Furthermore, as shown in FIG. **4**, the output unit **220** may graphically display the detected cardiac rhythm data/inter-pulse time **404** on a video display or monitor **402**.

Referring again to FIG. **2**, it is understood that components, such as **208**, **212**, **214**, **216**, **218**, and **220** may be in communication with one and other through a bus **222**. It is also understood that the term "bus", as used within this detailed description, may refer to any communication coupling method between the various components, including but not limited to wired communication and wireless communication.

As previously discussed, the present disclosure may include a paramedical device **120**, as shown in FIG. **1**. As shown in FIG. **5**, the paramedical device **120** may connected to an article of paramedical equipment **502**, such as an AED. The paramedical device **120** may send its location information to the cardiac arrest monitoring device **110**, as shown in FIG. **1**. The paramedical device **120** may also be configured to output the location information of a victim, e.g. user **115**, who wears the cardiac arrest monitoring device **110**, and generate an alarm to notify passersby of existence of a victim who need this paramedical equipment **502**, e.g. the AED.

Referring to FIGS. **1** and **5**, one embodiment of the paramedical device **120** may include a paramedical device location module **504**. The paramedical device location module **504** may provide the cardiac arrest monitoring device **110**

with the location information of the paramedical equipment **502** to which the paramedical device **120** is attached. The paramedical device location module **504** may send such information in responding to receiving a request from the cardiac arrest monitoring device **110**. Alternately, the paramedical device location module **504** may broadcast the location information periodically, regardless whether or not the cardiac arrest monitoring device **110** requests the location information. The paramedical device location module **504** may include a memory module (such as a non-volatile flash module), which may store the location information or may be a self-location acquisition unit such as a GPS receiver to obtain its location information.

The paramedical device **120** may also have an alarm unit **506**. The alarm unit **506** may generate an alarm, e.g. audible and/or visual, to notify a passerby of a cardiac anomaly that is occurring with the user, in responding to receiving the location information of the cardiac arrest monitoring device **110** (e.g. the location of the victim).

The paramedical device **120** may further include a communication interface **508**. The communication interface **508** may facilitate the communication between the paramedical device **120** and the cardiac arrest monitoring device **110** and/or the server **130**. The communication interface **508** may include, but is not limited to, a wireless communication device.

The paramedical device **120** may also have an output unit **510**. The output unit **510** may be, for example, a video display, audio speaker, and the like. The output unit **510** may output information of the location of a victim (e.g. user **115**) who wears the cardiac arrest monitoring device **110**. For example, the location of the victim may displayed on a map **304** on the monitor **302**, which can show the location of an electronic monitor **206** (e.g. location of the user **115**) and the location of nearby paramedical devices **120a** and **120b**, such as shown in FIG. 3.

Referring again to FIG. 5, it is understood that components, such as **504**, **506**, **508**, and **510** may be in communication with one and other through a bus **512**.

As previously discussed, another embodiment of the present disclosure may include the mobile terminal device **140**. The mobile terminal device **140** may be used by a passerby, e.g. user **135** (such as a care worker), who may encounter a victim (e.g. user **115**) of cardiac arrest. The mobile terminal device **140** may search for nearby paramedical devices **120** and may output the location information of the paramedical device **120**.

As shown in FIGS. 1 and 6, the mobile terminal device **140** may include a paramedical equipment locator **602**. The paramedical equipment locator **602** may broadcast or send message to request the location information of the paramedical device **120**, and may receive the location information from the paramedical device **120**. Upon receiving the location information of the paramedical device **120**, the paramedical equipment locator **602** may select one or more nearby paramedical device **120a** and **120b** by determining a distance between the mobile terminal device **140** and the paramedical device **120**. In another embodiment, the paramedical equipment locator **602** may request a location information for the paramedical device **120** from the server **130**, which may manage the location information of the paramedical devices **120**. The mobile terminal device **140** may send the server **130** its location information, and in turn, the server **130** may provide the location information of nearby paramedical devices **120**. To determine its location the mobile terminal device **140** may include a self-location acquisition unit **604**, such as a GPS receiver.

The mobile terminal device **140** may also have an output unit **606**. The output unit **606** may be, for example, a video display, audio speaker, and the like. The output unit **606** may output information of the location of the nearest paramedical devices **120**. For example, the location of the victim (e.g. user **115**) may be displayed on a map **304** on the monitor **302**, which may show the location of nearby paramedical devices **120**, such as shown in FIG. 3.

Referring again to FIG. 6, it is understood that components, such as **602**, **604**, and **606** may be in communication with one and other through a bus **608**.

FIGS. 7-10 show examples of process flows in accordance with at least some embodiments of the present disclosure. The processes described herein, set forth various functional blocks or actions that may be described as process flows, functional operations, events and/or acts, etc., which may be performed by hardware, software, and/or firmware. Those skilled in the art, in light of the present disclosure, will recognize that numerous alternatives to the functional blocks shown in FIGS. 7-10 may be practiced in various implementations. For example, although the processes, as shown in FIGS. 7-10, comprise one particular order of blocks or actions, the order in which these blocks or actions are presented does not necessarily limit claimed subject matter to any particular order. Likewise, intervening actions not shown in FIGS. 7-10 and/or additional actions not shown in FIG. 7-10 may be employed and/or some of the actions shown in FIGS. 7-10 may be eliminated, without departing from the scope of claimed subject matter.

The process **700** illustrates the operation of a cardiac arrest monitoring device, which receives a location information of paramedical equipment (e.g. an AED) from one or more paramedical devices to which the paramedical equipment is attached, and responsive to the received location information, communicates the location information for a paramedical equipment. Referring to FIG. 7, a cardiac rhythm may be monitored with a sensor **202**, at block **702**. At block **704**, the cardiac rhythm data may be analyzed. If an anomaly detection circuit **208** analyzes data received from the sensor **202** to detect anomaly of cardiac rhythm. The anomaly detection circuit **208** decides anomaly of cardiac rhythm on condition that it detects no beat in a certain period or substantial difference from the preprogrammed data. If anomaly is detected, the process moves to block **706**. If no anomaly is detected, the process moves back to block **702**. Block **706** may represent broadcasting a location information request for paramedical equipment upon detection of an anomaly. Block **708** may represent a paramedical device **120** receiving the broadcasted request from block **706**. Block **710** may represent the paramedical device **120** sending the location information for the paramedical equipment (e.g. the AED) back to the cardiac arrest monitoring device **110**. Block **712** may represent the cardiac arrest monitoring device receiving the location information of the paramedical equipment. Block **714** may represent the cardiac arrest monitoring device selecting one or more nearby paramedical equipment by calculating the distance between the cardiac arrest monitoring device **110** and each piece of paramedical equipment. Block **716** may represent communicating information regarding the location of nearby paramedical equipment, such as displaying the location on a map. Block **718** may represent generating an alarm to notify passersby of anomaly of the user, in responding to the anomaly detection circuit detecting the anomaly of the cardiac rhythm. It is, of course, understood that block **718** may occur at any point in the process after block **704** detects an anomaly.

The process **800** illustrates the operation of a cardiac arrest monitoring device, which receives the location information of the paramedical equipment from a server, which manages the location information of the paramedical equipment, and communicates the location information. Referring to FIG. **8**, block **802** may comprise monitoring a cardiac rhythm with a sensor **202**. Block **804** may represent analyzing the cardiac rhythm data. If an anomaly detection circuit **208** analyzes data received from the sensor **202** to detect anomaly of cardiac rhythm. The anomaly detection circuit **208** decides anomaly of cardiac rhythm on condition that it detects no beat in a certain period or substantial difference from the pre-programmed data. If anomaly is detected, the process moves to block **806**. If no anomaly is detected, the process moves back to block **802**. Block **806** may represent broadcasting a local information request for paramedical equipment and self-location information to a server upon detection of an anomaly. Block **808** may represent a server **130** receiving the broadcasted request from block **806**. Block **810** may represent the server selecting one or more paramedical devices based on the location information of the cardiac arrest monitoring device. Block **812** may represent the server sending the location information of paramedical equipment back to the cardiac arrest monitoring device. Block **814** may represent the cardiac arrest monitoring device receiving the location information of the paramedical equipment. Block **816** may represent communicating information regarding the location of nearby paramedical equipment, such as displaying the location on a map. Block **818** may represent generating an alarm to notify passersby of anomaly of the user, in responding to the anomaly detection circuit detecting the anomaly of the cardiac rhythm. It is, of course, understood that block **818** may occur at any point in the process after block **804** detects an anomaly.

The process **900** illustrates the operation of a paramedical device, which communicates the location information of a victim (e.g. user **115**), when the paramedical device receives the location information of a victim from the cardiac arrest monitoring device worn by the victim. Referring to FIGS. **2** and **9**, block **902** may comprise monitoring a cardiac rhythm with a sensor **202**. Block **904** may represent analyzing the cardiac rhythm data. If an anomaly detection circuit **208** analyzes data received from the sensor **202** to detect anomaly of cardiac rhythm. The anomaly detection circuit **208** decides anomaly of cardiac rhythm on condition that it detects no beat in a certain period or substantial difference from the pre-programmed data. If anomaly is detected, the process moves to block **906**. If no anomaly is detected, the process moves back to block **902**. Block **906** may represent the cardiac arrest monitoring device sending self-location information to the paramedical device upon detection of an anomaly. Block **908** may represent the paramedical device receiving the location information of the victim (i.e. the cardiac monitoring device). Block **910** may represent communicating information regarding the location of the victim, such as displaying the location on a map.

The process **1000** illustrates the operation of a mobile terminal device, which receives the location information of paramedical equipment from one or more paramedical devices to which the paramedical equipment is attached, and communicates the location information for the paramedical equipment. This device is for the use of passersby who encounter a victim of cardiac arrest. Referring to FIG. **10**, block **1002** may represent receiving a command to locate a nearby article of paramedical equipment, such as by a user who inputs a command on the mobile terminal device to locate nearby paramedical equipment. Block **1004** may rep-

resent broadcasting a local information request for paramedical equipment. Block **1006** may represent a paramedical device receiving the broadcasted request from block **1004**. Block **1008** may represent the paramedical device sending the location information of the paramedical equipment back to the mobile terminal device. As previously discussed, the location information of paramedical equipment may be stored in the memory of the paramedical device. In another embodiment, the paramedical device may include a self-location acquisition unit such as a GPS receiver to obtain its location information. Block **1010** may represent the mobile terminal device receiving the location information of the paramedical equipment. Block **1012** may represent the mobile terminal device selecting one or more nearby paramedical equipment by calculating the distance between the cardiac arrest monitoring device and each of the pieces of paramedical equipment. Block **1014** may represent communicating information regarding the location of nearby paramedical equipment, such as displaying the location on a map.

It is, of course, understood that the mobile terminal device may receive the location information of the paramedical equipment from a server, which manages the location information of the paramedical equipment, as discussed with regard to FIG. **8**.

FIG. **11** illustrates an example computer program product **1100** that is arranged in accordance with the present disclosure. Computer program product **1100** may include a signal bearing medium **1102**. Signal bearing medium **1102** may include one or more machine-readable instructions **1104**, which, if executed by one or more processors, may operatively enable a computing device to provide the functionality described above with respect to FIGS. **7-10**; in specific, analyzing cardiac rhythm, sending and/or receiving location information of system devices, and/or communication system device location information. Thus, for example, referring to FIG. **1**, cardiac arrest monitoring device **110**, paramedical device **120**, and/or server **130**, and/or mobile terminal device **140** may undertake one or more of the actions shown in FIGS. **7-10** in response to instructions **1104** conveyed by medium **1102**.

In some implementations, signal bearing medium **1102** may encompass a computer-readable medium **1106**, such as, but not limited to, a hard disk drive, a Compact Disc (CD), a Digital Versatile Disk (DVD), a digital tape, memory, etc. In some implementations, signal bearing medium **1102** may encompass a recordable medium **1108**, such as, but not limited to, memory, read/write (R/W) CDs, R/W DVDs, etc. In some implementations, signal bearing medium **1102** may encompass a communications medium **1110**, such as, but not limited to, a digital and/or an analog communication medium (e.g., a fiber optic cable, a waveguide, a wired communications link, a wireless communication link, etc.).

FIG. **12** is a block diagram illustrating an exemplary computing device **1200** that is arranged in accordance with the present disclosure. In one example configuration **1201**, computing device **1200** may include one or more processors **1210** and system memory **1220**. A memory bus **1230** can be used for communicating between the processor **1210** and the system memory **1220**.

Depending on the desired configuration, processor **1210** may be of any type including but not limited to a microprocessor (μ P), a microcontroller (μ C), a digital signal processor (DSP), or any combination thereof. Processor **1210** can include one or more levels of caching, such as a level one (L1) cache **1211** and a level two (L2) cache **1212**, a processor core **1213**, and registers **1214**. The processor core **1213** can include an arithmetic logic unit (ALU), a floating point unit

(FPU), a digital signal processing core (DSP Core), or any combination thereof. A memory controller **1215** can also be used with the processor **1210**, or in some implementations the memory controller **1215** can be an internal part of the processor **1210**.

Depending on the desired configuration, the system memory **1220** may be of any type including but not limited to volatile memory (such as RAM), non-volatile memory (such as ROM, flash memory, etc.) or any combination thereof. System memory **1220** may include an operating system **1221**, one or more applications **1222**, and program data **1224**. Application **1222** may include monitoring and location algorithms that are arranged to perform the functions and/or operations as described herein including the functional blocks and/or operations described with respect to FIGS. **7-10**. System Location Data **1224** may include information regarding the location of paramedical devices and/or cardiac arrest monitoring devices. In some example embodiments, application **1222** may be arranged to operate with program data **1224** on an operating system **1221** such that implementations of mobile sampling may be provided as described herein. This described basic configuration is illustrated in FIG. **12** by those components within dashed line **1201**.

Computing device **1200** may have additional features or functionality, and additional interfaces to facilitate communications between the basic configuration **1201** and any required devices and interfaces. For example, a bus/interface controller **1240** may be used to facilitate communications between the basic configuration **1201** and one or more data storage devices **1250** via a storage interface bus **1241**. The data storage devices **1250** may be removable storage devices **1251**, non-removable storage devices **1252**, or a combination thereof. Examples of removable storage and non-removable storage devices include magnetic disk devices such as flexible disk drives and hard-disk drives (HDD), optical disk drives such as compact disk (CD) drives or digital versatile disk (DVD) drives, solid state drives (SSD), and tape drives to name a few. Example computer storage media may include volatile and nonvolatile, removable and non-removable media implemented in any method or technology for storage of information, such as computer readable instructions, data structures, program modules, or other data.

System memory **1220**, removable storage **1251** and non-removable storage **1252** are all examples of computer storage media. Computer storage media includes, but is not limited to, RAM, ROM, EEPROM, flash memory or other memory technology, CD-ROM, digital versatile disks (DVD) or other optical storage, magnetic cassettes, magnetic tape, magnetic disk storage or other magnetic storage devices, or any other medium which may be used to store the desired information and which may be accessed by computing device **1200**. Any such computer storage media may be part of device **1200**.

Computing device **1200** may also include an interface bus **1242** for facilitating communication from various interface devices (e.g., output interfaces, peripheral interfaces, and communication interfaces) to the basic configuration **1201** via the bus/interface controller **1240**. Example output interfaces **1260** may include a graphics processing unit **1261** and an audio processing unit **1262**, which may be configured to communicate to various external devices such as a display or speakers via one or more A/V ports **1263**. Example peripheral interfaces **1260** may include a serial interface controller **1271** and/or a parallel interface controller **1272**, which may be configured to communicate with external devices such as input devices (e.g., keyboard, mouse, pen, voice input device, touch input device, etc.) or other peripheral devices (e.g., printer, scanner, etc.) via one or more I/O ports **1273**. An

example communication interface **1280** includes a network controller **1281**, which may be arranged to facilitate communications with one or more other computing devices **1290** over a network communication via one or more communication ports **1282**. A communication connection is one example of a communication media. Communication media may typically be embodied by computer readable instructions, data structures, program modules, or other data in a modulated data signal, such as a carrier wave or other transport mechanism, and may include any information delivery media. A “modulated data signal” may be a signal that has one or more of its characteristics set or changed in such a manner as to encode information in the signal. By way of example, and not limitation, communication media may include wired media such as a wired network or direct-wired connection, and wireless media such as acoustic, radio frequency (RF), infrared (IR) and other wireless media. The term computer readable media as used herein may include both storage media and communication media.

Computing device **1200** may be implemented as a portion of a small-form factor portable (or mobile) electronic device such as a cell phone, a personal data assistant (PDA), a personal media player device, a wireless web-watch device, a personal headset device, an application specific device, or a hybrid device that includes any of the above functions. Computing device **500** may also be implemented as a personal computer including both laptop computer and non-laptop computer configurations. In addition, computing device **500** may be implemented as part of a wireless base station or other wireless system or device.

Some portions of the foregoing detailed description are presented in terms of algorithms or symbolic representations of operations on data bits or binary digital signals stored within a computing system memory, such as a computer memory. These algorithmic descriptions or representations are examples of techniques used by those of ordinary skill in the data processing arts to convey the substance of their work to others skilled in the art. An algorithm is here, and generally, is considered to be a self-consistent sequence of operations or similar processing leading to a desired result. In this context, operations or processing involve physical manipulation of physical quantities. Typically, although not necessarily, such quantities may take the form of electrical or magnetic signals capable of being stored, transferred, combined, compared or otherwise manipulated. It has proven convenient at times, principally for reasons of common usage, to refer to such signals as bits, data, values, elements, symbols, characters, terms, numbers, numerals or the like. It should be understood, however, that all of these and similar terms are to be associated with appropriate physical quantities and are merely convenient labels. Unless specifically stated otherwise, as apparent from the following discussion, it is appreciated that throughout this specification discussions utilizing terms such as “processing,” “computing,” “calculating,” “determining” or the like refer to actions or processes of a computing device, that manipulates or transforms data represented as physical electronic or magnetic quantities within memories, registers, or other information storage devices, transmission devices, or display devices of the computing device.

The foregoing detailed description has set forth various embodiments of the devices and/or processes via the use of block diagrams, flowcharts, and/or examples. Insofar as such block diagrams, flowcharts, and/or examples contain one or more functions and/or operations, it will be understood by those within the art that each function and/or operation within such block diagrams, flowcharts, or examples can be implemented, individually and/or collectively, by a wide range of

hardware, software, firmware, or virtually any combination thereof. In one embodiment, several portions of the subject matter described herein may be implemented via Application Specific Integrated Circuits (ASICs), Field Programmable Gate Arrays (FPGAs), digital signal processors (DSPs), or other integrated formats. However, those skilled in the art will recognize that some aspects of the embodiments disclosed herein, in whole or in part, can be equivalently implemented in integrated circuits, as one or more computer programs running on one or more computers (e.g., as one or more programs running on one or more computer systems), as one or more programs running on one or more processors (e.g., as one or more programs running on one or more microprocessors), as firmware, or as virtually any combination thereof, and that designing the circuitry and/or writing the code for the software and/or firmware would be well within the skill of one of skill in the art in light of this disclosure. In addition, those skilled in the art will appreciate that the mechanisms of the subject matter described herein are capable of being distributed as a program product in a variety of forms, and that an illustrative embodiment of the subject matter described herein applies regardless of the particular type of signal bearing medium used to actually carry out the distribution. Examples of a signal bearing medium include, but are not limited to, the following: a recordable type medium such as a flexible disk, a hard disk drive (HDD), a Compact Disc (CD), a Digital Versatile Disk (DVD), a digital tape, a computer memory, etc.; and a transmission type medium such as a digital and/or an analog communication medium (e.g., a fiber optic cable, a waveguide, a wired communications link, a wireless communication link, etc.).

References made in this disclosure to the term “responsive to” or “in response to” are not limited to responsiveness to only a particular feature and/or structure. A feature may also be responsive to another feature and/or structure and also be located within that feature and/or structure. Moreover, when terms or phrases such as “coupled” or “responsive” or “in response to” or “in communication with”, etc. are used herein or in the claims that follow, these terms should be interpreted broadly. For example, the phrase “coupled to” may refer to being communicatively, electrically and/or operatively coupled as appropriate for the context in which the phrase is used.

Those skilled in the art will recognize that it is common within the art to describe devices and/or processes in the fashion set forth herein, and thereafter use engineering practices to integrate such described devices and/or processes into data processing systems. That is, at least a portion of the devices and/or processes described herein can be integrated into a data processing system via a reasonable amount of experimentation. Those having skill in the art will recognize that a typical data processing system generally includes one or more of a system unit housing, a video display device, a memory such as volatile and non-volatile memory, processors such as microprocessors and digital signal processors, computational entities such as operating systems, drivers, graphical user interfaces, and applications programs, one or more interaction devices, such as a touch pad or screen, and/or control systems including feedback loops and control motors (e.g., feedback for sensing position and/or velocity; control motors for moving and/or adjusting components and/or quantities). A typical data processing system may be implemented utilizing any suitable commercially available components, such as those typically found in data computing/communication and/or network computing/communication systems.

The herein described subject matter sometimes illustrates different components contained within, or connected with, different other components. It is to be understood that such depicted architectures are merely exemplary, and that in fact many other architectures can be implemented which achieve the same functionality. In a conceptual sense, any arrangement of components to achieve the same functionality is effectively “associated” such that the desired functionality is achieved. Hence, any two components herein combined to achieve a particular functionality can be seen as “associated with” each other such that the desired functionality is achieved, irrespective of architectures or intermedial components. Likewise, any two components so associated can also be viewed as being “operably connected”, or “operably coupled”, to each other to achieve the desired functionality, and any two components capable of being so associated can also be viewed as being “operably coupleable”, to each other to achieve the desired functionality. Specific examples of operably coupleable include but are not limited to physically mateable and/or physically interacting components and/or wirelessly interactable and/or wirelessly interacting components and/or logically interacting and/or logically interactable components.

With respect to the use of substantially any plural and/or singular terms herein, those having skill in the art can translate from the plural to the singular and/or from the singular to the plural as is appropriate to the context and/or application. The various singular/plural permutations may be expressly set forth herein for sake of clarity.

It will be understood by those within the art that, in general, terms used herein, and especially in the appended claims (e.g., bodies of the appended claims) are generally intended as “open” terms (e.g., the term “including” should be interpreted as “including but not limited to,” the term “having” should be interpreted as “having at least,” the term “includes” should be interpreted as “includes but is not limited to,” etc.). It will be further understood by those within the art that if a specific number of an introduced claim recitation is intended, such an intent will be explicitly recited in the claim, and in the absence of such recitation no such intent is present. For example, as an aid to understanding, the following appended claims may contain usage of the introductory phrases “at least one” and “one or more” to introduce claim recitations. However, the use of such phrases should not be construed to imply that the introduction of a claim recitation by the indefinite articles “a” or “an” limits any particular claim containing such introduced claim recitation to inventions containing only one such recitation, even when the same claim includes the introductory phrases “one or more” or “at least one” and indefinite articles such as “a” or “an” (e.g., “a” and/or “an” should typically be interpreted to mean “at least one” or “one or more”); the same holds true for the use of definite articles used to introduce claim recitations. In addition, even if a specific number of an introduced claim recitation is explicitly recited, those skilled in the art will recognize that such recitation should typically be interpreted to mean at least the recited number (e.g., the bare recitation of “two recitations,” without other modifiers, typically means at least two recitations, or two or more recitations). Furthermore, in those instances where a convention analogous to “at least one of A, B, and C, etc.” is used, in general such a construction is intended in the sense one having skill in the art would understand the convention (e.g., “a system having at least one of A, B, and C” would include but not be limited to systems that have A alone, B alone, C alone, A and B together, A and C together, B and C together, and/or A, B, and C together, etc.). In those instances where a convention analogous to “at least

one of A, B, or C, etc.” is used, in general such a construction is intended in the sense one having skill in the art would understand the convention (e.g., “a system having at least one of A, B, or C” would include but not be limited to systems that have A alone, B alone, C alone, A and B together, A and C together, B and C together, and/or A, B, and C together, etc.). It will be further understood by those within the art that virtually any disjunctive word and/or phrase presenting two or more alternative terms, whether in the description, claims, or drawings, should be understood to contemplate the possibilities of including one of the terms, either of the terms, or both terms. For example, the phrase “A or B” will be understood to include the possibilities of “A” or “B” or “A and B.”

It should also be understood that, the term “optimize” may include maximization and/or minimization. The term “minimization” and/or the like as used herein may include a global minimum, a local minimum, an approximate global minimum, and/or an approximate local minimum. Likewise, it should also be understood that, the term “maximization” and/or the like as used herein may include an global maximum, a local maximum, an approximate global maximum, and/or an approximate local maximum.

Reference in the specification to “an implementation,” “one implementation,” “some implementations,” or “other implementations” may mean that a particular feature, structure, or characteristic described in connection with one or more implementations may be included in at least some implementations, but not necessarily in all implementations. The various appearances of “an implementation,” “one implementation,” or “some implementations” in the preceding description are not necessarily all referring to the same implementations.

While certain exemplary techniques have been described and shown herein using various methods and systems, it should be understood by those skilled in the art that various other modifications may be made, and equivalents may be substituted, without departing from claimed subject matter. Additionally, many modifications may be made to adapt a particular situation to the teachings of claimed subject matter without departing from the central concept described herein. Therefore, it is intended that claimed subject matter not be limited to the particular examples disclosed, but that such claimed subject matter also may include all implementations falling within the scope of the appended claims, and equivalents thereof.

What is claimed:

1. A paramedical device connected to paramedical equipment, comprising;
 - a location module for providing location information of the paramedical equipment to a cardiac monitoring device;

- an anomaly detection circuit operable to detect an anomaly of cardiac rhythm of a victim that includes a comparison circuit that determines the anomaly of the cardiac rhythm from a comparison of the cardiac rhythm to preprogrammed data that includes a previous cardiac rhythm data of the victim, average populous data, and average data of a specific demographic; and
 - an output unit for outputting information of a location of the victim and the location of the paramedical equipment on a video display, wherein the location of the victim and the location of the paramedical equipment are displayed on a map on the video display.
2. The paramedical device as recited in claim 1, further comprising an alarm unit for generating an alarm.
3. A method for monitoring a cardiac arrest, comprising:
 - monitoring a cardiac rhythm;
 - detecting an anomaly based on the monitored cardiac rhythm;
 - comparing the cardiac rhythm to preprogrammed data that includes a previous cardiac rhythm data of a user, average populous data, and average data of a specific demographic;
 - identifying a location of paramedical equipment upon detection of the anomaly; and
 - displaying the location of the paramedical equipment on a map through a video display or monitor.
4. The method as recited in claim 3, wherein identifying the location of the paramedical equipment comprises transmitting a request for location information of the paramedical equipment.
5. The method as recited in claim 3, wherein identifying the location of the paramedical equipment comprises receiving location information from the paramedical equipment.
6. The method as recited in claim 3, wherein identifying the location of the paramedical equipment comprises receiving location information from a server.
7. The method as recited in claim 3, further comprising generating an alarm in response to detecting the anomaly.
8. An article comprising:
 - a signal bearing medium comprising machine-readable instructions stored thereon, which, if executed by one or more processors, operatively enable a computing device to analyze cardiac rhythm, compare the cardiac rhythm to preprogrammed data including a previous cardiac rhythm data of a user, average populous data, and average data of a specific demographic, send and/or receive location information of system devices, determine distances between system devices, communicate system device location information, and display the location information on a map using a video display or monitor.

* * * * *

UNITED STATES PATENT AND TRADEMARK OFFICE
CERTIFICATE OF CORRECTION

PATENT NO. : 8,923,960 B2
APPLICATION NO. : 13/682669
DATED : December 30, 2014
INVENTOR(S) : Goto

Page 1 of 2

It is certified that error appears in the above-identified patent and that said Letters Patent is hereby corrected as shown below:

In the Drawings

In Fig. 11, Sheet 10 of 11, in Box "1010", in Line 1, delete "1010 - A communication" and insert -- 1110 - A communications --, therefor. (See Attached)

In Fig. 12, Sheet 11 of 11, delete "uP/uC/DSP" and insert -- μ P/ μ C/DSP --, therefor.

In the Specification

In Column 1, Line 6, delete "divisional" and insert -- divisional filing under 35 U.S.C. §121 --, therefor.

In Column 9, Line 16, delete "Data 1224" and insert -- Data 1225 --, therefor.

In Column 9, Line 62, delete "interfaces 1260" and insert -- interfaces 1270 --, therefor.

In Column 11, Line 16, delete "and or" and insert -- and/or --, therefor.

In Column 13, Line 20, delete "an global" and insert -- a global --, therefor.

In the Claims

In Column 13, Line 49, in Claim 1, delete "comprising;" and insert -- comprising: --, therefor.

Signed and Sealed this
Eighth Day of September, 2015



Michelle K. Lee
Director of the United States Patent and Trademark Office




FIG. 11

专利名称(译)	心脏骤停监测装置		
公开(公告)号	US8923960	公开(公告)日	2014-12-30
申请号	US13/682669	申请日	2012-11-20
[标]申请(专利权)人(译)	英派尔科技开发有限公司		
当前申请(专利权)人(译)	EMPIRE科技发展有限责任公司		
[标]发明人	GOTO HIROSHI		
发明人	GOTO, HIROSHI		
IPC分类号	A61B5/00 A61B5/04 G06F19/00 A61N1/39 G08B21/02 A61B5/0402 A61B5/11		
CPC分类号	A61B5/0402 A61N1/3925 G06F19/3418 A61B5/1112 A61B5/0006 A61N1/3993 G08B21/02 G16H40/67		
其他公开文献	US20130076508A1		
外部链接	Espacenet USPTO		

摘要(译)

本公开涉及用于健康监测的设备，实现和技术。本公开的实施例涉及心脏骤停监测装置。

