



US 20020087053A1

(19) **United States**(12) **Patent Application Publication****Stoycos et al.**(10) **Pub. No.: US 2002/0087053 A1**(43) **Pub. Date: Jul. 4, 2002**

(54) **DISTRIBUTED REAL TIME
REPLICATION-BASED ANNOTATION AND
DOCUMENTATION SYSTEM FOR
CARDIOLOGY PROCEDURES**

(52) **U.S. Cl. 600/300**(57) **ABSTRACT**


(76) Inventors: **Stephen T. Stoycos**, Sugarland, TX
(US); **Ewin Michael Kiser**, Katy, TX
(US)

Correspondence Address:

Patrick S. Yoder
Fletcher, Yoder & Van Someren
P.O. Box 692289
Houston, TX 77269-2289 (US)

(21) Appl. No.: **09/752,159**(22) Filed: **Dec. 29, 2000****Publication Classification**(51) **Int. Cl.⁷ A61B 5/00**

A distributed multi-user system for real time data access during cardiology procedures. The system includes an interactive computer network which can be used to simultaneously display and manipulate data from a cardiology procedure on a plurality of devices and at a plurality of locations. The system is implemented through various replication topologies which allow the simultaneous access and annotation of a cardiology study during the procedure. The study can be displayed and annotated at any of the plurality of locations, which may be local or remote, during the procedure. Annotations made at one of the plurality of locations will be distributed to the other locations through a publisher.







FIG. 1

FIG. 2






FIG. 3




FIG. 4




FIG. 5

DISTRIBUTED REAL TIME REPLICATION-BASED ANNOTATION AND DOCUMENTATION SYSTEM FOR CARDIOLOGY PROCEDURES

BACKGROUND OF THE INVENTION

[0001] 1. Field of the Invention

[0002] The present invention relates generally to a distributed multi-user system for real time data access during cardiology procedures and, more particularly, to an interactive computer network which can be used to simultaneously display and annotate data from a cardiology procedure on a plurality of devices and at a plurality of locations during a cardiology procedure.

[0003] 2. Background of the Related Art

[0004] State of the art test and treatment facilities are essential to providing accurate monitoring, diagnoses, and treatment of heart disease. Medical facilities are often equipped to monitor and diagnose both mechanical and electrical defects in the heart. The present system relates to the monitoring of the heart's electrical activity.

[0005] The heart is a muscle and, like other muscles, it contracts when it is electrically stimulated. Unlike other muscles, however, the heart has its own electrical system which can generate electrical impulses to stimulate the contraction of the muscle and thus keep the heart beating in rhythmic sequence so blood is continually pumped throughout the body.

[0006] An electrophysiology study (EPS) is an invasive test involving the monitoring of the electrical signals in the heart. When defects in the heart tissue interfere with the normal formation or conduction of the heart's electrical activity, abnormal heart rhythms, known as cardiac arrhythmias, may develop. Cardiac arrhythmias may be caused by congenital defects, tissue damage due to heart attacks, or diseases such as arteriosclerosis (the deposition of fatty substances in the inner layer of the arteries) for instance, which accelerate, delay, or redirect the transmission of electrical activity, thereby disrupting the normal rhythmic contractions of the chambers of the heart. The electrophysiology study is used to assist in evaluating cardiac arrhythmias.

[0007] The basic electrophysiology procedure involves the recording and pacing of electrical signals within localized areas of the heart. During this study, catheters are placed near critical areas of the heart to record the heart's electrical signals. The heart is paced in various ways to study the speed and location of the flow of electricity within the heart. Typically, the study is used to determine if the heart has a tendency to pump faster or slower than normal and if the rhythm is dangerously irregular and thus requires treatment. Therapies for various rhythm disorders include medication, catheter ablation of the pathway, pacemakers, and defibrillators.

[0008] Tachycardia is an arrhythmia characterized by an abnormally fast heart rate (more than one-hundred beats per minute). Tachycardia falls into two categories, ventricular tachycardia (VT) and supra-ventricular tachycardia (SVT). VT is tachycardia that originates in the ventricles of the heart. SVT originates in the atria or at the junction between the atria and the ventricles of the heart. VT is a potentially

life-threatening condition caused by either abnormally rapid impulse formation or by slow ventricular conduction which interferes with the heart's normal electrical activity and causes abnormally frequent contractions in the ventricles. Rapid ventricular contractions often result in significantly reduced cardiac output due to the inefficient pumping of the blood from the heart. As a result, the body receives an inadequate supply of oxygen which may cause dizziness, unconsciousness, cardiac arrest, or death.

[0009] Patients suspected of suffering from VT are initially screened by a cardiologist (doctor specializing in the heart) by means of external cardiac monitoring, typically in the form of an electrocardiogram. An electrocardiogram captures electrical activity from surface leads placed on the patient's chest for twenty-four hours. When further testing is warranted, the patient is referred to a cardiac electrophysiologist (cardiologist who specializes in the electrical functioning of the heart) for an EPS.

[0010] An EPS evaluates the electrical integrity of the heart by stimulating multiple intra-cardiac sites and recording the electrical response. During an EPS, a patient's clinical tachycardia is induced in a controlled setting to diagnose the tachycardia and select an appropriate treatment or combination of treatments. EP studies using currently available technology are often lengthy and tedious procedures which include probing the interior of two or more chambers of the heart with single point contact catheters which may cause significant discomfort for the patient. However, single point contact catheters have limited utility in diagnosing complex tachycardia. The limited data produced in point by point mapping often fails to provide the electrophysiologist with sufficient diagnostic power for a complete understanding of the tachycardia.

[0011] One form of treatment of VT and SVT type arrhythmias which is becoming increasingly popular is catheter ablation. During the ablation (or "elimination") procedure which is similar to the procedure used in the EPS, a special catheter is inserted into the patient to deliver energy, such as radio frequency (RF) energy, to the precise areas of the heart which have been identified to cause the abnormal heartbeat. The tip of the catheter is heated to facilitate the destruction of the surrounding tissue thereby correcting the anomalous circuit within the heart which is causing the abnormal electrical activity. Catheter ablation is a potentially curative treatment which is continually being developed.

[0012] To perform procedures such as the EPS or catheter ablation, a cardiac catheterization lab is provided in which multiple clinicians can diagnose and treat heart conditions. It is desirable to provide the clinicians with a means to interact with, manipulate, and document observations on the clinical data in a study record. It would be advantageous for clinicians to be able to interact with the clinical data and document observations simultaneously during an EP procedure. Such clinicians may include a primary physician, nurse, anesthesiologist, cardiovascular technician, radiology technician, consulting physician, and so forth. For example, it may be necessary for the primary physician or cardiovascular technician to make measurements on intracardiac, hemodynamic, or imaging data, while the nurse or anesthesiologist documents the status of the patient for a report or a consulting physician makes measurements at a remote

location on a network system. It would be advantageous for several clinicians to be able to simultaneously view the data during the EP procedure and to be able to annotate and document the reports as necessary. The annotations should be available to all clinicians presently viewing a particular study. Current techniques to accommodate the complex workflow in a cardiac catheterization lab are insufficient to meet these needs.

[0013] One current technique used in a cardiac catheterization lab employs disparate systems which provide copies of studies which may be separately annotated and later integrated. Different clinicians document their clinical observations into different systems which are later integrated into an overall clinical information system. This approach has several disadvantages. First, clinicians do not have the advantage of seeing the dynamic relationship among data entered by other clinicians during the study which especially limits the potential contribution of a consulting physician who may be stationed at a remote facility. Second, the detail and context of the clinical data may be diluted during the integration. Third, report generation is often delayed while the integration process is performed, which often takes several days to complete. Fourth, having multiple systems creates more costs and requires more training for clinical personnel. Further, additional time and effort by clinicians is required to perform the integration process.

[0014] A second method which may be currently employed in a cardiac catheterization lab is toggling control of data entry among terminals using a keyboard switch. Multiple terminals in a single lab may have a keyboard, mouse, and monitor coupled to a single computer with a commonly available keyboard switch. To enter data at one terminal, a clinician executes a keystroke to gain control of the computer and enters the desired records to be annotated. Disadvantageously, only one clinician can take control of a record at a given time. Thus, if a nurse is documenting a medication, but a cardiovascular technician is tasked with changing the display for the physician, the technician must wait for the nurse to complete her documentation so that the technician can take control of the record. Further, interaction with clinical data is limited to terminals physically located within the proximity of the keyboard switches which generally means terminals located within the procedure room of the lab. This effectively eliminates the interaction with a consulting physician at a remote facility. Currently, the simultaneous viewing and annotation of an EPS is not possible since the review and annotation is a static process which only provides for a study to exist in one place at a time.

[0015] The present technique may address one or more of the problems set forth above.

SUMMARY OF THE INVENTION

[0016] The present technique provides a distributed multi-user system for real time data access and annotation during cardiology procedures. The system includes an interactive computer network which can be used to simultaneously display and annotate data from a cardiology procedure on a plurality of devices and at a plurality of locations. The system is implemented through various replication topologies which allow the simultaneous access and annotation of a cardiology study during the procedure. The study can be

displayed and annotated at any of the plurality of locations, which may be local or remote, during the procedure. Annotations made at one of the plurality of locations will be distributed to the other locations through a publisher.

BRIEF DESCRIPTION OF THE DRAWINGS

[0017] **FIG. 1** is a block diagram of an exemplary system including a cardiac catheterization lab and local and remote client workstations;

[0018] **FIG. 2** is a block diagram illustrating an exemplary implementation of the present technique;

[0019] **FIG. 3** is a block diagram illustrating a more detailed embodiment of an exemplary implementation of the present technique;

[0020] **FIG. 4** is a block diagram illustrating an archival scheme for permanently storing study data in accordance with the present technique; and

[0021] **FIG. 5** is a block diagram illustrating a messaging technique in accordance with the present technique.

DETAILED DESCRIPTION OF THE INVENTION

[0022] As previously discussed, a cardiac catheterization lab may be used by multiple clinicians to perform procedures such as an EPS or catheter ablation. **FIG. 1** illustrates one embodiment of a catheterization lab **10**. The catheterization lab **10** generally includes a procedure room **12** and a control room **14**. The procedure room **12** is generally the room in which the physical catheterization procedure takes place. The control room **14** is generally the room in which the control of the data gathering and display takes place. The procedure room **12** may include a bed **16** in which a patient **18** is placed during a cardiac catheterization procedure such as an EPS procedure or catheter ablation. An intravenous (IV) line **20** may be placed in the arm of the patient **18** to provide a means of dispensing medication during the procedure. Catheters **22** may be inserted through the femoral vein in the groin of the patient **18**. An x-ray imaging system (not shown) may be used to guide the catheter **22** into the appropriate region of the patient's heart. The patient **18** is also connected to an acquisition workstation **24** which includes display monitors to provide data such as signal or imaging data during the procedure and a means of annotating the data, such as a keyboard. Further, the lab **10** may also include one or more workstations **25** and **26** with display monitors to provide additional support during a procedure, as discussed below.

[0023] The catheterization lab **10** may also include a glass partition **27**, such as lead glass which separates the procedure room **12** from the control room **14**. The control room **14** also includes a workstation **28** with display monitors which may be similar to the display monitors contained in the procedure room **12**.

[0024] A team of clinicians generally conducts an EPS procedure. The team may include a doctor **30** to perform the procedure, a nurse **31** to maintain the patient's vital signs, a scrub nurse **32** to assist the doctor **30** with the procedure, a monitoring technician **33** who is responsible for providing the doctor **30** with the information and data that the doctor **30** needs to see during the procedure and other clinicians **34**

and **35** who assist in monitoring and/or annotation of a particular procedure, for example. The monitoring technician **33** is generally stationed in the control room **14**. The monitoring technician **33** is in communication with the doctor **30** during the EPS procedure through an intercom system, for example, and provides information in response to requests from the doctor **30** while the procedure is being conducted.

[0025] During the procedure, the doctor **30** stimulates the patient's heart with small electrical signals delivered through the catheter **22** to make the heart beat at various rates. The electrical signals are delivered from a stimulator **38** which may be a separate device from the acquisition workstation **24**. Because the monitoring technician **33** responds to requests from the doctor **30** to control the data viewed on the display monitors associated with the acquisition workstation **24** in the procedure room **12**, the display monitors associated with the workstation **28** in the control room **14** preferably display identical information. Likewise, other display monitors, such as those associated with workstations **25** and **26**, preferably display the information gathered during the procedure. Further, workstations including display monitors may advantageously be installed in other areas within the same facility but outside the catheterization lab **10**, such as a local diagnosis area **40**. The local diagnosis area **40** may include a workstation **42** with display monitors from which to view a study during or after a procedure.

[0026] Similarly, a facility **44** which may be located remotely with respect to the lab **10**, may include a workstation **46** with display monitors to be used by a remote specialist **48**. The remote specialist **48** may participate during the procedure to provide critical insight into the study which may not be available through the clinicians available locally. For instance, a remote specialist **48** whose office facility is equipped with display monitors associated with workstation **46**, can observe a procedure being performed in the catheterization lab **10** without being present during the procedure. As the remote specialist **48** observes the study, he can advise the local clinicians in real time while the procedure is being performed.

[0027] To optimize the treatment of the patient **18**, it may be desirable to provide each set of display monitors associated with workstations **24**, **25**, **26**, **28**, **42** and **46** with identical information simultaneously during the procedure. Further, it may be desirable to provide annotation capabilities at the various display monitors to annotate the data during the procedure. In one embodiment of the present technique, a plurality of local areas and remote areas will advantageously include display monitors which will allow annotation and real-time updating of the data in response to the annotation and in response to changes implemented during the procedure. The technique employed by the present embodiment is a dynamic technique which provides interactive reviewing of the EPS during the procedure. While a prior technique allowed only end of study transfers, the present technique provides for the transfer of information during the EPS study.

[0028] A general block diagram of the present scheme is indicated in **FIG. 2**. For simplicity new reference numerals are used to describe **FIG. 2**. However, it should be evident that some of the elements in **FIG. 2** were previously described in **FIG. 1** using different reference numerals. A

more detailed description of specific embodiments of the present scheme are described herein with reference to **FIGS. 35**.

[0029] Referring initially to **FIG. 2**, a cardiac catheterization lab comprising a procedure room **50** and a control room **52** is generally illustrated by block **54**. As previously discussed, the lab **54** facilitates the acquisition of data received during an EPS procedure. An acquisition database **56** and a controller **58** may reside in the control room **52** to store data taken during a procedure. The data is initially taken from a patient (not shown in **FIG. 2**) in the procedure room **50** and delivered to the control room **52** via a dedicated connection, for instance, to be stored in the acquisition database **56**.

[0030] In one implementation of the present technique, the controller **58** in the control room **52** serves as the "publisher" to a "local client" **60**. A "local client" refers to any user workstation located proximate to the control room **52**, such as those workstations within the procedure room **50** or within a hospital in which the lab **54** is housed. The "publisher" is responsible for the real-time processing of the data. Local clients, such as local client **60**, can access the acquisition database **56** directly from a user workstation **62** during the EPS procedure without going through a client server. In this topology, the local client **60** is coupled to the lab **40** via a local area network, for example. The local client **60** can communicate directly with the controller **58**, and can exchange data with the acquisition database **56**. The controller **58** will "publish" the EPS data to the requesting workstation **62**.

[0031] Annotation to the study made by clinicians are transmitted to the acquisition database **56** for storage and use by other local clients positioned at similar workstations residing locally with respect to the cardiac catheterization lab **54**. Each time a local client **60** annotates a study, the annotated data is sent back to the publisher (here controller **58**). The publisher stores the annotated study in the acquisition database **56** and notifies other local clients that are currently viewing a study that the study has been annotated. This notification may take place through a messaging system such as the messaging system described with reference to **FIG. 5**. The controller **58** replicates the study and distributes it to the local clients in real-time. This facilitates the real-time processing of the annotation and provides a means of displaying updates during an EPS procedure for local clients, such as local client **60**. As compared to previous techniques, the real-time annotation also preserves information, comments, concerns, and the like, which may be formulated during the procedure and which are often difficult to reconstruct or associate with examination data after the fact.

[0032] As discussed above, to facilitate the updating of studies to include annotations made by various clinicians viewing a study at various workstations, the publisher, controller **58** manages the updates and the dataflow. Each time a study is changed, the information is fed to the acquisition database **56**. The data is then replicated and sent to all other subscribers who are currently viewing the present study. One typical mechanism for implementing this and other topologies is by implementing a merge replication architecture.

[0033] Merge replication can be viewed as a mechanism for implementing the present embodiments. Prior techniques

of decentralizing study data by publishing from a central location, such as a server, to multiple locations residing within the cardiac catheterization labs or throughout a medical institution only provide for the instances when all data is entered at the central sites. Conversely, the present technique of using merge replication allows the system to utilize the present topology in a modified way. In this topology, a subscriber can process a transaction and have it propagated to the publisher. This replication topology functions significantly different from prior systems. As can be appreciated by one skilled in the art, merge replication is the most robust and manageable replication topology used in the industry. The replication procedure can be implemented using commercially available software, such as applications available commercially from Microsoft Corporation of Redmond, Washington or Oracle Corporation of Redwood City, Calif., for example.

[0034] Advantageously, by serving as the publisher for local clients, the controller 58 ensures that failure in the server operation will not disable the use of the study for local clients. Regardless of whether a server which may be associated with the acquisition database 56 is functioning, local clients will be able to access the acquisition database 56 and will be able to view and annotate any EPS being conducted.

[0035] However, in certain instances, it may be desirable to have local clients receive study data through a server. A second topology generally includes a segment server 66 and a segment server database 68, as illustrated in FIG. 2. The segment server 66 may be responsible for coordinating and universally updating changes made during an EPS procedure regardless of where the updates are being delivered. Each time a change to an EPS is made, the data is sent from the controller 58 to the segment server 66 and stored in the segment server database 68. The segment server 66 delivers a message to all clients currently subscribing to the system indicating that a change to the study has been made and that the data should be refreshed. This process may actually be invisible to a user and the client system may automatically update the study when the segment server 66 indicates that changes have been made. Each local client 60 having a user workstation 62 and any remote client 70 having a user workstation 70 that has the current EPS open receives the updated information from the segment server 66. This procedure is accomplished by replicating the segment server database 68 upon synchronization of the clinical data from the control room 52.

[0036] In this topology, the "publisher" is the controller 58 generally residing in the control room 52. The "subscriber" is generally the segment server 66 and the segment server database 68. It should be understood however that the subscriber may also perform as a publisher if the data in the EPS study is edited and a client, such as a local client 60 or a remote client 72, is working through the segment server 66. For example, certain parameters may be entered at a nurse's station. This data advantageously flows back, in real-time, to all other local clients 60 and remote clients 72 viewing that particular study. The segment server 66, thus, subscribes to the updates from the controller 58 and then publishes the updated study to the local and remote clients 60 and 72. Thus, in this topology, the data is transmitted from the control room 52 to a segment server 66. The segment server 66 ultimately serves as the central publisher.

The acquisition database 56 as well as subscriber workstations (located at facilities of the local and remote clients 60 and 72) replicate their data to a single segment server 66 which distributes the updated data to any subscribers viewing the current EPS procedure.

[0037] It may be advantageous to provide a central server 74, including a central server database 76, coupled to the segment server 66. As the number of clients and cardiac catheterization labs which provide data to the segment server 66 increases, it may be advantageous to periodically transfer data from the segment server database 68 to a central server database 76 for permanent storage.

[0038] Generally, FIG. 3 illustrates a more detailed embodiment of one implementation of the present scheme, depicting the simultaneous acquisition of study data in two catheterization labs. Up to this point and to simplify the general description, references to study data have been presented as a unified set of information which may be viewed and annotated. However, it may be advantageous to divide the study data into different types of data. In a present implementation, study data may be comprised of two data types: waveform data and file data. The advantages of separating data types will become evident in the description of FIG. 3, below.

[0039] Specifically, FIG. 3 illustrates two acquisition workstations 80 and 82. The acquisition workstations 80 and 82 may be located in the same catheterization lab or in two different catheterization labs. The acquisition workstations 80 and 82 are used to acquire and store study data taken during an EPS. The acquisition workstation 80 collects both types of study data, waveform data 86 and file data 88. The waveform data 86 comprises the graphical illustrations and information taken during the study. The file data 88 comprises the text accompanying the waveform data 86, as well as any annotations made by clinicians or clients. The file data 88 is stored in an acquisition database 90, which may be included in an acquisition storage unit 92, such as a hard drive. The waveform data 86 is stored in the acquisition storage unit 92. For each set of file data 88, a pointer is maintained in the acquisition database 90 to provide the corresponding waveform file path. The catalog 94 in the acquisition workstation 80 is a file that lists the studies located on that particular acquisition workstation 80.

[0040] Similarly, the acquisition workstation 82 collects both waveform data 98 and file data 100. The file data 100 is stored in an acquisition database 102, which may be included in an acquisition storage unit 104. The waveform data 98 is stored in the acquisition storage unit 104. For each set of file data 100, a pointer is maintained in the acquisition database 102 to provide the corresponding waveform file path. The catalog 106 in the acquisition workstation 82 is a file that lists the studies located in the acquisition workstation 82.

[0041] Each acquisition workstation 80 and 82 is coupled to a segment server 108. The segment server 108 includes a segment server storage unit 110 which may comprise a segment server database 112. Aside from storing waveform data 86 and 98 in their respective acquisition storage units (92 and 104), the acquisition workstation 80 and 82 stores the waveform data 86 and 98 in the segment server storage unit 110. The waveform data 86 and 98 is written to the segment server 108 via a low priority background thread. If

the connection between the segment server **108** and one of the acquisition workstations **80** and **82** is interrupted, the acquisition workstations **80** and **82** are not compromised. Finally, the segment server catalog **114** is a file that lists the studies on all acquisition workstations which are attached to the segment server **108** (here acquisition workstations **80** and **82**) and identifies on which workstation each study resides. The segment server catalog **114** is updated by replication of selected database information from each acquisition database (**90** and **102**).

[0042] A client, such as local client **116**, may wish to view the study record which is currently being produced by the workstation **84**. While the present embodiment describes the client as a local client **116**, the client may also be located remotely with respect to the catheterization lab. The local client **116** has a workstation **118** and a client storage unit **119**, including a local client database **120**. The local client **116** may concurrently review and edit study data by selecting a particular study from the replicated copy of the segment server catalog **114** which may be accessed from the local client **116**. The segment server catalog **114** lists all of the studies from any of the acquisition stations which are linked to the segment server **108**. A non-annotatable copy of the segment server catalog **114** which is accessed by the local workstation **116** is generally illustrated by reference numeral **114a**. The application stored on the client workstation **118** is then redirected by the file path stored in the segment server catalog **114** to the acquisition database **90**. The local client **116** is then essentially linked to the file data **88** stored in the acquisition database **90** by a link such as a local area network. The local client **116** receives the file data **88** directly from the acquisition database **90**. The local client may view and annotate any of the file data **88** on the local client workstation **118**. The file data **88** is returned to the acquisition database **90** with any annotations stored in the file.

[0043] While the file data **88** residing in the acquisition database **90** can generally be accessed and annotated directly by a local client **116**, the waveform data **86** is not directly accessible by the local client **116**. Instead, the local client **116** receives the replicated waveform data **86a** from the segment server **108**. One reason for this particular scheme is to prevent a local client **116** from altering the waveform data **86**. Since the waveform data is a representation of the raw test results from an EPS study, it may be important to safeguard the integrity of the data by providing access to only the replicated waveform data **86a** as described in the present embodiment.

[0044] Finally, it may be advantageous to provide a central server **122** to permanently store (archive) study data once a study has been completed. The central server **122** may include a central server storage unit **124** to store waveform data and a central server database **126** to store file data. Further, the central server **122** may include a central server catalog **128** which lists the studies on all segment servers, such as segment server **108**, which are coupled to the central server **122**. Since each segment server **108** includes a catalog **114** listing all study records contained on any of the acqui-

sition workstations which are coupled to the segment server **108**, such as acquisition workstations **80** and **82**, the central server catalog **128** provides a path to any study contained on any of the acquisition workstations throughout the network. The archival scheme is further discussed with reference to FIG. 4.

[0045] FIG. 4 illustrates one embodiment of an archival scheme for permanently storing study data once a study is complete. The Archival Generator (AG) software application selects study data older than a user selected number of days from short-term storage in an acquisition database **90** and **102**. All selected study records in the acquisition database **90** and **102**, including both the file data **88** and **100** and the waveform data **86** and **98**, are copied to the central server **122**. Once copied, the data may be tested for data integrity by comparing the study record to the study record stored in the segment server **108**. Once integrity is verified, the study records can be deleted from the acquisition databases **90** and **102**, as well as the segment server database **108**. The central server catalog **128**, the segment server catalog **114** and the acquisition station catalogs **94** and **101** are updated appropriately.

[0046] It should be evident that to provide real-time updates of the study data while a client is reviewing a study which is currently being conducted, a messaging system may be implemented to insure that updates are sent to clients viewing the particular study. FIG. 5 illustrates one implementation of a messaging technique corresponding to the present system. When the file data **88** is inserted into the acquisition database **90**, a message record may be added to a socket table in the acquisition database **90**. A messaging application, such as NetMsgSender, sends all message records located in the socket table through an output port of the acquisition workstation **80**, such as TCP/IP Port 50,000, to all systems, such as local workstation **118**, which are configured to receive data from the acquisition workstation **80**. The message records may be sent at a user-configurable interval. All acquisition workstations **80** and **82** listen on the output port. If a message is received on a particular workstation, such as workstation **80**, the workstation **80** reads the message and determines whether the message pertains to an active study. If it does, the workstation **80** determines which event is affected and refreshes the view of the appropriate study data accordingly.

[0047] While the present embodiment discloses a technique using data taken during an EPS, it should be evident to one skilled in the art that the technique described herein can be applied to other cardiology procedures performed in a catheterization lab in which electrical and/or hemodynamic data may be obtained.

[0048] While the invention may be susceptible to various modifications and alternative forms, specific embodiments have been shown by way of example in the drawings and have been described in detail herein. However, it should be understood that the invention is not intended to be limited to the particular forms disclosed. Rather, the invention is to cover all modifications, equivalents, and alternatives falling

within the spirit and scope of the invention as defined by the following appended claims.

What is claimed is:

1. A method of annotating a study record taken during a cardiac catheterization procedure, the procedure being conducted in a cardiac catheterization lab, comprising the acts of:

- (a) inserting at least one catheter into a patient comprising a heart, the catheters terminating in a position proximate to the heart and comprising one or more sensors configured to sense data from the heart;
- (b) stimulating the heart with electrical signals from the catheter;
- (c) sensing data from the heart;
- (d) transmitting the data from the sensors to a data collection device;
- (e) transmitting the data from the data collection device to a central publisher;
- (f) replicating the data;
- (g) transmitting the replicated data from the central publisher to a plurality of client workstations;
- (h) annotating the replicated data at at least one of the plurality of client workstations to produce annotated data;
- (i) transmitting the annotated data from the at least one client workstation to the central publisher;
- (j) replicating the annotated data; and
- (k) transmitting the replicated annotated data from the central publisher to the plurality of client workstations.

2. The method, as set forth in claim 1, wherein the catheterization procedure comprises an electrophysiology procedure.

3. The method, as set forth in claim 1, wherein the catheterization procedure comprises an ablation procedure.

4. The method, as set forth in claim 1, wherein the central publisher comprises a server.

5. The method, as set forth in claim 4, wherein the server is located locally with respect to the cardiac catheterization lab.

6. The method, as set forth in claim 1, wherein the central publisher is located within the cardiac catheterization lab.

7. The method, as set forth in claim 1, wherein each of the plurality of client workstations comprises a monitor configured to display digital data.

8. The method, as set forth in claim 1, wherein act (c) comprises the act of sensing electrical data from the heart.

9. The method, as set forth in claim 1, wherein act (c) comprises the act of sensing hemodynamic data from the heart.

10. The method, as set forth in claim 1, further comprising simultaneously displaying the data on the plurality of client workstations.

11. The method, as set forth in claim 10, wherein the act comprises simultaneously displaying the data on the plurality of client workstations during the cardiac catheterization procedure.

12. The method, as set forth in claim 11, wherein at least one of the plurality of client workstations is located remotely with respect to the cardiac catheterization lab.

13. The method, as set forth in claim 10, wherein the act of simultaneously displaying the data on the plurality of client workstations occurs in real time.

14. A method of annotating a study record taken during a cardiac catheterization procedure, the procedure being conducted in a cardiac catheterization lab, comprising the acts of:

- (a) transmitting data from a catheter to a data collection device;
- (b) transmitting the data from the data collection device to a central publisher;
- (c) replicating the data;
- (d) transmitting the replicated data from the central publisher to a plurality of client workstations; and
- (e) annotating the replicated data at at least one of the plurality of client workstations to produce annotated data;
- (f) transmitting the annotated data from the at least one client workstation to the central publisher;
- (g) replicating the annotated data; and
- (h) transmitting the replicated annotated data from the central publisher to the plurality of client workstations.

15. The method, as set forth in claim 14, wherein the catheterization procedure comprises a electrophysiology procedure.

16. The method, as set forth in claim 14, wherein the catheterization procedure comprises an ablation procedure.

17. The method, as set forth in claim 14, wherein the central publisher comprises a server.

18. The method, as set forth in claim 17, wherein the server is located locally with respect to the cardiac catheterization lab.

19. The method, as set forth in claim 14, wherein the central publisher is located within the cardiac catheterization lab.

20. The method, as set forth in claim 14, wherein each of the plurality of client workstations comprises a monitor configured to display digital data.

21. The method, as set forth in claim 14, wherein act (a) comprises the act of transmitting electrical data from the heart.

22. The method, as set forth in claim 14, wherein act (a) comprises the act of transmitting hemodynamic data from the heart.

23. The method, as set forth in claim 14, further comprising simultaneously displaying the data on the plurality of client workstations.

24. The method, as set forth in claim 23, wherein the act comprises simultaneously displaying the data on the plurality of client workstations during the cardiac catheterization procedure.

25. The method, as set forth in claim 24, wherein at least one of the plurality of client workstations is located remotely with respect to the cardiac catheterization lab.

26. The method, as set forth in claim 23, wherein the act of simultaneously displaying the data on the plurality of client workstations occurs in real time.

27. A system comprising:

- a device configured to perform an electrophysiology procedure and further configured to produce data as a result of the electrophysiology procedure;
- a data acquisition workstation electrically coupled to the device and configured to acquire data produced during the electrophysiology procedure;
- a plurality of client workstations coupled to the data acquisition workstation and configured to allow a user to annotate the data received from the data acquisition workstation to produce annotated data; and
- a publisher coupled to the data acquisition workstation and further coupled to the plurality of client workstations and configured to transmit and receive the data from the data acquisition workstation during the electrophysiology procedure and further configured to transmit and receive the annotated data from the plurality of client workstations during the electrophysiology procedure.

28. The system, as set forth in claim 27, wherein at least one of the plurality of client workstations is located remotely with respect to the cardiac catheterization lab.

29. The system, as set forth in claim 27, wherein the plurality of client workstations is coupled to the publisher through a server.

30. The system, as set forth in claim 27, wherein the plurality of client workstations is coupled to the publisher via a satellite link.

31. The system, as set forth in claim 27, wherein each of the plurality of client workstations comprises a monitor configured to display digital data.

32. The system, as set forth in claim 27, wherein the publisher comprises a server.

33. The system, as set forth in claim 27, wherein the system is further configured to simultaneously display the data and the annotated data on the plurality of client workstations.

* * * * *

专利名称(译)	用于心脏病学程序的分布式实时复制注释和文档系统		
公开(公告)号	US20020087053A1	公开(公告)日	2002-07-04
申请号	US09/752159	申请日	2000-12-29
[标]申请(专利权)人(译)	STOYCOS STEPHEN T. 凯泽EWIN MICHAEL		
申请(专利权)人(译)	STOYCOS STEPHEN T. 凯泽EWIN MICHAEL		
当前申请(专利权)人(译)	GE医疗系统信息技术股份有限公司.		
[标]发明人	STOYCOS STEPHEN T KISER EWIN MICHAEL		
发明人	STOYCOS, STEPHEN T. KISER, EWIN MICHAEL		
IPC分类号	A61B5/00 A61B5/044 G06F19/00		
CPC分类号	A61B5/044 A61B5/7445 G06F19/322 G06F19/324 G06F19/3406 G06F19/3418 A61B5/002 G16H10/60 G16H40/63		
其他公开文献	US6575901		
外部链接	Espacenet USPTO		

摘要(译)

一种分布式多用户系统，用于在心脏病学过程中进行实时数据访问。该系统包括交互式计算机网络，该交互式计算机网络可用于在多个设备上 and 多个位置同时显示和操纵来自心脏病学过程的数据。该系统通过各种复制拓扑实现，允许在程序期间同时访问和注释心脏病学研究。在该过程期间，可以在多个位置中的任何位置显示和注释该研究，所述多个位置可以是本地的或远程的。在多个位置之一处进行的注释将通过发布者分发到其他位置。

