



US009072474B2

(12) **United States Patent**
Al-Ali et al.

(10) **Patent No.:** **US 9,072,474 B2**
(45) **Date of Patent:** ***Jul. 7, 2015**

(54) **PULSE OXIMETER ACCESS APPARATUS
AND METHOD**

USPC 600/310, 322, 323, 344
See application file for complete search history.

(75) Inventors: **Ammar Al-Ali**, Tustin, CA (US);
Ronald Coverston, Portola Hills, CA
(US); **Massi E. Kiani**, Laguna Niguel,
CA (US)

(56) **References Cited**

U.S. PATENT DOCUMENTS

4,960,128	A	10/1990	Gordon et al.
4,964,408	A	10/1990	Hink et al.
5,041,187	A	8/1991	Hink et al.
5,069,213	A	12/1991	Polczynski
5,163,438	A	11/1992	Gordon et al.
5,337,744	A	8/1994	Branigan
5,341,805	A	8/1994	Stavridi et al.
D353,195	S	12/1994	Savage et al.
D353,196	S	12/1994	Savage et al.
5,377,676	A	1/1995	Vari et al.
D359,546	S	6/1995	Savage et al.
5,431,170	A	7/1995	Mathews
D361,840	S	8/1995	Savage et al.
D362,063	S	9/1995	Savage et al.

(Continued)

(73) Assignee: **MASIMO CORPORATION**, Irvine,
CA (US)

(*) Notice: Subject to any disclaimer, the term of this
patent is extended or adjusted under 35
U.S.C. 154(b) by 1030 days.

This patent is subject to a terminal dis-
claimer.

(21) Appl. No.: **12/360,830**

(22) Filed: **Jan. 27, 2009**

(65) **Prior Publication Data**

US 2009/0137885 A1 May 28, 2009

Related U.S. Application Data

(63) Continuation of application No. 10/981,186, filed on
Nov. 4, 2004, now Pat. No. 7,483,729.

(60) Provisional application No. 60/517,954, filed on Nov.
5, 2003.

(51) **Int. Cl.**
A61B 5/1455 (2006.01)

(52) **U.S. Cl.**
CPC **A61B 5/14551** (2013.01); **A61B 2560/0266**
(2013.01); **A61B 2562/08** (2013.01); **A61B**
2562/222 (2013.01)

(58) **Field of Classification Search**
CPC A61B 5/1455; A61B 5/14551; A61B
5/14552; A61B 2560/0266; A61B 2562/08;
A61B 2562/222


Primary Examiner — Eric Winakur

(74) *Attorney, Agent, or Firm* — Knobbe Martens Olson &
Bear LLP

(57) **ABSTRACT**

Access is provided to certain pulse oximetry systems utilizing a keyed sensor and a corresponding locked sensor port of a restricted access monitor. In such systems, the keyed sensor has a key comprising a memory element, and the monitor has a memory reader associated with the sensor port. The monitor is configured to function only when the key is in communications with the locked sensor port, and the memory reader is able to retrieve predetermined data from the memory element. The monitor is accessed by providing the key separate from the keyed sensor, integrating the key into an adapter cable, and connecting the adapter cable between the sensor port and an unkeyed sensor so that the monitor functions with the unkeyed sensor.

3 Claims, 6 Drawing Sheets



(56)

References Cited

U.S. PATENT DOCUMENTS

5,452,717 A	9/1995	Branigan et al.	6,430,525 B1	8/2002	Weber et al.
D363,120 S	10/1995	Savage et al.	6,463,311 B1	10/2002	Diab
5,456,252 A	10/1995	Vari et al.	6,470,199 B1	10/2002	Kopotic et al.
5,482,036 A	1/1996	Diab et al.	6,490,466 B1	12/2002	Fein et al.
5,490,505 A	2/1996	Diab et al.	6,501,975 B2	12/2002	Diab et al.
5,494,043 A	2/1996	O'Sullivan et al.	6,505,059 B1	1/2003	Kollias et al.
5,533,511 A	7/1996	Kaspari et al.	6,515,273 B2	2/2003	Al-Ali
5,561,275 A	10/1996	Savage et al.	6,519,487 B1	2/2003	Parker
5,562,002 A	10/1996	Lalin	6,525,386 B1	2/2003	Mills et al.
5,590,649 A	1/1997	Caro et al.	6,526,300 B1	2/2003	Kiani et al.
5,602,924 A	2/1997	Durand et al.	6,541,756 B2	4/2003	Schulz et al.
5,632,272 A	5/1997	Diab et al.	6,542,764 B1	4/2003	Al-Ali et al.
5,638,816 A	6/1997	Kiani-Azarbayjany et al.	6,580,086 B1	6/2003	Schulz et al.
5,638,818 A	6/1997	Diab et al.	6,584,336 B1	6/2003	Ali et al.
5,645,440 A	7/1997	Tobler et al.	6,595,316 B2	7/2003	Cybulski et al.
5,660,567 A	8/1997	Nierlich et al.	6,597,932 B2	7/2003	Tian et al.
5,685,299 A	11/1997	Diab et al.	6,597,933 B2	7/2003	Kiani et al.
5,720,293 A	2/1998	Quinn et al.	6,606,511 B1	8/2003	Ali et al.
D393,830 S	4/1998	Tobler et al.	6,632,181 B2	10/2003	Flaherty et al.
5,743,262 A	4/1998	Lepper, Jr. et al.	6,639,668 B1	10/2003	Trepagnier
5,758,644 A	6/1998	Diab et al.	6,640,116 B2	10/2003	Diab
5,760,910 A	6/1998	Lepper, Jr. et al.	6,643,530 B2	11/2003	Diab et al.
5,769,785 A	6/1998	Diab et al.	6,650,917 B2	11/2003	Diab et al.
5,782,757 A	7/1998	Diab et al.	6,654,624 B2	11/2003	Diab et al.
5,785,659 A	7/1998	Caro et al.	6,658,276 B2	12/2003	Kiani et al.
5,791,347 A	8/1998	Flaherty et al.	6,661,161 B1	12/2003	Lanzo et al.
5,807,247 A	9/1998	Merchant et al.	6,671,531 B2	12/2003	Al-Ali et al.
5,810,734 A	9/1998	Caro et al.	6,678,543 B2	1/2004	Diab et al.
5,823,950 A	10/1998	Diab et al.	6,684,090 B2	1/2004	Ali et al.
5,830,131 A	11/1998	Caro et al.	6,684,091 B2	1/2004	Parker
5,833,618 A	11/1998	Caro et al.	6,697,656 B1	2/2004	Al-Ali
5,860,919 A	1/1999	Kiani-Azarbayjany et al.	6,697,657 B1	2/2004	Shehada et al.
5,890,929 A	4/1999	Mills et al.	6,697,658 B2	2/2004	Al-Ali
5,904,654 A	5/1999	Wohltmann et al.	RE38,476 E	3/2004	Diab et al.
5,919,134 A	7/1999	Diab	6,699,194 B1	3/2004	Diab et al.
5,934,925 A	8/1999	Tobler et al.	6,708,049 B1 *	3/2004	Berson et al. 600/323
5,940,182 A	8/1999	Lepper, Jr. et al.	6,714,804 B2	3/2004	Al-Ali et al.
5,995,855 A	11/1999	Kiani et al.	RE38,492 E	4/2004	Diab et al.
5,997,343 A	12/1999	Mills et al.	6,721,582 B2	4/2004	Trepagnier et al.
6,002,952 A	12/1999	Diab et al.	6,721,585 B1	4/2004	Parker
6,011,986 A	1/2000	Diab et al.	6,725,075 B2	4/2004	Al-Ali
6,027,452 A	2/2000	Flaherty et al.	6,728,560 B2	4/2004	Kollias et al.
6,036,642 A	3/2000	Diab et al.	6,735,459 B2	5/2004	Parker
6,045,509 A	4/2000	Caro et al.	6,745,060 B2	6/2004	Diab et al.
6,067,462 A	5/2000	Diab et al.	6,760,607 B2	7/2004	Al-Ali
6,081,735 A	6/2000	Diab et al.	6,770,028 B1	8/2004	Ali et al.
6,088,607 A	7/2000	Diab et al.	6,771,994 B2	8/2004	Kiani et al.
6,110,522 A	8/2000	Lepper, Jr. et al.	6,792,300 B1	9/2004	Diab et al.
6,124,597 A	9/2000	Shehada	6,813,511 B2	11/2004	Diab et al.
6,144,868 A	11/2000	Parker	6,816,741 B2	11/2004	Diab
6,151,516 A	11/2000	Kiani-Azarbayjany et al.	6,822,564 B2	11/2004	Al-Ali
6,152,754 A	11/2000	Gerhardt et al.	6,826,419 B2	11/2004	Diab et al.
6,157,850 A	12/2000	Diab et al.	6,830,711 B2	12/2004	Mills et al.
6,165,005 A	12/2000	Mills et al.	6,850,787 B2	2/2005	Weber et al.
6,184,521 B1	2/2001	Coffin, IV et al.	6,850,788 B2	2/2005	Al-Ali
6,206,830 B1	3/2001	Diab et al.	6,852,083 B2	2/2005	Caro et al.
6,229,856 B1	5/2001	Diab et al.	6,861,639 B2	3/2005	Al-Ali
6,232,609 B1	5/2001	Snyder et al.	6,898,452 B2	5/2005	Al-Ali et al.
6,236,872 B1	5/2001	Diab et al.	6,920,345 B2	7/2005	Al-Ali et al.
6,241,683 B1	6/2001	Macklem et al.	6,931,268 B1	8/2005	Kiani-Azarbayjany et al.
6,256,523 B1	7/2001	Diab et al.	6,934,570 B2	8/2005	Kiani et al.
6,263,222 B1	7/2001	Diab et al.	6,939,305 B2	9/2005	Flaherty et al.
6,278,522 B1	8/2001	Lepper, Jr. et al.	6,943,348 B1	9/2005	Coffin IV
6,280,213 B1	8/2001	Tobler et al.	6,950,687 B2	9/2005	Al-Ali
6,285,896 B1	9/2001	Tobler et al.	6,961,598 B2	11/2005	Diab
6,321,100 B1	11/2001	Parker	6,970,792 B1	11/2005	Diab
6,334,065 B1	12/2001	Al-Ali et al.	6,979,812 B2	12/2005	Al-Ali
6,343,224 B1	1/2002	Parker	6,985,764 B2	1/2006	Mason et al.
6,349,228 B1	2/2002	Kiani et al.	6,993,371 B2	1/2006	Kiani et al.
6,360,114 B1	3/2002	Diab et al.	6,996,427 B2	2/2006	Ali et al.
6,368,283 B1	4/2002	Xu et al.	6,999,904 B2	2/2006	Weber et al.
6,371,921 B1	4/2002	Caro et al.	7,003,338 B2	2/2006	Weber et al.
6,377,829 B1	4/2002	Al-Ali	7,003,339 B2	2/2006	Diab et al.
6,388,240 B2	5/2002	Schulz et al.	7,015,451 B2	3/2006	Dalke et al.
6,397,091 B2	5/2002	Diab et al.	7,024,233 B2	4/2006	Ali et al.
			7,027,849 B2	4/2006	Al-Ali
			7,030,749 B2	4/2006	Al-Ali
			7,039,449 B2	5/2006	Al-Ali
			7,041,060 B2	5/2006	Flaherty et al.

(56)

References Cited

U.S. PATENT DOCUMENTS

7,044,918 B2 5/2006 Diab
 7,067,893 B2 6/2006 Mills et al.
 7,096,052 B2 8/2006 Mason et al.
 7,096,054 B2 8/2006 Abdul-Hafiz et al.
 7,132,641 B2 11/2006 Schulz et al.
 7,142,901 B2 11/2006 Kiani et al.
 7,149,561 B2 12/2006 Diab
 7,186,966 B2 3/2007 Al-Ali
 7,190,261 B2 3/2007 Al-Ali
 7,215,984 B2 5/2007 Diab
 7,215,986 B2 5/2007 Diab
 7,221,971 B2 5/2007 Diab
 7,225,006 B2 5/2007 Al-Ali et al.
 7,225,007 B2 5/2007 Al-Ali
 RE39,672 E 6/2007 Shehada et al.
 7,239,905 B2 7/2007 Kiani-Azarbayjany et al.
 7,245,953 B1 7/2007 Parker
 7,254,431 B2 8/2007 Al-Ali
 7,254,433 B2 8/2007 Diab et al.
 7,254,434 B2 8/2007 Schulz et al.
 7,272,425 B2 9/2007 Al-Ali
 7,274,955 B2 9/2007 Kiani et al.
 D554,263 S 10/2007 Al-Ali
 7,280,858 B2 10/2007 Al-Ali et al.
 7,289,835 B2 10/2007 Mansfield et al.

7,292,883 B2 11/2007 De Felice et al.
 7,295,866 B2 11/2007 Al-Ali
 7,328,053 B1 2/2008 Diab et al.
 7,332,784 B2 2/2008 Mills et al.
 7,340,287 B2 3/2008 Mason et al.
 7,341,559 B2 3/2008 Schulz et al.
 7,343,186 B2 3/2008 Lamego et al.
 D566,282 S 4/2008 Al-Ali et al.
 7,355,512 B1 4/2008 Al-Ali
 7,371,981 B2 5/2008 Abdul-Hafiz
 7,373,193 B2 5/2008 Al-Ali et al.
 7,373,194 B2 5/2008 Weber et al.
 7,376,453 B1 5/2008 Diab et al.
 7,377,794 B2 5/2008 Al Ali et al.
 7,377,899 B2 5/2008 Weber et al.
 7,383,070 B2 6/2008 Diab et al.
 7,415,297 B2 8/2008 Al-Ali et al.
 7,428,432 B2 9/2008 Ali et al.
 7,438,683 B2 10/2008 Al-Ali et al.
 7,440,787 B2 10/2008 Diab
 7,454,240 B2 11/2008 Diab et al.
 7,467,002 B2 12/2008 Weber et al.
 7,469,157 B2 12/2008 Diab et al.
 7,471,969 B2 12/2008 Diab et al.
 7,471,971 B2 12/2008 Diab et al.
 7,483,729 B2 1/2009 Al-Ali et al.
 7,483,730 B2 1/2009 Diab et al.

* cited by examiner




FIG. 1






FIG. 2



**FIG. 4**






FIG. 5

FIG. 6




FIG. 7




FIG. 8

PULSE OXIMETER ACCESS APPARATUS AND METHOD

REFERENCE TO RELATED APPLICATION

The present application claims priority benefit under 35 U.S.C. § 120 to, and is a continuation of U.S. patent application Ser. No. 10/981,186, filed Nov. 4, 2004 entitled "Pulse Oximeter Access Apparatus and Method," now U.S. Pat. No. 7,482,729, which claims priority benefit under 35 U.S.C. § 119(e) from U.S. Provisional Application No. 60/517,954, filed Nov. 5, 2003, entitled "Pulse Oximeter Access Apparatus and Method." The present application also incorporates the foregoing disclosures herein by reference.

BACKGROUND OF THE INVENTION

Pulse oximeters have gained rapid acceptance in a wide variety of medical applications, including surgical wards, intensive care units, general wards and home care by providing early detection of decreases in the arterial oxygen supply, reducing the risk of accidental death and injury. FIG. 1 illustrates a pulse oximetry system 100 having a sensor 110 applied to a patient 10, a monitor 160, and a patient cable 140 connecting the sensor 110 and the monitor 160. The sensor 110 has a sensor body 111 that houses emitters and a detector and is attached to a patient at a selected fleshy medium site, such as a fingertip or ear lobe. The emitters are positioned to project light of at least two wavelengths through the blood vessels and capillaries of the fleshy medium. The detector is positioned so as to detect the emitted light after absorption by the fleshy medium, including hemoglobin and other constituents of pulsatile blood flowing within the fleshy medium, and generate at least first and second intensity signals in response. The sensor 110 has a patient cable connector 114 and may have an integrated sensor cable 112. The sensor 110 may be a disposable adhesive sensor for use on a single patient or a reusable clip-on sensor for use on multiple patients.

As shown in FIG. 1, the monitor 160, which may be a standalone device or may be incorporated as a module or built-in portion of a multiparameter patient monitoring system, computes at least one physiological parameter responsive to magnitudes of the intensity signals. A monitor 160 typically provides a numerical readout of the patient's oxygen saturation 164, a numerical readout of pulse rate 166, and a display the patient's plethysmograph 168, which provides a visual display of the patient's pulse contour and pulse rate. The monitor 160 has a sensor port 162 that transmits emitter drive signals to the sensor 110 and receives the detector intensity signals from the sensor 110. The patient cable 140 provides the electrical and mechanical connection and communications link between the sensor port 162 and the sensor 110. The patient cable 140 has a sensor connector 142 that connects to the patient cable connector 114 and a monitor connector 144 that connects to the sensor port 162.

SUMMARY OF THE INVENTION

Pulse oximeters have gained rapid acceptance in a wide variety of medical applications, including surgical wards, intensive care units, general wards and home care by providing early detection of decreases in the arterial oxygen supply, reducing the risk of accidental death and injury. FIG. 1 illustrates a pulse oximetry system 100 having a sensor 110 applied to a patient 10, a monitor 160, and a patient cable 140 connecting the sensor 110 and the monitor 160. The sensor 110 has a sensor body 111 that houses emitters and a detector

and is attached to a patient at a selected fleshy medium site, such as a fingertip or ear lobe. The emitters are positioned to project light of at least two wavelengths through the blood vessels and capillaries of the fleshy medium. The detector is positioned so as to detect the emitted light after absorption by the fleshy medium, including hemoglobin and other constituents of pulsatile blood flowing within the fleshy medium, and generate at least first and second intensity signals in response. The sensor 110 has a patient cable connector 114 and may have an integrated sensor cable 112. The sensor 110 may be a disposable adhesive sensor for use on a single patient or a reusable clip-on sensor for use on multiple patients.

As shown in FIG. 1, the monitor 160, which may be a standalone device or may be incorporated as a module or built-in portion of a multiparameter patient monitoring system, computes at least one physiological parameter responsive to magnitudes of the intensity signals. A monitor 160 typically provides a numerical readout of the patient's oxygen saturation 164, a numerical readout of pulse rate 166, and a display the patient's plethysmograph 168, which provides a visual display of the patient's pulse contour and pulse rate. The monitor 160 has a sensor port 162 that transmits emitter drive signals to the sensor 110 and receives the detector intensity signals from the sensor 110. The patient cable 140 provides the electrical and mechanical connection and communications link between the sensor port 162 and the sensor 110. The patient cable 140 has a sensor connector 142 that connects to the patient cable connector 114 and a monitor connector 144 that connects to the sensor port 162.

SUMMARY OF THE INVENTION

FIG. 2 illustrates a restricted access pulse oximetry system 200 having a keyed sensor 210 and a restricted access monitor 260. The keyed sensor 210 and restricted access monitor 260 are designed so that the monitor 260 will only function with a specific sensor or family of sensors from a specific manufacturer or licensed vendors. Upon power up, the sensor port 262 is locked. That is, the monitor 260 will not function until it reads the correct information from the sensor port 262. In particular, a patient cable connector 214 has a memory device. The memory device and the data stored in the memory device act as a key. The sensor port 262 and a memory reader in the monitor associated with the sensor port 262 act as a lock. When the keyed patient cable connector 214 is in communications with the locked sensor port 262 via a patient cable 240, the memory reader can access the data stored in the memory device. If the stored data matches predetermined access data, the monitor unlocks the sensor port 262, i.e. properly functions with a sensor attached to the sensor port 262. A memory device commonly used for storing manufacturer and product information is the DS2502 from Dallas Semiconductor, which has a 1 kbit memory that is accessed through a single pin that provides data input, data output and power. Once the sensor port 262 is unlocked, the sensor 210, patient cable 240, sensor port 262 and monitor 260 function as described with respect to FIG. 1, above.

One aspect of a pulse oximeter access method is used in conjunction with a pulse oximetry system comprising a keyed sensor and a corresponding locked sensor port of a restricted access monitor. The keyed sensor has a key comprising a memory element. The monitor has a memory reader associated with the sensor port. The monitor is configured to function only when the key is in communications with the locked sensor port and the memory reader is able to retrieve predetermined data from the memory element. The access method comprises the steps of providing the key separate from the

keyed sensor, integrating the key into an adapter cable, and connecting the adapter cable between the sensor port and an unkeyed sensor so that the monitor functions with the unkeyed sensor.

Another aspect of a pulse oximeter access apparatus comprises a sensor having emitters adapted to transmit light of at least first and second wavelengths into a fleshy medium and a light sensitive detector adapted to generate at least first and second intensity signals by detecting the light after absorption by constituents of pulsatile blood flowing within the fleshy medium. A monitor is configured to non-invasively measure one or more physiological parameters responsive to magnitudes of the intensity signals. A key contains access information. A sensor port is configured to communicate emitter drive signals from the monitor to the sensor, intensity signals from the sensor to the monitor, and the access information from the key to the monitor. A lock associated with the sensor port is adapted to read the access information from the key and to enable the monitor to provide measurements of the physiological parameters in response to the access information. An adapter cable containing the key is configured to provide a communications link between the sensor and the sensor port.

A further aspect of a pulse oximeter access apparatus comprises a sensor means for providing a physiological signal to a monitor and a key means for providing access to a locked sensor port portion of the monitor. An adapter cable means containing the key means provides communications between the sensor and the sensor port.

BRIEF DESCRIPTION OF THE DRAWINGS

FIG. 1 is a perspective view of a prior art pulse oximetry system;

FIG. 2 is a perspective view of a prior art pulse oximetry system having a restricted access monitor with a locked sensor port;

FIG. 3 is a perspective view of a pulse oximeter access apparatus;

FIG. 4 is a flow diagram of a pulse oximeter access method;

FIGS. 5-6 are perspective views of a keyed sensor and a keyless adapter cable, respectively, illustrating lock removal and reattachment; and

FIGS. 7-8 are perspective views of a keyed adapter cable and an attached keyless sensor, respectively.

DETAILED DESCRIPTION OF THE PREFERRED EMBODIMENT

FIG. 3 illustrates a pulse oximeter access apparatus 300 having a keyless sensor 810, a keyed adapter cable 700 and a patient cable 240 that advantageously interconnect so as to allow the keyless sensor 810 to function with a restricted access monitor 260 having a locked sensor port 262. The keyed adapter cable 700 has a keyed connector 214 at one end, which mates with a sensor connector 242 of a patient cable 240, and a sensor connector 714 at the opposite end, which mates with a patient cable connector 814 of the keyless sensor 810. The monitor connector 244 mates with the sensor port 262, providing communications between the keyless sensor 810 and the sensor port 262 and between a memory element in the keyed connector 214 and a memory reader within the monitor 260. The sensor connector 714 of the keyed adapter cable 700 can be any of a number of connectors that mate with any of a number of patient cable connectors 814. Further, a family of keyed adapter cables 700 can be

configured, each with a different sensor connector 714 compatible with a different keyless sensor 810 or family of keyless sensors 810.

FIG. 4 illustrates a pulse oximeter access method 400 for creating and utilizing a keyed adapter cable 700 (FIGS. 3, 7). In an initial step, a sensor port key is provided by purchasing 410 a keyed sensor configured for a particular restricted access monitor 260 (FIG. 2) and removing 420 the associated keyed connector 214 (FIG. 2), as described in further detail with respect to FIG. 5, below. Further steps include providing 430 a keyless adapter cable 600 (FIG. 6), and attaching 440 the keyed connector 214 (FIG. 2) to one end to make the keyed adapter cable 700 (FIG. 7), as described in further detail with respect to FIGS. 6-7, below. Additional steps include connecting 450 a keyless sensor 810 (FIG. 8) to the keyed adapter cable, and accessing 460 the restricted access monitor with the resulting adapted sensor 800 (FIG. 8), as described in further detail with respect to FIG. 3, above, and FIG. 8, below.

FIGS. 5-6 illustrate obtaining a sensor key from a keyed sensor 210 (FIG. 5) and using the key in the construction of a keyed adapter cable 700 (FIG. 7). As shown in FIG. 5, the keyed connector 214 is removed from a keyed sensor 210, such as by cutting the sensor cable 212 so as to leave sufficient wire for reattachment. As shown in FIG. 6, a keyless adapter cable 600 is provided having a cable 720 with a sensor connector 714 attached to a first end and with unconnected wires 610 at a second end. The removed keyed connector 214 is spliced or otherwise attached to the second end by any of various well-known methods, such as soldering or crimping followed by heat-shrink insulation to name a few techniques.

Construction of a keyed adapter cable 700 (FIG. 7) is described above with respect to removal and reattachment of a keyed connector 214. In an alternative embodiment, the key or memory element itself is removed from the keyed connector 214 of a keyed sensor 210 (FIG. 5) and embedded into or otherwise integrated into or incorporated with either one or both connectors of an otherwise keyless adapter cable 600 to construct the keyed adapter cable 700 (FIG. 7). In yet another embodiment, an equivalent memory element is purchased, developed or otherwise obtained and programmed with access data compatible with the memory element of the keyed sensor 210 (FIG. 5) and embedded into or otherwise integrated into or incorporated with either one or both connectors of an otherwise keyless adapter cable 600 to construct the keyed adapter cable 700 (FIG. 7).

FIG. 7 illustrates a keyed adapter cable 700 having a sensor connector 714, a keyed connector 214 and a cable 720 interconnecting the sensor connector 714 and keyed connector 214. The sensor connector 714 is configured to connect to a sensor patient cable connector 814 (FIG. 8), and the keyed connector 214 is configured to connect to a patient cable sensor connector 242 (FIG. 3). The keyed connector 214 has a memory element that is readable by a restricted access monitor 260 (FIG. 3) so as to unlock a locked sensor port 262 (FIG. 3), as described above.

FIG. 8 illustrates an adapted sensor 800 having a keyed adapter cable 700 attached to a keyless sensor 810. The sensor connector 714 of the keyed adapter cable 700 is mated to the patient cable connector 814 of the keyless sensor 810. The resulting adapted sensor 800 is configured to function with a restricted access monitor 260 (FIG. 3) in an equivalent manner as a keyed sensor 210 (FIG. 2). In particular, the keyed connector 214 mates with a patient cable 240 (FIG. 3), which mates with a locked sensor port 262 (FIG. 3) of a restricted

5

access monitor **260** (FIG. 3) so that monitor **260** (FIG. 3) functions with the keyless sensor **810**, as described above with respect to FIG. 3.

A keyed adapter cable is described above with respect to an adapter between a keyless sensor **810** and a patient cable **240** (FIG. 3). Such an embodiment is particularly advantageous for utilization of a keyed connector **214** removed from a keyed sensor **210** (FIG. 5). In an alternative embodiment, the patient cable **240** (FIG. 3) itself is utilized as a keyed adapter cable between a keyless sensor **810** and a locked sensor port **262** (FIG. 3). In particular, a memory element containing access data is removed from a keyed sensor **210** (FIG. 5) or a memory element is purchased, developed or otherwise obtained and programmed with compatible access data. The memory element is embedded into or otherwise integrated into or incorporated with either one or both connectors of an otherwise keyless patient cable **240** (FIG. 3) to construct a keyed adapter cable.

A pulse oximeter access apparatus and method has been disclosed in detail in connection with various embodiments. These embodiments are disclosed by way of examples only and are not to limit the scope of the claims that follow. One of ordinary skill in art will appreciate many variations and modifications.

What is claimed is:

1. A method of assembling a mechanical device that unlocks a patient monitor, the patient monitor configured to process signals from a noninvasive optical sensor attached to

6

a patient to determine one or physiological parameters of the patient, the patient monitor including a programmatic lock unlockable by presenting appropriate access information, the method comprising:

5 acquiring an authorized sensor including a key storing electronic access information configured to change a locked patient monitor into an unlocked patient monitor, the key being non-removably incorporated into the authorized sensor to the extent that removal significantly damages the authorized sensor, the key and the authorized sensor having a one-to-one association with one another;

removing said key from said authorized sensor by damaging said authorized sensor; and

10 incorporating said key into a mechanical device, said mechanical device with said incorporated key together configured to communicate with said locked patient monitor to unlock said lock, said mechanical device with said incorporated key together having a one-to-many association with a plurality of unauthorized sensors.

2. The method of claim 1, wherein said incorporating said key into said mechanical device comprises incorporating said key into a patient cable.

25 3. The method of claim 1, wherein said incorporating said key into said mechanical device comprises incorporating said key into a connector.

* * * * *

专利名称(译)	脉搏血氧计接入设备和方法		
公开(公告)号	US9072474	公开(公告)日	2015-07-07
申请号	US12/360830	申请日	2009-01-27
[标]申请(专利权)人(译)	AL ALI AMMAR COVERSTON RONALD Kiani曾MASSIê		
申请(专利权)人(译)	AL-ALI AMMAR COVERSTON RONALD Kiani曾MASSIê		
当前申请(专利权)人(译)	Masimo公司		
[标]发明人	AL ALI AMMAR COVERSTON RONALD KIANI MASSI E		
发明人	AL-ALI, AMMAR COVERSTON, RONALD KIANI, MASSI E.		
IPC分类号	A61B5/1455 A61B5/00		
CPC分类号	A61B5/14551 A61B2560/0266 A61B2562/08 A61B2562/222 A61B5/7221 A61B5/7271 A61B2560/0475 A61B2562/221		
优先权	10/981186 2009-01-27 US 60/517954 2003-11-05 US		
其他公开文献	US20090137885A1		
外部链接	Espacenet USPTO		

摘要(译)

利用键控传感器和受限访问监视器的相应锁定传感器端口，为某些脉搏血氧测量系统提供访问。在这样的系统中，键控传感器具有包括存储元件的键，并且监视器具有与传感器端口相关联的存储器读取器。监视器被配置为仅在键与锁定的传感器端口通信时起作用，并且存储器读取器能够从存储器元件检索预定数据。通过提供与键控传感器分开的钥匙，将钥匙集成到适配器电缆中，并在传感器端口和未键控的传感器之间连接适配器电缆，使监视器与无键传感器一起工作，即可访问监视器。

