



US009724483B2

(12) United States Patent
Hyde et al.**(10) Patent No.: US 9,724,483 B2**
(45) Date of Patent: Aug. 8, 2017**(54) METHOD FOR ADMINISTERING AN INHALABLE COMPOUND**5/08 (2013.01); *A61B 5/082* (2013.01); *A61M 15/009* (2013.01); *A61M 15/0028* (2013.01); *A61M 15/0065* (2013.01); *A61M 2205/3553* (2013.01); *A61M 2205/3569* (2013.01); (Continued)**(75) Inventors:** **Roderick A. Hyde**, Redmond, WA (US); **Muriel Y. Ishikawa**, Livermore, CA (US); **Jordin T. Kare**, Seattle, WA (US); **Robert Langer**, Newton, MA (US); **Eric C. Leuthardt**, St. Louis, MO (US); **Elizabeth A. Sweeney**, Seattle, WA (US); **Clarence T. Tegreene**, Mercer Island, WA (US); **Lowell L. Wood, Jr.**, Bellevue, WA (US); **Victoria Y. H. Wood**, Livermore, CA (US)**(58) Field of Classification Search**

USPC 128/200.24, 200.14, 200.23, 203.12, 128/203.15, 204.21, 206.27, 206.21, 128/205.25

See application file for complete search history.

(56) References Cited

U.S. PATENT DOCUMENTS

4,068,624 A 1/1978 Ramney
4,265,236 A 5/1981 Pacella
(Continued)

FOREIGN PATENT DOCUMENTS

GB 2355627 A 4/2001
WO WO 2006/048417 A1 5/2006

OTHER PUBLICATIONS

Carrie R. Foote, Veterinary Products Laboratories Introduces First Ever Dog Appeasing Pheromone Collar, Veterinary Products Laboratories, May 4, 2006, printed Aug. 26, 2009 from http://www.vpl.com/press/view_press.php?id=100690, Published in: US.*Primary Examiner* — Kristen Matter*(74) Attorney, Agent, or Firm* — Suiter Swantz pc llo**(57) ABSTRACT**


A method may include dispensing a dose of an inhalable compound according to a dosing instruction set; and maintaining a hands-free article for dispensing the inhalable compound in an operable dispensing position.

21 Claims, 73 Drawing Sheets**(73) Assignee:** **Gearbox, LLC**, Bellevue, WA (US)**(*) Notice:** Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 1785 days.**(21) Appl. No.:** **12/455,672****(22) Filed:** **Jun. 4, 2009****(65) Prior Publication Data**

US 2010/0163040 A1 Jul. 1, 2010

Related U.S. Application Data**(63)** Continuation-in-part of application No. 12/317,934, filed on Dec. 30, 2008, now abandoned, and a (Continued)**(51) Int. Cl.***A61M 15/00* (2006.01)*A61M 16/00* (2006.01)

(Continued)

(52) U.S. Cl.CPC *A61M 15/02* (2013.01); *A61B 5/411* (2013.01); *A61D 7/04* (2013.01); *A61M 15/08* (2013.01); *G06F 19/3462* (2013.01); *A61B*

Related U.S. Application Data

continuation-in-part of application No. 12/319,143, filed on Dec. 31, 2008, and a continuation-in-part of application No. 12/378,284, filed on Feb. 12, 2009, now abandoned, and a continuation-in-part of application No. 12/378,485, filed on Feb. 13, 2009, now Pat. No. 8,725,529, and a continuation-in-part of application No. 12/380,013, filed on Feb. 20, 2009, now abandoned, and a continuation-in-part of application No. 12/380,108, filed on Feb. 23, 2009, now abandoned, and a continuation-in-part of application No. 12/380,587, filed on Feb. 27, 2009, now abandoned, and a continuation-in-part of application No. 12/380,679, filed on Mar. 2, 2009, now abandoned, and a continuation-in-part of application No. 12/383,509, filed on Mar. 25, 2009, now Pat. No. 8,706,518, and a continuation-in-part of application No. 12/383,819, filed on Mar. 26, 2009, and a continuation-in-part of application No. 12/384,104, filed on Mar. 31, 2009, and a continuation-in-part of application No. 12/384,203, filed on Apr. 1, 2009, now Pat. No. 8,694,330, and a continuation-in-part of application No. 12/386,574, filed on Apr. 20, 2009, and a continuation-in-part of application No. 12/386,669, filed on Apr. 21, 2009, now Pat. No. 8,738,395, and a continuation-in-part of application No. 12/387,057, filed on Apr. 27, 2009, now Pat. No. 8,712,794, and a continuation-in-part of application No. 12/387,151, filed on Apr. 28, 2009, and a continuation-in-part of application No. 12/387,321, filed on Apr. 30, 2009, now abandoned, and a continuation-in-part of application No. 12/387,472, filed on May 1, 2009.

(51) **Int. Cl.**

B05D 7/14 (2006.01)
B65D 83/06 (2006.01)
A61M 15/02 (2006.01)
A61B 5/00 (2006.01)
A61D 7/04 (2006.01)
A61M 15/08 (2006.01)
G06F 19/00 (2011.01)
A61B 5/08 (2006.01)

(52) **U.S. Cl.**

CPC *A61M 2205/3584* (2013.01); *A61M 2205/3592* (2013.01); *A61M 2205/581* (2013.01); *A61M 2205/582* (2013.01); *A61M 2205/583* (2013.01); *A61M 2205/588* (2013.01); *A61M 2209/088* (2013.01); *A61M 2230/201* (2013.01); *A61M 2230/205* (2013.01)

(56)

References Cited

U.S. PATENT DOCUMENTS

4,456,007 A 6/1984 Nakao et al.
 4,652,261 A 3/1987 Mech et al.
 4,784,162 A 11/1988 Ricks et al.
 5,071,704 A 12/1991 Fischel-Ghodsian
 5,455,043 A 10/1995 Fischel-Ghodsian
 5,458,853 A 10/1995 Porter et al.
 5,487,378 A 1/1996 Robertson et al.
 5,546,943 A 8/1996 Gould
 5,610,674 A 3/1997 Martin
 5,709,863 A 1/1998 Pageat
 5,725,472 A 3/1998 Weathers
 5,807,114 A 9/1998 Hodges et al.
 5,819,207 A 10/1998 Takagi

5,842,467 A 12/1998 Greco
 5,949,522 A 9/1999 Manne
 5,954,641 A 9/1999 Kehr et al.
 6,026,807 A 2/2000 Puderbaugh et al.
 6,052,114 A 4/2000 Morifuji
 6,077,867 A 6/2000 Pageat
 6,135,928 A 10/2000 Butterfield
 6,168,562 B1 1/2001 Miller et al.
 6,169,113 B1 1/2001 Pageat
 6,223,744 B1* 5/2001 Garon 128/200.14
 6,280,383 B1 8/2001 Damadian
 6,397,837 B1 6/2002 Ferris
 6,425,764 B1 7/2002 Lamson
 6,431,171 B1 8/2002 Burton
 6,443,153 B1 9/2002 Viljanen et al.
 6,513,523 B1 2/2003 Izuchukwu et al.
 6,585,519 B1 7/2003 Jenkins et al.
 6,609,068 B2 8/2003 Cranley et al.
 6,663,888 B2 12/2003 Percel et al.
 6,684,880 B2 2/2004 Trueba
 6,702,767 B1 3/2004 Douglas et al.
 6,780,171 B2 8/2004 Gabel et al.
 6,889,687 B1 5/2005 Olsson
 6,978,212 B1 12/2005 Sunshine
 6,981,502 B2 1/2006 McCormick et al.
 7,044,911 B2 5/2006 Drinan et al.
 7,198,044 B2 4/2007 Trueba
 7,353,065 B2 4/2008 Morrell
 7,373,377 B2 5/2008 Altieri
 7,383,837 B2 6/2008 Robertson et al.
 7,427,417 B2 9/2008 Jendrucko et al.
 7,447,541 B2 11/2008 Huiku et al.
 7,711,583 B2 5/2010 Epstein et al.
 7,720,696 B1 5/2010 Berger et al.
 7,780,981 B2 8/2010 DiPierro et al.
 8,068,983 B2 11/2011 Vian et al.
 2001/0006939 A1 7/2001 Niven et al.
 2001/0034023 A1 10/2001 Stanton, Jr. et al.
 2001/0043664 A1 11/2001 Grant
 2002/0084996 A1 7/2002 Temkin et al.
 2003/0036683 A1 2/2003 Kehr et al.
 2003/0113374 A1 6/2003 Percel et al.
 2003/0114475 A1 6/2003 Fox et al.
 2003/0221687 A1 12/2003 Kaigler
 2004/0107961 A1 6/2004 Trueba
 2004/0116784 A1 6/2004 Gavish
 2004/0131682 A1 7/2004 Percel et al.
 2004/0197271 A1 10/2004 Kunka et al.
 2004/0254501 A1 12/2004 Mault
 2005/0019734 A1 1/2005 Peled
 2005/0054942 A1 3/2005 Melker et al.
 2005/0115561 A1 6/2005 Stahmann et al.
 2005/0154290 A1 7/2005 Langleben
 2005/0220843 A1 10/2005 DeWitt et al.
 2005/0228245 A1 10/2005 Quay
 2005/0228691 A1 10/2005 Paparo
 2005/0234742 A1 10/2005 Hodgdon
 2005/0263150 A1 12/2005 Chathampally et al.
 2006/0031099 A1 2/2006 Vitello et al.
 2006/0085230 A1 4/2006 Brill et al.
 2006/0129432 A1 6/2006 Choi et al.
 2006/0207596 A1 9/2006 Lane
 2007/0009555 A1 1/2007 Borodic
 2007/0016265 A1 1/2007 Davoodi et al.
 2007/0023044 A1 2/2007 Kwok et al.
 2007/0054028 A1 3/2007 Perlman et al.
 2007/0068514 A1* 3/2007 Giroux 128/200.14
 2007/0068515 A1 3/2007 Churchill
 2007/0124175 A1 5/2007 Jung et al.
 2007/0191815 A1 8/2007 DiPierro
 2007/0255115 A1 11/2007 Anglin, Jr. et al.
 2008/0004540 A1 1/2008 Nakao et al.
 2008/0014566 A1 1/2008 Chapman et al.
 2008/0038701 A1 2/2008 Booth et al.
 2008/0066739 A1 3/2008 LeMahieu et al.
 2008/0087279 A1 4/2008 Tieck et al.
 2008/0097167 A1 4/2008 Yudkovitch et al.
 2008/0142010 A1* 6/2008 Weaver et al. 128/203.26
 2008/0209289 A1 8/2008 Farnsworth et al.


(56)

References Cited

U.S. PATENT DOCUMENTS

2008/0214903	A1	9/2008	Orbach
2008/0230057	A1	9/2008	Sutherland
2008/0281639	A1	11/2008	Quinn et al.
2008/0317846	A1	12/2008	Percel et al.
2008/0318913	A1	12/2008	Fox et al.
2009/0046140	A1	2/2009	Lashmet et al.
2009/0111749	A1	4/2009	Richardson et al.
2009/0171259	A1	7/2009	Soerensen et al.
2009/0223249	A1	9/2009	Julkowski et al.
2009/0306741	A1	12/2009	Hogle et al.
2010/0062403	A1	3/2010	Williams et al.
2010/0178316	A1	7/2010	Chauhan et al.
2011/0226242	A1	9/2011	Von Hollen et al.

* cited by examiner

**FIG. 1A**




FIG. 1B




FIG. 1C




FIG. 1D




FIG. 1E




FIG. 1F

FIG. 1G

FIG. 1H




FIG. 2




FIG. 3




FIG. 4




FIG. 5




FIG. 6




FIG. 7




FIG. 8




FIG. 9




FIG. 10




FIG. 11




FIG. 12




FIG. 13




FIG. 14




FIG. 15




FIG. 16




FIG. 17




FIG. 18




FIG. 19




FIG. 20




FIG. 21




FIG. 22




FIG. 23




FIG. 24




FIG. 25




FIG. 26




FIG. 27




FIG. 28




FIG. 29




FIG. 30




FIG. 31




FIG. 32




FIG. 33




FIG. 34




FIG. 35




FIG. 36




FIG. 37




FIG. 38




FIG. 39




FIG. 40




FIG. 41




FIG. 42




FIG. 43




FIG. 44




FIG. 45




FIG. 46




FIG. 47




FIG. 48




FIG. 49




FIG. 50




FIG. 51




FIG. 52




FIG. 53




FIG. 54




FIG. 55




FIG. 56




FIG. 57




FIG. 58




FIG. 59




FIG. 60




FIG. 61




FIG. 62




FIG. 63




FIG. 64




FIG. 65




FIG. 66




FIG. 67




FIG. 68

1

METHOD FOR ADMINISTERING AN INHALABLE COMPOUND

CROSS-REFERENCE TO RELATED APPLICATIONS

The present application is related to and claims the benefit of the earliest available effective filing date(s) from the following listed application(s) (the "Related Applications") (e.g., claims earliest available priority dates for other than provisional patent applications or claims benefits under 35 USC §119(e) for provisional patent applications, for any and all parent, grandparent, great-grandparent, etc. applications of the Related Application(s)). All subject matter of the Related Applications and of any and all parent, grandparent, great-grandparent, etc. applications of the Related Applications is incorporated herein by reference to the extent such subject matter is not inconsistent herewith.

RELATED APPLICATIONS

For purposes of the USPTO extra-statutory requirements, the present application constitutes a continuation-in-part of United States Patent Application entitled METHODS AND SYSTEMS FOR PRESENTING AN INHALATION EXPERIENCE, naming RODERICK A. HYDE; ROBERT LANGER; ERIC C. LEUTHARDT; ROBERT W. LORD; ELIZABETH A. SWEENEY; CLARENCE T. TEGREENE; AND LOWELL L. WOOD as inventors, filed Dec. 30, 2008, application Ser. No. 12/317,934, which is currently co-pending, or is an application of which a currently co-pending application is entitled to the benefit of the filing date.

For purposes of the USPTO extra-statutory requirements, the present application constitutes a continuation-in-part of United States Patent Application entitled METHODS AND SYSTEMS FOR PRESENTING AN INHALATION EXPERIENCE, naming RODERICK A. HYDE; ROBERT LANGER; ERIC C. LEUTHARDT; ROBERT W. LORD; ELIZABETH A. SWEENEY; CLARENCE T. TEGREENE; AND LOWELL L. WOOD as inventors, filed Dec. 31, 2008, application Ser. No. 12/319,143, which is currently co-pending, or is an application of which a currently co-pending application is entitled to the benefit of the filing date.

For purposes of the USPTO extra-statutory requirements, the present application constitutes a continuation-in-part of United States Patent Application entitled METHODS AND SYSTEMS FOR PRESENTING AN INHALATION EXPERIENCE, naming RODERICK A. HYDE; ROBERT LANGER; ERIC C. LEUTHARDT; ROBERT W. LORD; ELIZABETH A. SWEENEY; CLARENCE T. TEGREENE; AND LOWELL L. WOOD as inventors, filed Feb. 12, 2009, application Ser. No. 12/378,284, which is currently co-pending, or is an application of which a currently co-pending application is entitled to the benefit of the filing date.

For purposes of the USPTO extra-statutory requirements, the present application constitutes a continuation-in-part of United States Patent Application entitled METHODS AND SYSTEMS FOR PRESENTING AN INHALATION EXPERIENCE, naming RODERICK A. HYDE; ROBERT LANGER; ERIC C. LEUTHARDT; ROBERT W. LORD; ELIZABETH A.

2

SWEENEY; CLARENCE T. TEGREENE; AND LOWELL L. WOOD as inventors, filed Feb. 13, 2009, application Ser. No. 12/378,485, which is currently co-pending, or is an application of which a currently co-pending application is entitled to the benefit of the filing date.

For purposes of the USPTO extra-statutory requirements, the present application constitutes a continuation-in-part of United States Patent Application entitled METHODS AND SYSTEMS FOR PRESENTING AN INHALATION EXPERIENCE, naming RODERICK A. HYDE; ROBERT LANGER; ERIC C. LEUTHARDT; ROBERT W. LORD; ELIZABETH A. SWEENEY; CLARENCE T. TEGREENE; AND LOWELL L. WOOD as inventors, filed Feb. 20, 2009, application Ser. No. 12/380,013, which is currently co-pending, or is an application of which a currently co-pending application is entitled to the benefit of the filing date.

For purposes of the USPTO extra-statutory requirements, the present application constitutes a continuation-in-part of United States Patent Application entitled METHODS AND SYSTEMS FOR PRESENTING AN INHALATION EXPERIENCE, naming RODERICK A. HYDE; ROBERT LANGER; ERIC C. LEUTHARDT; ROBERT W. LORD; ELIZABETH A. SWEENEY; CLARENCE T. TEGREENE; AND LOWELL L. WOOD as inventors, filed Feb. 23, 2009, application Ser. No. 12/380,108, which is currently co-pending, or is an application of which a currently co-pending application is entitled to the benefit of the filing date.

For purposes of the USPTO extra-statutory requirements, the present application constitutes a continuation-in-part of United States Patent Application entitled METHODS AND SYSTEMS FOR PRESENTING AN INHALATION EXPERIENCE, naming RODERICK A. HYDE; ROBERT LANGER; ERIC C. LEUTHARDT; ROBERT W. LORD; ELIZABETH A. SWEENEY; CLARENCE T. TEGREENE; AND LOWELL L. WOOD as inventors, filed Feb. 27, 2009, application Ser. No. 12/380,587, which is currently co-pending, or is an application of which a currently co-pending application is entitled to the benefit of the filing date.

For purposes of the USPTO extra-statutory requirements, the present application constitutes a continuation-in-part of United States Patent Application entitled METHODS AND SYSTEMS FOR PRESENTING AN INHALATION EXPERIENCE, naming RODERICK A. HYDE; ROBERT LANGER; ERIC C. LEUTHARDT; ROBERT W. LORD; ELIZABETH A. SWEENEY; CLARENCE T. TEGREENE; AND LOWELL L. WOOD as inventors, filed Mar. 2, 2009, application Ser. No. 12/380,679, which is currently co-pending, or is an application of which a currently co-pending application is entitled to the benefit of the filing date.

For purposes of the USPTO extra-statutory requirements, the present application constitutes a continuation-in-part of United States Patent Application entitled METHODS AND SYSTEMS FOR PRESENTING AN INHALATION EXPERIENCE, naming RODERICK A. HYDE; ROBERT LANGER; ERIC C. LEUTHARDT; ROBERT W. LORD; ELIZABETH A. SWEENEY; CLARENCE T. TEGREENE; AND LOWELL L. WOOD as inventors, filed Mar. 25, 2009,

application Ser. No. 12/383,509, which is currently co-pending, or is an application of which a currently co-pending application is entitled to the benefit of the filing date.

For purposes of the USPTO extra-statutory requirements, the present application constitutes a continuation-in-part of United States Patent Application entitled METHODS AND SYSTEMS FOR PRESENTING AN INHALATION EXPERIENCE, naming RODERICK A. HYDE; ROBERT LANGER; ERIC C. LEUTHARDT; ROBERT W. LORD; ELIZABETH A. SWEENEY; CLARENCE T. TEGREENE; AND LOWELL L. WOOD as inventors, filed Mar. 26, 2009, application Ser. No. 12/383,819, which is currently co-pending, or is an application of which a currently co-pending application is entitled to the benefit of the filing date.

For purposes of the USPTO extra-statutory requirements, the present application constitutes a continuation-in-part of United States Patent Application entitled METHODS AND SYSTEMS FOR PRESENTING AN INHALATION EXPERIENCE, naming RODERICK A. HYDE; ROBERT LANGER; ERIC C. LEUTHARDT; ROBERT W. LORD; ELIZABETH A. SWEENEY; CLARENCE T. TEGREENE; AND LOWELL L. WOOD as inventors, filed Mar. 31, 2009, application Ser. No. 12/384,104, which is currently co-pending, or is an application of which a currently co-pending application is entitled to the benefit of the filing date.

For purposes of the USPTO extra-statutory requirements, the present application constitutes a continuation-in-part of United States Patent Application entitled METHODS AND SYSTEMS FOR PRESENTING AN INHALATION EXPERIENCE, naming RODERICK A. HYDE; ROBERT LANGER; ERIC C. LEUTHARDT; ROBERT W. LORD; ELIZABETH A. SWEENEY; CLARENCE T. TEGREENE; AND LOWELL L. WOOD as inventors, filed Apr. 1, 2009, application Ser. No. 12/384,203, which is currently co-pending, or is an application of which a currently co-pending application is entitled to the benefit of the filing date.

For purposes of the USPTO extra-statutory requirements, the present application constitutes a continuation-in-part of United States Patent Application entitled METHODS AND SYSTEMS FOR PRESENTING AN INHALATION EXPERIENCE, naming RODERICK A. HYDE; ROBERT LANGER; ERIC C. LEUTHARDT; ROBERT W. LORD; ELIZABETH A. SWEENEY; CLARENCE T. TEGREENE; AND LOWELL L. WOOD as inventors, filed Apr. 20, 2009, application Ser. No. 12/386,574, which is currently co-pending, or is an application of which a currently co-pending application is entitled to the benefit of the filing date.

For purposes of the USPTO extra-statutory requirements, the present application constitutes a continuation-in-part of United States Patent Application entitled METHODS AND SYSTEMS FOR PRESENTING AN INHALATION EXPERIENCE, naming RODERICK A. HYDE; ROBERT LANGER; ERIC C. LEUTHARDT; ROBERT W. LORD; ELIZABETH A. SWEENEY; CLARENCE T. TEGREENE; AND LOWELL L. WOOD as inventors, filed Apr. 21, 2009, application Ser. No. 12/386,669, which is currently

co-pending, or is an application of which a currently co-pending application is entitled to the benefit of the filing date.

For purposes of the USPTO extra-statutory requirements, the present application constitutes a continuation-in-part of United States Patent Application entitled METHODS AND SYSTEMS FOR PRESENTING AN INHALATION EXPERIENCE, naming RODERICK A. HYDE; ROBERT LANGER; ERIC C. LEUTHARDT; ROBERT W. LORD; ELIZABETH A. SWEENEY; CLARENCE T. TEGREENE; AND LOWELL L. WOOD as inventors, filed Apr. 27, 2009, application Ser. No. 12/387,057, which is currently co-pending, or is an application of which a currently co-pending application is entitled to the benefit of the filing date.

For purposes of the USPTO extra-statutory requirements, the present application constitutes a continuation-in-part of United States Patent Application entitled METHODS AND SYSTEMS FOR PRESENTING AN INHALATION EXPERIENCE, naming RODERICK A. HYDE; ROBERT LANGER; ERIC C. LEUTHARDT; ROBERT W. LORD; ELIZABETH A. SWEENEY; CLARENCE T. TEGREENE; AND LOWELL L. WOOD as inventors, filed Apr. 28, 2009, application Ser. No. 12/387,151, which is currently co-pending, or is an application of which a currently co-pending application is entitled to the benefit of the filing date.

For purposes of the USPTO extra-statutory requirements, the present application constitutes a continuation-in-part of United States Patent Application entitled METHODS AND SYSTEMS FOR PRESENTING AN INHALATION EXPERIENCE, naming RODERICK A. HYDE; ROBERT LANGER; ERIC C. LEUTHARDT; ROBERT W. LORD; ELIZABETH A. SWEENEY; CLARENCE T. TEGREENE; AND LOWELL L. WOOD as inventors, filed Apr. 30, 2009, application Ser. No. 12/387,321, which is currently co-pending, or is an application of which a currently co-pending application is entitled to the benefit of the filing date.

For purposes of the USPTO extra-statutory requirements, the present application constitutes a continuation-in-part of United States Patent Application entitled METHODS AND SYSTEMS FOR PRESENTING AN INHALATION EXPERIENCE, naming RODERICK A. HYDE; ROBERT LANGER; ERIC C. LEUTHARDT; ROBERT W. LORD; ELIZABETH A. SWEENEY; CLARENCE T. TEGREENE; AND LOWELL L. WOOD as inventors, filed May 1, 2009, application Ser. No. 12/387,472, which is currently co-pending, or is an application of which a currently co-pending application is entitled to the benefit of the filing date.

The United States Patent Office (USPTO) has published a notice to the effect that the USPTO's computer programs require that patent applicants reference both a serial number and indicate whether an application is a continuation or continuation-in-part. Stephen G. Kunin, Benefit of Prior-Filed Application, USPTO Official Gazette Mar. 18, 2003. The present Applicant Entity (hereinafter "Applicant") has provided above a specific reference to the application(s) from which priority is being claimed as recited by statute. Applicant understands that the statute is unambiguous in its specific reference language and does not require either a serial number or any characterization, such as "continua-

tion" or "continuation-in-part," for claiming priority to U.S. patent applications. Notwithstanding the foregoing, Applicant understands that the USPTO's computer programs have certain data entry requirements, and hence Applicant is designating the present application as a continuation-in-part of its parent applications as set forth above, but expressly points out that such designations are not to be construed in any way as any type of commentary and/or admission as to whether or not the present application contains any new matter in addition to the matter of its parent application(s).

SUMMARY

In an aspect, a method includes, but is not limited to, dispensing a dose of an inhalable compound according to a dosing instruction set; and maintaining a hands-free article for dispensing an inhalable compound in an operable dispensing position. In addition to the foregoing, other method aspects are described in the claims, drawings, and text forming a part of the present disclosure.

In an aspect, a method includes, but is not limited to, dispensing a dose of an inhalable compound according to a dosing instruction set; maintaining a hands-free article for dispensing an inhalable compound in an operable dispensing position; and receiving a dose of an inhalable compound for dispensing. In addition to the foregoing, other method aspects are described in the claims, drawings, and text forming a part of the present disclosure.

In an aspect, a method includes dispensing a dose of an inhalable compound according to a dosing instruction set; maintaining a hands-free article for dispensing an inhalable compound in an operable dispensing position; and receiving the inhalable compound. In addition to the foregoing, other method aspects are described in the claims, drawings, and text forming a part of the present disclosure.

In an aspect, a method includes dispensing a dose of an inhalable compound according to a dosing instruction set; maintaining a hands-free article for dispensing an inhalable compound in an operable dispensing position; and supporting a hands-free aerosol delivery system on the body of a mammal. In addition to the foregoing, other method aspects are described in the claims, drawings, and text forming a part of the present disclosure.

In an aspect, a method includes detecting a medical condition parameter of a mammal according to a medical condition parameter request; maintaining a hands-free article for dispensing an inhalable compound in an operable dispensing position; and dispensing a dose of an inhalable compound according to a dosing instruction set. In addition to the foregoing, other method aspects are described in the claims, drawings, and text forming a part of the present disclosure.

In addition to the foregoing, various other method and/or system and/or program product aspects are set forth and described in the teachings such as text (e.g., claims and/or detailed description) and/or drawings of the present disclosure.

The foregoing is a summary and thus may contain simplifications, generalizations, inclusions, and/or omissions of detail; consequently, those skilled in the art will appreciate that the summary is illustrative only and is NOT intended to be in any way limiting. Other aspects, features, and advantages of the devices and/or processes and/or other subject matter described herein will become apparent in the teachings set forth herein.

BRIEF DESCRIPTION OF THE FIGURES

FIG. 1A is a front elevation view illustrating a collar for dispensing one or more inhalable compounds.

FIG. 1B is a top plan view of a collar for dispensing one or more inhalable compounds.

FIG. 1C is a partial cross-sectional side elevation view of a collar for dispensing one or more inhalable compounds.

FIG. 1D is a partial cross-sectional side elevation view of a collar for dispensing one or more inhalable compounds.

FIG. 1E is a schematic of a collar for dispensing one or more inhalable compounds.

FIG. 1F is a schematic of a compound for being dispensed by a collar for dispensing one or more inhalable compounds.

FIG. 1G is a schematic of a compound for being dispensed by a collar for dispensing one or more inhalable compounds.

FIG. 1H is a schematic of a collar for dispensing one or more inhalable compounds, where the collar is connected to various storage media.

FIG. 2 illustrates an operational flow representing example operations related to maintaining a hands-free article for dispensing an inhalable compound according to a dosing instruction set, where the hands-free article is maintained in an operable dispensing position.

FIG. 3 illustrates an alternative embodiment of the operational flow of FIG. 2.

FIG. 4 illustrates an alternative embodiment of the operational flow of FIG. 2.

FIG. 5 illustrates an alternative embodiment of the operational flow of FIG. 2.

FIG. 6 illustrates an alternative embodiment of the operational flow of FIG. 2.

FIG. 7 illustrates an alternative embodiment of the operational flow of FIG. 2.

FIG. 8 illustrates an alternative embodiment of the operational flow of FIG. 56.

FIG. 9 illustrates an alternative embodiment of the operational flow of FIG. 56.

FIG. 10 illustrates an alternative embodiment of the operational flow of FIG. 56.

FIG. 11 illustrates an alternative embodiment of the operational flow of FIG. 56.

FIG. 12 illustrates an alternative embodiment of the operational flow of FIG. 56.

FIG. 13 illustrates an alternative embodiment of the operational flow of FIG. 56.

FIG. 14 illustrates an alternative embodiment of the operational flow of FIG. 56.

FIG. 15 illustrates an alternative embodiment of the operational flow of FIG. 56.

FIG. 16 illustrates an alternative embodiment of the operational flow of FIG. 56.

FIG. 17 illustrates an alternative embodiment of the operational flow of FIG. 57.

FIG. 18 illustrates an alternative embodiment of the operational flow of FIG. 57.

FIG. 19 illustrates an alternative embodiment of the operational flow of FIG. 57.

FIG. 20 illustrates an alternative embodiment of the operational flow of FIG. 57.

FIG. 21 illustrates an alternative embodiment of the operational flow of FIG. 57.

FIG. 22 illustrates an alternative embodiment of the operational flow of FIG. 57.

FIG. 23 illustrates an alternative embodiment of the operational flow of FIG. 57.

FIG. 24 illustrates an alternative embodiment of the operational flow of FIG. 57.

FIG. 25 illustrates an alternative embodiment of the operational flow of FIG. 57.

FIG. 64 illustrates an alternative embodiment of the operational flow of FIG. 62.

FIG. 65 illustrates an alternative embodiment of the operational flow of FIG. 62.

FIG. 66 illustrates an alternative embodiment of the operational flow of FIG. 62.

FIG. 67 illustrates an alternative embodiment of the operational flow of FIG. 62.

FIG. 68 illustrates an alternative embodiment of the operational flow of FIG. 62.

DETAILED DESCRIPTION

In the following detailed description, reference is made to the accompanying drawings, which form a part hereof. In the drawings, similar symbols typically identify similar components, unless context dictates otherwise. The illustrative embodiments described in the detailed description, drawings, and claims are not meant to be limiting. Other embodiments may be utilized, and other changes may be made, without departing from the spirit or scope of the subject matter presented here.

Referring generally to FIGS. 1A through 1H, a hands-free article for dispensing one or more inhalable compounds is described in accordance with the present disclosure. The hands-free article, such as collar 100, may be worn by a subject 102 who can inhale a compound 104 dispensed by the collar 100. Although the subject 102 is depicted as a human in the accompanying figures, the subject can generally include any biological entity having respiratory organs (e.g., lungs), such as a mammalian entity (e.g., a human, a dog, a lion, or another mammal), an avian entity (e.g., a bird of prey or another avian), an amphibian entity (e.g., a frog or another amphibian), a reptilian entity (e.g., an alligator, a crocodile, a tortoise, or another reptile), as well as other biological entities having respiratory organs.

The collar 100 is maintained in an operable dispensing position. For example, the collar 100 may comprise a support for a hands-free aerosol delivery system on the body of a mammal. Thus, the collar 100 may be disposed around a portion of the body of the subject 102. For example, in one embodiment, the collar 100 may encircle a neck portion 106 of the subject 102. In an embodiment, the collar 100 may encircle a limb portion (e.g., wrist portion 108) of the subject 102. In an embodiment, the collar 100 may encircle a torso portion (e.g., chest portion 110) of the subject 102. In an embodiment, the collar 100 may encircle a head portion 112 of the subject 102. It should be noted that the above-mentioned embodiments are provided by way of example and are not meant to be limiting of the present disclosure. Thus, it is contemplated that the collar 100 may be maintained in an operable dispensing position by attaching it to a variety of other portions of the body of the subject 102.

The collar 100 may comprise a support member having a first end 114 and a second end 116. The first end 114 may be connected to the second end 116, encircling and creating a closed loop (e.g., a circle) about the body part of the subject 102. In an embodiment, the first end 114 may be connected to the second end 116 via a magnet 118. In an embodiment, the first end 114 of the collar 100 may be connected to the second end 116 of the collar 100 via a hook 120. In an embodiment, the first end 114 may be connected to the second end 116 via a snap connection 122. In an embodiment, the first end 114 of the collar 100 may be connected to the second end 116 of the collar 100 via a threaded connection 124. In an embodiment, the first end 114 may be connected to the second end 116 via a belt-like connection

126. It will be appreciated that this list of connections is provided by way of example and is not meant to be restrictive of the present disclosure. Other fastening devices may be utilized with the collar 100.

The collar 100 includes a dispensing module 128 for dispensing some amount of material, such as a dose (e.g., measured quantity, prescribed quantity, therapeutic quantity, etc.) of a compound 104 (e.g., organic compound, pharmaceutical compound, therapeutic compound, homeopathic compound, nutraceutical compound, biological material, protein, nucleic acid, cell, peptide, etc.) for modulating, curing, diagnosing, mitigating, preventing, or treating one or more of a disease, disorder, symptom or a condition. Additionally, the compound 104 may be utilized for enhancing one or more of a physical well-being or a mental well-being. The dispensing module 128 may be oriented in order to optimize delivery of the compound 104 to the subject 102. For example, in the case of an inhalable compound, the dispensing module may be oriented to optimize respiratory receipt by the subject 102. This may include orienting the dispensing module 128 such that an outlet (nozzle) 130 or jet emanating from the dispensing module 128 is pointed at (oriented towards) the nose 132 or mouth 134 of the subject 102.

Some inhalable compounds for utilization with the collar 100 may include, but are not limited to inhalable insulin, an inhalable corticosteroid, an inhalable antibiotic, an inhalable beta-2 agonist, or an inhalable mast cell stabilizer. Further, compounds for utilization with the collar 100 may include a compound that acts locally or systemically. Compounds for utilization with the collar 100 may include a compound having a formulation such that the formulation includes a carrier, such as a gas carrier, a liquid carrier, or a solid carrier. Additionally, compounds for utilization with the collar 100 may include a compound having a formulation such that the formulation includes penetration or absorption enhancers. It should be noted that this list is provided by way of example only and is not meant to be restrictive of the present invention. Further, it will be appreciated that various mechanisms or compounds may be utilized to power (e.g., nebulize) the inhalable compound out of the collar 100, such as O₂ (oxygen) or helium-O₂ (heliox). Such compounds may be selected for improving the response of the subject (e.g., heliox when utilized with an inhaled bronchodilator such as an inhalable beta-2 agonist).

Further, the dispensing module 128 may be maintained in an optimal position for optimizing delivery of the compound 104 to the subject 102. In an embodiment, a relative position or direction to a desired respiratory target is determined. For example, a direction to the subject's nose 132 may be determined. In an embodiment, a position of the dispensing module 128 may then be maintained for optimizing delivery of the compound 104. For example, the orientation of the outlet 130 may be maintained in the direction determined for the subject's nose 132. In an embodiment, the position of the dispensing module 128 may be maintained via a weight 136. In an embodiment, the position of the dispensing module may be maintained via an adhesive 138. In an embodiment, the position of the dispensing module 128 may be maintained via a slide 140. In an embodiment, the position of the dispensing module 128 may be maintained via a magnet 142. In an embodiment, the position of the dispensing module 128 may be maintained via a fastener 144 (e.g., a button or a snap). In an embodiment, the position of the dispensing module 128 may be maintained via a spring 146.

It will be appreciated that this list is provided by way of example and is not meant to be restrictive of the present disclosure.

The delivery of the compound **104** can be controlled to optimize or regulate delivery of the material **104** to the subject **102**. The delivery mechanism can be one or more of the same type of material delivery system (e.g., nebulizer), or may include at least two different delivery systems (e.g., nebulizer and a dry powder inhaler), the at least one outlet **130** may be one of a suite or an array of outlets (e.g., nozzles) **148**. One or more outlets (e.g., the first nozzle **130** and a second nozzle **150**) may be selected to deliver the compound **104**. In an embodiment, the first and second nozzles **130** and **150** may be in different locations. The direction of the subject's nose **132** may be determined. Then, a discharge direction for the dispensing module **128** can be controlled for optimizing delivery of the compound **104**. For example, the orientation of the dispensing module **128** can be controlled to orient the first outlet **130** and the second outlet **150** in the direction determined for the subject's nose **132**. In an embodiment, directed delivery of the compound **104** may be accomplished via a demand valve **152** coupled with programmable dosing. In an embodiment, directed delivery of the compound **104** may be accomplished via a charged particle dispersion. In an embodiment, the first outlet **130**, the second outlet **150**, or the suite of outlets **148** may include outlets having variable discharge characteristics, such as directional, volumetric, spray area, or other characteristics.

Various mechanical systems for delivering inhalable materials may include, but are not limited to, a vaporizer (e.g., a device for vaporizing liquid material for inhalation), a nebulizer (e.g., a device for administering material in the form of a mist for inhalation), a liquid aerosol system (e.g., a system for propelling fine droplets of material utilizing a gas), a dry powder inhalation system, an atomizer (e.g., a device for reducing a liquid material to a spray or vapor for inhalation), a metered dose inhaler (e.g., a device for releasing a metered dose of material for inhalation), a propellant-delivered system, a piezo-electric inhaler (e.g., an inhaler utilizing a piezo vibrator to deaggregate a material powder for subsequent inhalation by the subject), etc. It is further contemplated that the material **104** may be provided in removable or replaceable storage units. For example, the material **104** may be provided in an easily replaceable dose packet. In an embodiment, the material **104** may be provided in a removable canister. It will be appreciated that these storage units are provided by way of example, and other various storage configurations having varying shapes, sizes, and form factors may be utilized with the collar **100**.

Following are a series of flowcharts depicting implementations. For ease of understanding, the flowcharts are organized such that the initial flowcharts present implementations via an example implementation and thereafter the following flowcharts present alternate implementations and/or expansions of the initial flowchart(s) as either sub-component operations or additional component operations building on one or more earlier-presented flowcharts. Those having skill in the art will appreciate that the style of presentation utilized herein (e.g., beginning with a presentation of a flowchart(s) presenting an example implementation and thereafter providing additions to and/or further details in subsequent flowcharts) generally allows for a rapid and easy understanding of the various process implementations. In addition, those skilled in the art will further

appreciate that the style of presentation used herein also lends itself well to modular and/or object-oriented program design paradigms.

FIG. **2** illustrates an operational flow **200** representing example operations related to maintaining a hands-free article for dispensing an inhalable compound according to a dosing instruction set, where the hands-free article is maintained in an operable dispensing position. In FIG. **2** and in following figures that include various examples of operational flows, discussion and explanation may be provided with respect to the above-described examples of FIGS. **1A** through **1H**, and/or with respect to other examples and contexts. However, it should be understood that the operational flows may be executed in a number of other environments and contexts, and/or in modified versions of FIGS. **1A** through **1H**. Also, although the various operational flows are presented in the sequence(s) illustrated, it should be understood that the various operations may be performed in other orders than those which are illustrated, or may be performed concurrently.

After a start operation, the operational flow **200** moves to an operation **210**. Operation **210** depicts dispensing for inhalation by a user a dose of an inhalable compound according to a dosing instruction set. For example, as shown in FIGS. **1A** through **1H**, the collar **100** may include a memory **154** for storing a dosing instruction set. The memory **154** may be connected to a processor **156** operatively configured for initiating the dispensing of a dose **158** of a compound **104**. In an embodiment, the processor **156** is connected to a pump **160**. The processor **156** may electronically signal the pump **160** to dispense the dose **158** of the compound **104**.

Then, operation **220** depicts maintaining in physical association with the user a hands-free article for dispensing an inhalable compound in an operable dispensing position. For example, as shown in FIGS. **1A** through **1H**, the collar **100** may be maintained in an operable position by positioning a weight **136** at one end of the collar **100**.

FIG. **3** illustrates alternative embodiments of the example operational flow **200** of FIG. **2**. FIG. **3** illustrates example embodiments where the operation **210** may include at least one additional operation. Additional operations may include an operation **302**, an operation **304**, an operation **306**, and/or an operation **308**.

The operation **302** illustrates dispensing a dose of an inhalable compound according to a defined dosing instruction set. For example, as shown in FIGS. **1A** through **1H**, the memory **154** may store a defined dosing instruction set, and a processor **156** coupled with the memory **154** may be configured for initiating dispensing of the compound **104** according to the dosing instruction set. Further, the operation **304** illustrates dispensing a dose of an inhalable compound according to a time defined dosing instruction set. For example, as shown in FIGS. **1A** through **1H**, the memory **154** may store a time defined dosing instruction set, and the processor **156** coupled with the memory **154** may be configured for initiating dispensing of the compound **104** according to the time defined dosing instruction set. In an embodiment, the processor **156** is connected to a time keeping module **162** for determining when to dispense the compound **104**. For example, the compound **104** may be dispensed while the subject **102** is sleeping (or is scheduled to sleep according to the time defined dosing instruction set). Alternatively, the compound **104** may be dispensed shortly before the subject is scheduled to sleep (e.g., in the case of a compound including a sleep aid, or the like). Further, the operation **306** illustrates dispensing a dose of an inhalable

compound according to a user defined dosing instruction set. For example, as shown in FIGS. 1A through 1H, the memory 154 may store a user defined dosing instruction set, and the processor 156 coupled with the memory 154 may be configured for initiating dispensing of the compound 104 according to the user defined dosing instruction set. In an embodiment, the collar 100 may include an interface 164 accessible by a user 166 for supplying the user defined dosing instruction set to the memory 154 (e.g., via the processor 156). Further, the operation 308 illustrates dispensing a dose of an inhalable compound according to a health care provider-defined dosing instruction set. For example, as shown in FIGS. 1A through 1H, the collar 100 may include an interface 164 accessible by a physician 168 for supplying a physician defined dosing instruction set to the memory 154 (e.g., via the processor 156).

FIG. 4 illustrates alternative embodiments of the example operational flow 200 of FIG. 2. FIG. 4 illustrates example embodiments where the operation 210 may include at least one additional operation. Additional operations may include an operation 402, an operation 404, an operation 406, and/or an operation 408. Further, the operation 402 illustrates dispensing a dose of an inhalable compound according to a need response dosing instruction set. For example, as shown in FIGS. 1A through 1H, the collar 100 may include a memory 154 for storing a need response dosing instruction set. The collar 100 may also include a transducer (e.g., a sensor module 170) for sensing a health or wellness-related characteristic (or another characteristic) of the subject 102. Based on the sensed characteristic of the subject 102, the processor 156 may be operatively configured to dispense the dose 158 of the compound 104 after verifying that the characteristic corresponds to a need stored in the need response dosing instruction set. In one instance, a sensed characteristic includes a blood glucose level, and the need response dosing instruction set includes instructions for dispensing a dose of the compound when the sensed blood glucose level is above a certain threshold. Further, the operation 404 illustrates dispensing a dose of an inhalable compound according to an environmental need response dosing instruction set. For example, as shown in FIGS. 1A through 1H, the collar 100 may include a memory 154 for storing an environmental need response dosing instruction set. The collar 100 may also include a sensor module 170 for sensing an environment occupied by the subject 102. Based on the sensed environment of the subject 102, the processor 156 may be operatively configured to dispense the dose 158 of the compound 104 after verifying that the environment corresponds to an environment stored in the environmental need response dosing instruction set. In an embodiment, the sensed environment may include sensing an actual or Likely trigger (e.g., an allergen, a chemical, an irritant, or a particulate). A likely trigger may include, for example, a sensed environment where the presence of an animal increases a likelihood of dander, or an outside environment where a time of year (e.g., the month of May) increases a likelihood of pollen exposure. In one instance, a sensed environment includes an outdoor environment, and the environment need response dosing instruction set includes instructions for dispensing a dose of the compound when the outdoor environment is sensed. In an embodiment, the sensed environment includes at least one other individual (and possibly a number of other individuals, e.g., a crowd), and the environmental need response dosing instruction set includes instructions for dispensing a dose of a vaccine when the other individual is sensed. In an embodiment, the environmental need response dosing instruction set includes instruc-

tions for dispensing a dose of a calming agent or anti-anxiety medication when one or more other individuals are sensed. In an embodiment, the sensed environment does not include another individual, and the environmental need response dosing instruction set includes instructions for dispensing a dose of a vaccine when the absence of other individuals is sensed. Further, the operation 406 illustrates dispensing a dose of an inhalable compound according to a location need response dosing instruction set. For example, as shown in FIGS. 1A through 1H, the collar 100 may include a memory 154 for storing a location need response dosing instruction set. The collar 100 may also include a sensor module 170 for sensing a location occupied by the subject 102. Based on the sensed location of the subject 102, the processor 156 may be operatively configured to dispense the dose 158 of the compound 104 after verifying that the location corresponds to a location stored in the location need response dosing instruction set. In one instance, a sensed location includes a school zone, and the location need response dosing instruction set includes instructions for dispensing a dose of the compound when the school zone is sensed. In another instance, the sensed location includes a living space, and the location need response dosing instruction set includes instructions for dispensing a dosage of a pheromone (or another substance) for preventing a pet from urinating in the living space. Alternatively, the sensed location may include a litter box, and the dosing instruction set may include instructions for dispensing a pheromone (or another substance) for enticing a pet to defecate in the litter box. Further, the operation 408 illustrates dispensing the inhalable compound in accordance with a dispensing order received by a dispensing module. For example, as shown in FIGS. 1A through 1H, the dispensing module 128 may receive a dispensing order from the processor 156.

In an embodiment, the dispensing order may be dispatched upon the sensor module 170 detecting a condition of the subject, such as an asthmatic incident (e.g., a narrowing of the subject's airways). In an embodiment, the sensor module 170 may identify a symptom of an asthmatic incident, such as a subject experiencing trouble breathing, a sneeze, a cough, a wheeze, a rhonchus, or a snore. In an embodiment, the sensor module 170 may identify a physical condition associated with an asthmatic incident, such as a narrowing of the subject's airways. Other symptoms or conditions detected by the sensor module 170 may include, but are not limited to, Chronic Obstructive Pulmonary Disease (COPD), bronchitis, abnormally high blood glucose level, etc. Further, it will be appreciated that the processor 156 may determine the most effective route of administration for a material based upon a particular condition or set of symptoms. In an embodiment, the processor 156 may determine that an inhalation route of delivery including the nasal cavity is a most effective route of treatment for an asthmatic incident, and may instruct administration of the dose 158 of the material 104 accordingly (e.g., in a case where the dose 158 includes a beta-2 agonist.) In an embodiment, the processor 156 may be programmed to determine whether a to-be-delivered agent should be provided to the subject via intra-nasal administration or inhalation, or both. For example, for a desired delivery of an agent to the brain of the subject, the device may be programmed to administer such agent through intranasal administration.

FIG. 5 illustrates alternative embodiments of the example operational flow 200 of FIG. 2. FIG. 5 illustrates example embodiments where the operation 210 may include at least one additional operation. Additional operations may include an operation 502, an operation 504, and/or an operation 506.

The operation **502** illustrates dispensing a dose of a nutraceutical compound. For example, as shown in FIGS. 1A through 1H, the compound **104** may include a nutraceutical compound **172**.

The operation **504** illustrates dispensing a dose of a therapeutic compound. For example, as shown in FIGS. 1A through 1H, the compound **104** may include a therapeutic compound **174**.

The operation **506** illustrates dispensing a dose of a homeopathic compound. For example, as shown in FIGS. 1A through 1H, the compound **104** may include a homeopathic compound **176**.

FIG. 6 illustrates alternative embodiments of the example operational flow **200** of FIG. 2. FIG. 6 illustrates example embodiments where the operation **210** may include at least one additional operation. Additional operations may include an operation **602**, an operation **604**, and/or an operation **606**.

The operation **602** illustrates generating an aerosol of the inhalable compound. For example, as shown in FIGS. 1A through 1H, the compound **104** may include an aerosol which may be dispensed via the nozzle **130**.

The operation **604** illustrates generating at least one of a vapor or a powder of the inhalable compound. For example, as shown in FIGS. 1A through 1H, the compound **104** may include a vapor which may be dispensed via the suite of nozzles **148**. Alternatively, the compound **104** may include a powder, which may be dispensed via the suite of nozzles **148**. Generating a powder may include, for example, generating particles, fine particles, micronized particles, microparticles, or particulates.

The operation **606** illustrates generating a liquid atomization of the inhalable compound. For example, as shown in FIGS. 1A through 1H, the compound **104** may include an atomized liquid which may be dispensed via the nozzle **130**.

FIG. 7 illustrates alternative embodiments of the example operational flow **200** of FIG. 2. FIG. 7 illustrates example embodiments where the operation **210** may include at least one additional operation. Additional operations may include an operation **702**, an operation **704**, an operation **706**, and/or an operation **708**.

The operation **702** illustrates administering the inhalable compound via spraying a compound. For example, as shown in FIGS. 1A through 1H, the compound **104** may be sprayed via the nozzle **130**.

The operation **704** illustrates administering the inhalable compound via at least one of dusting or powderizing a compound. For example, as shown in FIGS. 1A through 1H, the compound **104** may be dusted via the nozzle **130**. Powderizing the compound may include, for example, deagglomeration, or particularizing.

The operation **706** illustrates administering the inhalable compound via nebulizing a compound. For example, as shown in FIGS. 1A through 1H, the compound **104** may be nebulized and dispensed via the nozzle **130**.

The operation **708** illustrates administering the inhalable compound via vaporizing a compound. For example, as shown in FIGS. 1A through 1H, the compound **104** may be vaporized and dispensed via the nozzle **130**.

In an embodiment, the inhalable compound may include a carrier. For example, a carrier may include a gas carrier, a liquid carrier, or a solid carrier. In embodiments, the carrier may include a hydrocarbon, a fluorocarbon, a propellant, a salt, a saccharide, a lipid, a liposome, a synthetic, or a natural polymer. Further, various formulations including a carrier may include penetration or absorption enhancers.

FIG. 8 illustrates alternative embodiments of the example operational flow **5600** of FIG. 56. FIG. 8 illustrates example

embodiments where the operation **5630** may include at least one additional operation. Additional operations may include an operation **802**, an operation **804**, an operation **806**, and/or an operation **808**.

The operation **802** illustrates receiving a dose of a pharmaceutical compound for dispensing. For example, as shown in FIGS. 1A through 1H, the compound **104** may include a pharmaceutical compound **178**. The pharmaceutical compound **178** may be stored in a reservoir **180** of the collar **100**. The reservoir **180** may receive one or more doses of the pharmaceutical compound **178** for dispensing.

The operation **804** illustrates receiving a dose of a therapeutic compound for dispensing. For example, as shown in FIGS. 1A through 1H, the compound **104** may include a therapeutic compound **174**. The therapeutic compound **174** may be stored in a reservoir **180** of the collar **100**. The reservoir **180** may receive one or more doses of the therapeutic compound **174** for dispensing. Further, the operation **806** illustrates receiving a dosing instruction set. For example, as shown in FIGS. 1A through 1H, the dosing instruction set may be received via the interface **164**. Further, the operation **808** illustrates receiving a dosing instruction set via a wireless transmission. For example, as shown in FIGS. 1A through 1H, the dosing instruction set may be received via the interface **164**, which may include a wireless interface for receiving a wireless transmission.

FIG. 9 illustrates alternative embodiments of the example operational flow **5600** of FIG. 56. FIG. 9 illustrates example embodiments where the operation **5630** may include at least one additional operation. Additional operations may include an operation **902**, and/or an operation **904**. Further, the operation **902** illustrates receiving a dosing instruction set via a processor. For example, as shown in FIGS. 1A through 1H, the processor **156** may receive a dosing instruction set. Further, the operation **904** illustrates receiving a dosing instruction set via a connectable device containing digital instructions or data. For example, as shown in FIGS. 1A through 1H, the collar **100** may receive a dosing instruction set from a connectable device **182** (e.g., a laptop computer, a personal digital assistant (PDA), or a cellular telephone).

FIG. 10 illustrates alternative embodiments of the example operational flow **5600** of FIG. 56. FIG. 10 illustrates example embodiments where the operation **5630** may include at least one additional operation. Additional operations may include an operation **1002**, and/or an operation **1004**. Further, the operation **1002** illustrates receiving a dosing instruction set via a wire transmission. For example, as shown in FIGS. 1A through 1H, the device **182** may be connected to the interface **164** via a wired connection. Further, the operation **1004** illustrates receiving a dosing instruction set via an optical transmission. For example, as shown in FIGS. 1A through 1H, the device **182** may be connected to the interface **164** via an optical connection. For instance, the device **182** may include an optical transmitter (e.g., a light), and the interface **164** may include an optical receiver (e.g., a light sensor).

FIG. 11 illustrates alternative embodiments of the example operational flow **5600** of FIG. 56. FIG. 11 illustrates example embodiments where the operation **5630** may include at least one additional operation. Additional operations may include an operation **1102**, and/or an operation **1104**. Further, the operation **1102** illustrates receiving a dosing instruction set via a radio transmission. For example, as shown in FIGS. 1A through 1H, the device **182** may be connected to the interface **164** via a radio connection. For instance, the device **182** may include a Radio Frequency (RF) transmitter, and the interface **164** may include an RF

receiver. Further, the operation **1104** illustrates receiving a dosing instruction set via a mechanical transmission. For example, as shown in FIGS. 1A through 1H, the device **182** may be connected to the interface **164** via a mechanical connection.

FIG. **12** illustrates alternative embodiments of the example operational flow **5600** of FIG. **56**. FIG. **12** illustrates example embodiments where the operation **5630** may include at least one additional operation. Additional operations may include an operation **1202**, and/or an operation **1204**. Further, the operation **1202** illustrates receiving a dosing instruction set from a user. For example, as shown in FIGS. 1A through 1H, the interface **164** may be utilized to receive a dosing instruction set from a user **166**. Further, the operation **1204** illustrates receiving a dosing instruction set from a health care provider. A health care provider may include, for example, a physician, a physician's assistant, a nurse, a nurse practitioner, a pharmacist, or an emergency medical technician. For example, as shown in FIGS. 1A through 1H, the interface **164** may be utilized to receive a dosing instruction set from a physician **168**.

FIG. **13** illustrates alternative embodiments of the example operational flow **5600** of FIG. **56**. FIG. **13** illustrates example embodiments where the operation **5630** may include at least one additional operation. Additional operations may include an operation **1302**, and/or an operation **1304**. Further, the operation **1302** illustrates receiving a dosing instruction set from a pharmacist. For example, as shown in FIGS. 1A through 1H, the interface **164** may be utilized to receive a dosing instruction set from a pharmacist **184**. Further, the operation **1304** illustrates receiving a dosing instruction set from at least one of a parent or a guardian. For example, as shown in FIGS. 1A through 1H, the interface **164** may be utilized to receive a dosing instruction set from a parent **186**.

FIG. **14** illustrates alternative embodiments of the example operational flow **5600** of FIG. **56**. FIG. **14** illustrates example embodiments where the operation **5630** may include at least one additional operation. Additional operations may include an operation **1402**, and/or an operation **1404**. Further, the operation **1402** illustrates receiving a dosing instruction set from at least one of a pet owner, an animal researcher, or an animal owner. For example, as shown in FIGS. 1A through 1H, the interface **164** may be utilized to receive a dosing instruction set from a pet owner **188**. Further, the operation **1404** illustrates receiving a dosing instruction set from a veterinarian health care provider. A veterinarian health care provider may include, among others, a veterinarian, a veterinarian's assistant, or a veterinarian technician. For example, as shown in FIGS. 1A through 1H, the interface **164** may be utilized to receive a dosing instruction set from a veterinarian **190**. In an embodiment, the interface **164**, may be utilized to receive a dosing instruction set from a researcher.

FIG. **15** illustrates alternative embodiments of the example operational flow **5600** of FIG. **56**. FIG. **15** illustrates example embodiments where the operation **5630** may include at least one additional operation. Additional operations may include an operation **1502**. Further, the operation **1502** illustrates receiving a dosing instruction set from a medical response unit. For example, as shown in FIGS. 1A through 1H, the interface **164** may be utilized to receive a dosing instruction set from a medical response unit **192**.

FIG. **16** illustrates alternative embodiments of the example operational flow **5600** of FIG. **56**. FIG. **16** illustrates example embodiments where the operation **5630** may

include at least one additional operation. Additional operations may include an operation **1602**, and/or an operation **1604**.

The operation **1602** illustrates receiving a dose of a homeopathic compound for dispensing. For example, as shown in FIGS. 1A through 1H, the compound **104** may include one or more homeopathic compounds **176**.

The operation **1604** illustrates receiving a dose of a nutraceutical compound for dispensing. For example, as shown in FIGS. 1A through 1H, the compound **104** may include one or more nutraceutical compounds **172**.

FIG. **17** illustrates alternative embodiments of the example operational flow **5700** of FIG. **57**. FIG. **17** illustrates example embodiments where the operation **5730** may include at least one additional operation. Additional operations may include an operation **1702**, an operation **1704**, and/or an operation **1706**.

The operation **1702** illustrates receiving the inhalable compound in a reservoir. For example, as shown in FIGS. 1A through 1H, the compound **104** may be received in a reservoir **180**. Further, the operation **1704** illustrates monitoring a quantity of the inhalable compound in the reservoir. For example, as shown in FIGS. 1A through 1H, the processor **156** may be utilized to monitor the compound **104** in the reservoir **180**. Further, the operation **1706** illustrates logging a quantity of the inhalable compound in the reservoir. For example, as shown in FIGS. 1A through 1H, the processor **156** may be utilized to monitor the compound **104** in the reservoir **180**, and the memory **154** may be utilized to keep a log of a quantity of the compound **104** in the reservoir **180**.

FIG. **18** illustrates alternative embodiments of the example operational flow **5700** of FIG. **57**. FIG. **18** illustrates example embodiments where the operation **5730** may include at least one additional operation. Additional operations may include an operation **1802**, and/or an operation **1804**. Further, the operation **1802** illustrates logging a quantity of the inhalable compound dispensed from the reservoir. For example, as shown in FIGS. 1A through 1H, the processor **156** may be utilized to monitor an amount of the compound **104** dispensed from the reservoir **180**, and the memory **154** may be utilized to keep a log of a quantity of the compound **104** dispensed from the reservoir **180**. Further, the operation **1804** illustrates logging a time of the inhalable compound dispensed from the reservoir. For example, as shown in FIGS. 1A through 1H, the processor **156** may be utilized to monitor a time of dispensing the compound **104** from the reservoir **180** (e.g., by utilizing the time keeping module **162**), and the memory **154** may be utilized to keep a log of a time of dispensing the compound **104** from the reservoir **180**.

FIG. **19** illustrates alternative embodiments of the example operational flow **5700** of FIG. **57**. FIG. **19** illustrates example embodiments where the operation **5730** may include at least one additional operation. Additional operations may include an operation **1902**, and/or an operation **1904**. Further, the operation **1902** illustrates logging a dispersion pattern of the inhalable compound dispensed from the reservoir. For example, as shown in FIGS. 1A through 1H, the collar **100** may include a camera **194** for monitoring a dispersion pattern of the dispensed compound **104**, and the memory **154** may be utilized to log the dispersion pattern. Further, the operation **1904** illustrates logging a species of the inhalable compound dispensed from the reservoir. For example, as shown in FIGS. 1A through 1H, the processor **156** may be utilized to determine a species of the compound

104 dispensed from the reservoir **180**, and the memory **154** may be utilized to log the determined species.

FIG. **20** illustrates alternative embodiments of the example operational flow **5700** of FIG. **57**. FIG. **20** illustrates example embodiments where the operation **5730** may include at least one additional operation. Additional operations may include an operation **2002**. Further, the operation **2002** illustrates transmitting a set of logged reservoir information to an external location. For example, as shown in FIGS. **1A** through **1H**, the information logged by the memory **154** may be transmitted to an external location via the interface **164**.

FIG. **21** illustrates alternative embodiments of the example operational flow **5700** of FIG. **57**. FIG. **21** illustrates example embodiments where the operation **5730** may include at least one additional operation. Additional operations may include an operation **2102**, and/or an operation **2104**. Further, the operation **2102** illustrates activating an alert when a quantity threshold of the inhalable compound in the reservoir is achieved. For example, as shown in FIGS. **1A** through **1H**, the collar **100** may include a visual indicator **196** for issuing an alert when a quantity threshold of the compound **104** is achieved (e.g., as determined by the processor **156**). Further, the operation **2104** illustrates activating a visual alert when a quantity threshold of the inhalable compound in the reservoir is achieved. For example, as shown in FIGS. **1A** through **1H**, the visual indicator **196** may be activated when a quantity threshold of the compound **104** is achieved.

FIG. **22** illustrates alternative embodiments of the example operational flow **5700** of FIG. **57**. FIG. **22** illustrates example embodiments where the operation **5730** may include at least one additional operation. Additional operations may include an operation **2202**. Further, the operation **2202** illustrates activating an auditory alert when a quantity threshold of the inhalable compound in the reservoir is achieved. For example, as shown in FIGS. **1A** through **1H**, the collar **100** may include an audible indicator **198** for issuing an auditory alert when a quantity threshold of the compound **104** is achieved.

FIG. **23** illustrates alternative embodiments of the example operational flow **5700** of FIG. **57**. FIG. **23** illustrates example embodiments where the operation **5730** may include at least one additional operation. Additional operations may include an operation **2302**. Further, the operation **2302** illustrates activating an electronic alert when a quantity threshold of the inhalable compound in the reservoir is achieved. For example, as shown in FIGS. **1A** through **1H**, the collar **100** may include an electronic indicator **50** for issuing an electronic alert when a quantity threshold of the compound **104** is achieved.

FIG. **24** illustrates alternative embodiments of the example operational flow **5700** of FIG. **57**. FIG. **24** illustrates example embodiments where the operation **5730** may include at least one additional operation. Additional operations may include an operation **2402**, an operation **2404**, and/or an operation **2406**.

The operation **2402** illustrates receiving the inhalable compound in a reloadable reservoir. For example, as shown in FIGS. **1A** through **1H**, the reservoir **180** may include one or more reloadable reservoirs.

The operation **2404** illustrates receiving the inhalable compound in at least one of a disposable reservoir or a multi-component reservoir. For example, as shown in FIGS. **1A** through **1H**, the reservoir **180** may include one or more disposable reservoirs.

The operation **2406** illustrates receiving the inhalable compound in a multi-compound reservoir. For example, as shown in FIGS. **1A** through **1H**, the reservoir **180** may include one or more compounds, such as a first compound **104** and a second compound.

FIG. **25** illustrates alternative embodiments of the example operational flow **5700** of FIG. **57**. FIG. **25** illustrates example embodiments where the operation **5730** may include at least one additional operation. Additional operations may include an operation **2502**, an operation **2504**, and/or an operation **2506**.

The operation **2502** illustrates receiving the inhalable compound in a single compound reservoir. For example, as shown in FIGS. **1A** through **1H**, the reservoir **180** may include a single compound, such as the first compound **104**.

The operation **2504** illustrates receiving the inhalable compound in a dispensing reservoir. For example, as shown in FIGS. **1A** through **1H**, the compound **104** received in the reservoir **180** may be an inhalable compound.

The operation **2506** illustrates receiving the inhalable compound in a modular reservoir. For example, as shown in FIGS. **1A** through **1H**, the reservoir **180** may include a module reservoir.

FIG. **26** illustrates alternative embodiments of the example operational flow **5700** of FIG. **57**. FIG. **26** illustrates example embodiments where the operation **5730** may include at least one additional operation. Additional operations may include an operation **2602**, and/or an operation **2604**.

The operation **2602** illustrates receiving the inhalable compound in a programmable reservoir. For example, as shown in FIGS. **1A** through **1H**, the reservoir **180** may include a programmable reservoir, which may be programmable via the processor **156**.

The operation **2604** illustrates receiving the inhalable compound in a weighted reservoir. For example, as shown in FIGS. **1A** through **1H**, the reservoir **180** may include a weighted reservoir, which may be weighted with a weight **136**.

FIG. **27** illustrates alternative embodiments of the example operational flow **5900** of FIG. **59**. FIG. **27** illustrates example embodiments where the operation **5930** may include at least one additional operation. Additional operations may include an operation **2702**, an operation **2704**, and/or an operation **2706**.

The operation **2702** illustrates disposing the hands-free aerosol delivery system substantially around a portion of the body of a mammal. For example, as shown in FIGS. **1A** through **1H**, the collar **100** may encircle the neck portion **106** of a subject **102**. Further, the operation **2704** illustrates encircling a neck portion of the body of a mammal with a support member of the hands-free aerosol delivery device. For example, as shown in FIGS. **1A** through **1H**, the collar **100** may encircle the neck portion **106** of a subject **102**. Further, the operation **2706** illustrates encircling a wrist portion of the body of a mammal with a support member of the hands-free aerosol delivery device. For example, as shown in FIGS. **1A** through **1H**, the collar **100** may encircle the wrist portion **108** of a subject **102**.

FIG. **28** illustrates alternative embodiments of the example operational flow **5900** of FIG. **59**. FIG. **28** illustrates example embodiments where the operation **5930** may include at least one additional operation. Additional operations may include an operation **2802**, and/or an operation **2804**. Further, the operation **2802** illustrates encircling a chest portion of the body of a mammal with a support member of the hands-free aerosol delivery device. For

example, as shown in FIGS. 1A through 1H, the collar 100 may encircle a chest portion 110 of the subject 102. Further, the operation 2804 illustrates encircling a head portion of the body of a mammal with a support member of the hands-free aerosol delivery device. For example, as shown in FIGS. 1A through 1H, the collar 100 may encircle a head portion 112 of the subject 102.

FIG. 29 illustrates alternative embodiments of the example operational flow 5900 of FIG. 59. FIG. 29 illustrates example embodiments where the operation 5930 may include at least one additional operation. Additional operations may include an operation 2902, and/or an operation 2904. Further, the operation 2902 illustrates connecting a first end of a support member of a hands-free aerosol delivery device to a second end of a support member of a hands-free aerosol delivery device while creating a circle about the body part of a mammal. For example, as shown in FIGS. 1A through 1H, the collar 100 may comprise a support member having a first end 114 and a second end 116. The first end 114 may be connected to the second end 116, encircling and creating a closed loop (e.g., a circle) about the body part of the subject 102. Further, the operation 2904 illustrates connecting the first end of a support member of the hands-free aerosol delivery device to the second end of a support member of the hands-free aerosol delivery device via a magnet. For example, as shown in FIGS. 1A through 1H, the first end 114 may be connected to the second end 116 via a magnet 118.

FIG. 30 illustrates alternative embodiments of the example operational flow 5900 of FIG. 59. FIG. 30 illustrates example embodiments where the operation 5930 may include at least one additional operation. Additional operations may include an operation 3002. Further, the operation 3002 illustrates connecting the first end of a support member of the hands-free aerosol delivery device to the second end of a support member of the hands-free aerosol delivery device via a hook. For example, as shown in FIGS. 1A through 1H, the first end 114 of the collar 100 may be connected to the second end 116 of the collar 100 via a hook 120.

FIG. 31 illustrates alternative embodiments of the example operational flow 5900 of FIG. 59. FIG. 31 illustrates example embodiments where the operation 5930 may include at least one additional operation. Additional operations may include an operation 3102. Further, the operation 3102 illustrates connecting the first end of a support member of the hands-free aerosol delivery device to the second end of a support member of the hands-free aerosol delivery device via a snap connection. For example, as shown in FIGS. 1A through 1H, the first end 114 may be connected to the second end 116 via a snap connection 122.

FIG. 32 illustrates alternative embodiments of the example operational flow 5900 of FIG. 59. FIG. 32 illustrates example embodiments where the operation 5930 may include at least one additional operation. Additional operations may include an operation 3202. Further, the operation 3202 illustrates connecting the first end of a support member of the hands-free aerosol delivery device to the second end of a support member of the hands-free aerosol delivery device via a threaded connection. For example, as shown in FIGS. 1A through 1H, the first end 114 of the collar 100 may be connected to the second end 116 of the collar 100 via a threaded connection 124.

FIG. 33 illustrates alternative embodiments of the example operational flow 5900 of FIG. 59. FIG. 33 illustrates example embodiments where the operation 5930 may include at least one additional operation. Additional operations may include an operation 3302. Further, the operation 3302 illustrates connecting the first end of a support member of the hands-free aerosol delivery device to the second end of a support member of the hands-free aerosol delivery device via a belt-like connection. For example, as shown in FIGS. 1A through 1H, the first end 114 may be connected to the second end 116 via a belt-like connection 126.

FIG. 34 illustrates alternative embodiments of the example operational flow 6000 of FIG. 60. FIG. 34 illustrates example embodiments where the operation 6010 may include at least one additional operation. Additional operations may include an operation 3402, an operation 3404, and/or an operation 3406.

The operation 3402 illustrates detecting a blood glucose level in the mammal. For example, as shown in FIGS. 1A through 1H, the sensor module 170 may be utilized to detect a blood glucose level in the subject 102.

The operation 3404 illustrates detecting a blood oxygen level in the mammal. For example, as shown in FIGS. 1A through 1H, the sensor module 170 may be utilized to detect a blood oxygen level in the subject 102.

The operation 3406 illustrates detecting an infection in the mammal. For example, as shown in FIGS. 1A through 1H, the sensor module 170 may be utilized to detect an infection in the subject 102.

FIG. 35 illustrates alternative embodiments of the example operational flow 6000 of FIG. 60. FIG. 35 illustrates example embodiments where the operation 6010 may include at least one additional operation. Additional operations may include an operation 3502, an operation 3504, and/or an operation 3506.

The operation 3502 illustrates detecting vascular dysfunction in the mammal. For example, as shown in FIGS. 1A through 1H, the sensor module 170 may be utilized to detect a vascular dysfunction in the subject 102.

The operation 3504 illustrates detecting blood flow in the mammal. For example, as shown in FIGS. 1A through 1H, the sensor module 170 may be utilized to detect blood flow in the subject 102.

The operation 3506 illustrates detecting respiratory minute volume in the mammal. For example, as shown in FIGS. 1A through 1H, the sensor module 170 may be utilized to detect a respiratory volume in the subject 102. In an embodiment, the sensor module 170 may be utilized to detect a sneeze of the subject 102. In an embodiment, the sensor module 170 may be utilized to detect a cough of the subject 102. In an embodiment, the sensor module 170 may be utilized to detect a wheeze of the subject 102. In an embodiment, the sensor module 170 may be utilized to detect a rhonchus of the subject 102. In an embodiment, the sensor module 170 may be utilized to detect a snore of the subject 102. In an embodiment, the sensor module 170 may be utilized to detect a temperature (e.g., a body temperature) of the subject 102. In an embodiment, the sensor module 170 may be utilized to detect an expelled gas from the subject 102, such as a gas exhaled by the subject.

FIG. 36 illustrates an operational flow 3600 representing example operations related to maintaining a hands-free article for dispensing an inhalable compound according to a dosing instruction set, where the hands-free article is maintained in an operable dispensing position. FIG. 36 illustrates an example embodiment where the example operational flow 200 of FIG. 2 may include at least one additional operation. Additional operations may include an operation 3610.

After a start operation, an operation 210, and an operation 220, the operational flow 3600 moves to an operation 3610.

Operation **3610** illustrates dispensing a dose of a pharmaceutical compound. For example, as shown in FIGS. **1A** through **1H**, the collar **100** may be utilized to dispense a dose **158** of a pharmaceutical compound **178** to the subject **102**.

FIG. **37** illustrates an operational flow **3700** representing example operations related to maintaining a hands-free article for dispensing an inhalable compound according to a dosing instruction set, where the hands-free article is maintained in an operable dispensing position. FIG. **37** illustrates an example embodiment where the example operational flow **200** of FIG. **2** may include at least one additional operation. Additional operations may include an operation **3710**.

After a start operation, an operation **210**, and an operation **220**, the operational flow **3700** moves to an operation **3710**. Operation **3710** illustrates directing issuance of a dispensing order. For example, as shown in FIGS. **1A** through **1H**, the processor **156** may direct issuance of a dispensing order (e.g., to the pump **160**).

FIG. **38** illustrates alternative embodiments of the example operational flow **200** of FIG. **2**. FIG. **38** illustrates example embodiments where the operation **210** may include at least one additional operation. Additional operations may include an operation **3802**, an operation **3804**, and/or an operation **3806**. Further, the operation **3802** illustrates accepting a dosing instruction set from a user. For example, as shown in FIGS. **1A** through **1H**, the interface **164** may be utilized to receive a dosing instruction set from a user **166**. Further, the operation **3804** illustrates accepting a dosing instruction set from at least one of a physician, a health care provider, a physician's assistant, a nurse, a nurse practitioner, a registered nurse, a licensed practical nurse, a pharmacist, or an emergency responder. For example, as shown in FIGS. **1A** through **1H**, the interface **164** may be utilized to receive a dosing instruction set from a physician **168**. Further, the operation **3806** illustrates accepting a dosing instruction set from a medical response unit. For example, as shown in FIGS. **1A** through **1H**, the interface **164** may be utilized to receive a dosing instruction set from a medical response unit **192**.

FIG. **39** illustrates alternative embodiments of the example operational flow **200** of FIG. **2**. FIG. **39** illustrates example embodiments where the operation **210** may include at least one additional operation. Additional operations may include an operation **3902**, an operation **3904**, and/or an operation **3906**. Further, the operation **3902** illustrates validating a dosing instruction set for performing a function. For example, as shown in FIGS. **1A** through **1H**, the processor **156** may be utilized to validate a dosing instruction set (e.g., by check the dosing instruction set against information stored in the memory **154**). Further, the operation **3904** illustrates translating a dosing instruction set for performing a function into a dispensing order. For example, as shown in FIGS. **1A** through **1H**, the processor **156** may be utilized to translate a dosing instruction set into a dispensing order (e.g., by referencing the dosing instruction set to a lookup table stored in the memory **154**). Further, the operation **3906** illustrates translating a medical parameter into a dispensing order. For example, as shown in FIGS. **1A** through **1H**, the processor **156** may be utilized to translate a medical parameter into a dispensing order (e.g., by referencing the medical parameter to a lookup table stored in the memory **154**).

FIG. **40** illustrates alternative embodiments of the example operational flow **200** of FIG. **2**. FIG. **40** illustrates example embodiments where the operation **210** may include at least one additional operation. Additional operations may include an operation **4002**, an operation **4004**, and/or an

operation **4006**. Further, the operation **4002** illustrates generating a dispensing order according to the instruction set from a user. For example, as shown in FIGS. **1A** through **1H**, the processor **156** may be utilized to generate a dispensing order according to an instruction set from a user **166** stored in the memory **154**. Further, the operation **4004** illustrates generating a dispensing order according to the instruction set from a health care professional. For example, as shown in FIGS. **1A** through **1H**, the processor **156** may be utilized to generate a dispensing order according to an instruction set from a physician **168** stored in the memory **154**. Further, the operation **4006** illustrates generating a dispensing order according to the instruction set from a medical response unit. For example, as shown in FIGS. **1A** through **1H**, the processor **156** may be utilized to generate a dispensing order according to an instruction set from a medical response unit **192** stored in the memory **154**.

FIG. **41** illustrates alternative embodiments of the example operational flow **200** of FIG. **2**. FIG. **41** illustrates example embodiments where the operation **210** may include at least one additional operation. Additional operations may include an operation **4102**. Further, the operation **4102** illustrates requesting a dose of the inhalable compound in accordance with a dispensing order received by a dispensing module from a reservoir. For example, as shown in FIGS. **1A** through **1H**, the dispensing module **128** may receive a request from the reservoir **180** for a dose of the compound **104**.

FIG. **42** illustrates an operational flow **4200** representing example operations related to maintaining a hands-free article for dispensing an inhalable compound according to a dosing instruction set, where the hands-free article is maintained in an operable dispensing position. FIG. **42** illustrates an example embodiment where the example operational flow **200** of FIG. **2** may include at least one additional operation. Additional operations may include an operation **4210**.

After a start operation, an operation **210**, and an operation **220**, the operational flow **4200** moves to an operation **4210**. Operation **4210** illustrates transmitting a dispensing order to a dispensing module. For example, as shown in FIGS. **1A** through **1H**, the processor **156** may transmit a dispensing order to the dispensing module **128** (e.g., to the reservoir **180**).

FIG. **43** illustrates an operational flow **4300** representing example operations related to maintaining a hands-free article for dispensing an inhalable compound according to a dosing instruction set, where the hands-free article is maintained in an operable dispensing position. FIG. **43** illustrates an example embodiment where the example operational flow **200** of FIG. **2** may include at least one additional operation. Additional operations may include an operation **4310**.

After a start operation, an operation **210**, and an operation **220**, the operational flow **4300** moves to an operation **4310**. Operation **4310** illustrates transmitting a dispensing order to a dispensing module via a wireless transmission. For example, as shown in FIGS. **1A** through **1H**, the dispensing module **128** may receive a dispensing order from a physician **168** via a wireless transmission received by the interface **164**.

FIG. **44** illustrates an operational flow **4400** representing example operations related to maintaining a hands-free article for dispensing an inhalable compound according to a dosing instruction set, where the hands-free article is maintained in an operable dispensing position. FIG. **44** illustrates an example embodiment where the example operational

flow **200** of FIG. **2** may include at least one additional operation. Additional operations may include an operation **4410**.

After a start operation, an operation **210**, and an operation **220**, the operational flow **4400** moves to an operation **4410**. Operation **4410** illustrates transmitting a dispensing order to a dispensing module via an optical transmission. For example, as shown in FIGS. **1A** through **1H**, the dispensing module **128** may receive a dispensing order from a physician **168** via an optical transmission received by the interface **164**.

FIG. **45** illustrates an operational flow **4500** representing example operations related to maintaining a hands-free article for dispensing an inhalable compound according to a dosing instruction set, where the hands-free article is maintained in an operable dispensing position. FIG. **45** illustrates an example embodiment where the example operational flow **200** of FIG. **2** may include at least one additional operation. Additional operations may include an operation **4510**.

After a start operation, an operation **210**, and an operation **220**, the operational flow **4500** moves to an operation **4510**. Operation **4510** illustrates transmitting a dispensing order to a dispensing module via a wire transmission. For example, as shown in FIGS. **1A** through **1H**, the dispensing module **128** may receive a dispensing order from a physician **168** via a wire transmission received by the interface **164**.

FIG. **46** illustrates an operational flow **4600** representing example operations related to maintaining a hands-free article for dispensing an inhalable compound according to a dosing instruction set, where the hands-free article is maintained in an operable dispensing position. FIG. **46** illustrates an example embodiment where the example operational flow **200** of FIG. **2** may include at least one additional operation. Additional operations may include an operation **4610**.

After a start operation, an operation **210**, and an operation **220**, the operational flow **4600** moves to an operation **4610**. Operation **4610** illustrates transmitting a dispensing order to a dispensing module via a mechanical transmission. For example, as shown in FIGS. **1A** through **1H**, the dispensing module **128** may receive a dispensing order from a physician **168** via a mechanical transmission received by the interface **164**.

FIG. **47** illustrates an operational flow **4700** representing example operations related to maintaining a hands-free article for dispensing an inhalable compound according to a dosing instruction set, where the hands-free article is maintained in an operable dispensing position. FIG. **47** illustrates an example embodiment where the example operational flow **200** of FIG. **2** may include at least one additional operation. Additional operations may include an operation **4710**.

After a start operation, an operation **210**, and an operation **220**, the operational flow **4700** moves to an operation **4710**. Operation **4710** illustrates transmitting a dispensing order to a dispensing module via a radio transmission. For example, as shown in FIGS. **1A** through **1H**, the dispensing module **128** may receive a dispensing order from a physician **168** via a radio transmission received by the interface **164**.

FIG. **48** illustrates an operational flow **4800** representing example operations related to maintaining a hands-free article for dispensing an inhalable compound according to a dosing instruction set, where the hands-free article is maintained in an operable dispensing position. FIG. **48** illustrates an example embodiment where the example operational

flow **200** of FIG. **2** may include at least one additional operation. Additional operations may include an operation **4810**.

After a start operation, an operation **210**, and an operation **220**, the operational flow **4800** moves to an operation **4810**. Operation **4810** illustrates transmitting a dispensing order to a dispensing module via a processor transmission. For example, as shown in FIGS. **1A** through **1H**, the dispensing module **128** may receive a dispensing order from the processor **156**.

FIG. **49** illustrates an operational flow **4900** representing example operations related to maintaining a hands-free article for dispensing an inhalable compound according to a dosing instruction set, where the hands-free article is maintained in an operable dispensing position. FIG. **49** illustrates an example embodiment where the example operational flow **200** of FIG. **2** may include at least one additional operation. Additional operations may include an operation **4910**, an operation **4912**, an operation **4914**, and/or an operation **4916**.

After a start operation, an operation **210**, and an operation **220**, the operational flow **4900** moves to an operation **4910**. Operation **4910** illustrates controlling delivery of an inhalable compound. For example, as shown in FIGS. **1A** through **1H**, the demand valve **152** may be utilized to control delivery of the compound **104**.

The operation **4912** illustrates selecting one or more delivery nozzles from a suite of nozzles. For example, as shown in FIGS. **1A** through **1H**, the second nozzle **150** may be selected from the suite of nozzles **148**.

The operation **4914** illustrates directing delivery of the inhalable compound from one or more nozzles at different locations. For example, as shown in FIGS. **1A** through **1H**, the compound **104** may be delivered from the first nozzle **130** or the second nozzle **150**.

The operation **4916** illustrates directing delivery of the inhalable compound by controlling a discharge direction. For example, as shown in FIGS. **1A** through **1H**, the direction of the subject's nose **132** may be calculated. Then, a discharge direction for the dispensing module **128** may be controlled for optimizing delivery of the compound **104**.

FIG. **50** illustrates alternative embodiments of the example operational flow **4900** of FIG. **49**. FIG. **50** illustrates example embodiments where the operation **4910** may include at least one additional operation. Additional operations may include an operation **5002**, an operation **5004**, and/or an operation **5006**.

The operation **5002** illustrates directing delivery via a demand valve coupled with programmable dosing. For example, as shown in FIGS. **1A** through **1H**, the demand valve **152** may be operatively configured to dispense the compound **104** in accordance with a dosing schedule stored in the memory **154**.

The operation **5004** illustrates directing delivery via a charged particle dispersion. For example, as shown in FIGS. **1A** through **1H**, the dispensing module **128** may dispense the compound **104** as a charged particle dispersion.

The operation **5006** illustrates directing delivery via a nozzle comprising variable discharge characteristics. For example, as shown in FIGS. **1A** through **1H**, the first nozzle **130**, the second nozzle **150**, or the suite of nozzles **148** may include nozzles having variable discharge characteristics, such as directional, volumetric, spray area, or other characteristics.

FIG. **51** illustrates alternative embodiments of the example operational flow **200** of FIG. **2**. FIG. **51** illustrates example embodiments where the operation **220** may include

at least one additional operation. Additional operations may include an operation **5102**, an operation **5104**, and/or an operation **5106**.

The operation **5102** illustrates orienting a dispensing module to optimize respiratory receipt of an inhalable compound. For example, as shown in FIGS. **1A** through **1H**, the dispensing module **128** may be maintained in an optimal position for optimizing delivery of the compound **104** to the subject **102**.

The operation **5104** illustrates maintaining a dispensing module in position to optimize respiratory receipt of an inhalable compound. For example, as shown in FIGS. **1A** through **1H**, the orientation of the nozzle **130** may be maintained in the direction determined for the subject's nose **132**.

The operation **5106** illustrates determining a relative position or direction to a desired respiratory target. For example, as shown in FIGS. **1A** through **1H**, the direction to the subject's nose **132** may be calculated.

FIG. **52** illustrates alternative embodiments of the example operational flow **200** of FIG. **2**. FIG. **52** illustrates example embodiments where the operation **220** may include at least one additional operation. Additional operations may include an operation **5202**, an operation **5204**, and/or an operation **5206**.

The operation **5202** illustrates maintaining a position of the dispensing module via a weight. For example, as shown in FIGS. **1A** through **1H**, the position of the dispensing module **128** may be maintained via a weight **136**.

The operation **5204** illustrates maintaining a position of the dispensing module via an adhesive. For example, as shown in FIGS. **1A** through **1H**, the position of the dispensing module may be maintained via an adhesive **138**.

The operation **5206** illustrates maintaining a position of the dispensing module via a slide. For example, as shown in FIGS. **1A** through **1H**, the position of the dispensing module **128** may be maintained via a slide **140**.

FIG. **53** illustrates alternative embodiments of the example operational flow **200** of FIG. **2**. FIG. **53** illustrates example embodiments where the operation **220** may include at least one additional operation. Additional operations may include an operation **5302**, an operation **5304**, and/or an operation **5306**.

The operation **5302** illustrates maintaining a position of the dispensing module via a magnet. For example, as shown in FIGS. **1A** through **1H**, the position of the dispensing module **128** may be maintained via a magnet **142**.

The operation **5304** illustrates maintaining a position of the dispensing module via a fastener. For example, as shown in FIGS. **1A** through **1H**, the position of the dispensing module **128** may be maintained via a fastener **144** (e.g., a button or a snap).

The operation **5306** illustrates maintaining a position of the dispensing module via a spring. For example, as shown in FIG. **1A** through **1H**, the position of the dispensing module **128** may be maintained via a spring **146**.

FIG. **54** illustrates an operational flow **5400** representing example operations related to maintaining a hands-free article for dispensing an inhalable compound according to a dosing instruction set, where the hands-free article is maintained in an operable dispensing position. FIG. **54** illustrates an example embodiment where the example operational flow **200** of FIG. **2** may include at least one additional operation. Additional operations may include an operation **5410**, an operation **5412**, an operation **5414**, and/or an operation **5416**.

After a start operation, an operation **210**, and an operation **220**, the operational flow **5400** moves to an operation **5410**. Operation **5410** illustrates dispensing a tracer compound in association with the inhalable compound. For example, as shown in FIGS. **1A** through **1H**, the compound **104** may comprise an inhalable compound **52** and one or more tracer compounds.

The operation **5412** illustrates dispensing a visual tracer compound. For example, as shown in FIGS. **1A** through **1H**, the compound **104** may include a visual tracer **54**.

The operation **5414** illustrates dispensing an olfactory tracer compound. For example, as shown in FIGS. **1A** through **1H**, the compound **104** may include an olfactory tracer **56**.

The operation **5416** illustrates dispensing a tastable tracer compound. For example, as shown in FIGS. **1A** through **1H**, the compound **104** may include a tastable tracer **58**.

FIG. **55** illustrates an operational flow **5500** representing example operations related to maintaining a hands-free article for dispensing an inhalable compound according to a dosing instruction set, where the hands-free article is maintained in an operable dispensing position. FIG. **55** illustrates an example embodiment where the example operational flow **200** of FIG. **2** may include at least one additional operation. Additional operations may include an operation **5510**, an operation **5512**, an operation **5514**, an operation **5516**, and/or an operation **5518**.

After a start operation, an operation **210**, and an operation **220**, the operational flow **5500** moves to an operation **5510**. Operation **5510** illustrates providing an externally observable indication of dispensing of the inhalable compound. For example, as shown in FIGS. **1A** through **1H**, the collar **100** may include a visual indicator **196** for indicating dispensing of the inhalable compound.

The operation **5512** illustrates providing a visual indication of dispensing of the inhalable compound. For example, as shown in FIGS. **1A** through **1H**, the collar **100** may include the visual indicator **196** for indicating dispensing of the inhalable compound.

The operation **5514** illustrates providing an auditory indication of dispensing of the inhalable compound. For example, as shown in FIGS. **1A** through **1H**, the collar **100** may include an audible indicator **198**.

The operation **5516** illustrates providing a vibrational indication of dispensing of the inhalable compound. For example, as shown in FIGS. **1A** through **1H**, the collar **100** may include a vibrational indicator **60**.

The operation **5518** illustrates providing an electromagnetic indication of dispensing of the inhalable compound. For example, as shown in FIGS. **1A** through **1H**, the collar **100** may include an electromagnetic indicator **62**.

FIG. **56** illustrates an operational flow **5600** representing example operations related to maintaining a hands-free article for dispensing an inhalable compound according to a dosing instruction set, where the hands-free article is maintained in an operable dispensing position. In FIG. **56** and in following figures that include various examples of operational flows, discussion and explanation may be provided with respect to the above-described examples of FIGS. **1A** through **1H**, and/or with respect to other examples and contexts. However, it should be understood that the operational flows may be executed in a number of other environments and contexts, and/or in modified versions of FIGS. **1A** through **1H**. Also, although the various operational flows are presented in the sequence(s) illustrated, it should be under-

stood that the various operations may be performed in other orders than those which are illustrated, or may be performed concurrently.

After a start operation, the operational flow **5600** moves to an operation **5610**. Operation **5610** depicts dispensing for inhalation by a user a dose of an inhalable compound according to a dosing instruction set. For example, as shown in FIGS. **1A** through **1H**, the collar **100** may dispense a dose **158** of a compound **104** according to a dosing instruction set stored in a memory **154**.

Then, operation **5620** depicts maintaining in physical association with the user a hands-free article for dispensing an inhalable compound in an operable dispensing position. For example, as shown in FIGS. **1A** through **1H**, the collar **100** may be maintained in an operable dispensing position with an adhesive **138**.

Then, operation **5630** depicts receiving the dose of the inhalable compound for dispensing. For example, as shown in FIGS. **1A** through **1H**, the compound **104** may be received via the reservoir **180**.

FIG. **57** illustrates an operational flow **5700** representing example operations related to maintaining a hands-free article for dispensing an inhalable compound according to a dosing instruction set, where the hands-free article is maintained in an operable dispensing position. In FIG. **57** and in following figures that include various examples of operational flows, discussion and explanation may be provided with respect to the above-described examples of FIGS. **1A** through **1H**, and/or with respect to other examples and contexts. However, it should be understood that the operational flows may be executed in a number of other environments and contexts, and/or in modified versions of FIGS. **1A** through **1H**. Also, although the various operational flows are presented in the sequence(s) illustrated, it should be understood that the various operations may be performed in other orders than those which are illustrated, or may be performed concurrently.

After a start operation, the operational flow **5700** moves to an operation **5710**. Operation **5710** depicts dispensing for inhalation by a user a dose of an inhalable compound according to a dosing instruction set. For example, as shown in FIGS. **1A** through **1H**, the collar **100** may dispense a dose **158** of a compound **104** according to a dosing instruction set stored in a memory **154**.

Then, operation **5720** depicts maintaining in physical association with the user a hands-free article for dispensing an inhalable compound in an operable dispensing position. For example, as shown in FIGS. **1A** through **1H**, the collar **100** may be maintained in an operable dispensing position with an adhesive **138**.

Then, operation **5730** depicts receiving the inhalable compound. For example, as shown in FIGS. **1A** through **1H**, the compound **104** may be received via the reservoir **180**.

FIG. **58** illustrates an operational flow **5800** representing example operations related to maintaining a hands-free article for dispensing an inhalable compound according to a dosing instruction set, where the hands-free article is maintained in an operable dispensing position. FIG. **58** illustrates an example embodiment where the example operational flow **5700** of FIG. **57** may include at least one additional operation. Additional operations may include an operation **5810**.

After a start operation, an operation **5710**, an operation **5720**, and an operation **5730**, the operational flow **5800** moves to an operation **5810**. Operation **5810** illustrates containing the inhalable compound in a reservoir. For

example, as shown in FIGS. **1A** through **1H**, the compound **104** may be contained in the reservoir **180**.

FIG. **59** illustrates an operational flow **5900** representing example operations related to maintaining a hands-free article for dispensing an inhalable compound according to a dosing instruction set, where the hands-free article is maintained in an operable dispensing position. In FIG. **59** and in following figures that include various examples of operational flows, discussion and explanation may be provided with respect to the above-described examples of FIGS. **1A** through **1H**, and/or with respect to other examples and contexts. However, it should be understood that the operational flows may be executed in a number of other environments and contexts, and/or in modified versions of FIGS. **1A** through **1H**. Also, although the various operational flows are presented in the sequence(s) illustrated, it should be understood that the various operations may be performed in other orders than those which are illustrated, or may be performed concurrently.

After a start operation, the operational flow **5900** moves to an operation **5910**. Operation **5910** depicts dispensing for inhalation by a user a dose of an inhalable compound according to a dosing instruction set. For example, as shown in FIGS. **1A** through **1H**, the collar **100** may dispense a dose **158** of a compound **104** according to a dosing instruction set stored in a memory **154**.

Then, operation **5920** depicts maintaining in physical association with the user a hands-free article for dispensing an inhalable compound in an operable dispensing position. For example, as shown in FIGS. **1A** through **1H**, the collar **100** may be maintained in an operable dispensing position with an adhesive **138**.

Then, operation **5930** depicts supporting a hands-free aerosol delivery system on the body of a mammal. For example, as shown in FIGS. **1A** through **1H**, the collar **100** may be supported on the body of the subject **102**.

FIG. **60** illustrates an operational flow **6000** representing example operations related to maintaining a hands-free article for dispensing an inhalable compound according to a dosing instruction set, where the hands-free article is maintained in an operable dispensing position. In FIG. **60** and in following figures that include various examples of operational flows, discussion and explanation may be provided with respect to the above-described examples of FIGS. **1A** through **1H**, and/or with respect to other examples and contexts. However, it should be understood that the operational flows may be executed in a number of other environments and contexts, and/or in modified versions of FIGS. **1A** through **1H**. Also, although the various operational flows are presented in the sequence(s) illustrated, it should be understood that the various operations may be performed in other orders than those which are illustrated, or may be performed concurrently.

After a start operation, the operational flow **6000** moves to an operation **6010**. Operation **6010** depicts detecting a medical condition parameter of a mammal according to a medical condition parameter request. For example, as shown in FIGS. **1A** through **1H**, the collar **100** may utilize a sensor module **170** to detect a medical condition parameter for the subject **102** according to a request from a physician **168**. The request may be received via the interface **164** and then transferred to the sensor module **170** via the processor **156**.

Then, operation **6020** depicts maintaining in physical association with a user a hands-free article for dispensing an inhalable compound in an operable dispensing position. For

example, as shown in FIGS. 1A through 1H, the collar 100 may be maintained in an operable dispensing position with an adhesive 138.

Then, operation 6030 depicts dispensing for inhalation by the user a dose of an inhalable compound according to a dosing instruction set. For example, as shown in FIGS. 1A through 1H, the collar 100 may dispense a dose 158 of a compound 104 according to a dosing instruction set stored in a memory 154.

FIG. 61 illustrates an operational flow 6100 representing example operations related to maintaining a hands-free article for dispensing an inhalable compound according to a dosing instruction set, where the hands-free article is maintained in an operable dispensing position. FIG. 61 illustrates an example embodiment where the example operational flow 6000 of FIG. 60 may include at least one additional operation. Additional operations may include an operation 6110.

After a start operation, an operation 6010, an operation 6020, and an operation 6030, the operational flow 6100 moves to an operation 6110. Operation 6110 illustrates recording the detected medical condition parameter data. It will be appreciated that a steep state may be included as a medical condition. For example, as shown in FIGS. 1A through 1H, the detected medical condition data may be recorded to the memory 154.

FIG. 62 illustrates an operational flow 6200 representing example operations related to maintaining a hands-free article for dispensing an inhalable compound according to a dosing instruction set, where the hands-free article is maintained in an operable dispensing position. FIG. 62 illustrates an example embodiment where the example operational flow 6000 of FIG. 60 may include at least one additional operation. Additional operations may include an operation 6210, an operation 6212, and/or an operation 6214.

After a start operation, an operation 6010, an operation 6020, and an operation 6030, the operational flow 6200 moves to an operation 6210. Operation 6210 illustrates transferring the detected medical condition parameter data. For example, as shown in FIGS. 1A through 1H, the detected medical condition data stored in the memory 154 may be transferred to a flash drive 64.

The operation 6212 illustrates transferring the detected medical condition parameter data to a flash drive. For example, as shown in FIGS. 1A through 1H, the detected medical condition data stored in the memory 154 may be transferred to a flash drive 64.

The operation 6214 illustrates transferring the detected medical condition parameter data to a hard drive. For example, as shown in FIGS. 1A through 1H, the detected medical condition data stored in the memory 154 may be transferred to a hard drive 66.

FIG. 63 illustrates alternative embodiments of the example operational flow 6200 of FIG. 62. FIG. 63 illustrates example embodiments where the operation 6210 may include at least one additional operation. Additional operations may include an operation 6302.

The operation 6302 illustrates downloading the detected medical condition parameter data to a RAM. For example, as shown in FIGS. 1A through 1H, the detected medical condition data stored in the memory 154 may be downloaded to a random access memory (RAM) 68. In an embodiment, the detected medical condition data may be transmitted to a processor (e.g., processor 156). In an embodiment, the detected medical condition may be transmitted to an external site (e.g., the medical response unit 192).

FIG. 64 illustrates alternative embodiments of the example operational flow 6200 of FIG. 62. FIG. 64 illustrates example embodiments where the operation 6210 may include at least one additional operation. Additional operations may include an operation 6402, and/or an operation 6404.

The operation 6402 illustrates transmitting the detected medical condition parameter to a dispensing module. For example, as shown in FIGS. 1A through 1H, the detected medical condition data stored in the memory 154 may be transmitted to the dispensing module 128. Further, the operation 6404 illustrates transmitting the detected medical condition parameter to a dispensing module via a wireless transmission. For example, as shown in FIGS. 1A through 1H, the detected medical condition data stored in the memory 154 may be transmitted to the dispensing module 128 wirelessly.

FIG. 65 illustrates alternative embodiments of the example operational flow 6200 of FIG. 62. FIG. 65 illustrates example embodiments where the operation 6210 may include at least one additional operation. Additional operations may include an operation 6502. Further, the operation 6502 illustrates transmitting the detected medical condition parameter to a dispensing module via a wire transmission. For example, as shown in FIGS. 1A through 1H, the detected medical condition data stored in the memory 154 may be transmitted to the dispensing module 128 via a wired connection.

FIG. 66 illustrates alternative embodiments of the example operational flow 6200 of FIG. 62. FIG. 66 illustrates example embodiments where the operation 6210 may include at least one additional operation. Additional operations may include an operation 6602. Further, the operation 6602 illustrates transmitting the detected medical condition parameter to a dispensing module via a radio transmission. For example, as shown in FIGS. 1A through 1H, the detected medical condition data stored in the memory 154 may be transmitted to the dispensing module 128 via a radio signal.

FIG. 67 illustrates alternative embodiments of the example operational flow 6200 of FIG. 62. FIG. 67 illustrates example embodiments where the operation 6210 may include at least one additional operation. Additional operations may include an operation 6702. Further, the operation 6702 illustrates transmitting the detected medical condition parameter to a dispensing module via an optical transmission. For example, as shown in FIGS. 1A through 1H, the detected medical condition data stored in the memory 154 may be transmitted to the dispensing module 128 via an optical transmission.

FIG. 68 illustrates alternative embodiments of the example operational flow 6200 of FIG. 62. FIG. 68 illustrates example embodiments where the operation 6210 may include at least one additional operation. Additional operations may include an operation 6802. Further, the operation 6802 illustrates transmitting the detected medical condition parameter to a dispensing module via a mechanical transmission. For example, as shown in FIGS. 1A through 1H, the detected medical condition data stored in the memory 154 may be transmitted to the dispensing module 128 via a mechanical transmission.

In an embodiment, the collar 100 may include a metered dose inhaler for delivering a metered dosage of an inhaled bronchodilator when the sensor module 170 detects a condition (e.g., an asthmatic incident including narrowing of the subject's airways) or a symptom indicative of a condition (e.g., narrowing of the subject's airways, wheezing, or decreased exhalation volume). In an embodiment, the sensor

module 170 transmits the detected condition or symptom to the processor 156. The processor 156 utilizes information stored in the memory 154 to determine the most appropriate course of action for the detected condition/symptom. For example, the memory 154 may include instructions for dispensing (e.g., via the dispensing module 128) a metered dose of the inhaled bronchodilator (which is stored in reservoir 180) when the incident is detected. In an embodiment, the memory 154 includes instructions for subsequent administration of the bronchodilator at some time after the initial condition/symptom is detected (e.g., in the case of a late-phase allergic reaction). The memory 154 may also include instructions for activating a visual indicator 196 so that the subject 102 or an observer may be alerted to the subject's condition.

Those having skill in the art will recognize that the state of the art has progressed to the point where there is little distinction left between hardware, software, and/or firmware implementations of aspects of systems; the use of hardware, software, and/or firmware is generally (but not always, in that in certain contexts the choice between hardware and software can become significant) a design choice representing cost vs. efficiency tradeoffs. Those having skill in the art will appreciate that there are various vehicles by which processes and/or systems and/or other technologies described herein can be effected (e.g., hardware, software, and/or firmware), and that the preferred vehicle will vary with the context in which the processes and/or systems and/or other technologies are deployed. For example, if an implementer determines that speed and accuracy are paramount, the implementer may opt for a mainly hardware and/or firmware vehicle; alternatively, if flexibility is paramount, the implementer may opt for a mainly software implementation; or, yet again alternatively, the implementer may opt for some combination of hardware, software, and/or firmware. Hence, there are several possible vehicles by which the processes and/or devices and/or other technologies described herein may be effected, none of which is inherently superior to the other in that any vehicle to be utilized is a choice dependent upon the context in which the vehicle will be deployed and the specific concerns (e.g., speed, flexibility, or predictability) of the implementer, any of which may vary. Those skilled in the art will recognize that optical aspects of implementations will typically employ optically-oriented hardware, software, and or firmware.

In some implementations described herein, logic and similar implementations may include software or other control structures. Electronic circuitry, for example, may have one or more paths of electrical current constructed and arranged to implement various functions as described herein. In some implementations, one or more media may be configured to bear a device-detectable implementation when such media hold or transmit device detectable instructions operable to perform as described herein. In some variants, for example, implementations may include an update or modification of existing software or firmware, or of gate arrays or programmable hardware, such as by performing a reception of or a transmission of one or more instructions in relation to one or more operations described herein. Alternatively or additionally, in some variants, an implementation may include special-purpose hardware, software, firmware components, and/or general-purpose components executing or otherwise invoking special-purpose components. Specifications or other implementations may be transmitted by one or more instances of tangible transmission media as

described herein, optionally by packet transmission or otherwise by passing through distributed media at various times.

Alternatively or additionally, implementations may include executing a special-purpose instruction sequence or invoking circuitry for enabling, triggering, coordinating, requesting, or otherwise causing one or more occurrences of virtually any functional operations described herein. In some variants, operational or other logical descriptions herein may be expressed as source code and compiled or otherwise invoked as an executable instruction sequence. In some contexts, for example, implementations may be provided, in whole or in part, by source code, such as C++, or other code sequences. In other implementations, source or other code implementation, using commercially available and/or techniques in the art, may be compiled/implemented/translated/converted into a high-level descriptor language (e.g., initially implementing described technologies in C or C++ programming language and thereafter converting the programming language implementation into a logic-synthesizable language implementation, a hardware description language implementation, a hardware design simulation implementation, and/or other such similar mode(s) of expression). For example, some or all of a logical expression (e.g., computer programming language implementation) may be manifested as a Verilog-type hardware description (e.g., via Hardware Description Language (HDL) and/or Very High Speed Integrated Circuit Hardware Descriptor Language (VHDL)) or other circuitry model which may then be used to create a physical implementation having hardware (e.g., an Application Specific Integrated Circuit). Those skilled in the art will recognize how to obtain, configure, and optimize suitable transmission or computational elements, material supplies, actuators, or other structures in light of these teachings.

The foregoing detailed description has set forth various embodiments of the devices and/or processes via the use of block diagrams, flowcharts, and/or examples. Insofar as such block diagrams, flowcharts, and/or examples contain one or more functions and/or operations, it will be understood by those within the art that each function and/or operation within such block diagrams, flowcharts, or examples can be implemented, individually and/or collectively, by a wide range of hardware, software, firmware, or virtually any combination thereof. In one embodiment, several portions of the subject matter described herein may be implemented via Application Specific Integrated Circuits (ASICs), Field Programmable Gate Arrays (FPGAs), digital signal processors (DSPs), or other integrated formats. However, those skilled in the art will recognize that some aspects of the embodiments disclosed herein, in whole or in part, can be equivalently implemented in integrated circuits, as one or more computer programs running on one or more computers (e.g., as one or more programs running on one or more computer systems), as one or more programs running on one or more processors (e.g., as one or more programs running on one or more microprocessors), as firmware, or as virtually any combination thereof, and that designing the circuitry and/or writing the code for the software and or firmware would be well within the skill of one of skill in the art in light of this disclosure. In addition, those skilled in the art will appreciate that the mechanisms of the subject matter described herein are capable of being distributed as a program product in a variety of forms, and that an illustrative embodiment of the subject matter described herein applies regardless of the particular type of signal bearing medium used to actually carry out the distribution.

Examples of a signal bearing medium include, but are not limited to, the following: a recordable type medium such as a floppy disk, a hard disk drive, a Compact Disc (CD), a Digital Video Disk (DVD), a digital tape, a computer memory, etc.; and a transmission type medium such as a

digital and/or an analog communication medium (e.g., a fiber optic cable, a waveguide, a wired communications link, a wireless communication link (e.g., transmitter, receiver, transmission logic, reception logic, etc.), etc.).

In a general sense, those skilled in the art will recognize that the various embodiments described herein can be implemented, individually and/or collectively, by various types of electro-mechanical systems having a wide range of electrical components such as hardware, software, firmware, and/or virtually any combination thereof; and a wide range of components that may impart mechanical force or motion such as rigid bodies, spring or torsional bodies, hydraulics, electro-magnetically actuated devices, and/or virtually any combination thereof. Consequently, as used herein "electro-mechanical system" includes, but is not limited to, electrical circuitry operably coupled with a transducer (e.g., an actuator, a motor, a piezoelectric crystal, a Micro Electro Mechanical System (MEMS), etc.), electrical circuitry having at least one discrete electrical circuit, electrical circuitry having at least one integrated circuit, electrical circuitry having at least one application specific integrated circuit, electrical circuitry forming a general purpose computing device configured by a computer program (e.g., a general purpose computer configured by a computer program which at least partially carries out processes and/or devices described herein, or a microprocessor configured by a computer program which at least partially carries out processes and/or devices described herein), electrical circuitry forming a memory device (e.g., forms of memory (e.g., random access, flash, read only, etc.)), electrical circuitry forming a communications device (e.g., a modem, communications switch, optical-electrical equipment, etc.), and/or any non-electrical analog thereto, such as optical or other analogs. Those skilled in the art will also appreciate that examples of electromechanical systems include but are not limited to a variety of consumer electronics systems, medical devices, as well as other systems such as motorized transport systems, factory automation systems, security systems, and/or communication/computing systems. Those skilled in the art will recognize that electro-mechanical as used herein is not necessarily limited to a system that has both electrical and mechanical actuation except as context may dictate otherwise.

In a general sense, those skilled in the art will recognize that the various aspects described herein which can be implemented, individually and/or collectively, by a wide range of hardware, software, firmware, and/or any combination thereof can be viewed as being composed of various types of "electrical circuitry." Consequently, as used herein "electrical circuitry" includes, but is not limited to, electrical circuitry having at least one discrete electrical circuit, electrical circuitry having at least one integrated circuit, electrical circuitry having at least one application specific integrated circuit, electrical circuitry forming a general purpose computing device configured by a computer program (e.g., a general purpose computer configured by a computer program which at least partially carries out processes and/or devices described herein, or a microprocessor configured by a computer program which at least partially carries out processes and/or devices described herein), electrical circuitry forming a memory device (e.g., forms of memory (e.g., random access, flash, read only, etc.)), and/or electrical

circuitry forming a communications device (e.g., a modem, communications switch, optical-electrical equipment, etc.). Those having skill in the art will recognize that the subject matter described herein may be implemented in an analog or digital fashion or some combination thereof.

Those skilled in the art will recognize that at least a portion of the devices and/or processes described herein can be integrated into a data processing system. Those having skill in the art will recognize that a data processing system generally includes one or more of a system unit housing, a video display device, memory such as volatile or non-volatile memory, processors such as microprocessors or digital signal processors, computational entities such as operating systems, drivers, graphical user interfaces, and applications programs, one or more interaction devices (e.g., a touch pad, a touch screen, an antenna, etc.), and/or control systems including feedback Loops and control motors (e.g., feedback for sensing position and/or velocity; control motors for moving and/or adjusting components and/or quantities). A data processing system may be implemented utilizing suitable commercially available components, such as those typically found in data computing/communication and/or network computing/communication systems.

All of the above U.S. patents, U.S. patent application publications, U.S. patent applications, foreign patents, foreign patent applications and non-patent publications referred to in this specification and/or listed in any Application Data Sheet, are incorporated herein by reference, to the extent not inconsistent herewith.

One skilled in the art will recognize that the herein described components (e.g., operations), devices, objects, and the discussion accompanying them are used as examples for the sake of conceptual clarity and that various configuration modifications are contemplated. Consequently, as used herein, the specific exemplars set forth and the accompanying discussion are intended to be representative of their more general classes. In general, use of any specific exemplar is intended to be representative of its class, and the non-inclusion of specific components (e.g., operations), devices, and objects should not be taken limiting.

Although user 166 is shown/described herein as a single illustrated figure, those skilled in the art will appreciate that user 166 may be representative of a human user, a robotic user (e.g., computational entity), and/or substantially any combination thereof (e.g., a user may be assisted by one or more robotic agents) unless context dictates otherwise. Those skilled in the art will appreciate that, in general, the same may be said of "sender" and/or other entity-oriented terms as such terms are used herein unless context dictates otherwise.

With respect to the use of substantially any plural and/or singular terms herein, those having skill in the art can translate from the plural to the singular and/or from the singular to the plural as is appropriate to the context and/or application. The various singular/plural permutations are not expressly set forth herein for sake of clarity.

The herein described subject matter sometimes illustrates different components contained within, or connected with, different other components. It is to be understood that such depicted architectures are merely exemplary, and that in fact many other architectures may be implemented which achieve the same functionality. In a conceptual sense, any arrangement of components to achieve the same functionality is effectively "associated" such that the desired functionality is achieved. Hence, any two components herein combined to achieve a particular functionality can be seen as "associated with" each other such that the desired function-

ality is achieved, irrespective of architectures or intermedial components. Likewise, any two components so associated can also be viewed as being “operably connected”, or “operably coupled,” to each other to achieve the desired functionality, and any two components capable of being so associated can also be viewed as being “operably couplable,” to each other to achieve the desired functionality. Specific examples of operably couplable include but are not limited to physically mateable and/or physically interacting components, and/or wirelessly interactable, and/or wirelessly interacting components, and/or logically interacting, and/or logically interactable components.

In some instances, one or more components may be referred to herein as “configured to,” “configurable to,” “operable/operative to,” “adapted/adaptable,” “able to,” “conformable/conformed to,” etc. Those skilled in the art will recognize that such terms (e.g. “configured to”) can generally encompass active-state components and/or inactive-state components and/or standby-state components, unless context requires otherwise.

While particular aspects of the present subject matter described herein have been shown and described, it will be apparent to those skilled in the art that, based upon the teachings herein, changes and modifications may be made without departing from the subject matter described herein and its broader aspects and, therefore, the appended claims are to encompass within their scope all such changes and modifications as are within the true spirit and scope of the subject matter described herein. It will be understood by those within the art that, in general, terms used herein, and especially in the appended claims (e.g., bodies of the appended claims) are generally intended as “open” terms (e.g., the term “including” should be interpreted as “including but not limited to,” the term “having” should be interpreted as “having at least,” the term “includes” should be interpreted as “includes but is not limited to,” etc.). It will be further understood by those within the art that if a specific number of an introduced claim recitation is intended, such an intent will be explicitly recited in the claim, and in the absence of such recitation no such intent is present. For example, as an aid to understanding, the following appended claims may contain usage of the introductory phrases “at least one” and “one or more” to introduce claim recitations. However, the use of such phrases should not be construed to imply that the introduction of a claim recitation by the indefinite articles “a” or “an” limits any particular claim containing such introduced claim recitation to claims containing only one such recitation, even when the same claim includes the introductory phrases “one or more” or “at least one” and indefinite articles such as “a” or “an” (e.g., “a” and/or “an” should typically be interpreted to mean “at least one” or “one or more”); the same holds true for the use of definite articles used to introduce claim recitations. In addition, even if a specific number of an introduced claim recitation is explicitly recited, those skilled in the art will recognize that such recitation should typically be interpreted to mean at least the recited number (e.g., the bare recitation of “two recitations,” without other modifiers, typically means at least two recitations, or two or more recitations). Furthermore, in those instances where a convention analogous to “at least one of A, B, and C, etc.” is used, in general such a construction is intended in the sense one having skill in the art would understand the convention (e.g., “a system having at least one of A, B, and C” would include but not be limited to systems that have A alone, B alone, C alone, A and B together, A and C together, B and C together, and/or A, B, and C together, etc.). In those instances where a convention

analogous to “at least one of A, B, or C, etc.” is used, in general such a construction is intended in the sense one having skill in the art would understand the convention (e.g., “a system having at least one of A, B, or C” would include but not be limited to systems that have A alone, B alone, C alone, A and B together, A and C together, B and C together, and/or A, B, and C together, etc.). It will be further understood by those within the art that typically a disjunctive word and/or phrase presenting two or more alternative terms, whether in the description, claims, or drawings, should be understood to contemplate the possibilities of including one of the terms, either of the terms, or both terms unless context dictates otherwise. For example, the phrase “A or B” will be typically understood to include the possibilities of “A” or “B” or “A and B.”

With respect to the appended claims, those skilled in the art will appreciate that recited operations therein may generally be performed in any order. Also, although various operational flows are presented in a sequence(s), it should be understood that the various operations may be performed in other orders than those which are illustrated, or may be performed concurrently. Examples of such alternate orderings may include overlapping, interleaved, interrupted, reordered, incremental, preparatory, supplemental, simultaneous, reverse, or other variant orderings, unless context dictates otherwise. Furthermore, terms like “responsive to,” “related to,” or other past-tense adjectives are generally not intended to exclude such variants, unless context dictates otherwise.

The invention claimed is:

1. A method for administering an inhalable compound, comprising:

detecting a medical condition parameter of a user with a sensor on a hands-free article for dispensing an inhalable compound according to a medical condition parameter request received from a source external to the hands-free article;

maintaining in physical association with the user the hands-free article in an operable dispensing position, the operable dispensing position excluding physical contact between an outlet of the hands-free article and a face of the user; and

dispensing for inhalation by the user a dose of the inhalable compound according to a dosing instruction set.

2. The method of claim 1, wherein detecting a medical condition parameter of a user with a sensor on a hands-free article for dispensing an inhalable compound according to a medical condition parameter request received from a source external to the hands-free article comprises:

detecting a blood glucose level in the user.

3. The method of claim 1, wherein detecting a medical condition parameter of a user with a sensor on a hands-free article for dispensing an inhalable compound according to a medical condition parameter request received from a source external to the hands-free article comprises:

detecting a blood oxygen level in the user.

4. The method of claim 1, wherein detecting a medical condition parameter of a user with a sensor on a hands-free article for dispensing an inhalable compound according to a medical condition parameter request received from a source external to the hands-free article comprises:

detecting an infection in the user.

5. The method of claim 1, wherein detecting a medical condition parameter of a user with a sensor on a hands-free article for dispensing an inhalable compound according to a

39

medical condition parameter request received from a source external to the hands-free article comprises:

detecting vascular dysfunction in the user.

6. The method of claim 1, wherein detecting a medical condition parameter of a user with a sensor on a hands-free article for dispensing an inhalable compound according to a medical condition parameter request received from a source external to the hands-free article comprises:

detecting blood flow in the user.

7. The method of claim 1, wherein detecting a medical condition parameter of a user with a sensor on a hands-free article for dispensing an inhalable compound according to a medical condition parameter request received from a source external to the hands-free article comprises:

detecting at least one of a respiratory minute volume in the user, a sneeze, a cough, a wheeze, a rhonchus, a snore, a temperature, or an expelled gas.

8. The method of claim 1, further comprising:

recording the detected medical condition parameter data.

9. The method of claim 1, further comprising:

transferring the detected medical condition parameter data.

10. The method of claim 9, wherein transferring the detected medical condition parameter data comprises:

transferring the detected medical condition parameter data to a flash drive.

11. The method of claim 9, wherein transferring the detected medical condition parameter data comprises:

transferring the detected medical condition parameter data to a hard drive.

12. The method of claim 9, wherein transferring the detected medical condition parameter data comprises:

downloading the detected medical condition parameter data to a RAM.

13. The method of claim 9, wherein transferring the detected medical condition parameter data comprises:

transmitting the detected medical condition parameter data to a processor.

14. The method of claim 9, wherein transferring the detected medical condition parameter data comprises:

transmitting the detected medical condition parameter data to an external site.

15. The method of claim 9, wherein transferring the detected medical condition parameter data comprises:

transmitting the detected medical condition parameter to a dispensing module.

40

16. The method of claim 15, wherein transmitting the detected medical condition parameter to a dispensing module comprises:

transmitting the detected medical condition parameter to a dispensing module via a wireless transmission.

17. The method of claim 15, wherein transmitting the detected medical condition parameter to a dispensing module comprises:

transmitting the detected medical condition parameter to a dispensing module via a wire transmission.

18. The method of claim 15, wherein transmitting the detected medical condition parameter to a dispensing module comprises:

transmitting the detected medical condition parameter to a dispensing module via a radio transmission.

19. The method of claim 15, wherein transmitting the detected medical condition parameter to a dispensing module further comprises:

transmitting the detected medical condition parameter to a dispensing module via an optical transmission.

20. The method of claim 15, wherein transmitting the detected medical condition parameter to a dispensing module further comprises:

transmitting the detected medical condition parameter to a dispensing module via a mechanical transmission.

21. A method for administering an inhalable compound, comprising:

detecting a medical condition parameter of a user with a sensor on a hands-free article for dispensing an inhalable compound according to a medical condition parameter request received from a source external to the hands-free article;

maintaining in physical association with a user the hands-free article, the hands free article configured for disposal around at least one of a neck portion, a torso portion, or a wrist portion of the user, the hands free article including a support member configured for maintaining the inhalable compound in an operable dispensing position, the operable dispensing position oriented to exclude physical contact between an outlet of the hands-free article and a face of the user; and dispensing for inhalation by the user a dose of the inhalable compound according to a dosing instruction set.

* * * * *

专利名称(译)	给予可吸入化合物的方法		
公开(公告)号	US9724483	公开(公告)日	2017-08-08
申请号	US12/455672	申请日	2009-06-04
[标]申请(专利权)人(译)	特拉华州的SEARETE负债CORP		
申请(专利权)人(译)	SEARETE有限责任公司，特拉华州的有限责任公司		
当前申请(专利权)人(译)	齿轮箱有限责任公司		
[标]发明人	HYDE RODERICK A ISHIKAWA MURIEL Y KARE JORDIN T LANGER ROBERT LEUTHARDT ERIC C SWEENEY ELIZABETH A TEGREENE CLARENCE T WOOD JR LOWELL L WOOD VICTORIA Y H		
发明人	HYDE, RODERICK A. ISHIKAWA, MURIEL Y. KARE, JORDIN T. LANGER, ROBERT LEUTHARDT, ERIC C. SWEENEY, ELIZABETH A. TEGREENE, CLARENCE T. WOOD, JR., LOWELL L. WOOD, VICTORIA Y. H.		
IPC分类号	A61M15/00 A61M16/00 B05D7/14 B65D83/06 A61M15/02 A61B5/00 A61D7/04 A61M15/08 G06F19/00 A61B5/08 G07D5/00 G07D5/02 G07D5/10		
CPC分类号	A61M15/02 A61B5/411 A61D7/04 A61M15/08 G06F19/3462 A61B5/08 A61B5/082 A61M15/009 A61M15/0028 A61M15/0065 A61M2205/3553 A61M2205/3569 A61M2205/3584 A61M2205/3592 A61M2205/581 A61M2205/582 A61M2205/583 A61M2205/588 A61M2209/088 A61M2230/201 A61M2230/205 G16H20/13		
其他公开文献	US20100163040A1		
外部链接	Espacenet USPTO		

摘要(译)

一种方法可包括根据给药指令集分配一剂可吸入化合物;并且保持用于将可吸入化合物分配在可操作的分配位置的免提物品。

