


(19) **United States**(12) **Patent Application Publication**
Brown(10) **Pub. No.: US 2004/0117210 A1**(43) **Pub. Date: Jun. 17, 2004**(54) **NETWORKED REMOTE PATIENT
MONITORING WITH HANDHELD DEVICES**which is a continuation of application No. 07/977,
323, filed on Nov. 17, 1992, now Pat. No. 5,307,263.(75) **Inventor: Stephen J Brown, Woodside, CA (US)****Publication Classification**

Correspondence Address:

BLAKELY SOKOLOFF TAYLOR & ZAFMAN
12400 WILSHIRE BOULEVARD, SEVENTH
FLOOR
LOS ANGELES, CA 90025 (US)(51) **Int. Cl.⁷ G06F 17/60; A61B 5/00**(52) **U.S. Cl. 705/2; 600/316**(57) **ABSTRACT**

A networked health-monitoring system is configured to collect and process patient health-related data. The system includes at least one handheld microprocessor device having a display; and a memory. At least one central server is connected to receive health-related data communicated to the handheld microprocessor device and at least one remotely located health care professional computer is in signal communication with the central server. It receives patient health-related information based on the patient health-related data received from the handheld microprocessor device. The system is configured to convert the handheld microprocessor device into a healthcare monitoring device that functions to monitor patient health conditions and communicate data related to the monitored conditions to the central server.

(73) **Assignee: HEALTH HERO NETWORK, Moun-**
tain View, CA (US)(21) **Appl. No.: 10/605,229**(22) **Filed: Sep. 16, 2003****Related U.S. Application Data**(63) Continuation of application No. 09/237,194, filed on
Jan. 26, 1999, which is a continuation of application
No. 08/481,925, filed on Jun. 7, 1995, now Pat. No.
5,899,855, which is a continuation of application No.
08/233,397, filed on Apr. 26, 1994, now abandoned,




Fig. 1.




Fig. 2.




Fig. 3.

*Fig. 4.***Attention**

Calibration was
not successful.

Please insert
the code strip
again.

Fig. 5.


June 19 12:30 pm

Blood Glucose

109 mg /dl
remove test strip

Fig. 6.

Mon Sept. 28 1992

*Fig. 7.*

Sept. 20-26 1992



Fig. 8.

Glucose	
Ave:	123 mg/dl
SD:	56
Num:	15
No. under 50:	13
No. hypo sym:	23

Fig. 9.

June 12 9:30pm		
BG	113	mg/dl
Regin	12.5	U
NPHin	13.2	U
Food	1	BE
Pre-meal	HYPO	

Fig. 10.





Fig. 11.



NETWORKED REMOTE PATIENT MONITORING WITH HANDHELD DEVICES

[0001] Continuation-In-Part of application Ser. No. 07/977,323, filed Nov. 17, 1992 (which has since issued as U.S. Pat. No. 5,307,263); and a Continuation-In-Part of application Ser. No. 08/946,341, filed Oct. 7, 1997, now U.S. Pat. No. 5,997,476, which claims priority from Provisional Application Serial. No. 60/041,746 filed Mar. 28, 1997 and from provisional application Ser. No. 60/041,751 filed Mar. 28, 1997; all of which are incorporated herein by reference. This application is related to U.S. Pat. No. 5,897,493 (U.S. Ser. No. 08/847,009) which also claims priority from Provisional Application No. 60/041,751 and 60/041,746 filed Mar. 28, 1997. This application is related to U.S. application Ser. No. 09/658,209 filed on Sep. 8, 2000; U.S. application Ser. No. 10/233,296 filed on Aug. 30, 2002; U.S. application Ser. No. 09/665,242 Mar. 28, 1997; U.S. application Ser. No. 10/319,427 Dec. 12, 2002; and U.S. application Ser. No. 09/713,922 Nov. 15, 2000.

BACKGROUND OF INVENTION

[0002] Controlling or curing conditions of ill health generally involves both establishing a therapeutic program and monitoring the progress of the afflicted person. Based on that progress, decisions can be made as to altering therapy to achieve a cure or maintain the affliction or condition at a controlled level. Successfully treating certain health conditions calls for rather frequent monitoring and a relatively high degree of patient participation. For example, in order to establish and maintain a regimen for successful diabetes care, a diabetic should monitor his or her blood glucose level and record that information along with the date and time at which the monitoring took place. Since diet, exercise, and medication all affect blood glucose levels, a diabetic often must record data relating to those items of information along with blood glucose level so that the diabetic may more closely monitor his or her condition and, in addition, can provide information of value to the healthcare provider in determining both progress of the patient and detecting any need to change the patient's therapy program.

[0003] Advances in the field of electronics over the past several years have brought about significant changes in medical diagnostic and monitoring equipment, including arrangements for self-care monitoring of various chronic conditions. With respect to the control and monitoring of diabetes, relatively inexpensive and relatively easy-to-use blood glucose monitoring systems have become available that provide reliable information that allows a diabetic and his or her healthcare professional to establish, monitor and adjust a treatment plan (diet, exercise, and medication). More specifically, microprocessor-based blood glucose monitoring systems are being marketed which sense the glucose level of a blood sample that is applied to a reagent-impregnated region of a test strip that is inserted in the glucose monitor. When the monitoring sequence is complete, the blood glucose level is displayed by, for example, a liquid crystal display (LCD) unit.

[0004] Typically, currently available self-care blood glucose monitoring units include a calendar/clock circuit and a memory circuit that allows a number of blood glucose test results to be stored along with the date and time at which the monitoring occurred. The stored test results (blood glucose

level and associated time and date) can be sequentially recalled for review by the blood glucose monitor user or a health professional by sequentially actuating a push button or other control provided on the monitor. In some commercially available devices, the average of the blood glucose results that are stored in the monitor (or the average of the results for a predetermined period of time, e.g., fourteen days) also is displayed during the recall sequence. Further, some self-care blood glucose monitors allow the user to tag the test result with an "event code" that can be used to organize the test results into categories. For example, a user might use a specific event code to identify test results obtained at particular times of the day, a different event code to identify a blood glucose reading obtained after a period of exercise, two additional event codes to identify blood glucose readings taken during hypoglycemia symptoms and hyperglycemia symptoms, etc. When event codes are provided and used, the event code typically is displayed with each recalled blood glucose test result.

[0005] Microprocessor-based blood glucose monitoring systems have advantages other than the capability of obtaining reliable blood glucose test results and storing a number of the results for later recall and review. By using low power microprocessor and memory circuits and powering the units with small, high capacity batteries (e.g., a single alkaline battery), extremely compact and light designs have been achieved that allow taking the blood glucose monitoring system to work, school, or anywhere else the user might go with people encountered by the user not becoming aware of the monitoring system. In addition, most microprocessor-based self-care blood glucose monitoring systems have a memory capacity that allows the system to be programmed by the manufacturer so that the monitor displays a sequence of instructions during any necessary calibration or system tests and during the blood glucose test sequence itself. In addition, the system monitors various system conditions during a blood glucose test (e.g., whether a test strip is properly inserted in the monitor and whether a sufficient amount of blood has been applied to the reagent impregnated portion of the strip) and if an error is detected generates an appropriate display (e.g., "retest"). A data port may be provided that allows test results stored in the memory of the microprocessor-based blood glucose monitoring system to be transferred to a data port (e.g., RS-232 connection) of a personal computer 48 or other such device for subsequent analysis.

[0006] Microprocessor-based blood glucose monitoring systems are a significant advance over previously available self-care systems such as those requiring a diabetic to apply a blood sample to reagent activated portions of a test strip; wipe the blood sample from the test strip after a predetermined period of time; and, after a second predetermined period of time, determine blood glucose level by comparing the color of the reagent activated regions of the test strip with a color chart supplied by the test strip manufacturer. Despite what has been achieved, numerous drawbacks and disadvantages still exist. For example, establishing and maintaining diabetic healthcare often requires the diabetic to record additional data pertaining to medication, food intake, and exercise. However, the event codes of currently available microprocessor blood glucose monitoring systems provide only limited capability for tagging and tracking blood glucose test results according to food intake and other relevant factors. For example, the event codes of currently

available monitoring systems only allow the user to classify stored blood glucose readings in a manner that indicates blood glucose tests taken immediately after a heavy, light or normal meal. This method of recording information not only requires subjective judgment by the system user, but will not suffice in a situation in which successfully controlling the user's diabetes requires the recording and tracking of relatively accurate information relating to food intake, exercise, or medication (e.g., insulin dosage). An otherwise significant advantage of currently available blood glucose monitoring systems is lost when blood glucose test results must be recorded and tracked with quantitative information relating to medication, food intake, or exercise. Specifically, the system user must record the required information along with a time and date tagged blood glucose test result by, for example, writing the information in a log book.

[0007] The use of event codes to establish subcategories of blood glucose test results has an additional disadvantage or drawback. In particular, although alphanumeric display devices are typically used in currently available microprocessor-based blood glucose monitoring systems, the display units are limited to a single line of information having on the order of six characters. Moreover, since the systems include no provision for the user to enter alphanumeric information, any event codes that are used must be indicated on the display in a generic manner, e.g., displayed as "EVENT"EVENT etc. This limitation makes the system more difficult to use because the diabetic must either memorize his or her assignment of event codes or maintain a list that defines the event codes. The limited amount of data that can be displayed at any one time presents additional drawbacks and disadvantages. First, instructions and diagnostics that are displayed to the user when calibrating the system and using the system to obtain a blood glucose reading must be displayed a line at a time and in many cases, the information must be displayed in a cryptic manner.

[0008] The above-discussed display limitations and other aspects of currently available blood glucose monitoring systems is disadvantageous in yet another way. Little statistical information can be made available to the user. For example, in diabetic healthcare maintenance, changes or fluctuations that occur in blood glucose levels during a day, a week, or longer period can provide valuable information to a diabetic and/or his or her healthcare professional. As previously mentioned, currently available systems do not allow associating blood glucose test results with attendant quantitative information relating to medication, food intake, or other factors such as exercise that affect a person's blood glucose level at any particular point in time. Thus, currently available blood glucose monitoring systems have little or no capability for the generating and display of trend information that may be of significant value to a diabetic or the diabetic's healthcare professional.

[0009] Some currently available blood glucose monitoring systems provide a data port that can be interconnected with and transfer data to a personal computer 48 (e.g., via an RS-232 connection). With such a system and a suitable programmed computer, the user can generate and display trend information or other data that may be useful in administering his or her treatment plan. Moreover, in such systems, data also can be transferred from the blood glucose monitoring system to a healthcare professional's computer either directly or remotely by telephone if both the blood

glucose monitoring system (or computer) to which the data has been downloaded and the healthcare professional's computer are equipped with modems. Although such a data transfer provision allows a healthcare professional to analyze blood glucose data collected by a diabetic, this aspect of currently available blood glucose monitoring systems has not found widespread application. First, the downloading and subsequent analysis feature can only be used by system users that have ready access to a computer that is programmed with appropriate software and, in addition, have both the knowledge required to use the software (and the inclination to do so). This same problem exists with respect to data transfer to (and subsequent analysis by) a healthcare professional. Moreover, various manufacturers of systems that currently provide a data transfer feature do not use the same data format. Therefore, if a healthcare professional wishes to analyze data supplied by a number of different blood glucose monitoring systems, he or she must possess software for each of the systems and must learn to conduct the desired analyses with each software system.

[0010] The above-discussed disadvantages and drawbacks of microprocessor-based self-care health monitoring systems take on even greater significance with respect to children afflicted with diabetes, asthma and other chronic illnesses. In particular, a child's need for medication and other therapy changes as the child grows. Current microprocessor-based self-care health monitoring systems generally do not provide information that is timely and complete enough for a healthcare professional to recognize and avert problems before relatively severe symptoms develop. Too often, a need for a change in medication and/or other changes in therapeutic regimen is not detected until the child's condition worsens to the point that emergency room care is required.

[0011] Further, currently available microprocessor-based health monitoring systems have not been designed with children in mind. As previously mentioned, such devices are not configured for sufficient ease of use in situations in which it is desirable or necessary to record and track quantitative information that affects the physical condition of the system user (e.g., medication dosage administered by a diabetic and food intake). Children above the age at which they are generally capable of obtaining blood samples and administering insulin or other medication generally can learn to use at least the basic blood glucose monitoring features of currently available microprocessor-based blood glucose monitoring systems. However, the currently available monitoring systems provide nothing in the way of motivation for a child to use the device and, in addition, include little or nothing that educates the child about his or her condition or treatment progress.

[0012] The lack of provision for the entering of alphanumeric data also can be a disadvantage. For example, currently available blood glucose monitoring systems do not allow the user or the healthcare professional to enter information into the system such as medication dosage and other instructions or data that is relevant to the user's self-care health program.

[0013] The above-discussed disadvantages and drawbacks of currently available microprocessor-based blood glucose monitoring systems also have been impediments to adopting the basic technology of the system for other healthcare

situations in which establishing and maintaining an effective regimen for cure or control is dependent upon (or at least facilitated by) periodically monitoring a condition and recording that condition along with time and date tags and other information necessary or helpful in establishing and maintaining a healthcare program.

SUMMARY OF INVENTION

[0014] This invention provides a new and useful system for healthcare maintenance in which the invention either serves as a peripheral device to (or incorporates) a small handheld microprocessor-based unit of the type that includes a display screen, buttons or keys that allow a user to control the operation of the device and a program cartridge or other arrangement that can be inserted in the device to adapt the device to a particular application or function. The invention in effect converts the handheld microprocessor device into a healthcare monitoring system that has significant advantages over systems such as the currently available blood glucose monitoring systems. To perform this conversion, the invention includes a microprocessor-based healthcare data management unit, a program cartridge and a monitoring unit. When inserted in the handheld microprocessor unit **12**, the program cartridge provides the software necessary (program instructions) to program the handheld microprocessor unit **12** for operation with the microprocessor-based data management unit. Signal communication between the data management unit and the handheld microprocessor unit **12** is established by an interface cable. A second interface cable can be used to establish signal communication between the data management unit and the monitoring unit or, alternatively, the monitoring unit can be constructed as a plug-in unit having an electrical connector that mates with a connector mounted within a region that is configured for receiving the monitoring unit.

[0015] In operation, the control buttons or keys of the handheld microprocessor-based unit are used to select the operating mode for both the data management unit and the handheld microprocessor-based unit. In response to signals generated by the control buttons or keys, the data management unit generates signals that are coupled to the handheld microprocessor unit **12** and, under control of the program instructions contained in the program cartridge, establish an appropriate screen display on the handheld microprocessor-based unit display. In selecting system operating mode and other operations, the control buttons are used to position a cursor or other indicator in a manner that allows the system user to easily select a desired operating mode or function and provide any other required operator input. In the disclosed detailed embodiment of the invention several modes of operation are made available.

[0016] In the currently preferred embodiments of the invention, the handheld microprocessor unit **12** is a compact video game system such as the system manufactured by Nintendo of America Inc. under the trademark "GAME BOY." Use of a compact video game system has several general advantages, including the widespread availability and low cost of such systems. Further, such systems include switch arrangements that are easily adapted for use in the invention and the display units of such systems are of a size and resolution that can advantageously be employed in the practice of the invention. In addition, such systems allow educational or motivational material to be displayed to the

system user, with the material being included in the program cartridge that provides the monitor system software or, alternatively, in a separate program cartridge.

[0017] The use of a compact video game system for the handheld microprocessor-based unit of the invention is especially advantageous with respect to children. Specifically, the compact video game systems of the type that can be employed in the practice of the invention are well known and well accepted by children. Such devices are easily operated by a child and most children are well accustomed to using the devices in the context of playing video games. Motivational and educational material relating to the use of the invention can be presented in game-like or animated format to further enhance acceptance and use of the invention by children that require self-care health monitoring.

[0018] A microprocessor-based health monitoring system that is configured in accordance with the invention provides additional advantages for both the user and a healthcare professional. In accordance with one aspect of the invention, standardized reports are provided to a physician or other healthcare provider by means of facsimile transmission. To accomplish this, the data management unit of the currently preferred embodiments of the invention include a modem which allows test results and other data stored in system memory to be transmitted to a remote clearinghouse via a telephone connection. Data processing arrangements included in the clearinghouse perform any required additional data processing; format the standardized reports; and, transmit the reports to the facsimile machine of the appropriate healthcare professional.

[0019] The clearinghouse also can fill an additional communication need, allowing information such as changes in medication dosage or other information such as modification in the user's monitoring schedule to be electronically sent to a system user. In arrangements that incorporate this particular aspect of the invention, information can be sent to the user via a telephone connection and the data management unit modem when a specific inquiry is initiated by the user, or when the user establishes a telephone connection with the clearinghouse for other purposes such as providing data for standardized reports.

[0020] The clearinghouse-facsimile aspect of the invention is important because it allows a healthcare professional to receive timely information about patient condition and progress without requiring a visit by the patient (system user) and without requiring analysis or processing of test data by the healthcare professional. In this regard, the healthcare professional need not possess or even know how to use a computer and/or the software conventionally employed for analysis of blood glucose and other health monitoring data and information.

[0021] The invention also includes provision for data analysis and memory storage of information provided by the user and/or the healthcare professional. In particular, the data management units of the currently preferred embodiments of the invention include a data port such as an RS-232 connection that allows the system user or healthcare professional to establish signal communication between the data management unit and a personal computer or other data processing arrangement. Blood glucose test data or other information can then be downloaded for analysis and record keeping purposes. Alternatively, information such as

changes in the user's treatment and monitoring regimen can be entered into system memory. Moreover, if desired, remote communication between the data management unit and the healthcare professional's computer can be established using the clearinghouse as an element of the communications link. That is, in the currently preferred arrangements of the invention a healthcare professional has the option of using a personal computer that communicates with the clearinghouse via a modem and telephone line for purposes of transmitting instructions and information to a selected user of the system and/or obtaining user test data and information for subsequent analysis.

[0022] The invention can be embodied in forms other than those described above. For example, although small handheld microprocessor units such as a handheld video game system or handheld microprocessor units of the type often referred to as "palm computers provide many advantages, there are situations in which other compact microprocessor units can advantageously be used. Among the various types of units that can be employed are using compact video game systems of the type that employ a program cartridge, but uses a television set or video monitor instead of a display unit that is integrated into the previously described handheld microprocessor units.

[0023] Those skilled in the art also will recognize that the above-described microprocessor-implemented functions and operations can be apportioned between one or more microprocessors in a manner that differs from the above-described arrangement. For example, in some situations, the programmable microprocessor unit and the program cartridge used in practicing the invention may provide memory and signal processing capability that is sufficient for practicing the invention. In such situations, the microprocessor of the microprocessor-based data management unit of the above embodiments in effect is moved into the video game system, palm computer or programmable microprocessor device. In such an arrangement, the data management unit can be realized as a relatively simple interface unit that includes little or no signal processing capability. Depending upon the situation at hand, the interface unit may or may not include a telephone modem and/or an RS connection (or other data port) for interconnecting the healthcare system with a computer or other equipment. In other situations, the functions and operations associated with processing of the monitored health care data may be performed by a microprocessor that is added to or already present in the monitoring device that is used to monitor blood glucose or other condition.

[0024] Because the invention can be embodied to establish systems having different levels of complexity, the invention satisfies a wide range of self-care health monitoring applications. The arrangements that include a modem (or other signal transmission facility) and sufficient signal processing capability can be employed in situations in which reports are electronically transmitted to a healthcare professional either in hard copy (facsimile) form or in a signal format that can be received by and stored in the healthcare professional's computer. On the other hand, less complex (and, hence, less costly) embodiments of the invention are available for use in which transfer of system information need not be made by means of telephonic data transfer or other remote transmission methods. In these less complex embodiments, transfer of data to a healthcare professional can still be accom-

plished. Specifically, if the program cartridge includes a battery and suitable program instructions, monitored healthcare data can be stored in the program cartridge during use of the system as a healthcare monitor. The data cartridge can then be provided to the healthcare professional and inserted in a programmable microprocessor unit that is the same as or similar to that which was used in the healthcare monitoring system. The healthcare professional can then review the data, and record it for later use, and/or can use the data in performing various analyses. If desired, the microprocessor unit used by the healthcare professional can be programmed and arranged to allow information to be stored in the cartridge for return to and retrieval by the user of the healthcare monitoring system. The stored information can include messages (e.g., instructions for changes in medication dosage) and/or program instructions for reconfiguring the program included in the cartridge so as to effect changes in the treatment regimen, the analyses or reports to be generated by the healthcare monitoring system, or less important aspects such as graphical presentation presented during the operation of the health care system.

BRIEF DESCRIPTION OF DRAWINGS

[0025] The foregoing aspects and many of the attendant advantages of this invention will become more readily appreciated as the same becomes better understood by reference to the following detailed description, when taken in conjunction with the accompanying drawings, wherein:

[0026] **FIG. 1** is a block diagram that illustrates a healthcare monitoring system arranged in accordance with the invention;

[0027] **FIG. 2** diagrammatically illustrates monitoring systems constructed in accordance with the invention connected in signal communication with a remotely located computing facility which includes provision for making the data supplied by the monitoring system of the invention available to a designated healthcare professional and/or for providing data and instructions to the system user;

[0028] **FIG. 3** is a block diagram diagrammatically depicting the structural arrangement of the system data management unit and its interconnection with other components of the system shown in **FIG. 1**;

[0029] **FIGS. 4-10** depict typical system screen displays of data and information that can be provided by the arrangements shown in **FIGS. 1-3**; and

[0030] **FIG. 11** diagrammatically illustrates an alternative healthcare monitoring system that is arranged in accordance with the invention.

DETAILED DESCRIPTION

[0031] **FIG. 1** depicts a self-care health monitoring system arranged in accordance with the invention. In the arrangement shown in **FIG. 1** a data management unit **10** is electrically interconnected with a handheld microprocessor-based unit **12** via a cable **14**. In the depicted arrangement, data management unit **10** also is electrically interconnected with a blood glucose monitor **16** of the type capable of sensing blood glucose level and producing an electrical signal representative thereof. Although **FIG. 1** illustrates blood glucose monitor **16** as being connected to data management unit **10** by a cable **18** it may be preferable to

construct blood glucose monitor **16** as a plug-in unit that is placed in a recess or other suitable opening or slot in data management unit **10**. Regardless of the manner in which blood glucose monitor **16** is interconnected with data management unit **10** both that interconnection and cable **14** are configured for serial data communication between the interconnected devices.

[0032] Also shown in **FIG. 1** are two additional monitoring devices **20** and **22** which are electrically connected for serial data communication with data management unit **10** via cables **24** and **26** respectively. Monitoring units **20** and **22** of **FIG. 1** represent devices other than blood glucose monitor **16** that can be used to configure the invention for self-care health monitoring applications other than (or in addition to) diabetes care. For example, as is indicated in **FIG. 1** the monitoring device **20** can be a peak-flow meter that provides a digital signal representative of the airflow that results when a person suffering from asthma or another chronic respiratory affliction expels a breath of air through the meter. As is indicated by monitor **22** of **FIG. 1** various other devices can be provided for monitoring conditions such as blood pressure, pulse, and body temperature to thereby realize systems for self-care monitoring and control of conditions such as hypertension, certain heart conditions and various other afflictions and physical conditions. Upon understanding the hereinafter discussed aspects and features of the invention it will be recognized that the invention is easily implemented for these and other types of healthcare monitoring. In particular, monitors used in the practice of the invention can be arranged in a variety of ways as long as the data to be recorded or otherwise employed by handheld microprocessor unit **12** and/or data management unit **10** is provided in serial format in synchronization with clock signals provided by data management unit **10**. As is the case with blood glucose monitor **16** the additional monitors can be configured as plug-in units that are directly received by data management unit **10** or can be connected to data management unit **10** with cables (as shown in **FIG. 1**). As is shown in **FIG. 1**, handheld microprocessor unit **12** includes a display screen **28** and a plurality of switches or keys (**30, 32, 34, 36, and 38** in **FIG. 1**) which are mounted on a housing **40**. Located in the interior of housing **40** but not shown in **FIG. 1** are a microprocessor, memory circuits, and circuitry that interfaces switches **30, 32, 34, 36** and **38** with the microprocessor. Stored in the memory of program handheld microprocessor unit **12** is a set of program instructions that establishes a data protocol that allows handheld microprocessor unit **12** to perform digital data signal processing and generate desired data or graphics for display on display unit **28** when a program cartridge **42** is inserted in a slot or other receptacle in housing **40**. That is, program cartridge **42** of **FIG. 1** includes read-only memory units (or other memory means such as battery-powered random access memory) which store program instructions and data that adapt handheld microprocessor for operation in a blood glucose monitoring system. More specifically, when the instructions and data of program cartridge **42** are combined with program instructions and data included in the internal memory circuits of handheld microprocessor unit **12** handheld microprocessor unit **12** is programmed for processing and displaying blood glucose information in the manner described below and additional monitors to provide health monitoring for asthma and various other previously mentioned chronic conditions. In each case, the plurality of switches or keys

(**30, 32, 34, 36, and 38** in **FIG. 1**) are selectively operated to provide signals that result in pictorial and/or alphanumeric information being displayed by display unit **28**. Various devices are known that meet the above-set forth description of handheld microprocessor unit **12**. For example, compact devices are available in which the plurality of keys allows alphanumeric entry and internal memory is provided for storing information such as names, addresses, phone numbers, and an appointment calendar. Small program cartridge or cards can be inserted in these devices to program the device for various purposes such as the playing of games, spreadsheet application, and foreign language translation sufficient for use in travel. More recently, less compact products that have more extensive computational capability and are generally called "palm top computers" have been introduced into the marketplace. These devices also can include provision for programming the device by means of an insertable program card or cartridge.

[0033] The currently preferred embodiments of the invention are configured and arranged to operate in conjunction with yet another type of handheld microprocessor unit **12**. Specifically, in the currently preferred embodiments of the invention, program cartridge **42** is electrically and physically compatible with commercially available compact video game systems, such as the system manufactured by Nintendo of America Inc. under the trademark "GAME BOY." Configuring data management unit **10** and program cartridge **42** for operation with a handheld video game system has several advantages. For example, the display unit **28** of such a device provides display resolution that allows the invention to display both multi-line alphanumeric information and graphical data. In this regard, the 160x144 pixel dot matrix-type liquid crystal display screen **28** currently used in the above-referenced compact video game systems provides sufficient resolution for at least six lines of alphanumeric text, as well as allowing graphical representation of statistical data such as graphical representation of blood glucose test results for a day, a week, or longer.

[0034] Another advantage of realizing handheld microprocessor unit **12** in the form of a compact video game system is the relatively simple, yet versatile arrangement of switches that is provided by such a device. For example, as is indicated in **FIG. 1** a compact video game system includes a control pad **30** that allows an object displayed on display unit **28** to be moved in a selected direction (i.e., up-down or left-right). As also is indicated in **FIG. 1** compact video game systems typically provide two pair of distinctly-shaped push button switches. In the arrangement shown in **FIG. 1** a pair of spaced-apart circular push button switches (**36** and **38**) and a pair of elongate switches (**32** and **34**) are provided. The functions performed by the two pairs of switches is dependent upon the program instructions contained in each program cartridge **42**. Yet another advantage of utilizing a compact video game system for handheld microprocessor-based unit of **FIG. 1** is the widespread popularity and low cost of such units. In this regard, manufacture and sale of a data management unit **10** blood glucose monitor **16** and program cartridge **42** that operate in conjunction with a compact microprocessor-based video allows the self-care health monitoring system of **FIG. 1** to be manufactured and sold at a lower cost than could be realized in an arrangement in which handheld unit is designed and manufactured solely for use in the system of **FIG. 1**. An even further advantage of using a compact video

game system for handheld microprocessor is that such video game systems include means for easily establishing the electrical interconnection provided by cable in FIG. 1. In particular, such compact video game systems include a connector mounted to the game unit housing (40 in FIG. 1) and a cable that can be connected between the connectors of two video game units to allow interactive operation of the two interconnected units (i.e., to allow contemporaneous game play by two players or competition between players as they individually play identical but separate games). In the preferred embodiments of the invention, the "two-player" cable supplied with the compact video game unit being used as handheld microprocessor unit 12 is used as cable to establish serial data communication between the handheld microprocessor unit 12 (compact video game system) and data management unit 10. In these preferred embodiments, the program instructions stored on the memory of data management unit 10 and program cartridge 42 respectively program data management unit 10 and the compact video game system (i.e., handheld microprocessor unit 12) for interactive operation in which switches 30, 32, 34, 36 and 38 are used to control the operation of data management unit 10 (e.g., to select a particular operational mode such as performance of a blood glucose test or the display of statistical test data and, in addition, to control operation such as selection of an option during operation of the system in a particular operational mode). In each operational mode, data management unit 10 processes data in accordance with program instructions stored in the memory circuits of data management unit 10. Depending upon the operational mode selected by the user, data is supplied to data management unit 10 by blood glucose monitor 16 by additional monitors (20 and 22 in FIG. 1) or any interconnected computers or data processing facility (such as the hereinafter described user's computer 48 and clearinghouse 54 of FIG. 1). During such operation, mode switches are selectively activated so that signals are selectively coupled to the video game system (handheld microprocessor unit 12 and processed in accordance with program instructions stored in program cartridge 42. The signal processing performed by handheld microprocessor unit 12 results in the display of alphanumeric, symbolic, or graphic information on the video game display screen 28 (i.e., display unit 28 in FIG. 1 which allow the user to control system operation and obtain desired test results and other information.

[0035] Although the above-discussed advantages apply to use of the invention by all age groups, employing a compact video game system in the practice of the invention is of special significance in monitoring a child's blood glucose or other health parameters. Children and young adults are familiar with compact video game systems. Thus, children will accept a health monitoring system incorporating a compact video game system more readily than a traditional system, even an embodiment of the invention that uses a different type of handheld microprocessor unit 12. Moreover, an embodiment of the invention that functions in conjunction with a compact video game system can be arranged to motivate children to monitor themselves more closely than they might otherwise by incorporating game-like features and/or animation in system instruction and test result displays. Similarly, the program instructions can be included in program cartridge 41, 42 and 43 (or additional

cartridges) that allow children to select game-like displays that help educate the child about his or her condition and the need for monitoring.

[0036] With continued reference to FIG. 1 data management unit 10 of the currently preferred embodiments of the invention includes a data port 44 that allows communication between data management unit 10 and a personal computer 48 (or other programmable data processor). In the currently preferred embodiments of the invention, data port 44 is an RS-232 connection that allows serial data communication between data management unit 10 and personal computer 48. In the practice of the invention, personal computer 48 can be used to supplement data management unit 10 by, for example, performing more complex analyses of blood glucose and other data that has been supplied to and stored in the memory circuits of data management unit 10. With respect to embodiments of the invention configured for use by a child, personal computer 48 can be used by a parent or guardian to review and analyze the child's progress and to produce printed records for subsequent review by a healthcare professional. Alternatively, personal computer 48 can be used to supply data to data management unit 10 that is not conveniently supplied by using handheld microprocessor switches and as an operator interface to the system shown in FIG. 1. For example, some embodiments of the invention may employ a substantial amount of alphanumeric information that must be entered by the system user. Although it is possible to enter such data by using switches 30, 32, 34, 36 and 38 in conjunction with menus and selection screens displayed on display screen 28 of FIG. 1 it may be more advantageous to use a device such as personal computer 48 for entry of such data. However, if personal computer 48 is used in this manner, some trade-off of system features may be required because data management unit 10 must be temporarily interconnected with personal computer 48 during these operations. That is, some loss of system mobility might result because a suitably programmed personal computer 48 would be needed at each location at which data entry or analysis is to occur.

[0037] As is indicated in FIG. 1 data management unit 10 of the currently preferred embodiments of the invention also includes a modem that allows data communication between data management unit 10 and a remote computing facility identified in FIG. 1 as clearinghouse 54 via a conventional telephone line 64 (indicated by reference numeral 50 in FIG. 1 and a modem 52 that interconnects clearinghouse 54 and telephone line 50. As shall be described in more detail, clearinghouse computing facility 54 facilitates communication between a user of the system shown in FIG. 1 and his or her healthcare professional and can provide additional services such as updating system software. As is indicated by facsimile machine 55 of FIG. 1, a primary function of clearinghouse 54 is providing the healthcare professional with standardized reports 56, which indicate both the current condition and condition trends of the system user. Although a single facsimile machine 55 is shown in FIG. 1 it will be recognized that numerous healthcare professionals (and hence facsimile machine 55 can be connected in signal communication with a clearinghouse 54. Regardless of whether a compact video game system, another type of commercially available handheld microprocessor-based unit, or a specially designed unit is used, the preferred embodiments of FIG. 1 provide a self-care blood glucose monitoring system in which program cartridge 42 (a) hand-

held microprocessor unit **12** for displaying instructions for performing the blood glucose test sequence and associated calibration and test procedures; (b) handheld microprocessor unit **12** for displaying (graphically or alphanumerically) statistical data such as blood glucose test results taken during a specific period of time (e.g., a day, week, etc.); (c) handheld microprocessor unit **12** for supplying control signals and signals representative of food intake or other useful information to data management unit **10**; (d) handheld microprocessor unit **12** for simultaneous graphical display of blood glucose levels with information such as food intake; and, (e) handheld microprocessor unit **12** for displaying information or instructions from a healthcare professional that are coupled to data management unit **10** from a clearinghouse **54**. The manner in which the arrangement of **FIG. 1** implements the above-mentioned functions and others can be better understood with reference to **FIGS. 2 and 3**. Referring first to **FIG. 1** clearinghouse **54** receives data from a plurality of self-care microprocessor-based healthcare systems of the type shown in **FIG. 1** with the individual self-care health monitoring systems being indicated in **FIG. 2** by reference numeral. Preferably, the data supplied to clearinghouse **54** by each individual self-care health monitoring system consists of "raw data," i.e., test results and related data that was stored in memory circuits of data management unit **10** without further processing by data management unit **10**. For example, with respect to the arrangement shown in **FIG. 1** blood glucose test results and associated data such as food intake information, medication dosage and other such conditions are transmitted to clearinghouse **54** and stored with a digitally encoded signal that identifies both the source of the information (i.e., the system user or patient) and those having access to the stored information (i.e., the system user's doctor or other healthcare professional).

[0038] As shall be recognized upon understanding the manner in which it operates, clearinghouse **54** can be considered to be a central server for the various system users (**58** in **FIG. 2**) and each healthcare professional **60**. In that regard, clearinghouse **54** includes conventionally arranged and interconnected digital processing equipment (represented in **FIG. 2** by digital signal processor **57**) which receives digitally encoded information from a user **58** or healthcare professional **60**; processes the information as required; stores the information (processed or unprocessed) in memory if necessary; and, transmits the information to an intended recipient (i.e., user **58** or healthcare professional **60**). In **FIG. 2** rectangular outline **60** represents one of numerous remotely located healthcare professionals who can utilize clearinghouse **54** and the arrangement described relative to **FIG. 1** in monitoring and controlling patient healthcare programs. Shown within outline **60** is a computer **62** (e.g., personal computer), which is coupled to clearinghouse **54** by means of a modem (not shown in **FIG. 2**) and a telephone line **64**. Also shown in **FIG. 2** is the previously mentioned **55** which is coupled to clearinghouse **54** by means of a second telephone line **68**. Using the interface unit of computer **62** (e.g., a keyboard or pointing device such as a mouse), the healthcare professional can establish data communication between computer **62** and clearinghouse **54** via telephone line. Once data communication is established between computer and clearinghouse **54** patient information can be obtained from clearinghouse **54** in a manner similar to the manner in which subscribers to various database

services access and obtain information. In particular, the healthcare professional can transmit an authorization code to clearinghouse **54** that identifies the healthcare professional as an authorized user of the clearinghouse **54** and, in addition, can transmit a signal representing the patient for which healthcare information is being sought. As is the case with conventional database services and other arrangements, the identifying data is keyed into computer by means of a conventional keyboard (not shown in **FIGURE** in response to prompts that are generated at clearinghouse **54** for display by the display unit **28** of computer (not shown in **FIG. 2**). Depending upon the hardware and software arrangement of clearinghouse **54** and selections made by the healthcare professional via computer patient information can be provided to the healthcare professional in different ways. For example, computer **62** can be operated to access data in the form that it is stored in the memory circuits of clearinghouse **54** (i.e., raw data that has not been processed or altered by the computational or data processing arrangements of clearinghouse **54**). Such data can be processed, analyzed, printed and/or displayed by computer using commercially available or custom software. On the other hand, various types of analyses may be performed by clearinghouse **54** with the results of the analyses being transmitted to the remotely located healthcare professional. For example, clearinghouse **54** can process and analyze data in a manner identical to the processing and analysis provided by the self-care monitoring system of **FIG. 1**. With respect to such processing and any other analysis and processing provided by clearinghouse **54** results expressed in alphanumeric format can be sent to computer via telephone line **50** and the modem associated with computer with conventional techniques being used for displaying and/or printing the alphanumeric material for subsequent reference.

[0039] The arrangement of **FIG. 2** also allows the healthcare professional to send messages and/or instructions to each patient via computer telephone line and clearinghouse **54**. In particular, clearinghouse **54** can be programmed to generate a menu that is displayed by computer and allows the healthcare professional to select a mode of operation in which information is to be sent to clearinghouse **54** for subsequent transmission to a user of the system described relative to **FIG. 1**. This same menu (or related submenus) can be used by the healthcare professional to select one or more modes of operation of the above-described type in which either unmodified patient data or the results of data that has been analyzed by clearinghouse **54** is provided to the healthcare provider via computer and/or facsimile machine **55**. In the currently contemplated arrangements, operation of the arrangement of **FIG. 2** to provide the user of the invention with messages or instructions such as changes in medication or other aspects of the healthcare program is similar to the operation that allows the healthcare professional to access data sent by a patient, i.e., transmitted to clearinghouse **54** by a data management unit **10** of **FIG. 1**. The process differs in that the healthcare professional enters the desired message or instruction via the keyboard or other interface unit of computer. Once the data is entered and transmitted to clearinghouse **54** it is stored for subsequent transmission to the user for whom the information or instruction is intended.

[0040] With respect to transmitting stored messages or instructions to a user of the invention, at least two techniques are available. The first technique is based upon the manner

in which operational modes are selected in the practice of the invention. Specifically, in the currently preferred embodiments of the invention, program instructions that are stored in data management unit 10 and program cartridge 42 cause the system of FIG. 1 to generate menu screens which are displayed by display unit 28 of handheld microprocessor unit 12. The menu screens allow the system user to select the basic mode in which the system of FIG. 1 is to operate and, in addition, allow the user to select operational subcategories within the selected mode of operation. Various techniques are known to those skilled in the art for displaying and selecting menu items. For example, in the practice of this invention, one or more main menus can be generated and displayed which allow the system user to select operational modes that may include: (a) a monitor mode (e.g., monitoring of blood glucose level); (b) a display mode (e.g., displaying previously obtained blood glucose test results or other relevant information); (c) an input mode (e.g., a mode for entering data such as providing information that relates to the healthcare regimen, medication dosage, food intake, etc.); and, (d) a communications mode (for establishing a communication link between data management unit 10 and personal computer 48 of FIG. 1 or between data management unit 10 and a remote computing facility such as clearinghouse 54 of FIG. 2). In embodiments of the invention that employ a compact video game system for handheld microprocessor unit 12 the selection of menu screens and the selection of menu screen items preferably is accomplished in substantially the same manner as menu screens and menu items are selected during the playing of a video game. For example, the program instructions stored in data management unit 10 and program cartridge 42 of the arrangement of FIG. 1 can be established so that a predetermined one of the compact video game switches (e.g., switch 32 in FIG. 1 allows the system user to select a desired main menu in the event that multiple main menus are employed. When the desired main menu is displayed, operation by the user of control pad 30 allows a cursor or other indicator that is displayed on the menu to be positioned adjacent to or over the menu item to be selected. Activation of a switch (e.g., switch of the depicted handheld microprocessor unit 12 causes the handheld microprocessor unit 12 and/or data management unit 10 to initiate the selected operational mode or, if selection of operational submodes is required, causes handheld microprocessor unit 12 to display a submenu.

[0041] In view of the above-described manner in which menus and submenus are selected and displayed, it can be recognized that the arrangement of FIG. 1 can be configured and arranged to display a menu or submenu item that allows the user to obtain and display messages or instructions that have been provided by a healthcare professional and stored in clearinghouse 54. For example, a submenu that is generated upon selection of the previously mentioned communications mode can include submenu items that allow the user to select various communication modes, including a mode in which serial data communication is established between data management unit 10 and clearinghouse 54 and data management unit 10 transmits a message status request to clearinghouse 54. When this technique is used, the data processing system of clearinghouse 54 is programmed to search the clearinghouse 54 memory to determine whether a message exists for the user making the request. Any messages stored in memory for that user are then transmitted to the user and processed for display on display unit 28 of

handheld microprocessor unit 12. If no messages exist, clearinghouse 54 transmits a signal that causes display unit 28 to indicate "no messages." In this arrangement, clearinghouse 54 preferably is programmed to store a signal indicating that a stored message has been transmitted to the intended recipient (user). Storing such a signal allows the healthcare professional to determine that messages sent to clearinghouse 54 for forwarding to a patient have been transmitted to that patient. In addition, the program instructions stored in data management unit 10 of FIG. 1 preferably allow the system user to designate whether received messages and instructions are to be stored in the memory of data management unit 10 for subsequent retrieval or review. In addition, in some instances it may be desirable to program clearinghouse 54 and data management unit 10 so that the healthcare professional can designate (i.e., flag) information such as changes in medication that will be prominently displayed to the user (e.g., accompanied by a blinking indicator) and stored in the memory of data management unit 10 regardless of whether the system user designates the information for storage.

[0042] A second technique that can be used for forwarding messages or instructions to a user does not require the system user to select a menu item requesting transmission by clearinghouse 54 of messages that have been stored for forwarding to that user. In particular, clearinghouse 54 can be programmed to operate in a manner that either automatically transmits stored messages for that user when the user operates the system of FIG. 1 to send information to the clearinghouse 54 or programmed to operate in a manner that informs the user that messages are available and allows the user to access the messages when he or she chooses to do so.

[0043] Practicing the invention in an environment in which the healthcare professional uses a personal computer in some or all of the above-discussed ways can be very advantageous. On the other hand, the invention also provides healthcare professionals timely information about system users without the need for a computer (62 in FIG. 2) or any equipment other than a conventional facsimile machine (55 in FIGS. 1 and 2). Specifically, information provided to clearinghouse 54 by a system user can be sent to a healthcare professional 60 via telephone line 68 and facsimile machine 55 with the information being formatted as a standardized graphic or textual report (56 in FIG. 1). Formatting a standardized report 56 (i.e., analyzing and processing data supplied by blood glucose monitor 16 or other system monitor or sensor) can be effected either by data management unit 10 or within the clearinghouse 54 facility. Moreover, various standardized reports can be provided (e.g., the textual and graphic displays discussed below relating to FIGS. 6-10). Preferably, the signal processing arrangement included in clearinghouse 54 allows each healthcare professional 60 to select which of several standardized reports will be routinely transmitted to the healthcare professionals' facsimile 55, and, to do so on a patient-by-patient (user-by-user) basis.

[0044] FIG. 3 illustrates the manner in which data management unit 10 is arranged and interconnected with other system components for effecting the above-described operational aspects of the invention and additional aspects that are described relative to FIGS. 4-10. As is symbolically indicated in FIG. 3 handheld microprocessor unit 12 and blood glucose monitor 16 are connected to a dual universal

asynchronous receiver transmitter **70** (e.g., by cables **14** and **18** of **FIG. 1** respectively). As also is indicated in **FIG. 3** when a system user connects a personal computer **48** (or other programmable digital signal processor) to data port **44**, signal communication is established between personal computer **48** and a second dual universal asynchronous receiver transmitter **72** of data management unit **10**. Additionally, dual universal asynchronous receiver transmitter **72** is coupled to modem **46** so that data communication can be established between data management unit **10** and a remote clearinghouse **54** of **FIGS. 1 and 2**. Currently preferred embodiments of data management unit **10** include a plurality of signal sensors **74**, with an individual signal sensor being associated with each device that is (or may be) interconnected with data management unit **10**. As previously discussed and as is indicated in **FIG. 3**, these devices include handheld microprocessor unit **12**, blood glucose monitor **16**, personal computer **48**, remote computing facility **54** and, in addition, peak-flow meter **20** or other additional monitoring devices. Each signal sensor **74** that is included in data management unit **10** is electrically connected for receiving a signal that will be present when the device with which that particular signal sensor is associated is connected to data management unit **10** and, in addition, is energized (e.g., turned on). For example, in previously mentioned embodiments of the invention in which data port **44** is an RS-232 connection, the signal sensor **74** that is associated with personal computer **48** can be connected to an RS-232 terminal that is supplied power when a personal computer is connected to data port **44** and the personal computer is turned on. In a similar manner, the signal sensor **74** that is associated with clearinghouse **54** can be connected to modem **46** so that the signal sensor **74** receives an electrical signal when modem **46** is interconnected to a remote computing facility (e.g., clearinghouse **54** of **FIG. 2**) via a telephone line **50**. In the arrangement of **FIG. 3**, each signal sensor **74** is a low power switch circuit (e.g., a metal-oxide semiconductor field-effect transistor circuit), which automatically energizes data management unit **10** whenever any one (or more) of the devices associated with signal sensors **74** is connected to data management unit **10** and is energized. Thus, as is indicated in **FIG. 3** by signal path **76** each signal sensor **74** is interconnected with power supply **78** which supplies operating current to the circuitry of data management unit **10** and typically consists of one or more small batteries (e.g., three AAA alkaline cells).

[0045] The microprocessor and other conventional circuitry that enables data management unit **10** to process system signals in accordance with stored program instructions is indicated in **FIG. 3** by central processing unit (CPU) **80**. As is indicated in **FIG. 3** by interconnection **82** between CPU **80** and battery **78**, CPU **80** receives operating current from power supply **78** with power being provided only when one or more of the signal sensors **74** are activated in the previously described manner. A clock/calendar circuit **84** is connected to CPU **80** (via signal path **86** in **FIG. 3** to allow time and date tagging of blood glucose tests and other information. Although not specifically shown in **FIG. 3** operating power is supplied to clock/calendar **84** at all times.

[0046] In operation, CPU **80** receives and sends signals via a data bus (indicated by signal path **88** in **FIG. 3** which interconnects CPU **80** with dual universal asynchronous receiver transmitters **70** and **72**. The data bus **88** also interconnects CPU **80** with memory circuits which, in the

depicted embodiment, include a system read-only memory (ROM) **90** a program random access memory (RAM) **92** and an electronically erasable read-only memory (EEROM) **94**. System ROM **90** stores program instructions and any data required in order to program data management unit **10** so that data management unit **10** and a handheld microprocessor unit **12** that is programmed with a suitable program cartridge **42** provide the previously discussed system operation and, in addition, system operation of the type described relative to **FIGS. 4-10**. During operation of the system, program RAM **92** provides memory space that allows CPU **80** to carry out various operations that are required for sequencing and controlling the operation of the system of **FIG. 1**. In addition, RAM **92** can provide memory space that allows external programs (e.g., programs provided by clearinghouse **54** to be stored and executed. EEROM **94** allows blood glucose test results and other data information to be stored and preserved until the information is no longer needed (i.e., until purposely erased by operating the system to provide an appropriate erase signal to EEROM **94**. **FIGS. 4-10** illustrate typical screen displays that are generated by the arrangement of the invention described relative to **FIGS. 1-3**. Reference will first be made to **FIGS. 4 and 5** which exemplify screen displays that are associated with operation of the invention in the blood glucose monitoring mode. Specifically, in the currently preferred embodiments of the invention, blood glucose monitor **16** operates in conjunction with data management unit **10** and handheld microprocessor unit **12** to: (a) a test or calibration sequence in which tests are performed to confirm that the system is operating properly; and, (b) the blood glucose test sequence in which blood glucose meter **16** senses the user's blood glucose level. Suitable calibration procedures for blood glucose monitors are known in the art. For example, blood glucose monitors often are supplied with a "code strip," that is inserted in the monitor and results in a predetermined value being displayed and stored in memory at the conclusion of the code strip calibration procedure. When such a code strip calibration procedure is used in the practice of the invention, the procedure is selected from one of the system menus. For example, if the system main menu includes a "monitor" menu item, a submenu displaying system calibration options and an option for initiating the blood glucose test may be displayed when the monitor menu item is selected. When a code strip option is available and selected, a sequence of instructions is generated and displayed by display screen **28** of handheld microprocessor unit **12** to prompt the user to insert the code strip and perform all other required operations. At the conclusion of the code strip calibration sequence, display unit **28** of handheld microprocessor unit **12** displays a message indicating whether or not the calibration procedure has been successfully completed. For example, **FIG. 4** illustrates a screen display that informs the system user that the calibration procedure was not successful and that the code strip should be inserted again (i.e., the calibration procedure is to be repeated). As is indicated in **FIG. 4** display screens that indicate a potential malfunction of the system include a prominent message such as the "Attention" notation included in the screen display of **FIG. 4**. As previously indicated, the blood glucose test sequence that is employed in the currently preferred embodiment of the invention is of the type in which a test strip is inserted in a receptacle that is formed in the blood glucose monitor **16**. A drop of the user's blood is then applied to the test strip

and a blood glucose sensing sequence is initiated. When the blood glucose sensing sequence is complete, the user's blood glucose level is displayed.

[0047] In the practice of the invention, program instructions stored in data management unit 10 (e.g., system ROM 90 of FIG. 3) and program instructions stored in program cartridge 42 of handheld microprocessor unit 12 cause the system to display step-by-step monitoring instructions to the system user and, in addition, preferably result in display of diagnostic messages if the test sequence does not proceed in a normal fashion. Although currently available self-contained microprocessor-based blood glucose monitors also display test instruction and diagnostic messages, the invention provides greater message capacity and allows multi-line instructions and diagnostic messages that are displayed in easily understood language rather than cryptic error codes and abbreviated phraseology that is displayed one line or less at a time. For example, as is shown in FIG. 5 the complete results of a blood glucose test (date, time of day, and blood glucose level in milligrams per deciliter) can be concurrently displayed by display screen 28 of handheld microprocessor unit 12 along with an instruction to remove the test strip from blood glucose monitor 16. As previously mentioned, when the blood glucose test is complete, the time and date tagged blood glucose test result is stored in the memory circuits of data management unit 10 (e.g., stored in EEPROM 94 of FIG. 3). The arrangement shown and described relative to FIGS. 1-3 also is advantageous in that data relating to food intake, concurrent medication dosage and other conditions easily can be entered into the system and stored with the time and date tagged blood glucose test result for later review and analysis by the user and/or his or her healthcare professional. Specifically, a menu generated by the system at the beginning or end of the blood glucose monitoring sequence can include items such as "hypoglycemic" and "hyperglycemic," which can be selected using the switches of handheld microprocessor unit 12 (e.g., operation of control pad 30 and switch 36 in FIG. 1) to indicate the user was experiencing hypoglycemic or hyperglycemic symptoms at the time of monitoring blood glucose level. Food intake can be quantitatively entered in terms of "Bread Exchange" units or other suitable terms by, for example, selecting a food intake menu item and using a submenu display and the switches of handheld microprocessor 12 to select and enter the appropriate information. A similar menu item—submenu selection process also can be used to enter medication data such as the type of insulin used at the time of the glucose monitoring sequence and the dosage.

[0048] As was previously mentioned, program instructions stored in data management unit 10 and program instructions stored in program cartridge 42 of handheld microprocessor unit 12 enable the system to display statistical and trend information either in a graphic or alphanumeric format. As is the case relative to controlling other operational aspects of the system, menu screens are provided that allow the system user to select the information that is to be displayed. For example, in the previously discussed embodiments in which a system menu includes a "display" menu item, selection of the menu item results in the display of one or more submenus that list available display options. For example, in the currently preferred embodiments, the user can select graphic display of blood glucose test results over a specific period of time, such as one day, or a particular

week. Such selection results in displays of the type shown in FIGS. 6 and 7 respectively. When blood glucose test results for a single day are displayed (FIG. 6) the day of the week and date can be displayed along with a graphic representation of changes in blood glucose level between the times at which test results were obtained. In the display of FIG. 6 small icons identify points on the graphic representation that correspond to the blood glucose test results (actual samples). Although not shown in FIG. 6 coordinate values for blood glucose level and time of day can be displayed if desired. When the user chooses to display a weekly trend graph (FIG. 7) the display generated by the system is similar to the display of a daily graph, having the time period displayed in conjunction with a graph that consists of lines interconnecting points that correspond to the blood glucose test results.

[0049] The screen display shown in FIG. 8 is representative of statistical data that can be determined by the system of FIG. 1 (using conventional computation techniques) and displayed in alphanumeric format. As previously mentioned, such statistical data and information in various other textual and graphic formats can be provided to a healthcare professional (60 in FIG. 2) in the form of a standardized report 56 (FIG. 1) that is sent by clearinghouse 54 to facsimile machine 55. In the exemplary screen display of FIG. 8 statistical data for blood glucose levels over a period of time (e.g., one week) or, alternatively, for a specified number of monitoring tests is provided. In the exemplary display of FIG. 8, the system (data management unit 10 or clearinghouse 54 also calculates and displays (or prints) the average blood glucose level and the standard deviation. Displayed also is the number of blood glucose test results that were analyzed to obtain the average and the standard deviation; the number of test results under a predetermined level (50 milligrams per deciliter in FIG. 8) and the number of blood glucose tests that were conducted while the user was experiencing hypoglycemic symptoms. As previously noted, in the preferred embodiments of the invention, a screen display that is generated during the blood glucose monitoring sequence allows the user to identify the blood sample being tested as one taken while experiencing hyperglycemic or hypoglycemic symptoms and, in addition, allows the user to specify other relevant information such as food intake and medication information.

[0050] The currently preferred embodiments of the invention also allow the user to select a display menu item that enables the user to sequentially address, in chronological order, the record of each blood glucose test. As is indicated in FIG. 9, each record presented to the system user includes the date and time at which the test was conducted, the blood glucose level, and any other information that the user provided. For example, the screen display of FIG. 9 indicates that the user employed handheld microprocessor unit 12 as an interface to enter data indicating use of 12.5 units of regular insulin; 13.2 units of "NPH" insulin; food intake of one bread exchange unit; and pre-meal hypoglycemic symptoms.

[0051] Use of data management unit 10 in conjunction with handheld microprocessor unit 12 also allows display (or subsequent generation of a standardized report showing blood glucose test results along with food intake and/or medication information. For example, shown in FIG. 10 is a daily graph in which blood glucose level is displayed in the manner described relative to FIG. 6. Related food intake and

medication dosage is indicated directly below contemporaneous blood glucose levels by vertical bar graphs.

[0052] It will be recognized by those skilled in the art that the above-described screen displays and system operation can readily be attained with conventional programming techniques of the type typically used in programming microprocessor arrangements. It also will be recognized by those skilled in the art that various other types of screen displays can be generated and, in addition, that numerous other changes can be made in the embodiments described herein without departing from the scope and the spirit of the invention.

[0053] It will also be recognized by those skilled in the art that the invention can be embodied in forms other than the embodiments described relative to FIGS. 1-10. For example, the invention can employ compact video game systems that are configured differently than the previously discussed handheld video game systems and palm computers. More specifically, as is shown in FIG. 11, a self-health monitoring system arranged in accordance with the invention can employ a compact video game system of the type that includes one or more controllers 100 that are interconnected to a game console 102 via cable 104. As is indicated in FIG. 11 game console 102 is connected to a video monitor or television 106 by means of a cable 108. Although differing in physical configuration, controller 100, game console 102, and the television or video monitor 106 collectively function in the same manner as the handheld microprocessor 12 of FIG. 1. In that regard, a program cartridge 42 is inserted into a receptacle contained in game console 102 with program cartridge 42 including stored program instructions for controlling microprocessor circuitry that is located inside game console 102. Controller 100 includes a control pad 30 or other device functionally equivalent to control pad 30 of FIG. 1 and switches that functionally correspond to switches 32-38 of FIG. 1. Regardless of whether the invention is embodied with a handheld microprocessor unit 12 (FIG. 1) or an arrangement such as the compact video game system (FIG. 11) in some cases it is both possible and advantageous to apportion the signal processing functions and operations differently than was described relative to FIGS. 1-10. For example, in some situations, the microprocessor-based unit that is programmed by a card or cartridge (e.g., handheld unit 12 of FIG. 1 or compact video game console of FIG. 11) includes memory and signal processing capability that allows the microprocessor to perform all or most of the functions and operations attributed to data management unit 10 of the embodiments discussed relative to FIGS. 1-10. That is, the digitally encoded signal supplied by blood glucose monitor 16 (or one of the other monitors 20 and 22 of FIG. 1) can be directly coupled to the microprocessor included in game console 102 of FIG. 11 or handheld microprocessor 12 of FIG. 1. In such an arrangement, the data management unit 10 is a relatively simple signal interface (e.g., interface unit of FIG. 11) the primary purpose of which is carrying signals between the blood glucose monitor 16 (or other monitor) and the microprocessor of game console 102 (FIG. 11) or handheld unit 12 (FIG. 1). In some situations, the interface unit may consist primarily or entirely of a conventional cable arrangement such as a cable for interconnection between RS-232 data ports or other conventional connection arrangements. On the other hand, as is shown in FIG. 11 signal interface 110 can either internally include or be connected to a modem 52,

which receives and transmits signals via a telephone line 50 in the manner described relative to FIGS. 1 and 2.

[0054] It also should be noted that all or a portion of the functions and operations attributed to data management unit 10 of FIG. 1 can be performed by microprocessor circuitry located in blood glucose monitor 16 (or other monitor that is used with the system). For example, a number of commercially available blood glucose monitors include a clock/calendar circuit of the type described relative to FIG. 3 and, in addition, include microprocessor circuitry for generating visual display signals and signals representative of both current and past values of monitored blood glucose level. Conventional programming and design techniques can be employed to adapt such commercially available units for the performance of the various functions and operations attributed in the above discussion of FIGS. 1-11 to data management unit 10 and/or the microprocessors of handheld unit 12 and compact video console 102. In arrangements in which the blood glucose monitor 16 (or other system monitor) includes a microprocessor that is programmed to provide signal processing in the above-described manner, the invention can use a signal interface unit 110 of the above-described type. That is, depending upon the amount of signal processing effected by the monitoring unit (e.g., blood glucose monitor 16) and the amount of signal processing performed by the microprocessor of video game console 102 (or handheld unit 12) the signal interface required ranges from a conventional cable (e.g., interconnection of RS-232 ports) to an arrangement in which signal interface 110 is arranged for signal communication with an internal or external modem (e.g., modem 52 of FIG. 11) or an arrangement in which signal interface 110 provides only a portion of the signal processing described relative to FIGS. 1-10. The invention also is capable of transmitting information to a remote location (e.g., clearinghouse 54 and/or a remotely located healthcare professional) by means other than conventional telephone lines. For example, a modem (52 in FIGS. 1 and 11) that is configured for use with a cellular telephone system can be employed to transmit the signals provided by the healthcare monitoring system to a remote location via modulated RF transmission. Moreover, the invention can be employed with various digital networks such as recently developed interactive voice, video and data systems such as television systems in which a television and user interface apparatus is interactively coupled to a remote location via coaxial or fiberoptic cable and other transmission media (indicated in FIG. 11) by cable 112 which is connected to television or video monitor. In such an arrangement, compact video game controller and the microprocessor of video game console 102 can be programmed to provide the user interface functions required for transmission and reception of signals via the interactive system. Alternatively, the signals provided by video game console 102 (or handheld unit if FIG. 1) can be supplied to the user interface of the interactive system (not shown in FIG. 11) in a format that is compatible with the interactive system and allows the system user interface to be used to control signal transmission between the healthcare system and a remote facility such as clearinghouse 54. FIGS. 1 and 2.

1. A networked health-monitoring system configured to collect and process patient health-related data, comprising: at least one handheld microprocessor device including a display; and a memory; at least one central server connected

to receive health-related data communicated to the microprocessor device; and at least one health care professional computer, remotely located from and in signal communication with the central server to receive patient health-related information based on the patient health-related data received from the handheld microprocessor device, wherein the system is configured to convert the handheld microprocessor device into a healthcare monitoring device that functions to (a) monitor at least one patient health condition; and (b) communicate data related to the monitored condition to the central server.

2. The system of claim 1, wherein the memory includes stored program instructions for generating health-monitoring related information on the display.

3. The system of claim 2, wherein the handheld device is capable of displaying pictorial health-monitoring related information.

4. The system of claim 3, wherein the handheld device is capable of displaying animated health-monitoring related information.

5. The system of claim 2, wherein the memory is a program cartridge.

6. The system of claim 4, wherein the handheld device includes buttons, keys or switches.

7. The system of claim 2, further comprising at least one other health-monitoring device arranged to communicate health-related data to the health care professional computer.

8. The system of claim 7, further comprising a data management unit configured to facilitate collection of patient health-related data.

9. The system of claim 8, wherein the data management unit facilitates collection of health-related data by receiving data related to the monitored condition from at least one of the health-monitoring devices.

10. The system of claim 7, wherein at least one of the health-monitoring devices includes one or more of the set consisting of a blood glucose monitor; a peak flow meter; a blood pressure monitor; a pulse monitor; and a body temperature monitor.

11. The system of claim 7, wherein the remote sites further include at least one personal computer connected to the data management unit.

12. The system of claim 2, wherein the system generates at least one report based on the health-related data.

13. The system of claim 12, wherein at least one report is standardized.

14. The system of claim 12, wherein the system is configured to allow a health care professional to select which of a plurality of standardized reports is produced.

15. The system of claim 12, wherein the report uses graphs and/or icons.

16. The system of claim 12, wherein the report can be generated periodically.

17. The system of claim 12, wherein the server can generate the report.

18. The system of claim 12, wherein the system is configured to cause the presentation of at least one report on the display at a remote patient site.

19. The system of claim 12, wherein the system can display statistical and/or trend information.

20. The system of claim 19, wherein the system can display statistical or trend information to the patient.

21. The system of claim 12, wherein the report includes information data for a period of time.

22. The system of claim 2, wherein the system is configured to transmit at least one message for display on at least one display.

23. The system of claim 22, wherein the message includes step-by-step instructions.

24. The system of claim 22, wherein the message includes results of a test.

25. The system of claim 22, wherein the message includes diagnostic information indicating whether a test has proceeded in a normal fashion.

26. The system of claim 22, wherein the message is a multi-line message.

27. The system of claim 22, wherein the message is a health care professional selected message.

28. The system of claim 22, wherein the health care professional generates the selected message.

29. The system of claim 22, wherein the message is a educational or motivational.

30. The system of claim 27, wherein the system is configured to transmit the message can be to a specific patient.

31. The system of claim 27, wherein the system is configured to transmit the message automatically to the patient.

32. The system of claim 27, wherein the system enables the patient to choose when to receive the message.

33. The system of claim 27, wherein the message can be stored before being transmitted to the patient.

34. The system of claim 2, wherein the system is configured to allow the patient to control the display of information using at least one menu.

35. The system of claim 34, wherein the menu allows the patient to select any one of the operational modes from the set consisting of: a display mode for displaying relevant information; an input mode for providing information; and a communications mode for establishing a link with the central server.

36. The system of claim 31, wherein the menu allows a patient to select a monitoring mode in which at least one health-monitoring device is used to monitor at least one patient health condition at at least one remote patient site; and to communicate data related to the monitored condition to the central server.

37. The system of claim 34, wherein the menu allows the patient to display messages or instructions from a health care professional.

38. The system of claim 2, wherein the system is configured to enable the patient to respond to information on the display by using a cursor or other indicator positioned at a selected item.

39. The system of claim 2, wherein the system is configured to enable programs to be provided from the server, for storage in a memory and execution at a remote patient site.

40. The system of claim 2, wherein the patient can indicate user experienced symptoms to the system.

41. The system of claim 2, wherein the system can capture quantitative measurements.

42. The system of claim 41, wherein the system can capture medication data.

43. The system of claim 1, wherein the collected patient health-related data includes time data.

44. The system of claim 1, wherein the healthcare professional receives the report after transmitting an authoriza-

tion code to the server that identifies an associated health-care professional as an authorized user.

45. A method of collecting and processing patient health-related data, comprising: using at least one handheld micro-processor device, including a display and a memory, as a healthcare monitoring device to facilitate the collection of patient health-related data resulting from the monitoring of at least one patient health condition; connecting at least one central server to receive the collected data; communicating the collected data from the handheld device to the central server; putting at least one remotely-located, health-care-professional computer in signal communication with the central server; and receiving, at the health care professional computer, patient health-related information based on the collected data communicated to the server

46. The method of claim 45, wherein the memory includes stored program instructions for generating health-monitoring related information on the display.

47. The method of claim 46, further comprising displaying pictorial health-monitoring related information on the handheld device.

48. The method of claim 47, further comprising displaying animated health-monitoring related information on the handheld device.

49. The method of claim 46, wherein the memory is a program cartridge.

50. The method of claim 48, wherein the handheld device includes buttons, keys or switches.

51. The method of claim 46, further comprising at least one other health-monitoring device to communicate arranging health-related data to the health care professional computer.

52. The method of claim 51, further comprising using a data management unit to facilitate collection of patient health-related data.

53. The method of claim 52, wherein the data management unit facilitates collection of health-related data by receiving data related to the monitored condition from at least one of the health-monitoring devices.

54. The method of claim 53, further comprising connecting at least one personal computer to the data management unit at the remote sites.

55. The method of claim 51, wherein at least one of the health-monitoring devices is one or more of the set consisting of a blood glucose monitor; a peak flow meter; a blood pressure monitor; a pulse monitor; and a body temperature monitor.

56. The method of claim 46, further comprising producing reports based on the health-related data.

57. The method of claim 56, wherein the reports are standardized.

58. The method of claim 57, wherein a health care professional selects which of a plurality of standardized reports is produced.

59. The method of claim 56, wherein the reports use graphs and/or icons.

60. The method of claim 56, wherein the reports can be generated periodically.

61. The method of claim 56, wherein the server can generate the report.

62. The method of claim 56, further comprising displaying at least one report on a display at a remote patient site.

63. The method of claim 56, further comprising displaying statistical and/or trend information.

64. The method of claim 63, wherein the statistical or trend information is displayed to the patient.

65. The method of claim 56, wherein the report includes information data for a period of time.

66. The method of claim 46, further comprising transmitting at least one message for display on at least one display.

67. The method of claim 66, wherein the message includes step-by-step instructions.

68. The method of claim 66, wherein the message includes results of a test.

69. The method of claim 66, wherein the message includes diagnostic information indicating whether a test has proceeded in a normal fashion.

70. The method of claim 66, wherein the message is a multi-line message.

71. The method of claim 66, wherein a health care professional selects the message.

72. The method of claim 66 wherein the health care professional generates the selected message.

73. The method of claim 66, wherein the message is educational or motivational.

74. The method of claim 71, further comprising transmitting the message to a specific patient.

75. The method of claim 71, further comprising transmitting the message automatically to the patient.

76. The method of claim 71, further comprising transmitting to the patient when the patient chooses.

77. The method of claim 76, further comprising storing the message before transmitting to the patient.

78. The method of claim 46, wherein the patient controls the display of information using at least one menu.

79. The method of claim 48, wherein the menu allows a patient to select any one of the operational modes from the set consisting of: a display mode for displaying relevant information; an input mode for providing information; and a communications mode for establishing a link with the central server.

80. The method of claim 78, wherein using the menu the patient selects a monitoring mode in which at least one health-monitoring device is used to monitor at least one patient health condition at at least one remote patient site; and to communicate data related to the monitored condition to the central server.

81. The method of claim 78, wherein the menu allows a patient to display messages or instructions from a health care professional.

82. The method of claim 46, wherein the patient responds to information on the display by using a cursor or other indicator positioned at a selected item.

83. The method of claim 46, further comprising: providing programs from the server to a remote patient site; and storing in a memory and executing the programs at a remote site.

84. The method of claim 46, wherein the patient indicates user experienced symptoms to the handheld device.

85. The method of claim 46, further comprising capturing quantitative measurements.

86. The method of claim 85, further comprising capturing medication data.

87. The method of claim 45, wherein the collected patient health-related data includes time data.

88. The method of claim 56, wherein the healthcare professional receives the report after transmitting an authorization code to the server that identifies an associates healthcare professional as an authorized user.

89. A networked health-monitoring system configured to collect and process patient health-related data, comprising: At least one handheld microprocessor means, including a displayed and a memory, for monitoring at least one patient health condition; and communicating data related to the monitored condition to a central server means; at least one central server means for receiving health-related data communicated to the microprocessor device; and at least one

health care professional computer, remotely located from and in signal communication with the central server to receive patient health-related information based on the patient health-related data received from the handheld microprocessor device.

* * * * *

专利名称(译)	使用手持设备进行网络远程患者监护		
公开(公告)号	US20040117210A1	公开(公告)日	2004-06-17
申请号	US10/605229	申请日	2003-09-16
[标]申请(专利权)人(译)	健康英雄网络		
申请(专利权)人(译)	健康英雄网络		
当前申请(专利权)人(译)	健康英雄网络		
[标]发明人	BROWN STEPHEN J		
发明人	BROWN, STEPHEN J		
IPC分类号	A61B5/00 A61B5/0205 A61B5/087 G01N33/487 G06F15/02 G16H10/60 G06F17/60		
CPC分类号	A61B5/0205 A61B5/0022 A61B5/14532 A61B5/6896 A61B2560/0443 G01N33/48792 G06F15/025 G06F19/322 G06F19/3406 G06F19/3412 G06F19/3418 G06F19/345 G06F19/3456 G06F19/3475 G06F19/3481 G06F19/3487 G06Q10/10 G06Q40/08 G06Q50/22 G06Q50/24 Y10S128/903 A61B5/743 G06Q40/12 A61B5/087 G16H10/60 G16H15/00 G16H20/17 G16H40/40 G16H40/63 G16H40/67 G16H50/20		
其他公开文献	US8249894		
外部链接	Espacenet USPTO		

摘要(译)

联网健康监测系统被配置为收集和處理患者健康相关数据。该系统包括至少一个具有显示器的手持微处理器设备;和记忆。连接至少一个中央服务器以接收传送到手持微处理器设备的健康相关数据,并且至少一个远程定位的健康护理专业计算机与中央服务器进行信号通信。它基于从手持微处理器设备接收的患者健康相关数据接收患者健康相关信息。该系统被配置为将手持式微处理器设备转换为医疗监控设备,该医疗监控设备用于监控患者健康状况并将与监控的状况相关的数据传送到中央服务器。

