



US008167813B2

(12) **United States Patent**
Cohen et al.

(10) **Patent No.:** **US 8,167,813 B2**
(45) **Date of Patent:** **May 1, 2012**

(54) **SYSTEMS AND METHODS FOR LOCATING A BLOOD VESSEL**

(75) Inventors: **Robert F. Cohen**, Kensington, MD (US); **David M. Tumey**, Germantown, MD (US)

(73) Assignee: **Immersion Medical, Inc.**, Baltimore, MD (US)

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 721 days.

4,581,972 A	4/1986	Hoshino
4,603,284 A	7/1986	Perzley
4,794,392 A	12/1988	Selinko
4,823,634 A	4/1989	Culver
4,853,674 A	8/1989	Kiss
4,918,438 A	4/1990	Yamasaki
4,931,765 A	6/1990	Rollins et al.
4,964,004 A	10/1990	Barker
5,003,984 A	4/1991	Muraki et al.
5,117,449 A	5/1992	Metroka et al.
5,165,897 A	11/1992	Johnson
5,175,459 A	12/1992	Danial et al.

(Continued)

FOREIGN PATENT DOCUMENTS

(21) Appl. No.: **11/749,825**

DE 10 2004 001931 8/2005

(22) Filed: **May 17, 2007**

(Continued)

(65) **Prior Publication Data**

US 2008/0287824 A1 Nov. 20, 2008

OTHER PUBLICATIONS

Patent Cooperation Treaty, International Search Report, International Application No. PCT/US2008/004471, mailed Jul. 18, 2008.

(51) **Int. Cl.**

A61B 5/00 (2006.01)

(Continued)

(52) **U.S. Cl.** **600/549**

(58) **Field of Classification Search** **600/549**
See application file for complete search history.

Primary Examiner — Max Hindenburg

Assistant Examiner — Renee Danega

(74) *Attorney, Agent, or Firm* — Kilpatrick Townsend & Stockton LLP

(56) **References Cited**

U.S. PATENT DOCUMENTS


3,618,070 A	11/1971	Kagan
3,911,416 A	10/1975	Feder
4,028,502 A	6/1977	Moricca et al.
4,227,319 A	10/1980	Guy et al.
4,262,549 A	4/1981	Schwellenbach
4,278,920 A	7/1981	Ruoff, Jr.
4,333,070 A	6/1982	Barnes
4,352,091 A	9/1982	Yamasaki
4,421,953 A	12/1983	Zielinski
4,436,188 A	3/1984	Jones
4,464,117 A	8/1984	Foerst
4,484,191 A	11/1984	Vavra

(57)

ABSTRACT

Systems and methods for locating a blood vessel are described. One described method includes receiving a first temperature measure associated with a first point on a surface of a skin; receiving a second temperature measure associated with a second point on the surface of the skin, and determining a differential between the first temperature measure and the second temperature measure. The method further includes generating an output signal indicating the presence of a blood vessel if the differential exceeds a threshold.

41 Claims, 5 Drawing Sheets



U.S. PATENT DOCUMENTS

5,189,389 A 2/1993 DeLuca et al.
 5,205,293 A * 4/1993 Ito et al. 600/504
 5,283,970 A 2/1994 Aigner
 5,366,376 A 11/1994 Copperman et al.
 5,368,484 A 11/1994 Copperman et al.
 5,414,337 A 5/1995 Schuler
 5,436,622 A 7/1995 Gutman et al.
 5,437,607 A 8/1995 Taylor
 5,459,382 A 10/1995 Jacobus et al.
 5,482,051 A 1/1996 Reddy et al.
 5,489,812 A 2/1996 Furuhashi et al.
 5,506,605 A 4/1996 Paley
 5,508,688 A 4/1996 Mochizuki
 5,575,761 A 11/1996 Hajianpour
 5,619,181 A 4/1997 Murray
 5,625,576 A 4/1997 Massie et al.
 5,642,413 A 6/1997 Little
 5,646,589 A 7/1997 Murray et al.
 5,666,473 A 9/1997 Wallace
 5,692,956 A 12/1997 Rifkin
 5,696,497 A 12/1997 Mottier et al.
 5,729,589 A 3/1998 Samson
 5,754,096 A 5/1998 Muto et al.
 5,757,280 A 5/1998 Motohashi
 5,764,751 A 6/1998 Konishi
 5,767,787 A 6/1998 Kudoh et al.
 5,816,823 A 10/1998 Naimark et al.
 5,844,392 A 12/1998 Peurach et al.
 5,844,498 A 12/1998 Ide
 5,867,796 A 2/1999 Inutsuka
 5,873,024 A 2/1999 Suzuki
 5,887,995 A 3/1999 Holehan
 5,889,670 A 3/1999 Schuler et al.
 5,917,906 A 6/1999 Thornton
 5,955,964 A 9/1999 Tada
 5,956,484 A 9/1999 Rosenberg et al.
 5,966,655 A 10/1999 Hardouin
 5,973,689 A 10/1999 Gallery
 5,988,902 A 11/1999 Holehan
 6,014,572 A 1/2000 Takahashi
 6,046,726 A 4/2000 Keyson
 6,091,321 A 7/2000 Karell
 6,113,459 A 9/2000 Nammoto
 6,118,979 A 9/2000 Powell
 6,131,097 A 10/2000 Peurach et al.
 6,175,721 B1 1/2001 Hayato
 6,218,958 B1 4/2001 Eichstaedt et al.
 6,218,966 B1 4/2001 Goodwin et al.
 6,272,319 B1 8/2001 Narusawa
 6,300,938 B1 10/2001 Culver
 6,307,465 B1 10/2001 Kayama et al.
 6,373,463 B1 4/2002 Beeks
 6,374,255 B1 4/2002 Peurach et al.
 6,418,323 B1 7/2002 Bright et al.
 6,424,251 B1 7/2002 Byrne
 6,433,771 B1 8/2002 Yocum et al.
 6,448,977 B1 9/2002 Braun et al.
 6,464,646 B1 * 10/2002 Shalom et al. 600/549
 6,563,487 B2 5/2003 Martin et al.
 6,574,489 B1 6/2003 Uriya
 6,650,338 B1 11/2003 Kolarov et al.
 6,686,901 B2 2/2004 Rosenberg
 6,819,312 B2 11/2004 Fish
 6,864,877 B2 3/2005 Braun et al.
 2002/0145512 A1 10/2002 Sleichter, III et al.
 2002/0149561 A1 10/2002 Fukumoto et al.
 2003/0030619 A1 2/2003 Martin et al.
 2003/0090460 A1 5/2003 Schena et al.
 2003/0122658 A1 7/2003 Takahashi
 2003/0169151 A1 9/2003 Ebling et al.
 2003/0188594 A1 10/2003 Levin et al.
 2003/0222766 A1 12/2003 Rollins et al.
 2004/0014484 A1 1/2004 Kawashima
 2004/0056840 A1 3/2004 Goldenberg et al.
 2004/0152991 A1 8/2004 Pompei
 2005/0065451 A1 * 3/2005 Pompei et al. 600/549
 2005/0093847 A1 5/2005 Altkorn et al.
 2005/0109145 A1 5/2005 Levin et al.

2005/0162383 A1 7/2005 Rosenberg
 2006/0020212 A1 1/2006 Xu et al.
 2006/0253005 A1 * 11/2006 Drinan et al. 600/300

FOREIGN PATENT DOCUMENTS

WO WO 95/20787 8/1995
 WO WO 97/18546 5/1997
 WO WO 99/48420 9/1999
 WO WO 01/91100 11/2001
 WO WO 2007/006134 1/2007

OTHER PUBLICATIONS

Curry, K., Supporting Collaborative Interaction in Tele-immersion, Thesis submitted to the Faculty of the Virginia Polytechnic Institute and the State University in partial fulfillment of the requirements for the degree of Master of Science in Computer Science and Applications, 1998.

Dennerlein, J. et al., Vibrotactile Feedback for Industrial Telemanipulators, Presented at the Sixth Annual Symposium on Haptic Interfaces for Virtual Environment and Teleoperator Systems, ASME IMECE, Dallas, Texas, Nov. 15-21, 1999.

Eberhardt, S. et al., Force Reflection for Wimps: A Button Acquisition Experiment, Proceedings of the ASME Dynamic Systems and Control Division, presented at the 1997 ASME International Mechanical Engineering Congress and Exposition, Nov. 16-21, 1997, Dallas, Texas.

IEEE International Conference on Robotics and Automation, May 16-20, 1998, Lueven, Belgium.

Hayward, V. et al., Parameter Sensitivity Analysis for Design and Control of Force Transmission Systems, McGill University Center for Intelligent machines, 3480 University Street, Montreal, Quebec.

Kim, W., Telemanipulator Technology and Space Telerobotics, Proceedings from SPIE—The International Society for Optical Engineering, Sep. 7-9, 1993, Boston, Mass.

Kontarinis, D. et al., Tactile Display of Vibratory Information in Teleoperation and Virtual Environments, Presence, vol. 4, No. 4, Fall 1995, pp. 387-402.

Kontarinis, D. et al., Display of High-Frequency Tactile Information to Teleoperators, Harvard University Division of Applied Sciences, Cambridge, Mass.

MacLean, K., Designing with Haptic Feedback, Symposium on Haptic Feedback in the Proceedings of the IEEE Conference on Robotics and Automation, Apr. 22-28, 2000.

Marcus, B., Touch Feedback in Surgery, Official Proceedings of Virtual Reality and Medicine the Cutting Edge, Sep. 8-11, 1994, The New York Hilton.

McAfee, D. et al., Teleoperator Subsystem/ Telerobot Demonstrator: Force Reflecting Hand Controller Equipment Manual, Jet Propulsion Laboratory, Jan. 1988.

McLaughlin, M. et al., The USC Interactive Art Museum: Removing the Barriers between Museums and their Constituencies, web site at <http://ascusc.org/icmc/paperforica.html>, as available via the Internet and printed Jul. 22, 2003.

Mine, M. et al., Virtual Environment Interaction Techniques, Department of Computer Science, University of North Carolina, Chapel Hill, NC, 1995.

Minsky, M., Computational Haptics: The Sandpaper System for Synthesizing Texture for a Force-Feedback Display, Submitted to the Program in Media Arts and Sciences, School of Architecture and Planning, in partial fulfillment of the requirements for the degree of Doctor of Philosophy at the Massachusetts Institute of Technology, Jun. 1995.

Noll, M., Man-Machine Tactile, SID Journal, Jul./Aug. 1972.

Ouh-Young, M. et al., Creating an Illusion of Feel: Control Issues in Force Display, Computer Science Department, University of North Carolina at Chapel Hill, Sep. 16, 1989.

Ouh-Young, M., Force Display in Molecular Docking, The University of North Carolina at Chapel Hill, 1990.

Ouh-Young, M. et al., The Development of a Low-Cost Force Feedback Joystick and its Use in the Virtual Environment. Proceedings of the Third Pacific Conference on Computer Graphics and Applications, Pacific Graphics, Aug. 21-24, 1995.

- Pao, L. et al., Synergistic Visual/Haptic Computer Interfaces, Hanoi, Vietnam, pp. 155-162, May 1998.
- Patrick, N. et al., Design and Testing of a Non-Reactive, Fingertip, Tactile Display for Interaction with Remote Environments, Massachusetts Institute of Technology, Department of Mechanical Engineering.
- Patrick, N., Design, Construction, and Testing of a Fingertip Tactile Display for Interaction with Virtual and Remote Environments, Submitted to the Department of Mechanical Engineering in partial fulfillment of the requirement for the degree of Masters of Science in Mechanical Engineering at the Mass. University of Technology, Aug. 1990.
- Pimentel, K. et al., Virtual Reality through the New Looking Glass, Second Edition, 1995.
- Rabinowitz, W. et al., Multidimensional Tactile Displays: Identification of Vibratory Intensity, Frequency, and Contractor Area, Journal of the Acoustical Society of America, vol. 82, No. 4, Oct. 1987.
- Ramstein, C., Combining Haptic and Braille Technologies: Design Issues and Pilot Study, Second Annual ACM Conference on Assistive Technology, Apr. 11-12, 1996.
- Rosenburg, L., Virtual Fixtures: Perceptual Overlays Enhance Operator Performance in Telepresence Tasks, A Dissertation submitted to the Department of Mechanical Engineering and the Committee on Graduate Studies of Stanford University in partial fulfillment of the requirements for the degree of Doctor of Philosophy, Jun. 1994.
- Ruspini, D. et al., The Haptic Display of Complex Graphical Environments, Computer graphics Proceedings, Annual Conference Series, 1997.
- Russo, M., The Design and Implementation of a Three Degree of Freedom Force Output Joystick, Submitted to the Department of Mechanical Engineering in partial fulfillment of the requirement for the degree of Masters of Science in Mechanical Engineering at the Mass. University of Technology, May 1990.
- Safe Flight Instrument Corporation, Coaxial Control Shaker, part No. C-25502, Jul. 1, 1967, revised Jan. 28, 2002.
- Scannell, T., Taking a Joystick Ride, Computer Currents, Boston Edition, vol. 9, No. 11, Nov. 1994.
- Schena, B., Patent Application Transmittal, Directional Inertial Tactile Feedback using Rotating Masses, Sep. 28, 2001.
- Schmult, B. et al., Application Areas for a Force-Feedback Joystick, DSC-vol. 49, Advances in Robotics, Mechatronics, and Haptic Interfaces, ASME 1993.
- Shimoga, K. , Finger Force and Touch Feedback Issues in Dexterous Telemanipulation, Proceedings from the Fourth Annual Conference on Intelligent Robotic Systems for Space Exploration, Rensselaer Polytechnic Institute, Troy, New York, Sep. 30-Oct. 1, 1992.
- Snow, E. New Technology Transmittal, Model-X Force Reflecting Hand Controller, Jun. 15, 1989.
- SMK, Multi-Functional Touch panel, Force-Feedback Type, Developed, Sep. 30, 2002.
- SMK, Force Feedback Type Optical Touch Panel Developed, Oct. 30, 2002.
- Stanley, M. et al., Computer Simulation of Interacting Dynamic Mechanical Systems using Distributed Memory Parallel Processors, DSC-vol. 42, Advances in Robotics, ASME 1992.
- Terry, J. et al., Tactile Feedback in a Computer Mouse, Proceedings of the Fourteenth Annual Northeast Bioengineering Conference, Mar. 10-11, 1988, University of New Hampshire.
- Wiker, S., Teletouch Display Development : Phase 1 Report, Technical Report 1230, Jul. 1988.
- Patent Cooperation Treaty, Notification concerning Transmittal of International Preliminary Report on Patentability, International Application No. PCT/US2008/004471, mailed Nov. 26, 2009.

* cited by examiner




Figure 1




Figure 2




Figure 3




Figure 4




Figure 5

1

**SYSTEMS AND METHODS FOR LOCATING A
BLOOD VESSEL****FIELD OF THE INVENTION**

The present invention generally relates to medical care. More particularly, the present invention relates to systems and methods for locating a blood vessel.

BACKGROUND

Determining the location of a blood vessel is a common medical procedure. Historically however, the systems and methods that medical practitioners use for locating blood vessels have been imprecise, cumbersome, and/or expensive.

For example, one common conventional method for locating a blood vessel involves restricting blood flow to a patient's arm and visually identifying a blood vessel. While this conventional method is widely used and inexpensive, it suffers from several problems. For instance, even in ideal conditions, determining the precise location of a blood vessel using this method may be difficult. Also, the conventional method is invasive, causing a patient discomfort as their arm is being restricted. The procedure may be further complicated with patients who are experiencing trauma, or with patients who have darker or thicker skin.

Rather than using a conventional manual method, a medical practitioner may use a device for locating a blood vessel. However, conventional devices that attempt to locate blood vessels may suffer from inaccuracy, invasiveness, high cost, and relative impracticality. And some devices may only work on certain patients.

Thus a need exists for an accurate, convenient, and inexpensive device for locating blood vessels.

SUMMARY

Embodiments of the present invention disclosed herein provide systems and methods for locating a blood vessel.

One embodiment of the invention is a system comprising a temperature sensor operable to take at least two temperature measures of at least two points on a surface of a skin. The embodiment further comprises a processor in communication with the temperature sensor and configured to receive a first temperature measure from the temperature sensor, receive a second temperature measure from the temperature sensor, determine a differential between the first temperature measure and the second temperature measure, and generate an output signal indicating the presence of a blood vessel if the differential exceeds a threshold. The embodiment may further comprise an indicator configured to receive the output signal and, in response, indicate the presence of the blood vessel.

Another embodiment of the invention implements a method comprising receiving a first temperature measure associated with a first point on a surface of a skin, receiving a second temperature measure associated with a second point on the surface of the skin, and determining a differential between the first temperature measure and the second temperature measure. The method further comprises generating an output signal indicating the presence of a blood vessel if the differential exceeds a threshold. In another embodiment, a computer-readable medium (such as, for example random access memory or a computer disk) comprises code for carrying out such a method.

2

Further details and advantages of embodiments of the invention are set forth below.

BRIEF DESCRIPTION OF THE DRAWINGS

These and other features, aspects, and advantages of the invention are better understood when the following Detailed Description is read with reference to the accompanying drawings, wherein:

FIG. 1 is an illustration of a blood vessel locator in one embodiment of the present invention;

FIG. 2 is a block diagram illustrating a blood vessel locator in one embodiment of the present invention;

FIG. 3 is a block diagram illustrating a second blood vessel locator in one embodiment of the present invention;

FIG. 4 is a flow diagram illustrating a first method for locating a blood vessel in one embodiment of the present invention; and

FIG. 5 is a flow diagram illustrating a second method for locating a blood vessel in one embodiment of the present invention.

DETAILED DESCRIPTION

Embodiments of the present invention provide systems and methods for locating a blood vessel. In one illustrative embodiment, a blood vessel locator is embodied in a hand-held device that includes a temperature sensor. A medical practitioner holds the blood vessel locator on or near the patient's skin, for example, on the skin of the patient's arm. As the medical practitioner moves the locator across the patient's arm, the temperature sensor takes temperature readings at points on the surface of the skin and outputs these temperature readings to a processor housed in the device. Since the temperature of the skin above a blood vessel may be different from the temperature of skin below which no blood vessel is present, a blood vessel may be located by locating a temperature differential between two points on the surface of a skin. The processor continually calculates the differences in skin temperature between the current reading and the previous reading or readings.

When the processor determines that a difference in temperature exists, the processor compares the observed difference between two temperature readings to a pre-determined threshold stored in memory. If the difference exceeds the pre-determined threshold, a blood vessel may be present, and the device provides an indication that a blood vessel has been located. For instance, the device may light a light emitting diode (LED), vibrate the housing, beep, or provide some other indication. The device may also mark the skin with a small ink dot at the location of a blood vessel so the medical practitioner can easily find the spot after the locator has been moved away in preparation for inserting a needle into the blood vessel or performing some other procedure.

This example is given to introduce the reader to the general subject matter discussed. The invention is not limited to this example. Below, an illustrative blood vessel locator is introduced. Then, example blood vessel locators and methods to locate a blood vessel are described.

Illustrative Blood Vessel Locator

Referring now to the drawings in which like numerals indicate like elements throughout the several figures, FIG. 1 is an illustration of a blood vessel locator in one embodiment of the present invention.

3

In one embodiment, the blood vessel locator **102** shown in FIG. 1 is a self-contained, battery-powered handheld device. In other embodiments, the device may be tethered, for instance, to a power supply, visual display, or other device. The locator **102** shown in FIG. 1 is placed above or on the skin of a patient's arm **106**. A medical practitioner then guides the locator **102** across the surface of the patient's skin **106**. For example, the blood vessel locator **102** may be moved laterally in the direction of arrow **1-1** across the surface of the skin **106**.

In other embodiments, the blood vessel locator **102** may be moved in other directions. For instance, the locator **102** may be moved in a circular pattern or laterally and then longitudinally. In other embodiments, the surface of the skin **106** may be moved under the blood vessel locator **102**, while the locator **102** remains in a stationary position. For instance, the locator **102** may be fixed in a stand (not shown). While the embodiment shown in FIG. 1 is intended for manual operation, in some embodiments, the blood vessel locator **102** may be operated by mechanical means.

The blood vessel locator **102** also includes one or more temperature sensor(s) (not shown), which are at least partially contained within the housing. As the blood vessel locator **102** moves across the surface of the skin **106**, the temperature sensor(s) detect the temperature of the surface of the skin **106**. The temperature sensor(s) may be sensitive to a limited range of temperatures. The temperature sensor(s) may provide continuous temperature data when sensing temperatures within this range. The temperature sensor(s) may be located so that the actual sensor passes through an opening on the bottom surface of the housing of the locator **102**, and may detect the temperature of the surface of the skin through direct contact. Alternatively, the sensor(s) may be attached to the outside of the housing. Some embodiments utilize one or more temperature sensor(s) that are configured to sense the temperature of the skin without direct contact.

The blood vessel locator **102** shown in FIG. 1 also comprises a processor (not shown). In a handheld device, such as the one illustrated, the processor is contained within the housing of the locator **102**. In other embodiments the processor may be positioned externally, for instance, in a host device to which the locator **102** is attached. When the temperature sensor detects a temperature, it outputs the temperature measure to the processor, which stores the temperature measure in some type of computer-readable medium, such as random access memory (RAM).

In one embodiment, once the processor receives at least two temperature measures, it calculates a differential between the two measures. The processor may be programmed to ignore temperature measures within a range of the first temperature measure but may calculate a differential of measures. If the processor determines that the temperature differential indicates the presence of a blood vessel, the blood vessel locator **102** provides some indication that a blood vessel is present. For instance, the blood vessel locator **102** shown in FIG. 1 comprises a light emitting diode (LED) **104** that can be seen by a user of the locator **102**. If the processor determines that a blood vessel is present, the processor sends an output signal that causes the LED **104** to light. In some embodiments, the blood vessel locator **102** includes multiple visual indicators, such as several LEDs. In one such embodiment, the LEDs are lit in a pattern simulating a stud-finder, such that a medical practitioner may accurately determine the location of a blood vessel by moving the locator **102** back and forth over the location of a blood vessel while watching the LEDs alternately turn on and off.

In other embodiments, the blood vessel locator **102** may activate other types of indicators or a combination of types of

4

indicators to indicate the presence of a blood vessel. For example, in one embodiment, the blood vessel locator **102** comprises an actuator, such as an eccentric rotating mass (ERM) motor, for outputting haptic effects to a user of the locator **102**. Such a device may vibrate when a blood vessel is located or vibrate at an increasing frequency as a blood vessel is approached and a decreasing frequency as the locator **102** moves away from the blood vessel.

Another embodiment comprises a speaker contained within the blood vessel locator **102**. The speaker provides an audio cue as to the presence of a blood vessel. In one alternate embodiment of the present invention, the blood vessel locator **102** comprises a liquid crystal diode (LCD) display, configured to provide a thermal picture of the surface of the skin **106** and thereby indicate the location or locations of blood vessels.

Locator Having One Temperature Sensor and One Indicator

FIG. 2 is a block diagram illustrating a blood vessel locator in one embodiment of the present invention. In the embodiment shown, the blood vessel locator **202** comprises one temperature sensor **204**. In other embodiments, the locator may comprise two, three, or more temperature sensors. The temperature sensor **204** is operable to measure the temperature of a point on the surface of the skin and output the temperature measure. While much of the description contained herein references a human's skin, embodiments of the present invention are not limited to use on a human's skin and may be used, for instance, to locate blood vessels in various other animals, such as other primates, dogs, and cats. In some instances, for animals, the fur may have to be shaved prior to measuring skin temperatures.

The temperature sensor **204** may utilize any of a number of different temperature measuring technologies. For example, the temperature sensor **204** may comprise a thermocouple contact sensor. In such embodiments, the temperature sensor **204** may detect the temperature of the surface of the skin through direct contact with the skin. In other embodiments of the invention, the temperature sensor **204** may be a different type of temperature sensor. For example, the temperature sensor **204** may be an infrared thermometer, capable of detecting the temperature of the skin without direct skin contact.

In embodiments of the invention requiring direct contact with the skin for temperature measurement, the blood vessel locator **202** may comprise an additional disposable component. For example, the disposable component may comprise a sterile plastic sleeve, capable of covering the temperature sensor **204**. The additional disposable component may help to ensure good hygiene and may also help to shield the device from contamination.

While detection of blood vessels using embodiments of the present invention may be possible without any preparation, temperature differentials may in some circumstances be more easily detected by the temperature sensor **204** if the surface of the skin is warmed or cooled before the temperature measure is taken. For example, a practitioner may warm a patient's arm by soaking it with warm water before using the blood vessel locator **202**.

Referring still to FIG. 2, the blood vessel locator **202** shown also comprises a processor **206**. The processor **206** is in communication with the temperature sensor **204** to receive temperature measures.

The processor **206** may comprise a computer-readable medium, such as a random access memory (RAM) (not

shown) coupled to the processor. The processor **206** may execute computer-executable program instructions stored in memory. Such processors can include one or more microprocessors, ASICs, and state machines. Such processors may further comprise programmable electronic devices such as PLCs, programmable interrupt controllers (PICs), programmable logic devices (PLDs), programmable read-only memories (PROMs), electronically programmable read-only memories (EPROMs or EEPROMs), or other similar devices.

Such processors include, or can be in communication with, media, for example, which stores instructions that, when executed by the processor, cause the processor to perform the steps described herein. Embodiments of computer-readable media include, but are not limited to, an electronic, optical, magnetic, or other storage or transmission device capable of providing a processor with computer-readable instructions. Other examples of suitable media include, but are not limited to, a floppy disk, CD-ROM, DVD, magnetic disk, memory chip, ROM, RAM, an ASIC, a configured processor, all optical media, all magnetic tape or other magnetic media, or any other medium from which a computer processor can read instructions. Also, various other forms of computer-readable media can transmit or carry instructions to a computer, including a router, private or public network, or other transmission device or channel, both wired and wireless. The instructions can comprise code from any suitable computer-programming language, including, for example, C, C++, Visual Basic, Java, Python, and JavaScript.

The processor **206** may be configured to receive multiple temperature measures from a temperature sensor **204**. In other embodiments, the processor **206** may be configured to receive one or more temperature measures from multiple temperature sensors. In the embodiment shown in FIG. 2, the temperature sensor **204** and the processor **206** are in communication via a direct wired digital connection. In other embodiments, communication between a temperature sensor **204** and the processor **206** may be through analog signals and may be wireless. For instance, the temperature sensor **204** may be able to use Bluetooth or Wi-Fi to communicate with the processor **206**.

When the processor **206** receives the temperature measure from the temperature sensor **204**, the processor **206** may compare the measure to a previously-received temperature measure or to some other data stored in memory (not shown). For instance, the processor **206** may be configured to determine a differential between a first temperature measure and a second temperature measure. The processor **206** may be further configured to determine a differential between a second temperature measure and a third temperature measure. In other embodiments, the processor **206** may instead store a reference or calibration temperature measure and compare temperature measures received from the temperature sensor **204** to the reference or calibration temperature measure.

Once the processor has determined the differential, the processor **206** may compare the differential to a threshold. If the differential meets or exceeds the threshold, then the processor **206** may be configured to generate an output signal indicating the presence of a blood vessel.

In some embodiments, if the processor **206** determines that a differential between two temperature measures or between a temperature measure and a calibration or reference measure exceeds a threshold, the processor **206** generates an output signal. The threshold, for example, may be any differential amount that is indicative of the presence of a blood vessel. For instance, in one embodiment, the threshold is set at 0.5 degrees Fahrenheit. The differential may be predetermined as in the example described, or a medical practitioner may con-

figure the differential threshold during operation of the blood vessel locator **202** to account for variations in patients or environments.

Also, in some embodiments, if the processor **206** determines that a differential between two temperature measures does not exceed a threshold, the processor **206** does not generate an output signal. In other embodiments, if the processor **206** determines a differential between two temperature measures does not exceed a threshold, the processor **206** generates a signal indicating the absence of a blood vessel.

In some embodiments, the processor **206** may determine a direction or axis of a blood vessel. Two or more differentials exceeding the threshold may indicate the direction of the blood vessel. For example, a sequence or succession of differentials in excess of a threshold may indicate the direction of a blood vessel. When a direction of a blood vessel is determined, the processor **206** may generate an output signal indicating the direction.

The blood vessel locating device **202** shown in FIG. 2 also comprises an indicator **208**. The indicator **208** is configured to receive the output signal from the processor **206**. In other embodiments of the blood vessel locating device **202**, the device may comprise other types of indicators and may comprise various combinations of multiple indicators.

In some embodiments, the indicator **208** may comprise a visual indicator. Visual indicators may include one or more lights, or a LCD display. For example, the indicator **208** may comprise a single red LED. When the indicator **208** receives a signal from the processor **206** indicating the presence of a blood vessel, the red LED will be activated.

The indicator **208** may also comprise an audio indicator, for example, a speaker. In such embodiments, the indicator **208** may emit a tone when it receives a signal from the processor **206** indicating the presence of a blood vessel.

In some embodiments of the present invention, the blood vessel locator **202** may comprise a marker (not shown). In one such embodiment, the marker is configured to generate a mark on the surface of the skin over the located blood vessel by, for instance, spraying one or more drops of ink on the skin. Multiple drops may indicate the direction or axis of the blood vessel. Then, when the medical practitioner moves the blood vessel locator **202** away from the skin in order to perform a medical procedure, the mark or marks are visible on the skin.

In another embodiment, the marker comprises a light. In one example, the marker may be configured to illuminate the location of the blood vessel on the surface of the skin with a small beam of light. In another example, the light may indicate the direction or axis of the blood vessel. In yet another embodiment, the marker is configured to leave one or more small, temporary indentations on the surface of the skin where the blood vessel is located.

The blood vessel locator **202** may include additional features to enhance its convenience for practitioners. For example, in some embodiments of the blood vessel locator **202**, the marker may be used as a flashlight.

In other embodiments, the blood vessel locating device **202** may include a guide for directing medical devices to the located blood vessel. For example, the blood vessel locating device **202** may comprise a slot (not shown) in which or through which an intravenous needle can be directed. The slot is configured so that it directs the needle to the location of the blood vessel as indicated by the blood vessel locator **202**. These additional features are illustrative and not exhaustive; other features may also be incorporated into various embodiments of the present invention.

Locator Having Multiple Temperature Sensors and Multiple Indicators

FIG. 3 is a block diagram illustrating a second blood vessel locator in one embodiment of the present invention. The blood vessel locator **302** shown in FIG. 3 comprises two temperature sensors, **304a** and **304b**. Other embodiments of the blood vessel locator **302** may comprise one, three, or more than three temperature sensors.

The two or more temperature sensors **304** of the blood vessel locator **302** may be configured to detect and output temperature measures substantially simultaneously. For example, each temperature sensor **304a** and **304b** may be activated at the same time. In other embodiments, the temperature sensors **304** may output temperature measures at different times.

In embodiments of the invention with multiple temperature sensors **304**, the sensors may be substantially aligned. For example, in an embodiment comprising three or more temperature sensors, some or all of the temperature sensors may be placed in a linear arrangement. In such embodiments, the temperature sensors **304** may be configured to output temperature measures from adjacent surfaces of the skin. As such, the three temperature measures may originate from three points in a linear alignment on the surface of the skin. Such embodiments may provide faster detection of a blood vessel than an embodiment using fewer sensors.

In other embodiments of the invention with multiple temperature sensors, the temperature sensors may be arranged in an array. The array of temperature sensors may then be capable of capturing a thermal picture of an area of a patient's skin. In areas where the temperature differential exceeds a threshold, the thermal picture may then be used to locate the presence of a blood vessel within the boundary of the picture.

The location of the temperature sensors **304** may be impacted by the type of patient on which the blood vessel locator **302** is to be used. For instance, in order to locate the blood vessels of a child, the temperature sensors **304a** and **304b** may be aligned more closely together than they would be to locate the blood vessels of an adult. For example, the temperature sensors may be aligned closely together such that each sensor may simultaneously contact the surface of a smaller arm.

The location of the temperature sensors **304** may be fixed in the device. In other embodiments of the invention with multiple temperature sensors, a medical practitioner may manipulate the configuration of the temperature sensors to accommodate individual patients.

In some embodiments of the present invention, the blood vessel locator **302** comprises two or more indicators, such as indicators **308a** and **308b** shown in FIG. 3. The indicators **308** may be of the same type or of different types. For instance, in one embodiment, indicator **308a** may be an LED, while indicator **308b** may be a speaker. In such embodiments, the blood vessel locating device **302** may indicate the presence of a blood vessel by simultaneously flashing the LED and emitting a sound through the speaker. In other embodiments, the blood vessel locating device may have different combinations of one or more indicators.

In some embodiments, the blood vessel locating device **302** also comprises an actuator **310**. The actuator **310** is configured to provide a haptic effect, such as a vibrotactile effect to a user of the blood vessel locator **302**. Further embodiments of the blood vessel locator **302** may comprise a plurality of actuators.

The actuator **310** may be configured to receive the output signal from the processor **306** and provide a haptic effect in

response to the output signal. In some embodiments the haptic effect comprises a vibrotactile effect. For example, the actuator **310** may vibrate the housing of the blood vessel locator **302** in response to an output signal indicating the presence of a blood vessel. The actuator **310** may comprise any number of commercially available actuators, such as eccentric rotating mass (ERM) motors, voice coils, linear actuators, moving magnet actuators, piezoelectric actuators, pneumatic actuators, etc.

FIRST EXAMPLE OF A METHOD TO LOCATE A BLOOD VESSEL

FIG. 4 is a flow diagram illustrating a first method **400** for locating a blood vessel in one embodiment of the present invention. In step **402**, a first temperature measure is received by a processor from a temperature sensor. The temperature measure may comprise a temperature measure on any suitable scale, such as a Fahrenheit or a Celsius temperature measure. In some embodiments of the invention, the temperature measure may be any unit which is proportional to the temperature of the skin, such as, for example, millivolts. The temperature measure may correspond with the temperature of a point on the surface or above the surface of an area of skin. Temperature measures may originate from a human or other animal.

In step **404**, a second temperature measure is received by the processor from a temperature sensor. In some embodiments of the invention, a processor can receive the first temperature measure **402** and the second temperature measure **404** as a digital signal. In one embodiment, the first temperature measure and the second temperature measure are received from the same temperature sensor. In other embodiments, the first temperature measure and the second temperature measure may be received from different temperature sensors. Further, in some such embodiments, step **402** and step **404** may occur substantially simultaneously.

In step **406**, the processor determines a differential between the first temperature measure and the second temperature measure. For example, if the first temperature measure is 97.0 degrees Fahrenheit, and the second temperature measure is 97.7 degrees Fahrenheit, the temperature differential is 0.7 degrees Fahrenheit. In other embodiments, a processor may determine the differential between the second temperature measure and the third temperature measure.

In step **408**, the processor determines whether a blood vessel is present by comparing the differential with a threshold. In some embodiments, the threshold value may be predefined. In other embodiments, the threshold may be specified by a medical practitioner or determined during a calibration process.

If the differential exceeds the threshold, the processor generates an output signal **410**. For example, the threshold may be 0.3 degrees Fahrenheit. If the temperature differential between the first temperature measure and the second temperature measure is 0.4 degrees Fahrenheit, then the processor determines that a blood vessel is present and generates an output signal **410**. The processor may send the output signal to one or more indicators, including, for example, visual, auditory, and haptic indicators.

In the embodiment of FIG. 4, the processor does not generate an output signal if the presence of a blood vessel is not detected. For example, if the threshold is 3 degrees Fahrenheit, but the differential is 2 degrees Fahrenheit, no output signal is generated. In the process shown in FIG. 4, if the

temperature differential does not exceed the threshold, the processor waits for a new temperature measure **412**.

SECOND EXAMPLE OF A METHOD TO LOCATE A BLOOD VESSEL

FIG. 5 is a flow diagram illustrating a second method **500** for locating a blood vessel in one embodiment of the present invention. In step **502**, a first calibration temperature measure is received by a processor from a temperature sensor. In some embodiments, the calibration temperature measure is stored by the processor, and compared against successive temperature measures received by the processor. The calibration temperature measure may comprise a temperature measure on any suitable scale, such as a Fahrenheit or a Celsius temperature measure. The calibration temperature measure may correspond with the temperature of a point on the surface or above the surface of an area of skin. Calibration temperature measures may originate from a human or other animal.

In step **504**, a subsequent temperature measure is received by a processor from a temperature sensor. In one embodiment, the subsequent temperature measure is from a point on the surface of the skin adjacent to the first calibration temperature measure. In other embodiments, the subsequent temperature measure may be from a point located nonadjacent to the first calibration point.

In step **506**, the processor determines a differential between the first calibration temperature measure and the subsequent temperature measure.

In step **508**, the processor determines whether a blood vessel is present by comparing the differential between the temperature measures with a threshold. In some embodiments, the threshold value may be predefined. In other embodiments, the threshold may be specified by a medical practitioner or determined during a calibration process.

If the differential exceeds the threshold, the processor generates an output signal **510**. The processor may output this signal to one or more indicators, including, for example, visual, auditory, and haptic indicators.

If the differential does not exceed a threshold, the process shown continues by receiving a new subsequent temperature measure **504**. The new subsequent temperature measure may originate from a third point on the surface of the skin. The processor then determines a new differential between the calibration temperature measure and the new subsequent temperature measure **506**. If the processor determines the new differential exceeds a threshold **508**, the processor will generate an output signal indicating the presence of a blood vessel **510**.

Embodiments of the present invention provide various advantages over conventional systems and methods for locating blood vessels. For instance some embodiments allow medical practitioners to identify blood vessels in patients having varying skin tones and skin thickness, a task that may be difficult with conventional systems and methods. Further, some embodiments of the present invention are substantially less expensive than conventional devices for locating blood vessels. And embodiments of the present invention may be easier to use and less invasive, facilitating a higher level of care from the medical practitioner and less trauma for the patient.

GENERAL

The foregoing description of embodiments of the invention has been presented only for the purpose of illustration and description and is not intended to be exhaustive or to limit the

invention to the precise forms disclosed. Numerous modifications and adaptations thereof will be apparent to those skilled in the art without departing from the spirit and scope of the present invention.

That which is claimed:

1. A handheld system for locating a blood vessel, the system comprising:

a housing configured to be moved across a patient's skin; a temperature sensor disposed within the housing and operable to output a temperature measure of a location on a surface of the patient's skin; and

a processor in communication with the temperature sensor and configured to:

receive a first temperature measure at a first location from the temperature sensor,

receive a second temperature measure at a second location from the temperature sensor, the second location different from the first location,

determine a difference between the first temperature measure and the second temperature measure, and generate an output signal indicating the presence of a blood vessel if the difference exceeds a threshold,

wherein the temperature sensor is configured to output the first and second temperature measures at the first and second locations based on a movement of the housing across the patient's skin.

2. The system of claim 1, further comprising an indicator configured to receive the output signal and indicate the presence of the blood vessel.

3. The system of claim 1, wherein the processor is further configured to determine a direction of the blood vessel.

4. The system of claim 3, wherein the indicator is further configured to indicate the direction of the blood vessel.

5. The system of claim 2, wherein the indicator comprises a visual indicator.

6. The system of claim 2, wherein the indicator comprises an audible indicator.

7. The system of claim 2, wherein the indicator comprises a marker configured to generate a mark on the surface of the skin over the blood vessel.

8. The system of claim 1, further comprising an actuator configured to provide a haptic effect in response to the output signal.

9. The system of claim 8, wherein the haptic effect comprises a vibrotactile haptic effect.

10. A handheld system for locating a blood vessel, the system comprising:

a housing configured to be moved across a patient's skin; a first temperature sensor disposed within the housing and operable to output a temperature measure of a first location on a surface of a skin;

a second temperature sensor disposed within the housing and operable to output a second temperature measure of a second location on the surface of the skin; and

a processor in communication with the first temperature sensor and the second temperature sensor, the processor configured to:

receive the first temperature measure from the first temperature sensor,

receive the second temperature measure from the second temperature sensor,

determine a difference between the first temperature measure and the second temperature measure, and generate a first output signal indicating the presence of a blood vessel if the difference exceeds a threshold.

11

11. The system of claim 10, further comprising an indicator configured to receive the first output signal and indicate the presence of the blood vessel.

12. The system of claim 11, further comprising:
a third temperature sensor in communication with the processor, the third temperature sensor operable to output a third temperature measure of a third point on the surface of the skin;

and wherein the processor is further configured to:

receive the third temperature measure from the third temperature sensor;

determine a second difference between the second temperature measure and the third temperature measure, generate a second output signal indicating the presence of a blood vessel if the second difference exceeds a threshold; and

the indicator further configured to receive the second output signal and indicate the presence of the blood vessel.

13. The system of claim 12, wherein the first temperature sensor, the second temperature sensor, and the third temperature sensor are substantially aligned.

14. A handheld system for locating a blood vessel, the system comprising:

a plurality of temperature sensors, each operable to output a temperature measure of a point on the surface of a skin; and

a processor in communication with the plurality of temperature sensors, the processor configured to:

receive the temperature measure from each of the plurality of temperature sensors,

determine a difference between any of two of the temperature measures, and

generate an output signal indicating the presence of a blood vessel if the difference exceeds a threshold.

15. The system of claim 14, further comprising an indicator configured to receive the output signal and indicate the presence of the blood vessel.

16. The system of claim 14, wherein the plurality of temperature sensors are substantially aligned.

17. The system of claim 14, wherein the plurality of temperature sensors are arranged as an array.

18. A method for locating a blood vessel with a handheld device, the method comprising:

receiving a first temperature measure associated with a first location on a surface of a skin, the first temperature measure generated by a temperature sensor;

moving the temperature sensor to a second location;

receiving a second temperature measure associated with the second location on the surface of the skin, the second temperature measure generated by the temperature sensor;

determining a difference between the first temperature measure and the second temperature measure; and
generating an output signal indicating the presence of a blood vessel if the difference exceeds a threshold.

19. The method of claim 18, further comprising receiving the output signal and signaling the presence of a blood vessel.

20. The method of claim 18, further comprising determining a direction of a blood vessel.

21. The method of claim 18, further comprising:

receiving a third temperature measure associated with a third point on a surface of the skin;

determining a second difference between the second temperature measure and the third temperature measure; and

12

generating an output signal indicating the presence of a blood vessel if the second difference exceeds a threshold.

22. The method of claim 18, wherein the first temperature measure is a calibration temperature measure.

23. The method of claim 18, further comprising identifying the location of the blood vessel on the surface of the skin.

24. The method of claim 23, wherein identifying the location of the blood vessel on the surface of the skin comprises generating a mark on the surface of the skin.

25. The method of claim 20, further comprising identifying the direction of the blood vessel on the surface of the skin.

26. The method of claim 18, wherein the first temperature measure and the second temperature measure are received from a single sensor.

27. The method of claim 18, wherein the first temperature measure is received from a first sensor and the second temperature measure is received from a second sensor.

28. The method of claim 27, wherein:

the first sensor is in contact with a first point on the surface of the skin; and

the second sensor is in contact with a second point on the surface of the skin.

29. The method of claim 18, wherein receiving the first temperature measure and the second temperature measure occur substantially simultaneously.

30. The method of claim 19, wherein signaling the presence of a blood vessel comprises generating a visual effect.

31. The method of claim 19, wherein signaling the presence of a blood vessel comprises generating an auditory effect.

32. The method of claim 19, wherein signaling the presence of a blood vessel comprises generating a haptic effect.

33. The method of claim 32, wherein the haptic effect comprises a vibrotactile haptic effect.

34. The method of claim 19, wherein signaling the presence of a blood vessel comprises generating a plurality of sensory effects.

35. A method for locating a blood vessel with a handheld device, the method comprising:

receiving a plurality of temperature measures from a temperature sensor being moved across a patient's skin, each of the plurality of temperature measures associated with a different location on a surface of the patient's skin;

determining a difference between a pair of the plurality of temperature measures; and

generating an output signal indicating the presence of a blood vessel if the difference exceeds a threshold.

36. A non-transitory computer-readable medium on which is encoded computer-executable program code, the program code comprising:

program code for receiving a first temperature measure associated with a first location on a surface of a skin, the first temperature measure generated by a temperature sensor disposed within a housing of a handheld device;
program code for receiving a second temperature measure associated with a second location on the surface of the skin, the second temperature measure generated by the temperature sensor;

program code for determining a difference between the first temperature measure and the second temperature measure; and

program code for generating an output signal indicating the presence of a blood vessel if the difference exceeds a threshold,

13

wherein the temperature sensor is configured to output the first and second temperature measures at the first and second locations based on a movement of the housing across the patient's skin.

37. The non-transitory computer-readable medium of claim 36, further comprising:

program code for receiving a third temperature measure associated with a third point on a surface of the skin;
 program code for determining a second difference between the second temperature measure and the third temperature measure; and
 program code for generating an output signal indicating the presence of a blood vessel if the second difference exceeds a threshold.

38. The non-transitory computer-readable medium of claim 36, further comprising:

program code for determining a direction of the blood vessel; and
 program code for generating an output signal indicating the direction of the blood vessel.

39. A non-transitory computer readable medium on which is encoded computer-executable program code, the program code comprising:

program code for receiving a plurality of temperature measures, each of the plurality of temperature measures associated with a different location on a surface of a patient's skin from a temperature sensor disposed within a housing of a handheld device being moved across the patient's skin;
 program code for determining a difference between a pair of the plurality of temperature measures; and
 program code for generating an output signal indicating the presence of a blood vessel if the difference exceeds a threshold.

14

40. A system comprising:

a housing;

a temperature sensor disposed within the housing and operable to output a temperature measure of a location on a surface of a patient's skin; and

a processor in communication with the temperature sensor and configured to:

receive a first temperature measure at a first location from the temperature sensor,

receive a second temperature measure at a second location from the temperature sensor, the second location different from the first location,

determine a difference between the first temperature measure and the second temperature measure, and
 generate an output signal indicating the presence of a blood vessel if the difference exceeds a threshold.

41. A non-transitory computer-readable medium on which is encoded computer-executable program code, the program code comprising:

program code for receiving a first temperature measure associated with a first location on a surface of a patient's skin, the first temperature measure generated by a temperature sensor;

program code for receiving a second temperature measure associated with a second location on the surface of the skin, the second temperature measure generated by the temperature sensor;

program code for determining a difference between the first temperature measure and the second temperature measure; and

program code for generating an output signal indicating the presence of a blood vessel if the difference exceeds a threshold.

* * * * *

专利名称(译)	用于定位血管的系统和方法		
公开(公告)号	US8167813	公开(公告)日	2012-05-01
申请号	US11/749825	申请日	2007-05-17
[标]申请(专利权)人(译)	浸入式医疗		
申请(专利权)人(译)	浸泡液MEDICAL , INC.		
当前申请(专利权)人(译)	浸泡液MEDICAL , INC.		
[标]发明人	COHEN ROBERT F TUMEY DAVID M		
发明人	COHEN, ROBERT F. TUMEY, DAVID M.		
IPC分类号	A61B5/00		
CPC分类号	A61B5/015 A61B5/489		
代理机构(译)	KILPATRICK TOWNSEND & STOCKTON LLP		
其他公开文献	US20080287824A1		
外部链接	Espacenet USPTO		

摘要(译)

描述了用于定位血管的系统和方法。一种所述方法包括接收与皮肤表面上的第一点相关的第一温度测量值;接收与皮肤表面上的第二点相关联的第二温度测量值, 并确定第一温度测量值和第二温度测量值之间的差值。该方法还包括: 如果差异超过阈值, 则产生指示血管存在的输出信号。

