



US008579830B2

(12) **United States Patent**  
**Golosarsky et al.**

(10) **Patent No.:** **US 8,579,830 B2**  
(45) **Date of Patent:** **Nov. 12, 2013**

(54) **NEUROPATHY DIAGNOSTIC DEVICE**

(75) Inventors: **Boris Golosarsky**, Nashua, NH (US);  
**James Bernhard**, Plainville, MA (US);  
**Michael Brown**, Nashua, NH (US);  
**John McCarthy**, Newbury, NH (US)

(73) Assignee: **Prosenex, LLC**, Hudson, NH (US)

(\* ) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 313 days.

(21) Appl. No.: **13/054,136**

(22) PCT Filed: **Jul. 17, 2009**

(86) PCT No.: **PCT/US2009/004159**

§ 371 (c)(1),  
(2), (4) Date: **Jan. 14, 2011**

(87) PCT Pub. No.: **WO2010/008592**

PCT Pub. Date: **Jan. 21, 2010**

(65) **Prior Publication Data**

US 2011/0112431 A1 May 12, 2011

**Related U.S. Application Data**

(60) Provisional application No. 61/081,536, filed on Jul. 17, 2008.

(51) **Int. Cl.**  
**A61B 5/00** (2006.01)  
**A61B 19/00** (2006.01)  
**A61F 2/00** (2006.01)  
**A61F 7/00** (2006.01)  
**G01K 1/08** (2006.01)  
**G01K 1/14** (2006.01)  
**G01K 13/00** (2006.01)

(52) **U.S. Cl.**  
USPC ..... **600/557; 600/552; 600/555; 607/102;**  
**607/108; 607/111; 374/141; 374/142**

(58) **Field of Classification Search**

USPC ..... 600/549, 552, 553, 555, 557, 587;  
601/15, 18, 80; 606/20-31; 607/102,  
607/108, 111; 374/141-143  
See application file for complete search history.

(56) **References Cited**

**U.S. PATENT DOCUMENTS**

4,653,507 A \* 3/1987 Laudadio ..... 600/555  
5,002,065 A 3/1991 LaCourse et al.

(Continued)

**FOREIGN PATENT DOCUMENTS**

JP 2005052598 3/2005  
WO WO87/07969 12/1987

**OTHER PUBLICATIONS**

Written Opinion and International Preliminary Report on Patentability for PCT application No. PCT/US2009/004159, Jan. 18, 2011.  
Website printout for www.usneurologicals.com, Jul. 4, 2007, 17 pages.  
European Search Report for EP application 09798324.1, Dec. 12, 2012.

(Continued)


*Primary Examiner* — Sean Dougherty  
*Assistant Examiner* — Devin Henson

(74) *Attorney, Agent, or Firm* — Joseph E. Maenner; Maenner & Associates, LLC

(57) **ABSTRACT**

A neuropathy diagnostic device includes a body having a neutral temperature surface disposed on an exterior of the body, a variable temperature surface disposed on the exterior of the body, and a vibrating surface having a variable vibration amplitude. The vibrating surface extends outwardly from the body. A touch sensor extends outwardly from the body. A processor is disposed within the body. The processor is adapted to set a temperature of the neutral temperature surface, vary a temperature of the variable temperature surface, and vary the vibration amplitude of the vibrating surface.

**13 Claims, 5 Drawing Sheets**



(56)

**References Cited**

U.S. PATENT DOCUMENTS

5,363,859	A *	11/1994	Tuckett et al. ....	600/552
5,373,853	A *	12/1994	Assal et al. ....	600/555
7,854,703	B2 *	12/2010	Poisner .....	600/552
2007/0191730	A1	8/2007	Speidel	
2009/0227890	A1 *	9/2009	Lanfermann et al. ....	600/555

OTHER PUBLICATIONS

Bertelsmann, F.W. et al., "Thermal discrimination thresholds in normal subjects and in patients with diabetic neuropathy", *Journal of Neurology, Neurosurgery, and Psychiatry*, 1985, pp. 686-690.

\* cited by examiner




Fig. 1




Fig. 2




Fig. 3




Fig. 4




Fig. 5




Fig. 6




Fig. 7




Fig. 8

## NEUROPATHY DIAGNOSTIC DEVICE

## CROSS-REFERENCE TO RELATED APPLICATION

The present application is a U.S. National Stage Application of PCT application Ser. No. PCT/US2009/004159, filed on Jul. 17, 2009, which claims priority from U.S. Provisional Patent Application Ser. No. 61/081,536, filed on Jul. 17, 2008, both of which are incorporated by reference in their entireties.

## BACKGROUND OF THE INVENTION

Neuropathy is a medical condition where a patient has reduced sensitivity in through-the-skin sensing of temperature variations, vibrations, and tactile stimulation. Neuropathy is common for patients with diabetes. Attention to diabetes has increased significantly as more individuals are being diagnosed with some form of the disease. Early and accurate diagnosis of neuropathies associated with diabetes or other medical issues may lead to earlier treatment to reduce the effect of these issues on the patient.

## SUMMARY OF THE INVENTION

Briefly, the present invention provides a neuropathy diagnostic device that includes a body having a neutral temperature surface disposed on an exterior of the body, a variable temperature surface disposed on the exterior of the body, and a vibrating surface having a variable vibration amplitude. The vibrating surface extends outwardly from the body. A touch sensor extends outwardly from the body. A processor is disposed within the body. The processor is adapted to set a temperature of the neutral temperature surface, vary a temperature of the variable temperature surface, and vary the vibration amplitude of the vibrating surface.

## BRIEF DESCRIPTION OF THE DRAWINGS

The foregoing summary, as well as the following detailed description of exemplary embodiments of the invention, will be better understood when read in conjunction with the appended drawings, which are incorporated herein and constitute part of this specification. For the purposes of illustrating the invention, there are shown in the drawings exemplary embodiments of the present invention. It should be understood, however, that the invention is not limited to the precise arrangements and instrumentalities is shown. In the drawings, the same reference numerals are employed for designating the same elements throughout the several figures. In the drawings:

FIG. 1 is a top plan view of a neuropathy detection device according to an exemplary embodiment of the present invention;

FIG. 2 is a front perspective view of the neuropathy detection device of FIG. 1;

FIG. 3 is a rear perspective view of the neuropathy detection device of FIG. 1;

FIG. 4 is a top plan view of the neuropathy detection device of FIG. 1, with the top cover removed;

FIG. 5 is a schematic drawing of an exemplary embodiment of a force sensor for a vibrating end effector in the neuropathy detection device of FIG. 1;

FIG. 6 is a block diagram illustrating a functional layout of a circuit used to operate the neuropathy detection device of FIG. 1;

FIG. 7 is a top perspective view of a neuropathy detection device according to an alternative exemplary embodiment of the present invention; and

FIG. 8 is a top perspective view of a neuropathy detection device according to another alternative exemplary embodiment of the present invention.

## DETAILED DESCRIPTION OF THE INVENTION

Although the invention is illustrated and described herein with reference to specific embodiments, the invention is not intended to be limited to the details shown. Rather, various modifications may be made in the details within the scope and range of equivalents of the disclosure without departing from the invention. The invention is best understood from the following detailed description when read in connection with the accompanying drawing figures, which show exemplary embodiments of the invention selected for illustrative purposes. The invention will be illustrated with reference to the figures. Such figures are intended to be illustrative rather than limiting and are included is herewith to facilitate the explanation of the present invention.

Referring to FIGS. 1-4 in general, a neuropathy detection device **100** ("device **100**") that is used to diagnose neuropathy in patients is shown. Neuropathy is common for patients with medical issues, such as diabetes or erectile dysfunction. Device **100** includes a body **101** having an exposed neutral temperature surface **102** and an exposed variable temperature surface **104** at one end of body **101**, and an exposed vibration surface **106** that extends outwardly from an opposing end of body **101**. A filament **108** extends outwardly from body **101**. Filament **108** may be a monofilament, such as nylon wire.

A medical professional, such as, for example, a physician, may use device **100** on a patient by touching various locations on the patient's skin with surfaces **102**, **104**, **106** and/or filament **108**. The patient's reaction to these touches may give the physician an indication of a level of neuropathy in the patient, which may in turn aid or enable the physician to diagnose the patient.

Two separate modes of operation are provided for device **100**: temperature (using surfaces **102**, **104**) and vibration (using surface **106**), as well as a tactile test (using filament **108**). Each mode can be utilized at any time and the operator may switch back and forth between the two modes and/or the tactile test. Controls and indicators are included on s body **101** to allow the operator to control surfaces **102**, **104**, **106** and to give the operator an indication of the operating parameters of surfaces **102**, **104**, **106**. A controller, such as a microcontroller **107**, shown in FIGS. 4 and 5, is used to control operation of surfaces **102**, **104**, **106**.

The patient's ability to discern the differences between the temperatures of neutral temperature surface **102** and variable temperature surface **104**, positioned at various locations on the patient's skin, gives the physician an indication of the level of neuropathy. Referring specifically to FIGS. 1, 2, and 4, in an exemplary embodiment, neutral temperature surface **102** and variable temperature surface **104** are both generally square, flat pads with sides that are about 1-1/2 to 2 cm long.

Variable temperature surface **104** may be independently controlled by the operator such that the temperature difference between neutral temperature surface **102** and variable temperature surface **104** varies up to about 10 degrees Celsius. In an exemplary embodiment, neutral temperature surface **102** may be set by controller **107** at about 25 degrees Celsius. Variable temperature surface **104** may be varied at 2 degree increments between a temperature of between about 15 and about 25 degrees Celsius. While in this exemplary

embodiment, the temperature of variable temperature surface **104** may be set to be lower than the temperature of neutral temperature surface **102**, those skilled in the art will recognize that the temperature of variable surface **104** may be set higher than the temperature of neutral temperature surface **102**.

A power indicator LED **110** illuminates when power is provided to device **100**. A temperature mode button **111** may be pressed to activate the temperature mode and to provide power to heat surfaces **102**, **104**. Neutral temperature surface **102** is powered to a fixed temperature, such as, for example, 25 degrees Celsius, and variable temperature surface **104** at a variable temperature in degree increments, such as, for example, increments of 2 degrees Celsius. The operator can control the temperature of variable temperature surface **104** by using increment buttons **112**, **113**. Arrows **114** on either side of increment button **112** pointing toward surfaces **102**, **104** indicate that the operation of increment button **112** raises the temperature difference between neutral temperature surface **102** and variable surface **104**, while arrows **115** on either side of increment button **113** pointing away from surfaces **102**, **104** indicate that the operation of increment button **113** lowers the temperature difference between neutral temperature surface **102** and variable surface **104**. An LED bar graph **116** displays a temperature offset between neutral temperature surface **102** and variable temperature surface **104**. An "Off" button **119** turns off device **100**.

Temperature variations on surfaces **102**, **104** are created through standard solid state thermoelectric devices known as "Peltier Devices." As shown in FIG. 5, a Peltier Device **120** labeled "Steady Peltier" controls neutral temperature surface **102** (shown in FIG. 1), while a Peltier Device **122** labeled "Variable Peltier" controls variable temperature surface **104** (shown in FIG. 1).

A Peltier Device is essentially a solid state heat pump with no moving parts. A DC voltage is applied to the device, which causes heat to move from one side to the other. This movement of the heat causes an apparent cooling of one side and heating of the other side. Exemplary Peltier Devices used for surfaces **102**, **104** may be about 1.25 cm square and about 0.25 cm thick. The direction of heat flow within a Peltier Device can be reversed by simply reversing the polarity of the DC current applied to the device. By constructively controlling the current level and polarity of the current applied to a Peltier Device, a constant temperature can be maintained.

Peltier Devices **120**, **122** used in the exemplary embodiment of device **100** may be identical. Each Peltier Device **120**, **122** is powered by a separate dual H Bridge **124**, **126**, respectively. An H bridge has two outputs that can have its output commanded to reverse polarity. An H bridge is either "on" or "off," meaning that the H bridge either delivers full power to the Peltier, or no power. Since it is necessary to set various heat pump levels (and therefore temperature as measured on surfaces **102**, **104**), controller **107** varies the electrical current levels to H bridges **124**, **126**. This may be done via pulse width modulation (PWM) which provides a repeated signal of "on" and then "off." The relative time of "off" versus "on" will set, on average, the power going to each Peltier Device **120**, **122** and therefore the temperature at surfaces **102**, **104**, respectively.

Each surface **102**, **104** includes a respective temperature sensor **128**, **130**, which provides feedback to microcontroller **107** via a respective analog to digital (A/D) converter **132**, **134**.

The patient's ability to discern vibrations at various locations on the patient's skin also gives the physician an indication of the level of neuropathy. Referring specifically to FIGS.

**1**, **3**, and **4**, vibration surface **106** may extend outwardly from body **101** and have a generally cylindrical shape with a hemispherical end. Vibration surface **106** may be controlled to vibrate in and out at constant frequency, but with a variable amplitude. In an exemplary embodiment, vibration surface **106** vibrates at a frequency of about 120 Hz, is although other frequencies are also contemplated. The amplitude of vibration of vibration surface **106** may be varied between about 100 percent of full amplitude and about 20 percent of full amplitude. An LED bar graph **118** displays a percentage of vibration amplitude relative to a maximum available amplitude. In an exemplary embodiment, the amplitude may be adjusted in 20 percent increments (100, 80, 60, 40, or 20 percent of full amplitude), although those skilled in the art will recognize that other increments may be used.

As illustrated in FIG. 5, in an exemplary embodiment, vibration for vibrating surface **106** may be provided by a magnetic coil moving a magnet (shown collectively as magnet **105**). The magnet **105** may be coupled to vibrating surface **106**. A signal from microcontroller **107** to the coil is a constant frequency. A low power signal from microcontroller **107** may be amplified using a simple operational amplifier **136** (shown schematically in FIG. 6) and transistor (not shown). The amplitude of the vibration is also controlled by microcontroller **107**. While an exemplary mechanism for vibrating the vibrating surface **106** is shown, those skilled in the art will recognize that other mechanisms may be used.

Referring to FIGS. 1 and 4, increment buttons **112**, **113** may be used to adjust the vibration amplitude down or up as desired. Increment button **113** will increase the vibration amplitude, while increment button **112** will decrease the vibration amplitude. "Off" button **119** turns off device **100**.

Optionally, as illustrated in FIG. 5, vibration surface **106** may incorporate a pressure sensor **140**. Pressure sensor **140** may include a load cell **160** that is electronically coupled to a load sensing electronics component **162** in controller **107** and generates an indication when sufficient pressure is applied by device **100** on the patient's skin. The indication may be an audible indication, such as, for example, a beep, a visual indication such as, for example, a light, or some other suitable type of indication to signify to the user that device **100** is being applied to the patient's skin with sufficient force to enable the patient to sense the vibrations from vibration surface **106**. The indicator would operate as is long as the pressure applied to the patient is sufficient to enable the patient to sense the vibrations.

Load cell **160** may be coupled to magnet **105** and disposed between magnet **105** and vibration surface **106**. Optionally, as illustrated in FIG. 5, a mechanical extension **164** may couple load cell **160** to vibration surface **106**.

Referring to the control diagram of FIG. 6, microcontroller **107** may be used to control the temperature of surfaces **102**, **104** and the vibration of vibration surface **106**. Microcontroller **107** is disposed within body **101** and may be an 8 bit industrial processor with 16 digital inputs and outputs. An associated printed circuit board **121** (shown in FIG. 4) not only contains the circuitry, but also provides the proper layout and mounting for LED's **116**, **118** and buttons **110**, **111**, **112**, **113**, **117**, **119**.

Referring to FIGS. 2 and 3, filament **108** provides a touch sensation test. In an exemplary embodiment, the tactile aspect of device **100** utilizes a standard monofilament nylon wire for filament **108**, having a free end **108a**, which is used to check the patient's tactile sensitivity. For protection when not in use, filament **108** may be disposed against the outside of body **101** and can be readily pivoted about a pivoting end **108b** by the operator at any time. Alternatively, although not shown, fila-

ment **108** may be housed within body **101** and pulled out from body **101** when desired. After use, filament **101** may be pushed back into body **101** for storage.

In an exemplary embodiment, device **100** may be powered by standard **110** volt alternating current, stepped down to **6** 5 volt direct current through a transformer. Internally, a **5** volt regulator may be provided to provide voltage to digital components within device **100**.

Electrical power may be provided to device **100** through an electrical cord **150**, which is partially shown in FIGS. **1-4**. 10 Alternatively, device **100** may be powered by batteries (rechargeable or disposable) that are contained within body **101** of device **100**.

While body **101** is illustrated in FIGS. **1-4** as a generally rectangular enclosure, those skilled in the art will recognize that body **101** may be other shapes as well, including, but not limited to, a cylindrically shaped body. 15

Device **100** may optionally be used to record data obtained during testing. In a first embodiment, device **100** has no storage capacity within itself, but transmits data from microcontroller **107** via radio frequency or other suitable transmission medium to a storage device, such as, for example, a personal/laptop computer. The patient's profile may have already been called up on the storage device and the data transmitted from device **100** is automatically transmitted to the patient's file. The information transmitted from device **100** may include maximum/minimum temperatures and or vibration amplitudes generated by device **100**. 20

Alternatively, device **100** may have memory within microcontroller **107** or coupled to microcontroller **107** and the capability to receive/transmit information. Device **100** may receive patient information uploaded to device **100** from the personal/laptop computer. Device **100** may include an indicator, such as, for example, an LCD or LED screen that displays the patient information so that the operator knows that the correct patient information has been downloaded to device **100**. Data obtained during operation of device **100** is then associated with the patient information. This data may be transmitted back to the personal/laptop computer instantly, after all data for the particular patient is obtained, or even after uses with several different patients, such as, for example, at the end of a work day. Those skilled in the art will recognize that known methods may be used to store and transmit data between device **100** and another device. 30

Further, if device **100** is battery operated with rechargeable batteries that are recharged by inserting device into a recharging station (not shown), the recharging station may include a port to engage device **100** for downloading data from device **100** into a storage device. 45

To operate device **100**, the operator turns on device **100** by pressing either temperature mode button **111** or vibration mode button **117**. The operator can press either mode button **111**, **117** at any time to switch between temperature and vibration modes. 50

To conserve energy (and battery power, if batteries are used), device **100** is times out after 30 seconds on its own if no buttons are pressed. Any adjustment using increment buttons **112**, **113** adds a new period of 30 seconds to the timeout mechanism. The operator can add another 30 seconds by simply pressing the appropriate mode button **111**, **117**. "Off" button **119** may be pressed at any time to shut down device **100** prior to device **100** timing out. 55

When device **100** is first powered on, device **100** will default to make variable temperature surface **104** have a 2 degree offset from neutral temperature surface **102**. At any time, the operator can use increment buttons **112**, **113** to adjust this offset. LED bar graph **116** shows the operator 65

which offset is currently being provided by device **100**. There is a small delay in attaining the proper temperatures and LED bar graph **116** reflects this situation by blinking while surfaces **102**, **104** are brought to their desired temperatures. LED bar graph **116** remains steadily lit when surfaces **102**, **104** are at their desired temperature(s). The operator is free to adjust device **100** to any of the preprogrammed offsets based on his need for further tests as dictated by the patient's responses. Device **100** may be programmed to shut itself off if no buttons have been pushed for any desired time level, such as 60 seconds.

If the operator desires to operate the temperature mode first, the operator presses temperature mode button **111**. Device **100** will begin to appropriately heat or cool both temperature surfaces **102**, **104**. Device **100** will always attempt to make neutral temperature surface **102** stay at 25 degrees Celsius. If no other action is taken by the operator, device **100** will attempt to make variable temperature pad **104** two (2) degrees below the temperature of neutral temperature surface **102**. LED bar graph **116** will blink at "-2" while device **100** works to acquire the proper temperature, and will become steady when the proper temperatures on both surfaces **102**, **104** (i.e., a temperature difference of 2 degrees Celsius between surfaces **102**, **104**) are reached. Increment buttons **112**, **113** may be used to increase or decrease the temperature differential. With each change in desired offset, LED bar graph **116** moves to represent the new differential. The corresponding LED on LED bar graph **116** will blink while device **100** is working to achieve the new is temperature goal and will remain steady when the proper temperatures have been reached. 40

When LED bar graph **116** is illuminating in steady state, the operator then applies surfaces **102**, **104** simultaneously to an area on the patient's skin surface. The operator then asks for the patient's feedback depending on whether the patient could sense the temperature offset between surfaces **102**, **104**. This offset may first be set to the lowest amount (e.g., 2 degrees) and may then be incremented to larger offset values. In an exemplary embodiment, each increment makes variable surface **104** two (2) degrees cooler. Once the patient reports that he/she can feel the offset, the operator then knows the patient's temperature offset detection level for that particular part of the body. 45

In addition to temperature testing, the operator may also perform a vibration study. The operator presses vibration mode button **117**, activating vibration mode, causing vibration surface **106** to vibrate at 120 Hz, and at 100% of the amplitude of vibrating surface **106**. The operator may use increment buttons **112**, **113** to adjust the vibration amplitude down or up as desired. Increment button **113** will increase the vibration amplitude, while increment button **112** will decrease the vibration amplitude. As noted earlier with respect to the temperature mode, device **100** shuts down after 30 seconds if no additional inputs are provided. Any adjustment to the amplitude via increment buttons **112**, **113** will reset the 30 second clock. 50

The operator touches an end **106a** of vibration surface **106** to the area of interest on the patient's body. Load cell **160** transmits a signal to load sensing electronics component **162**, which transmits a signal (e.g., light, audible, etc.) to the operator to let the operator know that vibration surface **106** is engaging the patient with sufficient force. With vibration surface **106** vibrating, the patient may react by stating whether or not he/she can feel the vibration. The operator may then decrease the amplitude of the vibration and obtain further patient feedback to discern where the patient's threshold limit of detection may be. The operator can freely move 55

vibration amplitude up and down as desired, with the changes in amplitude happening virtually instantaneously.

The operator may also perform a tactile study. Filament 108 may be moved away from body 101 by rotating filament 108 about pivoting end 108b to allow free end 108a of filament 108 to extend away from body 101. Free end 108a may be gently pressed into the skin of the patient to determine the patient's sensation of filament 108 being pressed into the skin.

While an operating sequence of temperature, vibration, and touch using device 100 is described above, those skilled in the art will recognize that device 100 may be used in any other appropriate order, and in any combination of tests.

Alternative embodiments of devices 200, 300 according to the present invention are illustrated in FIGS. 7 and 8, respectively. Devices 200, 300 incorporate temperature surfaces on opposing sides of body 201, 301, respectively. In FIGS. 6 and 7, only neutral surfaces 202, 302 are shown, with variable temperature surfaces, not shown, being located on the underside of body 201, 301 respectively. In device 200, neutral surface 202 is flush with body 201, while in device 300, neutral surface 302 extends outwardly from body 301.

Although the invention is illustrated and described herein with reference to specific embodiments, the invention is not intended to be limited to the details shown. Rather, various modifications may be made in the details within the scope and range of equivalents of the claims and without departing from the invention. For example, device 100 may include three or more temperature surfaces. Alternatively, or in addition, device 100 may include two or more vibration surfaces, each capable of operating at different amplitudes and/or frequencies, or with different geometries to vary the amount of surface area in contact with the patient.

What is claimed:

1. A neuropathy diagnostic device comprising:  
a body having a first side and a second side opposite the first side, the body further comprising:  
a neutral temperature surface extending outwardly from the first side;  
a variable temperature surface extending outwardly from the second side; and  
a vibration surface having a variable vibration amplitude and extending outwardly from the body between the first side and the second side; and  
a processor disposed within the body, wherein the processor is adapted to set a temperature of the neutral temperature surface, vary a temperature of the variable temperature surface, and vary the vibration amplitude of the vibration surface.
2. The neuropathy diagnostic device according to claim 1, wherein the variable temperature surface is variable between a first temperature less than the neutral temperature surface and a second temperature greater than the neutral temperature surface.
3. The neuropathy diagnostic device according to claim 2, wherein the variable temperature surface is incrementally variable by about two degrees below the neutral temperature surface.

4. The neuropathy diagnostic device according to claim 2, wherein the variable temperature surface is incrementally variable by about two degrees above the neutral temperature surface.

5. The neuropathy diagnostic device according to claim 1, wherein the vibration surface comprises a pressure sensor.

6. The neuropathy diagnostic device according to claim 5, wherein the pressure sensor is coupled to an indicator for indicating sufficient pressure applied by the pressure sensor to a surface.

7. The neuropathy diagnostic device according to claim 1, further comprising an output for recording data generated by each of the neutral temperature surface, the variable temperature surface, and the vibration surface.

8. The neuropathy diagnostic device according to claim 1, further comprising a touch sensor extending outwardly from the body.

9. The neuropathy diagnostic device according to claim 1, wherein the device is handheld.

10. The neuropathy diagnostic device according claim 1, wherein the body comprises a single handheld body.

11. A neuropathy diagnostic device comprising:  
a body having:

a neutral temperature surface extending outwardly from the body;

a variable temperature surface extending outwardly from the body; and

a vibration surface having a variable vibration amplitude, the vibration surface extending outwardly from the body;

a processor disposed within the body, wherein the processor is adapted to set a temperature of the neutral temperature surface, vary a temperature of the variable temperature surface, and vary the vibration amplitude of the vibration surface; and

a first button operatively coupled to the processor to alternatively vary one of the temperature of the variable temperature surface and the vibration of the vibration surface in only a first direction; and

a second button operatively coupled to the processor to alternatively vary the one of the temperature of the variable temperature surface and the vibration of the vibration surface in only a second direction.

12. The neuropathy diagnostic device according claim 11, wherein the body comprises a single body.

13. A neuropathy diagnostic device comprising:

a body having a first side and a second side, the body further comprising:

a neutral temperature surface extending outwardly from the first side;

a variable temperature surface extending outwardly from the first side; and

a vibration surface having a variable vibration amplitude and extending outwardly from the second side; and

a processor disposed within the body, wherein the processor is adapted to set a temperature of the neutral temperature surface, vary a temperature of the variable temperature surface, and vary the vibration amplitude of the vibration surface.

\* \* \* \* \*

专利名称(译)	神经病变诊断装置		
公开(公告)号	<a href="#">US8579830</a>	公开(公告)日	2013-11-12
申请号	US13/054136	申请日	2009-07-17
[标]申请(专利权)人(译)	电子PRODS配饰 & CHEM		
申请(专利权)人(译)	电子产品配件 & CHEMICALS , LLC		
当前申请(专利权)人(译)	PROSENEX , LLC		
[标]发明人	GOLOSARSKY BORIS BERNHARD JAMES BROWN MICHAEL MCCARTHY JOHN		
发明人	GOLOSARSKY, BORIS BERNHARD, JAMES BROWN, MICHAEL MCCARTHY, JOHN		
IPC分类号	A61B5/00 G01K13/00 G01K1/14 G01K1/08 A61B19/00 A61F2/00 A61F7/00		
CPC分类号	A61B5/0051 A61B5/4827 A61B5/483 A61B5/441		
代理人(译)	MAENNER , 约瑟夫·		
优先权	61/081536 2008-07-17 US		
其他公开文献	US20110112431A1		
外部链接	<a href="#">Espacenet</a> <a href="#">USPTO</a>		

摘要(译)

一种神经病诊断装置，包括：主体，具有设置在主体外部的中性温度表面；可变温度表面，设置在主体的外部；以及振动表面，具有可变的振动幅度。振动表面从主体向外延伸。触摸传感器从主体向外延伸。处理器设置在主体内。处理器适于设定中性温度表面的温度，改变可变温度表面的温度，并改变振动表面的振动幅度。

