



US 20070060808A1

(19) **United States**

(12) **Patent Application Publication**
Hoarau

(10) **Pub. No.: US 2007/0060808 A1**

(43) **Pub. Date: Mar. 15, 2007**

(54) **MEDICAL SENSOR FOR REDUCING
MOTION ARTIFACTS AND TECHNIQUE
FOR USING THE SAME**

Publication Classification

(51) **Int. Cl.**
A61B 5/00 (2006.01)

(52) **U.S. Cl.** **600/323**

(76) **Inventor: Carine Hoarau, Lafayette, CA (US)**


Correspondence Address:
**FLETCHER YODER (TYCO
INTERNATIONAL, LTD.)
P.O. BOX 692289
HOUSTON, TX 77269-2289 (US)**

(57) **ABSTRACT**

A sensor may be adapted to reduce motion artifacts by damping the effects of outside forces and sensor motion. A sensor is provided with a motion damping structure adapted to reduce the effect of motion of a sensor emitter and/or detector. Further, a method of damping outside forces and sensor motion is also provided.

(21) **Appl. No.: 11/225,295**

(22) **Filed: Sep. 12, 2005**







FIG. 1B








FIG. 2






FIG. 6A




FIG. 6B




FIG. 7

**MEDICAL SENSOR FOR REDUCING MOTION
ARTIFACTS AND TECHNIQUE FOR USING THE
SAME**

BACKGROUND OF THE INVENTION

[0001] 1. Field of the Invention

[0002] The present invention relates generally to medical devices and, more particularly, to sensors used for sensing physiological parameters of a patient.

[0003] 2. Description of the Related Art

[0004] This section is intended to introduce the reader to various aspects of art that may be related to various aspects of the present invention, which are described and/or claimed below. This discussion is believed to be helpful in providing the reader with background information to facilitate a better understanding of the various aspects of the present invention. Accordingly, it should be understood that these statements are to be read in this light, and not as admissions of prior art

[0005] In the field of medicine, doctors often desire to monitor certain physiological characteristics of their patients. Accordingly, a wide variety of devices have been developed for monitoring many such physiological characteristics. Such devices provide doctors and other healthcare personnel with the information they need to provide the best possible healthcare for their patients. As a result, such monitoring devices have become an indispensable part of modern medicine.

[0006] One technique for monitoring certain physiological characteristics of a patient is commonly referred to as pulse oximetry, and the devices built based upon pulse oximetry techniques are commonly referred to as pulse oximeters. Pulse oximetry may be used to measure various blood flow characteristics, such as the blood-oxygen saturation of hemoglobin in arterial blood, the volume of individual blood pulsations supplying the tissue, and/or the rate of blood pulsations corresponding to each heartbeat of a patient. In fact, the "pulse" in pulse oximetry refers to the time varying amount of arterial blood in the tissue during each cardiac cycle.

[0007] Pulse oximeters typically utilize a non-invasive sensor that transmits light through a patient's tissue and that photoelectrically detects the absorption and/or scattering of the transmitted light in such tissue. One or more of the above physiological characteristics may then be calculated based upon the amount of light absorbed or scattered. More specifically, the light passed through the tissue is typically selected to be of one or more wavelengths that may be absorbed or scattered by the blood in an amount correlative to the amount of the blood constituent present in the blood. The amount of light absorbed and/or scattered may then be used to estimate the amount of blood constituent in the tissue using various algorithms.

[0008] Pulse oximetry readings depend on pulsation of blood through the tissue. Thus, any event that interferes with the ability of the sensor to detect that pulsation can cause variability in these measurements. Motion artifacts occur when a patient's movements cause interference in the signal detected by the sensor. Motion artifacts can also occur in response to outside forces acting on the sensor. For example,

a patient may be jostled by healthcare workers in emergency room settings. The type of force acting on a sensor will determine the nature of the motion artifact.

[0009] Generally, sensors are vulnerable to motion artifacts when the optical distance, or path length, between a sensor's emitter and detector varies due to an undesired mechanical change in the conformation of the sensor while in use. The mechanical deformation of the sensor may be in the form of a compression of the sensor, causing a decrease in path length. Alternately, a sensor may flex or move in a manner that increases the distance between an emitter and detector, resulting in an increase in path length. In any case, variability in the optical path length due to motion can cause motion artifacts and obscure the desired pulse oximetry signal.

SUMMARY

[0010] Certain aspects commensurate in scope with the originally claimed invention are set forth below. It should be understood that these aspects are presented merely to provide the reader with a brief summary of certain forms that the invention might take and that these aspects are not intended to limit the scope of the invention. Indeed, the invention may encompass a variety of aspects that may not be set forth below.

[0011] There is provided a sensor that includes a sensor body, and an emitter and a detector disposed on the sensor body. The sensor also includes a motion damping structure associated with the sensor body, whereby the motion damping structure is adapted to damp a force experienced by the sensor body.

[0012] There is also provided a pulse oximetry system that includes: a pulse oximetry monitor; and a pulse oximetry sensor adapted to be operatively coupled to the monitor. The sensor includes a sensor body, and an emitter and a detector disposed on the sensor body. The sensor also includes a motion damping structure associated with the sensor body, whereby the motion damping structure is adapted to damp a force experienced by the sensor body.

[0013] There is also provided a method of operating a sensor that includes damping a mechanical force affecting a sensor such that an effective force experienced by at least one of a emitter or a detector is less than the mechanical force.

[0014] There is also provided a method of manufacturing a sensor that includes providing a sensor body on which an emitter and a detector are disposed. The method also includes providing a motion damping structure disposed on the sensor body.

BRIEF DESCRIPTION OF THE DRAWINGS

[0015] Advantages of the invention may become apparent upon reading the following detailed description and upon reference to the drawings in which:

[0016] FIG. 1A illustrates a perspective view of an exemplary embodiment of a clip-style pulse oximetry sensor featuring a dashpot;

[0017] FIG. 1B illustrates a cross-sectional view of the pulse oximetry sensor of FIG. 1A applied to a patient digit that is pressing against an object;

[0018] FIG. 2 illustrates a cross-sectional view of an exemplary embodiment of a bandage-style pulse oximetry sensor applied to a patient's digit, whereby the sensor includes an impact-absorbing chamber at one end of the sensor;

[0019] FIG. 3 illustrates a perspective view of an alternate exemplary embodiment of a bandage-style pulse oximetry sensor with a fluid-filled impact-absorbing chamber disposed along the body of the sensor;

[0020] FIG. 4 illustrates a perspective view of an exemplary embodiment of a forehead pulse oximetry sensor whereby the emitter and detector are disposed within impact-absorbing chambers;

[0021] FIG. 5A illustrates a cross-sectional view of an exemplary embodiment of a bandage-style pulse oximetry sensor having a series of interconnected impact-absorbing chambers;

[0022] FIG. 5B illustrates a cross-sectional view of the pulse oximetry sensor of FIG. 5A applied to a patient digit that is flexed at the first finger joint;

[0023] FIG. 6A illustrates a perspective view of an embodiment of an exemplary clip-style pulse oximetry sensor with an impact-absorbing foam disposed on the surface that does not contact a patient's tissue during normal use according to the present invention;

[0024] FIG. 6B illustrates a cross-sectional view of the pulse oximetry sensor of FIG. 6A; and

[0025] FIG. 7 illustrates a pulse oximetry system coupled to a multi-parameter patient monitor and a sensor according to embodiments of the present invention.

DETAILED DESCRIPTION OF SPECIFIC EMBODIMENTS

[0026] One or more specific embodiments of the present invention will be described below. In an effort to provide a concise description of these embodiments, not all features of an actual implementation are described in the specification. It should be appreciated that in the development of any such actual implementation, as in any engineering or design project, numerous implementation-specific decisions must be made to achieve the developers' specific goals, such as compliance with system-related and business-related constraints, which may vary from one implementation to another. Moreover, it should be appreciated that such a development effort might be complex and time consuming, but would nevertheless be a routine undertaking of design, fabrication, and manufacture for those of ordinary skill having the benefit of this disclosure.

[0027] In accordance with the present technique, sensors for pulse oximetry or other applications utilizing spectrophotometry are provided that reduce motion artifacts by damping the effects of patient movement or outside forces. For example, sensors are provided that have various motion damping mechanisms adapted to reduce the effect of motion or outside forces on a pulse oximetry measurement.

[0028] Motion artifacts in pulse oximetry are often generated by the movement of the pulse oximetry sensor relative to the optically probed tissue, which is typically caused by patient movement. Because pulse oximetry is

often used in settings where it is difficult to prevent patient motion, it is desirable to provide a mechanism for reducing the effects of motion on the pulse oximetry measurement. For example, a squeezing motion by a patient may mechanically deform a sensor, causing the sensor's emitter and detector to change position relative to one another, resulting in a motion artifact. The squeezing motion may be damped by converting the mechanical energy of patient movement into thermal energy by damping the force with an impact-absorbing fluid or solid, thus dissipating the force and reducing mechanical deformation of the sensor. The force of squeezing may be damped such that the effective force experienced by the sensor's emitter and/or detector is reduced, and the relative change in the position of the emitter relative to the detector is also reduced. Similarly, outside forces, such as the mechanical force of an object pressing against a sensor, can be damped by absorbing the force such that the effective force experienced by the sensor components is reduced.

[0029] Mechanical forces, including those caused by translational and/or kinetic energy of an object, may be impeded by opposing forces. Specifically, as a force acts on a pulse oximetry sensor, it is opposed by the inertia of the sensor as well as the opposing force of a damper. The amplitude of the mechanical energy of movement is attenuated through energy lost to inertia and damping. For example, energy may be lost to viscous damping with a fluid, or by yielding or plastic straining of a damping material. Additionally, some energy will be converted to thermal energy through frictional forces.

[0030] Sensors are disclosed herein having a motion damping mechanism to reduce the effect of motion or outside forces on the measurements of physiological parameters, such as pulse oximetry measurements. FIG. 1A illustrates an exemplary clip-type sensor 10A appropriate for use on a patient's digit 12. The sensor 10A has a dashpot 14 disposed on the sensor body 16, a cross-sectional view of which is illustrated in FIG. 1B. A dashpot 14 is a mechanical device used to damp motion that includes a piston 18 that moves through a cylinder 20 containing a fluid 22. The dashpot 14 is partially embedded in the sensor body 16 such that the piston 18 protrudes from the sensor body 16 on a surface 24 that does not contact the sensor site of the patient's tissue during normal use. A force applied to the piston 18, such as tapping against an object 26, causes the piston 18 to move through the fluid 22 in the direction shown by arrow 28. As the piston 18 pushes through the fluid 22, the mechanical energy of the force acting on the piston 18 is converted into thermal energy. The damping force is proportional to the velocity of the piston 18 and the viscosity of the fluid 22 through which the piston moves. Thus, the dashpot 14 damps motion caused by tapping or pressing the sensor 10A against an object 26.

[0031] In other embodiments (not shown), the sensor 10A may have multiple dashpots 14 disposed on the sensor body 16 on the surface 24 that does not contact the sensor site of the patient's tissue during normal use. It may be advantageous to provide motion damping mechanisms on multiple sides of the sensor 10A, as it is difficult to predict the types of motion that the sensor 10A may experience. For example, dashpots 14 may be distributed on the sensor body 16 in locations directly opposing each other across the digit 12. Further, it should be understood that a dashpot 14 according

to the present technique may be adapted to damp forces applied at various angles. The piston 18 may be adapted move through the fluid 22 at an angle that corresponds to the angle with which the force was applied.

[0032] In certain embodiments, a fluid may be used to damp mechanical energy by other techniques. For reasons related to total sensor weight, it may be desirable to employ a lightweight motion damping device in conjunction with disposable sensors. For example, FIG. 2 illustrates a bandage-type sensor 10B applied to a patient digit 30. The sensor 10B has an impact-absorbing chamber 32 that contains a fluid 34. As depicted, the impact-absorbing chamber 32 is disposed on the sensor 10B such that it correlates with the fingertip region of the digit 30. The fluid 34 in the impact-absorbing chamber 32 damps energy caused by pressing or tapping a fingertip against an object. The impact-absorbing chamber 32 is flexible and not completely filled with fluid, and is thus compressible in response to an applied force. The mechanical energy of the pressing or tapping is damped through conversion to thermal energy and/or absorbed by the physical deformation of the fluid in an amount proportional to the force applied. Thus, the motion is damped and the effective force experienced by the emitter 36 and the detector 38 is reduced as a consequence.

[0033] In another embodiment, as shown in FIG. 3, an impact-absorbing chamber 42 may be disposed on a sensor 10C such that the impact-absorbing chamber 42 covers the surface 40 of the sensor body 44 that does not contact the tissue during normal use. The fluid 46 in the impact-absorbing chamber 42 will physically impede a finger squeezing motion as well as damp the mechanical energy associated with the motion. As the energy of squeezing is absorbed by the fluid 46, the sensor 10C remains substantially stable. As a consequence, the emitter 48 and the detector 50 also remain substantially unaffected by the motion.

[0034] It is also contemplated that a fluid may damp mechanical energy to reduce its direct action on an emitter 52 or a detector 54. FIG. 4 illustrates a reflectance-type sensor 10D adapted for use on a patient's forehead. The sensor 10D has impact-absorbing chambers 56 and 58 containing a fluid 60. The impact-absorbing chambers 56 and 58 enclose an emitter 52 and a detector 54, respectively. The emitter 52 and the detector 54 are surrounded by the fluid 60, which absorbs outside forces, thereby reducing the transmission of outside forces to the emitter 52 and the detector 54. The impact-absorbing chambers 56 and 58 also protect the emitter 52 and the detector 54 from damage during the period of use of the sensor 10D. Such an arrangement may be advantageous in outpatient situations in which it is contemplated that a patient may be ambulatory, and the sensor 10C may be subject to higher-than-normal outside forces.

[0035] In another embodiment, FIG. 5A illustrates an exemplary bandage-style sensor 10E adapted for use on a digit 62. The sensor 10E has a plurality of impact-absorbing chambers 64 connected by respective orifices 66, wherein the orifices 66 are sized so as to restrict the flow rate of a fluid 68 between the impact-absorbing chambers 64. As shown in FIG. 5B, as the digit 62 moves in a squeezing motion, the fluid 68 passes through the orifices 66 and is redistributed through the impact-absorbing chambers 64 in

response to the movement. The impact-absorbing chambers 64 are partially full of the fluid 68. The redistribution of the fluid 68 serves to damp the energy generated by the digit 62 moving in space. Specifically, the force of the digit 62 movement is opposed by the force required to push the fluid 68 through the orifices 66. The damped force experienced by the sensor 10E is thus reduced by roughly the amount of the opposing force provided by the damping mechanism.

[0036] The fluid (e.g. fluid 22, fluid 34, fluid 46, fluid 60, or fluid 68) described in the above embodiments may be any suitable fluid with the appropriate rheological properties for damping mechanical energy, such as a viscoelastic fluid or gel. In certain embodiments, the fluid may be air or other gases and gas mixtures. In other embodiments, the fluid may be an oil or liquid, such as mineral oil. Other examples of suitable fluids include, but are not limited to, polyethylene glycol, liquid silicone, magnetorheological fluids, and polyurethane polymer gels. It is contemplated that the fluid may be a mixture of liquid and gas. In certain embodiments, it may be desirable to employ a gas or gas mixture for reasons related to cost, manufacturing convenience, and total sensor weight. In situations where a sensor may be exposed to more extreme outside forces, it may be desirable to employ a viscoelastic oil, as oils generally provide more efficient damping than gases.

[0037] In certain embodiments, impact-absorbing solids and/or foams with viscoelastic properties may be appropriate for mechanical damping of motion to reduce motion artifacts in a pulse oximetry sensor. For example, a clip-style sensor 10F is illustrated in FIG. 6A that has an impact-absorbing foam 70 disposed over a non-tissue-contacting surface 72 of the sensor body 74. FIG. 6B is a cross-sectional view of the sensor 10F. The impact-absorbing foam 70 dissipates the effect of an outside force on the sensor 10F. In another embodiment (not shown), the impact absorbing foam 70 is disposed on the tissue-contacting surface of the sensor 10F. Impact-absorbing solids and foams according to the present invention include, but are not limited to, neoprene, silicone, rubber, Sorbothane® (available from Sorbothane, Incorporated), and ISODAMP® SD or CONFOR® foams (available from E-A-R Specialty Composites).

[0038] A sensor, illustrated generically as a sensor 10, may be used in conjunction with a pulse oximetry monitor 76, as illustrated in FIG. 7. It should be appreciated that the cable 78 of the sensor 10 may be coupled to the monitor 76 or it may be coupled to a transmission device (not shown) to facilitate wireless transmission between the sensor 10 and the monitor 76. The monitor 76 may be any suitable pulse oximeter, such as those available from Nellcor Puritan Bennett Inc. Furthermore, to upgrade conventional pulse oximetry provided by the monitor 76 to provide additional functions, the monitor 76 may be coupled to a multi-parameter patient monitor 80 via a cable 82 connected to a sensor input port or via a cable 84 connected to a digital communication port.

[0039] The sensor 10 includes an emitter 86 and a detector 88 that may be of any suitable type. For example, the emitter 86 may be one or more light emitting diodes adapted to transmit one or more wavelengths of light in the red to infrared range, and the detector 88 may be a photodetector selected to receive light in the range or ranges emitted from

the emitter **86**. For pulse oximetry applications using either transmission or reflectance type sensors the oxygen saturation of the patient's arterial blood may be determined using two or more wavelengths of light, most commonly red and near infrared wavelengths. Similarly, in other applications, a tissue water fraction (or other body fluid related metric) or a concentration of one or more biochemical components in an aqueous environment may be measured using two or more wavelengths of light, most commonly near infrared wavelengths between about 1,000 nm to about 2,500 nm. It should be understood that, as used herein, the term "light" may refer to one or more of infrared, visible, ultraviolet, or even X-ray electromagnetic radiation, and may also include any wavelength within the infrared, visible, ultraviolet, or X-ray spectra.

[0040] The emitter **86** and the detector **88** may be disposed on a sensor body **90**, which may be made of any suitable material, such as plastic, foam, woven material, or paper. Alternatively, the emitter **86** and the detector **88** may be remotely located and optically coupled to the sensor **10** using optical fibers. In the depicted embodiments, the sensor **10** is coupled to a cable **78** that is responsible for transmitting electrical and/or optical signals to and from the emitter **86** and detector **88** of the sensor **10**. The cable **78** may be permanently coupled to the sensor **10**, or it may be removably coupled to the sensor **10**—the latter alternative being more useful and cost efficient in situations where the sensor **10** is disposable.

[0041] The sensor **10** may be a "transmission type" sensor. Transmission type sensors include an emitter **86** and detector **88** that are typically placed on opposing sides of the sensor site. If the sensor site is a fingertip, for example, the sensor **10** is positioned over the patient's fingertip such that the emitter **86** and detector **88** lie on either side of the patient's nail bed. In other words, the sensor **10** is positioned so that the emitter **86** is located on the patient's fingernail and the detector **88** is located 180° opposite the emitter **86** on the patient's finger pad. During operation, the emitter **86** shines one or more wavelengths of light through the patient's fingertip and the light received by the detector **88** is processed to determine various physiological characteristics of the patient. In each of the embodiments discussed herein, it should be understood that the locations of the emitter **86** and the detector **88** may be exchanged. For example, the detector **88** may be located at the top of the finger and the emitter **86** may be located underneath the finger. In either arrangement, the sensor **10** will perform in substantially the same manner.

[0042] Reflectance type sensors generally operate under the same general principles as transmittance type sensors. However, reflectance type sensors include an emitter **86** and detector **88** that are typically placed on the same side of the sensor site. For example, a reflectance type sensor may be placed on a patient's fingertip or forehead such that the emitter **86** and detector **88** lie side-by-side. Reflectance type sensors detect light photons that are scattered back to the detector **88**.

[0043] While the invention may be susceptible to various modifications and alternative forms, specific embodiments have been shown by way of example in the drawings and have been described in detail herein. However, it should be understood that the invention is not intended to be limited to the particular forms disclosed. Indeed, the present tech-

niques may not only be applied to measurements of blood oxygen saturation, but these techniques may also be utilized for the measurement and/or analysis of other blood constituents. For example, using the same, different, or additional wavelengths, the present techniques may be utilized for the measurement and/or analysis of carboxyhemoglobin, methemoglobin, total hemoglobin, intravascular dyes, and/or water content. Rather, the invention is to cover all modifications, equivalents, and alternatives falling within the spirit and scope of the invention as defined by the following appended claims.

What is claimed is:

1. A sensor comprising:

a sensor body;

an emitter and a detector disposed on the sensor body; and

a motion damping structure associated with the sensor body, wherein the motion damping structure is adapted to damp a force experienced by the sensor body.

2. The sensor, as set forth in claim 1, wherein the sensor comprises at least one of a pulse oximetry sensor or a sensor for measuring a water fraction.

3. The sensor, as set forth in claim 1, wherein the emitter comprises at least one light emitting diode.

4. The sensor, as set forth in claim 1, wherein the detector comprises at least one photodetector.

5. The sensor, as set forth in claim 1, wherein the motion damping structure comprises a dashpot.

6. The sensor, as set forth in claim 1, wherein the motion damping structure comprises a foam.

7. The sensor, as set forth in claim 1, wherein the motion damping structure comprises viscoelastic solid.

8. The sensor, as set forth in claim 1, wherein the motion damping structure comprises a fluid.

9. The sensor, as set forth in claim 1, wherein the emitter is disposed within a chamber comprising a fluid.

10. The sensor, as set forth in claim 1, wherein the detector is disposed within a chamber comprising a fluid.

11. The sensor, as set forth in claim 1, wherein the motion damping structure comprises a plurality of impact-absorbing chambers connected by respective orifices, wherein the orifices are sized so as to restrict the flow rate of a fluid between the plurality of impact-absorbing chambers.

12. The sensor, as set forth in claim 1, wherein the sensor comprises a bandage-type sensor.

13. The sensor, as set forth in claim 1, wherein the sensor comprises a clip-type sensor.

14. A pulse oximetry system comprising:

a pulse oximetry monitor; and

a pulse oximetry sensor adapted to be operatively coupled to the monitor, the sensor comprising:

a sensor body;

an emitter and a detector disposed on the sensor body; and

a motion damping structure associated with the sensor body, wherein the motion damping structure is adapted to damp a force experienced by the sensor body.

15. The system, as set forth in claim 14, wherein the emitter comprises at least one light emitting diode.

16. The system, as set forth in claim 14, wherein the detector comprises at least one photodetector.

17. The system, as set forth in claim 14, wherein the motion damping structure comprises a dashpot.

18. The system, as set forth in claim 14, wherein the motion damping structure comprises a fluid.

19. The system, as set forth in claim 14, wherein the motion damping structure comprises a foam.

20. The system, as set forth in claim 14, wherein the motion damping structure comprises a viscoelastic solid.

21. The system, as set forth in claim 14, wherein the emitter is disposed in a chamber comprising a fluid.

22. The system, as set forth in claim 14, wherein the detector is disposed in a chamber comprising a fluid.

23. The system, as set forth in claim 14, wherein the motion damping structure comprises a plurality of impact-absorbing chambers connected by respective orifices, wherein the orifices are sized so as to restrict the flow rate of a fluid between the plurality of impact-absorbing chambers.

24. The system, as set forth in claim 14, wherein the sensor comprises a bandage-type sensor.

25. The system, as set forth in claim 14, wherein the sensor comprises a clip-type sensor.

26. A method comprising:

damping a mechanical force affecting a sensor such that an effective force experienced by at least one of a emitter or a detector is less than the mechanical force.

27. The method, as set forth in claim 26, wherein damping the mechanical force comprises forcing ambient air through an orifice at a controlled rate to dissipate mechanical energy.

28. The method, as set forth in claim 26, wherein damping the mechanical force comprises forcing a fluid through a plurality of impact-absorbing chambers connected by respective orifices, wherein the orifices are sized so as to restrict the flow rate of the fluid between the plurality of impact-absorbing chambers.

29. The method, as set forth in claim 26, wherein damping the mechanical force comprises dissipating mechanical energy through a fluid.

30. The method, as set forth in claim 26, wherein damping the mechanical force comprises dissipating mechanical energy through a foam.

31. The method, as set forth in claim 26, wherein damping the mechanical force comprises dissipating mechanical energy through a viscoelastic solid.

32. A method of manufacturing a sensor, comprising:

providing a sensor body on which an emitter and a detector are disposed; and

providing a motion damping structure disposed on the sensor body.

33. The method, as set forth in claim 32, wherein the sensor comprises at least one of a pulse oximetry sensor or a sensor for measuring a water fraction.

34. The method, as set forth in claim 32, wherein providing the emitter comprises providing one or more light emitting diodes.

35. The method, as set forth in claim 32, wherein providing the detector comprises providing one or more photodetectors.

36. The method, as set forth in claim 32, wherein providing the motion damping structure comprises providing a dashpot.

37. The method, as set forth in claim 32, wherein providing the motion damping structure comprises providing a chamber comprising a fluid.

38. The method, as set forth in claim 32, wherein providing the motion damping structure comprises providing a chamber comprising a fluid within which the emitter is disposed.

39. The method, as set forth in claim 32, wherein providing the motion damping structure comprises providing a foam disposed on the sensor body.

40. The method, as set forth in claim 32, wherein providing the motion damping structure comprises providing a chamber comprising a fluid within which the detector is disposed.

41. The method, as set forth in claim 32, wherein providing the motion damping structure comprises providing a plurality of impact-absorbing chambers connected by respective orifices, wherein the orifices are sized so as to restrict the flow rate of a fluid between the plurality of impact-absorbing chambers.

* * * * *

专利名称(译)	用于减少运动伪影的医疗传感器及其使用技术		
公开(公告)号	US20070060808A1	公开(公告)日	2007-03-15
申请号	US11/225295	申请日	2005-09-12
[标]申请(专利权)人(译)	HOARAU CARINE		
申请(专利权)人(译)	HOARAU CARINE		
当前申请(专利权)人(译)	NELLCOR PURITAN BENNETT INCORPORATED		
[标]发明人	HOARAU CARINE		
发明人	HOARAU, CARINE		
IPC分类号	A61B5/00		
CPC分类号	A61B5/14552 A61B5/6826 Y10T29/49826 A61B5/7207 A61B5/6838		
外部链接	Espacenet USPTO		

摘要(译)

传感器可以适于通过抑制外力和传感器运动的影响来减少运动伪影。传感器设置有运动阻尼结构，其适于减小传感器发射器和/或检测器的运动的影响。此外，还提供了一种阻尼外力和传感器运动的方法。

