



US007416532B1

(12) **United States Patent**
Broshears

(10) **Patent No.:** **US 7,416,532 B1**
(45) **Date of Patent:** **Aug. 26, 2008**

(54) **TRACH SENSORY ALERT SYSTEM**

(75) Inventor: **Loretta S. Broshears**, Spring Hill, FL
(US)

(73) Assignee: **Loretta Broshears Doughty**,
Tallahassee, FL (US)

(*) Notice: Subject to any disclaimer, the term of this
patent is extended or adjusted under 35
U.S.C. 154(b) by 1153 days.

(21) Appl. No.: **10/035,472**

(22) Filed: **Oct. 23, 2001**

Related U.S. Application Data

(60) Provisional application No. 60/242,993, filed on Oct.
23, 2000.

(51) **Int. Cl.**
A61B 5/00 (2006.01)

(52) **U.S. Cl.** **600/549**

(58) **Field of Classification Search** 600/537,
600/529, 549; 340/608; 712/131; 128/207.14
See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

3,903,876	A *	9/1975	Harris		600/537
4,046,139	A *	9/1977	Horn		600/549
4,830,022	A *	5/1989	Harshe et al.		600/537
5,070,321	A *	12/1991	Einhorn et al.		600/537

* cited by examiner


Primary Examiner—Max Hindenburg


Assistant Examiner—Jonathan M Foreman

(57) **ABSTRACT**

An alarm device that includes a temperature sensor placed in
the tube of a trach tube and which is adapted to activate an
audible alarm when predetermine low temperature has been
detected.

1 Claim, 1 Drawing Sheet





1

TRACH SENSORY ALERT SYSTEM

This application claims the benefit of priority to U.S. Provisional Application No. 60/242,993 filed Oct. 23, 2000.

TECHNICAL FIELD

The present invention relates to medical safety equipment and more particularly to a trach tube sensory alert mechanism that includes an alarm system with temperature controlled sensor which is positioned within the tracheotomy tube of a patient that is inserted into the windpipe area and which is configured to emit an audible alert alarm when the temperature detected by the sensor falls below a predetermined set temperature to alert the patient care givers that the trach tube may have been pulled out or a drastic drop in body temperature has occurred.

BACKGROUND OF INVENTION

The disconnection of tracheotomy tubes can cause death through asphyxiation if the trach opening is closed or cannot be reopened because a tracheotomy tube has been fully pulled out. It would be desirable, therefore, to have an alert device which would sense the temperature of the interior or exterior of the trach tube and which would provide an audible alarm for alerting care givers that the trach tube is working its way out of the trach opening and/or the body temperature of the patient has fallen below a safe level.

SUMMARY OF INVENTION

It is thus an object of the invention to provide a trach sensory alert system that includes an alarm system with temperature controlled sensor which is positioned within the tracheotomy tube of a patient that is inserted into the windpipe area and which is configured to emit an audible alert alarm when the temperature detected by the sensor falls below a predetermined set temperature to alert the patient care givers that the trach tube may have been pulled out or a drastic drop in body temperature has occurred.

Accordingly, a trach sensory alert system is provided. The trach sensory alert system includes an alarm system with temperature controlled sensor which is positioned within the tracheotomy tube of a patient that is inserted into the windpipe area and which is configured to emit an audible alert alarm when the temperature detected by the sensor falls below a predetermined set temperature to alert the patient care givers that the trach tube may have been pulled out or a drastic drop in body temperature has occurred.

BRIEF DESCRIPTION OF DRAWINGS

For a further understanding of the nature and objects of the present invention, reference should be had to the following detailed description, taken in conjunction with the accompa-

2

nying drawings, in which like elements are given the same or analogous reference numbers and wherein:

FIG. 1 shows an exemplary embodiment of a trach tube with the trach sensory alert positioned within the stoma tube.

FIG. 2 shows the stoma tube into the patient and the sensor positioned within the neck area of the patient.

EXEMPLARY EMBODIMENTS

FIGS. 1 and 2 show various aspects of an exemplary embodiment of the trach sensory alert system of the present invention generally designated 10 in use with a representative tracheotomy device 12 and installed in the trachea 14 of a representative patient 16. Trach sensory alert system 10 includes a temperature controlled sensor 18 that is placed within the alarm portion 20 of a trach tube 22 of tracheotomy device 12. In use, trach tube 22 is positioned within the trachea 14 of patient 16 and is therefore subjected to the normal body temperature of patient 16. Should tracheotomy device 12 begin to work its way out through the ostomy opening 30 through which it is inserted, sensor 18 will detect a corresponding drop in body temperature and trigger an alerting device 20 contained within itself which generates a high pitched audible alarm to alert the patient 16 as well as any care givers.

It can be seen from the preceding description that a trach sensory alert system has been provided.

It is noted that the embodiment of the a trach sensory alert system described herein in detail for exemplary purposes is of course subject to many different variations in structure, design, application and methodology. Because many varying and different embodiments may be made within the scope of the inventive concept(s) herein taught, and because many modifications may be made in the embodiment herein detailed in accordance with the descriptive requirements of the law, it is to be understood that the details herein are to be interpreted as illustrative and not in a limiting sense.

What is claimed is:

1. A method of alerting a care giver before a tracheotomy tube is expelled comprising:
 providing a tracheotomy tube;
 positioning within the interior lumen of said tracheotomy tube an alert system, wherein the alert system includes a temperature controlled sensor for sensing the temperature of the interior or exterior of said tracheotomy tube and an alerting device for providing an audible alarm;
 inserting the tracheotomy tube within a patient's trachea;
 subjecting said temperature controlled sensor to the normal body temperature of the patient;
 detecting a corresponding drop in body temperature due to said tracheotomy tube being too far out of the patient's stoma;
 triggering said alerting device and generating a high pitched audible alarm.

* * * * *

专利名称(译)	Trach感官警报系统		
公开(公告)号	US7416532	公开(公告)日	2008-08-26
申请号	US10/035472	申请日	2001-10-23
[标]申请(专利权)人(译)	道蒂LORETTA BROSHEARS		
申请(专利权)人(译)	道蒂, LORETTA BROSHEARS		
当前申请(专利权)人(译)	道蒂, LORETTA BROSHEARS		
[标]发明人	BROSHEARS LORETTA S		
发明人	BROSHEARS, LORETTA S.		
IPC分类号	A61B5/00		
CPC分类号	A61B5/01 A61M16/0465 A61B1/2676 A61M2205/3368 A61M16/0434 A61B2560/0276		
优先权	60/242993 2000-10-23 US		
外部链接	Espacenet USPTO		

摘要(译)

一种报警装置，其包括放置在气管导管中的温度传感器，并且适于在检测到预定的低温时激活声音报警。

