



US007698909B2

(12) **United States Patent**
Hannula et al.

(10) **Patent No.:** **US 7,698,909 B2**
(45) **Date of Patent:** **Apr. 20, 2010**

(54) **HEADBAND WITH TENSION INDICATOR**

4,825,872 A 5/1989 Tan et al.
4,825,879 A 5/1989 Tan et al.

(75) Inventors: **Don Hannula**, San Luis Obispo, CA
(US); **Joseph Coakley**, Dublin, CA
(US); **Paul D. Mannheimer**, Danville,
CA (US)

(Continued)

FOREIGN PATENT DOCUMENTS

CN 1306260 8/2001

(Continued)

OTHER PUBLICATIONS

U.S. Appl. No. 10/677,742, filed Oct. 1, 2003, Hannula et al.

(Continued)

Primary Examiner—Danny Worrell

(74) *Attorney, Agent, or Firm*—Fletcher Yoder

(73) Assignee: **Nellcor Puritan Bennett LLC**, Boulder,
CO (US)

(*) Notice: Subject to any disclaimer, the term of this
patent is extended or adjusted under 35
U.S.C. 154(b) by 1347 days.

(21) Appl. No.: **10/779,331**

(22) Filed: **Feb. 13, 2004**

(57) **ABSTRACT**

(65) **Prior Publication Data**

US 2004/0221370 A1 Nov. 11, 2004

(51) **Int. Cl.**
D04B 1/24 (2006.01)

(52) **U.S. Cl.** **66/172 E**; 2/181

(58) **Field of Classification Search** 66/169 R,
66/172 E, 170, 171; 2/171, 181, 181.2
See application file for complete search history.


(56) **References Cited**

U.S. PATENT DOCUMENTS

4,025,733 A 5/1977 Klar et al.
4,047,400 A * 9/1977 Thorneburg 66/171
4,462,116 A 7/1984 Sanzone et al.
4,499,741 A * 2/1985 Harris 66/171
4,510,938 A 4/1985 Jobsis et al.
4,570,638 A 2/1986 Stoddart et al.
4,675,919 A 6/1987 Heine et al.
4,739,757 A 4/1988 Edwards
4,775,116 A 10/1988 Klein
4,784,162 A 11/1988 Ricks et al.
4,802,485 A 2/1989 Bowers et al.

A headband having a low stretch segment sized to fit around a wearer's head, and an elastic segment being smaller than the low stretch segment, and having a free end and an attached end, where the elastic segment is attached at its attached end with the low stretch segment. The headband also includes a tab portion having a first end and a second end, the first end of the tab portion being connected with the free end of the elastic portion, the second end of the tab portion configured to form a closed loop with the low stretch segment, around the wearer's head. The headband also includes visual indicator configured for monitoring the extended position of elastic segment and optionally a stop portion that is configured to engage against the elastic segment to limit its stretch. When having a stop portion, the tab portion also includes an indicator portion between its first end and the stop portion such that the indicator portion when visible indicates that the headband needs re-tightening; and when the indicator portion is not visible it indicates an adequate level of tension corresponding with delivering a pressure in the range higher than the venous pressure and lower than the capillary pressure to the forehead of the wearer.

18 Claims, 6 Drawing Sheets



U.S. PATENT DOCUMENTS					
4,833,734 A *	5/1989	Der Estephanian	2/171	5,596,987 A	1/1997 Chance
4,838,279 A	6/1989	Fore		5,617,865 A	4/1997 Palczewska et al.
4,856,116 A	8/1989	Sullivan		5,617,866 A	4/1997 Marian, Jr.
4,890,619 A	1/1990	Hatschek		5,627,323 A	5/1997 Stern
4,910,804 A *	3/1990	Lidgren	2/209.3	5,634,466 A	6/1997 Gruner
4,918,758 A *	4/1990	Rendina	2/171	5,638,593 A	6/1997 Gerhardt et al.
4,930,888 A	6/1990	Freisleben et al.		5,638,818 A	6/1997 Diab et al.
4,942,877 A	7/1990	Sakai et al.		5,640,953 A	6/1997 Bishop et al.
4,972,331 A	11/1990	Chance		5,645,440 A	7/1997 Tobler et al.
4,977,011 A	12/1990	Smith		5,645,586 A	7/1997 Meltzer
4,991,234 A	2/1991	Greenberg		5,646,416 A	7/1997 Van De Velde
4,996,975 A	3/1991	Nakamura		5,671,750 A	9/1997 Shinoda
5,005,374 A	4/1991	Spitler et al.		5,673,708 A	10/1997 Athanasiou et al.
5,054,488 A	10/1991	Muz		5,678,544 A	10/1997 DeLonzor et al.
5,080,096 A	1/1992	Hooper et al.		5,681,285 A	10/1997 Ford et al.
5,080,098 A	1/1992	Willett et al.		5,683,434 A	11/1997 Archer
H1039 H	4/1992	Tripp, Jr. et al.		5,697,363 A	12/1997 Hart
5,111,817 A	5/1992	Clark et al.		5,697,367 A	12/1997 Lewis et al.
5,119,815 A	6/1992	Chance		5,701,894 A	12/1997 Cherry et al.
5,122,974 A	6/1992	Chance		5,706,820 A	1/1998 Hossack et al.
5,125,403 A	6/1992	Culp		5,732,475 A	3/1998 Sacks et al.
5,167,230 A	12/1992	Chance		5,738,612 A	4/1998 Tsuda
5,188,108 A	2/1993	Secker		5,743,856 A	4/1998 Oka et al.
5,191,891 A	3/1993	Righter		5,743,857 A	4/1998 Shinoda et al.
5,209,230 A	5/1993	Swedlow et al.		5,752,913 A	5/1998 Oka
5,214,409 A	5/1993	Beigel		5,752,920 A	5/1998 Ogura et al.
5,217,012 A	6/1993	Young et al.		5,758,644 A	6/1998 Diab et al.
5,217,013 A	6/1993	Lewis et al.		5,772,601 A	6/1998 Oka et al.
5,241,300 A	8/1993	Buschmann		5,776,058 A	7/1998 Levinson et al.
5,246,003 A	9/1993	DeLonzor		5,776,071 A	7/1998 Inuaki et al.
5,253,645 A	10/1993	Friedman et al.		5,779,631 A	7/1998 Chance
5,267,563 A	12/1993	Swedlow et al.		5,779,639 A	7/1998 Yeung
5,267,567 A	12/1993	Aung et al.		5,782,757 A	7/1998 Diab et al.
5,295,490 A	3/1994	Dodakian		5,786,592 A	7/1998 Hök
5,313,940 A	5/1994	Fuse et al.		5,791,347 A	8/1998 Flaherty et al.
5,337,744 A	8/1994	Branigan		5,791,348 A	8/1998 Aung et al.
5,348,008 A	9/1994	Bornn et al.		5,792,052 A	8/1998 Isaacson
5,353,798 A	10/1994	Sieben		5,792,058 A	8/1998 Lee et al.
5,354,979 A	10/1994	Adelson et al.		5,797,841 A	8/1998 Delonzor et al.
5,357,953 A	10/1994	Merrick et al.		5,810,724 A	9/1998 Gronvall
5,368,025 A	11/1994	Young et al.		5,813,980 A	9/1998 Levinson et al.
5,368,562 A	11/1994	Blomquist et al.		5,823,012 A *	10/1998 HacsKaylo 66/171
5,383,874 A	1/1995	Jackson et al.		5,823,952 A	10/1998 Levinson et al.
5,392,777 A	2/1995	Swedlow et al.		5,826,277 A	10/1998 McConville
5,398,689 A	3/1995	Conner et al.		5,830,136 A	11/1998 Delonzor et al.
5,400,267 A	3/1995	Denen et al.		5,830,137 A	11/1998 Scharf
5,405,269 A	4/1995	Stupecky		5,830,148 A	11/1998 Inuaki et al.
5,405,614 A	4/1995	D'Angelo et al.		5,830,149 A	11/1998 Oka et al.
5,413,099 A	5/1995	Schmidt et al.		5,833,602 A	11/1998 Osemwota
5,413,101 A	5/1995	Sugiura		5,836,887 A	11/1998 Oka et al.
5,413,102 A	5/1995	Schmidt et al.		5,839,439 A	11/1998 Nierlich et al.
5,415,166 A	5/1995	Imran		RE36,000 E	12/1998 Swedlow et al.
5,425,360 A	6/1995	Nelson		5,842,981 A	12/1998 Larsen et al.
5,431,170 A	7/1995	Mathews		5,842,982 A	12/1998 Mannheimer
5,437,275 A	8/1995	Amundsen et al.		5,851,179 A	12/1998 Ritson et al.
5,437,634 A	8/1995	Amano		5,857,974 A	1/1999 Eberle et al.
5,444,254 A	8/1995	Thomson		5,860,932 A	1/1999 Goto et al.
5,451,763 A	9/1995	Pickett et al.		5,860,957 A	1/1999 Jacobsen et al.
5,452,717 A	9/1995	Branigan et al.		5,868,133 A	2/1999 DeVries et al.
5,465,714 A	11/1995	Scheuing		5,870,626 A	2/1999 Lebeau
5,469,845 A	11/1995	DeLonzor et al.		5,872,713 A	2/1999 Douglas et al.
5,482,034 A	1/1996	Lewis		5,873,821 A	2/1999 Chance et al.
5,490,523 A	2/1996	Isaacson		5,879,294 A	3/1999 Anderson et al.
5,528,519 A	6/1996	Ohkura et al.		5,891,021 A	4/1999 Dillon et al.
5,546,955 A	8/1996	Wilk		5,891,026 A	4/1999 Wang et al.
5,551,423 A	9/1996	Sugiura		5,895,359 A	4/1999 Peel
5,562,718 A	10/1996	Palermo		5,902,235 A	5/1999 Lewis et al.
5,564,108 A	10/1996	Hunsaker et al.		5,906,581 A	5/1999 Tsuda
5,564,417 A	10/1996	Chance		5,913,819 A	6/1999 Taylor et al.
5,584,296 A	12/1996	Cui et al.		5,916,154 A	6/1999 Hobbs et al.
5,592,408 A	1/1997	Keskin et al.		5,919,133 A	7/1999 Taylor et al.
				5,931,790 A	8/1999 Peel
				5,931,791 A	8/1999 Saltzstein et al.

5,934,925 A	8/1999	Tobler et al.	6,321,100 B1	11/2001	Parker
5,936,539 A	8/1999	Fuchs	6,322,516 B1	11/2001	Masuda et al.
5,947,905 A	9/1999	Hadjicostis et al.	6,343,223 B1	1/2002	Chin et al.
5,954,053 A	9/1999	Chance et al.	6,343,224 B1	1/2002	Parker
5,957,850 A	9/1999	Marian, Jr. et al.	6,346,886 B1	2/2002	De La Huerga
5,964,701 A	10/1999	Asada et al.	6,349,228 B1	2/2002	Kiani et al.
5,980,464 A	11/1999	Tsuda	6,356,774 B1	3/2002	Bernstein et al.
5,983,129 A	11/1999	Cowan et al.	6,362,622 B1	3/2002	Stauber et al.
5,987,343 A	11/1999	Kinast	6,368,282 B1	4/2002	Oka et al.
5,987,351 A	11/1999	Chance	6,370,411 B1	4/2002	Osadchy et al.
5,991,648 A	11/1999	Levin	6,377,829 B1	4/2002	Al-Ali
5,995,077 A	11/1999	Wilcox et al.	6,381,480 B1	4/2002	Stoddart et al.
5,995,855 A	11/1999	Kiani et al.	6,381,481 B1	4/2002	Levendowski et al.
5,995,856 A	11/1999	Mannheimer et al.	6,385,486 B1	5/2002	John et al.
5,995,857 A	11/1999	Toomim et al.	6,385,821 B1	5/2002	Modgil et al.
6,007,492 A	12/1999	Goto et al.	6,387,092 B1	5/2002	Burnside et al.
6,011,986 A	1/2000	Diab et al.	6,388,240 B2	5/2002	Schulz et al.
6,022,320 A	2/2000	Ogura et al.	6,397,091 B2	5/2002	Diab et al.
6,027,453 A	2/2000	Miwa et al.	6,405,075 B1	6/2002	Levin
6,030,351 A	2/2000	Schmidt et al.	6,416,471 B1	7/2002	Kumar et al.
6,031,603 A	2/2000	Fine et al.	6,416,474 B1	7/2002	Penner et al.
6,036,651 A	3/2000	Inuaki et al.	6,417,774 B1	7/2002	Hibbs et al.
6,041,247 A	3/2000	Weckstrom et al.	6,423,010 B1	7/2002	Friedman et al.
6,047,201 A	4/2000	Jackson	6,430,423 B2	8/2002	DeLonzor et al.
6,047,203 A	4/2000	Sackner et al.	6,432,050 B1	8/2002	Porat et al.
6,049,958 A	4/2000	Eberle et al.	6,450,168 B1	9/2002	Nguyen
6,050,951 A	4/2000	Friedman et al.	6,450,957 B1	9/2002	Yoshimi et al.
6,052,619 A	4/2000	John	6,450,981 B1	9/2002	Shabty et al.
6,073,038 A	6/2000	Wang et al.	6,454,708 B1	9/2002	Ferguson et al.
6,084,380 A	7/2000	Burton	6,461,305 B1	10/2002	Schnall
6,085,752 A	7/2000	Kehr et al.	6,463,310 B1	10/2002	Swedlow et al.
6,088,607 A	7/2000	Diab et al.	6,466,809 B1	10/2002	Riley
6,106,780 A	8/2000	Douglas et al.	6,468,241 B1	10/2002	Gelfand et al.
6,112,107 A	8/2000	Hannula	6,470,199 B1	10/2002	Kopotic et al.
6,115,621 A	9/2000	Chin	6,470,279 B1	10/2002	Samssoondar
6,118,382 A	9/2000	Hibbs et al.	6,480,762 B1	11/2002	Uchikubo et al.
6,134,459 A	10/2000	Roberts et al.	6,491,638 B2	12/2002	Oka
6,144,868 A	11/2000	Parker	6,491,639 B1	12/2002	Turcott
6,149,481 A	11/2000	Wang et al.	6,503,087 B1	1/2003	Eggert et al.
6,152,754 A	11/2000	Gerhardt et al.	6,503,204 B1	1/2003	Sumanaweera et al.
6,154,667 A	11/2000	Miura et al.	6,505,061 B2	1/2003	Larson
6,162,188 A	12/2000	Barnea	6,511,478 B1	1/2003	Burnside et al.
6,165,173 A	12/2000	Kamdar et al.	6,516,289 B2	2/2003	David
6,171,258 B1	1/2001	Karakasoglu et al.	6,519,487 B1	2/2003	Parker
6,173,196 B1	1/2001	Delonzor et al.	6,524,257 B2	2/2003	Ogura
6,179,786 B1	1/2001	Young	6,525,386 B1	2/2003	Mills et al.
6,181,959 B1	1/2001	Schollermann et al.	6,526,309 B1	2/2003	Chance
6,184,521 B1	2/2001	Coffin, IV et al.	6,526,970 B2	3/2003	DeVries et al.
6,186,953 B1	2/2001	Narimatsu	6,527,725 B1	3/2003	Inuaki et al.
6,186,954 B1	2/2001	Narimatsu	6,527,726 B2	3/2003	Goto et al.
6,190,325 B1	2/2001	Narimatsu	6,535,765 B1	3/2003	Amely-Velez et al.
6,196,974 B1	3/2001	Miwa	6,537,220 B1	3/2003	Friemel et al.
6,198,952 B1	3/2001	Miesel	6,541,756 B2	4/2003	Schulz et al.
6,199,550 B1	3/2001	Wiesmann et al.	6,542,081 B2	4/2003	Torch
6,209,144 B1	4/2001	Carter	6,547,742 B2	4/2003	Oka et al.
6,216,021 B1	4/2001	Franceschini et al.	6,547,743 B2	4/2003	Brydon
6,223,063 B1	4/2001	Chaiken et al.	6,551,252 B2	4/2003	Sackner et al.
6,241,680 B1	6/2001	Miwa	6,553,242 B1	4/2003	Sarussi
6,248,083 B1	6/2001	Smith et al.	6,575,902 B1	6/2003	Burton
6,251,076 B1	6/2001	Hovland et al.	6,575,904 B2	6/2003	Nagai et al.
6,251,080 B1	6/2001	Henkin et al.	6,580,086 B1	6/2003	Schulz et al.
6,251,081 B1	6/2001	Narimatsu	6,582,371 B2	6/2003	Miller
6,251,113 B1	6/2001	Appelbaum et al.	6,582,374 B2	6/2003	Yokozeki
6,256,523 B1	7/2001	Diab et al.	6,584,356 B2	6/2003	Wassmund et al.
6,256,524 B1	7/2001	Walker et al.	6,589,171 B2	7/2003	Keirsbilck
6,263,221 B1	7/2001	Chance et al.	6,589,183 B2	7/2003	Yokozeki
6,263,223 B1	7/2001	Shepherd et al.	6,589,189 B2	7/2003	Meyerson et al.
6,280,213 B1	8/2001	Tobler et al.	6,594,513 B1	7/2003	Jobsis et al.
6,282,450 B1	8/2001	Hartlaub et al.	6,597,933 B2	7/2003	Kiani et al.
6,283,922 B1	9/2001	Goto et al.	6,605,038 B1	8/2003	Teller et al.
6,285,895 B1	9/2001	Ristolainen et al.	6,606,993 B1	8/2003	Wiesmann et al.
6,306,076 B1	10/2001	Gill	6,611,793 B1	8/2003	Burnside et al.
6,308,089 B1	10/2001	von der Ruhr et al.	6,615,065 B1	9/2003	Barrett et al.

6,622,034 B1	9/2003	Gorski et al.	2003/0120183 A1	6/2003	Simmons
6,635,048 B1	10/2003	Ullestad et al.	2003/0122706 A1	7/2003	Choi et al.
6,640,116 B2	10/2003	Diab	2003/0125616 A1	7/2003	Black et al.
6,645,154 B2	11/2003	Oka	2003/0135127 A1	7/2003	Sackner et al.
6,645,155 B2	11/2003	Inuaki et al.	2003/0144579 A1	7/2003	Buss
6,653,557 B2	11/2003	Wolf et al.	2003/0156288 A1	8/2003	Barnum et al.
6,654,622 B1	11/2003	Eberhard et al.	2003/0176810 A1	9/2003	Maahs et al.
6,662,033 B2	12/2003	Casciani et al.	2003/0189492 A1	10/2003	Harvie
6,666,860 B1	12/2003	Takahashi	2003/0216728 A1	11/2003	Stern et al.
6,671,531 B2	12/2003	Al-Ali et al.	2003/0225323 A1	12/2003	Kiani et al.
6,671,545 B2	12/2003	Fincke	2004/0002655 A1	1/2004	Bolorforosh et al.
6,678,543 B2	1/2004	Diab et al.	2004/0007585 A1	1/2004	Griffith et al.
6,681,454 B2	1/2004	Modgil et al.	2004/0030258 A1	2/2004	Williams et al.
6,684,091 B2	1/2004	Parker	2004/0044545 A1	3/2004	Wiesmann et al.
6,704,601 B1	3/2004	Amely-Velez et al.	2004/0117891 A1	6/2004	Hannula et al.
6,736,759 B1	5/2004	Stubbs et al.	2004/0163648 A1	8/2004	Burton
6,748,254 B2	6/2004	O'Neil et al.	2005/0027207 A1	2/2005	Westbrook et al.
6,811,538 B2	11/2004	Westbrook et al.	2005/0059869 A1	3/2005	Scharf et al.
6,934,570 B2	8/2005	Kiani et al.	2005/0070776 A1	3/2005	Mannheimer et al.
6,934,571 B2	8/2005	Wiesmann et al.	2005/0113656 A1	5/2005	Chance
6,985,763 B2	1/2006	Boas et al.	2005/0188991 A1	9/2005	Sun et al.
7,001,334 B2	2/2006	Reed et al.	2005/0261594 A1	11/2005	Banet
7,027,850 B2	4/2006	Wasserman	2005/0277819 A1	12/2005	Kiani et al.
7,047,054 B2	5/2006	Benni	2006/0195026 A1	8/2006	Casciani et al.
7,047,055 B2	5/2006	Boas et al.	2006/0195027 A1	8/2006	Casciani et al.
7,054,453 B2	5/2006	Causevic et al.	2006/0211929 A1	9/2006	Casciani et al.
7,054,454 B2	5/2006	Causevic et al.	2006/0217604 A1	9/2006	Fein et al.
7,072,704 B2	7/2006	Bucholz	2006/0217605 A1	9/2006	Fein et al.
7,085,597 B2	8/2006	Fein et al.	2006/0217606 A1	9/2006	Fein et al.
7,113,815 B2	9/2006	O'Neil et al.	2006/0217607 A1	9/2006	Fein et al.
7,132,641 B2	11/2006	Schulz et al.	2006/0217608 A1	9/2006	Fein et al.
7,171,251 B2	1/2007	Sarussi et al.	2006/0229510 A1	10/2006	Fein et al.
7,181,264 B2	2/2007	Wiesmann et al.	2006/0229511 A1	10/2006	Fein et al.
7,190,999 B2	3/2007	Geheb et al.	2006/0264726 A1	11/2006	Mannheimer et al.
7,204,250 B1	4/2007	Burton	2006/0264727 A1	11/2006	Mannheimer et al.
7,220,220 B2	5/2007	Stubbs et al.	2006/0276700 A1	12/2006	O'Neil et al.
7,231,240 B2	6/2007	Eda et al.	2006/0281984 A1	12/2006	Mannheimer et al.
7,245,953 B1	7/2007	Parker	2007/0032732 A1	2/2007	Shelley et al.
7,248,910 B2	7/2007	Li et al.	2007/0149871 A1	6/2007	Sarussi et al.
7,289,837 B2	10/2007	Mannheimer et al.	2007/0293746 A1	12/2007	Sarussi et al.
7,297,119 B2	11/2007	Westbrook et al.	2008/0009691 A1	1/2008	Parker
7,305,262 B2	12/2007	Brodnick et al.	2008/0045822 A1	2/2008	Phillips et al.
7,313,427 B2	12/2007	Benni	2008/0076988 A1	3/2008	Sarussi et al.
7,349,726 B2	3/2008	Casciani et al.	2008/0076990 A1	3/2008	Sarussi et al.
7,367,949 B2	5/2008	Korhonen et al.			
7,376,454 B2	5/2008	Casciani et al.			
7,415,298 B2	8/2008	Casciani et al.			
2001/0000790 A1	5/2001	DeLonzor et al.	DE 3705493	8/1988	
2001/0009398 A1	7/2001	Sekura et al.	DE 3744781	1/1989	
2002/0013538 A1	1/2002	Teller	DE 3810411	10/1989	
2002/0042558 A1	4/2002	Mendelson	DE 3927038	2/1991	
2002/0052539 A1	5/2002	Haller et al.	DE 4429845	10/1995	
2002/0084904 A1	7/2002	De La Huerga	DE 29515877 U1	11/1995	
2002/0091335 A1	7/2002	John et al.	DE 19541605	5/1997	
2002/0095092 A1	7/2002	Kondo et al.	DE 19939302	5/2001	
2002/0103445 A1	8/2002	Rahdert et al.	DE 10029205	1/2002	
2002/0109600 A1	8/2002	Mault et al.	EP 268850	6/1988	
2002/0124295 A1	9/2002	Fenwick et al.	EP 0313238	4/1989	
2002/0139368 A1	10/2002	Bashinski	EP 338518	10/1989	
2002/0148470 A1	10/2002	Blue et al.	EP 463620	1/1992	
2002/0151929 A1	10/2002	Goto et al.	EP 543172	5/1993	
2002/0156354 A1	10/2002	Larson	EP 0572684	12/1993	
2002/0161309 A1	10/2002	Marro	EP 0573137	12/1993	
2002/0173706 A1	11/2002	Takatani et al.	EP 578530	1/1994	
2002/0173708 A1	11/2002	DeLonzor et al.	EP 580385	1/1994	
2003/0004547 A1	1/2003	Owens et al.	EP 775311	8/1994	
2003/0009119 A1	1/2003	Kamm et al.	EP 621026	10/1994	
2003/0009308 A1	1/2003	Kirtley	EP 0631756	1/1995	
2003/0018243 A1	1/2003	Gerhardt et al.	EP 0631756 A1	1/1995	
2003/0023140 A1	1/2003	Chance	EP 665025	8/1995	
2003/0036685 A1	2/2003	Goodman	EP 0695139	2/1996	
2003/0065275 A1	4/2003	Mault et al.	EP 0721110	7/1996	
2003/0086156 A1	5/2003	McGuire	EP 1048323	2/2000	

FOREIGN PATENT DOCUMENTS

US 7,698,909 B2

Page 5

EP	996063	4/2000
EP	1130412	5/2001
EP	1169965	1/2002
EP	1547515	6/2005
FR	2555744	11/1983
FR	2601137	1/1988
GB	2135074	8/1984
GB	834 469	5/1992
GB	2390903	1/2004
JP	55024614	2/1980
JP	04057161	2/1992
JP	07336597	12/1995
JP	08111295	4/1996
JP	08112257	5/1996
JP	08336546	12/1996
JP	09010319	1/1997
JP	09154937	6/1997
JP	10314149	12/1998
JP	11259583	9/1999
JP	2000/189440	7/2000
JP	2001/161648	6/2001
JP	2001/190498	7/2001
JP	2001/308576	11/2001
JP	2001/332832	11/2001
JP	2001/346775	12/2001
JP	2002/065647	3/2002
JP	2003/210402	7/2003
JP	2003/235813	8/2003
JP	2003/265425	9/2003
JP	2004/016659	1/2004
JP	2004/065832	3/2004
RU	2132204	6/1999
WO	WO9001293	2/1990
WO	WO9111137	8/1991
WO	WO 9115151	10/1991

WO	WO 9118550	12/1991
WO	WO 9220273	11/1992
WO	WO 95/06430	3/1995
WO	WO9512349	5/1995
WO	WO 9615714	5/1996
WO	WO 9616591	6/1996
WO	WO 9641138	12/1996
WO	WO 9720494	6/1997
WO	WO 9720497	6/1997
WO	WO9817174	4/1998
WO	WO9947039	9/1999
WO	WO 9963883	12/1999
WO	WO0059374	10/2000
WO	WO 00/78209	12/2000
WO	WO 01/01855	1/2001
WO	WO 01/17425	3/2001
WO	WO0176471	10/2001
WO	WO 01/87224	11/2001
WO	WO 02/15784	2/2002
WO	WO 02/065901	8/2002
WO	WO 02066977	8/2002
WO	WO 02/089664	11/2002
WO	WO 03/026558	4/2003
WO	WO 03/057030	7/2003
WO	WO03071928	9/2003
WO	WO 03080152	10/2003
WO	WO2005010568	2/2005

OTHER PUBLICATIONS

Letter dated May 13, 2003 to Howard Alhanati (Custom Fab Inc.) from Joe Coakley (TYCO Healthcare Nellcor); 1p.
Nellcor Puritan Bennett "Specification, Headband, Posey, Maxfast" Apr. 4, 2002; 1p.

* cited by examiner




FIG. 1




FIG. 2




FIG. 3




FIG. 4A







FIG. 4






FIG. 8











FIG. 9






FIG. 11

HEADBAND WITH TENSION INDICATOR**BACKGROUND OF THE INVENTION**

The present invention relates to headbands, and in particular to headbands that have a tension indicator for indicating when a headband is appropriately stretched and is thus capable of imparting an appropriate level of pressure to a wearer's head.

Various headband devices are known. These include athletic type headband devices as well as more sophisticated headband devices, such as those used to mount devices carried on the head. Some headband devices are used to apply a certain level of pressure to the region under the headband. Such applied pressures are useful, for example, to support a medical sensor for the wearer of the headband. In such circumstances, there is a need for an improved headband having a tension indicator.

BRIEF SUMMARY OF THE INVENTION

Embodiments of the present invention are directed to a headband device. In one embodiment, the present invention provides a headband having a low stretch segment sized to fit around a wearer's head; and an elastic segment being smaller than the low stretch segment. The elastic segment has a free end and an attached end, where the elastic segment is attached at its attached end with the low stretch segment, and the free end of the elastic segment is configured to form a closed loop with the low stretch segment around a wearer's head.

In one aspect, the headband also includes a visual indicator that is configured for monitoring the extended position of the free end of the elastic segment. The visual indicator can be a notch, a line or a marking on the low stretch segment.

In one aspect, the headband also includes a stop portion, where the stop portion is configured to engage against the elastic segment to limit the stretch of the elastic segment. In one embodiment, the stop portion has an opening having a width that is smaller than the width of the low stretch segment and the width of the elastic segment.

In another aspect, the headband also includes a closure mechanism configured to couple the free end of the elastic portion with the low stretch segment to secure the closed loop. The closure mechanism can be a hook and loop closure, a snap, a button, an adhesive, a pin, or combinations thereof.

In another aspect, the headband also includes a tab portion having a first end and a second end, where the first end of the tab portion is connected with the free end of the elastic portion, and the second end of the tab portion is configured to form a closed loop with the low stretch segment.

In one aspect, the tab portion is less elastic than the elastic portion.

In another aspect, the headband also includes a stop portion, where the stop portion is configured to engage against the elastic segment to limit the stretch of the elastic segment. The tab portion also includes an indicator portion between its first end and the stop portion such that the indicator portion when visible indicates that the headband needs re-tightening; and when the indicator portion is not visible it indicates an adequate level of tension corresponding with delivering a pressure in the range higher than the venous pressure and lower than the capillary pressure to the forehead of the wearer.

In another aspect, the present invention provides a headband for applying pressure to an oximetry sensor on the forehead of a patient. The headband includes a low stretch segment sized to fit around a patient's head, and an elastic segment being smaller than the low stretch segment. The

elastic segment has a free end and an attached end, where the elastic segment is attached at its attached end with the low stretch segment. The headband also includes a tab portion having a first end and a second end, where the first end of the tab portion is connected with the free end of the elastic portion, and the second end of the tab portion is configured to form a closed loop with the low stretch segment around a patient's head. The headband also includes a visual indicator that is configured to show the extended position for the elastic segment. The headband also includes a stop portion, where the stop portion is configured to engage against the elastic segment to limit the stretch of the elastic segment. The stop portion has an opening having a width that is smaller than the width of the low stretch segment and the width of the elastic segment. The headband also has a closure mechanism configured to couple the second end of the tab portion with the low stretch segment to secure the closed loop.

In one aspect, the tab portion includes an indicator portion between its first end and the stop portion such that the indicator portion when visible indicates that the headband needs re-tightening; and when the indicator portion is not visible it indicates an adequate level of tension corresponding with delivering a pressure in the range higher than the venous pressure and lower than the capillary pressure to the forehead of the patient.

In another aspect, the indicator is a notch, a line or a marking on the low stretch segment.

For a further understanding of the nature and advantages of the invention, reference should be made to the following description taken in conjunction with the accompanying drawings.

BRIEF DESCRIPTION OF THE DRAWINGS

FIG. 1 is a diagram of a forehead oximetry sensor being applied to a patient.

FIG. 2 is a diagram of a forehead oximetry sensor being held to a patient's forehead with a headband.

FIG. 3 is a diagram of one embodiment of the headband in accordance with the present invention.

FIG. 4 is a diagram of an alternate embodiment of the headband in accordance with the present invention.

FIG. 4A is a top view detail diagram of the crease or fold of FIG. 4.

FIG. 5 is a front view diagram of an embodiment of the headband in accordance with the present invention shown worn by a user.

FIG. 6 is a top view diagram of an embodiment of the headband in accordance with the present invention shown in proper tension when worn by a user.

FIG. 7 is a top view diagram of an embodiment of the headband in accordance with the present invention shown in less than proper tension when worn by a user.

FIG. 8 is a diagram of an alternate embodiment of the headband in accordance with the present invention.

FIG. 9 is a diagram of an alternate embodiment of the headband in accordance with the present invention.

FIG. 10A-E are diagrams showing the method of placing the headband of FIG. 9 on a patient's head.

FIG. 11 is a top view diagram of the headband of FIG. 9 when placed on a patient's head.

DETAILED DESCRIPTION OF THE INVENTION

The embodiments of the present invention are directed towards a headband with a tension indicator. Such a headband may be used to support the administration of a health care

related service to a patient. Such a service may include the placement of a sensor **101** on a patient's forehead, such as for example, an oximetry sensor (e.g., those manufactured by Nellcor Puritan Bennett, the assignee herein), as is shown in FIG. 1. A typical pulse oximeter measures two physiological parameters, percent oxygen saturation of arterial blood hemoglobin (SpO₂ or sat) and pulse rate. Oxygen saturation can be estimated using various techniques. In one common technique, the photocurrent generated by the photo-detector is conditioned and processed to determine the ratio of modulation ratios (ratio of ratios) of the red to infrared signals. This modulation ratio has been observed to correlate well to arterial oxygen saturation. The pulse oximeters and sensors are empirically calibrated by measuring the modulation ratio over a range of in vivo measured arterial oxygen saturations (SaO₂) on a set of patients, healthy volunteers, or animals. The observed correlation is used in an inverse manner to estimate blood oxygen saturation (SpO₂) based on the measured value of modulation ratios of a patient. The estimation of oxygen saturation using modulation ratios is described in U.S. Pat. No. 5,853,364, entitled "METHOD AND APPARATUS FOR ESTIMATING PHYSIOLOGICAL PARAMETERS USING MODEL-BASED ADAPTIVE FILTERING", issued Dec. 29, 1998, and U.S. Pat. No. 4,911,167, entitled "METHOD AND APPARATUS FOR DETECTING OPTICAL PULSES", issued Mar. 27, 1990, and the relationship between oxygen saturation and modulation ratio is further described in U.S. Pat. No. 5,645,059, entitled "MEDICAL SENSOR WITH MODULATED ENCODING SCHEME," issued Jul. 8, 1997, the disclosures of which are herein incorporated by reference in their entirety. Most pulse oximeters extract the plethysmographic signal having first determined saturation or pulse rate. An exemplary forehead oximetry sensor is described in a co-pending U.S. patent application Ser. No. 10/256,245, entitled: "Stacked Adhesive Optical Sensor," the disclosure of which is herein incorporated by reference in its entirety for all purposes.

The force applied to the oximetry sensor can be a factor in the proper functioning of the sensor. In certain clinical scenarios, a headband **200** is required to be used in conjunction with a forehead sensor **101** (e.g., an oximetry sensor), as is shown in FIG. 2. FIG. 2 shows the sensor leads extending from the sensor (not shown) outward from beneath the headband. Such clinical scenarios include scenarios where: patient is lying down with his/her head near or below chest level; patient is subject to elevated venous pressure; patient is diaphoretic; patient is moving excessively, such as during exercise; as well as other scenarios where venous pulsations can introduce errors in oximetry calculations. In those scenarios, without a headband, or force on the oximetry sensor, venous pulsations could cause an incorrect interpretation of the waveform, and therefore result in a less than accurate determination of the oxygen saturation and pulse rate values. The headband can be used to apply pressure to the oximetry sensor, thus reducing the effects of venous pulsations. When used to support an oximetry sensor, the amount of force applied by the sensor on the forehead should be greater than the venous pressure, but less than the arteriole pressure. Generally, a good pressure range is one where the applied pressure is higher than venous pressure (e.g., 3-5 mm Hg) and lower than the capillary pressure (e.g., 22 mm Hg). Preferably, this is between 10 mm Hg and 20 mm Hg in the adult patient. The headband in accordance with the embodiments of the present invention may be adjusted for use with any size wearer by using an adjustable closure mechanism, such as for example a hook and loop closure mechanism. Alternately, the headband may be provided in varying sizes, depending on the

general size of the wearer's head; for example using a small headband for a neonate, a larger one for a child and an even larger one for an adult wearer. The user can apply a wide range of pressures to the forehead oximetry sensor depending on the amount of tension which has been applied to the headband during its placement around the wearer's head.

The embodiments of the present invention are intended to alleviate the guesswork by the caregivers by giving them a visual indicator of the proper amount of tension required in the headband during placement around the head. The required tension is related to the pressure being applied by the sensor when it is attached with the patient.

In one embodiment, shown in FIG. 3, an elastic headband **102** is shown in an unstretched position. A non-elastic fabric **104** is shown attached to the elastics portion **102** along two of its edges **106**. The other two edges of the non-elastic portion are not attached to the elastic segment and are thus free to project outward away from the face of the elastic segment. The non-elastic segment is smaller the elastic segment. The non-elastic segment is sized to span a portion of the elastic segment when the elastic segment is stretched. The non-elastic segment is larger than the portion of the elastic segment it spans when the elastic segment is not stretched. As the elastic segment **102** is stretched from its non-stretched position, the non-elastic portion is pulled at its edges **106** along with the stretching elastic segment **102** until the elastic portion between the edges has stretched to a length equal to the length of the non-elastic portion. The headband also includes closure mechanisms (not shown), which are described below in conjunction with FIG. 4. FIG. 5 shows a front view diagram of an embodiment of the headband in accordance with the present invention shown worn by a user. It is noted that the headband may be used to hold and impart a pressure against a sensor, such as an oximetry sensor applied to a patient's forehead, as shown in FIG. 2. For clarity in describing the tension indicator, such a sensor is not shown in FIGS. 5-7. FIG. 6 is a top view diagram of an embodiment of the headband **102** in accordance with the present invention shown in proper tension when worn by a user. As is shown in this figure, when the headband is properly tightened, the pressure indicator portion **104** is pulled tight across the elastic portion **102**, thus not providing a visual indication that the headband needs to be retightened. On the other hand, FIG. 7 shows a top view diagram of an embodiment of the headband in accordance with the present invention shown in less than proper tension when worn by a user. As is shown in FIG. 7, when a less than adequate pressure is being applied by the headband to a user's forehead, or when the headband is not tight enough, the indicator **104** projects out from the surface creating a loop which provides a visual cue that the headband needs retightening.

When the headband is not stretched there is an amount of slack between the non-elastic and elastic portions. When the headband is stretched, the slack in the non-elastic strap is eliminated, giving the visual indication that the headband stretch is sufficient. The headband is chosen to be long enough to fit around the head of a user (or patient). The elastic material may be made of any suitable fabric, such as an open cell urethane foam. The non-elastic fabric, which is shorter than the elastic portion is sewn or attached otherwise (e.g., adhesively, etc.) onto the elastic headband at a spacing that is less than the lengths of the non-elastic portion. The non-elastic material may be made of any suitable fabric, such as a Dacron-type fabric.

FIG. 4 is a diagram of an alternate embodiment of the headband in accordance with the present invention. An elastic headband **102** is shown in an unstretched position. A non-

elastic fabric **104** is shown attached to the elastics portion **102** along two of its edges **106**. The other two edges of the non-elastic portion are not attached to the elastic segment and are thus free to project outward away from the face of the elastic segment. The non-elastic segment **104** is smaller than the elastic segment **102**. The non-elastic segment is sized to span a portion of the elastic segment when the elastic segment is stretched. The non-elastic segment is larger than the portion of the elastic segment it spans when the elastic segment is not stretched. As the elastic segment **102** is stretched from its non-stretched position, the non-elastic portion is pulled at its edges **106** along with the stretching elastic segment **102** until the elastic portion between the edges has stretched to a length equal to the length of the non-elastic portion.

FIG. 4 also shows the non-elastic portion to include a permanent crease or a fold **110**. As shown in FIG. 4A, such a fold **110** may be made by overlapping the non-elastic portion to form a fold and then heat pressing or heat sealing the fabric to form a permanent fold or crease. In one embodiment, the fold or crease is made in the middle of the inelastic segment, which causes it to project outward in a sharp, angular fashion as the elastic band **102** retracts or relaxes. In operation, it has been shown that the sharp, angular crease or fold acts as a mechanical amplifier and provides a more distinct visual cue and better sensitivity as to when the threshold of minimal headband tension has been passed. The creased tension indicator **110** exhibits increased sensitivity to a loss in headband tension by projecting further away from the elastic band in a skewed fashion. The creased tension indicator **110** provides a more pronounced visual cue both from the perspective of looking directly at the forehead and from looking down at the top (edge) of the headband. The material chosen for the inelastic portion having a fold or a crease can be similar to the noncreased or nonfolded inelastic material. In addition, a material such as a polyester webbing material, which is capable of holding a fold or a crease, may also be used. The elastic material may be made of a material as is described above, or made using other suitable material such as a terry band.

When the headband is not stretched there is an amount of slack between the non-elastic and elastic portions. When the headband is stretched, the slack in the non-elastic strap is eliminated, giving the visual indication that the headband stretch is sufficient.

Also shown in FIG. 4, and applicable to the embodiment described in conjunction with FIG. 3, is the closure device **108**. One such closure device is a hook and loop type closure. The headband in accordance with the embodiments of the present invention may use other closure mechanisms such as snaps, buttons, adhesives, pins, or combinations thereof, as well as others known to those of skill in the relevant arts. Alternately, the headband may be a pre-formed loop, without a separate closure mechanism.

The headband described above includes a sensor attachment pressure indicator. As described above, the headband may be used to allow a sensor's attachment pressure with the patient's tissue location (e.g. forehead, and so on) to be chosen which is greater than venous pulsations (e.g., 5-10 mm Hg) but less than a maximum amount (e.g., 30 mm Hg, or so). As described above, such a pressure indicator is attached with the headband. Alternately, the pressure indicator may be attached with the sensor, such as an oximetry sensor. One embodiment of the pressure indicator is a tension indicator as described above with reference to FIGS. 3-4. Other pressure indicating means include pressure or force sensors small and light enough to be included with either the sensor or the headband assembly.

The information provided by the pressure indicator may be used to help establish an acceptable windows of pressure for the sensor's attachment with a patient. The acceptable window of pressure may also be enhanced to include the affects of the patient's head elevation relative to the patient's heart.

Additionally, the concept of using a headband to ensure an acceptable sensor attachment pressure is extendible to other patient body locations; locations where a sensor attachment pressure can help provide a more accurate sensor reading.

An alternate embodiment of the tension or pressure indicating headband in accordance with the present invention is shown in FIG. 8. As is shown in FIG. 8, the headband includes an inelastic portion **604** and an elastic portion **602**. The tension indicating portion **606** is also made of an inelastic material. The tension indicating portion **606** may be a creased or folded as described in conjunction with FIG. 4 or as is shown uncreased or unfolded as described in conjunction with FIG. 3. The description of the closure devices and how the elastic and inelastic portions are attached to one another are also set forth above. In this embodiment, the main stretchable portion is elastic portion **602**. Once the headband has been stretched such that section **602** is stretched to match the length of section **606**, the headband's stretch will be limited. This embodiment by having a shorter elastic portion limits the extension of the headband and hence limits the range of pressures that can be applied by the headband against a user's forehead or the sensor applied to a user's forehead.

FIG. 9 is an exemplary diagram of an alternate embodiment of the headband in accordance with the present invention. The headband may be used for the purpose of applying a small, controlled amount of pressure against the forehead of its wearer. As set forth above, when used to support an oximetry sensor, the amount of force applied by the sensor on the forehead should be greater than the venous pressure, but less than the arteriole pressure. Generally, a good pressure range is one where the applied pressure is higher than venous pressure (e.g., 3-5 mm Hg) and lower than the capillary pressure (e.g., 22 mm Hg). Preferably, this is between 10 mm Hg and 20 mm Hg in the adult patient. The headband in accordance with the embodiments of the present invention may be adjusted for use with any size wearer by using an adjustable closure mechanism, such as for example a hook and loop closure mechanism. Alternately, the headband may be provided in varying sizes, depending on the general size of the wearer's head; for example using a small headband for a neonate, a larger one for a child and an even larger one for an adult wearer. The user can apply a wide range of pressures to the forehead oximetry sensor depending on the amount of tension which has been applied to the headband during its placement around the wearer's head. In one embodiment, the different head sizes of the wearer's are accommodated by providing a suite of different sized headbands; starting with the smallest and graduating to larger sized ones; all having common features as described herein. In another embodiment, a hook and loop type closure device is configured such that the entire back side of the low stretch band (described below) is capable of engaging an end of the headband having the mating hook and loop surface. In this manner, a one size headband is enabled to accommodate any size head. Further details are described below.

The embodiment shown in FIG. 9 enables a clinician to accurately and consistently apply the headband with the proper tension in an intuitive manner as described below. As shown in FIG. 9, the headband includes a substantially inelastic, or low stretch band **202** having a closure device **208** on or near its end and preferably on a portion of or the entire outer surface thereof. One such closure device is a hook and loop

type closure. The headband in accordance with the embodiments of the present invention may use other closure mechanisms such as snaps, buttons, adhesives, pins, or combinations thereof, as well as others known to those of skill in the relevant arts. The inelastic or low stretch band **202** can be made of any type of low-stretch fabric, such as a Nylon, polyester or equivalent materials, including those described above.

The headband also includes an elastic segment **204** of a specific length, to provide a specific spring force once stretched, attached at one end **203** to the outer facing side of the low stretch material (i.e. band **202**) that wraps around the patient's head. The attachment of the elastic segment **204** to band **202** at **203** may be achieved by sewing the segment **204** at **203** to **202**. Alternately, the segment **204** may be adhesively attached to band **202** at **203**. At the other, free end, **205** the elastic segment **204** is configured to be attached with a segment of band **202** using a closure device **208**, as described above (e.g., inelastic material that has a patch of Velcro™ hook material). In one embodiment, the free end **205** of the elastic segment is attached with a low stretch portion or tab **206**, which attaches with a segment of band **202** using a closure device **208** to form a closable loop. The band **206** slips through slots in the band **202** at the stop **207**, in a manner similar to a belt through a loop. To apply a proper tension, and hence a proper amount of pressure against the skin, to the low stretch material band **202** wrapped around the head, the elastic segment **204** is stretched a controlled distance, and then fastened to the low stretch strip **202** using the closure device **208**. The stretch of the elastic segment **204** is controlled, as it meets a physical stop. In one embodiment, the physical stop is provided by having the width of the elastic portion **204** sized slightly larger than the opening of the stop **207** in the band **202**, and thus once stretched a certain distance, the elastic portion **204** meets a physical stop **207**. The stop **207** may be an opening in the band **202** that is slightly smaller in width than the elastic portion **204**. Alternately, the stop may be provided by a narrow band similar in shape and function to a belt loop that is sewn on or attached with the band **202**. By stretching and fastening the elastic portion **204** with the band **202**, the tension in the elastic segment **204** is transferred to the entire low stretch strip that is wrapped around the patient's head. This controlled tension, in turn, translates into a controllable pressure against the patient's forehead skin. In other words, proper tension in the band and hence proper pressure against the forehead of the patient is achieved by wrapping the band **202** around a patient's head; then pulling on the elastic segment directly or via a pulling force on the member **206** to extend the elastic segment **204** until its edge **210** meets the stop **207**, and then securing the free end of segment **206** against the band **202** using the closure device **208**.

The headband also includes a visual indicator that is used to monitor the stretch of the elastic portion **204**. In one embodiment, the tab **206** includes a visible or indicator portion **211** between the free end of the elastic portion **205** and the stop **207**, such that when the headband is properly tensioned, the elastic portion **204** is stretched and thus portion **211** is no longer visible, as the elastic portion **204** abuts against the stop **207**. Alternately, headband includes visual indicator **212** (shown in FIG. 10D' and 10D''), that enable the visual monitoring of the edge of the free end of the elastic segment **204** against the indicator **212**, as the segment **204** is stretched. While the indicator **212** is shown as a notch, it can be a line, or any other suitable marker. The headband described herein provides structures that monitor and/or control the stretch of the elastic segment **204**. The stretch of the elastic segment is controlled by the stop **207**. The stop **207** ensures that the elastic segment's stretch is limited, as describe above. For example, a clinician is prevented from over stretching the elastic segment, since the free edge of the elastic segment will

meet against the stop **207** once it is fully stretched. The visual indicator **211** or **212** enable the monitoring of the amount of the stretch of the elastic segment. In addition, the adequacy of the tension or stretch of the segment is monitored visually by observing either the indicator **211** or the position of the free edge of the segment against the indicator **212**. So, for example, once the headband has been properly applied, it is expected that the headband or portions thereof may relax and in which case the visual indicators will show that the headband needs re-tensioning.

FIGS. 10A-E are diagrams showing the method of placing the headband of FIG. 9 on a patient's head. For ease of description, it is assumed that the patient or headband wearer is lying down on his (or her) back on a surface and facing up. As shown in FIG. 10A, first the headband is placed under the patient's head with the elastic segment side facing down and on the same side as that of a forehead oximetry sensor **300**. For ease of placement, it is preferred to allow the length of the band to extend more on the elastic segment side. Next, as shown in FIG. 10B, the shorter end is rolled towards the patient's forehead. Next, as shown in FIG. 10C, the elastic segment side is rolled over the patient's forehead covering the sensor **300**. It may be preferable to provide a sensor design outline on the elastic portion of the headband, in which case it is preferred to align the sensor outline on the elastic band portion of the forehead sensor approximately with the sensor **300**. Next, as shown in FIG. 10D, the tab **206** is pulled until the elastic portion **204** reaches the stop **207** and indicator or visible portion **211** of the band is no longer visible. Note that the tab **206** has a portion **211** (e.g., indicator portion) that is partially visible between the elastic portion **204** and the stop **207** in FIG. 10C, when the band is not adequately stretched, and the same tab portion **211** (e.g., indicator portion) is no longer visible between the elastic portion **204** and stop **207** when the elastic portion is adequately stretched, as shown in FIGS. 10D and 10E. Alternately, as shown in FIGS. 10D'-D'', after the elastic segment side is rolled over the patient's forehead covering the sensor **300**, the tab **206** is pulled until the elastic segment **204** reaches the position mark or indicator **212**. An adequately stretched headband is enabled to impart an adequate tension in the headband and hence an adequate pressure against the forehead and the sensor that is placed between the forehead and the headband. Therefore, when there is no tab portion **211** visible between the elastic portion **204** and the stop **207**, or when the elastic segment is properly aligned with the indicator **212**, or when the elastic portion has been adequately stretched against its stop, the clinician has an indicator that a proper pressure is being applied to the wearer's forehead.

FIG. 11 is a top view diagram of the headband of FIG. 9 when placed on a patient's head with an adequate tension. As can be seen, band **202** is wrapped around the patient's head, elastic portion **204** is adequately stretched and fastened with the band **202** via tab portion **206**.

As will be understood by those skilled in the art, the present invention may be embodied in other specific forms without departing from the essential characteristics thereof. These other embodiments are intended to be included within the scope of the present invention, which is set forth in the following claims.

What is claimed is:

1. A headband for applying pressure to an oximetry sensor on the forehead of a patient, comprising:

- a low stretch segment sized to fit around a patient's head;
- an elastic segment being smaller than the low stretch segment, the elastic segment having a free end and an attached end, the elastic segment being attached at the attached end with the low stretch segment;

a tab portion having a first end and a second end, the first end of the tab portion being connected to the free end of the elastic portion, the second end of the tab portion configured to form a closed loop with the low stretch segment around a patient's head;

a visual indicator configured for monitoring the extended position of the free end of the elastic segment;

a stop portion configured to engage against the elastic segment to limit the stretch of the elastic segment, the stop portion comprising an opening having a width that is smaller than the width of the low stretch segment and the width of the elastic segment; and

a closure mechanism configured to couple the second end of the tab portion with the low stretch segment to secure the closed loop.

2. The headband of claim 1 wherein the visual indicator is on the tab portion between its first end and the stop portion such that the indicator portion when visible indicates that the headband needs re-tightening; and when the indicator portion is not visible it indicates an adequate level of tension corresponding with delivering a pressure in the range higher than the venous pressure and lower than the capillary pressure to the forehead of the patient.

3. The headband of claim 1 wherein the visual indicator comprises a notch, a line, a marking, or a combination thereof on the low stretch segment.

4. The headband of claim 1 wherein the closure mechanism is a hook and loop closure, a snap, a button, an adhesive, or a pin, or a combination thereof.

5. A headband, comprising:

a low stretch segment sized to fit around a wearer's head; an elastic segment being smaller than the low stretch segment, the elastic segment having a free end and an attached end, the elastic segment being attached at the attached end with the low stretch segment;

a tab portion having a first end and a second end, the first end of the tab portion being connected with the free end of the elastic portion, the second end of the tab portion configured to form a closed loop with the low stretch segment; and

a stop portion configured to engage against the elastic segment to limit the stretch of the elastic segment, wherein the tab portion comprises an indicator portion between the free end of the elastic portion and the stop portion, such that the indicator portion, when visible, indicates that the headband needs re-tightening; and when the indicator portion is not visible it indicates an adequate level of tension corresponding with delivering a pressure in a range higher than venous pressure and lower than capillary pressure to the wearer's head.

6. A headband, comprising:

a low stretch segment sized to fit around a wearer's head; an elastic segment being smaller than the low stretch segment, the elastic segment having a free end and an attached end, the elastic segment being attached at the attached end with the low stretch segment;

a tab portion having a first end and a second end, the first end of the tab portion being connected with the free end of the elastic portion, the second end of the tab portion configured to form a closed loop with the low stretch segment;

an indicator configured to indicate whether the headband is applying pressure in a given range when the headband is around the wearer's head, wherein the indicator comprises a marker associated with the free end of the elastic segment, such that pulling the tab outwardly along the headband moves the free end of the elastic segment

relative to the marker to indicate whether the headband is delivering a level of tension corresponding to a pressure in a range higher than venous pressure and lower than capillary pressure to the wearer's head.

7. A headband, comprising:

a low stretch segment sized to fit around a wearer's head; an elastic segment being smaller than the low stretch segment, the elastic segment having a free end and an attached end, the elastic segment being attached at the attached end with the low stretch segment, the free end of the elastic segment configured to form a closed loop with the low stretch segment around a wearer's head; and

a sensor configured to be placed on a wearer's head and to be forced against the wearer's head via pressure from the headband.

8. The headband of claim 7, comprising a pressure sensor coupled to the sensor or to the headband.

9. The headband of claim 8, wherein the pressure sensor is visible from a side of the headband not in contact with the wearer's head.

10. The headband of claim 1, comprising a sensor configured to be placed on the patient's head and to be forced against the patient's head via pressure from the headband.

11. The headband of claim 10, comprising a pressure sensor coupled to the sensor or to the headband.

12. The headband of claim 11, wherein the pressure sensor is visible from a side of the headband not in contact with the patient's head.

13. A headband at least long enough to encircle a wearer's head, comprising:

a substantially inelastic band having a first end portion and a second end portion;

an elastic band having a first end and a second end, wherein the first end of the elastic band is attached to the substantially inelastic band;

a tab having a first end and a second end, wherein the first end of the tab is attached to the second end of the elastic band, and the second end of the tab is configured to extend outwardly from the second end portion of the substantially inelastic band and to couple to the first end portion of the substantially inelastic band;

a visual indicator configured to indicate a position of the second end of the elastic band;

a sensor configured to be placed on the wearer's head and to be forced against the wearer's head via pressure from the headband; and

a pressure sensor coupled to the sensor or to the headband.

14. The headband of claim 13, wherein the pressure sensor is visible from a side of the headband not in contact with the wearer's head.

15. A headband at least long enough to encircle a wearer's head, comprising:

a substantially inelastic band having a first end portion and a second end portion;

an elastic band having a first end and a second end, wherein the first end of the elastic band is attached to the substantially inelastic band;

a tab having a first end and a second end, wherein the first end of the tab is attached to the second end of the elastic band, and the second end of the tab is configured to extend outwardly from the second end portion of the substantially inelastic band and to couple to the first end portion of the substantially inelastic band;

a visual indicator configured to indicate a position of the second end of the elastic band; and

11

a stop configured to limit stretching of the elastic band, wherein the stop comprises an opening in the substantially inelastic band having a width large enough for the tab to pass through, but small enough to restrain the elastic band from passing through.

16. A headband at least long enough to encircle a wearer's head, comprising:

a substantially inelastic band;

an elastic band having one end attached to the substantially inelastic band, and configured to be pulled in a direction away from the end attached to the substantially inelastic band and in a direction along the headband when the headband is around the wearer's head, and configured to stretch when pulled such that the tension created when stretched applies pressure to the wearer's head;

12

a visual indicator configured to indicate whether the pressure applied to the wearer's head from the headband is in a pressure range higher than venous pressure and lower than capillary pressure; and

a sensor configured to be placed on the wearer's head and to be forced against the wearer's head via pressure from the headband.

17. The headband of claim **16**, comprising a pressure sensor coupled to the sensor or to the headband.

18. The headband of claim **17**, wherein the pressure sensor is visible from a side of the headband not in contact with the wearer's head.

* * * * *

专利名称(译)	带张力指示器的头带		
公开(公告)号	US7698909	公开(公告)日	2010-04-20
申请号	US10/779331	申请日	2004-02-13
[标]申请(专利权)人(译)	内尔科尔普里坦贝内特公司		
申请(专利权)人(译)	NELLCOR PURITAN BENNETT INCORPORATED		
当前申请(专利权)人(译)	COVIDIEN LP		
[标]发明人	HANNULA DON COAKLEY JOSEPH MANNHEIMER PAUL D		
发明人	HANNULA, DON COAKLEY, JOSEPH MANNHEIMER, PAUL D.		
IPC分类号	D04B1/24 A41D20/00 A61B5/00		
CPC分类号	A41D20/00 A61B5/6843 A61B5/6814 A61B5/14552 A41D13/1281		
优先权	10/677742 2003-10-01 US 60/415468 2002-10-01 US		
其他公开文献	US20040221370A1		
外部链接	Espacenet USPTO		

摘要(译)

一种头带，其具有适于围绕佩戴者头部的低拉伸段，并且弹性段小于低拉伸段，并且具有自由端和附接端，其中弹性段在其附接端处附接有低拉伸段。头带还包括具有第一端和第二端的翼片部分，翼片部分的第一端与弹性部分的自由端连接，翼片部分的第二端构造成与低端形成闭环。伸展段，围绕佩戴者的头部。头带还包括视觉指示器，其配置用于监测弹性段的伸展位置，并且可选地包括止动部分，该止动部分构造成抵靠弹性段接合以限制其伸展。当具有止动部分时，翼片部分还包括在其第一端和止动部分之间的指示器部分，使得当可见时指示器部分指示头带需要重新紧固；当指示器部分不可见时，它表示足够的张力水平，对应于输送高于静脉压的压力并且低于穿戴者前额的毛细血管压力。

