



US006559620B2

(12) **United States Patent**
Zhou et al.

(10) **Patent No.:** **US 6,559,620 B2**
(45) **Date of Patent:** **May 6, 2003**

(54) **SYSTEM AND METHOD FOR REMOTE MONITORING UTILIZING A RECHARGEABLE BATTERY**

(75) Inventors: **Peter Y. Zhou**, Smithtown, NY (US);
Dexing Pang, Smithtown, NY (US)

(73) Assignee: **Digital Angel Corporation**, So. St. Paul, MN (US)

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 0 days.

(21) Appl. No.: **09/813,477**

(22) Filed: **Mar. 21, 2001**

(65) **Prior Publication Data**

US 2002/0135336 A1 Sep. 26, 2002

(51) **Int. Cl.**⁷ **H01M 10/46**; H01M 10/44

(52) **U.S. Cl.** **320/101**

(58) **Field of Search** 320/101, 103, 320/104, 123, 132, 135, 137, 136, 150; 323/906; 136/291, 293

(56) **References Cited**

U.S. PATENT DOCUMENTS

4,163,447 A 8/1979 Orr
4,468,656 A 8/1984 Clifford et al.
4,531,526 A 7/1985 Genest
4,619,653 A 10/1986 Fischell
4,665,385 A 5/1987 Henderson
4,706,689 A 11/1987 Man
5,043,736 A 8/1991 Darnell et al.
5,119,102 A 6/1992 Barnard
5,153,584 A 10/1992 Engira
5,204,670 A 4/1993 Stinton
5,235,633 A 8/1993 Dennison et al.
5,299,132 A 3/1994 Wortham
5,379,224 A 1/1995 Brown et al.
5,389,934 A 2/1995 Kass
5,418,537 A 5/1995 Bird
5,461,365 A 10/1995 Schlager et al.
5,462,051 A 10/1995 Oka et al.
5,519,403 A 5/1996 Bickley et al.
5,519,760 A 5/1996 Borkowski et al.
5,552,772 A 9/1996 Janky et al.
5,565,858 A 10/1996 Guthrie
5,594,425 A 1/1997 Ladner et al.
5,624,376 A 4/1997 Ball et al.
5,626,630 A 5/1997 Markowitz et al.
5,629,678 A 5/1997 Gargano et al.
5,630,206 A 5/1997 Urban et al.
5,650,770 A 7/1997 Schlager et al.
5,652,570 A 7/1997 Lepkofker
5,712,619 A 1/1998 Simkin
5,714,931 A 2/1998 Petite et al.
5,724,025 A 3/1998 Tavori
5,742,233 A 4/1998 Hoffman et al.
5,742,509 A 4/1998 Goldberg et al.
5,748,147 A 5/1998 Bickley et al.
5,749,909 A * 5/1998 Schroepfel et al.

5,751,246 A 5/1998 Hertel
5,767,788 A 6/1998 Ness
5,772,586 A 6/1998 Heinonen et al.
5,791,294 A 8/1998 Manning
5,838,237 A 11/1998 Revell et al.
5,874,897 A 2/1999 Klempau et al.
5,892,454 A 4/1999 Schipper et al.
5,905,450 A 5/1999 Kim et al.
5,917,425 A 6/1999 Crimmins et al.
5,939,982 A 8/1999 Gagnon et al.
5,963,130 A 10/1999 Schlager et al.
5,971,931 A 10/1999 Raff
5,977,913 A 11/1999 Christ
5,982,281 A 11/1999 Layson, Jr.
6,026,304 A 2/2000 Hilsenrath et al.
6,028,514 A 2/2000 Lemelson et al.
6,031,454 A 2/2000 Lovejoy et al.
6,034,622 A 3/2000 Levine
6,046,687 A 4/2000 Janky
6,069,570 A 5/2000 Herring
6,072,396 A 6/2000 Gaukel
6,078,804 A 6/2000 Alperovich et al.
6,084,512 A 7/2000 Elberty et al.
6,121,881 A 9/2000 Bieback et al.
6,127,925 A 10/2000 Bonsignore et al.
6,131,067 A 10/2000 Gired et al.
6,140,956 A 10/2000 Hillman et al.
6,140,957 A 10/2000 Wilson et al.
6,148,261 A 11/2000 Obradovich et al.
6,154,676 A 11/2000 Levine
6,157,841 A 12/2000 Bolduc et al.
6,160,478 A 12/2000 Jacobsen et al.
6,160,481 A 12/2000 Taylor, Jr.
6,166,642 A 12/2000 Farshid
6,167,276 A 12/2000 Pite
6,169,484 B1 1/2001 Schuchman et al.
6,172,640 B1 * 1/2001 Durst et al.
6,175,308 B1 1/2001 Tallman et al.
6,198,394 B1 3/2001 Jacobsen et al.
6,198,930 B1 3/2001 Schipper
6,199,550 B1 3/2001 Wiesmann et al.
6,208,290 B1 3/2001 Krasner
6,211,781 B1 4/2001 McDonald
6,219,556 B1 4/2001 Lee
6,225,901 B1 5/2001 Kail, IV
6,236,358 B1 5/2001 Durst et al.
6,300,903 B1 10/2001 Richards et al.
6,313,791 B1 11/2001 Klanke
6,421,001 B1 7/2002 Durst et al.



* cited by examiner

Primary Examiner—Edward H. Tso
(74) *Attorney, Agent, or Firm*—Stroock & Stroock & Lavan LLP

(57) **ABSTRACT**

A method and a system for remotely monitoring a person includes a portable unit including a self-recharging battery, the portable unit being adapted to monitor a biological parameter and a physical location of the person; a global positioning satellite transmitting global positioning system (GPS) data to the portable unit; and a central unit disposed remotely from the portable unit, the central unit being in communication with the portable unit via a ground station.

26 Claims, 4 Drawing Sheets






FIG.3




FIG.4




FIG.5




FIG.6




FIG.7




FIG.8

SYSTEM AND METHOD FOR REMOTE MONITORING UTILIZING A RECHARGEABLE BATTERY

FIELD OF THE INVENTION

The present invention generally relates to a system and a method for remotely monitoring, and, more specifically, to a system and a method for remotely monitoring a person using a portable unit that is powered by a self-recharging battery.

BACKGROUND INFORMATION

Medical devices that monitor a biological parameter of a patient are often implanted with a battery. Typically, the battery is replaced before the energy supply is substantially drained. A conventional battery implanted in the patient does not generally reveal the amount of remaining energy supply at a given time. Thus, a conventional battery is replaced periodically. This results in a waste of batteries as well as possibly subjecting the patient to invasive surgery which carries with it enhanced costs, labor and risk.

Some medical devices are powered by rechargeable batteries; however, such batteries still require the patient to make hospital visits in which an external power supply device is coupled to the rechargeable battery. This may require an uncomfortable procedure in which the patient is hooked up to electrodes or subjected to high intensity electromagnetic radiation.

What is needed to help avoid these disadvantages is a portable monitoring unit that is powered by a self-recharging battery.

SUMMARY OF THE INVENTION

The present invention provides for a system for remotely monitoring a person, which includes a portable unit with a self-recharging battery, the portable unit being adapted to monitor a biological parameter and a physical position or location of the person; a global positioning satellite transmitting global positioning system (GPS) data to the portable unit; and a central unit disposed remotely from the portable unit, the central unit being in communication with the portable unit via a ground station.

The present invention further provides for a method for remotely monitoring a person including the steps of adapting a portable unit to be powered by a self-recharging battery; self-recharging the self-recharging battery; receiving, from a global positioning system (GPS) satellite to the portable unit, information relating to a physical location; monitoring, at the portable unit, a biological parameter of the person; and wirelessly communicating the information relating to the physical location and the biological parameter of the person from the portable unit to a central unit via a ground station.

The present invention also provides for a self-recharging battery including a photocell disposed proximately to and under a skin surface of a person; a recharging cell coupled to the photocell; and a battery cell coupled to the recharging cell. The photocell is adapted to receive ambient light and is adapted to generate a potential difference across the recharging cell in response to receiving the ambient light. The recharging cell is adapted to store charge in response to the potential difference. The battery cell is adapted to recharge using the stored charge.

The present invention also provides for a self-recharging battery including a transducer disposed in a region of a

person with a substantial temperature gradient; a recharging cell coupled to the transducer; and a battery cell coupled to the recharging cell. The transducer is adapted to generate a potential difference across the recharging cell in response to heat flow through the transducer. The recharging cell is adapted to store charge in response to the potential difference. The battery cell is adapted to recharge using the stored charge.

The present invention also provides for a self-recharging battery including a transducer coupled to a pulsing blood vessel; a rectifier coupled to the transducer; a recharging cell coupled to the rectifier; and a battery cell coupled to the recharging cell. The transducer is adapted to generate an alternating electrical signal in response to the pulsing blood vessel. The rectifier is adapted to rectify the alternating electrical signal. The recharging cell is adapted to store charge in response to the rectified electrical signal. The battery cell is adapted to recharge using the stored charge.

The present invention also provides for a self-recharging battery including a transducer coupled to a human voice box of a person; a rectifier coupled to the transducer; a recharging cell coupled to the rectifier; and a battery cell coupled to the recharging cell. The transducer is adapted to generate an alternating electrical signal in response to acoustic waves generated by the human voice box. The rectifier is adapted to rectify the alternating electrical signal. The recharging cell is adapted to store charge in response to the rectified electrical signal. The battery cell is adapted to recharge using the stored charge.

The present invention also provides for a self-recharging battery including a transducer disposed proximately to and under a skin surface of a person; a rectifier coupled to the transducer; a recharging cell coupled to the rectifier; and a battery cell coupled to the recharging cell. The transducer is adapted to generate an alternating electrical signal in response to acoustic waves generated by an ambient environment. The rectifier is adapted to rectify the alternating electrical signal. The recharging cell is adapted to store charge in response to the rectified electrical signal. The battery cell is adapted to recharge using the stored charge.

BRIEF DESCRIPTION OF THE DRAWINGS

FIG. 1 illustrates an embodiment of a system and a method for remotely monitoring of a person according to the present invention.

FIG. 2 illustrates an embodiment of a portable unit according to the present invention.

FIG. 3 illustrates an embodiment of a self-recharging battery according to the present invention.

FIG. 4 illustrates another embodiment of the self-recharging battery according to the present invention.

FIG. 5 illustrates two possible locations for a transducer of the self-recharging battery according to the present invention.

FIG. 6 illustrates another possible location for the transducer of the self-recharging battery according to the present invention.

FIG. 7 illustrates still another embodiment of the self-recharging battery according to the present invention.

FIG. 8 illustrates a possible location for a transducer of the self-recharging battery according to the present invention.

DETAILED DESCRIPTION

Although the present invention is generally applicable to systems and methods for remote monitoring, the following

embodiments according to the present invention contemplate systems and methods for remotely monitoring a person.

FIG. 1 illustrates an embodiment of a system and a method for remotely monitoring a person according to the present invention. A portable unit **100** is coupled to a person **110** that is to be monitored. The portable unit **100** is coupled to a satellite **130**. The satellite **130** may be, for example, a set or an array of satellites of an existing global positioning system (GPS). The portable unit **100** is coupled to a ground station **120**. The ground station **120** may be, for example, a part of an existing mobile phone grid or a radio communications array. The ground station **120** is coupled to a central unit **140**.

The portable unit **100** is adapted to monitor biological parameters of the person **100**. The portable unit, may monitor acoustic, thermal, mechanical, chemical, electrical and/or electromagnetic parameters, for example, related to human biological parameters including, for example, temperature, heart rate, blood flow rate, muscular activity, respiratory rate, and brain activity of the person being monitored.

Furthermore, the portable unit **100** is adapted to monitor the physical location of the person **110**. In an embodiment according to the present invention, the portable unit **100** receives GPS data transmitted by the satellite **130**. With the GPS data, information relating to a physical location of the person **110** may be determined.

In an embodiment according to the present invention, the central unit **140** makes a request for information to the ground station **120**, with which the central unit **140** is in two-way communication. The ground station **120** wirelessly transmits an interrogation signal to the portable unit **100**, with which the ground station **120** is in two-way wireless communication. In response to the interrogation signal, the portable unit **100** wirelessly transmits information relating to the physical location and/or the human biological parameters of the person **110** being monitored. Further information can be sent that is stored in the portable unit **100** such as, for example, identifying information, personal information or special medical information such as personal medical conditions. The ground station **120** sends information relating to information received from the portable unit **100** to the central unit **140**. The information received by the central unit **140** can ultimately be stored, displayed, printed, processed or sent to other central units in a network, for example.

The central unit **140**, which may be located in a hospital or a monitoring center, for example, may make the request for information periodically or aperiodically, for example, by manual intervention or a command triggered by a particular circumstance. Furthermore, the central unit **140** may be in wire-to-wire or wireless communication with the ground station **120**.

In another embodiment according to the present invention, the portable unit **100**, without the receipt of the interrogation signal from the ground station **120**, periodically sends information to the ground station **120**. Information relating to the received information is sent by the ground station **120** to the central unit **140**. In yet another embodiment according to the present invention, the portable unit **100** sends information to the ground station **120** in response to a particular circumstance monitored by the portable unit **100** or in response to a manual command by the person **110** being monitored. For example, the portable unit **100** may send information to the ground station **120** in response to a particular biological parameter which may be

indicative of a dangerous medical condition. In another example, the portable unit **100** sends information to the ground station **120** in response to a manual actuation of a switch or a specifically programmed button by the person **110**.

The processing of data relating to, for example, the physical location and/or the human biological parameters of the person **110** being monitored may occur either in the portable unit **100**, the ground station **120**, the central unit **140** or some combination thereof. For example, the portable unit **100** may receive GPS data from the satellite. The GPS data is processed by the portable unit **100**, the portable unit **100** calculating the physical location of the person **110** before sending the calculated physical location to the ground station **120** and, subsequently, to the central unit **140**.

Alternatively, the GPS data received by the portable unit **100** may be sent to the ground station **120**, which processes the information and calculates the physical location of the person **110**, the calculated physical location of the person being sent to the central unit. In yet another alternative, the GPS data is sent to the portable unit **100** which sends the information to the ground station **120** which, in turn, sends the information to the central unit **140**. In this embodiment, it is the central unit **140** which processes the GPS data and calculates the physical location of the person **110**. Furthermore, the present invention contemplates a distributed processing scheme in which part of the processing of the information received by the portable unit **100** from the person **110** and/or the satellite **130** is processed, in part, by a combination of the portable unit **100**, the ground station **120** and/or the central unit **140**.

FIG. 2 illustrates an embodiment of a portable unit **100** according to the present invention. The portable unit **100** includes a microchip **210**, a transceiver **220**, a self-recharging battery **230** and at least one sensor **240**. The portable unit **100** may optionally include a receiver **250**. Furthermore, the microchip **210** includes a processing unit **260** and an information storage device **270**.

Although FIG. 2 illustrates some parts included on the microchip **210** and some parts coupled to the microchip **210**, one of ordinary skill in the art understands, and the present invention contemplates, that different levels of integration may be achieved by integrating any of the coupled parts as illustrated in FIG. 2 onto the microchip **210**.

The self-recharging battery **230**, the at least one sensor **240**, the transceiver **220** and, optionally, the receiver **250** are each coupled to the microchip **210**. In an embodiment according to the present invention, the at least one sensor **240**, the transceiver **220** and, optionally, the receiver **250** are each coupled to the processing unit **260**, which, in turn, is coupled to the information storage device. The self-recharging battery **230** powers the microchip **210**, including the processing unit **260** and the information storage device **270**. The self-recharging battery **230** may also power directly or indirectly the transceiver **220**, the at least one sensor **240** and/or, optionally, the receiver **250**.

In an embodiment according to the present invention, the transceiver **220** is adapted to be in two-way wireless communication with the ground station **120** and in one-way wireless communication with the satellite **130**. The transceiver **220** may be a single antenna or an antenna array, for example.

In another embodiment according to the present invention, the portable unit **100** includes the transceiver **220** and the receiver **250**. In this embodiment, the transceiver **220** is in two-way wireless communication with the ground

station 120 and the receiver 250 is in one-way wireless communication with the satellite 130. The use of the transceiver 220 and the receiver 250 is advantageous in that the portable unit 100 generally consumes less energy. GPS frequencies tend to be relatively high and sending information over such frequencies by the portable unit 100 via the transceiver 220 can be energy intensive. This embodiment contemplates the receiver 250 being adapted for receiving at high frequencies and the transceiver 220 being adapted for receiving and sending at lower frequencies. The sending of information over lower frequencies by the transceiver 220 results in less energy consumption by the portable unit 100.

The at least one sensor 240 is adapted to monitor acoustic, thermal, mechanical, chemical, electrical and/or electromagnetic parameters, for example, related to human biological parameters including, for example, temperature, heart rate, blood flow rate, muscular activity, respiratory rate, and/or brain activity of the person being monitored. The conversion of acoustic, thermal, mechanical, chemical, electrical and/or electromagnetic parameters into electrical signals, for example, is understood by one of ordinary skill in the art and is not detailed further.

The microchip 210 includes the processing unit 260 and the information storage device 270 in an embodiment according to the present invention. The processing unit 260 may include, for example, a microprocessor, a cache, input terminals and output terminals. The processing unit 260 may include an information storage device which includes an electronic memory which may or may not include the cache of the processing unit 260.

In operation, according to at least one embodiment of the present invention, the receiver 250 receives GPS data from the satellite 130. The GPS data is received by the microchip 210 and, in particular, the processing unit 260. Although the GPS data is continuously received by the receiver 250, the processing unit 260 may periodically or aperiodically (i.e., via manual intervention or as a function of circumstance, for example) receive the GPS data. The GPS data may then be processed in the processing unit 260 which may include determining the physical location of the person 110 being monitored. The GPS data and/or the determined physical location are stored in the information storage device 270.

The at least one sensor 240 senses biological parameters of the person 110. These biological parameters are converted into electrical signals by the at least one sensor 240 and received by the processing unit 260. The sensing of biological parameters by the at least one sensor 240 may be a periodic or an aperiodic function (i.e., triggered by a request from the processing unit 260 or as a function of circumstance, for example). The processing unit 260 may process the electrical signals by converting them into information relating to, for example, a measure of temperature, heart rate, blood flow rate, muscular activity, respiratory rate, and/or brain activity. The processing unit 260 stores the processed and/or unprocessed electrical signals in the information storage device 270. The transceiver 220 receives the interrogation signal, for example, from the ground station 120. The transceiver 220 then sends the interrogation signal to the microchip 210, in particular, to the processing unit 260. Upon receiving the interrogation signal the processing unit 260 uploads the information stored in the information storage device onto the transceiver 220. The transceiver then sends the uploaded information to the ground station 120.

In another embodiment according to the present invention, the microchip is activated only when the transceiver 220 receives the interrogation signal from the ground

station 120. This embodiment has an advantage in that energy consumption is minimized. Upon receiving the interrogation signal, the processing unit 260 accepts data from the receiver 250 and the at least one sensor 240. The processing unit 260 may accept the data over a time interval to achieve more precise data or to develop a history of data. Such data may be processed and/or stored in the information storage device 270. Upon completion of the processing and/or storing of the data, the information contained in the information storage device is uploaded onto the transceiver 220 and transmitted to the ground station 120. After completing the transmission of the uploaded data via the transceiver 220, the processing unit 260 is no longer active in receiving, processing and/or storing information until the next interrogation signal is received from the ground station.

In another embodiment according to the present invention, the transceiver 220, without the optional receiver 250, is adapted to receive the GPS data from the satellite 130 and the interrogation signal from the ground station 120. Furthermore, the transceiver 220 transmits information from the processing unit 260 to the ground station. Operation is similar as described above.

The information storage device 270 may also store preset information relating to identification, personal information or special medical information, for example. This information may have been programmed before the coupling of the portable device 100 to the person 110. Alternatively, the information may have been transmitted to the portable device 100 after the portable device 100 was coupled to the person 110. Such information may include the person's name, home address, phone number and/or a listing of relatives to contact in case of emergency. Furthermore, the information permanently stored in the portable device 100 may relate to special medical information such as allergies to medication or that the patient is diabetic or asthmatic, for example. All of this information may be uploaded onto the transceiver 220 and transmitted to the ground station 120. Such information may be of special significance to medical personnel when the person is disoriented or unconscious and unable to communicate.

FIGS. 3-8 illustrate exemplary embodiments of the self-recharging battery 230 according to the present invention. A self-recharging battery 230 is advantageous in a method and a system for remote monitoring.

FIG. 3 illustrates an embodiment of the self-recharging battery 230 according to the present invention. The self-recharging battery 230 includes a photocell 310, a recharging cell 320 and a battery cell 330. The photocell 310 is disposed proximately to a skin surface 340 of the person 110. In the illustrated example, the photocell 310 is just under the skin surface 340. The photocell 310 is coupled to the recharging cell 320. In one embodiment, the recharging cell is a capacitor. The recharging cell 320 is coupled to the battery cell 330. The battery cell 330 is coupled to and powers the microchip 210.

In operation, ambient light 350 (e.g., environmental light, natural light) penetrates the skin surface 340. The ambient light 350 is absorbed by the photocell 310. In response to the ambient light 350 being absorbed by the photocell 310, the photocell 310 generates a potential difference (e.g., a voltage) across the recharging cell 320. The recharging cell 320 stores charge which, in turn, is used to recharge the battery cell 330.

FIG. 4 illustrates another embodiment of the self-recharging battery 230 according to the present invention. The self-recharging battery 230 includes a transducer 410,

the recharging cell **320** and the battery cell **330**. In the illustrated example, the transducer **410** is disposed proximately to the skin surface **340**. Because of differences in temperature between the body just below the skin surface **340** and the ambient atmosphere **430**, a heat flow **420** is generated. In part, the heat flow **420** passes through the transducer **410**. The transducer **410** may be, for example, a heat sensitive semiconductor transducer. The heat flow **420** passing through the transducer **410** creates a potential difference between opposite sides of the transducer. The potential difference is provided across the recharging cell **320**, the recharging cell **320** storing charge. The stored charge is used to recharge the battery cell **330**.

Although FIG. 4 illustrates a temperature difference between the skin surface **340** and the ambient atmosphere **430**, other temperature differences may be employed. For example, FIG. 5 illustrates that the transducer **410** may be placed between a fat layer **520** and a muscle layer **530**, or between the fat layer **520** and a skin layer **510**. Since each layer **510**, **520**, **530** has different relative thermal properties, different heat flows can be generated. Accordingly, the effectiveness of the transducer **410** as a recharger is dependent upon the location within the body and upon what materials are employed in creating the heat flow. FIG. 6 illustrates that the transducer **410** may be disposed between a first body part **610** and a second body part **620**. The transducer **410** employs the heat flow from the first body part **610** to the second body part **620** in charging the recharging cell **320**.

FIG. 7 illustrates an embodiment of the self-recharging battery **230** according to the present invention. As the schematic indicates, the self-recharging battery **230** includes the battery cell **330**, the recharging cell **320**, a rectifier **710** and a transducer **720** (e.g., a piezo-electric device). The battery cell **330** is coupled to the recharging cell **320** which, in turn, is coupled to the rectifier **710** which, in turn, is coupled to the transducer **720** which, in turn, is coupled to a blood vessel **730**.

In operation, blood is naturally pulsed through the blood vessel **730** causing the blood vessel **730** to have a cycle of expansion and compression. The expansion and compression of the blood vessel **730** is hereinafter referred to as the pulse. The pulse acts upon the transducer **720**. The mechanical pressure provided on the transducer **720** by the pulse causes the transducer **720** to generate an alternating electrical signal. The alternating electrical signal passes through the rectifier **710**. The recharging cell **320** uses the rectified electrical signal to store charge which, in turn, is used to recharge the battery cell **330**.

FIG. 8 illustrates the placement of the transducer **720** in an advantageous location proximate to the skin surface **340** and to a human voice box **810** from which resonates audible sounds (e.g., talking). The transducer **720** (e.g., a microphone) is stimulated either by the vibrations generated by the voice box **810** as indicated via sound waves **830** or by vibrations generated in the ambient atmosphere **430** as indicated by sound waves **820**. Thus, via the transducer **720**, the self-recharging battery **230** is recharged when the person **110** is talking, for example, or when the person **110** is in a noisy ambient environment.

In the foregoing description, the method and the system of the present invention have been described with reference to specific embodiments. It is to be understood and expected that variations in the principles of the method and the system herein disclosed may be made by one of ordinary skill in the art and it is intended that such modifications, changes and

substitutions are to be included within the scope of the present invention as set forth in the appended claims. The specification and the drawings are accordingly to be regarded in an illustrative, rather than in a restrictive sense.

What is claimed is:

1. A system for remotely monitoring a living being, comprising:

a portable unit including a self-recharging battery, the portable unit being adapted to monitor a biological parameter and a physical location of the living being, the self-recharging battery being rechargeable based on a physiological condition of the living being; the portable unit further adapted to receive global positioning system (GPS) data; and

a central unit disposed remotely from the portable unit, the control unit being in communication with the portable unit, the central unit adapted to receive information indicative of the biological parameter and physical location of the living being from the portable unit.

2. A portable unit for remote monitoring of a living being, the unit comprising:

a self-recharging battery

wherein the self-recharging battery includes a photocell, a recharging cell and a battery cell, the photocell being coupled to the recharging cell, the recharging cell being coupled to the battery cell,

wherein the photocell is disposed proximately to and under a skin surface of the living being,

wherein the photocell is adapted to receive ambient light and is adapted to generate a potential difference across the recharging cell in response to receiving the ambient light,

wherein the recharging cell is adapted to store charge in response to the potential difference, and

wherein the battery cell is adapted to recharge using the stored charge.

3. A portable unit for remote monitoring of a living being, the unit comprising:

a rechargeable battery,

wherein the rechargeable battery includes a transducer, a recharging cell and a battery cell, the transducer being coupled to the recharging cell, the recharging cell being coupled to the battery cell,

wherein the transducer is disposed in a region with a substantial temperature gradient,

wherein the transducer is adapted to generate a potential difference across the recharging cell in response to heat flow through the transducer,

wherein the recharging cell is adapted to store charge in response to the potential difference, and

wherein the rechargeable battery cell is adapted to recharge using the stored charge.

4. A portable unit for remote monitoring of a living being, the unit comprising:

a rechargeable battery;

wherein the rechargeable battery includes a transducer, a rectifier, a recharging cell and a battery cell, the transducer being coupled to the rectifier, the rectifier being coupled to the recharging cell, the recharging cell being coupled to the battery cell,

wherein the transducer is coupled to a pulsing blood vessel,

wherein the transducer is adapted to generate an alternating electrical signal in response to the pulsing blood vessel,

9

wherein the rectifier is adapted to rectify the alternating electrical signal,

wherein the recharging cell is adapted to store charge in response to the rectified electrical signal, and

wherein the battery cell is adapted to recharge using the stored charge.

5. A portable unit for remote monitoring comprising:

a rechargeable battery;

wherein the rechargeable battery includes a transducer, a rectifier, a recharging cell and a battery cell, the transducer being coupled to the rectifier, the rectifier being coupled to the recharging cell, the recharging cell being coupled to the battery cell,

wherein the transducer is disposed proximately to and under the skin surface of the living being,

wherein the transducer is adapted to generate an alternating electrical signal in response to acoustic waves generated by an ambient environment,

wherein the rectifier is adapted to rectify the alternating electrical signal,

wherein the recharging cell is adapted to store charge in response to the rectified electrical signal, and

wherein the stored charge recharges the battery cell.

6. A portable unit for remote monitoring of a living being, the unit comprising:

a rechargeable battery;

wherein the rechargeable battery includes a transducer, a rectifier, a recharging cell and a battery cell, the transducer being coupled to the rectifier, the rectifier being coupled to the recharging cell, the recharging cell being coupled to the battery cell,

wherein the transducer is coupled to a human voice box,

wherein the transducer is adapted to generate an alternating electrical signal in response to acoustic waves generated by the human voice box,

wherein the rectifier is adapted to rectify the alternating electrical signal,

wherein the recharging cell is adapted to store charge in response to the rectified electrical signal, and

wherein the stored charge recharges the battery cell.

7. A method for remotely monitoring a living being, comprising the steps of:

adapting a portable unit to be powered by a self-recharging battery, the portable unit providing at least one sensor;

self-recharging the self-recharging battery based on a physiological condition of the living being;

receiving, by the portable unit, information relating to a physical location and a biological parameter of the person; and

wirelessly communicating the information relating to the physical location and the biological parameter of the person from the portable unit to a central unit via a ground station.

8. A self-recharging battery, comprising:

a photocell disposed proximately to and under a skin surface of a person;

a recharging cell coupled to the photocell; and

a battery cell coupled to the recharging cell,

wherein the photocell is adapted to receive ambient light and is adapted to generate a potential difference across the recharging cell in response to receiving the ambient light,

10

wherein the recharging cell is adapted to store charge in response to the potential difference, and

wherein the battery cell is adapted to recharge using the stored charge.

9. A self-recharging battery, comprising:

a transducer disposed in a region of a living being with a substantial temperature gradient;

a recharging cell coupled to the transducer;

a battery cell coupled to the recharging cell,

wherein the transducer is adapted to generate a potential difference across the recharging cell in response to heat flow through the transducer,

wherein the recharging cell is adapted to store charge in response to the potential difference, and

wherein the battery cell is adapted to recharge using the stored charge.

10. The self-recharging battery according to claim 9,

wherein the transducer is disposed proximately to and under the skin surface of the living being, and

wherein the substantial temperature gradient is between an ambient environment and a region disposed proximately to and under the skin surface.

11. The self-recharging battery according to claim 9,

wherein the transducer is disposed between a skin layer and a fat layer of the living being, and

wherein the substantial temperature gradient is between the skin layer and the fat layer.

12. The self-recharging battery according to claim 9,

wherein the transducer is disposed between a first body part and a second body part of the living being, and

wherein the substantial temperature gradient is between the first body part and the second body part.

13. A self-recharging battery, comprising:

a transducer coupled to a pulsing blood vessel;

a rectifier coupled to the transducer;

a recharging cell coupled to the rectifier; and

a battery cell coupled to the recharging cell,

wherein the transducer is adapted to generate an alternating electrical signal in response to the pulsing blood vessel,

wherein the rectifier is adapted to rectify the alternating electrical signal,

wherein the recharging cell is adapted to store charge in response to the rectified electrical signal, and

wherein the battery cell is adapted to recharge using the stored charge.

14. A self-recharging battery, comprising:

a transducer coupled to a human voice box of a person;

a rectifier coupled to the transducer;

a recharging cell coupled to the rectifier; and

a battery cell coupled to the recharging cell,

wherein the transducer is adapted to generate an alternating electrical signal in response to acoustic waves generated by the human voice box,

wherein the rectifier is adapted to rectify the alternating electrical signal,

wherein the recharging cell is adapted to store charge in response to the rectified electrical signal, and

wherein the battery cell is adapted to recharge using the stored charge.

15. A self-recharging battery, comprising:

a transducer disposed proximately to and under a skin surface of a person;

11

a rectifier coupled to the transducer;
 a recharging cell coupled to the rectifier; and
 a battery cell coupled to the recharging cell,
 wherein the transducer is adapted to generate an alternat- 5
 ing electrical signal in response to acoustic waves
 generated by an ambient environment,
 wherein the rectifier is adapted to rectify the alternating
 electrical signal,
 wherein the recharging cell is adapted to store charge in 10
 response to the rectified electrical signal, and
 wherein the battery cell is adapted to recharge using the
 stored charge.
16. The portable unit of claim **2**, wherein the portable unit
 is adapted to: 15
 monitor a physical location of the portable unit;
 receive GPS data; and
 communicate GPS location information indicative of the
 physical location to a remote control unit. 20
17. The portable unit of claim **3**, wherein the portable unit
 is adapted to:
 monitor a physical location of the portable unit;
 receive GPS data; and
 communicate GPS location information indicative of the 25
 physical location to a remote control unit.
18. The portable unit of claim **4**, wherein the portable unit
 is adapted to:
 monitor a physical location of the portable unit;
 receive GPS data; and 30
 communicate GPS location information indicative of the
 physical location to a remote control unit.
19. The portable unit of claim **5**, wherein the portable unit
 is adapted to:

12

monitor a physical location of the portable unit;
 receive GPS data; and
 communicate GPS location information indicative of the
 physical location to a remote control unit.
20. The portable unit of claim **6**, wherein the portable unit
 is adapted to:
 monitor a physical location of the portable unit;
 receive GPS data; and
 communicate GPS location information indicative of the
 physical location to a remote control unit.
21. A method for charging a portable unit receiving power
 from a rechargeable battery, the portable unit for remote
 monitoring of a living being, the method comprising:
 recharging the rechargeable battery based on a tempera-
 ture gradient across a transducer.
22. The method of claim **21** wherein the living being is a
 person.
23. A method for charging a portable unit receiving power
 from a rechargeable battery, the portable unit for remote
 monitoring of a living being, the method comprising:
 recharging the rechargeable battery based on a pulsing
 blood vessel in the living being.
24. The method of claim **23** wherein the living being is a
 person. 25
25. A method for charging a portable unit receiving power
 from a rechargeable battery, the portable unit for remote
 monitoring of a living being, the method comprising:
 recharging the rechargeable battery based on acoustic
 waves, wherein the acoustic waves are generated by
 vocal chords of the living being.
26. The method of claim **25** wherein the living being is a
 person.

* * * * *

专利名称(译)	利用可充电电池进行远程监控的系统和方法		
公开(公告)号	US6559620	公开(公告)日	2003-05-06
申请号	US09/813477	申请日	2001-03-21
[标]申请(专利权)人(译)	数字安吉尔公司		
申请(专利权)人(译)	数字天使公司		
当前申请(专利权)人(译)	数字天使公司		
[标]发明人	ZHOU PETER Y PANG DEXING		
发明人	ZHOU, PETER Y. PANG, DEXING		
IPC分类号	A61B5/00 A61B5/11 G01S13/00 G01S13/82 H02J7/35 H02J7/32 H01M10/42 H01M10/46 A61N1/378 A61N1/372 G01S5/14 H01M10/44 H01M16/00 G01S19/35		
CPC分类号	A61B5/0031 A61B5/1117 A61B5/411 A61B5/681 G01S13/825 H01M10/42 H01M10/465 H02J7/32 H02J7/355 A61B5/1112 A61B5/6811 A61B5/14532 A61B5/4806 A61B5/486 A61B2560/0214 A61B2560 /0219 A61N1/3787 G01S19/17 H01M10/44 H01M10/46 H01M16/00 H02J7/35		
其他公开文献	US20020135336A1		
外部链接	Espacenet USPTO		

摘要(译)

一种用于远程监控人的方法和系统，包括：便携式单元，包括自充电电池；所述便携式单元适于监测所述人的生物参数和物理位置；全球定位卫星向便携式单元发送全球定位系统（GPS）数据；以及远离便携式单元设置的中央单元，中央单元通过地面站与便携式单元通信。

