



US006398718B1

(12) **United States Patent**
Yachia et al.

(10) **Patent No.:** **US 6,398,718 B1**
(45) **Date of Patent:** **Jun. 4, 2002**

- (54) **INTRAVESICULAR DEVICE**
- (75) Inventors: **Daniel Yachia**, Herzliya on Sea; **Eran Hirszowicz**, Ramat-Chen, both of (IL)
- (73) Assignee: **Innoventions, Inc.**, Edina., MN (US)
- (*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 0 days.

(21) Appl. No.: **09/594,641**
(22) Filed: **Jun. 15, 2000**

(51) **Int. Cl.**⁷ **A61F 2/00**; A61M 37/00
(52) **U.S. Cl.** **600/29**; 604/93.01
(58) **Field of Search** 600/29, 30; 604/103.9, 604/323, 264; 606/41; 607/88; 128/899

(56) **References Cited**

U.S. PATENT DOCUMENTS

4,055,178 A	10/1977	Harrigan	128/260
4,258,705 A	3/1981	Sorenson et al.	128/1 R
4,804,375 A	* 2/1989	Robertson	604/323
4,834,704 A	5/1989	Reinicke	604/51
4,850,963 A	7/1989	Sparks et al.	600/29
4,871,542 A	10/1989	Vihardt	424/423
5,019,032 A	5/1991	Robertson	600/29
5,030,199 A	7/1991	Barwick et al.	600/29
5,188,109 A	2/1993	Saito	128/635
5,234,409 A	8/1993	Goldberg et al.	604/96

5,334,197 A	8/1994	Kriesel et al.	604/132
5,443,470 A	8/1995	Stern et al.	607/98
5,472,441 A	* 12/1995	Edwards et al.	606/41
5,513,659 A	5/1996	Buuck et al.	128/885
5,579,781 A	12/1996	Cooke	128/733
5,604,531 A	2/1997	Iddan et al.	348/76
5,653,689 A	* 8/1997	Buelna et al.	604/103.9
5,704,353 A	1/1998	Kalb et al.	128/634
5,732,714 A	3/1998	Morrissey et al.	128/846
5,762,599 A	* 6/1998	Sohn	600/30
5,800,478 A	* 9/1998	Chen et al.	607/88
5,806,527 A	9/1998	Borodulin et al.	128/885
5,989,230 A	* 11/1999	Frassica	604/264
6,039,967 A	4/2000	Ottoboni et al.	424/426
6,066,088 A	* 5/2000	Davis	600/29


* cited by examiner

Primary Examiner—Eric F. Winakur
Assistant Examiner—Nikita R Veniaminov
(74) *Attorney, Agent, or Firm*—Ladas & Parry

(57) **ABSTRACT**

A resiliently flexible body having a non-spherical shape and having a magnetizable portion for use in sealing an anatomical cavity such as a urinary bladder. The body is compressed and then inserted into the cavity. In the cavity the body is experimented and positioned at the cavity outlet. The body is rotated in the outlet using a hand-held magnet between a sealing orientation in which the outlet is sealed, and a non-sealing orientation in which fluid, such as urine, can flow out of the cavity.

52 Claims, 22 Drawing Sheets






FIG. 1A




FIG. 1B




FIG. 2




FIG. 3




FIG. 4




FIG. 5




FIG. 6




FIG. 7




FIG. 8




FIG. 9A




FIG. 9B




FIG. 9C




FIG. 9D




FIG. 9E




FIG. 9F




FIG. 9H





FIG. 9G






FIG. 9I




FIG. 9J




FIG. 9L




FIG. 9M




FIG. 9K





FIG. 10





FIG. 11





FIG. 12




FIG. 13




FIG. 14




FIG. 15A




FIG. 15B




FIG. 16A




FIG. 16B




FIG. 17A




FIG. 17B




FIG. 18




FIG. 19

1

INTRAVESICULAR DEVICE

FIELD OF THE INVENTION

The invention is in the field of medical devices. More specifically, the invention relates to devices for the treatment of urinary incontinence.

BACKGROUND OF THE INVENTION

Several disorders of the urinary tract are known. Among these are urinary incontinence, chronic urinary tract infections, urinary bladder tumors.

Urinary Incontinence

Urinary incontinence mostly affects women (approximately 10 million in the U.S.A. alone) primarily after childbirth or due to old age. In men, urinary incontinence often occurs as a complication of surgery or old age (approximately 3 million in the U.S.A).

Incontinence has serious economic, health, social and psychological consequences. Its estimated cost to the health system in the United States in 1993 was US \$16 billion. It leads to chronic and severe skin irritation in the genital area, an increase in urinary infections and urosepsis. Fear of incontinence and odors in public cause incontinent people to severely restrict their social activities. The impact on the mental health of the affected people may be even more devastating than the social and health consequences. They suffer severe embarrassment, loss of self-esteem, depression and anxiety.

Urinary incontinence can be divided into four groups:

Stress Incontinence—is the involuntary release of urine due to a sudden increase in the intra-abdominal pressure caused by laughing, sneezing, coughing, running, etc. This is the most common type of incontinence and in women may be the result of anatomical changes in the pelvic organs after childbirth, estrogen deficiency, unsuccessful surgical repairs for incontinence or pelvic irradiation. In men, it often happens after surgery for benign enlargement of the prostate gland or after radical removal of the prostate.

Total Incontinence—is the continuous leak of urine entering the bladder due to failure of the sphincteric muscles.

Urge Incontinence—is involuntary loss of urine due to involuntary bladder contractions. This type of incontinence mostly affects the elderly who leak until they reach a toilet.

Mixed Incontinence—is a combination of stress and urge incontinence. This condition is more common in elderly women than men.

Ideally, treatment of incontinence should provide permanent dryness and is easy to perform.

Phannacological treatments of bladder dysfunctions are based either on estrogen replacement for treating postmenopausal vaginal and urethral atrophy or on agents affecting the tonus of the bladder muscle. Since affected elderly women suffer from both hormonal deficiency and urinary incontinence, both types of agents are usually prescribed simultaneously.

Surgical treatments are based on restoring the anatomical changes causing the incontinence. Although in the short-term most surgical procedures restore continence, the long-term prognosis is usually unsatisfactory. Moreover, surgery entails morbidity and high expenses.

Conservative/behavioral treatments are based on pelvic floor muscle exercises, bladder training, biofeedback, vagi-

2

nal cones, low-frequency electrostimulation of pelvic floor muscles, intravaginal bladder neck support pessaries, urethral meatus suction cups and intraurethral devices. Conservative treatments are time consuming and require the patients' understanding, cooperation and persistence.

Devices which have been used to obtain almost immediate dryness in incontinent people can be divided into two groups:

(1) Urethral Plugs/Inserts

These comprise a flexible rod having, a 14 Ch. (approximately 4.5 mm) diameter and a length adjusted to fit the length of the patient's urethra. The rod has an inflatable device on its bladder end and a flange at other end. After insertion of the device, the device is inflated in the bladder.

The device and the flange, maintain the device in its proper position within the urethra. The device and rod form a mechanical barrier to retain the urine within the bladder. The device must be deflated and the device removed and discarded prior to voiding. Such inserts are known in the art, for example, the device known as RELIANCE produced by UroMed Corp., U.S.A. Since insets are discarded after each voiding and replaced with a new one by the patient, manual dexterity of the patient is required. Insertion of an insert into a female has the risk of pushing vaginal and perineal bacteria into the bladder and insertion of an insert a few times a day increases this risk. The inconvenience of removing and inserting a new device and its costs, in addition to the infection risk, are the major disadvantages of these devices.

(2) Valve Catheters

These comprise a tube with a valve at one end. The bladder end of the device typically has a device or flanges for retaining the device in place and a flange at the other end to prevent migration into the bladder. The valve is opened for voiding through the lumen of the catheter with the help of an external magnet. The tube typically has a 18 Ch. (6 mm.) to 20 Ch. (approximately 7 mm) diameter and a length adjusted to fit the patient's urethra. For male incontinence, an active intraurethral Foley-type catheter is used. This device has a retaining, device at its bladder end and another smaller device under the prostate for fixing the device in place. The magnet activated valve is situated at the end of the device near the distal end of the urethra. Active inserts are typically left indwelling up to 4 weeks and are then replaced.

Examples of such catheters are disclosed in U.S. Pat. Nos. 5,030,199 and 5,234,409. Valve catheters are more convenient for the patient than the inserts; however, in females they cause ascending infection because they connect the bladder with the vulva which is rich in pathogenic bacteria, especially *Escherichia Coli*. Even with continuous use of antibiotics, infection is inevitable in the majority of cases. During prolonged use of catheters or inserts in female patients, a relaxation of the urethra occurs and the patients may start to leak around the device. Unfortunately valve catheters and inserts are unavailable in increasing diameters.

A significant disadvantage of both the inserts and the valve catheters is the discomfort felt by the patient especially when sitting and during sexual intercourse (felt by the patient and the partner).

The present invention therefore provides a device for the treatment of urinary incontinence in which the disadvantages of the prior art devices are substantially reduced or eliminated.

(3) Urinary Bladder Plugs

U.S. Pat. No. 4,850,963 to Sparks et al. discloses a bolus for insertion in to a urinary bladder for the treatment of urinary incontinence. The bolus contains a ferromagnetic

material and has a specific gravity greater than that of urine. The bolus is maintained at the urinary bladder outlet to the urethra under the influence of gravity so as to prevent the flow of urine into the urethra. For voiding, the bolus is displaced from the opening using an external magnet.

Urinary Tract Infections

Nearly half of all women experience urinary tract infection (UTI) at some point in their lifetime and most of these infections are confined to the bladder. Isolated UTIs can be treated by short and effective antibiotic treatment. However, recurrent UTIs often occur in women due to antibiotic resistant bacteria. In this case complicated infections often exhibit multidrug resistance and necessitate longer antimicrobial drug administrations.

Treatment of UTIs often requires urinary levels of antimicrobial drugs that are several hundred times greater than those allowable in the blood. Many antibacterials cannot be used in UTI because, when taken orally or intravenously, they do not attain the required concentration in the urine, without exceeding the allowable limit in the blood. It would therefore be desirable to be able to continuously introduce antimicrobial drugs continuously and directly into the bladder.

Bladder Tumors

Even after resection, bladder tumors may not only recur but may also invade deeper in the bladder wall. Due to the heterogeneity of these tumors (from low-grade tumors showing a benign course to highly malignant high-grade tumors), there does not exist a single approach to the surveillance and treatment of these tumors. Intravesical drug therapies are often used for reducing tumor recurrence. In this approach an immunotherapeutic or chemotherapeutic agent is inserted into the bladder through a catheter. This treatment is typically repeated once a week for 6 weeks and then once a month for a period of 6-12 months. However, periodic treatment has not been established as being effective in altering the progression of the tumor. Continuous local treatment with chemotherapeutic or radioactive materials may treat or prevent not only superficial tumors but also deep tumors as well. It would therefore be desirable to be able to introduce antitumoral drugs continuously and directly into the bladder.

Bladder Dysfunction

During filling, the bladder muscle relaxes for keeping the intravesical pressure low while it contracts for voiding. Certain diseases such as spinal cord injuries, diabetes, multiple sclerosis, or hormonal changes after menopause or old age in both sexes may cause a hypo contractility or, paradoxically, hyper contractility of the muscle. In atonic bladder, pharmacological treatment is not very effective. In hyperreflexic bladder, drugs for relaxing the bladder cause constipation and mouth dryness and are therefore not tolerated well by the patients.

Diagnosis of bladder dysfunction requires continuously monitoring various bladder parameters during filling and/or voiding. These measurements usually are made by inserting a catheter connected to a measuring device into the bladder. This is done for example, in uroflowmetry (measurement of urinary flow rate) which is non-invasive, simple and inexpensive. However, its sensitivity and specificity are low. Cystometry is an invasive technique for measuring bladder capacity, compliance and muscle tonus. Pressure-flow study is an invasive and costly test for distinguishing patients with

low urinary flow due to obstruction or bladder antonia, from those with high intravesical pressure and high urinary flow. It is therefore a need in the art for a simple and inexpensive technique for intravesicular monitoring.

In the diagnostic procedure known as "urodynamics", the bladder is filled through a catheter, and the response of the bladder is monitored. Available 24 hour urodynamic monitors have catheters or wires passing through the urethra, connecting sensors inserted into the bladder to a recorder. The connecting wires and catheters inadvertently introduce pathogenic bacteria from the genital areas into the bladder. It is therefore desirable to be able to monitor bladder function over several cycles of filling and voiding without the need for such wires or catheters.

Diagnosis of some intravesical pathological conditions often involves inserting an endoscope into the bladder and optically scanning the bladder walls. In cases of bleeding in the ureters or the kidneys, the observation of blood coming through the ureteral orifices allows determination of the origin of the bleeding. However, if the bleeding has temporarily stopped at the time of the examination, or if the blood concentration in the urine is insufficient to make the urine red or pink, endoscopy is of little value in reaching a diagnosis. In such cases more invasive procedures are performed in order to enter the upper urinary tract. It is therefore desirable to be able to monitor the bladder over long periods of time.

Bladder shape during filling and its contraction during voiding is important for the diagnosis of certain bladder pathologies. These functions can be followed in fluoroscopy and by sonography. These techniques however are not accurate and cannot be used for monitoring changes in bladder shape over long periods of time. It would therefore be desirable to be able to continuously image the bladder interior over long periods of time.

The present invention therefore provides a device for continuous monitoring of the bladder interior and for the treatment of bladder disorders in which the disadvantages of the prior art devices are substantially reduced or eliminated.

SUMMARY OF THE INVENTION

The present invention provides a flexibly resilient body having a non-spherical shape, for insertion into an anatomical cavity such as a urinary bladder. The non-spherical shape may be formed, for example, by introducing one or more grooves or protrusions onto the surface of a sphere or by introducing a channel through a sphere. The body may be completely solid, or may contain a fluid in an interior lumen. The body is compressed prior to insertion and then allowed to expand after insertion in the cavity. In the case of a body configured to contain a fluid in a lumen, the body may be inserted into the cavity in a collapsed state with no fluid in the lumen. After insertion the body is expanded by introducing the fluid into the lumen. The body has a magnetizable portion allowing it to be positioned in an outlet of the cavity by means of a hand-held magnet placed in the vicinity of the cavity. The hand-held magnet is also used to rotate the body in the outlet of the cavity.

The body is used for the intermittent sealing of the outlet for preventing inappropriate release of fluid from the cavity. Sealing the outlet involves rotating the body in the outlet into a sealing orientation in which fluid is unable to flow around or through the body. Rotation of the body is done without displacing it from the outlet. Unsealing the outlet to allow voiding of the cavity involves rotating the body into a non-sealing orientation in which fluid flows around or

5

through the body. The body is preferably coated with a hydrophilic coating to reduce frictional forces between the body and the wall of the outlet in order to facilitate rotation of the body in the outlet.

The body may also be used for such purposes as, for example, delivery of drugs, imaging the cavity, and measuring intravesicular parameters such as pressure in the cavity or the composition of a body fluid in the cavity such as urine.

The invention is entirely confined to the cavity. As will become apparent in the description below, the body is easily inserted and removed. It may be left in the cavity for prolonged periods of time with minimal risk of encrusting or causing infections and is displaced within the cavity at will using a hand held magnet. The invention is comfortable for the patient and does not interfere with the daily activities of the patient including sitting, jogging, riding, or sexual intercourse.

In its first aspect the invention thus provides a resiliently flexible body having a magnetizable portion for use in medical procedures within an outlet of a cavity of an individual, the body having a non-spherical shape and configured to rotate within the outlet between a sealing orientation and a non-sealing orientation.

In its second aspect the invention thus provides a system for use in medical procedures within a cavity of an individual comprising a body of the specified type and one or more devices from the list comprising:

- (a) an applicator for inserting the body into the cavity or for removing the body from the cavity, the applicator fitted at an end thereof with a gripping device for releasably gripping the body; and
- (b) a rotating member comprising a magnetizable portion for rotating the body in an outlet of the cavity between the sealing orientation and the non-sealing orientation.

In its third aspect the invention thus provides a method for treating urinary incontinence in an individual comprising the steps of:

- (a) compressing a body of the specified type;
- (b) inserting the body into a urinary bladder outlet of the individual;
- (c) expanding the body in the urinary bladder outlet;
- (d) rotating the body within the urinary bladder outlet into a sealing position for sealing the urinary bladder outlet; and
- (e) rotating the body within the urinary bladder outlet into an unsealing position for voiding the urinary bladder.

In its fourth aspect the invention thus provides a method for releasing one or more substances into a cavity of an individual comprising the steps of:

- (a) loading the one or more substances into a body of the specified type, comprising a compartment containing the one or more substances;
- (b) compressing the body;
- (c) inserting the body into the cavity; and
- (d) expanding the body in the cavity.

In its fifth aspect the invention thus provides a method for monitoring the interior of a cavity of an individual comprising the steps of:

- (a) compressing a body of the specified type, comprising one or more devices for monitoring the cavity;
- (b) inserting the body into the cavity;
- (c) expanding the body in the cavity; and
- (d) transmitting signals from at least one of the monitoring devices to a receiver.

6

In its sixth aspect the invention thus provides a method for imaging the interior of a cavity of an individual comprising the steps of:

- (a) compressing a flexibly resilient body of the specified type, comprising a device for imaging the cavity;
- (b) inserting the body into the cavity;
- (c) expanding the body in the cavity; and
- (d) transmitting signals from the imaging device to a receiver.

In its seventh aspect the invention thus provides a method for releasing one or more substances into a cavity of an individual comprising the steps of:

- (a) providing a body of the specified type, comprising a pump fed by a reservoir;
- (b) loading the reservoir with the one or more substances;
- (c) inserting the body into the cavity; and
- (d) activating the pump so as to release the one or more substances into the cavity.

BRIEF DESCRIPTION OF THE DRAWINGS

In order to understand the invention and to see how it may be carried out in practice, a preferred embodiment will now be described, by way of non-limiting example only, with reference to the accompanying drawings, in which:

FIG. 1 shows a body in accordance with one embodiment of the invention;

FIG. 2 shows an applicator for inserting a body according to the invention into the urinary bladder of an individual;

FIG. 3 shows a body after having been inserted into a urinary bladder with an applicator;

FIG. 4 shows a retrieval device for retrieving a body;

FIG. 5 shows the retrieval device shown in FIG. 4 holding a body;

FIG. 6 shows use of a rotating member to rotate the body into a sealing orientation within the urinary bladder;

FIG. 7 shows use of a rotating member to rotate the body from a sealing orientation to a non-sealing orientation in the urinary bladder;

FIG. 8 shows use of an immobilizing member;

FIG. 9 shows other embodiments of the body in accordance with the invention.

FIG. 10 shows a body comprising an imaging device;

FIG. 11 shows a body comprising devices for measuring urinary bladder parameters;

FIG. 12 shows a body comprising a pump;

FIG. 13 shows various embodiments of the balloon according to the invention;

FIG. 14 shows a portion of a balloon according to the invention having a duck-bill valve;

FIG. 15 shows a portion of a balloon according to the invention having a ball valve;

FIG. 16 shows a balloon fitted after having been inserted into the bladder,

FIG. 17 shows a balloon filled before being inserted into the urinary bladder;

FIG. 18 shows a retrieval device for removing a balloon from the urinary bladder; and

FIG. 19 shows a body comprising one or more electrode pairs.

DETAILED DESCRIPTION OF SPECIFIC EMBODIMENTS

While the present invention will be described with reference to the urinary bladder, it should be understood that the

invention may be used with any anatomical cavity having an outlet through which a fluid leaves the cavity.

Reference is first made to FIG. 1 which shows an embodiment of the body in accordance with the invention. The body, generally designated as **100**, is shown in a three-dimensional perspective in FIG. 1*a*, and in cross-section in FIG. 1*b*. The body in this embodiment is formed by introducing a circumferential groove **105** into a sphere. The body **100** may be made of a resiliently flexible elastic biocompatible material. Alternatively the body **100** may be a balloon formed from a flexible material and having an interior lumen configured to contain a fluid. The body may be coated on its outer surface with a hydrophilic coating **110**. The body comprises a magnetizable portion. In the embodiment of the body **100** shown in FIG. 1, magnetizable portion consists of a metal rod **115** located in the interior of the body **100** and substantially perpendicular to the plane of the circumferential groove **105**.

The body may have one or more chambers **120** for storing one or more substances. Such substances could be, for example, drugs, antibiotics or radioactive substances, etc. After insertion of the body **100** into the lumen of the urinary bladder, the substances are released from the body **100** into the bladder in order to achieve a desired effect.

FIG. 2 shows an applicator **31** for inserting a solid body into the lumen of the urinary bladder of an individual. The applicator **31** consists of a slender cylindrical sheath **32** and a piston **33**. When the body **100** is initially loaded into applicator it is maintained in a compressed state at the distal end **32** of the applicator. As shown in FIG. 3, the distal end **32** of the applicator-body combination is inserted into the urethra until it reaches the lumen of the bladder. The body **100** is then released from the applicator by pushing the body **100** from applicator **31** with pushing piston **33**. The applicator is then removed from the bladder, leaving the body **100** in the bladder lumen **39**. Following its release from the applicator into the bladder, the body regains its initial shape.

FIG. 4 shows a retrieval device generally designated **51** for removing a solid body **100** from the bladder **39**. A catheter **52** has a slender shaft **53** in its lumen which has at its distal end a magnetizable portion **54** so as to engage a body **100** at the distal tip by means of the magnetizable portion **115** associated with the body **100**. As shown in FIG. 5, when probe **53** is then retracted, body **100** is deformed and brought into catheter **52**. The retrieval device is then withdrawn from the patient together with the body **100**.

Reference is now made to FIG. 13 which shows a body in accordance with the invention generally designated as **200**. The body **200** is a balloon having a wall **202** made of a flexible biocompatible material enclosing a lumen **204**. Balloon **200** comprises a magnetizable portion **115** in the form of a metal rod extending along a diameter of the balloon **200**. The lumen **204** of balloon **200** is configured to be filled with a biocompatible fluid, which may be presterilized such as air, water, saline or an oil such as liquid paraffin.

A self-sealing valve **205** in the wall of the balloon is used to fill the balloon. The valve **205** may be for example a duck-bill type valve as shown in FIG. 14 or a ball valve as shown in FIG. 15 in which a ball **208** may be in a sealing position (FIG. 15*a*) or an unsealing position (FIG. 15*b*). The canula **206** of a syringe **207** is inserted through the valve **205** into the lumen **204** of the balloon. The fluid injected into the lumen **204** causes the balloon to expand. After filling, the syringe needle **206** is withdrawn, and the valve **205** seals itself

As shown in FIG. 16, the balloon may first be inserted into the bladder by means of an applicator **220** to be described below in detail (FIG. 16*a*) and following its release from the applicator into the bladder, the balloon is then filled with fluid **224** from a syringe **207** (FIG. 16*b*). Alternatively, as shown in FIG. 17*a*, the balloon **200** may be filled and compressed before being inserted into the bladder by means of applicator **220**. The prefilled balloon is clutched by the flanges **223** which are initially kept closed by constraining sleeve **226** (FIG. 17*a*). After insertion of the applicator **220** with the prefilled balloon **200** into the urinary bladder, ring **225** is pulled as indicated by arrow **221** in FIG. 17*b* to urge the constraining sleeve **226** away from the flanges **223**, allowing flanges **223** to open and release the prefilled balloon **200** into the bladder.

FIG. 18 shows a retrieval device generally designated as **230** for removing the balloon **200** from the bladder. A catheter **227** has at its distal end **228** a magnetizable portion **229** so as to hold the balloon **200** at the distal tip **228** by means of the magnetizable portion **115** associated with the balloon **200**.

The retrieval device **230** is inserted into a full bladder. After opening the flanges **231** of the retrieval device, the engaging probe **232** with magnetizable portion **229** in its tip is inserted into the lumen of the full bladder so as to engage the magnetizable portion **115** of the balloon **200** and push the balloon into the lumen of the bladder. The probe **232** is then pulled so as to bring the balloon **200** into the grip of flanges **231** of the retrieval device. A piercer **233** is inserted into the balloon to drain the fluid contained in its lumen **204** into an attached syringe (not shown) or into the bladder lumen. The retrieval device **220** is then withdrawn from the bladder together with the deflated balloon **200**.

FIGS. 6 and 7 show use of a rotating member **61** used to position a body **100** having a magnetizable portion **115** within the outlet **65** of a urinary bladder in a female individual. Rotating member **61** is located outside the individual's body and comprises a magnetizable portion **63**. The rotating member is placed at a location on the surface, of the individual's body over the outlet **65** so as to position the body in the outlet **65**. Rotating the rotating member **61** around an axis **69** generally perpendicular to the surface of the individual's body, as indicated by arrow **66** causes the body **100** to rotate in the urinary bladder outlet **65**.

FIG. 6 shows use of a body **100** for sealing the urinary bladder outlet in a female subject. Rotating member **61** is placed over the urinary bladder **39** and is rotated. Due to the magnetizable portion **63** associated with rotating member **61** and the magnetizable portion **115** associated with body, the body is rotated into the sealing orientation within the bladder outlet **65**. In this orientation, the circumferential groove **105** lies in a plane perpendicular to the axis of the bladder outlet **65** indicated by the broken line **62**. The body **100** contacts the outlet wall, in an annular region **68** so that urine is unable to flow around the body **100**. As the amount of urine in the bladder increases, a hydrostatic pressure is exerted on the body further lodging it in the outlet **65** and reinforcing the seal. The invention is used similarly for sealing the urinary bladder outlet in male subjects

As seen in FIG. 7, in order to open the urinary bladder for voiding, rotating member **61** is placed over the urinary bladder **39** and is rotated. Due to the magnetizable portion **115** of the body, the body is rotated into the unsealing orientation. In this orientation, the circumferential groove **105** lies in a plane parallel to the bladder outlet axis **62**. The body now contacts the outlet wall in a region **78** consisting

of two separated circular arcs. This allows urine to flow through the circumferential groove **105** around the body **100** as indicated by arrow **73**. After voiding, the body **100** is rotated in the bladder outlet back to the sealing orientation by the rotating member **61** so as to seal the outlet again as shown in FIG. 6.

FIG. 8 shows use of an immobilizing member **81** comprising a magnetizable portion **82** affixed to the surface of the individual's body so as to maintain body **100** in the urinary bladder outlet **65**. Magnetizable portion **82** of immobilizing member **81** may be enclosed in a coating **83** so as to form, for example, a hygienic pad. The immobilizing member may be affixed to the surface by means of tape, or by pressure applied to it by the individual's underwear.

Reference is now made to FIG. 9 which shows several other embodiments of the body in accordance with the invention. These embodiments have components in common with the embodiment of FIG. 1 that have been indicated by the same numerals in both figures.

In the embodiment shown in three-dimensional perspective in FIG. 9a and in cross-section in FIG. 9b, the body generally indicated by **91** is formed by introducing a circumferential protrusion **910** onto a sphere. The body **91** is in a sealing orientation when the circumferential protrusion **910** lies in a plane perpendicular to the outlet axis **62**, and is in the non-sealing orientation when the circumferential protrusion **910** lies in a plane parallel to the outlet axis **62**.

In the embodiment shown in three-dimensional perspective in FIG. 9c and in cross-section in FIG. 9d, the body generally indicated by **92** is formed by introducing into a sphere a channel **920** extending along the entire length of a diameter of the sphere. The channel **920** is lined with a hollow cylindrically-shaped magnet **925**. The body **92** is in a sealing orientation when the channel **920** lies in a plane perpendicular to the outlet axis **62** and is in the non-sealing orientation when the channel **920** lies in a plane parallel to the outlet axis **62**.

In the embodiment shown in FIG. 9e in three-dimensional perspective and in FIG. 9f in cross-section, the body **93** is formed by introducing into a sphere a channel **930** extending along the entire length of a diameter of the sphere. A rod-shaped magnetizable portion **115** is located in the interior of hole **930** and is supported by several arms **935** that project from the wall **940** of the body **93** to the magnetizable portion **115**. The body **93** is in a sealing orientation when the hole **930** lies in a plane perpendicular to the outlet axis **62** and is in the non-sealing orientation when the hole **930** lies in a plane parallel to the outlet axis **62**.

In the embodiment shown in FIG. 9g in three-dimensional perspective and in FIG. 9h in cross-section, the body **94** has a generally tapered shape. The wide end **940** of the body **94** is a hemispherical surface. The body **94** is in a sealing orientation when the wide end **940** of the body **94** is in contact with the bladder wall in proximity to the bladder outlet. The body **94** is in a non-sealing orientation when the wide end **940** is distal to the bladder outlet.

In the embodiment shown in FIG. 9i and 9j the body **95** comprises a rod **950**. The rod **950** is hinged at one end to the interior of a hemispherical base **955** by means of a hinge **956**. The body **95** is in a sealing orientation when the rod **950** is perpendicular to the base **955** so that a hole **960** located in the base **955** is closed as shown in FIG. 9i. The body **95** is in a non-sealing orientation when rod **950** is rotated about the hinge **956** so that the hole **960** is open as shown in FIG. 9j.

In yet another embodiment of the body shown in FIG. 9k, and **91** and **9m**, a body **96** is formed by introducing four

grooves **962a**, **962b**, **962c** and **962d** onto the surface of a sphere. The body is shown in three-dimensional perspective in FIG. 9k. In FIG. 9l, the body **96** is shown in cross-section through a plane passing through the grooves **962a** and **962c**. A side view of the body **96** in FIG. 9m shows all four grooves **962a** to **962d**. Each of the four grooves **962a** to **962d** extend along about one quarter of a circumference of the sphere and they are all included in a single hemispherical surface **961** of the body **96** located to one side of the circumference indicated by the broken line **963**. When the hemispherical surface **961** containing the grooves **962a** to **962d** is in contact with the outlet wall, urine may flow around the body **96** through the grooves **962a** to **962d**. The body **96** is thus in a non-sealing orientation. When the hemispherical surface **964**, located on the opposite side of the circumference **963** is in contact with the outlet wall, the body **96** is in a sealing orientation.

FIG. 10 shows a body **100** constructed so as to comprise an imaging device such as a microvideo camera **119** for imaging the interior of the bladder. The video camera **119** may have associated with it a transmitter **110** for transmitting images to a remote receiver **111**. Such microvideo cameras and transmitters are known in the art, for example, as disclosed in U.S. Pat. Nos. 5,604,531, 5,579,781 and 5,188,109. The receiver **111** may be connected to a processing unit **112** for processing the images, or a display **113** for displaying images.

FIG. 11 shows a body **100** constructed so as to comprise one or more devices **214** for measuring one or more parameters associated with the urinary bladder, for example, bladder pressure, bladder volume, urine temperature, urine density, urine conductivity or urine composition. The measuring devices **214** may have associated with it a transmitter **215** for transmitting measurements to a remote receiver **216**. The receiver may be connected to a processing unit **217** for processing the measurements or to a display **218** for displaying results. Such measuring devices are known in the art, for example as disclosed in U.S. Pat. Nos. 5,579,781 and 5,188,109.

FIG. 12 shows a body **100** comprising a pump **120** for the controlled release of one or more substances into the bladder. The pump **120** has a reservoir **121** for storing the substances. The pump **120** may have a receiver **122** for receiving signals from a remote control **123**. The rate of release of the substance may thus be varied at will using the remote control. Such flow controllers are known in the art, for example, as disclosed in U.S. Pat. Nos. 5,593,134 and 5,996,954.

FIG. 19 shows a body **100** constructed so as to comprise one or more electrode pairs **814** on its surface for use in stimulating a hypotonic urinary bladder. The electrode pairs are part of a circuit that includes a battery **815** and a remote controlled switch **816**. A receiver **822** in the switch receives signals from a remote control **823** that is used to open and close the switch **816**. When the switch **816** is closed a voltage is applied across the electrode pairs **814**. When the electrodes are in contact with the wall of the urinary bladder **39**, for example, the region **68** in FIG. 6, and a voltage is applied across the electrode muscle fibers in the bladder wall are stimulated to contract.

The invention has been described with a certain degree of particularity only for the sake of clarity. However, several variations and modifications in the invention are possible without exceeding the scope and spirit of the invention as defined in the following set of claims.

What is claimed is:

1. A resiliently flexible body having a magnetizable portion for use in medical procedures within an outlet of a cavity of an individual, the body having a non-spherical shape and configured to rotate within the outlet between a sealing orientation and a non-sealing orientation.

2. The body according to claim 1, having a spherical surface with one or more grooves therein.

3. The body according to claim 1, having a spherical surface with a circumferential protrusion.

4. The body according to claim 1, having a spherical surface and a channel extending along the length of a diameter of the body.

5. The body according to claim 1, having a tapered shape.

6. The body according to claim 1, comprising a base having a hole, and a plug configured to rotate between an orientation in which the hole is open and an orientation in which the hole is closed.

7. The body according to claim 1 wherein the body is coated on at least a portion of an outer surface with a hydrophilic coating.

8. The body according to claim 1 wherein the body is capable of storing one or more compounds and releasing them into the urinary bladder.

9. The body according to claim 8, wherein at least one substance is selected from the group consisting of antibiotics, anti-microbial agents, drugs, radioactive substances, contrast agents, and substances having a local or systemic effect on cells or tissues of the individual.

10. The body according to claim 1, wherein the cavity is a urinary bladder.

11. The body according to claim 1, having a solid wall and a lumen containing a fluid.

12. The body according to claim 1, having associated with it an imaging device for imaging the cavity.

13. The body according to claim 1, having associated with it a measuring device for measuring a parameter of the cavity.

14. The body according to claim 13, wherein the measuring device measures a parameter selected from the group consisting;

- (a) a pressure in the cavity;
- (b) a volume of the cavity;
- (c) a temperature of a fluid in the cavity;
- (d) a density of a fluid in the cavity;
- (e) a conductivity of a fluid in the cavity; and
- (f) the composition of a fluid in the cavity.

15. The body according to claim 1, having associated with it a pump for storing and releasing substances into the cavity.

16. The body according to claim 1, having associated with it an electrode pair configured to apply an electrical stimulus to a wall of the cavity.

17. A method of activating a wall of a hypotnic cavity comprising steps of:

- (a) compressing a body according to claim 16;
- (b) inserting the body into the cavity;
- (c) expanding the body in the cavity;
- (d) activating an electrode pair associated with the body using a remote control.

18. A system for use in medical procedures within a cavity of an individual comprising a body according to claim 1, and one or more devices selected from the group consisting:

- (a) an applicator for inserting the body into the cavity or for removing the body from the cavity, the applicator fitted at an end thereof with a gripping device for releasably gripping the body; and

(b) a rotating member comprising a magnetizable portion for rotating the body in an outlet of the cavity between the sealing orientation and the non-sealing orientation.

19. The system according to claim 18, wherein the cavity is a urinary bladder.

20. The system according to claim 18 wherein the body comprises a device which can emit or absorb a signal detectable by an apparatus for imaging the cavity.

21. The system according to claim 20, wherein said device further comprises a transmitter transmitting signals to a receiver.

22. The system according to claim 21 further comprising a receiver receiving signals from the transmitter.

23. The system according to claim 22 further comprising one or more components selected from the list consisting:

- (a) a processing unit processing signals received by the receiver;
- (b) a display for displaying signals received by the receiver;
- (c) a display for displaying an output produced by the processing unit.

24. The system according to claim 21 for use in imaging the cavity.

25. The system according to claim 18, wherein the body comprises one or more monitoring devices for sampling a morphological or physiological parameter of the cavity and for emitting a signal indicative of a quality or quantity of a sampled parameter.

26. The system according to claim 25, wherein at least one of the devices monitors a parameter of the cavity selected from the group consisting of pressure, temperature, fluid density, fluid conductivity, and fluid composition.

27. The system according to claim 26, wherein the fluid is urine.

28. The system according to claim 26 wherein the immobilizing member is in the form of a hygienic pad adapted to be placed in the individual's underwear.

29. The system according to claim 25, further comprising a transmitter transmitting signals from a monitoring device to a receiver.

30. The system according to claim 29 further comprising a receiver receiving signals from the transmitter.

31. The system according to claim 30, further comprising one or more components selected from the list consisting:

- (a) a processing unit processing signals received by the receiver;
- (b) a display for displaying signals received by the receiver;
- (c) a display for displaying an output produced by the processing unit.

32. The system according to claim 25 for monitoring the cavity.

33. The system according to claim 18 further comprising an immobilizing member comprising a magnetizable portion, the immobilizing member being fitted for securing onto the individual's body for immobilizing the body in the outlet.

34. The system according to claim 18 for use in the treatment of a disorder selected from the group consisting of urinary incontinence, urinary bladder infections, urinary bladder tumors, and bladder dysfunction.

35. The system of claim 18 wherein the gripping device comprises a magnetizable portion for securing the body thereto during application by means of a magnetic interaction.

36. The system according to claim 18, wherein the body has associated with it electrodes configured to apply an

13

electrical stimulus to a wall of the cavity, the system further comprising a remote control for activating the deactivating the electrodes.

37. The system according to claim 36 for use in activating a wall of a hypotonic cavity.

38. The system according to claim 18 for releasing one or more substances in the cavity.

39. A method for treating urinary incontinence in an individual comprising the steps of:

- (a) compressing a body, according to claim 1;
- (b) inserting the body into a urinary bladder outlet of the individual;
- (c) expanding the body in the urinary bladder outlet;
- (d) rotating the body within the urinary bladder outlet into a sealing position for sealing the urinary bladder outlet; and
- (e) rotating the body within the urinary bladder outlet into an unsealing position for voiding the bladder.

40. The method according to claim 39 wherein the body is coated on its outer surface with a hydrophilic coating.

41. A method for releasing one or more substances into the cavity of an individual comprising the steps of:

- (a) loading the one or more substances into a solid, flexibly resilient body according to claim 1;
- (b) compressing the body;
- (c) inserting the body into the cavity; and
- (d) expanding the body in the cavity.

42. The method of claim 41 wherein one or more of the one or more substances are selected from the list consisting of antibiotics, anti-microbial agents, drugs, radioactive substances, contrast agents, and substances having a local or systemic effect on cells or tissues of the individual.

43. The method of claim 41, wherein the cavity is a urinary bladder.

44. A method for monitoring the interior of the cavity of an individual comprising the steps of:

- (a) compressing a body according to claim 1, comprising one or more devices for monitoring the cavity;
- (b) inserting the body into the cavity;
- (c) expanding the body in the cavity; and
- (d) transmitting signals from at least one of the monitoring devices to a receiver.

14

45. The method of claim 44, further comprising one or more steps selected from the list comprising:

- (a) storing the signals in a computer memory;
- (b) displaying the signals on a display;
- (c) processing the signals in a computer processing unit;
- (d) storing results of the processing in a computer memory; and
- (e) displaying results of the processing on a display.

46. The method of claim 44, wherein the cavity is a urinary bladder.

47. A method for imaging the interior of the cavity of an individual comprising the steps of:

- (a) compressing a body according to claim 1, comprising a device for imaging the cavity;
- (b) inserting the body into the cavity;
- (c) expanding the body in the cavity; and
- (d) transmitting signals from the imaging device to a receiver.

48. The method of claim 47, further comprising one or more steps selected from the list comprising:

- (a) storing the signals in a computer memory;
- (b) displaying the signals on a display;
- (c) processing the signals in a computer processing unit;
- (d) storing results of the processing in a computer memory; and
- (e) displaying results of the processing on a display.

49. The method of claim 47, wherein the cavity is a urinary bladder.

50. A method for releasing one or more substances into the cavity of an individual comprising steps of.

- (a) providing a body according to claim 1, comprising a pump fed by a reservoir;
- (b) loading the reservoir with the one or more substances;
- (c) inserting the body into the cavity; and
- (d) activating the pump so as to release the one or more substances into the cavity.

51. The method according to claim 50, wherein the pump is activated by a remote control.

52. The method of claim 50, wherein the cavity is a urinary bladder.

* * * * *

专利名称(译)	囊泡内装置		
公开(公告)号	US6398718	公开(公告)日	2002-06-04
申请号	US09/594641	申请日	2000-06-15
[标]申请(专利权)人(译)	英诺威讯有限公司		
申请(专利权)人(译)	INNOVENTIONS INC.		
当前申请(专利权)人(译)	INNOVENTIONS INC.		
[标]发明人	YACHIA DANIEL HIRSZOWICZ ERAN		
发明人	YACHIA, DANIEL HIRSZOWICZ, ERAN		
IPC分类号	A61F2/00 A61B5/00 A61B5/20 A61B5/03 A61M37/00		
CPC分类号	A61B5/0031 A61B5/14507 A61B5/201 A61B5/204 A61B5/205 A61B5/6874 A61F2/0022 A61F2/0027 A61B1/00147 A61M2210/1085 A61B5/036 A61F2210/0095 A61F2250/0067 A61M2209/04 A61B1/041		
代理机构(译)	LADAS & PARRY		
外部链接	Espacenet USPTO		

摘要(译)

一种弹性柔性主体，具有非球形形状并具有可磁化部分，用于密封诸如膀胱的解剖学腔。将主体压缩，然后插入空腔。在腔体中，对体进行实验并将其定位在腔体出口处。使用手持磁铁在出口处使主体在出口被密封的密封方向和非密封方向之间旋转，在该非密封方向中诸如尿液的流体可以流出空腔。

