



US010321850B2

(12) **United States Patent**
Forsell

(10) **Patent No.:** **US 10,321,850 B2**
(45) **Date of Patent:** ***Jun. 18, 2019**

(54) **DEVICE FOR TREATMENT OF ANEURYSM**

(76) Inventor: **Peter Forsell**, Zug (CH)

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 777 days.

This patent is subject to a terminal disclaimer.

(21) Appl. No.: **12/682,462**

(22) PCT Filed: **Oct. 10, 2008**

(86) PCT No.: **PCT/SE2008/000574**

§ 371 (c)(1),

(2), (4) Date: **Apr. 9, 2010**

(87) PCT Pub. No.: **WO2009/048385**

PCT Pub. Date: **Apr. 16, 2009**

(65) **Prior Publication Data**

US 2010/0211091 A1 Aug. 19, 2010

Related U.S. Application Data

(60) Provisional application No. 60/960,715, filed on Oct. 11, 2007, provisional application No. 60/960,716, filed on Oct. 11, 2007.

(51) **Int. Cl.**

A61M 29/00 (2006.01)

A61B 5/07 (2006.01)

(Continued)

(52) **U.S. Cl.**

CPC **A61B 5/076** (2013.01); **A61B 5/02007** (2013.01); **A61B 5/4393** (2013.01); **A61B 5/6862** (2013.01); **A61B 5/6876** (2013.01); **A61B 5/6885** (2013.01); **A61B 17/12009** (2013.01); **A61B 17/1355** (2013.01); **A61B**

2017/00221 (2013.01); **A61B 2017/00411** (2013.01); **A61B 2017/00703** (2013.01); **A61B 2017/00734** (2013.01); **A61B 2090/065** (2016.02); **A61B 2562/0247** (2013.01); **A61B 2562/0261** (2013.01);

(Continued)

(58) **Field of Classification Search**

CPC **A61M 1/10**; **A61M 1/12**; **A61M 1/125**

USPC **606/194, 201**; **600/16, 17, 18**

See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

4,256,094 A * 3/1981 Kapp et al. 601/152

5,741,283 A 4/1998 Fahy

(Continued)

FOREIGN PATENT DOCUMENTS

WO WO 9919010 A1 * 4/1999

WO WO 01/12108 2/2001

(Continued)

OTHER PUBLICATIONS

International Search Report for PCT/SE2008/000574, dated Jan. 28, 2009.


(Continued)

Primary Examiner — Diane D Yabut

(57) **ABSTRACT**

In a system, device and method for treating an aneurysm of a human or mammal patient an implantable member adapted to hold fluid is provided. The member is adapted to be placed in connection with a blood vessel having the aneurysm and to exercise a pressure on the aneurysm of said blood vessel.

27 Claims, 16 Drawing Sheets



(51)	Int. Cl.		6,579,301 B1 *	6/2003	Bales et al.	606/191
	<i>A61B 5/02</i>	(2006.01)	6,745,077 B1	6/2004	Griffith	
	<i>A61B 5/00</i>	(2006.01)	7,587,247 B2 *	9/2009	Schaer et al.	607/129
	<i>A61B 17/12</i>	(2006.01)	2003/0060893 A1 *	3/2003	Forsell	623/23.65
	<i>A61B 17/135</i>	(2006.01)	2003/0233023 A1 *	12/2003	Khaghani et al.	600/18
	<i>A61M 1/10</i>	(2006.01)	2005/0266042 A1	12/2005	Tseng	
	<i>A61M 1/12</i>	(2006.01)	2006/0281966 A1 *	12/2006	Peacock, III	600/37
	<i>A61B 17/00</i>	(2006.01)	2007/0100368 A1 *	5/2007	Quijano et al.	606/192
	<i>A61F 2/30</i>	(2006.01)				
	<i>A61B 90/00</i>	(2016.01)				

FOREIGN PATENT DOCUMENTS

(52)	U.S. Cl.	
	CPC	<i>A61F 2002/3067</i> (2013.01); <i>A61F 2002/30668</i> (2013.01); <i>A61F 2250/0001</i> (2013.01); <i>A61F 2250/0002</i> (2013.01); <i>A61M 1/10</i> (2013.01); <i>A61M 1/12</i> (2013.01); <i>A61M 1/125</i> (2014.02)

WO	WO 0154615	8/2001	
WO	WO 2005/084730	9/2005	
WO	WO 2005084730 A1 *	9/2005 A61M 1/12
WO	2006039555 A1	4/2006	

OTHER PUBLICATIONS

Written Opinion of the International Searching Authority for PCT/SE2008/000574, dated Jan. 28, 2009.

(56) **References Cited**

U.S. PATENT DOCUMENTS

6,030,336 A *	2/2000	Franchi	600/18
6,050,932 A *	4/2000	Franchi	600/16

* cited by examiner

Fig. 1




Fig. 2




Fig. 3




Fig. 4




Fig. 5




Fig. 6




Fig. 7




Fig. 8




Fig. 9




Fig. 10




Fig. 11




Fig.12




Fig.13




Fig.14




Fig.15






Fig.16











Fig.25




Fig.26




Fig.27




Fig.28




Fig.29




Fig.30




Fig.31




Fig.32




Fig.33




Fig.34




Fig.35




Fig.36




Fig.37




Fig.38




Fig.39




Fig.40a




Fig.40b




Fig.40c




Fig.41




Fig.42a




Fig.42b





Fig.42c



DEVICE FOR TREATMENT OF ANEURYSM

This application is the U.S. national phase of International Application No. PCT/SE2008/000574 filed 10 Oct. 2008, which designated the U.S. and claims the benefit of U.S. Provisional Appln. No. 60/960,715 filed 11 Oct. 2007, and U.S. Provisional Appln. No. 60/960,716 filed 11 Oct. 2007, the entire contents of each of which are hereby incorporated by reference.

TECHNICAL FIELD

The present invention relates to a method and a device for treating a vascular aneurysm of a human or mammal patient.

BACKGROUND

An aneurysm (or aneurism) is a localized, blood-filled dilation (balloon-like bulge) of a blood vessel caused by disease or weakening of the vessel wall. Aneurysms most commonly occur in arteries at the base of the brain (the circle of Willis) and in the aorta (the main artery coming out of the heart), a so-called aortic aneurysm. The bulge in a blood vessel can burst and lead to death at any time. The larger an aneurysm becomes, the more likely it is to burst and since aneurysms naturally grow, given enough time they will inevitably reach the bursting point if undetected.

Given the severe consequences of an aneurysm screening is now commonly performed in order to early detect the presence of an aneurism. In case of an aortic aneurism the blood-filled dilation is commonly located in the abdomen close to the Y-bifurcation extending to the legs. At this location the aorta is typically about 2.5 centimeters wide, which can be measured for example using ultra-sonic or X-ray based measuring devices.

Existing treatment when detecting an aortic aneurysm includes implantation of a stent around the vessel using open surgery. An alternative surgical procedure is to implant a tube from the groin an guide the stent via arteria femoralis into position where the blood flow can by-pass the aortic aneurysm via the tube. The latter treatment has the drawback that an embolism easily is formed when introducing alien material into the bloodstream.

Hence, there exists a need for a treatment of aortic aneurysm that is more robust and which brings about fewer complications.

SUMMARY

It is an object of the present invention to overcome or at least reduce some of the problems associated with treatment and monitoring of an aneurysm.

This object and others are obtained by the method, system and device as set out in the appended claims. Thus, by providing a member around the aneurysm, the aneurysm can be treated and monitored.

In accordance with one embodiment a device comprising an implantable member adapted to hold fluid is provided. The member is adapted to be placed in connection with a blood vessel having the aneurysm and to exercise a pressure on the aneurysm. Hereby the aneurysm can be prevented from bursting.

In accordance with one embodiment the device is adapted to prevent or reduce an expansion of said aneurysm.

In accordance with one embodiment the device is adapted to be postoperatively adjusted.

In accordance with one embodiment the device is adapted to perform self adjustments of the pressure applied onto said aneurysm within a predetermined treatment interval.

In accordance with one embodiment the device can also comprise a control unit and a sensor. The control unit is then adapted to control pressure adjustments of based on a signal generated by the sensor.

In accordance with one embodiment the device can also comprise a pressure regulator adapted to regulate the pressure in the member.

In accordance with one embodiment the implantable member can be Y-shaped and adapted to be placed at the Aorta Bifurcation

In accordance with one embodiment the device can be configured to apply a pressure that is equal or less than the diastolic blood pressure of a treated patient.

In accordance with one embodiment the device can be adapted to increase the pressure on the blood vessel when the aneurysm expands.

In accordance with one embodiment the device can also comprise a sensor for sensing an expansion of the aneurysm.

In accordance with one embodiment the device can also comprise an electrical pulse generator adapted to provide electrical signals for stimulation of the aneurysm wall via electrodes located on the inside of the implantable member.

In a preferred embodiment, the system comprises at least one switch implantable in the patient for manually and non-invasively controlling the device.

In another preferred embodiment, the system comprises a wireless remote control for non-invasively controlling the device.

In a preferred embodiment, the system comprises a hydraulic operation device for operating the device.

In one embodiment, the system comprises comprising a motor or a pump for operating the device.

The invention also extends to methods for implanting the device and to a computer program product adapted to control the device.

Any feature in any of the four combinations of features in the combination embodiments described below may be used in any combination and furthermore in combination with any other feature or embodiment described in any of the other figures or figure text or descriptions in this application.

First Combination Embodiments Includes Electrical Stimulation Comprising:

A medical device including a stimulation device for treating a vascular aneurysm of a human or mammal patient comprising:

at least one implantable electrode adapted to placed in close connection to the aneurysm, the at least one electrode being adapted to provide an electrical stimulation pulse on a wall portion of the aneurysm.

At least one electrode is adapted to stimulate multiple stimulation points. Alternatively at least two electrodes are provided and wherein groups of stimulation points are controllable to be individually stimulated.

A pulse generator adapted to generate positive and negative electrical stimulation pulses.

Electrical stimulation pulses, which may have a constant current and preferable the stimulation device deliver the electrical stimulation pulse as pulse train stimulation with breaks to allow the vessel to rest.

A stimulation device that deliver the electrical stimulation pulses at different time intervals.

A device preferable delivering the electrical stimulation pulse as a pulse width modulated stimulation pulse.

A stimulation device preferable deliver the electrical stimulation pulse during the systolic phase.

A stimulation device further comprising a monitoring system for detecting an expansion of the aneurysm. Also to avoid any fast expansion and burst leading to death.

If so said monitoring system may increase intensity and or position of the stimulation, when detecting an expansion of the aneurysm.

A method of treating an aneurysm of a mammal patient by providing the medical device according to any feature disclosed herein, comprising the steps of:

inserting a needle or a tube like instrument into the patient's abdominal cavity,

using the needle or tube like instrument to fill a part of the patient's body with gas and thereby expanding said abdominal cavity,

placing at least two laparoscopic trocars in said cavity, inserting a camera through one of the laparoscopic trocars into said cavity,

inserting at least one dissecting tool through one of said at least two laparoscopic trocars,

dissecting an area of an aneurysm of a blood vessel, placing said medical device, comprising a stimulation device, onto said the aneurysmic blood vessel, and stimulating said aneurysm to increase the tonus of the aneurysm wall.

An alternative method of treating an aneurysm of a mammal patient by providing the medical device including any feature disclosed herein, comprising the steps of:

inserting a needle or a tube like instrument into the patient's thoraxial cavity,

using the needle or tube like instrument to fill a part of the patient's body with gas and thereby expanding said thoraxial cavity,

placing at least two laparoscopic trocars in said cavity, inserting a camera through one of the laparoscopic trocars into said cavity,

inserting at least one dissecting tool through one of said at least two laparoscopic trocars, dissecting an area of an aneurysm of a blood vessel,

placing said medical device, comprising a stimulation device, onto said the aneurysmic blood vessel, and stimulating said aneurysm to increase the tonus of the aneurysm wall.

An alternative method of treating an aneurysm of a mammal patient by providing the medical device including any feature disclosed herein, said method comprising the steps of:

cutting the skin in the abdominal or thoraxial wall of said mammal patient,

dissecting an area of the aneurysm, placing said medical device, comprising a stimulation device, onto said aneurysm, and

stimulating said aneurysm to increase the tonus of the aneurysm wall.

A method of treating an aneurysm of a mammal patient by providing the medical device including any feature disclosed herein, said method comprising the steps of:

cutting the skin of said mammal patient, dissecting an area of the aneurysm,

placing said medical device, comprising a stimulation device, onto said aneurysm, and

stimulating said aneurysm to increase the tonus of the aneurysm wall.

Additionally a computer program product comprising computer program segments that when executed on a computer causes the computer to generate a pattern of signals for

an implantable electrode adapted to placed in close connection to an aneurysm, the at least one electrode being adapted to provide an electrical stimulation pulse on a wall portion of the aneurysm.

A device including a digital storage medium comprising the computer program product.

Second Combination Embodiments Includes a Hydraulic System Putting Pressure on the Aneurysm Comprising:

A device for treating an aneurysm of a human or mammal patient comprising:

An implantable member adapted to hold fluid, wherein said member is adapted to be placed in connection with a blood vessel having the aneurysm, the member being adapted to exercise a pressure on the aneurysm of said blood vessel.

A device preferable adapted to prevent or reduce an expansion of said aneurysm.

A device adapted to be postoperatively adjusted. The device is normally non-invasively adjustable.

A device preferable adapted to perform self adjustments of the pressure applied onto said aneurysm within a predetermined treatment interval.

A device normally comprising a control unit and a sensor, the control unit being adapted to control pressure adjustments of based on a signal generated by the sensor.

The sensor may comprise any type of sensor. Preferable a pressure regulator is adapted to regulate the pressure in the member, wherein the pressure regulator preferable is adapted to even out the difference in pressure in the implantable member during the systolic and diastolic phase for reducing the pressure difference or providing a substantially even outside pressure on the aneurysm. The pressure regulator may comprise pressure tank.

An implantable member which is alternatively Y-shaped, wherein the implantable Y-shaped member normally is adapted to be placed at the Aorta Bifurcation

A pressure regulator in one embodiment comprises an expandable first reservoir.

The expandable first reservoir preferable is spring loaded.

A device wherein the pressure regulator in a preferred embodiment comprises a pump.

A device further comprising a second reservoir and a pump adapted to move liquid between the first and second reservoirs.

A device wherein preferable said first reservoir has a predetermined optimal pressure regulation volume treatment interval and wherein said pump is adapted to pump liquid from the first to the second reservoir to keep said first reservoir within said regulation interval, when said aneurysm expands and to pump liquid from said implantable member into said first reservoir.

A device preferable provides a pressure equal or less than the diastolic blood pressure of a treated patient.

A device preferable adapted to increase the pressure on the blood vessel when the aneurysm expands.

A device comprising a control device adapted to increase the pressure on the blood vessel when the aneurysm expands more than a predetermined value, preferable during a time period.

A control unit adapted to control the expansion of said aneurysm by controlling the pressure applied on the blood vessel when the aneurysm expands.

A device preferable further comprising a sensor for sensing an expansion of the aneurysm.

A device preferable further comprising a volume control unit adapted to directly or indirectly control the volume in the implantable member based on a signal generated by the

sensor for controlling an expansion of the aneurysm, wherein normally said volume control unit controls the volume in the implantable member based on a signal indicative of: flow of fluid from said implantable member or pressure in said fluid filled in said implantable member.

A device wherein the implantable member is divided into a plurality of sub-reservoirs.

A device wherein the sub-reservoirs are provided axially along the blood vessel or radially along the blood vessel.

A device wherein preferable at least one reservoir is located above said aneurysm and one reservoir is located below said aneurysm.

A device further comprising a logic circuitry for determining when the aneurysm is expanding based on the signal from the sensor.

A device further comprising an electrical pulse generator adapted to provide electrical signals for stimulation of the aneurysm wall via electrodes located on the inside of the implantable member.

A control unit adapted to vary to position of the electrical stimulation signals for stimulation of the aneurysm.

A method of treating an aneurysm of a mammal patient by providing the medical device according to any feature disclosed herein, comprising the steps of:

inserting a needle or a tube like instrument into the patient's abdominal cavity,

using the needle or tube like instrument to fill a part of the patient's body with gas and thereby expanding said abdominal cavity,

placing at least two laparoscopic trocars in said cavity, inserting a camera through one of the laparoscopic trocars into said cavity,

inserting at least one dissecting tool through one of said at least two laparoscopic trocars,

dissecting an area of an aneurysm of a blood vessel,

placing the device onto said the aneurysmic blood vessel, and adjusting the pressure the device exerts onto said aneurysm.

An alternative method of treating an aneurysm of a mammal patient by providing the medical device including any feature disclosed herein, comprising the steps of:

inserting a needle or a tube like instrument into the patient's thoraxial cavity,

using the needle or tube like instrument to fill a part of the patient's body with gas and thereby expanding said thoraxial cavity,

placing at least two laparoscopic trocars in said cavity, inserting a camera through one of the laparoscopic trocars into said cavity,

inserting at least one dissecting tool through one of said at least two laparoscopic trocars,

dissecting an area of an aneurysm of a blood vessel,

placing the device onto said the aneurysmic blood vessel, and

adjusting the pressure said device exerts onto said aneurysm.

An alternative method of treating an aneurysm of a mammal patient by providing the medical device including any feature disclosed herein, said method comprising the steps of:

cutting the skin in the abdominal or thoraxial wall of said mammal patient, dissecting an area of the aneurysm,

placing said device onto said aneurysm, and

starting the stimulation device and adapted to adjust any parameter related to said stimulation.

adjusting the pressure said device exerts onto said aneurysm.

adjusting the pressure said device exerts onto said aneurysm.

A computer program product comprising computer program segments that when executed on a computer causes the computer to control the pressure applied by an implantable member adapted to hold fluid and adapted to be placed in connection with a blood vessel having an aneurysm. A digital storage medium comprising the computer program product.

Third Combination Embodiments Includes a Mechanical System Putting Pressure on the Aneurysm Including Any Feature in Any Combination, Comprising:

A device for treating a vascular aneurysm of a human or mammal patient comprising:

15 An implantable member adapted to be placed in connection with a blood vessel having an aneurysm for providing a pressure from outside the blood vessel, the device being adapted to be adjusted postoperatively.

A device preferable adapted to prevent or reduce an expansion of said aneurysm.

A device adapted to monitor an expansion of said aneurysm.

The device is preferable adjustable non-invasively.

A device adapted to perform self adjustments of the pressure applied onto said aneurysm within a predetermined treatment interval.

A device comprising an control unit and a sensor, wherein the control unit is adapted to control the pressure applied onto said aneurysm based on said signal generated by the sensor.

A device, wherein the surface of the member facing the blood vessel is adapted to exercise pressure on the blood vessel.

A device, wherein the pressure on the blood vessel is mechanically exercised.

A, wherein the mechanically exercised pressure is controlled hydraulically.

A device, wherein mechanical pressure on the blood vessel is directly or indirectly exercised by a motor or a pump.

A, wherein the implantable member is generally cylindrical

A device, wherein the implantable member comprises a number of segments being individually adjustable.

A device, wherein the implantable member is a Y-shaped member

A device, wherein the implantable Y-shaped member is adapted to be placed at the Aorta Bifurcation.

A pressure regulating system adapted to even out the difference in pressure in the implantable reservoir in the systolic and diastolic phase to reduce the differences or to achieve a substantially even pressure affecting said aneurysm from the outside of said blood vessel.

A device, wherein the implantable member is an elastic member.

A device, wherein the elastic member is a band.

A device, wherein the elastic member is adapted to apply a pressure onto said aneurysm and has an expansion interval wherein the pressure applied is substantially constant or within an interval for treating and reducing expansion of the aneurysm.

A device, wherein the implantable member is spring loaded.

A device according to claim 1, wherein the implantable member is hydraulically operated.

A device, wherein the implantable member is pneumatically operated

A device, wherein the implantable member is adapted to exert an essentially constant pressure or a pressure reducing the pressure difference, caused by the changes in blood pressure in said blood vessel, on the aneurysm.

A device, wherein the provided pressure is equal or less than the diastolic blood pressure of a treated patient.

A device further comprising a control unit adapted to increase the pressure on the blood vessel when the aneurysm expands.

A device comprising a control device adapted to increase the pressure on the blood vessel when the aneurysm expands more than a predetermined value.

A device comprising a control device adapted to increase the pressure on the blood vessel when the aneurysm expands more than a predetermined value during a time period.

A device, further comprising a sensor or a measuring device for sensing an expansion of the aneurysm.

A device, further comprising logic circuitry for determining when the aneurysm is expanding based on a signal from a sensor or measuring device.

A device, further comprising an electrical pulse generator adapted to provide stimulation of the aneurysm wall via electrodes located on the inside of the implantable member.

A method of treating an aneurysm of a mammal patient by providing the medical device according to any feature disclosed herein, comprising the steps of:

inserting a needle or a tube like instrument into the patient's abdominal cavity,

using the needle or tube like instrument to fill a part of the patient's body with gas and thereby expanding said abdominal cavity,

placing at least two laparoscopic trocars in said cavity, inserting a camera through one of the laparoscopic trocars into said cavity,

inserting at least one dissecting tool through one of said at least two laparoscopic trocars,

dissecting an area of an aneurysm of a blood vessel, placing the device onto said the aneurysmic blood vessel, and adjusting the pressure the device exerts onto said aneurysm.

An alternative method of treating an aneurysm of a mammal patient by providing the medical device including any feature disclosed herein, comprising the steps of:

inserting a needle or a tube like instrument into the patient's thoraxial cavity,

using the needle or tube like instrument to fill a part of the patient's body with gas and thereby expanding said thoraxial cavity,

placing at least two laparoscopic trocars in said cavity, inserting a camera through one of the laparoscopic trocars into said cavity,

inserting at least one dissecting tool through one of said at least two laparoscopic trocars,

dissecting an area of an aneurysm of a blood vessel, placing the device onto said the aneurysmic blood vessel, and

adjusting the pressure said device exerts onto said aneurysm.

An alternative method of treating an aneurysm of a mammal patient by providing the medical device including any feature disclosed herein, said method comprising the steps of:

cutting the skin in the abdominal or thoraxial wall of said mammal patient,

dissecting an area of the aneurysm,

placing said device onto said aneurysm, and

starting the stimulation device and adapted to adjust any parameter related to said stimulation.

adjusting the pressure said device exerts onto said aneurysm.

adjusting the pressure said device exerts onto said aneurysm.

A computer program product comprising computer program segments that when executed on a computer causes the computer to control the pressure applied by an implantable member adapted to be placed in connection with a blood vessel having an aneurysm.

A digital storage medium comprising the computer program product.

Fourth Combination Embodiments Includes a Monitoring/Sensor System Putting Pressure on the Aneurysm Including Any Feature in Any Combination, Comprising:

A device for monitoring an aneurysm of a human or mammal patient comprising:

A sensor placed in relation to a wall portion of the aneurysm for generating, a signal corresponding to a parameter related to the aneurysm or the treatment of the aneurysm.

A device, wherein the parameter corresponds to the size of the aneurysm.

A device, wherein the parameter corresponds to the diameter of the aneurysm.

A device wherein the sensor is a gauge sensor.

A device wherein the parameter corresponds to a pressure.

A device wherein the pressure corresponds to a pressure from a hydraulic cuff provided around the aneurysm.

A device wherein the pressure corresponds to a pressure from a mechanical implantable member provided around the aneurysm.

A device wherein the pressure corresponds to a pressure in a blood vessel.

A device wherein the sensor is adapted to measure the pressure exerted on an implantable member provided around the aneurysm.

A device wherein the sensor is adapted to measure the volume of a hydraulic implantable member.

A method of treating an aneurysm of a mammal patient by providing the medical device, comprising the steps of inserting a needle or a tube like instrument into the patient's abdominal cavity,

using the needle or tube like instrument to fill a part of the patient's body with gas and thereby expanding said abdominal cavity,

placing at least two laparoscopic trocars in said cavity, inserting a camera through one of the laparoscopic trocars into said cavity,

inserting at least one dissecting tool through one of said at least two laparoscopic trocars,

dissecting an area of an aneurysm of a blood vessel, placing the device onto said the aneurysmic blood vessel,

and monitoring the expansion of the aneurysm by measuring the expansion the aneurysm exerts onto the device.

A method of treating an aneurysm of a mammal patient by providing the medical device, comprising the steps of:

inserting a needle or a tube like instrument into the patient's thoraxial cavity,

using the needle or tube like instrument to fill a part of the patient's body with gas and thereby expanding said thoraxial cavity,

placing at least two laparoscopic trocars in said cavity, inserting a camera through one of the laparoscopic trocars into said cavity,

inserting at least one dissecting tool through one of said at least two laparoscopic trocars,
 dissecting an area of an aneurysm of a blood vessel,
 placing the device onto said the aneurysmic blood vessel,
 and

monitoring the expansion of the aneurysm by measuring the expansion the aneurysm exerts onto the device.

A method of treating an aneurysm of a mammal patient by providing the medical device, said method comprising the steps of:

cutting the skin in the abdominal or thoraxial wall of said mammal patient, dissecting an area of the aneurysm,

placing said device onto said aneurysm, and

monitoring the expansion of the aneurysm by measuring the expansion the aneurysm exerts onto the device.

A method of treating an aneurysm of a mammal patient by providing the medical device, said method comprising the steps of:

cutting the skin of said mammal patient,

dissecting an area of the aneurysm,

placing said device onto said aneurysm, and

monitoring the expansion of the aneurysm by measuring the expansion the aneurysm exerts onto the device.

BRIEF DESCRIPTION OF THE DRAWINGS

The present invention will now be described in more detail by way of non-limiting examples and with reference to the accompanying drawings, in which:

FIG. 1 is general view of a human body having a device for treating aneurysm implanted,

FIG. 2 is a view illustrating a device for treating aneurysm with associated equipment,

FIG. 3 is a view illustrating a mechanical device for treating aneurysm,

FIG. 4 is a view illustrating a mechanical device for treating aneurysm,

FIG. 5 is a view illustrating a hydraulic device for treating aneurysm,

FIG. 6 is a view illustrating a hydraulic device for treating aneurysm,

FIG. 7 is a view illustrating a hydraulic device for treating aneurysm,

FIG. 8 is a view illustrating a stimulation device for treating a vascular aneurysm of a human or mammal patient,

FIG. 9 is a view illustrating a sensor used when treating or monitoring a vascular aneurysm of a human or mammal patient,

FIG. 10 is a view from above of a device for treating aneurysm implanted around a blood vessel,

FIG. 11 is a view of a device for treating aneurysm having a Y-shape,

FIG. 12 is a flowchart illustrating steps performed when implanting a device for treating or monitoring an aneurysm in accordance with one embodiment,

FIG. 12 is a flowchart illustrating steps performed when implanting a device for treating or monitoring an aneurysm in accordance with one embodiment,

FIG. 13 is a flowchart illustrating steps performed when implanting a device for treating or monitoring an aneurysm in accordance with one embodiment,

FIG. 14 is a flowchart illustrating steps performed when implanting a device for treating or monitoring an aneurysm in accordance with one embodiment, and

FIG. 15 is a flowchart illustrating steps performed when implanting a device for treating or monitoring an aneurysm in accordance with one embodiment.

FIG. 16 illustrates a system for treating a disease, wherein the system includes a device of the invention implanted in a patient.

FIGS. 17-31 schematically show various embodiments of the system for wirelessly powering the device shown in FIG. 16.

FIG. 32 is a schematic block diagram illustrating an arrangement for supplying an accurate amount of energy used for the operation of the device shown in FIG. 16.

FIG. 33 schematically shows an embodiment of the system, in which the device is operated with wire bound energy.

FIG. 34 is a more detailed block diagram of an arrangement for controlling the transmission of wireless energy used for the operation of the device shown in FIG. 16.

FIG. 35 is a circuit for the arrangement shown in FIG. 34, according to a possible implementation example.

FIGS. 36-42 show various ways of arranging hydraulic or pneumatic powering of a device implanted in a patient.

DETAILED DESCRIPTION

In FIG. 1 a general view of a human 100 having a member, in particular a cuff 101, implanted for treating an aneurism is shown. In FIG. 1 the treated aneurism is located on the aorta in the abdomen close to the Y-bifurcation extending to the legs. The cuff 101 can be designed in various ways but is generally formed as an implantable member adapted to be placed in connection with a blood vessel having said vascular aneurysm, and adapted to exert a pressure on said aneurysm from the outside of said blood vessel. In particular the pressure exerted on the blood vessel is essentially uniform from all direction and adapted to hinder the blood vessel to expand in all directions thereby acting to prevent the blood vessel from bursting. The pressure can in accordance with one embodiment be essentially equal to or lower than the diastolic blood pressure of the treated patient. The cuff 101 can be made in any suitable material such as an elastic material adapted for implantation in a human or mammal body.

The cuff 101 can exercise the pressure in a number of different ways. In accordance with one embodiment of the present invention the pressure applied on the blood vessel can be mechanical and adjustable by means of an adjustable screw or a similar means in order to apply a pressure on the blood vessel. The cuff 101 can also be formed by a spring loaded member and operated in a suitable manner such as hydraulically or pneumatically.

In FIG. 2 a cuff 101 in accordance with one embodiment of the present invention is shown in more detail. The cuff 101 comprises a number of segments 103 each adjustable and possible to tailor to fit a particular aneurism 102 of a blood vessel 104 to be treated. Each segment 103 can be adjusted either as a whole or individually. The segments 103 can be controlled and adjusted mechanically by an adjustable screw or similar or adapted to be filled with a fluid. For example, the segments can be provided axially along the blood vessel and also radially along the blood vessel forming a matrix of sub-segments that constitutes the cuff 101. In particular one segment can be located above and one below the aneurysm along the blood vessel.

The adjustment can be controlled by an electronic control unit 105 adapted to receive and transmit signals from a transmitter/receiver 106 located outside the body of a treated patient. The electronic control unit can also comprise a chargeable battery 111 chargeable from the outside by an external charger unit 112. The electronic control unit can

comprise an electrical pulse generator **109** for generating electrical pulses as is described in more detail below.

The electronic control unit **105**, such as a microprocessor or a MCU or a FPGA or a ASIC and can further be connected to or comprise a hydraulic pump **110** associated with a reservoir **115** containing of a fluid used to regulate the pressure of the cuff **101**. The pump is thus adapted to pump the hydraulic fluid in or out from the cuff **101** in order to adjust the pressure applied in the aneurism. The control mechanism used for keeping the pressure in the cuff **101** can comprise a pressure tank **117**.

In a preferred embodiment the pressure tank **117** is adapted to be able to change its volume still keeping substantially the same pressure, thus keeping the same pressure onto the aneurysm although some expansion of size of the aneurysm may occur. However, if the expansion goes too far the pressure tank may come out of range to keep the pressure constant and with some kind of volume detection in the pressure tank the pump **110** is then able to move fluid out from the pressure tank into the reservoir **115** to again be within pressure range in the pressure tank. The pressure tank is also able to even out the systolic pulses supplied to the aneurysmic wall.

The cuff **101** can be shaped in any desirable form to enable treatment of an aneurism wherever it is located. In accordance with one embodiment the cuff **101** is provided with at least one sensor **107** adapted to sense the pressure from the blood vessel that the cuff is surrounding.

The sensor(s) **107** used to generate a signal indicative of one or many parameters related to the aneurism and the device **101** used for treating the aneurism can for example be a gauge sensor. The sensor **107** can be adapted to generate sensor signals used for monitoring parameters including but not limited to the pressure in a hydraulic cuff, the pressure of a mechanical cuff, the pressure of a pneumatic cuff, the pressure in a blood vessel; the shape of the blood vessel in particular a parameter related to the diameter of the aneurism.

An alternative or complement to the remote placed transmitter **106** is a switch (part of **105**), preferable subcutaneously placed, such a switch may be mechanical or electrical, such as a microprocessor or a MCU or a FPGA or a ASIC, or the switch may comprise a small hydraulic control reservoir.

The restriction device may comprise any hydraulic device or mechanical device or stimulation device alone or monitoring/sensor device in any combination as described in the present application. The stimulation device may comprise both thermal stimulation or electrical stimulation. If a hydraulic system is used the hydraulic pump may in a system comprise an injection port (part of **110**) for the injection of hydraulic fluid, preferable for calibration of hydraulic fluid. A subcutaneously place switch may also be used as well as an feed back alarm system connected to the sensor/monitoring system.

Although the device has specific placements on the drawings it should be understood that the placement might vary.

Any combination of features or embodiments may comprise from any source within this application. Any embodiment in any combination that is disclosed in this application, specially, but not limited to, in FIG. 1-42, may be used.

In FIG. 3 a view illustrating a mechanical cuff **101** is shown. The cuff can for example comprise an elastic material **301** kept in place by a suitable compressing device. The cuff **101** in accordance with one embodiment of the present invention comprises an elastic material in the form of a number of gel filled pads **301**. The pads **301** can be shaped

in a suitable manner and in particular formed to absorb the geometrical shape of the aneurysm. This can for example be achieved by providing pads with different tilting angles. The elastic material **301** can be kept in place by at least one adjustable fastening member **303**. The fastening member **303** can for example be adjusted by a screw **305** or a similar device. By adjusting the fastening member **303** the pressure applied on the aneurysm can be controlled.

In FIG. 4, a view illustrating a mechanical cuff **101** is shown. The cuff can for example comprise an elastic band **401**. The band **401** can be adjusted by an adjustor **403** to provide a higher or smaller pressure on the aneurysm.

In FIG. 5, a view illustrating a hydraulic cuff **101** is shown. The cuff can for example comprise implantable member **501** adapted to hold fluid. The member **501** is adapted to be placed in connection with a blood vessel having an aneurysm. The member can exercise a pressure on the aneurysm the blood vessel in response to the conditions of the fluid of the member **501**. By filling the member with a fluid pressure can be applied onto the aneurysm in order to prevent or reduce an expansion the aneurysm when implanted in a patient thereby enabling postoperative treatment of the aneurysm. Further the treatment can be adjusted postoperatively by regulating the pressure using an implanted pressure regulator **503**. The pressure regulator can for example be formed by a pressure tank **503** implanted in the patient interconnected via a hose **504** with the member **501**. The pressure tank can comprise an expandable reservoir **505** for storing superfluous fluid.

In FIG. 6, a view illustrating a hydraulic cuff **101** is shown. The cuff can for example comprise implantable member **601** adapted to hold fluid. The member **601** is adapted to be placed in connection with a blood vessel having an aneurysm. The member can exercise a pressure on the aneurysm the blood vessel in response to the conditions of the fluid of the member **601**. By filling the member with a fluid pressure can be applied onto the aneurysm in order to prevent or reduce an expansion the aneurysm when implanted in a patient thereby enabling postoperative treatment of the aneurysm. Further the treatment can be adjusted postoperatively by regulating the pressure using an implanted pressure regulator **603**. The pressure regulator can for example be formed by a spring loaded tank **603** implanted in the patient interconnected via a hose **604** with the member **601**. The spring **606** used to control the pressure of the tank and thereby indirectly the pressure applied by the cuff **101** on the aneurysm can be an adjustable spring in order to control the pressure.

In FIG. 7, a view illustrating a hydraulic cuff **101** is shown. The cuff can for example comprise implantable member **701** adapted to hold fluid. The member **601** is adapted to be placed in connection with a blood vessel having an aneurysm. The member can exercise a pressure on the aneurysm the blood vessel in response to the conditions of the fluid of the member **701**. By filling the member with a fluid pressure can be applied onto the aneurysm in order to prevent or reduce an expansion the aneurysm when implanted in a patient thereby enabling postoperative treatment of the aneurysm. Further the treatment can be adjusted postoperatively by regulating the pressure using an implanted pressure regulator **703**. The pressure regulator can for example be formed by a pump **703** implanted in the patient on a hose **704** interconnecting a tank **705** with the member **701**. The pump **703** is used to control the pressure of the member **703** by pumping fluid in and out of the member **701** and thereby controlling the pressure applied by the cuff **101** on the aneurysm.

By sensing the pressure from the blood vessel the cuff can be controlled to apply a correct pressure on the blood vessel thereby keeping the form of the blood vessel essentially constant. For example the pressure may vary over time as a result of changes in the wall of the blood vessel of surrounding tissue. Also the pressure will change as a function of the phase in which the heart is working. In other words the pressure will be different in a systolic phase as compared to a diastolic phase. By using a pressure sensor the pressure applied by the cuff **101** can be adapted to react to changes in the sensed pressure and apply a corresponding counter pressure. The sensor signals generated by the sensor(s) **107** of the cuff can also be used to trigger an alarm in response to the sensor signal indicating an expansion of the aneurism. In response to an alarm signal being generated the cuff can be automatically controlled to exercise a counter pressure on the blood vessel to counter or limit the expansion of the aneurism.

In yet another embodiment, electrodes **108** can be provided in the cuff. The electrodes can be connected to the electrical pulse generator, which is adapted to generate electrical pulses for stimulating the wall of the aneurism. The purpose of the electrical stimulation is to increase the tonus of the wall of the aneurism.

In FIG. **8**, a stimulation device **801** for treating a vascular aneurism of a human or mammal patient is shown. The device **801** comprises at least one implantable electrode **803** adapted to be placed in close connection to the aneurism. The electrode is adapted to provide an electrical stimulation pulse on a wall portion of the aneurism. The electrical stimulation pulse can for example be generated by a pulse generator **805**. The pulse generator can be implanted in the patient.

In accordance with one embodiment the electrical stimulation device used for treating a vascular aneurism of a human or mammal patient is connected to electrodes adapted to stimulate the wall of the aneurism at multiple stimulation points. The multiple stimulation groups may further be organized in different stimulation groups which can be stimulated independently of each other. In accordance with one embodiment the electrical stimulation is performed with positive and or negative voltage stimulation pulses. In one embodiment the current used for stimulation of the aneurism wall is kept essentially constant.

The sequence of electrical pulses used to stimulation the wall of the aneurism can be applied with a predetermined periodicity having periods of no stimulation therein between during which periods without stimulation the wall of the aneurism is allowed to rest. The electrical stimulation signal can also be Pulse Width Modulated to control the energy applied. In accordance with one embodiment the electrical stimulation is applied during the systolic phase to increase the tonus of the wall of the aneurism. The systolic phase can be detected by the sensors **107** used to sense the pressure of the aneurism as described above.

In accordance with one embodiment the stimulation can be controlled to be applied with a temporarily increased intensity and position during emergency situations when the aneurism is detected to rapidly expands, to limit the expansion of said aneurism.

In order to provide input for controlling the pressure and or to monitor the aneurism a device **107** can be provided. In FIG. **9** a view illustrating a sensor **901** used when treating or monitoring a vascular aneurism of a human or mammal patient is shown. The sensor **901** is placed in relation to a wall portion of the aneurism for generating a signal corresponding to a parameter related to the aneurism or the

treatment of the aneurism. The signal generated by the sensor can be a signal corresponding to the size of the aneurism and is accessible via a signal output **903**. For example the signal can be indicative of the diameter of the aneurism. In accordance with one embodiment of the he sensor is a gauge sensor. The sensor **901** can also be adapted to generate any output related to monitoring or treatment of the aneurism. For example the sensor can be adapted to sense the resistance, capacitance, pressure, volume extension, flexure of a member in contact with the aneurism.

The shape of the cuff **101** can as stated above be tailor made to suit the location where an aneurism is to be treated. In FIG. **10**, a cuff **101** is seen from above in a direction aligned with a treated blood vessel. As can be seen in FIG. **3** each segment **3** can be sub-divided into a number of sub segments **103a**, **103b** . . . together forming a closed loop around the treated aneurism. In case the aneurism is located in the aorta bifurcation region the cuff **101** can be Y-shaped as is shown in FIG. **11**.

The device as described herein can be implanted in a patient using some suitable surgical procedure as depicted in FIG. **12**. For example, the device can be implanted by inserting a needle or a tube like instrument into the patient's abdominal cavity, step **1201**. Next in a step **1203** a part of the patient's body with gas using the needle or tube like instrument thereby expanding said abdominal cavity. Next in a step **1205** at least two laparoscopic trocars are placed in the cavity. Thereupon in a step **1207** a camera is inserted through one of the laparoscopic trocars into the cavity. Next in a step **1209** at least one dissecting tool is inserted through one of said at least two laparoscopic trocars. An area of an aneurism of a blood vessel is then dissected in a step **1211**. The device is then placed onto the aneurismic blood vessel in a step **1213**, and the pressure that the device exerts onto the aneurism is adjusted in a step **1215**.

In accordance with one embodiment of the present invention the device can be implanted by a procedure depicted in FIG. **13**. First in a step **1301** a needle or a tube like instrument is inserted into the patient's thoraxial cavity. Next, in a step **1303** a part of the patient's body with gas using the needle or tube like instrument to fill and thereby expanding the thoraxial cavity. Thereupon at least two laparoscopic trocars are placed in said cavity in a step **1305** Thereupon in a step **1307** a camera is inserted through one of the laparoscopic trocars into the cavity. Next in a step **1309** at least one dissecting tool is inserted through one of said at least two laparoscopic trocars. An area of an aneurism of a blood vessel is then dissected in a step **1311**. The device is then placed onto the aneurismic blood vessel in a step **1313**, and the pressure that the device exerts onto the aneurism is adjusted in a step **1315**.

In accordance with one embodiment of the present invention the device can be implanted by a procedure depicted in FIG. **14**. First in a step **1401**, the skin in the abdominal or thoraxial wall of the mammal patient is cut. Next, in a step **1403** an area of the aneurism is dissected.

Next, the device is then placed onto the aneurismic blood vessel in a step **1405**, and the pressure that the device exerts onto the aneurism is adjusted in a step **1407**.

In accordance with one embodiment of the present invention the device can be implanted by a procedure depicted in FIG. **15**. First in a step **1501**, the skin of the mammal patient is cut.

Next, in a step **1503** an area of the aneurism is dissected. Next, the device is then placed onto the aneurismic blood vessel in a step **1505**, and the pressure that the device exerts onto the aneurism is adjusted in a step **1507**.

FIG. 16 illustrates a system for treating a disease comprising a device 10 of the present invention placed in the abdomen of a patient. An implanted energy-transforming device 3020 is adapted to supply energy consuming components of the device with energy via a power supply line 3030. An external energy-transmission device 3040 for non-invasively energizing the device 10 transmits energy by at least one wireless energy signal. The implanted energy-transforming device 3020 transforms energy from the wireless energy signal into electric energy which is supplied via the power supply line 3030.

In one embodiment at least one battery may be a part of or replace the energy transforming device 3020 to supply energy to the device 10 over a power supply line 3030. In one embodiment the battery is not rechargeable. In an alternative embodiment the battery is rechargeable. The battery supply may of course be placed both remote to and incorporated in the device.

The wireless energy signal may include a wave signal selected from the following: a sound wave signal, an ultrasound wave signal, an electromagnetic wave signal, an infrared light signal, a visible light signal, an ultra violet light signal, a laser light signal, a micro wave signal, a radio wave signal, an x-ray radiation signal and a gamma radiation signal.

Alternatively, the wireless energy signal may include an electric or magnetic field, or a combined electric and magnetic field.

The wireless energy-transmission device 3040 may transmit a carrier signal for carrying the wireless energy signal. Such a carrier signal may include digital, analogue or a combination of digital and analogue signals. In this case, the wireless energy signal includes an analogue or a digital signal, or a combination of an analogue and digital signal.

Generally speaking, the energy-transforming device 3020 is provided for transforming wireless energy of a first form transmitted by the energy-transmission device 3040 into energy of a second form, which typically is different from the energy of the first form. The implanted device 10 is operable in response to the energy of the second form. The energy-transforming device 3020 may directly power the device with the second form energy, as the energy-transforming device 3020 transforms the first form energy transmitted by the energy-transmission device 3040 into the second form energy. The system may further include an implantable accumulator, wherein the second form energy is used at least partly to charge the accumulator.

Alternatively, the wireless energy transmitted by the energy-transmission device 3040 may be used to directly power the device, as the wireless energy is being transmitted by the energy-transmission device 3040. Where the system comprises an operation device for operating the device, as will be described below, the wireless energy transmitted by the energy-transmission device 1004 may be used to directly power the operation device to create kinetic energy for the operation of the device.

The wireless energy of the first form may comprise sound waves and the energy-transforming device 3020 may include a piezo-electric element for transforming the sound waves into electric energy. The energy of the second form may comprise electric energy in the form of a direct current or pulsating direct current, or a combination of a direct current and pulsating direct current, or an alternating current or a combination of a direct and alternating current. Normally, the device comprises electric components that are energized with electrical energy. Other implantable electric components of the system may be at least one voltage level

guard or at least one constant current guard connected with the electric components of the device.

Optionally, one of the energy of the first form and the energy of the second form may comprise magnetic energy, kinetic energy, sound energy, chemical energy, radiant energy, electromagnetic energy, photo energy, nuclear energy or thermal energy. Preferably, one of the energy of the first form and the energy of the second form is non-magnetic, non-kinetic, non-chemical, non-sonic, non-nuclear or non-thermal.

The energy-transmission device may be controlled from outside the patient's body to release electromagnetic wireless energy, and the released electromagnetic wireless energy is used for operating the device. Alternatively, the energy-transmission device is controlled from outside the patient's body to release non-magnetic wireless energy, and the released non-magnetic wireless energy is used for operating the device.

The external energy-transmission device 3040 also includes a wireless remote control having an external signal transmitter for transmitting a wireless control signal for non-invasively controlling the device. The control signal is received by an implanted signal receiver which may be incorporated in the implanted energy-transforming device 3020 or be separate there from.

The wireless control signal may include a frequency, amplitude, or phase modulated signal or a combination thereof. Alternatively, the wireless control signal includes an analogue or a digital signal, or a combination of an analogue and digital signal. Alternatively, the wireless control signal comprises an electric or magnetic field, or a combined electric and magnetic field.

The wireless remote control may transmit a carrier signal for carrying the wireless control signal. Such a carrier signal may include digital, analogue or a combination of digital and analogue signals. Where the control signal includes an analogue or a digital signal, or a combination of an analogue and digital signal, the wireless remote control preferably transmits an electromagnetic carrier wave signal for carrying the digital or analogue control signals.

FIG. 17 illustrates the system of FIG. 16 in the form of a more generalized block diagram showing the device 10, the energy-transforming device 3020 powering the device 10 via power supply line 3030, and the external energy-transmission device 3040. The patient's skin 3050, generally shown by a vertical line, separates the interior of the patient to the right of the line from the exterior to the left of the line.

FIG. 18 shows an embodiment of the invention identical to that of FIG. 17, except that a reversing device in the form of an electric switch 3060 operable for example by polarized energy also is implanted in the patient for reversing the device 10. When the switch is operated by polarized energy the wireless remote control of the external energy-transmission device 3040 transmits a wireless signal that carries polarized energy and the implanted energy-transforming device 3020 transforms the wireless polarized energy into a polarized current for operating the electric switch 3060. When the polarity of the current is shifted by the implanted energy-transforming device 3020 the electric switch 3060 reverses the function performed by the device 10.

FIG. 19 shows an embodiment of the invention identical to that of FIG. 17, except that an operation device 3070 implanted in the patient for operating the device 10 is provided between the implanted energy-transforming device 3020 and the device 10. This operation device can be in the form of a motor 3070, such as an electric servomotor. The motor 3070 is powered with energy from the implanted

energy-transforming device **3020**, as the remote control of the external energy-transmission device **3040** transmits a wireless signal to the receiver of the implanted energy-transforming device **3020**.

FIG. **20** shows an embodiment of the invention identical to that of FIG. **17**, except that it also comprises an operation device is in the form of an assembly **3080** including a motor/pump unit **3090** and a fluid reservoir **3100** is implanted in the patient. In this case the device **10** is hydraulically operated, i.e. hydraulic fluid is pumped by the motor/pump unit **3090** from the fluid reservoir **3100** through a conduit **3110** to the device **10** to operate the device, and hydraulic fluid is pumped by the motor/pump unit **3090** back from the device **10** to the fluid reservoir **3100** to return the device to a starting position. The implanted energy-transforming device **1002** transforms wireless energy into a current, for example a polarized current, for powering the motor/pump unit **1009** via an electric power supply line **3120**.

Instead of a hydraulically operated device **10**, it is also envisaged that the operation device comprises a pneumatic operation device. In this case, the hydraulic fluid can be pressurized air to be used for regulation and the fluid reservoir is replaced by an air chamber.

In all of these embodiments the energy-transforming device **3020** may include a rechargeable accumulator like a battery or a capacitor to be charged by the wireless energy and supplies energy for any energy consuming part of the system.

As an alternative, the wireless remote control described above may be replaced by manual control of any implanted part to make contact with by the patient's hand most likely indirect, for example a press button placed under the skin.

FIG. **21** shows an embodiment of the invention comprising the external energy-transmission device **3040** with its wireless remote control, the device **10**, in this case hydraulically operated, and the implanted energy-transforming device **3020**, and further comprising a hydraulic fluid reservoir **3130**, a motor/pump unit **3090** and an reversing device in the form of a hydraulic valve shifting device **3140**, all implanted in the patient. Of course the hydraulic operation could easily be performed by just changing the pumping direction and the hydraulic valve may therefore be omitted. The remote control may be a device separated from the external energy-transmission device or included in the same. The motor of the motor/pump unit **3090** is an electric motor. In response to a control signal from the wireless remote control of the external energy-transmission device **3040**, the implanted energy-transforming device **3020** powers the motor/pump unit **3090** with energy from the energy carried by the control signal, whereby the motor/pump unit **3090** distributes hydraulic fluid between the hydraulic fluid reservoir **3130** and the device **10**. The remote control of the external energy-transmission device **3040** controls the hydraulic valve shifting device **3140** to shift the hydraulic fluid flow direction between one direction in which the fluid is pumped by the motor/pump unit **3090** from the hydraulic fluid reservoir **3130** to the device **10** to operate the device, and another opposite direction in which the fluid is pumped by the motor/pump unit **3090** back from the device **10** to the hydraulic fluid reservoir **3130** to return the device to a starting position.

FIG. **22** shows an embodiment of the invention comprising the external energy-transmission device **1004** with its wireless remote control, the device **10**, the implanted energy-transforming device **3020**, an implanted internal control unit **3150** controlled by the wireless remote control

of the external energy-transmission device **3040**, an implanted accumulator **3160** and an implanted capacitor **3170**. The internal control unit **1015** arranges storage of electric energy received from the implanted energy-transforming device **3020** in the accumulator **3160**, which supplies energy to the device **10**. In response to a control signal from the wireless remote control of the external energy-transmission device **3040**, the internal control unit **3150** either releases electric energy from the accumulator **3160** and transfers the released energy via power lines **3180** and **3190**, or directly transfers electric energy from the implanted energy-transforming device **3020** via a power line **3200**, the capacitor **3170**, which stabilizes the electric current, a power line **3210** and the power line **3190**, for the operation of the device **10**.

The internal control unit is preferably programmable from outside the patient's body. In a preferred embodiment, the internal control unit is programmed to regulate the device **10** according to a pre-programmed time-schedule or to input from any sensor sensing any possible physical parameter of the patient or any functional parameter of the system.

In accordance with an alternative, the capacitor **3170** in the embodiment of FIG. **7** may be omitted. In accordance with another alternative, the accumulator **3160** in this embodiment may be omitted.

FIG. **23** shows an embodiment of the invention identical to that of FIG. **17**, except that a battery **3220** for supplying energy for the operation of the device **10** and an electric switch **3230** for switching the operation of the device **10** also are implanted in the patient. The electric switch **3230** may be controlled by the remote control and may also be operated by the energy supplied by the implanted energy-transforming device **3020** to switch from an off mode, in which the battery **3220** is not in use, to an on mode, in which the battery **3220** supplies energy for the operation of the device **10**.

FIG. **24** shows an embodiment of the invention identical to that of FIG. **23**, except that an internal control unit **3150** controllable by the wireless remote control of the external energy-transmission device **3040** also is implanted in the patient. In this case, the electric switch **3230** is operated by the energy supplied by the implanted energy-transforming device **3020** to switch from an off mode, in which the wireless remote control is prevented from controlling the internal control unit **3150** and the battery is not in use, to a standby mode, in which the remote control is permitted to control the internal control unit **3150** to release electric energy from the battery **3220** for the operation of the device **10**.

FIG. **25** shows an embodiment of the invention identical to that of FIG. **24**, except that an accumulator **3160** is substituted for the battery **3220** and the implanted components are interconnected differently. In this case, the accumulator **3160** stores energy from the implanted energy-transforming device **3020**. In response to a control signal from the wireless remote control of the external energy-transmission device **3040**, the internal control unit **3150** controls the electric switch **3230** to switch from an off mode, in which the accumulator **3160** is not in use, to an on mode, in which the accumulator **3160** supplies energy for the operation of the device **10**. The accumulator may be combined with or replaced by a capacitor.

FIG. **26** shows an embodiment of the invention identical to that of FIG. **25**, except that a battery **3220** also is implanted in the patient and the implanted components are interconnected differently. In response to a control signal from the wireless remote control of the external energy-

transmission device **3040**, the internal control unit **3150** controls the accumulator **3160** to deliver energy for operating the electric switch **3230** to switch from an off mode, in which the battery **3220** is not in use, to an on mode, in which the battery **3220** supplies electric energy for the operation of the device **10**.

Alternatively, the electric switch **3230** may be operated by energy supplied by the accumulator **3160** to switch from an off mode, in which the wireless remote control is prevented from controlling the battery **3220** to supply electric energy and is not in use, to a standby mode, in which the wireless remote control is permitted to control the battery **3220** to supply electric energy for the operation of the device **10**.

It should be understood that the switch **3230** and all other switches in this application should be interpreted in its broadest embodiment. This means a transistor, MCU, MCP, ASIC, FPGA or a DA converter or any other electronic component or circuit that may switch the power on and off. Preferably the switch is controlled from outside the body, or alternatively by an implanted internal control unit.

FIG. **27** shows an embodiment of the invention identical to that of FIG. **23**, except that a motor **3070**, a mechanical reversing device in the form of a gear box **3240**, and an internal control unit **3150** for controlling the gear box **3240** also are implanted in the patient. The internal control unit **3150** controls the gear box **3240** to reverse the function performed by the device **10** (mechanically operated). Even simpler is to switch the direction of the motor electronically. The gear box interpreted in its broadest embodiment may stand for a servo arrangement saving force for the operation device in favor of longer stroke to act.

FIG. **28** shows an embodiment of the invention identical to that of FIG. **24** except that the implanted components are interconnected differently. Thus, in this case the internal control unit **3150** is powered by the battery **3220** when the accumulator **3160**, suitably a capacitor, activates the electric switch **3230** to switch to an on mode. When the electric switch **3230** is in its on mode the internal control unit **3150** is permitted to control the battery **3220** to supply, or not supply, energy for the operation of the device **10**.

FIG. **29** schematically shows conceivable combinations of implanted components of the device for achieving various communication options. Basically, there are the device **10**, the internal control unit **3150**, motor or pump unit **3090**, and the external energy-transmission device **3040** including the external wireless remote control. As already described above the wireless remote control transmits a control signal which is received by the internal control unit **3150**, which in turn controls the various implanted components of the device.

A feedback device, preferably comprising a sensor or measuring device **3250**, may be implanted in the patient for sensing a physical parameter of the patient. The physical parameter may be at least one selected from the group consisting of pressure, volume, diameter, stretching, elongation, extension, movement, bending, elasticity, muscle contraction, nerve impulse, body temperature, blood pressure, blood flow, heartbeats and breathing. The sensor may sense any of the above physical parameters. For example, the sensor may be a pressure or motility sensor. Alternatively, the sensor **3250** may be arranged to sense a functional parameter. The functional parameter may be correlated to the transfer of energy for charging an implanted energy source and may further include at least one selected from the group of parameters consisting of; electricity, any electrical

parameter, pressure, volume, diameter, stretch, elongation, extension, movement, bending, elasticity, temperature and flow.

The feedback may be sent to the internal control unit or out to an external control unit preferably via the internal control unit. Feedback may be sent out from the body via the energy transfer system or a separate communication system with receiver and transmitters.

The internal control unit **3150**, or alternatively the external wireless remote control of the external energy-transmission device **3040**, may control the device **10** in response to signals from the sensor **3250**. A transceiver may be combined with the sensor **3250** for sending information on the sensed physical parameter to the external wireless remote control. The wireless remote control may comprise a signal transmitter or transceiver and the internal control unit **3150** may comprise a signal receiver or transceiver. Alternatively, the wireless remote control may comprise a signal receiver or transceiver and the internal control unit **3150** may comprise a signal transmitter or transceiver. The above transceivers, transmitters and receivers may be used for sending information or data related to the device **10** from inside the patient's body to the outside thereof.

Where the motor/pump unit **3090** and battery **3220** for powering the motor/pump unit **3090** are implanted, information related to the charging of the battery **3220** may be fed back. To be more precise, when charging a battery or accumulator with energy feed back information related to said charging process is sent and the energy supply is changed accordingly.

FIG. **30** shows an alternative embodiment wherein the device **10** is regulated from outside the patient's body. The system **3000** comprises a battery **3220** connected to the device **10** via a subcutaneous electric switch **3260**. Thus, the regulation of the device **10** is performed non-invasively by manually pressing the subcutaneous switch, whereby the operation of the device **10** is switched on and off. It will be appreciated that the shown embodiment is a simplification and that additional components, such as an internal control unit or any other part disclosed in the present application can be added to the system. Two subcutaneous switches may also be used. In the preferred embodiment one implanted switch sends information to the internal control unit to perform a certain predetermined performance and when the patient press the switch again the performance is reversed.

FIG. **31** shows an alternative embodiment, wherein the system **3000** comprises a hydraulic fluid reservoir **3130** hydraulically connected to the device. Non-invasive regulation is performed by manually pressing the hydraulic reservoir connected to the device.

The system may include an external data communicator and an implantable internal data communicator communicating with the external data communicator. The internal communicator feeds data related to the device or the patient to the external data communicator and/or the external data communicator feeds data to the internal data communicator.

FIG. **32** schematically illustrates an arrangement of the system that is capable of sending information from inside the patient's body to the outside thereof to give feedback information related to at least one functional parameter of the device or system, or related to a physical parameter of the patient, in order to supply an accurate amount of energy to an implanted internal energy receiver **3020** connected to implanted energy consuming components of the device **10**. Such an energy receiver **3020** may include an energy source and/or an energy-transforming device. Briefly described, wireless energy is transmitted from an external energy

source **3040a** located outside the patient and is received by the internal energy receiver **3020** located inside the patient. The internal energy receiver is adapted to directly or indirectly supply received energy to the energy consuming components of the device **10** via a switch **3260**. An energy balance is determined between the energy received by the internal energy receiver **3020** and the energy used for the device **10**, and the transmission of wireless energy is then controlled based on the determined energy balance. The energy balance thus provides an accurate indication of the correct amount of energy needed, which is sufficient to operate the device **10** properly, but without causing undue temperature rise.

In FIG. **32** the patient's skin is indicated by a vertical line **3050**. Here, the energy receiver comprises an energy-transforming device **1002** located inside the patient, preferably just beneath the patient's skin **3050**. Generally speaking, the implanted energy-transforming device **1002** may be placed in the abdomen, thorax, muscle fascia (e.g. in the abdominal wall), subcutaneously, or at any other suitable location. The implanted energy-transforming device **3020** is adapted to receive wireless energy *E* transmitted from the external energy source **3040a** provided in an external energy-transmission device **3040** located outside the patient's skin **3050** in the vicinity of the implanted energy-transforming device **3020**.

As is well known in the art, the wireless energy *E* may generally be transferred by means of any suitable Transcutaneous Energy Transfer (TET) device, such as a device including a primary coil arranged in the external energy source **1004a** and an adjacent secondary coil arranged in the implanted energy-transforming device **3020**. When an electric current is fed through the primary coil, energy in the form of a voltage is induced in the secondary coil which can be used to power the implanted energy consuming components of the device, e.g. after storing the incoming energy in an implanted energy source, such as a rechargeable battery or a capacitor. However, the present invention is generally not limited to any particular energy transfer technique, TET devices or energy sources, and any kind of wireless energy may be used.

The amount of energy received by the implanted energy receiver may be compared with the energy used by the implanted components of the device. The term "energy used" is then understood to include also energy stored by implanted components of the device. A control device includes an external control unit **3040b** that controls the external energy source **3040a** based on the determined energy balance to regulate the amount of transferred energy. In order to transfer the correct amount of energy, the energy balance and the required amount of energy is determined by means of a determination device including an implanted internal control unit **3150** connected between the switch **3260** and the device **10**. The internal control unit **3150** may thus be arranged to receive various measurements obtained by suitable sensors or the like, not shown, measuring certain characteristics of the device **10**, somehow reflecting the required amount of energy needed for proper operation of the device **10**. Moreover, the current condition of the patient may also be detected by means of suitable measuring devices or sensors, in order to provide parameters reflecting the patient's condition. Hence, such characteristics and/or parameters may be related to the current state of the device **10**, such as power consumption, operational mode and temperature, as well as the patient's condition reflected by parameters such as; body temperature, blood pressure, heart-

beats and breathing. Other kinds of physical parameters of the patient and functional parameters of the device are described elsewhere.

Furthermore, an energy source in the form of an accumulator **3160** may optionally be connected to the implanted energy-transforming device **3020** via the control unit **3150** for accumulating received energy for later use by the device **10**. Alternatively or additionally, characteristics of such an accumulator, also reflecting the required amount of energy, may be measured as well. The accumulator may be replaced by a rechargeable battery, and the measured characteristics may be related to the current state of the battery, any electrical parameter such as energy consumption voltage, temperature, etc. In order to provide sufficient voltage and current to the device **10**, and also to avoid excessive heating, it is clearly understood that the battery should be charged optimally by receiving a correct amount of energy from the implanted energy-transforming device **3020**, i.e. not too little or too much. The accumulator may also be a capacitor with corresponding characteristics.

For example, battery characteristics may be measured on a regular basis to determine the current state of the battery, which then may be stored as state information in a suitable storage means in the internal control unit **3150**. Thus, whenever new measurements are made, the stored battery state information can be updated accordingly. In this way, the state of the battery can be "calibrated" by transferring a correct amount of energy, so as to maintain the battery in an optimal condition.

Thus, the internal control unit **3150** of the determination device is adapted to determine the energy balance and/or the currently required amount of energy, (either energy per time unit or accumulated energy) based on measurements made by the above-mentioned sensors or measuring devices of the device **10**, or the patient, or an implanted energy source if used, or any combination thereof. The internal control unit **3150** is further connected to an internal signal transmitter **3270**, arranged to transmit a control signal reflecting the determined required amount of energy, to an external signal receiver **3040c** connected to the external control unit **3040b**. The amount of energy transmitted from the external energy source **3040a** may then be regulated in response to the received control signal.

Alternatively, the determination device may include the external control unit **3040b**. In this alternative, sensor measurements can be transmitted directly to the external control unit **3040b** wherein the energy balance and/or the currently required amount of energy can be determined by the external control unit **3040b**, thus integrating the above-described function of the internal control unit **3150** in the external control unit **3040b**. In that case, the internal control unit **3150** can be omitted and the sensor measurements are supplied directly to the internal signal transmitter **3270** which sends the measurements over to the external signal receiver **3040c** and the external control unit **3040b**. The energy balance and the currently required amount of energy can then be determined by the external control unit **3040b** based on those sensor measurements.

Hence, the present solution according to the arrangement of FIG. **32** employs the feed back of information indicating the required energy, which is more efficient than previous solutions because it is based on the actual use of energy that is compared to the received energy, e.g. with respect to the amount of energy, the energy difference, or the energy receiving rate as compared to the energy rate used by implanted energy consuming components of the device. The device may use the received energy either for consuming or

for storing the energy in an implanted energy source or the like. The different parameters discussed above would thus be used if relevant and needed and then as a tool for determining the actual energy balance. However, such parameters may also be needed per se for any actions taken internally to specifically operate the device.

The internal signal transmitter **3270** and the external signal receiver **3040c** may be implemented as separate units using suitable signal transfer means, such as radio, IR (Infrared) or ultrasonic signals. Alternatively, the internal signal transmitter **3270** and the external signal receiver **3040c** may be integrated in the implanted energy-transforming device **3020** and the external energy source **3040a**, respectively, so as to convey control signals in a reverse direction relative to the energy transfer, basically using the same transmission technique. The control signals may be modulated with respect to frequency, phase or amplitude.

Thus, the feedback information may be transferred either by a separate communication system including receivers and transmitters or may be integrated in the energy system. In accordance with the present invention, such an integrated information feedback and energy system comprises an implantable internal energy receiver for receiving wireless energy, the energy receiver having an internal first coil and a first electronic circuit connected to the first coil, and an external energy transmitter for transmitting wireless energy, the energy transmitter having an external second coil and a second electronic circuit connected to the second coil. The external second coil of the energy transmitter transmits wireless energy which is received by the first coil of the energy receiver. This system further comprises a power switch for switching the connection of the internal first coil to the first electronic circuit on and off, such that feedback information related to the charging of the first coil is received by the external energy transmitter in the form of an impedance variation in the load of the external second coil, when the power switch switches the connection of the internal first coil to the first electronic circuit on and off. In implementing this system in the arrangement of FIG. 32, the switch **3260** is either separate and controlled by the internal control unit **3150**, or integrated in the internal control unit **3150**. It should be understood that the switch **3260** should be interpreted in its broadest embodiment. This means a transistor, MCU, MCP, ASIC, FPGA or a DA converter or any other electronic component or circuit that may switch the power on and off.

To conclude, the energy supply arrangement illustrated in FIG. 32 may operate basically in the following manner. The energy balance is first determined by the internal control unit **3150** of the determination device. A control signal reflecting the required amount of energy is also created by the internal control unit **3150**, and the control signal is transmitted from the internal signal transmitter **3270** to the external signal receiver **3040c**. Alternatively, the energy balance can be determined by the external control unit **3040b** instead depending on the implementation, as mentioned above. In that case, the control signal may carry measurement results from various sensors. The amount of energy emitted from the external energy source **1004a** can then be regulated by the external control unit **3040b**, based on the determined energy balance, e.g. in response to the received control signal. This process may be repeated intermittently at certain intervals during ongoing energy transfer, or may be executed on a more or less continuous basis during the energy transfer.

The amount of transferred energy can generally be regulated by adjusting various transmission parameters in the

external energy source **3040a**, such as voltage, current, amplitude, wave frequency and pulse characteristics.

This system may also be used to obtain information about the coupling factors between the coils in a TET system even to calibrate the system both to find an optimal place for the external coil in relation to the internal coil and to optimize energy transfer. Simply comparing in this case the amount of energy transferred with the amount of energy received. For example if the external coil is moved the coupling factor may vary and correctly displayed movements could cause the external coil to find the optimal place for energy transfer. Preferably, the external coil is adapted to calibrate the amount of transferred energy to achieve the feedback information in the determination device, before the coupling factor is maximized.

This coupling factor information may also be used as a feedback during energy transfer. In such a case, the energy system of the present invention comprises an implantable internal energy receiver for receiving wireless energy, the energy receiver having an internal first coil and a first electronic circuit connected to the first coil, and an external energy transmitter for transmitting wireless energy, the energy transmitter having an external second coil and a second electronic circuit connected to the second coil. The external, second coil of the energy transmitter transmits wireless energy which is received by the first coil of the energy receiver. This system further comprises a feedback device for communicating out the amount of energy received in the first coil as a feedback information, and wherein the second electronic circuit includes a determination device for receiving the feedback information and for comparing the amount of transferred energy by the second coil with the feedback information related to the amount of energy received in the first coil to obtain the coupling factor between the first and second coils. The energy transmitter may regulate the transmitted energy in response to the obtained coupling factor.

With reference to FIG. 33, although wireless transfer of energy for operating the device has been described above to enable non-invasive operation, it will be appreciated that the device can be operated with wire bound energy as well. Such an example is shown in FIG. 33, wherein an external switch **3260** is interconnected between the external energy source **3040a** and an operation device, such as an electric motor **3070** operating the device **10**. An external control unit **3040b** controls the operation of the external switch **3260** to effect proper operation of the device **10**.

FIG. 34 illustrates different embodiments for how received energy can be supplied to and used by the device **10**. Similar to the example of FIG. 32, an internal energy receiver **3020** receives wireless energy E from an external energy source **3040a** which is controlled by a transmission control unit **3040b**. The internal energy receiver **3020** may comprise a constant voltage circuit, indicated as a dashed box "constant V" in the figure, for supplying energy at constant voltage to the device **10**. The internal energy receiver **3020** may further comprise a constant current circuit, indicated as a dashed box "constant C" in the figure, for supplying energy at constant current to the device **10**.

The device **10** comprises an energy consuming part **10a**, which may be a motor, pump, restriction device, or any other medical appliance that requires energy for its electrical operation. The device **10** may further comprise an energy storage device **10b** for storing energy supplied from the internal energy receiver **3020**. Thus, the supplied energy may be directly consumed by the energy consuming part **10a**, or stored by the energy storage device **10b**, or the

supplied energy may be partly consumed and partly stored. The device 10 may further comprise an energy stabilizing unit 10c for stabilizing the energy supplied from the internal energy receiver 3020. Thus, the energy may be supplied in a fluctuating manner such that it may be necessary to stabilize the energy before consumed or stored.

The energy supplied from the internal energy receiver 3020 may further be accumulated and/or stabilized by a separate energy stabilizing unit 3280 located outside the device 10, before being consumed and/or stored by the device 10. Alternatively, the energy stabilizing unit 3280 may be integrated in the internal energy receiver 3020. In either case, the energy stabilizing unit 3280 may comprise a constant voltage circuit and/or a constant current circuit.

It should be noted that FIG. 32 and FIG. 34 illustrate some possible but non-limiting implementation options regarding how the various shown functional components and elements can be arranged and connected to each other. However, the skilled person will readily appreciate that many variations and modifications can be made within the scope of the present invention.

FIG. 35 schematically shows an energy balance measuring circuit of one of the proposed designs of the system for controlling transmission of wireless energy, or energy balance control system. The circuit has an output signal centered on 2.5V and proportionally related to the energy imbalance. The derivative of this signal shows if the value goes up and down and how fast such a change takes place. If the amount of received energy is lower than the energy used by implanted components of the device, more energy is transferred and thus charged into the energy source. The output signal from the circuit is typically feed to an A/D converter and converted into a digital format. The digital information can then be sent to the external energy-transmission device allowing it to adjust the level of the transmitted energy. Another possibility is to have a completely analog system that uses comparators comparing the energy balance level with certain maximum and minimum thresholds sending information to external energy-transmission device if the balance drifts out of the max/min window.

The schematic FIG. 35 shows a circuit implementation for a system that transfers energy to the implanted energy components of the device of the present invention from outside of the patient's body using inductive energy transfer. An inductive energy transfer system typically uses an external transmitting coil and an internal receiving coil. The receiving coil, L1, is included in the schematic FIG. 18; the transmitting parts of the system are excluded.

The implementation of the general concept of energy balance and the way the information is transmitted to the external energy transmitter can of course be implemented in numerous different ways. The schematic FIG. 35 and the above described method of evaluating and transmitting the information should only be regarded as examples of how to implement the control system.

Circuit Details

In FIG. 35 the symbols Y1, Y2, Y3 and so on symbolize test points within the circuit. The components in the diagram and their respective values are values that work in this particular implementation which of course is only one of an infinite number of possible design solutions.

Energy to power the circuit is received by the energy receiving coil L1. Energy to implanted components is transmitted in this particular case at a frequency of 25 kHz. The energy balance output signal is present at test point Y1.

Those skilled in the art will realize that the above various embodiments of the system could be combined in many

different ways. For example, the electric switch 3060 of FIG. 18 could be incorporated in any of the embodiments of FIGS. 21-27, the hydraulic valve shifting device 3140 of FIG. 21 could be incorporated in the embodiment of FIG. 20, and the gear box 3240 could be incorporated in the embodiment of FIG. 19. Please observe that the switch simply could mean any electronic circuit or component.

The embodiments described in connection with FIGS. 32, 34 and 35 identify a method and a system for controlling transmission of wireless energy to implanted energy consuming components of an electrically operable device. Such a method and system will be defined in general terms in the following.

A method is thus provided for controlling transmission of wireless energy supplied to implanted energy consuming components of a device as described above. The wireless energy E is transmitted from an external energy source located outside the patient and is received by an internal energy receiver located inside the patient, the internal energy receiver being connected to the implanted energy consuming components of the device for directly or indirectly supplying received energy thereto. An energy balance is determined between the energy received by the internal energy receiver and the energy used for the device. The transmission of wireless energy E from the external energy source is then controlled based on the determined energy balance.

The wireless energy may be transmitted inductively from a primary coil in the external energy source to a secondary coil in the internal energy receiver. A change in the energy balance may be detected to control the transmission of wireless energy based on the detected energy balance change. A difference may also be detected between energy received by the internal energy receiver and energy used for the medical device, to control the transmission of wireless energy based on the detected energy difference.

When controlling the energy transmission, the amount of transmitted wireless energy may be decreased if the detected energy balance change implies that the energy balance is increasing, or vice versa. The decrease/increase of energy transmission may further correspond to a detected change rate.

The amount of transmitted wireless energy may further be decreased if the detected energy difference implies that the received energy is greater than the used energy, or vice versa.

The decrease/increase of energy transmission may then correspond to the magnitude of the detected energy difference.

As mentioned above, the energy used for the medical device may be consumed to operate the medical device, and/or stored in at least one energy storage device of the medical device.

When electrical and/or physical parameters of the medical device and/or physical parameters of the patient are determined, the energy may be transmitted for consumption and storage according to a transmission rate per time unit which is determined based on said parameters. The total amount of transmitted energy may also be determined based on said parameters.

When a difference is detected between the total amount of energy received by the internal energy receiver and the total amount of consumed and/or stored energy, and the detected difference is related to the integral over time of at least one measured electrical parameter related to said energy balance, the integral may be determined for a monitored voltage and/or current related to the energy balance.

When the derivative is determined over time of a measured electrical parameter related to the amount of consumed and/or stored energy, the derivative may be determined for a monitored voltage and/or current related to the energy balance.

The transmission of wireless energy from the external energy source may be controlled by applying to the external energy source electrical pulses from a first electric circuit to transmit the wireless energy, the electrical pulses having leading and trailing edges, varying the lengths of first time intervals between successive leading and trailing edges of the electrical pulses and/or the lengths of second time intervals between successive trailing and leading edges of the electrical pulses, and transmitting wireless energy, the transmitted energy generated from the electrical pulses having a varied power, the varying of the power depending on the lengths of the first and/or second time intervals.

In that case, the frequency of the electrical pulses may be substantially constant when varying the first and/or second time intervals. When applying electrical pulses, the electrical pulses may remain unchanged, except for varying the first and/or second time intervals. The amplitude of the electrical pulses may be substantially constant when varying the first and/or second time intervals. Further, the electrical pulses may be varied by only varying the lengths of first time intervals between successive leading and trailing edges of the electrical pulses.

A train of two or more electrical pulses may be supplied in a row, wherein when applying the train of pulses, the train having a first electrical pulse at the start of the pulse train and having a second electrical pulse at the end of the pulse train, two or more pulse trains may be supplied in a row, wherein the lengths of the second time intervals between successive trailing edge of the second electrical pulse in a first pulse train and leading edge of the first electrical pulse of a second pulse train are varied.

When applying they electrical pulses, the electrical pulses may have a substantially constant current and a substantially constant voltage. The electrical pulses may also have a substantially constant current and a substantially constant voltage. Further, the electrical pulses may also have a substantially constant frequency. The electrical pulses within a pulse train may likewise have a substantially constant frequency.

The circuit formed by the first electric circuit and the external energy source may have a first characteristic time period or first time constant, and when effectively varying the transmitted energy, such frequency time period may be in the range of the first characteristic time period or time constant or shorter.

A system comprising a device as described above is thus also provided for controlling transmission of wireless energy supplied to implanted energy consuming components of the device. In its broadest sense, the system comprises a control device for controlling the transmission of wireless energy from an energy-transmission device, and an implantable internal energy receiver for receiving the transmitted wireless energy, the internal energy receiver being connected to implantable energy consuming components of the device for directly or indirectly supplying received energy thereto. The system further comprises a determination device adapted to determine an energy balance between the energy received by the internal energy receiver and the energy used for the implantable energy consuming components of the device, wherein the control device controls the transmission of

wireless energy from the external energy-transmission device, based on the energy balance determined by the determination device.

Further, the system may comprise any of the following:

A primary coil in the external energy source adapted to transmit the wireless energy inductively to a secondary coil in the internal energy receiver.

The determination device is adapted to detect a change in the energy balance, and the control device controls the transmission of wireless energy based on the detected energy balance change

The determination device is adapted to detect a difference between energy received by the internal energy receiver and energy used for the implantable energy consuming components of the device, and the control device controls the transmission of wireless energy based on the detected energy difference.

The control device controls the external energy-transmission device to decrease the amount of transmitted wireless energy if the detected energy balance change implies that the energy balance is increasing, or vice versa, wherein the decrease/increase of energy transmission corresponds to a detected change rate.

The control device controls the external energy-transmission device to decrease the amount of transmitted wireless energy if the detected energy difference implies that the received energy is greater than the used energy, or vice versa, wherein the decrease/increase of energy transmission corresponds to the magnitude of said detected energy difference.

The energy used for the device is consumed to operate the device, and/or stored in at least one energy storage device of the device.

Where electrical and/or physical parameters of the device and/or physical parameters of the patient are determined, the energy-transmission device transmits the energy for consumption and storage according to a transmission rate per time unit which is determined by the determination device based on said parameters. The determination device also determines the total amount of transmitted energy based on said parameters.

When a difference is detected between the total amount of energy received by the internal energy receiver and the total amount of consumed and/or stored energy, and the detected difference is related to the integral over time of at least one measured electrical parameter related to the energy balance, the determination device determines the integral for a monitored voltage and/or current related to the energy balance.

When the derivative is determined over time of a measured electrical parameter related to the amount of consumed and/or stored energy, the determination device determines the derivative for a monitored voltage and/or current related to the energy balance.

The energy-transmission device comprises a coil placed externally to the human body, and an electric circuit is provided to power the external coil with electrical pulses to transmit the wireless energy. The electrical pulses have leading and trailing edges, and the electric circuit is adapted to vary first time intervals between successive leading and trailing edges and/or second time intervals between successive trailing and leading edges of the electrical pulses to vary the power of the transmitted wireless energy. As a result, the energy receiver receiving the transmitted wireless energy has a varied power.

The electric circuit is adapted to deliver the electrical pulses to remain unchanged except varying the first and/or second time intervals.

The electric circuit has a time constant and is adapted to vary the first and second time intervals only in the range of the first time constant, so that when the lengths of the first and/or second time intervals are varied, the transmitted power over the coil is varied.

The electric circuit is adapted to deliver the electrical pulses to be varied by only varying the lengths of first time intervals between successive leading and trailing edges of the electrical pulses.

The electric circuit is adapted to supplying a train of two or more electrical pulses in a row, said train having a first electrical pulse at the start of the pulse train and having a second electrical pulse at the end of the pulse train, and

the lengths of the second time intervals between successive trailing edge of the second electrical pulse in a first pulse train and leading edge of the first electrical pulse of a second pulse train are varied by the first electronic circuit.

The electric circuit is adapted to provide the electrical pulses as pulses having a substantially constant height and/or amplitude and/or intensity and/or voltage and/or current and/or frequency.

The electric circuit has a time constant, and is adapted to vary the first and second time intervals only in the range of the first time constant, so that when the lengths of the first and/or second time intervals are varied, the transmitted power over the first coil are varied.

The electric circuit is adapted to provide the electrical pulses varying the lengths of the first and/or the second time intervals only within a range that includes the first time constant or that is located relatively close to the first time constant, compared to the magnitude of the first time constant.

FIGS. 36-39 show in more detail block diagrams of four different ways of hydraulically or pneumatically powering an implanted device according to the invention.

FIG. 36 shows a system as described above with. The system comprises an implanted device 10 and further a separate regulation reservoir 10130, a one way pump 10090 and an alternate valve 10140.

FIG. 37 shows the device 10 and a fluid reservoir 10130. By moving the wall of the regulation reservoir or changing the size of the same in any other different way, the adjustment of the device may be performed without any valve, just free passage of fluid any time by moving the reservoir wall.

FIG. 38 shows the device 10, a two way pump 10090 and the regulation reservoir 10130.

FIG. 39 shows a block diagram of a reversed servo system with a first closed system controlling a second closed system. The servo system comprises a regulation reservoir 10130 and a servo reservoir 10500. The servo reservoir 10500 mechanically controls an implanted device 10 via a mechanical interconnection 10540. The device has an expandable/contactable cavity. This cavity is preferably expanded or contracted by supplying hydraulic fluid from the larger adjustable reservoir 10520 in fluid connection with the device 10. Alternatively, the cavity contains compressible gas, which can be compressed and expanded under the control of the servo reservoir 10500.

The servo reservoir 10500 can also be part of the device itself.

In one embodiment, the regulation reservoir is placed subcutaneous under the patient's skin and is operated by

pushing the outer surface thereof by means of a finger. This system is illustrated in FIGS. 40a-c. In FIG. 40a, a flexible subcutaneous regulation reservoir 10130 is shown connected to a bulge shaped servo reservoir 10500 by means of a conduit 10110. This bellow shaped servo reservoir 10500 is comprised in a flexible device 10. In the state shown in FIG. 40a, the servo reservoir 10500 contains a minimum of fluid and most fluid is found in the regulation reservoir 10130. Due to the mechanical interconnection between the servo reservoir 10500 and the device 10, the outer shape of the device 10 is contracted, i.e., it occupies less than its maximum volume. This maximum volume is shown with dashed lines in the figure.

FIG. 40b shows a state wherein a user, such as the patient in with the device is implanted, presses the regulation reservoir 10130 so that fluid contained therein is brought to flow through the conduit 10110 and into the servo reservoir 10500, which, thanks to its bellow shape, expands longitudinally. This expansion in turn expands the device 10 so that it occupies its maximum volume, thereby stretching the stomach wall (not shown), which it contacts.

The regulation reservoir 10130 is preferably provided with means 10130a for keeping its shape after compression. This means, which is schematically shown in FIG. 40c, will thus keep the device 10 in a stretched position also when the user releases the regulation reservoir. In this way, the regulation reservoir essentially operates as an on/off switch for the system.

An alternative embodiment of hydraulic or pneumatic operation will now be described with reference to FIGS. 41 and 42a-c. The block diagram shown in FIG. 41 comprises with a first closed system controlling a second closed system. The first system comprises a regulation reservoir 10130 and a servo reservoir 10500. The servo reservoir 10500 mechanically controls a larger adjustable reservoir 10520 via a mechanical interconnection 10540. An implanted device 10 having an expandable/contactable cavity is in turn controlled by the larger adjustable reservoir 10520 by supply of hydraulic fluid from the larger adjustable reservoir 10520 in fluid connection with the device 10.

An example of this embodiment will now be described with reference to FIG. 42a-c. Like in the previous embodiment, the regulation reservoir is placed subcutaneous under the patient's skin and is operated by pushing the outer surface thereof by means of a finger. The regulation reservoir 10130 is in fluid connection with a bellow shaped servo reservoir 10500 by means of a conduit 10110. In the first closed system 10130, 10110, 10500 shown in FIG. 42a, the servo reservoir 10500 contains a minimum of fluid and most fluid is found in the regulation reservoir 10130.

The servo reservoir 10500 is mechanically connected to a larger adjustable reservoir 10520, in this example also having a bellow shape but with a larger diameter than the servo reservoir 10500. The larger adjustable reservoir 1052 is in fluid connection with the device 10. This means that when a user pushes the regulation reservoir 10130, thereby displacing fluid from the regulation reservoir 10130 to the servo reservoir 10500, the expansion of the servo reservoir 10500 will displace a larger volume of fluid from the larger adjustable reservoir 10520 to the device 10. In other words, in this reversed servo, a small volume in the regulation reservoir is compressed with a higher force and this creates a movement of a larger total area with less force per area unit.

Like in the previous embodiment described above with reference to FIGS. 40a-c, the regulation reservoir 10130 is preferably provided with means 10130a for keeping its

shape after compression. This means, which is schematically shown in the figure, will thus keep the device 10 in a stretched position also when the user releases the regulation reservoir. In this way, the regulation reservoir essentially operates as an on/off switch for the system.

The invention claimed is:

1. A device for treating an aneurysm of a human or mammal patient comprising:

an implantable member adapted to hold fluid, the member being adapted to be placed in connection with the outside of a blood vessel having the aneurysm, and to exercise a pressure on the outside of the blood vessel having the aneurysm, wherein the device is adapted to prevent or reduce an expansion of the aneurysm by exerting said pressure on the outside of the blood vessel, and

a pressure regulator adapted to regulate the pressure in the member

a sensor or measuring device for sensing or measuring an expansion of the aneurysm

a control unit adapted to control pressure adjustments based on a signal generated by the sensor and control the pressure regulator such that the provided pressure does not exceed a diastolic blood pressure of a treated patient having the diastolic blood pressure, such that the blood flow of the treated patient remains unaffected.

2. The device according to claim 1, wherein the device is adapted to be postoperatively adjusted.

3. The device according to claim 2, wherein the device is adapted to perform self adjustments of the pressure applied to the aneurysm within a predetermined treatment interval.

4. The device according to claim 1, wherein the pressure regulator is adapted to even out the difference in pressure in the implantable member during the systolic and diastolic phase for reducing the pressure difference or providing a substantially even outside pressure on the aneurysm.

5. The device according to claim 1, wherein the implantable member is adapted to exert an essentially constant pressure or a pressure reducing the pressure difference, caused by the changes in blood pressure in said blood vessel, on the aneurysm.

6. The device according to claim 1, wherein the implantable member is Y-shaped, and wherein the implantable Y-shaped member is adapted to be placed at the Aorta Bifurcation.

7. The device according to claim 1, wherein the pressure regulator comprises an expandable implantable first reservoir, and wherein the pressure regulator is adapted to even out the difference in pressure in the implantable first reservoir in the systolic and diastolic phase to reduce the differences or to achieve a substantially even pressure affecting the aneurysm from the outside of said blood vessel.

8. The device according to claim 7, wherein the expandable implantable first reservoir is spring loaded.

9. The device according to claim 1, wherein the pressure regulator comprises a pump.

10. The device according to claim 1, wherein the device is adapted to increase the pressure on the blood vessel when the aneurysm expands, and wherein the device comprises a control device adapted to increase the pressure on the blood vessel when at least one of: the aneurysm expands more than a predetermined value and the aneurysm expands more than a predetermined value during a time period.

11. The device according to claim 10, further comprising a volume control unit adapted to directly or indirectly control the volume in the implantable member based on a

signal generated by the sensor or measuring device for controlling an expansion of the aneurysm.

12. The device according to claim 11, wherein the volume control unit controls the volume in the implantable member for generating a signal corresponding to a parameter related to the aneurysm or the treatment of the aneurysm based on a signal indicative of at least one of: a parameter that corresponds to the size of the aneurysm, flow of fluid from the implantable member to the first reservoir, volume in the first reservoir, and pressure in the fluid filled implantable member.

13. The device according to claim 1, wherein the implantable member is divided into a plurality of sub-reservoirs, and wherein the sub-reservoirs are provided in at least one of the following ways: axially along the blood vessel and radially along the blood vessel.

14. The device according to claim 1, further comprising an electrical pulse generator adapted to provide electrical signals for stimulation of the aneurysm wall via electrodes located on the inside of the implantable member.

15. The device according to claim 14, further comprising a control unit adapted to vary the position of the electrical stimulation signals for stimulation of the aneurysm.

16. The device according to claim 1, further comprising a feed back alarm system based on control of the expansion of the aneurysm.

17. The device according to claim 1, further comprising an implantable internal energy source for powering implantable energy consuming components of the device.

18. The device according claim 17, further comprising a wireless energy-transmission device for non-invasively energizing implantable energy consuming components of the device with wireless energy.

19. The device according to claim 17, further comprising a feedback device for sending feedback information from inside the patient's body to the outside thereof, the feedback information being related to at least one of a physical parameter of the patient and a functional parameter related to the device.

20. The device according to claim 17, further comprising a sensor and/or a measuring device and an implantable internal control unit for controlling the device in response to information being related to at least one of: a) a physical parameter of the patient sensed by the sensor or measured by the measuring device, and b) a functional parameter related to the device sensed by the sensor or measured by the measuring device.

21. The device according to claim 17, further comprising implantable electrical components including (i) at least one voltage level guard, (ii) at least one constant current guard, or (iii) at least one voltage level guard and at least one constant current guard.

22. The device according to claim 17, further comprising an operation device for operating the device, the operating device comprising at least one of: a) at least one motor, b) at least one motor comprising a servo designed to decrease the force needed for the motor to operate the device, instead the motor acting a longer way increasing the time for a determined action, and c) at least one pump for operating the device, wherein the pump is adapted to operate a hydraulic operation device for operating the device.

23. The device according to claim 17, further comprising an external data communicator and an implantable internal data communicator communicating with the external data communicator, wherein (i) the internal communicator feeds data related to the device or the patient to the external data communicator, (ii) the external data communicator feeds

33

data to the internal data communicator, or (iii) the internal communicator feeds data related to the device or the patient to the external data communicator and the external data communicator feeds data to the internal data communicator.

24. The device according to claim **1**, wherein the implantable member is a hydraulic implantable member adapted to exert a pressure using hydraulic force.

25. The device according to claim **24**, wherein the pressure regulator comprises:

an implantable expandable first reservoir, wherein the expandable first reservoir is connected to the implantable member and adapted to regulate the pressure in the implantable member by receiving a volume of liquid from the implantable member to regulate the pressure in the implantable member, when the aneurysm expands, the first reservoir having a predetermined optimal pressure regulation volume treatment interval, and

34

a second reservoir connected to the first reservoir, the device being adapted to move liquid from the first reservoir to the second reservoir to keep the first reservoir within the regulation interval, when the aneurysm expands and liquid is moved from the implantable member into the first reservoir.

26. The device according to claim **25**, wherein at least one of the first and second reservoirs is spring loaded.

27. The device according to claim **24**, further comprising a volume control unit adapted to control the volume in the implantable member for generating a signal corresponding to a parameter related to the aneurysm or the treatment of the aneurysm based on a signal indicative of at least one of a parameter that corresponds to the size of the aneurysm, flow of fluid from the implantable member to the first reservoir, volume in the first reservoir, and pressure in the fluid filled implantable member.

* * * * *

专利名称(译)	用于治疗动脉瘤的装置		
公开(公告)号	US10321850	公开(公告)日	2019-06-18
申请号	US12/682462	申请日	2008-10-10
[标]申请(专利权)人(译)	福塞尔PETER		
申请(专利权)人(译)	福塞尔PETER		
当前申请(专利权)人(译)	福塞尔, PETER		
[标]发明人	FORSELL PETER		
发明人	FORSELL, PETER		
IPC分类号	A61M29/00 A61B5/00 A61B5/02 A61B5/07 A61B17/12 A61B17/135 A61M1/10 A61M1/12 A61B17/00 A61F2/30 A61B90/00		
CPC分类号	A61B5/076 A61B5/02007 A61B5/4393 A61B5/6862 A61B5/6876 A61B5/6885 A61B17/12009 A61B17/1355 A61B2017/00221 A61B2017/00411 A61B2017/00703 A61B2017/00734 A61B2090/065 A61B2562/0247 A61B2562/0261 A61F2002/3067 A61F2002/30668 A61F2250/0001 A61F2250/0002 A61M1/10 A61M1/12 A61M1/125 A61B5/02014 A61M1/1043 A61M1/1049 A61M1/106 A61M1/1067 A61M1/1086		
优先权	60/960715 2007-10-11 US 60/960716 2007-10-11 US		
其他公开文献	US20100211091A1		
外部链接	Espacenet		

摘要(译)

在用于治疗人或哺乳动物患者的动脉瘤的系统，装置和方法中，提供了适于保持流体的可植入构件。该构件适于与具有动脉瘤的血管连接并对所述血管的动脉瘤施加压力。

