



US010212528B2

(12) **United States Patent**
Goldstein

(10) **Patent No.:** **US 10,212,528 B2**
(45) **Date of Patent:** ***Feb. 19, 2019**

(54) **METHOD AND DEVICE FOR AUDIO RECORDING**

G06F 19/00 (2013.01); *G06F 19/36* (2013.01); *G16H 50/20* (2018.01); *G16H 50/30* (2018.01);

(71) Applicant: **Staton Techiya LLC**, Delray Beach, FL (US)

(Continued)

(72) Inventor: **Steven W Goldstein**, Delray Beach, FL (US)

(58) **Field of Classification Search**
CPC H04R 29/004; A61B 5/021; A61B 5/024; A61B 5/1117; A61B 5/14542; A61B 5/6817

(73) Assignee: **Staton Techiya, LLC**, Delray Beach, FL (US)

See application file for complete search history.

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 0 days.

(56) **References Cited**

This patent is subject to a terminal disclaimer.

U.S. PATENT DOCUMENTS

6,118,878 A 9/2000 Jones
6,754,359 B1 6/2004 Svean et al.
(Continued)

FOREIGN PATENT DOCUMENTS

EP 1640972 A1 3/2006

Primary Examiner — Long K Tran

(74) *Attorney, Agent, or Firm* — Akerman LLP; Peter A. Chiabotti; Mammen (Roy) P. Zachariah, Jr.

(21) Appl. No.: **15/790,771**

(22) Filed: **Oct. 23, 2017**

(65) **Prior Publication Data**

US 2018/0132050 A1 May 10, 2018

(57) **ABSTRACT**

An acquisition system includes a processor, one or more sensors operatively coupled to the processor where the one or more sensors acquire at the ear, on the ear or within an ear canal, one or more of acceleration, blood oxygen saturation, blood pressure or heart-rate, and the one or more sensors configured to monitor a biological state or a physical motion or both for an event. The event can be a detection of a discrepancy when compared with a set of reference data by the one or more sensors or the biological state or the event can be one of a detection of an abrupt movement of a headset operatively coupled to the processor, a change in location of an earpiece operatively coupled to the processor, a touching of the headset, a recognizing of a voice command, a starting or ending of a phone call, or a scheduled time.


Related U.S. Application Data

(60) Continuation of application No. 15/137,730, filed on Apr. 25, 2016, now Pat. No. 9,900,718, which is a (Continued)

(51) **Int. Cl.**
A61B 5/11 (2006.01)
H04R 29/00 (2006.01)
(Continued)

(52) **U.S. Cl.**
CPC *H04R 29/004* (2013.01); *A61B 5/0205* (2013.01); *A61B 5/1117* (2013.01); *A61B 5/14542* (2013.01); *A61B 5/6817* (2013.01);

20 Claims, 11 Drawing Sheets



Related U.S. Application Data

continuation of application No. 14/576,236, filed on Dec. 19, 2014, now Pat. No. 9,323,899, which is a continuation of application No. 14/048,324, filed on Oct. 8, 2013, now Pat. No. 8,918,141, which is a division of application No. 13/556,509, filed on Jul. 24, 2012, now Pat. No. 8,582,782, which is a continuation of application No. 12/024,842, filed on Feb. 1, 2008, now Pat. No. 8,254,591.

(60) Provisional application No. 60/887,800, filed on Feb. 1, 2007.

- (51) **Int. Cl.**
H04R 25/00 (2006.01)
H04M 1/65 (2006.01)
A61B 5/0205 (2006.01)
A61B 5/145 (2006.01)
A61B 5/00 (2006.01)
G06F 19/00 (2018.01)
H04R 1/10 (2006.01)
G16H 50/30 (2018.01)
G16H 50/20 (2018.01)

- A61B 5/021* (2006.01)
A61B 5/024 (2006.01)
 (52) **U.S. Cl.**
 CPC *H04M 1/65* (2013.01); *H04R 1/1091* (2013.01); *H04R 25/70* (2013.01); *A61B 5/021* (2013.01); *A61B 5/024* (2013.01); *H04R 2201/109* (2013.01); *H04R 2410/05* (2013.01); *H04R 2499/11* (2013.01)

(56) **References Cited**

U.S. PATENT DOCUMENTS

- | | | | |
|--------------|----|---------|---------------|
| 7,502,484 | B2 | 3/2009 | Ngia et al. |
| 7,707,268 | B2 | 4/2010 | Saito et al. |
| 7,908,617 | B2 | 3/2011 | Kimura |
| 8,718,295 | B2 | 5/2014 | Sung et al. |
| 2001/0046304 | A1 | 11/2001 | Rast |
| 2002/0143242 | A1 | 10/2002 | Nemirovski |
| 2006/0262938 | A1 | 11/2006 | Gauger et al. |
| 2008/0101638 | A1 | 5/2008 | Ziller |
| 2008/0130906 | A1 | 6/2008 | Goldstein |
| 2009/0105605 | A1 | 4/2009 | Abreu |
| 2011/0293105 | A1 | 12/2011 | Arie |
| 2012/0257764 | A1 | 10/2012 | Sung |
| 2015/0094914 | A1 | 4/2015 | Abreu |




FIG. 1





FIG. 2



250

FIG. 3




FIG. 4




FIG. 5




FIG. 6




FIG. 7




FIG. 8




FIG. 9




FIG. 10




FIG. 11




FIG. 12

METHOD AND DEVICE FOR AUDIO RECORDING

CROSS REFERENCE TO RELATED APPLICATIONS

This Application is a continuation Application of U.S. application Ser. No. 15/137,730 filed on Apr. 25, 2016 which is a continuation Application of U.S. application Ser. No. 14/576,236 (now U.S. Pat. No. 9,323,899), filed on Dec. 19, 2014, which is a continuation Application of U.S. application Ser. No. 14/048,324 filed Oct. 8, 2013 (now U.S. Pat. No. 8,918,141) which is a Divisional Application of U.S. application Ser. No. 13/556,509, filed Jul. 24, 2012 (now U.S. Pat. No. 8,582,782) which is a continuation of U.S. application Ser. No. 12/024,842, filed Feb. 1, 2008 (now U.S. Pat. No. 8,254,591) which claims priority to Provisional Application No. 60/887,800 filed on Feb. 1, 2007, the entire disclosures of which are incorporated herein by reference.

FIELD

The present invention is generally directed to the detection and recording of acoustic events, and in particular, though not exclusively, to the detection and recording of acoustic events as measured by an earpiece.

BACKGROUND

The human auditory system has been increasingly stressed to tolerate high noise and sound levels. However, excessive high level exposure over long durations can damage hearing. Moreover, a user's attention to sounds within the environment can be compromised when media devices such as music players, cell phones, and Bluetooth™ earpieces deliver audio to the ear.

In industrial environments where noise is frequently present, workers can be subject to loud excessive noises over long periods of time in addition to the sounds presented by the media devices. Although earplugs help suppress the noise and mitigate the physiological and psychological effects of the noise on the workers, there are few accurate indications of the noise exposure to which the workers are subjected.

A need therefore can be appreciated for assessing sound exposure levels in various environmental settings.

SUMMARY

Embodiments in accordance with the present invention provide a method and device for audio recording.

At least one exemplary embodiment is directed to the detection and recording of acoustic events, and in at least one exemplary embodiment is further directed to a device for sound reproduction, sound recording, audio forensics and audio communications using earpieces.

At least one exemplary embodiment is directed to a multiple earpiece device (e.g., a headset) which can include a left earpiece, a right earpiece, a memory and a processor. The left earpiece can include a left Ambient Sound Microphone (LASM) to capture ambient sound in an environment, and a left Ear Canal Microphone (LECM) to capture internal sound in a left ear canal. The right earpiece can include a right Ambient Sound Microphone (RASM) to capture the ambient sound in the environment and a right Ear Canal Microphone (RECM) to capture internal sound in a right ear

canal. The internal sound can be an ambient sound, speech, or audio content portion resident in the ear canal. The memory (e.g., RAM) can record a history (e.g., Sound pressure level (SPL) as a function of time) of the ambient sound and the internal sound, and the processor can save a recent portion of the history responsive to an event. The event can be a touching of the headset, a recognizing of a voice command, a starting or ending of a phone call, or a scheduled time. In one configuration, the processor can trigger the event responsive to detecting an abrupt movement of the headset, or a change in location of the earpiece.

The memory can include a data buffer to temporarily capture the ambient sound and the internal sound, and a storage memory to save from the data buffer the recent portion of the history in a compressed data format responsive to a directive by the processor. In one configuration, the data buffer can be a circular buffer that temporarily stores the ambient sound and the internal sound at a current time point to a previous time point. The processor can save a last two minutes of the history, and audibly present the last two minutes responsive to a user request. The history can be at least one among a conversation, a voice mail, and an audio recording. Additionally the history can record data (e.g., SPL values) from both earpieces. Also note that in at least one exemplary embodiment a single earpiece can be used. The earpiece can include an audio interface communicatively coupled to the processor to deliver audio content by way of a left Ear Canal Receiver (LECR) and a right ECR, wherein the memory records a history of the audio content with the residual sound and the internal sound. In one arrangement, at least a portion of the left earpiece and a portion of the right earpiece can constitute a microphone array, and the processor can increase a signal to noise ratio of the audio content with respect to the ambient sound using the microphone array. The processor can binaurally record the ambient sound and the internal sound from the left earpiece and the right earpiece.

At least one further exemplary embodiment is directed to an earpiece at least partially occluding an ear canal, which can include an Ambient Sound Microphone (ASM) to capture ambient sound in an environment, an Ear Canal Microphone (ECM) to capture internal sound in the ear canal, a memory to record a history of the ambient sound and the internal sound, and a processor operatively coupled to the ASM, the ECM and the memory to save a recent portion of the history responsive to an event. The event can be a touching of the headset, a recognizing of a voice command, a starting or ending of a phone call, a scheduled time, or an abrupt movement of the headset. The processor can save the history of at least one among a conversation, a voice mail, and an audio recording responsive to the event. In another arrangement, the processor can monitor the ambient sound for a Sound Pressure Level (SPL) change, and in response to detecting the SPL change commit the history to the memory.

At least one further exemplary embodiment is directed to an earpiece at least partially occluding an ear canal, which can include an Ambient Sound Microphone (ASM) to capture ambient sound in an environment, an Ear Canal Microphone (ECM) to capture internal sound in the ear canal, an Ear Canal Receiver (ECR) to deliver audio content to an ear canal, a memory to record a history of the ambient sound, the internal sound, and the audio content, and a processor operatively coupled to the ASM, the ECM and the memory to save a recent portion of the history responsive to an event. The processor can continually record the history in the memory. The event can be a touching of the headset, a

recognizing of a voice command, a starting or ending of a phone call, or an abrupt movement of the headset.

At least one exemplary embodiment is directed to a method for audio recording, which can include the steps of measuring ambient sound in an environment, measuring internal sound in an ear canal, continually recording a history of the ambient sound and the internal sound, and saving a recent portion of the history responsive to detecting an event. The step of continually recording can include temporarily saving the history to a circular data buffer based on a chosen data management scheme (e.g., first-in first-out (FIFO)). A time stamp, a location, and the earpiece (e.g., if there are multiple earpieces) can also be recorded with the history. The method can include recording an audio content delivered to the ear canal with the history in a compressed data format. The event can be a touching of the headset, a recognizing of a voice command, a starting or ending of a phone call, an abrupt movement of the headset, or a scheduled time.

At least one further exemplary embodiment is directed to a method for audio recording, which can include measuring ambient sound in an environment, measuring internal sound in an ear canal, measuring audio content delivered to the ear canal, continually recording a history of the ambient sound, the internal sound and the audio content, and saving a recent portion of the history responsive to detecting an event that is at least one among a touching of the headset, a recognizing of a voice command, a starting or ending of a phone call, or an abrupt movement of the headset. The method can further include data compressing the recent portion of the history in a memory, and issuing a warning message to inform a user when a remaining memory receiving the recent portion of the history is below a predetermined value. The recent portion of the history can be audibly presented responsive to a user request.

BRIEF DESCRIPTION OF THE DRAWINGS

FIG. 1 is a pictorial diagram of an earpiece in accordance with at least one exemplary embodiment;

FIG. 2 is a block diagram of the earpiece in accordance with at least one exemplary embodiment;

FIG. 3 is a flowchart of a method for audio recording in accordance with at least one exemplary embodiment;

FIG. 4 is a block diagram for audio selection in accordance with at least one exemplary embodiment;

FIG. 5 is a block diagram for always-on binaural recording in accordance with at least one exemplary embodiment;

FIG. 6 is a block diagram for activating audio recording in accordance with at least one exemplary embodiment;

FIG. 7 is a flowchart of a method for transient event detection in accordance with at least one exemplary embodiment;

FIG. 8 is a flowchart of a method for event detection in accordance with at least one exemplary embodiment;

FIG. 9 is a flowchart of a method for forensic audio evaluation in accordance with at least one exemplary embodiment;

FIG. 10 is a flowchart of a method for low remaining-memory warning in accordance with at least one exemplary embodiment;

FIG. 11 is a flowchart of a method for remaining record-time in accordance with at least one exemplary embodiment; and

FIG. 12 is a flowchart of a method for remaining memory in accordance with at least one exemplary embodiment.

DETAILED DESCRIPTION

The following description of at least one exemplary embodiment is merely illustrative in nature and is in no way intended to limit the invention, its application, or uses.

Processes, techniques, apparatus, and materials as known by one of ordinary skill in the relevant art may not be discussed in detail but are intended to be part of the enabling description where appropriate, for example the fabrication and use of transducers.

In all of the examples illustrated and discussed herein, any specific values, for example the sound pressure level change, should be interpreted to be illustrative only and non-limiting. Thus, other examples of the exemplary embodiments could have different values.

Note that similar reference numerals and letters refer to similar items in the following figures, and thus once an item is defined in one figure, it may not be discussed for following figures.

Note that herein when referring to correcting or preventing an error or damage (e.g., hearing damage), a reduction of the damage or error and/or a correction of the damage or error are intended.

At least one exemplary embodiment of the invention is directed to an earpiece for ambient sound monitoring and warning detection. Reference is made to FIG. 1 in which an earpiece device, generally indicated as earpiece 100, is constructed and operates in accordance with at least one exemplary embodiment of the invention. As illustrated, earpiece 100 depicts an electro-acoustical assembly 113 for an in-the-ear acoustic assembly, as it would typically be placed in the ear canal 131 of a user 135. The earpiece 100 can be an in the ear earpiece, behind the ear earpiece, receiver in the ear, open-fit device, or any other suitable earpiece type. The earpiece 100 can be partially or fully occluded in the ear canal 131, and is suitable for use with users having healthy or abnormal auditory functioning.

Earpiece 100 includes an Ambient Sound Microphone (ASM) 111 to capture ambient sound, an Ear Canal Receiver (ECR) 125 to deliver audio to an ear canal 131, and an Ear Canal Microphone (ECM) 123 to assess a sound exposure level within the ear canal 131. The earpiece 100 can partially or fully occlude the ear canal 131 to provide various degrees of acoustic isolation. The assembly is designed to be inserted into the users ear canal 131, and to form an acoustic seal with the walls 129 of the ear canal at a location 127 between the entrance 117 to the ear canal 131 and the tympanic membrane (or ear drum) 133. Such a seal is typically achieved by means of a soft and compliant housing of assembly 113. Such a seal creates a closed cavity 131 of approximately 5 cc between the in-ear assembly 113 and the tympanic membrane 133. As a result of this seal, the ECR (speaker) 125 is able to generate a full range bass response when reproducing sounds for the user. This seal also serves to significantly reduce the sound pressure level at the user's eardrum 133 resulting from the sound field at the entrance to the ear canal 131. This seal is also a basis for a sound isolating performance of the electro-acoustic assembly 113.

Located adjacent to the ECR 125, is the ECM 123, which is acoustically coupled to the (closed) ear canal cavity 131. One of its functions is that of measuring the sound pressure level in the ear canal cavity 131 as a part of testing the hearing acuity of the user as well as confirming the integrity of the acoustic seal and the working condition of the

earpiece **100**. In one arrangement, the ASM **111** can be housed in the assembly **113** to monitor sound pressure at the entrance to the occluded or partially occluded ear canal **131**. All transducers shown can receive or transmit audio signals to a processor **121** that undertakes audio signal processing and provides a transceiver for audio via the wired or wireless communication path **119**.

Referring to FIG. 2, a block diagram **200** of the earpiece **100** in accordance with an exemplary embodiment is shown. As illustrated, the earpiece **100** can include the processor **121** operatively coupled to the ASM **111**, ECR **125**, and ECM **123** via one or more Analog to Digital Converters (ADC) **202** and Digital to Analog Converters (DAC) **203**. The processor **121** can utilize computing technologies such as a microprocessor, Application Specific Integrated Chip (ASIC), and/or digital signal processor (DSP) with associated storage memory **208** such as Flash, ROM, RAM, SRAM, DRAM or other memory based technologies for controlling operations of the earpiece device **100**. The processor **121** can also include a clock to record a time stamp.

The memory **208** can store program instructions for execution on the processor **121** as well as captured audio processing data. For instance, memory **208** can be off-chip and external to the processor **121**, and include a data buffer **209** to temporarily capture the ambient sound and the internal sound as a history, and a storage memory to save from the data buffer the recent portion of the history in a compressed data format responsive to a directive by the processor. The data buffer **209** can be a circular buffer that temporarily stores audio sound at a current time point to a previous time point. It should also be noted that the data buffer **209** can in one configuration reside on the processor **121** to provide high speed data access. The storage memory **208** can be non-volatile memory such as SRAM to store captured or compressed data format.

The earpiece **100** can include an audio interface **212** operatively coupled to the processor **121** to receive audio content, for example from a media player or cell phone, and deliver the audio content to the processor **121**. The processor **121** responsive to detecting events can among various operations save the history in the data buffer **209** to the longer term storage memory **208**. The processor **121** by way of the ECM **123** can also actively monitor the internal sound exposure level inside the ear canal **131** and adjust the audio to within a safe and subjectively optimized listening level range.

The earpiece **100** can further include a transceiver **204** that can support singly or in combination any number of wireless access technologies including without limitation Bluetooth™, Wireless Fidelity (WiFi), Worldwide Interoperability for Microwave Access (WiMAX), and/or other short or long range communication protocols. The transceiver **204** can also provide support for dynamic downloading over-the-air to the earpiece **100**. It should be noted that next generation access technologies can also be applied to the present disclosure.

The location receiver **232** can utilize common technology such as a common GPS (Global Positioning System) receiver that can intercept satellite signals and therefrom determine a location fix of the earpiece **100**.

The power supply **210** can utilize common power management technologies such as replaceable batteries, supply regulation technologies, and charging system technologies for supplying energy to the components of the earpiece **100** and to facilitate portable applications. A motor (not shown) can be a single supply motor driver coupled to the power

supply **210** to improve sensory input via haptic vibration. As an example, the processor **121** can direct the motor to vibrate responsive to an action, such as a detection of a warning sound or an incoming voice call.

The earpiece **100** can further represent a single operational device or a family of devices configured in a master-slave arrangement, for example, a mobile device and an earpiece. In the latter embodiment, the components of the earpiece **100** can be reused in different form factors for the master and slave devices.

FIG. 3 is a flowchart of a method **250** for audio recording in accordance with an exemplary embodiment. The method **250** can be practiced with more or less than the number of steps shown and is not limited to the order shown. To describe the method **250**, reference will be made to components of FIG. 1 and FIG. 2, although it is understood that the method **250** can be implemented in any other manner using other suitable components. The method **250** can be implemented in a single earpiece, a pair of earpieces, headphones, or other suitable headset audio delivery device.

The method **250** can start in a state wherein the earpiece **100** has been inserted and powered on. As shown in step **252**, the earpiece **100** can measure ambient sounds in the environment received at the ASM **111**. Ambient sounds correspond to sounds within the environment such as the sound of traffic noise, street noise, conversation babble, or any other acoustic sound. Ambient sounds can also correspond to industrial sounds present in an industrial setting, such as factory noise, lifting vehicles, automobiles, and robots to name a few.

Although the earpiece **100** when inserted in the ear can partially occlude the ear canal, the earpiece **100** may not completely attenuate the ambient sound. During the measuring of ambient sounds in the environment, the earpiece **100** can also measure internal sounds, such as ear canal levels, via the ECM **123** as shown in step **254**. The passive aspect of the earpiece **100**, due to the mechanical and sealing properties, can provide upwards of a 22 dB noise reduction. However, portions of ambient sounds higher than the noise reduction level may still pass through the earpiece **100** into the ear canal thereby producing residual sounds. For instance, high energy low frequency sounds may not be completely attenuated. Accordingly, residual sound may be present in the ear canal producing internal sounds that can be measured by the ECM **123**. Internal sounds can also correspond to spoken voice when the user is speaking or audio content delivered by the ECR **125** to the ear canal **131** by way of the audio interface **212**.

If at step **256**, audio is playing (e.g., music, cell phone, etc.), the earpiece **100** at step **258** can capture audio content directed to the ECR **125**. Portions of the audio content can be saved in the data buffer **209** with the ambient sound and internal sounds. For instance, the audio interface **212** can deliver sound to the occluded ear canal **131** via the ECR **125**. The audio interface **212** can receive the audio content from at least one among a portable music player, a cell phone, and a portable communication device. For instance, a user can elect to play music through the earpiece **100** which can be audibly presented to the ear canal **131** for listening. The user can also elect to receive voice communications (e.g., cell phone, voice mail, messaging) via the earpiece **100**. The user can receive audio content for voice mail or a phone call directed to the ear canal via the ECR **125**.

At step **260**, the data buffer **209** temporarily records a history of the ambient sound and the internal sound; and if present, the audio content. The internal sound can correspond to residual ambient sound in the ear canal, speech

generated by the user wearing the earpiece **100** when talking, or audio content delivered from the audio interface **212** from a media device (e.g., iPod®, cell phone, radio, etc.). The history can correspond to at least one among a conversation, a voice mail, and an audio recording. For instance, the portions of audio data from a voice mail can be stored for later retrieval (e.g., phone number, address, names, etc.).

Notably, the data buffer **209** stores the ambient sound from the ASM **111** and internal sound from the ECM **123** only temporarily until an event is detected. In one arrangement, the data buffer **209** can temporarily store at least 2 minutes of recording history. The data buffer **209** continually buffers in data while the last data samples in time (unable to be stored in the data buffer **209** due to limited memory) are discarded from the data buffer **209** to make room for the new data. The processor **121** can also interleave the data onto the data buffer **209** during real-time continuous data acquisition.

If at step **262**, an event is detected the processor can proceed to save a history of the ambient sound, internal sound, and audio content in the data buffer **209** to the memory **208**. An event can correspond to a user event such as a touching of the headset, a recognizing of a voice command, a starting or ending of a phone call, or a scheduled event. The event can also be due to a change in Sound Pressure Level (SPL) or a detected sound signature; that is, a specific sound within the ambient sound (e.g. “horn”, “siren”, “help”). The processor **121** can monitor the ambient sound for a Sound Pressure Level (SPL) change event, and in response to detecting the SPL change event commits the audio history on the data buffer **209** to the memory **208**. For instance, the earpiece **100** can commit recently captured data on the data buffer **209** to the memory **208** responsive to detecting a loud explosion or crashing sound. The earpiece **100** can continue back to step **260** if an event is not detected, while continuing to monitor for events at step **262**.

The event can also correspond to an abrupt movement or a change in location of the earpiece **100**. For instance, the processor can trigger the event responsive to detecting an abrupt movement of the headset, for instance, due to an accident, or a change in location of the earpiece, for instance, an abrupt aggregated movement. In such regard, the earpiece **100** performs as a black box to record the few minutes prior to an event. Notably, this audio history is available on the data buffer **209** at the time of the event. Moreover, if dual earpieces are used (e.g., headphones), the processor **121** can binaurally record the ambient sound and the internal sound (and, if present, the audio content) from a left earpiece and a right earpiece. The binaural data can be further analyzed to identify a location of sound sources triggering the event.

Upon detecting the event at step **262**, the processor **121** can apply data compression techniques to reduce the dimensionality of the data as shown in step **264**. The processor **121** can retrieve data from the data buffer **209**, compress the data, and store the data in the storage memory **208** as shown in step **266**. For instance, the processor **121** can implement a voice coding (vocoder) operation to compress the data from Pulse Code Modulation (PCM) format to a smaller memory footprint format (e.g., EFR723, EFR726, EFR729). If audio content is present, the processor **121** can stream the data from audio interface **212** in an already compressed format (e.g., MP3, AAC, WMA, etc.) Other audio compression techniques can be used for storing the data to the memory **208**.

The processor **121** can also time stamp the data (e.g., D/M/Y, hh:mm:ss, etc.) and record a location (e.g., latitude,

longitude, elevation, degrees) of the earpiece at the time of the event, as shown in step **268**. For instance, in response to an abrupt movement of the earpiece **100** due to an accident, the processor **121** can capture the history of the audio prior to the accident, as well as the time and the location. This information can then be reported to a system that monitors the earpiece **100** for reporting a potential accident or alarming incident. The processor **121**, can also tag the data in the storage memory **208** with a filename or header that reflects the condition of the user event. For instance, the header can be saved with the history and include the time stamp, location, and event type (user initiated, abrupt movement, location change, etc.).

If at step **270** a user request (or any other request) is initiated to retrieve stored data, the earpiece **100** can audibly present the recent portion of the history to the user via the ECR **125**, as shown in step **272**. The recent portion can include any historic audio data previously captured (by way of ASM, ECM, ECR) and stored to the memory **208**. Notably, the processor **121** can keep track (e.g., look-up table) of the recent portions stored in the memory **208**. For instance, a first entry in the memory **208** can correspond to a recording at 1 PM, and a second entry can correspond to a recording at 1:40 PM. The earpiece **100** can continue back to step **260** if a user request is not received, and continue to monitor for a user request.

The user request can also correspond to a system request to retrieve audio data from the earpiece **100**. For instance, the user can subscribe to a service that stores the audio data when memory capacity is reached. Upon the processor determining that memory capacity is full, the earpiece **100** by way of the transceiver **204** can inform the service to retrieve (upload) data from the earpiece. A service provider of the service can then download the data from the earpiece **100** and forensically analyze content within the audio (e.g., spoken commands, passing sounds, voice identification, etc.)

FIG. **4** is a block diagram **300** for audio selection in accordance with an exemplary embodiment. To describe the block diagram **300**, reference will be made to components of FIG. **2**, although it is understood that the block diagram **300** can be implemented in any other manner using other suitable components. The block diagram **300** can be implemented in a single earpiece, a pair of earpieces, headphones, or other suitable headset audio delivery device.

Block diagram **300** describes an input audio channel selection system to select which audio signals are recorded using an “Always-on” Binaural Recording System (AOBRS). Input signals to the AOBRS comprise the signal generated by one or both the Ear Canal Microphones (left ECM **313** and right ECM **315**), which are processed using gain and equalizer (EQ) circuitry **317** (which may be implemented using analog or digital electronics). Other input signals may comprise one or both Ambient Sound Microphones (left ASM **303** and right ASM **305**) from separate left and right headset electroacoustic assemblies, or from the output of multiple ASM signals in the same right headset electroacoustic assembly. The ASM signals are processed using gain and equalizer circuitry **311** (which may be implemented using analog or digital electronics) housed in assembly **113**. Audio Content **319** can be recorded during simultaneous reproduction with left and right Ear Canal Receivers **333**, **335**, via the automatic gain control (AGC) circuitry **321** (which may comprise either or both analog or digital signal processing). Audio Content **319** may be, for example, from a cell-phone **301**; a Personal Media Player (PMP) **307**; or an auditory warning signal **309** such as a low

battery alarm generated by the AOBRS or from a second device such as a second data storage system. The audio signals from circuitry 317, 319, 311, and 321 are selected for recording 337 using the switching assembly 323, and configured either manually with user input system 325 (e.g. using buttons mounted on the electroacoustic headset system) or with automatic selection 327 which may be initiated in response to a specific record start/stop command, for example, generated by the system 449 described in FIG. 6.

FIG. 5 is a block diagram 400 for an “Always-On” Binaural Recording System (AOBRS) in accordance with an exemplary embodiment. To describe the block diagram 400, reference will be made to components of FIG. 2, although it is understood that the block diagram 400 can be implemented in any other manner using other suitable components. The block diagram 400 can be implemented in a single earpiece, a pair of earpieces, headphones, or other suitable headset audio delivery device.

Following activation at step 421 and selection (300 shown in FIG. 4) of the audio signals to be recorded (for example, by manual operation 425), the selected audio signals 437 are analyzed by the recording activation circuitry 449 described in FIG. 6. Depending on the operating mode selected 441 (for example, by user input 426), the audio input audio signals 437 are first processed by an optional audio signal CODEC 439, which may reduce the data bit-rate of the signal using either a lossy or lossless data compression system. The audio data is then continuously recorded to a circular data buffer 443 which in the preferred embodiment is housed within the earpiece 100, or on a second device such as a Personal media player (PMP). The circular buffer 443 consists of computer memory, and is a familiar device for those skilled in the art. Following recording activation determined by decision unit 445, the contents of the circular data buffer 443 are recorded to a second non-volatile memory 450, which may be at a compressed data rate using audio signal CODEC 447 (which may use a lossy or loss-less data compression system) receiving recorded audio 448. The recording may continue until a stop recording signal is generated 453. With either a wired or wireless data communication system 452, the contents of the data storage 450 may be stored on a separate data memory device 451, such as a portable hard drive. The remaining data memory of either or both systems 450 and 451 are monitored using a low memory warning system (see 600 FIG. 10), which alert the user when remaining memory is low. A remote audio forensic analysis system 559 described in FIG. 9 can analyze the contents of the first 450 or second 451 audio data storage system, for example, following a detected accident.

FIG. 6 is a block diagram for activating audio recording by recording activation circuitry 449 in accordance with an exemplary embodiment. To describe the block diagram, reference will be made to components of FIG. 2, although it is understood that the block diagram can be implemented in any other manner using other suitable components. The block diagram can be implemented in a single earpiece, a pair of earpieces, headphones, or other suitable headset audio delivery device.

The input audio signal for analysis are selected with the input channel selection system 300 described in FIG. 4. The signals 454 comprise the ASM signals from one or both earphones (though different audio signals may be recorded to data memory for storage). A keyword detector module 455 analyzes the input signals 454 and activates or deactivates recording 453 if specific verbal commands are detected (e.g. “Start”, “Stop”, which may be in multiple languages). Alternatively or additionally, a method 459 for

Transient Event Detection (described in FIG. 7) generates a stop or start signal to the system 300 in response to a detected transient in signal 454 with a particular temporal envelope profile. Alternatively or additionally, an accident detector module 500 (see FIG. 8) generates a stop or start signal to the system 300 in response to a particular user biological state or movement. Alternately or additionally, a stop or start signal 453 is generated to the system 300 in response to a manual user activation 457, such as with a switch mounted on the earphone assembly.

FIG. 7 is a flowchart further detailing the method 459 for transient event detection in accordance with an exemplary embodiment. The method 459 can include more or less than the number of steps shown and is not limited to the order of the steps. To describe the method 459, reference will be made to components of FIG. 2, although it is understood that the method 459 can be implemented in any other manner using other suitable components. The method 459 can be implemented in a single earpiece, a pair of earpieces, headphones, or other suitable headset audio delivery device.

Transient Event detection generates a stop or start signal to the system 300 in response to a detected transient in either or both the ASM signals 403, 404 (which may be from the same or different earphones). The audio data is continuously recorded to a circular data buffer 443, and a recent history of data samples (e.g. the past 10 ms) is used to estimate the SPL 461 at the entrance to the occluded ear canal 131 (e.g. in dB). The Background Noise Level (BNL) is also estimated at step 463 from a running time-smoothed average of the SPL, which may use circuitry to remove transient peaks in the SPL to calculate the BNL. If the decision unit 467 deems that the difference between the SPL 461 and BNL 463 is less than a predefined amount (which may be determined on a frequency selective basis)—as calculated with unit 465—then the recording is stopped 469 if it is already activated. If the recording is already active, then the Transient Detection Timer (TDT) 471 (which is the time since recording was activated) is compared with a predefined constant 475 using comparator 477, and if the TDT 471 is greater than the threshold 475 then recording is stopped 483. Alternatively, if a loud transient is detected 467, then the TDT clock is started 479 and recording of the circular buffer 443 to a second data storage device is initiated; and if recording is already activated (as determined at step 473), the TDT clock is reset and restarted, at step 481.

FIG. 8 is a flowchart of a method 500 for event detection in accordance with an exemplary embodiment. The method 500 can include more or less than the number of steps shown and is not limited to the order of the steps. To describe the method 500, reference will be made to components of FIG. 2, although it is understood that the method 500 can be implemented in any other manner using other suitable components. The method 500 can be implemented in a single earpiece, a pair of earpieces, headphones, or other suitable headset audio delivery device.

In one embodiment, the method 500 describes an accident detection platform, with the purpose of recording the audio signals selected in the system 300 process in FIG. 4 in response to a detected accident involving an AOBRS user. Following activation of accident detection 585, aspects of both the User’s health 587 and physical motion 589 can be simultaneously and continuously monitored. Aspects of user health may include (but are not limited to) blood oxygen saturation 591, blood pressure 593 and heart-rate 595. These health aspects may be monitored using a probe mounted on the earphone device. The resulting biometric data 501 is compared SOS with a set of reference (normal, healthy) data

507, which may be from a database adapted to the particular user, or from a database generalized for users of a similar age, sex etc. If the comparison SOS of current biometric data 501 and reference data 507 indicates a sudden discrepancy, such as a drop in blood pressure 593, then decision unit 509 initiates a specific response 511. The user motion sensor system 589 monitors the location of the user using either of or a combination of analysis of the sound level at each earphone 597 using the output of the ASMs 403, 404 in both the left and right earphone; and/or an analysis of the spatial acceleration of the earphone device using accelerometers 599 and or internal sensors housed within the earphone assembly. If either or both the motion sensors 597, 599 indicate a sudden movement indicative of a fall, then decision unit 503 initiates a specific response 511. Such specific responses include starting the binaural recording system 513, and transmitting selected audio signals (see FIG. 4) to a second data storage device 515, which may involve a wireless data communication system 517, and may automatically invoke a system to alert the emergency services of a detected accident involving the AOBRS user 519.

FIG. 9 is a flowchart of a method 559 for forensic audio evaluation in accordance with an exemplary embodiment. The method 559 can include more or less than the number of steps shown and is not limited to the order of the steps. To describe the method 559, reference will be made to components of FIG. 2, although it is understood that the method 559 can be implemented in any other manner using other suitable components. The method 559 can be implemented in a single earpiece, a pair of earpieces, headphones, or other suitable headset audio delivery device.

Method 559 describes an audio forensics system for transferring recording audio data 537 from memory on the earphone 550 or a second data storage system 551 to an online server 537 for analysis 539 (for example, via Internet 531), or automatic speech-to-text processing 533, 535. The recorded audio data 536, (responsive to record start/stop module 535), is time-stamped 520 to mark when the recording commenced, and time-stamps may be embedded in the recorded data stream at regular intervals or to mark significant events such as detected transient events (FIG. 7). Transmission of data 529 recorded on non-volatile memory in the earphone 550 to a second data system may be invoked automatically by decision unit 525 when an in-cradle detection system 527 detects that the earphones are located in a docking station (e.g. for recharging batteries). Alternatively, or additionally, transmission of data 529 recorded on non-volatile memory in the earphone 550 to a second data system 551 may be invoked automatically whenever the AOBRS detects 523 the presence of a wireless communication system 521, such as Wifi or Bluetooth.

FIG. 10 is a flowchart of a method 600 for low remaining-memory warning in accordance with an exemplary embodiment. The method 600 can include more or less than the number of steps shown and is not limited to the order of the steps. To describe the method 600, reference will be made to components of FIG. 2, although it is understood that the method 600 can be implemented in any other manner using other suitable components. The method 600 can be implemented in a single earpiece, a pair of earpieces, headphones, or other suitable headset audio delivery device.

The method 600 can inform the user when the remaining data memory for storage of audio signals in the system 300 is critically low (similar to a low battery alarm). The record start/stop module 635 can get audio from the input buffer at step 636, and input the audio signal at step 638, to the

non-volatile memory 208 on the earpiece 100 as shown in 651. A time stamp 620 can be included with the recorded audio signal.

During recording, the processor 121 at step 637 proceeds to determine if a total remaining record time is available. If the remaining record time is not available, the processor 121 can calculate it as shown in step 700 (see FIG. 11) and store the remaining record time to memory at step 643. At step 645 the processor 121 then determines if the total remaining record time is low. If the total record time is not low, the method proceeds back to step 636 to get the next audio from the input buffer. If however, the total record time is low, a low-memory warning message generation system 800 (see FIG. 12) generates a low memory warning message at step 801. Upon delivering the low-memory warning message, a determination is made at step 647 to continue recording. The recording can stop at step 648, for example, in response to a user request or automatic event detection. The method 600 can proceed back to step 636 to get the next audio data if the recording is continued.

FIG. 11 is a flowchart of a method 700 for remaining record-time in accordance with an exemplary embodiment. The method 700 can include more or less than the number of steps shown and is not limited to the order of the steps. To describe the method 700, reference will be made to components of FIG. 2, although it is understood that the method 700 can be implemented in any other manner using other suitable components. The method 700 can be implemented in a single earpiece, a pair of earpieces, headphones, or other suitable headset audio delivery device.

At step 750, the method 700 can start. At step 751, the processor 121 can determine if a total remaining memory of data storage of a device is known. If the total remaining memory is known, and the recording data rate is known at step 755, the data can be recorded at a designated recording rate as shown in step 761 based on the remaining memory and the data rate. If the recording rate is not known at step 755, the processor 121 can calculate the recording data rate at step 759 (e.g., 512 kps).

If however at step 751, the total remaining memory is not known, the processor 121 can calculate a total remaining memory of data storage at step 752 using the non-volatile memory on the earpiece 100 from step 754. At step 753, the total remaining memory of the device can be used in step 757 to estimate a remaining recording time (A/B). At step 763, the total remaining recording time can be output. For instance, upon the completion of method 700, the earpiece 100 can present a warning indication with the total remaining recording time left on the earpiece 100.

FIG. 12 is a flowchart of a method 800 for remaining memory in accordance with an exemplary embodiment. The method 800 can include more or less than the number of steps shown and is not limited to the order of the steps. To describe the method 800, reference will be made to components of FIG. 2, although it is understood that the method 800 can be implemented in any other manner using other suitable components. The method 800 can be implemented in a single earpiece, a pair of earpieces, headphones, or other suitable headset audio delivery device.

Briefly, method 800 prioritizes warning levels for reporting based on memory usage and remaining memory capacity. The method 800 can start when the "always-on" binaural recording feature is running on the earpiece 100. Notably, the memory 208 will be filled as recent portions of audio history are committed to the memory 208. The processor

121 can periodically check the memory capacity to determine when, and a type of warning message, to be sent to the user.

At step 867, the processor 121 can compare the remaining memory to a warning memory threshold (WMT_2) indicated in a database 865. For instance, the WMT_2 can be set to 5% remaining capacity. If the remaining memory is greater than the WMT_2 (>95% used capacity), the processor 121 can assign a priority level 1 and generate a polite verbal warning message to the user at step 873. The audio output of the warning message can be conditioned (e.g., gain, EQ) at step 821 and delivered to the user via the left ECR 833 and right ECR 835 of the earpiece. If however at step 871, the remaining memory is less than the WMT_2, but greater than a WMT_3, the processor 121 can assign a priority level 2 and generate a repeating warning message (obtrusive auditory alarm) audibly presented to the user as shown in step 875. If however at step 871, the remaining memory is less than a WMT_3 retrieved from data base 869, the processor 121 can assign a priority level 3 and generate a final verbal warning message to the user at step 877.

While the present invention has been described with reference to exemplary embodiments, it is to be understood that the invention is not limited to the disclosed exemplary embodiments. The scope of the following claims is to be accorded the broadest interpretation so as to encompass all modifications, equivalent structures and functions of the relevant exemplary embodiments. Thus, the description of the invention is merely exemplary in nature and, thus, variations that do not depart from the gist of the invention are intended to be within the scope of the exemplary embodiments of the present invention. Such variations are not to be regarded as a departure from the spirit and scope of the present invention.

What is claimed is:

1. An acquisition system comprising:
a processor;

one or more sensors within an earpiece operatively coupled to the processor, wherein the earpiece is configured to acquire at the ear, on the ear or within an ear canal, one or more of acceleration, blood oxygen saturation, blood pressure or heart-rate, the one or more sensors configured to monitor a biological state or a physical motion or both for an event, the processor configured to analyze a portion of the biological state or the physical motion; and

wherein the event is a detection of a discrepancy when compared with a set of reference data by the one or more sensors that monitor the physical motion or the biological state or the event is one of a detection of an abrupt movement of a headset operatively coupled to the processor, a change in location of the earpiece operatively coupled the processor, a touching of the headset, a recognizing of a voice command, a starting or ending of a phone call, or a scheduled time, wherein resulting biometric data from the one or more sensors is compared with the set of reference data, wherein the processor initiates a response when a sudden discrepancy is detected between the resulting biometric data and the set of reference data;

wherein the earpiece includes at least one ambient sound microphone and at least one ear canal microphone.

2. The acquisition system of claim 1, further comprising a memory operatively coupled to the processor, wherein the processor is configured to save or temporarily save the portion of the biological state or the physical motion in the memory responsive to detection of the event or save a

history of at least one among a conversation, a voice mail, or an audio recording responsive to the event.

3. The acquisition system of claim 1, wherein the event is a fall detected by the one or more sensors that monitor the physical motion or a biometric discrepancy detected by the one or more sensors.

4. The acquisition system of claim 1, wherein the one or more sensors comprise sensors for monitoring one or more of blood oxygen saturation, blood pressure or heart-rate configured to monitor the biological state.

5. The acquisition system of claim 1, wherein the one or more sensors comprise acoustical sensors for monitoring one or more of blood oxygen saturation, blood pressure or heart-rate configured to monitor the biological state.

6. The acquisition system of claim 1, wherein the one or more sensors comprise sensors for monitoring acceleration configured to monitor the physical motion.

7. The acquisition system of claim 1, wherein the system further comprises a microphone mounted on a mobile phone or a second device configured to capture ambient sound proximate to the mobile phone or the second device.

8. The acquisition system of claim 1, wherein the processor monitors an internal sound exposure level inside the ear canal, adjusts audio to within an optimized listening level range, or a combination thereof.

9. The acquisition system of claim 1, wherein the one or more sensors detect a sudden movement, the processor initiates a response.

10. The acquisition system of claim 1, wherein the event includes a detected sound signature within a captured ambient sound captured by a microphone.

11. The acquisition system of claim 1, further comprising an accident detector module coupled to the processor.

12. The acquisition system of claim 11, wherein the accident detector module is configured to generate a stop or start signal in response to a biological state or movement detected by the one or more sensors or in response to a manual user activation.

13. The acquisition system of claim 1, wherein the system transmits data to a server for remote storage or for remote analysis or stores data in a local storage operatively coupled to the processor for local storage or local analysis.

14. An earpiece or headset comprising:
a processor;

an ambient microphone operatively coupled to the processor and configured to capture an ambient sound; and one or more sensors within the earpiece configured to couple at the ear, on the ear, or within an ear canal operatively coupled to the processor, wherein the one or more sensors monitor at the ear, on the ear, or within the ear canal one or more of acceleration, blood oxygen saturation, blood pressure, heart-rate, or an internal sound wherein the earpiece includes at least one ear canal microphone, wherein resulting biometric data from the one or more sensors is compared with a set of reference data, wherein the processor initiates a response when a sudden discrepancy is detected between the resulting biometric data and the set of reference data; and

a memory operatively coupled to the processor, wherein the memory stores a signal from ambient microphone or from the one or more sensors or both in response to an event.

15. The earpiece or headset of claim 14, wherein the event comprises one or more of a touching of the headset, a

15

recognizing of a voice command, a starting or ending of a phone call, a scheduled time, or an abrupt movement of the headset.

16. The earpiece or headset of claim 14, wherein the event comprises one or more of a detection of a biological state or a detection of movement detected by the one or more sensors or in response to a manual user activation.

17. An acquisition system, comprising:
a processor;

one or more biometric or motion sensors within an earpiece coupled to the processor, wherein the earpiece is configured to monitor at the ear, on the ear, or within an ear canal one or more of acceleration, blood oxygen saturation, blood pressure, an internal sound, or heart-rate configured to monitor a biological state or a physical motion or both, the processor configured to analyze a portion of the biological state or the physical motion in response to an event and wherein the earpiece includes at least one ear canal microphone configured to monitor sounds within the ear canal; and wherein the one or more sensors are configured to detect the event by detecting a discrepancy between sensor

16

data and a set of reference data or by detecting at least one of a touching of a headset operatively coupled to the processor, a recognizing of a voice command, a starting or ending of a phone call, a scheduled time, or an abrupt movement of the headset, wherein resulting biometric data from the one or more biometric or motion sensors is compared with the set of reference data, wherein the processor initiates a response when a sudden discrepancy is detected between the resulting biometric data and the set of reference data.

18. The acquisition system of claim 17, wherein the set of reference data is reference data for a normal user, reference data for a healthy user, or reference data adapted for a particular user.

19. The acquisition system of claim 17, wherein the processor is configured to report at least one of the event, an accident, a potential accident, or an alarming incident.

20. The acquisition system of claim 17, further comprising a remote audio forensic analysis system.

* * * * *

专利名称(译)	用于录音的方法和设备		
公开(公告)号	US10212528	公开(公告)日	2019-02-19
申请号	US15/790771	申请日	2017-10-23
[标]发明人	GOLDSTEIN STEVEN W		
发明人	GOLDSTEIN, STEVEN W		
IPC分类号	A61B5/11 H04R25/00 G16H50/20 G16H50/30 H04R1/10 H04R29/00 H04M1/65 A61B5/0205 A61B5/145 A61B5/00 A61B5/024 A61B5/021		
CPC分类号	H04R29/004 G16H20/10 A61B5/1117 A61B5/14542 A61B5/6817 G16H50/20 G16H50/30 H04M1/65 H04R1/1091 H04R25/70 A61B5/0205 A61B5/021 A61B5/024 H04R2201/109 H04R2410/05 H04R2499/11 G06F19/36 G16H40/60 G16H10/20		
优先权	14/048324 2014-12-23 US 60/887800 2007-02-01 US		
其他公开文献	US20180132050A1		
外部链接	Espacenet		

摘要(译)

采集系统包括处理器，可操作地耦合到处理器的一个或多个传感器，其中一个或多个传感器在耳朵，耳朵或耳道内获取加速度，血氧饱和度，血压或心脏中的一个或多个-rate，以及配置成监视事件的生物状态或物理运动或两者的一个或多个传感器。当与一组或多个传感器或生物状态的一组参考数据相比时，该事件可以是差异的检测，或者该事件可以是检测到可操作地耦合到处理器的耳机的突然移动之一，改变可操作地连接处理器的耳机的位置，触摸耳机，识别语音命令，电话呼叫的开始或结束，或预定时间。

