



US009872623B2

(12) **United States Patent**
Al-Ali

(10) **Patent No.:** **US 9,872,623 B2**
(45) **Date of Patent:** ***Jan. 23, 2018**

(54) **ARM MOUNTABLE PORTABLE PATIENT MONITOR**

(71) Applicant: **Masimo Corporation**, Irvine, CA (US)

(72) Inventor: **Ammar Al-Ali**, San Juan Capistrano, CA (US)

(73) Assignee: **MASIMO CORPORATION**, Irvine, CA (US)

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 9 days.

This patent is subject to a terminal disclaimer.

(21) Appl. No.: **15/494,967**

(22) Filed: **Apr. 24, 2017**

(65) **Prior Publication Data**

US 2017/0224231 A1 Aug. 10, 2017

Related U.S. Application Data

(63) Continuation of application No. 15/448,989, filed on Mar. 3, 2017, which is a continuation of application (Continued)

(51) **Int. Cl.**
A61B 5/1455 (2006.01)
A61B 5/00 (2006.01)
(Continued)

(52) **U.S. Cl.**
CPC **A61B 5/0205** (2013.01); **A61B 5/0004** (2013.01); **A61B 5/6824** (2013.01);
(Continued)

(58) **Field of Classification Search**
CPC ... A61B 5/0002; A61B 5/0004; A61B 5/0024;
A61B 5/02; A61B 5/0205; A61B 5/0402;
(Continued)

(56) **References Cited**

U.S. PATENT DOCUMENTS

3,646,606 A 2/1972 Buxton et al.
3,690,313 A 9/1972 Weppner et al.
(Continued)

FOREIGN PATENT DOCUMENTS

EP 0602459 6/1994
EP 0 735 499 10/1996
(Continued)

OTHER PUBLICATIONS

US 8,845,543, 09/2014, Diab et al. (withdrawn)
(Continued)


Primary Examiner — Eric Winakur

(74) *Attorney, Agent, or Firm* — Knobbe Martens Olson & Bear LLP

(57) **ABSTRACT**

An arm mountable portable patient monitoring device configured for both on patient monitoring of parameter measurements using one or more sensors operatively connected to the portable patient monitoring device and wireless transmission of parameter measurements. The arm mountable portable patient monitoring device includes a pulse oximetry sensor configured to be wrapped around a digit of a patient, a housing having a size and shape configured for mounting to a lower arm of the patient, and a strap mountable to the back side of the housing and configured to secure the housing to the lower arm of the patient. The housing includes a display, a first sensor port positioned on the housing to face toward a hand of the patient, second and third sensor ports, a battery, signal processing arrangements to cause display of parameter measurements, and a transmitter to transmit information indicative of the measurements.

20 Claims, 17 Drawing Sheets



Related U.S. Application Data

- No. 14/815,232, filed on Jul. 31, 2015, now abandoned, which is a continuation of application No. 14/217,788, filed on Mar. 18, 2014, now Pat. No. 9,113,832, which is a continuation of application No. 14/037,137, filed on Sep. 25, 2013, now Pat. No. 9,113,831, which is a continuation of application No. 12/955,826, filed on Nov. 29, 2010, now Pat. No. 8,548,548, which is a continuation of application No. 11/417,006, filed on May 3, 2006, now Pat. No. 7,844,315, which is a continuation of application No. 11/048,330, filed on Feb. 1, 2005, now Pat. No. 7,844,314, which is a continuation of application No. 10/377,933, filed on Feb. 28, 2003, now Pat. No. 6,850,788.
- (60) Provisional application No. 60/367,428, filed on Mar. 25, 2002.
- (51) **Int. Cl.**
A61B 5/0205 (2006.01)
A61B 5/0402 (2006.01)
A61B 5/021 (2006.01)
A61B 5/024 (2006.01)
- (52) **U.S. Cl.**
 CPC *A61B 5/6826* (2013.01); *A61B 5/6831* (2013.01); *A61B 5/7271* (2013.01); *A61B 5/021* (2013.01); *A61B 5/02438* (2013.01); *A61B 5/0402* (2013.01); *A61B 5/14552* (2013.01)
- (58) **Field of Classification Search**
 CPC . A61B 5/1455; A61B 5/14551; A61B 5/6825; A61B 5/6826; A61B 5/6831; A61B 5/72; A61B 2560/0043; A61B 2562/06
 See application file for complete search history.

(56) References Cited

U.S. PATENT DOCUMENTS

3,810,102	A	5/1974	Parks, III et al.	5,331,549	A	7/1994	Crawford, Jr.
3,815,583	A	6/1974	Scheidt	5,333,106	A	7/1994	Lanpher et al.
3,972,320	A	8/1976	Kalman	5,337,744	A	8/1994	Branigan
3,978,849	A	9/1976	Geneen	5,341,805	A	8/1994	Stavridi et al.
4,013,067	A	3/1977	Kresse et al.	5,348,008	A	9/1994	Bornn et al.
4,108,166	A	8/1978	Schmid	5,358,519	A	10/1994	Grandjean
4,231,354	A	11/1980	Kurtz et al.	D353,195	S	12/1994	Savage et al.
4,589,415	A	5/1986	Haaga	D353,196	S	12/1994	Savage et al.
4,662,378	A	5/1987	Thomis	5,375,599	A	12/1994	Shimizu
4,773,422	A	9/1988	Isaacson et al.	5,375,604	A	12/1994	Kelly et al.
4,838,275	A	6/1989	Lee	5,377,676	A	1/1995	Vari et al.
4,852,570	A	8/1989	Levine	5,392,777	A	2/1995	Swedlow et al.
4,960,128	A	10/1990	Gordon et al.	5,400,794	A	3/1995	Gorman
4,964,408	A	10/1990	Hink et al.	D357,982	S	5/1995	Dahl et al.
RE33,643	E	7/1991	Isaacson et al.	5,416,695	A	5/1995	Stutman et al.
5,041,187	A	8/1991	Hink et al.	5,417,222	A	5/1995	Dempsey et al.
5,069,213	A	12/1991	Polczynski	D359,546	S	6/1995	Savage et al.
5,090,410	A	2/1992	Safer et al.	5,431,170	A	7/1995	Mathews
5,092,340	A	3/1992	Yamaguchi et al.	5,434,611	A	7/1995	Tamura
5,140,519	A	8/1992	Friesdorf et al.	D361,840	S	8/1995	Savage et al.
5,159,932	A	11/1992	Zanetti et al.	D362,063	S	9/1995	Savage et al.
5,161,539	A	11/1992	Evans et al.	5,452,717	A	9/1995	Branigan et al.
5,163,438	A	11/1992	Gordon et al.	D363,120	S	10/1995	Savage et al.
5,203,342	A	4/1993	Sakai	5,456,252	A	10/1995	Vari et al.
5,262,944	A	11/1993	Weisner et al.	5,479,934	A	1/1996	Imran
5,277,189	A	1/1994	Jacobs	5,482,036	A	1/1996	Diab et al.
5,278,627	A	1/1994	Aoyagi et al.	5,483,968	A	1/1996	Adam et al.
5,282,474	A	2/1994	Valdes Sosa et al.	5,490,505	A	2/1996	Diab et al.
5,296,688	A	3/1994	Hamilton et al.	5,490,523	A	2/1996	Isaacson et al.
5,318,037	A	6/1994	Evans et al.	5,494,041	A	2/1996	Wilk
5,319,355	A	6/1994	Russek	5,494,043	A	2/1996	O'Sullivan et al.
				5,503,149	A	4/1996	Beavin
				5,505,202	A	4/1996	Mogi et al.
				5,511,553	A	4/1996	Segalowitz
				5,533,511	A	7/1996	Kaspari et al.
				5,534,851	A	7/1996	Russek
				5,537,289	A	7/1996	Dahl
				5,544,649	A	8/1996	David et al.
				5,553,609	A	9/1996	Chen et al.
				5,558,638	A	9/1996	Evers et al.
				5,561,275	A	10/1996	Savage et al.
				5,562,002	A	10/1996	Lalin
				5,566,676	A	10/1996	Rosenfeldt et al.
				5,576,952	A	11/1996	Stutman et al.
				5,579,001	A	11/1996	Dempsey et al.
				5,584,296	A	12/1996	Cui et al.
				5,590,649	A	1/1997	Caro et al.
				5,602,924	A	2/1997	Durand et al.
				5,619,991	A	4/1997	Sloane
				5,632,272	A	5/1997	Diab et al.
				5,638,816	A	6/1997	Kiani-Azarbayjany et al.
				5,638,818	A	6/1997	Diab et al.
				5,640,967	A	6/1997	Fine et al.
				5,645,440	A	7/1997	Tobler et al.
				5,658,316	A	8/1997	Lamond et al.
				5,673,692	A	10/1997	Schulze et al.
				5,685,299	A	11/1997	Diab et al.
				5,685,314	A	11/1997	Geheb et al.
				5,687,717	A	11/1997	Halpern et al.
				5,694,020	A	12/1997	Lang et al.
				5,724,580	A	3/1998	Levin et al.
				5,724,983	A	3/1998	Selker et al.
				5,725,308	A	3/1998	Smith et al.
				5,734,739	A	3/1998	Sheehan et al.
				D393,830	S	4/1998	Tobler et al.
				5,743,262	A	4/1998	Lepper, Jr. et al.
				5,746,697	A	5/1998	Swedlow et al.
				5,758,079	A	5/1998	Ludwig et al.
				5,758,644	A	6/1998	Diab et al.
				5,760,910	A	6/1998	Lepper, Jr. et al.
				5,769,785	A	6/1998	Diab et al.
				5,772,585	A	6/1998	Lavin et al.
				5,779,631	A	7/1998	Chance
				5,782,757	A	7/1998	Diab et al.
				5,782,805	A	7/1998	Meinzer
				5,785,659	A	7/1998	Caro et al.
				5,791,347	A	8/1998	Flaherty et al.
				5,792,052	A	8/1998	Isaacson et al.
				5,800,349	A	9/1998	Isaacson et al.

(56)

References Cited

U.S. PATENT DOCUMENTS

5,801,637 A	9/1998	Lomholt	6,195,576 B1	2/2001	John	
5,810,734 A	9/1998	Caro et al.	6,206,830 B1	3/2001	Diab et al.	
5,813,403 A	9/1998	Soller et al.	6,215,403 B1	4/2001	Chan et al.	
5,822,544 A	10/1998	Chaco et al.	6,221,012 B1	4/2001	Maschke et al.	
5,822,546 A	10/1998	George	6,224,553 B1	5/2001	Nevo	
5,823,950 A	10/1998	Diab et al.	6,229,856 B1	5/2001	Diab et al.	
5,829,723 A	11/1998	Brunner	6,230,142 B1	5/2001	Benigno et al.	
5,830,131 A	11/1998	Caro et al.	6,232,609 B1	5/2001	Snyder et al.	
5,830,137 A	11/1998	Scharf	6,236,872 B1	5/2001	Diab et al.	
5,833,618 A	11/1998	Caro et al.	6,241,683 B1	6/2001	Macklem et al.	
RE36,000 E	12/1998	Swedlow et al.	6,241,684 B1 *	6/2001	Amano	A61B 5/02438 600/503
5,855,550 A	1/1999	Lai et al.	6,251,113 B1	6/2001	Appelbaum	
5,860,919 A	1/1999	Kiani-Azarbayjany et al.	6,253,097 B1	6/2001	Aronow et al.	
5,865,736 A	2/1999	Baker et al.	6,256,523 B1	7/2001	Diab et al.	
5,876,351 A	3/1999	Rohde	6,263,222 B1	7/2001	Diab et al.	
5,879,292 A	3/1999	Sternberg et al.	6,267,723 B1	7/2001	Matsumura et al.	
5,890,929 A	4/1999	Mills et al.	6,269,262 B1	7/2001	Kandori et al.	
5,904,654 A	5/1999	Wohlmann et al.	6,278,522 B1	8/2001	Lepper, Jr. et al.	
5,910,139 A	6/1999	Cochran et al.	6,280,213 B1	8/2001	Tobler et al.	
5,919,134 A	7/1999	Diab	6,285,896 B1	9/2001	Tobler et al.	
5,921,920 A	7/1999	Marshall et al.	6,289,238 B1	9/2001	Besson et al.	
5,924,074 A	7/1999	Evans	6,301,493 B1	10/2001	Marro et al.	
5,931,160 A	8/1999	Gilmore et al.	6,304,767 B1	10/2001	Soller et al.	
5,931,791 A	8/1999	Saltzstein et al.	6,312,378 B1	11/2001	Bardy	
5,934,925 A	8/1999	Tobler et al.	6,317,627 B1	11/2001	Ennen et al.	
5,940,182 A	8/1999	Lepper, Jr. et al.	6,321,100 B1	11/2001	Parker	
5,942,986 A	8/1999	Shabot et al.	6,322,502 B1	11/2001	Schoenberg et al.	
5,957,854 A	9/1999	Besson et al.	6,325,761 B1	12/2001	Jay	
5,987,519 A	11/1999	Peifer et al.	6,329,139 B1	12/2001	Nova et al.	
5,995,855 A	11/1999	Kiani et al.	6,334,065 B1	12/2001	Al-Ali et al.	
5,997,343 A	12/1999	Mills et al.	6,338,039 B1	1/2002	Lonski et al.	
6,002,952 A	12/1999	Diab et al.	6,343,224 B1	1/2002	Parker	
6,006,119 A	12/1999	Soller et al.	6,349,228 B1	2/2002	Kiani et al.	
6,011,985 A	1/2000	Athan et al.	6,352,504 B1	3/2002	Ise	
6,011,986 A	1/2000	Diab et al.	6,354,235 B1	3/2002	Davies	
6,014,346 A	1/2000	Malone	6,360,114 B1	3/2002	Diab et al.	
6,018,673 A	1/2000	Chin et al.	6,364,834 B1	4/2002	Reuss et al.	
6,024,699 A	2/2000	Surwit et al.	6,364,839 B1	4/2002	Little et al.	
6,027,452 A	2/2000	Flaherty et al.	6,368,283 B1	4/2002	Xu et al.	
6,032,678 A	3/2000	Rottem	6,371,921 B1	4/2002	Caro et al.	
6,035,230 A	3/2000	Kang et al.	6,374,129 B1	4/2002	Chin et al.	
6,036,642 A	3/2000	Diab et al.	6,377,829 B1	4/2002	Al-Ali	
6,036,718 A	3/2000	Ledford et al.	6,385,476 B1	5/2002	Osadchy et al.	
6,045,509 A	4/2000	Caro et al.	6,385,589 B1	5/2002	Trusheim et al.	
6,045,527 A	4/2000	Appelbaum et al.	6,387,039 B1	5/2002	Moses	
6,057,758 A	5/2000	Dempsey et al.	6,388,240 B2	5/2002	Schulz et al.	
6,067,462 A	5/2000	Diab et al.	6,397,091 B2	5/2002	Diab et al.	
6,081,735 A	6/2000	Diab et al.	6,405,083 B1	6/2002	Rockwell et al.	
6,088,607 A	7/2000	Diab et al.	6,407,335 B1	6/2002	Franklin-Lees	
6,090,056 A	7/2000	Bystrom et al.	6,430,437 B1	8/2002	Marro	
6,093,146 A	7/2000	Filangeri	6,430,525 B1	8/2002	Weber et al.	
6,101,478 A	8/2000	Brown	6,440,067 B1	8/2002	Deluca et al.	
6,106,463 A	8/2000	Wilkinson	6,454,708 B1	9/2002	Ferguson et al.	
6,110,522 A	8/2000	Lepper, Jr. et al.	6,463,311 B1	10/2002	Diab	
6,124,597 A	9/2000	Shehada	6,470,199 B1	10/2002	Kopotic et al.	
6,128,521 A	10/2000	Marro et al.	6,470,893 B1	10/2002	Boesen	
6,129,675 A	10/2000	Jay	6,491,647 B1	12/2002	Bridger et al.	
6,132,218 A	10/2000	Benja-Athon	6,501,975 B2	12/2002	Diab et al.	
6,139,494 A	10/2000	Cairnes	6,505,059 B1	1/2003	Kollias et al.	
6,144,868 A	11/2000	Parker	6,515,273 B2	2/2003	Al-Ali	
6,151,516 A	11/2000	Kiani-Azarbayjany et al.	6,516,289 B2 *	2/2003	David	A61B 5/04085 600/300
6,152,754 A	11/2000	Gerhardt et al.	6,519,487 B1	2/2003	Parker	
6,154,667 A	11/2000	Miura et al.	6,524,240 B1	2/2003	Thede	
6,157,850 A	12/2000	Diab et al.	6,525,386 B1	2/2003	Mills et al.	
6,165,005 A	12/2000	Mills et al.	6,526,300 B1	2/2003	Kiani et al.	
6,167,258 A	12/2000	Schmidt et al.	6,541,756 B2	4/2003	Schulz et al.	
D437,058 S	1/2001	Gozani	6,542,764 B1	4/2003	Al-Ali et al.	
6,168,563 B1	1/2001	Brown	6,544,173 B2	4/2003	West et al.	
6,171,237 B1	1/2001	Avitall et al.	6,544,174 B2	4/2003	West et al.	
6,175,752 B1	1/2001	Say et al.	6,551,243 B2	4/2003	Bocionek et al.	
6,178,343 B1	1/2001	Bindzus et al.	6,553,242 B1	4/2003	Sarussi	
6,183,417 B1	2/2001	Gehab et al.	6,577,893 B1	6/2003	Besson et al.	
6,184,521 B1	2/2001	Coffin, IV et al.	6,578,428 B1	6/2003	Dromms et al.	
6,185,448 B1	2/2001	Borovsky	6,580,086 B1	6/2003	Schulz et al.	
6,190,327 B1	2/2001	Isaacson et al.	6,584,336 B1	6/2003	Ali et al.	
			6,595,316 B2	7/2003	Cybulski et al.	
			6,597,932 B2	7/2003	Tian et al.	

(56)

References Cited

U.S. PATENT DOCUMENTS

6,597,933 B2	7/2003	Kiani et al.	6,934,570 B2	8/2005	Kiani et al.
6,606,511 B1	8/2003	Ali et al.	6,939,305 B2	9/2005	Flaherty et al.
6,612,984 B1	9/2003	Kerr, II	6,942,616 B2	9/2005	Kerr, II
6,616,606 B1	9/2003	Peterson et al.	6,943,348 B1	9/2005	Coffin, IV
6,632,181 B2	10/2003	Flaherty et al.	6,950,687 B2	9/2005	Al-Ali
6,639,668 B1	10/2003	Trepagnier	6,952,340 B2	10/2005	Son
6,640,116 B2	10/2003	Diab	6,961,598 B2	11/2005	Diab
6,641,533 B2	11/2003	Causey et al.	6,970,792 B1	11/2005	Diab
6,643,530 B2	11/2003	Diab et al.	6,979,812 B2	12/2005	Al-Ali
6,646,556 B1	11/2003	Smith et al.	6,980,419 B2	12/2005	Smith et al.
6,650,917 B2	11/2003	Diab et al.	6,983,179 B2	1/2006	Ben-haim
6,650,939 B2	11/2003	Takpke, II et al.	6,985,764 B2	1/2006	Mason et al.
6,654,624 B2	11/2003	Diab et al.	6,988,989 B2	1/2006	Weiner et al.
D483,872 S	12/2003	Cruz et al.	6,990,087 B2	1/2006	Rao et al.
6,658,276 B2	12/2003	Kianl et al.	6,993,371 B2	1/2006	Kiani et al.
6,661,161 B1	12/2003	Lanzo et al.	6,996,427 B2	2/2006	Ali et al.
6,663,570 B2	12/2003	Mott et al.	6,997,884 B2	2/2006	Ulmsten
6,671,531 B2	12/2003	Al-Ali et al.	6,999,904 B2	2/2006	Weber et al.
6,678,543 B2	1/2004	Diab et al.	7,003,338 B2	2/2006	Weber et al.
6,684,090 B2	1/2004	Ali et al.	7,003,339 B2	2/2006	Diab et al.
6,684,091 B2	1/2004	Parker	7,015,451 B2	3/2006	Dalke et al.
6,694,160 B2	2/2004	Chin	7,024,233 B2	4/2006	Ali et al.
6,694,180 B1	2/2004	Boesen	7,025,729 B2	4/2006	De Chazal et al.
6,697,656 B1	2/2004	Al-Ali	7,027,849 B2	4/2006	Al-Ali
6,697,657 B1	2/2004	Shehada et al.	7,030,749 B2	4/2006	Al-Ali
6,697,658 B2	2/2004	Al-Ali	7,033,761 B2	4/2006	Shafer
RE38,476 E	3/2004	Diab et al.	7,035,686 B2	4/2006	Hogan
6,699,194 B1	3/2004	Diab et al.	7,039,449 B2	5/2006	Al-Ali
6,714,804 B2	3/2004	Al-Ali et al.	7,041,060 B2	5/2006	Flaherty et al.
RE38,492 E	4/2004	Diab et al.	7,044,918 B2	5/2006	Diab
6,719,694 B2	4/2004	Weng et al.	7,044,930 B2	5/2006	Stromberg
6,720,734 B2	4/2004	Norris	7,063,666 B2	6/2006	Weng et al.
6,721,582 B2	4/2004	Trepagnier et al.	7,067,893 B2	6/2006	Mills et al.
6,721,585 B1	4/2004	Parker	7,079,035 B2	7/2006	Bock et al.
6,725,075 B2	4/2004	Al-Ali	7,096,052 B2	8/2006	Mason et al.
6,725,086 B2	4/2004	Marinello	7,096,054 B2	8/2006	Abdul-Hafiz et al.
6,728,560 B2	4/2004	Kollias et al.	7,125,382 B2	10/2006	Zhou et al.
6,731,962 B1	5/2004	Katarow et al.	7,132,641 B2	11/2006	Schulz et al.
6,735,459 B2	5/2004	Parker	7,142,901 B2	11/2006	Kiani et al.
6,745,060 B2	6/2004	Diab et al.	7,149,561 B2	12/2006	Diab
6,746,406 B2	6/2004	Lia et al.	7,186,966 B2	3/2007	Al-Ali
6,750,463 B1	6/2004	Riley	7,188,621 B2	3/2007	DeVries et al.
6,751,492 B2	6/2004	Ben-Haim	7,190,261 B2	3/2007	Al-Ali
6,760,607 B2	7/2004	Al-Ali	7,208,119 B1	4/2007	Kurtcock et al.
6,766,188 B2	7/2004	Soller	7,215,984 B2	5/2007	Diab
6,770,028 B1	8/2004	Ali et al.	7,215,986 B2	5/2007	Diab
6,771,994 B2	8/2004	Kiani et al.	7,221,971 B2	5/2007	Diab
6,783,492 B2	8/2004	Dominguez	7,225,006 B2	5/2007	Al-Ali et al.
6,790,178 B1	9/2004	Mault et al.	7,225,007 B2	5/2007	Al-Ali
6,792,300 B1	9/2004	Diab et al.	RE39,672 E	6/2007	Shehada et al.
6,795,724 B2	9/2004	Hogan	7,229,415 B2	6/2007	Schwartz
6,796,186 B2	9/2004	Lia et al.	7,239,905 B2	7/2007	Kiani-Azarbayjany et al.
6,804,656 B1	10/2004	Rosenfeld	7,241,287 B2	7/2007	Shehada et al.
6,807,050 B1	10/2004	Whitehorn et al.	7,244,251 B2	7/2007	Shehada et al.
6,813,511 B2	11/2004	Diab et al.	7,245,373 B2	7/2007	Soller et al.
6,816,741 B2	11/2004	Diab	7,245,953 B1	7/2007	Parker
6,817,979 B2	11/2004	Nihtila et al.	7,252,659 B2	8/2007	Shehada et al.
6,822,564 B2	11/2004	Al-Ali	7,254,429 B2	8/2007	Schurman et al.
6,826,419 B2	11/2004	Diab et al.	7,254,431 B2	8/2007	Al-Ali
6,830,711 B2	12/2004	Mills et al.	7,254,433 B2	8/2007	Diab et al.
6,837,848 B2	1/2005	Bonner et al.	7,254,434 B2	8/2007	Schulz et al.
6,841,535 B2	1/2005	Divita et al.	7,256,708 B2	8/2007	Rosenfeld
6,845,256 B2	1/2005	Chin et al.	7,257,438 B2	8/2007	Kinast
6,850,787 B2	2/2005	Weber et al.	7,261,697 B2	8/2007	Berstein
6,850,788 B2	2/2005	Al-Ali	7,264,616 B2	9/2007	Shehada et al.
6,852,083 B2	2/2005	Caro et al.	7,267,671 B2	9/2007	Shehada et al.
6,855,112 B2	2/2005	Kao et al.	7,272,425 B2	9/2007	Al-Ali
6,860,266 B2	3/2005	Blike	7,274,955 B2	9/2007	Kiani et al.
6,861,639 B2	3/2005	Al-Ali	D554,263 S	10/2007	Al-Ali
6,897,788 B2	5/2005	Khair et al.	7,280,858 B2	10/2007	Al-Ali et al.
6,898,452 B2	5/2005	Al-Ali et al.	7,285,090 B2	10/2007	Stivoric
6,907,237 B1	6/2005	Dorenbosch et al.	7,289,835 B2	10/2007	Mansfield et al.
6,915,149 B2	7/2005	Ben-Haim	7,292,883 B2	11/2007	De Felice et al.
6,920,345 B2	7/2005	Al-Ali et al.	7,295,866 B2	11/2007	Al-Ali
6,931,268 B1	8/2005	Kiani-Azarbayjany et al.	7,307,543 B2	12/2007	Rosenfeld
			7,313,423 B2	12/2007	Griffin et al.
			7,314,446 B2	1/2008	Byrd et al.
			7,315,825 B2	1/2008	Rosenfeld
			7,321,862 B2	1/2008	Rosenfeld

(56)

References Cited

U.S. PATENT DOCUMENTS

7,322,971 B2	1/2008	Shehada et al.	7,618,375 B2	11/2009	Flaherty
7,328,053 B1	2/2008	Diab et al.	D606,659 S	12/2009	Kiani et al.
7,332,784 B2	2/2008	Mills et al.	7,639,145 B2	12/2009	Lawson et al.
7,340,287 B2	3/2008	Mason et al.	7,647,083 B2	1/2010	Al-Ali et al.
7,341,559 B2	3/2008	Schulz et al.	7,650,291 B2	1/2010	Rosenfeld
7,343,186 B2	3/2008	Lamego et al.	D609,193 S	2/2010	Al-Ali et al.
D566,282 S	4/2008	Al-Ali et al.	7,654,966 B2	2/2010	Westinskow et al.
7,355,512 B1	4/2008	Al-Ali	7,684,845 B2	3/2010	Juan
7,356,178 B2	4/2008	Ziel et al.	7,689,437 B1	3/2010	Teller et al.
7,356,365 B2	4/2008	Schurman	RE41,236 E	4/2010	Seely
7,359,742 B2	4/2008	Maser et al.	D614,305 S	4/2010	Al-Ali et al.
7,371,981 B2	5/2008	Abdul-Hafiz	7,693,697 B2	4/2010	Westinskow et al.
7,373,193 B2	5/2008	Al-Ali et al.	RE41,317 E	5/2010	Parker
7,373,194 B2	5/2008	Weber et al.	D615,655 S	5/2010	Maser et al.
7,376,453 B1	5/2008	Diab et al.	7,722,542 B2	5/2010	Lia et al.
7,377,794 B2	5/2008	Al Ali et al.	7,729,733 B2	6/2010	Al-Ali et al.
7,377,899 B2	5/2008	Weber et al.	7,734,320 B2	6/2010	Al-Ali
7,378,975 B1	5/2008	Smith et al.	7,736,318 B2	6/2010	Consentino et al.
7,382,247 B2	6/2008	Welch et al.	7,740,590 B2	6/2010	Bernstein
7,383,070 B2	6/2008	Diab et al.	7,761,127 B2	7/2010	Al-Ali et al.
7,390,299 B2	6/2008	Weiner et al.	7,761,128 B2	7/2010	Al-Ali et al.
7,392,074 B2	6/2008	Isaacson et al.	7,763,420 B2	7/2010	Strizker et al.
7,395,216 B2	7/2008	Rosenfeld	7,764,982 B2	7/2010	Dalke et al.
7,411,509 B2	8/2008	Rosenfeld	D621,515 S	8/2010	Chua et al.
7,413,546 B2	8/2008	Agutter et al.	D621,516 S	8/2010	Kiani et al.
7,415,297 B2	8/2008	Al-Ali et al.	7,766,818 B2	8/2010	Iketani et al.
7,419,483 B2	9/2008	Shehada	7,774,060 B2	8/2010	Westenskow et al.
7,428,432 B2	9/2008	Ali et al.	7,778,851 B2	8/2010	Schoenberg et al.
7,433,827 B2	10/2008	Rosenfeld	7,791,155 B2	9/2010	Diab
7,438,683 B2	10/2008	Al-Ali et al.	7,794,407 B2	9/2010	Rothenberg
7,439,856 B2	10/2008	Weiner et al.	7,801,581 B2	9/2010	Diab
7,440,787 B2	10/2008	Diab	7,801,605 B2	9/2010	Smirles et al.
7,454,240 B2	11/2008	Diab et al.	7,806,830 B2	10/2010	Bernstein
7,454,359 B2	11/2008	Rosenfeld	7,820,184 B2	10/2010	Strizker et al.
7,454,360 B2	11/2008	Rosenfeld	7,822,452 B2	10/2010	Schurman et al.
7,462,151 B2	12/2008	Childre et al.	RE41,912 E	11/2010	Parker
7,467,002 B2	12/2008	Weber et al.	7,831,450 B2	11/2010	Schoenberg
7,467,094 B2	12/2008	Rosenfeld	7,841,986 B2	11/2010	He et al.
7,469,157 B2	12/2008	Diab et al.	7,844,313 B2	11/2010	Kiani et al.
7,471,969 B2	12/2008	Diab et al.	7,844,314 B2	11/2010	Al-Ali
7,471,971 B2	12/2008	Diab et al.	7,844,315 B2	11/2010	Al-Ali
7,475,019 B2	1/2009	Rosenfeld	7,848,935 B2	12/2010	Gotlib
7,483,729 B2	1/2009	Al-Ali et al.	7,858,322 B2	12/2010	Tymianski et al.
7,483,730 B2	1/2009	Diab et al.	7,865,222 B2	1/2011	Weber et al.
7,486,977 B2	2/2009	Sweitzer et al.	7,865,232 B1	1/2011	Krishnaswamy et al.
7,489,250 B2	2/2009	Bock et al.	7,873,497 B2	1/2011	Weber et al.
7,489,958 B2	2/2009	Diab et al.	7,880,606 B2	2/2011	Al-Ali
7,496,391 B2	2/2009	Diab et al.	7,880,626 B2	2/2011	Al-Ali et al.
7,496,393 B2	2/2009	Diab et al.	7,881,892 B2	2/2011	Soyemi et al.
D587,657 S	3/2009	Al-Ali et al.	7,884,314 B2	2/2011	Hamada
7,497,828 B1	3/2009	Wilk et al.	7,890,156 B2	2/2011	Ooi et al.
7,499,739 B2	3/2009	Sweitzer et al.	7,891,355 B2	2/2011	Al-Ali et al.
7,499,741 B2	3/2009	Diab et al.	7,894,868 B2	2/2011	Al-Ali et al.
7,499,835 B2	3/2009	Weber et al.	7,899,507 B2	3/2011	Al-Ali et al.
7,500,950 B2	3/2009	Al-Ali et al.	7,899,518 B2	3/2011	Trepagnier et al.
7,509,154 B2	3/2009	Diab et al.	7,904,132 B2	3/2011	Weber et al.
7,509,494 B2	3/2009	Al-Ali	7,909,772 B2	3/2011	Popov et al.
7,510,849 B2	3/2009	Schurman et al.	7,910,875 B2	3/2011	Al-Ali
7,515,043 B2	4/2009	Welch et al.	7,914,514 B2	3/2011	Calderon
7,515,044 B2	4/2009	Welch et al.	7,919,713 B2	4/2011	Al-Ali et al.
7,526,328 B2	4/2009	Diab et al.	7,937,128 B2	5/2011	Al-Ali
7,530,942 B1	5/2009	Diab	7,937,129 B2	5/2011	Mason et al.
7,530,949 B2	5/2009	Al Ali et al.	7,937,130 B2	5/2011	Diab et al.
7,530,955 B2	5/2009	Diab et al.	7,941,199 B2	5/2011	Kiani
7,532,919 B2	5/2009	Soyemi et al.	7,951,086 B2	5/2011	Flaherty et al.
7,549,961 B1	6/2009	Hwang	7,957,780 B2	6/2011	Lamego et al.
7,551,717 B2	6/2009	Tome et al.	7,962,188 B2	6/2011	Kiani et al.
7,559,520 B2	7/2009	Quijano et al.	7,962,190 B1	6/2011	Diab et al.
7,563,110 B2	7/2009	Al-Ali et al.	7,963,927 B2	6/2011	Kelleher et al.
7,577,475 B2	8/2009	Consentino et al.	7,967,749 B2	6/2011	Hutchinson et al.
7,590,950 B2	9/2009	Collins et al.	7,970,450 B2	6/2011	Kroecker
7,596,398 B2	9/2009	Al-Ali et al.	7,976,472 B2	7/2011	Kiani
7,597,665 B2	10/2009	Wilk et al.	7,988,637 B2	8/2011	Diab
7,612,999 B2	11/2009	Clark et al.	7,988,639 B2	8/2011	Starks
7,616,303 B2	11/2009	Yang et al.	7,990,382 B2	8/2011	Kiani
			7,991,446 B2	8/2011	Ali et al.
			7,991,463 B2	8/2011	Kelleher et al.
			7,991,625 B2	8/2011	Rosenfeld
			8,000,761 B2	8/2011	Al-Ali

(56)

References Cited

U.S. PATENT DOCUMENTS

8,008,088 B2	8/2011	Bellott et al.	8,353,842 B2	1/2013	Al-Ali et al.
RE42,753 E	9/2011	Kiani-Azarbayjany et al.	8,355,766 B2	1/2013	MacNeish, III et al.
8,019,400 B2	9/2011	Diab et al.	8,359,080 B2	1/2013	Diab et al.
8,027,846 B2	9/2011	Schoenberg	8,360,936 B2	1/2013	Dibenedetto et al.
8,028,701 B2	10/2011	Al-Ali et al.	8,364,223 B2	1/2013	Al-Ali et al.
8,029,765 B2	10/2011	Bellott et al.	8,364,226 B2	1/2013	Diab et al.
8,033,996 B2	10/2011	Behar	8,374,665 B2	2/2013	Lamego
8,036,727 B2	10/2011	Schurman et al.	8,385,972 B2	2/2013	Bochenko et al.
8,036,728 B2	10/2011	Diab et al.	8,385,995 B2	2/2013	Al-ali et al.
8,036,736 B2	10/2011	Snyder et al.	8,385,996 B2	2/2013	Smith et al.
8,038,625 B2	10/2011	Afonso et al.	D679,018 S	3/2013	Fullerton et al.
8,046,040 B2	10/2011	Ali et al.	8,388,353 B2	3/2013	Kiani
8,046,041 B2	10/2011	Diab et al.	8,399,822 B2	3/2013	Al-Ali
8,046,042 B2	10/2011	Diab et al.	8,401,602 B2	3/2013	Kiani
8,048,040 B2	11/2011	Kiani	8,401,874 B2	3/2013	Rosenfeld
8,050,728 B2	11/2011	Al-Ali et al.	8,405,608 B2	3/2013	Al-Ali et al.
8,068,104 B2	11/2011	Rampersad	8,414,499 B2	4/2013	Al-Ali et al.
8,073,707 B2	12/2011	Teller et al.	8,418,524 B2	4/2013	Al-Ali
8,094,013 B1	1/2012	Lee et al.	8,423,106 B2	4/2013	Lamego et al.
RE43,169 E	2/2012	Parker	8,428,967 B2	4/2013	Olsen et al.
8,118,620 B2	2/2012	Al-Ali et al.	8,430,817 B1	4/2013	Al-Ali et al.
8,126,528 B2	2/2012	Diab et al.	8,437,825 B2	5/2013	Dalvi et al.
8,128,572 B2	3/2012	Diab et al.	8,455,290 B2	6/2013	Siskavich
8,130,105 B2	3/2012	Al-Ali et al.	8,457,703 B2	6/2013	Al-Ali
8,145,287 B2	3/2012	Diab et al.	8,457,704 B2	6/2013	Sweitzer et al.
8,150,487 B2	4/2012	Diab et al.	8,457,707 B2	6/2013	Kiani
D659,836 S	5/2012	Bensch et al.	8,463,349 B2	6/2013	Diab et al.
8,170,887 B2	5/2012	Rosenfeld	8,466,286 B2	6/2013	Bellot et al.
8,175,672 B2	5/2012	Parker	8,467,556 B2	6/2013	Shennib et al.
8,175,895 B2	5/2012	Rosenfeld	8,471,713 B2	6/2013	Poeze et al.
8,180,420 B2	5/2012	Diab et al.	8,473,020 B2	6/2013	Kiani et al.
8,182,443 B1	5/2012	Kiani	8,483,787 B2	7/2013	Al-Ali et al.
8,185,180 B2	5/2012	Diab et al.	8,489,167 B2	7/2013	Buxton et al.
8,190,223 B2	5/2012	Al-Ali et al.	8,489,364 B2	7/2013	Weber et al.
8,190,227 B2	5/2012	Diab et al.	8,498,684 B2	7/2013	Weber et al.
8,200,308 B2	6/2012	Zhang et al.	8,500,692 B2	8/2013	Yodfat et al.
8,203,438 B2	6/2012	Kiani et al.	8,504,128 B2	8/2013	Blank et al.
8,203,704 B2	6/2012	Merritt et al.	8,509,867 B2	8/2013	Workman et al.
8,204,566 B2	6/2012	Schurman et al.	8,515,509 B2	8/2013	Bruinsma et al.
8,206,312 B2	6/2012	Farquhar	8,523,781 B2	9/2013	Al-Ali
8,214,007 B2	7/2012	Baker et al.	8,529,301 B2	9/2013	Al-Ali et al.
8,219,172 B2	7/2012	Schurman et al.	8,532,727 B2	9/2013	Ali et al.
8,224,411 B2	7/2012	Al-Ali et al.	8,532,728 B2	9/2013	Diab et al.
8,228,181 B2	7/2012	Al-Ali	D692,145 S	10/2013	Al-Ali et al.
8,229,533 B2	7/2012	Diab et al.	8,545,445 B2	10/2013	Kamen et al.
8,233,955 B2	7/2012	Al-Ali et al.	8,547,209 B2	10/2013	Kiani et al.
8,235,907 B2	8/2012	Wilk et al.	8,548,548 B2	10/2013	Al-Ali
8,239,780 B2	8/2012	Manetta et al.	8,548,549 B2	10/2013	Schurman et al.
8,241,213 B2	8/2012	Lynn et al.	8,548,550 B2	10/2013	Al-Ali et al.
8,244,325 B2	8/2012	Al-Ali et al.	8,560,032 B2	10/2013	Al-Ali et al.
8,249,815 B2	8/2012	Taylor	8,560,034 B1	10/2013	Diab et al.
8,255,026 B1	8/2012	Al-Ali	8,564,613 B2	10/2013	Prior et al.
8,255,027 B2	8/2012	Al-Ali et al.	8,565,847 B2	10/2013	Buxton et al.
8,255,028 B2	8/2012	Al-Ali et al.	8,568,361 B2	10/2013	Yodfat et al.
8,260,577 B2	9/2012	Weber et al.	8,570,167 B2	10/2013	Al-Ali
8,265,723 B1	9/2012	McHale et al.	8,570,503 B2	10/2013	Vo et al.
8,274,360 B2	9/2012	Sampath et al.	8,571,617 B2	10/2013	Reichgott et al.
8,294,588 B2	10/2012	Fisher et al.	8,571,618 B1	10/2013	Lamego et al.
8,294,716 B2	10/2012	Lord et al.	8,571,619 B2	10/2013	Al-Ali et al.
8,301,217 B2	10/2012	Al-Ali et al.	8,577,431 B2	11/2013	Lamego et al.
8,306,596 B2	11/2012	Schurman et al.	8,578,082 B2	11/2013	Medina et al.
8,310,336 B2	11/2012	Muhsin et al.	8,579,813 B2	11/2013	Causey, III et al.
8,311,747 B2	11/2012	Taylor	8,581,732 B2	11/2013	Al-Ali et al.
8,311,748 B2	11/2012	Taylor et al.	8,584,345 B2	11/2013	Al-Ali et al.
8,315,683 B2	11/2012	Al-Ali et al.	8,588,880 B2	11/2013	Abdul-Hafiz et al.
8,315,812 B2	11/2012	Taylor	8,588,924 B2	11/2013	Dion
8,315,813 B2	11/2012	Taylor et al.	8,597,287 B2	12/2013	Benamou et al.
8,315,814 B2	11/2012	Taylor et al.	8,600,467 B2	12/2013	Al-Ali et al.
8,321,150 B2	11/2012	Taylor	8,600,777 B2	12/2013	Schoenberg
RE43,860 E	12/2012	Parker	8,606,342 B2	12/2013	Diab
8,326,392 B2	12/2012	Grubac et al.	8,615,281 B2	12/2013	Yodfat et al.
8,326,649 B2	12/2012	Rosenfeld	8,620,678 B2	12/2013	Gotlib
8,328,793 B2	12/2012	Birkenbach et al.	8,626,255 B2	1/2014	Al-Ali et al.
8,337,403 B2	12/2012	Al-Ali et al.	8,630,691 B2	1/2014	Lamego et al.
8,346,330 B2	1/2013	Lamego	8,634,889 B2	1/2014	Al-Ali et al.
			8,641,631 B2	2/2014	Sierra et al.
			8,641,670 B2	2/2014	Yodfat et al.
			8,652,060 B2	2/2014	Al-Ali
			8,663,107 B2	3/2014	Kiani

(56)

References Cited

U.S. PATENT DOCUMENTS

8,666,468	B1	3/2014	Al-Ali	8,922,382	B2	12/2014	Al-Ali et al.
8,667,967	B2	3/2014	Al- Ali et al.	8,929,964	B2	1/2015	Al-Ali et al.
8,670,810	B2	3/2014	Isaacson	8,939,914	B2	1/2015	Turnquist et al.
8,670,811	B2	3/2014	O'Reilly	8,942,777	B2	1/2015	Diab et al.
8,670,814	B2	3/2014	Diab et al.	8,948,834	B2	2/2015	Diab et al.
8,676,286	B2	3/2014	Weber et al.	8,948,835	B2	2/2015	Diab
8,682,407	B2	3/2014	Al-Ali	8,951,248	B2	2/2015	Messerly et al.
RE44,823	E	4/2014	Parker	8,956,292	B2	2/2015	Wekell et al.
RE44,875	E	4/2014	Kiani et al.	8,962,170	B2	2/2015	Frey et al.
8,690,771	B2	4/2014	Wekell et al.	8,965,471	B2	2/2015	Lamego
8,690,799	B2	4/2014	Telfort et al.	8,977,351	B2	3/2015	Kivisto
8,695,206	B2	4/2014	Isaacson et al.	8,983,564	B2	3/2015	Al-Ali
8,700,112	B2	4/2014	Kiani	8,989,831	B2	3/2015	Al-Ali et al.
8,702,627	B2	4/2014	Telfort et al.	8,996,085	B2	3/2015	Kiani et al.
8,706,179	B2	4/2014	Parker	8,998,809	B2	4/2015	Kiani
8,712,494	B1	4/2014	MacNeish, III et al.	9,014,778	B2	4/2015	Datta et al.
8,715,206	B2	5/2014	Telfort et al.	9,017,355	B2	4/2015	Smith et al.
8,718,735	B2	5/2014	Lamego et al.	9,028,407	B1	5/2015	Bennett-Guerrero
8,718,737	B2	5/2014	Diab et al.	9,028,429	B2	5/2015	Telfort et al.
8,718,738	B2	5/2014	Blank et al.	9,037,207	B2	5/2015	Al-Ali et al.
8,720,249	B2	5/2014	Al-Ali	9,041,529	B2	5/2015	Booij et al.
8,721,541	B2	5/2014	Al-Ali et al.	9,057,689	B2	6/2015	Soller
8,721,542	B2	5/2014	Al-Ali et al.	9,060,721	B2	6/2015	Reichgott et al.
8,723,677	B1	5/2014	Kiani	9,066,666	B2	6/2015	Kiani
8,725,226	B2	5/2014	Isaacson et al.	9,066,680	B1	6/2015	Al-Ali et al.
8,740,792	B1	6/2014	Kiani et al.	9,072,474	B2	7/2015	Al-Ali et al.
8,754,776	B2	6/2014	Poeze et al.	9,078,560	B2	7/2015	Schurman et al.
8,755,535	B2	6/2014	Telfort et al.	9,084,569	B2	7/2015	Weber et al.
8,755,856	B2	6/2014	Diab et al.	9,095,291	B2	8/2015	Soller
8,755,872	B1	6/2014	Marinow	9,095,316	B2	8/2015	Welch et al.
8,761,850	B2	6/2014	Lamego	9,106,038	B2	8/2015	Telfort et al.
8,761,852	B2	6/2014	Parthasarathy	9,107,625	B2	8/2015	Telfort et al.
D709,846	S	7/2014	Oswaks	9,107,626	B2	8/2015	Al-Ali et al.
8,764,671	B2	7/2014	Kiani	9,113,831	B2	8/2015	Al-Ali
8,768,423	B2	7/2014	Shakespeare et al.	9,113,832	B2	8/2015	Al-Ali
8,771,204	B2	7/2014	Telfort et al.	9,119,595	B2	9/2015	Lamego
8,777,634	B2	7/2014	Kiani et al.	9,131,881	B2	9/2015	Diab et al.
8,781,543	B2	7/2014	Diab et al.	9,131,882	B2	9/2015	Al-Ali et al.
8,781,544	B2	7/2014	Al-Ali et al.	9,131,883	B2	9/2015	Al-Ali
8,781,549	B2	7/2014	Al-Ali et al.	9,131,917	B2	9/2015	Telfort et al.
8,788,003	B2	7/2014	Schurman et al.	9,138,180	B1	9/2015	Coverston et al.
8,790,268	B2	7/2014	Al-Ali	9,138,182	B2	9/2015	Al-Ali et al.
8,792,950	B2	7/2014	Larsen et al.	9,138,192	B2	9/2015	Weber et al.
8,801,613	B2	8/2014	Al-Ali et al.	9,142,117	B2	9/2015	Muhsin et al.
8,814,822	B2	8/2014	Yodfat et al.	9,149,228	B2	10/2015	Kinast
8,818,477	B2	8/2014	Soller	9,153,112	B1	10/2015	Kiani et al.
8,821,397	B2	9/2014	Al-Ali et al.	9,153,121	B2	10/2015	Kiani et al.
8,821,415	B2	9/2014	Al-Ali et al.	9,161,696	B2	10/2015	Al-Ali et al.
8,830,449	B1	9/2014	Lamego et al.	9,161,713	B2	10/2015	Al-Ali et al.
8,831,700	B2	9/2014	Schurman et al.	9,167,995	B2	10/2015	Lamego et al.
8,840,549	B2	9/2014	Al-Ali et al.	9,173,993	B2	11/2015	Yodfat et al.
8,845,530	B2	9/2014	Bruce et al.	9,176,141	B2	11/2015	Al-Ali et al.
8,847,740	B2	9/2014	Kiani et al.	9,183,738	B1	11/2015	Allen, Sr. et al.
8,849,365	B2	9/2014	Smith et al.	9,186,102	B2	11/2015	Bruinsma et al.
8,852,094	B2	10/2014	Al-Ali et al.	9,192,312	B2	11/2015	Al-Ali
8,852,994	B2	10/2014	Wojtczuk et al.	9,192,329	B2	11/2015	Al-Ali
8,866,620	B2	10/2014	Amir	9,192,351	B1	11/2015	Telfort et al.
8,868,147	B2	10/2014	Stippick et al.	9,195,385	B2	11/2015	Al-Ali et al.
8,868,150	B2	10/2014	Al-Ali et al.	D745,167	S	12/2015	Canas et al.
8,870,792	B2	10/2014	Al-Ali et al.	9,211,072	B2	12/2015	Kiani
8,873,035	B2	10/2014	Yang et al.	9,211,095	B1	12/2015	Al-Ali
D718,455	S	11/2014	Maser et al.	9,218,454	B2	12/2015	Kiani et al.
8,878,888	B2	11/2014	Rosenfeld	9,226,696	B2	1/2016	Kiani
8,886,271	B2	11/2014	Kiani et al.	9,241,662	B2	1/2016	Al-Ali et al.
8,888,539	B2	11/2014	Al-Ali et al.	9,245,668	B1	1/2016	Vo et al.
8,888,708	B2	11/2014	Diab et al.	9,254,087	B2	2/2016	Isaacson et al.
8,892,180	B2	11/2014	Weber et al.	9,259,185	B2	2/2016	Abdul-Hafiz et al.
8,897,847	B2	11/2014	Al-Ali	9,262,586	B2	2/2016	Steiger et al.
8,903,467	B2	12/2014	Sweitzer et al.	9,267,572	B2	2/2016	Barker et al.
8,907,287	B2	12/2014	Vanderpohl	9,277,864	B2	3/2016	Yang et al.
8,909,310	B2	12/2014	Lamego et al.	9,277,880	B2	3/2016	Poeze et al.
8,911,377	B2	12/2014	Al-Ali	9,289,167	B2	3/2016	Diab et al.
8,912,909	B2	12/2014	Al-Ali et al.	9,295,421	B2	3/2016	Kiani et al.
8,920,317	B2	12/2014	Al-Ali et al.	9,307,928	B1	4/2016	Al-Ali et al.
8,921,699	B2	12/2014	Al-Ali et al.	9,323,894	B2	4/2016	Kiani
				D755,392	S	5/2016	Hwang et al.
				9,326,712	B1	5/2016	Kiani
				9,333,316	B2	5/2016	Kiani
				9,339,220	B2	5/2016	Lamego et al.

(56)

References Cited

U.S. PATENT DOCUMENTS

9,341,565 B2	5/2016	Lamego et al.	2005/0113655 A1	5/2005	Hull
9,351,673 B2	5/2016	Diab et al.	2005/0119580 A1	6/2005	Eveland
9,351,675 B2	5/2016	Al-Ali et al.	2005/0124864 A1	6/2005	MacK et al.
9,364,155 B2	6/2016	Bardy et al.	2005/0125256 A1	6/2005	Schoenberg
9,364,181 B2	6/2016	Kiani et al.	2005/0131288 A1	6/2005	Turner et al.
9,368,671 B2	6/2016	Wojtczuk et al.	2005/0164933 A1	7/2005	Tymianski et al.
9,370,325 B2	6/2016	Al-Ali et al.	2005/0191294 A1	9/2005	Arap et al.
9,370,326 B2	6/2016	McHale et al.	2005/0197550 A1	9/2005	Al-Ali et al.
9,370,335 B2	6/2016	Al-ali et al.	2005/0228298 A1	10/2005	Banet et al.
9,375,179 B2	6/2016	Schultz et al.	2005/0228299 A1	10/2005	Banet
9,375,185 B2	6/2016	Ali et al.	2005/0234317 A1	10/2005	Kiani
9,386,953 B2	7/2016	Al-Ali	2005/0245839 A1	11/2005	Stivoric
9,386,961 B2	7/2016	Al-Ali et al.	2005/0268401 A1	12/2005	Dixon et al.
9,392,945 B2	7/2016	Al-Ali et al.	2005/0277872 A1	12/2005	Colby, Jr. et al.
9,397,448 B2	7/2016	Al-Ali et al.	2006/0049936 A1	3/2006	Collins, Jr. et al.
9,402,544 B2	8/2016	Yee et al.	2006/0058647 A1	3/2006	Strommer et al.
9,436,645 B2	9/2016	Al-Ali et al.	2006/0089543 A1	4/2006	Kim et al.
9,439,566 B2	9/2016	Arne et al.	2006/0089546 A1	4/2006	Mahony et al.
9,480,408 B2	11/2016	Isaacson et al.	2006/0094936 A1	5/2006	Russ
9,498,158 B2	11/2016	Isaacson	2006/0106294 A1	5/2006	Maser et al.
9,529,762 B2	12/2016	Gisler et al.	2006/0149393 A1	7/2006	Calderon
2001/0011355 A1	8/2001	Kawai	2006/0155175 A1	7/2006	Ogino et al.
2001/0031922 A1	10/2001	Weng et al.	2006/0167351 A1	7/2006	Isaacson et al.
2001/0046366 A1	11/2001	Susskind	2006/0217684 A1	9/2006	Shehada et al.
2002/0045836 A1	4/2002	Alkawwas	2006/0217685 A1	9/2006	Shehada et al.
2002/0052311 A1	5/2002	Solomon et al.	2006/0224413 A1	10/2006	Kim et al.
2002/0063690 A1	5/2002	Chung et al.	2006/0235300 A1	10/2006	Weng et al.
2002/0099277 A1	7/2002	Harry et al.	2006/0253042 A1	11/2006	Stahmann et al.
2002/0107436 A1	8/2002	Barton	2006/0276714 A1	12/2006	Holt et al.
2002/0140675 A1	10/2002	Ali et al.	2007/0000490 A1	1/2007	DeVries et al.
2002/0165462 A1	11/2002	Westbrook et al.	2007/0002533 A1	1/2007	Kogan et al.
2002/0177758 A1	11/2002	Schoenberg	2007/0021675 A1	1/2007	Childre et al.
2002/0198445 A1	12/2002	Dominguez et al.	2007/0027368 A1	2/2007	Collins et al.
2003/0027326 A1	2/2003	Ulmsten et al.	2007/0032733 A1	2/2007	Burton et al.
2003/0033102 A1	2/2003	Dietiker	2007/0055116 A1	3/2007	Clark et al.
2003/0052787 A1	3/2003	Zerhusen et al.	2007/0055544 A1	3/2007	Jung et al.
2003/0058838 A1	3/2003	Wengrovitz	2007/0060798 A1	3/2007	Krupnik et al.
2003/0149349 A1	8/2003	Jensen	2007/0088406 A1	4/2007	Bennett et al.
2003/0158466 A1	8/2003	Lynn et al.	2007/0096897 A1	5/2007	Weiner
2003/0181798 A1	9/2003	Al-Ali	2007/0100222 A1	5/2007	Mastrototaro et al.
2003/0181817 A1	9/2003	Mori	2007/0118399 A1	5/2007	Avinash et al.
2003/0214408 A1	11/2003	Grajales et al.	2007/0140475 A1	6/2007	Kurtock et al.
2003/0216670 A1	11/2003	Beggs	2007/0156033 A1	7/2007	Causey et al.
2003/0229276 A1	12/2003	Sarussi et al.	2007/0157285 A1	7/2007	Frank et al.
2004/0000713 A1	1/2004	Yamashita et al.	2007/0159332 A1	7/2007	Koblasz
2004/0013647 A1	1/2004	Solomon et al.	2007/0163589 A1	7/2007	DeVries et al.
2004/0097797 A1	5/2004	Porges	2007/0185390 A1	8/2007	Perkins et al.
2004/0102687 A1	5/2004	Brashears et al.	2007/0232941 A1	10/2007	Rabinovich
2004/0122787 A1	6/2004	Avinash et al.	2007/0244724 A1	10/2007	Pendergast et al.
2004/0126007 A1	7/2004	Ziel et al.	2007/0254593 A1	11/2007	Jollota et al.
2004/0127775 A1	7/2004	Miyazaki et al.	2007/0255114 A1	11/2007	Ackermann et al.
2004/0139571 A1	7/2004	Chang et al.	2007/0255116 A1	11/2007	Mehta et al.
2004/0147818 A1	7/2004	Levy et al.	2007/0255250 A1	11/2007	Moberg
2004/0186357 A1	9/2004	Soderberg et al.	2007/0282478 A1	12/2007	Al-Ali et al.
2004/0230118 A1	11/2004	Shehada et al.	2008/0000479 A1	1/2008	Elaz et al.
2004/0230132 A1	11/2004	Shehada et al.	2008/0003200 A1	1/2008	Arap et al.
2004/0230179 A1	11/2004	Shehada et al.	2008/0021854 A1	1/2008	Jung et al.
2004/0242976 A1	12/2004	Abreu	2008/0033661 A1	2/2008	Syroid et al.
2004/0243017 A1	12/2004	Causevic	2008/0039701 A1	2/2008	Ali et al.
2004/0249670 A1	12/2004	Noguchi et al.	2008/0053438 A1	3/2008	DeVries et al.
2004/0254431 A1	12/2004	Shehada et al.	2008/0058657 A1	3/2008	Schwartz et al.
2004/0254432 A1	12/2004	Shehada et al.	2008/0090626 A1	4/2008	Griffin et al.
2004/0260161 A1	12/2004	Melker et al.	2008/0091089 A1	4/2008	Guillory et al.
2004/0267103 A1	12/2004	Li et al.	2008/0091090 A1	4/2008	Guillory et al.
2005/0010087 A1	1/2005	Banet et al.	2008/0091471 A1	4/2008	Michon et al.
2005/0020918 A1	1/2005	Wilk et al.	2008/0097167 A1	4/2008	Yudkovitch et al.
2005/0038326 A1	2/2005	Mathur	2008/0099366 A1	5/2008	Niemiec et al.
2005/0038332 A1	2/2005	Saidara et al.	2008/0113621 A1	5/2008	Parthasarathy
2005/0038680 A1	2/2005	McMahon	2008/0119412 A1	5/2008	Tymianski et al.
2005/0070773 A1	3/2005	Chin et al.	2008/0138278 A1	6/2008	Scherz et al.
2005/0070775 A1	3/2005	Chin et al.	2008/0169922 A1	7/2008	Issokson
2005/0080336 A1	4/2005	Byrd et al.	2008/0171919 A1	7/2008	Stivoric et al.
2005/0096542 A1	5/2005	Weng et al.	2008/0188795 A1	8/2008	Katz et al.
2005/0106713 A1	5/2005	Phan et al.	2008/0194918 A1	8/2008	Kulik et al.
2005/0113653 A1	5/2005	Fox et al.	2008/0208009 A1	8/2008	Shklarski
			2008/0208023 A1	8/2008	Grubac et al.
			2008/0208912 A1	8/2008	Garibaldi
			2008/0221396 A1	9/2008	Garces et al.
			2008/0221420 A1	9/2008	Grubac et al.

(56)

References Cited

U.S. PATENT DOCUMENTS

2008/0222251 A1	9/2008	Parthasarathy	2011/0082711 A1	4/2011	Poeze et al.
2008/0228077 A1	9/2008	Wilk et al.	2011/0087083 A1	4/2011	Poeze et al.
2008/0275309 A1	11/2008	Stivoric et al.	2011/0087084 A1	4/2011	Jeong et al.
2008/0281167 A1	11/2008	Soderberg et al.	2011/0087117 A1	4/2011	Tremper et al.
2008/0281168 A1	11/2008	Gibson et al.	2011/0087756 A1	4/2011	Biondi
2008/0281181 A1	11/2008	Manziona et al.	2011/0098583 A1	4/2011	Pandia et al.
2008/0287751 A1	11/2008	Stivoric et al.	2011/0105854 A1	5/2011	Kiani et al.
2008/0292172 A1	11/2008	Assmann et al.	2011/0105956 A1	5/2011	Hirth
2008/0300020 A1	12/2008	Nishizawa et al.	2011/0118573 A1	5/2011	Mckenna
2008/0319275 A1	12/2008	Chiu et al.	2011/0125060 A1	5/2011	Telfort et al.
2008/0319354 A1	12/2008	Bell et al.	2011/0152629 A1	6/2011	Eaton et al.
2009/0005651 A1	1/2009	Ward et al.	2011/0172967 A1	7/2011	Al-Ali et al.
2009/0018808 A1	1/2009	Bronstein et al.	2011/0184252 A1	7/2011	Archer et al.
2009/0024008 A1	1/2009	Brunner et al.	2011/0184253 A1	7/2011	Archer et al.
2009/0043172 A1	2/2009	Zagorchev et al.	2011/0208015 A1	8/2011	Welch et al.
2009/0043180 A1	2/2009	Tschautscher et al.	2011/0208018 A1	8/2011	Kiani
2009/0052623 A1	2/2009	Tome et al.	2011/0208073 A1	8/2011	Matsukawa et al.
2009/0054735 A1	2/2009	Higgins et al.	2011/0209915 A1	9/2011	Telfort et al.
2009/0062682 A1	3/2009	Bland et al.	2011/0212090 A1	9/2011	Pedersen et al.
2009/0069642 A1	3/2009	Gao et al.	2011/0213212 A1	9/2011	Al-Ali
2009/0099480 A1	4/2009	Salgo et al.	2011/0227739 A1	9/2011	Gilham et al.
2009/0119330 A1	5/2009	Sampath et al.	2011/0230733 A1	9/2011	Al-Ali
2009/0119843 A1	5/2009	Rodgers et al.	2011/0237911 A1	9/2011	Lamego et al.
2009/0124867 A1	5/2009	Hirsch et al.	2011/0237969 A1	9/2011	Eckerbom et al.
2009/0131759 A1	5/2009	Sims et al.	2011/0257544 A1	10/2011	Kaasinen
2009/0143832 A1	6/2009	Saba	2011/0263203 A1	10/2011	Parthasarathy
2009/0157058 A1	6/2009	Ferren et al.	2011/0288383 A1	11/2011	Diab
2009/0171170 A1	7/2009	Li et al.	2011/0295094 A1	12/2011	Doyle et al.
2009/0171225 A1	7/2009	Gadodia et al.	2011/0301444 A1	12/2011	Al-Ali
2009/0177090 A1	7/2009	Grunwald et al.	2012/0004579 A1	1/2012	Luo et al.
2009/0182287 A1	7/2009	Kassab	2012/0029300 A1	2/2012	Paquet
2009/0226372 A1	9/2009	Ruolahti et al.	2012/0029879 A1	2/2012	Sing et al.
2009/0247984 A1	10/2009	Lamego et al.	2012/0041316 A1	2/2012	Al-Ali et al.
2009/0259114 A1	10/2009	Johnson et al.	2012/0046557 A1	2/2012	Kiani
2009/0264778 A1	10/2009	Markowitz et al.	2012/0059230 A1	3/2012	Teller et al.
2009/0275813 A1	11/2009	Davis	2012/0059267 A1	3/2012	Lamego et al.
2009/0275844 A1	11/2009	Al-Ali	2012/0071771 A1	3/2012	Behar
2009/0281462 A1	11/2009	Heliot et al.	2012/0075464 A1	3/2012	Derenne et al.
2009/0299157 A1	12/2009	Telfort et al.	2012/0088984 A1	4/2012	Al-Ali et al.
2009/0299675 A1	12/2009	Isaacson et al.	2012/0095778 A1	4/2012	Gross et al.
2009/0309645 A1	12/2009	Isaacson et al.	2012/0101353 A1	4/2012	Reggiardo et al.
2009/0309755 A1	12/2009	Williamson	2012/0116175 A1	5/2012	Al-Ali et al.
2009/0322540 A1	12/2009	Richardson et al.	2012/0123799 A1	5/2012	Nolen et al.
2010/0004518 A1	1/2010	Vo et al.	2012/0136221 A1	5/2012	Killen et al.
2010/0030040 A1	2/2010	Poeze et al.	2012/0165629 A1	6/2012	Merritt et al.
2010/0030094 A1	2/2010	Lundback	2012/0179006 A1	7/2012	Jansen et al.
2010/0036209 A1	2/2010	Ferren et al.	2012/0184120 A1	7/2012	Basta et al.
2010/0069725 A1	3/2010	Al-Ali	2012/0197619 A1	8/2012	Namer Yelin et al.
2010/0125188 A1	5/2010	Schilling et al.	2012/0203078 A1	8/2012	Sze et al.
2010/0125217 A1	5/2010	Kuo et al.	2012/0209082 A1	8/2012	Al-Ali
2010/0130840 A1	5/2010	Isaacson et al.	2012/0209084 A1	8/2012	Olsen et al.
2010/0144627 A1	6/2010	Vitek et al.	2012/0226160 A1	9/2012	Kudoh
2010/0185101 A1	7/2010	Sakai et al.	2012/0227739 A1	9/2012	Kiani
2010/0198622 A1	8/2010	Gajic et al.	2012/0239434 A1	9/2012	Breslow et al.
2010/0210924 A1	8/2010	Parthasarathy	2012/0242501 A1	9/2012	Tran et al.
2010/0210958 A1	8/2010	Manwaring et al.	2012/0265039 A1	10/2012	Kiani
2010/0298659 A1	11/2010	McCombie et al.	2012/0277597 A1	11/2012	Eshbaugh et al.
2010/0298660 A1	11/2010	McCombie et al.	2012/0282583 A1	11/2012	Thaler et al.
2010/0298661 A1	11/2010	McCombie et al.	2012/0283524 A1	11/2012	Kiani et al.
2010/0298742 A1	11/2010	Perlman et al.	2012/0284053 A1	11/2012	Rosenfeld
2010/0305412 A1	12/2010	Darrah et al.	2012/0286955 A1	11/2012	Welch et al.
2010/0309207 A1	12/2010	Prior et al.	2012/0289800 A1	11/2012	Isaacson et al.
2010/0312079 A1	12/2010	Larsen et al.	2012/0294801 A1	11/2012	Scherz et al.
2010/0312080 A1	12/2010	Isaacson	2012/0296178 A1	11/2012	Lamego et al.
2010/0312103 A1	12/2010	Gorek et al.	2012/0302894 A1	11/2012	Diab et al.
2010/0317936 A1	12/2010	Al-Ali et al.	2012/0303476 A1	11/2012	Krzyzanowski et al.
2010/0317951 A1	12/2010	Rutkowski et al.	2012/0304784 A1	12/2012	Isaacson et al.
2011/0021930 A1	1/2011	Mazzeo et al.	2012/0319816 A1	12/2012	Al-Ali
2011/0023130 A1	1/2011	Gudgel et al.	2012/0330112 A1	12/2012	Lamego et al.
2011/0028809 A1	2/2011	Goodman	2013/0006131 A1	1/2013	Narayan et al.
2011/0046495 A1	2/2011	Osyepka	2013/0006151 A1	1/2013	Main et al.
2011/0066051 A1	3/2011	Moon et al.	2013/0023775 A1	1/2013	Lamego et al.
2011/0077473 A1	3/2011	Lisogurski	2013/0035603 A1	2/2013	Jaraus et al.
2011/0078596 A1	3/2011	Rawlins et al.	2013/0041591 A1	2/2013	Lamego
2011/0080294 A1	4/2011	Tanishima et al.	2013/0046197 A1	2/2013	Dlugos, Jr. et al.
			2013/0046204 A1	2/2013	Lamego et al.
			2013/0060108 A1	3/2013	Schurman et al.
			2013/0060147 A1	3/2013	Welch et al.
			2013/0079610 A1	3/2013	Al-Ali

(56)

References Cited

U.S. PATENT DOCUMENTS

2013/0092805	A1	4/2013	Funk et al.	2014/0194709	A1	7/2014	Al-Ali et al.
2013/0096405	A1	4/2013	Garfio	2014/0194711	A1	7/2014	Al-Ali
2013/0096936	A1	4/2013	Sampath et al.	2014/0194766	A1	7/2014	Al-Ali et al.
2013/0109929	A1	5/2013	Menzel	2014/0200422	A1	7/2014	Weber et al.
2013/0109935	A1	5/2013	Al-Ali et al.	2014/0206963	A1	7/2014	Al-Ali
2013/0123616	A1	5/2013	Merritt et al.	2014/0213864	A1	7/2014	Abdul-Hafiz et al.
2013/0162433	A1	6/2013	Muhsin et al.	2014/0221798	A1	8/2014	Isaacson
2013/0178749	A1	7/2013	Lamego	2014/0243627	A1	8/2014	Diab et al.
2013/0190581	A1	7/2013	Al-Ali et al.	2014/0243632	A1	8/2014	Ulrich et al.
2013/0197328	A1	8/2013	Diab et al.	2014/0257057	A1	9/2014	Reis Cunha et al.
2013/0197364	A1	8/2013	Han	2014/0266787	A1	9/2014	Tran
2013/0211214	A1	8/2013	Olsen	2014/0266790	A1	9/2014	Al-Ali et al.
2013/0243021	A1	9/2013	Siskavich	2014/0275808	A1	9/2014	Poeze et al.
2013/0253334	A1	9/2013	Al-Ali et al.	2014/0275816	A1	9/2014	Sandmore
2013/0261494	A1	10/2013	Bloom et al.	2014/0275835	A1	9/2014	Lamego et al.
2013/0267804	A1	10/2013	Al-Ali	2014/0275871	A1	9/2014	Lamego et al.
2013/0274571	A1	10/2013	Diab et al.	2014/0275872	A1	9/2014	Merritt et al.
2013/0274572	A1	10/2013	Al-Ali et al.	2014/0275881	A1	9/2014	Lamego et al.
2013/0279109	A1	10/2013	Lindblad et al.	2014/0275883	A1	9/2014	Haisley et al.
2013/0296672	A1	11/2013	O'Neil et al.	2014/0275885	A1	9/2014	Isaacson et al.
2013/0296713	A1	11/2013	Al-Ali et al.	2014/0275932	A1	9/2014	Zadig
2013/0310667	A1	11/2013	Grubac et al.	2014/0276115	A1	9/2014	Dalvi et al.
2013/0317327	A1	11/2013	Al-Ali et al.	2014/0288388	A1	9/2014	Isaacson et al.
2013/0317370	A1	11/2013	Dalvi et al.	2014/0288400	A1	9/2014	Diab et al.
2013/0317393	A1	11/2013	Weiss et al.	2014/0296664	A1	10/2014	Bruinsma et al.
2013/0324804	A1	12/2013	McKeown et al.	2014/0303520	A1	10/2014	Telfort et al.
2013/0324808	A1	12/2013	Al-Ali et al.	2014/0309506	A1	10/2014	Lamego et al.
2013/0324817	A1	12/2013	Diab	2014/0309559	A1	10/2014	Telfort et al.
2013/0331660	A1	12/2013	Al-Ali et al.	2014/0316217	A1	10/2014	Purdon et al.
2013/0331670	A1	12/2013	Kiani	2014/0316218	A1	10/2014	Purdon et al.
2013/0338461	A1	12/2013	Lamego et al.	2014/0316228	A1	10/2014	Blank et al.
2013/0340176	A1	12/2013	Stevens et al.	2014/0323825	A1	10/2014	Al-Ali et al.
2014/0012100	A1	1/2014	Al-Ali et al.	2014/0323897	A1	10/2014	Brown et al.
2014/0022081	A1	1/2014	Ribble et al.	2014/0323898	A1	10/2014	Purdon et al.
2014/0025306	A1	1/2014	Weber et al.	2014/0330092	A1	11/2014	Al-Ali et al.
2014/0031650	A1	1/2014	Weber et al.	2014/0330098	A1	11/2014	Merritt et al.
2014/0034353	A1	2/2014	Al-Ali et al.	2014/0330099	A1	11/2014	Al-Ali et al.
2014/0046674	A1	2/2014	Rosenfeld	2014/0333440	A1	11/2014	Kiani
2014/0051952	A1	2/2014	Reichgott et al.	2014/0336481	A1	11/2014	Shakespeare et al.
2014/0051953	A1	2/2014	Lamego et al.	2014/0343389	A1	11/2014	Goldstein et al.
2014/0051954	A1	2/2014	Al-Ali et al.	2014/0343436	A1	11/2014	Kiani
2014/0058230	A1	2/2014	Abdul-Hafiz et al.	2014/0343889	A1	11/2014	Shalom et al.
2014/0066783	A1	3/2014	Kiani et al.	2014/0357966	A1	12/2014	Al-Ali et al.
2014/0066880	A1	3/2014	Prince et al.	2014/0357970	A1	12/2014	Larsen et al.
2014/0073167	A1	3/2014	Al-Ali et al.	2014/0364705	A1	12/2014	Parthasarathy et al.
2014/0077956	A1	3/2014	Sampath et al.	2014/0371548	A1	12/2014	Al-Ali et al.
2014/0081097	A1	3/2014	Al-Ali et al.	2014/0371632	A1	12/2014	Al-Ali et al.
2014/0081100	A1	3/2014	Muhsin et al.	2014/0378784	A1	12/2014	Kiani et al.
2014/0081175	A1	3/2014	Telfort	2015/0005600	A1	1/2015	Blank et al.
2014/0094667	A1	4/2014	Schurman et al.	2015/0011907	A1	1/2015	Purdon et al.
2014/0100434	A1	4/2014	Diab et al.	2015/0012231	A1	1/2015	Poeze et al.
2014/0114199	A1	4/2014	Lamego et al.	2015/0018650	A1	1/2015	Al-Ali et al.
2014/0120564	A1	5/2014	Workman et al.	2015/0025406	A1	1/2015	Al-Ali
2014/0121482	A1	5/2014	Merritt et al.	2015/0031970	A1	1/2015	Lain
2014/0121483	A1	5/2014	Kiani	2015/0032029	A1	1/2015	Al-Ali et al.
2014/0127137	A1	5/2014	Bellott et al.	2015/0038859	A1	2/2015	Dalvi et al.
2014/0128696	A1	5/2014	Al-Ali	2015/0045637	A1	2/2015	Dalvi
2014/0128699	A1	5/2014	Al-Ali et al.	2015/0051462	A1	2/2015	Olsen
2014/0129702	A1	5/2014	Lamego et al.	2015/0080754	A1	3/2015	Purdon et al.
2014/0135588	A1	5/2014	Al-Ali et al.	2015/0087936	A1	3/2015	Al-Ali et al.
2014/0135602	A1	5/2014	Lemke et al.	2015/0094546	A1	4/2015	Al-Ali
2014/0142399	A1	5/2014	Al-Ali et al.	2015/0094618	A1	4/2015	Russell et al.
2014/0142401	A1	5/2014	Al-Ali et al.	2015/0097701	A1	4/2015	Al-Ali et al.
2014/0142402	A1	5/2014	Al-Ali et al.	2015/0099950	A1	4/2015	Al-Ali et al.
2014/0152673	A1	6/2014	Lynn et al.	2015/0099951	A1	4/2015	Al-Ali et al.
2014/0155712	A1	6/2014	Lamego et al.	2015/0099955	A1	4/2015	Al-Ali et al.
2014/0163344	A1	6/2014	Al-Ali	2015/0101844	A1	4/2015	Al-Ali et al.
2014/0163402	A1	6/2014	Lamego et al.	2015/0106121	A1	4/2015	Muhsin et al.
2014/0166076	A1	6/2014	Kiani et al.	2015/0112151	A1	4/2015	Muhsin et al.
2014/0171763	A1	6/2014	Diab	2015/0116076	A1	4/2015	Al-Ali et al.
2014/0180038	A1	6/2014	Kiani	2015/0126830	A1	5/2015	Schurman et al.
2014/0180154	A1	6/2014	Sierra et al.	2015/0133755	A1	5/2015	Smith et al.
2014/0180160	A1	6/2014	Brown et al.	2015/0140863	A1	5/2015	Al-Ali et al.
2014/0187973	A1	7/2014	Brown et al.	2015/0141779	A1	5/2015	Johnson et al.
2014/0188516	A1	7/2014	Kamen	2015/0141780	A1	5/2015	Meyer et al.
				2015/0141781	A1	5/2015	Weber et al.
				2015/0165312	A1	6/2015	Kiani
				2015/0196237	A1	7/2015	Lamego
				2015/0201874	A1	7/2015	Diab

(56)

References Cited

U.S. PATENT DOCUMENTS

2015/0208966	A1	7/2015	Al-Ali
2015/0216459	A1	8/2015	Al-Ali et al.
2015/0230755	A1	8/2015	Al-Ali et al.
2015/0238094	A1	8/2015	Lai et al.
2015/0238722	A1	8/2015	Al-Ali
2015/0245773	A1	9/2015	Lamego et al.
2015/0245794	A1	9/2015	Al-Ali
2015/0257689	A1	9/2015	Al-Ali et al.
2015/0272514	A1	10/2015	Kiani et al.
2015/0289814	A1	10/2015	Magar et al.
2015/0351697	A1	12/2015	Weber et al.
2015/0351704	A1	12/2015	Kiani et al.
2015/0359429	A1	12/2015	Al-Ali et al.
2015/0366472	A1	12/2015	Kiani
2015/0366507	A1	12/2015	Blank
2015/0374298	A1	12/2015	Al-Ali et al.
2015/0374905	A1	12/2015	Yodfat et al.
2015/0380875	A1	12/2015	Coverston et al.
2016/0000362	A1	1/2016	Diab et al.
2016/0007930	A1	1/2016	Weber et al.
2016/0029932	A1	2/2016	Al-Ali
2016/0029933	A1	2/2016	Al-Ali et al.
2016/0045118	A1	2/2016	Kiani
2016/0051205	A1	2/2016	Al-Ali et al.
2016/0058338	A1	3/2016	Schurman et al.
2016/0058347	A1	3/2016	Reichgott et al.
2016/0066823	A1	3/2016	Al-Ali et al.
2016/0066824	A1	3/2016	Al-Ali et al.
2016/0066879	A1	3/2016	Telfort et al.
2016/0072429	A1	3/2016	Kiani et al.
2016/0073967	A1	3/2016	Lamego et al.
2016/0081552	A1	3/2016	Wojtczuk et al.
2016/0095543	A1	4/2016	Telfort et al.
2016/0095548	A1	4/2016	Al-Ali et al.
2016/0103598	A1	4/2016	Al-Ali et al.
2016/0106914	A1	4/2016	Yodfat et al.
2016/0113527	A1	4/2016	Al-Ali
2016/0143548	A1	5/2016	Al-Ali
2016/0166183	A1	6/2016	Poeze et al.
2016/0166188	A1	6/2016	Bruinsma et al.
2016/0166210	A1	6/2016	Al-Ali
2016/0166213	A1	6/2016	Isaacson
2016/0192869	A1	7/2016	Kiani et al.
2016/0196388	A1	7/2016	Lamego
2016/0197436	A1	7/2016	Barker et al.
2016/0213281	A1	7/2016	Eckerbom et al.
2016/0235344	A1	8/2016	Auerbach
2016/0262673	A1	9/2016	Skorich et al.
2016/0324486	A1	11/2016	Al-Ali et al.
2016/0327984	A1	11/2016	Al-Ali et al.
2016/0328528	A1	11/2016	Al-Ali et al.
2016/0359150	A1	12/2016	Martin et al.
2016/0367164	A1	12/2016	Felix

FOREIGN PATENT DOCUMENTS

EP	1408823	5/2010
EP	2 335 569	6/2011
EP	2 766 834	8/2014
EP	2 811 894	12/2014
JP	10-336064	12/1998
JP	2001-501847	2/2001
JP	2002-165764	6/2002
JP	2002-172096	6/2002
JP	2003-275183	9/2003
JP	2004-024551	1/2004
JP	2005-218036	8/2005
JP	2005-295375	10/2005
JP	2007-021213	2/2007
JP	2007-095365	4/2007
JP	2007-174051	7/2007
JP	2008-541045	11/2008
JP	2009-017959	1/2009
JP	2009-207836	9/2009
JP	2010-503134	1/2010

JP	2010-524510	7/2010
JP	2011-519607	7/2011
JP	2011-152261	8/2011
JP	2014-533997	12/2014
RU	2199723	2/2003
WO	WO 1996/016591	6/1996
WO	WO 1997/000708	1/1997
WO	WO 1998/015224	4/1998
WO	WO 98/029790	7/1998
WO	WO 1998/039749	9/1998
WO	WO 99/013766	3/1999
WO	WO 99/056613	11/1999
WO	WO 00/063713	10/2000
WO	WO 2000/062665	10/2000
WO	WO 2000/069328	11/2000
WO	WO 2001/041634	6/2001
WO	WO 2003/065926	8/2003
WO	WO 2004/056266	7/2004
WO	WO 2004/059551	7/2004
WO	WO 2005/048830	6/2005
WO	WO 2005/092177	10/2005
WO	WO 2006/051461	5/2006
WO	WO 2011/001302	1/2011
WO	WO 2011/002904	1/2011
WO	WO 2011/025549	3/2011
WO	WO 2013/056160	4/2013
WO	WO 2013/119982	8/2013
WO	WO 2015/054665	4/2015

OTHER PUBLICATIONS

Crilly et al., "An Integrated Pulse Oximeter System for Telemedicine Applications", IEEE Instrumentation and Measurement Technology Conference, Ottawa, Canada, May 19-21, 1997, in 3 pages.

"Medicine" Textbook of Anaesthesiology/Ed. By Aitkonhead A.R. et al., vol. 1, 1999, pp. 437-440.

Dissertation thesis for an MBA class given by the inventor on Dec. 18, 2004. "Reducing Health Care Costs and Improving Patient Care with the Uni-Ox Pulse Oximeter from Snap Medical Technologies", Robert Sweitzer and Samantha Goetz, in 7 pages.

European Search Report in EP Application No. 02 748 235.5, dated Oct. 4, 2006.

Official Communication in EP Application No. 02 748 235.5, dated Jul. 25, 2008.

International Search Report in PCT Application No. PCT/US02/03434, dated Dec. 19, 2002.

Capuano et al., "Remote Telemetry—New Twists for Old Technology", Nursing Management, Jul. 1995, vol. 26, No. 7, pp. 26-32.

Elmer-Dewitt, Philip, "Apple's iWatch: The killer apps may be in hospitals, not health clubs", Fortune.com, Feb. 3, 2014, <http://fortune.com/2014/02/03/apples-iwatch-the-killer-apps-may-be-in-hospitals-not-health-clubs/>, 4 pages.

Grundy et al., "Telemedicine in Critical Care: An Experiment in Health Care Delivery", JACEP, Oct. 1977, vol. 6, No. 10, pp. 439-444.

Grundy et al., "Telemedicine in Critical Care: Problems in Design, Implementation and Assessment", Jul. 1982, vol. 10, No. 7, pp. 471-475.

Rysavy, Peter, "Making the Call with Two-Way Paging", Network Computing, Published Jan. 15, 1997, www.rysavy.com/Articles/twoway.htm, pp. 5.

Wachter et al., "The Employment of an Iterative Design Process to Develop a Pulmonary Graphical Display", Journal of the American Medical Informatics Association, vol. 10, No. 4, Jul./Aug. 2003, pp. 363-372.

Official Communication in European Application No. 10195398.2 dated Jul. 5, 2012.

Official Communication in European Application No. 10195398.2 dated Jun. 15, 2015.

International Search Report & Written Opinion in PCT Application No. PCT/US2013/025384, dated Aug. 6, 2013.

International Search Report & Written Opinion in PCT Application No. PCT/US2012/060109, dated Jun. 5, 2013.

(56)

References Cited

OTHER PUBLICATIONS

International Preliminary Report on Patentability in PCT Application No. PCT/US2012/060109, dated Apr. 24, 2014.

International Search Report & Written Opinion in PCT Application No. PCT/US2014/060177, dated Dec. 19, 2014.

International Preliminary Report on Patentability & Written Opinion in PCT Application No. PCT/US2013/025384, dated Aug. 21, 2014.

International Preliminary Report on Patentability & Written Opinion in PCT Application No. PCT/US2014/060177, dated Apr. 21, 2016.

* cited by examiner




FIG. 1 (Prior Art)




FIG. 2 (Prior Art)




FIG. 3




FIG. 4A




FIG. 4B




FIG. 5A




FIG. 5B




FIG. 5C




FIG. 6




FIG. 7




FIG. 8




FIG. 9




FIG. 10




FIG. 11




FIG. 12




FIG. 13




FIG. 14

1

ARM MOUNTABLE PORTABLE PATIENT MONITOR

REFERENCE TO RELATED APPLICATION

The present application is a continuation of U.S. patent application Ser. No. 15/448,989, filed on Mar. 3, 2017, entitled "Physiological Measurement Communications Adapter," which is a continuation of U.S. patent application Ser. No. 14/815,232, filed on Jul. 31, 2015, entitled "Physiological Measurement Communications Adapter," which is a continuation of U.S. patent application Ser. No. 14/217,788, filed on Mar. 18, 2014, entitled "Wrist-Mounted Physiological Measurement Device," now U.S. Pat. No. 9,113,832, which is a continuation of U.S. patent application Ser. No. 14/037,137, filed on Sep. 25, 2013, entitled "Physiological Measurement Communications Adapter," now U.S. Pat. No. 9,113,831, which is a continuation of U.S. patent application Ser. No. 12/955,826, filed on Nov. 29, 2010, entitled "Physiological Measurement Communications Adapter," now U.S. Pat. No. 8,548,548, which is a continuation of U.S. patent application Ser. No. 11/417,006, filed on May 3, 2006, entitled "Physiological Measurement Communications Adapter," now U.S. Pat. No. 7,844,315, which claims priority benefit under 35 U.S.C. §120 to, and is a continuation of, U.S. patent application Ser. No. 11/048,330, filed Feb. 1, 2005, entitled "Physiological Measurement Communications Adapter," now U.S. Pat. No. 7,844,314, which is a continuation of U.S. patent application Ser. No. 10/377,933, entitled "Physiological Measurement Communications Adapter," now U.S. Pat. No. 6,850,788, which claims priority benefit under 35 U.S.C. §119(e) from U.S. Provisional Application No. 60/367,428, filed Mar. 25, 2002, entitled "Physiological Measurement Communications Adapter." The present application also incorporates the foregoing utility disclosures herein by reference.

BACKGROUND OF THE INVENTION

Patient vital sign monitoring may include measurements of blood oxygen, blood pressure, respiratory gas, and EKG among other parameters. Each of these physiological parameters typically requires a sensor in contact with a patient and a cable connecting the sensor to a monitoring device. For example, FIGS. 1-2 illustrate a conventional pulse oximetry system **100** used for the measurement of blood oxygen. As shown in FIG. 1, a pulse oximetry system has a sensor **110**, a patient cable **140** and a monitor **160**. The sensor **110** is typically attached to a finger **10** as shown. The sensor **110** has a plug **118** that inserts into a patient cable socket **142**. The monitor **160** has a socket **162** that accepts a patient cable plug **144**. The patient cable **140** transmits an LED drive signal **252** (FIG. 2) from the monitor **160** to the sensor **110** and a resulting detector signal **254** (FIG. 2) from the sensor **110** to the monitor **160**. The monitor **160** processes the detector signal **254** (FIG. 2) to provide, typically, a numerical readout of the patient's oxygen saturation, a numerical readout of pulse rate, and an audible indicator or "beep" that occurs in response to each arterial pulse.

As shown in FIG. 2, the sensor **110** has both red and infrared LED emitters **212** and a photodiode detector **214**. The monitor **160** has a sensor interface **271**, a signal processor **273**, a controller **275**, output drivers **276**, a display and audible indicator **278**, and a keypad **279**. The monitor **160** determines oxygen saturation by computing the differential absorption by arterial blood of the two wavelengths emitted by the sensor emitters **212**, as is well-known in the

2

art. The sensor interface **271** provides LED drive current **252** which alternately activates the red and IR LED emitters **212**. The photodiode detector **214** generates a signal **254** corresponding to the red and infrared light energy attenuated from transmission through the patient finger **10** (FIG. 1). The sensor interface **271** also has input circuitry for amplification, filtering and digitization of the detector signal **254**. The signal processor **273** calculates a ratio of detected red and infrared intensities, and an arterial oxygen saturation value is empirically determined based on that ratio. The controller **275** provides hardware and software interfaces for managing the display and audible indicator **278** and keypad **279**. The display and audible indicator **278** shows the computed oxygen status, as described above, and provides the pulse beep as well as alarms indicating oxygen desaturation events. The keypad **279** provides a user interface for setting alarm thresholds, alarm enablement, and display options, to name a few.

SUMMARY OF THE INVENTION

Conventional physiological measurement systems are limited by the patient cable connection between sensor and monitor. A patient must be located in the immediate vicinity of the monitor. Also, patient relocation requires either disconnection of monitoring equipment and a corresponding loss of measurements or an awkward simultaneous movement of patient equipment and cables. Various devices have been proposed or implemented to provide wireless communication links between sensors and monitors, freeing patients from the patient cable tether. These devices, however, are incapable of working with the large installed base of existing monitors and sensors, requiring caregivers and medical institutions to suffer expensive wireless upgrades. It is desirable, therefore, to provide a communications adapter that is plug-compatible both with existing sensors and monitors and that implements a wireless link replacement for the patient cable.

An aspect of a physiological measurement communications adapter comprises a sensor interface configured to receive a sensor signal. A transmitter modulates a first baseband signal responsive to the sensor signal so as to generate a transmit signal. A receiver demodulates a receive signal corresponding to the transmit signal so as to generate a second baseband signal corresponding to the first baseband signal. Further, a monitor interface is configured to communicate a waveform responsive to the second baseband signal to a sensor port of a monitor. The waveform is adapted to the monitor so that measurements derived by the monitor from the waveform are generally equivalent to measurements derivable from the sensor signal. The communications adapter may further comprise a signal processor having an input in communications with the sensor interface, where the signal processor is operable to derive a parameter responsive to the sensor signal and where the first baseband signal is responsive to the parameter. The parameter may correspond to at least one of a measured oxygen saturation and a pulse rate.

One embodiment may further comprise a waveform generator that synthesizes the waveform from a predetermined shape. The waveform generator synthesizes the waveform at a frequency adjusted to be generally equivalent to the pulse rate. The waveform may have a first amplitude and a second amplitude, and the waveform generator may be configured to adjusted the amplitudes so that measurements derived by the monitor are generally equivalent to a measured oxygen saturation.

In another embodiment, the sensor interface is operable on the sensor signal to provide a plethysmograph signal output, where the first baseband signal is responsive to the plethysmograph signal. This embodiment may further comprise a waveform modulator that modifies a decoded signal responsive to the second baseband signal to provide the waveform. The waveform modulator may comprise a demodulator that separates a first signal and a second signal from the decoded signal, an amplifier that adjusts amplitudes of the first and second signals to generate a first adjusted signal and a second adjusted signal, and a modulator that combines the first and second adjusted signals into the waveform. The amplitudes of the first and second signals may be responsive to predetermined calibration data for the sensor and the monitor.

An aspect of a physiological measurement communications adapter method comprises the steps of inputting a sensor signal at a patient location, communicating patient data derived from the sensor signal between the patient location and a monitor location, constructing a waveform at the monitor location responsive to the sensor signal, and providing the waveform to a monitor via a sensor port. The waveform is constructed so that the monitor calculates a parameter generally equivalent to a measurement derivable from the sensor signal.

In one embodiment, the communicating step may comprise the substeps of deriving a conditioned signal from the sensor signal, calculating a parameter signal from the conditioned signal, and transmitting the parameter signal from the patient location to the monitor location. The constructing step may comprise the substep of synthesizing the waveform from the parameter signal. In an alternative embodiment, the communicating step may comprise the substeps of deriving a conditioned signal from said sensor signal and transmitting the conditioned signal from the patient location to the monitor location. The constructing step may comprise the substeps of demodulating the conditioned signal and re-modulating the conditioned signal to generate the waveform. The providing step may comprise the substeps of inputting a monitor signal from an LED drive output of the sensor port, modulating the waveform in response to the monitor signal, and outputting the waveform on a detector input of the sensor port.

Another aspect of a physiological measurement communications adapter comprises a sensor interface means for inputting a sensor signal and outputting a conditioned signal, a transmitter means for sending data responsive to the sensor signal, and a receiver means for receiving the data. The communications adapter further comprises a waveform processor means for constructing a waveform from the data so that measurements derived by a monitor from the waveform are generally equivalent to measurements derivable from the sensor signal, and a monitor interface means for communicating the waveform to a sensor port of the monitor. The communications adapter may further comprise a signal processor means for deriving a parameter signal from the conditioned signal, where the data comprises the parameter signal. The waveform processor means may comprise a means for synthesizing the waveform from the parameter signal. The data may comprise the conditioned signal, and the waveform processor means may comprise a means for modulating the conditioned signal in response to the monitor.

BRIEF DESCRIPTION OF THE DRAWINGS

FIG. 1 is an illustration of a prior art pulse oximetry system;

FIG. 2 is a functional block diagram of a prior art pulse oximetry system;

FIG. 3 is an illustration of a physiological measurement communications adapter;

FIGS. 4A-B are illustrations of communications adapter sensor modules;

FIGS. 5A-C are illustrations of communications adapter monitor modules;

FIG. 6 is a functional block diagram of a communications adapter sensor module;

FIG. 7 is a functional block diagram of a communications adapter monitor module;

FIG. 8 is a functional block diagram of a sensor module configured to transmit measured pulse oximeter parameters;

FIG. 9 is a functional block diagram of a monitor module configured to receive measured pulse oximeter parameters;

FIG. 10 is a functional block diagram of a sensor module configured to transmit a plethysmograph;

FIG. 11 is a functional block diagram of a monitor module configured to receive a plethysmograph;

FIG. 12 is a functional block diagram of a waveform modulator;

FIG. 13 is a functional block diagram of a sensor module configured for multiple sensors; and

FIG. 14 is a functional block diagram of a monitor module configured for multiple sensors.

DETAILED DESCRIPTION OF THE PREFERRED EMBODIMENT

Overview

FIG. 3 illustrates one embodiment of a communications adapter. FIGS. 4-5 illustrate physical configurations for a communications adapter. In particular, FIGS. 4A-B illustrate sensor module configurations and FIGS. 5A-C illustrate monitor module configurations. FIGS. 6-14 illustrate communications adapter functions. In particular, FIGS. 6-7 illustrate general functions for a sensor module and a monitor module, respectively. FIGS. 8-9 functionally illustrate a communications adapter where derived pulse oximetry parameters, such as saturation and pulse rate are transmitted between a sensor module and a monitor module. Also, FIGS. 10-12 functionally illustrate a communications adapter where a plethysmograph is transmitted between a sensor module and a monitor module. FIGS. 13-14 functionally illustrate a multiple-parameter communications adapter.

FIG. 3 illustrates a communications adapter 300 having a sensor module 400 and a monitor module 500. The communications adapter 300 communicates patient data derived from a sensor 310 between the sensor module 400, which is located proximate a patient 20 and the monitor module 500, which is located proximate a monitor 360. A wireless link 340 is provided between the sensor module 400 and the monitor module 500, replacing the conventional patient cable, such as a pulse oximetry patient cable 140 (FIG. 1). Advantageously, the sensor module 400 is plug-compatible with a conventional sensor 310. In particular, the sensor connector 318 connects to the sensor module 400 in a similar manner as to a patient cable. Further, the sensor module 400 outputs a drive signal to the sensor 310 and inputs a sensor signal from the sensor 310 in an equivalent manner as a conventional monitor 360. The sensor module 400 may be battery powered or externally powered. External power may be for recharging internal batteries or for powering the sensor module during operation or both.

As shown in FIG. 3, the monitor module 500 is advantageously plug-compatible with a conventional monitor 360. In particular, the monitor's sensor port 362 connects to the monitor module 500 in a similar manner as to a patient cable, such as a pulse oximetry patient cable 140 (FIG. 1). Further, the monitor module 500 inputs a drive signal from the monitor 360 and outputs a corresponding sensor signal to the monitor 360 in an equivalent manner as a conventional sensor 310. As such, the combination sensor module 400 and monitor module 500 provide a plug-compatible wireless replacement for a patient cable, adapting an existing wired physiological measurement system into a wireless physiological measurement system. The monitor module 500 may be battery powered, powered from the monitor, such as by tapping current from a monitor's LED drive, or externally powered from an independent AC or DC power source.

Although a communications adapter 300 is described herein with respect to a pulse oximetry sensor and monitor, one of ordinary skill in the art will recognize that a communications adapter may provide a plug-compatible wireless replace for a patient cable that connects any physiological sensor and corresponding monitor. For example, a communications adapter 300 may be applied to a biopotential sensor, a non-invasive blood pressure (NIBP) sensor, a respiratory rate sensor, a glucose sensor and the corresponding monitors, to name a few.

Sensor Module Physical Configurations

FIGS. 4A-B illustrate physical embodiments of a sensor module 400. FIG. 4A illustrates a wrist-mounted module 410 having a wrist strap 411, a case 412 and an auxiliary cable 420. The case 412 contains the sensor module electronics, which are functionally described with respect to FIG. 6, below. The case 412 is mounted to the wrist strap 411, which attaches the wrist-mounted module 410 to a patient 20. The auxiliary cable 420 mates to a sensor connector 318 and a module connector 414, providing a wired link between a conventional sensor 310 and the wrist-mounted module 410. Alternatively, the auxiliary cable 420 is directly wired to the sensor module 400. The wrist-mounted module 410 may have a display 415 that shows sensor measurements, module status and other visual indicators, such as monitor status. The wrist-mounted module 410 may also have keys (not shown) or other input mechanisms to control its operational mode and characteristics. In an alternative embodiment, the sensor 310 may have a tail (not shown) that connects directly to the wrist-mounted module 410, eliminating the auxiliary cable 420.

FIG. 4B illustrates a clip-on module 460 having a clip 461, a case 462 and an auxiliary cable 470. The clip 461 attaches the clip-on module 460 to patient clothing or objects near a patient 20, such as a bed frame. The auxiliary cable 470 mates to the sensor connector 318 and functions as for the auxiliary cable 420 (FIG. 4A) of the wrist-mounted module 410 (FIG. 4A), described above. The clip-on module 460 may have a display 463 and keys 464 as for the wrist-mounted module 410 (FIG. 4A). Either the wrist-mounted module 410 or the clip-on module 460 may have other input or output ports (not shown) that download software, configure the module, or provide a wired connection to other measurement instruments or computing devices, to name a few examples.

Monitor Module Physical Configurations

FIGS. 5A-C illustrate physical embodiments of a monitor module 500. FIG. 5A illustrates a direct-connect module 510 having a case 512 and an integrated monitor connector 514. The case 512 contains the monitor module electronics, which are functionally described with respect to FIG. 7,

below. The monitor connector 514 mimics that of the monitor end of a patient cable, such as a pulse oximetry patient cable 140 (FIG. 1), and electrically and mechanically connects the monitor module 510 to the monitor 360 via the monitor's sensor port 362.

FIG. 5B illustrates a cable-connect module 540 having a case 542 and an auxiliary cable 550. The case 542 functions as for the direct-connect module 510 (FIG. 5A), described above. Instead of directly plugging into the monitor 360, the cable-connect module 540 utilizes the auxiliary cable 550, which mimics the monitor end of a patient cable, such as a pulse oximetry patient cable 140 (FIG. 1), and electrically connects the cable-connect module 540 to the monitor sensor port 362.

FIG. 5C illustrates a plug-in module 570 having a plug-in case 572 and an auxiliary cable 580. The plug-in case 572 is mechanically compatible with the plug-in chassis of a multiparameter monitor 370 and may or may not electrically connect to the chassis backplane. The auxiliary cable 580 mimics a patient cable and electrically connects the plug-in module 570 to the sensor port 372 of another plug-in device. A direct-connect module 510 (FIG. 5A) or a cable-connect module 540 (FIG. 5B) may also be used with a multiparameter monitor 370.

In a multiparameter embodiment, such as described with respect to FIGS. 13-14, below, a monitor module 500 may connect to multiple plug-in devices of a multiparameter monitor 370. For example, a cable-connect module 540 (FIG. 5B) may have multiple auxiliary cables 550 (FIG. 5B) that connect to multiple plug-in devices installed within a multiparameter monitor chassis. Similarly, a plug-in module 570 may have one or more auxiliary cables 580 with multiple connectors for attaching to the sensor ports 372 of multiple plug-in devices.

Communications Adapter Functions

FIGS. 6-7 illustrate functional embodiments of a communications adapter. FIG. 6 illustrates a sensor module 400 having a sensor interface 610, a signal processor 630, an encoder 640, a transmitter 650 and a transmitting antenna 670. A physiological sensor 310 provides an input sensor signal 612 at the sensor connector 318. Depending on the sensor 310, the sensor module 400 may provide one or more drive signals 618 to the sensor 310. The sensor interface 610 inputs the sensor signal 612 and outputs a conditioned signal 614. The conditioned signal 614 may be coupled to the transmitter 650 or further processed by a signal processor 630. If the sensor module configuration utilizes a signal processor 630, it derives a parameter signal 632 responsive to the sensor signal 612, which is then coupled to the transmitter 650. Regardless, the transmitter 650 inputs a baseband signal 642 that is responsive to the sensor signal 612. The transmitter 650 modulates the baseband signal 642 with a carrier to generate a transmit signal 654. The transmit signal 654 may be derived by various amplitude, frequency or phase modulation schemes, as is well known in the art. The transmit signal 654 is coupled to the transmit antenna 670, which provides wireless communications to a corresponding receive antenna 770 (FIG. 7), as described below.

As shown in FIG. 6, the sensor interface 610 conditions and digitizes the sensor signal 612 to generate the conditioned signal 614. Sensor signal conditioning may be performed in the analog domain or digital domain or both and may include amplification and filtering in the analog domain and filtering, buffering and data rate modification in the digital domain, to name a few. The resulting conditioned signal 614 is responsive to the sensor signal 612 and may be used to calculate or derive a parameter signal 632.

Further shown in FIG. 6, the signal processor 630 performs signal processing on the conditioned signal 614 to generate the parameter signal 632. The signal processing may include buffering, digital filtering, smoothing, averaging, adaptive filtering and frequency transforms to name a few. The resulting parameter signal 632 may be a measurement calculated or derived from the conditioned signal, such as oxygen saturation, pulse rate, blood glucose, blood pressure and EKG to name a few. Also, the parameter signal 632 may be an intermediate result from which the above-stated measurements may be calculated or derived.

As described above, the sensor interface 610 performs mixed analog and digital pre-processing of an analog sensor signal and provides a digital output signal to the signal processor 630. The signal processor 630 then performs digital post-processing of the front-end processor output. In alternative embodiments, the input sensor signal 612 and the output conditioned signal 614 may be either analog or digital, the front-end processing may be purely analog or purely digital, and the back-end processing may be purely analog or mixed analog or digital.

In addition, FIG. 6 shows an encoder 640, which translates a digital word or serial bit stream, for example, into the baseband signal 642, as is well-known in the art. The baseband signal 642 comprises the symbol stream that drives the transmit signal 654 modulation, and may be a single signal or multiple related signal components, such as in-phase and quadrature signals. The encoder 640 may include data compression and redundancy, also well-known in the art.

FIG. 7 illustrates a monitor module 500 having a receive antenna 770, a receiver 710, a decoder 720, a waveform processor 730 and a monitor interface 750. A receive signal 712 is coupled from the receive antenna 770, which provides wireless communications to a corresponding transmit antenna 670 (FIG. 6), as described above. The receiver 710 inputs the receive signal 712, which corresponds to the transmit signal 654 (FIG. 6). The receiver 710 demodulates the receive signal to generate a baseband signal 714. The decoder 720 translates the symbols of the demodulated baseband signal 714 into a decoded signal 724, such as a digital word stream or bit stream. The waveform processor 730 inputs the decoded signal 724 and generates a constructed signal 732. The monitor interface 750 is configured to communicate the constructed signal 732 to a sensor port 362 of a monitor 360. The monitor 360 may output a sensor drive signal 754, which the monitor interface 750 inputs to the waveform processor 730 as a monitor drive signal 734. The waveform processor 730 may utilize the monitor drive signal 734 to generate the constructed signal 732. The monitor interface 750 may also provide characterization information 758 to the waveform processor 730, relating to the monitor 360, the sensor 310 or both, that the waveform processor 730 utilizes to generate the constructed signal 732.

The constructed signal 732 is adapted to the monitor 360 so that measurements derived by the monitor 360 from the constructed signal 732 are generally equivalent to measurements derivable from the sensor signal 612 (FIG. 6). Note that the sensor 310 (FIG. 6) may or may not be directly compatible with the monitor 360. If the sensor 310 (FIG. 6) is compatible with the monitor 360, the constructed signal 732 is generated so that measurements derived by the monitor 360 from the constructed signal 732 are generally equivalent (within clinical significance) with those derivable directly from the sensor signal 612 (FIG. 6). If the sensor 310 (FIG. 6) is not compatible with the monitor 360, the constructed signal 732 is generated so that measurements

derived by the monitor 360 from the constructed signal 732 are generally equivalent to those derivable directly from the sensor signal 612 (FIG. 6) using a compatible monitor.

Wireless Pulse Oximetry

FIGS. 8-11 illustrate pulse oximeter embodiments of a communications adapter. FIGS. 8-9 illustrate a sensor module and a monitor module, respectively, configured to communicate measured pulse oximeter parameters. FIG. 10-11 illustrate a sensor module and a monitor module, respectively, configured to communicate a plethysmograph signal. Parameter Transmission

FIG. 8 illustrates a pulse oximetry sensor module 800 having a sensor interface 810, signal processor 830, encoder 840, transmitter 850, transmitting antenna 870 and controller 890. The sensor interface 810, signal processor 830 and controller 890 function as described with respect to FIG. 2, above. The sensor interface 810 communicates with a standard pulse oximetry sensor 310, providing an LED drive signal 818 to the LED emitters 312 and receiving a sensor signal 812 from the detector 314 in response. The sensor interface 810 provides front-end processing of the sensor signal 812, also described above, providing a plethysmograph signal 814 to the signal processor 830. The signal processor 830 then derives a parameter signal 832 that comprises a real time measurement of oxygen saturation and pulse rate. The parameter signal 832 may include other parameters, such as measurements of perfusion index and signal quality. In one embodiment, the signal processor is an MS-5 or MS-7 board available from Masimo Corporation, Irvine, Calif.

As shown in FIG. 8, the encoder 840, the transmitter 850 and the transmitting antenna 870 function as described with respect to FIG. 6, above. For example, the parameter signal 832 may be a digital word stream that is serialized into a bit stream and encoded into a baseband signal 842. The baseband signal 842 may be, for example, two bit symbols that drive a quadrature phase shift keyed (QPSK) modulator in the transmitter 850. Other encodings and modulations are also applicable, as described above. The transmitter 850 inputs the baseband signal 842 and generates a transmit signal 854 that is a modulated carrier having a frequency suitable for short-range transmission, such as within a hospital room, doctor's office, emergency vehicle or critical care ward, to name a few. The transmit signal 854 is coupled to the transmit antenna 870, which provides wireless communications to a corresponding receive antenna 970 (FIG. 9), as described below.

FIG. 9 illustrates a monitor module 900 having a receive antenna 970, a receiver 910, a decoder 920, a waveform generator 930 and an interface cable 950. The receive antenna 970, receiver 910 and decoder 920 function as described with respect to FIG. 7, above. In particular, the receive signal 912 is coupled from the receive antenna 970, which provides wireless communications to a corresponding transmit antenna 870 (FIG. 8). The receiver 910 inputs the receive signal 912, which corresponds to the transmit signal 854 (FIG. 8). The receiver 910 demodulates the receive signal 912 to generate a baseband signal 914. Not accounting for transmission errors, the baseband signal 914 corresponds to the sensor module baseband signal 842 (FIG. 8), for example a symbol stream of two bits each. The decoder 920 assembles the baseband signal 914 into a parameter signal 924, which, for example, may be a sequence of digital words corresponding to oxygen saturation and pulse rate. Again, not accounting for transmission errors, the monitor

module parameter signal **924** corresponds to the sensor module parameter signal **832** (FIG. 8), derived by the signal processor **830** (FIG. 8).

Also shown in FIG. 9, the waveform generator **930** is a particular embodiment of the waveform processor **730** (FIG. 7) described above. The waveform generator **930** generates a synthesized waveform **932** that the pulse oximeter monitor **360** can process to calculate SpO_2 and pulse rate values or exception messages. In the present embodiment, the waveform generator output does not reflect a physiological waveform. In particular, the synthesized waveform is not physiological data from the sensor module **800**, but is a waveform synthesized from predetermined stored waveform data to cause the monitor **360** to calculate oxygen saturation and pulse rate equivalent to or generally equivalent (within clinical significance) to that calculated by the signal processor **830** (FIG. 8). The actual intensity signal from the patient received by the detector **314** (FIG. 8) is not provided to the monitor **360** in the present embodiment. Indeed, the waveform provided to the monitor **360** will usually not resemble a plethysmographic waveform or other physiological data from the patient to whom the sensor module **800** (FIG. 8) is attached.

The synthesized waveform **932** is modulated according to the drive signal input **934**. That is, the pulse oximeter monitor **360** expects to receive a red and IR modulated intensity signal originating from a detector, as described with respect to FIGS. 1-2, above. The waveform generator **930** generates the synthesized waveform **932** with a predetermined shape, such as a triangular or sawtooth waveform stored in waveform generator memory or derived by a waveform generator algorithm. The waveform is modulated synchronously with the drive input **934** with first and second amplitudes that are processed in the monitor **360** as red and IR portions of a sensor signal. The frequency and the first and second amplitudes are adjusted so that pulse rate and oxygen saturation measurements derived by the pulse oximeter monitor **360** are generally equivalent to the parameter measurements derived by the signal processor **830** (FIG. 8), as described above. One embodiment of a waveform generator **930** is described in U.S. Patent Application No. 60/117,097 entitled "Universal/Upgrading Pulse Oximeter," assigned to Masimo Corporation, Irvine, Calif. and incorporated by reference herein. Although the waveform generator **930** is described above as synthesizing a waveform that does not resemble a physiological signal, one of ordinary skill will recognize that another embodiment of the waveform generator **930** could incorporate, for example, a plethysmograph simulator or other physiological signal simulator.

Further shown in FIG. 9, the interface cable **950** functions in a manner similar to the monitor interface **750** (FIG. 7) described above. The interface cable **950** is configured to communicate the synthesized waveform **932** to the monitor **360** sensor port and to communicate the sensor drive signal **934** to the waveform generator **930**. The interface cable **950** may include a ROM **960** that contains monitor and sensor characterization data. The ROM **960** is read by the waveform generator **930** so that the synthesized waveform **932** is adapted to a particular monitor **360**. For example, the ROM **960** may contain calibration data of red/IR versus oxygen saturation, waveform amplitude and waveform shape information. An interface cable is described in U.S. Patent Application No. 60/117,092, referenced above. Monitor-specific SatShare™ brand interface cables are available from Masimo Corporation, Irvine, Calif. In an alternative embodiment, such as a direct connect monitor module as

illustrated in FIG. 5A, an interface cable **950** is not used and the ROM **960** may be incorporated within the monitor module **900** itself.

Plethysmograph Transmission

FIG. 10 illustrates another pulse oximetry sensor module **1000** having a sensor interface **1010**, encoder **1040**, transmitter **1050**, transmitting antenna **1070** and controller **1090**, which have the corresponding functions as those described with respect to FIG. 8, above. The encoder **1040**, however, inputs a plethysmograph signal **1014** rather than oxygen saturation and pulse rate measurements **832** (FIG. 8). Thus, the sensor module **1000** according to this embodiment encodes and transmits a plethysmograph signal **1014** to a corresponding monitor module **1100** (FIG. 11) in contrast to derived physiological parameters, such as oxygen saturation and pulse rate. The plethysmograph signal **1014** is illustrated in FIG. 10 as being a direct output from the sensor interface **1010**. In another embodiment, the sensor module **1000** incorporates a decimation processor, not shown, after the sensor interface **1010** so as to provide a plethysmograph signal **1014** having a reduced sample rate.

FIG. 11 illustrates another pulse oximetry monitor module **1100** having a receive antenna **1170**, a receiver **1110**, a decoder **1120** and an interface cable **1150**, which have the corresponding functions as those described with respect to FIG. 9, above. This monitor module embodiment **1100**, however, has a waveform modulator **1200** rather than a waveform generator **930** (FIG. 9), as described above. The waveform modulator **1200** inputs a plethysmograph signal from the decoder **1120** rather than oxygen saturation and pulse rate measurements, as described with respect to FIG. 9, above. Further, the waveform modulator **1200** provides an modulated waveform **1132** to the pulse oximeter monitor **360** rather than a synthesized waveform, as described with respect to FIG. 9. The modulated waveform **1132** is a plethysmographic waveform modulated according to the monitor drive signal input **1134**. That is, the waveform modulator **1200** does not synthesize a waveform, but rather modifies the received plethysmograph signal **1124** to cause the monitor **360** to calculate oxygen saturation and pulse rate generally equivalent (within clinical significance) to that derivable by a compatible, calibrated pulse oximeter directly from the sensor signal **1012** (FIG. 10). The waveform modulator **1200** is described in further detail with respect to FIG. 12, below.

FIG. 12 shows a waveform modulator **1200** having a demodulator **1210**, a red digital-to-analog converter (DAC) **1220**, an IR DAC **1230**, a red amplifier **1240**, an IR amplifier **1250**, a modulator **1260**, a modulator control **1270**, a look-up table (LUT) **1280** and a ratio calculator **1290**. The waveform modulator **1200** demodulates red and IR plethysmographs ("pleths") from the decoder output **1124** into a separate red pleth **1222** and IR pleth **1232**. The waveform modulator **1200** also adjusts the amplitudes of the pleths **1222**, **1232** according to stored calibration curves for the sensor **310** (FIG. 10) and the monitor **360** (FIG. 11). Further, the waveform modulator **1200** re-modulates the adjusted red pleth **1242** and adjusted IR pleth **1252**, generating a modulated waveform **1132** to the monitor **360** (FIG. 11).

As shown in FIG. 12, the demodulator **1210** performs the demodulation function described above, generating digital red and IR pleth signals **1212**, **1214**. The DACs **1220**, **1230** convert the digital pleth signals **1212**, **1214** to corresponding analog pleth signals **1222**, **1232**. The amplifiers **1240**, **1250** have variable gain control inputs **1262**, **1264** and perform the amplitude adjustment function described above, generating adjusted red and IR pleth signals **1242**, **1252**. The

modulator 1260 performs the re-modulation function described above, combining the adjusted red and IR pleth signals 1242, 1252 according to a control signal 1272. The modulator control 1270 generates the control signal 1272 synchronously with the LED drive signal(s) 1134 from the monitor 360.

Also shown in FIG. 12, the ratio calculator 1290 derives a red/IR ratio from the demodulator outputs 1212, 1214. The LUT 1280 stores empirical calibration data for the sensor 310 (FIG. 10). The LUT 1280 also downloads monitor-specific calibration data from the ROM 1160 (FIG. 11) via the ROM output 1158. From this calibration data, the LUT 1280 determines a desired red/IR ratio for the modulated waveform 1132 and generates red and IR gain outputs 1262, 1264 to the corresponding amplifiers 1240, 1250, accordingly. A desired red/IR ratio is one that allows the monitor 360 (FIG. 11) to derive oxygen saturation measurements from the modulated waveform 1132 that are generally equivalent to that derivable directly from the sensor signal 1012 (FIG. 10).

One of ordinary skill in the art will recognize that some of the signal processing functions described with respect to FIGS. 8-11 may be performed either within a sensor module or within a monitor module. Signal processing functions performed within a sensor module may advantageously reduce the transmission bandwidth to a monitor module at a cost of increased sensor module size and power consumption. Likewise, signal processing functions performed within a monitor module may reduce sensor module size and power consumption at a cost of increase transmission bandwidth.

For example, a monitor module embodiment 900 (FIG. 9) described above receives measured pulse oximeter parameters, such as oxygen saturation and pulse rate, and generates a corresponding synthesized waveform. In that embodiment, the oxygen saturation and pulse rate computations are performed within a sensor module 800 (FIG. 8). Another monitor module embodiment 1100 (FIG. 11), also described above, receives a plethysmograph waveform and generates a remodulated waveform. In that embodiment, minimal signal processing is performed within a sensor module 1000 (FIG. 10). In yet another embodiment, not shown, a sensor module transmits a plethysmograph waveform or a decimated plethysmograph waveform having a reduced sample rate. A corresponding monitor module has a signal processor, such as described with respect to FIG. 8, in addition to a waveform generator, as described with respect to FIG. 9. The signal processor computes pulse oximeter parameters and the waveform generator generates a corresponding synthesized waveform, as described above. In this embodiment, minimal signal processing is performed within the sensor module, and the monitor module functions are performed on the pulse oximeter parameters computed within the monitor module.

Wireless Multiple Parameter Measurements

FIGS. 13-14 illustrate a multiple parameter communications adapter. FIG. 13 illustrates a multiple parameter sensor module 1300 having sensor interfaces 1310, one or more signal processors 1330, a multiplexer and encoder 1340, a transmitter 1350, a transmitting antenna 1370 and a controller 1390. One or more physiological sensors 1301 provide input sensor signals 1312 to the sensor module 1300. Depending on the particular sensors 1301, the sensor module 1300 may provide one or more drive signals 1312 to the sensors 1301 as determined by the controller 1390. The sensor interfaces 1310 input the sensor signals 1312 and output one or more conditioned signals 1314. The condi-

tioned signals 1314 may be coupled to the transmitter 1350 or further processed by the signal processors 1330. If the sensor module configuration utilizes signal processors 1330, it derives multiple parameter signals 1332 responsive to the sensor signals 1312, which are then coupled to the transmitter 1350. Regardless, the transmitter 1350 inputs a baseband signal 1342 that is responsive to the sensor signals 1312. The transmitter 1350 modulates the baseband signal 1342 with a carrier to generate a transmit signal 1354, which is coupled to the transmit antenna 1370 and communicated to a corresponding receive antenna 1470 (FIG. 14), as described with respect to FIG. 6, above. Alternatively, there may be multiple baseband signals 1342, and the transmitter 1350 may transmit on multiple frequency channels, where each channel conveys data responsive to one or more of the sensor signals 1314.

As shown in FIG. 13, the sensor interface 1310 conditions and digitizes the sensor signals 1312 as described for a single sensor with respect to FIG. 6, above. The resulting conditioned signals 1314 are responsive to the sensor signals 1312. The signal processors 1330 perform signal processing on the conditioned signals 1314 to derive parameter signals 1332, as described for a single conditioned signal with respect to FIG. 6, above. The parameter signals 1332 may be physiological measurements such as oxygen saturation, pulse rate, blood glucose, blood pressure, EKG, respiration rate and body temperature to name a few, or may be intermediate results from which the above-stated measurements may be calculated or derived. The multiplexer and encoder 1340 combines multiple digital word or serial bit streams into a single digital word or bit stream. The multiplexer and encoder also encodes the digital word or bit stream to generate the baseband signal 1342, as described with respect to FIG. 6, above.

FIG. 14 illustrates a multiple parameter monitor module 1400 having a receive antenna 1470, a receiver 1410, a demultiplexer and decoder 1420, one or more waveform processors 1430 and a monitor interface 1450. The receiver 1410 inputs and demodulates the receive signal 1412 corresponding to the transmit signal 1354 (FIG. 13) to generate a baseband signal 1414 as described with respect to FIG. 7, above. The demultiplexer and decoder 1420 separates the symbol streams corresponding to the multiple conditioned signals 1314 (FIG. 13) and/or parameter signals 1332 (FIG. 13) and translates these symbol streams into multiple decoded signals 1422, as described for a single symbol stream with respect to FIG. 7, above. Alternatively, multiple frequency channels are received to generate multiple baseband signals, each of which are decoded to yield multiple decoded signals 1422. The waveform processors 1430 input the decoded signals 1422 and generate multiple constructed signals 1432, as described for a single decoded signal with respect to FIGS. 7-12, above. The monitor interface 1450 is configured to communicate the constructed signals 1432 to the sensor ports of a multiple parameter monitor 1401 or multiple single parameter monitors, in a manner similar to that for a single constructed signal, as described with respect to FIGS. 7-12, above. In particular, the constructed signals 1432 are adapted to the monitor 1401 so that measurements derived by the monitor 1401 from the constructed signals 1432 are generally equivalent to measurements derivable directly from the sensor signals 1312 (FIG. 13).

A physiological measurement communications adapter is described above with respect to wireless communications and, in particular, radio frequency communications. A sensor module and monitor module, however, may also communicate via wired communications, such as telephone, Internet

13

or fiberoptic cable to name a few. Further, wireless communications can also utilize light frequencies, such as IR or laser to name a few.

A physiological measurement communications adapter has been disclosed in detail in connection with various embodiments. These embodiments are disclosed by way of examples only. One of ordinary skill in the art will appreciate many variations and modifications of a physiological measurement communications adapter within the scope of the claims that follow.

What is claimed is:

1. An arm mountable portable patient monitoring device configured for both on-patient monitoring of parameter measurements using one or more sensors operatively connected to the portable patient monitoring device and wireless transmission of parameter measurements, the portable patient monitoring device comprising:

a pulse oximetry sensor configured to be wrapped around a digit of a patient, the pulse oximetry sensor including at least:

a light emitter configured to emit light into a tissue site of the digit of the patient;

a light detector configured output a signal responsive to at least a portion of the emitted light after attenuation by tissue of the tissue site; and

a tail configured to electrically convey the signal;

a housing configured for, and having a size and shape configured for, mounting to a lower arm of the patient, the housing including at least:

a display positioned on a front side of the housing that is opposite a back side of the housing, the display configured to show a status of the portable patient monitoring device and one or more parameter measurements so as to be viewable by a user;

a first sensor port positioned on a first side of the housing, the first side of the housing configured to face toward a hand having the digit of the patient under measurement, the first sensor port configured to physically couple to the tail of the pulse oximetry sensor and to electrically receive the signal from the pulse oximetry sensor, wherein the first sensor port is positioned on the first side of the housing such that, when the tail is physically coupled to the first sensor port, the tail extends from the first sensor port along an axis perpendicular to a face of the first side of the housing on which the first sensor port is positioned;

a second sensor port configured to receive information from an EKG sensor arrangement via a wired connection;

a third sensor port configured to receive information from a blood pressure sensor arrangement via a wired connection;

a rechargeable battery configured to power the portable patient monitoring device including the pulse oximetry sensor;

one or more signal processing arrangements configured to:

receive the signal from the pulse oximetry sensor; derive, based on the signal, measurements of oxygen saturation and pulse rate; and

cause to be displayed, on the display, the measurements of oxygen saturation and pulse rate; and

a transmitter configured to: wirelessly transmit a transmit signal indicative of the measurements of oxygen saturation and pulse rate

14

to a separate computing device configured to display the measurements of oxygen saturation and pulse rate; and

a strap mountable to the back side of the housing, the strap configured to secure the housing to the lower arm of the patient.

2. The portable patient monitoring device of claim 1, wherein the tail comprises a cable extending from the pulse oximetry sensor to the first sensor port of the housing.

3. The portable patient monitoring device of claim 2, wherein the cable is removably coupled to the first sensor port of the housing, and wherein the digit of the patient is a thumb of the patient.

4. The portable patient monitoring device of claim 1, wherein the one or more signal processing arrangements comprise at least:

a sensor interface configured to:

receive the signal from the pulse oximetry sensor; and process the signal to generate a conditioned signal by at least one of:

amplification, filtering, analog to digital conversion, buffering, data rate modification, digital filtering, adaptive filtering, smoothing, averaging, or frequency transforming; and

a signal processor configured to:

receive the conditioned signal from the sensor interface;

derive, from the conditioned signal, the measurements of oxygen saturation and pulse rate; and

provide information indicative of the measurements of oxygen saturation and pulse rate to the transmitter.

5. The portable patient monitoring device of claim 4, wherein the sensor interface is further configured to: provide the conditioned signal to the transmitter.

6. The portable patient monitoring device of claim 1 further comprising:

an EKG sensor arrangement in electrical communication with the second sensor port of the housing;

wherein the one or more signal processing arrangements are further configured to:

receive the information from the EKG sensor arrangement at least in part via digital communication;

determine, from the information from the EKG sensor arrangement, an EKG measurement; and

cause to be displayed, on the display, the EKG measurement;

wherein the housing further includes a data combining arrangement configured to:

combine at least information indicative of the measurements of oxygen saturation, pulse rate, and EKG; and

wherein the transmitter is further configured to:

wirelessly transmit the transmit signal indicative of the measurements of oxygen saturation, pulse rate, and EKG to the separate computing device configured to display the measurements of oxygen saturation, pulse rate, and EKG.

7. The portable patient monitoring device of claim 6 further comprising:

a blood pressure sensor arrangement in electrical communication with the third sensor port of the housing;

wherein the one or more signal processing arrangements are further configured to:

receive the information from the blood pressure sensor arrangement at least in part via digital communication;

15

determine, from the information from the blood pressure sensor arrangement, a measurement of blood pressure; and
 cause to be displayed, on the display, the measurement of blood pressure;
 wherein the data combining arrangement is further configured to:
 combine at least information indicative of the measurements of oxygen saturation, pulse rate, EKG, and blood pressure; and
 wherein the transmitter is further configured to:
 wirelessly transmit the transmit signal indicative of the measurements of oxygen saturation, pulse rate, EKG, and blood pressure to the separate computing device configured to display the measurements of oxygen saturation, pulse rate, EKG, and blood pressure.
 8. The portable patient monitoring device of claim 7, wherein the one or more signal processing arrangements are further configured to:
 cause the measurements of oxygen saturation, pulse rate, EKG, and blood pressure to all be displayed on the display of the portable patient monitoring device.
 9. The portable patient monitoring device of claim 7, wherein:
 the one or more signal processing arrangements are further configured to:
 receive the additional signals indicative of additional physiological parameters including at least one of: respiration rate or body temperature;
 determine, from the additional signals, measurements of the additional physiological parameters; and
 cause to be displayed, on the display, the measurements of the additional physiological parameters;
 wherein the data combining arrangement is further configured to:
 combine at least information indicative of the measurements of oxygen saturation, pulse rate, EKG, blood pressure and the additional physiological parameters; and
 wherein the transmitter is further configured to:
 wirelessly transmit the transmit signal indicative of the measurements of oxygen saturation, pulse rate, EKG, blood pressure, and additional physiological parameters to the separate computing device configured to display the measurements of oxygen saturation, pulse rate, EKG, blood pressure, and additional physiological parameters.
 10. The portable patient monitoring device of claim 9, wherein the one or more signal processing arrangements are further configured to:
 cause the measurements of oxygen saturation, pulse rate, EKG, blood pressure, and additional physiological parameters to all be displayed on the display of the portable patient monitoring device.
 11. The portable patient monitoring device of claim 10, wherein the data combining arrangement is at least one of a multiplexer or an encoder.
 12. The portable patient monitoring device of claim 1, wherein the measurements of oxygen saturation and pulse rate comprise real time measurements of oxygen saturation and pulse rate.
 13. The portable patient monitoring device of claim 1, wherein the one or more signal processing arrangements are further configured to determine, based on the signal, a measurement of signal quality.
 14. The portable patient monitoring device of claim 1, wherein the housing further includes at least one or more

16

user input mechanisms configured to control an operational mode of the portable patient monitoring device in response to inputs from a user.

15. The portable patient monitoring device of claim 1, wherein the transmit signal indicative of the measurements of oxygen saturation and pulse rate comprises the derived measurements of oxygen saturation and pulse rate.

16. The portable patient monitoring device of claim 15, wherein the transmit signal indicative of the measurements of oxygen saturation and pulse rate further comprises raw data indicative of the signal from the pulse oximetry sensor.

17. An arm mountable portable patient monitoring device configured for both on-patient monitoring of parameter measurements using one or more sensors operatively connected to the portable patient monitoring device and wireless transmission of parameter measurements, the portable patient monitoring device comprising:

a pulse oximetry sensor configured to be wrapped around a digit of a patient, the pulse oximetry sensor including at least:

a light emitter configured to emit light into a tissue site of the digit of the patient; and

a light detector configured output a signal responsive to at least a portion of the emitted light after attenuation by tissue of the tissue site;

a housing configured to be mounted to an arm of the patient, the housing including at least:

a display positioned on a front side of the housing that is opposite a back side of the housing, the display configured to show a status of the portable patient monitoring device and one or more parameter measurements so as to be viewable by a user;

a first sensor port positioned on a first side of the housing, the first side of the housing having a face that is configured to face toward a hand having the digit of the patient under measurement, the first sensor port configured to electrically receive the signal from the pulse oximetry sensor via a wire extending from the pulse oximetry sensor to the first sensor port, wherein the wire extends from the first sensor port perpendicularly to the face of the first side of the housing;

second and third sensor ports configured to receive signals from two or more additional sensor arrangements via wired communications;

a rechargeable battery configured to power the portable patient monitoring device including the pulse oximetry sensor;

one or more signal processing arrangements configured to:

receive the signal from the pulse oximetry sensor; and

cause to be displayed, on the display, measurements of oxygen saturation and pulse rate derived from the received signal; and

a transmitter configured to:

wirelessly transmit a transmit signal indicative of the measurements of oxygen saturation and pulse rate to a separate computing device configured to display the measurements of oxygen saturation and pulse rate; and

a strap mountable to the back side of the housing, the strap configured to secure the housing to the arm of the patient.

18. The portable patient monitoring device of claim 17 further comprising:

17

a second physiological sensor arrangement in electrical communication with the second sensor port of the housing, the second physiological sensor arrangement comprising at least one of: a blood pressure sensor arrangement, an EKG sensor arrangement, a respiration rate sensor arrangement, or a body temperature sensor arrangement;
 wherein the one or more signal processing arrangements are further configured to:
 receive information from the second physiological sensor arrangement indicative of a physiological parameter of the patient, wherein the information from the second physiological sensor arrangement is at least partly digital; and
 cause to be displayed, on the display one or more additional parameter measurements, based on the information from the second physiological sensor arrangement, including measurements of at least one of: blood pressure, EKG, respiration rate, or body temperature;
 wherein the transmitter is further configured to wirelessly transmit the transmit signal indicative of the measurements of oxygen saturation and pulse rate, and the one or more additional parameter measurements, to the separate computing device configured to display the measurements of oxygen saturation and pulse rate, and the one or more additional parameter measurements.

19. The portable patient monitoring device of claim **18** further comprising:

a third physiological sensor arrangement, different from the second physiological sensor arrangement, in electrical communication with the third sensor port of the housing, the third physiological sensor arrangement comprising at least one of: a blood pressure sensor arrangement, an EKG sensor arrangement, a respiration rate sensor arrangement, or a body temperature sensor arrangement;
 wherein the one or more signal processing arrangements are further configured to:
 receive information from the third physiological sensor arrangement indicative of a physiological parameter of the patient; and
 cause to be displayed, on the display, the second one or more additional parameter measurements, based on information from the third physiological sensor arrangement, including measurements of at least one of: blood pressure, EKG, respiration rate, or body temperature;
 wherein the transmitter is further configured to wirelessly transmit the transmit signal indicative of the measurements of oxygen saturation and pulse rate, the one or more additional parameter measurements, and the second one or more additional parameter measurements, to the separate computing device configured to display the measurements of oxygen saturation and pulse rate, the one or more additional parameter measurements, and the second one or more additional parameter measurements.

20. An arm mountable portable patient monitoring device configured for both on-patient monitoring of parameter measurements using one or more sensors operatively connected to the portable patient monitoring device and wireless transmission of parameter measurements, the portable patient monitoring device comprising:

a pulse oximetry sensor configured to be wrapped around a digit of a patient, the pulse oximetry sensor including at least:

18

a light emitter configured to emit light into a tissue site of the digit of the patient;
 a light detector configured output a first signal responsive to at least a portion of the emitted light after attenuation by tissue of the tissue site; and
 a cable extending from the pulse oximetry sensor and configured to electrically convey the first signal;
 a blood pressure sensor configured to output a second signal responsive to at least a blood pressure parameter of the patient;
 an additional sensor arrangement configured to output a third signal responsive to at least one additional physiological parameter of a patient other than blood pressure or oxygen saturation, the at least one additional physiological parameter including at least one of: temperature or respiration rate;
 a housing configured to be secured to a lower arm of the patient, the housing having a size and shape configured to be secured to the lower arm of the patient;
 a strap mountable to the back side of the housing, the strap configured to secure the housing to the lower arm of the patient;
 a display positioned on a front side of the housing that is opposite a back side of the housing, the display configured to show a status of the portable patient monitoring device and one or more parameter measurements so as to be viewable by a user, wherein the display is positioned centrally on the front side of the display and is sized such that the display spans most of a length of a shortest dimension of the front side of the housing, and wherein the front side of the housing comprises a single user interface and a bezel;
 one or more user input mechanisms configured to control an operational mode of the portable patient monitoring device in response to inputs from a user;
 a first sensor port positioned on a first side of the housing, wherein:
 the first side of the housing is configured to face toward a hand having the digit of the patient under measurement when the housing is secured to the lower arm of the patient,
 the first sensor port is configured to removably physically couple with the pulse oximetry sensor via the cable and to electrically receive the first signal from the pulse oximetry sensor,
 the cable is configured to run from the first sensor port, at least part way down the arm of the patient, and to the digit of the patient to which the pulse oximetry sensor is configured to be wrapped around,
 the first sensor port is positioned on the first side of the housing such that, when the cable is physically coupled to the first sensor port, the cable extends from the first sensor port along a path perpendicular to the first side of the housing on which the first sensor port is positioned,
 the front side of the housing is raised from the strap and the lower arm of the patient to enable positioning of the first sensor port on the first side of the housing between the lower arm of the patient and the front side of the housing, and
 a top of the first sensor port is located below the front of the housing;
 a second sensor port positioned on the housing and configured to provide electrical communication with the blood pressure sensor arrangement and to electrically receive second signal from the blood pressure sensor arrangement, wherein the second sensor port is

19

connectable to wire extending from the blood pressure sensor arrangement to provide the electrical communication with the blood pressure sensor arrangement;

a third sensor port positioned on the housing and configured to provide electrical communication with the additional sensor arrangement and to electrically receive the third signal from the additional sensor arrangement, wherein the third sensor port is connectable to wire extending from the additional sensor arrangement to provide the electrical communication with the additional sensor arrangement;

a rechargeable battery within the housing and configured to power the portable patient monitoring device including at least the pulse oximetry sensor such that the portable patient monitoring device is portable and wearable by the patient;

one or more signal processing arrangements within the housing and configured to:

receive the first signal from the pulse oximetry sensor via one or more sensor interfaces;

process the first signal from the pulse oximetry sensor to determine measurements of oxygen saturation and pulse rate, wherein the first signal is processed at least in part in the analog domain by at least one of: the one or more sensor interfaces, or the one or more signal processing arrangements;

receive the second signal from the blood pressure sensor arrangement via the one or more sensor interfaces, wherein the second signal is processed at least in part in the digital domain by at least one of: the one or more sensor interfaces, or the one or more signal processing arrangements;

20

receive the third signal from the additional sensor arrangement via the one or more sensor interfaces, wherein the third signal is processed at least in part in the digital domain by at least one of: the one or more sensor interfaces, or the one or more signal processing arrangements; and

cause the measurements of oxygen saturation, pulse rate, blood pressure, and the at least one additional physiological parameter to all be displayed on the display of the portable patient monitoring device;

a multiplexer within the housing and configured to combine at least information indicative of the measurements of oxygen saturation, pulse rate, blood pressure, and the at least one additional physiological parameter into a single digital word or bit stream;

an encoder within the housing and configured to encode the single digital word or bit stream to generate a baseband signal; and

a transmitter within the housing and configured to:

modulate the baseband signal with a carrier to generate a transmit signal; and

wirelessly transmit a transmit signal including the information indicating the measurements of oxygen saturation, pulse rate, blood pressure, and the at least one additional physiological parameter to a separate computing device configured to decode the transmit signal and display, on a remote display, the measurements of oxygen saturation, pulse rate, blood pressure, and the at least one additional physiological parameter.

* * * * *

专利名称(译)	手臂可安装便携式病人监护仪		
公开(公告)号	US9872623	公开(公告)日	2018-01-23
申请号	US15/494967	申请日	2017-04-24
[标]申请(专利权)人(译)	梅西莫股份有限公司		
申请(专利权)人(译)	Masimo公司		
当前申请(专利权)人(译)	Masimo公司		
[标]发明人	AL ALI AMMAR		
发明人	AL-ALI, AMMAR		
IPC分类号	A61B5/1455 A61B5/00 A61B5/0205 A61B5/0402 A61B5/021 A61B5/024		
CPC分类号	A61B5/0205 A61B5/0004 A61B5/6824 A61B5/6826 A61B5/7271 A61B5/6831 A61B5/14552 A61B5/021 A61B5/02438 A61B5/0402 A61B5/002 A61B5/1455 A61B5/6838 H04W4/70 Y10S128/903 A61B5/0015 A61B5/0024 A61B5/0026 A61B5/02427 A61B5/0404 A61B5/0428 A61B5/72 A61B5/7228 A61B5/742 A61B5/7425 A61B5/7445 A61B5/7475 A61B2560/0214 A61B2562/222 A61B2562/227 G08B21/0453		
优先权	14/217788 2015-08-25 US 14/037137 2015-08-25 US 12/955826 2013-10-01 US 11/417006 2010-11-30 US 11/048330 2010-11-30 US 10/377933 2005-02-01 US 60/367428 2002-03-25 US		
其他公开文献	US20170224231A1		
外部链接	Espacenet USPTO		

摘要(译)

一种可安装在臂上的便携式患者监测装置，其配置用于使用可操作地连接到便携式患者监测装置的一个或多个传感器以及参数测量的无线传输来对患者进行参数测量的监测。可安装臂的便携式患者监测设备包括：脉冲血氧测量传感器，被配置为缠绕在患者的手指周围；壳体，其尺寸和形状被配置为安装到患者的下臂；以及带子，可安装到患者的背部。壳体并构造成将壳体固定到患者的下臂。壳体包括显示器，位于壳体上以面向患者的手的第一传感器端口，第二和第三传感器端口，电池，用于引起参数测量的显示的信号处理装置，以及用于发送指示的信息的发送器。测量。

