



US010517330B2

(12) **United States Patent**
Sur

(10) **Patent No.:** **US 10,517,330 B2**
(45) **Date of Patent:** **Dec. 31, 2019**

(54) **HEART RATE MONITOR FOR AN AEROSOL DELIVERY DEVICE**

FOREIGN PATENT DOCUMENTS

(71) Applicant: **RAI STRATEGIC HOLDINGS, INC.**,
Winston-Salem, NC (US)

AU 276250 7/1965
CA 2 641 869 5/2010
(Continued)

(72) Inventor: **Rajesh Sur**, Winston-Salem, NC (US)

OTHER PUBLICATIONS

(73) Assignee: **RAI Strategic Holdings, Inc.**,
Winston-Salem, NC (US)

International Search Report dated Aug. 21, 2018 in corresponding
International application No. PCT/IB2018/053628 filed May 22,
2018.

(*) Notice: Subject to any disclaimer, the term of this
patent is extended or adjusted under 35
U.S.C. 154(b) by 396 days.

(Continued)

(21) Appl. No.: **15/602,932**

Primary Examiner — Thor S Campbell

(22) Filed: **May 23, 2017**

(74) *Attorney, Agent, or Firm* — Womble Bond Dickinson
(US) LLP

(65) **Prior Publication Data**

US 2018/0338527 A1 Nov. 29, 2018

(57) **ABSTRACT**

(51) **Int. Cl.**
A24F 47/00 (2006.01)
A61M 15/06 (2006.01)
(Continued)

An aerosol delivery device is provided that includes at least one housing enclosing a reservoir configured to retain an aerosol precursor composition. The device includes a heating element, and a microprocessor configured to operate in an active mode in which the control body is configured to control the heating element to activate and vaporize components of the aerosol precursor composition. And the device includes a heart rate monitor including a plurality of biopotential electrodes affixed to the housing and configured to obtain biopotential measurements from a user, and including signal conditioning circuitry configured to produce an electrocardiogram signal from the biopotential measurements. The microprocessor is coupled to the signal conditioning circuitry and further configured to control operation of at least one functional element of the aerosol delivery device based on the electrocardiogram signal or a heart rate of the user calculated therefrom.

(52) **U.S. Cl.**
CPC **A24F 47/008** (2013.01); **A24B 15/167**
(2016.11); **A61B 5/0006** (2013.01);
(Continued)


(58) **Field of Classification Search**
None
See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

1,514,682 A 11/1924 Wilson
1,771,366 A 7/1930 Wyss et al.
(Continued)

18 Claims, 3 Drawing Sheets



- (51) **Int. Cl.**
A24B 15/16 (2006.01)
A61B 5/00 (2006.01)
A61B 5/024 (2006.01)
A61B 5/0402 (2006.01)
H05B 1/02 (2006.01)
A61B 5/02 (2006.01)
A61B 5/0245 (2006.01)
H04W 84/12 (2009.01)
F23Q 7/00 (2006.01)
- (52) **U.S. Cl.**
 CPC *A61B 5/02* (2013.01); *A61B 5/024* (2013.01); *A61B 5/0245* (2013.01); *A61B 5/02438* (2013.01); *A61B 5/0402* (2013.01); *A61B 5/6887* (2013.01); *H05B 1/02* (2013.01); *A61B 5/0022* (2013.01); *F23Q 2007/002* (2013.01); *H04W 84/12* (2013.01)
- (56) **References Cited**
 U.S. PATENT DOCUMENTS
- | | | | | | |
|-------------|---------|---------------------|-------------------|---------|-----------------------------------|
| 2,057,353 A | 10/1936 | Whittemore, Jr. | 6,164,287 A | 12/2000 | White |
| 2,104,266 A | 1/1938 | McCormick | 6,196,218 B1 | 3/2001 | Voges |
| 3,200,819 A | 8/1965 | Gilbert | 6,196,219 B1 | 3/2001 | Hess et al. |
| 3,479,561 A | 11/1969 | Janning | 6,598,607 B2 | 7/2003 | Adiga et al. |
| 4,284,089 A | 8/1981 | Ray | 6,601,776 B1 | 8/2003 | Oljaca et al. |
| 4,303,083 A | 12/1981 | Burruss, Jr. | 6,615,840 B1 | 9/2003 | Fournier et al. |
| 4,735,217 A | 4/1988 | Gerth et al. | 6,688,313 B2 | 2/2004 | Wrenn et al. |
| 4,848,374 A | 7/1989 | Chard et al. | 6,772,756 B2 | 8/2004 | Shayan |
| 4,907,606 A | 3/1990 | Lilja et al. | 6,803,545 B2 | 10/2004 | Blake et al. |
| 4,922,901 A | 5/1990 | Brooks et al. | 6,854,461 B2 | 2/2005 | Nichols |
| 4,945,931 A | 8/1990 | Gori | 6,854,470 B1 | 2/2005 | Pu |
| 4,947,874 A | 8/1990 | Brooks et al. | 7,117,867 B2 | 10/2006 | Cox et al. |
| 4,947,875 A | 8/1990 | Brooks et al. | 7,293,565 B2 | 11/2007 | Griffin et al. |
| 4,986,286 A | 1/1991 | Roberts et al. | 7,513,253 B2 | 4/2009 | Kobayashi et al. |
| 5,019,122 A | 5/1991 | Clearman et al. | 7,775,459 B2 | 8/2010 | Martens, III et al. |
| 5,042,510 A | 8/1991 | Curtiss et al. | 7,832,410 B2 | 11/2010 | Hon |
| 5,060,671 A | 10/1991 | Counts et al. | 7,845,359 B2 | 12/2010 | Montaser |
| 5,093,894 A | 3/1992 | Deevi et al. | 7,896,006 B2 | 3/2011 | Hamano et al. |
| 5,144,962 A | 9/1992 | Counts et al. | 8,127,772 B2 | 3/2012 | Montaser |
| 5,249,586 A | 10/1993 | Morgan et al. | 8,314,591 B2 | 11/2012 | Terry et al. |
| 5,261,424 A | 11/1993 | Sprinkel, Jr. | 8,365,742 B2 | 2/2013 | Hon |
| 5,322,075 A | 6/1994 | Deevi et al. | 8,402,976 B2 | 3/2013 | Fernando et al. |
| 5,353,813 A | 10/1994 | Deevi et al. | 8,499,766 B1 | 8/2013 | Newton |
| 5,369,723 A | 11/1994 | Counts et al. | 8,528,569 B1 | 9/2013 | Newton |
| 5,372,148 A | 12/1994 | McCafferty et al. | 8,550,069 B2 | 10/2013 | Alelov |
| 5,388,574 A | 2/1995 | Ingebretsen et al. | 8,851,081 B2 | 10/2014 | Fernando et al. |
| 5,408,574 A | 4/1995 | Deevi et al. | 9,603,386 B2 * | 3/2017 | Xiang A24F 47/008 |
| 5,468,936 A | 11/1995 | Deevi et al. | 9,675,114 B2 * | 6/2017 | Timmermans A24F 47/008 |
| 5,498,850 A | 3/1996 | Das | 2002/0146242 A1 | 10/2002 | Vieira |
| 5,515,842 A | 5/1996 | Ramseyer et al. | 2003/0226837 A1 | 12/2003 | Blake et al. |
| 5,530,225 A | 6/1996 | Hajaligol | 2004/0118401 A1 | 6/2004 | Smith et al. |
| 5,564,442 A | 10/1996 | MacDonald et al. | 2004/0129280 A1 | 7/2004 | Woodson et al. |
| 5,649,554 A | 7/1997 | Sprinkel et al. | 2004/0200488 A1 | 10/2004 | Felter et al. |
| 5,666,977 A | 9/1997 | Higgins et al. | 2004/0226568 A1 | 11/2004 | Takeuchi et al. |
| 5,687,746 A | 11/1997 | Rose et al. | 2005/0016550 A1 | 1/2005 | Katase |
| 5,726,421 A | 3/1998 | Fleischhauer et al. | 2006/0016453 A1 | 1/2006 | Kim |
| 5,727,571 A | 3/1998 | Meiring et al. | 2006/0196518 A1 | 9/2006 | Hon |
| 5,743,251 A | 4/1998 | Howell et al. | 2007/0074734 A1 | 4/2007 | Braunshsteyn et al. |
| 5,799,663 A | 9/1998 | Gross et al. | 2007/0102013 A1 | 5/2007 | Adams et al. |
| 5,819,756 A | 10/1998 | Mielordt | 2007/0215167 A1 | 9/2007 | Crooks et al. |
| 5,865,185 A | 2/1999 | Collins et al. | 2008/0085103 A1 | 4/2008 | Beland et al. |
| 5,865,186 A | 2/1999 | Volsey, II | 2008/0092912 A1 | 4/2008 | Robinson et al. |
| 5,878,752 A | 3/1999 | Adams et al. | 2008/0257367 A1 | 10/2008 | Paterno et al. |
| 5,894,841 A | 4/1999 | Voges | 2008/0276947 A1 | 11/2008 | Martzel |
| 5,934,289 A | 8/1999 | Watkins et al. | 2008/0302374 A1 | 12/2008 | Wengert et al. |
| 5,954,979 A | 9/1999 | Counts et al. | 2009/0095311 A1 | 4/2009 | Hon |
| 5,967,148 A | 10/1999 | Harris et al. | 2009/0095312 A1 | 4/2009 | Herbrich et al. |
| 6,040,560 A | 3/2000 | Fleischhauer et al. | 2009/0126745 A1 | 5/2009 | Hon |
| 6,053,176 A | 4/2000 | Adams et al. | 2009/0188490 A1 | 7/2009 | Hon |
| 6,089,857 A | 7/2000 | Matsuura et al. | 2009/0230117 A1 | 9/2009 | Fernando et al. |
| 6,095,153 A | 8/2000 | Kessler et al. | 2009/0272379 A1 | 11/2009 | Thorens et al. |
| 6,125,853 A | 10/2000 | Susa et al. | 2009/0283103 A1 | 11/2009 | Nielsen et al. |
| 6,155,268 A | 12/2000 | Takeuchi | 2009/0312656 A1 * | 12/2009 | Lau A61B 5/02438
600/509 |
| | | | 2009/0320863 A1 | 12/2009 | Fernando et al. |
| | | | 2010/0043809 A1 | 2/2010 | Magnon |
| | | | 2010/0083959 A1 | 4/2010 | Siller |
| | | | 2010/0200006 A1 | 8/2010 | Robinson et al. |
| | | | 2010/0229881 A1 | 9/2010 | Hearn |
| | | | 2010/0242974 A1 | 9/2010 | Pan |
| | | | 2010/0307518 A1 | 12/2010 | Wang |
| | | | 2010/0313901 A1 | 12/2010 | Fernando et al. |
| | | | 2011/0005535 A1 | 1/2011 | Xiu |
| | | | 2011/0011396 A1 | 1/2011 | Fang |
| | | | 2011/0036363 A1 | 2/2011 | Urtsev et al. |
| | | | 2011/0036365 A1 | 2/2011 | Chong et al. |
| | | | 2011/0094523 A1 | 4/2011 | Thorens et al. |
| | | | 2011/0126848 A1 | 6/2011 | Zuber et al. |
| | | | 2011/0155153 A1 | 6/2011 | Thorens et al. |
| | | | 2011/0155718 A1 | 6/2011 | Greim et al. |
| | | | 2011/0168194 A1 | 7/2011 | Hon |
| | | | 2011/0265806 A1 | 11/2011 | Alarcon et al. |
| | | | 2011/0309157 A1 | 12/2011 | Yang et al. |
| | | | 2012/0042885 A1 | 2/2012 | Stone et al. |
| | | | 2012/0060853 A1 | 3/2012 | Robinson et al. |
| | | | 2012/0090630 A1 * | 4/2012 | Hon A24F 47/002
131/273 |
| | | | 2012/0111347 A1 | 5/2012 | Hon |
| | | | 2012/0132643 A1 | 5/2012 | Choi et al. |

(56)

References Cited

U.S. PATENT DOCUMENTS

2012/0172684 A1* 7/2012 Buchheim A61B 5/721
600/301

2012/0227752 A1 9/2012 Alelov

2012/0231464 A1 9/2012 Yu et al.

2012/0260927 A1 10/2012 Liu

2012/0279512 A1 11/2012 Hon

2012/0318882 A1 12/2012 Abehasera

2013/0037041 A1 2/2013 Worm et al.

2013/0056013 A1 3/2013 Terry et al.

2013/0081625 A1 4/2013 Rustad et al.

2013/0081642 A1 4/2013 Safari

2013/0192619 A1 8/2013 Tucker et al.

2013/0220315 A1* 8/2013 Conley A24F 47/008
128/202.21

2013/0255702 A1 10/2013 Griffith, Jr. et al.

2013/0303922 A1* 11/2013 Buchheim A61B 5/02416
600/479

2013/0306084 A1 11/2013 Flick

2013/0319439 A1 12/2013 Gorelick et al.

2013/0340750 A1 12/2013 Thorens et al.

2013/0340775 A1 12/2013 Juster et al.

2014/0000638 A1 1/2014 Sebastian et al.

2014/0018635 A1* 1/2014 Buchheim A61B 5/721
600/301

2014/0060554 A1* 3/2014 Collett H05B 3/265
131/328

2014/0060555 A1 3/2014 Chang et al.

2014/0096781 A1 4/2014 Sears et al.

2014/0096782 A1 4/2014 Ampolini et al.

2014/0109921 A1 4/2014 Chen

2014/0157583 A1 6/2014 Ward et al.

2014/0209105 A1 7/2014 Sears et al.

2014/0253144 A1 9/2014 Novak et al.

2014/0261408 A1 9/2014 DePiano et al.

2014/0261486 A1 9/2014 Potter et al.

2014/0261487 A1 9/2014 Chapman et al.

2014/0261495 A1 9/2014 Novak et al.

2014/0270727 A1 9/2014 Ampolini et al.

2014/0270729 A1 9/2014 DePiano et al.

2014/0270730 A1 9/2014 DePiano et al.

2014/0345631 A1* 11/2014 Bowen A24B 15/16
131/328

2015/0007838 A1 1/2015 Fernando et al.

2015/0053217 A1 2/2015 Steingraber et al.

2015/0257647 A1* 9/2015 Buck A61B 5/0028
600/388

2016/0037826 A1 2/2016 Hearn et al.

2016/0058074 A1* 3/2016 Liu A24F 47/008
131/329

2016/0066808 A1* 3/2016 Hijazi A61B 5/04085
600/382

2017/0020192 A1* 1/2017 Fregonese H05B 3/0014

2017/0340209 A1* 11/2017 Klaassen A61B 5/021

2019/0053540 A1* 2/2019 Baker A24F 47/008

FOREIGN PATENT DOCUMENTS

CN 1541577 11/2004

CN 2719043 8/2005

CN 200997909 1/2008

CN 101116542 2/2008

CN 101176805 5/2008

CN 201379072 1/2010

DE 10 2006 004 4 8/2007

DE 102006041042 3/2008

DE 20 2009 010 4 11/2009

EP 0 295 122 12/1988

EP 0 430 566 6/1991

EP 0 845 220 6/1998

EP 1 618 803 1/2006

EP 2 316 286 5/2011

GB 2469850 11/2010

WO WO 1997/48293 12/1997

WO WO 2003/034847 5/2003

WO WO 2004/043175 5/2004

WO WO 2004/080216 9/2004

WO WO 2005/099494 10/2005

WO WO 2007/078273 7/2007

WO WO 2007/131449 11/2007

WO WO 2009/105919 9/2009

WO WO 2009/155734 12/2009

WO WO 2010/003480 1/2010

WO WO 2010/045670 4/2010

WO WO 2010/073122 7/2010

WO WO 2010/118644 10/2010

WO WO 2010/140937 12/2010

WO WO 2011/010334 1/2011

WO WO 2012/072762 6/2012

WO WO 2012/100523 8/2012

WO WO 2013/089551 6/2013

WO 2017/055795 4/2017

OTHER PUBLICATIONS

“Analog Devices, 50µA, 2 mm×1.7 mm WLCSP, Low Noise, Heart Rate Monitor for Wearable Products”, AD8233 Data Sheet, p. 1-30, Created Aug. 9, 2016.

* cited by examiner




FIG. 1





FIG. 2



HEART RATE MONITOR FOR AN AEROSOL DELIVERY DEVICE

TECHNOLOGICAL FIELD

The present disclosure relates to aerosol delivery devices such as smoking articles, and more particularly to aerosol delivery devices that may utilize electrically generated heat for the production of aerosol (e.g., smoking articles commonly referred to as electronic cigarettes). The smoking articles may be configured to heat an aerosol precursor, which may incorporate materials that may be made or derived from, or otherwise incorporate tobacco, the precursor being capable of forming an inhalable substance for human consumption.

BACKGROUND

Many devices have been proposed through the years as improvements upon, or alternatives to, smoking products that require combusting tobacco for use. Many of those devices purportedly have been designed to provide the sensations associated with cigarette, cigar, or pipe smoking, but without delivering considerable quantities of incomplete combustion and pyrolysis products that result from the burning of tobacco. To this end, there have been proposed numerous alternative smoking products, flavor generators, and medicinal inhalers that utilize electrical energy to vaporize or heat a volatile material, or attempt to provide the sensations of cigarette, cigar, or pipe smoking without burning tobacco to a significant degree. See, for example, the various alternative smoking articles, aerosol delivery devices and heat generating sources set forth in the background art described in U.S. Pat. No. 8,881,737 to Collett et al., U.S. Pat. App. Pub. No. 2013/0255702 to Griffith Jr. et al., U.S. Pat. App. Pub. No. 2014/0000638 to Sebastian et al., U.S. Pat. App. Pub. No. 2014/0096781 to Sears et al., U.S. Pat. App. Pub. No. 2014/0096782 to Ampolini et al., U.S. Pat. App. Pub. No. 2015/0059780 to Davis et al., and U.S. patent application Ser. No. 15/222,615 to Watson et al., filed Jul. 28, 2016, all of which are incorporated herein by reference. See also, for example, the various implementations of products and heating configurations described in the background sections of U.S. Pat. No. 5,388,594 to Counts et al. and U.S. Pat. No. 8,079,371 to Robinson et al., which are incorporated by reference.

However, it may be desirable to provide aerosol delivery devices with improved electronics such as may extend usability of the devices.

BRIEF SUMMARY

The present disclosure relates to aerosol delivery devices, methods of forming such devices, and elements of such devices. The present disclosure includes, without limitation, the following example implementations.

Some example implementations provide an aerosol delivery device comprising at least one housing enclosing a reservoir configured to retain an aerosol precursor composition; a heating element; a microprocessor configured to operate in an active mode in which the control body is configured to control the heating element to activate and vaporize components of the aerosol precursor composition; and a heart rate monitor including a plurality of biopotential electrodes affixed to the housing and configured to obtain biopotential measurements from a user, and including signal conditioning circuitry configured to produce an electrocar-

diogram signal from the biopotential measurements, wherein the microprocessor is coupled to the signal conditioning circuitry and further configured to control operation of at least one functional element of the aerosol delivery device based on the electrocardiogram signal or a heart rate of the user calculated therefrom.

In some example implementations of the aerosol delivery device of the preceding or any subsequent example implementation, or any combination thereof, the microprocessor being further configured to control operation of the at least one functional element includes being configured to calculate the heart rate of the user from the electrocardiogram signal, and control operation of the at least one functional element based on the heart rate so calculated.

In some example implementations of the aerosol delivery device of any preceding or any subsequent example implementation, or any combination thereof, the microprocessor being further configured to control operation of the at least one functional element includes being configured to control an indicator to provide a user-perceptible feedback.

In some example implementations of the aerosol delivery device of any preceding or any subsequent example implementation, or any combination thereof, the aerosol delivery device further comprises a communication interface configured to enable wireless communication, wherein the microprocessor being further configured to control operation of the at least one functional element includes being configured to cause the communication interface to wirelessly communicate the electrocardiogram signal or heart rate to a computing device configured to control operation of at least one functional element of the computing device based on the electrocardiogram signal or heart rate.

In some example implementations of the aerosol delivery device of any preceding or any subsequent example implementation, or any combination thereof, the communication interface being caused to wirelessly communicate the electrocardiogram signal or heart rate includes being caused to wirelessly communicate the electrocardiogram signal, and wherein the computing device being configured to control operation of the at least one functional element of the computing device includes being configured to calculate the heart rate of the user from the electrocardiogram signal, and control operation of the at least one functional element of the computing device based on the heart rate so calculated.

In some example implementations of the aerosol delivery device of any preceding or any subsequent example implementation, or any combination thereof, the computing device being configured to control operation of the at least one functional element of the computing device includes being configured to control an indicator of the computing device to provide a user-perceptible feedback.

In some example implementations of the aerosol delivery device of any preceding or any subsequent example implementation, or any combination thereof, the aerosol delivery device further comprises a communication interface configured to enable wireless communication with a service platform over at least one network including a wireless local area network (WLAN), wherein the microprocessor being further configured to control operation of the at least one functional element includes being configured to cause the communication interface to wirelessly communicate the electrocardiogram signal or heart rate to the service platform for storage in a database.

In some example implementations of the aerosol delivery device of any preceding or any subsequent example implementation, or any combination thereof, the microprocessor is configured to cause the communication interface to wire-

lessly communicate the electrocardiogram signal or heart rate to the service platform to further enable a medical professional to monitor or track the electrocardiogram signal or heart rate.

In some example implementations of the aerosol delivery device of any preceding or any subsequent example implementation, or any combination thereof, the aerosol precursor composition comprises glycerin and nicotine.

Some example implementations provide a control body coupled or coupleable with a cartridge to form an aerosol delivery device, the cartridge being equipped with a heating element and containing an aerosol precursor composition, the control body comprising a housing; a microprocessor configured to operate in an active mode in which the control body is coupled with the cartridge, the microprocessor in the active mode being configured to control the heating element to activate and vaporize components of the aerosol precursor composition; and a heart rate monitor including a plurality of biopotential electrodes affixed to the housing and configured to obtain biopotential measurements from a user, and including signal conditioning circuitry configured to produce an electrocardiogram signal from the biopotential measurements, wherein the microprocessor is coupled to the signal conditioning circuitry and further configured to control operation of at least one functional element of the control body or the aerosol delivery device based on the electrocardiogram signal or a heart rate of the user calculated therefrom.

In some example implementations of the control body of any preceding or any subsequent example implementation, or any combination thereof, the microprocessor being further configured to control operation of the at least one functional element includes being configured to calculate the heart rate of the user from the electrocardiogram signal, and control operation of the at least one functional element based on the heart rate so calculated.

In some example implementations of the control body of any preceding or any subsequent example implementation, or any combination thereof, the microprocessor being further configured to control operation of the at least one functional element includes being configured to control an indicator to provide a user-perceptible feedback.

In some example implementations of the control body of any preceding or any subsequent example implementation, or any combination thereof, the control body further comprises a communication interface configured to enable wireless communication, wherein the microprocessor being further configured to control operation of the at least one functional element includes being configured to cause the communication interface to wirelessly communicate the electrocardiogram signal or heart rate to an computing device configured to control operation of at least one functional element of the computing device based on the electrocardiogram signal or heart rate.

In some example implementations of the control body of any preceding or any subsequent example implementation, or any combination thereof, the communication interface being caused to wirelessly communicate the electrocardiogram signal or heart rate includes being caused to wirelessly communicate the electrocardiogram signal, and wherein the computing device being configured to control operation of the at least one functional element of the computing device includes being configured to calculate the heart rate of the user from the electrocardiogram signal, and control operation of the at least one functional element of the computing device based on the heart rate so calculated.

In some example implementations of the control body of any preceding or any subsequent example implementation, or any combination thereof, the computing device being configured to control operation of the at least one functional element of the computing device includes being configured to control an indicator of the computing device to provide a user-perceptible feedback.

In some example implementations of the control body of any preceding or any subsequent example implementation, or any combination thereof, the control body further comprises a communication interface configured to enable wireless communication with a service platform over at least one network including a wireless local area network (WLAN), wherein the microprocessor being further configured to control operation of the at least one functional element includes being configured to cause the communication interface to wirelessly communicate the electrocardiogram signal or heart rate to the service platform for storage in a database.

In some example implementations of the control body of any preceding or any subsequent example implementation, or any combination thereof, the microprocessor is configured to cause the communication interface to wirelessly communicate the electrocardiogram signal or heart rate to the service platform to further enable a medical professional to monitor or track the electrocardiogram signal or heart rate.

In some example implementations of the control body of any preceding or any subsequent example implementation, or any combination thereof, the aerosol precursor composition comprises glycerin and nicotine.

These and other features, aspects, and advantages of the present disclosure will be apparent from a reading of the following detailed description together with the accompanying drawings, which are briefly described below. The present disclosure includes any combination of two, three, four or more features or elements set forth in this disclosure, regardless of whether such features or elements are expressly combined or otherwise recited in a specific example implementation described herein. This disclosure is intended to be read holistically such that any separable features or elements of the disclosure, in any of its aspects and example implementations, should be viewed as combinable, unless the context of the disclosure clearly dictates otherwise.

It will therefore be appreciated that this Brief Summary is provided merely for purposes of summarizing some example implementations so as to provide a basic understanding of some aspects of the disclosure. Accordingly, it will be appreciated that the above described example implementations are merely examples and should not be construed to narrow the scope or spirit of the disclosure in any way. Other example implementations, aspects and advantages will become apparent from the following detailed description taken in conjunction with the accompanying drawings which illustrate, by way of example, the principles of some described example implementations.

BRIEF DESCRIPTION OF THE DRAWING(S)

Having thus described the disclosure in the foregoing general terms, reference will now be made to the accompanying drawings, which are not necessarily drawn to scale, and wherein:

FIG. 1 illustrates a side view of an aerosol delivery device including a cartridge coupled to a control body, according to an example implementation of the present disclosure;

FIG. 2 is a partially cut-away view of the aerosol delivery device according to various example implementations; and

FIG. 3 illustrates a system including an aerosol delivery device in wireless communication with a computing device, according to various example implementations.

DETAILED DESCRIPTION

The present disclosure will now be described more fully hereinafter with reference to example implementations thereof. These example implementations are described so that this disclosure will be thorough and complete, and will fully convey the scope of the disclosure to those skilled in the art. Indeed, the disclosure may be embodied in many different forms and should not be construed as limited to the implementations set forth herein; rather, these implementations are provided so that this disclosure will satisfy applicable legal requirements. As used in the specification and the appended claims, the singular forms “a,” “an,” “the” and the like include plural referents unless the context clearly dictates otherwise.

As described hereinafter, example implementations of the present disclosure relate to aerosol delivery devices. Aerosol delivery devices according to the present disclosure use electrical energy to heat a material (preferably without combusting the material to any significant degree) to form an inhalable substance; and components of such systems have the form of articles most preferably are sufficiently compact to be considered hand-held devices. That is, use of components of preferred aerosol delivery devices does not result in the production of smoke in the sense that aerosol results principally from by-products of combustion or pyrolysis of tobacco, but rather, use of those preferred systems results in the production of vapors resulting from volatilization or vaporization of certain components incorporated therein. In some example implementations, components of aerosol delivery devices may be characterized as electronic cigarettes, and those electronic cigarettes most preferably incorporate tobacco and/or components derived from tobacco, and hence deliver tobacco derived components in aerosol form.

Aerosol generating pieces of certain preferred aerosol delivery devices may provide many of the sensations (e.g., inhalation and exhalation rituals, types of tastes or flavors, organoleptic effects, physical feel, use rituals, visual cues such as those provided by visible aerosol, and the like) of smoking a cigarette, cigar or pipe that is employed by lighting and burning tobacco (and hence inhaling tobacco smoke), without any substantial degree of combustion of any component thereof. For example, the user of an aerosol generating piece of the present disclosure can hold and use that piece much like a smoker employs a traditional type of smoking article, draw on one end of that piece for inhalation of aerosol produced by that piece, take or draw puffs at selected intervals of time, and the like.

While the systems are generally described herein in terms of implementations associated with aerosol delivery devices such as so-called “e-cigarettes,” it should be understood that the mechanisms, components, features, and methods may be embodied in many different forms and associated with a variety of articles. For example, the description provided herein may be employed in conjunction with implementations of traditional smoking articles (e.g., cigarettes, cigars, pipes, etc.), heat-not-burn cigarettes, and related packaging for any of the products disclosed herein. Accordingly, it should be understood that the description of the mechanisms, components, features, and methods disclosed herein

are discussed in terms of implementations relating to aerosol delivery devices by way of example only, and may be embodied and used in various other products and methods.

Aerosol delivery devices of the present disclosure also can be characterized as being vapor-producing articles or medicament delivery articles. Thus, such articles or devices can be adapted so as to provide one or more substances (e.g., flavors and/or pharmaceutical active ingredients) in an inhalable form or state. For example, inhalable substances can be substantially in the form of a vapor (i.e., a substance that is in the gas phase at a temperature lower than its critical point). Alternatively, inhalable substances can be in the form of an aerosol (i.e., a suspension of fine solid particles or liquid droplets in a gas). For purposes of simplicity, the term “aerosol” as used herein is meant to include vapors, gases and aerosols of a form or type suitable for human inhalation, whether or not visible, and whether or not of a form that might be considered to be smoke-like.

In use, aerosol delivery devices of the present disclosure may be subjected to many of the physical actions employed by an individual in using a traditional type of smoking article (e.g., a cigarette, cigar or pipe that is employed by lighting and inhaling tobacco). For example, the user of an aerosol delivery device of the present disclosure can hold that article much like a traditional type of smoking article, draw on one end of that article for inhalation of aerosol produced by that article, take puffs at selected intervals of time, etc.

Aerosol delivery devices of the present disclosure generally include a number of components provided within an outer body or shell, which may be referred to as a housing. The overall design of the outer body or shell can vary, and the format or configuration of the outer body that can define the overall size and shape of the aerosol delivery device can vary. Typically, an elongated body resembling the shape of a cigarette or cigar can be a formed from a single, unitary housing or the elongated housing can be formed of two or more separable bodies. For example, an aerosol delivery device can comprise an elongated shell or body that can be substantially tubular in shape and, as such, resemble the shape of a conventional cigarette or cigar. In one example, all of the components of the aerosol delivery device are contained within one housing. Alternatively, an aerosol delivery device can comprise two or more housings that are joined and are separable. For example, an aerosol delivery device can possess at one end a control body comprising a housing containing one or more reusable components (e.g., an accumulator such as a rechargeable battery and/or rechargeable supercapacitor, and various electronics for controlling the operation of that article), and at the other end and removably coupleable thereto, an outer body or shell containing a disposable portion (e.g., a disposable flavor-containing cartridge). More specific formats, configurations and arrangements of components within the single housing type of unit or within a multi-piece separable housing type of unit will be evident in light of the further disclosure provided herein. Additionally, various aerosol delivery device designs and component arrangements can be appreciated upon consideration of the commercially available electronic aerosol delivery devices.

Aerosol delivery devices of the present disclosure most preferably comprise some combination of a power source (i.e., an electrical power source), at least one control component (e.g., means for actuating, controlling, regulating and ceasing power for heat generation, such as by controlling electrical current flow the power source to other components of the article—e.g., a microprocessor, individually or as part of a microcontroller), a heater or heat generation member

(e.g., an electrical resistance heating element or other component) or vibrating piezoelectric mesh, which alone or in combination with one or more further elements may be commonly referred to as an “atomizer”, an aerosol precursor composition (e.g., commonly a liquid capable of yielding an aerosol upon application of sufficient heat, such as ingredients commonly referred to as “smoke juice,” “e-liquid” and “e-juice”), and a mouthend region or tip for allowing draw upon the aerosol delivery device for aerosol inhalation (e.g., a defined airflow path through the article such that aerosol generated can be withdrawn therefrom upon draw).

Alignment of the components within the aerosol delivery device of the present disclosure can vary. In specific implementations, the aerosol precursor composition can be located near an end of the aerosol delivery device which may be configured to be positioned proximal to the mouth of a user so as to maximize aerosol delivery to the user. Other configurations, however, are not excluded. Generally, the heating element can be positioned sufficiently near the aerosol precursor composition so that heat from the heating element can volatilize the aerosol precursor (as well as one or more flavorants, medicaments, or the like that may likewise be provided for delivery to a user) and form an aerosol for delivery to the user. When the heating element heats the aerosol precursor composition, an aerosol is formed, released, or generated in a physical form suitable for inhalation by a consumer. It should be noted that the foregoing terms are meant to be interchangeable such that reference to release, releasing, releases, or released includes form or generate, forming or generating, forms or generates, and formed or generated. Specifically, an inhalable substance is released in the form of a vapor or aerosol or mixture thereof, wherein such terms are also interchangeably used herein except where otherwise specified.

As noted above, the aerosol delivery device may incorporate a battery or other electrical power source to provide current flow sufficient to provide various functionalities to the aerosol delivery device, such as powering of a heater, powering of control systems, powering of indicators, and the like. The power source can take on various implementations. Preferably, the power source is able to deliver sufficient power to rapidly heat the heating element to provide for aerosol formation and power the aerosol delivery device through use for a desired duration of time. The power source preferably is sized to fit conveniently within the aerosol delivery device so that the aerosol delivery device can be easily handled. Additionally, a preferred power source is of a sufficiently light weight to not detract from a desirable smoking experience.

More specific formats, configurations and arrangements of components within the aerosol delivery devices of the present disclosure will be evident in light of the further disclosure provided hereinafter. Additionally, the selection and arrangement of various aerosol delivery device components can be appreciated upon consideration of commercially-available electronic aerosol delivery devices. Further information regarding formats, configurations and arrangements of components within the aerosol delivery devices of the present disclosure, as well as commercially-available electronic aerosol delivery devices, may be found in U.S. patent application Ser. No. 15/291,771 to Sur et al., filed Oct. 12, 2016, which is incorporated herein by reference.

FIG. 1 illustrates a side view of an aerosol delivery device **100** including a control body **102** and a cartridge **104**, according to various example implementations of the present disclosure. In particular, FIG. 1 illustrates the control body and the cartridge coupled to one another. The control

body and the cartridge may be detachably aligned in a functioning relationship. Various mechanisms may connect the cartridge to the control body to result in a threaded engagement, a press-fit engagement, an interference fit, a magnetic engagement or the like. The aerosol delivery device may be substantially rod-like, substantially tubular shaped, or substantially cylindrically shaped in some example implementations when the cartridge and the control body are in an assembled configuration. The aerosol delivery device may also be substantially rectangular, rhomboidal or triangular in cross-section, multifaceted shapes, or the like, some of which may lend itself to greater compatibility with a substantially flat or thin-film power source, such as a power source including a flat battery.

The control body **102** and cartridge **104** may include separate, respective housings or outer bodies, which may be formed of any of a number of different materials. The housing may be formed of any suitable, structurally-sound material. In some examples, the housing may be formed of a metal or alloy, such as stainless steel, aluminum or the like. Other suitable materials include various plastics (e.g., polycarbonate), metal-plating over plastic, ceramics and the like.

In some example implementations, one or both of the control body **102** or the cartridge **104** of the aerosol delivery device **100** may be referred to as being disposable or as being reusable. For example, the control body may have a replaceable battery, rechargeable battery (e.g., rechargeable thin-film solid state battery) or rechargeable supercapacitor, and thus may be combined with any type of recharging technology, including connection to a typical wall outlet, connection to a car charger (i.e., a cigarette lighter receptacle), connection to a computer, such as through a universal serial bus (USB) cable or connector, connection to a photovoltaic cell (sometimes referred to as a solar cell) or solar panel of solar cells, wireless connection to a Radio Frequency (RF), wireless connection to induction-based charging pads, or connection to a RF-to-DC converter. Further, in some example implementations, the cartridge may comprise a single-use cartridge, as disclosed in U.S. Pat. No. 8,910,639 to Chang et al., which is incorporated herein by reference.

FIG. 2 more particularly illustrates the aerosol delivery device **100**, in accordance with some example implementations. As seen in the cut-away view illustrated therein, again, the aerosol delivery device can comprise a control body **102** and a cartridge **104** each of which include a number of respective components. The components illustrated in FIG. 2 are representative of the components that may be present in a control body and cartridge and are not intended to limit the scope of components that are encompassed by the present disclosure. As shown, for example, the control body can be formed of a control body shell **206** that can include a control component **208** (e.g., a microprocessor, individually or as part of a microcontroller), a flow sensor **210**, a power source **212** and one or more light-emitting diodes (LEDs) **214**, quantum dot enabled LEDs or the like, and such components can be variably aligned. The power source may include, for example, a battery (single-use or rechargeable), rechargeable supercapacitor, rechargeable solid-state battery (SSB), rechargeable lithium-ion battery (LiB) or the like, or some combination thereof. Some examples of a suitable power source are provided in U.S. patent application Ser. No. 14/918,926 to Sur et al., filed Oct. 21, 2015, which is incorporated herein by reference. Other examples of a suitable power source are provided in U.S. Pat. App. Pub. No. 2014/0283855 to Hawes et al., U.S. Pat. App. Pub. No. 2014/0014125 to Fernando et al., U.S. Pat. App. Pub.

No. 2013/0243410 to Nichols et al., U.S. Pat. App. Pub. No. 2010/0313901 to Fernando et al., and U.S. Pat. App. Pub. No. 2009/0230117 to Fernando et al., all of which are incorporated herein by reference.

The LED **214** may be one example of a suitable visual indicator with which the aerosol delivery device **100** may be equipped. Other indicators such as audio indicators (e.g., speakers), haptic indicators (e.g., vibration motors) or the like can be included in addition to or as an alternative to visual indicators such as the LED, quantum dot enabled LEDs.

The cartridge **104** can be formed of a cartridge shell **216** enclosing a reservoir **218** configured to retain the aerosol precursor composition, and including a heater **222** (sometimes referred to as a heating element). In various configurations, this structure may be referred to as a tank; and accordingly, the terms “cartridge,” “tank” and the like may be used interchangeably to refer to a shell or other housing enclosing a reservoir for aerosol precursor composition, and including a heater.

As shown, in some examples, the reservoir **218** may be in fluid communication with a liquid transport element **220** adapted to wick or otherwise transport an aerosol precursor composition stored in the reservoir housing to the heater **222**. In some examples, a valve may be positioned between the reservoir and heater, and configured to control an amount of aerosol precursor composition passed or delivered from the reservoir to the heater.

Various examples of materials configured to produce heat when electrical current is applied therethrough may be employed to form the heater **222**. The heater in these examples may be a resistive heating element such as a wire coil, micro heater or the like. Example materials from which the heating element may be formed include Kanthal (Fe-CrAl), Nichrome, stainless steel, Molybdenum disilicide (MoSi₂), molybdenum silicide (MoSi), Molybdenum disilicide doped with Aluminum (Mo(Si,Al)₂), graphite and graphite-based materials (e.g., carbon-based foams and yarns) and ceramics (e.g., positive or negative temperature coefficient ceramics). Example implementations of heaters or heating members useful in aerosol delivery devices according to the present disclosure are further described below, and can be incorporated into devices such as those described herein.

An opening **224** may be present in the cartridge shell **216** (e.g., at the mouthend) to allow for egress of formed aerosol from the cartridge **104**.

The cartridge **104** also may include one or more electronic components **226**, which may include an integrated circuit, a memory component (e.g., EEPROM, flash memory), a sensor, or the like. The electronic components may be adapted to communicate with the control component **208** and/or with an external device by wired or wireless means. The electronic components may be positioned anywhere within the cartridge or a base **228** thereof.

Although the control component **208** and the flow sensor **210** are illustrated separately, it is understood that various electronic components including the control component and the flow sensor may be combined on an electronic printed circuit board (PCB) that supports and electrically connects the electronic components. Further, the PCB may be positioned horizontally relative the illustration of FIG. 1 in that the PCB can be lengthwise parallel to the central axis of the control body. In some examples, the air flow sensor may comprise its own PCB or other base element to which it can be attached. In some examples, a flexible PCB may be utilized. A flexible PCB may be configured into a variety of

shapes, include substantially tubular shapes. In some examples, a flexible PCB may be combined with, layered onto, or form part or all of a heater substrate.

The control body **102** and the cartridge **104** may include components adapted to facilitate a fluid engagement therebetween. As illustrated in FIG. 2, the control body can include a coupler **230** having a cavity **232** therein. The base **228** of the cartridge can be adapted to engage the coupler and can include a projection **234** adapted to fit within the cavity. Such engagement can facilitate a stable connection between the control body and the cartridge as well as establish an electrical connection between the power source **212** and control component **208** in the control body and the heater **222** in the cartridge. Further, the control body shell **206** can include an air intake **236**, which may be a notch in the shell where it connects to the coupler that allows for passage of ambient air around the coupler and into the shell where it then passes through the cavity **232** of the coupler and into the cartridge through the projection **234**.

A coupler and a base useful according to the present disclosure are described in U.S. Pat. App. Pub. No. 2014/0261495 to Novak et al., which is incorporated herein by reference. For example, the coupler **230** as seen in FIG. 2 may define an outer periphery **238** configured to mate with an inner periphery **240** of the base **228**. In one example the inner periphery of the base may define a radius that is substantially equal to, or slightly greater than, a radius of the outer periphery of the coupler. Further, the coupler may define one or more protrusions **242** at the outer periphery configured to engage one or more recesses **244** defined at the inner periphery of the base. However, various other examples of structures, shapes and components may be employed to couple the base to the coupler. In some examples the connection between the base of the cartridge **104** and the coupler of the control body **102** may be substantially permanent, whereas in other examples the connection therebetween may be releasable such that, for example, the control body may be reused with one or more additional cartridges that may be disposable and/or refillable.

The reservoir **218** illustrated in FIG. 2 can be a container or can be a fibrous reservoir, as presently described. For example, the reservoir can comprise one or more layers of nonwoven fibers substantially formed into the shape of a tube encircling the interior of the cartridge shell **216**, in this example. An aerosol precursor composition can be retained in the reservoir. Liquid components, for example, can be sorptively retained by the reservoir. The reservoir can be in fluid connection with the liquid transport element **220**. The liquid transport element can transport the aerosol precursor composition stored in the reservoir via capillary action to the heater **222** that is in the form of a metal wire coil in this example. As such, the heater is in a heating arrangement with the liquid transport element.

In some examples, a microfluidic chip may be embedded in the reservoir **218**, and the amount and/or mass of aerosol precursor composition delivered from the reservoir may be controlled by a micro pump, such as one based on micro-electromechanical systems (MEMS) technology. The heater **222** may be configured to implement radio-frequency inductive based heating of the aerosol precursor composition without a wick or physical contact with the aerosol precursor composition, such as in a manner described in U.S. patent application Ser. No. 14/934,763 to Davis et al., filed Nov. 6, 2015, which is incorporated by reference. Other example implementations of reservoirs and transport elements useful in aerosol delivery devices according to the present disclo-

sure are further described below, and such reservoirs and/or transport elements can be incorporated into devices such as those described herein. In particular, specific combinations of heating members and transport elements as further described below may be incorporated into devices such as

In use, when a user draws on the aerosol delivery device **100**, airflow is detected by the flow sensor **210**, and the heater **222** is activated to vaporize components of the aerosol precursor composition. Drawing upon the mouthend of the aerosol delivery device causes ambient air to enter the air intake **236** and pass through the cavity **232** in the coupler **230** and the central opening in the projection **234** of the base **228**. In the cartridge **104**, the drawn air combines with the formed vapor to form an aerosol. The aerosol is whisked, aspirated or otherwise drawn away from the heater and out the opening **224** in the mouthend of the aerosol delivery device.

In some examples, the aerosol delivery device **100** may include a number of additional software-controlled functions. For example, the aerosol delivery device may include a power-source protection circuit configured to detect power-source input, loads on the power-source terminals, and charging input. The power-source protection circuit may include short-circuit protection, under-voltage lock out and/or over-voltage charge protection, battery temperature compensation. The aerosol delivery device may also include components for ambient temperature measurement, and its control component **208** may be configured to control at least one functional element to inhibit power-source charging—particularly of any battery—if the ambient temperature is below a certain temperature (e.g., 0° C.) or above a certain temperature (e.g., 45° C.) prior to start of charging or during charging.

Additionally or alternatively, in some examples, the control component **208** may include a microprocessor with an embedded analog-to-digital converter (ADC) useful for measurement of the temperature of the heater **222**. More particularly, for example, the microprocessor may be programmed to cause a fixed current to the heater, and measure the voltage across the heater. The microprocessor may then be configured to calculate the resistance of the heater that varies with temperature from the current and voltage ($R=V/I$). The resistance may then be used to determine the temperature of the heater from a known relationship between resistance and temperature for the heater material. This relationship may be expressed in a number of different manners, such as by a lookup table.

Power delivery from the power source **212** may vary over the course of each puff on the device **100** according to a power control mechanism. The device may include a “long puff” safety timer such that in the event that a user or component failure (e.g., flow sensor **210**) causes the device to attempt to puff continuously, the control component **208** may control at least one functional element to terminate the puff automatically after some period of time (e.g., four seconds). Further, the time between puffs on the device may be restricted to less than a period of time (e.g., 100 seconds). A watchdog safety timer may automatically reset the aerosol delivery device if its control component or software running on it becomes unstable and does not service the timer within an appropriate time interval (e.g., eight seconds). Further safety protection may be provided in the event of a defective or otherwise failed flow sensor **210**, such as by permanently disabling the aerosol delivery device in order to prevent inadvertent heating. A puffing limit switch may deactivate the device in the event of a pressure sensor fail causing the

device to continuously activate without stopping after the four second maximum puff time.

The aerosol delivery device **100** may include a puff tracking algorithm configured for heater lockout once a defined number of puffs has been achieved for an attached cartridge (based on the number of available puffs calculated in light of the e-liquid charge in the cartridge). The aerosol delivery device may include a sleep, standby or low-power mode function whereby power delivery may be automatically cut off after a defined period of non-use. Further safety protection may be provided in that all charge/discharge cycles of the power source **212** may be monitored by the control component **208** over its lifetime. After the power source has attained the equivalent of a predetermined number (e.g., 200) of full discharge and full recharge cycles, it may be declared depleted, and the control component may control at least one functional element to prevent further charging of the power source.

The various components of an aerosol delivery device according to the present disclosure can be chosen from components described in the art and commercially available. Examples of batteries that can be used according to the disclosure are described in U.S. Pat. No. 9,484,155 to Peckerar et al., which is incorporated herein by reference.

The aerosol delivery device **100** can incorporate the sensor **210** or another sensor or detector for control of supply of electric power to the heater **222** when aerosol generation is desired (e.g., upon draw during use). As such, for example, there is provided a manner or method of turning off power to the heater when the aerosol delivery device is not be drawn upon during use, and for turning on power to actuate or trigger the generation of heat by the heater during draw. Additional representative types of sensing or detection mechanisms, structure and configuration thereof, components thereof, and general methods of operation thereof, are described in U.S. Pat. No. 5,261,424 to Sprinkel, Jr., U.S. Pat. No. 5,372,148 to McCafferty et al., and PCT Pat. App. Pub. No. WO 2010/003480 to Flick, all of which are incorporated herein by reference.

The aerosol delivery device **100** most preferably incorporates the control component **208** or another control mechanism for controlling the amount of electric power to the heater **222** during draw. Representative types of electronic components, structure and configuration thereof, features thereof, and general methods of operation thereof, are described in U.S. Pat. No. 4,735,217 to Gerth et al., U.S. Pat. No. 4,947,874 to Brooks et al., U.S. Pat. No. 5,372,148 to McCafferty et al., U.S. Pat. No. 6,040,560 to Fleischhauer et al., U.S. Pat. No. 7,040,314 to Nguyen et al., U.S. Pat. No. 8,205,622 to Pan, U.S. Pat. No. 8,881,737 to Collet et al., U.S. Pat. No. 9,423,152 to Ampolini et al., U.S. Pat. No. 9,439,454 to Fernando et al., and U.S. Pat. App. Pub. No. 2015/0257445 to Henry et al., all of which are incorporated herein by reference.

Representative types of substrates, reservoirs or other components for supporting the aerosol precursor are described in U.S. Pat. No. 8,528,569 to Newton, U.S. Pat. App. Pub. No. 2014/0261487 to Chapman et al., U.S. Pat. App. Pub. No. 2015/0059780 to Davis et al., and U.S. Pat. App. Pub. No. 2015/0216232 to Bless et al., all of which are incorporated herein by reference. Additionally, various wicking materials, and the configuration and operation of those wicking materials within certain types of electronic cigarettes, are set forth in U.S. Pat. No. 8,910,640 to Sears et al., which is incorporated herein by reference.

The aerosol precursor composition, also referred to as a vapor precursor composition, may comprise a variety of

components including, by way of example, a polyhydric alcohol (e.g., glycerin, propylene glycol or a mixture thereof), nicotine, tobacco, tobacco extract and/or flavorants. Representative types of aerosol precursor components and formulations also are set forth and characterized in U.S. Pat. No. 7,217,320 to Robinson et al., U.S. Pat. No. 9,254,002 to Chong et al., U.S. Pat. No. 8,881,737 to Collett et al., U.S. Pat. Pub. No. 2013/0008457 to Zheng et al., U.S. Pat. Pub. No. 2015/0020823 to Lipowicz et al., and U.S. Pat. Pub. No. 2015/0020830 to Koller, as well as PCT Pat. App. Pub. No. WO 2014/182736 to Bowen et al., and U.S. patent application Ser. No. 15/222,615 to Watson et al., filed Jul. 28, 2016, the disclosures of which are incorporated herein by reference. Other aerosol precursors that may be employed include the aerosol precursors that have been incorporated in the VUSE® product by R. J. Reynolds Vapor Company, the BLU™ product by Imperial Tobacco Group PLC, the MISTIC MENTHOL product by Mistic Ecigs, and the VYPE product by CN Creative Ltd. Also desirable are the so-called “smoke juices” for electronic cigarettes that have been available from Johnson Creek Enterprises LLC.

Implementations of effervescent materials can be used with the aerosol precursor, and are described, by way of example, in U.S. Pat. App. Pub. No. 2012/0055494 to Hunt et al., which is incorporated herein by reference. Further, the use of effervescent materials is described, for example, in U.S. Pat. No. 4,639,368 to Niazi et al., U.S. Pat. No. 5,178,878 to Wehling et al., U.S. Pat. No. 5,223,264 to Wehling et al., U.S. Pat. No. 6,974,590 to Pather et al., U.S. Pat. No. 7,381,667 to Bergquist et al., U.S. Pat. No. 8,424,541 to Crawford et al., and U.S. Pat. No. 8,627,828 to Strickland et al., as well as U.S. Pat. No. 9,307,787 to Sun et al., U.S. Pat. App. Pub. No. 2010/0018539 to Brinkley et al., and PCT Pat. App. Pub. No. WO 97/06786 to Johnson et al., all of which are incorporated by reference herein. Additional description with respect to implementations of aerosol precursor compositions, including description of tobacco or components derived from tobacco included therein, is provided in U.S. patent application Ser. Nos. 15/216,582 and 15/216,590, each filed Jul. 21, 2016 and each to Davis et al., which are incorporated herein by reference.

Additional representative types of components that yield visual cues or indicators may be employed in the aerosol delivery device **100**, such as visual indicators and related components, audio indicators, haptic indicators and the like. Examples of suitable LED components, and the configurations and uses thereof, are described in U.S. Pat. No. 5,154,192 to Sprinkel et al., U.S. Pat. No. 8,499,766 to Newton, U.S. Pat. No. 8,539,959 to Scatterday, and U.S. Pat. No. 9,451,791 to Sears et al., all of which are incorporated herein by reference.

Yet other features, controls or components that can be incorporated into aerosol delivery devices of the present disclosure are described in U.S. Pat. No. 5,967,148 to Harris et al., U.S. Pat. No. 5,934,289 to Watkins et al., U.S. Pat. No. 5,954,979 to Counts et al., U.S. Pat. No. 6,040,560 to Fleischhauer et al., U.S. Pat. No. 8,365,742 to Hon, U.S. Pat. No. 8,402,976 to Fernando et al., U.S. Pat. App. Pub. No. 2005/0016550 to Katase, U.S. Pat. No. 8,689,804 to Fernando et al., U.S. Pat. App. Pub. No. 2013/0192623 to Tucker et al., U.S. Pat. No. 9,427,022 to Leven et al., U.S. Pat. App. Pub. No. 2013/0180553 to Kim et al., U.S. Pat. App. Pub. No. 2014/0000638 to Sebastian et al., U.S. Pat. App. Pub. No. 2014/0261495 to Novak et al., and U.S. Pat. No. 9,220,302 to DePiano et al., all of which are incorporated herein by reference.

As indicated above, the control component **208** includes a number of electronic components, and in some examples may be formed of a PCB. The electronic components may include a microprocessor or processor core, and a memory. In some examples, the control component may include a microcontroller with integrated processor core and memory, and may further include one or more integrated input/output peripherals. In some examples, the control component may be coupled to a communication interface **246** to enable wireless communication with one or more networks, computing devices or other appropriately-enabled devices. Examples of suitable communication interfaces are disclosed in U.S. Pat. App. Pub. No. 2016/0261020 to Marion et al., the content of which is incorporated herein by reference. Another example of a suitable communication interface is the CC3200 single chip wireless microcontroller unit (MCU) from Texas Instruments. And examples of suitable manners according to which the aerosol delivery device may be configured to wirelessly communicate are disclosed in U.S. Pat. App. Pub. No. 2016/0007651 to Ampolini et al., and U.S. Pat. App. Pub. No. 2016/0219933 to Henry, Jr. et al., each of which is incorporated herein by reference.

As further shown in FIGS. **1** and **2**, in accordance with some example implementations, the control body **102** includes a heart rate monitor **248** including a plurality of biopotential electrodes **250** affixed to the shell **206** (housing) and configured to obtain biopotential measurements from a user. This may include, for example, two or three biopotential electrodes that obtain biopotential measurements from a user who contacts the biopotential electrodes with their hands. The biopotential electrodes may be any of a number of different types of electrodes capable of obtaining biopotential measurements that represent activity of the heart, which manifests its function through electric activity.

The heart rate monitor **248** also includes signal conditioning circuitry **252** configured to produce an electrocardiogram signal from the biopotential measurements. One example of suitable signal conditioning circuitry is implemented in an integrated circuit (IC) such as the model AD8233 heart rate monitor from Analog Devices.

In some examples, the control component **208** (microprocessor) is coupled to the signal conditioning circuitry **252** and further configured to control operation of at least one functional element of the control body **102** or the aerosol delivery device **100** based on the electrocardiogram signal or a heart rate of the user calculated therefrom. This may include the control component being configured to calculate the heart rate of the user from the electrocardiogram signal, and control operation of the functional element(s) based on the heart rate so calculated. The heart rate may be calculated in any suitable manner and expressed in beats per minute (bpm).

Functional element(s) of the control body **102** or the aerosol delivery device **100** may be controlled in any of a number of different manners in based on the electrocardiogram signal or heart rate. For example, an indicator **254** (e.g., visual indicator, audio indicator, haptic indicator) may be controlled to provide a user-perceptible feedback (e.g., visual, audible, haptic feedback). The feedback may include, for example, a visual readout of the electrocardiogram signal or heart rate. Additionally or alternatively, for example, the feedback may include a visual, audible and/or haptic notification that the heart rate is above or below a predefined threshold, or within or outside a predefined range. In these instances, the indicator may provide the user-perceptible feedback such as an alarm, buzzer, vibration or visual indicator (e.g., LED).

FIG. 3 illustrates a system 300 including an aerosol delivery device 100 in wireless communication with a computing device 302 external to the aerosol delivery device (an external computing device). This computing device may also be embodied as a number of different devices, such as any of a number of different mobile computers. More particular examples of suitable mobile computers include portable computers (e.g., laptops, notebooks, tablet computers), mobile phones (e.g., cell phones, smartphones), wearable computers (e.g., smartwatches) and the like. In other examples, the computing device may be embodied as other than a mobile computer, such as in the manner of a desktop computer, server computer or the like.

In some examples, the communication interface 246 of the aerosol delivery device 100 is configured to enable establishment of or connection to a wireless personal area network (WPAN) 304 that includes the computing device 302. Examples of suitable WPAN technologies include those based on or specified by IEEE 802.15 standards, including Bluetooth, Bluetooth low energy (Bluetooth LE), ZigBee, infrared (e.g., IrDA), radio-frequency identification (RFID), Wireless USB and the like. Other examples of suitable WPAN technologies include Wi-Fi Direct, as well as certain other technologies based on or specified by IEEE 802.11 standards and that support direct device-to-device communication.

In some examples, the communication interface 246 of the aerosol delivery device 100 is configured to enable connection to a wireless local area network (WLAN) 306. Examples of suitable WLAN technologies include those based on or specified by IEEE 802.11 standards and marketed as Wi-Fi. The WLAN includes appropriate networking hardware, some of which may be integral and others of which may be separate and interconnected. As shown, for example, the WLAN includes a wireless access point 308 configured to permit wireless devices including the aerosol delivery device 100 and computing device 302 to connect to the WLAN. As also shown, for example, the WLAN may include a gateway device 310 such as a residential gateway configured to connect the WLAN to an external computer network 312 such as a wide area network (WAN) like the Internet. In some examples, the wireless access point or gateway device may include an integrated router to which other systems or devices may be connected. The WLAN may also include other integral or separate and connected networking hardware, such as a network switch, hub, digital subscriber line (DSL) modem, cable modem or the like.

In some examples, the system 300 further includes a service platform 314, which may be embodied as a computer system accessible by the WLAN 306 or external network 312 (as shown). The service platform may include one or more servers, such as may be provided by one or more blade servers, a cloud computing infrastructure or the like. In some examples, the service platform is embodied as a distributed computing apparatus including multiple computing devices, such as may be used to provide a cloud computing infrastructure. And in these examples, the computing devices that form the service platform may be in communication with each other via a network such as the external network.

In some examples, the service platform 314 is accessible by the aerosol delivery device 100 over the WLAN 306 and external network 312, and configured to provide one or more services for a user of the aerosol delivery device and perhaps the users of other aerosol delivery devices. For example, the service platform may be operated by a medical professional, a health, activity or fitness tracking company or organization, or the like. The service platform may enable a user to

access and use various features, such as features for monitoring or tracking the electrocardiogram signal and/or heart rate of the user of the aerosol delivery device.

Similar to the aerosol delivery device 100, in some examples, the service platform 314 is accessible by the computing device 302 over the WLAN 306 and external network 312, although the WLAN or external network may be different between the aerosol delivery device and computing device. The computing device may include or otherwise provide an installed application or other interface through which the service platform may be accessible. This application or other interface may be or may be provided by a thin client and/or other client application, such as a web browser application through which a web page (e.g., service portal) provided by the service platform may be accessible. As another example, the application or other interface may be or may be provided by a dedicated application, such as a mobile app installed on a computing device embodied as a mobile computing device.

In some examples, then, the control component 208 is configured to cause the communication interface 246 to wirelessly communicate the electrocardiogram signal or heart rate to the computing device 302 and/or service platform 314 configured to control operation of at least one of their respective functional elements based on the electrocardiogram signal or heart rate. In more particular examples, the communication interface may be caused to wirelessly communicate the electrocardiogram signal. In these examples, the computing device and/or service platform may calculate the heart rate of the user from the electrocardiogram signal, and control operation of their respective functional element(s) based on the heart rate so calculated.

Similar to the aerosol delivery device 100, functional element(s) of the computing device 302 and/or service platform 314 may be controlled in any of a number of different manners in based on the electrocardiogram signal or heart rate. For example, the computing device may control an indicator 316 (e.g., visual indicator, audio indicator, haptic indicator) to provide a user-perceptible feedback (e.g., visual, audible, haptic feedback), such as a visual readout of the electrocardiogram signal or heart rate, and/or a visual, audible and/or haptic notification that the heart rate is above or below a predefined threshold, or within or outside a predefined range. In another example, the service platform may include a database 318 controlled to store the electrocardiogram signal and/or heart rate for later retrieval, analysis and/or display, such as by the user and/or a medical professional authorized for access by the user. This may also trigger other actions, such as dispatch of an ambulance or a call to an emergency contact in instances in which the heart rate is above or below a predefined threshold.

The foregoing description of use of the article(s) can be applied to the various example implementations described herein through minor modifications, which can be apparent to the person of skill in the art in light of the further disclosure provided herein. The above description of use, however, is not intended to limit the use of the article but is provided to comply with all necessary requirements of disclosure of the present disclosure. Any of the elements shown in the article(s) illustrated in FIGS. 1-5 or as otherwise described above may be included in an aerosol delivery device according to the present disclosure.

Many modifications and other implementations of the disclosure set forth herein will come to mind to one skilled in the art to which this disclosure pertains having the benefit of the teachings presented in the foregoing descriptions and the associated drawings. Therefore, it is to be understood

that the disclosure is not to be limited to the specific implementations disclosed, and that modifications and other implementations are intended to be included within the scope of the appended claims. Moreover, although the foregoing descriptions and the associated drawings describe example implementations in the context of certain example combinations of elements and/or functions, it should be appreciated that different combinations of elements and/or functions may be provided by alternative implementations without departing from the scope of the appended claims. In this regard, for example, different combinations of elements and/or functions than those explicitly described above are also contemplated as may be set forth in some of the appended claims. Although specific terms are employed herein, they are used in a generic and descriptive sense only and not for purposes of limitation.

What is claimed is:

1. An aerosol delivery device comprising:

at least one housing enclosing a reservoir configured to retain an aerosol precursor composition;

a heating element;

a microprocessor configured to operate in an active mode in which the control body is configured to control the heating element to activate and vaporize components of the aerosol precursor composition; and

a heart rate monitor including a plurality of biopotential electrodes affixed to the housing and configured to obtain biopotential measurements from a user, and including signal conditioning circuitry configured to produce an electrocardiogram signal from the biopotential measurements,

wherein the microprocessor is coupled to the signal conditioning circuitry and further configured to control operation of at least one functional element of the aerosol delivery device based on the electrocardiogram signal or a heart rate of the user calculated therefrom.

2. The aerosol delivery device of claim 1, wherein the microprocessor being further configured to control operation of the at least one functional element includes being configured to calculate the heart rate of the user from the electrocardiogram signal, and control operation of the at least one functional element based on the heart rate so calculated.

3. The aerosol delivery device of claim 1, wherein the microprocessor being further configured to control operation of the at least one functional element includes being configured to control an indicator to provide a user-perceptible feedback.

4. The aerosol delivery device of claim 1 further comprising a communication interface configured to enable wireless communication,

wherein the microprocessor being further configured to control operation of the at least one functional element includes being configured to cause the communication interface to wirelessly communicate the electrocardiogram signal or heart rate to a computing device configured to control operation of at least one functional element of the computing device based on the electrocardiogram signal or heart rate.

5. The aerosol delivery device of claim 4, wherein the communication interface being caused to wirelessly communicate the electrocardiogram signal or heart rate includes being caused to wirelessly communicate the electrocardiogram signal, and

wherein the computing device being configured to control operation of the at least one functional element of the computing device includes being configured to calcu-

late the heart rate of the user from the electrocardiogram signal, and control operation of the at least one functional element of the computing device based on the heart rate so calculated.

6. The aerosol delivery device of claim 5, wherein the computing device being configured to control operation of the at least one functional element of the computing device includes being configured to control an indicator of the computing device to provide a user-perceptible feedback.

7. The aerosol delivery device of claim 1 further comprising a communication interface configured to enable wireless communication with a service platform over at least one network including a wireless local area network (WLAN),

wherein the microprocessor being further configured to control operation of the at least one functional element includes being configured to cause the communication interface to wirelessly communicate the electrocardiogram signal or heart rate to the service platform for storage in a database.

8. The aerosol delivery device of claim 7, wherein the microprocessor is configured to cause the communication interface to wirelessly communicate the electrocardiogram signal or heart rate to the service platform to further enable a medical professional to monitor or track the electrocardiogram signal or heart rate.

9. The aerosol delivery device of claim 1, wherein the aerosol precursor composition comprises glycerin and nicotine.

10. A control body coupled or coupleable with a cartridge to form an aerosol delivery device, the cartridge being equipped with a heating element and containing an aerosol precursor composition, the control body comprising:

a housing;

a microprocessor configured to operate in an active mode in which the control body is coupled with the cartridge, the microprocessor in the active mode being configured to control the heating element to activate and vaporize components of the aerosol precursor composition; and

a heart rate monitor including a plurality of biopotential electrodes affixed to the housing and configured to obtain biopotential measurements from a user, and including signal conditioning circuitry configured to produce an electrocardiogram signal from the biopotential measurements,

wherein the microprocessor is coupled to the signal conditioning circuitry and further configured to control operation of at least one functional element of the control body or the aerosol delivery device based on the electrocardiogram signal or a heart rate of the user calculated therefrom.

11. The control body of claim 10, wherein the microprocessor being further configured to control operation of the at least one functional element includes being configured to calculate the heart rate of the user from the electrocardiogram signal, and control operation of the at least one functional element based on the heart rate so calculated.

12. The control body of claim 10, wherein the microprocessor being further configured to control operation of the at least one functional element includes being configured to control an indicator to provide a user-perceptible feedback.

13. The control body of claim 10 further comprising a communication interface configured to enable wireless communication,

wherein the microprocessor being further configured to control operation of the at least one functional element includes being configured to cause the communication

19

interface to wirelessly communicate the electrocardiogram signal or heart rate to an computing device configured to control operation of at least one functional element of the computing device based on the electrocardiogram signal or heart rate.

14. The control body of claim **13**, wherein the communication interface being caused to wirelessly communicate the electrocardiogram signal or heart rate includes being caused to wirelessly communicate the electrocardiogram signal, and

wherein the computing device being configured to control operation of the at least one functional element of the computing device includes being configured to calculate the heart rate of the user from the electrocardiogram signal, and control operation of the at least one functional element of the computing device based on the heart rate so calculated.

15. The control body of claim **14**, wherein the computing device being configured to control operation of the at least one functional element of the computing device includes

20

being configured to control an indicator of the computing device to provide a user-perceptible feedback.

16. The control body of claim **10** further comprising a communication interface configured to enable wireless communication with a service platform over at least one network including a wireless local area network (WLAN),

wherein the microprocessor being further configured to control operation of the at least one functional element includes being configured to cause the communication interface to wirelessly communicate the electrocardiogram signal or heart rate to the service platform for storage in a database.

17. The control body of claim **16**, wherein the microprocessor is configured to cause the communication interface to wirelessly communicate the electrocardiogram signal or heart rate to the service platform to further enable a medical professional to monitor or track the electrocardiogram signal or heart rate.

18. The control body of claim **10**, wherein the aerosol precursor composition comprises glycerin and nicotine.

* * * * *

专利名称(译)	气雾剂输送装置的心率监测器		
公开(公告)号	US10517330	公开(公告)日	2019-12-31
申请号	US15/602932	申请日	2017-05-23
[标]申请(专利权)人(译)	R.J.雷诺兹烟草公司		
申请(专利权)人(译)	RAI战略投资者持股，INC.		
[标]发明人	SUR RAJESH		
发明人	SUR, RAJESH		
IPC分类号	A24B15/16 A61B5/0245 A61B5/02 H05B1/02 A61B5/0402 A61B5/024 A61M15/06 A24F47/00 A61B5/00 H04W84/12 F23Q7/00		
CPC分类号	A61B5/02438 A61B5/0006 A61B5/6887 A61B5/0402 A61B5/024 H05B1/02 A24B15/167 A61B5/02 A24F47/008 A61B5/0245 H04W84/12 F23Q2007/002 A61B5/0022		
其他公开文献	US20180338527A1		
外部链接	Espacenet		

摘要(译)

提供了一种气雾剂输送装置，其包括至少一个壳体，该壳体包围被构造保持气雾剂前体组合物的储器。该装置包括加热元件和配置为以主动模式操作的微处理器，其中控制体被配置为控制加热元件以活化和气雾化气溶胶前体组合物的组分。并且该设备包括心率监测器，该心率监测器包括多个生物电势电极，该多个生物电势电极固定到壳体并且被配置为从用户获得生物电势测量值，并且包括信号调节电路，该信号调节电路被配置为从生物电势测量值产生心电图信号。所述微处理器耦合到所述信号调节电路，并且进一步被配置为基于所述心电图信号或由此计算出的用户的心率来控制所述气雾剂输送装置的至少一个功能元件的操作。

