



US 20150208988A1

(19) **United States**(12) **Patent Application Publication**
Zhu et al.(10) **Pub. No.: US 2015/0208988 A1**(43) **Pub. Date: Jul. 30, 2015**(54) **DETECTING INDICATIONS OF
INTRADIALYTIC MORBID EVENTS BY
MEASUREMENT OF RELATIVE BLOOD
VOLUME, BLOOD PRESSURE AND HEART
RATE****Publication Classification**(51) **Int. Cl.***A61B 5/00* (2006.01)*A61M 1/16* (2006.01)(52) **U.S. Cl.**CPC *A61B 5/746* (2013.01); *A61M 1/1603*
(2014.02)(71) Applicant: **Fresenius Medical Care Holdings, Inc.**,
Waltham, MA (US)(72) Inventors: **Fansan Zhu**, Flushing, NY (US); **Peter
Kotanko**, New York, NY (US); **Stephan
Thijssen**, New York, NY (US); **Nathan
W. Levin**, New York, NY (US)(21) Appl. No.: **14/424,005**(22) PCT Filed: **Aug. 27, 2013**(86) PCT No.: **PCT/US2013/056769**


§ 371 (c)(1),

(2) Date: **Feb. 25, 2015****Related U.S. Application Data**(60) Provisional application No. 61/694,149, filed on Aug.
28, 2012.

(57)

ABSTRACT

A method of detecting an indication of a potential intradialytic morbid event (IME) by monitoring a patient's condition during excess fluid removal by ultrafiltration during a hemodialysis treatment includes determining the patient's relative blood volume (RBV), and removing a portion of the volume of excess fluid from blood of the patient at an initial ultrafiltration rate while periodically monitoring a second derivative over time of the relative blood volume (SDRBV). The method then includes continuing to remove excess fluid from blood of the patient at the same ultrafiltration rate, or, optionally, incrementally increasing the ultrafiltration rate. The method further includes triggering an alarm for an IME for the patient if the SDRBV is in a range of between a low SDRBV alarm level and a high SDRBV alarm level, and, alternatively or additionally monitoring the patient's normalized blood pressure ratio, and taking a remedial action if the alarm is triggered.






FIG. 1A




FIG. 1B




FIG. 2




FIG. 3




FIG. 4




FIG. 5




FIG. 6




FIG. 7




FIG. 8




FIG. 9




FIG 10

DETECTING INDICATIONS OF INTRADIALYTIC MORBID EVENTS BY MEASUREMENT OF RELATIVE BLOOD VOLUME, BLOOD PRESSURE AND HEART RATE

RELATED APPLICATIONS

[0001] This application claims the benefit of U.S. Provisional Application No. 61/694,149, filed on Aug. 28, 2012. The entire teachings of this application are incorporated herein by reference.

BACKGROUND OF THE INVENTION

[0002] Prediction of an intradialytic morbid event (IME) during hemodialysis (HD) is difficult in clinical practice because no reliable and accurate technique is available. An IME is typically defined by a patient's systolic blood pressure (SBP) decreasing to less than about 90 mmHg and a heart rate (HR) greater than about 100 beats/min with muscle cramps, dizziness or fainting of the patient, often leading to the need to discontinue ultrafiltration before the end of an HD treatment. Monitoring of relative blood volume (RBV) by means of a device such as CRIT-LINE™ (Hema Metrics, Kaysville, Utah, see U.S. Pat. No. 5,803,908) or blood volume monitor (BVM, Fresenius AG, Germany) has been used to assess critical thresholds of RBV which may indicate the risk of an IME. See C. Barth, W. Boer, D. Garzoni, T. Kuenzi, W. Ries, R. Schaefer, D. Schneditz, T. Tsobanelis, F. van der Sande, R. Wojke, H. Schilling, and J. Passlick-Deetjen, "Characteristics of hypotension-prone haemodialysis patients: is there a critical relative blood volume?," *Nephrol Dial Transplant*, vol. 18, pp. 1353-60, Jul 2003. However, the relationship between a change in RBV and an IME depends on multiple factors including, but not limited to, ultrafiltration rate (UFR), degree of fluid overload, plasma refilling rate, and autonomic nervous system control. For this reason, measurement of changes in RBV alone fails to reliably predict an IME. See D. N. Reddan, L. A. Szczech, V. Hasselblad, E. G. Lowrie, R. M. Lindsay, J. Himmelfarb, R. D. Toto, J. Stivelman, J. F. Winchester, L. A. Zillman, R. M. Califf, and W. F. Owen, Jr., "Intradialytic blood volume monitoring in ambulatory hemodialysis patients: a randomized trial," *J Am Soc Nephrol*, vol. 16, pp. 2162-9, July 2005.

[0003] Therefore, there is a need for a more reliable method of predicting the occurrence of an IME in a patient having excess fluid removed by ultrafiltration during a hemodialysis treatment.

SUMMARY OF THE INVENTION

[0004] In one embodiment, a method of detecting an indication of a potential intradialytic morbid event (IME) by monitoring a patient's condition during excess fluid removal by ultrafiltration during a hemodialysis treatment includes establishing an initial ultrafiltration rate of fluid removal, determining the patient's relative blood volume (RBV), and removing a portion of the volume of excess fluid from blood of the patient at the initial ultrafiltration rate while periodically monitoring the second derivative of the patient's relative blood volume (SDRBV) over time, which can be calculated from $d^2(RBV)/dt^2$.

[0005] In a preferred embodiment, the method can further include monitoring the patient's normalized blood pressure ratio, and triggering an alarm for a potential IME for the

patient if the SDRBV is in a range of between a low SDRBV alarm level and a high SDRBV alarm level and if the normalized blood pressure ratio is less than a ratio alarm level.

[0006] In an alternative embodiment, the method can include independently monitoring the normalized blood pressure ratio, and triggering an alarm for a potential IME for the patient if the ratio is less than a ratio alarm level.

[0007] The low SDRBV alarm level can be about $-0.08\%/min^2$. The high SDRBV alarm level can be about $-0.035\%/min^2$. The ratio alarm level can be about 0.019 min/beat for a diastolic blood pressure greater than 50 mmHg, or about 0.02 min/beat for a diastolic blood pressure less than 50 mmHg.

[0008] The method then includes continuing to remove excess fluid from blood of the patient at the same ultrafiltration rate, or, optionally, incrementally increasing the ultrafiltration rate. The method then includes taking a remedial action if the alarm is triggered. The remedial action can be decreasing the ultrafiltration rate, infusion of fluid into the patient, compressing lower extremities of the patient, and/or changing the position of the patient, such as placing the patient in the Trendelenburg position or raising the patient's legs, or a combination of these remedial actions.

[0009] In another embodiment, a method of detecting an indication of a potential intradialytic morbid event (IME) by monitoring a patient's condition during excess fluid removal by ultrafiltration during a hemodialysis treatment includes the computer implemented steps of establishing an initial ultrafiltration rate of fluid removal, determining the patient's relative blood volume (RBV), and removing a portion of the volume of excess fluid from blood of the patient at the initial ultrafiltration rate while periodically monitoring the second derivative of the patient's relative blood volume (SDRBV) over time, which can be calculated from $d^2(RBV)/dt^2$. The method then includes continuing to remove excess fluid from blood of the patient at the same ultrafiltration rate, or, optionally, incrementally increasing the ultrafiltration rate.

[0010] In a preferred embodiment, the computer implemented method can further include monitoring the patient's normalized blood pressure ratio, and triggering an alarm for a potential IME for the patient if the SDRBV is in a range of between a low SDRBV alarm level and a high SDRBV alarm level and if the normalized blood pressure ratio is less than a ratio alarm level.

[0011] Some of the above methods can be incorporated into a hemodialysis system and/or procedure, and include many advantages including the ability to reliably predict an IME prior to its occurrence in a timely fashion and thereby prevent its occurrence while optimizing the removal of excess fluid from a hemodialysis patient.

BRIEF DESCRIPTION OF THE DRAWINGS

[0012] The foregoing will be apparent from the following more particular description of example embodiments of the invention, as illustrated in the accompanying drawings. The drawings are not necessarily to scale, emphasis instead being placed upon illustrating embodiments of the present invention.

[0013] FIG. 1A is a graph of relative blood volume percent RBV [%] (left axis) and the first derivative of RBV, FDRBV [%/min] and second derivative of RBV, SDRBV [%/min²] (right axis) as a function of time [min] illustrating data from a hemodialysis patient that experienced an IME. The line of circles represents the patient's RBV curve, the line of squares represents the patient's FDRBV, and the line of triangles

represents the patient's SDRBV as a function of time. Variation in the data is reduced with SDRBV. The patient had an IME at 180 min of hemodialysis and ultrafiltration was stopped at 190 min due to hypotensive symptoms.

[0014] FIG. 1B is a graph of relative blood volume percent RBV [%] (left axis) and first derivative of RBV, FDRBV [%/min] and second derivative of RBV, SDRBV [%/min²] (right axis) as a function of time [min] for a hemodialysis patient without an IME during removal of excess fluid by ultrafiltration.

[0015] FIG. 2 is a flow chart of the integration of systolic blood pressure (SBP), diastolic blood pressure (DBP), and heart rate (HR) according to this invention.

[0016] FIG. 3 is a flowchart used for predicting an IME with two criteria according to this invention. The first criteria includes monitoring RBV and calculating SDRBV every 5 minutes. If $-0.08 < \text{SDRBV}_i < -0.035$ at i th minutes, then for the second criteria, SBP, DBP and HR are immediately measured and SDH is calculated. If $\text{SDH}_i < \text{SDH}_{\text{Threshold}}$, a signal for predicting an IME will be sent. SDH is also monitored every 10 minutes. If $\text{SDH} < \text{SDH}_{\text{Threshold}}$, a signal for predicting an IME will be sent.

[0017] FIG. 4 is a graph of SBP/DBP/HR [1/min], referred herein as the SDH ratio, showing a comparison, for patients that experienced an IME, between an average of the SDH ratio during the first 30 min, when an IME did not occur (thus establishing a baseline (BL)), and the time when an IME occurred, as predicted by the methods according to this invention.

[0018] FIG. 5 is a graph of the SDH ratio [min/beat] comparing two groups of patients: no IME and IME.

[0019] FIG. 6 is a graph of results of a predicted IME using the algorithm combining SDRBV and SDH. 59.7% and 40.3% of actual IMEs (124) were predicted and missed, respectively, by the methods according to this invention.

[0020] FIG. 7 is a graph of percentage of the number of patients with no IMEs (121) recorded in the study identified (23%) with IME (false positive) by the model.

[0021] However, 77% of patients with no recorded IMEs (121) were identified as having no IMEs by the methods according to this invention.

[0022] FIG. 8 is a graph showing that the average interval between the prediction and occurrence of an IME time for patient data studied was -30.8 ± 36 minutes with monitoring only SDRBV by the methods according to this invention.

[0023] FIG. 9 is a graph showing that the average interval between the prediction and occurrence of an IME time for patient data studied was 13.3 ± 11 minutes with monitoring the combination of SDRBV and SDH by the methods according to this invention.

[0024] FIG. 10 is a block diagram of a computer apparatus implementing methods of the present invention.

DETAILED DESCRIPTION OF THE INVENTION

[0025] In one embodiment, a method of detecting an indication of a potential intradialytic morbid event (IME) by monitoring a patient's condition during excess fluid removal by ultrafiltration during a hemodialysis treatment includes establishing an initial ultrafiltration rate (UFR) of fluid removal, determining the patient's relative blood volume (RBV), and removing a portion of the volume of excess fluid from blood of the patient at the initial ultrafiltration rate while periodically monitoring the second derivative of the patient's relative blood volume (SDRBV) over time, which can be

calculated from $d^2(\text{RBV})/dt^2$. Monitoring over time can be, for example, every 5 minutes. The method then includes continuing to remove excess fluid from blood of the patient at the same ultrafiltration rate, or, optionally, incrementally increasing the ultrafiltration rate by, for example, about 10%. The ultrafiltration rate can be, for example, increased up to the rate required to remove the clinically indicated (i.e., physician prescribed) amount of excess fluid from the patient over the hemodialysis treatment time.

[0026] In a preferred embodiment, the method can further include monitoring the patient's normalized blood pressure ratio, and triggering an alarm for a potential IME for the patient if the SDRBV is in a range of between a low SDRBV alarm level and a high SDRBV alarm level and if the normalized blood pressure ratio is less than a ratio alarm level. The method then includes taking a remedial action if the alarm is triggered. The low SDRBV alarm level can be about $-0.08\%/min^2$. The high SDRBV alarm level can be about $-0.035\%/min^2$. The normalized blood pressure ratio (SDH) is calculated using the patient's systolic blood pressure (SBP), diastolic blood pressure (DBP), and heart rate (HR), and calculating the ratio $\text{SDH} = (\text{SBP}/\text{DBP})/\text{HR}$.

[0027] In an alternative embodiment, the method can include independently monitoring the ratio, and triggering an alarm for a potential IME for the patient if the ratio is less than a ratio alarm level. The ratio alarm level can be about 0.019 min/beat for a diastolic blood pressure greater than 50 mmHg, or about 0.02 min/beat for a diastolic blood pressure less than 50 mmHg. The ratio can be monitored periodically, such as, for example, every 10 minutes.

[0028] The remedial action can be decreasing the ultrafiltration rate (e.g., by about 5-10%), or infusion of fluid into the patient, or compressing lower extremities of the patient (e.g., by application of a compression device, such as, for example Kendall 7325, Covidien, Mansfield, Mass.), or changing the position of the patient, such as placing the patient in the Trendelenburg position, or raising the patient's legs, or a combination of these remedial actions. Some of the above methods can be incorporated into a hemodialysis system and/or procedure. See Handbook of Dialysis, J. T. Daugirdas, P. G. Blake, and T. S. Ing, 4th Edition, p. 59-78 (2007).

[0029] Two principal criteria to predict IME are considered in the present application: (a) the second derivative of RBV and (b) blood pressure (BP) combined with heart rate (HR).

1. Second Derivative of RBV Criterion

[0030] Using the FDRBV or slope of the RBV ($d(\text{RBV})/dt$) in the first 30 min of HD to predict an IME has been discussed in previous publications. See e.g., Titapiccolo, et al, 32nd Annual International Conference of the IEEE EMBS, 2010. A recent study showed that the slope of the RBV in the first 30 min of hemodialysis is significantly higher than at the end of treatment in patients that develop an IME. See E. Seibert, F. Zhu, M. K. Kuhlmann, R. Henson, A. M. Oribello, M. Girndt, P. Kotanko, and N. W. Levin, "Slope analysis of blood volume and calf bioimpedance monitoring in hemodialysis patients," *Nephrol. Dial. Transplant.*, 27(12):4430-6, (2012). As shown in Eq.1, the first derivative or slope of RBV (FDRBV or sRBV) indicates the difference between plasma refilling rate (PRR ml/min) and ultrafiltration rate (UFR ml/min). In principle, an IME might occur when the PRR is less than the UFR. In practice, however, an individual UFR may not be constant even in the same treatment so that the FDRBV is difficult to standardize sufficiently to be useful in clinical practice.

Therefore, a method to use the second derivative of RBV (SDRBV) to calculate change in PRR (Eq. 2) is disclosed herein. The major advantage of this method is that it is independently monitoring the change in PRR.

$$\frac{dRBV}{dt} = \frac{1}{BV_0} [PRR - UFR] \quad \text{Eq. 1}$$

$$\frac{d^2RBV}{dt^2} = \frac{1}{BV_0} d[PRR - UFR]/dt = \frac{dPRR/dt}{BV_0} \quad \text{Eq. 2}$$

[0031] In Eq. 1, RBV represents relative blood volume calculated by change in absolute blood volume (BV) divided by initial BV_0 , where PRR represents plasma refilling rate. In Eq. 2, the second derivative of RBV (SDRBV) can be written as the derivative of RBV slope ($d^2(RBV)/dt^2$, %/min²), which represents change in PRR, with UFR and BV_0 considered constant. To simplify notation, SDRBV will be used to represent the second derivative of RBV in this application.

2. SDH Criterion

[0032] The SDH ratio is defined as the ratio of systolic BP (SBP; mmHg) to diastolic BP (DBP; mmHg) divided by heart rate (HR; beat/min) as follows:

$$SDH [\text{min/beat}] = (SBP/DBP)/HR \quad \text{Eq. 3}$$

[0033] The integrated assessment of SBP, DBP, and HR is illustrated in FIG. 2. Note that the interpretation of SDH depends on the level of DBP, so that with $DBP \geq 50$ mmHg the $SDH_{Threshold}$ is 0.019 [beat/min], and with $DBP < 50$ mmHg the $SDH_{Threshold}$ is 0.02 [beat/min]. For example, in a patient with DBP of 90 mmHg and a SDH of 0.015 [beat/min] the risk of IME is higher compared to a patient with the same DBP but an SDH of 0.025 [beat/min].

[0034] Without wishing to be bound by any particular theory, the rationale for the SDH ratio is thought to be as follows: in the majority of IMEs (and per definition in all cases of intradialytic hypotension (IDH)), blood pressure (BP) is reduced. Physiologically, an initial drop in BP is counteracted by a rise in HR in an effort to maintain cardiac output and BP; actually, the relative increase in HR is more pronounced than the relative decrease in BP. For this reason a ratio of BP over HR may provide an augmented signal. However, levels of absolute BP vary greatly among HD patients (SBP: 70-250 mmHg; DBP: 40-150 mmHg). The ratio of SBP to DBP shows less variability. In a recent study, it was found that the ratio of SBP to DBP at beginning of HD differs between patients with IME (SBP/DBP: 0.024 ± 0.004) and without (0.025 ± 0.005) IME (Zhu et al. 49th ERA-EDTA Congress, 2012). Moreover, the differentiation between patients with and without an IME can be improved by the use of SDH in addition to the SDRBV discussed above.

3. A Flowchart Combining SDRBV and SDH

[0035] It is general knowledge that rapid reduction of blood volume by a higher UFR is the major cause of an IME. SDRBV can show the change in relative blood volume as (%/min²), while the SDH indicates individual tolerance for an IME according to information about blood pressure and heart rate. Since reduction of blood volume is the primary factor for a possible IME, monitoring RBV slope is the first criterion. If the SDRBV is in the range between the values of the SDRBV_i

criteria ($-0.08 < SDRBV_i < 0.035$, i represents any time) at the time i, and SDH_i is less than the $SDH_{Threshold}$ ($SDH_i < SDH_{Threshold}$), then an IME can be predicted.

[0036] FIG. 3 illustrates a flowchart for prediction of a potential IME during the treatment. The criteria of SDH and SDRBV are observed from experimental data. A person of skill in the art can obtain revised numerical values for the SDH and SDRBV criteria from additional and/or different experimental data. As shown in FIG. 3, a method 100 of detecting an indication of a potential intradialytic morbid event (IME) in a patient having excess fluid removed by ultrafiltration during a hemodialysis treatment includes setting an initial UFR at step 105, then, at step 110, checking the ultrafiltration rate and optionally adjusting the ultrafiltration rate as clinically indicated. The method then includes at step 120 determining the patient's relative blood volume (RBV) periodically (e.g., every 5 minutes), monitoring a second derivative of the relative blood volume (SDRBV) over time, which can be calculated from $d^2(RBV)/dt^2$. If, at step 130, the SDRBV is in a range of between a low SDRBV alarm level and a high SDRBV alarm level, and, at step 140, if the patient's normalized blood pressure ratio SDH is less than a SDH alarm level, wherein the SDH is calculated from the patient's systolic blood pressure (SBP), diastolic blood pressure (DBP), and heart rate (HR), using the formula $SDH = (SBP/DBP)/HR$, then the method includes triggering an alarm at step 150 and, if, at step 160, the treatment time is not at an end, taking a remedial action at step 170 and incrementing the time i at step 175 and continuing to check and/or adjust the UFR at step 110 as appropriate. Adjusting the UFR can include increasing or decreasing the UFR (e.g., by about 10%). As shown in FIG. 3, the treatment ends at step 180 once the treatment time is reached. The low SDRBV alarm level can be about $-0.08\%/min^2$. The high SDRBV alarm level can be about $-0.035\%/min^2$. The SDH alarm level can be about 0.019 min/beat for a diastolic blood pressure greater than 50 mmHg, or about 0.02 min/beat for a diastolic blood pressure less than 50 mmHg.

[0037] The method 100 can further include periodically monitoring, at step 125, the patient's systolic blood pressure (SBP), diastolic blood pressure (DBP), heart rate (HR), and a normalized blood pressure ratio $SDH = (SBP/DBP)/HR$, and, at step 135, if the SDH is less than a SDH alarm level, triggering an alarm at step 150 for an IME for the patient, as described above. At step 125, the SDH can be monitored periodically, such as, for example, every 10 minutes.

4. Pre-Processing of RBV Data

[0038] RBV raw data can be influenced by several factors not associated with the change in the plasma refilling rate. One of the potential interferences is a rapid change in the RBV curve which could result from sudden vasoconstriction, shown as high frequency noise. To reduce this noise, a low-pass filter with a moving average method was used to smooth the RBV curve before calculation of the first derivative of the RBV (FDRBV) and the second derivative of the RBV (SDRBV). The other source of error from RBV raw data was a sudden change in body position of the patient during the measurement. This error can produce about -0.08 to $-0.1\%/min^2$ variation in the curve of SDRBV. To reduce this error, when the value of SDRBV was less than -0.08 , it was considered as interference and was not utilized for data analysis. Accordingly, in this study the criterion for IME has been set as a range: $-0.08 < SDRBV_i < -0.035$, %/min². A person of

skill in the art can obtain different numerical values for the SDRBV and SDH alarm levels from additional studies and error analysis.

5. Computer Implementation

[0039] In another embodiment, a method of detecting an indication of a potential intradialytic morbid event (IME) by monitoring a patient's condition during excess fluid removal by ultrafiltration during a hemodialysis treatment includes the computer implemented steps of establishing an initial ultrafiltration rate of fluid removal, determining the patient's relative blood volume (RBV), and removing a portion of the volume of excess fluid from blood of the patient at the initial ultrafiltration rate while periodically monitoring the second derivative of the patient's relative blood volume (SDRBV) over time, which can be calculated from $d^2(\text{RBV})/dt^2$. The method then includes continuing to remove excess fluid from blood of the patient at the same ultrafiltration rate, or, optionally, incrementally increasing the ultrafiltration rate.

[0040] In a preferred embodiment, the method can further include monitoring the patient's normalized blood pressure ratio, and triggering an alarm for a potential IME for the patient if the SDRBV is in a range of between a low SDRBV alarm level and a high SDRBV alarm level and if the normalized blood pressure ratio is less than a ratio alarm level.

[0041] One or more computers **50** execute the program code and can be of a variety of computer architectures such as client-server, standalone processor, networked or distributed processor. FIG. 10 is a diagram of the internal structure of a computer **50** in a computer network or other computer based environment in which the present invention can be implemented. Each computer **50** contains system bus **79**, where a bus is a set of hardware lines used for data transfer among the components of a computer or processing system. Bus **79** is essentially a shared conduit that connects different elements of a computer system (e.g., processor, disk storage, memory, input/output ports, network ports, etc.) that enables the transfer of information between the elements. Attached to system bus **79** is I/O device interface **82** for connecting various input and output devices (e.g., keyboard, mouse, displays, printers, speakers, etc.) to the computer **50**. Network interface **86** allows the computer to connect to various other devices attached to a network (e.g., global computer network, local area network, wide area network, and the like). Memory **90** provides volatile storage for computer software instructions **92** and data **94** used to implement an embodiment of the present invention (e.g., the flowchart shown in FIG. 3 and detailed above). Disk storage **95** provides non-volatile storage for computer software instructions **92** and data **94** used to implement an embodiment of the present invention. Central processor unit **84** is also attached to system bus **79** and provides for the execution of computer instructions.

[0042] In one embodiment, the processor routines **92** and data **94** are a computer program product (generally referenced **92**), including a computer readable medium (e.g., a removable storage medium such as one or more DVD-ROM's, CD-ROM's, diskettes, tapes, etc.) that provides at least a portion of the software instructions for the invention system. Computer program product **92** can be installed by any suitable software installation procedure, as is well known in the art. In another embodiment, at least a portion of the software instructions may also be downloaded over a cable, communication and/or wireless connection. In other embodiments, the invention programs are a computer program propa-

gated signal product embodied on a propagated signal on a propagation medium (e.g., a radio wave, an infrared wave, a laser wave, a sound wave, or an electrical wave propagated over a global network such as the Internet, or other network (s)). Such carrier medium or signals provide at least a portion of the software instructions for the present invention routines/program **92**.

[0043] In alternate embodiments, the propagated signal is an analog carrier wave or digital signal carried on the propagated medium. For example, the propagated signal may be a digitized signal propagated over a global network (e.g., the Internet), a telecommunications network, or other network. In one embodiment, the propagated signal is a signal that is transmitted over the propagation medium over a period of time, such as the instructions for a software application sent in packets over a network over a period of milliseconds, seconds, minutes, or longer. In another embodiment, the computer readable medium of computer program product **92** is a propagation medium that the computer system **50** may receive and read, such as by receiving the propagation medium and identifying a propagated signal embodied in the propagation medium, as described above for computer program propagated signal product.

[0044] Generally speaking, the term "carrier medium" or transient carrier encompasses the foregoing transient signals, propagated signals, propagated medium, storage medium and the like.

Exemplification

[0045] Preliminary results were analyzed from 45 patients with 245 measurements (average age 55.7 ± 14 years, average height 167.7 ± 10 cm, average pre-dialysis Wt 79.3 ± 16.6 kg and average post-dialysis Wt 76.3 ± 16 kg) with the algorithm shown in FIG. 3. The average value of SDH was higher in the first 30 minutes of measurement, when no IME occurred (thus providing a baseline (BL)), than in the time when an IME occurred as predicted by the model, as shown in FIG. 4. In a total of 245 treatments, IMEs were recorded in 124 treatments with different aspects of IME such as ultrafiltration (UF) stopped, SBP < 90 mmHg and HR > 100 beats /min with muscle cramps, dizziness or fainting.

[0046] With the SDRBV model only, as shown in FIG. 8, prediction of the time for the IME is given ahead about 30.8 ± 36 minutes (minimum: -193.4, maximum: 36.1, Q1: -35.6, Q2 (median): -21.8, Q3: -10.4, 95% CI: -38.3--36.1) before an IME occurred. When using the combination of SDRBV and SDH, as shown in FIG. 9, the prediction of time for an IME to occur was reduced to 13.3 ± 11 minutes (minimum: -45.5, maximum: 0, Q1: -19.8, Q2 (median): -10, Q3: -6.2, 95% CI: -15.9--10.8), which reflects the reduced variability of predicted time by reducing the coefficient of variation (CV), where $CV = \text{standard deviation}/\text{mean}$. The shorter prediction of the time is an acceptable tradeoff for the increase in sensitivity of prediction of an IME from 62.3% by using the SDRBV alone to 72.5% by using the combined SDRBV and SDH. The results are summarized in Table 1. Dotted lines in FIGS. 8 and 9 represent the time when UF was stopped. Each dot represents predicting time of IME by the model in individual treatments. It should be noted that the prediction time is based on the time of IME.

TABLE 1

Summary of prediction of IME with three methods							
	Number	SDRBV + SDH		SDRBV only		SDH only	
		Yes	No	Yes	No	Yes	No
IME	124	74	50	114	10	83	41
No IME	121	28	93	69	52	54	67
Sensitivity, %		72.5		62.3		60.6	
Specificity, %		65		83.9		38	

[0047] Summary (Table 1) of prediction of IMEs with SDRBV, SDH and combination of SDRBV and SDH method shows that the best prediction of IME can be obtained with SDRBV+SDH.

[0048] The relevant teachings of all patents, published applications and references cited herein are incorporated by reference in their entirety.

[0049] While this invention has been particularly shown and described with references to example embodiments thereof, it will be understood by those skilled in the art that various changes in form and details may be made therein without departing from the scope of the invention encompassed by the appended claims.

1. A method of detecting an indication of a potential intradialytic morbid event (IME) by monitoring a patient's condition during excess fluid removal by ultrafiltration during a hemodialysis treatment, the method comprising:

- i) establishing an initial ultrafiltration rate of fluid removal;
- ii) determining the patient's relative blood volume (RBV);
- iii) removing a portion of the volume of excess fluid from blood of the patient at the initial ultrafiltration rate while periodically monitoring: a second derivative of the relative blood volume over time (SDRBV);
- iv) continuing to remove excess fluid from blood of the patient at the same ultrafiltration rate, or, optionally, incrementally increasing the ultrafiltration rate;
- v) if the SDRBV is in a range of between a low SDRBV alarm level and a high SDRBV alarm level, triggering an alarm for a potential IME for the patient; and
- vi) taking a remedial action if the alarm is triggered.

2. The method of claim 1, wherein the low SDRBV level is about $-0.08\%/min^2$.

3. The method of claim 2, wherein the high SDRBV alarm level is about $-0.035\%/min^2$.

4. The method of claim 3, further including monitoring the patient's normalized blood pressure ratio.

5. The method of claim 4, wherein further including triggering an alarm for a potential IME for the patient if the SDRBV is in a range of between a low SDRBV alarm level and a high SDRBV alarm level and if the normalized blood pressure ratio is less than a ratio alarm level.

6. The method of claim 5, wherein, wherein the ratio alarm level is about 0.019 min/beat for a diastolic blood pressure greater than 50 mmHg.

7. The method of claim 5, wherein the ratio alarm level is about 0.02 min/beat for a diastolic blood pressure less than 50 mmHg.

8. The method of claim 1, wherein the remedial action is decreasing the ultrafiltration rate.

9. The method of claim 1, wherein the remedial action is infusion of fluid into the patient.

10. The method of claim 1, wherein the remedial action is increasing pressure on lower extremities of the patient.

11. The method of claim 1, wherein the remedial action is changing the position of the patient.

12. The method of claim 11, wherein the remedial action is selected from placing the patient in the Trendelenburg position and raising the patient's legs.

13. A method of detecting an indication of a potential intradialytic morbid event (IME) by monitoring a patient's condition during excess fluid removal by ultrafiltration during a hemodialysis treatment, the method comprising:

- i) establishing an initial ultrafiltration rate of fluid removal;
- ii) determining the patient's systolic blood pressure (SBP), diastolic blood pressure (DBP), and heart rate (HR);
- iii) removing a portion of the volume of excess fluid from blood of the patient at the initial ultrafiltration rate while periodically monitoring a normalized blood pressure ratio calculated using the patient's systolic and diastolic blood pressure and heart rate data obtained in step ii);
- iv) continuing to remove excess fluid from blood of the patient at the same ultrafiltration rate, or, optionally, incrementally increasing the ultrafiltration rate;
- v) if the ratio is less than a ratio alarm level, triggering an alarm for a potential IME for the patient; and
- vi) taking a remedial action if the alarm is triggered.

14. The method of claim 13, wherein, wherein the ratio alarm level is about 0.019 min/beat for a diastolic blood pressure greater than 50 mmHg.

15. The method of claim 14, wherein the ratio alarm level is about 0.02 min/beat for a diastolic blood pressure less than 50 mmHg.

16. The method of claim 15, wherein the remedial action is decreasing the ultrafiltration rate.

17. The method of claim 15, wherein the remedial action is infusion of fluid into the patient.

18. The method of claim 15, wherein the remedial action is increasing pressure on lower extremities of the patient.

19. The method of claim 15, wherein the remedial action is changing the position of the patient.

20. The method of claim 19, wherein the remedial action is selected from placing the patient in the Trendelenburg position and raising the patient's legs.

21. A method of detecting an indication of a potential intradialytic morbid event (IME) by monitoring a patient's condition during excess fluid removal by ultrafiltration during a hemodialysis treatment, the method comprising the computer implemented steps of:

- i) establishing an initial ultrafiltration rate of fluid removal;
- ii) determining the patient's relative blood volume (RBV);
- iii) removing a portion of the volume of excess fluid from blood of the patient at the initial ultrafiltration rate while periodically monitoring: a second derivative of the relative blood volume over time (SDRBV);
- iv) continuing to remove excess fluid from blood of the patient at the same ultrafiltration rate, or, optionally, incrementally increasing the ultrafiltration rate;
- v) if the SDRBV is in a range of between a low SDRBV alarm level and a high SDRBV alarm level, triggering an alarm for a potential IME for the patient; and
- vi) taking a remedial action if the alarm is triggered.

22. The method of claim 21, wherein the low SDRBV alarm level is about $-0.08\%/min^2$.

23. The method of claim 22, wherein the high SDRBV alarm level is about $-0.035\%/min^2$.

24. The method of claim 23, further including monitoring the patient's normalized blood pressure ratio.

25. The method of claim 24, wherein further including triggering an alarm for a potential IME for the patient if the SDRBV is in a range of between a low SDRBV alarm level and a high SDRBV alarm level and if the normalized blood pressure ratio is less than a ratio alarm level.

26. The method of claim 25, wherein the ratio alarm level is about 0.019 min/beat for a diastolic blood pressure greater than 50 mmHg.

27. The method of claim 25, wherein the ratio alarm level is about 0.02 min/beat for a diastolic blood pressure less than 50 mmHg.

28. The method of claim 27, wherein the remedial action is decreasing the ultrafiltration rate.

29. The method of claim 27, wherein the remedial action is infusion of fluid into the patient.

30. The method of claim 27, wherein the remedial action is increasing pressure on lower extremities of the patient.

31. The method of claim 27, wherein the remedial action is changing the position of the patient.

32. The method of claim 31, wherein the remedial action is selected from placing the patient in the Trendelenburg position and raising the patient's legs.

* * * * *

专利名称(译)	通过测量相对血容量，血压和心率来检测透析中的病态事件的指示		
公开(公告)号	US20150208988A1	公开(公告)日	2015-07-30
申请号	US14/424005	申请日	2013-08-27
[标]申请(专利权)人(译)	费森尤斯医疗保健集团		
申请(专利权)人(译)	费森尤斯医药HOLDINGS，INC.		
当前申请(专利权)人(译)	费森尤斯医药HOLDINGS，INC.		
[标]发明人	ZHU FANSAN KOTANKO PETER THIJSEN STEPHAN LEVIN NATHAN W		
发明人	ZHU, FANSAN KOTANKO, PETER THIJSEN, STEPHAN LEVIN, NATHAN W.		
IPC分类号	A61B5/00 A61M1/16		
CPC分类号	A61M1/1603 A61B5/746 A61B5/021 A61M1/16 A61M1/1615 A61M1/341 A61M1/3413 A61M1/3609 A61M2230/06 A61M2230/30		
优先权	61/694149 2012-08-28 US		
其他公开文献	US9974491		
外部链接	Espacenet USPTO		

摘要(译)

通过在血液透析治疗期间通过超滤去除过量流体期间监测患者状况来检测潜在的透析中病态事件（IME）的指示的方法包括确定患者的相对血容量（RBV），并去除一部分体积的过量流体从初始超滤速率的患者血液中，同时定期监测相对血容量（SDRBV）随时间的二阶导数。该方法然后包括继续以相同的超滤速率从患者的血液中去掉多余的流体，或者任选地，逐渐增加超滤速率。该方法还包括如果SDRBV处于低SDRBV警报水平和高SDRBV警报水平之间的范围内，则触发针对患者的IME的警报，并且可选地或另外地监测患者的标准化血压比，并且采取如果触发警报，则采取补救措施。

