



US 20140085082A1

(19) **United States**
(12) **Patent Application Publication**
Lyon et al.

(10) **Pub. No.: US 2014/0085082 A1**
(43) **Pub. Date: Mar. 27, 2014**

(54) **PATIENT MONITORING DEVICE WITH REMOTE ALERT**

Related U.S. Application Data

(71) Applicant: **Physio-Control, Inc.**, Redmond, WA (US)

(60) Provisional application No. 61/704,710, filed on Sep. 24, 2012.

(72) Inventors: **Richard Mark Lyon**, Edinburgh (GB); **Robert G. Walker**, Seattle, WA (US); **Jeffrey S. Edwards**, Redmond, WA (US); **Niklas Andersson**, Seattle, WA (US); **Bethany Joyce Johnson**, Snoqualmie, WA (US)

Publication Classification

(51) **Int. Cl.**
A61B 5/00 (2006.01)
(52) **U.S. Cl.**
CPC *A61B 5/0004* (2013.01)
USPC **340/539.12**


(73) Assignee: **PHYSIO-CONTROL, INC.**, Redmond, WA (US)

(57) **ABSTRACT**

A remote patient monitoring system provides patient physiological data and alerts/alarms from a main patient monitor to a remote patient monitor worn by a medical professional. The medical professional is alerted as to physiological data of the monitored patient, and provided alerts or alarms when predetermined levels are reached. The medical professional is able to reset the alert or alarms at the remote patient monitor.

(21) Appl. No.: **14/035,903**

(22) Filed: **Sep. 24, 2013**






FIG. 1




FIG. 2




FIG. 3

METHODS




FIG. 4

METHODS




FIG. 5

PATIENT MONITORING DEVICE WITH REMOTE ALERT

RELATED APPLICATION

[0001] This application claims the benefit of priority of U.S. Provisional Patent Application Ser. No. 61/704,710 filed Sep. 24, 2012, the disclosure of which is hereby incorporated by reference for all purposes.

BACKGROUND

[0002] In typical medical care situations, monitors are connected to devices that receive physiological data from patients. Such devices may be passive monitoring devices or active delivery devices. Active delivery devices, for example, may provide stimulus (e.g., cardiopulmonary resuscitation (CPR) machines), drugs, and/or oxygen.

[0003] In such situations, the monitors of such devices provide critical patient information to the caregivers, such as health care providers or medical professionals (e.g., medical doctors, nurses, emergency medical technicians, etc.). In many cases, the monitors are connected to the devices as an integrated package. Oftentimes, the monitors are not readily visible to the caregivers, particularly if the caregivers are away from the patient and the devices.

[0004] Although caregivers are away from the monitors and devices, the need to be aware of a patient's condition(s) continues. In certain cases, a medical professional may not be able to view a monitor and be aware of the patient's condition (s). Examples of such situations, include instances when the caregiver has to walk away to check on another patient or attend to another task. In certain cases, a caregiver is physically unable to view a monitor. An example includes a medical evacuation situation in a helicopter when a technician and patient are physically situated such that the technician is unable to view the monitor of the device. Furthermore, in such medical evacuation situations, the environment may not be ideal (e.g., noisy, dimly lit, etc.) to properly view the monitor.

[0005] In certain situations, a monitor not only provides status of physiological data and of the connected device, but may also provide alerts as to critical levels of a patient. For example, a blood pressure device may alert the medical professional as to a critically low blood pressure level and/or irregular heartbeat. In the case of an oxygen sensing device, a monitor may alert the professional as to low levels of oxygen to the patient. Such alerts may be triggered by abnormalities/conditions experienced by the patient and/or problems/malfunctions of the device.

[0006] If a caregiver is away from a monitor, the patient's care may be compromised because the caregiver cannot properly view the condition of the patient or be aware of alerts provided by the device through the monitor.

BRIEF SUMMARY

[0007] The present description gives instances of medical technology that facilitates the remote monitoring of patients.

[0008] In one embodiment, a medical device facilitates monitoring of a patient. The medical system includes a main patient monitor collecting patient physiological parameter data, and also capable of transmitting the collected patient physiological parameter data. The main patient monitor alarms if the collected data is determined to reach a predetermined value. The device further includes a remote patient monitor, also referred to as a remote patient monitoring

device, in the form of a wrist band, worn by a caregiver, configured to receive the collected patient physiological parameter data, display the collected patient physiological parameter data received from the main patient monitor, and receive a signal in response to an alarm(s) from the main patient monitor.

[0009] In one embodiment, the remote patient monitor can be a bracelet, a wrist or arm band, or other type of a small, compact, or wearable device. The remote patient monitor interfaces with the main patient monitor, a defibrillator, and/or other medical device or system. Alternatively, the remote patient monitor operates as a stand-alone, such as a puck or is incorporated into another device, such as a cell phone, a watch, bag valve mask, defibrillation electrodes, etc. The remote patient monitor allows a wearer of the device to monitor a patient through pre-set alarms, which can manifest as one or a combination of visual, tactile, auditory types of notifications, which may vary in intensity and duration depending on the preset parameters.

[0010] In some embodiments, the remote patient monitor includes a sensory feedback, such as haptic feedback, guiding a rescuer, dictating the rate via metronome, and/or notifying of elapsed time in Cardiopulmonary Resuscitation (CPR). The remote patient monitor further may include haptic feedback mechanism in bag valve mask (BVM). The remote patient monitor is, in one example, configured to differentiate haptic sensation to the wearer/rescuer to signify that a two-minute cycle has elapsed, and further to detect ventricular fibrillation (VF) or shockable rhythm, ST-elevation, ROSC (Return of Spontaneous Circulation), apnea, desaturation, etc. These and other features and advantages of this description will become more readily apparent from the following Detailed Description, which proceeds with reference to the drawings, in which:

BRIEF DESCRIPTION OF THE DRAWINGS

[0011] FIG. 1 is a diagram of a remote patient monitoring system used to remotely provide physiological data and alerts of a patient according to one or more embodiments described herein.

[0012] FIG. 2 is a diagram of a sample of a remote patient monitoring system used to remotely provide physiological data and alerts of a patient according to one or more embodiments described herein.

[0013] FIG. 3 is a diagram of sample physiological data and alerts that are remotely provided according to one or more embodiments described herein.

[0014] FIG. 4 is a flowchart for illustrating methods to remotely provide physiological data and alerts of a patient according to one or more embodiments described herein.

[0015] FIG. 5 is another flowchart for illustrating methods to remotely provide physiological data and alerts of a patient according to one or more embodiments described herein.

DETAILED DESCRIPTION

[0016] As has been mentioned, the present description pertains to remote patient monitoring technology. Embodiments are now described in more detail.

Patient Monitoring System

[0017] FIG. 1 is a diagram of a remote patient monitoring system 100 according to the technology described herein. A patient 102 may be in particular location 104. A patient may

be, by way of example, a hospital patient in bed in a particular unit with more less stationary devices and monitors around his/her bed or may be an ambulatory or outside-a-hospital patient accessorized with devices such as implantable devices or monitoring and therapy devices attached to the patient. In certain instances, a caregiver (not shown) may be in a different location. Various medical probes and/or delivery devices **106** are connected to the patient **102**. A main patient monitor **108** is connected to medical probes and/or delivery devices **106**. The medical probes and/or delivery devices **106** may actively provide medicine, oxygen and/or liquids to the patient **102**. In some embodiments, the medical probes and/or delivery devices **106** monitor and/or track physiological parameter data. The physiological parameter data may include one or more vital signs. For example, physiological parameter data may include heart rate, blood pressure, oxygen saturation, end-tidal CO₂, respiration rate level of the monitored patient **102**.

[0018] The main patient monitor **108** may be configured to collect patient physiological parameter data, to transmit the collected patient physiological parameter data, and to alarm if the collected data is determined to reach a predetermined value. Other alarms may be provided, such as condition states of the main patient monitor **108** and/or devices connected to the patient of the main patient monitor **108**. Examples of condition states include low power/battery of the patient monitor **108** and/or devices, transmission connectivity to the remote patient monitor **110** and other networks, etc.

[0019] The main patient monitor **108** may be connected to a remote patient monitor **110**. The connection between the main patient monitor **108** and the remote patient monitor **110** may be a wired or wireless connection as represented by connection **112**. In other words, the main patient monitor **108** and the remote patient monitor **110** may be wired or wirelessly coupled to one another.

[0020] In certain embodiments, the main patient monitor **108** and remote patient monitor **110** may be connected intermediately through a network, such as a cloud based network. In other words, the connection **112** may go through or be part of a network or networks, which may include cloud based network(s). In certain embodiments, cloud based network(s) may perform monitoring based on information received from the main patient monitor **108**.

[0021] The remote patient monitor **110** may be configured as or be part of a cell phone, puck, or arm or wrist band **114**, that may be worn or carried by a caregiver, for example on a caregiver's wrist **116**. In another embodiment, the band **114** may be in a form of a necklace, arm band, or waist band, or other wearable device. Other embodiments are possible. Caregivers may include laypeople such as family members, and/or trained medical professionals such as medical doctors, medical directors, nurses, emergency medical technicians (EMTs), and the like. Therefore in some embodiments, the remote patient monitor **110** may be in the form of a band, such as a wrist band **114** and configured to be worn by a caregiver, to receive the collected patient physiological parameter data. The remote patient monitor **110** further may display the collected patient physiological parameter data received from the main patient monitor **108**, and to receive a signal in response to an alarm from the main patient monitor **108**.

[0022] In some embodiments, the band **114** may be adjustable and may include a buckle **118** and holes to attach the buckle **118** to adjust to accommodate for various sized wrists, waists, etc. A slider **122** may be used to secure to excess

length of the band **114**. In addition to being adjustable, the band **114** may also be waterproof and/or shock-resistant. In certain embodiments, the band **114** may be in the form of or attached to a necklace or lanyard around the caregiver's neck. In other embodiments the band **114** may be in the form of or attached to a belt around the caregiver's waist. Other embodiments may provide for the remote patient monitor **110** to be clipped onto the caregiver's clothing, such as on a lapel or chest pocket. Other embodiments may provide for the remote patient monitor **110** to be implemented as a wearable device. [0023] The remote patient monitor **110** may include an alarm reset button **124** to reset any alarms received from the main patient monitor **108**. In certain embodiments, the alarm (s) that is(are) received by the remote patient monitor **110** include one or more of vibrate (e.g., tactile/haptic alarm), light up, and/or an audible noise. In particular embodiments, the remote patient monitor **110** only vibrates as determined by the main patient monitor **108**.

[0024] In certain embodiments, the remote patient monitor **110** receives haptic/sensory feedback for patient monitoring that may include a guide rate for chest compression, such as used in CPR. In such an implementation, a patient may have a physiologic monitoring sensor, which is not necessarily "wearable", but merely attached to the patient. The patient sensor provides data to the remote patient monitor **110**. The remote patient monitor **110** may include a haptic motor that conveys information to the caregiver in the form of "mimicked" sensory feedback from the patient. In yet certain other embodiments, monitoring data transmitted to the remote patient monitor **110** may be include information about ventilation (e.g. rate, tidal volume, airway pressure) being provided to the patient. The patient sensors may be incorporated as a wearable device (e.g., wrist band, head band, bracelet, etc.), standalone sensor, or incorporated into another device (e.g. bag valve mask).

[0025] In certain embodiments, the patient may be provided with disposable components such as a sticker with a wireless identifier (i.e., an RFID chip) to initiate or inform as to a haptic component/feedback. Different variations of such disposable components may make use of color coded stickers with RFID used to set various rates (e.g., 100/min for chest compression and 8/min for ventilation). Other colors may be used for various rate guidance purposes. Disposable component/sticker or RFIDs may be used to start or stop a patient/caregiver haptic motor when patient/caregiver is in proximity of the RFID. In certain implementation, a disposable component/sticker may be incorporated into a device, such as a defibrillator.

[0026] Other haptic signals may include use of different frequencies, duty cycles, sensations (vibration, taps, squeeze, etc.) to communicate different information. Physiological feedback could provide input signal to vibration intensity, rate, sensation, etc. The remote patient monitor **110** and particularly a wearable portion may incorporate a display, such that a haptic signal would alert the caregiver and the display would provide detailed information about the alert.

[0027] In certain embodiments, depending on the level of a caregiver's expertise, the alarm(s) that is(are) received by the remote patient monitor **110** may be activated based on specific preset threshold values. The alarms may include a general overall urgency alarm, and/or specific alarms. Variety of settings may be determined depending on the patient's condition, parameters, status and combined with the caregiver's rank, skills, expertise, and preferences. An alarm may be

initiated at the remote patient monitor **110** to indicate an urgent need to respond to the patient, such as a cardiac arrest, an oxygen desaturation, etc. In such cases, a general urgency alarm may be activated, and/or specific alarms indicating specific medical conditions may be activated. Specific alarms may further be selected by a user/caregiver to differentiate between sounds, vibration patterns, and intensity depending on the patient identification, location, and other parameters. If several caregivers receive alarms pertaining to the same patient, and one of the alerted caregivers responds, other caregivers may be notified that the patient is being attended to. If the attending to the patient caregiver still needs additional help, the caregiver may be able to send another alarm to solicit further help. Alternatively, upon arrival at the patient's side or resolution as to the patient needs, one caregiver may terminate alarms sent to others and may further be able to follow up with a message as to the resolution of the issue.

[0028] Alarms may be sent by signals from the main patient monitor **108** to the remote patient monitor **110**. After a period of time the signals may be degraded. Therefore, in certain embodiments a decoupling or a disconnection may occur between the main patient monitor **108** and the remote patient monitor **110** after a determined time period after a signal(s) is degraded. In certain instances it may be desirable for a caregiver to reset the alarm(s) of the remote patient monitor **110**. An alarm reset button **124** is provided by the remote patient monitor **110** to allow resetting of the alarm(s).

[0029] The patient monitor **110**, or a wearable portion of the patient monitor **110**, may include a start/stop haptic feedback metronome which may include different pre-selected metronome rates such as ventilation (e.g., 8/min), compression (e.g., 100/min), etc.

[0030] In certain embodiments, the remote patient monitor **110** may be coupled to more than one main patient monitors, including the main patient monitor **108** that is shown. In such embodiments, the remote patient monitor **110** is configured to receive various patient physiological parameter data and alarms from different medical devices and/or patients.

[0031] In certain embodiments, there may be more than one patient. Therefore, the remote patient monitor **110** may be coupled to more than one main patient monitors and/or one or more patients.

[0032] The patient monitoring system **100** may be part of different health care environments. In certain embodiments, the patient monitoring system **100** may be part of a hospital environment that includes nursing stations. A nursing station may include multiple patient monitors, such as main patient monitor **108**.

[0033] Caregivers, such as medical doctors, nurses, etc., are able to simultaneously monitor patients from a central station at the nursing station. However, in certain situations the caregiver may be away from the central stations and the monitors, but would still need to be aware of the patients. In such cases, the remote patient monitor **110** may be configured to provide alarms to let the caregiver know the status of the patients and/or determine which patient(s) need to be attended to. In certain embodiments, the remote patient monitor **110** may provide a patient's name, room number (location) and/or other specific patient information. In certain embodiments, either through preset thresholds that are set at particular main patient monitor(s) **108**, patients may be listed in order of need for medical attention or listed some other order, such as first request. In a further embodiment, the remote patient monitor is configured to monitor more than

one patient simultaneously. If one caregiver is monitoring more than one patient, the remote patient monitor **110** can provide ranking of urgency between patients, depending on a patient's symptoms.

[0034] In certain embodiments, there may be multiple caregivers connected to the patient monitoring system **100**. Provision may be made to allow a caregiver that is the first responder to the patient, to notify other caregivers that the first responding caregiver has reached the patient. Provision may also be provided to allow the first responding caregiver to request for additional help if needed. This may be performed through the remote patient monitor that is worn by the first responding caregiver.

[0035] In certain embodiments, the main patient monitor **108** may be configured with a cellular, global positioning system (GPS), or other tracking unit (not shown). The tracking unit may provide specific location of the patient (i.e., patient location **104**). This may assist in identifying specific location of an ambulatory patient, to the remote patient monitor **110**. The foregoing indications and responses described in conjunction with FIG. **1** can be implemented in various combinations in other embodiments, with each indication and/or response providing its advantages even if combined with other indication(s) and/or response(s).

Example Patient Monitoring System Components

[0036] FIG. **2** is a diagram of a sample structure of a remote patient monitoring system **100** used to remotely provide physiological data and alerts of a patient according to the technology described herein. In the illustrated embodiment, one or more main patient monitors **108** are wire or wirelessly coupled to a remote patient monitor **110** by wire and/or wireless connections **112**.

[0037] In this embodiment, a main patient monitor **108-1** is shown to include a patient data collection module **200** which communicates with and receives patient physiological data from one or more medical devices and/or probes, such as medical probes and/or delivery devices **106** described above. In particular, the patient data collection module **200** gathers patient physiological parameter data, which may include one or more vital signs of a monitored patient (e.g., patient **102**). As an example, the patient physiological parameter data may particularly include one or more of the following: blood pressure, heart rate, respiration rate, pulse rate, oxygen saturation, air flow, temperature, ECG parameters, and/or other parameters. Device data, such as low battery on one of the devices/probes interfacing/interacting with the patient or the band's inability to access information, or other parameters/data, can also be included. Other example data that may be sent can include 1) physiologic data, such as vital signs data, and/or alarm info on vital signs excursions out of normal/stable ranges; 2) monitoring device data, battery status, sensor status, etc. (i.e., information meriting the attention or intervention of a caregiver); and 3) Medical care/intervention data, i.e., information about the presence or quality of the care being applied to the patient by someone other than the person wearing the remote patient monitor, for example, alert the person managing a resuscitation (and e.g. wearing a haptic wristband) that the person managing the airway is ventilating too fast, or the person doing chest compressions has paused for too long.

[0038] The main patient monitor **108-1** may include a patient data evaluation module **202** which is configured with values for patient physiological parameter data. Such values

may be preset by a caregiver to trigger an alarm. For example, if a particular value reaches or exceeds a particular level or levels, the alarm or alarms may be triggered. In this example, an alarm module **204** may be configured to provide such alert(s) in response to reaching a predetermined value(s) for the patient physiological parameter data. Alarms or alerts may initiate one or more actions such as vibration, light up, or a noise/audible sound. Such alarms or alerts may be communicated to the remote patient monitor **110**.

[0039] The main patient monitor **108-1** may include a display module **206** to display the patient physiological parameter data and/or alarms. A transmitting module **208** provides signals (e.g., one or more alarm signals) to the remote patient monitor **110**. The signals to the remote patient monitor **110** may include the one or more actions such as vibration, light up, or a noise/audible/haptic sound/response. In certain embodiments, the transmitting module **208** is a wireless module that may implement one or more various wireless technologies, including but not limited to Bluetooth®, one or more the various IEEE 802.11 standards, etc.

[0040] The main patient monitor **108-1** includes one or more processors **210** couple with the other components of the main patient monitor **108-1**. Volatile and nonvolatile memory **212** is included in main patient monitor **108-1**. Memory **212** may include computer-readable storage medium that includes instructions to perform the acts/methods described herein.

[0041] The remote patient monitor **110** is wired or wireless coupled to the main patient monitors **108** by respective links or connections **112**. The remote patient monitor **110** includes a receiving module **214**. In certain embodiments the receiving module **214** is a wireless receiving module, which may implement one or more various wireless technologies, including but not limited to Bluetooth®, one or more the various IEEE 802.11 standards, etc. The receiving module **214** receives one or more alerts, which may be in the form of one or more transmitted signals from the main patient monitors **108**. The received signals from main patient monitors **108** may include the one or more actions such as vibration, light up, or a noise/audible sound.

[0042] The remote patient monitor **110** may include display module **216** may display the patient physiological parameter data and/or alarms (alerts). The display module **216** may light up with a particular alert or alerts. The remote patient monitor **110** may include a separate alert module **218**. A function the alert module may perform is to vibrate when a particular alert or alerts is/are received from the main patient monitors **108**. An alarm reset module **220**, which may be reset by alarm reset button **124** described above, may be implemented by the remote patient monitor **110** to reset one or more alerts and alarms that are activated/displayed.

[0043] The remote patient monitor **110** includes one or more processors **222** coupled with the other components of the remote patient monitor **110**. Volatile and nonvolatile memory **224** is included in remote patient monitor **110**. Memory **224** may include computer-readable storage medium that includes instructions to perform the acts/methods described herein. In certain embodiments, and particular where the remote patient monitor **110** is a portable unit, a long lasting battery(ies) **226** may be part of the remote patient monitor **110**.

[0044] The foregoing indications and responses described in conjunction with FIG. 2 can be implemented in various combinations in other embodiments, with each indication

and/or response providing its advantages even if combined with other indication(s) and/or response(s).

Example Physiological Data and Alerts

[0045] FIG. 3 is a diagram of sample physiological data and alerts that are remotely provided according to the technology described herein. The main patient monitor **108** may provide alarms/alerts of collected physiological data to the remote patient monitor **110**. The physiological data may be for patient physiological parameter data. As described above, such patient physiological parameter data may have values that preset by a caregiver to trigger an alarm. For example, if a particular value reaches or exceeds a particular level or levels, the alarm or alarms may be triggered.

[0046] Shown in FIG. 3 are monitored physiological data **300** that includes current patient monitored values. In this example, pulse oxygen, temperature, blood pressure and heart rate values are monitored and displayed. Such values are communicated to the remote patient monitor **110** are displayed as patient physiological data **302**. The displayed values shown in remote patient monitor **110** are a compact or condensed version displayed by the main patient monitor **108**.

[0047] The functions of this description may be implemented by one or more devices that include logic circuitry. The device performs functions and/or methods as are described in this document. The logic circuitry may include a processor that may be programmable for a general purpose, or dedicated, such as microcontroller, a microprocessor, a Digital Signal Processor (DSP), etc. For example, the device may be a digital computer like device, such as a general-purpose computer selectively activated or reconfigured by a computer program stored in the computer. Alternately, the device may be implemented by an Application Specific Integrated Circuit (ASIC), etc.

[0048] Moreover, methods are described below. The methods and algorithms presented herein are not necessarily inherently associated with any particular computer or other apparatus. Rather, various general-purpose machines may be used with programs in accordance with the teachings herein, or it may prove more convenient to construct more specialized apparatus to perform the required method steps. The required structure for a variety of these machines will become apparent from this description.

[0049] In all cases there should be borne in mind the distinction between methods in this description, and the method of operating a computing machine. This description relates both to methods in general, and also to steps for operating a computer and for processing electrical or other physical signals to generate other desired physical signals.

[0050] Programs are additionally included in this description, as are methods of operation of the programs. A program is generally defined as a group of steps leading to a desired result, due to their nature and their sequence. A program is usually advantageously implemented as a program for a computing machine, such as a general-purpose computer, a special purpose computer, a microprocessor, etc.

[0051] Storage media are additionally included in this description. Such media, individually or in combination with others, have stored thereon instructions of a program made according to the technology described herein. A storage medium according to the technology described herein is a computer-readable medium, such as a memory, and is read by the computing machine mentioned above.

[0052] Performing the steps or instructions of a program requires physical manipulations of physical quantities. Usually, though not necessarily, these quantities may be transferred, combined, compared, and otherwise manipulated or processed according to the instructions, and they may also be stored in a computer-readable medium. These quantities include, for example electrical, magnetic, and electromagnetic signals, and also states of matter that can be queried by such signals. It is convenient at times, principally for reasons of common usage, to refer to these quantities as bits, data bits, samples, values, symbols, characters, images, terms, numbers, or the like. It should be borne in mind, however, that all of these and similar terms are associated with the appropriate physical quantities, and that these terms are merely convenient labels applied to these physical quantities, individually or in groups.

[0053] This detailed description is presented largely in terms of flowcharts, display images, algorithms, and symbolic representations of operations of data bits within at least one computer readable medium, such as a memory. Indeed, such descriptions and representations are the type of convenient labels used by those skilled in programming and/or the data processing arts to effectively convey the substance of their work to others skilled in the art. A person skilled in the art of programming may use these descriptions to readily generate specific instructions for implementing a program according to the technology described herein.

[0054] Often, for the sake of convenience only, it is preferred to implement and describe a program as various interconnected distinct software modules or features, individually and collectively also known as software. This is not necessary, however, and there may be cases where modules are equivalently aggregated into a single program with unclear boundaries. In any event, the software modules or features of this description may be implemented by themselves, or in combination with others. Even though it is said that the program may be stored in a computer-readable medium, it should be clear to a person skilled in the art that it need not be a single memory, or even a single machine. Various portions, modules or features of it may reside in separate memories, or even separate machines. The separate machines may be connected directly, or through a network, such as a local access network (LAN), or a global network, such as the Internet.

[0055] It will be appreciated that some of these methods may include software steps that may be performed by different modules of an overall software architecture. For example, data forwarding in a router may be performed in a data plane, which consults a local routing table. Collection of performance data may also be performed in a data plane. The performance data may be processed in a control plane, which accordingly may update the local routing table, in addition to neighboring ones. A person skilled in the art will discern which step is best performed in which plane.

[0056] An economy is achieved in the present document in that flowcharts are used to describe both programs, and also methods. So, while flowcharts are described in terms of boxes, they can mean both method and programs.

[0057] For this description, the methods may be implemented by machine operations. In other words, embodiments of programs are made such that they perform methods in accordance to embodiments of the technology that are described in this document. These may be optionally performed in conjunction with one or more human operators performing some, but not all of them. As per the above, the

users need not be collocated with each other, but each only with a machine that houses a portion of the program. Alternately, some of these machines may operate automatically, without users and/or independently from each other.

Example Methods

[0058] FIG. 4 shows a flowchart 400 for describing methods according to the technology described herein, for a patient monitoring system to remotely provide physiological data and alerts of a patient. The method of flowchart 400 may also be practiced by patient monitoring systems made according to the technology described herein described above.

[0059] According to an operation 402, a main patient monitor obtains patient's physiological data.

[0060] According to an operation 404, the main patient monitor transmits the obtained patient physiological data to a remote patient monitor, which may be part of or integrated as a wrist band, and the evaluates obtained patient physiological data.

[0061] According to an operation 406, a decision is made whether a threshold value is reached. If the threshold value is not reached, following the "NO" branch of operation 406, operation 402 is performed.

[0062] According to an operation 408, if the threshold value is reached as determined by operation 406, then following the "YES" branch of operation 406, the main patient monitor triggers or performs an alarm or alarms.

[0063] According to an operation 410, the main patient monitor transmits the alarm or alarms to the remote patient monitor.

[0064] According to an operation 412, the remote patient monitor vibrates, alerting a caregiver.

[0065] According to an operation 412, an alarm reset button on the remote patient monitor may be activated by the caregiver to silence the alarm or alarms.

[0066] For flowchart 400, it will be recognized that a number of their operations can be augmented with what was described above.

[0067] FIG. 5 is another flowchart 500 for describing methods according to the technology described herein, for a patient monitoring system to remotely provide physiological data and alerts of a patient. The method of flowchart 500 may also be practiced by patient monitoring systems made according to the technology described herein described above.

[0068] An operation 502 obtains patient physiological data at a remote patient monitor. The remote patient monitor may be part of or integrated as a wrist band.

[0069] An operation 502 displays the patient physiological data at the remote patient monitor.

[0070] An operation 506 determines if the remote patient monitor is vibrating. If the remote patient monitor is not vibrating, then following the "NO" branch of operation 506, operation 502 is performed.

[0071] According to an operation 508, if the remote patient monitor is vibrating as determined by operation 506, then following the "YES" branch of operation 506, the alarm or alarms on the remote patient monitor may be reset.

[0072] For flowchart 500, it will be recognized that a number of their operations can be augmented with what was described above.

Notes and Additional/Alternative Implementation Details

[0073] In the above description of exemplary implementations, for purposes of explanation, specific numbers, materials configurations, and other details are set forth in order to better explain the present invention, as claimed. However, it will be apparent to one skilled in the art that the claimed invention may be practiced using different details than the exemplary ones described herein. In other instances, well-known features are omitted or simplified to clarify the description of the exemplary implementations.

[0074] The inventor intends the described exemplary implementations to be primarily examples. The inventor does not intend these exemplary implementations to limit the scope of the appended claims. Rather, the inventor has contemplated that the claimed invention might also be embodied and implemented in other ways, in conjunction with other present or future technologies.

[0075] Moreover, the word “exemplary” is used herein to mean serving as an example, instance, or illustration. Any aspect or design described herein as exemplary is not necessarily to be construed as preferred or advantageous over other aspects or designs. Rather, use of the word “exemplary” is intended to present concepts and techniques in a concrete fashion. The term “technology,” for instance, may refer to one or more devices, apparatuses, systems, methods, articles of manufacture, and/or computer-readable instructions as indicated by the context described herein.

[0076] As used in this application, the term “or” is intended to mean an inclusive “or” rather than an exclusive “or.” That is, unless specified otherwise or clear from context, “X employs A or B” is intended to mean any of the natural inclusive permutations. That is, if X employs A; X employs B; or X employs both A and B, then “X employs A or B” is satisfied under any of the foregoing instances. In addition, the articles “a” and “an” as used in this application and the appended claims should generally be construed to mean “one or more,” unless specified otherwise or clear from context to be directed to a singular form.

[0077] Note that the order in which the processes are described is not intended to be construed as a limitation, and any number of the described process blocks can be combined in any order to implement the processes or an alternate process. Additionally, individual blocks may be deleted from the processes without departing from the spirit and scope of the subject matter described herein.

[0078] One or more embodiments described herein may be implemented fully or partially in software and/or firmware. This software and/or firmware may take the form of instructions contained in or on a non-transitory computer-readable storage medium. Those instructions may then be read and executed by one or more processors to enable performance of the operations described herein. The instructions may be in any suitable form, such as but not limited to source code, compiled code, interpreted code, executable code, static code, dynamic code, and the like. Such a computer-readable medium may include any tangible non-transitory medium for storing information in a form readable by one or more computers, such as but not limited to read only memory (ROM); random access memory (RAM); magnetic disk storage media; optical storage media; a flash memory, etc.

[0079] The term “computer-readable media” includes computer-storage media. For example, computer-storage media may include, but are not limited to, magnetic storage devices (e.g., hard disk, floppy disk, and magnetic strips), optical

disks (e.g., compact disk [CD] and digital versatile disk [DVD]), smart cards, flash memory devices (e.g., thumb drive, stick, key drive, and SD cards), and volatile and non-volatile memory (e.g., RAM and ROM).

[0080] In the claims appended herein, the inventor invokes 35 U.S.C. §112, paragraph 6 only when the words “means for” or “steps for” are used in the claim. If such words are not used in a claim, then the inventor does not intend for the claim to be construed to cover the corresponding structure, material, or acts described herein (and equivalents thereof) in accordance with 35 U.S.C. §112, paragraph 6.

What is claimed is:

1. A patient monitoring system, comprising:

a main patient monitor configured to monitor and collect patient physiological parameter data, and alarm in response to a determination that the collected data has reached a predetermined value; and

a remote patient monitor in a form of a band, the remote patient monitor being configured to be worn by a caregiver, to receive a signal in response to an alarm from the main patient monitor.

2. A system in accordance with claim 1, wherein the main patient monitor further transmits at least one of the collected patient physiological parameter data, patient identification, location identification, device data, and messages to a caregiver.

3. A system in accordance with claim 1, wherein the remote patient monitor further receives and displays at least one of the collected patient physiological parameter received from the main patient monitor, patient identification, location identification, device data, and messages to a caregiver.

4. A medical system in accordance with claim 1, wherein patient physiological parameter data includes at least one of heart rate, blood pressure, oxygen saturation, end-tidal CO₂, respiration rate.

5. A medical system in accordance with claim 1, wherein the band is a band attachable to a caregiver’s extremities, neck, belt, and waist and further has properties selected from a group consisting of adjustable, waterproof, and shock-resistant.

6. A medical system in accordance with claim 1, wherein the main patient monitor and remote patient monitor are coupled wirelessly through one or more networks such as a cloud based network.

7. A medical system in accordance with claim 1, wherein the signal in response to an alarm is selected from a group consisting of vibration, visual, or auditory signal and capable of changes in intensity depending on the risk to a patient.

8. A medical system in accordance with claim 1, wherein the alarm includes one or more alarms which include overall urgency alarm and specific alarms that are activated based on preset threshold values.

9. A medical system in accordance with claim 1 further comprising one or more different main patient monitors, each main patient monitor monitoring an individual patient, and capable of providing alarm signals to one or more remote patient monitors and caregivers.

10. A patient monitoring device comprising:

a patient data collection module configured to gather patient physiological parameter data received from a monitored patient;

a patient data evaluation module configured to store values for patient physiological parameter data;

an alert module configured to provide an alerts in response to reaching predetermined values for the patient physiological parameter data;
 a display module configured to display the patient physiological parameter data; and
 a transmitting module configured to send the patient physiological parameter data and one or more alarm signals to a remote patient monitor device.

11. A patient monitoring device in accordance with claim **10**, wherein the patient physiological parameter data includes measurements of at least one of heart rate, blood pressure, oxygen saturation, end-tidal CO₂, respiration rate.

12. A patient monitoring device in accordance with claim **10**, wherein the alert is selected from a group consisting of vibration, illumination, and noise generation.

13. A patient monitoring device claim **10**, wherein the alarm signals include overall urgency alarm and specific alarms that are activated based on the preset threshold values.

14. A patient monitoring device in accordance with claim **10**, wherein the patient monitoring device and the remote patient monitor device are coupled through one or more networks, including cloud based networks.

15. A method that facilitates remotely monitoring a patient using a wrist band remote patient monitor, the method comprising:

receiving patient physiological parameter data at the wrist band remote patient monitor via a transmitting module;
 displaying the patient physiological parameter data on the wrist band remote patient monitor;
 determining whether the wrist band remote patient monitor is vibrating; and
 in response to a determination that the wrist band remote patient monitor is vibrating, receiving an indication at the wrist band remote patient monitor to reset an alarm associated with the wrist band remote patient monitor vibration.

16. A method in accordance with claim **15**, wherein the wrist band remote patient monitor vibrates in response to a predetermined patient physiological parameter data being encountered.

17. A method in accordance with claim **16**, wherein the predetermined patient physiological parameter provides for at least one of a general urgency alarm and a specific alarm and can escalate in intensity depending on risk to a patient.

18. A method in accordance with claim **17**, wherein patient physiological parameter data includes at least one of heart rate, blood pressure, oxygen saturation, end-tidal CO₂, respiration rate.

19. A method in accordance with claim **17**, wherein patient physiological parameter data is from more than one patient.

20. An article comprising: a storage medium, the storage medium having instructions stored thereon, wherein when the instructions are executed by at least one medical device configured to remotely monitoring a patient using a wrist band remote patient monitor, they result in:

receiving patient physiological parameter data at the wrist band remote patient monitor via a wireless module;

displaying the patient physiological parameter data on the wrist band remote patient monitor;

determining whether the wrist band remote patient monitor is vibrating; and

in response to a determination that the wrist band remote patient monitor is vibrating, receiving an indication at the wrist band remote patient monitor to reset an alarm associated with the wrist band remote patient monitor vibration.

21. An article in accordance with claim **20**, wherein the wrist band remote patient monitor vibrates in response to a predetermined patient physiological parameter data being encountered.

22. An article in accordance with claim **20**, wherein patient physiological parameter data includes at least one of heart rate, blood pressure, oxygen saturation, end-tidal CO₂, respiration rate.

23. An article in accordance with claim **20**, wherein patient physiological parameter data is from more than one patient.

* * * * *

专利名称(译)	具有远程警报的患者监测设备		
公开(公告)号	US20140085082A1	公开(公告)日	2014-03-27
申请号	US14/035903	申请日	2013-09-24
申请(专利权)人(译)	生理控制, INC.		
当前申请(专利权)人(译)	生理控制, INC.		
[标]发明人	LYON RICHARD MARK WALKER ROBERT G EDWARDS JEFFREY S ANDERSSON NIKLAS JOHNSON BETHANY JOYCE		
发明人	LYON, RICHARD MARK WALKER, ROBERT G. EDWARDS, JEFFREY S. ANDERSSON, NIKLAS JOHNSON, BETHANY JOYCE		
IPC分类号	A61B5/00		
CPC分类号	A61B5/0004 A61B5/0002 A61B5/0205 A61B5/746 A61B5/7465 G16H40/67 G16Z99/00 G06F19/00 G06F19/3418 G16H40/63		
优先权	61/704710 2012-09-24 US		
其他公开文献	US9314159		
外部链接	Espacenet USPTO		

摘要(译)

远程患者监测系统从主要患者监测器向医疗专业人员佩戴的远程患者监测器提供患者生理数据和警报/警报。向医疗专业人员发出关于被监测患者的生理数据的警报，并在达到预定水平时提供警报或警报。医疗专业人员能够重置远程患者监护仪上的警报或警报。

