

US010052034B2

(12) **United States Patent**  
**Braun et al.**

(10) **Patent No.:** **US 10,052,034 B2**  
(45) **Date of Patent:** **Aug. 21, 2018**

(54) **WEARABLE DEVICES FOR SENSING, DISPLAYING, AND COMMUNICATING DATA ASSOCIATED WITH A USER**

(58) **Field of Classification Search**  
CPC ..... A61B 5/02055  
See application file for complete search history.

(71) Applicants: **Zachary Joseph Braun**, Atlanta, GA (US); **Tyler Evan Sisk**, Atlanta, GA (US)

(56) **References Cited**

U.S. PATENT DOCUMENTS

(72) Inventors: **Zachary Joseph Braun**, Atlanta, GA (US); **Tyler Evan Sisk**, Atlanta, GA (US)

2004/0135693 A1\* 7/2004 Schubert ..... G08B 21/0453  
340/573.1  
2010/0010832 A1\* 1/2010 Boute ..... G06F 19/3418  
705/3

(73) Assignee: **FireHUD Inc.**, Atlanta, GA (US)

(Continued)

(\* ) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 0 days.

OTHER PUBLICATIONS

Wearable Advanced Sensor Platform, <http://globeturnoutgear.com/innovation/wasp>.

(Continued)

(21) Appl. No.: **15/451,877**

*Primary Examiner* — Joseph Feild  
*Assistant Examiner* — Pameshanand Mahase

(22) Filed: **Mar. 7, 2017**

(74) *Attorney, Agent, or Firm* — Troutman Sanders LLP; Ryan A. Schneider

(65) **Prior Publication Data**

US 2017/0251933 A1 Sep. 7, 2017

**Related U.S. Application Data**

(60) Provisional application No. 62/304,728, filed on Mar. 7, 2016.

(51) **Int. Cl.**  
**H04Q 9/00** (2006.01)  
**G08C 17/02** (2006.01)


(Continued)

(52) **U.S. Cl.**  
CPC ..... **A61B 5/02055** (2013.01); **A61B 5/0008** (2013.01); **A61B 5/6817** (2013.01); **G06F 1/163** (2013.01); **A61B 5/021** (2013.01); **A61B 5/02405** (2013.01); **A61B 5/02438** (2013.01); **A61B 5/0816** (2013.01); **A61B 5/0833** (2013.01); **A61B 5/4866** (2013.01); **A61B 2503/20** (2013.01); **G02B 27/017** (2013.01); **G06T 11/206** (2013.01); **G06T 2200/24** (2013.01)

(57) **ABSTRACT**

Embodiments of the present disclosure can comprise a wearable device for sensing, displaying, and communicating data associated with a condition of a user. In some embodiments, the wearable device can comprise a biometric sensor unit configured to sense biometric data associated with a physiological condition of the user, a display unit configured to display a visual representation of the sensed biometric data from the biometric sensor unit to the user, and a control unit operatively coupled to the biometric sensor unit and the display unit. The control unit may also comprise at least one processor configured to receive indications of the sensed biometric data and cause the display unit to display the at least one visual representation of the biometric data and a communication unit, the communication unit configured to transmit and/or receive information associated with the sensed biometric data.

**17 Claims, 18 Drawing Sheets**



(51)	<p><b>Int. Cl.</b>  <i>H04Q 9/14</i> (2006.01)  <i>A61B 5/0205</i> (2006.01)  <i>G06F 1/16</i> (2006.01)  <i>A61B 5/00</i> (2006.01)  <i>G06T 11/20</i> (2006.01)  <i>G02B 27/01</i> (2006.01)  <i>A61B 5/024</i> (2006.01)  <i>A61B 5/083</i> (2006.01)  <i>A61B 5/08</i> (2006.01)  <i>A61B 5/021</i> (2006.01)</p>	<p>2016/0094899 A1* 3/2016 Aumer ..... G08B 21/18  340/870.07  2016/0157717 A1* 6/2016 Gaster ..... A61B 5/0444  600/301  2016/0199002 A1* 7/2016 Lee ..... A61B 5/0008  340/870.07  2016/0278700 A1* 9/2016 Lee ..... A61B 5/02438</p>
------	---	---

OTHER PUBLICATIONS

Batalin, M., Yuen, E., Dolezal, B., Smith, D., Cooper, C., Mapar, J. Phaser: Physiological Health Assessment System for Emergency Responders. IEEE 2013.  
Hawkinson, W., Samanant, P., McCroskey, R., Ingvalson, R., Kulkarni, A., Hass, L., English, B. Glanser: Geospatial location, accountability, and Navigation System for Emergency Responders—system concept and performance assessment. IEEE 2012.

(56) **References Cited**

U.S. PATENT DOCUMENTS

2011/0257551 A1*	10/2011	Banet .....	A61B 5/0809 600/534
2012/0112903 A1*	5/2012	Kaib .....	A61N 1/3993 340/539.12

\* cited by examiner




FIG. 1a




FIG. 1b




FIG. 2a




FIG. 2b




FIG. 2c




FIG. 3a




FIG. 3b




FIG. 4




FIG. 5





FIG. 6






FIG. 8a




FIG. 8b




FIG. 9a




FIG. 9b




FIG. 10




FIG. 11

Detail Overview Settings [Download Data](#) [Refresh Data](#) [Logout User](#) [Download](#)

ID	Name	Battery	Heart Rate	Body Temp	External Temp	VO2	Calories	Steps
2	Tyler Sisk	48%	146 BPM	92°F	461°F	47	198	98
5	Zack Braun	57%	78 BPM	91°F	207°F	53	201	101
3	Chris Ward	58%	188 BPM	108°F	233°F	72	199	99
4	Sean Buckingham	47%	12 BPM	91°F	986°F	14	200	100
7	Joe Boettcher	58%	67 BPM	91°F	741°F	2	203	103

FIG. 12


UNIT #	NAME	STATUS	MESSAGE	ACTION ITEMS
1	Miller		—	<p>-Clear Basement -Chk 3rd FL -Find Victim on 2nd FL</p> <p>Current Time: 02:56:45 Elapsed Time: 00:32:24 Squad 8</p> 
2	Clark	● HIGH HR	Take a rest	
3	Taylor		—	
4	Kellogg		—	
5	White		—	
6	Davis	● HIGH RR	Fall Back	
7	Lee		—	
8	Sisk		—	
9	Walker		—	

FIG. 13

## WEARABLE DEVICES FOR SENSING, DISPLAYING, AND COMMUNICATING DATA ASSOCIATED WITH A USER

### CROSS-REFERENCE TO RELATED APPLICATION

This application claims priority to and benefit from Provisional Patent Application No. 62/304,728 filed Mar. 7, 2016, which is hereby incorporated by reference herein in its entirety as if fully set forth below.

### BACKGROUND

When on the job, first responders, such as firefighters, are subject to numerous psychological and physical stressors, including a number of dangerous conditions that may lead to serious injury or even death. However, it is projected that the majority of injuries or fatalities occurring while on the job are caused by overexertion. Overexertion can result from a variety of physiological and atmospheric factors involved in the course of a first responder's duties. As a recognized medical ailment, overexertion can be monitored and indicated by a plurality of biometrics including heart rate, body temperature, and  $VO_2$  saturation of a person.

Currently, first responders, such as firefighters, use various personal safety devices to protect against atmospheric stressors. One common safety device is a Self-Contained Breathing Apparatus (SCBA). The SCBA helps to provide breathable air to firefighters in an immediately dangerous environment, such as what is often a smoke-filled environment. While common personal safety devices, such as the SCBA, help mitigate the effects of atmospheric stressors on the human body, they are incapable of providing users with real-time data telling of overexertion, such that a first responder can take control of their health during a stressful situation. It is with respect to these and other considerations that various embodiments of the present disclosure are presented below.

### SUMMARY

Embodiments of the present disclosure can include a wearable device for sensing, displaying, and communicating data associated with a condition of a user. In an embodiment, the wearable device can comprise a biometric sensor unit, a display unit, and a control unit. The biometric sensor unit can be configured to sense biometric data associated with a physiological condition of the user. In some embodiments, the biometric sensor unit can comprise one or more sensors configured to sense a plurality of biometrics associated with the physiological condition of the user while using the wearable device. The plurality of biometrics can comprise, for instance, at least one of the user's body temperature, heart rate,  $VO_{2,max}$  respiration, steps taken, blood pressure, heart rate variability, and calories burnt. In an embodiment, the biometric sensor unit can comprise an earpiece configured to be received by an ear of the user of the wearable device.

The wearable device can also comprise a display unit that can be configured to display at least one visual representation of the sensed biometric data from the biometric sensor unit to the user of the wearable device. In some embodiments, the display unit can comprise at least one of a near-eye display and a heads up display. In some embodiments, the display unit can be configured to display the at least one visual representation to the user of the wearable

device in a location of the wearable device that is clear from obstructing a main view of the user of the wearable device.

The wearable device can also comprise a control unit operatively coupled to the biometric sensor unit and the display unit. The control unit can comprise at least one processor configured to receive indications of the sensed biometric data and cause the display unit to display the at least one visual representation of the biometric data to the user. Additionally, the control unit can comprise at least one communication unit, the communication unit configured to perform at least one of transmitting and receiving information associated with the sensed biometric data to and from a remote unit, respectively.

In some embodiments, the communication unit of the control unit can comprise at least one of a transmitter configured to transmit the biometric data to the remote unit and a receiver configured to receive information from the remote unit, the received information including one or more messages indicating at least one of i) the biometric data associated with the user of the wearable device, ii) action items to be performed by the user of the wearable device, and iii) status messages associated with a condition of the user of the wearable device.

In some embodiments, the condition of the user of the wearable device can comprise a physiological condition of the user of the wearable device while the wearable device is in use.

In some embodiments, the biometric sensor unit, display unit, and control unit can be selectively attachable to head-wear of the user of the wearable device.

In some embodiments, the biometric sensor unit and the control unit can comprise one or more sensors configured to sense at least one of the internal or external temperature associated with the wearable device while the wearable device is in use.

Embodiments of the present disclosure can also comprise a system for sensing, displaying, and communicating data associated with a condition of a user of a wearable device. The system can comprise a wearable device, and the wearable device can comprise a biometric sensor unit, a display unit, and a control unit. The biometric sensor unit can be configured to sense biometric data associated with the condition of the user. The display unit can be configured to display one or more visual representations of at least the sensed biometric data from the biometric sensor unit to the user. The control unit can be operatively coupled to the biometric sensor unit and the display unit, and the control unit can be configured to receive indications of the sensed biometric data from the biometric sensor unit and cause the display unit to display the one or more visual representations to the user.

In some embodiments, the system can comprise a remote unit in communication with the wearable device. In some embodiments, the remote unit can comprise a receiver configured to receive the indications of the sensed biometric data from the control unit and a computer-executable application comprising a graphical user interface for interacting with a user of the remote unit.

In some embodiments, the computer-executable application can be stored in a memory coupled to one or more processors and is executable by the one or more processors to perform functions that comprise at least one of: extracting a numerical representation of the sensed biometric data; comparing the numerical representation of the sensed biometric data to a threshold value corresponding to a predetermined biometric range; creating one or more graphical representations of the sensed biometric data for display on

the graphical user interface; and generating one or more messages indicating at least one of i) the biometric data associated with the user of the wearable device, ii) action items to be performed by the user of the wearable device, and iii) status messages associated with a condition of the user of the wearable device.

In some embodiments, the one or more messages can be communicated to the control unit of the wearable device, the control unit further configured to communicate the one or more messages to the display unit and the display unit configured to display the information to the user via a visual representation. In some embodiments, the biometric sensor unit can comprise at least one sensor configured to sense a plurality of biometrics associated with the physiological condition of the user while using the wearable device, the plurality of biometrics comprising at least one of the user's body temperature, heart rate,  $VO_{2max}$  respiration, steps taken, blood pressure, and calories burnt. In some embodiments, as discussed previously, the biometric sensor unit can comprise an earpiece configured to be received by an ear of the user of the wearable device.

Another embodiment of the present disclosure can comprise a method for sensing, displaying, and communicating data associated with a condition of a user of a wearable device, the method comprising: sensing, by a biometric sensor unit, biometric data associated with a physiological condition of the user, the biometric sensor unit configured to communicate the sensed biometric data to a control unit; receiving, by the control unit, the sensed biometric data, the control unit configured to communicate the biometric data to a display unit; and displaying, by a display unit, at least one visual representation of the sensed biometric data to the user.

In some embodiments, the method can further comprise transmitting, by the control unit, the biometric data to a remote unit; and receiving, by the control unit, one or more messages from the remote unit, the one or more messages including information associated with the biometric data. Additionally, in some embodiments, the method can comprise displaying, by the display unit, the one or more messages to the user of the wearable device.

Similar to that discussed above, the remote unit can comprise a computer-executable application including a graphical user interface for interacting with a user of the remote unit. Additionally, similar to that discussed above, the sensing, by the biometric sensor unit, can comprise sensing, by one or more sensors, a plurality of metrics associated with the physiological condition of the user. In some embodiments, the plurality of metrics comprising at least one of the user's body temperature, heart rate,  $VO_{2max}$  respiration, steps taken, blood pressure, and calories burnt while using the wearable device.

### BRIEF DESCRIPTION OF THE DRAWINGS

Reference will now be made to the accompanying drawings, which are not necessarily drawn to scale.

FIGS. 1a and 1b illustrate systems for sensing, displaying, and/or communicating a plurality of data corresponding to a user, in accordance with an embodiment of the present disclosure.

FIG. 2a illustrates an embodiment of a wearable device attached to headwear, in accordance with the present disclosure.

FIG. 2b illustrates a control unit of the wearable device, in accordance with an embodiment of the present disclosure.

FIG. 2c illustrates an attachment interface for attaching the control unit to headwear, in accordance with an embodiment of the present disclosure.

FIGS. 3a and 3b illustrate a biometric sensor unit comprising a biometric earpiece, in accordance with an embodiment of the present disclosure.

FIG. 4 illustrates a display unit of the wearable device, in accordance with an embodiment of the present disclosure.

FIG. 5 illustrates an implementation of systems and devices with users of wearable devices according to embodiments of the present disclosure.

FIG. 6 illustrates exemplary architecture of a control unit interacting with other components of the wearable device and a remote unit, in accordance with an embodiment of the present disclosure.

FIG. 7 illustrates another embodiment of a wearable device for sensing, displaying, and/or communicating a plurality of data corresponding to a user, in accordance with the present disclosure.

FIGS. 8a and 8b illustrate another embodiment of a wearable device for sensing, displaying, and/or communicating a plurality of data corresponding to a user, in accordance with the present disclosure.

FIGS. 9a and 9b illustrate another embodiment of a wearable device for sensing, displaying, and/or communicating a plurality of data corresponding to a user, in accordance with the present disclosure.

FIG. 10 is an exemplary computer architecture for use with various aspects of a computer-executable application, in accordance with an embodiment of the present disclosure.

FIG. 11 illustrates a graphical user interface of a computer-executable application, in accordance with an embodiment of the present disclosure.

FIG. 12 is another illustration of a graphical user interface of a computer-executable application, in accordance with an embodiment of the present disclosure.

FIG. 13 is another illustration of a graphical user interface of a computer-executable application, in accordance with an embodiment of the present disclosure.

### DETAILED DESCRIPTION

In some aspects, the present disclosure relates to wearable devices for detecting, displaying, and communicating data associated with a user. Although example embodiments of the present disclosure are explained in detail herein, it is to be understood that other embodiments are contemplated. Accordingly, it is not intended that the present disclosure be limited in its scope to the details of construction and arrangement of components set forth in the following description or illustrated in the drawings. The present disclosure is capable of other embodiments and of being practiced or carried out in various ways.

It must also be noted that, as used in the specification and the appended claims, the singular forms "a," "an" and "the" include plural referents unless the context clearly dictates otherwise. Ranges may be expressed herein as from "about" or "approximately" one particular value and/or to "about" or "approximately" another particular value. When such a range is expressed, other exemplary embodiments include from the one particular value and/or to the other particular value.

By "comprising" or "containing" or "including" is meant that at least the named compound, element, particle, or method step is present in the composition or article or method, but does not exclude the presence of other compounds, materials, particles, method steps, even if the other

such compounds, material, particles, method steps have the same function as what is named.

In describing example embodiments, terminology will be resorted to for the sake of clarity. It is intended that each term contemplates its broadest meaning as understood by those skilled in the art and includes all technical equivalents that operate in a similar manner to accomplish a similar purpose. It is also to be understood that the mention of one or more steps of a method does not preclude the presence of additional method steps or intervening method steps between those steps expressly identified. Steps of a method may be performed in a different order than those described herein without departing from the scope of the disclosed technology. Similarly, it is also to be understood that the mention of one or more components in a device or system does not preclude the presence of additional components or intervening components between those components expressly identified.

A detailed description of aspects of the present disclosure, in accordance with various example embodiments, will now be provided with reference to the accompanying drawings. The drawings form a part hereof and show, by way of illustration, specific embodiments and examples. In referring to the drawings, like numerals represent like elements throughout the several figures.

In some aspects, the present disclosure can relate to systems for sensing, displaying, and/or communicating a plurality of data associated with a condition of the user. FIGS. 1a and 1b illustrate exemplary systems 100a, 100b for sensing, displaying, and/or communicating a plurality of data corresponding to a user. As illustrated at FIG. 1a, a wearable device 110 can be in communication with a remote unit 120. The wearable device 110 can be configured to sense biometric data associated with a condition of a user of the wearable device 110 and can comprise a communication unit 130 configured to transmit indications of the biometric data along a transmission pathway 150a to the remote unit 120. The remote unit 120 can be configured to receive the indications of the biometric data from the wearable device 110 via a remote communication unit 140. The remote unit 120 can be further configured to transmit information (e.g. one or more messages) along a transmission pathway 150b to the wearable device 110.

In some embodiments, as illustrated at FIG. 1a, the communication unit 130 and the remote communication unit 140 can be corresponding antenna units. For example, the wearable device can comprise a communication unit 130 attached thereto that is an antenna that transmits a signal, and the remote unit 120, which can include a computer, can be operatively connected to a corresponding communication unit 140 (e.g. through a USB port), that can be an antenna that can transmit a signal. Such interaction can, for instance, facilitate tracking and monitoring of a user's wellbeing or activity while the user is wearing the wearable device 110, by facilitating the transfer of relevant data between the wearable device 110 and the remote unit 120.

In other embodiments, the communication unit 130 and the remote unit 120 can comprise a cell phone chip enabling connecting, transmitting, and receiving data via a cellular network. The cell phone chip can include any telecommunications technology currently available, including GSM, 3G, or 4G systems, or subsequently developed.

FIG. 1b illustrates an exemplary system 100b and corresponding process for sensing, displaying, and communicating data associated with a condition of the user. The system 100b can comprise a wearable device 110, a server 160, a remote unit 120, and mobile device 170a used by a mobile

user 170b. As shown in FIG. 1b, the wearable device 110, remote unit 120, and mobile device 170a can communicate with each other through the server 160. The mobile user 170b can be, for instance, a past or future user of the wearable device 110.

As illustrated at FIG. 1b, transmission pathways can comprise a mobile user device 170a setting initial calibration data for when the mobile user 170b uses the wearable device 110. In some embodiments, the calibration data can include personal information about the mobile user 170b including but not limited to height, weight, age, and gender. Additionally, in some embodiments, each wearable device 110 may receive a unique identification number and may be recognized by a computer-executable application running on a computer of the remote unit 120, based on that identification number. Therefore, when a mobile user 170b is initially calibrating the wearable device 110, the mobile user 170b can input the unique identification number corresponding to the wearable device 110, thereby linking the mobile user's 170b profile with the wearable device 110. Associating a mobile user's 170 profile with an identification number of the wearable device 110 can permit various users to use the same wearable device 110. When the wearable device 110 is calibrated, the wearable device 110 can correspond with the specific mobile user 170b who will wear the wearable device 110 and calculate and transmit biometric data specific to that user.

The wearable device 110 can be in communication with the remote unit 120. For instance, as discussed previously, the wearable device 110 can detect data associated with a condition of a user and transmit that data to the remote unit 120. As illustrated in FIG. 1b, a server 160 can serve as an intermediary between the wearable device 110 and the remote unit 120. The remote unit 120 can be configured to receive the data from the server 160, and in some embodiments, display such data to a remote user accessing the remote unit via a computer-executable application. Additionally, the remote unit 120 can be configured to transmit information to the wearable device 110, which can include one or more messages. The server 160 can act as an intermediary between the remote unit 120 and the wearable device 110 and transmit the information to the wearable device 110.

In other embodiments (not shown), the wearable device 110 can communicate directly to the remote unit 120 without interfacing through the server 160. Following, the remote unit 120 can be in communication with the server 160 for the purpose of storing or otherwise communicating data associated with the user of the wearable device.

FIGS. 2a-2c, 3a, 3b, and 4 illustrate aspects of the present disclosure include a wearable device 110 for sensing, displaying, and/or communicating a plurality of data associated with a condition of a user of the wearable device 110. As illustrated in 2a-2c, 3a, 3b, and 4, the wearable device 110 can comprise a control unit 200 (FIGS. 2a-2c), a biometric sensor unit 300 (FIGS. 3a and 3b), and a display unit 400 (FIG. 4). The control unit 200 can be integrally connected with or selectively attached to headwear 220 worn by a user and can comprise an attachment interface 230a, 230b, as illustrated in FIGS. 2a-2c. In some embodiments, the headwear 220 worn by a user can be a SCBA. As illustrated in FIGS. 3a-3b, the biometric sensor unit 300 can comprise a plurality of biosensors (325a, 325b) capable of detecting a plurality of conditions indicative of a state of the user's body while the user is wearing the wearable device 110. In some embodiments, the biometric sensor unit 300 can comprise an ear-receiving portion 310 wearable on and/or in the user's

ear, as illustrated in FIGS. 3a-3b. As illustrated in FIGS. 4 and 5, in some embodiments, the display unit 400 can be positioned within a field of view of the user and provide a visual representation of the biometric data and/or other information to the user.

FIGS. 2a and 2b illustrate an exemplary embodiment of a control unit 200 for use in a wearable device 110. In some embodiments, a biometric sensor unit 300 can be connected to the control unit 200 via a wire 330. Aspects of the biometric sensor unit 300 will be discussed in greater detail with respect to FIGS. 3a-3b.

As shown in FIG. 2b, the control unit 200 can comprise a housing 215 containing a variety of hardware and devices for controlling and directing information flow as well as tracking other relevant metrics associated with the user of the wearable device. Additionally, in some embodiments, the control unit 200 can comprise an external or internal antenna. For example, FIGS. 2a-2b illustrate an external antenna 250 attached to the control unit 200, in accordance with an embodiment of the present disclosure. The external antenna 250 can permit transmission of data acquired by the wearable device 110 to a remote unit 120, such as that illustrated in FIGS. 1a-1b.

The housing 215 can contain a variety of hardware and devices (illustrated in greater detail at FIG. 6). For instance, the housing 215 can include one or more of a microcontroller (e.g., one or more programmable computer processors), magnetometer, gyroscope, accelerometer, radio (comprising one or more antennas), battery, one or more buses, and one or more temperature sensors. Additionally, the housing 215 of the control unit 200 can be made of any suitable material currently available or subsequently developed that is sufficiently durable for a variety of uses. In an embodiment for use within a very hot area, the housing 215 can be made out of a material that can provide heat-resistance. For instance, the material can be one or more of Teflon, fiberglass, and high-temperature epoxy. In other embodiments, the housing 215 can be made of a flame-retardant material.

FIG. 2c illustrates an exemplary attachment interface 260 for attaching the control unit 200 to the headwear 220, in accordance with an embodiment of the present disclosure. The attachment interface can comprise a socket 230b that can receive a corresponding fastener 230a (as shown in FIG. 2a). The socket 230b can be embedded into a frame 225 of the headwear 220. The attachment interface 260 can allow for attaching the control unit (shown in FIGS. 2a-2b) to headwear 220.

FIGS. 3a and 3b illustrate an exemplary biometric sensor unit 300 comprising a biometric earpiece configured to be received by an ear of the user of the wearable device. The biometric sensor unit 300 can be any device comprising a plurality of sensors capable of sensing biometric data associated with the user. For instance, in some embodiments, as illustrated at FIG. 3a, the biometric sensor unit 300 can comprise a plurality of sensors (325a, 325b) for sensing biometric data associated with a physiological condition of the user. While embodiments of the biometric sensor unit 300 are illustrated in the drawings as a biometric earpiece, it is understood that the biometric sensor unit can comprise other devices (wearable or not) capable of sensing biometric data associated with a physiological condition of the user. Additionally, the plurality of sensors integrated with the biometric sensor unit can be a variety of sensors capable of detecting data associated with a condition of the user, including electro-optical sensors, thermal sensors, oxygen sensors, moisture sensors, and/or biosensors.

As illustrated in FIG. 3a, the biometric earpiece can comprise an ear-receiving portion 310 having an ear interface 320. Additionally, one or more sensors 325a, 325b can be integrated with the ear-receiving portion 310 to detect a plurality of data associated with a condition of the user. In some embodiments, the ear-receiving portion 310 can comprise one or more sensors 325b located in a lower portion of the ear-receiving portion and one or more sensors 325a located proximate the ear interface 320. For example, a plurality of sensors 325b detecting the heart rate, the  $VO_{2max}$ , heart rate quality signal, and steps can be integrated in the lower portion of the ear-receiving portion 310 and a digital temperature sensor 325a can be integrated in the ear interface 320. In some embodiments, the plurality of sensors integrated in the ear-receiving portion 310 can be Valencell's PerformTek® sensor. In other embodiments, the plurality of sensors 325a, 325b integrated with the ear-receiving portion 310 can be one or more optical sensors. Additionally, in some embodiments, the ear-receiving portion 310 can comprise a speaker to serve a variety of purposes, including amplification of external sounds or communications from remote users, or a plurality of moisture sensors. In other embodiments, the ear-receiving portion can comprise a bone conduction microphone to, for instance, transmit the user's voice to the remote user.

In some embodiments, the biometric sensor unit 300 can comprise a biometric earpiece having an ear-receiving portion 310 that can be configured to fit snugly within the user's ear, as illustrated at FIG. 3b. For instance, in some embodiments, the ear-receiving portion 310 can include a flexible ring 335 attached proximate an upper portion of the ear-receiving portion 310. In some embodiments, the flexible ring 335 can comprise a resilient material to maintain a snug fit within the user's ear, as illustrated at FIG. 3b. In other embodiments, the biometric earpiece can comprise an over the ear loop (not shown) that fits behind the user's ear and assists with holding the earpiece in place.

Additionally, the biometric sensor unit 300 can be operatively connected with the control unit 200. In embodiments comprising a biometric earpiece, as illustrated at FIG. 3a, the biometric earpiece can comprise a wire 330 extending from the ear-receiving portion 310 and connecting with the control unit 200 via an electrical connector 350. As such, the biometric earpiece can relay the data detected by the sensors 325a, 325b to the control unit 200. For instance, in an embodiment, the biometric sensor unit 300 can be connected to the control unit 200 by a simple wire that connects to a Japanese solderless terminal (JST) bus. Additionally, to improve resistance to atmospheric factors, the wire 330 of the biometric sensor unit 300 can be coated in a flame-retardant or high-temperature epoxy or silicon sleeving to protect the wire 330.

While embodiments of the biometric sensor unit 300 described above can use a wired connection between the biometric sensor unit 300 and the control unit 200, the biometric sensor unit 300 can be in wireless communication with the control unit 200. For example, in some embodiments, the biometric sensor unit 300 can include, for instance, a Bluetooth device for providing wireless communication between the biometric sensor unit 300 and the control unit 200.

FIG. 4 illustrates an exemplary display unit 400 mounted within headwear 220 worn by a user. The display unit 400 can comprise any device capable of displaying information to a user. In some embodiments, the display unit 400 can comprise a near-eye display capable of displaying a variety of information to the user of the wearable device. In other

embodiments, the display unit **400** can comprise a heads up display capable of displaying a variety of information to the user of the wearable device. In other embodiments, the display unit **400** can display the information on a semi-transparent surface, like a screen or the visor of the headwear. Other optical systems that can be incorporated in the display unit **400** include a virtual reality display, eye tracking, head tracking, a head-mounted display, display magnification, and/or an optical head-mounted display.

As illustrated at FIG. **4**, the display unit **400** can be mounted within a field of view of the user and can be positioned proximate the wearer's eye(s) when the wearer is wearing headwear **220**. The display unit **400** can comprise a casing **410**, a screen **420**, and an optical display system **430** (showing a lens, the remainder of the optical display system not shown) for displaying information to the user. For instance, as illustrated at FIG. **4**, the display unit **400** can be mounted on a left-most portion of the interior of the headwear **220**, relative to the user of the wearable device **110**. As such, the display unit **400** and the information displayed thereon can be visible in the left eye of the user. Those skilled in the art will understand that mounting the display unit **400** in a side portion of the headwear **220** can avoid obstructing the user's view. In other embodiments, however, the display unit **400** can be mounted on the right-most portion of the headwear **220** or on both side portions of the headwear **220**.

In some embodiments, the display unit **400** can comprise a near-eye display. Near-eye displays can utilize the human eye for up-close image display such that the human eye acts as the last element in the optical chain with a final image being created on the eye's retina. The near-eye display can generally comprise a virtual image, a microdisplay, and a lens. The lens of the near-eye display can provide magnification of the virtual image to the user of the near-eye display. Additionally, the microdisplay contained within the near-eye display can comprise a waveguide optical element that collects light at the input and relays it towards the user's eye. In some embodiments, the near-eye display can comprise additional components for minimizing latency, maximizing optical contrast, and maximizing the field of view.

In some embodiments, the display unit **400** can comprise a heads up display. In embodiments incorporating a heads up display, the heads up display can comprise a projector unit, a combiner, and an optical display system. The projector unit can comprise an optical collimator including a convex lens or a concave mirror and a lighting element. For example, the lighting element can comprise LEDs or backlight sources. In some embodiments, the combiner can comprise a beam splitter. In some embodiments the optical display system can comprise a computer unit incorporating a receiver for receiving information to be displayed to the user.

In some embodiments, the display unit **400** can be mounted to the headwear **220** using an adjustable, flexible or semi-flexible member **440** such as a wire (e.g., selectively bendable copper wire). The adjustable member **440** can permit the user to adjust the display unit **400** within the headwear **220** to make slight adjustments and clear the user's line of sight. Mounting the display unit **400** in line with the user's eyes can have the added advantage of not obstructing the user's view of the floor or ceiling, for instance. Additionally, those skilled in the art will understand that the display unit **400** can be mounted within the interior of the headwear **220** in a variety of ways, including adhesive, hook and loop fasteners, or other adjustable mounting elements composed of other suitable materials, other than copper.

In some embodiments, to connect the display unit **400** with the control unit **200**, a high temperature ribbon cable **450** attached to the display unit **400** can be navigated through the headwear **220** and integrated with the control unit **200**. In some embodiments, the display unit **400** can comprise a UART bus controllable by the processor. In other embodiments, the display unit **400** can be connected to the control unit **200** using Bluetooth or other similar wireless technology.

In another embodiment, the display unit **400** can be incorporated into the outer housing of the control unit **200**. In such an embodiment, the display unit can comprise one or more indicator lights that communicate with the user if certain biometrics are within a normal or risky range. For instance, in some embodiments, the display unit can comprise two indicator lights, one green and one red. If the green indicator light is lit up, then that will indicate to the user that all biometrics are in a normal range. If the red indicator light is lit up, this will indicate to the user that some or all biometrics are exceeding the normal level and indicative of a warning that the biometric is approaching a dangerous or unhealthy level.

FIG. **5** illustrates an implementation **500** of certain aspects of systems and devices in accordance with embodiments of the present disclosure. FIG. **5** illustrates a visual representation **510** that a user **520** wearing the wearable device may view using the display unit **400**. As illustrated at FIG. **5**, the display unit, such as that illustrated in FIG. **4**, can display a variety of information **530** to the wearer **520** in an abbreviated format. For instance, the display unit **400** can show life-critical data to the user including the ambient temperature surrounding the user, the current battery level of the device, the compass heading the user is facing, a biometric data line, sensor readings, action items, and/or personal text messages (see also FIGS. **11-13**). In an embodiment, as illustrated at FIG. **5**, the display unit **400** can provide the user **520** with the ambient temperature **531**, the user's compass direction **533**, the user's heart rate **535**, action items **537**, and messages **539**.

In some embodiments, an ambient temperature reading can be useful in detecting flashover events. In some embodiments, the text messages can be from a remote user to the user of the wearable device, for example messages regarding the wellbeing of the user of the wearable device **110**. The action items can be, for instance, sent from a remote user accessing a device incorporating a communication unit, as illustrated at FIGS. **1a-1b**, which can transmit a message receivable by a radio unit incorporated within the wearable device **110**. In some embodiments, the action items and personal message areas can incorporate scrolling text if the message received is above a particular character limit. For instance, the scrolling text can incorporate automated scrolling functionality. In some embodiments, the biometric data line displays the heart rate, pulse, oxygenation level, and respiratory rate of the user of the wearable device. In some embodiments, the display unit can cycle through a plurality of displays incorporating different information. It should be appreciated that having an integrated display unit in the wearable device, as described above, can allow for real-time monitoring of a variety of biometrics as well as incorporate communication functionality, essential for receiving commands, instructions, or other messages.

Additionally, in some embodiments, the display unit **400** can cycle through various combinations of metrics or messages over time. Other metrics that the display unit **400** can provide to the user **320** may include body temperature, heart rate, external temperature,  $VO_{2,max}$ , heart-rate variability,

signal level of the wearable device 110, battery level of the wearable device 110, and/or blood pressure.

FIG. 6 is an exemplary diagram of the interior of the control unit 200. The control unit 200 can comprise a housing 215 that may contain one or more of a processor 610, a gyroscope and accelerometer unit 620, one or more temperature sensors 630, one or more magnetometers 640, a battery 650, and a communication unit including a receiver 660 and a transmitter 670. In some embodiments the processor 610 can be a microcontroller comprising one or more programmable computer processors. In some embodiments, the receiver 660 and the transmitter 670 can comprise one or more antennas. In addition to the components illustrated in FIG. 6, the control unit 200 can comprise various other devices including one or more buses, various other sensors, and other electrical components.

As illustrated at FIG. 6, in some embodiments, the processor 610 can control and direct the flow of information from the sensors located in the biometric sensor unit 300 and the other devices housed within the control unit 200, such as the gyroscope/accelerometer unit 620, the temperature sensor 630, and the magnetometer 640, or other additional sensor unit or device known in the art. Additionally, the processor 610 can control and direct the flow of information to and from the transmitter 670 and the receiver 660, respectively, permitting communication with a remote unit or server. The processor 610 can further control and direct the flow of information to the display unit 400.

The processor 610 can be any microcontroller, for example Teensy++. The magnetometer 640 can be any suitable magnetometer that can, for instance, include a three-axis sensor that can detect Earth's magnetic field to provide a compass heading. The gyroscope/accelerometer unit(s) 620 can comprise any gyroscope that includes a three-axis angular rate sensor and the accelerometer 620 can be any accelerometer that includes a three-axis sensor that can detect acceleration. The gyroscope and accelerometer data can be combined to deduce the yaw, tilt, and roll of the housing on the side of the headwear. The yaw, tilt, and roll can then be normalized and calibrated with the magnetometer data to give an accurate compass heading despite the orientation of the magnetometer 640. In other embodiments, the processor can be configured to determine the geo-location using the radio signal. Additionally, the processor can be configured for indoor tracking or triangulation. For instance, the control unit 200 can trace or track the movements of a user throughout an area.

The temperature sensor 630 can serve a variety of functions, including monitoring the temperature inside the housing 215 of the control unit 200 to determine if the inside of the housing 215 is cool enough for the processor 610 to be in an operating state and also monitoring the ambient temperature around the user. In some embodiments, if an unsafe temperature inside the housing 215 is reached, the control unit 200 can be configured to shut down. The temperature sensor that can detect the ambient temperature surrounding the user can be exposed to the atmosphere around the control unit. For example, the temperature sensor can be exposed through a small hole in the housing.

Additionally, the control unit 200 can be in communication with a variety of devices including the biometric sensor unit 300, the display unit 400, a remote server, and a remote unit (as shown in FIGS. 1a and 1b). To allow the wearable device 110 to communicate with, for instance, a server and a remote unit, the control unit 200 can include a communication unit 250 comprising a receiver 660 and a transmitter 670. In some embodiments, the communication unit 250 can

comprise a radio unit, such as the Xbee Pro Series 1 60 mW Wire Antenna. This radio unit can operate at 3.3 V at a current value of 215 mA, with a range of one mile. The radio unit can use the 802.15.4 IEEE standard for packet transmission. The data gathered by the processor 610 can be transmitted back to a remote user using the communication unit 250 via the transmitter 670 and information from the remote unit or server can be received by the control unit at the receiver 660.

FIG. 7 illustrates another embodiment of a wearable device 700 in accordance with the present disclosure. As shown, the wearable device 700 can be worn concurrently with headwear 720. The wearable device 700 can comprise a control unit 710, a biometric sensor unit (not shown, but similar to that illustrated in FIG. 1d), and a display unit 730. The control unit 710 can comprise a housing 715 mounted to a side of the headwear 720. For instance, the housing 715 can be integrally connected to the headwear 720 and thereby comprise an attachment interface (not shown, but similar to that illustrated in FIG. 1c). The attachment interface can comprise a fastener, such as a screw, that can engage a corresponding socket thereby attaching the housing 715 to the headwear 720. As illustrated in FIG. 7, the control unit 710 can attach to a left side of the headwear 720 on a frame 721 surrounding the visor 723. The control unit 710 can be sized and positioned so as not to block the user's visibility or components of the headwear 720, such as mechanical speaking diaphragms 725 in the headwear 720. To attach the control unit 710 to the headwear 720 as such, a socket can be embedded in the frame 721 of the headwear 720 on the left side (relative to the user). In other embodiments, however, the control unit 710 can be positioned on a right side of the headwear 720 and include a fastener in the frame 721 on the right side of the headwear 720.

Some embodiments of the wearable device 700 as illustrated at FIG. 7 can incorporate a biometric sensor unit, such as that illustrated in FIGS. 3a-3b, and a display unit 730. Therefore, the biometric sensor unit and the display unit 730 can comprise some or all of the features discussed above. As illustrated at FIG. 7, and similarly to FIG. 4, the display unit 730 can be located within the interior of the headwear 720 near at least one eye of the user, and can include an adjustable member 735 (such as a wire) that can be used for adjusting the position and/or location of the display unit 730 relative to an eye of the user. Additionally, the wearable device 700 can comprise a plurality of add-ons allowing a user to interact with the device 700 attached to the control unit 710. For instance, the add-ons can include a light 740 or thermal imaging camera to assist with visibility in front of and around the user. Additionally, the control unit 710 may comprise a plurality of switches 745a, 745b for turning the wearable device 700 on and off and/or the additional light 740. Additionally, in some embodiments, the control unit 710 can comprise an indicator light 750 that will light up upon turning on the wearable device 700.

FIGS. 8a and 8b illustrate another embodiment of a wearable device 800, in accordance with the present disclosure, worn concurrently with headwear 820. The wearable device 800 can comprise a control unit 810, a biometric sensor unit (not shown, but similar to that illustrated in FIG. 4), and a display unit. The control unit 810 can comprise a dashboard 815 mounted to a front portion of the headwear 820. The dashboard 815 can comprise an arced, hollow enclosure that fits around a front portion of the headwear 820. The dashboard 815 can contain a plurality of devices and hardware, as discussed above, and also encase two display units 830a, 830b, as illustrated in FIG. 8b. The

control unit **810** can be integrally connected to headwear **820** worn by a user and thereby comprise an attachment interface, as discussed above with respect to FIG. **2c**. The attachment interface can comprise a fastener, such as a screw, that can screw into a corresponding socket thereby attaching the housing to the headwear. In contrast to the attachment interface illustrated in FIG. **2c**, the attachment interface can include a fastener and socket on each side of the headwear. In other embodiments, the control unit **810** can be attached to the front of a mask of the headwear using adhesive or other suitable attachment mechanism.

As illustrated at FIG. **8b**, the wearable device can include dual display units **830a**, **830b** embedded within the housing. The dual display units **830a**, **830b** can comprise screens on which a plurality of items of information can be displayed. Additionally, in some embodiments, each display unit **830a**, **830b** can display different information. For instance, display unit **830a** can display the user's temperature, heart rate, action items, and battery life of the wearable device, while display unit **830b** can show the user's acceleration in the x-, y-, and z-directions.

FIGS. **9a-9b** illustrate another embodiment of a wearable device **900** in accordance with the present disclosure. As shown, the wearable device **900** comprises a control unit **910**, a biometric sensor unit **930**, and a display unit (illustrated in FIG. **9b**). The control unit **910** can be attached to the headwear **920**. As illustrated at FIG. **9a**, the control unit **910** can comprise a housing **915** that is configured to wrap around a side of the headwear **920** and connect to an attachment interface. As shown in FIG. **9**, the control unit **910** can comprise a housing **915** having an elongated portion that houses a plurality of hardware and devices. Additionally, a display unit **940** can be disposed external to the headwear **920** and can be located proximate a bottom portion of the visor **925**.

As illustrated at FIG. **9b**, the display unit **940** can comprise an icon portion **945** and a data portion **955**. The icon portion **945** can be located on a top portion of the housing **915** of the control unit **910** and can comprise a plurality of icons indicative of individual biometrics. For instance, as illustrated at FIG. **9b**, the plurality of icons can be a compass indicator, a heart rate indicator, an internal temperature indicator, and an external temperature indicator. The plurality of icons can be LED backlit and configured to change color (e.g. green, yellow, or red) to correspond to the range in which the user's biometric fall (discussed in more detail below). For instance, green can correspond to a biometric within a pre-determined range indicative of a normal level, yellow can correspond to a biometric exceeding the normal level and indicative of a warning that the biometric is approaching a risky level, and red where the biometric has reached a dangerous or unhealthy level. Such threshold ranges for color changes in the icons can be predetermined in accordance with similar methods as those discussed below with respect to FIGS. **11-12**.

In some embodiments, the pre-determined range can be specific to the user. For instance, the pre-determined range can be calculated from a variety of metrics including the user's health characteristics, such as age, gender, weight, and height.

The data portion **955** can display alphanumeric representations of data associated with a user. For instance, as illustrated in FIG. **9b**, the data portion can display the compass heading (e.g. NE), the heart rate (e.g. **165**), the body temperature (e.g. **98.6**) and the external temperature (e.g. **198**). The data portion **955** can be configured to provide updated data corresponding to the data sensed by the bio-

metric sensor unit. In other embodiments, the display unit **940** can include icons related to other biometrics and display data on the data portion **955** corresponding to various other biometrics, as described previously.

While the previously described embodiments are illustrated in reference to headwear, it is understood that the described wearable devices can be incorporated within a variety of garments or protective gear. For instance, the control unit can attach to the user's shirt, within the user's pocket, to the user's belt, to SCBA or other protective helmets or masks.

In some embodiments, the wearable device described above can also be in communication with a computer-executable application remotely located from the wearable device. The computer-executable application can be configured for receiving, displaying, and/or tracking the plurality of biometric data corresponding to a user of the remote device.

As described above, the control unit of the wearable device can comprise a communication unit, including a transmitter and a receiver, for transmitting the biometric data to the application and receiving a plurality of messages from the application. The remote unit can include a separate communication unit (as illustrated at FIGS. **1a** and **1b**). The application can be implemented on any platform including, but not limited to, a desktop or lap-top computer, a tablet computer, a mobile phone, or other computing device. FIGS. **1a** and **1b**, discussed previously, illustrate an exemplary remote unit **120** for allowing communication from the wearable device **110** to a remote user accessing the remote unit. The remote unit **120** can comprise, for instance, a command station, a base station, a wearable device user accessing a profile tracking his individual metrics. Or, in some embodiments, the remote unit **120** can be a server or other intermediary device.

FIG. **10** is a computer architecture diagram showing a general computing system capable of implementing aspects of the disclosed technology in accordance with one or more embodiments described herein. A computer **1000** may be configured to perform one or more functions associated with, for example, the remote unit **120** shown in FIGS. **1a** and **1b** and aspects of the computer-executable application illustrated with respect to FIGS. **11-13**. For example, the computer **1000** may be configured to perform various aspects of receiving, processing, displaying, and/or transmitting a plurality of biometric data received from and/or transmitted to a wearable device to a remote user accessing an application. It should be appreciated that the computer **1000** may be implemented within a single computing device or a computing system formed with multiple connected computing devices. The computer **1000** may be configured to perform various distributed computing tasks, in which processing and/or storage resources may be distributed among the multiple devices.

As shown, the computer **1000** includes a processing unit **1002** ("CPU"), a system memory **1004**, and a system bus **1006** that couples the memory **1004** to the CPU **1002**. The computer **1000** further includes a mass storage device **1012** for storing program modules **1014**. The program modules **1014** may be operable to perform various functions associated with associated with receiving, processing, and displaying a plurality of biometric data received from a wearable device to user accessing an application, as illustrated in one or more of FIGS. **11-13** discussed above. The program modules **1014** may include a computer-executable application **1018** for performing data acquisition and/or processing functions as described herein, for example to acquiring,

calculating, organizing, and analyzing data associated with a condition of the user. The computer **1000** can include a data store **1020** for storing data that may include biometric-related data **1022** such as indications of sensed biometric data corresponding to a physiological condition of a user, in accordance with various embodiments.

The mass storage device **1012** is connected to the CPU **1002** through a mass storage controller (not shown) connected to the bus **1006**. The mass storage device **1012** and its associated computer-storage media provide non-volatile storage for the computer **1000**. Although the description of computer-storage media contained herein refers to a mass storage device, such as a hard disk or CD-ROM drive, it should be appreciated by those skilled in the art that computer-storage media can be any available computer storage media that can be accessed by the computer **1000**.

By way of example and not limitation, computer storage media (also referred to herein as “computer-readable storage medium” or “computer-readable storage media”) may include volatile and non-volatile, removable and non-removable media implemented in any method or technology for storage of information such as computer-storage instructions, data structures, program modules, or other data. For example, computer storage media includes, but is not limited to, RAM, ROM, EPROM, EEPROM, flash memory or other solid state memory technology, CD-ROM, digital versatile disks (“DVD”), HD-DVD, BLU-RAY, or other optical storage, magnetic cassettes, magnetic tape, magnetic disk storage or other magnetic storage devices, or any other medium which can be used to store the desired information and which can be accessed by the computer **1000**. “Computer storage media”, “computer-readable storage medium” or “computer-readable storage media” as described herein do not include transitory signals.

According to various embodiments, the computer **1000** may operate in a networked environment using connections to other local or remote computers through a network **1016** via a network interface unit **1010** connected to the bus **1006**. The network interface unit **1010** may facilitate connection of the computing device inputs and outputs to one or more suitable networks and/or connections such as a local area network (LAN), a wide area network (WAN), the Internet, a cellular network, a radio frequency (RF) network, a Bluetooth-enabled network, a Wi-Fi enabled network, a satellite-based network, or other wired and/or wireless networks for communication with external devices and/or systems. The computer **1000** may also include an input/output controller **1008** for receiving and processing input from any of a number of input devices. Input devices may include one or more of keyboards, mice, stylus, touchscreens, microphones, audio capturing devices, and image/video capturing devices. An end user may utilize the input devices to interact with a user interface, for example a graphical user interface, for managing various functions performed by the computer **1000**. The bus **1006** may enable the processing unit **1002** to read code and/or data to/from the mass storage device **1012** or other computer-storage media. The computer-storage media may represent apparatus in the form of storage elements that are implemented using any suitable technology, including but not limited to semiconductors, magnetic materials, optics, or the like. The computer-storage media may represent memory components, whether characterized as RAM, ROM, flash, or other types of technology.

The computer storage media may also represent secondary storage, whether implemented as hard drives or otherwise. Hard drive implementations may be characterized as solid state, or may include rotating media storing magneti-

cally-encoded information. The program modules **1014**, which include the imaging application **1018**, may include instructions that, when loaded into the processing unit **1002** and executed, cause the computer **1000** to provide functions associated with one or more example embodiments and implementations illustrated in, for example, FIGS. **1a**, **1b**, and **11-13**. The program modules **1014** may also provide various tools or techniques by which the computer **1000** may participate within the overall systems or operating environments using the components, flows, and data structures discussed throughout this description.

In general, the program modules **1014** may, when loaded into the processing unit **1002** and executed, transform the processing unit **1002** and the overall computer **1000** from a general-purpose computing system into a special-purpose computing system. The processing unit **1002** may be constructed from any number of transistors or other discrete circuit elements, which may individually or collectively assume any number of states. More specifically, the processing unit **1002** may operate as a finite-state machine, in response to executable instructions contained within the program modules **1014**. These computer-executable instructions may transform the processing unit **1002** by specifying how the processing unit **1002** transitions between states, thereby transforming the transistors or other discrete hardware elements constituting the processing unit **1002**. In other embodiments the processing unit can operate as a real time operating system configured to schedule and coordinate multiple tasks from the sensors, communication units, etc.

Encoding the program modules **1014** may also transform the physical structure of the computer-storage media. The specific transformation of physical structure may depend on various factors, in different implementations of this description. Examples of such factors may include, but are not limited to the technology used to implement the computer-storage media, whether the computer storage media are characterized as primary or secondary storage, and the like. For example, if the computer storage media are implemented as semiconductor-based memory, the program modules **1014** may transform the physical state of the semiconductor memory, when the software is encoded therein. For example, the program modules **1014** may transform the state of transistors, capacitors, or other discrete circuit elements constituting the semiconductor memory.

As another example, the computer storage media may be implemented using magnetic or optical technology. In such implementations, the program modules **1014** may transform the physical state of magnetic or optical media, when the software is encoded therein. These transformations may include altering the magnetic characteristics of particular locations within given magnetic media. These transformations may also include altering the physical features or characteristics of particular locations within given optical media, to change the optical characteristics of those locations. Other transformations of physical media are possible without departing from the scope of the present description, with the foregoing examples provided only to facilitate this discussion.

In some embodiments, the computer-executable application associated with the remote unit may be accessible by a variety of users simultaneously. The computer-executable application can receive a plurality of biometric data from one or more users of the wearable device. The received biometric data can include a variety of biometric data including, but not limited to, ambient temperature, body temperature, heart rate, oxygen consumption, oxygen saturation of the blood, blood pressure, energy expenditure,

respiration rate, speed, calories burnt, steps taken, cardiac efficiency, and heart rate variability. A remote user using the computer-executable application can then track the biometric data received from the wearable device. Additionally, in some embodiments, the computer-executable application can permit the remote user to transmit a plurality of messages to users wearing the wearable device. For instance, the remote user can transmit messages regarding biometrics of the user wearing the wearable device, such as telling such user to take a break, or action items for the user to perform. In other embodiments the remote user can transmit a plurality of messages to multiple users wearing wearable devices, at the same time. In some embodiments, the computer-executable application can be configured to extract a numerical representation of the sensed biometric data from indications of the biometric data transmitted from the wearable device. The computer-executable application can then analyze the biometric data to provide a method for a remote user to monitor biometric data associated with a user of the wearable device. For instance, the computer-executable application may be configured to compare the numerical representation of the sensed biometric data to a threshold value corresponding to a predetermined biometric range and create one or more graphical representations of the sensed biometric data for display on the graphical user interface. The one or more graphical representations will be discussed in further detail with respect to FIGS. 11-13.

Following display of the graphical representations to the remote user, the remote user may generate one or more messages to communicate with a user of the wearable device. For instance, the computer-executable application can generate one or more messages indicating at least one of i) the biometric data associated with the user of the wearable device, ii) action items to be performed by the user of the wearable device, and iii) status messages associated with a condition of the user of the wearable device.

external temperature, and  $VO_{2max}$  within a particular range. The gauge charts can comprise a variety of colors in a spectrum indicative of where the detected biometric falls in a range from normal or safe to abnormal or unsafe. For instance, as illustrated at FIGS. 11-12, the gauge for heart rate can display a range of BPMs between 30 and 230 BPM. In some embodiments, the GUI can display the heart rate of the user of the wearable device underneath the gauge chart and the gauge chart can change colors. For instance, green can correspond to a heart rate in a normal range, yellow can correspond to a heart rate in a moderately unhealthy or dangerous range, and red can correspond to a heart rate in a highly unhealthy or dangerous range. Exemplary ranges that these biometrics fall in are illustrated in Table 1. Similar concepts can be applied to body temperature, external temperature, and  $VO_{2max}$  measurements received, as well as any other biometric of interest.

Additionally, other metrics can be included in the chart, including the number of calories burned by a user, the number of steps taken, the battery life of the wearable device, and the respective wireless connections between the wearable device and the remote device accessing the application. Other metrics that can be displayed in the chart further include a level of fatigue, respiration rate, speed, cardiac efficiency, and heart rate variability. Table 1 below illustrates the ranges in which a user will receive different updates including whether certain biometrics are within a safe, warning, or danger range, and what measurements fall into what range. The ranges for each of the biometrics, such as those shown in Table 1, can be measured by the wearable device and can be predetermined in the application. Additionally, the thresholds set for charts, such as gauge charts, that illustrate biometric levels with incident color changes can be set via the application.

TABLE 1

Data Item	Minimum Value	Maximum Value	Safe Range	Warning Range	Danger Range	Units
External Temperature	0	1000	0-400	400-700	700-1000	Degrees Fahrenheit
Internal Temperature	0	110	96-100	None	0-96 & 100-110	Degrees Fahrenheit
Heart Rate	0	200	45-120	120-160	0-45 & 160-200	Beats/min
Battery	0	100	50-100	30-50	0-30	Percentage
$VO_{2max}$	0	100	38-100	28-37	0-27	ml/kg/min
Heart Rate Quality Signal	0	100	50-100	30-50	0-30	Percentage
Steps	0	N/A	N/A	N/A	N/A	Number of Steps
GSM Quality Signal	0	100	50-100	30-50	0-30	Percentage

The computer-executable application associated with the remote unit can comprise a graphical user interface (GUI). FIGS. 11-13 illustrate a variety of examples of GUIs that can be visible to a user when accessing the application. The GUIs can comprise a variety of windows, icons, and menus through which a user can interact with the application. For example, as illustrated at FIGS. 11-12, the GUI can comprise a window displaying a table comprising a plurality of charts associated with different biometrics. The plurality of charts can comprise any variety of charts that can display different biometrics, for instance histograms, gauge charts, and line charts. For instance, FIGS. 11-12 illustrate a plurality of gauge charts indicative of heart rate, body temperature,

Additionally, the ranges and thresholds chosen for monitoring various biometrics can be tuned to individual users. For instance, ranges can be determined based on the height, weight, age, and/or gender of the user. Additionally, ranges can be determined to compensate for activities engaged in by the user. For example, a nominal heart rate of the user may be computed to compensate for physical activity, such as carrying heavy loads, running, walking up stairs, in addition to bodily responses to emergency or exciting situations such as perpetuated adrenaline release, which can result in increases in the rate of blood circulation and breathing.

FIG. 13 illustrates another exemplary GUI in accordance with another embodiment of the present disclosure. The GUI illustrated in FIG. 13 is an abbreviated version of that shown in FIG. 13. The GUI can display various fields including “unit #,” “name,” “status,” and a message for each respective user. The “unit #” field can correspond with the number of the wearable device worn by the user. The “status” field can display any bodily status that may be outside a normal range, such as “High HR” corresponding to a high heart rate. Additionally, the message field can display a particular message conveyed to a user in response to the status of that user’s biometrics. Additionally, the application can display various “action items” that need to be carried out by the users.

Additionally, in some embodiments, the computer-executable application can include the ability to predict fatigue using machine learning. For instance, the application can comprise a variety of machine learning techniques including, but not limited to, Multi-class classification, two-class classification, regression and anomaly detection. Additionally, the machine learning algorithm can include any of Naïve Bayes Classification, Ordinary Least Squares Regression, Logistic Regression, Support Vector Machine, Ensemble methods, Principal Component Analysis, Gaussian Naïve Bayes, Multinomial Naïve Bayes, Bayesian Belief Networks, K-means, Neural Networks, etc. In some embodiments, using machine learning algorithms, discrete classification of fatigue levels can be obtained based off of both current and historical biometric data to predict fatigue of users in real time. Such learning can be achieved, for instance, in the context of supervised, reinforced or unsupervised learning by the algorithm and could also include deep learning (having multiple layers made up of the above machine learning algorithms such as first using a Support Vector Machine followed by using Logistic Regression).

The various embodiments described above are provided by way of illustration only and should not be construed to limit the scope of the present disclosure. Those skilled in the art will readily recognize various modifications and changes that may be made to the present disclosure without following the example embodiments and applications illustrated and described herein, and without departing from the true spirit and scope of the disclosure as set forth in the appended claims.

What is claimed is:

1. A wearable device at least partially attachable to headwear of a user, the wearable device for sensing, displaying, and communicating data associated with a condition of the user, the wearable device comprising:

a biometric sensor unit configured to sense biometric data associated with a physiological condition of the user, the biometric sensor unit comprising an earpiece configured to be received by an ear of the user, the biometric sensor unit outputting sensed biometric data;

a display unit configured to display at least one visual representation of the sensed biometric data to the user; and

a control unit attachable to the headwear, the control unit comprising a housing and operatively coupled to the biometric sensor unit and the display unit, wherein the display unit is integrated with the housing and positioned such that when the control unit is attached to the headwear, the visual representation is displayed within a field of view of the user, the control unit comprising:

at least one processor configured to receive indications of the sensed biometric data and cause the display

unit to display the at least one visual representation of the biometric data to the user, and

at least one communication unit, the communication unit configured to perform at least one of transmitting and receiving information associated with the sensed biometric data to and from a remote unit, respectively.

2. The wearable device of claim 1, wherein the biometric sensor unit comprises one or more sensors configured to sense a plurality of biometrics associated with the physiological condition of the user while using the wearable device, the plurality of biometrics comprising at least one of the user’s body temperature, heart rate, VO<sub>2</sub> max, respiration, steps taken, blood pressure, heart rate variability, and calories burnt.

3. The wearable device of claim 1, wherein the display unit is configured to display the at least one visual representation to the user of the wearable device in a location of the wearable device that is clear from obstructing a main view of the user of the wearable device.

4. The wearable device of claim 1, wherein the communication unit of the control unit comprises at least one of a transmitter configured to transmit the biometric data to the remote unit and a receiver configured to receive information from the remote unit, the received information including one or more messages indicating at least one of i) the biometric data associated with the user of the wearable device, ii) action items to be performed by the user of the wearable device, and iii) status messages associated with a condition of the user of the wearable device.

5. The wearable device of claim 4, wherein the condition of the user of the wearable device comprises a physiological condition of the user of the wearable device while the wearable device is in use.

6. The wearable device of claim 1, wherein at least one of the biometric sensor unit and the control unit comprise one or more sensors configured to sense at least one of the internal or external temperature associated with the wearable device while the wearable device is in use.

7. A system for sensing, displaying, and communicating data associated with a condition of a user wearing headwear, the system comprising:

a wearable device comprising:

a biometric sensor unit disposed within the headwear and configured to sense biometric data associated with the condition of the user,

a display unit configured to display one or more visual representations of at least the sensed biometric data from the biometric sensor unit to the user, and

a control unit operatively coupled to the biometric sensor unit and attachable to the headwear of the user, the display unit integrably affixed with the control unit and positioned near the user’s eyes such that the visual representation is displayed within a field of view of the user, the control unit configured to receive indications of the sensed biometric data from the biometric sensor unit and cause the display unit to display the one or more visual representations to the user.

8. The system of claim 7, further comprising a remote unit in communication with the wearable device, the remote unit comprising:

a receiver configured to receive the indications of the sensed biometric data from the control unit; and

a computer-executable application comprising a graphical user interface for interacting with a user of the remote unit.

## 21

9. The system of claim 8, wherein the computer-executable application is stored in a memory coupled to one or more processors and is executable by the one or more processors to perform functions that comprise at least one of:

extracting a numerical representation of the sensed biometric data;

comparing the numerical representation of the sensed biometric data to a threshold value corresponding to a predetermined biometric range;

creating one or more graphical representations of the sensed biometric data for display on the graphical user interface; and

generating one or more messages indicating at least one of  
i) the biometric data associated with the user of the wearable device, ii) action items to be performed by the user of the wearable device, and iii) status messages associated with a condition of the user of the wearable device.

10. The system of claim 9, wherein the one or more messages is communicated to the control unit of the wearable device, the control unit further configured to communicate the one or more messages to the display unit and the display unit configured to display the information to the user via a visual representation.

11. The system of claim 7, wherein the biometric sensor unit comprises at least one sensor configured to sense a plurality of biometrics associated with the physiological condition of the user while using the wearable device, the plurality of biometrics comprising at least one of the user's body temperature, heart rate, VO<sub>2</sub> max, respiration, steps taken, blood pressure, and calories burnt.

12. The system of claim 11, wherein the biometric sensor unit comprises an earpiece configured to be received by an ear of the user of the wearable device.

13. A method for sensing, displaying, and communicating data associated with a condition of a user of a wearable device, the method comprising:

## 22

sensing, by a biometric sensor unit, biometric data associated with a physiological condition of the user, the biometric sensor unit configured to communicate the sensed biometric data to a control unit;

receiving, by the control unit, the sensed biometric data, the control unit configured to communicate the biometric data to a display unit; and

displaying, by a display unit, at least one visual representation of the sensed biometric data to the user, the display unit integratably affixed with the control unit and positioned near the user's eyes such that the at least one visual representation is displayed within a field of view of the user;

wherein the biometric sensor unit comprises a biometric earpiece configured to be received by an ear of the user.

14. The method of claim 13, further comprising:

transmitting, by the control unit, the biometric data to a remote unit; and

receiving, by the control unit, one or more messages from the remote unit, the one or more messages including information associated with the biometric data.

15. The method of claim 14, further comprising, displaying, by the display unit, the one or more messages to the user of the wearable device.

16. The method of claim 14, wherein the remote unit comprises a computer-executable application including a graphical user interface for interacting with a user of the remote unit.

17. The method of claim 13, wherein sensing, by the biometric sensor unit, the biometric sensor unit comprises sensing, by one or more sensors, a plurality of metrics associated with the physiological condition of the user, the plurality of metrics comprising at least one of the user's body temperature, heart rate, VO<sub>2</sub> max, respiration, steps taken, blood pressure, and calories burnt while using the wearable device.

\* \* \* \* \*

专利名称(译)	用于感测，显示和传送与用户相关联的数据的可穿戴设备		
公开(公告)号	<a href="#">US10052034</a>	公开(公告)日	2018-08-21
申请号	US15/451877	申请日	2017-03-07
[标]发明人	BRAUN ZACHARY JOSEPH SISK TYLER EVAN		
发明人	BRAUN, ZACHARY JOSEPH SISK, TYLER EVAN		
IPC分类号	H04Q9/00 G06F1/16 A61B5/00 G08C17/02 H04Q9/14 A61B5/0205 A61B5/083 A61B5/08 A61B5/021 G06T11/20 G02B27/01 A61B5/024		
CPC分类号	A61B5/02055 A61B5/0008 A61B5/6817 G06F1/163 A61B5/021 A61B5/02405 G06T2200/24 A61B5/0816 A61B5/0833 A61B5/4866 A61B2503/20 G02B27/017 G06T11/206 A61B5/02438 A61B5/117 A61B5/6803 G06T11/003		
优先权	62/304728 2016-03-07 US		
其他公开文献	US20170251933A1		
外部链接	<a href="#">Espacenet</a>		

摘要(译)

本公开的实施例可以包括用于感测，显示和传送与用户的状况相关联的数据的可穿戴设备。在一些实施例中，可穿戴设备可包括生物识别传感器单元，其被配置为感测与用户的生理状况相关联的生物识别数据，显示单元被配置为将来自生物识别传感器单元的所感测的生物识别数据的视觉表示显示给用户，控制单元可操作地连接到生物传感器单元和显示单元。控制单元还可以包括：至少一个处理器，被配置为接收所感测的生物特征数据的指示并使显示单元显示生物特征数据的至少一个视觉表示和通信单元，通信单元被配置为发送和/或接收与感测的生物识别数据相关联的信息。

