



US010537250B2

(12) **United States Patent**  
**Albert**

(10) **Patent No.:** **US 10,537,250 B2**  
(45) **Date of Patent:** **Jan. 21, 2020**

(54) **DISCORDANCE MONITORING**

*A61B 5/046* (2013.01); *A61B 5/0464*

(71) Applicant: **AliveCor, Inc.**, San Francisco, CA (US)

(2013.01); *A61B 5/04085* (2013.01); *A61B*

(72) Inventor: **David E. Albert**, Oklahoma City, OK (US)

*5/1118* (2013.01); *A61B 2562/0219* (2013.01)

(58) **Field of Classification Search**

None  
See application file for complete search history.

(73) Assignee: **AliveCor, Inc.**, Mountain View, CA (US)

(56) **References Cited**

(\*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 0 days.

U.S. PATENT DOCUMENTS

(21) Appl. No.: **15/656,745**

3,717,857 A 2/1973 Evans  
3,731,311 A 5/1973 Williams  
3,768,014 A 10/1973 Smith et al.  
3,776,228 A 12/1973 Semler

(Continued)

(22) Filed: **Jul. 21, 2017**

FOREIGN PATENT DOCUMENTS

(65) **Prior Publication Data**

US 2017/0319080 A1 Nov. 9, 2017

CH 675675 A5 10/1990  
CN 101828915 A 9/2010

(Continued)

**Related U.S. Application Data**

(63) Continuation of application No. 15/154,849, filed on May 13, 2016.

(60) Provisional application No. 62/161,092, filed on May 13, 2015.

Adidas miCoach Pacer Review: Like Nike+, Only Better; printed from website: <http://gizmodo.com/5479456/adidas> printed on Mar. 4, 2010, 5 pages.

(Continued)

(51) **Int. Cl.**

*A61B 5/02* (2006.01)  
*A61B 5/0205* (2006.01)  
*A61B 5/00* (2006.01)  
*A61B 5/024* (2006.01)  
*A61B 5/11* (2006.01)  
*A61B 5/046* (2006.01)  
*A61B 5/0464* (2006.01)  
*A61B 5/0408* (2006.01)

*Primary Examiner* — Ankit D Tejani

(74) *Attorney, Agent, or Firm* — Womble Bond Dickinson (US) LLP; William D. Jacobs, Jr.


(52) **U.S. Cl.**

CPC ..... *A61B 5/0205* (2013.01); *A61B 5/681* (2013.01); *A61B 5/7267* (2013.01); *A61B 5/02405* (2013.01); *A61B 5/02438* (2013.01);

(57) **ABSTRACT**

Described herein are systems, devices, and methods for cardiac monitoring. In particular, the systems, devices, and methods described herein may be used to conveniently sense the presence of an intermittent arrhythmia in an individual. The systems, devices, and methods described herein may be further configured to sense an electrocardiogram.

**16 Claims, 7 Drawing Sheets**



(56)

## References Cited

## U.S. PATENT DOCUMENTS

3,779,237 A	12/1973	Roth et al.	5,518,001 A	5/1996	Snell
3,779,249 A	12/1973	Semler	5,522,396 A	6/1996	Langer et al.
3,782,367 A	1/1974	Hochberg et al.	5,539,705 A	7/1996	Akerman et al.
3,805,227 A	4/1974	Lester	D372,785 S	8/1996	Sabri
3,882,277 A	5/1975	Depedro et al.	5,544,661 A	8/1996	Davis et al.
3,885,552 A	5/1975	Kennedy	5,551,953 A	9/1996	Lattin et al.
3,898,984 A	8/1975	Mandel et al.	5,561,712 A	10/1996	Nishihara
3,909,599 A	9/1975	Trott, Jr. et al.	5,568,448 A	10/1996	Tanigushi et al.
4,027,146 A	5/1977	Gilmore	5,579,284 A	11/1996	May
4,045,767 A	8/1977	Nishihara et al.	D377,983 S	2/1997	Sabri
4,083,366 A	4/1978	Gombrich et al.	5,608,723 A	3/1997	Felsenstein
4,095,050 A	6/1978	Beachem et al.	5,634,468 A	6/1997	Platt et al.
4,221,223 A	9/1980	Linden	5,652,570 A	7/1997	Lepkofker
4,230,127 A	10/1980	Larson	5,661,699 A	8/1997	Sutton
4,231,031 A	10/1980	Crowther et al.	5,675,325 A	10/1997	Taniguchi et al.
4,250,888 A	2/1981	Grosskopf	5,678,562 A	10/1997	Sellers
4,281,664 A	8/1981	Duggan	5,701,894 A	12/1997	Cherry et al.
4,295,472 A	10/1981	Adams	5,704,364 A	1/1998	Saltzstein et al.
4,312,358 A	1/1982	Barney	5,724,025 A	3/1998	Tavori
4,318,130 A	3/1982	Heuer	5,730,143 A	3/1998	Schwarzberg
4,364,397 A	12/1982	Citron et al.	5,735,285 A	4/1998	Albert et al.
4,367,752 A	1/1983	Jimenez et al.	5,742,251 A	4/1998	Gerber
4,409,984 A	10/1983	Dick	5,748,103 A	5/1998	Flach et al.
4,531,527 A	7/1985	Reinhold, Jr. et al.	5,764,763 A	6/1998	Jensen et al.
4,567,883 A	2/1986	Langer et al.	5,772,586 A	6/1998	Heinonen et al.
4,572,182 A	2/1986	Royse	5,818,788 A	10/1998	Kimura et al.
4,580,250 A	4/1986	Kago et al.	5,825,718 A	10/1998	Ueki et al.
4,583,553 A	4/1986	Shah et al.	5,827,179 A	10/1998	Lichter et al.
4,622,979 A	11/1986	Katchis et al.	5,840,020 A	11/1998	Heinonen et al.
4,625,730 A	12/1986	Fountain et al.	5,844,997 A	12/1998	Murphy, Jr.
4,803,625 A	2/1989	Fu et al.	5,861,018 A	1/1999	Feierbach
4,889,131 A	12/1989	Salem et al.	5,873,369 A	2/1999	Laniado et al.
4,920,489 A	4/1990	Hubelbank et al.	5,876,351 A	3/1999	Rohde
4,938,228 A	7/1990	Righter et al.	5,877,675 A	3/1999	Rebstock et al.
4,938,229 A	7/1990	Bergelson et al.	5,889,730 A	3/1999	May
4,958,641 A	9/1990	Digby et al.	5,929,761 A	7/1999	Van et al.
4,977,899 A	12/1990	Digby et al.	D414,870 S	10/1999	Saltzstein
4,981,141 A	1/1991	Segalowitz	5,970,388 A	10/1999	Will
5,012,814 A	5/1991	Mills et al.	5,976,083 A	11/1999	Richardson et al.
5,023,906 A	6/1991	Novas	5,982,297 A	11/1999	Welle
5,025,794 A	6/1991	Albert et al.	5,983,127 A	11/1999	Depinto
5,058,597 A	10/1991	Onoda et al.	6,008,703 A	12/1999	Perrott et al.
5,090,418 A	2/1992	Squires et al.	6,024,705 A	2/2000	Schlager et al.
5,111,396 A	5/1992	Mills et al.	6,037,704 A	3/2000	Welle
5,128,552 A	7/1992	Fang et al.	6,047,257 A	4/2000	Dewaele
5,136,555 A	8/1992	Gardos	6,048,319 A	4/2000	Hudgins et al.
5,181,552 A	1/1993	Eiermann	D427,315 S	6/2000	Saltzstein
5,191,891 A	3/1993	Righter	6,072,396 A	6/2000	Gaukel
5,201,321 A	4/1993	Fulton	6,083,248 A	7/2000	Thompson
5,218,969 A	6/1993	Bredesen et al.	6,084,510 A	7/2000	Lemelson et al.
5,226,424 A	7/1993	Bible	6,102,856 A	8/2000	Groff et al.
5,238,001 A	8/1993	Gallant et al.	6,153,532 A	11/2000	Dow et al.
D341,659 S	11/1993	Homayoun	6,159,147 A	12/2000	Lichter et al.
5,259,387 A	11/1993	Depinto	6,198,394 B1	3/2001	Jacobsen et al.
5,301,679 A	4/1994	Taylor	6,224,548 B1	5/2001	Gopinathan et al.
5,304,186 A	4/1994	Semler et al.	6,236,889 B1	5/2001	Soykan et al.
5,313,953 A	5/1994	Yomtov et al.	6,264,614 B1	7/2001	Albert et al.
5,321,618 A	6/1994	Gessman	6,282,440 B1	8/2001	Brodnick et al.
5,333,616 A	8/1994	Mills et al.	6,282,441 B1	8/2001	Raymond et al.
5,336,245 A	8/1994	Adams et al.	6,289,238 B1	9/2001	Besson et al.
5,337,752 A	8/1994	Reeves	6,319,201 B1	11/2001	Wilk
5,339,824 A	8/1994	Engira	6,343,049 B1	1/2002	Toda
5,343,869 A	9/1994	Pross et al.	6,363,139 B1	3/2002	Zurek et al.
5,343,870 A	9/1994	Gallant et al.	6,364,834 B1	4/2002	Reuss et al.
5,348,008 A	9/1994	Bornn et al.	6,366,871 B1	4/2002	Geva
5,360,005 A	11/1994	Wilk	6,377,843 B1	4/2002	Naydenov et al.
5,365,935 A	11/1994	Righter et al.	6,418,394 B1	7/2002	Puolakanaho et al.
5,410,587 A	4/1995	Grunwell	6,433,689 B1	8/2002	Hovind et al.
5,417,222 A	5/1995	Dempsey et al.	6,453,164 B1	9/2002	Fuller et al.
5,433,736 A	7/1995	Nilsson	6,478,736 B1	11/2002	Mault
5,452,356 A	9/1995	Albert	6,485,416 B1	11/2002	Platt et al.
5,466,246 A	11/1995	Silvian	6,507,734 B1	1/2003	Berger et al.
5,467,773 A	11/1995	Bergelson et al.	6,513,532 B2	2/2003	Mault et al.
5,481,255 A	1/1996	Albert et al.	6,549,756 B1	4/2003	Engstrom
5,503,158 A	4/1996	Coppock et al.	6,558,320 B1	5/2003	Causey, III et al.
			6,579,231 B1	6/2003	Phipps
			6,595,929 B2	7/2003	Stivoric et al.
			6,600,471 B2	7/2003	Lee et al.
			6,605,038 B1	8/2003	Teller et al.

(56)

## References Cited

## U.S. PATENT DOCUMENTS

6,612,985 B2	9/2003	Eiffert et al.	8,126,728 B2	2/2012	Dicks et al.
6,616,613 B1	9/2003	Goodman	8,130,093 B2	3/2012	Mazar et al.
6,636,761 B2	10/2003	Brodnick	8,150,750 B2	4/2012	Ray
6,685,633 B2	2/2004	Albert et al.	8,160,276 B2	4/2012	Liao et al.
6,717,983 B1	4/2004	Toda	8,165,677 B2	4/2012	Von et al.
6,790,178 B1	9/2004	Mault et al.	8,216,136 B2	7/2012	Addison et al.
6,804,558 B2	10/2004	Haller et al.	8,224,429 B2	7/2012	Prstojevich et al.
6,820,057 B1	11/2004	Loch et al.	8,265,907 B2	9/2012	Nanikashvili et al.
6,845,263 B2	1/2005	Kawaguchi	8,275,553 B2	9/2012	Ochs et al.
6,893,396 B2	5/2005	Schulze et al.	8,275,635 B2	9/2012	Stivoric et al.
6,928,535 B2	8/2005	Yamashita et al.	8,282,550 B2	10/2012	Rasdal et al.
6,950,681 B2	9/2005	Hofmann	8,285,356 B2	10/2012	Bly et al.
6,970,737 B1	11/2005	Brodnick et al.	8,301,232 B2	10/2012	Albert et al.
6,987,965 B2	1/2006	Ng et al.	8,301,236 B2	10/2012	Baumann et al.
7,018,339 B2	3/2006	Birnbaum et al.	8,323,188 B2	12/2012	Tran
7,020,508 B2	3/2006	Stivoric et al.	8,328,718 B2	12/2012	Tran
7,031,745 B2	4/2006	Shen	8,332,233 B2	12/2012	Ott et al.
7,061,381 B2	6/2006	Forcier et al.	8,364,250 B2	1/2013	Moon et al.
7,103,407 B2	9/2006	Hjelt et al.	8,369,936 B2	2/2013	Farringdon et al.
7,107,095 B2	9/2006	Manolas	8,374,688 B2	2/2013	Libbus et al.
7,108,659 B2	9/2006	Ross et al.	8,449,471 B2	5/2013	Tran
7,153,262 B2	12/2006	Stivoric et al.	8,500,636 B2	8/2013	Tran
7,162,291 B1	1/2007	Nachaliel	8,509,882 B2	8/2013	Albert et al.
7,162,294 B2	1/2007	Rowlandson et al.	8,519,835 B2	8/2013	Dunko
7,188,151 B2	3/2007	Kumar et al.	8,543,185 B2	9/2013	Yuen et al.
7,222,054 B2	5/2007	Geva	8,548,770 B2	10/2013	Yuen et al.
7,236,818 B2	6/2007	McLeod et al.	8,700,137 B2	4/2014	Albert
7,257,448 B2	8/2007	Crowe et al.	8,725,229 B2	5/2014	Furue et al.
7,260,429 B2	8/2007	Siejko et al.	8,755,871 B2	6/2014	Weng et al.
7,261,690 B2	8/2007	Teller et al.	8,923,958 B2	12/2014	Gupta et al.
7,285,090 B2	10/2007	Stivoric et al.	8,951,189 B2	2/2015	Osorio
7,319,425 B2	1/2008	Fiorenza et al.	8,951,192 B2	2/2015	Osorio
7,324,836 B2	1/2008	Steenstra et al.	8,974,396 B1	3/2015	Brady et al.
7,349,574 B1	3/2008	Sodini et al.	8,977,347 B2	3/2015	Mestha et al.
7,351,207 B2	4/2008	Priemer	9,026,202 B2	5/2015	Albert
7,354,400 B2	4/2008	Asafusa et al.	9,220,430 B2	12/2015	Albert
7,382,247 B2	6/2008	Welch et al.	9,254,095 B2	2/2016	Galloway et al.
7,383,297 B1	6/2008	Atsmon et al.	9,351,654 B2	5/2016	Albert
7,398,115 B2	7/2008	Lynn	2001/0027384 A1	10/2001	Schulze et al.
7,415,304 B2	8/2008	Rowlandson et al.	2001/0031998 A1	10/2001	Nelson et al.
7,444,116 B2	10/2008	Ivanov et al.	2001/0051766 A1	12/2001	Gazdzinski
7,460,899 B2	12/2008	Almen	2002/0016541 A1	2/2002	Glossop
7,502,643 B2	3/2009	Farringdon et al.	2002/0032386 A1	3/2002	Sackner et al.
7,509,159 B2	3/2009	Xue et al.	2002/0111556 A1	8/2002	Wegner
7,515,043 B2	4/2009	Welch et al.	2002/0143576 A1	10/2002	Nolvak et al.
7,515,044 B2	4/2009	Welch et al.	2003/0004425 A1	1/2003	Narimatsu et al.
7,520,860 B2	4/2009	Guion-Johnson et al.	2003/0093002 A1	5/2003	Kuo
7,542,878 B2	6/2009	Nanikashvili	2003/0107487 A1	6/2003	Korman et al.
7,548,623 B2	6/2009	Manabe	2003/0117987 A1	6/2003	Brebner
7,596,405 B2	9/2009	Kurzweil et al.	2003/0149344 A1	8/2003	Nizan
7,603,148 B2	10/2009	Michalak	2003/0193839 A1	10/2003	Singh
7,647,185 B2	1/2010	Tarassenko et al.	2004/0034284 A1	2/2004	Aversano et al.
7,654,148 B2	2/2010	Tomlinson	2004/0044292 A1	3/2004	Yasushi et al.
7,657,479 B2	2/2010	Henley	2004/0059205 A1	3/2004	Carlson et al.
7,668,589 B2	2/2010	Bauer	2004/0117212 A1	6/2004	Kong et al.
7,689,437 B1	3/2010	Teller et al.	2004/0120356 A1	6/2004	Davenport et al.
7,701,895 B2	4/2010	Gehasie et al.	2004/0143403 A1	7/2004	Brandon et al.
7,733,224 B2	6/2010	Tran	2004/0215088 A1	10/2004	Hubelbank
7,742,808 B2	6/2010	Nissila et al.	2004/0215094 A1	10/2004	Baumer et al.
7,806,832 B2	10/2010	Gallagher et al.	2004/0220487 A1	11/2004	Vyshedskiy et al.
7,819,814 B2	10/2010	Gavriely et al.	2004/0220488 A1	11/2004	Vyshedskiy et al.
7,846,104 B2	12/2010	MacQuarrie et al.	2004/0225199 A1	11/2004	Evanyk et al.
7,846,106 B2	12/2010	Andrews	2004/0228217 A1	11/2004	Szeto
7,904,160 B2	3/2011	Brodnick et al.	2004/0236819 A1	11/2004	Anati et al.
7,945,064 B2	5/2011	O'Brien et al.	2004/0266407 A1	12/2004	Lee et al.
7,946,959 B2	5/2011	Shum et al.	2004/0266480 A1	12/2004	Hjelt et al.
7,955,273 B2	6/2011	Rahe-Meyer	2005/0014531 A1	1/2005	Findikli
7,983,749 B2	7/2011	Warren	2005/0027207 A1	2/2005	Westbrook et al.
8,019,609 B2	9/2011	Tamir et al.	2005/0078533 A1	4/2005	Vyshedskiy et al.
8,034,006 B2	10/2011	Celik-Butler et al.	2005/0124864 A1	6/2005	Mack et al.
8,062,090 B2	11/2011	Atsmon et al.	2005/0234353 A1	10/2005	Xue et al.
8,078,136 B2	12/2011	Atsmon et al.	2006/0022833 A1	2/2006	Ferguson et al.
8,078,278 B2	12/2011	Penner	2006/0047215 A1	3/2006	Newman et al.
8,126,526 B2	2/2012	Kitajima et al.	2006/0173259 A1	8/2006	Flaherty et al.
8,126,566 B2	2/2012	Stahmann et al.	2006/0190045 A1	8/2006	Marcus et al.
			2006/0193270 A1	8/2006	Gehasie et al.
			2006/0252999 A1	11/2006	Devaul et al.
			2007/0021677 A1	1/2007	Markel
			2007/0027386 A1	2/2007	Such et al.



(56)

## References Cited

## FOREIGN PATENT DOCUMENTS

MX	2009011781	A	5/2011
WO	WO-8200910	A1	3/1982
WO	WO-8805282	A1	7/1988
WO	WO-9008361	A1	7/1990
WO	WO-9206551	A1	4/1992
WO	WO-9731437	A1	8/1997
WO	WO-9838611	A1	9/1998
WO	WO-9944494	A1	9/1999
WO	WO-0041620	A1	7/2000
WO	WO-0147597	A2	7/2001
WO	WO-0157619	A2	8/2001
WO	WO-02080762	A1	10/2002
WO	WO-03075118	A2	9/2003
WO	WO-03094720	A1	11/2003
WO	WO-2004037080	A1	5/2004
WO	WO-2006001005	A2	1/2006
WO	WO-2006021956	A2	3/2006
WO	WO-2007014545	A2	2/2007
WO	WO-2007088315	A1	8/2007
WO	WO-2008005015	A1	1/2008
WO	WO-2008066682	A2	6/2008
WO	WO-2010025166	A1	3/2010
WO	WO-2010099066	A2	9/2010
WO	WO-2010108287	A1	9/2010
WO	WO-2010113354	A1	10/2010
WO	WO-2010144626	A1	12/2010
WO	WO-2011006356	A1	1/2011
WO	WO-2011008838	A1	1/2011
WO	WO-2011014292	A1	2/2011
WO	WO-2011022942	A1	3/2011
WO	WO-2011040877	A1	4/2011
WO	WO-2011040878	A1	4/2011
WO	WO-2011113070	A1	9/2011
WO	WO-2011137375	A2	11/2011
WO	WO-2011156374	A2	12/2011
WO	WO-2012046158	A1	4/2012
WO	WO-2012108895	A1	8/2012
WO	WO-2012129413	A1	9/2012
WO	WO-2012160550	A1	11/2012
WO	WO-2013028960	A1	2/2013
WO	WO-2013036307	A1	3/2013
WO	WO-2013066642	A1	5/2013
WO	WO-2013093690	A1	6/2013
WO	WO-2013122788	A1	8/2013
WO	WO-2013138500	A1	9/2013
WO	WO-2013155196	A2	10/2013
WO	WO-2013192166	A1	12/2013
WO	WO-2014172451	A1	10/2014

## OTHER PUBLICATIONS

Australian Design Awards. Heatplus Micro; printed from website <http://www.designawards.com/au>; printed on Apr. 12, 2002, 6 pages.

Bajaj, M.D.; "Event Recording in Ambulatory Patients with Syncope Events"; University of Kansas; Wichita, Kansas; (no date); pp. 15-18; printed on or before Apr. 14, 2010.

Bluetooth. Headset Profile (HSP), printed from website <http://bluetooth.com/English/Technology/Works/Pates/HSP.aspx>, printed on May 12, 2010, 1 Page.

Bramanti et al., Multichannel telemetric system for biomedical signals via switched telephone lines, *Medical and Biological Engineering and Computing*, Sep. 1982, vol. 20, No. 5, pp. 653-656.

Burke, "A Micropower Dry-Electrode ECG Preamplifier", *IEEE Transactions on Biomedical Engineering*, Feb. 2000, vol. 47, No. 2, pp. 155-162.

Card Guard CG-6108 ACT Ambulatory Cardiac Telemetry Brochure; Card Guard; The Telemedicine Company; Switzerland; 2006, 2 pages.

Cardiocomm Solutions; Gems Air. (PC based on ECG management) printed from website <http://www.cardiocommsolutions.com>; printed on Mar. 19, 2010; 1 page.

Charuvastra. Transtelephonic Cardiac Event Recording for Arrhythmia Surveillance; printed from website <http://tchin.org/resource-room/c-art> printed on Mar. 26, 2010• 2 pages.

Cheng, Allen C.; "Real-Time Cardiovascular Diseases Detection on a Smartphone"; Departments of Electrical And Computer Engineering, Bioengineering, Neurological Surgery and Computer Science; University of Pittsburgh; Pittsburgh, PA; printed on or before Apr. 14, 2010, 2 pages.

Chinese Patent Application No. 2013800135500 First Office Action dated Oct. 20, 2015.

Creative. PC-80B Portable ECG Monitor w/sd card extension slow; printed from website [www.amazon.com/Portable-Monitor-extension-leather-shipping/dp/B0010jWKUE](http://www.amazon.com/Portable-Monitor-extension-leather-shipping/dp/B0010jWKUE); printed on Feb. 4, 2010• 5 pages.

Deveau, "Health Care eyes smart phones to heal ills", printed from the website <http://www.theQiobeandmail.com> on Sep. 17, 2009, 4 pages.

Dinh. Heart activity monitoring on smartphone. IPCBEE—Int conf Biomedical Eng and Technol. Jun. 17-19, 2011. 11:45-49.

Dobrev, et al., Bootstrapped two-electrode biosignal amplifier, *Med Bio Eng Comput*, 2008, 7 pages.

Dolan; Qualcomm launches ECG smartphone program in China; Sep. 8, 2011; 11 pgs.; retrieved Mar. 19, 2014 from the internet (<http://mobihealthnews.com/13092/qualcomm-launches-ecg-smartphone-program-in-china/>).

Elert, Glenn (Editor); Frequency Range of Human Hearing; The Physics Factbook; web version as of Mar. 29, 2010; 2 pgs.; printed Jun. 6, 2012 (<http://web.archive.org/web/20100329141847/http://hypertextbook.com/facts/2003/ChrisDAmbrose.shtml>).

European search report and opinion dated Nov. 21, 2014 for EP Application No. 11865699.0.

Favorite Plus. Handheld Easy ECG Monitor—Handheld EKG Monitor; printed from website [www.favoriteplus.com/easy-ecg-handgeld-monitor-fp](http://www.favoriteplus.com/easy-ecg-handgeld-monitor-fp); printed on Feb. 4, 2010; 2 pages.

Favorite Plus. Handheld ECG Monitor—Handheld EKG Monitor at Favoriteplus.com; printed from website [www.favoriteplus.com/handheld-ecg-ekg-monitor](http://www.favoriteplus.com/handheld-ecg-ekg-monitor); printed on Feb. 4, 2010; 3 pages.

Favorite Plus. Handheld ECG Monitor—Handheld EKG Monitor InstantCheck; printed from website <http://www.favoriteplus.com/instantcheck-hand-held-ecg-ekg-monitor>; printed on Feb. 4, 2010; 2 pages.

Ferrick, M.D.; "Holter Monitoring and cardiac Event Recording in Assessing Symptomatic Patients"; Albert Einstein College of Medicine; Bronx, New York; (no date) pp. 11-14• printed on or before Apr. 14, 2010.

Free2move. Vitaphone 2300; [www.free2move.us/News/NewsVitaghone240105.htm](http://www.free2move.us/News/NewsVitaghone240105.htm), printed May 12, 2010.

Fulford-Jones, et al., "A Portable, Low-Power, Wireless Two-Lead EKG System", Division of Engineering and Applied Sciences, Harvard University, Sep. 2004, 4 pages.

Garabelli et al. Accuracy and Novelty of an Inexpensive iPhone-based Event Recorder (Presentation Poster/Abstract) Heart Rhythm 2012, 33rd Annual Scientific Session. SP23. Innovation Poster Session II. No IA02-1; May 11, 2012.

GBI Portal. Qualcomm's wireless reach mHealth project to improve cardiovascular disease in resource scarce China; Feb. 17, 2012; 7 pgs. Retrieved Mar. 19, 2014 from [www.intergrallc.com/2012/02/17/qualcooms-wireless-reach-mhealth-project-to-improve-cardiovascular-disease-in-resource-scarce-china/](http://www.intergrallc.com/2012/02/17/qualcooms-wireless-reach-mhealth-project-to-improve-cardiovascular-disease-in-resource-scarce-china/).

GE; Healthcare., "Marquette heart rate turbulence analysis program", 2005, DC-1060-12.05-EN-US. 4 pages.

Gillette, M.D.; "Diagnosis of Pediatric Arrhythmias with Event Recording"; Medical University of South Carolina; Charleston, South Carolina; (no date); pp. 25-32; printed on or before Apr. 14, 2010.

Grier, James W.; "How to use 1-lead ECG recorders to obtain 12-lead resting ECGs and exercise ("stress") ECGs"; Department of Biological Sciences; printed from website <http://www.ndsu.edu/pubweb/rvgrier>; printed on Jun. 7, 2010; 13 pages.

Hannaford, Kat; "How To Turn Your iPhone Into A Laser, Fan or Flashlight"; printed from website <http://m.qizmodo.com/5534904> printed on Feb. 3, 2011, 2 pages.

(56) **References Cited**

## OTHER PUBLICATIONS

- Hartmann, "ECG Front-End Design is Simplified with MicroConverter" Analog Dialogue, Nov. 2003, vol. 37, pp. 1-5.
- Hayes, M.D.; "Approaches to Diagnosing Transient Arrhythmias" An Overview; Mayo Clinic; Rochester Minnesota; (no date); pp. 7-10; printed on or before Apr. 14, 2010.
- Hearing Loss Assoc. of Kentuckiana; Decibal Ratings/Hazardous Time Exposures of Common Noise (excerpt from Survivor's Manual); web version as of Oct. 5, 2008; 2 pgs.; printed Jun. 6, 2012 (<http://web.archive.org/web/20081005143856/http://www.hearinglossky.org/hlasurvival1.html>).
- Huang, Tina; Age-related hearing loss; Minnesota Medicine; 90(10); pp. 48-50; Oct. 2007; printed Jun. 6, 2012 from: <http://www.minnesotamedicine.com/PastIssues/PastIssues2007/October2007/CiincalHuangOctober2007.aspx>).
- IMEC News; IMEC extends flexible ECG patch to enable arrhythmia detection; printed from website <http://www2.imec.be/imec/> printed on Aug. 18, 2009 1 page.
- Instromedix. Cardiac Event Recording FAQ's; Instromedix A Card Guard Company, San Diego, CA.; printed from website [www.instromedix.com/pdf/products/cardiac](http://www.instromedix.com/pdf/products/cardiac); printed on or before Apr. 14, 2010.
- Instromedix. The Arrhythmia Monitoring System; King of Hearts Express AF Recorder Brochure from Instromedix A CardGuard Company; Rosemont IL; 2004• 3 pages.
- International preliminary report on patentability dated Jul. 29, 2014 for PCT/US2013/023370.
- International search report and written opinion dated Feb. 12, 2015 for PCT Application No. US2014/054414.
- International search report and written opinion dated Feb. 17, 2012 for PCT/US2011/039445.
- International search report and written opinion dated Apr. 27, 2012 for PCT/US2011/053708.
- International search report and written opinion dated Apr. 30, 2015 for PCT/US2014/070170.
- International search report and written opinion dated May 15, 2013 for PCT/US2013/023370.
- International search report and written opinion dated Dec. 17, 2013 for PCT/2013/055458.
- International search report dated Sep. 1, 2014 for PCT/US2014/034350.
- International search report dated Dec. 10, 2013 for PCT/US2013/057576.
- Jenkins II, W.; Time/Frequency Relationships for an FFT-Based Acoustic Modem; Naval Postgraduate School; pp. 1-102; Sep. 2010 ([http://edocs.nps.edu/npspubs/scholarly/theses/2010/Sep/1\\_OSep\\_Jenkins.pdf](http://edocs.nps.edu/npspubs/scholarly/theses/2010/Sep/1_OSep_Jenkins.pdf)) printed Feb. 10, 2013.
- Kim, et al., "Detection of Atrial Fibrillation Episodes using Multiple Heart Rate Variability Features in Different Time Periods." Conference Proceedings IEEE Eng Med Biol Soc EMBS, 30th Annual International Conference, Aug. 20-25, 2008 pp. 5482-5485.
- Koerner. The Author's Metrics; Wired Magazine Article; New York, NY; Jul. 2009; pp. 93-126.
- Kumar, M.D., "Zio Patch"; printed from website <http://www.irhythmtech.com/zio-solution/zio-gach/>, printed on Apr. 12, 2010.
- Kumarak, Greg; "Visa officially announces their case that turns your iPhone into a credit card (and we've got pies!)" ; May 17, 2010; printed from website [www.mobilecrunch.com](http://www.mobilecrunch.com) printed on Feb. 3, 2011.
- Lau, et al. iPhone ECG application for community screening to detect silent atrial fibrillation: A novel technology to prevent stroke. Int J Cardiol. Apr 30;165(1):193-4.
- Lau, et al. Performance of an Automated iPhone ECG Algorithm to Diagnose Atrial Fibrillation in a Community AF Screening Program (Search-AF). Heart, Lung and Circulation. 2013; 22:S205.
- Lau et al. Validation of an iPhone ECG application suitable for community screening for silent atrial fibrillation—A novel way to prevent stroke (Presentation Abstract 16810); American Heart Association 2012 Scientific Sessions and Resuscitation Science Symposium; 126(1); Nov. 20, 2012, 2 pages.
- Leijdekkers et al., "Trial Results of a Novel Cardiac Rhythm Management System using Smart Phones and wireless ECG Sensors", Proceedings of the International Conf. On Smart homes and health Telematics., Jul. 1-3, 2009, Tours, France, 8 pages.
- Levkov et al., "Removal of power-line interference from the ECG: a review of the subtraction procedure" BioMedical Engineering Online 2005, printed from website <http://www.biomedical-engineeringonline.com/content/4/1/50> pp. 1-18.
- Lin; et al., "An intelligent telecardiology system using a wearable and wireless ECG to detect atrial fibrillation.", May 2010, 14(3), 726-33.
- Lowres, et al. Screening Education And Recognition in Community Pharmacies of Atrial Fibrillation to prevent stroke in an ambulant population aged =65 years (Search-AF stroke prevention study): a cross-sectional study protocol. BMJ Open. Jun. 25, 2012; 2(3)e001355.
- M Med Choice. Handheld ECG Monitor Brochure; M Med Choice, Beijing Choice Electronic Technology Co. LTD. published on or before Apr. 14, 2010, 6 pages.
- M Med Choice. Handheld ECG Monitor MD100A1; printed from website <http://www.choicemed.com/products.asp>; printed on 12/28/2009; 2 pages.
- M Med Choice. Handheld ECG Monitor MD100B; printed from website <http://www.choicemed.com/productshow.asp>; printed on Dec. 28, 2009• 2 pages.
- M Med Choice, printed from website <http://www.choicemed.com/1xwm.asp>; printed on Dec. 28, 2009• 1 page.
- MacFarlane, et al. Resting 12-lead ECG electrode placement and associated problems; SCST update 1995; 15pgs. Printed Feb. 18, 2014 from [www.scst.org.uk/resources/RESTING\\_12.pdf](http://www.scst.org.uk/resources/RESTING_12.pdf).
- Mauvila ECG Tutorial; Basic ECG Interpretation Tutorial; Sections 1-12; printed website <http://mauvila.com/ECG/ecg.htm> printed on Mar. 26, 2010• 56 pages.
- Medgadget. Zio Patch Wins Medical Design Award. MedGadget internet journal of emerging medical technologies, 2010, 1 page, printed from website: [http://medaadaet.com/archives/2010/04/zio\\_patch\\_wins\\_medial\\_design\\_award\\_1.html](http://medaadaet.com/archives/2010/04/zio_patch_wins_medial_design_award_1.html).
- MiCardioMobile: Remote Wireless Cardiac Rehabilitation Monitoring printed from website <http://alivetec.cable.nu/cardiomobile> printed on or before Apr. 14, 2010, 1 page.
- Mobility Mind. Use your Treo 650 as a portable ECG monitoring device, Mobility Mind Celebrating mobile Internet lifestyle and culture, Sep. 14, 2005, 1 page. printed from website <http://treetoday.net/2005/09/14/use-your-treo-650-as-a-portable-ecg-monitoring-device/>.
- Modem Protocols Explained; <ftp://kermit.columbia.edu/kermit/cu/protocol.html>; 5 pgs.; printed Oct. 2, 2013.
- Modem Tutorial; <http://www.lsu.edu/OCS/its/unix/tutoriai/ModemTutoriai/ModemTutorial.html>; 2 pgs.; printed Oct. 2, 2013.
- Muench, Frederick, PhD; "HRV; The Manufacturers and Vendors Speak; The portable StressEraser Heart Rate Variability Biofeedback Device: Background and Research" Biofeedback vol. 36 Issue 1, pp. 35-39 published Spring 2008.
- Murph. RedEye mini converts iPhone, iPad or iPod into IR-beaming universal remote; printed from website <http://www.engadget.com/2010/03/02/redeye>; printed on Mar. 2, 2010; 3 pages.
- Nam et al.; An Ultrasonic Sensor Based Low-Power Acoustic Modem for Underwater Communication in Underwater Wireless Sensor Networks; Computer Network Lab, Dept. of Elec. Eng., Korea Univ.; pp. 494-504; Dec. 2007 ([http://nesl.ee.ucla.edu/fw/torres/home/Dropbox/good\\_paper\\_mico\\_controller.pdf](http://nesl.ee.ucla.edu/fw/torres/home/Dropbox/good_paper_mico_controller.pdf)); 11 pgs.; printed Oct. 2, 2013).
- Neuroreille; Audiometry; web version as of Oct. 14, 2008; 1 pg.; printed Jun. 6, 2012 (<http://www.neuroreille.com/promenade/english/audiometry/audiometry.htm>).
- New Professional Quality ECG/ECG Portable Heart Monitor; printed from website <http://cgibay.com/ws/eBayiSAP1.dll> printed on Feb. 4, 2010• 3 pages.
- Notice of allowance dated Aug. 28, 2012 for U.S. Appl. No. 13/420,520.
- Notice of allowance dated Jul. 9, 2013 for U.S. Appl. No. 12/796,188.
- Notice of allowance dated Dec. 4, 2013 for U.S. Appl. No. 14/015,303.
- Notice of allowance dated Jan. 8, 2014 for U.S. Appl. No. 14/015,303.

(56)

## References Cited

## OTHER PUBLICATIONS

- Notice of allowance dated Jan. 27, 2014 for U.S. Appl. No. 14/015,303.
- Notice of allowance dated Feb. 26, 2014 for U.S. Appl. No. 14/015,303.
- Notice of allowance dated May 23, 2014 for U.S. Appl. No. 13/108,738.
- Notice of allowance dated Mar. 29, 2016 for U.S. Appl. No. 14/254,310.
- Notice of allowance dated Jun. 16, 2016 for U.S. Appl. No. 14/569,513.
- Office action dated Jun. 18, 2012 for U.S. Appl. No. 13/420,520.
- Office action dated Oct. 29, 2012 for U.S. Appl. No. 12/796,188.
- Office action dated Jan. 2, 2014 for U.S. Appl. No. 13/108,738.
- Office action dated Sep. 12, 2014 for U.S. Appl. No. 13/108,738.
- Office action dated Oct. 6, 2014 for U.S. Appl. No. 14/252,044.
- Office action dated Nov. 19, 2014 for U.S. Appl. No. 13/969,446.
- Office Action dated May 18, 2015 for U.S. Appl. No. 13/752,048.
- Office Action dated Aug. 25, 2015 for U.S. Appl. No. 14/479,105.
- Office Action dated Oct. 6, 2015 for U.S. Appl. No. 14/589,513.
- Office Action dated Dec. 21, 2015 for U.S. Appl. No. 13/964,490.
- Office Action dated for Feb. 24, 2016 for U.S. Appl. No. 14/730,122.
- Office Action dated Jun. 13, 2016 for U.S. Appl. No. 14/730,122.
- Omron Portable ECG EKG Handheld HCG-801 Monitor; printed from website <http://www.amazon.com/Omron-Portable-Handheld-HCG-801-Monitor/dp/B0019WH3EO> printed on Feb. 24, 2010• 5 pages.
- Omron Portable ECG Monitor; printed from website <http://www.target.com/gp/detail.html>; printed on Mar. 26, 2010• 1 page.
- Oresko, et al., “Detecting Cardiovascular Diseases via Real-Time Electrocardiogram Processing on a Smartphone”, 2009 Workshop on Biomedicine in Computing: Systems, Architectures, and Circuits, pp. 13-16.
- PCT Patent Application No. PCT/US2014/070170 International Preliminary Report on Patentability dated Jun. 23, 2016.
- PCT/US2014/054414 International Preliminary Report on Patentability dated Mar. 16, 2016.
- Perez, Sarah; No NFC? No Problem; New Startup Zoosh Provides Workaround Technology (Jun. 20, 2011); printed on or before Jun. 27, 2011 from website; 2 pgs.; (<http://www.readwriteweb.com/archives>).
- Prystowsky, M.D.; “Chairmans Introduction”; Duke University Medical Center; Indianapolis, Indiana• (no date)• pp. 5-6• printed on before Apr. 14, 2010.
- Prystowsky, M.D.; “Chairmans Summary”; Duke University Medical Center; Indianapolis Indiana; (no date); pp. 39-40• printed on or before Apr. 14, 2010.
- Prystowsky, M.D., “The Clinical Application, Diagnostic Yield and Cost Considerations of Cardiac Event Recorders;”, Indianapolis, Indiana (no date) pp. 19-23. printed on or before Apr. 14, 2010.
- Puurtinen, et al., Best Electrode Locations for a Small Bipolar ECG Device; Signal Strength Analysis of Clinical Data, Annals of Biomedical Engineering, vol. 37, No.s 2, Feb. 2009 (© 2008) pp. 331-336.
- Raju, Heart-Rate and EKG Monitor Using the MSP430FG439, SLAA280—Oct. 2005—Revised Sep. 2007, 11 pages.
- Read-My-Heart. ECG Machine Handheld Read MyHeart; (product item No. HH-3413) printed from website <http://www.helioliving.com/ECG-Machine-Handheld-ReadMyHeart>; printed on Feb. 4, 2010; 1 page.
- Readmyheart Personal Handheld ECG Monitor with Free Illustrator Book & Free Electrodes V2.2; printed from website <http://www.amazon.com/Readmyheart-Personal-Handheld-illustrator-Electrodes/dp/B0010AN63W>; printed on Mar. 26, 2010; 4 pages.
- Ricker. Square payment dongle demoed for iPhone toting hippies you (video); printed from website <http://www.engadget.com/2010/01/18/square-payment>; printed on Jan. 18, 2010; 6 pages.
- Rockwood. The Networked Body Magazine Article from Fast Talk Magazine; Jul./Aug. 2009; pp. 19-26.
- Salahuddin, et al., “Ultra Short Term Analysis of Heart Rate Variability using Normal Sinus Rhythm and Atrial Fibrillation ECG Data”, Engineering in Medicine and Biology Society, Aug. 2007, pp. 4656-4659.
- Saxon, et al. iPhone rhythm strip—the implications of wireless and ubiquitous heart rate monitoring. JACC; 59(13):E726; Mar. 2012.
- Saxon. Ubiquitous Wireless ECG Recording: A Powerful Tool Physicians Should Embrace. J Cardiobasc Electrophysiol. 24(4):pp. 480-483; Apr. 2013.
- Semler, M.D.; “The Future of Cardiac Event Monitoring”; St. Vincent Hospital and Medical Center; Portland Oregon; (no date); pp. 33-37; printed on or before Apr. 14, 2010.
- SFO Medical. Choice Portable Handheld ECG EKG Monitor; printed from website <http://www.amazon.com/Choice-Portable-Handheld-ECG-Monitor/dp/B001Q74VOM>; printed on Mar. 26, 2010; 1 page.
- Shenzhen New Element Med. Equipment. Wireless ECG Monitoring System, printed from website [http://www.alibaba.com/product-gs/248168581/Wireless\\_ECG\\_Monitoring\\_system.html](http://www.alibaba.com/product-gs/248168581/Wireless_ECG_Monitoring_system.html), printed on Mar. 26, 2010, 2 pages.
- Shumaker, J.; Designing an Ultrasonic Modem for Robotic Communications; Army Research Laboratory; 26 pgs.; Mar. 2009 (<http://www.dtic.mil/cgi-bin/GetTRDoc?AD=ADA499556>) printed Oct. 2, 2013.
- Smith. Smartphone may keep the cardiologist away, The Independent, Health & Families, Mar. 5, 2010, printed from website <http://www.independent.co.uk/life-style/health-and-families/healthnews/smartphone-may-keep-the-cardiologist-away-1916652.html>, printed on Mar. 26, 2010.
- Stevens, “Apple’s Seamlessly Embedded Heart Rate Monitor could turn the iPhone into a new-age mood ring”, printed from the website <http://www.enaadaet.com> on May 6, 2010, 3 pages.
- Talbeb Medical. Observer Hand-held ECG Monitor MD100B; (no date); printed on or before Apr. 14, 2010, 1 page.
- Tei, et al., New index of combined systolic and diastolic myocardial performance: a simple and reproducible measure of cardiac function—a study in normals and dilated cardiomyopathy; J Cardiol.; 26(6):357-366; Dec. 1995.
- Texas Instruments. Information for Medical Applications, “Biophysical Monitoring—Electrocardiogram (ECG) Front End”, Apr. 2004, 2 pages.
- Tschida. Power A’s New Case Turns Your iPhone Into A Universal Remote; printed from website <http://appadvice.com/appnn>; printed on Mar. 1, 2010• 2 pages.
- Vanhemert, Kyle; “XWave Headset Lets You Control iPhone Apps With Your Brain”; Sep. 8, 2010; printed from website <http://gizmodo.com>; printed on Sep. 8, 2010, 4 pages.
- Vitaphone. Telemedicine since 1999: Modern health management is our special subject. 3 pgs. Retrieved Mar. 19, 2014 from [www.vitaphone.de/en/company/history-of-vitaphone/](http://www.vitaphone.de/en/company/history-of-vitaphone/).
- Wikimedia Laboratories; Acoustics; web archive version dated Jan. 25, 2009; 2 pgs.; printed Jun. 6, 2012 (<http://liveweb.archive.org/http://en.labs.wikimedia.org/wiki/Acoustics>).
- Wikipedia; Aliasing; web version as of Apr. 3, 2011; 5 pgs.; printed Jun. 6, 2012 (<http://liveweb.archive.org/http://en.wikipedia.org/w/index.php?title=Aliasing&oldid=422141882>).
- Wikipedia; Hearing Range; web version as of Feb. 6, 2010; 5 pgs.; printed Jun. 6, 2012 ([http://web.archive.org/web/20100206213741/http://en.wikipedia.org/wiki/Hearing\\_range](http://web.archive.org/web/20100206213741/http://en.wikipedia.org/wiki/Hearing_range)).
- Wikipedia. “Pulse oximetry”, printed from website <http://en.wikigedia.org> on May 10, 2010, 4 pages.
- Wisneski, C.; Ultrasonic Local Area Communication; <http://alumni.media.mit.edu/~wiz/ultracom.html>; 2 pgs.; printed Oct. 2, 2013.
- Woodward et al.; “Bio-Potential-To-Frequency Converter/Modulator”; Electronic Design• Aug. 1999, p. 177.
- Ziegler, Chris; “EPI Life phone sports ECG function, can let doctors know if you’re gonna make it”; printed from website [www.enaadoet.com/2010/06/](http://www.enaadoet.com/2010/06/); Jun. 17, 2010, 3 pages.
- U.S. Appl. No. 14/479,105 Office Action dated Jul. 22, 2016.
- U.S. Appl. No. 14/494,191 Office Action dated Jul. 20, 2016.

\* cited by examiner




FIG. 1




FIG. 2




FIG. 3




FIG. 4




FIG. 5




FIG. 6




FIG. 7

**DISCORDANCE MONITORING**

## CROSS-REFERENCE

This application is a continuation of U.S. patent application Ser. No. 15/154,849, filed May 13, 2016, entitled "DISCORDANCE MONITORING", which claims the benefit of U.S. Provisional Application No. 62/161,092, filed May 13, 2015, both of which are incorporated herein by reference in its entirety.

## BACKGROUND

Irregular heartbeats and arrhythmias are associated with significant morbidity and mortality in patients. Arrhythmias may occur continuously or may occur intermittently. Types of arrhythmia include atrial fibrillation and supraventricular tachycardia. Non-invasive cardiac monitoring is useful in diagnosing cardiac arrhythmia.

## SUMMARY

Described herein are systems, devices, and methods for cardiac monitoring. The systems, devices, and methods described herein for cardiac monitoring may comprise portable computing devices such as smartphones, smartwatches, laptops, and tablet computers. Cardiac monitoring using the systems, devices, and methods described herein may be used to predict or identify the occurrence of arrhythmias.

Arrhythmias may occur continuously or may occur intermittently. Continuously occurring arrhythmias may be diagnosed using a number of different techniques including, for example, palpating a radial pulse of an individual, auscultating heart sounds of an individual, recording a heart rate of an individual, and recording an electrocardiogram of an individual. Because a continuous or essentially continuous arrhythmia is always present or essentially always present in the patient, any of the aforementioned diagnosis techniques may be applied at any time in order to make a diagnosis. For intermittent arrhythmia diagnosis any of the aforementioned diagnosis techniques may also be used, however, because intermittent arrhythmias do not always present, the diagnostic technique cannot be applied at any time, but must be applied at the time when the individual is experiencing the arrhythmia. Thus, diagnosing, intermittent arrhythmias may be difficult, because, for example, it is not practical to be prepared to apply one of the aforementioned diagnostic modalities at the exact time that an individual experiences an intermittent arrhythmia. This particular difficulty may also be compounded when an individual is not aware that they are experiencing an intermittent arrhythmia so that they would not, for example, seek out a health care provider during the intermittent arrhythmia.

However, certain parameter values may be conveniently sensed continuously such as, for example, heart rate and activity level, and analyzed to predict or determine the presence of an arrhythmia. One or more conveniently continuously sensed parameter values such as, for example, heart rate and activity level may be analyzed to determine the future onset of or the presence of an arrhythmia by identifying discordance between these two parameter values. For example, discordance between two sensed values may indicate the future onset of or the presence of an arrhythmia. In response to the identification of the future onset of or presence of an arrhythmia an electrocardiogram may be caused to be sensed.

Additional sensed parameters may also be used in an analysis as part of the cardiac monitoring systems, devices, and methods described herein. For example, a determined heart rate variability may be compared to a sensed heart rate and activity level to determine the presence of, for example, atrial fibrillation or supraventricular tachycardia.

Described herein is a method for cardiac monitoring, comprising: sensing an activity level value of an individual with a first sensor of a wearable device worn by said individual; sensing a heart rate value of said individual with a second sensor of said wearable device; determining a heart rate variability value with a processor of said wearable device; determining if a discordance is present between two or more of said activity level value, said heart rate value, and said heart rate variability value with said processor; and indicating to said individual with said wearable device to record an electrocardiogram when said discordance is determined to be present. In some embodiments, said first sensor comprises an accelerometer. In some embodiments, said first sensor comprises a gyroscope. In some embodiments, said second sensor comprises a photosensor. In some embodiments, said discordance is determined to be present when said activity level value is normal and said heart rate value is elevated. In some embodiments, said discordance is determined to be present when said activity level value is normal, said heart rate value is elevated, and said heart rate variability value is increased. In some embodiments, said method comprises indicating a presence of atrial fibrillation. In some embodiments, said discordance is determined to be present when said activity level value is normal, said heart rate value is elevated, and said heart rate variability value is decreased. In some embodiments, said method comprises indicating a presence of a supraventricular tachycardia. In some embodiments, setting one or more threshold values based on said activity level value, said heart rate value, and said heart rate variability value. In some embodiments, said one or more threshold values is determined using a machine learning algorithm.

Described herein is wearable device for cardiac monitoring, comprising: a processor; a first sensor configured to sense an activity level value of an individual, wherein said first sensor is coupled to said processor; a second sensor configured to sense a heart rate value of an individual, wherein said second sensor is coupled to said processor; a first electrode and a second electrode configured to sense an electrocardiogram; a non-transitory computer readable storage medium encoded with a computer program including instructions executable by said processor to cause said processor to: determine if a discordance is present between said activity level value of said individual and said heart rate value of said individual; and indicate that said electrocardiogram be recorded when said discordance is determined to be present. In some embodiments, said first sensor comprises an accelerometer. In some embodiments, said first sensor comprises a gyroscope. In some embodiments, said second sensor comprises a photosensor. In some embodiments, said discordance is determined to be present when said activity level value is normal and said heart rate value is elevated. In some embodiments, said computer program includes instructions that cause said processor to determine a heart rate variability value. In some embodiments, said discordance is determined to be present when said activity level value is normal, said heart rate value is elevated, and said heart rate variability value is increased. In some embodiments, said computer program includes instructions that cause said processor to indicate a presence of atrial fibrillation. In some embodiments, said discordance is deter-

mined to be present when said activity level value is normal, said heart rate value is elevated, and said heart rate variability value is elevated. In some embodiments, said computer program includes instructions that cause said processor to indicate a presence of a supraventricular tachycardia. In some embodiments, said computer program includes instructions that cause said processor to set one or more threshold values based on said activity level value, and said heart rate value.

In some embodiments, said one or more threshold values is determined using a machine learning algorithm.

Described herein is a method for cardiac monitoring, comprising: sensing an activity level value of an individual with a first sensor of a wearable device worn by said individual; sensing a heart rate value of said individual with a second sensor of said wearable device; determining if a discordance is present between two or more of said activity level value and said heart rate value by using an activity level threshold and a heart rate threshold with a processor of said wearable device; and adjusting said activity level threshold and said heart rate level threshold using a machine learning algorithm executed by said processor.

#### BRIEF DESCRIPTION OF THE DRAWINGS

The novel features of the individual matter described herein are set forth with particularity in the appended claims. A better understanding of the features and advantages of the present individual matter described herein will be obtained by reference to the following detailed description that sets forth illustrative embodiments, in which the principles of the individual matter described herein are utilized, and the accompanying drawings of which:

FIG. 1 shows a heart rate tracing with a corresponding electrocardiogram (ECG) tracing both sensed from the same individual over the same period.

FIG. 2 shows a graphic showing both heart rate and rhythm analysis over a period of time in an individual who experienced different arrhythmias.

FIG. 3 shows a close up of a heart rate tracing sensed over a period of paroxysmal atrial fibrillation.

FIG. 4 shows available technologies for continuously sensing a heart rate or an activity level.

FIG. 5 shows a photosensor commonly used to measure heart rates integrated with a smartwatch.

FIG. 6 exemplifies a computer system that is programmed or otherwise configured to sense one or more physiologic parameters of an individual.

FIG. 7 shows a schematic of an algorithm for discordance monitoring.

#### DETAILED DESCRIPTION

##### Cardiac Monitoring

Described herein are systems, devices, and methods for use in cardiac monitoring. Cardiac monitoring typically comprises monitoring of the heart function of an individual for changes in, for example, heart rate or heart rhythm.

Heart rate may vary between, for example, bradycardia which typically is defined as a heart rate of less than 60 beats per minute, normal resting heart rate which typically is defined as a heart rate of between 60-100 beats per minute, and tachycardia which typically is defined as a heart rate of greater than 100 beats per minute. Variance of heart rate over a period of time may be referred to as Heart Rate Variability (HRV).

Heart function is also measured in terms of regularity of rhythm. A normal heart rhythm comprises of a systole (ejection phase) and diastole (filling phase). During the phases of systole and diastole, the ventricles of the heart act in concert in a regular manner that is repeated with every single heartbeat. When there is an abnormality of rhythm, the condition is typically referred to as an arrhythmia. Examples of arrhythmias include atrial fibrillation, WPW syndrome, prolonged QT syndrome, and premature ventricular contractions.

Many arrhythmias occur intermittently and relatively infrequently. Thus, in order to monitor and capture an intermittent arrhythmia, continuous monitoring is typically required. ECGs can be measured continuously in the ambulatory patient using holter monitoring, but this type of monitoring is cumbersome for the patient and is thus not widely used. A device or system configured to take an intermittent ECG is much more convenient for users. Such devices or systems comprise a mobile computing device that includes one or more electrodes that sense an ECG when contacted by a skin surface of the patient. Such devices are light and portable and don't necessarily require the user to be in continuous physical contact with one or more electrodes as they would with a holter type monitor. Intermittent arrhythmias can be recorded with these devices and systems when a user is given an indication that an intermittent arrhythmia is occurring. HRV sensing is used in combination with these devices or systems to indicate to a user when to contact one or more electrodes in order to sense an ECG.

FIG. 1 shows a heart rate tracing **100** with a corresponding electrocardiogram (ECG) tracing **104** both sensed from the same individual over the same period. As is shown in the ECG tracing **104**, the individual experienced a period of intermittent atrial fibrillation **106** during the time that the ECG was sensed. As is also shown in the heart rate tracing **100**, the heart rate of the individual rapidly increased **102** during the period of intermittent atrial fibrillation. As such, the HRV of the individual increased during the period of intermittent atrial fibrillation as the heart rate of the individual increased from a resting heart rate to an increased heart rate **102**. HRV changes are therefore associated with atrial fibrillation, wherein increased HRV is found during periods of intermittent atrial fibrillation.

FIG. 2 shows a graphic showing both heart rate **202** and rhythm analysis **200** over a period of time in an individual who experienced different arrhythmias. As shown, the measured heart rate **202** tended to increase above 100 beats per minute during the periods of sensed atrial fibrillation **200**. Thus, elevated heart rate above resting heart rate occurred in this individual during the period of arrhythmia.

FIG. 3 shows a close up of a heart rate tracing sensed over a period of paroxysmal atrial fibrillation. As shown, there was a substantial step increase from a normal heart of between 60-100 beats per minute to above 100 beats per minute **302** during the period of atrial fibrillation.

FIG. 4 shows available technologies **400** for continuously sensing a heart rate or an activity level. Shown are smartwatches made available by manufactures such as, for example, Apple. A wearer of one of the shown smartwatch technologies **400** may conveniently and continuously wear one or more sensors that are either coupled to or integrated with the watch throughout the day, thus, effectively continuously monitoring one or more parameter values via the one or more sensors that are either coupled to or integrated with the smartwatch. Thus, one of the smartwatch technologies **400** are an example of a type of device in the form of a wearable that conveniently provides continuous monitoring

of one or more parameters of a user. Non-limiting examples of wearable devices that may have one or more sensors either coupled to them or integrated with them include watches (e.g. smartwatches), eyeglasses, wristbands, necklaces, and clothing. The one or more continuously sensed parameters of the user of such a technology as, for example, shown in FIG. 4, are then used to indicate to the user to use a device or system to sense an ECG. For example, a user wearing a smartwatch having a heart rate sensor is alerted by the smartwatch to record an ECG when the HRV of the user increases.

FIG. 5 shows a photosensor 500 commonly used to measure heart rates integrated with a smartwatch 502.

Activity level is correlated with arrhythmia in many individuals who have a predisposition to develop arrhythmia wherein increased activity level is associated with onset of arrhythmia. In other individuals an increased activity level that is detected by one or more activity sensors in the presence of increased HRV is likely normal and is not associated with arrhythmia. Thus, as described herein, the addition of continuous heart rate monitoring along with continuous activity level monitoring may achieve the same results, in terms of arrhythmia monitoring, as continuous electrocardiogram monitoring. Using one or more sensors associated with the devices or systems described herein two parameter values of heart rate and activity level may be conveniently and accurately continuously and simultaneously sensed.

#### Devices and Systems

FIG. 6 exemplifies a computer system 601 that is programmed or otherwise configured to sense one or more physiologic parameters of an individual. Non-limiting examples of physiologic parameters include heart rate, blood pressure, temperature, oxygen saturation, ECG, HRV, and activity level. The computer system 601 comprises an electronic device of a user 635, or comprises a computer system that is remotely located with respect to the electronic device 635. Electronic devices suitable for use with the system 601 include mobile electronic devices such as smartphones, smartwatches, tablets, and laptops. The electronic device 601 comprises one or more sensors configured to sense a physiologic parameter. Numerous sensors are known for measuring heart rate. Non-limiting examples of suitable sensors include light based sensors such as, for example, infrared sensor/emitter, ultrasound sensors, and tactile sensors. Sensors for measuring rhythm include electrodes for measuring electrocardiograms (ECG) and light based sensors for measuring photoplethysmograms.

The computer system 601 includes a central processing unit (CPU, also “processor” and “computer processor” herein) 605, which can be a single core or multi core processor, or a plurality of processors for parallel processing. The computer system 601 also includes memory or memory location 610 (e.g., random-access memory, read-only memory, flash memory), electronic storage unit 615 (e.g., hard disk), communication interface 602 (e.g., network adapter) for communicating with one or more other systems, and peripheral devices 625, such as cache, other memory, data storage and/or electronic display adapters. The memory 610, storage unit 615, interface 602 and peripheral devices 625 are in communication with the CPU 605 through a communication bus (solid lines), such as a motherboard. The storage unit 615 can be a data storage unit (or data repository) for storing data. The computer system 601 can be operatively coupled to a computer network (“network”) 603 with the aid of the communication interface 602. The network 603 can be the Internet, an internet and/or extranet,

or an intranet and/or extranet that is in communication with the Internet. The network 603 in some cases is a telecommunication and/or data network. The network 603 can include one or more computer servers, which can enable distributed computing, such as cloud computing. The network 603, in some cases with the aid of the computer system 601, can implement a peer-to-peer network, which may enable devices coupled to the computer system 601 to behave as a client or a server.

The CPU 605 can execute a sequence of machine-readable instructions, which can be embodied in a program or software. The instructions may be stored in a memory location, such as the memory 610. The instructions can be directed to the CPU 605, which can subsequently program or otherwise configure the CPU 605 to implement methods of the present disclosure. Examples of operations performed by the CPU 605 can include fetch, decode, execute, and writeback.

The CPU 605 can be part of a circuit, such as an integrated circuit. One or more other components of the system 601 can be included in the circuit. In some cases, the circuit is an application specific integrated circuit (ASIC).

The storage unit 615 can store files, such as drivers, libraries and saved programs. The storage unit 615 can store user data, e.g., user preferences and user programs. The computer system 601 in some cases can include one or more additional data storage units that are external to the computer system 601, such as located on a remote server that is in communication with the computer system 601 through an intranet or the Internet.

The computer system 601 can communicate with one or more remote computer systems through the network 603. For instance, the computer system 601 can communicate with a remote computer system of a user (e.g., mobile device, server, etc.). Examples of remote computer systems include personal computers (e.g., portable PC), slate or tablet PC’s (e.g., Apple® iPad, Samsung® Galaxy Tab), telephones, Smart phones (e.g., Apple® iPhone, Android-enabled device, Blackberry®), or personal digital assistants. The user can access the computer system 601 via the network 603.

Methods as described herein can be implemented by way of machine (e.g., computer processor) executable code stored on an electronic storage location of the computer system 601, such as, for example, on the memory 610 or electronic storage unit 615. The machine executable or machine readable code can be provided in the form of software. During use, the code can be executed by the processor 605. In some cases, the code can be retrieved from the storage unit 615 and stored on the memory 610 for ready access by the processor 605. In some situations, the electronic storage unit 615 can be precluded, and machine-executable instructions are stored on memory 610.

The code can be pre-compiled and configured for use with a machine have a processor adapted to execute the code, or can be compiled during runtime. The code can be supplied in a programming language that can be selected to enable the code to execute in a pre-compiled or as-compiled fashion.

Aspects of the systems and methods provided herein, such as the computer system 601, can be embodied in programming. Various aspects of the technology may be thought of as “products” or “articles of manufacture” typically in the form of machine (or processor) executable code and/or associated data that is carried on or embodied in a type of machine readable medium. Machine-executable code can be stored on an electronic storage unit, such memory (e.g., read-only memory, random-access memory, flash memory)

or a hard disk. "Storage" type media can include any or all of the tangible memory of the computers, processors or the like, or associated modules thereof, such as various semiconductor memories, tape drives, disk drives and the like, which may provide non-transitory storage at any time for the software programming. All or portions of the software may at times be communicated through the Internet or various other telecommunication networks. Such communications, for example, may enable loading of the software from one computer or processor into another, for example, from a management server or host computer into the computer platform of an application server. Thus, another type of media that may bear the software elements includes optical, electrical and electromagnetic waves, such as used across physical interfaces between local devices, through wired and optical landline networks and over various air-links. The physical elements that carry such waves, such as wired or wireless links, optical links or the like, also may be considered as media bearing the software. As used herein, unless restricted to non-transitory, tangible "storage" media, terms such as computer or machine "readable medium" refer to any medium that participates in providing instructions to a processor for execution.

Hence, a machine readable medium, such as computer-executable code, may take many forms, including but not limited to, a tangible storage medium, a carrier wave medium or physical transmission medium. Non-volatile storage media include, for example, optical or magnetic disks, such as any of the storage devices in any computer(s) or the like, such as may be used to implement the databases, etc. shown in the drawings. Volatile storage media include dynamic memory, such as main memory of such a computer platform. Tangible transmission media include coaxial cables; copper wire and fiber optics, including the wires that comprise a bus within a computer system. Carrier-wave transmission media may take the form of electric or electromagnetic signals, or acoustic or light waves such as those generated during radio frequency (RF) and infrared (IR) data communications. Common forms of computer-readable media therefore include for example: a floppy disk, a flexible disk, hard disk, magnetic tape, any other magnetic medium, a CD-ROM, DVD or DVD-ROM, any other optical medium, punch cards paper tape, any other physical storage medium with patterns of holes, a RAM, a ROM, a PROM and EPROM, a FLASH-EPROM, any other memory chip or cartridge, a carrier wave transporting data or instructions, cables or links transporting such a carrier wave, or any other medium from which a computer may read programming code and/or data. Many of these forms of computer readable media may be involved in carrying one or more sequences of one or more instructions to a processor for execution

The computer system 601 can include or be in communication with an electronic display 535 that comprises a user interface (UI) 640 for providing, for example, distributions of magnetic fields, distributions of electrical currents, distributions of local myocardial activities, etc. Examples of UI's include, without limitation, a graphical user interface (GUI) and web-based user interface.

Methods and systems of the present disclosure can be implemented by way of one or more algorithms. An algorithm can be implemented by way of software upon execution by the central processing unit 605. The algorithm, for example, is used to analyze a sensed physiologic parameter.

A device as described herein is in some embodiments configured to sense two or more physiologic parameters. For example, a device configured to measure the heart rate of an individual as described herein is also in some embodiments

configured to sense the electrocardiogram of said individual. In these embodiments, a device as described herein includes one or more electrodes configured to sense an electrocardiogram of an individual. In some embodiments, a device as described herein comprises two electrodes. In some embodiments, a device as described herein comprises three electrodes. In some embodiments, a device as described herein comprises four electrodes. In some embodiments, a device as described herein comprises five electrodes. In some embodiments, a device as described herein comprises six electrodes. In some embodiments, a device as described herein comprises seven electrodes. In some embodiments, a device as described herein comprises eight electrodes. In some embodiments, a device as described herein comprises nine electrodes. In some embodiments, a device as described herein comprises ten electrodes. Electrodes of the device described herein are configured to sense an electrocardiogram of an individual and transmit the sensed electrocardiogram data to a processor integrated with the device or part of the system described herein. In some embodiments, the processor is configured to display the electrocardiogram on a display of the device described herein. In some embodiments, the device is configured to sense and/or display a single lead electrocardiogram. In some embodiments, the single lead comprises any of Lead I, Lead II, Lead aVR, Lead aVL, Lead aVF, Lead V1, Lead V2, Lead V3, Lead V4, Lead V5, and Lead V6. In some embodiments, the device is configured to sense and/or display two leads comprising any two of Lead I, Lead II, Lead aVR, Lead aVL, Lead aVF, Lead V1, Lead V2, Lead V3, Lead V4, Lead V5, and Lead V6. In some embodiments, the device is configured to sense and/or display two leads comprising any three of Lead I, Lead II, Lead aVR, Lead aVL, Lead aVF, Lead V1, Lead V2, Lead V3, Lead V4, Lead V5, and Lead V6. In some embodiments, the device is configured to sense and/or display three leads comprising any three of Lead I, Lead II, Lead aVR, Lead aVL, Lead aVF, Lead V1, Lead V2, Lead V3, Lead V4, Lead V5, and Lead V6. In some embodiments, the device is configured to sense and/or display four leads comprising any four of Lead I, Lead II, Lead aVR, Lead aVL, Lead aVF, Lead V1, Lead V2, Lead V3, Lead V4, Lead V5, and Lead V6. In some embodiments, the device is configured to sense and/or display five leads comprising any five of Lead I, Lead II, Lead aVR, Lead aVL, Lead aVF, Lead V1, Lead V2, Lead V3, Lead V4, Lead V5, and Lead V6. In some embodiments, the device or system is configured to sense and/or display six leads comprising any six of Lead I, Lead II, Lead aVR, Lead aVL, Lead aVF, Lead V1, Lead V2, Lead V3, Lead V4, Lead V5, and Lead V6. In some embodiments, the device is configured to sense and/or display seven leads comprising any seven of Lead I, Lead II, Lead aVR, Lead aVL, Lead aVF, Lead V1, Lead V2, Lead V3, Lead V4, Lead V5, and Lead V6. In some embodiments, the device is configured to sense and/or display eight leads comprising any eight of Lead I, Lead II, Lead aVR, Lead aVL, Lead aVF, Lead V1, Lead V2, Lead V3, Lead V4, Lead V5, and Lead V6. In some embodiments, the device is configured to sense and/or display nine leads comprising any nine of Lead I, Lead II, Lead aVR, Lead aVL, Lead aVF, Lead V1, Lead V2, Lead V3, Lead V4, Lead V5, and Lead V6. In some embodiments, the device is configured to sense and/or display ten leads comprising any ten of Lead I, Lead II, Lead aVR, Lead aVL, Lead aVF, Lead V1, Lead V2, Lead V3, Lead V4, Lead V5, and Lead V6. In some embodiments, the device is configured to sense and/or display eleven leads comprising any eleven of Lead I, Lead II, Lead aVR, Lead aVL, Lead aVF, Lead V1, Lead V2,

Lead V3, Lead V4, Lead V5, and Lead V6. In some embodiments, the device is configured to sense and/or display twelve leads comprising any twelve of Lead I, Lead II, Lead aVR, Lead aVL, Lead aVF, Lead V1, Lead V2, Lead V3, Lead V4, Lead V5, and Lead V6. In some embodiments, the device includes software configured to cause a processor of said device to analyze the sensed electrocardiogram. An analysis of a sensed electrocardiogram performed by the processor of the device identifies the presence of an abnormal heart condition. For example, an analysis performed by a processor of a device, in some embodiments, identifies arrhythmias by, for example, analysis of the PQRST waveform and/or comparing multiple PQRST waveforms within an electrocardiogram. In some embodiments, the processor carries out an analysis of an electrocardiogram by comparing one or more PQRST waveforms of an individual against a one or more PQRST waveforms of other individuals from a database containing electrocardiograms of other individuals. In some embodiments of the devices described herein, an individual is alerted to sense an electrocardiogram by, for example, engaging one or more electrodes when the device senses one or more physiologic parameters. For example, in some embodiments, a device as described herein is configured to sense a blood pressure of an individual, and in some of these embodiments, the device is configured to sense a second physiologic parameter of the individual such as for example a heart rate. An accelerated heart rate of an individual sensed by the device in addition to, for example, a low blood pressure of the individual concurrently sensed by the device, triggers the processor of the device to indicate to the individual to engage with the electrodes of the device in order to sense an electrocardiogram.

The combination of a sensed accelerated heart rate and low blood pressure typically indicate an abnormality, however, other physiologic conditions may also produce an elevated heart rate accompanied by low blood pressure including, for example, dehydration. Thus, in some embodiments, accuracy is enhanced when physiologic parameters such as, for example, heart rate, blood pressure, oxygen saturation, and temperature are compared to baseline values of the individual or to a data from a database containing the physiological parameters of other individuals. Some elite athletes, for example, have physiologic parameter values that would be abnormal in another individual such as, for example, very low heart rates or increased heart rate variability (e.g. during a period of exercise).

A device as described herein is in some embodiments configured to sense a photoplethysmogram of an individual. A photoplethysmogram, for example, provides cardiac cycle information and may, for example, be analyzed by a processor of a device described herein to determine a presence of a premature ventricular contraction.

In some embodiments, a device as described herein is configured to sense a pulse oxygenation of an individual. A device as described herein is configured to sense a pulse oxygenation of an individual in some embodiments.

#### Analysis

In some embodiments, a device as described herein is configured to sense and/or analyze a number of additional physiologic parameters. Non-limiting examples of parameter values sensed and/or analyzed by the devices and systems described herein include heart rate, activity level, blood pressure, temperature, pulse oxygen, and heart rate variability. Analysis includes in some embodiments the comparison of a first sensed physiologic parameter to a

second sensed physiologic and determining if a discordance exists between the first and second sensed parameter values.

In some embodiments, a device as described herein is configured to monitor for arrhythmia in an individual, wherein monitoring may comprise the identification of onset of an arrhythmia. In some embodiments, cardiac monitoring carried out by the devices described herein comprises, for example, monitoring for the presence or onset of arrhythmia in an individual who has not previously been identified to have an arrhythmia. In some embodiments, cardiac monitoring carried out by the devices described herein comprises the identification of onset of a known or suspected intermittent arrhythmia. In some embodiments, the devices described herein are configured to predict an onset of an arrhythmia in an individual. The onset of an arrhythmia is, for example, predicted due to a sudden and significant shift in the value of a sensed physiologic parameter such as heart rate. A prediction of arrhythmia is more accurate when two or more physiologic parameters are concurrently sensed and analyzed with respect to one another. For example, sensing of heart rate changes with respect to a sensed activity level provides contextual information for the sensed heart rate.

A subset of arrhythmias are sometimes termed tachyarrhythmias. Tachyarrhythmias typically comprise a tachycardic heart rate which may comprise a heart rate above 100 beats per minute. Tachyarrhythmias may comprise, for example, certain types of atrial fibrillation and supraventricular tachycardia. In some embodiments, the devices as described herein are configured to identify the presence or onset of a tachyarrhythmia, such as, for example, atrial fibrillation or supraventricular tachycardia. In some embodiments, the devices as described herein are configured to identify the presence or onset of a tachyarrhythmia. In some embodiments, the devices as described herein are configured to predict the onset of a tachyarrhythmia.

In some embodiments, the devices as described herein are configured to provide continuous cardiac monitoring. In some embodiments, the devices as described herein are configured to provide continuous cardiac monitoring for a period of up to one year. In some embodiments, the devices as described herein are configured to provide continuous cardiac monitoring for a period of up to 12 months. In some embodiments, the devices described herein are configured to provide continuous cardiac monitoring for a period of up to 6 months. In some embodiments, the devices described herein are configured to provide continuous cardiac monitoring for a period of up to 3 months. In some embodiments, the devices described herein are configured to provide continuous cardiac monitoring for a period of up to 1 month. In some embodiments, the devices described herein are configured to provide continuous cardiac monitoring for a period of up to 2 weeks. In some embodiments, the devices described herein are configured to provide continuous cardiac monitoring for a period of up to 1 week. In some embodiments, the devices described herein are configured to provide continuous cardiac monitoring for a period of up to 72 hours. In some embodiments, the devices described herein are configured to provide continuous cardiac monitoring for a period of up to 48 hours. In some embodiments, the devices described herein are configured to provide continuous cardiac monitoring for a period of up to 24 hours. In some embodiments, the devices described herein are configured to provide continuous cardiac monitoring for a period of up to 12 hours. In some embodiments, the devices described herein are configured to provide continuous cardiac monitoring for a period of up to 8 hours. In some embodiments, the devices described herein are configured to

provide continuous cardiac monitoring for a period of up to 4 hours. In some embodiments, the devices described herein are configured to provide continuous cardiac monitoring for a period of up to 2 months.

In some embodiments, the devices described herein are configured to provide intermittent cardiac monitoring. In some embodiments, intermittent cardiac monitoring is initiated in response to one or more sensed parameter values. Non-limiting examples of the one or more sensed parameter value that may cause initiation of intermittent cardiac monitoring may comprise, for example, a heart rate of an individual, a blood pressure of an individual, an activity level of an individual, a temperature of an individual, a pulse oximetry of an individual, or any other sensed biometric parameter of an individual. In some embodiments, an electrocardiogram of an individual may be sensed in response to one or more sensed parameters. For example, an electrocardiogram may be caused to be sensed in response to a heart rate value.

In some embodiments, one or more continuous sensors may sense one or more parameters that cause the initiation of intermittent cardiac monitoring by one or more sensors. In some embodiments, a heart rate of an individual is sensed continuously. In some embodiments, an activity level of an individual is sensed continuously. In some embodiments, a heart rate variability of an individual is sensed continuously. In some embodiments, an electrocardiogram of an individual is sensed intermittently. In some embodiments, an intermittently sensed electrocardiogram is caused to be sensed in response to a continuously measured heart rate of an individual. In some embodiments, an intermittently sensed electrocardiogram is caused to be sensed in response to an activity level of an individual. In some embodiments, an intermittently sensed electrocardiogram is caused to be sensed in response to both a continuously measured heart rate and a continuously measured activity level. In some embodiments, an intermittently sensed electrocardiogram is caused to be sensed in response to a continuously sensed heart rate, a continuously sensed activity level, and a continuously sensed heart rate variability.

In some embodiments, a device or system as described herein comprises one or more sensors configured for continuous cardiac monitoring. In some embodiments, a device or system as described herein comprises one or more sensors configured for intermittent cardiac monitoring. In some embodiments, a device or system as described herein comprises one or more heart rate sensors, which may, for example, comprise a photosensor. In some embodiments, a device or system as described herein comprises one or more activity level sensors, which may, for example, comprise an accelerometer or a gyroscope. In some embodiments, a device or system as described herein comprises one or more electrocardiogram sensors, which may, for example, comprise one or more electrodes. Non-limiting examples of other sensors suitable for use with the devices, systems, and methods described herein further comprise blood pressure sensors, temperature sensors, and pulse oximetry sensors.

In some embodiments, a device or system as described herein comprises a processor. In some embodiments, a process is coupled with one or more sensors that are configured to sense continuously and one or more sensors that are configured to sense intermittently. In some embodiments, a processor is configured to receive parameter values from one or more sensors. In some embodiments, a processor is configured to activate one or more sensors or to initiate the sensing of a parameter value. In some embodiments, a processor is configured to analyze a parameter value. In some embodiments, a processor is configured to compare a

first parameter value with a second parameter value. In some embodiments, a first and a second parameter value to be compared are simultaneously or essentially simultaneously sensed.

In some embodiments, a device or system as described herein further comprises software in the form of a program or application. In some embodiments, the program or application may be configured to cause a processor to carry out one or more functions. In some embodiments, the program or application may be configured to cause a processor to receive parameter values from one or more sensors. In some embodiments, the program or application may be configured to cause a processor to activate one or more sensors or to initiate the sensing of a parameter value. In some embodiments, the program or application may be configured to cause a processor to analyze a parameter value. In some embodiments, the program or application may be configured to cause a processor to compare a first parameter value with a second parameter value. In some embodiments, a first and a second parameter value to be compared are simultaneously or essentially simultaneously sensed.

In some embodiments, the devices described herein are configured to carry out an analysis, wherein the analysis is performed by a processor. In some embodiments, an analysis of one or more parameter values carried out by the devices described herein comprises a comparison of a sensed parameter value to a threshold or range. For example, an analysis may comprise determining whether a sensed heart rate value falls within one or more ranges. For example, in some embodiments, a sensed heart rate may be determined to be within a heart rate range comprising a range between 60-100 beats per minute. For example, in some embodiments, a sensed heart rate may be determined to be in a heart rate range comprising a range of values less than 60 beats per minute. For example, in some embodiments, a sensed heart rate may be determined to be within a heart rate range comprising a range of values above 100 beats for minute.

In some embodiments, an analysis of one or more parameter values carried out by the devices described herein comprises a comparison of a first sensed parameter to a second sensed parameter. For example, in some embodiments, a heart rate value is compared to a sensed activity level of an individual.

In some embodiments, a first sensed value is compared to a second sensed value, and it is determine whether a discordance exists between the two values. For example, in some embodiments, an elevated heart rate value would be expected to be present during a period of elevated activity, thus an elevated heart rate and an elevated activity level that are simultaneously sensed would not be found to be in discordance with one another.

A discordance may be identified when a first sensed parameter value would not be expected to coincide with a second sensed parameter value. For example, an elevated heart rate value would not be expected to be present with a normal or resting activity level and thus the two values are in discordance with one another. For example, in some embodiments, when a heart rate sensor senses a heart rate above 100 beats per minute and a simultaneously sensed activity level is determined to be a resting activity level, an analysis of the two sensed values determines that they are in discordance with one another.

In some embodiments, an analysis carried out by the devices and systems described herein comprises the determination of an increase in a heart rate variability. In some embodiments, an analysis carried out by the devices and systems described herein comprises comparing a heart rate

variability with one or more sensed parameter values. For example, in some embodiments, a heart rate variability is compared to concurrently or essentially concurrently sensed heart rate and activity level values.

In some embodiments, an analysis carried out by the devices and systems described herein comprises the prediction of or the identification of the initiation of an arrhythmia using an identified discordance as described herein. In some embodiments, a discordance comprising a simultaneously or essentially simultaneously sensed elevated heart rate and resting or normal activity level is determined to indicate the imminent initiation of an arrhythmia or the presence of an arrhythmia. In particular, because the heart rate is elevated, the arrhythmia with this type of discordance typically comprises a tachyarrhythmia.

In some embodiments, a simultaneously sensed increase in heart rate variability, an elevated heart rate, and a resting or normal activity rate is determined to indicate the future onset or presence of atrial fibrillation. In some embodiments, a sensed increased heart rate variability, normal resting heart rate, and resting or normal activity rate may also be determined to indicate the future onset of or the presence of atrial fibrillation. In some embodiments, a simultaneously sensed decrease in heart rate variability, an elevated heart rate, and a resting or normal activity rate is determined to indicate the future onset or presence of supraventricular tachycardia. In some embodiments, when an arrhythmia is determined to be imminent or present, an electrocardiogram is recorded. In some embodiments, an individual is instructed or signaled by a cardiac monitoring device or system described herein to engage one or more electrodes in order to sense in electrocardiogram. In some embodiments, one or more electrodes may be positioned on a surface of a cardiac monitoring device so that the individual may, for example, comfortably engage a first electrode with a skin surface of a first extremity while simultaneously engaging a second electrode with a skin surface of a second extremity. In some embodiments, one or more electrodes may be affixed to an individual's body and are automatically engaged to sense an electrocardiogram by a cardiac monitoring device or system when an arrhythmia is determined to be imminent or present in the individual. For example, a first electrode may be positioned on smartwatch worn by the individual on a first extremity and a second electrode may be positioned on a wristlet worn by the individual on a second extremity. In this example, the first electrode on the smartwatch and the second electrode on the wristlet are both in communication with and controlled by the cardiac monitoring device.

In some embodiments, the devices described herein are configured to carry out machine learning. In some embodiments, the devices, systems, and methods described herein comprise machine learning algorithms which analyze parameter values sensed from an individual over period of time. In some embodiments, the devices, systems, and methods described herein comprise machine learning algorithms which analyze parameter values sensed from a plurality of individuals. In some embodiments, a machine learning algorithm causes the devices, systems, and methods described herein to more accurately identify or predict the presence of an arrhythmia in a given individual. For example, in some embodiments, sensed electrocardiogram data may be compared back to parameter values such as, for example, sensed heart rates and activity levels that triggered the sensing of said electrocardiograms. When, for example, sensed electrocardiograms confirm the presence of an arrhythmia, the presence of which was indicated by, for example, a discordance between other parameter values, the

machine algorithm causes the device or system described herein to learn from that data. Similarly, when, for example, sensed electrocardiograms do not confirm the presence of an arrhythmia, the presence of which was indicated by, for example, a discordance between other parameter values, the machine algorithm causes the device or system described herein to learn from that data as well. That is, in some embodiments, the machine learning algorithm correlates the sensed electrocardiogram with the discordance between parameter values that caused it (i.e. the electrocardiogram) to be sensed. The presence or absence of an arrhythmia on the electrocardiogram either respectively reinforces the correlation of an arrhythmia with the discordance that caused the electrocardiogram to be sensed or contradicts the presence of a correlation of an arrhythmia with the discordance. For example, when a heart rate of 110 is sensed and simultaneously a resting activity is sensed, an electrocardiogram is caused to be sensed, and when the sensed electrocardiogram does not indicate a presence of an arrhythmia the machine learning algorithm causes the device or system as described herein to learn that for that individual a heart rate of 110 at rest does not necessarily indicate a presence of an arrhythmia. In some embodiments, the machine learning algorithm continues to cause the storing of parameter value data, such as, for example, heart rate, activity level, and heart rate variability, and compare the parameter values to the associated electrocardiogram data over time. Thus, in some embodiments, with multiple parameter values sensed over time and compared to associated electrocardiogram data, a cardiac monitoring device or system improves its ability to predict or identify the onset of arrhythmia based on a discordance between parameter values for a specific individual. In some embodiments, a machine learning algorithm may obviate the need to sense an electrocardiogram when a particular discordance is present between parameter values of a specific individual, because of an extremely high likelihood of a presence or absence of an arrhythmia based on the parameter values as determined by the machine learning algorithm.

Any of the devices, systems, and methods for cardiac monitoring described herein may comprise one or more of a smartphone, a laptop or desktop computer, a smartwatch, or a tablet computer.

#### Discordance Monitoring

FIG. 7 shows a schematic of an algorithm for discordance monitoring. In a step 700, a heart rate and an activity level are sensed by, for example, a device or system as described herein. In some embodiments, an activity level is sensed with a gyroscope or an accelerometer that is. Heart rate is sensed with a light based or other commonly used heart rate sensors. The device that measures the heart rate and the activity level may be the same device or more than one device. For example, a smartwatch or other wearable device may be configured to include a heart rate sensor as well as an activity level sensor.

If, as shown in a step 702, an increased heart rate is sensed together with a normal or resting activity level, the two values are determined to be in discordance by the device or system processor. That is, the elevated heart rate does not match the sensed stable activity level. Determination of the presence of the discordance is done by a processor of either the device or system as described herein. The identified discordance may indicate the presence of an arrhythmia. As such, an ECG is caused to be sensed in a step 712A. The step 712A, may, for example, comprise indicating to the user through the device or system that sensed the heart rate and activity level to contact one or more electrodes of an ECG

sensing device and thus sense the ECG. The ECG sensing device may be the device or part of the system used to sense the heart rate and activity level or may be a separate device. For example, a user wearing a smartwatch with heart rate and activity level monitoring receives an audible and/or visual indication from the smartwatch to sense an ECG when a discordance is present between a sensed heart rate value and a sensed activity level value. In some embodiments, the smartwatch comprises one or more electrodes and a user contacts one electrode with the left side of their body and one electrode with the right side of their body when an indication is received to do so from the smartwatch because a discordance is present thus sensing an ECG. In some embodiments, a smartphone comprises one or more electrodes and a user contacts one electrode with the left side of their body and one electrode with the right side of their body when an indication is received to do so from the smartwatch because a discordance is present thus sensing an ECG.

If, as shown in step 704, an increased heart rate is sensed together with an increased heart rate variability, and a normal or resting activity level is sensed. The increased heart rate and HRV are in discordance with the normal or resting activity level, and a presence of a discordance is determined by the device or system processor. Once the discordance is determined, an ECG is caused to be sensed in a step 712B as, for example, described herein with respect to step 712A. As shown, in step 716, this particular discordance may be indicative of the presence of atrial fibrillation and it should be confirmed with the ECG 712B.

If, as shown in step 706, an increased heart rate is sensed together with a decreased heart rate variability and a normal or resting activity level is sensed. The increased heart rate, decreased heart rate variability, and normal or resting activity level are in discordance with each other, and a presence of a discordance is determined by the device or system processor. Once the discordance is determined, an ECG is caused to be sensed in a step 712C as, for example, described herein with respect to step 712A. As shown, in a step 718, supraventricular tachycardia may be present and it should be confirmed with the ECG of 712C.

If, as shown in a step 708, an increased heart rate is sensed together with an increased activity level, the device or system processor determines that no discordance is present, and an ECG is not recorded as the individual is probably exercising 714.

If, as shown in a step 710, a regular heart rate is sensed (e.g. 60-100 beats per minute) and an increased heart rate variability is sensed together with a normal or resting activity level. The normal heart rate, increased heart rate variability, and normal or resting activity level are in discordance with each other, and a presence of a discordance is determined by the device or system processor. Once the discordance is determined, an ECG is caused to be sensed in a step 712D as, for example, described herein with respect to step 712A. As shown, in a step 720, atrial fibrillation may be present and it should be confirmed with the ECG of 712D.

In some embodiments, a determination of the presence of a discordance is based on a comparison of two or more sensed physiologic parameters with each other. That is, for example, an elevated heart rate of 110 is compared to a resting activity level as sensed by an accelerometer which measures that the individual is traveling at 0 miles/hr. The 110 heart rate is elevated whereas the activity level of 0 miles/hr is a resting level, which indicates a discordance between the sensed heart rate and activity level. In some embodiments, a processor determines that the value of a sensed physiologic parameter is either above or below a

threshold value or range of values. In some embodiments, the threshold value or range of values are deemed to be normal or resting values in the population. In some embodiments, the thresholds are specific to the biometric data of the user so that the user is, for example, age-matched or gender matched to the appropriate threshold from the general population. For example, an activity level is determined to be increased in a 70 year old user but would not be increased in a 7 year old user. Thus, a discordance is determined by qualifying if a sensed physiologic parameter is elevated, decreased, or normal (or resting) and then comparing that qualified value to a qualified value of another sensed physiologic parameter. That is, for example, a value that is qualified as either increased, decreased, or normal (or resting) is compared to a value that is also qualified as increased, decreased, or normal (or resting).

In some embodiments, there is the added step (not shown in FIG. 7) of the devices and systems described herein running machine learning algorithms so that the threshold values and ranges used to determine whether a sensed physiologic parameter is increased, decreased, normal (or resting) are adjusted to more accurately fit the user. That is, for example, a user who was determined, through ECG, to have an arrhythmia at a heart rate of 80 will have their heart rate threshold lowered so that a heart of 85 (which is normal in some) would be determined to be an increased rate. The machine learning algorithm more accurately sets the thresholds over time so that discordances are more accurately determined resulting in more accurate (and efficient) recording of ECGs in response to the determination of the presence of the discordance.

Table 1 below presents some of the information found in FIG. 7 in table form.

TABLE 1

HR Data	Activity Level Data	HRV Data	Action
HR increases	Activity level stable		Take an ECG, possible arrhythmia
HR increases	Activity level stable	HRV increases	Take an ECG, possible atrial fibrillation
HR increases	Activity level stable	HRV decreases	Take an ECG, possible supraventricular tachycardia or ventricular tachycardia
HR increases	Activity level increases		Don't take an ECG, probable exercise
HR stable	Activity level stable	HRV increases	Take an ECG, possible atrial fibrillation

While preferred embodiments of the present individual matter described herein have been shown and described herein, it will be obvious to those skilled in the art that such embodiments are provided by way of example only. Numerous variations, changes, and substitutions will now occur to those skilled in the art without departing from the individual matter described herein. It should be understood that various alternatives to the embodiments of the individual matter described herein described herein may be employed in practicing the individual matter described herein. It is intended that the following claims define the scope of the individual matter described herein and that methods and structures within the scope of these claims and their equivalents be covered thereby.

What is claimed is:

1. A computer-implemented system comprising:
  - a digital processing device comprising an activity level sensor configured to sense an activity level value and a heart rate sensor configured to sense a heart rate value;
  - a memory operatively coupled to the digital processing device, the memory device comprising executable instructions that cause the digital processing device to: receive the activity level value that is measured by the activity level sensor and the heart rate value that is sensed by the heart rate sensor;
  - determine that a discordance is present between the activity level value and the heart rate value; and
  - apply, in response to determining that the discordance is present, a machine learning algorithm to determine that an arrhythmia is present.
2. The system of claim 1, wherein the digital processing device comprises a smartwatch.
3. The system of claim 1, wherein the digital processing device comprises a first electrode and a second electrode configured to sense an electrocardiogram.
4. The system of claim 1, wherein the machine learning algorithm is trained with data comprising an electrocardiogram showing the arrhythmia when the discordance is present.
5. The system of claim 3, wherein the digital processing device is further configured to determine a heart rate variability based on the heart rate value.
6. The system of claim 5, wherein the discordance is determined to be present between the activity level value and the heart rate value based on the heart rate variability value.
7. The system of claim 6, wherein the machine learning algorithm is configured to determine a presence of said arrhythmia on said electrocardiogram, and determine a correlation between the discordance and the arrhythmia when said arrhythmia is present on said electrocardiogram.

8. The system of claim 1, wherein the digital processing device is further configured to determine a duration of said arrhythmia.

9. A method for determining the presence of an arrhythmia, comprising:

- sensing an activity level value of an individual with a first sensor of a digital processing device;
- sensing a heart rate value of said individual with a second sensor of said digital processing device;
- determining that a discordance is present between said activity level value and said heart rate value; and
- applying, in response to determining that the discordance is present, a machine learning algorithm to determine that an arrhythmia is present.

10. The method of claim 9, wherein the digital processing device comprises a smartwatch.

11. The method of claim 9, wherein the digital processing device comprises a first electrode and a second electrode configured to sense an electrocardiogram.

12. The method of claim 10, wherein the machine learning algorithm is trained with data comprising an electrocardiogram showing the arrhythmia when the discordance is present.

13. The method of claim 11, further comprising determining a heart rate variability based on the heart rate value.

14. The method of claim 13, wherein the discordance is determined to be present between the activity level value and the heart rate value based on the heart rate variability value.

15. The method of claim 14, wherein the machine learning algorithm is configured to determine a presence of said arrhythmia on said electrocardiogram, and determine a correlation between the discordance and the arrhythmia when said arrhythmia is present on said electrocardiogram.

16. The method of claim 11, wherein the computer program comprises a software module configured to determine a duration of said arrhythmia.

\* \* \* \* \*

专利名称(译)	不一致监控		
公开(公告)号	<a href="#">US10537250</a>	公开(公告)日	2020-01-21
申请号	US15/656745	申请日	2017-07-21
[标]申请(专利权)人(译)	阿利弗克公司		
申请(专利权)人(译)	ALIVECOR INC.		
当前申请(专利权)人(译)	ALIVECOR INC.		
[标]发明人	ALBERT DAVID E		
发明人	ALBERT, DAVID E.		
IPC分类号	A61B5/02 A61B5/00 A61B5/0205 A61B5/0464 A61B5/046 A61B5/11 A61B5/024 A61B5/0408		
CPC分类号	A61B5/0205 A61B5/7267 A61B5/681 A61B5/04085 A61B5/02405 A61B2562/0219 A61B5/02438 A61B5/0464 A61B5/1118 A61B5/046 G16H40/63 G16H40/67 G16H50/20 G16H50/30		
优先权	62/161092 2015-05-13 US		
其他公开文献	US20170319080A1		
外部链接	<a href="#">Espacenet</a>		

摘要(译)

本文描述了用于心脏监测的系统，设备和方法。特别地，本文描述的系统，设备和方法可用于方便地感测个体中间歇性心律不齐的存在。本文描述的系统，设备和方法可以进一步被配置为感测心电图。

