



US009480435B2

(12) **United States Patent**
Olsen

(10) **Patent No.:** **US 9,480,435 B2**
(45) **Date of Patent:** **Nov. 1, 2016**

(54) **CONFIGURABLE PATIENT MONITORING SYSTEM**

A61B 5/7405 (2013.01); *A61B 5/746* (2013.01); *G06F 19/345* (2013.01); *G06F 19/3406* (2013.01); *G06T 11/206* (2013.01); *G06T 13/80* (2013.01); *A61B 5/0008* (2013.01); *A61B 5/01* (2013.01); *A61B 5/02055* (2013.01); *A61B 5/14532* (2013.01); *A61B 5/14546* (2013.01); *A61B 5/14551* (2013.01); *A61B 5/744* (2013.01); *G06T 2219/2016* (2013.01)

(71) Applicant: **Cercacor Laboratories, Inc.**, Irvine, CA (US)

(72) Inventor: **Gregory A. Olsen**, Trabuco Canyon, CA (US)

(73) Assignee: **MASIMO CORPORATION**, Irvine, CA (US)

(58) **Field of Classification Search**
CPC *G06F 19/3406*; *G06F 19/345*; *G06F 3/04817*; *G06F 3/04842*; *A61B 5/02*; *A61B 5/746*; *A61B 5/7435*; *A61B 5/72*; *G06T 11/001-11/80*; *G06T 13/20*
See application file for complete search history.

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 726 days.

(21) Appl. No.: **13/762,751**

(56) **References Cited**

(22) Filed: **Feb. 8, 2013**

U.S. PATENT DOCUMENTS

(65) **Prior Publication Data**
US 2013/0211214 A1 Aug. 15, 2013

4,300,548 A 11/1981 Jones
4,960,128 A 10/1990 Gordon et al.
(Continued)

Related U.S. Application Data

(60) Provisional application No. 61/597,140, filed on Feb. 9, 2012.

OTHER PUBLICATIONS

US 8,845,543, 09/2014, Diab et al. (withdrawn).


(51) **Int. Cl.**
A61B 5/00 (2006.01)
G06F 19/00 (2011.01)
A61B 5/026 (2006.01)
A61B 5/1455 (2006.01)
G06T 11/20 (2006.01)
G06T 13/80 (2011.01)
G06T 13/00 (2011.01)
G06T 11/00 (2006.01)
A61B 5/145 (2006.01)
A61B 5/0205 (2006.01)
A61B 5/01 (2006.01)

Primary Examiner — William Thomson
Assistant Examiner — Marie Archer
(74) *Attorney, Agent, or Firm* — Knobbe, Martens, Olson & Bear, LLP

(52) **U.S. Cl.**
CPC *A61B 5/743* (2013.01); *A61B 5/0261* (2013.01); *A61B 5/14552* (2013.01); *A61B 5/7282* (2013.01); *A61B 5/742* (2013.01);

(57) **ABSTRACT**
A patient monitoring system can display one or more configurable health monitors on a configurable user interface. The health indicators are configured to display a physiological signal from a patient. The patient monitoring system can calculate ranges of values for the health indicator that correspond to a status of the patient. The health indicators can display different outputs based on the value of the physiological signal.

22 Claims, 5 Drawing Sheets



(56)

References Cited

U.S. PATENT DOCUMENTS

4,964,408	A	10/1990	Hink et al.	6,253,097	B1	6/2001	Aronow et al.
5,041,187	A	8/1991	Hink et al.	6,256,523	B1	7/2001	Diab et al.
5,069,213	A	12/1991	Polczynski	6,263,222	B1	7/2001	Diab et al.
5,163,438	A	11/1992	Gordon et al.	6,278,522	B1	8/2001	Lepper, Jr. et al.
5,319,355	A	6/1994	Russek	6,280,213	B1	8/2001	Tobler et al.
5,337,744	A	8/1994	Branigan	6,285,896	B1	9/2001	Tobler et al.
5,341,805	A	8/1994	Stavridi et al.	6,301,493	B1	10/2001	Marro et al.
D353,195	S	12/1994	Savage et al.	6,317,627	B1	11/2001	Ennen et al.
D353,196	S	12/1994	Savage et al.	6,321,100	B1	11/2001	Parker
5,377,676	A	1/1995	Vari et al.	6,325,761	B1	12/2001	Jay
D359,546	S	6/1995	Savage et al.	6,334,065	B1	12/2001	Al-Ali et al.
5,431,170	A	7/1995	Mathews	6,343,224	B1	1/2002	Parker
D361,840	S	8/1995	Savage et al.	6,349,228	B1	2/2002	Kiani et al.
D362,063	S	9/1995	Savage et al.	6,360,114	B1	3/2002	Diab et al.
5,452,717	A	9/1995	Branigan et al.	6,368,283	B1	4/2002	Xu et al.
D363,120	S	10/1995	Savage et al.	6,371,921	B1	4/2002	Caro et al.
5,456,252	A	10/1995	Vari et al.	6,377,829	B1	4/2002	Al-Ali
5,479,934	A	1/1996	Imran	6,388,240	B2	5/2002	Schulz et al.
5,482,036	A	1/1996	Diab et al.	6,397,091	B2	5/2002	Diab et al.
5,490,505	A	2/1996	Diab et al.	6,430,437	B1	8/2002	Marro
5,494,043	A	2/1996	O'Sullivan et al.	6,430,525	B1	8/2002	Weber et al.
5,533,511	A	7/1996	Kaspari et al.	6,463,311	B1	10/2002	Diab
5,534,851	A	7/1996	Russek	6,470,199	B1	10/2002	Kopotic et al.
5,561,275	A	10/1996	Savage et al.	6,501,975	B2	12/2002	Diab et al.
5,562,002	A	10/1996	Lalin	6,505,059	B1	1/2003	Kollias et al.
5,590,649	A	1/1997	Caro et al.	6,515,273	B2	2/2003	Al-Ali
5,602,924	A	2/1997	Durand et al.	6,519,487	B1	2/2003	Parker
5,632,272	A	5/1997	Diab et al.	6,525,386	B1	2/2003	Mills et al.
5,638,816	A	6/1997	Kiani-Azarbayjany et al.	6,526,300	B1	2/2003	Kiani et al.
5,638,818	A	6/1997	Diab et al.	6,541,756	B2	4/2003	Schulz et al.
5,645,440	A	7/1997	Tobler et al.	6,542,764	B1	4/2003	Al-Ali et al.
5,685,299	A	11/1997	Diab et al.	6,580,086	B1	6/2003	Schulz et al.
D393,830	S	4/1998	Tobler et al.	6,584,336	B1	6/2003	Ali et al.
5,743,262	A	4/1998	Lepper, Jr. et al.	6,595,316	B2	7/2003	Cybulski et al.
5,758,644	A	6/1998	Diab et al.	6,597,932	B2	7/2003	Tian et al.
5,760,910	A	6/1998	Lepper, Jr. et al.	6,597,933	B2	7/2003	Kiani et al.
5,769,785	A	6/1998	Diab et al.	6,606,511	B1	8/2003	Ali et al.
5,782,757	A	7/1998	Diab et al.	6,632,181	B2	10/2003	Flaherty et al.
5,785,659	A	7/1998	Caro et al.	6,639,668	B1	10/2003	Trepagnier
5,791,347	A	8/1998	Flaherty et al.	6,640,116	B2	10/2003	Diab
5,810,734	A	9/1998	Caro et al.	6,643,530	B2	11/2003	Diab et al.
5,823,950	A	10/1998	Diab et al.	6,650,917	B2	11/2003	Diab et al.
5,830,131	A	11/1998	Caro et al.	6,654,624	B2	11/2003	Diab et al.
5,833,618	A	11/1998	Caro et al.	6,658,276	B2	12/2003	Kiani et al.
5,860,919	A	1/1999	Kiani-Azarbayjany et al.	6,661,161	B1	12/2003	Lanzo et al.
5,890,929	A	4/1999	Mills et al.	6,671,531	B2	12/2003	Al-Ali et al.
5,904,654	A	5/1999	Wohlmann et al.	6,678,543	B2	1/2004	Diab et al.
5,919,134	A	7/1999	Diab	6,684,090	B2	1/2004	Ali et al.
5,934,925	A	8/1999	Tobler et al.	6,684,091	B2	1/2004	Parker
5,940,182	A	8/1999	Lepper, Jr. et al.	6,697,656	B1	2/2004	Al-Ali
5,995,855	A	11/1999	Kiani et al.	6,697,657	B1	2/2004	Shehada et al.
5,997,343	A	12/1999	Mills et al.	6,697,658	B2	2/2004	Al-Ali
6,002,952	A	12/1999	Diab et al.	RE38,476	E	3/2004	Diab et al.
6,011,986	A	1/2000	Diab et al.	6,699,194	B1	3/2004	Diab et al.
6,027,452	A	2/2000	Flaherty et al.	6,714,804	B2	3/2004	Al-Ali et al.
6,036,642	A	3/2000	Diab et al.	RE38,492	E	4/2004	Diab et al.
6,045,509	A	4/2000	Caro et al.	6,721,582	B2	4/2004	Trepagnier et al.
6,067,462	A	5/2000	Diab et al.	6,721,585	B1	4/2004	Parker
6,081,735	A	6/2000	Diab et al.	6,725,075	B2	4/2004	Al-Ali
6,088,607	A	7/2000	Diab et al.	6,728,560	B2	4/2004	Kollias et al.
6,110,522	A	8/2000	Lepper, Jr. et al.	6,735,459	B2	5/2004	Parker
6,124,597	A	9/2000	Shehada	6,745,060	B2	6/2004	Diab et al.
6,128,521	A	10/2000	Marro et al.	6,760,607	B2	7/2004	Al-Ali
6,129,675	A	10/2000	Jay	6,770,028	B1	8/2004	Ali et al.
6,144,868	A	11/2000	Parker	6,771,994	B2	8/2004	Kiani et al.
6,151,516	A	11/2000	Kiani-Azarbayjany et al.	6,792,300	B1	9/2004	Diab et al.
6,152,754	A	11/2000	Gerhardt et al.	6,813,511	B2	11/2004	Diab et al.
6,157,850	A	12/2000	Diab et al.	6,816,741	B2	11/2004	Diab
6,165,005	A	12/2000	Mills et al.	6,822,564	B2	11/2004	Al-Ali
6,184,521	B1	2/2001	Coffin, IV et al.	6,826,419	B2	11/2004	Diab et al.
6,206,830	B1	3/2001	Diab et al.	6,830,711	B2	12/2004	Mills et al.
6,229,856	B1	5/2001	Diab et al.	6,850,787	B2	2/2005	Weber et al.
6,232,609	B1	5/2001	Snyder et al.	6,850,788	B2	2/2005	Al-Ali
6,236,872	B1	5/2001	Diab et al.	6,852,083	B2	2/2005	Caro et al.
6,241,683	B1	6/2001	Macklem et al.	6,861,639	B2	3/2005	Al-Ali
				6,898,452	B2	5/2005	Al-Ali et al.
				6,920,345	B2	7/2005	Al-Ali et al.
				6,931,268	B1	8/2005	Kiani-Azarbayjany et al.
				6,934,570	B2	8/2005	Kiani et al.

(56)

References Cited

U.S. PATENT DOCUMENTS

6,939,305 B2	9/2005	Flaherty et al.	D587,657 S	3/2009	Al-Ali et al.
6,943,348 B1	9/2005	Coffin, IV	7,499,741 B2	3/2009	Diab et al.
6,950,687 B2	9/2005	Al-Ali	7,499,835 B2	3/2009	Weber et al.
6,961,598 B2	11/2005	Diab	7,500,950 B2	3/2009	Al-Ali et al.
6,970,792 B1	11/2005	Diab	7,509,154 B2	3/2009	Diab et al.
6,979,812 B2	12/2005	Al-Ali	7,509,494 B2	3/2009	Al-Ali
6,985,764 B2	1/2006	Mason et al.	7,510,849 B2	3/2009	Schurman et al.
6,993,371 B2	1/2006	Kiani et al.	7,526,328 B2	4/2009	Diab et al.
6,996,427 B2	2/2006	Ali et al.	7,530,942 B1	5/2009	Diab
6,999,904 B2	2/2006	Weber et al.	7,530,949 B2	5/2009	Al Ali et al.
7,003,338 B2	2/2006	Weber et al.	7,530,955 B2	5/2009	Diab et al.
7,003,339 B2	2/2006	Diab et al.	7,563,110 B2	7/2009	Al-Ali et al.
7,015,451 B2	3/2006	Dalke et al.	7,596,398 B2	9/2009	Al-Ali et al.
7,024,233 B2	4/2006	Ali et al.	7,618,375 B2	11/2009	Flaherty
7,027,849 B2	4/2006	Al-Ali	D606,659 S	12/2009	Kiani et al.
7,030,749 B2	4/2006	Al-Ali	7,647,083 B2	1/2010	Al-Ali et al.
7,039,449 B2	5/2006	Al-Ali	D609,193 S	2/2010	Al-Ali et al.
7,041,060 B2	5/2006	Flaherty et al.	D614,305 S	4/2010	Al-Ali et al.
7,044,918 B2	5/2006	Diab	RE41,317 E	5/2010	Parker
7,067,893 B2	6/2006	Mills et al.	7,729,733 B2	6/2010	Al-Ali et al.
7,096,052 B2	8/2006	Mason et al.	7,734,320 B2	6/2010	Al-Ali
7,096,054 B2	8/2006	Abdul-Hafiz et al.	7,761,127 B2	7/2010	Al-Ali et al.
7,132,641 B2	11/2006	Schulz et al.	7,761,128 B2	7/2010	Al-Ali et al.
7,142,901 B2	11/2006	Kiani et al.	7,764,982 B2	7/2010	Dalke et al.
7,149,561 B2	12/2006	Diab	D621,516 S	8/2010	Kiani et al.
7,186,966 B2	3/2007	Al-Ali	7,791,155 B2	9/2010	Diab
7,190,261 B2	3/2007	Al-Ali	7,801,581 B2	9/2010	Diab
7,215,984 B2	5/2007	Diab	7,822,452 B2	10/2010	Schurman et al.
7,215,986 B2	5/2007	Diab	RE41,912 E	11/2010	Parker
7,221,971 B2	5/2007	Diab	7,844,313 B2	11/2010	Kiani et al.
7,225,006 B2	5/2007	Al-Ali et al.	7,844,314 B2	11/2010	Al-Ali
7,225,007 B2	5/2007	Al-Ali	7,844,315 B2	11/2010	Al-Ali
RE39,672 E	6/2007	Shehada et al.	7,865,222 B2	1/2011	Weber et al.
7,239,905 B2	7/2007	Kiani-Azarbayjany et al.	7,873,497 B2	1/2011	Weber et al.
7,245,953 B1	7/2007	Parker	7,880,606 B2	2/2011	Al-Ali
7,254,429 B2	8/2007	Schurman et al.	7,880,626 B2	2/2011	Al-Ali et al.
7,254,431 B2	8/2007	Al-Ali	7,891,355 B2	2/2011	Al-Ali et al.
7,254,433 B2	8/2007	Diab et al.	7,894,868 B2	2/2011	Al-Ali et al.
7,254,434 B2	8/2007	Schulz et al.	7,899,507 B2	3/2011	Al-Ali et al.
7,272,425 B2	9/2007	Al-Ali	7,899,518 B2	3/2011	Trepagnier et al.
7,274,955 B2	9/2007	Kiani et al.	7,904,132 B2	3/2011	Weber et al.
D554,263 S	10/2007	Al-Ali	7,909,772 B2	3/2011	Popov et al.
7,280,858 B2	10/2007	Al-Ali et al.	7,910,875 B2	3/2011	Al-Ali
7,289,835 B2	10/2007	Mansfield et al.	7,919,713 B2	4/2011	Al-Ali et al.
7,292,883 B2	11/2007	De Felice et al.	7,937,128 B2	5/2011	Al-Ali
7,295,866 B2	11/2007	Al-Ali	7,937,129 B2	5/2011	Mason et al.
7,328,053 B1	2/2008	Diab et al.	7,937,130 B2	5/2011	Diab et al.
7,332,784 B2	2/2008	Mills et al.	7,941,199 B2	5/2011	Kiani
7,340,287 B2	3/2008	Mason et al.	7,951,086 B2	5/2011	Flaherty et al.
7,341,559 B2	3/2008	Schulz et al.	7,957,780 B2	6/2011	Lamego et al.
7,343,186 B2	3/2008	Lamego et al.	7,962,188 B2	6/2011	Kiani et al.
D566,282 S	4/2008	Al-Ali et al.	7,962,190 B1	6/2011	Diab et al.
7,355,512 B1	4/2008	Al-Ali	7,976,472 B2	7/2011	Kiani
7,356,365 B2	4/2008	Schurman	7,988,637 B2	8/2011	Diab
7,371,981 B2	5/2008	Abdul-Hafiz	7,990,382 B2	8/2011	Kiani
7,373,193 B2	5/2008	Al-Ali et al.	7,991,446 B2	8/2011	Ali et al.
7,373,194 B2	5/2008	Weber et al.	8,000,761 B2	8/2011	Al-Ali
7,376,453 B1	5/2008	Diab et al.	8,008,088 B2	8/2011	Bellott et al.
7,377,794 B2	5/2008	Al-Ali et al.	RE42,753 E	9/2011	Kiani-Azarbayjany et al.
7,377,899 B2	5/2008	Weber et al.	8,019,400 B2	9/2011	Diab et al.
7,383,070 B2	6/2008	Diab et al.	8,028,701 B2	10/2011	Al-Ali et al.
7,415,297 B2	8/2008	Al-Ali et al.	8,029,765 B2	10/2011	Bellott et al.
7,428,432 B2	9/2008	Ali et al.	8,036,727 B2	10/2011	Schurman et al.
7,438,683 B2	10/2008	Al-Ali et al.	8,036,728 B2	10/2011	Diab et al.
7,440,787 B2	10/2008	Diab	8,046,040 B2	10/2011	Ali et al.
7,454,240 B2	11/2008	Diab et al.	8,046,041 B2	10/2011	Diab et al.
7,467,002 B2	12/2008	Weber et al.	8,046,042 B2	10/2011	Diab et al.
7,469,157 B2	12/2008	Diab et al.	8,048,040 B2	11/2011	Kiani
7,471,969 B2	12/2008	Diab et al.	8,050,728 B2	11/2011	Al-Ali et al.
7,471,971 B2	12/2008	Diab et al.	RE43,169 E	2/2012	Parker
7,483,729 B2	1/2009	Al-Ali et al.	8,118,620 B2	2/2012	Al-Ali et al.
7,483,730 B2	1/2009	Diab et al.	8,126,528 B2	2/2012	Diab et al.
7,489,958 B2	2/2009	Diab et al.	8,128,572 B2	3/2012	Diab et al.
7,496,391 B2	2/2009	Diab et al.	8,130,105 B2	3/2012	Al-Ali et al.
7,496,393 B2	2/2009	Diab et al.	8,145,287 B2	3/2012	Diab et al.
			8,150,487 B2	4/2012	Diab et al.
			8,175,672 B2	5/2012	Parker
			8,180,420 B2	5/2012	Diab et al.
			8,182,443 B1	5/2012	Kiani

(56)

References Cited

U.S. PATENT DOCUMENTS

8,185,180 B2	5/2012	Diab et al.	8,588,880 B2	11/2013	Abdul-Hafiz et al.
8,190,223 B2	5/2012	Al-Ali et al.	8,600,467 B2	12/2013	Al-Ali et al.
8,190,227 B2	5/2012	Diab et al.	8,606,342 B2	12/2013	Diab
8,203,438 B2	6/2012	Kiani et al.	8,626,255 B2	1/2014	Al-Ali et al.
8,203,704 B2	6/2012	Merritt et al.	8,630,691 B2	1/2014	Lamego et al.
8,204,566 B2	6/2012	Schurman et al.	8,634,889 B2	1/2014	Al-Ali et al.
8,219,172 B2	7/2012	Schurman et al.	8,641,631 B2	2/2014	Sierra et al.
8,224,411 B2	7/2012	Al-Ali et al.	8,652,060 B2	2/2014	Al-Ali
8,228,181 B2	7/2012	Al-Ali	8,663,107 B2	3/2014	Kiani
8,229,533 B2	7/2012	Diab et al.	8,666,468 B1	3/2014	Al-Ali
8,233,955 B2	7/2012	Al-Ali et al.	8,667,967 B2	3/2014	Al-Ali et al.
8,244,325 B2	8/2012	Al-Ali et al.	8,670,811 B2	3/2014	O'Reilly
8,255,026 B1	8/2012	Al-Ali	8,670,814 B2	3/2014	Diab et al.
8,255,027 B2	8/2012	Al-Ali et al.	8,676,286 B2	3/2014	Weber et al.
8,255,028 B2	8/2012	Al-Ali et al.	8,682,407 B2	3/2014	Al-Ali
8,260,577 B2	9/2012	Weber et al.	RE44,823 E	4/2014	Parker
8,265,723 B1	9/2012	McHale et al.	RE44,875 E	4/2014	Kiani et al.
8,274,360 B2	9/2012	Sampath et al.	8,690,799 B2	4/2014	Telfort et al.
8,301,217 B2	10/2012	Al-Ali et al.	8,700,112 B2	4/2014	Kiani
8,306,596 B2	11/2012	Schurman et al.	8,702,627 B2	4/2014	Telfort et al.
8,310,336 B2	11/2012	Muhsin et al.	8,706,179 B2	4/2014	Parker
8,315,683 B2	11/2012	Al-Ali et al.	8,712,494 B1	4/2014	MacNeish, III et al.
RE43,860 E	12/2012	Parker	8,715,206 B2	5/2014	Telfort et al.
8,337,403 B2	12/2012	Al-Ali et al.	8,718,735 B2	5/2014	Lamego et al.
8,346,330 B2	1/2013	Lamego	8,718,737 B2	5/2014	Diab et al.
8,353,842 B2	1/2013	Al-Ali et al.	8,718,738 B2	5/2014	Blank et al.
8,355,766 B2	1/2013	MacNeish, III et al.	8,720,249 B2	5/2014	Al-Ali
8,359,080 B2	1/2013	Diab et al.	8,721,541 B2	5/2014	Al-Ali et al.
8,364,223 B2	1/2013	Al-Ali et al.	8,721,542 B2	5/2014	Al-Ali et al.
8,364,226 B2	1/2013	Diab et al.	8,723,677 B1	5/2014	Kiani
8,374,665 B2	2/2013	Lamego	8,740,792 B1	6/2014	Kiani et al.
8,385,995 B2	2/2013	Al-Ali et al.	8,754,776 B2	6/2014	Poeze et al.
8,385,996 B2	2/2013	Smith et al.	8,755,535 B2	6/2014	Telfort et al.
8,388,353 B2	3/2013	Kiani et al.	8,755,856 B2	6/2014	Diab et al.
8,399,822 B2	3/2013	Al-Ali	8,755,872 B1	6/2014	Marinow
8,401,602 B2	3/2013	Kiani	8,761,850 B2	6/2014	Lamego
8,405,608 B2	3/2013	Al-Ali et al.	8,764,671 B2	7/2014	Kiani
8,414,499 B2	4/2013	Al-Ali et al.	8,768,423 B2	7/2014	Shakespeare et al.
8,418,524 B2	4/2013	Al-Ali	8,771,204 B2	7/2014	Telfort et al.
8,423,106 B2	4/2013	Lamego et al.	8,777,634 B2	7/2014	Kiani et al.
8,428,967 B2	4/2013	Olsen et al.	8,781,543 B2	7/2014	Diab et al.
8,430,817 B1	4/2013	Al-Ali et al.	8,781,544 B2	7/2014	Al-Ali et al.
8,437,825 B2	5/2013	Dalvi et al.	8,781,549 B2	7/2014	Al-Ali et al.
8,455,290 B2	6/2013	Siskavich	8,788,003 B2	7/2014	Schurman et al.
8,457,703 B2	6/2013	Al-Ali	8,790,268 B2	7/2014	Al-Ali
8,457,707 B2	6/2013	Kiani	8,801,613 B2	8/2014	Al-Ali et al.
8,463,349 B2	6/2013	Diab et al.	8,821,397 B2	9/2014	Al-Ali et al.
8,466,286 B2	6/2013	Bellott et al.	8,821,415 B2	9/2014	Al-Ali et al.
8,471,713 B2	6/2013	Poeze et al.	8,830,449 B1	9/2014	Lamego et al.
8,473,020 B2	6/2013	Kiani et al.	8,831,700 B2	9/2014	Schurman et al.
8,483,787 B2	7/2013	Al-Ali et al.	8,840,549 B2	9/2014	Al-Ali et al.
8,489,364 B2	7/2013	Weber et al.	8,847,740 B2	9/2014	Kiani et al.
8,498,684 B2	7/2013	Weber et al.	8,849,365 B2	9/2014	Smith et al.
8,504,128 B2	8/2013	Blank et al.	8,852,094 B2	10/2014	Al-Ali et al.
8,509,867 B2	8/2013	Workman et al.	8,852,994 B2	10/2014	Wojtczuk et al.
8,515,509 B2	8/2013	Bruinsma et al.	8,868,147 B2	10/2014	Stippick et al.
8,523,781 B2	9/2013	Al-Ali	8,868,150 B2	10/2014	Al-Ali et al.
8,529,301 B2	9/2013	Al-Ali et al.	8,870,792 B2	10/2014	Al-Ali et al.
8,532,727 B2	9/2013	Ali et al.	8,886,271 B2	11/2014	Kiani et al.
8,532,728 B2	9/2013	Diab et al.	8,888,539 B2	11/2014	Al-Ali et al.
D692,145 S	10/2013	Al-Ali et al.	8,888,708 B2	11/2014	Diab et al.
8,547,209 B2	10/2013	Kiani et al.	8,892,180 B2	11/2014	Weber et al.
8,548,548 B2	10/2013	Al-Ali	8,897,847 B2	11/2014	Al-Ali
8,548,549 B2	10/2013	Schurman et al.	8,909,310 B2	12/2014	Lamego et al.
8,548,550 B2	10/2013	Al-Ali et al.	8,911,377 B2	12/2014	Al-Ali
8,560,032 B2	10/2013	Al-Ali et al.	8,912,909 B2	12/2014	Al-Ali et al.
8,560,034 B1	10/2013	Diab et al.	8,920,317 B2	12/2014	Al-Ali et al.
8,570,167 B2	10/2013	Al-Ali	8,921,699 B2	12/2014	Al-Ali et al.
8,570,503 B2	10/2013	Vo et al.	8,922,382 B2	12/2014	Al-Ali et al.
8,571,617 B2	10/2013	Reichgott et al.	8,929,964 B2	1/2015	Al-Ali et al.
8,571,618 B1	10/2013	Lamego et al.	8,942,777 B2	1/2015	Diab et al.
8,571,619 B2	10/2013	Al-Ali et al.	8,948,834 B2	2/2015	Diab et al.
8,577,431 B2	11/2013	Lamego et al.	8,948,835 B2	2/2015	Diab
8,581,732 B2	11/2013	Al-Ali et al.	8,965,471 B2	2/2015	Lamego
8,584,345 B2	11/2013	Al-Ali et al.	8,983,564 B2	3/2015	Al-Ali
			8,989,831 B2	3/2015	Al-Ali et al.
			8,996,085 B2	3/2015	Kiani et al.
			8,998,809 B2	4/2015	Kiani
			9,028,429 B2	5/2015	Telfort et al.

(56)

References Cited

U.S. PATENT DOCUMENTS

9,037,207 B2	5/2015	Al-Ali et al.	2012/0179006 A1	7/2012	Jansen et al.
9,060,721 B2	6/2015	Reichgott et al.	2012/0209082 A1	8/2012	Al-Ali
9,066,666 B2	6/2015	Kiani	2012/0209084 A1	8/2012	Olsen et al.
9,066,680 B1	6/2015	Al-Ali et al.	2012/0227739 A1	9/2012	Kiani
9,072,474 B2	7/2015	Al-Ali et al.	2012/0283524 A1	11/2012	Kiani et al.
9,078,560 B2	7/2015	Schurman et al.	2012/0296178 A1	11/2012	Lamego et al.
9,084,569 B2	7/2015	Weber et al.	2012/0319816 A1	12/2012	Al-Ali
9,095,316 B2	8/2015	Welch et al.	2012/0330112 A1	12/2012	Lamego et al.
9,106,038 B2	8/2015	Telfort et al.	2013/0023775 A1	1/2013	Lamego et al.
9,107,625 B2	8/2015	Telfort et al.	2013/0041591 A1	2/2013	Lamego
9,107,626 B2	8/2015	Al-Ali et al.	2013/0045685 A1	2/2013	Kiani
9,113,831 B2	8/2015	Al-Ali	2013/0046204 A1	2/2013	Lamego et al.
9,113,832 B2	8/2015	Al-Ali	2013/0060147 A1	3/2013	Welch et al.
9,119,595 B2	9/2015	Lamego	2013/0096405 A1	4/2013	Garfio
9,131,881 B2	9/2015	Diab et al.	2013/0096936 A1	4/2013	Sampath et al.
9,131,882 B2	9/2015	Al-Ali et al.	2013/0109935 A1	5/2013	Al-Ali et al.
9,131,883 B2	9/2015	Al-Ali	2013/0162433 A1	6/2013	Muhsin et al.
9,131,917 B2	9/2015	Telfort et al.	2013/0190581 A1	7/2013	Al-Ali et al.
9,138,180 B1	9/2015	Coverston et al.	2013/0197328 A1	8/2013	Diab et al.
9,138,182 B2	9/2015	Al-Ali et al.	2013/0243021 A1	9/2013	Siskavich
9,138,192 B2	9/2015	Weber et al.	2013/0253334 A1	9/2013	Al-Ali et al.
9,142,117 B2	9/2015	Muhsin et al.	2013/0274571 A1	10/2013	Diab et al.
9,153,112 B1	10/2015	Kiani et al.	2013/0296672 A1	11/2013	O'Neil et al.
9,153,121 B2	10/2015	Kiani et al.	2013/0317370 A1	11/2013	Dalvi et al.
9,161,696 B2	10/2015	Al-Ali et al.	2013/0324808 A1	12/2013	Al-Ali et al.
9,161,713 B2	10/2015	Al-Ali et al.	2013/0331670 A1	12/2013	Kiani
9,167,995 B2	10/2015	Lamego et al.	2013/0338461 A1	12/2013	Lamego et al.
9,176,141 B2	11/2015	Al-Ali et al.	2014/0012100 A1	1/2014	Al-Ali et al.
9,186,102 B2	11/2015	Bruinsma et al.	2014/0025306 A1	1/2014	Weber et al.
9,192,312 B2	11/2015	Al-Ali	2014/0034353 A1	2/2014	Al-Ali et al.
9,192,329 B2	11/2015	Al-Ali	2014/0051953 A1	2/2014	Lamego et al.
9,192,351 B1	11/2015	Telfort et al.	2014/0058230 A1	2/2014	Abdul-Hafiz et al.
9,195,385 B2	11/2015	Al-Ali et al.	2014/0066783 A1	3/2014	Kiani et al.
9,211,072 B2	12/2015	Kiani	2014/0077956 A1	3/2014	Sampath et al.
9,211,095 B1	12/2015	Al-Ali	2014/0081100 A1	3/2014	Muhsin et al.
9,218,454 B2	12/2015	Kiani et al.	2014/0081175 A1	3/2014	Telfort
9,226,696 B2	1/2016	Kiani	2014/0094667 A1	4/2014	Schurman et al.
9,241,662 B2	1/2016	Al-Ali et al.	2014/0100434 A1	4/2014	Diab et al.
9,245,668 B1	1/2016	Vo et al.	2014/0114199 A1	4/2014	Lamego et al.
9,259,185 B2	2/2016	Abdul-Hafiz et al.	2014/0120564 A1	5/2014	Workman et al.
9,267,572 B2	2/2016	Barker et al.	2014/0121482 A1	5/2014	Merritt et al.
9,277,880 B2	3/2016	Poeze et al.	2014/0121483 A1	5/2014	Kiani
9,289,167 B2	3/2016	Diab et al.	2014/0127137 A1	5/2014	Bellott et al.
9,295,421 B2	3/2016	Kiani et al.	2014/0128696 A1	5/2014	Al-Ali
9,307,928 B1	4/2016	Al-Ali et al.	2014/0128699 A1	5/2014	Al-Ali et al.
9,323,894 B2	4/2016	Kiani	2014/0129702 A1	5/2014	Lamego et al.
D755,392 S	5/2016	Hwang et al.	2014/0135588 A1	5/2014	Al-Ali et al.
9,326,712 B1	5/2016	Kiani	2014/0142401 A1	5/2014	Al-Ali et al.
9,333,316 B2	5/2016	Kiani	2014/0142402 A1	5/2014	Al-Ali et al.
9,339,220 B2	5/2016	Lamego et al.	2014/0163344 A1	6/2014	Al-Ali
9,341,565 B2	5/2016	Lamego et al.	2014/0163402 A1	6/2014	Lamego et al.
2006/0074321 A1*	4/2006	Kouchi	2014/0166076 A1	6/2014	Kiani et al.
		A61B 5/044	2014/0171763 A1	6/2014	Diab
		600/481	2014/0180038 A1	6/2014	Kiani
2009/0043446 A1	2/2009	Drew et al.	2014/0180154 A1	6/2014	Sierra et al.
2009/0046096 A1*	2/2009	Rampersad	2014/0194709 A1	7/2014	Al-Ali et al.
		G06F 19/3406	2014/0194711 A1	7/2014	Al-Ali
		345/419	2014/0194766 A1	7/2014	Al-Ali et al.
2009/0054743 A1*	2/2009	Stewart	2014/0206963 A1	7/2014	Al-Ali
		G06T 11/206	2014/0213864 A1	7/2014	Abdul-Hafiz et al.
		600/301	2014/0243627 A1	8/2014	Diab et al.
2009/0171167 A1*	7/2009	Baker, Jr.	2014/0266790 A1	9/2014	Al-Ali et al.
		A61B 5/0002	2014/0275808 A1	9/2014	Poeze et al.
		600/301	2014/0275835 A1	9/2014	Lamego et al.
2009/0247984 A1	10/2009	Lamego et al.	2014/0275871 A1	9/2014	Lamego et al.
2009/0275844 A1	11/2009	Al-Ali	2014/0275872 A1	9/2014	Merritt et al.
2010/0004518 A1	1/2010	Vo et al.	2014/0275881 A1	9/2014	Lamego et al.
2010/0030040 A1	2/2010	Poeze et al.	2014/0288400 A1	9/2014	Diab et al.
2010/0261979 A1	10/2010	Kiani	2014/0296664 A1	10/2014	Bruinsma et al.
2011/0001605 A1	1/2011	Kiani et al.	2014/0303520 A1	10/2014	Telfort et al.
2011/0082711 A1	4/2011	Poeze et al.	2014/0309506 A1	10/2014	Lamego et al.
2011/0105854 A1	5/2011	Kiani et al.	2014/0316228 A1	10/2014	Blank et al.
2011/0208015 A1	8/2011	Welch et al.	2014/0323825 A1	10/2014	Al-Ali et al.
2011/0213212 A1	9/2011	Al-Ali	2014/0330092 A1	11/2014	Al-Ali et al.
2011/0227927 A1	9/2011	Garmon et al.			
2011/0230733 A1	9/2011	Al-Ali			
2011/0237911 A1	9/2011	Lamego et al.			
2012/0059267 A1	3/2012	Lamego et al.			
2012/0116175 A1	5/2012	Al-Ali et al.			

(56)

References Cited

U.S. PATENT DOCUMENTS

2014/0330098 A1 11/2014 Merritt et al.
2014/0330099 A1 11/2014 Al-Ali et al.

2014/0333440 A1 11/2014 Kiani
2014/0336481 A1 11/2014 Shakespeare et al.
2014/0343436 A1 11/2014 Kiani
2015/0018650 A1 1/2015 Al-Ali et al.

* cited by examiner




FIG. 1




FIG. 2




FIG. 3




FIG. 4




FIG. 5

CONFIGURABLE PATIENT MONITORING SYSTEM

CROSS-REFERENCE TO RELATED APPLICATIONS

This application claims priority to U.S. Application No. 61/597,140, filed Feb. 9, 2012, titled PATIENT MONITOR, the entire contents of which are incorporated by reference herein and made a part of this specification.

BACKGROUND

1. Field of the Invention

The present disclosure relates to the field of patient monitoring systems.

2. Description of the Related Art

Patient monitoring systems are used to track and monitor the health and wellness of a patient. A patient's health can be monitored using physiological sensors to record and process a patient's vital signs, such as, pulse rate, temperature, glucose level, and other physiological parameters. A medical practitioner can use this information to track the health of a patient. Each patient has different physiological characteristics, such as gender, age, weight, height, fitness, medical history, and other characteristics, which can affect the range of signals that are considered healthy for each person. For example, the normal resting heart rate for an athlete may be close to fifty beats per minute, whereas for another adult, the normal resting heart rate may be closer to one hundred beats per minute. As such it can be difficult for medical practitioners to quickly evaluate the health of the patient without consulting additional information prior to analyzing the patient's physiological signals, which can be a time consuming process. In some cases, a patient's physiological signals may appear healthy, even though the patient is in need of medical attention. Additional, typical sensors only display the current value for a patient's physiological sensors, which can make it difficult for a medical practitioner to identify trends in the patient's health.

SUMMARY

Patient monitoring systems can help health practitioners to quickly evaluate a patient's state of health and wellness by providing health indicators that help differentiate between healthy and unhealthy signals. Indicators that are easy to see and understand quickly are critical in the patient care industry. Even more important are indicators that can be readily understood by less educated care providers and by those that speak and/or read a different language than the device displays. In some embodiments of this disclosure, customized health indicators can be configured to account for a patient's specific physiological parameters, including medical history, current medications, and other health considerations. These customizations can assist in the quick recognition of potential problems by the less educated and foreign language observers. In some embodiments, the health indicators can be configured to show the signal over a period of time, which can help a medical practitioner identify how the patient's health is trending.

In one embodiment, a patient monitoring system has a first physiological sensor that is configured to measure at least one physiological signal from a patient. A health indicator is configured to display a signal value based on the output of at least one physiological signal. The patient monitoring system is configured to receive patient informa-

tion and calculate a first range of values and a second range of values for the health indicator. The first range of values corresponds to a first range of physiological signals from the patient and to a healthy patient condition. The second range of values corresponds to a second range of physiological signals from the patient and to an unhealthy patient condition. In some embodiments the calculated ranges can be based at least in part on patient information. The patient monitoring system also has a user interface configured to display the health indicator. The health indicator is configured to display a first output when the signal value is within the first range of values and the health indicator is configured to display a second output when the signal value is within the second range of values.

In some embodiments the patient monitoring system is further configured to calculate a third range of values for the health indicator. The third range of values corresponds to a third range of physiological signals from the patient and corresponds to an intermediate patient condition. In some embodiments, the first, second, and the third ranges of values can overlap.

In some embodiments the health indicator is configured to output an alarm signal when the signal value moves from the first range of values to the second range of values. The alarm signal can be an audible alarm, an electronic message, a visual alarm, or other type of alert system. The patient monitoring system can be configured to communicate with remote devices.

In some embodiments, the first output can be a first color displayed on the health indicator. The second output can be a second color displayed on the health indicator. The first output and the second output can both be displayed when the signal value is in the second range of values.

In some embodiments, the patient information can be age, gender, medical history, or other information about the patient. The health indicator can be number of different indicators such as, a circular indicator, a vertical bar indicator, a trend graph indicator, a Gaussian trend indicator, combinations of the one or more indicators, or other types of indicator. The signal value can be a point on a trend graph, a numeric value, an analog indicator, or other type of representation of the physiological signal value. The physiological sensor can be configured to measure glucose, blood pressure, pulse rate, respiration rate, oxygen saturation, total hemoglobin, carboxyhemoglobin, methemoglobin, perfusion index, temperature, or other physiological parameter. The physiological sensor can be a pulse oximeter, a heart rate monitor, respiratory monitor (e.g., an acoustic monitor), a thermometer, or other physiological sensor.

An embodiment of a method of monitoring a patient has the steps of measuring at least one physiological signal from a patient using a physiological sensor, providing a first health indicator having a signal value based upon the at least one physiological signal, receiving patient information, and calculating a first range of values for the health indicator. The first range of values corresponds to a first range of physiological signals from the patient and to a first patient condition. The method also includes calculating a second range of values for the health indicator. The second range of values corresponds to a second range of physiological signals from the patient and to a second patient condition. The method also includes displaying the first health indicator on a user interface. The first range of values and the second range of values are displayed on the first health indicator. The method also includes displaying the signal value on the first health indicator, displaying a first output on the health indicator when the first value is within the first

range of values, and displaying a second output on the health indicator when the second value is within the second range of values.

In some embodiments the method includes the step of displaying a threshold indicator separating the first range of values from the second range of values.

BRIEF DESCRIPTION OF THE DRAWINGS

FIG. 1 is an embodiment of a user interface showing a plurality of health indicators.

FIG. 2 is another embodiment of a configuration of user interface showing a plurality of health indicators.

FIG. 3 is another embodiment of a configuration of a user interface showing a plurality of health indicators.

FIG. 4 is another embodiment of a user interface showing a plurality of health indicators.

FIG. 5 illustrates an embodiment of an exemplary handheld monitor having a display and an exemplary noninvasive optical sensor of a patient monitoring system.

DETAILED DESCRIPTION

A patient monitoring system can display one or more of a patient's physiological parameters using one or more configurable health indicators on a configurable user interface. Each health indicators can display one or more physiological parameters of the patient. The health indicators can be configured to be easy to read and interpret. The health indicators can include one or more thresholds that can help medical practitioners to evaluate the health and wellness of a patient. The patient monitoring system can display health indicators for a patient's physiological parameters, including heart rate, respiration rate, oxygen saturation (SpO₂, % SpO₂), temperature, blood pressure, total hemoglobin (SpHb), perfusion index (PI), carboxyhemoglobin (SpCO), methemoglobin, and other physiological parameters. The physiological signals displayed in each health indicator can be represented by one or more analog indicators and/or one or more digital indicators. The health indicators can be a variety of types including a trend graphs, Gaussian trend graphs, circle indicators, arc indicators, bar indicators, line indicators, and/or other types of indicators. In some embodiments, a health indicator can combine one or more physiological parameters as part of a single health indicator. The displayed values for the health indicators can be derived from sensor signals taken from a patient. For example, pulse rate, blood pressure, and respiration rate can be normalized and combined to determine an overall health indicator. Physiological sensors capable of reading physiological signals are available from healthcare products manufacturers, such as Masimo Corporation located of Irvine, Calif. An example of a physiological sensor and patient monitor is illustrated in FIG. 5.

A user interface of the patient monitoring system can be configured to display the health indicators. The user interfaces can be customized for each patient. The user interface of the patient monitoring system can provide a centralized display of a patient's health and wellness information. In some embodiments, the patient monitoring system can be configured to display all of and the information associated with the patient on a single display console. In some embodiments the user interface can be displayed on a plurality of display consoles. Each screen of the user interface can be configured to display one or more health indicators and other information associated with the patient.

In some embodiments the health indicators can be configured to be displayed on a handheld display or handheld patient monitor.

The user interface is configurable and can be configured individually for each patient. A user can configure the user interface. In some embodiments the patient monitoring system can configure the user interface. In some embodiments, the user interface can be generated automatically based on the physiological sensors connected to the patient monitoring system. In some embodiments, the user interface can be configured using a template and/or preconfigured health indicators. Preconfigured user interfaces and health indicators can be further configured and adjusted by the user. The health indicators may include both analog and digital indicators. The analog and digital indicators can be positioned in any number of formations, such as side-by-side, above, below, transposed, etc. The number, type, and arrangement of the health indicators displayed can be determined by various factors, including, the number of physiological sensors, the type of physiological sensors, the settings of the user interface, the hardware configuration, the software configuration, and other factors. Embodiments of user interfaces are illustrated in FIGS. 1 through 4.

Analog and digital indicators can display measurements of physiological parameters. The indicators can indicate an actual level or a normalized level. The user interfaces can also display information, such as network connection status, network connection strength, network type, power levels, battery power, time, patient identifying information, health provider information, sensor signal confidence levels, sensor placement, and other information.

In some embodiments a user interface can be configured to display health indicators for each physiological sensor connected to a patient. In some embodiments, a plurality of user interface screens can be configured to display a patient's health information. The user interface screens can be displayed on one or more display consoles. The patient monitoring system can be configured to transfer the signal information to a remote source over a network. In some embodiments the user interface information can be displayed and formatted for viewing on portable computing device, such as a laptop computer, a mobile phone, a tablet computer, and/or other computing device.

FIGS. 1 through 4 illustrate embodiments of configurable user interfaces. FIG. 1 is an embodiment of user interface 100 displaying a plurality of analog and digital health indicators. The user interface 100 includes health indicators for heart rate 10a, respiration rate 10b, oxygen saturation (SpO₂) 10c, temperature 30a, blood pressure 30b, glucose 50a, total hemoglobin (SpHb) 50b, ECG 50c, and respiration rate (RRa) 50d. The user interface 100 also includes sensor confidence 60, and sensor placement 70 indicators.

The user interface 100 has three circular health indicators for heart rate 10a, respiration rate 10b and oxygen saturation (SpO₂) 10c. The circular health indicators have shaped blocks 12 arranged circumferentially around the circular indicator. The blocks 12 increase in size from smaller to larger about the circle. The blocks 12 can illuminate as the value of the measured physiological parameter increases. In some embodiments the blocks display a muted color for each block 12 when the block 12 is not illuminated, such as in indicators 10a and 10c. In some embodiments, the blocks 12 can be clear or display a background color when not illuminated, as in 10b. In some embodiments an arrow or other measurement indicator can point to a specific value on the indicator.

A color pattern **14** can be associated with the blocks **12**. The color pattern **14** can be configured to indicate patient wellness. The colors of the blocks **12** can help medical practitioners to quickly and easily determine the current status of the physiological parameter. In one embodiment, green can indicate a healthy or normal condition, yellow can indicate deteriorating conditions, and red can indicate critical or severe conditions. In some embodiments, other colors can be used to indicate patient wellness. In some embodiments the blocks **12** can gradually change color around the entire circle moving through blue, green, yellow, orange and, and red, where each block **12** can have one or more colors, as illustrated by patterns **14** on the heart rate indicator **10a**. In some embodiment each block **12** can have a discrete color, as illustrated by the color patterns **14** on indicator **10c**. In some embodiments, red can be used to indicate that a value is too high or too low. In some embodiments, other colors can be used to indicate when the measurements are too low or too high.

In some embodiments, a numeric indicator **16** can be displayed within the circular indicator **10a-c**. A measurement unit, such as BPM, can be associated with the numeric indicator. The numeric value **16** indicates the current measurement of the physiological sensor. In some embodiments the numeric value **16** can be colored to match the color of the associated blocks **12**. In some embodiments the numeric value can be colored to match a color typically associated with the physiological parameter. In some embodiments, the circular indicators **10a-c** can include time based data **24**, such as a respiration auditory waveform or a plethysmograph. The time based data **24** can display the measured signal over a period of time and/or a specific number of measurements.

In some embodiments, the circular indicators **10a-c** can include dial indicators **20**. The numbers of the dial **20** can move past a stationary pointer **22**, such as an arrow. The pointer **22** indicates the current measurement of the physiological sensors, similar to numeric value **16**. The dial **20** can scroll up and down to indicate the current value. In some embodiments the pointer **22** can move up and down to indicate the current measurement. In some embodiments the numbers of the dial **20** and/or the arrow **22** may be colored to indicate the level of patient wellness, similar to blocks **12**.

The user interface **100** has vertical bar indicators, temperature **30a** and blood pressure **30b**. The bar indicators **30a-b** have a plurality of bars **32**, descriptors **34**, a measurement indicator **36**, and a measured value **38**. The bars **32** can have a color pattern **14**. In some embodiments, the bars **32** can be implemented as dots, dashes, arrow, rectangles, squares, or the like. The indicators **30a-b** can have descriptors **34**, such as numbers, words, or symbols relating to the measured condition. The measurement pointer **36** can move up and down along the vertical scale to indicate the current measurement of the physiological sensors. In some embodiments, the bars can scroll through the values and the pointer **36** can remain stationary. The pointer **36** can be implemented using other shapes such as an arrow, circle, star, line or other shape. A measured value **38** can be associated with the pointer **36**. The indicator **36** and/or the measured value **38** can be colored to indicate the level of patient wellness. In some embodiments the bars and/or descriptors can illuminate or flash based on the occurrence of an event, such as an alarm.

The temperature indicator **30a**, in this embodiment, has numeric descriptors **34** with an arrow-shaped pointer **36**. The pointer **36** moves up and down the bars **32** to indicate

the current temperature value. The measured value **38** shows a numeric value for the current measurement of the patient's temperature.

The blood pressure indicator **30b**, in this embodiment, has a plurality of bars **32**, with each bar **32** associated with a text descriptor **34**. The descriptors **34** indicate conditions relating to blood pressure measurements, including stages of hypertension. The pointer **36** is a block arrow with a value **38** showing the current blood pressure measurement. Each bar **32** has an associated range of measurement values. The pointer **36** moves discretely between bars. The pointer **36** only moves between bars **32** when an upper or lower threshold has been surpassed.

The user interface **100** also includes sensor information, such as sensor confidence indicators **60** and sensor placement indicators **70**. The sensor confidence indicator **60** can display the strength and integrity of the sensor signal. In this embodiment the sensor confidence indicator is a vertical bar chart with bars illustrating the relative strength of the sensor signals. In some embodiments the indicator can be color coded. In some embodiments there can be a sensor confidence indicator for each sensor. Sensor confidence indicators can be used to provide information for any of the sensors used by the patient monitoring system.

The sensor placement indicator **70** shows the relative placement of each sensor on the patient. The sensor placement indicator shows an illustration of the patient with the positioning of each sensors connected to the patient. The illustration can change to match the characteristics of the actual patient (e.g., man, woman, child, elderly, etc.). The indicator can display the recommended or expected placement of the sensor on the patient. In some embodiments, the sensor placement indicator can show the actual position of the sensor(s) on the patient.

The user interface **100** also includes trend graphs to show physiological parameter measurements over time, such as glucose **50a**, total hemoglobin (SpHb) **50b**, ECG, **50c**, and respiration rate (RRa) **50d**. The trend indicators can help to identify trends in a patient's health, such as when a patient is moving from a healthy condition toward an unhealthy condition. Trends in the patient's measurements can be shown by displaying physiological measurements over a period of time. Trend graph **50a** includes a vertical axis **52**, a horizontal axis **54**, a measurement indicator **56**, and threshold levels **58**. The trend graph **50a** shows measurements of the physiological parameters over a defined time period. The vertical axis **52** indicates the magnitude of the measurement and the horizontal axis **54** indicates time. In some embodiments the vertical and horizontal axes may not have values displayed. In some embodiments, the current value of the physiological parameter can be displayed on the upper right side of the trend graph.

The measurements can show discrete measurements with continuous measurements in real-time. In some embodiments, the measurement indicator **56** can be used to provide additional information about the measurement data. For example, a circle indicator **56a** can indicate discrete non-invasive measurements and a triangle indicator **56b** can indicate a discrete invasive measurement. Other shapes, such as a flag indicator **56c**, can be used to show other conditions and/or measurements. In some embodiments, an indicator **56** can be used to show when a measurement has exceeded an upper or lower threshold. The type of measurement indicator **56** can be used to indicate a severe or critical condition based on multiple measurements from different physiological parameters. For discrete measurements, connecting lines, such as a dashed line, may be added between

measurements to better visualize the trends of the measurements. For real-time or continuous measurements the information can be shown as a solid line. In some embodiments, the most recent or current value may be displayed above the graph. Threshold levels **58** may be shown on the trend graph. The threshold levels **58** can indicate upper and/or lower thresholds, such as in **50a**, **50b**, and **50d**. The threshold levels **58** may be accompanied by threshold descriptors, as illustrated by the trend graph **150** in FIG. 3. Trend graphs **50b-d** have the same characteristics as those described in association with trend graph **50a**.

The trend graph **50a-d** may be scaled and shaped as appropriate to fit within a user interface. The trend graph **50a-d** may be interchangeable. The larger trend graph **50a** can be replaced with one of smaller trend graphs **50b-c**. The larger trend graph **50a** can be minimized and exchanged with one of the smaller trend graphs **50b-d**. In some embodiment the trend graphs can change position based on the occurrence of an event. For example, in if an alarm is triggered in one of the trend graphs **50b-d**, trend graph **50a** could be replaced with the alarming parameter by the patient monitoring system.

The health indicators illustrated in the user interface **100** can have ranges and thresholds to help evaluate the health and wellness of the patient. A range can have one or more thresholds. Some physiological parameters may have upper thresholds and lower thresholds, while other parameters may only have an upper threshold or a lower threshold. The thresholds can be useful in tracking and monitoring a patient's health. Some physiological parameters can have a single threshold to determine whether the patient is in a healthy or unhealthy range. Some physiological parameters can have a plurality of thresholds that can be used to help evaluate the state of health of the patient. For example, a blood pressure measurement can identify different stages of hypertension, as illustrated in indicator **30b**. The ranges and thresholds can be adjusted based on the physiological parameter being monitored. For example, a SpO2 health indicator, such as **10b**, can have only a lower threshold, whereas a heart rate indicator, such as **10a**, can have both an upper and a lower threshold.

The ranges and thresholds for each physiological parameter can be based on typical or expected values for a patient. The ranges and thresholds can be based on gender, age, height, weight, and other patient data. For example, females can have different ranges and thresholds than males. In some embodiments, a medical practitioner can determine ranges and thresholds for each parameter. In some embodiments, the patient monitoring system can determine the ranges and thresholds based at least in part on patient information provided to the system. A user can provide the system with information about the patient, such as gender, age, height, weight, medical history, and the like. The system can analyze the information and determine appropriate ranges and thresholds for the patient. In some embodiments, the ranges and thresholds can be determined by referencing one or more predefined look-up tables. In some embodiments, the ranges and thresholds can be calculated using one or more algorithms. In some embodiments the user can modify the ranges and thresholds after the system has completed a determination of the ranges and thresholds.

When a threshold is met or exceeded, the system may be programmed to trigger an event. The event may be an alarm, an on-screen notification, an audible alarm, an electronic message sent to a health practitioner, or other user-specified event. In some embodiments, the user interface can change to indicate that an event has been triggered. For example, the

indicators can change color, the indicator can flash, the indicator can increase in size, the indicator can switch to a different position on the display, or other change to the user interface to indicate that an event has been triggered. In some embodiments the triggered indicator can replace another more prominent indicator on the display

The health indicators can display the range and threshold information in a number of ways. The indicators can have marks, text, or other indication on the health indicator that identifies threshold. Other descriptors or annotations can be placed on the health indicators to identify ranges and or thresholds, which could be based on gender, age, or other information about the patient. The indicators can have numeric values associated with the descriptors. In some embodiments, no numeric values are associated with the indicators, such as the indicator **450** in FIG. 4. The indicators can have descriptors that indicate maximum and minimum thresholds for the physiological parameter, such as descriptors **422**, described in association with FIG. 4, showing minimum and maximums for males and females, or thresholds **58** in trend graph **50a**. A practitioner can use the ranges and thresholds to assess the severity of the physiological parameter levels.

In some embodiments, the ranges can be identified by color patterns, and the thresholds are identified by changes to the color pattern. This can aid the less educated or foreign language speakers to identify problems quickly. The color of the health indicator bars can indicate patient condition, such as normal, deteriorating, severe, and critical. For example, green can indicate a normal physiological signal, yellow can indicate a deteriorating condition, orange can indicate a severe condition, and red can indicate a critical condition. A health practitioner can quickly assess a patient's health by evaluating the color of each health indicator. This can be particularly helpful for when a health practitioner sees a new or unfamiliar patient. The patient monitoring system can use ranges and thresholds in all of the indicators.

FIG. 2 illustrates another configuration of the health indicators illustrated in FIG. 1.

FIG. 3 is another embodiment of a configuration of a user interface **300** that shows a plurality of health indicators for heart rate **10a**, respiration rate **10b**, temperature **30a**, blood pressure **30b**, glucose **150**, ECG **50c**, and respiration rate (RRa) **50d**, oxygen saturation (% SpO2) **80a**, perfusion index (PI) **80b**, total hemoglobin (SpHb) **80c**, carboxyhemoglobin (SpCO) **80d**, and bar indicators **90**. The heart rate **10a**, respiration rate **10b**, temperature **30a**, blood pressure **30b**, indicators are substantially the same as the indicators described in association with FIG. 1. In this embodiment of the user interface **300**, the indicators have been positioned and sized differently than those in FIG. 1.

The user interface **300** illustrates another embodiment of a trend chart **150**. The trend chart **150** is substantially similar to the trend chart **50a**. The trend chart **150** has upper and lower thresholds forming three regions, identified by descriptors on the left side of the chart. Measurement values above the upper threshold are "High," measurement values below the lower threshold are "Low," and measurement values between the upper and lower thresholds are "Safe." In this embodiment the current measurement value is displayed by the lines on the trend graph and not by a numerical indicator.

The user interface **300** illustrates another embodiment of a vertical bar indicator **90**. The measurement value is illustrated by the height of the indicator **90**. The width of the indicators **90** can indicate the amount of data being used and the upper and lower bounds next to the indicators **90** can

indicate specific measurement values. In some embodiments, the indicator can change color to indicate the criticality of the measurement value. For example the indicator can be red if the value exceeds a threshold.

The user interface **300** also includes digital indicators for oxygen saturation (% SpO₂) **80a**, perfusion index (PI) **80b**, total hemoglobin (SpHb) **80c**, and carboxyhemoglobin (SpCO) **80d**. The indicators **80a-d** display the current values of the various physiological parameters. The indicator **80a** is larger than the other indicators **80b-d**. The indicators can be configured to position the indicator that is most critical in the position of indicator **80a**. The measured value can be colored to indicate the level of patient wellness. In some embodiments the indicators can illuminate or flash based on the occurrence of an event, such as an alarm.

FIG. 4 illustrates another embodiment of a user interface **400**. The user interface **400** shows a plurality of health indicators, including total hemoglobin (SpHb), circular indicator **410a** and Gaussian indicator **450**, oxygen saturation (SpO₂) **410b**, heart rate (PR) **410c**, and perfusion index (PI) **410d**. The user interface **400** also includes network information **430**, power, battery power **432**, time **434**, patient site information **436**, and additional program specific commands **440a-d**.

The user interface **400** illustrates another embodiment of circular indicators **410a-d**. The circular indicators **410a-d** have a gauge **412** arranged circumferentially about a numeric value **416**. In this embodiment, a quarter of the indicator is used to display the name and units of the physiological parameter and $\frac{3}{4}$ of the indicator is the gauge **412**. The gauge **412** can illuminate to correspond to the current sensor measurement. The gauge can include one or more blocks, as illustrated in **410a-c**. The circular indicator **410a** can have a measurement pointer **420** that identifies the current measurement. In some embodiments the gauge **412** has a color pattern associated with the health indicator reading.

The circular indicators **410a-d** can have one or more reference points **418** at specific positions about the indicator. The reference points **418** can be lines, points, or other indicators that can indicate ranges and thresholds of the physiological parameter. In some embodiments, no values are displayed on the gauge, such as **410d**. In some embodiments, reference point **418** can have numeric values, such as indicators **410a-c**.

The indicators can have descriptors or reference information **422** on or about the gauge **412**. The descriptors **422** can indicate wellness thresholds or other information related to the health indicator. The health indicator **410a** has descriptors **422** showing ranges for male and female patients. In some embodiments, the descriptors **422** can illustrate ranges for other classifications such as age (e.g., children, elderly, etc.), fitness level (e.g., athlete), or other classification. In some embodiments the descriptors **422** can indicate a maximum threshold and/or a minimum threshold.

The circular indicators **410a-d** may be interchangeable. The larger indicator **410a** can be replaced with one of smaller indicators **410b-d**. The larger indicator **410a** can be reduced in size and the other indicator can be increased in size. In some embodiments the indicator **450** can also be replaced when the indicator **410a** is replaced. In some embodiment the indicators **410a-d** can change position based on the occurrence of an event. For example, if an alarm is triggered in one of the indicators **410b-d**, indicator **410a** could be replaced with the alarming parameter by the patient monitoring system.

In some embodiments the indicators **410a-d** can illustrate trends based on the color and intensity of the gauge **412**. In one embodiment the highest intensity portion of the gauge **412** can indicate the most recent measurement with the intensity reducing for previous measurements. The intensity can be varied by the luminescence and/or the shade of color of the gauge **412**. The intensity can be varied based on time or the number of measurements. For example, an indicator may be configured to show the last four measurements, with each measurement having a different intensity. In another example, the indicator may show measurements over the previous hour with a representative measurement shown for every ten minute period having a different intensity. In some embodiments the intensity can be increased to show which value has the most measurements, similar to a Gaussian trend. In some embodiments the indicator can have discrete intensity levels and/or colors that indicate timing of the measurements. For example the indicator **410c** has three blocks that can represent different intensities and/or colors. In some embodiments the gauge can use the color associated with the severity of the measurement, for example if the measurement is a healthy measurement, that portion of the gauge can be a shade of green, whereas if it is an unhealthy measurement, that portion of the gauge can be a shade of red.

The user interface **400** also includes the indicator **450** configured to illustrate a distribution of measurements over a period of time, such as a Gaussian trend. The Gaussian trend indicator can have descriptors **452**, an indicator **454**, a distribution graph **456**. The indicator **454** can indicate the current measurement. The distribution graph **456** indicates the amount of time spent at each measurement relative to other measurements. The distribution graph can be updated with each measurement. In some embodiments, the distribution graph can calculate the distribution for an indefinite period of time. In some embodiments the distribution can be a rolling window of time that only monitors distribution for a set amount of time going backwards. For example, the distribution graph **456** could show the distribution of measurements for 30 minutes, one hour, 6 hours, 24 hours or any appropriate length of time. An example of a Gaussian trend graph **460** being used in conjunction with a circular indicator is illustrated in indicator **410d**. An embodiment of a time distribution graph, such as a Gaussian trend, can be used in conjunction with all indicators and parameters discussed herein.

The user interface **400** also includes exemplary program specific commands **440a-d**. In this embodiment, the program specific commands include paging a medical practitioner **440a**, sending the user interface information via electronic messaging **440b**, printing **440c**, and exiting out of the interface **440d**.

FIG. 5 illustrates an embodiment of a patient monitoring system **500**. In the depicted embodiment, the patient monitoring system **500** includes a display **520** and a monitoring device **500**, which includes a finger clip sensor **501** connected to a monitor **509** via a cable **512**. The patient monitoring system display **520** is configured to display a user interface **522**, such as one of the user interfaces described in association with FIGS. 1-4.

In the embodiment shown, the monitor **509** includes a display **510**. The monitor **509** can advantageously include electronic processing, signal processing, and data storage devices capable of receiving signal data from said sensor **501**, processing the signal data to determine one or more output measurement values indicative of one or more physiological parameters of a monitored patient, and displaying

the measurement values, trends of the measurement values, combinations of measurement values, and the like.

The monitor 509 can also include other components, such as a speaker, power button, removable storage or memory (e.g., a flash card slot), an AC power port, one or more control buttons 508 and one or more network interfaces, such as a universal serial bus interface or an Ethernet port. The display 510 can have a user interface displaying one or more health indicators, such as the indicators described herein. The cable 512 connecting the sensor 501 and the monitor 509 can be implemented using one or more wires, optical fiber, flex circuits, or the like.

The embodiments set forth above are illustrative of inventive principles and features, and these principles may be applied to patient monitoring systems that have different user interfaces or health indicators that do not match the embodiments of the patient monitoring system illustrated in the Figures. For example, the user interfaces may have different or additional health indicators. The health indicators may have different sizes and shapes, or different color patterns. As such, the principles and features discussed herein can be applied in embodiments of various shapes, sizes and configurations.

Although this invention has been disclosed in the context of certain preferred embodiments and examples, it will be understood by those skilled in the art that the present invention extends beyond the specifically disclosed embodiments to other alternative embodiments and/or uses of the invention and obvious modifications and equivalents thereof. In addition, while a number of variations of the invention have been shown and described in detail, other modifications, which are within the scope of this invention, will be readily apparent to those of skill in the art based upon this disclosure. Accordingly, Applicants contemplate that various features and aspects of the disclosed embodiments can be combined with or substituted for one another in order to form varying modes of the disclosed invention. Thus, it is intended that the scope of the present invention herein disclosed should not be limited by the particular disclosed embodiments described above, but should be determined only by a fair reading of the claims that follow.

What is claimed is:

1. A patient monitoring system, comprising:
 - at least one physiological sensor including a first and second light emitter and a detector, wherein the physiological sensor is configured to measure at least one physiological signal from a patient;
 - a user interface configured to display at least one circular health indicator, the at least one circular health indicator comprising;
 - a plurality of indicator elements disposed circumferentially around at least a portion of the circular health indicator, wherein the plurality of indicator elements display visual indications based, at least in part, on the at least one physiological signal;
 - a numeric indicator disposed within the circular health indicator, wherein the numeric indicator displays a signal value based, at least in part, on the at least one physiological signal; and
 - a processor comprising computer-executable instructions that when executed cause the processor to:
 - receive patient information;
 - calculate a first range of values for the at least one circular health indicator based at least in part on the patient information, wherein the first range of values corresponds to a first range of physiological signals

from the patient, wherein the first range of values corresponds to a first patient condition;

calculate a second range of values for the at least one circular health indicator based at least in part on the patient information, wherein the second range of values corresponds to a second range of physiological signals from the patient, wherein the second range of values corresponds to an second patient condition; and

wherein the at least one circular health indicator is configured to display a first output when the signal value is within the first range of values; and

wherein the at least one circular health indicator is configured to display a second output when the signal value is within the second range of values.

2. The patient monitoring system of claim 1, wherein the first patient condition is a healthy condition.

3. The patient monitoring system of claim 1, wherein the first patient condition is an unhealthy condition.

4. The patient monitoring system of claim 1, wherein the patient monitoring system is further configured to calculate a third range of values for the health indicator, wherein the third range of values corresponds to a third range of physiological signals from the patient, wherein the third range of values corresponds to an intermediate patient condition.

5. The patient monitoring system of claim 4, wherein the first range of values, the second range of values, and the third range of values do not overlap.

6. The patient monitoring system of claim 1, wherein the first output is a first color displayed on the health indicator and the second output is a second color displayed on the health indicator.

7. The patient monitoring system of claim 1, wherein the first output and the second output are both displayed when the signal value is in the second range of values.

8. The patient monitoring system of claim 1, wherein the patient monitoring system is configured to communicate the signal value with a mobile device.

9. The patient monitoring system of claim 1, wherein the patient information is at least one of age, gender, height, or weight.

10. The patient monitoring system of claim 1, wherein the patient information is based at least in part on the medical history of the patient.

11. The patient monitoring system of claim 1, wherein the user interface is further configured to display the signal value as an analog indicator.

12. The patient monitoring system of claim 1, wherein the at least one physiological sensor is configured to measure glucose, blood pressure, pulse rate, respiration rate, oxygen saturation, total hemoglobin, carboxyhemoglobin, methemoglobin, perfusion index, or temperature.

13. The patient monitoring system of claim 1, wherein the physiological sensor is a pulse oximeter.

14. A method of monitoring a patient, comprising;

- by a patient monitoring system comprising hardware processor,
- receiving patient information;
- outputting instructions to display at least one circular health indicator, the at least one health indicator comprising;

a plurality of indicator elements disposed circumferentially around at least a portion of the circular health indicator, wherein the plurality of indicator elements display visual indications based, at least in part, on the at least one physiological signal; and

13

a numeric indicator disposed within the circular health indicator, wherein the numeric indicator displays a signal value based, at least in part, on the at least one physiological signal;

calculating a first range of values for the at least one circular health indicator, wherein the first range of values corresponds to a first range of physiological signals from the patient, wherein the first range of values corresponds to a healthy patient condition;

calculating a second range of values for the at least one circular health indicator, wherein the second range of values corresponds to a second range of physiological signals from the patient, wherein the second range of values corresponds to a an unhealthy patient condition; and

measuring at least one physiological signal from a patient using a physiological sensor having a first and second light emitter and a detector;

displaying the signal value on the at least one circular health indicator;

displaying a first output on the at least one circular health indicator when the first value is within the first range of values; and

displaying a second output on the at least one circular health indicator when the second value is within the second range of values.

15. The method of claim 14, further comprising the step of displaying a threshold indicator separating the first range of values from the second range of values.

16. The method of claim 14, wherein the physiological signal value provides a measurement of at least one of: glucose, blood pressure, pulse rate, respiration rate, oxygen saturation, total hemoglobin, carboxyhemoglobin, methemoglobin, perfusion index, or temperature.

17. The patient monitoring system of claim 14, wherein the patient information is at least one of age, gender, height, or weight.

18. A patient monitoring system, comprising:
 at least one physiological sensor including a first and second light emitter and a detector, wherein the physiological sensor is configured to measure at least one physiological signal from a patient;

a user interface configured to display at least one circular health indicator, the at least one circular health indicator comprising:
 a plurality of indicator elements disposed circumferentially around at least a portion of the circular health indicator, wherein the plurality of indicator elements display visual indications based, at least in part, on the at least one physiological signal;

14

a numeric indicator disposed within the circular health indicator, wherein the numeric indicator displays a signal value based, at least in part, on the at least one physiological signal; and

a dial indicator comprising a stationary indicator and a plurality of numeric elements, wherein the plurality of numeric elements move relative to the stationary indicator to indicate the signal value based, at least in part, on the at least one physiological signal; and

a processor comprising computer-executable instructions that when executed cause the processor to:
 calculate a first range of values for the circular health indicator based at least in part on the patient information, wherein the first range of values corresponds to a first range of physiological signals from the patient, wherein the first range of values corresponds to a first patient condition;

calculate a second range of values for the circular health indicator based at least in part on the patient information, wherein the second range of values corresponds to a second range of physiological signals from the patient, wherein the second range of values corresponds to an second patient condition; and

wherein a first set of one or more indicator elements of the plurality of indicator elements are configured to display a first visual indication when the signal value is within the first range of values; and

wherein a second set of one or more indicator elements of the plurality of indicator elements are configured to display a second visual indication when the signal value is within the second range of values.

19. The patient monitoring system of claim 18, wherein the first patient condition is a healthy condition and the second patient condition is an unhealthy condition.

20. The patient monitoring system of claim 18, wherein the first visual indication is a first color displayed on the first set of one or more indicator elements and the second visual indication is a second color displayed on the second set of one or more indicator elements.

21. The patient monitoring system of claim 18, wherein the first visual indication and the second visual indication are both displayed when the signal value is in the second range of values.

22. The patient monitoring system of claim 18, wherein the first set of one or more indicator elements are different indicator elements than the second set of one or more indicator elements.

* * * * *

UNITED STATES PATENT AND TRADEMARK OFFICE
CERTIFICATE OF CORRECTION

PATENT NO. : 9,480,435 B2
APPLICATION NO. : 13/762751
DATED : November 1, 2016
INVENTOR(S) : Gregory A. Olsen

Page 1 of 1

It is certified that error appears in the above-identified patent and that said Letters Patent is hereby corrected as shown below:

In the Specification

In Column 8 at Line 6, After “display” insert --.--.

In Column 8 at Line 11, Change “and or” to --and/or--.

In Column 9 at Line 35, Change “indentifies” to --identifies--.

In the Claims

In Column 11 at Line 51, In Claim 1, change “comprising;” to --comprising:--.

In Column 12 at Line 61, In Claim 1, change “comprising;” to --comprising:--.

In Column 13 at Line 14, In Claim 14, after “to” delete “a”.

Signed and Sealed this
Fourth Day of July, 2017



Joseph Matal

*Performing the Functions and Duties of the
Under Secretary of Commerce for Intellectual Property and
Director of the United States Patent and Trademark Office*

专利名称(译)	可配置的患者监护系统		
公开(公告)号	US9480435	公开(公告)日	2016-11-01
申请号	US13/762751	申请日	2013-02-08
[标]申请(专利权)人(译)	CERCACOR LAB		
当前申请(专利权)人(译)	Masimo公司		
[标]发明人	OLSEN GREGORY A		
发明人	OLSEN, GREGORY A.		
IPC分类号	A61B5/00 A61B5/026 A61B5/1455 G06T11/20 G06T13/80 G06F19/00 G06T13/00 G06T11/00 A61B5/145 A61B5/0205 A61B5/01		
CPC分类号	A61B5/743 A61B5/0261 A61B5/14552 A61B5/7282 A61B5/742 A61B5/7405 A61B5/746 G06F19/345 G06F19/3406 G06T11/206 G06T13/80 A61B5/0008 A61B5/01 A61B5/02055 A61B5/14532 A61B5/14546 A61B5/14551 A61B5/744 G06T2219/2016 G16H40/63 G16H50/20 A61B5/021 A61B5/02416 A61B5/0816		
审查员(译)	THOMSON, WILLIAM		
助理审查员(译)	ARCHER, MARIE		
优先权	61/597140 2012-02-09 US		
其他公开文献	US20130211214A1		
外部链接	Espacenet USPTO		

摘要(译)

患者监视系统可以在可配置的用户界面上显示一个或多个可配置的健康监视器。健康指示器被配置为显示来自患者的生理信号。患者监视系统可以计算对应于患者的状态的健康指示符的值的范围。健康指示器可以基于生理信号的值显示不同的输出。

