



US010251585B2

(12) **United States Patent**
Al-Ali et al.

(10) **Patent No.:** **US 10,251,585 B2**
(45) **Date of Patent:** ***Apr. 9, 2019**

(54) **NONINVASIVE MULTI-PARAMETER
PATIENT MONITOR**

(71) Applicant: **Cercacor Laboratories, Inc.**, Irvine,
CA (US)

(72) Inventors: **Ammar Al-Ali**, San Juan Capistrano,
CA (US); **Joe E. Kiani**, Laguna Niguel,
CA (US)

(73) Assignee: **Cercacor Laboratories, Inc.**, Irvine,
CA (US)

(*) Notice: Subject to any disclaimer, the term of this
patent is extended or adjusted under 35
U.S.C. 154(b) by 322 days.

This patent is subject to a terminal dis-
claimer.

(21) Appl. No.: **15/138,008**

(22) Filed: **Apr. 25, 2016**

(65) **Prior Publication Data**

US 2016/0310052 A1 Oct. 27, 2016

Related U.S. Application Data

(63) Continuation of application No. 14/557,761, filed on
Dec. 2, 2014, now Pat. No. 9,351,675, which is a
(Continued)

(51) **Int. Cl.**
G08B 23/00 (2006.01)
A61B 5/1455 (2006.01)
(Continued)

(52) **U.S. Cl.**
CPC **A61B 5/1455** (2013.01); **A61B 5/0022**
(2013.01); **A61B 5/0205** (2013.01);
(Continued)

(58) **Field of Classification Search**

CPC A61B 1/00; G06F 1/00
See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

3,316,395 A 4/1967 Lavin
3,316,396 A 4/1967 Lavin
(Continued)

FOREIGN PATENT DOCUMENTS

DE 3244695 C2 10/1985
EP 41 92 23 3/1991
(Continued)

OTHER PUBLICATIONS

US 8,845,543 B2, 09/2014, Diab et al. (withdrawn)
(Continued)


Primary Examiner — Shirley Lu

(74) *Attorney, Agent, or Firm* — Knobbe, Martens, Olson
& Bear, LLP

(57) **ABSTRACT**

Embodiments of the present disclosure include a handheld multi-parameter patient monitor capable of determining multiple physiological parameters from the output of a light sensitive detector capable of detecting light attenuated by body tissue. For example, in an embodiment, the monitor is capable of advantageously and accurately displaying one or more of pulse rate, plethysmograph data, perfusion quality, signal confidence, and values of blood constituents in body tissue, including for example, arterial carbon monoxide saturation ("HbCO"), methemoglobin saturation ("Hb-Met"), total hemoglobin ("Hbt"), arterial oxygen saturation ("SpO2"), fractional arterial oxygen saturation ("SpaO2"), or the like. In an embodiment, the monitor displays a line associated with a patient wellness level.

19 Claims, 18 Drawing Sheets



Related U.S. Application Data

- continuation of application No. 14/076,556, filed on Nov. 11, 2013, now Pat. No. 8,912,909, which is a continuation of application No. 13/412,428, filed on Mar. 5, 2012, now Pat. No. 8,581,732, which is a continuation of application No. 11/366,208, filed on Mar. 1, 2006, now Pat. No. 8,130,105.
- (60) Provisional application No. 60/657,759, filed on Mar. 1, 2005, provisional application No. 60/657,596, filed on Mar. 1, 2005, provisional application No. 60/657,281, filed on Mar. 1, 2005, provisional application No. 60/657,268, filed on Mar. 1, 2005.

(51) Int. Cl.

G06F 19/00 (2018.01)
A61B 5/0205 (2006.01)
A61B 5/145 (2006.01)
A61B 5/00 (2006.01)
A61B 5/026 (2006.01)
A61B 5/0295 (2006.01)
A61B 5/024 (2006.01)
A61B 5/1495 (2006.01)
A61B 1/00 (2006.01)

(52) U.S. Cl.

CPC **A61B 5/0261** (2013.01); **A61B 5/0295** (2013.01); **A61B 5/02416** (2013.01); **A61B 5/1495** (2013.01); **A61B 5/14532** (2013.01); **A61B 5/14546** (2013.01); **A61B 5/14551** (2013.01); **A61B 5/14552** (2013.01); **A61B 5/6815** (2013.01); **A61B 5/6826** (2013.01); **A61B 5/6829** (2013.01); **A61B 5/6832** (2013.01); **A61B 5/6838** (2013.01); **A61B 5/7221** (2013.01); **A61B 5/7246** (2013.01); **A61B 5/7275** (2013.01); **A61B 5/7278** (2013.01); **A61B 5/742** (2013.01); **A61B 5/7405** (2013.01); **A61B 5/746** (2013.01); **A61B 5/7475** (2013.01); **G06F 19/00** (2013.01); **G06F 19/3418** (2013.01); **A61B 1/00** (2013.01); **A61B 5/02427** (2013.01); **A61B 2562/08** (2013.01); **A61B 2562/085** (2013.01); **A61B 2562/222** (2013.01); **Y10S 439/909** (2013.01)

(56)**References Cited****U.S. PATENT DOCUMENTS**

3,910,701 A	10/1975	Henderson et al.	4,655,225 A	4/1987	Dahne et al.
3,998,550 A	12/1976	Konishi et al.	4,685,464 A	8/1987	Goldberger et al.
4,014,321 A	3/1977	March	4,694,833 A	9/1987	Hamaguri
4,051,522 A	9/1977	Healy et al.	4,695,955 A	9/1987	Faisandier
4,134,678 A	1/1979	Brown et al.	4,700,708 A	10/1987	New et al.
4,157,708 A	6/1979	Imura	4,714,341 A	12/1987	Hamaguri et al.
4,163,290 A	7/1979	Sutherland et al.	4,770,179 A	9/1988	New et al.
4,167,331 A	9/1979	Nielsen	4,773,422 A	9/1988	Isaacson et al.
4,266,554 A	5/1981	Hamaguri	4,781,195 A	11/1988	Martin
4,267,844 A	5/1981	Yamanishi	4,800,885 A	1/1989	Johnson
4,295,475 A	10/1981	Torzala	4,805,623 A	2/1989	Jobsis
4,305,059 A	12/1981	Benton	4,822,997 A	4/1989	Fuller et al.
4,331,161 A	5/1982	Patel	4,832,484 A	5/1989	Aoyagi et al.
4,399,824 A	8/1983	Davidson	4,846,183 A	7/1989	Martin
4,446,871 A	5/1984	Imura	4,854,328 A	8/1989	Pollack
4,491,725 A	1/1985	Pritchard	4,863,265 A	9/1989	Flower et al.
4,531,527 A	7/1985	Reinhold, Jr. et al.	4,867,571 A	9/1989	Frick et al.
4,561,440 A	12/1985	Kubo et al.	4,868,476 A	9/1989	Respaut
4,586,513 A	5/1986	Hamaguri	4,869,254 A	9/1989	Stone et al.
4,603,700 A	8/1986	Nichols et al.	4,890,306 A	12/1989	Noda
4,621,643 A	11/1986	New et al.	4,907,876 A	3/1990	Suzuki et al.
4,653,498 A	3/1987	New, Jr. et al.	4,911,167 A	3/1990	Corenman et al.
			4,934,372 A	6/1990	Corenman et al.
			4,938,218 A	7/1990	Goodman et al.
			4,942,877 A	7/1990	Sakai et al.
			4,955,379 A	9/1990	Hall
			4,960,126 A	10/1990	Conlon et al.
			4,960,128 A	10/1990	Gordon et al.
			4,964,010 A	10/1990	Miyasaka et al.
			4,964,408 A	10/1990	Hink et al.
			4,967,571 A	11/1990	Sporri
			4,975,581 A	12/1990	Robinson et al.
			4,975,647 A	12/1990	Downer et al.
			4,986,665 A	1/1991	Yamanishi et al.
			4,996,975 A	3/1991	Nakamura
			4,997,769 A	3/1991	Lundsgaard
			5,003,979 A	4/1991	Merickel et al.
			5,025,791 A	6/1991	Niwa
			RE33,643 E	7/1991	Isaacson et al.
			5,028,787 A	7/1991	Rosenthal et al.
			5,033,472 A	7/1991	Sato et al.
			5,041,187 A	8/1991	Hink et al.
			5,054,495 A	10/1991	Uemura et al.
			5,058,588 A	10/1991	Kaestle et al.
			5,069,213 A	12/1991	Polczynski
			5,077,476 A	12/1991	Rosenthal
			5,078,136 A	1/1992	Stone et al.
			5,101,825 A	4/1992	Gravensetin et al.
			5,137,023 A	8/1992	Mendelson et al.
			5,155,697 A	10/1992	Bunsen
			5,162,725 A	11/1992	Hodson et al.
			5,163,438 A	11/1992	Gordon et al.
			5,188,108 A	2/1993	Secker
			5,189,609 A	2/1993	Tivig et al.
			5,190,040 A	3/1993	Aoyagi
			5,203,329 A	4/1993	Takatani et al.
			5,209,230 A	5/1993	Swedlow et al.
			5,226,053 A	7/1993	Cho et al.
			5,226,417 A	7/1993	Swedlow et al.
			5,246,002 A	9/1993	Prosser
			5,247,931 A	9/1993	Norwood
			5,259,381 A	11/1993	Chung
			5,267,562 A	12/1993	Ukawa et al.
			5,267,563 A	12/1993	Swedlow et al.
			5,278,627 A	1/1994	Aoyagi
			5,297,548 A	3/1994	Pologe
			5,313,940 A	5/1994	Fuse et al.
			5,319,355 A	6/1994	Russek
			5,331,549 A	7/1994	Crawford, Jr.
			5,335,659 A	8/1994	Pologe et al.
			5,337,744 A	8/1994	Branigan
			5,337,745 A	8/1994	Benaron
			5,341,805 A	8/1994	Stavridi et al.
			5,348,004 A	9/1994	Hollub
			5,351,685 A	10/1994	Potratz
			5,355,129 A	10/1994	Baumann
			5,355,880 A	10/1994	Thomas et al.
			5,355,882 A	10/1994	Ukawa et al.
			5,361,758 A	11/1994	Hall et al.

(56)

References Cited

U.S. PATENT DOCUMENTS

5,368,041 A	11/1994	Shambroom	5,685,301 A	11/1997	Klomhaus
5,368,224 A	11/1994	Richardson et al.	5,687,719 A	11/1997	Sato et al.
D353,195 S	12/1994	Savage et al.	5,687,722 A	11/1997	Tien et al.
D353,196 S	12/1994	Savage et al.	5,690,104 A	11/1997	Kanemoto et al.
5,370,114 A	12/1994	Wong et al.	5,692,503 A	12/1997	Kuenstner
5,372,136 A	12/1994	Steuer et al.	5,697,371 A	12/1997	Aoyagi
5,377,676 A	1/1995	Vari et al.	5,713,355 A	2/1998	Richardson et al.
5,383,874 A	1/1995	Jackson et al.	5,719,589 A	2/1998	Norman et al.
5,385,143 A	1/1995	Aoyagi	5,720,284 A	2/1998	Aoyagi et al.
5,387,122 A	2/1995	Goldberger et al.	5,720,293 A	2/1998	Quinn et al.
5,392,777 A	2/1995	Swedlow et al.	5,730,125 A	3/1998	Prutchi et al.
5,400,267 A	3/1995	Denen et al.	D393,830 S	4/1998	Tobler et al.
5,413,101 A	5/1995	Sugiura	5,742,718 A	4/1998	Harman et al.
D359,546 S	6/1995	Savage et al.	5,743,262 A	4/1998	Lepper, Jr. et al.
5,421,329 A	6/1995	Casciani et al.	5,743,263 A	4/1998	Baker, Jr.
5,424,545 A	6/1995	Block et al.	5,746,206 A	5/1998	Mannheimer
5,425,362 A	6/1995	Siker et al.	5,746,697 A	5/1998	Swedlow et al.
5,425,375 A	6/1995	Chin et al.	5,752,914 A	5/1998	Delonzor et al.
5,427,093 A	6/1995	Ogawa et al.	5,755,226 A	5/1998	Carim et al.
5,429,128 A	7/1995	Cadell et al.	5,758,644 A	6/1998	Diab et al.
5,431,170 A	7/1995	Mathews	5,760,910 A	6/1998	Lepper, Jr. et al.
5,435,309 A	7/1995	Thomas et al.	5,769,785 A	6/1998	Diab et al.
D361,840 S	8/1995	Savage et al.	5,772,587 A	6/1998	Gratton et al.
D362,063 S	9/1995	Savage et al.	5,779,630 A	7/1998	Fein et al.
5,452,717 A	9/1995	Branigan et al.	5,782,237 A	7/1998	Casciani et al.
D363,120 S	10/1995	Savage et al.	5,782,756 A	7/1998	Mannheimer
5,456,252 A	10/1995	Vari et al.	5,782,757 A	7/1998	Diab et al.
5,469,845 A	11/1995	DeLonzor et al.	5,785,659 A	7/1998	Caro et al.
RE35,122 E	12/1995	Corenman et al.	5,790,729 A	8/1998	Pologe et al.
5,479,934 A	1/1996	Imran	5,791,347 A	8/1998	Flaherty et al.
5,482,036 A	1/1996	Diab et al.	5,792,052 A	8/1998	Isaacson et al.
5,487,386 A	1/1996	Wakabayashi et al.	5,793,485 A	8/1998	Gourley
5,490,505 A	2/1996	Diab et al.	5,800,348 A	9/1998	Kaestle et al.
5,490,523 A	2/1996	Isaacson et al.	5,800,349 A	9/1998	Isaacson et al.
5,494,032 A	2/1996	Robinson et al.	5,803,910 A	9/1998	Potratz
5,494,043 A	2/1996	O'Sullivan et al.	5,807,246 A	9/1998	Sakaguchi et al.
5,503,148 A	4/1996	Pologe et al.	5,807,247 A	9/1998	Merchant et al.
5,520,177 A	5/1996	Ogawa	5,810,723 A	9/1998	Aldrich
5,528,519 A	6/1996	Ohkura et al.	5,810,724 A	9/1998	Gronvall
5,533,507 A	7/1996	Potratz	5,810,734 A	9/1998	Caro et al.
5,533,511 A	7/1996	Kaspari et al.	5,817,010 A	10/1998	Hibl
5,534,851 A	7/1996	Russek	5,818,985 A	10/1998	Merchant et al.
5,551,423 A	9/1996	Sugiura	5,823,950 A	10/1998	Diab et al.
5,553,615 A	9/1996	Carim et al.	5,823,952 A	10/1998	Levinson et al.
5,555,882 A	9/1996	Richardson et al.	5,827,182 A	10/1998	Raley et al.
5,561,275 A	10/1996	Savage et al.	5,830,121 A	11/1998	Enomoto et al.
5,562,002 A	10/1996	Lalin	5,830,131 A	11/1998	Caro et al.
5,575,284 A	11/1996	Athan et al.	5,830,137 A	11/1998	Sharf
5,577,500 A	11/1996	Potratz	5,833,602 A	11/1998	Osemwota
5,584,299 A	12/1996	Sakai et al.	5,833,618 A	11/1998	Caro et al.
5,588,427 A	12/1996	Tien	5,839,439 A	11/1998	Nierlich et al.
5,590,649 A	1/1997	Caro et al.	RE36,000 E	12/1998	Swedlow et al.
5,590,652 A	1/1997	Inai	5,842,979 A	12/1998	Jarman
5,595,176 A	1/1997	Yamaura	5,846,190 A	12/1998	Woehrle
5,596,992 A	1/1997	Haaland et al.	5,850,443 A	12/1998	Van Oorschot et al.
5,602,924 A	2/1997	Durand et al.	5,851,178 A	12/1998	Aronow
5,603,323 A	2/1997	Pflugrath et al.	5,851,179 A	12/1998	Ritson et al.
5,603,623 A	2/1997	Nishikawa et al.	5,853,364 A	12/1998	Baker, Jr. et al.
5,615,672 A	4/1997	Braig et al.	5,857,462 A	1/1999	Thomas et al.
5,617,857 A	4/1997	Chader et al.	5,860,099 A	1/1999	Milios et al.
5,630,413 A	5/1997	Thomas et al.	5,860,919 A	1/1999	Kiani-Azarbayjany et al.
5,632,272 A	5/1997	Diab et al.	5,865,736 A	2/1999	Baker, Jr. et al.
5,638,816 A	6/1997	Kiani-Azarbayjany et al.	5,876,348 A	3/1999	Sugo
5,638,818 A	6/1997	Diab et al.	5,885,213 A	3/1999	Richardson et al.
5,645,059 A	7/1997	Fein et al.	5,890,929 A	4/1999	Mills et al.
5,645,060 A	7/1997	Yorkey	5,891,022 A	4/1999	Pologe
5,645,440 A	7/1997	Tobler et al.	5,891,024 A	4/1999	Jarman et al.
5,651,780 A	7/1997	Jackson et al.	5,900,632 A	5/1999	Sterling et al.
5,658,248 A	8/1997	Klein et al.	5,904,654 A	5/1999	Wohlmann et al.
5,660,567 A	8/1997	Nierlich et al.	5,910,108 A	6/1999	Solenberger
5,662,106 A	9/1997	Swedlow et al.	5,916,154 A	6/1999	Hobbs et al.
5,676,139 A	10/1997	Goldberger et al.	5,919,133 A	7/1999	Taylor
5,676,141 A	10/1997	Hollub	5,919,134 A	7/1999	Diab
5,678,544 A	10/1997	Delonzor et al.	5,921,921 A	7/1999	Potratz et al.
5,685,299 A	11/1997	Diab et al.	5,924,979 A	7/1999	Swedlow
			5,934,277 A	8/1999	Mortz
			5,934,925 A	8/1999	Tobler et al.
			5,939,609 A	8/1999	Knapp et al.
			5,940,182 A	8/1999	Lepper, Jr. et al.

(56)

References Cited

U.S. PATENT DOCUMENTS

5,954,644	A	9/1999	Dettling	6,298,255	B1	10/2001	Cordero et al.
5,976,466	A	11/1999	Ratner et al.	6,301,493	B1	10/2001	Marro et al.
5,978,691	A	11/1999	Mills	6,304,675	B1	10/2001	Osbourne et al.
5,983,122	A	11/1999	Jarman et al.	6,304,767	B1	10/2001	Soller et al.
5,987,343	A	11/1999	Kinast	6,308,089	B1	10/2001	von der Ruhr
5,991,355	A	11/1999	Dahlke	6,317,627	B1	11/2001	Ennen et al.
5,995,855	A	11/1999	Kiani et al.	6,321,100	B1	11/2001	Parker
5,995,856	A	11/1999	Mannheimer et al.	6,325,761	B1	12/2001	Jay
5,995,859	A	11/1999	Takahashi	6,330,468	B1	12/2001	Scharf
5,997,343	A	12/1999	Mills et al.	6,334,065	B1	12/2001	Al-Ali et al.
5,999,841	A	12/1999	Aoyagi et al.	6,336,900	B1	1/2002	Alleckson et al.
6,002,952	A	12/1999	Diab et al.	6,339,715	B1	1/2002	Bahr et al.
6,006,119	A	12/1999	Soller et al.	6,341,257	B1	1/2002	Haaland
6,011,986	A	1/2000	Diab et al.	6,343,224	B1	1/2002	Parker
6,014,576	A	1/2000	Raley	6,356,774	B1	1/2002	Bernstein et al.
6,018,673	A	1/2000	Chin et al.	6,349,228	B1	2/2002	Kiani et al.
6,018,674	A	1/2000	Aronow	6,351,658	B1	2/2002	Middleman et al.
6,023,541	A	2/2000	Merchant et al.	6,360,113	B1	3/2002	Dettling
6,027,452	A	2/2000	Flaherty et al.	6,360,114	B1	3/2002	Diab et al.
6,035,223	A	3/2000	Baker, Jr.	6,363,269	B1	3/2002	Hanna et al.
6,036,642	A	3/2000	Diab et al.	6,368,283	B1	4/2002	Xu et al.
6,045,509	A	4/2000	Caro et al.	6,371,921	B1	4/2002	Caro et al.
6,064,898	A	5/2000	Aldrich	6,374,129	B1	4/2002	Chin et al.
6,067,462	A *	5/2000	Diab A61B 5/02416 600/310	6,377,828	B1	4/2002	Chaiken et al.
6,068,594	A	5/2000	Schloemer et al.	6,377,829	B1	4/2002	Al-Ali
6,073,037	A	6/2000	Alam et al.	6,388,240	B2	5/2002	Schulz et al.
6,081,735	A	6/2000	Diab et al.	6,393,310	B1	5/2002	Kuenstner
6,083,172	A	7/2000	Baker, Jr. et al.	6,397,091	B2	5/2002	Diab et al.
6,088,607	A	7/2000	Diab et al.	6,397,092	B1	5/2002	Norris et al.
6,094,592	A	7/2000	Yorkey et al.	6,397,093	B1	5/2002	Aldrich
6,104,938	A	8/2000	Huiku	6,402,690	B1	6/2002	Rhee et al.
6,110,522	A	8/2000	Lepper, Jr. et al.	6,408,198	B1	6/2002	Hanna et al.
6,112,107	A	8/2000	Hannula	6,411,833	B1	6/2002	Baker, Jr. et al.
6,122,042	A	9/2000	Wunderman et al.	6,415,166	B1	7/2002	Van Hoy et al.
6,124,597	A	9/2000	Shehada et al.	6,415,233	B1	7/2002	Haaland
6,128,521	A	10/2000	Marro et al.	6,415,236	B2	7/2002	Kobayashi et al.
6,129,675	A	10/2000	Jay	6,421,549	B1	7/2002	Jacques
6,132,363	A	10/2000	Freed et al.	6,430,437	B1	8/2002	Marro
6,144,868	A	11/2000	Parker	6,430,525	B1	8/2002	Weber et al.
6,149,588	A	11/2000	Noda et al.	6,434,408	B1	8/2002	Heckel
6,151,516	A	11/2000	Kiani-Azarbayjany et al.	6,441,388	B1	8/2002	Thomas et al.
6,151,518	A	11/2000	Hayashi	6,453,184	B1	9/2002	Hyogo et al.
6,152,754	A	11/2000	Gerhardt et al.	6,455,340	B1	9/2002	Chua et al.
6,154,667	A	11/2000	Miura et al.	6,463,310	B1	10/2002	Swedlow et al.
6,157,041	A	12/2000	Thomas et al.	6,463,311	B1	10/2002	Diab
6,157,850	A	12/2000	Diab et al.	6,466,824	B1	10/2002	Struble
6,163,715	A	12/2000	Larsen et al.	6,470,199	B1	10/2002	Kopotic et al.
6,165,005	A	12/2000	Mills et al.	6,480,729	B2	11/2002	Stone
6,165,173	A	12/2000	Kamdar et al.	6,490,466	B1	12/2002	Fein et al.
6,174,283	B1	1/2001	Nevo et al.	6,490,684	B1	12/2002	Fenstermaker et al.
6,175,752	B1	1/2001	Say et al.	6,497,659	B1	12/2002	Rafert
6,184,521	B1	2/2001	Coffin et al.	6,501,974	B2	12/2002	Huiku
6,192,261	B1	2/2001	Gratton et al.	6,501,975	B2	12/2002	Diab et al.
6,206,830	B1	3/2001	Diab et al.	6,504,943	B1	1/2003	Sweatt et al.
6,226,539	B1	5/2001	Potratz	6,505,059	B1	1/2003	Kollias et al.
6,229,856	B1	5/2001	Diab et al.	6,505,060	B1	1/2003	Norris
6,230,035	B1	5/2001	Aoyagi et al.	6,505,061	B2	1/2003	Larson
6,232,609	B1	5/2001	Snyder et al.	6,505,133	B1	1/2003	Hanna
6,236,872	B1	5/2001	Diab et al.	6,510,329	B2	1/2003	Heckel
6,237,604	B1	5/2001	Burnside et al.	6,515,273	B2	2/2003	Al-Ali
6,241,683	B1	6/2001	Macklem et al.	6,519,486	B1	2/2003	Edgar, Jr. et al.
6,248,083	B1	6/2001	Smith et al.	6,519,487	B1	2/2003	Parker
6,253,097	B1	6/2001	Aronow et al.	6,522,398	B2	2/2003	Cadell et al.
6,256,523	B1	7/2001	Diab et al.	6,525,386	B1	2/2003	Mills et al.
6,262,698	B1	7/2001	Blum	6,526,300	B1	2/2003	Kiani et al.
6,263,222	B1	7/2001	Diab et al.	6,526,301	B2	2/2003	Larsen et al.
6,266,551	B1	7/2001	Osadchy et al.	6,528,809	B1	3/2003	Thomas et al.
6,272,363	B1	8/2001	Casciani et al.	6,537,225	B1	3/2003	Mills
6,278,522	B1	8/2001	Lepper, Jr. et al.	6,541,756	B2	4/2003	Schulz et al.
6,280,213	B1	8/2001	Tobler et al.	6,542,763	B1	4/2003	Yamashita et al.
6,285,895	B1	9/2001	Ristolainen et al.	6,542,764	B1	4/2003	Al-Ali et al.
6,285,896	B1	9/2001	Tobler et al.	6,545,652	B1	4/2003	Tsuji
6,295,330	B1	9/2001	Skog et al.	6,546,267	B1	4/2003	Sugiura
6,298,252	B1	10/2001	Kovach et al.	6,553,241	B2	4/2003	Mannheimer et al.
				6,564,077	B2	5/2003	Mortara
				6,571,113	B1	5/2003	Fein et al.
				6,580,086	B1	6/2003	Schulz et al.
				6,582,964	B1	6/2003	Samsouondar et al.
				6,584,336	B1	6/2003	Ali et al.

(56)

References Cited

U.S. PATENT DOCUMENTS

6,584,413 B1	6/2003	Keenan et al.	6,748,253 B2	6/2004	Norris et al.
6,591,123 B2	7/2003	Fein et al.	6,748,254 B2	6/2004	O'Neil et al.
6,594,511 B2	7/2003	Stone et al.	6,754,515 B1	6/2004	Pologe
6,594,518 B1	7/2003	Benaron et al.	6,754,516 B2	6/2004	Mannheimer
6,595,316 B2	7/2003	Cybulski et al.	6,760,607 B2	7/2004	Al-Ali
6,597,932 B2	7/2003	Tian et al.	6,760,609 B2	7/2004	Jacques
6,597,933 B2	7/2003	Kiani et al.	6,770,028 B1	8/2004	Ali et al.
6,600,940 B1	7/2003	Fein et al.	6,771,994 B2	8/2004	Kiani et al.
6,606,509 B2	8/2003	Schmitt	6,773,397 B2	8/2004	Kelly
6,606,510 B2	8/2003	Swedlow et al.	6,778,923 B2	8/2004	Norris et al.
6,606,511 B1	8/2003	Ali et al.	6,780,158 B2	8/2004	Yarita
6,609,016 B1	8/2003	Lynn	6,788,849 B1	9/2004	Pawluczyk
6,611,698 B1	8/2003	Yamashita et al.	6,792,300 B1	9/2004	Diab et al.
6,614,521 B2	9/2003	Samsoondar et al.	6,800,373 B2	10/2004	Corczyca
6,615,064 B1	9/2003	Aldrich	6,801,797 B2	10/2004	Mannheimer et al.
6,615,151 B1	9/2003	Seccina et al.	6,801,799 B2	10/2004	Mendelson
6,618,602 B2	9/2003	Levin	6,810,277 B2	10/2004	Edgar, Jr. et al.
6,622,095 B2	9/2003	Kobayashi et al.	6,813,511 B2	11/2004	Diab et al.
6,628,975 B1	9/2003	Fein et al.	6,816,741 B2	11/2004	Diab
6,631,281 B1	10/2003	Kastle	6,819,950 B2	11/2004	Mills
6,632,181 B2	10/2003	Flaherty et al.	6,822,564 B2	11/2004	Al-Ali
6,639,668 B1	10/2003	Trepagnier	6,825,619 B2	11/2004	Norris
6,640,116 B2	10/2003	Diab	6,826,419 B2	11/2004	Diab et al.
6,643,530 B2	11/2003	Diab et al.	6,829,496 B2	12/2004	Nagai et al.
6,645,142 B2	11/2003	Braig et al.	6,829,501 B2	12/2004	Nielsen et al.
6,650,917 B2	11/2003	Diab et al.	6,830,711 B2	12/2004	Mills et al.
6,654,623 B1	11/2003	Kastle	6,836,679 B2	12/2004	Baker, Jr. et al.
6,654,624 B2	11/2003	Diab et al.	6,839,579 B1	1/2005	Chin
6,657,717 B2	12/2003	Cadell et al.	6,839,580 B2	1/2005	Zonios et al.
6,658,276 B2	12/2003	Kianl et al.	6,839,582 B2	1/2005	Heckel
6,658,277 B2	12/2003	Wasserman	6,842,702 B2	1/2005	Haaland et al.
6,661,161 B1	12/2003	Lanzo et al.	6,845,256 B2	1/2005	Chin et al.
6,662,033 B2	12/2003	Casciani et al.	6,847,835 B1	1/2005	Yamanishi
6,665,551 B1	12/2003	Suzuki	6,850,787 B2	2/2005	Weber et al.
6,668,183 B2	12/2003	Hicks et al.	6,850,788 B2	2/2005	Al-Ali
6,671,526 B1	12/2003	Aoyagi et al.	6,852,083 B2	2/2005	Caro et al.
6,671,531 B2	12/2003	Al-Ali et al.	6,861,639 B2	3/2005	Al-Ali
6,675,031 B1	1/2004	Porges et al.	6,861,641 B1	3/2005	Adams
6,675,106 B1	1/2004	Keenan et al.	6,869,402 B2	3/2005	Arnold
6,676,600 B1	1/2004	Conero et al.	6,882,874 B2	4/2005	Huiku
6,678,543 B2	1/2004	Diab et al.	6,898,452 B2	5/2005	Al-Ali et al.
6,681,126 B2	1/2004	Solenberger	6,912,049 B2	6/2005	Pawluczyk et al.
6,684,090 B2	1/2004	Ali et al.	6,917,422 B2	7/2005	Samsoondar et al.
6,684,091 B2	1/2004	Parker	6,919,566 B1	7/2005	Cadell
6,687,620 B1	2/2004	Haaland et al.	6,920,345 B2	7/2005	Al-Ali et al.
6,690,466 B2	2/2004	Miller et al.	6,921,367 B2	7/2005	Mills
6,694,157 B1	2/2004	Stone et al.	6,922,645 B2	7/2005	Haaland et al.
6,697,655 B2	2/2004	Sueppel et al.	6,928,311 B1	8/2005	Pawluczyk et al.
6,697,656 B1	2/2004	Al-Ali	6,931,268 B1	8/2005	Kiani-Azarbayjany et al.
6,697,657 B1	2/2004	Shehada et al.	6,931,269 B2	8/2005	Terry
6,697,658 B2	2/2004	Al-Ali	6,934,570 B2	8/2005	Kiani et al.
RE38,476 E	3/2004	Diab et al.	6,939,305 B2	9/2005	Flaherty et al.
6,699,194 B1	3/2004	Diab et al.	6,943,348 B1	9/2005	Coffin, IV
6,701,170 B2	3/2004	Stetson	6,944,487 B2	9/2005	Maynard et al.
6,708,049 B1	3/2004	Berson et al.	6,950,687 B2	9/2005	Al-Ali
6,711,503 B2	3/2004	Haaland	6,956,572 B2	10/2005	Zaleski
6,714,803 B1	3/2004	Mortz	6,961,598 B2	11/2005	Diab
6,714,804 B2	3/2004	Al-Ali et al.	6,970,792 B1	11/2005	Diab
6,714,805 B2	3/2004	Jeon et al.	6,975,891 B2	12/2005	Pawluczyk
RE38,492 E	4/2004	Diab et al.	6,979,812 B2	12/2005	Al-Ali
6,719,705 B2	4/2004	Mills	6,985,764 B2	1/2006	Mason et al.
6,720,734 B2	4/2004	Norris	6,987,994 B1	1/2006	Mortz
6,721,582 B2	4/2004	Trepagnier et al.	6,993,371 B2	1/2006	Kiani et al.
6,721,584 B2	4/2004	Baker, Jr. et al.	6,996,427 B2	2/2006	Ali et al.
6,721,585 B1	4/2004	Parker	6,999,904 B2	2/2006	Weber et al.
6,725,074 B1	4/2004	Kastle	7,001,337 B2	2/2006	Dekker
6,725,075 B2	4/2004	Al-Ali	7,003,338 B2	2/2006	Weber et al.
6,726,634 B2	4/2004	Freeman	7,003,339 B2	2/2006	Diab et al.
6,728,560 B2	4/2004	Kollias et al.	7,006,856 B2	2/2006	Baker, Jr. et al.
6,735,459 B2	5/2004	Parker	7,015,451 B2	3/2006	Dalke et al.
6,741,875 B1	5/2004	Pawluczyk et al.	7,024,233 B2	4/2006	Ali et al.
6,741,876 B1	5/2004	Seccina et al.	7,027,849 B2	4/2006	Al-Ali
6,743,172 B1	6/2004	Blike	7,030,749 B2	4/2006	Al-Ali
6,745,060 B2	6/2004	Diab et al.	7,039,449 B2	5/2006	Al-Ali
6,745,061 B1	6/2004	Hicks et al.	7,041,060 B2	5/2006	Flaherty et al.
			7,044,918 B2	5/2006	Diab
			7,067,893 B2	6/2006	Mills et al.
			7,096,052 B2	8/2006	Mason et al.
			7,096,054 B2	8/2006	Abdul-Hafiz et al.

(56)

References Cited

U.S. PATENT DOCUMENTS

7,132,641 B2	11/2006	Schulz et al.	D614,305 S	4/2010	Al-Ali et al.
7,142,901 B2	11/2006	Kiani et al.	RE41,317 E	5/2010	Parker
7,149,561 B2	12/2006	Diab	7,729,733 B2	6/2010	Al-Ali et al.
7,186,966 B2	3/2007	Al-Ali	7,734,320 B2	6/2010	Al-Ali
7,190,261 B2	3/2007	Al-Ali	7,761,128 B2	7/2010	Al-Ali et al.
7,215,984 B2	5/2007	Diab et al.	7,764,982 B2	7/2010	Dalke et al.
7,215,986 B2	5/2007	Diab et al.	D621,516 S	8/2010	Kiani et al.
7,221,971 B2	5/2007	Diab et al.	7,791,155 B2	9/2010	Diab
7,225,006 B2	5/2007	Al-Ali et al.	7,801,581 B2	9/2010	Diab
7,225,007 B2	5/2007	Al-Ali et al.	7,822,452 B2	10/2010	Schurman et al.
RE39,672 E	6/2007	Shehada et al.	RE41,912 E	11/2010	Parker
7,239,905 B2	7/2007	Kiani-Azarbayjany et al.	7,844,313 B2	11/2010	Kiani et al.
7,245,953 B1	7/2007	Parker	7,844,314 B2	11/2010	Al-Ali
7,254,429 B2	8/2007	Schurman et al.	7,844,315 B2	11/2010	Al-Ali
7,254,431 B2	8/2007	Al-Ali et al.	7,865,222 B2	1/2011	Weber et al.
7,254,433 B2	8/2007	Diab et al.	7,873,497 B2	1/2011	Weber et al.
7,254,434 B2	8/2007	Schulz et al.	7,880,606 B2	2/2011	Al-Ali
7,272,425 B2	9/2007	Al-Ali	7,880,626 B2	2/2011	Al-Ali et al.
7,274,955 B2	9/2007	Kiani et al.	7,891,355 B2	2/2011	Al-Ali et al.
D554,263 S	10/2007	Al-Ali	7,894,868 B2	2/2011	Al-Ali et al.
7,280,858 B2	10/2007	Al-Ali et al.	7,899,507 B2	3/2011	Al-Ali et al.
7,289,835 B2	10/2007	Mansfield et al.	7,899,518 B2	3/2011	Trepagnier et al.
7,292,883 B2	11/2007	De Felice et al.	7,904,132 B2	3/2011	Weber et al.
7,295,866 B2	11/2007	Al-Ali	7,909,772 B2	3/2011	Popov et al.
7,299,080 B2	11/2007	Acosta et al.	7,910,875 B2	3/2011	Al-Ali
7,328,053 B1	2/2008	Diab et al.	7,919,713 B2	4/2011	Al-Ali et al.
7,332,784 B2	2/2008	Mills et al.	7,937,128 B2	5/2011	Al-Ali
7,340,287 B2	3/2008	Mason et al.	7,937,129 B2	5/2011	Mason et al.
7,341,559 B2	3/2008	Schulz et al.	7,937,130 B2	5/2011	Diab et al.
7,343,186 B2	3/2008	Lamego et al.	7,941,199 B2	5/2011	Kiani
D566,282 S	4/2008	Al-Ali et al.	7,951,086 B2	5/2011	Flaherty et al.
7,355,512 B1	4/2008	Al-Ali	7,957,780 B2	6/2011	Lamego et al.
7,356,365 B2	4/2008	Schurman	7,962,188 B2	6/2011	Kiani et al.
7,371,981 B2	5/2008	Abdul-Hafiz	7,962,190 B1	6/2011	Diab et al.
7,373,193 B2	5/2008	Al-Ali et al.	7,976,472 B2	7/2011	Kiani
7,373,194 B2	5/2008	Weber et al.	7,988,637 B2	8/2011	Diab
7,376,453 B1	5/2008	Diab et al.	7,990,382 B2	8/2011	Kiani
7,377,794 B2	5/2008	Al-Ali et al.	7,991,446 B2	8/2011	Al-Ali et al.
7,377,899 B2	5/2008	Weber et al.	8,000,761 B2	8/2011	Al-Ali
7,383,070 B2	6/2008	Diab et al.	8,008,088 B2	8/2011	Bellott et al.
7,415,297 B2	8/2008	Al-Ali et al.	RE42,753 E	9/2011	Kiani-Azarbayjany et al.
7,428,432 B2	9/2008	Ali et al.	8,019,400 B2	9/2011	Diab et al.
7,438,683 B2	10/2008	Al-Ali et al.	8,028,701 B2	10/2011	Al-Ali et al.
7,440,787 B2	10/2008	Diab	8,029,765 B2	10/2011	Bellott et al.
7,454,240 B2	11/2008	Diab et al.	8,036,727 B2	10/2011	Schurman et al.
7,457,652 B2	11/2008	Porges et al.	8,036,728 B2	10/2011	Diab et al.
7,467,002 B2	12/2008	Weber et al.	8,046,040 B2	10/2011	Ali et al.
7,469,157 B2	12/2008	Diab et al.	8,046,041 B2	10/2011	Diab et al.
7,471,969 B2	12/2008	Diab et al.	8,046,042 B2	10/2011	Diab et al.
7,471,971 B2	12/2008	Diab et al.	8,048,040 B2	11/2011	Kiani
7,483,729 B2	1/2009	Al-Ali et al.	8,050,728 B2	11/2011	Al-Ali et al.
7,483,730 B2	1/2009	Diab et al.	RE43,169 E	2/2012	Parker
7,489,958 B2	2/2009	Diab et al.	8,118,620 B2	2/2012	Al-Ali et al.
7,496,391 B2	2/2009	Diab et al.	8,126,528 B2	2/2012	Diab et al.
7,496,393 B2	2/2009	Diab et al.	8,128,572 B2	3/2012	Diab et al.
D587,657 S	3/2009	Al-Ali et al.	8,130,105 B2	3/2012	Al-Ali et al.
7,499,741 B2	3/2009	Diab et al.	8,145,287 B2	3/2012	Diab et al.
7,499,835 B2	3/2009	Weber et al.	8,150,487 B2	4/2012	Diab et al.
7,500,950 B2	3/2009	Al-Ali et al.	8,175,672 B2	5/2012	Parker
7,509,154 B2	3/2009	Diab et al.	8,180,420 B2	5/2012	Diab et al.
7,509,494 B2	3/2009	Al-Ali	8,182,443 B1	5/2012	Kiani
7,510,849 B2	3/2009	Schurman et al.	8,185,180 B2	5/2012	Diab et al.
7,526,328 B2	4/2009	Diab et al.	8,190,223 B2	5/2012	Al-Ali et al.
7,530,942 B1	5/2009	Diab	8,190,227 B2	5/2012	Diab et al.
7,530,949 B2	5/2009	Al Ali et al.	8,203,438 B2	6/2012	Kiani et al.
7,530,955 B2	5/2009	Diab et al.	8,203,704 B2	6/2012	Merritt et al.
7,563,110 B2	7/2009	Al-Ali et al.	8,204,566 B2	6/2012	Schurman et al.
7,596,398 B2	9/2009	Al-Ali et al.	8,219,172 B2	7/2012	Schurman et al.
7,606,861 B2	10/2009	Killcommons et al.	8,224,411 B2	7/2012	Al-Ali et al.
7,618,375 B2	11/2009	Flaherty et al.	8,228,181 B2	7/2012	Al-Ali
D606,659 S	12/2009	Kiani et al.	8,229,532 B2	7/2012	Davis
7,647,083 B2	1/2010	Al-Ali et al.	8,229,533 B2	7/2012	Diab et al.
D609,193 S	2/2010	Al-Ali et al.	8,233,955 B2	7/2012	Al-Ali et al.
7,670,726 B2	3/2010	Lu	8,244,325 B2	8/2012	Al-Ali et al.
7,679,519 B2	3/2010	Lindner et al.	8,255,026 B1	8/2012	Al-Ali
			8,255,027 B2	8/2012	Al-Ali et al.
			8,255,028 B2	8/2012	Al-Ali et al.
			8,260,577 B2	9/2012	Weber et al.
			8,265,723 B1	9/2012	McHale et al.

(56)

References Cited

U.S. PATENT DOCUMENTS

8,274,360 B2	9/2012	Sampath et al.	8,690,799 B2	4/2014	Telfort et al.
8,301,217 B2	10/2012	Al-Ali et al.	8,700,112 B2	4/2014	Kiani
8,306,596 B2	11/2012	Schurman et al.	8,702,627 B2	4/2014	Telfort et al.
8,310,336 B2	11/2012	Muhsin et al.	8,706,179 B2	4/2014	Parker
8,315,683 B2	11/2012	Al-Ali et al.	8,712,494 B1	4/2014	MacNeish, III et al.
RE43,860 E	12/2012	Parker	8,715,206 B2	5/2014	Telfort et al.
8,337,403 B2	12/2012	Al-Ali et al.	8,718,735 B2	5/2014	Lamego et al.
8,346,330 B2	1/2013	Lamego	8,718,737 B2	5/2014	Diab et al.
8,353,842 B2	1/2013	Al-Ali et al.	8,718,738 B2	5/2014	Blank et al.
8,355,766 B2	1/2013	MacNeish, III et al.	8,720,249 B2	5/2014	Al-Ali
8,359,080 B2	1/2013	Diab et al.	8,721,541 B2	5/2014	Al-Ali et al.
8,364,223 B2	1/2013	Al-Ali et al.	8,721,542 B2	5/2014	Al-Ali et al.
8,364,226 B2	1/2013	Diab et al.	8,723,677 B1	5/2014	Kiani
8,374,665 B2	2/2013	Lamego	8,740,792 B1	6/2014	Kiani et al.
8,385,995 B2	2/2013	Al-Ali et al.	8,754,776 B2	6/2014	Poeze et al.
8,385,996 B2	2/2013	Dalke et al.	8,755,535 B2	6/2014	Telfort et al.
8,388,353 B2	3/2013	Kiani et al.	8,755,856 B2	6/2014	Diab et al.
8,399,822 B2	3/2013	Al-Ali	8,755,872 B1	6/2014	Marinow
8,401,602 B2	3/2013	Kiani	8,761,850 B2	6/2014	Lamego
8,405,608 B2	3/2013	Al-Ali et al.	8,764,671 B2	7/2014	Kiani
8,414,499 B2	4/2013	Al-Ali et al.	8,768,423 B2	7/2014	Shakespeare et al.
8,418,524 B2	4/2013	Al-Ali	8,771,204 B2	7/2014	Telfort et al.
8,423,106 B2	4/2013	Lamego et al.	8,777,634 B2	7/2014	Kiani et al.
8,428,967 B2	4/2013	Olsen et al.	8,781,543 B2	7/2014	Diab et al.
8,430,817 B1	4/2013	Al-Ali et al.	8,781,544 B2	7/2014	Al-Ali et al.
8,437,825 B2	5/2013	Dalvi et al.	8,781,549 B2	7/2014	Al-Ali et al.
8,455,290 B2	6/2013	Siskavich	8,788,003 B2	7/2014	Schurman et al.
8,457,703 B2	6/2013	Al-Ali	8,790,268 B2	7/2014	Al-Ali
8,457,707 B2	6/2013	Kiani	8,801,613 B2	8/2014	Al-Ali et al.
8,463,349 B2	6/2013	Diab et al.	8,821,397 B2	9/2014	Al-Ali et al.
8,466,286 B2	6/2013	Bellott et al.	8,821,415 B2	9/2014	Al-Ali et al.
8,471,713 B2	6/2013	Poeze et al.	8,830,449 B1	9/2014	Lamego et al.
8,473,020 B2	6/2013	Kiani et al.	8,831,700 B2	9/2014	Schurman et al.
8,483,787 B2	7/2013	Al-Ali et al.	8,840,549 B2	9/2014	Al-Ali et al.
8,489,364 B2	7/2013	Weber et al.	8,847,740 B2	9/2014	Kiani et al.
8,498,684 B2	7/2013	Weber et al.	8,849,365 B2	9/2014	Smith et al.
8,504,128 B2	8/2013	Blank et al.	8,852,094 B2	10/2014	Al-Ali et al.
8,509,867 B2	8/2013	Workman et al.	8,852,994 B2	10/2014	Wojtczuk et al.
8,515,509 B2	8/2013	Bruinsma et al.	8,868,147 B2	10/2014	Stippick et al.
8,523,781 B2	9/2013	Al-Ali	8,868,150 B2	10/2014	Al-Ali et al.
8,529,301 B2	9/2013	Al-Ali et al.	8,870,792 B2	10/2014	Al-Ali et al.
8,532,727 B2	9/2013	Al-Ali et al.	8,886,271 B2	11/2014	Kiani et al.
8,532,728 B2	9/2013	Diab et al.	8,888,539 B2	11/2014	Al-Ali et al.
D692,145 S	10/2013	Al-Ali et al.	8,888,708 B2	11/2014	Diab et al.
8,547,209 B2	10/2013	Kiani et al.	8,892,180 B2	11/2014	Weber et al.
8,548,548 B2	10/2013	Al-Ali	8,897,847 B2	11/2014	Al-Ali
8,548,549 B2	10/2013	Schurman et al.	8,909,310 B2	12/2014	Lamego et al.
8,548,550 B2	10/2013	Al-Ali et al.	8,911,377 B2	12/2014	Al-Ali
8,560,032 B2	10/2013	Al-Ali et al.	8,912,909 B2	12/2014	Al-Ali et al.
8,560,034 B1	10/2013	Diab et al.	8,920,317 B2	12/2014	Al-Ali et al.
8,570,167 B2	10/2013	Al-Ali	8,921,699 B2	12/2014	Al-Ali et al.
8,570,503 B2	10/2013	Vo et al.	8,922,382 B2	12/2014	Al-Ali et al.
8,571,617 B2	10/2013	Reichgott et al.	8,929,964 B2	1/2015	Al-Ali et al.
8,571,618 B1	10/2013	Lamego et al.	8,942,777 B2	1/2015	Diab et al.
8,571,619 B2	10/2013	Al-Ali et al.	8,948,834 B2	2/2015	Diab et al.
8,577,431 B2	11/2013	Lamego et al.	8,948,835 B2	2/2015	Diab
8,581,732 B2	11/2013	Al-Ali et al.	8,965,471 B2	2/2015	Lamego et al.
8,584,345 B2	11/2013	Al-Ali et al.	8,983,564 B2	3/2015	Al-Ali
8,588,880 B2	11/2013	Abdul-Hafiz et al.	8,989,831 B2	3/2015	Al-Ali et al.
8,600,467 B2	12/2013	Al-Ali et al.	8,996,085 B2	3/2015	Kiani et al.
8,606,342 B2	12/2013	Diab	8,998,809 B2	4/2015	Kiani
8,626,255 B2	1/2014	Al-Ali et al.	9,028,429 B2	5/2015	Telfort et al.
8,630,691 B2	1/2014	Lamego et al.	9,037,207 B2	5/2015	Al-Ali et al.
8,634,889 B2	1/2014	Al-Ali et al.	9,060,721 B2	6/2015	Reichgott et al.
8,641,631 B2	2/2014	Sierra et al.	9,066,666 B2	6/2015	Kiani
8,652,060 B2	2/2014	Al-Ali	9,066,680 B1	6/2015	Al-Ali et al.
8,663,107 B2	3/2014	Kiani	9,072,474 B2	7/2015	Al-Ali et al.
8,666,468 B1	3/2014	Al-Ali	9,078,560 B2	7/2015	Schurman et al.
8,667,967 B2	3/2014	Al-Ali et al.	9,084,569 B2	7/2015	Weber et al.
8,670,811 B2	3/2014	O'Reilly	9,095,316 B2	8/2015	Welch et al.
8,670,814 B2	3/2014	Diab et al.	9,106,038 B2	8/2015	Telfort et al.
8,676,286 B2	3/2014	Weber et al.	9,107,625 B2	8/2015	Telfort et al.
8,682,407 B2	3/2014	Al-Ali	9,107,626 B2	8/2015	Al-Ali et al.
RE44,823 E	4/2014	Parker	9,113,831 B2	8/2015	Al-Ali
RE44,875 E	4/2014	Kiani et al.	9,113,832 B2	8/2015	Al-Ali
			9,119,595 B2	9/2015	Lamego
			9,131,881 B2	9/2015	Diab et al.
			9,131,882 B2	9/2015	Al-Ali et al.
			9,131,883 B2	9/2015	Al-Ali

(56)

References Cited

U.S. PATENT DOCUMENTS

9,131,917 B2	9/2015	Telfort et al.	2002/0051290 A1	5/2002	Hannington
9,138,180 B1	9/2015	Coverston et al.	2002/0059047 A1	5/2002	Haaland
9,138,182 B2	9/2015	Al-Ali et al.	2002/0068858 A1	6/2002	Braig et al.
9,138,192 B2	9/2015	Weber et al.	2002/0082488 A1	6/2002	Al-Ali et al.
9,142,117 B2	9/2015	Muhsin et al.	2002/0095076 A1	7/2002	Krausman et al.
9,153,112 B1	10/2015	Kiani et al.	2002/0095077 A1	7/2002	Swedlow et al.
9,153,121 B2	10/2015	Kiani et al.	2002/0095078 A1	7/2002	Mannheimer et al.
9,161,696 B2	10/2015	Al-Ali et al.	2002/0111748 A1	8/2002	Kobayashi et al.
9,161,713 B2	10/2015	Al-Ali et al.	2002/0115919 A1	8/2002	Al-Ali
9,167,995 B2	10/2015	Lamego et al.	2002/0154665 A1	10/2002	Funabashi et al.
9,176,141 B2	11/2015	Al-Ali et al.	2002/0156353 A1	10/2002	Larson
9,186,102 B2	11/2015	Bruinsma et al.	2002/0159002 A1	10/2002	Chang
9,192,312 B2	11/2015	Al-Ali	2002/0161291 A1	10/2002	Kiani et al.
9,192,329 B2	11/2015	Al-Ali	2002/0165440 A1	11/2002	Mason et al.
9,192,351 B1	11/2015	Telfort et al.	2002/0183819 A1	12/2002	Struble
9,195,385 B2	11/2015	Al-Ali et al.	2002/0198442 A1	12/2002	Rantala et al.
9,211,072 B2	12/2015	Kiani	2003/0045784 A1	3/2003	Palatnik et al.
9,211,095 B1	12/2015	Al-Ali	2003/0045785 A1	3/2003	Diab et al.
9,218,454 B2	12/2015	Kiani et al.	2003/0049232 A1	3/2003	Page et al.
9,226,696 B2	1/2016	Kiani	2003/0109775 A1	6/2003	O'Neil et al.
9,241,662 B2	1/2016	Al-Ali et al.	2003/0116769 A1	6/2003	Song et al.
9,245,668 B1	1/2016	Vo et al.	2003/0117296 A1	6/2003	Seely
9,259,185 B2	2/2016	Abdul-Hafiz et al.	2003/0120160 A1	6/2003	Yarita
9,267,572 B2	2/2016	Barker et al.	2003/0120164 A1	6/2003	Nielsen et al.
9,277,880 B2	3/2016	Poeze et al.	2003/0135099 A1	7/2003	Al-Ali
9,289,167 B2	3/2016	Diab et al.	2003/0139657 A1	7/2003	Solenberger
9,295,421 B2	3/2016	Kiani et al.	2003/0160257 A1	8/2003	Bader et al.
9,307,928 B1	4/2016	Al-Ali et al.	2003/0195402 A1	10/2003	Fein et al.
9,323,894 B2	4/2016	Kiani	2004/0006261 A1	1/2004	Swedlow et al.
D755,392 S	5/2016	Hwang et al.	2004/0033618 A1	2/2004	Haass et al.
9,326,712 B1	5/2016	Kiani	2004/0034898 A1	2/2004	Bruegl
9,333,316 B2	5/2016	Kiani	2004/0059209 A1	3/2004	Al Ali et al.
9,339,220 B2	5/2016	Lamego et al.	2004/0064259 A1	4/2004	Haaland et al.
9,341,565 B2	5/2016	Lamego et al.	2004/0081621 A1	4/2004	Arndt et al.
9,351,673 B2	5/2016	Diab et al.	2004/0092805 A1	5/2004	Yarita
9,351,675 B2	5/2016	Al-Ali et al.	2004/0097797 A1	5/2004	Porges et al.
9,364,181 B2	6/2016	Kiani et al.	2004/0133087 A1	7/2004	Ali et al.
9,368,671 B2	6/2016	Wojtczuk et al.	2004/0138538 A1	7/2004	Stetson
9,370,325 B2	6/2016	Al-Ali et al.	2004/0138540 A1	7/2004	Baker, Jr. et al.
9,370,326 B2	6/2016	McHale et al.	2004/0147822 A1	7/2004	Al-Ali et al.
9,370,335 B2	6/2016	Al-Ali et al.	2004/0147823 A1	7/2004	Kiani et al.
9,375,185 B2	6/2016	Ali et al.	2004/0158132 A1	8/2004	Zaleski
9,386,953 B2	7/2016	Al-Ali	2004/0158134 A1	8/2004	Diab et al.
9,386,961 B2	7/2016	Al-Ali et al.	2004/0158135 A1	8/2004	Baker, Jr. et al.
9,392,945 B2	7/2016	Al-Ali et al.	2004/0158162 A1	8/2004	Narimatsu
9,397,448 B2	7/2016	Al-Ali et al.	2004/0162472 A1	8/2004	Berson et al.
9,408,542 B1	8/2016	Kinast et al.	2004/0167382 A1	8/2004	Gardner et al.
9,436,645 B2	9/2016	Al-Ali et al.	2004/0171940 A1	9/2004	Narimatsu
9,445,759 B1	9/2016	Lamego et al.	2004/0176670 A1	9/2004	Takamura et al.
9,466,919 B2	10/2016	Kiani et al.	2004/0181134 A1	9/2004	Baker, Jr. et al.
9,474,474 B2	10/2016	Lamego et al.	2004/0199063 A1	10/2004	O'Neil et al.
9,480,422 B2	11/2016	Al-Ali	2004/0204639 A1	10/2004	Casciani et al.
9,480,435 B2	11/2016	Olsen	2004/0204868 A1	10/2004	Maynard et al.
9,492,110 B2	11/2016	Al-Ali et al.	2004/0229391 A1	11/2004	Ohya et al.
9,510,779 B2	12/2016	Poeze et al.	2004/0262046 A1	12/2004	Simon et al.
9,517,024 B2	12/2016	Kiani et al.	2004/0267103 A1	12/2004	Li et al.
9,532,722 B2	1/2017	Lamego et al.	2004/0267140 A1	12/2004	Ito et al.
9,538,949 B2	1/2017	Al-Ali et al.	2005/0011488 A1	1/2005	Doucet
9,538,980 B2	1/2017	Telfort et al.	2005/0033128 A1	2/2005	Ali et al.
9,549,696 B2	1/2017	Lamego et al.	2005/0043902 A1	2/2005	Haaland et al.
9,554,737 B2	1/2017	Schurman et al.	2005/0049469 A1	3/2005	Aoyagi et al.
9,560,996 B2	2/2017	Kiani	2005/0054908 A1	3/2005	Blank et al.
9,560,998 B2	2/2017	Al-Ali et al.	2005/0070773 A1	3/2005	Chin et al.
9,566,019 B2	2/2017	Al-Ali et al.	2005/0070775 A1	3/2005	Chin et al.
9,579,039 B2	2/2017	Jansen et al.	2005/0075546 A1	4/2005	Samsoondar et al.
9,839,381 B1	12/2017	Weber et al.	2005/0085704 A1	4/2005	Schulz et al.
9,848,807 B2	12/2017	Lamego	2005/0085735 A1	4/2005	Baker, Jr. et al.
2001/0044700 A1	11/2001	Kobayashi et al.	2005/0115561 A1*	6/2005	Stahmann A61B 5/0031 128/200.24
2001/0045532 A1	11/2001	Schulz et al.	2005/0124871 A1	6/2005	Baker, Jr. et al.
2002/0021269 A1	2/2002	Rast	2005/0143634 A1	6/2005	Baker, Jr. et al.
2002/0026107 A1	2/2002	Kiani et al.	2005/0143943 A1	6/2005	Brown
2002/0035315 A1	3/2002	Ali et al.	2005/0148834 A1	7/2005	Hull et al.
2002/0035318 A1	3/2002	Mannheimer et al.	2005/0184895 A1	8/2005	Petersen et al.
2002/0038078 A1	3/2002	Ito	2005/0187446 A1	8/2005	Nordstrom et al.
2002/0038081 A1	3/2002	Fein et al.	2005/0187447 A1	8/2005	Chew et al.
			2005/0187448 A1	8/2005	Petersen et al.
			2005/0187449 A1	8/2005	Chew et al.
			2005/0187450 A1	8/2005	Chew et al.

(56)

References Cited

U.S. PATENT DOCUMENTS

2005/0187452 A1	8/2005	Petersen et al.	2013/0006076 A1	1/2013	McHale et al.
2005/0187453 A1	8/2005	Petersen et al.	2013/0023775 A1	1/2013	Lamego et al.
2005/0197549 A1	9/2005	Baker, Jr.	2013/0041591 A1	2/2013	Lamego
2005/0197579 A1	9/2005	Baker, Jr.	2013/0045685 A1	2/2013	Kiani
2005/0197793 A1	9/2005	Baker, Jr.	2013/0046204 A1	2/2013	Lamego et al.
2005/0203357 A1	9/2005	Debreczeny et al.	2013/0060108 A1	3/2013	Schurman et al.
2005/0207943 A1	9/2005	Puzey	2013/0060147 A1	3/2013	Welch et al.
2005/0209515 A1*	9/2005	Hockersmith A61B 5/14532 600/316	2013/0079610 A1	3/2013	Al-Ali
2005/0228253 A1	10/2005	Debreczeny	2013/0096405 A1	4/2013	Garfio
2005/0250997 A1	11/2005	Takedo et al.	2013/0096936 A1	4/2013	Sampath et al.
2006/0030764 A1	2/2006	Porges et al.	2013/0109935 A1	5/2013	Al-Ali et al.
2006/0210120 A1	9/2006	Rowe et al.	2013/0162433 A1	6/2013	Muhsin et al.
2006/0211922 A1	9/2006	Al-Ali et al.	2013/0178749 A1	7/2013	Lamego
2006/0211923 A1	9/2006	Al-Ali et al.	2013/0190581 A1	7/2013	Al-Ali et al.
2006/0211924 A1	9/2006	Smith et al.	2013/0197328 A1	8/2013	Diab et al.
2006/0211925 A1	9/2006	Lamego et al.	2013/0211214 A1	8/2013	Olsen
2006/0211932 A1	9/2006	Al-Ali et al.	2013/0243021 A1	9/2013	Siskavich
2006/0226992 A1	10/2006	Al-Ali et al.	2013/0253334 A1	9/2013	Al-Ali et al.
2006/0229509 A1	10/2006	Al-Ali et al.	2013/0267804 A1	10/2013	Al-Ali
2006/0238358 A1	10/2006	Al-Ali et al.	2013/0274571 A1	10/2013	Diab et al.
2006/0241358 A1	10/2006	Al-Ali et al.	2013/0274572 A1	10/2013	Al-Ali et al.
2006/0241363 A1	10/2006	Al-Ali et al.	2013/0296672 A1	11/2013	O'Neil et al.
2006/0264718 A1	11/2006	Ruchti et al.	2013/0296713 A1	11/2013	Al-Ali et al.
2007/0078311 A1	4/2007	Al-Ali et al.	2013/0317327 A1	11/2013	Al-Ali
2007/0093701 A1	4/2007	Myers	2013/0317370 A1	11/2013	Dalvi et al.
2007/0149864 A1	6/2007	Laakkonen	2013/0324808 A1	12/2013	Al-Ali et al.
2007/0129616 A1	7/2007	Rantala	2013/0324817 A1	12/2013	Diab
2007/0185397 A1	8/2007	Govari et al.	2013/0331660 A1	12/2013	Al-Ali et al.
2007/0282478 A1	12/2007	Al-Ali et al.	2013/0331670 A1	12/2013	Kiani
2008/0281174 A1	11/2008	Dietiker	2013/0338461 A1	12/2013	Lamego et al.
2009/0163775 A1	6/2009	Barrett et al.	2014/0012100 A1	1/2014	Al-Ali et al.
2009/0247849 A1	10/2009	McCutcheon et al.	2014/0025306 A1	1/2014	Weber et al.
2009/0247924 A1	10/2009	Lamego et al.	2014/0031650 A1	1/2014	Weber et al.
2009/0247984 A1	10/2009	Lamego et al.	2014/0034353 A1	2/2014	Al-Ali et al.
2009/0275844 A1	11/2009	Al-Ali	2014/0051952 A1	2/2014	Reichgott et al.
2009/0299157 A1	12/2009	Telfort et al.	2014/0051953 A1	2/2014	Lamego et al.
2010/0004518 A1	1/2010	Vo et al.	2014/0051954 A1	2/2014	Al-Ali et al.
2010/0030040 A1	2/2010	Poeze et al.	2014/0058230 A1	2/2014	Abdul-Hafiz et al.
2010/0069725 A1	3/2010	Al-Ali	2014/0066783 A1	3/2014	Kiani et al.
2010/0261979 A1	10/2010	Kiani	2014/0077956 A1	3/2014	Sampath et al.
2010/0317936 A1	12/2010	Al-Ali et al.	2014/0081097 A1	3/2014	Al-Ali et al.
2011/0001605 A1	1/2011	Kiani et al.	2014/0081100 A1	3/2014	Muhsin et al.
2011/0009719 A1	1/2011	Al-Ali et al.	2014/0081175 A1	3/2014	Telfort
2011/0082711 A1	4/2011	Poeze et al.	2014/0094667 A1	4/2014	Schurman et al.
2011/0105854 A1	5/2011	Kiani et al.	2014/0100434 A1	4/2014	Diab et al.
2011/0125060 A1	5/2011	Telfort et al.	2014/0114199 A1	4/2014	Lamego et al.
2011/0172967 A1	7/2011	Al-Ali et al.	2014/0120564 A1	5/2014	Workman et al.
2011/0208015 A1	8/2011	Welch et al.	2014/0121482 A1	5/2014	Merritt et al.
2011/0209915 A1	9/2011	Telfort et al.	2014/0121483 A1	5/2014	Kiani
2011/0213212 A1	9/2011	Al-Ali	2014/0125495 A1	5/2014	Al-Ali
2011/0230733 A1	9/2011	Al-Ali	2014/0127137 A1	5/2014	Bellott et al.
2011/0237911 A1	9/2011	Lamego et al.	2014/0128696 A1	5/2014	Al-Ali
2011/0237969 A1	9/2011	Eckerbom et al.	2014/0128699 A1	5/2014	Al-Ali et al.
2011/0288383 A1	11/2011	Diab	2014/0129702 A1	5/2014	Lamego et al.
2012/0041316 A1	2/2012	Al-Ali et al.	2014/0135588 A1	5/2014	Al-Ali et al.
2012/0046530 A1	2/2012	Al-Ali	2014/0142399 A1	5/2014	Al-Ali et al.
2012/0046557 A1	2/2012	Kiani	2014/0142401 A1	5/2014	Al-Ali et al.
2012/0059267 A1	3/2012	Lamego et al.	2014/0142402 A1	5/2014	Al-Ali et al.
2012/0088984 A1	4/2012	Al-Ali et al.	2014/0163344 A1	6/2014	Al-Ali
2012/0116175 A1	5/2012	Al-Ali et al.	2014/0163402 A1	6/2014	Lamego et al.
2012/0161970 A1	6/2012	Al-Ali	2014/0166076 A1	6/2014	Kiani et al.
2012/0165629 A1	6/2012	Merritt et al.	2014/0171763 A1	6/2014	Diab
2012/0179006 A1	7/2012	Jansen et al.	2014/0180038 A1	6/2014	Kiani
2012/0209082 A1	8/2012	Al-Ali	2014/0180154 A1	6/2014	Sierra et al.
2012/0209084 A1	8/2012	Olsen et al.	2014/0180160 A1	6/2014	Brown et al.
2012/0227739 A1	9/2012	Kiani	2014/0187973 A1	7/2014	Brown et al.
2012/0232359 A1	9/2012	Al-Ali et al.	2014/0194711 A1	7/2014	Al-Ali
2012/0232363 A1	9/2012	Al-Ali et al.	2014/0194766 A1	7/2014	Al-Ali et al.
2012/0265039 A1	10/2012	Kiani	2014/0200420 A1	7/2014	Al-Ali
2012/0283524 A1	11/2012	Kiani et al.	2014/0200422 A1	7/2014	Weber et al.
2012/0286955 A1	11/2012	Welch et al.	2014/0206963 A1	7/2014	Al-Ali
2012/0296178 A1	11/2012	Lamego et al.	2014/0213864 A1	7/2014	Abdul-Hafiz et al.
2012/0319816 A1	12/2012	Al-Ali	2014/0243627 A1	8/2014	Diab et al.
2012/0330112 A1	12/2012	Lamego et al.	2014/0266790 A1	9/2014	Al-Ali et al.
			2014/0275808 A1	9/2014	Poeze et al.
			2014/0275835 A1	9/2014	Lamego et al.
			2014/0275871 A1	9/2014	Lamego et al.
			2014/0275872 A1	9/2014	Merritt et al.
			2014/0275881 A1	9/2014	Lamego et al.

(56)

References Cited

U.S. PATENT DOCUMENTS

2014/0276115 A1 9/2014 Dalvi et al.
 2014/0288400 A1 9/2014 Diab et al.
 2014/0296664 A1 10/2014 Bruinsma et al.
 2014/0303520 A1 10/2014 Telfort et al.
 2014/0309559 A1 10/2014 Telfort et al.
 2014/0316217 A1 10/2014 Purdon et al.
 2014/0316218 A1 10/2014 Purdon et al.
 2014/0316228 A1 10/2014 Blank et al.
 2014/0323825 A1 10/2014 Al-Ali et al.
 2014/0323897 A1 10/2014 Brown et al.
 2014/0323898 A1 10/2014 Purdon et al.
 2014/0330092 A1 11/2014 Al-Ali et al.
 2014/0330098 A1 11/2014 Merritt et al.
 2014/0330099 A1 11/2014 Al-Ali et al.
 2014/0333440 A1 11/2014 Kiani
 2014/0336481 A1 11/2014 Shakespeare et al.
 2014/0343436 A1 11/2014 Kiani
 2014/0357966 A1 12/2014 Al-Ali et al.
 2015/0005600 A1 1/2015 Blank et al.
 2015/0011907 A1 1/2015 Purdon et al.
 2015/0012231 A1 1/2015 Poeze et al.
 2015/0025406 A1 1/2015 Al-Ali
 2015/0032029 A1 1/2015 Al-Ali et al.
 2015/0038859 A1 2/2015 Dalvi et al.
 2015/0045637 A1 2/2015 Dalvi
 2015/0051462 A1 2/2015 Olsen
 2015/0080754 A1 3/2015 Purdon et al.
 2015/0087936 A1 3/2015 Al-Ali et al.
 2015/0094546 A1 4/2015 Al-Ali
 2015/0097701 A1 4/2015 Al-Ali et al.
 2015/0099950 A1 4/2015 Al-Ali et al.
 2015/0099951 A1 4/2015 Al-Ali et al.
 2015/0099955 A1 4/2015 Al-Ali et al.
 2015/0101844 A1 4/2015 Al-Ali et al.
 2015/0106121 A1 4/2015 Muhsin et al.
 2015/0112151 A1 4/2015 Muhsin et al.
 2015/0116076 A1 4/2015 Al-Ali et al.
 2015/0126830 A1 5/2015 Schurman et al.
 2015/0133755 A1 5/2015 Smith et al.
 2015/0141781 A1 5/2015 Weber et al.
 2015/0165312 A1 6/2015 Kiani
 2015/0196237 A1 7/2015 Lamego
 2015/0201874 A1 7/2015 Diab
 2015/0208966 A1 7/2015 Al-Ali
 2015/0216459 A1 8/2015 Al-Ali et al.
 2015/0230755 A1 8/2015 Al-Ali et al.
 2015/0238722 A1 8/2015 Al-Ali
 2015/0245773 A1 9/2015 Lamego et al.
 2015/0245794 A1 9/2015 Al-Ali
 2015/0257689 A1 9/2015 Al-Ali et al.
 2015/0272514 A1 10/2015 Kiani et al.
 2015/0351697 A1 12/2015 Weber et al.
 2015/0351704 A1 12/2015 Kiani et al.
 2015/0359429 A1 12/2015 Al-Ali et al.
 2015/0366472 A1 12/2015 Kiani
 2015/0366507 A1 12/2015 Blank
 2015/0374298 A1 12/2015 Al-Ali et al.
 2015/0380875 A1 12/2015 Coverston et al.
 2016/0000362 A1 1/2016 Diab et al.
 2016/0007930 A1 1/2016 Weber et al.
 2016/0029932 A1 2/2016 Al-Ali
 2016/0029933 A1 2/2016 Al-Ali et al.
 2016/0045118 A1 2/2016 Kiani
 2016/0051205 A1 2/2016 Al-Ali et al.
 2016/0058338 A1 3/2016 Schurman et al.
 2016/0058347 A1 3/2016 Reichgott et al.
 2016/0066823 A1 3/2016 Al-Ali et al.
 2016/0066824 A1 3/2016 Al-Ali et al.
 2016/0066879 A1 3/2016 Telfort et al.
 2016/0072429 A1 3/2016 Kiani et al.
 2016/0073967 A1 3/2016 Lamego
 2016/0081552 A1 3/2016 Wojtczuk et al.
 2016/0095543 A1 4/2016 Telfort et al.
 2016/0095548 A1 4/2016 Al-Ali et al.
 2016/0103598 A1 4/2016 Al-Ali et al.

2016/0113527 A1 4/2016 Al-Ali et al.
 2016/0143548 A1 5/2016 Al-Ali
 2016/0166182 A1 6/2016 Al-Ali
 2016/0166183 A1 6/2016 Poeze et al.
 2016/0166188 A1 6/2016 Bruinsma et al.
 2016/0166210 A1 6/2016 Al-Ali
 2016/0192869 A1 7/2016 Kiani et al.
 2016/0196388 A1 7/2016 Lamego
 2016/0197436 A1 7/2016 Barker et al.
 2016/0213281 A1 7/2016 Eckerbom et al.
 2016/0228043 A1 8/2016 O'Neil et al.
 2016/0233632 A1 8/2016 Scruggs et al.
 2016/0234944 A1 8/2016 Schmidt et al.
 2016/0270735 A1 9/2016 Diab et al.
 2016/0283665 A1 9/2016 Sampath et al.
 2016/0287090 A1 10/2016 Al-Ali et al.
 2016/0287786 A1 10/2016 Kiani
 2016/0296169 A1 10/2016 McHale et al.
 2016/0314260 A1 10/2016 Kiani
 2016/0324486 A1 11/2016 Al-Ali et al.
 2016/0324488 A1 11/2016 Olsen
 2016/0327984 A1 11/2016 Al-Ali et al.
 2016/0328528 A1 11/2016 Al-Ali et al.
 2016/0331332 A1 11/2016 Al-Ali
 2016/0367173 A1 12/2016 Dalvi et al.
 2017/0007134 A1 1/2017 Al-Ali et al.
 2017/0007190 A1 1/2017 Al-Ali et al.
 2017/0007198 A1 1/2017 Al-Ali et al.
 2017/0014084 A1 1/2017 Al-Ali et al.
 2017/0021099 A1 1/2017 Al-Ali et al.
 2017/0027456 A1 2/2017 Kinast et al.
 2017/0042488 A1 2/2017 Muhsin
 2018/0007086 A1 1/2018 Smith
 2018/0132770 A1 5/2018 Lamego

FOREIGN PATENT DOCUMENTS

EP 0 569 670 2/1993
 EP 0 675 540 10/1995
 EP 0 675 541 10/1995
 EP 0469395 B1 2/1996
 EP 0417447 B1 10/1997
 EP 0606356 B1 6/1998
 EP 0734221 B1 7/1998
 EP 0 529 412 11/1998
 EP 1 080 683 3/2001
 EP 1 207 536 5/2002
 EP 1 895 892 5/2010
 EP 2 286 721 2/2011
 EP 2 305 104 4/2011
 EP 2 139 383 2/2013
 EP 2 476 369 10/2014
 JP 61-28172 2/1986
 JP 62-000324 1/1987
 JP 63-275327 11/1988
 JP 64-500495 2/1989
 JP 2-126829 5/1990
 JP 2-145457 12/1990
 JP 03-252604 11/1991
 JP 05-200017 8/1993
 JP 05-207993 8/1993
 JP H06-178776 6/1994
 JP 6-505903 7/1994
 JP 6-237013 8/1994
 JP H07-391 1/1995
 JP H07-171089 7/1995
 JP H07-171090 7/1995
 JP 7-281618 10/1995
 JP 07-325546 12/1995
 JP 09-108203 4/1997
 JP 9-192120 7/1997
 JP 09-308623 12/1997
 JP 10-216112 8/1998
 JP 10-509352 9/1998
 JP 10-269344 A 10/1998
 JP 10-295676 11/1998
 JP 10-305026 11/1998
 JP 11-037932 2/1999
 JP 11-163412 6/1999

(56)

References Cited

FOREIGN PATENT DOCUMENTS

JP	11-164826	6/1999
JP	11-506834	6/1999
JP	11-183377	7/1999
JP	2000-116625	4/2000
JP	2000-199880	7/2000
JP	2001-504256	3/2001
JP	2002-150821	5/2002
JP	2002-516689	6/2002
JP	2002-228579	8/2002
JP	2002-525151	8/2002
JP	2002-315739	10/2002
JP	2002-352609	12/2002
JP	2003-507718	2/2003
JP	2003-084108	3/2003
JP	2003-521985	7/2003
JP	2004-070179	3/2004
JP	2004-173866	6/2004
JP	2004-226277	8/2004
JP	2004-296736	10/2004
JP	2004-532526	10/2004
JP	2004-327760	11/2004
JP	2005-501589	1/2005
JP	2005-253478	9/2005
JP	4879913	12/2011
WO	WO 88/01150	2/1988
WO	WO 88/002020	2/1988
WO	WO 92/16142	10/1992
WO	WO 93/06776	4/1993
WO	WO 1995/05621	2/1995
WO	WO 95/16387	6/1995
WO	WO 96/013208	5/1996
WO	WO 96/41138	12/1996
WO	WO 97/01985	1/1997
WO	WO 97/29678	8/1997
WO	WO 97/029710	8/1997
WO	WO 98/43071	10/1998
WO	WO 00/18290	4/2000
WO	WO 00/42911	7/2000
WO	WO 00/59374	10/2000
WO	WO 01/13790	3/2001
WO	WO 01/30414	5/2001
WO	WO 01/058347	8/2001
WO	WO 02/017780	3/2002
WO	WO 02/026123	4/2002
WO	WO 02/089664	11/2002
WO	WO 03/020129	3/2003
WO	WO 03/068060	8/2003
WO	WO 03/077761	9/2003
WO	WO 04/034898	4/2004
WO	WO 04/038801	5/2004
WO	WO 05/004712	1/2005
WO	WO 05/011488	2/2005
WO	WO 06/017117	2/2006
WO	WO 06/094107	9/2006
WO	WO 06/094108	9/2006
WO	WO 06/094155	9/2006
WO	WO 06/094168	9/2006
WO	WO 06/094169	9/2006
WO	WO 06/094170	9/2006
WO	WO 06/094171	9/2006
WO	WO 06/094279	9/2006
WO	WO 06/115580	11/2006
WO	WO 2006/118654	11/2006
WO	WO 09/013835	1/2009
WO	WO 09/137524	11/2009

OTHER PUBLICATIONS

U.S. Appl. No. 12/082,810, filed Apr. 14, 2008, Al-Ali.
 U.S. Appl. No. 14/148,462, filed Jan. 6, 2014, Al-Ali et al.
 "Medical." 50 Ways to Touch Memory. 3rd ed. Dallas: Dallas Semiconductor Corporation, Aug. 1994: pp. 24-25. Print.

"Application Note 84 Use of Add-Only Memory for Secure Storage of Monetary Equivalent Data," Dallas Semiconductor, Jun. 22, 1999, in 5 pages.

Burritt, Mary F.; Current Analytical Approaches to Measuring Blood Analytes; vol. 36; No. 8(B); 1990.

Dallas Semiconductor Corp: DS2430A Announcement, retrieved Jun. 10, 1998, in 2 pages. <https://web.archive.org/web/19980610045525/http://dalsemi.com/News_Center/New_Products/1996/2430a.html>.

European Exam Report re EPO App. No. 10162402.1, dated Mar. 4, 2013.

European Extended Search Report re EPO App. No. 10162402.1, SR dated Aug. 9, 2010.

European Extended Search Report of European Application No. 12163719.3, dated Jun. 18, 2012, in 6 pages.

Favennec, J.M. "Smart sensors in industry." J. Phys. E: Sci. Instrum. 20(9): Sep. 1987, pp. 1087-1090.

Hall, et al., Jeffrey W.; Near-Infrared Spectrophotometry: A New Dimension in Clinical Chemistry; vol. 38; No. 9; 1992.

Japanese Final Office Action re Amendments re JP Application No. 2007-558249, dated Apr. 17, 2012.

Japanese Office Action re JP Application No. 2007-558249, dated Aug. 28, 2012.

Japanese Office Action re JP Application No. 2007-558249, dated Jul. 13, 2011.

Japanese Office Action re JP Application No. 2007-558249, dated Nov. 8, 2011.

Japanese Office Action re JP Application No. 2007-558245, dated Oct. 25, 2011.

Jones, K.L., et al. "A Protocol for Automatic Sensor Detection and Identification in a Wireless Biodevice Network," IEEE, Jun. 1998, 6 pages.

Kuenstner, et al., J. Todd; Measurement of Hemoglobin in Unlysed Blood by Near-Infrared Spectroscopy; vol. 48; No. 4, 1994.

Manzke, et al., B., Multi Wavelength Pulse Oximetry in the Measurement of Hemoglobin Fractions; vol. 2676, date unknown.

Naumenko, E. K.; Choice of Wavelengths for Stable Determination of Concentrations of Hemoglobin Derivatives from Absorption Spectra of Erythrocytes; vol. 63; No. 1; pp. 60-66 Jan.-Feb. 1996; Original article submitted Nov. 3, 1994.

Patent Cooperation Treaty (PCT) International Search Report; PCT/US 2006/007389; dated Jul. 17, 2006; pp. 1-9.

PCT International Search Report; PCT/US2006/007387; dated Jul. 17, 2006; pp. 1-9.

PCT International Search Report; PCT/US2006/007388; dated Jul. 17, 2006; pp. 1-9.

PCT International Search Report; PCT/US2006/007506; dated Jul. 17, 2006; pp. 1-10.

PCT International Search Report; PCT/US2006/007536; dated Jul. 17, 2006; pp. 1-9.

PCT International Search Report; PCT/US2006/007537; dated Jul. 17, 2006; pp. 1-10.

PCT International Search Report; PCT/US2006/007538; dated Jul. 17, 2006; pp. 1-9.

PCT International Search Report; PCT/US2006/007539; dated Jul. 17, 2006; pp. 1-9.

PCT International Search Report; PCT/US2006/007540; dated Jul. 17, 2006; pp. 1-9.

PCT International Search Report; PCT/US2006/007958; dated Jul. 17, 2006; pp. 1-8.

PCT Report on Patentability of International Application No. PCT/US2008/058327, dated Jun. 30, 2009, in 12 pages.

Schmitt, Joseph M.; Simple Photon Diffusion Analysis of the Effects of Multiple Scattering on Pulse Oximetry; Mar. 14, 1991; revised Aug. 30, 1991.

Schmitt, Joseph M.; Zhou, Guan-Xiong; Miller, Justin, Measurement of Blood Hematocrit by Dual-wavelength Near-IR Photoplethysmography, published May 1992, Proc. SPIE vol. 1641, p. 150-161, Physiological Monitoring and Early Detection Diagnostic Methods, Thomas S. Mang; Ed. (SPIE homepage), in 12 pages.

Schnapp, et al., L.M.; Pulse Oximetry. Uses and Abuses.; Chest 1990; 98; 1244-1250001 10.1378/Chest.98.5.1244.


(56)

References Cited

OTHER PUBLICATIONS

Subramanian, S., et al. "Design for Constraint Violation Detection in Safety-Critical Systems," IEEE, Nov. 1998: pp. 1-8.

* cited by examiner








FIG. 2








FIG. 5




FIG. 6







FIG. 7










FIG. 11A




FIG. 11B




FIG. 11C




FIG. 11D




FIG. 11E




FIG. 11F




FIG. 11G




FIG. 11H

1

**NONINVASIVE MULTI-PARAMETER
PATIENT MONITOR****PRIORITY CLAIM**

The present application is a continuation of U.S. application Ser. No. 14/557,761, filed Dec. 2, 2014, entitled "Noninvasive Multi-Parameter Patient Monitor," which is a continuation of Ser. No. 14/076,556, filed Nov. 11, 2013, entitled "Noninvasive Multi-Parameter Patient Monitor," which is a continuation of U.S. application Ser. No. 13/412,428, filed Mar. 5, 2012, entitled "Noninvasive Multi-Parameter Patient Monitor," which is a continuation of U.S. application Ser. No. 11/366,208, filed Mar. 1, 2006, entitled "Noninvasive Multi-Parameter Patient Monitor," which claims priority benefit under 35 U.S.C. § 119(e) to U.S. Provisional Patent Application Ser. No. 60/657,596, filed Mar. 1, 2005, entitled "Multiple Wavelength Sensor," No. 60/657,281, filed Mar. 1, 2005, entitled "Physiological Parameter Confidence Measure," No. 60/657,268, filed Mar. 1, 2005, entitled "Configurable Physiological Measurement System," and No. 60/657,759, filed Mar. 1, 2005, entitled "Noninvasive Multi-Parameter Patient Monitor." The present application incorporates the foregoing disclosures herein by reference.

**INCORPORATION BY REFERENCE OF
RELATED UTILITY APPLICATIONS**

The present application is related to the following U.S. utility applications:

application Ser. No.	Filing Date	Title
1 11/367,013	Mar. 1, 2006	Multiple Wavelength Sensor Emitters
2 11/366,995	Mar. 1, 2006	Multiple Wavelength Sensor Equalization
3 11/366,209	Mar. 1, 2006	Multiple Wavelength Sensor Substrate
4 11/366,210	Mar. 1, 2006	Multiple Wavelength Sensor Interconnect
5 11/366,833	Mar. 1, 2006	Multiple Wavelength Sensor Attachment
6 11/366,997	Mar. 1, 2006	Multiple Wavelength Sensor Drivers
7 11/367,034	Mar. 1, 2006	Physiological Parameter Confidence Measure
8 11/367,036	Mar. 1, 2006	Configurable Physiological Measurement System
9 11/367,033	Mar. 1, 2006	Noninvasive Multi-Parameter Patient Monitor
10 11/367,014	Mar. 1, 2006	Noninvasive Multi-Parameter Patient Monitor

The present application incorporates the foregoing disclosures herein by reference.

FIELD OF THE DISCLOSURE

The present disclosure relates to the field of noninvasive patient monitors. More specifically, the disclosure relates to monitors displaying measurements derived using signals from optical sensors.

BACKGROUND

Spectroscopy is a common technique for measuring the concentration of organic and some inorganic constituents of

2

a solution. The theoretical basis of this technique is the Beer-Lambert law, which states that the concentration c_i of an absorbent in solution can be determined by the intensity of light transmitted through the solution, knowing the path-length d_{λ} , the intensity of the incident light $I_{0,\lambda}$, and the extinction coefficient $\epsilon_{i,\lambda}$ at a particular wavelength λ . In generalized form, the Beer-Lambert law is expressed as:

$$I_{\lambda} = I_{0,\lambda} e^{-d_{\lambda} \mu_{0,\lambda}} \quad (1)$$

$$\mu_{0,\lambda} = \sum_{i=1}^n \epsilon_{i,\lambda} \cdot c_i \quad (2)$$

where $\mu_{0,\lambda}$ is the bulk absorption coefficient and represents the probability of absorption per unit length. The minimum number of discrete wavelengths that are required to solve Equations 1-2 are the number of significant absorbers that are present in the solution.

A practical application of this technique is pulse oximetry, which utilizes a noninvasive sensor to measure oxygen saturation (SpO_2) and pulse rate. In general, the sensor has light emitting diodes (LEDs) that transmit optical radiation of red and infrared wavelengths into a tissue site and a detector that responds to the intensity of the optical radiation after absorption (e.g., by transmission or transreflectance) by pulsatile arterial blood flowing within the tissue site. Based on this response, a processor determines measurements for SpO_2 , pulse rate, and can output representative plethysmographic waveforms. Thus, "pulse oximetry" as used herein encompasses its broad ordinary meaning known to one of skill in the art, which includes at least those noninvasive procedures for measuring parameters of circulating blood through spectroscopy. Moreover, "plethysmograph" as used herein (commonly referred to as "photoplethysmograph"), encompasses its broad ordinary meaning known to one of skill in the art, which includes at least data representative of a change in the absorption of particular wavelengths of light as a function of the changes in body tissue resulting from pulsing blood.

Pulse oximeters capable of reading through motion induced noise are available from Masimo Corporation ("Masimo") of Irvine, Calif. Moreover, portable and other oximeters capable of reading through motion induced noise are disclosed in at least U.S. Pat. Nos. 6,770,028, 6,658,276, 6,157,850, 6,002,952, and 5,769,785. Read which are owned by Masimo, and are incorporated by reference herein. Such reading through motion oximeters have gained rapid acceptance in a wide variety of medical applications, including surgical wards, intensive care and neonatal units, general wards, home care, physical training, and virtually all types of monitoring scenarios.

SUMMARY

Despite the success of read through motion oximeter systems, there is a need to provide patient monitors capable of displaying multiple physiological parameters, other than or in addition to SpO_2 , plethysmograph waveforms, or pulse rates. For example, in accessing a patient's condition, caregivers often desire knowledge of other blood constituents, including for example, a percent value for arterial carbon monoxide saturation ("HbCO") or a percent value for methemoglobin saturation ("HbMet") or the like. For example, in an embodiment, the display advantageously displays one or more of the following: pulse rate, plethys-

mograph waveform data, perfusion index, values of blood constituents in body tissue, including for example, HbCO, HbMet, total hemoglobin ("Hbt"), arterial oxygen saturation ("SpO₂"), fractional arterial oxygen saturation ("SpaO₂"), or the like. In other embodiments, the monitor may advantageously and accurately determine values for one or more of HbO₂, Hb, blood glucose, water, the presence or absence of therapeutic drugs (aspirin, Dapson, nitrates, or the like) or abusive/recreational drugs (methamphetamine, alcohol, steroids, or the like), concentrations of carbon dioxide ("CO₂") or oxygen ("O"), pH levels, bilirubin, perfusion quality, signal quality or the like. Accordingly, the present disclosure includes a multi-parameter patient monitor capable of determining one or more of the foregoing parameters, other than or in addition to, SpO₂, plethysmograph waveforms, or perfusion quality index.

In an embodiment, the display of a noninvasive multi-parameter patient monitor advantageously includes a plurality of display modes enabling more parameter data to be displayed than the available physical display area or real estate. In an embodiment, a user may cycle different parameter values through an area of the display common to both parameters even when one parameter is shifted, through, for example, actuation of a user input key. The patient monitor may also display different parameters as color-coded. For example, when the following measured parameters are within "normal" ranges, SpO₂ may be displayed red, pulse rate (BPM) may be displayed green, HbCO may be displayed orange, HbMet may be displayed blue, or the like. In an embodiment, measured values of SpO₂ may be displayed in white, BPM may be displayed in yellow green or aquamarine, P_{IT}™ may be displayed in violet, Hbt may be displayed in grass green, HbMet may be displayed in blue or light blue, HbCO may be displayed in orange, and SpaO₂ may be displayed in electric blue.

Moreover, parameter trend data may also be displayed using the same or similar color coding, especially when multiple trends are displayed on one or more display graphs. In addition, more coarse or gross parameter indications may be displayed for quick reference to indicate to a caregiver whether any of a variety of monitored parameters, such as, for example, SpO₂, HbCO or HbMet is within acceptable ranges. The monitor may advantageously include additional display information, such as, for example, parametric displays where one parameter is displayed as a function of another, three dimensional displays (for example, extending a parametric display along time or an additional parameter), directional indicators predicting where a parameter is likely heading or reporting a general direction a parameters has been trending, or the like.

In addition to the foregoing, caregivers often desire to more closely monitor parameters that are close to, approaching, or beyond normal safe thresholds. In an embodiment, the patient monitor provides an indication that the caregiver should change display modes to view more critical monitored parameters. In alternative embodiments, the patient monitor automatically changes display modes to show parameters moving closer to or beyond normal thresholds.

In an embodiment, the patient monitor includes an audible or visual indication of a type of sensor communicating with the monitor. For example, the monitor may determine how many wavelengths a particular attached sensor will emit through communication with memory devices associated with the attached sensor or cable.

Additional embodiments include audio or visual alarms for each of multiple monitored parameters, combinations of parameters, an indication of perfusion in the tissue of the

measurement site, an indication of the confidence the signal processing has in its output measurements, or the like.

For purposes of summarization, certain aspects, advantages and novel features are described herein. Of course, it is to be understood that not necessarily all such aspects, advantages or features need to be present in any particular embodiment.

BRIEF DESCRIPTION OF THE DRAWINGS

The drawings and the associated descriptions are provided to illustrate embodiments of the disclosure and not to limit the scope of the claims.

FIG. 1 illustrates a block diagram of an exemplary embodiment of a patient monitoring system including a sensor and a multi-parameter patient monitor.

FIG. 2 illustrates a top elevation view of an exemplary handheld noninvasive multi-parameter patient monitor capable of displaying at least HbCO, such as, for example, the patient monitor of FIG. 1.

FIG. 3 illustrates an exemplary display of the patient monitor of FIG. 2.

FIG. 4 illustrates the display of FIG. 3 showing measured values of SpO₂, BPM, perfusion, and type of sensor according to an exemplary embodiment of the patient monitor of FIG. 1.

FIG. 5 illustrates the display of FIG. 3 showing measured values of HbCO, perfusion, and type of sensor according to an exemplary embodiment of the patient monitor of FIG. 1.

FIG. 6 illustrates the display of FIG. 3 showing measured values of SpO₂, HbCO, BPM, perfusion, and type of sensor, according to an exemplary embodiment of the patient monitor of FIG. 1.

FIG. 7 illustrates a top elevation view of an exemplary handheld noninvasive multi-parameter patient monitor capable of displaying at least HbCO and HbMet, such as, for example, the patient monitor of FIG. 1.

FIG. 8 illustrates an exemplary display of the patient monitor of FIG. 7.

FIG. 9 illustrates the display of FIG. 8 showing measured values of SpO₂, BPM, HbCO, HbMet, and type of sensor according to an exemplary embodiment of the patient monitor of FIG. 1.

FIG. 10 illustrates the display of FIG. 8 showing measured values of HbCO, HbMet, and type of sensor according to an exemplary embodiment of the patient monitor of FIG. 1.

FIG. 11A illustrates a perspective view of an exemplary noninvasive multi-parameter patient monitor such as, for example, the patient monitor of FIG. 1.

FIGS. 11B-11H illustrate display screens of the patient monitor of FIG. 11A.

DETAILED DESCRIPTION

Embodiments of the present disclosure include a portable or other multi-parameter patient monitor capable of determining multiple physiological parameters from one or more signals output from one or more light sensitive detectors capable of detecting light attenuated by body tissue carrying pulsing blood. For example, in an embodiment, the monitor advantageously and accurately determines a wide variety of physiological parameters or other calculations as discussed above.

In an embodiment, the display of patient monitor advantageously includes a plurality of display modes enabling more parameter data to be displayed than the available

physical display real estate. For example, the patient monitor may include one or more user input keys capable of toggling through measurement data. In an embodiment, the displays include mode indicators providing caregivers easily identifiable visual queues, such as LED's, text, icons, or other indicia providing readily identifiable queues as to which parameter is being displayed. In an embodiment, the display may shift, may be parameter color-coded, or the like to further ensure quick comprehension of which measured parameter is the displayed parameter. For example, in an embodiment, the monitor displays SpO_2 in white, pulse rate (BPM) in green, HbCO in orange, and HbMet in blue when the respective measured parameter is within a "normal" range.

In an embodiment, the patient monitor provides an indication that the caregiver should change display modes to view more critical or time sensitive measured parameters, specific caregiver selected parameters, or the like. For example, the patient monitor may advantageously sound audio or visual alarms that alert the caregiver to particular one or more of worsening parameters, parameters changing in a predetermined pattern or rate, parameters stabilizing below user defined or safe thresholds, caregiver selected parameters, or the like. The monitor may also use alerts that provide audio or visual indications of the severity of the condition, severity of the change, or the like. In alternative embodiments, the patient monitor may automatically change display modes when a particular parameter crosses one or more thresholds. For example, a patient monitor may be displaying a first parameter, such as a plethysmograph, and upon determining measurements indicating that HbMet is trending toward an alarm condition, the monitor may automatically switch from displaying the first parameter to the alarming parameter, or in this case, a trend of the alarming parameter.

In an embodiment, a switch is provided to allow a user to switch displays to view an alarming measurement. In an embodiment, during an alarm condition, a parameter display may switch to a trend graph in the same or different color, line weight, flash, flash rate, intensity, size, or the like.

The patient monitor may also include one or more displays capable of displaying trend data for any one or more of the monitored or derived patient parameters. For example, the trend data may be displayed in graph form, may include multiple trend lines, each representing a different monitored or derived patient parameter. Moreover, each trend line may be color-coded to facilitate quick comprehension of which trend line represents which measured parameter. However, an artisan will recognize from the disclosure herein a large number of identification techniques including color-coding, identifying text, or the like. Additionally, user input may toggle displayed trend data, may select which parameters to display simultaneously, or the like.

In an embodiment, the patient monitor includes an audible or visual indication of a type of sensor communicating with the monitor. For example, the patient monitor may provide a particular audio or visual indication, such as a beep, LED activation, graphic activation, text messages, voice messages, or the like, to indicate communication with or connection to an approved sensor, patient cable, combination, or the like. In an embodiment, the indication may change based on the manufacturer, type of sensor recognized or not recognized, type of patient, type of physiological parameters measurable with the attached sensor, or the like. Additional embodiments include an indication of perfusion in the tissue

of the measurement site and an indication of the confidence the signal processing has in its output measurements or input signal quality.

To facilitate an understanding of the disclosure, the remainder of the description references exemplary embodiments illustrated in the drawings. Moreover, in this application, reference is made to many blood parameters. Some references that have common shorthand designations are referenced through such shorthand designations. For example, as used herein, HbCO designates carboxyhemoglobin, HbMet designates methemoglobin, and Hbt designates total hemoglobin. Other shorthand designations such as COHb, MetHb, and tHb are also common in the art for these same constituents. These constituents are generally reported herein in terms of a percentage, often referred to as saturation, relative concentration or fractional saturation. Total hemoglobin is generally reported as a concentration in g/dL. The use of the particular shorthand designators presented in this application does not restrict the term to any particular manner in which the designated constituent is reported.

FIG. 1 illustrates a block diagram of an exemplary embodiment of a patient monitoring system 100. As shown in FIG. 1, the system 100 includes a patient monitor 102 comprising a processing board 104 and a host instrument 108. The processing board 104 communicates with a sensor 106 to receive one or more intensity signal(s) indicative of one or more parameters of tissue of a patient. The processing board 104 also communicates with a host instrument 108 to display determined values calculated using the one or more intensity signals. According to an embodiment, the processing board 104 comprises processing circuitry arranged on one or more printed circuit boards capable of installation into the monitor 102, or capable of being distributed as some or all of one or more OEM components for a wide variety of host instruments monitoring a wide variety of patient information. In an embodiment, the processing board 104 comprises a sensor interface 110, a digital signal processor and signal extractor ("DSP" or "processor") 112, and an instrument manager 114. In general, the sensor interface 110 converts digital control signals into analog drive signals capable of driving sensor emitters, and converts composite analog intensity signal(s) from light sensitive detectors into digital data.

In an embodiment, the sensor interface 110 manages communication with external computing devices. For example, in an embodiment, a multipurpose sensor port (or input/output port) is capable of connecting to the sensor 106 or alternatively connecting to a computing device, such as a personal computer, a PDA, additional monitoring equipment or networks, or the like. When connected to the computing device, the processing board 104 may upload various stored data for, for example, off-line analysis and diagnosis. The stored data may comprise trend data for any one or more of the measured parameter data, plethysmograph waveform data acoustic sound waveform, or the like. Moreover, the processing board 104 may advantageously download from the computing device various upgrades or executable programs, may perform diagnosis on the hardware or software of the monitor 102. In addition, the processing board 104 may advantageously be used to view and examine patient data, including raw data, at or away from a monitoring site, through data uploads/downloads, or network connections, combinations, or the like, such as for customer support purposes including software maintenance, customer technical support, and the like. Upgradable sensor ports are disclosed in copending U.S. application Ser. No. 10/898,

680, filed on Jul. 23, 2004, titled "Multipurpose Sensor Port," incorporated by reference herein.

As shown in FIG. 1, the digital data is output to the DSP 112. According to an embodiment, the DSP 112 comprises a processing device based on the Super Harvard ARCHitecture ("SHARC"), such as those commercially available from Analog Devices. However, a skilled artisan will recognize from the disclosure herein that the DSP 112 can comprise a wide variety of data and/or signal processors capable of executing programs for determining physiological parameters from input data. In particular, the DSP 112 includes program instructions capable of receiving multiple channels of data related to one or more intensity signals representative of the absorption (from transmissive or reflective sensor systems) of a plurality of wavelengths of emitted light by body tissue. In an embodiment, the DSP 112 accepts data related to the absorption of eight (8) wavelengths of light, although an artisan will recognize from the disclosure herein that the data can be related to the absorption of two (2) to sixteen (16) or more wavelengths.

FIG. 1 also shows the processing board 104 including the instrument manager 114. According to an embodiment, the instrument manager 114 may comprise one or more microcontrollers controlling system management, including, for example, communications of calculated parameter data and the like to the host instrument 108. The instrument manager 114 may also act as a watchdog circuit by, for example, monitoring the activity of the DSP 112 and resetting it when appropriate.

The sensor 106 may comprise a reusable clip-type sensor, a disposable adhesive-type sensor, a combination sensor having reusable and disposable components, or the like. Moreover, an artisan will recognize from the disclosure herein that the sensor 106 can also comprise mechanical structures, adhesive or other tape structures, Velcro wraps or combination structures specialized for the type of patient, type of monitoring, type of monitor, or the like. In an embodiment, the sensor 106 provides data to the board 104 and vice versa through, for example, a patient cable. An artisan will also recognize from the disclosure herein that such communication can be wireless, over public or private networks or computing systems or devices, or the like.

As shown in FIG. 1, the sensor 106 includes a plurality of emitters 116 irradiating the body tissue 118 with differing wavelengths of light, and one or more detectors 120 capable of detecting the light after attenuation by the tissue 118. In an embodiment, the emitters 116 comprise a matrix of eight (8) emission devices mounted on a flexible substrate, the emission devices being capable of emitting eight (8) differing wavelengths of light. In other embodiments, the emitters 116 may comprise twelve (12) or sixteen (16) emitters, although other numbers of emitters are contemplated, including two (2) or more emitters. As shown in FIG. 1, the sensor 106 may include other electrical components such as, for example, a memory device 122 comprising an EPROM, EEPROM, ROM, RAM, microcontroller, combinations of the same, or the like. In an embodiment, other sensor components may include a temperature determination device 123 or other mechanisms for, for example, determining real-time emission wavelengths of the emitters 116.

The memory 122 may advantageously store some or all of a wide variety data and information, including, for example, information on the type or operation of the sensor 106; type or identification of sensor buyer or distributor or groups of buyer or distributors, sensor manufacturer information, sensor characteristics including the number of emitting devices, the number of emission wavelengths, data relating to emis-

sion centroids, data relating to a change in emission characteristics based on varying temperature, history of the sensor temperature, current, or voltage, emitter specifications, emitter drive requirements, demodulation data, calculation mode data, the parameters for which the sensor is capable of supplying sufficient measurement data (e.g., HpCO, HpMet, HbT, or the like), calibration or parameter coefficient data, software such as scripts, executable code, or the like, sensor electronic elements, whether the sensor is a disposable, reusable, multi-site, partially reusable, partially disposable sensor, whether it is an adhesive or non-adhesive sensor, whether the sensor is a reflectance, transmittance, or transreflectance sensor, whether the sensor is a finger, hand, foot, forehead, or ear sensor, whether the sensor is a stereo sensor or a two-headed sensor, sensor life data indicating whether some or all sensor components have expired and should be replaced, encryption information, keys, indexes to keys or hash functions, or the like, monitor or algorithm upgrade instructions or data, some or all of parameter equations, information about the patient, age, sex, medications, and other information that may be useful for the accuracy or alarm settings and sensitivities, trend history, alarm history, or the like. In an embodiment, the monitor may advantageously store data on the memory device, including, for example, measured trending data for any number of parameters for any number of patients, or the like, sensor use or expiration calculations, sensor history, or the like.

FIG. 1 also shows the patient monitor 102 including the host instrument 108. In an embodiment, the host instrument 108 communicates with the board 104 to receive signals indicative of the physiological parameter information calculated by the DSP 112. The host instrument 108 preferably includes one or more display devices 124 capable of displaying indicia representative of the calculated physiological parameters of the tissue 118 at the measurement site. In an embodiment, the host instrument 108 may advantageously comprise a handheld housing capable of displaying one or more of a pulse rate, plethysmograph data, perfusion quality such as a perfusion quality index ("PITM"), signal or measurement quality ("SQ"), values of blood constituents in body tissue, including for example, SpO₂, HbCO, HbMet, Hbt, or the like. In other embodiments, the host instrument 108 is capable of displaying values for one or more of Hbt, Hb, blood glucose, bilirubin, or the like. The host instrument 108 may be capable of storing or displaying historical or trending data related to one or more of the measured values, combinations of the measured values, plethysmograph data, or the like. The host instrument 108 also includes an audio indicator 126 and user input device 128, such as, for example, a keypad, touch screen, pointing device, voice recognition device, or the like.

In still additional embodiments, the host instrument 108 includes audio or visual alarms that alert caregivers that one or more physiological parameters are falling below predetermined safe thresholds. The host instrument 108 may include indications of the confidence a caregiver should have in the displayed data. In a further embodiment, the host instrument 108 may advantageously include circuitry capable of determining the expiration or overuse of components of the sensor 106, including, for example, reusable elements, disposable elements, or combinations of the same.

Although described in terms of certain embodiments, other embodiments or combination of embodiments will be apparent to those of ordinary skill in the art from the disclosure herein. For example, the monitor 102 may comprise one or more monitoring systems monitoring param-

eters, such as, for example, vital signs, blood pressure, ECG or EKG, respiration, glucose, bilirubin, or the like. Such systems may combine other information with intensity-derived information to influence diagnosis or device operation. Moreover, the monitor **102** may advantageously include an audio system, preferably comprising a high quality audio processor and high quality speakers to provide for voiced alarms, messaging, or the like. In an embodiment, the monitor **102** may advantageously include an audio out jack, conventional audio jacks, headphone jacks, or the like, such that any of the display information disclosed herein may be audiblized for a listener. For example, the monitor **102** may include an audible transducer input (such as a microphone, piezoelectric sensor, or the like) for collecting one or more of heart sounds, lung sounds, trachea sounds, or other body sounds and such sounds may be reproduced through the audio system and output from the monitor **102**. Also, wired or wireless communications (such as Bluetooth or WiFi, including IEEE 801.11a, b, or g), mobile communications, combinations of the same, or the like, may be used to transmit the audio output to other audio transducers separate from the monitor **102**.

For example, patterns or changes in the continuous non-invasive monitoring of intensity-derived information may cause the activation of other vital sign measurement devices, such as, for example, blood pressure cuffs.

FIG. 2 illustrates a perspective view of an exemplary handheld noninvasive multi-parameter patient monitor **200**, such as, for example, the patient monitor **102** of FIG. 1. Patient monitors **200** exhibiting combinations of many of the features described herein are advantageously commercially available from Masimo under the brand name “Rad 57c.” As shown in FIG. 2, the monitor **200** includes a patient cable connector **202** capable of mechanical mating with a patient cable to establish communication between the processing board **104** and the sensor **106**. In an embodiment, the connector **202** comprises a multipurpose cable connector such as that disclosed in the incorporated U.S. application Ser. No. 10/898,680, titled “Multipurpose Sensor Port,” disclosing communication between the processing board **104** and an external computing device.

The monitor **202** also comprises a HbCO indicator **204** advantageously providing a visual queue that a HbCO capable sensor is properly connected through the connector **202**. For example, the HbCO indicator **204** may advantageously activate when a sensor is connected that communicates sufficient information to determine HbCO, such as, for example, a sensor capable of emitting sufficient different wavelengths of light, a sensor storing sufficient data on the memory **122**, a sensor having appropriate encryption data or key, combinations of the same, or the like. For example, in an embodiment, the processor **112** may receive information from a memory **122** indicating a number of available LED wavelengths for the attached sensor. Based on the number of wavelengths, or other information stored on the memory **122**, the processor **112** may determine whether an HbCO-ready sensor has been attached to the monitor **200**. An artisan will also recognize from the disclosure herein that the HbCO indicator **204** may advantageously comprise a HbMet indicator, Hbt indicator, or the like, which activates to a predetermined color associated with a parameter, or any color, or deactivates the same, to convey a type of attached sensor. Moreover, the artisan will recognize from the disclosure herein other parameters that may use other sensor components and the monitor **200** may include indicators capable of indicating communication with those types of sensors.

In an embodiment, the monitor **200** may also audibly indicate the type of sensor connected. For example, the monitor **200** may emit predetermined number or frequency of beeps associated with recognition of a particular sensor, a particular manufacturer, failure to recognize the sensor, or the like. Moreover, the sensor type may be indicative of the componentry, such as, for example, whether the sensor produces sufficient data for the determination of HbCO, HbMet, Hbt and SpO₂, SpO₂ only, SpO₂ and HbMet, any combination of the foregoing or other parameters, or the like. Additionally, the sensor type may be indicative of specific sensors designed for a type of patient, type of patient tissue, or the like. In other embodiments, the monitor **200** may announce the type of connector through speaker **236**.

An artisan will also recognize from the disclosure herein that other mechanical (such as keys), electrical, or combination devices may inform the monitor **202** of the type of attached sensor. In an embodiment, the processor **112** also may select to drive less emitters that are currently available, such as, for example, in the presence of low noise and when power consumption is an issue.

The monitor **202** also comprises a multi-mode display **206** capable of displaying, for example, measurements of SpO₂ and HbCO (or alternatively, HbMet). In an embodiment, the display **206** has insufficient space or display real estate to display the many parameters capable of being measured by the monitor **200**. Thus, the multi-mode display **206** may advantageously cycle through two or more measured parameters in an area common to both parameters even when shifted. In such embodiments, the monitor **200** may also advantageously include parameter indicators **208**, **210**, providing additional visual queues as to which parameter is currently displayed. In an embodiment, the display may also cycle colors, flash rates, or other audio or visual queues providing readily identifiable information as to which measured parameter is displayed. For example, when the multi-mode display **206** displays measured values of SpO₂ that are normal, the numbers may advantageously appear in green, while normal measured values of HbCO may advantageously appear in orange, and normal measured values of HbMet may appear in blue. Moreover, in an embodiment, the display **206** flashes at a predefined rate when searching for saturation and at another predefined rate when a signal quality is below a predetermined threshold.

The monitor **202** also comprises a HbCO bar **212** where in an embodiment a plurality of LED's activate from a bottom toward a top such that the bar “fills” to a level proportional to the measured value. For example, the bar **212** is lowest when the dangers from carbon monoxide poisoning are the least, and highest when the dangers are the greatest. The bar **212** includes indicia **214** that provide an indication of the severity of carbon monoxide saturation in a patient's blood. As shown in FIG. 2, the bar **212** and the indicia **214** continuously indicate the concentration of HbCO in about 5% increments. The indicia **214** indicate a measurement of HbCO saturation percentage between about 0 and about 50% with a granularity of about 5%. However, an artisan will also recognize from the disclosure herein a wide variety of ranges and granularities could be used, the indicia **214** could be electronically displayed in order to straightforwardly increase or decrease resolution, or the like. For example, HbCO may advantageously be displayed with greater resolution than \pm about %5 in a lower portion of the scale. For example, an HbCO bar may advantageously include a scale of about <3%, about 6%, about 9%, about 12%, about 15%, about 20%, about 25%, about 30%, about 35%, and about >40%.

As is known in the art, carbon monoxide in the blood can lead to serious medical issues. For example and depending upon the particular physiology of a patient, about 10% carbon monoxide saturation can lead to headaches, about 20% can lead to throbbing headaches, or dyspnea on exertion, about 30% can lead to impaired judgment, nausea, dizziness and/or vomiting, visual disturbance, or fatigue, about 40% can lead to confusion and syncope, and about 50% and above can lead to comas, seizures, respiratory failure and even death.

In an embodiment, the bar **212** is the same or similar color as the multi-mode display **206** when displaying HbCO. In other embodiments, the bar **212** is lowest and green when the dangers from carbon monoxide poisoning are the least, and highest and red when the dangers are the greatest. In an embodiment, as HbCO increases, the entire bar **212** may advantageously change color, such as, for example, from green to red, to provide a clear indication of deepening severity of the condition. In other embodiments, the bar **212** may advantageously blink or flash, an audio alarm may beep or provide a continuation or rise in pitch or volume, or the like to alert a caregiver of deepening severity. Moreover, straightforward to complex alarm rules may be implemented to reduce false alarms based on, for example, knowledge of the physiological limitations on the rate of change in HbCO or the like.

Additionally, the monitor **200** may be capable of storing and outputting historical parameter data, display trend traces or data, or the like. Although the foregoing bar **212** has been described in terms of certain preferred embodiments, other embodiments will be apparent to those of ordinary skill in the art from the disclosure herein.

FIG. 2 also shows the monitor **200** including a pulse display **216** displaying measured pulse rate in beats per minute ("BPM"). In an embodiment, the display **212** flashes when searching for a pulse. The pulse display **216** advantageously displays measured pulse rates from about zero (0) to about two hundred and forty (240) BPM. Moreover, when the measured pulse rates are considered normal, the pulse display **216** is advantageously green. Similar to other displays associated with the monitor **200**, the pulse display **216** may employ a variety of color changes, audio alarms, or combinations of the same to indicate measured BPM below predetermined safe thresholds. In an embodiment, the pulse rate display **216** displays the measured pulse rate during the display of SpO₂ and displays message data during the display of other parameters. For example, during the display of HbCO, the display **216** may advantageously display the term "CO." In an embodiment, the display of the message data may be in the same or similar color as the other displays. For example, in an embodiment, the multi-mode display **206**, the bar **212**, and the pulse display **216** may all display data or messages in orange when the multi-mode display **206** displays measured HbCO values.

FIG. 2 also illustrates the monitor **200** comprising user input keys **218**, including a HbCO button **220**, mode/enter button **222**, next button **224**, power on/off button **226**, up/down button **228**, and alarm silence button **230**. In an embodiment, activation of the HbCO button **220** toggles the measured value displayed in the multi-mode display **206**. For example, activation of the HbCO button **220** toggles the multi-mode display **206** from displaying measured values of SpO₂ to HbCO for about ten (10) seconds. Activation of the mode/enter button **222** or the next button **224** during the ten (10) second period returns the multi-mode display **206** back to SpO₂. A skilled artisan will also recognize that activation of the HbCO button **220** may advantageously toggle through

a plurality of measured values, and that such values may be displayed for short segments and then return to SpO₂, may remain displayed until further activation of the button **220**, or the like.

Activation of the mode/enter button **222** cycles through various setup menus allowing a caregiver to select or activate certain entries within the menu setup system, including alarm threshold customizations, or the like. Activation of the next button **224** can move through setup options within the menu setup system and in an embodiment is not active during normal patient monitoring. For example, a caregiver may activate the mode/enter button **222** and the next button **224** to specify high and low alarm thresholds for one or more of the measured parameters, to specify device sensitivity, trend settings, display customizations, color code parameters, or the like. In an embodiment, the high alarm setting for SpO₂ can range from about two percent (2%) to about one hundred percent (100%) with a granularity of about one percent (1%). The low alarm setting for SpO₂ can range from about one percent (1%) to about one hundred percent (100%) with a granularity of about one percent (1%). Moreover, the high alarm setting for pulse rate can range from about thirty (30) BPM to about two hundred and forty (240) BPM with a granularity of about five (5) BPM. The low alarm setting for pulse rate can range from about twenty five (25) BPM to about two hundred and thirty five (235) BPM with a granularity of about five (5) BPM. Other high and low ranges for other measured parameters will be apparent to one of ordinary skill in the art from the disclosure herein.

In a further embodiment, a caregiver may activate the mode/enter button **222** and the next button **224** to specify device sensitivity, such as, for example, device averaging times, probe off detection, whether to enable fast saturation calculations, or the like. Various embodiments of fast saturation calculations are disclosed in U.S. patent application Ser. No. 10/213,270, filed Aug. 5, 2002, titled "Variable Indication Estimator" and incorporated by reference herein. Using the menus, a caregiver may also advantageously enter appropriate information governing trend collection on one or more of the measured parameters, input signals, or the like.

FIG. 2 also shows the power on/off button **226**. Activation of the power on/off button **226** activates and deactivates the monitor **200**. In an embodiment, press-and-hold activation for about two (2) seconds shuts the monitor **200** off. In an additional embodiment, activation of the on/off button **226** advantageously initiates detection of a type of attached sensor. For example, activation of the on/off button **226** may advantageously cause the monitor **200** to read information from a memory on an attached sensor and determine whether sufficient wavelengths exist on the sensor to determine one or more the physiological parameters discussed in the foregoing.

An artisan will recognize from the disclosure herein that the on/off button **226** may advantageously cause an electronic determination of whether to operate in at powers consisted with the U.S. (60 Hz) or another nationality (50 Hz). In an embodiment, such automatic determination and switching is removed from the monitor **200** in order to reduce a likelihood of problematic interfering crosstalk caused by such power switching devices.

Activation of the up/down button **228** may advantageously adjust the volume of the pulse beep tone. Additionally, activation of the up/down button **228** within the menu setup system, causes the selection of values with various menu options.

Moreover, activation of the alarm silence button **230** temporarily silences audio alarms for a predetermined period, such as, for example, about one hundred and twenty (120) seconds. A second activation of the alarm silence button **230** mutes (suspends) the alarm indefinitely, while a third activation returns the monitor **200** to standard alarm monitoring. FIG. 2 also shows the alarm silence button **230** includes an alarm silenced indicator **232**. The alarm silenced indicator **232** may advantageously flash to indicate one or more alarms are temporarily silenced, may illuminate solid to indicate the alarms have been muted, or the like. Moreover, an artisan will recognize from the disclosure herein a wide variety of alarm silencing methodologies.

The monitor **202** also includes a battery level indicator **234** indicating remaining battery life. In the illustrated embodiment, four LED's indicate the status of the battery by incrementally deactivating to indicate proportionally decreasing battery life. In an embodiment, the four LED's may also change color as the battery charge decreases, and the final LED may begin to flash to indicate that the caregiver should replace the batteries.

FIG. 2 also shows the monitor **202** including an audio transducer or speaker **236**. The speaker **236** advantageously provides audible indications of alarm conditions, pulse tone and feedback for key-presses, or the like. Moreover, the monitor **202** includes a low signal quality indicator ("SQ" or "SIQ™") **238**. The signal IQ indicator **238** activates to inform a caregiver that a measured value of the quality of the incoming signal is below predetermined threshold values. For example, in an embodiment, the measured value for signal IQ is at least partially based on an evaluation of the plethysmograph data's correspondence to predetermined models or characteristics of physiological signals. In an embodiment, the signal IQ indicator **238** output may be associated with the displayed parameter. For example, the output may be associated with one threshold for the display of SpO₂ and another for the display of other parameter data.

The monitor **202** also comprises a perfusion quality index ("PI™") bar **240** (which quantifies the measure of perfusion of the patient) where in an embodiment a plurality of LED's activate from a bottom toward a top such that the bar "fills" to a level proportional to the measured value. In one embodiment, the PI™ bar **240** shows a static value of perfusion for a given time period, such as, for example, one or more pulses. In another embodiment, or functional setting, the PI™ bar **240** may advantageously pulse with a pulse rate, may hold the last reading and optionally fade until the next reading, may indicate historical readings through colors or fades, or the like. Additionally, the PI™ bar **240** may advantageously change colors, flash, increasingly flash, or the like to indicate worsening measured values of perfusion.

The PI™ bar **240** can be used to simply indicate inappropriate occlusion due, for example, to improper attachment of the sensor **106**. The PI™ bar **240** can also be used as a diagnostic tool during low perfusion for the accurate prediction of illness severity, especially in neonates. Moreover, the rate of change in the PI™ bar **240** can be indicative of blood loss, sleep arousal, severe hypertension, pain management, the presence or absence of drugs, or the like. According to one embodiment, the PI™ bar **240** values may comprise a measurement of the signal strength of the arterial pulse as a percentage of the total signal received. For example, in one preferred embodiment, the alternating portion of at least one intensity signal from the sensor **106** may advantageously be divided by the static portion of the signal.

For example, an infrared intensity signal may advantageously be used as it is less subjective to noise.

In an embodiment, a measurement below about 1.25% may indicate medical situations in need of caregiver attention, specifically in monitored neonates. Because of the relevance of about 1.25%, the PI™ bar **240** may advantageously include level indicia **242** where the indicia **242** swap sides of the PI™ bar **240**, thus highlighting any readings below about that threshold. Moreover, behavior of the PI™ bar **240**, as discussed above, may advantageously draw attention to monitored values below such a threshold.

As discussed above, the monitor **200** may include output functionality that outputs, for example, trend perfusion data, such that a caregiver can monitor measured values of perfusion over time. Alternatively or additionally, the monitor **200** may display historical trace data on an appropriate display indicating the measured values of perfusion over time. In an embodiment, the trend data is uploaded to an external computing device through, for example, the multi-purpose sensor connector **202** or other input output systems such as USB, serial or parallel ports or the like.

The monitor **200** also includes an alarm indicator **244** capable of providing visual queues of the status of one or more of the measured parameters. For example, the alarm indicator **244** may advantageously be green when all of the measured parameters are within normal conditions, may gradually fade to red, may flash, increasing flash, or the like, as one or more of the measured values approaches or passes predetermined thresholds. In an embodiment, the alarm indicator **244** activates when any parameter falls below an associated threshold, thereby advantageously informing a caregiver that perhaps a nondisplayed parameters is at an alarm condition. In another embodiment, the alarm indicator **244** may indicate the status of the parameter displayed on the multi-mode display **206**. In an embodiment, the speaker **236** may sound in conjunction with and/or in addition to the indicator **244**. Moreover, in an embodiment, an alarming parameter may automatically be displayed, may be emphasized, flashed, colored, combinations of the same or the like to draw a user's attention to the alarming parameter.

Although the foregoing invention has been described in terms of certain preferred embodiments, other embodiments will be apparent to those of ordinary skill in the art from the disclosure herein.

FIG. 3 illustrates an exemplary display of the patient monitor **200**. As shown in FIG. 3, the display includes the multi-mode display **206**, the pulse rate display **216**, parameter indicators **208**, **210**, the HbCO bar **212** and indicator **204**, the PI™ bar **240**, and the alarm indicator **244**. In an embodiment, the multi-mode display **206** and the pulse rate display **216** each comprise a plurality of seven segment displays **302** capable of displaying alpha-numeric information. As disclosed in the foregoing, the exemplary display may advantageously include color-coded parameter displays. Moreover, the exemplary display may include color progressions, flashing, flashing progressions, audible alarms, audible progressions, or the like, indicating worsening measured values of physiological data. In addition, in an embodiment, some or all of the displays may flash at a first rate to indicate attempts to acquire data when actual measured values are unavailable. Moreover, some or all of the display may flash at a second rate to indicate low signal quality where confidence is decreasing that the measured values reflect actual physiological conditions.

FIG. 4 illustrates the display of FIG. 3 showing measured values of SpO₂, BPM, perfusion, and type of sensor, according to an exemplary embodiment of the patient monitor of

15

FIG. 1. As shown in FIG. 4, the multi-mode display **206** is displaying a percentage value of SpO₂, and the pulse rate display **216** is displaying a pulse rate in beats per minute. Accordingly, the parameter indicator **210** is activated to confirm the display of measured values of SpO₂. As disclosed in the foregoing, in an embodiment, the multi-mode display **206** is red, indicating blood oxygen measurements while the pulse rate display **216** is green, indicating normal values of a patient's pulse.

FIG. 4 also shows the PITTM bar **240** almost fully activated, representing good perfusion. In addition, the HbCO indicator **204** is showing communication with a sensor producing insufficient data to determine measured values of additional parameters, such as, HbCO. In an embodiment, such sensors may comprise sensors capable of emitting light at about two (2) different wavelengths, may comprise sensors with insufficient data stored on a memory associated therewith, or the like.

FIG. 5 illustrates the display of FIG. 3 showing measured values of HbCO, perfusion, and type of sensor, according to an exemplary embodiment of the patient monitor of FIG. 1. As shown in FIG. 5, the multi-mode display **206** is displaying a percentage value of HbCO, and the pulse rate display **216** is displaying an appropriate message indicating the HbCO measurement, such as, for example, "CO". Also, the multi-mode display **206** has shifted the data to the left to quickly and efficiently indicate that the displayed parameter is other than SpO₂. Accordingly, the parameter indicator **208** is also activated to confirm the display of measured values of HbCO. As disclosed in the foregoing, in an embodiment, the multi-mode display **206** and pulse rate display message **216** are orange.

FIG. 5 also shows the PITTM bar **240** almost fully activated, representing good perfusion. In addition, the activation of the HbCO indicator **204** represents communication with a sensor capable of producing sufficient data to determine measured values of HbCO. In an embodiment, such sensors may comprise sensors capable of emitting light at about eight (8) or more different wavelengths; however, such sensors may comprise about two (2) or more different wavelengths. Moreover, such sensors may have appropriate data stored on a memory associated therewith, or the like. FIG. 5 also shows the HbCO measurement being about 20% (as illustrated on the HbCO bar **212** and multi-mode display **206**) thereby indicating a potentially dangerous situation that if exacerbated, will become quite problematic. Therefore, the alarm indicator **244** is also activated, and in some embodiments, the speaker **236** as well.

FIG. 6 illustrates the display of FIG. 3 showing measured values of SpO₂, HbCO, BPM, perfusion, and type of sensor, according to an exemplary embodiment of the patient monitor of FIG. 1. In contrast to FIG. 4, FIG. 6 shows that the monitor **200** is communicating with a sensor capable of producing sufficient data to determine measured values of HbCO, even though the displayed values are that of SpO₂ and BPM. Thus, FIG. 6 shows the activation of the HbCO indicator **204**, and the continuous monitoring of HbCO by the HbCO bar **212**. FIG. 6 also shows a high value of HbCO, and therefore, the indication of an alarm condition by activation of the alarm indicator **244**. In an embodiment, upon determination of an alarm condition on a nondisplayed parameter, the monitor **200** may advantageously provide an alarm indication through speaker and alarm indicator activation, automatic toggle to the nondisplayed parameter on the multi-mode display **206** for a defined or undefined time, or the like.

16

FIG. 7 illustrates a top elevation view of an exemplary handheld noninvasive multi-parameter patient monitor **700** capable of displaying at least HbCO and HbMet, such as, for example, the patient monitor of FIG. 1. Patient monitors exhibiting combinations of many of the features described herein are advantageously commercially available from Masimo under the brand name "Rad 57cm." As shown in FIG. 7, the monitor **700** comprises a monitor similar to monitor **200** disclosed with reference to FIG. 2. Moreover, monitor **700** further includes a multi-mode display **706** capable of displaying, for example, measurements of HbMet and BPM. In an embodiment, the display **706** has insufficient space or display real estate to display the many parameters capable of being measured by the monitor **700**. Thus, the multi-mode display **706** may advantageously cycle through two or more measured parameters. In such embodiments, the monitor **700** may also advantageously include parameter indicators **708**, **710**, providing additional visual queues as to which parameter is currently displayed. In an embodiment, the display **706** may also cycle colors, flash rates, or other audio or visual queues providing readily identifiable information as to which measured parameter is displayed. For example, when the multi-mode display **706** displays measured values of BPM that are normal, the numbers may advantageously appear in green, while normal measured values of HbMet may appear in blue. Moreover, in an embodiment, the display **706** may flash at a predefined rate when searching for saturation and at another predefined rate when a signal quality is below a predetermined threshold.

FIG. 7 also illustrates the monitor **700** comprising user input keys **718**, including an HbCO/HbMet button **720**. In an embodiment, activation of the HbCO/HbMet button **720** toggles the measured value displayed in the multi-mode display **706**. For example, activation of the HbCO/HbMet button **720** toggles the multi-mode display **206** from displaying measured values of SpO₂ and BPM, to HbCO and HbMet for about ten (10) seconds. Activation of the mode/enter button **722** or the next button **724** during the ten (10) second period returns the multi-mode display **706** back to SpO₂ and BPM. A skilled artisan will also recognize that activation of the HbCO/HbMet button **720** may advantageously toggle through a plurality of measured values, and that such values may be displayed for short segments and then return to SpO₂ and BPM, may remain displayed until further activation of the button **720**, or the like.

The monitor **700** also comprises a coarser indication of HbMet through an HbMet bar **740**. In an embodiment, a plurality of LED's activate from a bottom toward a top such that the bar "fills" to a level proportional to the measured value, with increments at about 0.5%, about 1%, about 2%, about 3%, about 4%, about 5%, about 7.5%, about 10%, about 15% and greater than about 20%, although an artisan will recognize from the disclosure herein other useful delineations. Additionally, the HbMet bar **740** may advantageously change colors, flash, increasingly flash, or the like to indicate worsening measured values of perfusion.

Although disclosed with reference to the HbMet bar **740**, and artisan will recognize from the disclosure herein other coarse or even gross indications of HbMet, or any measured parameter. For example, a single LED may advantageously show green, yellow, and red, to indicate worsening coarse values of HbMet. Alternatively, a single LED may simply light to indicate an alarm or approaching alarm condition.

FIG. 8 illustrates an exemplary display of the patient monitor **700** of FIG. 7. As shown in FIG. 8, the display includes the multi-mode displays **206**, **706**, parameter indicators **208**, **210**, **708**, **710**, the HbCO bar **212** and indicator

204, the HbMet bar 740, and the alarm indicator 244. In an embodiment, the multi-mode display 706 is similar to multi-mode display 206, comprising a plurality of seven segment displays 302 capable of displaying alpha-numeric information, and capable of altering its display characteristics or aspects in a wide variety of configurations discussed with reference to the display 206.

FIG. 9 illustrates the display of FIG. 8 showing measured values of SpO₂, BPM, HbCO, HbMet, and type of sensor according to an exemplary embodiment of the patient monitor of FIG. 1. FIG. 9 also shows the HbMet bar 740 near the bottom and corresponding to about 1%, representing acceptable HbMet, while the HbCO bar 212 hovers at a dangerous near 20%. In addition, the HbCO indicator 204 is showing communication with a sensor producing sufficient data to determine measured values of additional parameters, such as, HbMet, HbCO or the like. In an embodiment, such sensors may comprise sensors capable of emitting light of more than two (2) different wavelengths, preferably more than four (4) different wavelengths, and more preferably eight (8) or more different wavelengths.

FIG. 10 illustrates the display of FIG. 8 showing measured values of HbCO, HbMet, and type of sensor according to an exemplary embodiment of the patient monitor of FIG. 1. As shown in FIG. 10, the multi-mode display 706 is displaying a percentage value of HbMet that is shifted using the parameter indicator 708. The data has been advantageously shifted to the left to quickly and efficiently indicate that the displayed parameter is other than BPM. Accordingly, the parameter indicator 708 is also activated to confirm the display of measured values of HbMet. As disclosed in the foregoing, in an embodiment, the multi-mode display 706 is blue.

FIG. 10 also shows the HbMet bar 740 nearly empty, representing acceptable HbMet. In addition, the activation of the HbCO indicator 204 represents communication with a sensor capable of producing sufficient data to determine measured values of HbCO. In an embodiment, such sensors may have appropriate data stored on a memory associated therewith, or the like. FIG. 10 also shows the HbCO measurement being about 20% (as illustrated on the HbCO bar 212 and multi-mode display 206) thereby indicating a potentially dangerous situation that if exacerbated, will become quite problematic. Therefore, the alarm indicator 244 is also activated, and in some embodiments, the speaker 236 as well.

FIG. 11A illustrates a perspective view of an exemplary noninvasive multi-parameter patient monitor 1100, such as, for example, the patient monitor of FIG. 1. Moreover, FIGS. 11B-11E illustrate exemplary display screens of the patient monitor of FIG. 11A. As shown in FIGS. 11A-11B, an embodiment of the monitor 1100 includes a display 1101 showing a plurality of parameter data. For example, the display may advantageously comprise a CRT or an LCD display including circuitry similar to that available on oximeters commercially available from Masimo Corporation of Irvine, Calif. sold under the name Radical™, and disclosed in the U.S. patents referenced above and incorporated above. However, an artisan will recognize from the disclosure herein many commercially available display components capable of displaying multiple parameter data along with the ability to display graphical data such as plethysmographs, trend traces, and the like.

In an embodiment, the display includes a measured value of SpO₂ 1102, a measured value of pulse rate 1104 in BPM, a plethysmograph 1106, a measured value of HbCO 1108, a measured value of HbMet 1110, a measured value of a

perfusion quality 1112, a measured value of Hbt 1114, and a derived value of fractional saturation "SpaO₂" 1116. In an embodiment, SpaO₂ comprises HbO₂ expressed as a percentage of the four main hemoglobin species, i.e., HbO₂, Hb, HbCO, and HbMet.

In an embodiment, one or more of the foregoing parameter includes trending or prediction indicators 1118 showing the current trend or prediction for that corresponding parameter. In an embodiment, the indicators 1118 may advantageously comprise an up arrow, a down arrow, and a hyphen bar to indicate up trending/prediction, down trending/prediction, or neutral trending/prediction.

FIG. 11C illustrates an exemplary display screen showing trend graph 1140 including trend line 1142 for HbMet. In an embodiment, the trend line 1142 may be advantageously colored for quick straightforward recognition of the trending parameter, may be associated with any one or more of the foregoing alarm attributes, may include trending lines for other parameters, or the like. The display screen also shows trending directional indicators 1142, 1144 for many of the displayed physiological parameters. In an embodiment, the directional indicators 1142, 1144 may advantageously comprises arrows showing the recent trend, predicted trend, user-customizable trend, combinations thereof, or the like for the associated parameters. In an embodiment, the directional indicators 1142, 1144 comprises an up arrow indicating a rising trend/predicted trend, a middle bar indicating a somewhat stable trend/predicted trend, and a down arrow indicating a lowering trend/predicted trend. An artisan will recognize a wide variety of other directional indicators 1142, 1144 from the disclosure herein.

FIG. 11D shows an exemplary display screen in vertical format. Such vertical format could be user actuated or based on a gravity switch. FIGS. 11E-11F illustrate additional displays of various physiological parameters similar to those discussed in the foregoing. As shown in FIG. 11G, the display includes a measured value of SpO₂ 1162, a measured value of pulse rate 1164 in BPM, a plethysmograph 1166, a HbCO bar 1168, and a HbMet bar 1170. In an embodiment, the HbCO bar 1168 and HbMet bar 1170 may advantageously behave the same or similarly to the HbCO bar 212 and HbMet bar 712. Moreover, similar bars may advantageously display any of the physiological parameters discussed herein using display indicia appropriate to that parameter. For example, a SpO₂ or SpaO₂ bar may advantageously range from about 0% to about 100%, and more preferably range from about 50% to about 100%, while a Hbt bar may advantageously range from about 0 to about 30.

Moreover, similar to the disclosure above, the measured value of SpO₂ 1162 may advantageously toggle to measured values of HbCO, HbMet, Hbt, or the like based on, for example, actuation of user input keys, or the like.

In addition to the foregoing, the display may also include graphical data showing one or more color-coded or other identifying indicia for traces of trend data. Moreover, other graphical presentations may advantageously provide readily identifiable indications of monitored parameters or combinations of monitored parameters of the patient. For example, in an embodiment, the display includes a SpaO₂ graph 1172. The SpaO₂ graph 1172 plots SpO₂ as a function of other blood analytes (1-SpaO₂), where SpaO₂ comprises HbO₂ expressed as a percentage of the four main hemoglobin species, i.e., HbO₂, Hb, HbCO, and HbMet. Thus, as shown in FIG. 11G, as the slope of the displayed line or arrow increases, the caregiver can readily note that the majority of hemoglobin carriers are being used to carry oxygen, and not, for example, harmful carbon monoxide. On the other hand,

as the slope decreases, the caregiver can readily and advantageously note that the number of hemoglobin species available to carry oxygen is decreasing, regardless of the current value of SpO₂. Moreover, the length of the arrow or line also provides an indication of wellness, e.g., the higher the line the more oxygen saturation, the lower the line, the more likely there may be desaturation event, or the like.

Thus, the SpO₂ graph 1172 provides the caregiver with the ability to recognize that even though the measured value of SpO₂ may be within acceptable ranges, there are potentially an unacceptable number of hemoglobin carriers unavailable for carrying oxygen, and that other potential problems may exist, such as, for example, harmful carbon monoxide levels, or the like. In an embodiment, various alarm conditions may cause the graph 1172 to change color, flash, or any combination of alarm indications discussed in the forgoing. Moreover, FIG. 11H illustrates yet an additional display of the foregoing parameters.

An embodiment may also include the monitor 1100 advantageously defining regions of wellness/severity of the monitored patient. For example, because the graph 1172 comprises two dimensions, the monitor 1100 may advantageously define regions where the patient's measured physiological parameters are considered acceptable, regions where the patient is considered at risk, regions where the patient is critical, and the like. For example, one region of acceptability may include a high SpO₂ and a low 1-SpO₂, another region of risk may include a high SpO₂ and a high 1-SpO₂, and another critical region may include a low SpO₂ and a high 1-SpO₂. Moreover, an artisan will recognize from the disclosure herein that different parameters may also be combined to provide readily identifiable indications of patient wellness.

In addition to or as an alternative to the two dimensional SpO₂ graph 1172, the monitor 1100 may also include a three dimensional graph, such as, for example, extending the graph 1172 along the variable of time. In this embodiment, the foregoing regions advantageously become three dimensional surfaces of wellness. Moreover, trend data may also be advantageously added to the surface to provide a history of when particular monitored parameters dipped in and out of various surfaces of wellness, risk, criticality, or the like. Such trend data could be color-coded, text identified, or the like. An artisan will also recognize that such surfaces may be dynamic. For example, measurements of HbCO>about 5 may dictate that trend data showing SpO₂<about 90% should be considered critical; however, measurements of HbCO<about 5 may dictate only SpO₂<about 85% would be critical. Again, an artisan will recognize from the disclosure herein other parameter combinations to create a wide variety of wellness/critical regions or surfaces that provide readily available visual or audio indications of patient well being, trigger specific alarms, or the like.

Moreover, the monitor 1100 may advantageously employ enlargement or reorganization of parameter data based on, for example, the severity of the measurement. For example, the monitor 1100 may display values for HbCO in a small portion of the screen or in the background, and when HbCO begins to approach abnormal levels, the small portion may advantageously grown as severity increases, even in some embodiments to dominate the display. Such visual alarming can be combined with audio alarms such as announcements, alarms, rising frequencies, or the like, and other visual alarms such as flashing, coloration, or the like to assist a caregiver in noticing the increasing severity of a monitored parameter. In an embodiment, a location of the display of an alarming value is changed to be displayed in a larger display

area, such as 1102, so as to be readily noticeable and its display values readily ascertainable.

Although the foregoing invention has been described in terms of certain preferred embodiments, other embodiments will be apparent to those of ordinary skill in the art from the disclosure herein. For example, the monitor 100 may advantageously be adapted to monitor or be included in a monitor capable of measuring physiological parameters other than those determined through absorption spectroscopy, such as, for example, blood pressure, ECG, EKG, respiratory rates, volumes, inputs for blood pressure sensors, acoustical sensors, and the like. Moreover, the monitor 100 may be adapted for wireless communication to and from the sensor 106, and/or to and from other monitoring devices, such as, for example, multi-parameter or legacy monitoring devices.

Also, other combinations, omissions, substitutions and modifications will be apparent to the skilled artisan in view of the disclosure herein. Accordingly, the present invention is not intended to be limited by the reaction of the preferred embodiments, but is to be defined by reference to the appended claims.

Additionally, all publications, patents, and patent applications mentioned in this specification are herein incorporated by reference to the same extent as if each individual publication, patent, or patent application was specifically and individually indicated to be incorporated by reference.

What is claimed is:

1. A method, comprising:

processing one or more signals with one or more signal processors, said one or more signals responsive to attenuation of light by body tissue of a monitored patient;

noninvasively, electronically determining measured values of oxygen saturation and arterial carbon monoxide saturation, based at least in part on the processed one or more signals;

determining a dynamic oxygen saturation threshold for the oxygen saturation based at least in part on an arterial carbon monoxide saturation level, wherein the dynamic oxygen saturation threshold increases based at least in part on an increase in the arterial carbon monoxide saturation level; and

activating a caregiver alert associated with a display based at least in part on at least one measured value of the oxygen saturation satisfying the dynamic oxygen saturation threshold.

2. The method of claim 1, wherein the caregiver alert comprises at least one of an LED activation, an alarm message, or an audible alarm.

3. The method of claim 1, wherein the caregiver alert changes as measured values of the oxygen saturation move further from the dynamic oxygen saturation threshold.

4. The method of claim 1, wherein said activating the caregiver alert comprises emphasizing on the display the measured values of the oxygen saturation.

5. The method of claim 1, wherein said activating the caregiver alert further comprises at least one of altering a size of measured values of the oxygen saturation on the display or alternately displaying and removing from the display the measured values of the oxygen saturation.

6. The method of claim 1, further comprising:

displaying on the display the at least one measured value of the oxygen saturation; and

displaying on the display a prediction indicator corresponding to the oxygen saturation, wherein the prediction indicator indicates a predicted trend of measured values of the oxygen saturation.

21

7. A patient monitor, comprising:
 a sensor port configured to receive one or more signals
 from a sensor, wherein the one or more signals are
 responsive to attenuation of light by body tissue of a
 monitored patient; and
 a processor in communication with the sensor port and
 configured to:
 noninvasively, electronically determine measured val-
 ues of oxygen saturation and arterial carbon mon-
 oxide saturation using the one or more signals
 received from the sensor;
 determine a dynamic oxygen saturation threshold for
 the oxygen saturation based at least in part on an
 arterial carbon monoxide saturation level, wherein
 the dynamic oxygen saturation threshold increases
 based at least in part on an increase in the arterial
 carbon monoxide saturation level; and
 activate a caregiver alert associated with a display
 based at least in part on at least one measured value
 of the oxygen saturation satisfying the dynamic
 oxygen saturation threshold.
8. The patient monitor of claim 7, wherein the caregiver
 alert comprises an LED activation on the display.
9. The patient monitor of claim 7, wherein the caregiver
 alert comprises at least one of an alarm message or an
 audible alarm.
10. The patient monitor of claim 7, wherein the caregiver
 alert comprises emphasizing on the display measured values
 of the oxygen saturation.
11. The patient monitor of claim 7, wherein the caregiver
 alert comprises at least one of an altered size of measured
 values of the oxygen saturation on the display or an alter-
 nating display and removal from the display of the measured
 values of the oxygen saturation.
12. The patient monitor of claim 7, wherein the processor
 is further configured to cause the display to display thereon:
 the at least one measured value of the oxygen saturation;
 and
 a prediction indicator corresponding to the oxygen satu-
 ration, wherein the prediction indicator indicates a
 predicted trend of measured values of the oxygen
 saturation.
13. The patient monitor of claim 7, wherein the processor
 is further configured to cause the display to display thereon

22

a wellness qualitative indication indicative of a patient
 wellness level based at least in part on a combination of the
 measured values of the oxygen saturation and the arterial
 carbon monoxide saturation level.

14. A method comprising:
 noninvasively, electronically determining measured val-
 ues of a first blood constituent and a second blood
 constituent, wherein the determining is performed by
 processing one or more signals with one or more signal
 processors, said one or more signals responsive to
 attenuation of light by body tissue of a monitored
 patient;
 determining a dynamic threshold for the first blood con-
 stituent based at least in part on a second blood con-
 stituent level, wherein the dynamic threshold increases
 based at least in part on an increase in the second blood
 constituent level; and
 activating a caregiver alert associated with a display based
 at least in part on at least one measured value of the first
 blood constituent satisfying the dynamic threshold.
15. The method of claim 14, wherein the caregiver alert
 comprises at least one of an LED activation, an alarm
 message, or an audible alarm.
16. The method of claim 14, wherein the caregiver alert
 changes as measured values of the oxygen saturation move
 further from the dynamic threshold.
17. The method of claim 14, wherein said activating the
 caregiver alert comprises emphasizing on the display the
 measured values of the first blood constituent.
18. The method of claim 14, wherein said activating the
 caregiver alert comprises at least one of altering a size of
 measured values of the first blood constituent displayed on
 the display or alternately displaying and removing from
 display the measured values of the first blood constituent.
19. The method of claim 14, further comprising:
 displaying on the display the at least one measured value
 of the first blood constituent; and
 displaying on the display a prediction indicator corre-
 sponding to the first blood constituent, wherein the
 prediction indicator indicates a predicted trend of mea-
 sured values of the first blood constituent.

* * * * *

专利名称(译)	无创多参数病人监护仪		
公开(公告)号	US10251585	公开(公告)日	2019-04-09
申请号	US15/138008	申请日	2016-04-25
[标]申请(专利权)人(译)	CERCACOR LAB		
申请(专利权)人(译)	CERCACOR LABORATORIES , INC.		
当前申请(专利权)人(译)	CERCACOR LABORATORIES , INC.		
[标]发明人	AL ALI AMMAR KIANI JOE E		
发明人	AL-ALI, AMMAR KIANI, JOE E.		
IPC分类号	G08B23/00 A61B5/0205 A61B5/145 A61B5/00 A61B5/026 A61B5/1455 A61B5/0295 A61B5/1495 A61B5/024 A61B1/00		
CPC分类号	A61B5/1455 G16H40/67 A61B5/0205 A61B5/0261 A61B5/0295 A61B5/02416 A61B5/1495 A61B5/14532 A61B5/14546 A61B5/14551 A61B5/14552 A61B5/6815 A61B5/6826 A61B5/6829 A61B5/6832 A61B5/6838 A61B5/7221 A61B5/7246 A61B5/7275 A61B5/7278 A61B5/742 A61B5/7405 A61B5/746 A61B5/7475 A61B5/0022 A61B1/00 A61B5/02427 A61B2562/08 A61B2562/085 A61B2562/222 Y10S439/909 G06F19/3418 G16H10/40 H05K999/99		
优先权	14/076556 2014-12-16 US 60/657759 2005-03-01 US 60/657596 2005-03-01 US 60/657281 2005-03-01 US 60/657268 2005-03-01 US		
其他公开文献	US20160310052A1		
外部链接	Espacenet		

摘要(译)

本公开的实施例包括手持式多参数患者监视器，其能够从能够检测由身体组织衰减的光的光敏检测器的输出确定多个生理参数。例如，在一个实施例中，监视器能够有利且准确地显示脉搏率，体积描记器数据，灌注质量，信号置信度和身体组织中血液成分的值中的一个或多个，包括例如动脉一氧化碳饱和度（“HbCO”），高铁血红蛋白饱和度（“HbMet”），总血红蛋白（“Hbt”），动脉血氧饱和度（“SpO2”），分数动脉血氧饱和度（“SpaO2”）等。在一个实施例中，监视器显示与患者健康水平相关联的线。

