



(19) **United States**

(12) **Patent Application Publication** (10) **Pub. No.: US 2020/0100728 A1**

**FERREIRA DOS SANTOS DA FONSECA et al.** (11) **Pub. Date: Apr. 2, 2020**

(54) **SYSTEMS AND METHODS FOR USING BREATH EVENTS IN SLEEP STAGING**

*A61B 5/087* (2006.01)  
*A61M 16/00* (2006.01)  
*A61B 5/091* (2006.01)

(71) Applicant: **KONINKLIJKE PHILIPS N.V.**, Eindhoven (NL)

(52) **U.S. Cl.**  
CPC ..... *A61B 5/4818* (2013.01); *A61B 5/085* (2013.01); *A61B 5/087* (2013.01); *A61M 16/024* (2017.08); *A61M 2230/40* (2013.01); *A61B 5/486* (2013.01); *A61B 5/7264* (2013.01); *A61B 5/091* (2013.01); *A61B 5/4812* (2013.01)

(72) Inventors: **Pedro Miguel FERREIRA DOS SANTOS DA FONSECA**, Borgerhout (BE); **Angela GRASSI**, Eindhoven (NL); **Gregory Delano MATTHEWS**, Pittsburgh, PA (US); **Michael Thomas KANE**, Harrison City, PA (US); **Raymond Charles VASKO, JR.**, Turtle Creek, PA (US); **Mareike KLEE**, Straelen (DE)

(21) Appl. No.: **16/589,191**

(22) Filed: **Oct. 1, 2019**

**Related U.S. Application Data**


(60) Provisional application No. 62/739,591, filed on Oct. 1, 2018.

**Publication Classification**

(51) **Int. Cl.**  
*A61B 5/00* (2006.01)  
*A61B 5/085* (2006.01)

(57) **ABSTRACT**

The present disclosure describes a sleep staging system. The sleep staging system comprising: one or more sensors configured to generate output signals conveying information related to one or more breathing parameters of subject; and one or more physical computer processors operatively connected with the one or more sensors, the one or more physical computer processors configured by computer readable instructions to: determine, based on the output signals, one or more breathing features of individual breaths of the subject; determine a distribution of the one or more breathing features over one or more time windows; detect presence of a breathing event based on the output signals; determine sleep states of the subject with a sleep stage classifier model based upon the distribution of the breathing features and the one or more breathing events; and provide feedback indicating the sleep states.






FIG. 1




FIG. 2




FIG. 3




FIG. 4




FIG. 5




FIG. 6A




FIG. 6B




FIG. 7

## SYSTEMS AND METHODS FOR USING BREATH EVENTS IN SLEEP STAGING

### BACKGROUND

#### 1. Field

[0001] The present disclosure pertains to systems and methods the use breath events in determining sleep staging determination.

#### 2. Description of the Related Art

[0002] The present disclosure relates to systems and methods for determining sleep stages. The disclosure, in one embodiment, incorporates the system and methodology into systems and methods that can also be used to detect or treat breathing disorders. Obstructive Sleep Apnea (OSA) is a common form of sleep-disordered breathing (SDB). Continuous Positive Airway Pressure (CPAP) is usually a first-line medical therapy for treatment of OSA. Currently, CPAP machines provide a feedback to the patient, that it is mainly focused on parameters related to the therapy itself, (treated) apnea-hypopnea index (AHI), usage history, leaks, etc. However, CPAP systems that provide effective feedback regarding the effect of therapy on the objective measured sleep quality has been limited or non-existent.

### SUMMARY

[0003] Accordingly, one or more aspects of the present disclosure relate to a sleep staging system. The sleep staging system comprising: one or more sensors configured to generate output signals conveying information related to one or more breathing parameters of subject; and one or more physical computer processors operatively connected with the one or more sensors, the one or more physical computer processors configured by computer readable instructions to: determine, based on the output signals, one or more breathing features of individual breaths of the subject; determine a distribution of the one or more breathing features over one or more time windows; detect presence of a breathing event based on the output signals; determine sleep states of the subject with a sleep stage classifier model based upon the distribution of the breathing features and the one or more breathing events; and provide feedback indicating the sleep states.

[0004] Another aspect of the present disclosure provides a method comprising: generating, with one or more sensors, output signals conveying information related to one or more breathing parameters of subject; determining, with one or more physical computer processors, based on the output signals, one or more breathing features of individual breaths of the subject; determining, with one or more physical computer processors, a distribution of the one or more breathing features over one or more time windows; detecting, with one or more physical computer processors, presence of a breathing event based on the output signals; determining, with one or more physical computer processors, sleep states of the subject with a sleep stage classifier model based upon the distribution of the breathing features and the one or more breathing events; and providing, with one or more physical computer processors, feedback indicating the sleep states.

[0005] Another aspect of the present disclosure relates to a method for generating, with one or more sensors, output

signals conveying information related to one or more breathing parameters of subject; determining, with one or more physical computer processors, based on the output signals, one or more breathing features of individual breaths of the subject; determining, with one or more physical computer processors, a distribution of the one or more breathing features over one or more time windows; detecting, with one or more physical computer processors, presence of a breathing event based on the output signals; determining, with one or more physical computer processors, sleep states of the subject with a sleep stage classifier model based upon the distribution of the breathing features and the one or more breathing events; and providing, with one or more physical computer processors, feedback indicating the sleep states.

[0006] Still another aspect of the present disclosure relates to sleep staging system comprising: means for sensing, configured for generating output signals conveying information related to one or more breathing parameters of subject; means for determining, configured for determining, based on the output signals, one or more breathing features of individual breaths of the subject; means for determining, configured for determining a distribution of the one or more breathing features over one or more time windows; means for detecting, configured for detecting presence of a breathing event based on the output signals; means for determining, configured for determining sleep states of the subject with a sleep stage classifier model based upon the distribution of the breathing features and the one or more breathing events; and means for providing feedback configured to provide feedback indicating the sleep states.

[0007] These and other objects, features, and characteristics of the present disclosure, as well as the methods of operation and functions of the related elements of structure and the combination of parts and economies of manufacture, will become more apparent upon consideration of the following description and the appended claims with reference to the accompanying drawings, all of which form a part of this specification, wherein like reference numerals designate corresponding parts in the various figures. It is to be expressly understood, however, that the drawings are for the purpose of illustration and description only and are not intended as a definition of the limits of the disclosure.

### BRIEF DESCRIPTION OF THE DRAWINGS

[0008] FIG. 1 illustrates a sleep staging system 100 for classifying sleep stages for a subject, according to one or more embodiments;

[0009] FIG. 2 illustrates an example 200 of a sleep staging system 200 for classifying sleep stages for a subject, according to one or more embodiments;

[0010] FIG. 3 illustrates an example 300 of a windowing process, according to one or more embodiments;

[0011] FIG. 4 illustrates a method 400 for classifying sleep stages for a subject, according to one or more embodiments.

[0012] FIG. 5 illustrates of a windowing process 500 used to determine distribution of a given breathing event feature over time, according to one or more embodiments;

[0013] FIGS. 6A-6B illustrate examples 600 for classifying sleep stages for a subject during a respiratory therapy session with a CPAP device, according to one or more embodiments; and

[0014] FIG. 7 illustrates a method for classifying sleep stages for a subject during a respiratory therapy session with a CPAP device, according to one or more embodiments.

## DETAILED DESCRIPTION OF EXEMPLARY EMBODIMENTS

[0015] As used herein, the singular form of “a”, “an”, and “the” include plural references unless the context clearly dictates otherwise. As used herein, the statement that two or more parts or components are “coupled” shall mean that the parts are joined or operate together either directly or indirectly, i.e., through one or more intermediate parts or components, so long as a link occurs. As used herein, “directly coupled” means that two elements are directly in contact with each other. As used herein, “fixedly coupled” or “fixed” means that two components are coupled so as to move as one while maintaining a constant orientation relative to each other.

[0016] As used herein, the word “unitary” means a component is created as a single piece or unit. That is, a component that includes pieces that are created separately and then coupled together as a unit is not a “unitary” component or body. As employed herein, the statement that two or more parts or components “engage” one another shall mean that the parts exert a force against one another either directly or through one or more intermediate parts or components. As employed herein, the term “number” shall mean one or an integer greater than one (i.e., a plurality).

[0017] Directional phrases used herein, such as, for example and without limitation, top, bottom, left, right, upper, lower, front, back, and derivatives thereof, relate to the orientation of the elements shown in the drawings and are not limiting upon the claims unless expressly recited therein.

[0018] FIG. 1 illustrates an example of a system **100** for classifying sleep stages for a subject, according to one or more embodiments of the present disclosure. In some embodiments, system **100** is configured to determine breathing parameters of a subject. Determining the breathing parameters include detecting individual breaths of the subject. System **100** is configured to classify sleep stages of the subject based on breathing features of the individual breaths. The breathing features of each breath may include duration of the breath, duration of inspiration vs expiration of the breath, minimum and/or maximum flow of the breath, and/or tidal volume of the breath. In one embodiment, the sensors (**40**) to be described in detail below, can be incorporated into a device that interfaces with the subject and obtains output signals (such as those pertain to breathing (flow rate, pressure, tidal volume, etc), cardiovascular (heart rate, blood pressure, etc), and/or other physiological measurements from the subject. For example, in one embodiment, the sensors (**40**) can be incorporated in a CPAP machine as well be described in connection with some embodiments.

[0019] Presence of sleep events may have an impact on the sleep architecture of a subject, and/or the characteristics of features used for sleep classification. For example, if a subject is in sleep stage N3 and a central sleep apnea event occurs. central sleep apnea event may cause a change in the respiratory characteristics during the event (no breathing effort during the apnea) and in the period immediately after the event (usually breathing resumes, with higher frequency and amplitude during the hyperpnea). The central apnea event is often followed by an arousal event, which may cause a change in heart rate variability characteristics due to the burst in sympathetic activity during the arousal period. After the arousal, the subject enters a period of “lighter” sleep, typically N1 or N2. Without information about the

occurrence of this breathing event, and if the cardiac or respiratory features are analyzed in a time window during which the event occurs, the classifier might be unable to detect the N3 period preceding the arousal (typically N3 is characterized by a low sympathetic tone with regular breathing amplitude and frequency). Knowing that an apnea and subsequent arousal occurred, the classifier may easily associate the characteristics of the features to the sequence of sleep stages and may easily infer what the following sleep stage will likely be. Using breath events in the determination of the sleep states provides for an improved sleep classification performance.

[0020] In some embodiments, the breathing features are first extracted, and then respiratory characteristics are analyzed using different time windows to characterize a value distribution of the features. The respiratory characteristics are analyzed with descriptive using one or more windows (lasting 30, 30, or more seconds) to characterize the value distribution of the breathing features. The size of the windows is time based (e.g. 30, 30, 90, 150 seconds, etc.), independently from the number of breaths contained in the window. In some embodiments, the statistics (meta-features) for a breathing feature describe the shape of a distribution of the feature over one or more time windows (e.g., a median, different percentiles, range, etc.) This is more advantageous than measuring variance or standard deviation of the breathing features in the analysis windows. The statistics (meta-features) are then used as input to a sleep stage classifier to classify the sleep stages of the subject during the therapy session. This step provides for a good mapping between sleep stages and measured statistics. The mapping would not be as robust (which results in a model with lower classification performance) if the sleep stages are mapped directly from breathing features. The term “mapping” as used herein should be itself broadly construed to mean determining a sleep state with the model, using the provided inputs into the model.

[0021] In some embodiments, the sleep stage classifier uses models that express the likelihood of a state happening based on the observations of that state, what happened in the preceding state, and on the history of states until then. In some cases, the sleep stage classifier uses bidirectional models, where the likelihood of a stage at a given point during the night depends on what happened before, but also what will happen after that point, until the subject finally wakes up in the morning. These models may be more advantageous than models that uses time-shifted input (e.g., Markov) in expressing the likelihood of a current state using memory (e.g., preceding state and history of states until then) to provide context to the current detection. Models with memory such as recurrent neural networks, long short term memory, or causal convolutional neural networks, are beneficial to explore the structured nature of sleep, and the changes in the likelihood that a sleep stage occurs after a given history of (detected) sleep stages during the night, until that point. For example, if more than one hour of N3 has been detected, it becomes increasingly less likely that N3 still occurs. Memory-based models can use this information to infer not only the most likely sleep stage at each point in time, but also the most likely sequence of sleep stages throughout the whole night based on what happened until that point. Optionally, and if causal staging is not required (e.g. for real-time applications) and observations from the whole night are available, bidirectional models can

be used, whereby inference about the sleep stage at a given point can use information about the future, i.e. what the observations are after that point. For example, if the observations of a following state are very likely indicating the presence of a REM stage, it is very unlikely that the current stage is N3 or Wake, but more likely N1 or N2. The inclusion of BE meta-features improves the performance of a system where only breathing feature statistics (meta-features) are used and no influence of breathing events are taken into account. The idea behind this is that the occurrence of breathing events (e.g. apnea, hypopnea) influence the sleep architecture. For instance, after an apnea event, likely there will be an arousal and the most likely sleep stage will be N1 or N2. The result is that the sleep staging classifier, using the BE meta-features, can learn more about the sleep architecture, and will show better classification performances.

[0022] In some embodiments, system 100 comprises one or more sensors 40, one or more physical computer processors 30, a user interface 120, electronic storage 130, a network 150, and/or other components.

[0023] In some embodiments, sensor(s) 40 are configured to generate output signals conveying information related to one or more breathing parameters of subject 70. In some embodiments, the one or more breathing parameters may comprise gas parameters related to pressurized flow of breathable gas provided by device for providing respiratory therapy to the subject (e.g., PAP machine) breathing parameters related to respiration of subject 70, physiological parameters of subject 70, and/or other parameters. The one or more gas parameters of the pressurized flow of breathable gas may comprise, for example, one or more of a flow rate, volume, pressure, humidity, temperature, acceleration, velocity, and/or other parameters of the breathable gas. Breathing parameters related to the respiration of subject 70 may comprise a tidal volume, a timing (e.g., beginning and/or end of inhalation, beginning and/or end of exhalation, etc.), a respiration rate, a respiration airflow, a duration (e.g., of inhalation, of exhalation, of a breathing cycle, etc.), respiration frequency, effort of breathing, and/or other breathing parameters. Physiological parameters may include oximetry parameters, pulse, temperature, blood pressure, and/or other physiological parameters. In one embodiment, the breathing features detected by the one or more sensors may also include “breathing features” of individual breaths of the subject as will be described later.

[0024] In some embodiments, various types of sensor(s) 40 can be used. In various embodiments, such sensors will be or include one or more one or more non EEG type sensors (configured to generate non-EEG signals). For example, sensor(s) 40 may be one or more PPG sensor(s) that generate photoplethysmogram (PPG) signals. PPG is an optically obtained plethysmogram that can be used to detect blood volume changes in the microvascular bed of tissue, changes in chest and/or abdominal volume. A PPG may be obtained by using a pulse oximeter, belts around patient’s chest and abdomen. In some embodiments, sensor(s) 40 may be one or more ECG sensor(s) that generate electrocardiography signal. An electrocardiogram (ECG) is a recording of the electrical activity of the heart. An ECG may be obtained using electrodes placed on the skin of the patient. In some embodiments, sensor(s) 40 may be one or more BCG sensors that generate a ballistocardiograph (BCG) signal. A BCG signal is a graphical representation of repetitive motions of the human body arising from the sudden ejection

of blood into the great vessels with each heartbeat. BCG can be obtained using noninvasive methods (e.g., from sensors on the surface of the body, or using a sensor in the form of a camera in a non-contact manner. In some embodiments, sensor(s) 40 may be configured for tracking movement of a chest/abdomen marker by using an infrared camera to measure respiratory effort of the subject. In some embodiments, PPG, ECG, and/or BCG may be used to determine the subjects respiratory effort.

[0025] Sensor(s) 40 may comprise one or more sensors that measure such parameters directly (e.g., through fluid communication with the subject, a subject interface, a respiratory therapy device, etc.) In some embodiments, sensor(s) 40 may comprise one or more sensors that generate output signals related to the one or more parameters indirectly. For example, sensor(s) 40 may comprise one or more sensors configured to generate an output based on an operating parameter of a respiratory therapy device (e.g., subject flow and/or pressure estimations from motor current, voltage, rotational velocity, and/or other operating parameters), and/or other sensors. In some embodiments, sensor(s) 40 may include one or more of flow, position, volume, pressure, humidity, temperature, heart, motion, acceleration, oximetry, audio, video, photo sensors, and/or other sensors. Sensor(s) 40 may comprise sensors disposed in a plurality of locations, such as for example, at various locations within (or in communication with) subject interface, on subject 70, within (or in communication with) a respiratory therapy device, a conduit 50, and/or other locations.

[0026] Processor(s) 30 is configured to provide information processing capabilities in system 100. As such, processor(s) 30 may include one or more digital processors, one or more analog processor, one or more digital circuits designed to process information, one or more analog circuits designed to process information, a state machine, and/or other mechanisms for electronically processing information. In some embodiments, processor(s) is operatively connected to sensors (40). Although processor(s) 30 is shown in FIG. 1 as a single entity, this is for illustrative purposes only. In some implementations, processor(s) 30 includes a plurality of processing units. These processing units may be physically located within the same device (e.g., sensors(40) or a device that includes sensors (40)), or processor(s) 30 may represent processing functionality of a plurality of devices operating in coordination and located outside of system 100 (e.g., in the Cloud). In some embodiments, processors (30) may represent processing functionality of a plurality of devices located within and/or outside system 100 (e.g., communicatively coupled via a network 150).

[0027] As shown in FIG. 1, processor(s) 30 is configured to execute one or more computer program components. The one or more computer program components may comprise one or more of a parameter component 32, a control component 33, a breathing feature determination component 34, a feature distribution component 33, a sleep classification component 38, a feedback component 39, and/or other components. Processor(s) 30 may be configured to execute components 32, 33, 34, 33, 38 and 39 by software; hardware; firmware; some combination of software, hardware, and/or firmware; and/or other mechanisms for configuring processing capabilities on Processor(s) 30.

[0028] It should be appreciated that although components 32, 33, 34, 33, 38 and 39 are illustrated in FIG. 1 as being co-located within a single processing unit, in implementa-

tions in which Processor(s) 30 comprises multiple processing units, one or more of components 32, 33, 34, 33, 38 and 39 may be located remotely from the other components. The description of the functionality provided by the different components 32, 33, 34, 33, 38 and 39 described below is for illustrative purposes, and is not intended to be limiting, as any of components 32, 33, 34, 33, 38 and 39 may provide more or less functionality than is described. For example, one or more of components 32, 33, 34, 33, 38 and 39 may be eliminated, and some or all of its functionality may be provided by other components 32, 33, 34, 33, 38 and/or 39. As another example, Processor(s) 30 may be configured to execute one or more additional components that may perform some or all of the functionality attributed below to one of components 32, 34, 33, 38 and/or 39.

[0029] Parameter component 32 may be configured to receive, determine and/or obtain one or more parameters within system 100. For example, the one or more parameters may be determined based on the output signals from sensor (s) 40. In some embodiments, parameter component 32 is configured to determine one or more breathing parameters related to respiration of subject 70, one or more parameters of a breathable gas within system 100, (e.g., parameters related to pressurized flow of breathable gas delivered by a respiratory therapy device), one or more physiological parameters of subject 70, and/or other parameters. The breathing parameters related to the respiration of subject 70 may comprise beginning and/or end of individual breaths. In some embodiments, the breathing parameters may comprise a tidal volume, a timing (e.g., beginning and/or end of inhalation, beginning and/or end of exhalation, etc.), a respiration rate, a duration (e.g., of inhalation, of exhalation, of a single breathing cycle, etc.), respiratory airflow, breathing effort, respiration frequency, AHI index (apnea and hypopnea index) and/or other breathing parameters. The one or more gas parameters of the pressurized flow of breathable gas may comprise, for example, one or more of a flow rate, heart rate, volume, pressure, humidity, temperature, acceleration, velocity, and/or other gas parameter. Physiological parameters may include oximetry parameters, a pulse, temperature, blood pressure, movement, and/or other physiological parameters.

[0030] In some embodiments, parameter component 32 may be configured to detect breathing events experienced by the subject. Such breathing events may include events that disrupt respiration by subject 70. In some embodiments, parameter component may be configured to detect disruptions of the respiration of subject indicative of presence of respiratory events. For example, such breathing events may include one or more of obstructive apneas, central apneas, glottal closures, Cheyne-Stokes respiration, hypopnea, snoring, hyperventilation, arousal, and/or other breathing events, and/or other respiratory events. Parameter component 32 detects such breathing events based on the output signals generated by sensors 40. For example, by monitoring one or more of flow rate, pressure, respiratory airflow, breathing effort, instantaneous tidal volume, and/or other gas parameters at or near the airway of subject 70 (e.g., within a subject interface).

[0031] Control component 33, in some embodiments, is configured to control operations of sensors (40). For example, in some embodiments control component may be configured to activate/deactivate the one or more sensors

based on user input, measurement results, on a request from one or more components within or outside of system 100.

[0032] Breathing feature determination component 34, is configured to determine one or more breathing features of individual breaths of the subject. In some embodiments, each breath can be characterized by more than one breathing feature. For example, the breath duration, the duration of inspiration vs expiration, minimum and maximum flow rate values, tidal volume, etc. In some embodiments, one or more breathing features may vary depending on the sleep stage of the subject. For example, during N3, breathing becomes slower, and more regular, both in terms of amplitude as well as in terms of frequency. In some embodiments, system 200 comprises computer processors configured to detect individual breaths 203 of the subject based on the output signals. The output signals are non-EEG signals (e.g. ECG, PPG, BCG, respiratory effort, etc.). In some embodiments, each breath is then characterized in terms of several of its signal properties. For example, describing its duration, the duration of inspiration vs expiration, minimum and maximum flow values, tidal volume, etc. The breath features 208 are post-processed 210 and adopted by a pre-trained machine learning model 211, with memory, to automatically classify sleep stages 212 in pre-defined epochs of 30 seconds based on those features. In some embodiments, this information is then fed back to the user in the form of a feedback indicating the sleep state. For example, system 200 may be configured to display the determined sleep stage 212. For example, the display may be user interface (described above), an app on his/her smartphone 120, etc.

[0033] In some embodiments, the (BE) feature values 207 (numeric values) are used to indicate the category of a detected event 205. This process is illustrated in FIG. 3. FIG. 3 illustrates an example 300 of a windowing process used to determine the distribution of a given BE feature 302 over time, according to one or more embodiments.

[0034] FIG. 3 describes a distribution 302 of breathing event (BE) feature 304 over time. The Y axis of the distribution represents the breathing event (BE) feature values 304. The X axis of the distribution represents time centered on 30-second epochs 308, is used in characterization the (BE) feature over the time window 308. FIG. 3 shows that 15 new meta-features 306 are created, indicating, for each epoch, whether the corresponding event was detected (as indicated by the BE feature 304) inside the window defined by the boundaries of that epoch.

[0035] For example, if for a given epoch 308, at least one event of type 2 (hypopnea) 304 was detected, then the corresponding feature 306 (\_PE\_HYPOPNEA) will have a value of 1 for that epoch. If no events of type 2 were detected for a given epoch, then the feature will have a value of 0. Note that this is the case even if multiple events of the same type are detected in the same epoch, i.e., each epoch will have a flag value of 0 or 1, meaning that one or more events of that type were detected. If multiple events of different types are detected in the same epoch, then all corresponding features will have a flag of 1. This is the case for example, in the first epoch of the example illustrated in FIG. 3 where events 304 of type 2 and 15 were detected in the same epoch. In this case, features 306\_PE\_HYPOPNEA (2) and \_PE\_BIG\_LEAK\_SNORE (15) both get a flag of 1 for the first epoch, whereas all other features get a flag of 0.

[0036] Feature distribution component 36, is configured to determine/describe a distribution of the one or more breath-

ing features over one or more-time windows. In some embodiments, feature distribution component **36** describes the shape of the distribution of the breathing feature over time. For example, a median, different percentiles, range, and/or other description (e.g., characteristics) of the shape of the distribution adequate to characterize the properties of the breath feature over the time windows. In some embodiments, the time windows have a length of at least 30 seconds each. For example, the time windows may have 30, 90, 120, 150 seconds, or other lengths. In some embodiments, the length of time windows may be first estimated based on a known behavior of sleep. Longer windows (e.g., longer than 30 seconds usually used in sleep stages annotated with polysomnography) are more advantageous in characterizing the breathing features in a way that is correlated with the occurrence of different sleep stages. For example, during N3 longer windows may be better in characterizing the breathing features because breathing becomes slower, and more regular. In some embodiments, feature distribution component **36**, is configured to determine distribution of the one or more breathing features over one or more-time windows having different sizes (different length). For example, brief awakenings occurring during the night, often lasting less than one or two minutes, are associated with abrupt changes in breathing patterns and breathing frequency. A combination of breath feature statistics, (meta-features) captured with different window sizes, will allow a proper separation of sleep stages with distinct time and frequency patterns. For example, the sleep state N3 is characterized by longer periods of breathing stability, where for example, Awake is characterized by short transient activity. Sleep is scored within 30 second epochs, so makes sense to use multiples of 30 for window sizes. Through a training process (for the classifier) that accounts for meta-features from all window lengths, an optimal set of meta-features, and thus, an optimal set of window sizes is determined.

**[0037]** Sleep staging component **38** is configured to determine a current sleep state of the subject. For example, wake, N1, N2, N3, REM or combination of these states (e.g., wake, N1+N2, N3, REM). In some embodiments the current sleep state is determined by mapping the distribution of the breathing features to one or more sleep states using a sleep stage classifier. In some embodiments, the sleep stage classifier comprises one or more models configured to determine the current sleep state. In some embodiments, using a selected number of breath feature statistics(meta-features), machine learning models can be used to map parts of the feature space to given sleep stages (wake, N1, N2, N3, REM) or combination of these (most commonly wake, N1+N2, N3, REM). This classification process is performed separately on each of the 30-second epochs, to obtain as a result, a categorical classification of each epoch according to which sleep stage it is more likely to have occurred there. In some embodiments, sleep state models may be trained with inputs (e.g., meta-features) and answers (e.g., the sleep stage). Once trained (with inputs and corresponding answers) the models are ready to be used. In some embodiments, in operation, the sleep state model receives input (e.g., meta-feature) and uses the stored relationships to give its prediction of sleep stage based on how it had been trained. In some embodiments, a bidirectional model that uses information from the past and future may be used. In some embodiments, an unidirectional or causal model that only has information from the past may be used.

**[0038]** In some embodiments, the one or more models are configured to determine the current sleep state based on a plurality of sleep states directly preceding the current state. In some embodiments, the sleep stage classifier uses models that express the likelihood of a state happening based on the observations of that state, what happened in the preceding state, and on the history of states until then. In some cases, the sleep stage classifier uses bidirectional models, where the likelihood of a stage at a given point during the night depends on what happened before, but also what will happen after that point, until the subject finally wakes up in the morning. These models may be more advantageous than models that uses time-shifted input (e.g., Markov) in expressing the likelihood of a current state using memory (e.g., preceding state and history of states until then) to provide context to the current detection.

**[0039]** Models with memory such as recurrent neural networks, long short term memory, or causal convolutional neural networks, are beneficial to explore the structured nature of sleep, and the changes in the likelihood that a sleep stage occurs after a given history of (detected) sleep stages during the night, until that point. For example, if more than one hour of N3 has been detected, it becomes increasingly less likely that N3 still occurs. Memory-based models can use this information to infer not only the most likely sleep stage at each point in time, but also the most likely sequence of sleep stages throughout the whole night based on what happened until that point.

**[0040]** In some embodiments, where causal staging is not required (e.g., for non real-time applications) and observations from the whole night are available, bidirectional models can be used, whereby inference about the sleep stage at a given point can use information about the future, i.e. what the observations are after that point. For example, if the observations of a following state are very likely indicating the presence of a REM stage, it is very unlikely that the current stage is N3 or Wake, but more likely N1 or N2.

**[0041]** Feedback component **39** is configured to provide feedback indicating the current sleep state information. In some embodiments, for sleep stages detected for a full- or partial-night recording, feedback can be given to the user regarding the progression of sleep stages throughout his/her sleep, regarding some statistics, such as the number of minutes (or percentage) in import sleep stages such as N3 or REM, the number of awakenings during the night, the sleep efficiency (percentage of time asleep versus amount of time in bed), etc. In some embodiments, some of the measured sleep statistics (meta-features) can be combined in a single sleep score quantifying the “quality” of the user’s sleep, for example using a weighted average of these sleep statistics, normalized by the person’s age. In some embodiments, feedback on the user interface on the CPAP machine, a smart phone, etc.

**[0042]** User interface **120** is configured to provide an interface between system **100** and subject **70** and/or other users through which subject **70** and/or other users may provide information to and receive information from system **100**. Other users may comprise, for example, a caregiver, a doctor, and/or other users. This enables data, cues, results, and/or instructions and any other communicable items, collectively referred to as “information,” to be communicated between a user (e.g., subject **70**) and one or more of pressure generator **20**, Processor(s) **30**, and/or other components of system **100**. As another example, sleep stages,

sleep duration, breathing feature distribution, therapy information feedback, the breath rate of subject 70, and/or other information may be displayed to a user (e.g., subject 70) via user interface 120. Examples of interface devices suitable for inclusion in user interface 120 comprise a keypad, buttons, switches, a keyboard, knobs, levers, a display screen, a touch screen, speakers, a microphone, an indicator light, an audible alarm, a printer, a tactile feedback device, and/or other interface devices. In one embodiment, user interface 120 comprises a plurality of separate interfaces.

[0043] It is to be understood that other communication techniques, either hard-wired or wireless, are also contemplated by the present disclosure as user interface 120. For example, the present disclosure contemplates that user interface 120 may be integrated with a removable storage interface provided by electronic storage 130. In this example, information may be loaded into system 100 from removable storage (e.g., a smart card, a flash drive, a removable disk, etc.) that enables the user(s) to customize the implementation of system 100. Other exemplary input devices and techniques adapted for use with system 100 as user interface 120 comprise, but are not limited to, an RS-232 port, RF link, an IR link, modem (telephone, cable or other). In short, any technique for communicating information with system 100 is contemplated by the present disclosure as user interface 120.

[0044] In some embodiments, electronic storage 130 comprises electronic storage media that electronically stores information. The electronic storage media of electronic storage 130 may comprise one or both of system storage that is provided integrally (i.e., substantially non-removable) with system 100 and/or removable storage that is removably connectable to system 100 via, for example, a port (e.g., a USB port, a firewire port, etc.) or a drive (e.g., a disk drive, etc.). Electronic storage 130 may comprise one or more of optically readable storage media (e.g., optical disks, etc.), magnetically readable storage media (e.g., magnetic tape, magnetic hard drive, floppy drive, etc.), electrical charge-based storage media (e.g., EEPROM, RAM, etc.), solid-state storage media (e.g., flash drive, etc.), and/or other electronically readable storage media. Electronic storage 130 may store software algorithms, information determined by Processor(s) 30, information received via user interface 120, and/or other information that enables system 100 to function properly. Electronic storage 130 may be (in whole or in part) a separate component within system 100, or electronic storage 130 may be provided (in whole or in part) integrally with one or more other components of system 100 (e.g., user interface 120, Processor(s) 30, etc.)

[0045] Network 150 may include the Internet and/or other networks, Intranets, a PAN (Personal Area Network), a LAN (Local Area Network), a WAN (Wide Area Network), a SAN (Storage Area Network), a MAN (Metropolitan Area Network), near field communication, frequency (RF) link, Bluetooth, Wi-Fi, Li-Fi, a cellular communications network, a Public Switched Telephone Network, and/or any type(s) of wired or wireless network(s). It will be appreciated that this is not intended to be limiting and that the scope of this disclosure includes embodiments in which the components of system 100 are operatively linked via some other communication media. In some cases, the network is a secure local area network, such as a wired Ethernet network behind a firewall.

[0046] Information determined by Processor(s) 30 and/or stored by electronic storage 130 may comprise information related to sensor measurements, respiration of subject 70, sleep states, feedback, and/or other information. The information stored by electronic storage 130 may be viewed via user interface 120, by connecting (wired and/or wireless) to a separate computer, and/or other via other methods. The information stored by electronic storage 130 may be used, for example, to adjust therapy settings, used by a doctor to make medical decisions, and/or for other uses. In some embodiments, system 100 may include a wireless transmitter (not shown) and the information determined by Processor (s) 30, the information stored by electronic storage 130, and/or other information may be communicated to a caregiver, for example, over a wireless network. By way of a non-limiting example, the caregiver may receive use information, subject status, and/or other information, allowing the caregiver to remotely track the therapy delivered by system 100.

[0047] In some embodiments, processing functionality of system 100, described herein, is accomplished locally in a therapy device (e.g., a sensor, a respirator therapy device, etc.) that includes the components of system 100 described above. In some embodiments, processing functionality of system 100 described herein is accomplished outside of system 100 (e.g., remotely by one or more devices connected to system 100 via network 100.) In some embodiments, the processing functionality described herein, may be a combination of processing functionality executed locally and processing functionality executed remotely.

[0048] FIG. 4 illustrates a method 400 for using breathing events in classifying sleep stages for a subject, during a respiratory therapy session with a CPAP device. The operations of method 700 presented below are intended to be illustrative. In some embodiments, method 400 may be accomplished with one or more additional operations not described, and/or without one or more of the operations discussed. Additionally, the order in which the operations of method 400 are illustrated in FIG. 4 and described below is not intended to be limiting.

[0049] In some embodiments, method 400 may be implemented in one or more processing devices (e.g., a digital processor, an analog processor, a digital circuit designed to process information, an analog circuit designed to process information, a state machine, and/or other mechanisms for electronically processing information). The one or more processing devices may include one or more devices executing some or all of the operations of method 400 in response to instructions stored electronically on an electronic storage medium. The one or more processing devices may include one or more devices configured through hardware, firmware, and/or software to be specifically designed for execution of one or more of the operations of method 400.

[0050] At an operation 404, output signals conveying information related to one or more breathing parameters of the subject are generated. In some embodiments, operation 404 is performed by one or more sensors the same as or similar to sensor(s) 40 (shown in FIG. 1 and described herein).

[0051] At an operation 406, one or more breathing features of individual breaths of the subject are determined based on the output signals. In some embodiments, opera-

tion **406** is performed by a physical computer processor the same as or similar to Processor(s) **60** (shown in FIG. 1 and described herein).

[0052] At operation **408**, a distribution of the one or more breathing features over one or more time windows is determined. In some embodiments, operation **406** is performed by a physical computer processor the same as or similar to Processor(s) **60** (shown in FIG. 1 and described herein).

[0053] At an operation **410**, one or more breathing events are detected based on the output signals. In some embodiments, operation **410** is performed by a physical computer processor the same as or similar to Processor(s) **60** (shown in FIG. 1 and described herein).

[0054] At an operation **412**, a sleep state of the subject is determined based upon the distribution of the breathing features and the one or more breathing events. In some embodiments, operation **412** is performed by a physical computer processor the same as or similar to Processor(s) **60** (shown in FIG. 1 and described herein).

[0055] At an operation **414** feedback indicating the current sleep state information is provided. In some embodiments, operation **414** is performed by a physical computer processor the same as or similar to Processor(s) **60** (shown in FIG. 1 and described herein).

[0056] The system and methods of the present disclosure may provide users of CPAP therapy an objective feedback about their sleep. This feedback may be used, for example in a coaching app, to improve their education about sleep in general, and the benefits of sleeping with CPAP machine in their specific case, potentially helping to drive up compliance.

[0057] FIG. 6A illustrates a system **600** for classifying sleep stages for a subject during a respiratory therapy session with a CPAP device **10**, according to one or more embodiments. In some embodiments, system **600** is configured to determine breathing parameters of a subject during a respiratory therapy session provided with the CPAP device **10**. Determining the breathing parameters include detecting individual breaths of the subject. System **600** is configured to classify sleep stages of the subject during the therapy session based on breathing features of the individual breaths. In some embodiments, CPAP device comprises one or more of a pressure generator **20**, one or more sensors **40** (described in relation to FIG. 1 above), a subject interface **90**, one or more physical computer processors **60** (described in relation to FIG. 1 above), a user interface **120** (described in relation to FIG. 1 above), electronic storage **130** (described in relation to FIG. 1 above), a network **150** (described in relation to FIG. 1 above), and/or other components.

[0058] “Respiratory therapy” as meant herein is a session or period of time during which the CPAP device is being used by a subject to treat OSA. The therapy typically involves providing positive airway pressure to the subject in accordance with a software program or algorithm that is controlled by one or more processors (e.g., processors **60** described below). In some embodiments, “Respiratory therapy” as meant herein is a breathable gas therapy (e.g., Oxygen, or other breathable gas therapy). In one or more embodiments, the CPAP device, sensors, pressure generator and one or more processors may be constructed in accordance with the teachings of US Pat. No. 7,168,429B2, hereby incorporated by reference in their entirety.

[0059] In some embodiments, pressure generator **20** is configured to generate a pressurized flow of gas for delivery

to the airway of a subject **70**. Pressure generator **20** may control one or more parameters of the flow of gas (e.g., flow rate, pressure, volume, temperature, gas composition, etc.) for therapeutic purposes, and/or for other purposes. By way of a non-limiting example, pressure generator **20** may be configured to control the flow rate and/or pressure of the flow of gas to provide pressure support to the airway of subject **70**.

[0060] In some embodiments, pressure generator **20** receives a supply of breathable gas from a gas source and elevates the pressure of that gas for delivery to the airway of a subject. Pressure generator **20** may include any device, such as a pump, blower, piston, or bellows that is capable of elevating the pressure of the received breathable gas from the gas source for delivery to the subject. For example, in some embodiments pressure generator **20** may be a blower that is driven at a constant speed during the course of a pressure support treatment to produce a constant pressure or flow rate. In some embodiments, pressure generator **20** may include one or more valves for controlling the pressure, flow rate, flow direction, and/or other parameters of the flow of gas. The present disclosure contemplates controlling the operating speed of the blower, for example, either alone or in combination with one or more valves and/or other devices contained in and/or external to pressure generator **20**, to control the pressure and/or flow of gas provided to subject **70**.

[0061] The gas source may be atmospheric air drawn into the system by pressure generator **20**. In some embodiments, the gas source may comprise a tank of pressurized gas (such as oxygen, air, or other mixture of breathable gas) in fluid communication with pressure generator **20**. In some cases, a separate gas source need not be used, but instead the pressure generator **20** may itself be defined by a canister or tank of pressurized gas, with the pressure delivered to the patient being controlled by a pressure regulator.

[0062] Subject interface **90** is configured to communicate the pressurized flow of breathable gas to the airway of subject **70**. As such, in some embodiments, subject interface **90** comprises conduit **50**, interface appliance **80**, and/or other components. In some embodiments, conduit **50** is configured to convey the pressurized flow of gas to interface appliance **80**. Interface appliance **80** is configured to deliver the flow of gas to the airway of subject **70**. In some embodiments, interface appliance **80** is configured to be non-invasively engaged by subject **70**. Non-invasive engagement comprises removably engaging one or more external orifices of the airway of subject **70** (e.g., nostrils and/or mouth) to communicate gas between the airway of subject **70** and interface appliance **80**. In some embodiments, interface appliance **80** is removably coupled to conduit **50**. Interface appliance **80** may be removed for cleaning and/or for other purposes. In some embodiments, conduit **50** is configured as a mouthpiece to be engaged by the mouth of subject **70**.

[0063] In some embodiments, other interface appliances may be configured as interface appliance **80**. Some examples of interface appliance **80** may comprise, for example, a nasal cannula, a nasal mask, a nasal/oral mask, a full-face mask, a total face mask, or other interface appliances that communicate a flow of gas with an airway of a subject. The present disclosure is not limited to these examples and contemplates delivery of the flow of gas to the subject using any interface appliance. For example, an

endotracheal tube, a tracheotomy tube, a laryngeal mask airway, and/or other invasive interface appliances.

**[0064]** In some embodiments, control component **33** (described in relation to FIG. **1** above) is configured to control operations of CPAP device **10**. For example, in some embodiments, control component **33** is configured to control the pressure generator **20** to generate the flow of gas in accordance with one or more therapy regimes (positive pressure support therapy regime, or other respiratory therapy). In some cases, control component **33** may be configured to control operation of pressure generator **20** based on the output signals from sensor(s) **40**, based on information determined by parameter component **32**, and/or based on information from one or more components within or outside of system **100**. For example, in positive airway pressure support therapy the pressurized flow of gas generated by pressure generator **20** is controlled to replace and/or compliment a patient's regular breathing. Positive airway pressure support therapy may be used to maintain an open airway in a patient so that oxygen and carbon dioxide may be exchanged more easily, requiring little and/or no effort from the patient.

**[0065]** In some embodiments, control component **33** may control pressure generator **20** such that the pressure support provided to the subject via the flow of gas comprises continuous positive airway pressure support (CPAP), bi-level positive airway pressure support (BPAP), proportional positive airway pressure support (PPAP), forced oscillation technique, and/or other types of pressure support therapy. CPAP supplies a fixed positive pressure to maintain a continuous level of positive airway pressure in a patient. BPAP provides a first inspiratory pressure (IPAP) and a second, typically lower, expiratory pressure (EPAP) for easier exhalation during ventilation. In some therapy modes (e.g., PPAP), control component **33** may control pressure generator **20** to apply variable pressure support in which the amount of pressure delivered to the patient during inhalation and/or during exhalation is determined and delivered on a breath by breath basis. In some embodiments, control component **33** may be configured to control pressure generator **20** to temporarily drop the supplied pressure during exhalation (C-Flex) to reduce exhalation effort required by the patient.

**[0066]** In some embodiments, control component **33** is configured to control pressure generator **20** to deliver staged pressure support. In staged pressure support therapy, the pressure delivered by pressure generator **20** gradually increases over time. In some embodiments, control component **33** may control pressure generator **20** to switch therapy modes based on information related to the respiration of subject **70** and/or other information. For example, control component **33** may control pressure generator **20** to change from BPAP to CPAP after a certain number of breaths by subject **70**.

**[0067]** FIG. **5** illustrates an example **500** of a windowing process used to determine distribution of a given breath feature over time, according to one or more embodiments. FIG. **5** describes a distribution **502** of breathing feature values **504** over time. The Y axis of the distribution represents the breathing feature values **504**. For example, in some embodiments, the breathing feature may be a tidal volume of the subject. In this case, the Y axis would represent tidal volume values. The X axis of the distribution represents time. In the example of FIG. **5**, a sliding window **503**,

centered on 30-second epochs **508**, is used in characterization **510** the breathing feature over the sliding time window **503**. The sliding window **503** represents the amount of time over which the breathing feature values are analyzed (or characterized). As can be seen, the sliding time window **503** has a length of at least 30 s. in some examples, the length of window **503** may be of different sizes (e.g., 60, 90, 120, etc.). In some cases, the characterization **510** may be performed over a plurality of windows **503** having different sizes (lengths). The time windows **503** are independent from the number of breaths contained in the windows. This is better than prior methods where characterization of breathing features is either localized to individual breaths or performed in short sequences of breaths (e.g. five breaths) and where variability (variance or standard deviation) is measured. A number of characteristic values **512** are computed over each of the set of breathing feature values (associated, in time, with detected breaths) that occur during each window **503**. It should also be noted that the location of the window relative to the current epoch can take on different positions. FIG. **5** shows the window centered around the current epoch, and thus is using data from both the past and future epochs surrounding the current epoch. In other scenarios where the desire is to implement a purely casual sleep state classifier, the windows could proceed the current epoch, and could also be inclusive of the current epoch.

**[0068]** In some embodiments, processing functionality of system **600**, described herein, is accomplished locally in a therapy device (e.g., a CPAP device) that includes the components of system **100** described above. In some embodiments, processing functionality of system **100** described herein is accomplished outside of system **100** (e.g., remotely by one or more devices connected to system **100** via network **100**.) In some embodiments, the processing functionality described herein, may be a combination of processing functionality executed locally and processing functionality executed remotely.

**[0069]** FIG. **6B** illustrates an example of a system **600** for classifying sleep stages for a subject during a respiratory therapy session with a CPAP device **10**, according to one or more embodiments. The system comprises a CPAP device **10** for providing respiratory therapy to the subject. The CPAP device **10** comprises the pressure generator **20** (not shown here) for generating a pressurized flow of breathable gas for delivery to the subject. System **600** comprises one or more sensors (not shown here) for generating output signals conveying information related to breathing parameters of the subject. For example, the one or more sensors may be configured to measure airflow **602**, and/or pressure **604**. System **600** comprises computer processors configured to detect individual breaths **603** of the subject based on the output signals. The computer processors may be configured to determine a distribution **608** of the breathing features over one or more-time windows. In some embodiments the time windows are of different length **610**. The computer processors are configured to determine a current sleep state of the subject **612** by mapping the distribution of the breathing features to one or more sleep states using a sleep stage classifier. System **600** may provide **614** feedback indicating the current sleep state information. For example, system **600** may be configured to display **613** the determined sleep stage. For example, the display may be user interface described above.

[0070] FIG. 7 illustrates a method 700 for classifying sleep stages for a subject, during a respiratory therapy session with a CPAP device. The operations of method 700 presented below are intended to be illustrative. In some embodiments, method 700 may be accomplished with one or more additional operations not described, and/or without one or more of the operations discussed. Additionally, the order in which the operations of method 700 are illustrated in FIG. 7 and described below is not intended to be limiting.

[0071] In some embodiments, method 700 may be implemented in one or more processing devices (e.g., a digital processor, an analog processor, a digital circuit designed to process information, an analog circuit designed to process information, a state machine, and/or other mechanisms for electronically processing information). The one or more processing devices may include one or more devices executing some or all of the operations of method 700 in response to instructions stored electronically on an electronic storage medium. The one or more processing devices may include one or more devices configured through hardware, firmware, and/or software to be specifically designed for execution of one or more of the operations of method 700.

[0072] At an operation 704, output signals conveying information related to one or more breathing parameters of the subject are generated. In some embodiments, operation 704 is performed by one or more sensors the same as or similar to sensor(s) 40 (shown in FIG. 1 and described herein).

[0073] At an operation 706, one or more breathing features of individual breaths of the subject are determined based on the output signals. In some embodiments, operation 706 is performed by a physical computer processor the same as or similar to Processor(s) 60 (shown in FIG. 1 and described herein).

[0074] At an operation 708, a distribution of the one or more breathing features over one or more-time windows having a length of at least 60 s each is determined. In some embodiments, operation 708 is performed by a physical computer processor the same as or similar to Processor(s) 60 (shown in FIG. 1 and described herein).

[0075] At an operation 710, a sleep state of the subject may be determined. by mapping the distribution of the breathing features to one or more sleep states using a sleep stage classifier, the sleep stage classifier comprising one or more models configured to determine the current sleep state. In some embodiments, operation 710 is performed by a physical computer processor the same as or similar to Processor(s) 60 (shown in FIG. 1 and described herein).

[0076] At an operation 712, feedback indicating the during the respiratory sleep session sleep state information is provided. In some embodiments, operation 712 is performed by a physical computer processor the same as or similar to Processor(s) 60 (shown in FIG. 1 and described herein).

[0077] In the claims, any reference signs placed between parentheses shall not be construed as limiting the claim. The word “comprising” or “including” does not exclude the presence of elements or steps other than those listed in a claim. In a device claim enumerating several means, several of these means may be embodied by one and the same item of hardware. The word “a” or “an” preceding an element does not exclude the presence of a plurality of such elements. In any device claim enumerating several means, several of these means may be embodied by one and the same item of hardware. The mere fact that certain elements

are recited in mutually different dependent claims does not indicate that these elements cannot be used in combination.

[0078] Although the description provided above provides detail for the purpose of illustration based on what is currently considered to be the most practical and preferred embodiments, it is to be understood that such detail is solely for that purpose and that the disclosure is not limited to the expressly disclosed embodiments, but, on the contrary, is intended to cover modifications and equivalent arrangements that are within the spirit and scope of the appended claims. For example, it is to be understood that the present disclosure contemplates that, to the extent possible, one or more features of any embodiment can be combined with one or more features of any other embodiment.

What is claimed is:

1. A sleep staging system comprising:
  - one or more sensors (40) configured to generate output signals conveying information related to one or more breathing parameters of subject; and
  - one or more physical computer processors (60) operatively connected with the one or more sensors, the one or more physical computer processors configured by computer readable instructions to:
    - determine, based on the output signals, one or more breathing features of individual breaths of the subject;
    - determine a distribution of the one or more breathing features over one or more time windows;
    - detect presence of a breathing event based on the output signals;
    - determine sleep states of the subject with a sleep stage classifier model based upon the distribution of the breathing features and the one or more breathing events; and
    - provide feedback indicating the sleep states.
2. The system of claim 1, wherein the one or more physical computer processors are further configured to:
  - determine at least one measured parameter related to the detected breathing event, the measured parameter indicating a number of times one or more breathing events similar to the detected breathing event are detected over one or more of the time windows; and
  - determine sleep states of the subject based on the at least one measured parameter and the distribution of the breathing feature.
3. The system of claim 1, wherein the one or more physical computer processors are further configured to determine a distribution of the one or more breathing features over a plurality of time windows, at least one of the time windows having a length of at least 60 seconds.
4. The system of claim 1, wherein the output signals are non-electroencephalogram (non-EEG) signals.
5. The system of claim, 1 wherein the one or more breathing parameters include respiratory effort of the subject.
6. The system of claim, 1 wherein the one or more breathing parameters include respiratory airflow of the subject.
7. The system of claim 1, wherein the sleep staging system comprises a CPAP device (100), the CPAP device further comprising a pressure generator (20) configured to generate a pressurized flow of breathable gas for delivery to the airway of a subject (70), the one or more physical computer processors (60) being operatively connected with the pressure generator to control delivery of the pressurized

flow of breathable gas to the airway of the subject based on the output signals from the one or more sensors.

8. The system of claim 1, wherein the one or more breathing features of the individual breaths comprise breath duration, duration of inspiration vs expiration, minimum and maximum flow values, and/or tidal volume of each individual breath.

9. A method comprising:

generating, with one or more sensors (40), output signals conveying information related to one or more breathing parameters of subject;

determining, with one or more physical computer processors (60), based on the output signals, one or more breathing features of individual breaths of the subject;

determining, with one or more physical computer processors (60), a distribution of the one or more breathing features over one or more time windows;

detecting, with one or more physical computer processors (60), presence of a breathing event based on the output signals;

determining, with one or more physical computer processors (60), sleep states of the subject with a sleep stage classifier model based upon the distribution of the breathing features and the one or more breathing events; and

providing, with one or more physical computer processors (60), feedback indicating the sleep states.

10. The method of claim 9, wherein the method further comprises:

determining, with one or more physical computer processors (60), at least one measured parameter related to the detected breathing event, the measured parameter indicating a number of times one or more breathing events similar to the detected breathing event are detected over one or more of the time windows; and

determining, with one or more physical computer processors (60), sleep states of the subject based on the at least one measured parameter and the distribution of the breathing feature.

11. The method of claim 9, further comprising determining a distribution of the one or more breathing features over a plurality of time windows, at least one of the time windows having a length of at least 60 seconds.

12. The method of claim 9, wherein the output signals are non-electroencephalogram (non-EEG) signals.

13. The method of claim 9, wherein the one or more breathing parameters include respiratory effort of the subject.

14. The method of claim 9, wherein the one or more breathing parameters include respiratory airflow of the subject.

15. The method of claim 9, further comprising generating a pressurized flow of breathable gas for delivery to the airway of a subject (70), the one or more physical computer processors (60) being operatively connected with the pres-

sure generator to control deliver of the pressurized flow of breathable gas to the airway of the subject based on the output signals.

16. A sleep staging system comprising:

means for sensing (40), configured for generating output signals conveying information related to one or more breathing parameters of subject;

means for determining (60), configured for determining, based on the output signals, one or more breathing features of individual breaths of the subject;

means for determining (60), configured for determining a distribution of the one or more breathing features over one or more time windows;

means for detecting (60), configured for detecting presence of a breathing event based on the output signals;

means for determining (60), configured for determining sleep states of the subject with a sleep stage classifier model based upon the distribution of the breathing features and the one or more breathing events; and

means for providing feedback (60) configured to provide feedback indicating the sleep states.

17. The system of claim 16, further comprising:

means for determining (60), configured for determining at least one measured parameter related to the detected breathing event, the measured parameter indicating a number of times one or more breathing events similar to the detected breathing event are detected over one or more of the time windows; and

means for determining (60), configured for determining sleep states of the subject based on the at least one measured parameter and the distribution of the breathing feature.

18. The system of claim 16, comprising:

means for determining (60), configured for determining a distribution of the one or more breathing features over a plurality of time windows, at least one of the time windows having a length of at least 60 seconds.

19. The system of claim 16, wherein the output signals are non-electroencephalogram (non-EEG) signals.

20. The system of claim 16, wherein the one or more breathing parameters include respiratory effort of the subject.

21. The system of claim 16, wherein the one or more breathing parameters include respiratory airflow of the subject.

22. The system of claim 16, further comprising:

the sleep staging system comprises a CPAP device (100), the CPAP device further comprising a pressure generating means (20) configured to generate a pressurized flow of breathable gas for delivery to the airway of a subject (70), the CPAP device comprising one or more physical computer processors (60) being operatively connected with the pressure generating means to control deliver of the pressurized flow of breathable gas to the airway of the subject based on the output signals from the sensing means.

\* \* \* \* \*

专利名称(译)	在睡眠阶段使用呼吸事件的系统和方法		
公开(公告)号	<a href="#">US20200100728A1</a>	公开(公告)日	2020-04-02
申请号	US16/589191	申请日	2019-10-01
[标]申请(专利权)人(译)	皇家飞利浦电子股份有限公司		
申请(专利权)人(译)	皇家飞利浦N.V.		
当前申请(专利权)人(译)	皇家飞利浦N.V.		
[标]发明人	FERREIRA DOS SANTOS DA FONSECA PEDRO MIGUEL MATTHEWS GREGORY DELANO KANE MICHAEL THOMAS VASKO JR RAYMOND CHARLES KLEE MAREIKE		
发明人	FERREIRA DOS SANTOS DA FONSECA, PEDRO MIGUEL GRASSI, ANGELA MATTHEWS, GREGORY DELANO KANE, MICHAEL THOMAS VASKO, JR., RAYMOND CHARLES KLEE, MAREIKE		
IPC分类号	A61B5/00 A61B5/085 A61B5/087 A61M16/00 A61B5/091		
CPC分类号	A61B5/4818 A61B5/087 A61B5/091 A61B5/4812 A61B5/085 A61M16/024 A61B5/486 A61M2230/40 A61B5/7264 A61B5/02416 A61B5/0245 A61B5/0816 A61B5/0871 A61B5/1102 A61B5/113 A61B5 /4836 A61B5/7267 A61B5/7278 A61B5/7282 A61M16/0069 A61M2016/0027 A61M2016/0033 A61M2205/3306 A61M2205/3331 A61M2205/3368 A61M2205/3553 A61M2205/3584 A61M2205/3592 A61M2205/505 A61M2230/04 A61M2230/10 A61M2230/205 A61M2230/30 A61M2230/50 A61M2230 /63 G16H50/20 A61M16/026		
优先权	62/739591 2018-10-01 US		
外部链接	<a href="#">Espacenet</a> <a href="#">USPTO</a>		

摘要(译)

本公开描述了睡眠分期系统。该睡眠分期系统包括：一个或多个传感器，被配置为生成输出信号，该输出信号传达与受试者的一个或多个呼吸参数有关的信息；以及 和一个或多个与上述一个或多个传感器可操作地连接的物理计算机处理器，所述一个或多个物理计算机处理器由计算机可读指令配置为：基于所述输出信号，确定所述受试者的个体呼吸的一种或多种呼吸特征；确定一个或多个呼吸特征在一个或多个时间窗口内的分布；根据输出信号检测呼吸事件的存在；基于呼吸特征的分布和一个或多个呼吸事件，使用睡眠阶段分类器模型确定受试者的睡眠状态；并提供指示睡眠状态的反馈。

