



US010130279B2

(12) **United States Patent**
Moon et al.

(10) **Patent No.: US 10,130,279 B2**
(45) **Date of Patent: Nov. 20, 2018**

(54) **PORTABLE APPARATUS AND METHOD OF CHANGING SCREEN OF CONTENT THEREOF**

5/6898 (2013.01); A61B 5/742 (2013.01); A61B 5/7475 (2013.01); A61H 5/00 (2013.01);

(Continued)

(71) Applicant: **Samsung Electronics Co., Ltd.**, Suwon-si, Gyeonggi-do (KR)

(58) **Field of Classification Search**

CPC A61B 3/00; A61B 5/0002; A61B 5/0478; A61B 5/048; A61B 5/0482; A61B 5/16; A61B 5/6898; A61B 5/742; A61B 5/7475; G06F 2203/04806; G06F 3/013; (Continued)

(72) Inventors: **Sun-ho Moon**, Suwon-si (KR); **Jong-ho Choi**, Suwon-si (KR); **Se-jin Kwak**, Seoul (KR); **Sung-soo Kim**, Osan-si (KR); **Hwa-kyung Kim**, Seoul (KR); **Jong-youb Ryu**, Suwon-si (KR); **Sang-hyup Lee**, Suwon-si (KR)

(56) **References Cited**

U.S. PATENT DOCUMENTS

(73) Assignee: **Samsung Electronics Co., Ltd.**, Suwon-si (KR)

6,483,485 B1 11/2002 Huang et al.
2010/0137748 A1* 6/2010 Sone A61B 5/1118 600/595

(Continued)

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 0 days.

FOREIGN PATENT DOCUMENTS

(21) Appl. No.: **15/078,445**

CN 103414908 A * 11/2013
JP 3075971 U 3/2001

(Continued)

(22) Filed: **Mar. 23, 2016**

Primary Examiner — Jwalant Amin

(65) **Prior Publication Data**

US 2016/0317056 A1 Nov. 3, 2016

(74) *Attorney, Agent, or Firm* — Jefferson IP Law, LLP

(30) **Foreign Application Priority Data**

Apr. 30, 2015 (KR) 10-2015-0061725

(57) **ABSTRACT**

A portable apparatus and a method of changing a content screen of the portable apparatus are provided. The portable apparatus includes changing a displayed content in response to an increase in a visual fatigue and a method of changing a content screen of the portable apparatus. Some of disclosed various embodiments provide a portable apparatus that calculates a visual fatigue by using user electroencephalogram (EEG) information received from a wearable apparatus and changing a displayed content into another content in response to an increase in the calculated visual fatigue, and a method of changing a content screen of the portable apparatus.

16 Claims, 23 Drawing Sheets


(51) **Int. Cl.**

A61B 5/0482 (2006.01)
G06F 3/01 (2006.01)

(Continued)

(52) **U.S. Cl.**

CPC **A61B 5/0482** (2013.01); **A61B 5/0002** (2013.01); **A61B 5/0478** (2013.01); **A61B 5/16** (2013.01); **A61B 5/6803** (2013.01); **A61B**



- | | |
|--|---|
| <p>(51) Int. Cl.
 <i>A61B 5/00</i> (2006.01)
 <i>G06F 3/0488</i> (2013.01)
 <i>A61B 5/0478</i> (2006.01)
 <i>A61B 5/16</i> (2006.01)
 <i>G06K 9/00</i> (2006.01)
 <i>G16H 40/63</i> (2018.01)
 <i>A61H 5/00</i> (2006.01)
 <i>G06F 19/00</i> (2018.01)
 <i>A61B 3/00</i> (2006.01)
 <i>A61B 5/048</i> (2006.01)
 <i>A61B 3/113</i> (2006.01)</p> | <p>2013/0044291 A1* 2/2013 Kato A61B 3/0025
 351/209
 2014/0016837 A1* 1/2014 Nechyba G06K 9/00228
 382/118
 2014/0276090 A1* 9/2014 Breed A61B 5/18
 600/473
 2014/0333435 A1* 11/2014 Huang G08B 21/24
 340/573.1
 2014/0347265 A1* 11/2014 Aimone G09G 3/003
 345/156
 2015/0051887 A1* 2/2015 Lee G06K 9/00335
 703/2
 2015/0213634 A1* 7/2015 Karmarkar G06T 11/60
 345/589
 2016/0293139 A1* 10/2016 Kwon G09G 5/02</p> |
| <p>(52) U.S. Cl.
 CPC <i>G06F 3/013</i> (2013.01); <i>G06F 3/015</i>
 (2013.01); <i>G06F 3/04886</i> (2013.01); <i>G06F</i>
 <i>19/00</i> (2013.01); <i>G06K 9/00496</i> (2013.01);
 <i>G06K 9/00597</i> (2013.01); <i>G16H 40/63</i>
 (2018.01); <i>A61B 3/00</i> (2013.01); <i>A61B 3/113</i>
 (2013.01); <i>A61B 5/048</i> (2013.01); <i>G06F</i>
 <i>2203/04806</i> (2013.01)</p> | |

FOREIGN PATENT DOCUMENTS

- (58) **Field of Classification Search**
CPC . G06F 3/015; G06F 3/04886; G06K 9/00496;
G06K 9/00597; G16H 40/63
See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

2012/0210245 A1* 8/2012 McCoy H04N 21/47
715/747

JP	2004-110546 A	4/2004
JP	2004-191628 A	7/2004
JP	2005-230030 A	9/2005
JP	2012-227752 A	11/2012
JP	2013-077013 A	4/2013
KR	10-2000-0046835 A	7/2000
KR	10-0463345 B1	5/2005
KR	10-1267637 B1	5/2013
KR	10-2014-0021208 A	2/2014
KR	10-1402739 B1	6/2014
KR	10-2014-0097675 A	8/2014
KR	10-1432044 B1	8/2014

* cited by examiner

FIG. 1




FIG. 2




FIG. 3A




FIG. 3B




FIG. 4




FIG. 5A




FIG. 5B




FIG. 5C




FIG. 5D




FIG. 5E




FIG. 5F




FIG. 6A




FIG. 6B




FIG. 6C




FIG. 6D




FIG. 7A




FIG. 7B




FIG. 7C



FIG. 8A

FIG. 8B




FIG. 9C




FIG. 9B




FIG. 9A




FIG. 10A




FIG. 10B




FIG. 11A




FIG. 11B




FIG. 12A




FIG. 12B





FIG. 12C



**PORTABLE APPARATUS AND METHOD OF
CHANGING SCREEN OF CONTENT
THEREOF**

CROSS-REFERENCE TO RELATED
APPLICATION(S)

This application claims the benefit under 35 U.S.C. § 119(a) of a Korean patent application filed on Apr. 30, 2015 in the Korean Intellectual Property Office and assigned Serial No. 10-2015-0061725, the entire disclosure of which is hereby incorporated by reference.

TECHNICAL FIELD

The present disclosure relates to a portable apparatus and a method of changing a content screen thereof. More particularly, the present disclosure relates to a portable apparatus that changes a displayed content into another content in response to an increase in a visual fatigue of a user, and a method of changing a content screen thereof.

BACKGROUND

Various types of services and functions that are currently provided from a portable apparatus have been gradually expanded. Also, the portable apparatus provides a screen having a high resolution to a user.

As the user uses a screen having high luminance and high resolution for a long time, a visual fatigue of the user may increase. If the visual fatigue of the user is accumulated, a visual display terminal (VDT) syndrome may appear in the user. Also, eyesight of the user may be deteriorated and/or eye disease of the user may occur due to the accumulation of the visual fatigue of the user.

Therefore, there is a need for an apparatus and method of calculating a visual fatigue of a user and addressing an increase in the visual fatigue of the user.

The above information is presented as background information only to assist with an understanding of the present disclosure. No determination has been made, and no assertion is made, as to whether any of the above might be applicable as prior art with regard to the present disclosure.

SUMMARY

Aspects of the present disclosure are to address at least the above-mentioned problems and/or the disadvantages and to provide at least the advantages described below. Accordingly, an aspect of the present disclosure is to provide a display apparatus and a method of changing a content screen of a portable apparatus that includes displaying content, receiving bio-information of the user from a wearable apparatus, calculating a visual fatigue based on the bio-information of the user, and displaying other content in response to an increase in the visual fatigue.

In accordance with an aspect of the present disclosure, a portable apparatus is provided. The portable apparatus includes a display unit configured to display content, a communicator configured to be connected to a wearable apparatus, and a controller configured calculate a visual fatigue by using bio-information of the user received from the wearable apparatus through the communicator and display other content in response to an increase in the visual fatigue.

In accordance with another aspect of the present disclosure, a wearable apparatus is provided. The wearable appa-

ratus includes a sensor located in a body of the wearable apparatus and include a measurement electrode and a reference electrode contacting a body of a user, a communicator configured to be connected to a portable apparatus, and a controller configured to detect an electroencephalogram (EEG) of the user using the sensor and transmit EEG information of the user corresponding to the EEG to the portable apparatus through the communicator, wherein the body of the wearable apparatus may have one of a circular shape, an elliptical shape, and a polygonal shape.

A portable apparatus for changing a displayed content into another content in response to an increase in a visual fatigue of a user and a method of changing a content screen of the portable apparatus may be provided.

A portable apparatus for changing a displayed content into another content to relax a visual fatigue in response to an increase in the visual fatigue and a method of changing a content screen of the portable apparatus may be provided.

A portable apparatus for changing a displayed content into various types of contents relaxing a visual fatigue in response to an increase in the visual fatigue and a method of changing a content screen of the portable apparatus may be provided.

A portable apparatus for calculating a visual fatigue of a user by using EEG data of the user and a method of changing a content screen of the portable apparatus may be provided.

A portable apparatus for changing a displayed content into another content in response to an increase in a visual fatigue calculated by using EEG information of a user received from a wearable apparatus and a method of changing a content screen of the portable apparatus may be provided.

A portable apparatus for changing a displayed content into another content including an ocular movement guide in response to an increase in a visual fatigue calculated by using EEG information of the user received from a wearable apparatus and detecting whether an ocular movement of the user is performed, by using a camera and a method of changing a content screen of the portable apparatus may be provided.

In accordance with another aspect of the present disclosure, a portable apparatus that may calculate a visual fatigue by using brainwave information received from an external source, and a method of changing a content screen thereof may be provided.

Other aspects, advantages, and salient features of the disclosure will become apparent to those skilled in the art from the following detailed description, which, taken in conjunction with the annexed drawings, discloses various embodiments of the present disclosure.

BRIEF DESCRIPTION OF THE DRAWINGS

The above and other aspects, features, and advantages of certain embodiments of the present disclosure will be more apparent from the following description taken in conjunction with the accompanying drawings, in which:

FIG. 1 schematically illustrates a connection between a portable apparatus, a wearable apparatus, and a server according to an embodiment of the present disclosure;

FIG. 2 is a schematic block diagram of a portable apparatus, a wearable apparatus, and a server according to an embodiment of the present disclosure;

FIGS. 3A and 3B are schematic perspective views of a wearable apparatus according to an embodiment of the present disclosure;

FIG. 4 is a schematic flowchart of a method of changing a content screen of a portable apparatus according to an embodiment of the present disclosure;

FIGS. 5A to 11B illustrate a content screen of a portable apparatus according to various embodiments of the present disclosure; and

FIG. 12A to 12C illustrate an environment setting screen of a portable apparatus according to various embodiments of the present disclosure.

Throughout the drawings, it should be noted that like reference numbers are used to depict the same or similar elements, features, and structures.

DETAILED DESCRIPTION

The following description with reference to the accompanying drawings is provided to assist in a comprehensive understanding of various embodiments of the present disclosure as defined by the claims and their equivalents. It includes various specific details to assist in that understanding but these are to be regarded as merely exemplary. Accordingly, those of ordinary skill in the art will recognize that various changes and modifications of the various embodiments described herein can be made without departing from the scope and spirit of the present disclosure. In addition, descriptions of well-known functions and constructions may be omitted for clarity and conciseness.

The terms and words used in the following description and claims are not limited to the bibliographical meanings, but, are merely used by the inventor to enable a clear and consistent understanding of the present disclosure. Accordingly, it should be apparent to those skilled in the art that the following description of various embodiments of the present disclosure is provided for illustration purpose only and not for the purpose of limiting the present disclosure as defined by the appended claims and their equivalents.

It is to be understood that the singular forms “a,” “an,” and “the” include plural referents unless the context clearly dictates otherwise. Thus, for example, reference to “a component surface” includes reference to one or more of such surfaces.

In the following description, the same drawing reference numerals are used for the same elements even in different drawings. The matters defined in the description, such as detailed construction and elements, are provided to assist in a comprehensive understanding of the present disclosure. Thus, it is apparent that the various embodiments of the present disclosure can be carried out without those specifically defined matters. Also, well-known functions or constructions are not described in detail since they would obscure the disclosure with unnecessary detail.

Also, the terms “first”, “second”, etc. may be used to describe diverse components, but the components are not limited by the terms. The terms are only used to distinguish one component from the others. For example, a first element may be referred to as a second element, and the second element may also be referred to as the first element without departing from the scope of the present disclosure. As used herein, the term “and/or” includes any and all combinations of one or more of the associated listed items.

An application refers to application software that is executed in a computer operating system (OS) or a mobile OS to provide services (or information) to a user. For example, the application may include a word processor, a spread sheet, a contacts application, a calendar application, a memo application, an alarm application, a social network system (SNS) application, a chatting application, a map

application, a music player, a visual fatigue management application, or a video player. The application according to various embodiments of the present disclosure may refer to a visual fatigue management application that is executed in a portable apparatus or a visual fatigue management application that is executed in a wearable apparatus (e.g., a brainwave measurement wearable apparatus or the like) that is connected to the portable apparatus by wireless or wired. The application according to the various embodiments of the present disclosure may also refer to software that is executed in a portable apparatus in response to a received user input (e.g., a touch or the like).

According to various embodiments of the present disclosure, a status of a wearable apparatus may refer to a context of the wearable apparatus. Status information corresponding to the status of the wearable apparatus may refer to context information of the wearable apparatus. A status change of the wearable apparatus may be the same as a context change of the wearable apparatus.

A widget refers to a mini application that is one of graphic user interfaces (GUIs) that further smoothly support an interaction between a user and an application or an OS. For example, there may be a weather widget, a calculator widget, a watch widget, etc.

A content may be displayed in an application that is executed in a portable apparatus or a wearable apparatus. For example, the content may include a video file or an audio file played in a video player that is one of applications, a music file played in a music player, a photo file displayed in a photo gallery, a webpage file displayed in a web browser, etc. The content may also include a video file, an audio file, a text file, an image file, or a webpage that is displayed or executed in an application. The term “video” used in the various embodiments of the present disclosure may be used as the same meaning as a moving image. Also, the content may include a video file, an audio file, a text file, an image file, or a webpage that is executed in response to a received user input (e.g., a touch or the like).

The content may include an application screen executed in a wearable apparatus and a user interface (UI) configuring the application screen. The content may also include one content or a plurality of contents.

In various embodiments of the present disclosure, a display may include a screen of a touch screen or a screen of a display unit that displays a content.

In various embodiments of the present disclosure, bio-information of a user may include brainwaves, a temperature, pulses, a heartbeat, pulse rate variations, a blood pressure, blood glucose, breath information, oxygen saturation, a skin status, stress, a stress index, sleep information, etc. of a user.

In various embodiments of the present disclosure, a wearable apparatus may refer to a bio-information detecting apparatus that detects bio-information of a user. The bio-information detecting apparatus may be realized as a watch, glasses, a ring, a bracelet, a necklace, a headband, or the like.

In various embodiments of the present disclosure, a change of another content may include a font size of a content displayed in a displayed application, an addition of a color screen to the content, a display of an ocular movement guide in the content, or a display of an ocular movement animation in the content.

A visual fatigue may occur to a user who concentrates on a content displayed in a portable apparatus or views a content for a long time. Surrounding environment elements (e.g., ambient light, temperature, humidity, etc.) causing the visual fatigue and user bio-elements (e.g., corresponding to

bio-information such as a body temperature, a heartbeat, etc.) may be diverse. Elements causing the visual fatigue may include dazzle, humidity, bloodshot eyes, dimness of letters, dizziness, lethargy and/or insensibility of eyes, or a physical abnormality degree of eyes. Also, the elements causing the visual fatigue may include a fatigue of a part such as a neck or the like, fatigue of an arm and/or a wrist and/or a shoulder, a fatigue of a leg part, or headache. In addition, elements causing the visual fatigue may include a brightness degree of ambient light or a surrounding noise degree.

In the present application, the terms “include” and “comprise” designate the presence of features, numbers, operations, components, elements, or a combination thereof that are written in the specification, but do not exclude the presence or possibility of addition of one or more other features, numbers, operations, components, elements, or a combination thereof. The like reference numerals in the drawings denote elements that perform the same functions.

FIG. 1 schematically illustrates a connection between a portable apparatus, a wearable apparatus, and a server, according to an embodiment of the present disclosure.

Referring to FIG. 1, the portable apparatus 100, the wearable apparatus 200, and the server 300 may be wirelessly connected to one another by respectively using communicators (refer to FIG. 2) of the portable apparatus 200, the wearable apparatus 200, and the server 300. For example, the portable apparatus 100, the wearable apparatus 200, and the server 300 may be connected to one another in an infra-structure mode where the portable apparatus 100, the wearable apparatus 200, and the server 300 are wirelessly connected to one another through an ad-hoc mode or an access point (AP). The portable apparatus 100 and the wearable apparatus 200 may respectively transmit a content received from the server 300 to each other.

The server 300 may be located around the portable apparatus 100 and the wearable apparatus 200 or may be located remotely from the portable apparatus 100 and the wearable apparatus 200 (e.g., in a cloud server or the like).

For example, a wireless communication may be a wireless local area network (LAN), Wi-Fi, Bluetooth low energy, Zigbee, Wi-Fi direct (WFD), ultra-wideband (UWB), infrared data association (IrDA), near field communication (NFC), or the like but is not limited thereto. Also, the portable apparatus 100, an electronic apparatus, the server 300, and the wearable apparatus 200 may be connected to one another by wire through a connector.

The portable apparatus 100 may receive status change information corresponding to a status change (e.g., turning on and/or off, a brainwave detection, or the like) of the wearable apparatus 200 from the wearable apparatus 200 through an application. The portable apparatus 100 may also receive the status change information corresponding to the status change (e.g., turning on and/or off, the brainwave detection, or the like) of the wearable apparatus 200 through the server 300. The portable apparatus may include a front surface 100a and a back surface (not shown). Also, the portable apparatus 100 may include a home screen 191, which may include an icon menu screen 193 that includes, among others, a shortcut icon 193g.

The portable apparatus 100 may change a status of the wearable apparatus 200 (e.g., may request turning on, a brainwave detection, or the like of the wearable apparatus 200) through one of the application and the server 300.

The portable apparatus 100, the wearable apparatus 200, and the server 300 have been described as being directly connected to one another with reference to FIG. 1. However,

the portable apparatus 100, the wearable apparatus 200, and the server 300 may be connected to one another through a sharer, a router, a wireless internet network, or the like.

FIG. 2 is a schematic block diagram of a portable apparatus, a wearable apparatus, and a server according to an embodiment of the present disclosure.

Referring to FIG. 2, the portable apparatus 100 may be connected to another apparatus (e.g., the wearable apparatus 200 or the server 300) by wire or wirelessly by using a mobile communicator 120, a sub communicator 130, and a connector 165.

The portable apparatus 100 according to an embodiment may refer to an apparatus that may calculate a visual fatigue of a user by using bio-information and an application including user electroencephalogram (EEG) received from the wearable apparatus 200 and/or an apparatus that may infer the visual fatigue of the user by using an application without the bio-information of the user (e.g., EEG) received from the wearable apparatus 200.

The portable apparatus 100 may refer to an apparatus that may change a content displayed on a touch screen or a display unit in response to the calculated visual fatigue. For example, the portable apparatus 100 may include a portable phone, a smartphone, a tablet apparatus, a head-mounted display apparatus having a display unit, a Motion Picture Experts Group (MPEG-1 or MPEG-2) Audio Layer 3 (MP3) player, a moving image player, an electronic bulletin board, a monitor, an electronic apparatus (e.g., a refrigerator, a washer, an air conditioner, or the like) having a display unit, a display apparatus, or the like. The head-mounted display apparatus (not shown) that is one of portable apparatuses 100 may include a sensor (e.g., an electrode) that may detect user EEG. If the visual fatigue detected through the sensor increases, the head-mounted display apparatus including the sensor capable of detecting the user EEG may change a content displayed on a display unit (not shown) into another content capable of reducing the visual fatigue.

It will be easily understood by those skilled in the art that the display apparatus may be realized as an analog television (TV), a digital TV, a 3-dimensional (3D) TV, a smart TV, a light emitting diode (LED) TV, an organic LED (OLED) TV, a plasma TV, a curved TV having a fixed curvature screen, a flexible TV having a fixed curvature screen, a bended TV having a fixed curvature screen, and/or a curvature variable TV capable of changing a curvature of a screen through a user input but is not limited thereto.

The portable apparatus 100 may include a touch screen 190 to transmit data (or a content) to an external source through the mobile communicator 120 or the sub communicator 130 or receive the data (or the content) from the external source through the mobile communicator 120 or the sub communicator 130. The portable apparatus 100 may include an input pen 167 and the touch screen 190 to transmit the data (or the content) to the external source through the mobile communicator 120 or the sub communicator 130 or receive the data (or the content) from the external source through the mobile communicator 120 or the sub communicator 130. The portable apparatus 100 may transmit the data to the external source or receive the data from the external source in response to an interaction (e.g., a touch or a touch gesture) input on the touch screen 190. The portable apparatus 100 may also include a display unit (not shown) having only a display panel (e.g., having no touch panel) to transmit the data (or the content) to the external source or receive the data (or the content) from the external source through the mobile communicator 120 or the sub communicator 130.

The portable apparatus **100** may include a controller **110**, the mobile communicator **120**, the sub communicator **130**, a multimedia unit **140**, a camera **150**, a global positioning system (GPS) **155**, an input/output (I/O) unit **160**, a sensor unit **170**, a storage unit **175**, and a power supply unit **180**. The portable apparatus **100** also includes the touch screen **190** and a touch screen controller **195**.

The controller **110** may include a processor **111**, a read only memory (ROM) **112** that stores a control program for controlling the portable apparatus **100**, and a random access memory (RAM) **113** that stores a signal or data input from an outside of the portable apparatus **100** or that is used as a storage area for various types of jobs performed in the portable apparatus **100**.

The controller **110** controls an overall operation of the portable apparatus **100** and a signal flow between internal elements **120** through **195** of the portable apparatus **100** and performs a function of processing the data. The controller **110** controls power supplied to the internal elements **120** through **195** by using the power supply unit **180**. If an input of the user is received or a set condition is satisfied, the controller **110** may operate a sensor of the sensor unit **170** or may execute an OS or an application stored in the storage unit **175**.

The processor **111** may include a graphic processing unit (GPU) (not shown) for graphic processing. The processor **111** may be realized as a system on chip (SoC) including a core (not shown) and a GPU (not shown). The processor **111** may include a single core, a dual core, a triple core, a quad core, and a multiple core. Also, the processor **111**, the ROM **112**, and the RAM **113** may be connected to one another through a bus.

The controller **110** may control the mobile communicator **120**, the sub communicator **130**, the multimedia unit **140**, the camera **150**, the GPS **155**, the I/O unit **160**, the sensor unit **170**, the storage unit **175**, the power supply unit **180**, the touch screen **190**, and the touch screen controller **195**.

The controller **110** according to an embodiment displays the content on a screen, is connected to the wearable apparatus **200** through a communicator, calculates a visual fatigue by using EEG information of the user received from the wearable apparatus **200** through the communicator, and changes the content into another content in response to an increase in the visual fatigue.

The controller **110** may display a content, receive EEG information of the user from the wearable apparatus **200**, calculate a visual fatigue based on the EEG information of the user, and change the content into another content in response to an increase in the visual fatigue.

The controller **110** may control to request the wearable apparatus **200** to detect EEG through the communicator.

If the other content is a content including an ocular movement guide, the controller **110** may control the other content including the ocular movement guide to execute the camera **150** in response to an execution according to an increase in the visual fatigue.

The controller **110** may control to display different color screens in response to a second application displaying the content.

The controller **110** may control to change the other content in response to the second application displaying the content.

The controller **110** may control to display a pop-up window corresponding to the increase in the visual fatigue.

The controller **110** may control to provide a feedback corresponding to the increase in the visual fatigue.

The term “controller” used herein includes the processor **111**, the ROM **112**, and the RAM **113**.

The mobile communicator **120** may be connected to another apparatus (e.g., the wearable apparatus **200** or the server **300**) through a mobile communication network by using one antenna or two or more antennas under control of the controller **110**. The mobile communicator **120** may receive EEG data from the wearable apparatus **200** under control of the controller **110**. The received EEG data (e.g., analog data or digital data) may be stored in the storage unit **175** under control of the controller **110**.

The mobile communicator **120** may transmit and/or receive a wireless signal for a voice call, video call, a text message (e.g., a short message service (SMS)), a multimedia message (e.g., a multimedia messaging service (MMS)), and data communication with a portable phone (not shown), a smartphone (not shown), a tablet personal computer (PC), or another portable apparatus (not shown) having a connectable phone number.

The sub communicator **130** may be connected to another apparatus (e.g., the wearable apparatus **200** or the server **300**) through a wireless LAN **131** and a short-range communicator **132** under control of the controller **110**. The sub communicator **130** may include at least one selected from the wireless LAN **131** and the short-range communicator **132** (e.g., one or both of the wireless LAN **131** and the short-range communicator **132**).

The sub communicator **130** may receive the EEG data from the wearable apparatus **200** under control of the controller **110**. The received EEG data (e.g., analog data or digital data) may be stored in the storage unit **175** under control of the controller **110**.

The wireless LAN **131** may be wirelessly connected to an AP in a place, where the AP is installed, under control of the controller **110**. The wireless LAN **131** may, for example, include Wi-Fi. The wireless LAN **131** supports wireless LAN standard IEEE 802.11x of IEEE. The short-range communicator **132** may perform a short-range communication between the portable apparatus **100** and an external apparatus by wireless without the AP under control of the controller **110**. The short-range communication may include Bluetooth, Bluetooth low energy, IrDA, UWB, NFC, etc.

The portable apparatus **100** may include at least one selected from the mobile communicator **120**, the wireless LAN **131**, and the short-range communicator **132** according to a performance thereof. For example, the portable apparatus **100** may include one of the mobile communicator **120**, the wireless LAN **131**, and the short-range communicator **132** or a combination of the mobile communicator **120**, the wireless LAN **131**, and the short-range communicator **132**. The portable apparatus **100** may be connected to various types of external accessories (e.g., a wireless speaker, a wireless headset, etc.) by using one of the mobile communicator **120** and the sub communicator **130**.

The term “communicator” used herein includes the mobile communicator **120** and the sub communicator **130**.

The multimedia unit **140** may receive an external broadcast and play audio and/or a moving image under control of the controller **110**. The multimedia unit **140** may include a broadcast receiver **141**, an audio player **142**, and a moving image player **143**.

The broadcast receiver **141** may receive a broadcast signal and additional broadcast information (e.g., an electronic program guide (EPG) or an electronic service guide (ESG)) from an external broadcasting station through an antenna (not shown) under control of the controller **110**. Also, the controller **110** may control to play the received broadcast

signal and additional broadcast information by using a touch screen, a video codec (not shown), and an audio codec (not shown).

The audio player **142** may play an audio source (e.g., an audio file including file extension mp3, ogg, or way) pre-stored in the storage unit **175** of the portable apparatus **100** or received from an external source by using the audio codec under control of the controller **110**.

According to an embodiment of the present disclosure, the audio player **142** may play an auditory feedback corresponding to a content changed in response to an increase in a visual fatigue. For example, the audio player **142** may receive EEG information from the wearable apparatus **200** and analyze the received EEG information to play an auditory feedback (e.g., an output of an audio source stored in a storage unit or the like) corresponding to a content changed in response to an increase in a visual fatigue through an audio codec under control of the controller **110**.

According to an embodiment of the present disclosure, the audio player **142** may play an auditory feedback (e.g., an output of an audio source stored in a storage unit or the like) corresponding to a touch detected on the touch screen **190** or consecutive motions of the touch through an audio codec under control of the controller **110**.

The moving image player **143** may play a digital moving image source (e.g., a video file including file extension mpeg, mpg, mp4, avi, mov, or mkv), which is pre-stored in the storage unit **175** of the portable apparatus **100** or received from an external source, by using a video codec under control of the controller **110**. A multimedia application that may be installed in the portable apparatus **100** may play an audio source or a moving image source by using an audio codec and/or a video codec. The multimedia application that may be installed in the portable apparatus **100** may also play a moving source image by using a hardware codec (not shown) and/or a software codec (not shown).

According to an embodiment of the present disclosure, the moving image player **143** may play a visual feedback corresponding to a content changed in response to an increase in a visual fatigue. For example, the moving image player **143** may receive EEG information from the wearable apparatus **200** and analyze the received EEG information to play a visual feedback (e.g., an output of a moving image source stored in a storage unit or the like) corresponding to a content changed in response to an increase in a visual fatigue through a video codec under control of the controller **110**.

It will be easily understood by those skilled in the art that various types of video codecs and audio codecs capable of playing audio and/or video files having various types of file extensions have been produced and sold.

The multimedia unit **140** may include the audio player **142** and the moving image player **143** except the broadcast receiver **141** in response to a performance or a structure of the portable apparatus **100**. Also, the controller **110** may be realized to include the audio player **142** or the moving image player **143** of the multimedia unit **140**.

The term "audio codec" used herein may include one audio codec or two or more audio codecs. The term "video codec" used herein may include one video codec or two or more video codecs.

The camera **150** may capture a still image or a moving image under control of the controller **110**. The camera **150** may include at least one selected from a first camera **151** provided in a front surface (e.g., **100a** of FIG. 1) of the portable apparatus **100** and a second camera **152** provided in a back surface (not shown) of the portable apparatus **100**.

For example, the camera **150** may include one or both of the first camera **151** and the second camera **152**. Also, the first camera **151** or the second camera **152** may include a sub light source (e.g., a flash **153**) that provides an amount of light necessary for capturing.

The camera **150** may be realized to further include the first camera **151** provided in the front surface and an additional camera (e.g., a third camera (not shown)) adjacent to the first camera **151**. For example, a distance between the third camera and the first camera **151** may be realized to be longer than 30 mm and shorter than 80 mm. If the camera **150** further includes the third camera, the controller **110** may capture a 3D still image or a 3D moving image by using the first camera **151** and the third camera.

The camera **150** may be realized to further include the second camera **152** provided in the back surface and an additional camera (e.g., a fourth camera (not shown)) adjacent to the second camera **152**. For example, a distance between the fourth camera and the second camera **152** may be realized to be longer than 30 mm and shorter than 80 mm. If the camera **150** further includes the fourth camera, the controller **110** may capture a 3D still image or a 3D moving image by using the second camera **152** and the fourth camera. Also, the cameras **151** and **152** may perform wide-angle capturing, telephoto capturing, and close-up capturing by using an additional lens (not shown) that is removable from an additional adaptor (not shown).

The GPS **155** periodically receives signals (e.g., orbit information, time information, navigation messages, etc. of GPS satellites) from a plurality of GPS satellites that exist on earth's orbit. In an outdoor place, the portable apparatus **100** may calculate locations of the plurality of GPS satellites and a location of the portable apparatus **100** by using signals received from the plurality of GPS satellites and calculate distances between the plurality of GPS satellites and the portable apparatus **100** by using transmission and/or reception time differences. A location, a time, or a movement speed of the portable apparatus **100** may be calculated through a triangulation. An additional GPS satellite may be required for an orbit correction or a time correction. Even indoors, where signals are received from the plurality of GPS satellites through the GPS **155**, the portable apparatus **100** may calculate a location, a time, or a movement speed of the portable apparatus **100**.

In the outdoor place, the portable apparatus **100** may detect a location or a movement speed by using a wireless AP (not shown). The detection of the location of the portable apparatus **100** may be performed by using a cell-identification (ID) method using an ID of the wireless AP, an enhanced cell-ID method using the ID and a received signal strength (RSS) of the wireless AP, or an angle of arrival (AoA) method using an angle of a signal transmitted from an AP to the portable apparatus **100**.

The portable apparatus **100** may also detect the location or the movement speed of the portable apparatus **100** located indoors by using a wireless beacon (not shown). It will be easily understood by those skilled in the art that an indoor location of the portable apparatus **100** may be detected through various types of methods including the above-described method.

The I/O unit **160** may include at least one selected from one button **161** or two or more buttons **161**, a microphone **162**, a speaker **163**, a vibration motor **164**, the connector **165**, a keypad **166**, and the input pen **167**.

Referring to FIGS. 1 and 5A, the button **161** includes a home button **161a**, a menu button **161b**, and/or a back button **161c** provided in a lower part of the front surface **100a** of the

portable apparatus 100. The button 161 may include a power and/or lock button 161*d* and at least one volume button 161*e* provided in sides thereof. The button 161 of the portable apparatus 100 may also include only the home button 161*a*, the power and/or lock button 161*d*, and the volume button 161*e*. The button 161 of the portable apparatus 100 may be realized as a physical button or a touch button of the touch screen 190. Also, the button 161 of the portable apparatus 100 may be displayed in a text, image, or icon form on the touch screen 190. It will be easily understood by those skilled in the art that a shape, a location, a function, a name, etc. of the button 161 of FIGS. 1 and 5A is only an embodiment for descriptions and thus may be changed, modified, or revised without being limited thereto.

The microphone 162 receives a voice or a sound from an external source to generate an electrical signal under control of the controller 110. The electrical signal generated by the microphone 162 may be converted through an audio codec and then stored in the storage unit 175 or output through the speaker 163 under control of the controller 110. Referring to FIG. 5A, one microphone 162 or two or more microphones 162 may be located in the front surface 100*a*, a side 100*b*, and/or the back surface of the portable apparatus 100. One microphone 162 or two or more microphones 162 may be located only in the side 100*b* of the portable apparatus 100.

The speaker 163 may output sounds corresponding to various types of signals (e.g., a wireless signal, a broadcast signal, an audio source, a moving image file, photo capturing, or the like) decoded by an audio codec under control of the controller 110.

The speaker 163 may output a sound (e.g., a touch manipulation sound corresponding to a phone number input or a photo capturing button manipulation sound) corresponding to a function performed by the portable apparatus 100. Referring to FIGS. 1 and 5A, one speaker 163 or a plurality of speakers 163 may be located in the front surface 100*a*, the side 100*b*, and/or the back surface of the portable apparatus 100. One speaker 163 or a plurality of speakers 163 may be located in the front surface 100*a* of the portable apparatus 100. One speaker 163 may be located in each of the front surface 100*a* and the back surface of the portable apparatus 100. One speaker 163*a* may be located in the front surface 100*a* of the portable apparatus 100, and a plurality of speakers (not shown) may be located in the back surface of the portable apparatus 100.

A plurality of speakers (not shown) may be located in the side 100*b* of the portable apparatus 100. The portable apparatus 100 where an additional speaker (not shown) is located in the side 100*b* may provide a user with a sound effect distinguished from another portable apparatus (not shown) where speakers are located in a front surface and a back surface.

According to an embodiment of the present disclosure, the speaker 163 may output an auditory feedback corresponding to a content changed in response to an increase in a visual fatigue. For example, the speaker 163 may receive EEG information from the wearable apparatus 200 and analyze the received EEG information to output an auditory feedback corresponding to a content changed in response to an increase in a visual fatigue under control of the controller 110.

The vibration motor 164 may convert an electrical signal into a mechanical vibration under control of the controller 110. The vibration motor 164 may include a linear vibration motor, a bar type vibration motor, a coin type vibration motor, or a piezoelectric element vibration motor. For example, if a voice call request is received from another

portable apparatus (not shown), the vibration motor 164 may operate under control of the controller 110 in the portable apparatus 100 that is in a vibration mode.

One vibration motor 164 or two or more vibration motors 164 may be located in the portable apparatus 100. The vibration motor 164 may also vibrate a whole part of the portable apparatus 100 or may locally vibrate a part of the portable apparatus 100.

According to an embodiment of the present disclosure, the vibration motor 164 may output a haptic feedback corresponding to a content changed in response to an increase in a visual fatigue. For example, the vibration motor 164 may receive EEG information from the wearable apparatus 200 and analyze the received EEG information to output a haptic feedback corresponding to a content changed in a response to an increase in a visual fatigue under control of the controller 110. The vibration motor 164 may also provide various types of haptic feedbacks (e.g., a strength and a duration time of vibrations) that are pre-stored or received from an external source based on a control command of the controller 110.

The connector 165 may be used as an interface for connecting the portable apparatus 100 to an external apparatus (not shown) or a power source (not shown).

The portable apparatus 100 may transmit data (or a content) stored in the storage unit 175 to an external source through a wired cable connected to the connector 165 or receive the data (or the content) from the external source through the wired cable under control of the controller 110. The portable apparatus 100 may receive power from a power source (not shown) through a wired cable connected to the connector 165 or charge a battery (not shown) from the power source through the wired cable under control of the controller 110. The portable apparatus 100 may also be connected to an accessory (e.g., a speaker (not shown) and a keyboard dock (not shown)) through the connector 165.

The keypad 166 may receive a key input from the user to control the portable apparatus 100. The keypad 166 includes a physical keypad (not shown) formed in a front surface of the portable apparatus 100, a virtual keypad (not shown) displayed in the touch screen 190, and a physical keypad (not shown) that is connectable by wireless or wired. It will be easily understood by those skilled in the art that the physical keypad formed in the front surface of the portable apparatus 100 may be excluded according to a performance or a structure of the portable apparatus 100.

The input pen 167 may touch (or select) an object (e.g., a menu, a text, an image, a video, a figure, an icon, or a shortcut icon) displayed on (or configuring) a screen (e.g., a memo screen, a notepad screen, a calendar screen, or the like) displayed on the touch screen 190 or a handwriting and/or drawing application of the portable apparatus 100 by the user.

The input pen 167 may touch or select a content (e.g., a text file, an image file, an audio file, a video file, or a webpage) displayed on a screen (e.g., a memo screen, a note screen, a calendar screen, or the like) displayed on the touch screen 190 or a handwriting and/or drawing application of the portable apparatus 100 by the user.

The input pen 167 may perform handwriting or drawing (painting or sketching) on a screen of a handwriting or drawing application displayed on the touch screen 190 of the portable apparatus 100 by the user.

The input pen 167 may touch a capacitive type, resistive type, or electromagnetic resonance (EMR) type touch screen or may input letters or the like by using a displayed virtual keypad. The input pen 167 may include a stylus pen or a

haptic pen where an embedded vibration device (e.g., an actuator or a vibration motor) vibrates. The input pen 167 may also operate (e.g., vibrate) the vibration device in response to control information received from the portable apparatus 100 and sensing information sensed by a sensor (e.g., an acceleration sensor (not shown)) embedded in the input pen 167.

If the input pen 167 is taken from an insertion hole (not shown), the controller 110 may execute a set handwriting and/or drawing application to display a screen (not shown) of the handwriting and/or drawing application on the touch screen 190.

The input pen 167 may include a finger (e.g., including a thumb) of the user. For example, handwriting or drawing may be input by the user in an application displayed on a capacitive type or resistive type touch screen.

If handwriting or drawing is input by a finger of the user in an application displayed on a capacitive type or resistive type touch screen, the controller 110 may detect one touch of fingers including a thumb by using the touch screen 190 and the touch screen controller 195.

It will be easily understood by those skilled in the art that a shape of the insertion hole (not shown) of the portable apparatus 100 and/or a shape (e.g., a circular cross-section or a polygonal cross-section) or a structure (e.g., a battery (not shown)) of the input pen 167 may be changed according to a performance or a structure of the portable apparatus 100.

The sensor unit 170 may detect a status of the portable apparatus 100 and/or a surrounding status of the portable apparatus 100. The sensor unit 170 may include one sensor or a plurality of sensors. For example, the sensor unit 170 may include a proximity sensor 171 that detects a proximity of the user to the portable apparatus 100, an illumination sensor 172 that detects an amount of light around the portable apparatus 100, and a gyro sensor 173 that detects a direction of the portable apparatus 100 by using rotational inertia of the portable apparatus 100. The sensor unit 170 may also include an acceleration sensor that detects an acceleration of a triaxis (e.g., x, y, and z axes) applied to the portable apparatus 100, a gravity sensor that detects an action direction of gravity, or an altimeter that measures a pressure of air to detect an altitude.

The sensor unit 170 may measure a motion acceleration and a gravity acceleration of the portable apparatus 100. If the portable apparatus 100 does not move, the sensor unit 170 may measure only the gravity acceleration. The sensor unit 170 may further include a fingerprint sensor (not shown) that detects a fingerprint of the user or a heart rate sensor that detects a heartbeat of the user.

At least one sensor included in the sensor unit 170 detects a status of the portable apparatus 100, generates an electrical signal corresponding to the detection, and transmits the electrical signal to the controller 110. It will be easily understood by those skilled in the art that a sensor included in the sensor unit 170 may be added, changed, or deleted according to a performance of the portable apparatus 100.

The storage unit 175 may store signals or data that are input and/or output in response to operations of the mobile communicator 120, the sub communicator 130, the multimedia unit 140, the camera 150, the GPS 155, the I/O unit 160, the sensor unit 170, and the touch screen 190 under control of the controller 110. The storage unit 175 may store a GUI related to a control program for controlling the portable apparatus 100 or the controller 110 and an application provided by a manufacturer or downloaded from an

external source, images for providing the GUI, user information, documents, databases (DBs), or pieces of related data.

The storage unit 175 according to an embodiment of the present disclosure may store portable apparatus information, wearable apparatus information, or server information.

The storage unit 175 may store received wearable apparatus status information.

The storage unit 175 may store first through third touches, first through third touch locations, and first through third touch location information.

The storage unit 175 may store a visual feedback (e.g., a video source or the like) that is output from the touch screen 190 in response to an increase in a visual fatigue and is recognizable by the user, an auditory feedback (e.g., a sound source or the like) that is output from the speaker 163 and is recognizable by the user, and a haptic feedback (e.g., a haptic pattern or the like) that is output from the vibration motor 164 and is recognizable by the user.

The storage unit 175 may store a feedback providing time (e.g., 300 msec) of a feedback provided to the user.

The term "storage unit" used herein includes the storage unit 175, the ROM 112 or the RAM 113 of the controller 110, or a memory card (not shown) (e.g., a micro secure digital (SD) card, a memory stick, or the like) installed in the portable apparatus 100. The storage unit may include a nonvolatile memory, a volatile memory, a hard disk drive (HDD), or a solid state drive (SSD).

The power supply unit 180 may supply power to elements 120 through 195 located in the portable apparatus 100 under control of the controller 110. The power supply unit 180 may supply elements of the portable apparatus 100 with power, which is input from a power source (not shown) through a wired cable (not shown) connected to the connector 165, under control of the controller 110. The power supply unit 180 may also supply power to one battery or two or more batteries (not shown) to charge the one battery or the two or more batteries under control of the controller 110. The one battery or the two or more batteries may be located between the touch screen 190 located in the front surface 100a and the back surface.

The power supply unit 180 may wirelessly charge one battery or two or more batteries (not shown) (e.g., according to a magnetic resonance method, an electromagnetic wave method, or a magnetic induction method) under control of the controller 110.

The touch screen 190 includes a touch panel (not shown) that receives a touch input and a display panel (not shown) that displays a screen. The touch screen 190 may provide the user with GUIs corresponding to various types of services (e.g., a voice call, a video call, a data transmission, a broadcast reception, photo capturing, a moving image view, an application execution, etc.). The touch screen 190 transmits an analog signal, which corresponds to a single touch or a multi touch input through the home screen 191 or a GUI, to the touch screen controller 195. The touch screen 190 may receive a single touch or a multi touch through a body of the user (e.g., fingers including a thumb) or the input pen 167.

The display panel (not shown) includes a plurality of pixels and displays an image through the plurality of pixels. For example, the display panel may include a liquid crystal display (LCD), an LED, an OLED, or the like. The display panel may display various operation statuses of the portable apparatus 100, and various types of images and a plurality of objects depending on an execution of an application or a service.

In various embodiments of the present disclosure, a touch is not limited to a touch of the body of the user or the input pen **167** on the touch screen **190** but includes a non-touch of the body of the user or the input pen **167** on the touch screen **190**. For example, the non-touch may include hovering where a distance between the touch screen **190** and the body of the user or the input pen **167** is lower than or equal to 50 mm. It will be easily understood by those skilled in the art that a non-touch distance detectable from the touch screen **190** may be changed according to a performance or a structure of the portable apparatus **100**.

The touch screen **190** may, for example, be realized as a resistive type, a capacitive type, an infrared type, or an acoustic wave type.

The touch screen **190** may include an EMR type. The EMR type touch screen may further include an additional EMR type touch panel (not shown) that receives an input of an input pen (not shown) having a resonance circuit resonating in an EMR type loop coil.

The touch screen **190** according to an embodiment of the present disclosure may output a visual feedback corresponding to a content changed in response to an increase in a visual fatigue. The touch screen **190** may receive EEG information from the wearable apparatus **200** and analyze the received EEG information to display a visual feedback corresponding to a content changed in response to an increase in a visual fatigue under control of the controller **110**.

In the various embodiments of the present disclosure, a display unit may include the touch screen **190**.

The touch screen controller **195** converts an analog signal corresponding to a single touch or a multi touch, which is received from the touch screen **190**, into a digital signal and transmits the digital signal to the controller **110**. The controller **110** may calculate X coordinates and Y coordinates corresponding to a touch location on the touch screen **190** by using the digital signal received from the touch screen controller **195**.

The controller **110** may control the touch screen **190** by using the digital signal received from the touch screen controller **195**. For example, the controller **110** may display a shortcut icon (e.g., denoted by reference numeral **193a** of FIG. **5A**) displayed on the touch screen **190** so as to enable the shortcut icon **193a** to be distinguished from other shortcut icons (e.g., denoted by reference numerals **193b** through **193h**) or execute an application (e.g., a call) corresponding to the selected shortcut icon **193a** of FIG. **5A** to display an application screen in response to an input touch.

The touch screen controller **195** may be realized as one touch screen controller **195** or a plurality of touch screen controllers **195**. The touch screen controller **195** may be included in the controller **110** according to a performance or a structure of the portable apparatus **100**.

The touch screen controller **195** converts an analog signal into a digital signal and transmits the digital signal to the controller **110**, wherein the analog signal corresponds to a touch received from an EMR type touch screen separately from an analog signal corresponding to a single touch or a multi touch received from the touch screen **190**. The controller **110** may calculate X and Y coordinates corresponding to a touch location on an EMR type touch screen by using the digital signal received from the touch screen controller **195**. The EMR type touch screen may also use an EMR type touch screen controller (not shown).

The portable apparatus **100** has been illustrated as including only one touch screen in FIGS. **1** and **2** but may include a plurality of touch screens. The plurality of touch screens

may be respectively located in housings (not shown), and the housings may be connected to one another by a hinge (not shown). Also, a plurality of flexible touch screens may be located in one housing (not shown). The plurality of flexible touch screens may include one display panel and a plurality of touch panels. The plurality of flexible touch screens may include one touch panel corresponding to a plurality of display panels. The plurality of flexible touch screens may also include a plurality of touch panels corresponding to a plurality of display panels.

It will be easily understood by those skilled in the art that at least one element of the portable apparatus **100** of FIG. **2** may be added, delete, or changed in response to a performance of the portable apparatus **100**.

Referring to FIGS. **1** and **2**, the wearable apparatus **200** may be connected to the portable apparatus **100** or the server **300** by wire or wirelessly by using a communicator **230**.

The wearable apparatus **200** according to an embodiment of the present disclosure may refer to an apparatus that may detect bio-information (e.g., EEG of the user). For example, the bio-information of the user may include EEG, a body temperature, a heartbeat, a pulse rate variation, a blood pressure, a blood glucose, breath information, an oxygen saturation, a skin state, a motion amount, stress, a stress index, sleep information, etc. Also, the wearable apparatus **200** may refer to an apparatus that may transmit detected EEG to the portable apparatus **100** and/or the server **300**. For example, the wearable apparatus **200** that detects the EEG of the user may include a headband type wearable apparatus, a cap type wearable apparatus, a hat type wearable apparatus, a headset type wearable apparatus, a headphone type wearable apparatus, or the like.

The wearable apparatus **200** may be connected to the portable apparatus **100** or the server **300** by using the communicator **230**. The wearable apparatus **200** may detect EEG of the user by using a touch type or a non-touch type sensor **270** under control of a controller **210**.

The wearable apparatus **200** may include the controller **210**, the communicator **230**, an I/O unit **260**, the sensor **270**, a storage unit **275**, a battery **280**, and a display unit **290**.

The controller **210** may include a processor **211**, a ROM **212** that stores a control program for controlling the wearable apparatus **200**, and a RAM **213** that stores a signal or data input from an outside of the wearable apparatus **200** and is used as a storage area for various types of jobs performed in the wearable apparatus **200**.

The controller **210** controls an overall operation of the wearable apparatus **200** and a signal flow between internal elements **220** through **290** of the wearable apparatus **200** and performs a function of processing data. The controller **210** may control the battery **280** to supply power to the internal elements **220** through **290** or interrupt power supplied to the internal elements **220** through **290**. Also, if an input of the user or a preset condition is satisfied, the controller **210** may operate the sensor **270**.

The processor **211** may include a GPU (not shown) for graphic processing. The processor **211** may be realized as a SoC type including a core (not shown) and a GPU (not shown). The processor **211** may include a single core, a dual core, a triple core, a quad core, and a multiple core. Also, the processor **211**, the ROM **212**, and the RAM **213** may be connected to one another through a bus.

The controller **210** may control the communicator **230**, the I/O unit **260**, the sensor **270**, the storage unit **275**, the battery **280**, and the display unit **290**.

The controller **210** according to an embodiment of the present disclosure may detect EEG of the user by using the

sensor 270 or may detect a status of the wearable apparatus 200 through an additional sensor (not shown).

The controller 210 may transmit EEG information of the user corresponding to the detected EEG of the user to the portable apparatus 100 or the server 300 through the communicator 230.

The controller 210 may control to transmit changed wearable apparatus status information to the portable apparatus 100 by using the communicator 230 and stored portable apparatus information.

The term "controller 210 of the wearable apparatus 200" used herein includes the processor 211, the ROM 212, and the RAM 213.

The communicator 230 may be connected to the portable apparatus 100 or the server 300 by using a wireless LAN 231 and/or a short-range communicator 232. The communicator 230 may transmit the EEG information of the user to the portable apparatus 100 or the server 300 under control of the controller 210.

The communicator 230 may include the wireless LAN 231 and/or the short-range communicator 232. For example, the communicator 230 may include one or both of the wireless LAN 231 and the short-range communicator 232. The communicator 230 may further include wired Ethernet.

The wireless LAN 231 may be wirelessly connected to an AP in an installation place of the AP under control of the controller 210. For example, the wireless LAN 231 may include Wi-Fi. The wireless LAN 231 supports the wireless LAN standard IEEE 802.11x of IEEE. The short-range communicator 232 may wirelessly perform a short-range communication between the portable apparatus 100 and an external apparatus without the AP under control of the controller 210. The short-range communication may include Bluetooth, Bluetooth low energy, IrDA, UWB, an NFC, etc.

The communicator 230 may transmit the EEG of the user detected by (or stored in) the sensor 270 to the portable apparatus 100 or the server 300 under control of the controller 210. The communicator 230 may periodically (e.g., 500 msec that is changeable) transmit the EEG of the user detected by (or stored in) the sensor 270 to the portable apparatus 100 or the server 300 under control of the controller 210. The communicator 230 may also receive a transmission request of the detected (or stored) EEG of the user or wearable apparatus status information from the portable apparatus 100 and/or the server 300.

The wearable apparatus 200 may be connected to another external apparatus (e.g., a wireless speaker, a wireless headset, another user EEG detecting apparatus, or the like) by using the communicator 230.

The wearable apparatus 200 may also include a mobile communicator (not shown). The mobile communicator of the wearable apparatus 200 may transmit and/or receive a wireless signal for a voice call, a video call, an SMS, an MMS, and a data communication with a portable phone (not shown) having a connectable phone number, a smartphone (not shown), a tablet PC, a tablet apparatus, or another portable apparatus (not shown).

The wearable apparatus 200 may include a camera (not shown) capturing a still image or a moving image under control of the controller 210. The camera may be located in a front surface (e.g., a forehead area of the user) of the wearable apparatus 200.

The wearable apparatus 200 may include a GPS (not shown). The wearable apparatus 200 may calculate a current location of an outdoor wearable apparatus 200 by using the GPS and calculate a location of an indoor wearable apparatus 200 by using an AP.

The I/O unit 260 may include at least one selected from one button or two or more buttons (not shown), a microphone (not shown), a speaker (not shown), a vibration motor (not shown), and a connector (not shown).

The button (not shown) includes a power button. The button may include a volume button (not shown) or a back button (not shown). The button may also include a touch button.

The microphone (not shown) receives a voice or a sound from an external source to generate an electrical signal under control of the controller 210.

The speaker (not shown) may output a sound corresponding to a function or an operation performed in the wearable apparatus 200 under control of the controller 210.

The vibration motor (not shown) may output a vibration corresponding to a function or an operation performed in the wearable apparatus 200 under control of the controller 210.

The connector (not shown) may transmit data (e.g., EEG of the user or the like) stored in the storage unit 275 of the wearable apparatus 200 to an external source or may charge the battery 280 under control of the controller 210.

The sensor 270 may detect EEG of the user under control of the controller 210. The sensor 270 may include a plurality of electrodes. The sensor unit 270 may detect the EEG through the plurality of electrodes. A material of the electrodes may include a conductive fiber (e.g., a silver fiber), a conductive polymer (e.g., polyethylene, polyparaphenylene, polyphenol, polyaniline, or the like), or a metal coated with highly conductive metal. The sensor unit 270 may detect a potential difference occurring from the plurality of electrodes. An EEG measurement may be similar to a voltage measurement having a very large impedance (e.g., a high resistance). EEG data detected by the sensor 270 may be transmitted to the controller 210. For example, the EEG data may include analog data that is raw data or digital data that is acquired by processing raw data. The detected EEG data may be stored in the storage unit 275 under control of the controller 210.

EEG of the user may refer to a current that appears according to a brain activity or waveforms that are acquired by driving, amplifying, and recording the current. Types of EEG vibrating in complicated patterns may be classified into a delta (δ) wave between 0.2 Hz and 3.99 Hz, a theta (θ) wave between 4 Hz and 7.99 Hz, an alpha (α) wave between 8 Hz and 12 Hz, a beta (β) wave between 13 Hz and 29.99 Hz, and a gamma (γ) wave between 30 Hz and 50 Hz. It will be easily understood by those skilled in the art that a frequency band of the above-described EEG is one embodiment and thus may be changed by a surrounding environment and a detecting apparatus.

The δ wave may be remarkably detected from a user who is in deep sleep or a newborn baby. The θ wave may be mainly detected from a child who enters an emotional stability or sleep. The α wave may be mainly detected in a comfortable status such as tension relaxation. The β wave may be mainly detected from a frontal region of the user, i.e., may be detected when the user is awake or performs a conscious activity such as speaking. The (γ) wave may vibrate faster than the (β) wave and may be detected when the user is in an impatient state or processes high-level cognitive information.

The sensor 270 may also detect an internal status or an external status of the wearable apparatus 200. Also, the sensor 270 may detect a change in the internal status or the external status of the wearable apparatus 200 under control of the controller 210. For example, the sensor 270 may include an acceleration sensor (not shown) that detects an

acceleration of tri-axis (e.g., x, y, and z axes) applied to the wearable apparatus 200 or a gyro sensor (not shown) that detects a direction of the wearable apparatus 200 by using rotational inertia of the wearable apparatus 200. It will be easily understood by those skilled in the art that a sensor included in the sensor 270 may be added, changed, or deleted according to a performance of the wearable apparatus 200.

The storage unit 275 may store signals or data that are input and/or output to correspond to operations of the communicator 230, the I/O unit 260, the sensor 270, and the display unit 290 under control of the controller 210. The storage unit 275 may store a GUI related to a control program for controlling the wearable apparatus 200 or the controller 210 and an application provided by a manufacturer or downloaded from an external source, images for providing the GUI, user information, documents, DBs, or pieces of related data.

The storage unit 275 may store data related to an operation of the wearable apparatus 200 or environment information (e.g., a temperature, an acceleration, an illumination intensity, or the like) or status information (e.g. power on, an operation, or the like) detected by the sensor 270 under control of the controller 210.

The storage unit 275 may store EEG data detected by the sensor 270.

The storage unit 275 may store EEG information of the user including at least one selected from raw data and digital data.

The storage unit 275 may store wearable apparatus information corresponding to the wearable apparatus 200, portable apparatus information corresponding to the portable apparatus 100, or server information corresponding to the server 300. For example, it will be easily understood by those skilled in the art that apparatus information may include a plurality of items indicating an identification (ID) for a history management, an apparatus ID, an apparatus name, an apparatus URI, and an apparatus status but may include items indicating various statuses of an apparatus without being limited thereto.

The battery 280 may supply power to internal elements 230 through 290 of the wearable apparatus 200 under control of the controller 210. A power supply unit (not shown) may supply the wearable apparatus 200 with power that is input from an external power source (not shown) through a wired cable (not shown) connected to a connector (not shown) under control of the controller 210. The power supply unit may also charge the one battery 280 or two or more batteries 280 with power that is supplied under control of the controller 210.

The power supply unit may wirelessly (e.g., according to a magnetic resonance method, an electromagnetic method, or a magnetic induction method) charge one battery 280 or two or more batteries 280 under control of the controller 210.

The display unit 290 may provide the user with a GUI corresponding to various types of services (e.g., a voice call, a video call, a data transmission, a broadcast reception, photo capturing, a moving image view, an application execution, etc.) under control of the controller 210. A display panel (not shown) includes a plurality of pixels and displays an image through the pixels. For example, the display panel may be realized as an LCD, an OLED, an LED, or the like. The display panel may display various types of images and a plurality of objects according to various types of statuses, applications, or service executions of the wearable apparatus 200.

The display unit 290 may include a touch screen (not shown) including a display panel (not shown) and a touch panel (not shown). The touch screen may be realized as a resistive type, a capacitive type, an infrared type, or an acoustic wave type.

According to an embodiment of the present disclosure, the display unit 290 may output a visual feedback corresponding to a user EEG detection under control of the controller 210.

It will be easily understood by those skilled in the art that the portable apparatus 100 and the wearable apparatus 200 are classified in FIGS. 1 and 2, but a plurality of portable apparatuses (e.g., tablet apparatuses 1 and 2) having the same types may be embodied.

It will be easily understood by those skilled in the art that at least one selected from elements of the wearable apparatus 200 shown in FIG. 2 may be added, changed, or deleted according to a performance of the wearable apparatus 200.

Referring to FIG. 2, the server 300 may be connected to at least one selected from the portable apparatus 100 and the wearable apparatus 200 through a communicator (not shown) by a wireless or wired connection. The server 300 may request status information from the wearable apparatus 200. The server 300 may receive status information from the wearable apparatus 200. The server 300 may receive a request corresponding to a transmission of the status information of the wearable apparatus 200 from the portable apparatus 100. The server 300 may transmit the status information of the wearable apparatus 200 to the portable apparatus 100.

In various embodiments of the present disclosure, the server 300 may refer to a computing apparatus that may store EEG data received from the wearable apparatus 200 and transmit the stored EEG data to the portable apparatus 100. The server 300 may refer to a computing apparatus that may store EEG data from the wearable apparatus 200 and calculate a visual fatigue by using the stored EEG data.

The server 300 may also refer to a computing apparatus that may store status information of the wearable apparatus 200 received from the wearable apparatus 200 and transmit the stored status information of the wearable apparatus 200 to the portable apparatus 100. The server 300 may include a gateway (not shown), a home network server (not shown) or a cloud server (not shown). A display apparatus (not shown) or a refrigerator (not shown) may act as the server 300 in a home network environment.

It will be easily understood by those skilled in the art that at least one element of the server 300 of FIGS. 1 and 2 may be added, changed, or deleted according to a performance of the server 300.

FIGS. 3A and 3B are schematic perspective views of a wearable apparatus according to an embodiment of the present disclosure.

Referring to FIGS. 3A and 3B, the wearable apparatus 200 that is worn on a head of a user may be realized in a ring shape. The ring shape may include a concentric circle or an ellipse. The wearable apparatus 200 may be realized in a polygon having three or more vertexes. The wearable apparatus 200 may also be realized as a headband type wearable apparatus, a headset type wearable apparatus, or a helmet type wearable apparatus. It will be easily understood by those skilled in the art that the wearable apparatus 200 may be realized in various shapes or types besides the above-mentioned types of wearable apparatuses to detect EEG of the user.

A body 200a of the wearable apparatus 200 may be formed of a high molecular compound, metal, fiber, or

ceramics. A size (e.g., a diameter) of the body 200a of the wearable apparatus 200 having elasticity may vary according to whether to wear or do not wear the body 200a of the wearable apparatus 200. The wearable apparatus 200 may have various diameters in response to a size of a head of the user. For example, the wearable apparatus 200 may be classified as infant, child, youth, or adult.

Some of the elements 210 through 290 shown in FIG. 2 may be located in the body 200a of the wearable apparatus 200. A button of the I/O unit 260 or the display unit 290 may be exposed to an outside of the body 200a of the wearable apparatus 200. Also, the sensor 270 may be exposed to an outside of the wearable apparatus 200.

One electrode or a plurality of electrodes 271 and 272 may be exposed in an internal side 200a1 of the body 200a in the wearable apparatus 200. The sensor 270 may include a measurement electrode 271 that detects EEG and a reference electrode 272 (e.g., ground). A structure of the measurement electrode 271 and a structure of the reference electrode 272 are the same, and thus their repeated descriptions are omitted.

A material of the measurement electrode 271 may include a conductive fiber (e.g., a silver fiber), conductive polymer (e.g., polyacetylene, polyparaphenylene, polyphenol, polyaniline, or the like), or metal coated with conductive metal.

The measurement electrode 271 may contact a body (e.g., a head) of the user. The measurement electrode 271 may have a base 271a and one protrusion 271a1. The protrusion 271a1 of the measurement electrode 271 may have elasticity.

If the protrusion 271a1 having elasticity contacts the body of the user, the protrusion 271a1 may be bent in response to a movement direction of the wearable apparatus 200. For example, if the wearable apparatus 200 is worn on the user, the protrusion 271a1 may be bent in an opposite direction to the movement direction (e.g., a wearing direction) of the wearable apparatus 200. Also, if the wearable apparatus 200 is separated from the body of the user, the protrusion 271a1 may return to the opposite direction to the movement direction of the wearable apparatus 200.

Locations of the measurement electrode 271 and the reference electrode 272 in the wearable apparatus 200 may vary according to the number of measurement electrodes 271 and the reference electrodes 272 of the wearable apparatus 200. A location of the measurement electrode 271 that measures EEG of the user and a location of the reference electrode 272 may be determined based on an activation degree of a visual cortex and a frontal lobe recognizing and processing the activation degree of the visual cortex.

Table 1 below shows examples of a location of the measurement electrode 271 and a location of the reference electrode 272 corresponding to the number of measurement electrodes 271 in the wearable apparatus 200.

TABLE 1

Number of Measurement Electrodes	Location of Measurement Electrode	Location of Reference Electrode
2	Central Area of Forehead, Central Area of Back of the Head	Ear Area, Both Ear Areas
3	Both Areas Based on Central Area of Forehead, Central Area of Back of the Head	Ear Area, Both Ear Areas

As shown in FIG. 3A, if the number of measurement electrodes 271 is 2, the measurement electrodes 271 may be located in a central area of a forehead (e.g., a frontal bone area or a glabella area corresponding to a frontal lobe) and a central area of a back of the head (e.g., an occipital bone area corresponding to an occipital lobe). The reference electrodes 272 may be located in an ear area (e.g., a temporal bone corresponding to a temporal lobe) or both ear areas.

The locations of the measurement electrodes 271 and the locations of the reference electrodes 272 may intersect with each other (e.g., at an angle between 45° and 135°). Locations of a plurality of measurement electrodes face one another. Also, the reference electrodes 272 face each other. The reference electrodes 272 may intersect with one another (e.g., at an angle between 45° and 135°).

As shown in FIG. 3B, if the number of measurement electrodes 271 is 3, one of the measurement electrodes 271 may be located in the central area of the forehead (e.g., the frontal bone area or the glabella area corresponding to the frontal lobe), and two of the measurement electrodes 271 may be located in the central area of the back of the head (e.g., the occipital area corresponding to the occipital lobe). The reference electrodes 272 may be located in the ear area (e.g., the temporal bone corresponding to the temporal lobe) or both ear areas.

The locations of the measurement electrodes 271 may intersect with the locations of the reference electrodes 272. A plurality of measurement electrodes 271 that are located in the back of the head based on a virtual extension line that is connected from the measurement electrode 271 located in the forehead toward the back of the head may be located at the same intervals (e.g., on left and right sides). Also, locations of a plurality of reference electrodes 272 face one another. The reference electrodes 272 may intersect with one another (e.g., at an angle between 45° and 135°).

If the number of measurement electrodes 271 increases, the measurement electrodes 271 may be located in a top area of the head (e.g., a parietal bone area corresponding to a parietal lobe).

It will be easily understood by those skilled in the art that Table 1 above does not limit the number of measurement electrodes 271, locations of the measurement electrodes 271, and locations of the reference electrodes 272 to the above-described items but may indicate various combinations of locations of the measurement electrodes 271 and locations of the reference electrodes 272 corresponding to the number of measurement electrodes 271.

FIG. 4 is a schematic flowchart of a method of changing a content screen of a portable apparatus according to an embodiment of the present disclosure.

FIGS. 5A to 12B illustrate a screen of a portable apparatus according to various embodiments of the present disclosure.

Referring to FIG. 4, an application is executed in the portable apparatus in operation S410.

Referring to FIG. 5A, the portable apparatus 100 may display an application (e.g., corresponding to shortcut icons 193a through 193i) or a widget 194 on a home screen 191 distinguished from a status bar 192. Also, a user wears the wearable apparatus 200. For example, the wearable apparatus 200 may be worn on a head of the user.

The user may perform a first touch (501) on the shortcut icon 193g corresponding to a visual fatigue application (e.g., Smart-eye) that is a selection target of the shortcut icons 193a through 193i displayed on a screen of the portable apparatus 100. It will be easily understood by those skilled in the art that a calculation of a visual fatigue of a user may

be embodied as a visual fatigue calculation application, a visual fatigue OS, or visual fatigue calculation middleware.

The controller **110** may detect the first touch **501** by using the touch screen **190** and the touch screen controller **195**. The controller **110** may calculate a first touch location **501a** (e.g., X1 and Y1 coordinates) corresponding to the first touch **501** by using an electrical signal received from the touch screen controller **195**.

The controller **110** may store first touch location information corresponding to the first touch location **501** in the storage unit **175**. The stored first touch location information may include a touch ID for a history management, a touch location, a touch detection time, or touch information (e.g., a touch pressure, a touch direction, a touch duration time, or the like).

The controller **110** may also or alternatively detect a first hovering (not shown) by using the touch screen **190** and the touch screen controller **195**. The controller **110** may calculate a first hovering location (not shown) (e.g., X11 and Y11 coordinates) corresponding to the first hovering by using an electrical signal received from the touch screen controller **195**.

The controller **110** may store first hovering location information corresponding to the first hovering location in the storage unit **175**. The stored first hovering location information may include a hovering ID for a history management, a hovering detection location, a hovering detection time, or hovering information (e.g., a hovering height *h*, a hovering direction, a hovering duration time, or the like).

A touch of the input pen **167** is a single point touch. The controller **110** may detect the touch of the input pen **167** as the single point touch. Also, the controller **110** may determine a touch of an EMR type input pen (not shown) through a second touch panel (not shown). The controller **110** may determine a touch of an input pen (e.g., a capacitive type input pen), which is not an EMR type, according to a single point touch.

Referring to FIG. **5B**, the controller **110** of the portable apparatus **100** may display an application (e.g., Smart-eye) screen **600** corresponding to the first touch **501** on a screen of the portable apparatus **100**. The application screen **600** displayed to correspond to the first touch **501** may include a home screen of an application.

The home screen **600** of the application may include may include an introduction area **601** that introduces the application (e.g., Smart-eye) and an interaction area **602** that receives an interaction (e.g., a touch, a touch gesture input, or the like) between the application and the user. The interaction area **602** may display a button **602a** corresponding to “connect the headband” and/or a button **602b** corresponding to “start checking EEG . . .” corresponding to a visual fatigue.

FIGS. **12A** to **12C** illustrate an environment setting screen of a portable apparatus according to an embodiment of the present disclosure.

Referring to FIGS. **12A** to **12C**, if a user selects a shortcut icon **600a** corresponding to an environment setting located on a top of the home screen **600** of the application, the controller **110** may display an environment setting screen **800** as shown in FIG. **12A**. If the user selects the shortcut icon **600a**, the controller **110** may change the home screen **600** of the application into the environment setting screen **800** corresponding to a visual fatigue.

Visual fatigue settings menu **800a** displayed on the environment setting screen **800** may include selections to address visual fatigue related to an application **801**, which addresses a visual fatigue according to each application, or

related to a time zone **802**, which addresses a visual fatigue according to time. It will be easily understood by those skilled in the art that the items displayed on the environment setting screen **800** may be changed or deleted according to a function and/or a performance of the portable apparatus **100**.

If the user selects the application **801** that is a menu for setting the visual fatigue according to applications, the controller **110** may display a visual fatigue setting screen **810** according to each application.

FIG. **12B** illustrates an example of the visual fatigue setting screen **810** according to each application. Referring to FIG. **12B**, items displayed on the visual fatigue setting screen **810** according to each application may include an e-book **811**, a web browser **812**, a video player **813**, a game **814**, a magazine **815**, or a social network system **816**. The user may select the items **811** through **816** and set a detailed environment to be provided in the event of visual fatigue. For example, if the user selects the web browser **812**, the user may set a detailed visual fatigue environment of the web browser **812**. The setting of the detailed visual fatigue environment of the web browser **812** may include an ocular movement guide **812a**, a font change **812b**, and a content UI change **812c**. The setting of the detailed visual fatigue environment of the web browser **812** may further include a color screen (e.g., a color filter) control, a luminance control, a color control, a chroma control, etc.

It will be easily understood by those skilled in the art that items (e.g., applications **811** through **816** or visual fatigue corresponding items **812a** through **812c**) displayed on the visual fatigue setting screen **810** according to each application may be added, changed, or deleted according to a function and/or a performance of the portable apparatus **100**.

If the user selects the time zone **802**, the controller **110** may display a visual fatigue setting screen **820** according to each time zone. FIG. **12C** illustrates an example of a visual fatigue setting screen **820** for setting a visual fatigue according to time zone. Referring to FIG. **12C**, items displayed on the visual fatigue setting screen **820** according to each time zone may include a time zone **821** between 8 o'clock and 17 o'clock and a time zone **822** between 17 o'clock and 24 o'clock. The user may select the items **821** and **822** and set a detailed environment. For example, if the user selects the time zone **822** between 17 o'clock and 24 o'clock, the user may set a detailed visual fatigue environment of the time zone **822** between 17 o'clock and 24 o'clock. The setting of the detailed visual fatigue environment of the time zone between 17 o'clock and 24 o'clock may include an ocular movement guide **822a**, a font change **822b**, and a content UI change **822c**.

It will be easily understood by those skilled in the art that the items (e.g., the time zones **821** and **822**) displayed on the visual fatigue setting screen **820** according to each time zone and the items **822a** through **822c** corresponding to a visual fatigue may be added, changed, or deleted according to a function and/or a performance of the portable apparatus **100**.

In operation **S420** of FIG. **4**, a wearable apparatus is connected.

Referring to FIG. **5B**, the user may perform a second touch **502** on the button **602a** corresponding to “connect the headband” on the home screen **600** of the application (e.g., Smart-eye).

The controller **110** may detect the second touch **502** by using the touch screen **190** and the touch screen controller **195**. The controller **110** may calculate a second touch location **502a** (e.g., X2 and Y2 coordinates) corresponding

to the second touch **502** by using an electrical signal received from the touch screen controller **195**.

The controller **110** may store second touch location information corresponding to the second touch location **502a** in the storage unit **175**. The stored second touch location information may include a touch ID for a history management, a touch location, a touch detection time, or touch information (e.g., a touch pressure, a touch direction, a touch duration time, or the like).

A detection of a second hovering performed in operation **S420** of FIG. **4** is similar to a detection of first hovering performed in operation **S410** of FIG. **4**, and thus a repeated description thereof is omitted.

The controller **110** of the portable apparatus **100** may search for the wearable apparatus **200** around the portable apparatus **100** by using a communicator. The wearable apparatus **200** that is a connection target may be selected from a search list (not shown) corresponding to a search result of a wearable apparatus displayed on the screen of the portable apparatus **100**. The wearable apparatus **200** that is the connection target may be selected by the user or the controller **110**. If only the wearable apparatus **200** that is the connection target is searched from the search list, the controller **110** may select the wearable apparatus **200** that is the connection target without a user input.

The controller **110** of the portable apparatus **100** may be connected to a communicator of the wearable apparatus **200** through a first wireless communication by using a communicator in response to the selection. For example, the first wireless communication may be a wireless communication (e.g., a short-range communication) having a limited transmission distance (e.g., a distance lower than or equal to 1 m, lower than or equal to 50 m, or lower than or equal to 100 m). The portable apparatus **100** and the wearable apparatus **200** may be connected to each other through the first wireless communication having the limited transmission distance. The first wireless communication may be a short-range wireless communication but is not limited thereto. A second wireless communication may be a long-range wireless communication, e.g., may be a mobile communication, but is not limited thereto.

If the portable apparatus **100** and the wearable apparatus **200** are connected to each other through Bluetooth that is one of first wireless communications, the portable apparatus **100** and the wearable apparatus **200** may be connected to each other through a mutual support profile (e.g. a serial port profile (SPP), an advanced audio distribution profile (A2DP), an audio/video remote control profile (AVRCP), or a hands-free profile (HFP)). Also, the portable apparatus **100** and the wearable apparatus **200** may be connected to each other through Wi-Fi that is one of first wireless communications. It will be easily understood by those skilled in the art that the above-described profile is only an example, and a profile mutually supporting the portable apparatus **100** and the wearable apparatus **200** may be added, changed, or deleted.

If the portable apparatus **100** and the wearable apparatus **200** are connected to each other, the controller **110** of the portable apparatus **100** may store wearable apparatus information received from the wearable apparatus **200** in the storage unit **175**. The stored wearable apparatus information may include wireless connection information (e.g., a subsystem identification (SSID), an Internet protocol (IP) address, an media access control (MAC) address, a channel number, a security key, or the like), a product name of the wearable apparatus **200**, an ID of the wearable apparatus **200**, an MAC address of the wearable apparatus **200**, a type

of the wearable apparatus **200**, a profile of the wearable apparatus **200**, a communication method of the wearable apparatus **200**, etc.

If the portable apparatus **100** and the wearable apparatus **200** are connected to each other, the controller **210** of the wearable apparatus **200** may store portable apparatus information received from the portable apparatus **100** in the storage unit **275**. The portable apparatus information stored in the storage unit **275** of the wearable apparatus **200** is similar to the wearable apparatus information stored in the storage unit **175** of the portable apparatus **100**, and thus a repeated description thereof is omitted.

If the portable apparatus **100** and the wearable apparatus **200** are connected to each other, the controller **110** of the portable apparatus **100** may request a current status from the wearable apparatus **200**. The current status of the wearable apparatus **200** may include an operation status (e.g., a working or busy status), a standby status, a sleep status, or a hold status.

In various embodiments of the present disclosure, the current status of the wearable apparatus **200** may be the standby status.

The controller **210** of the wearable apparatus **200** may transmit wearable apparatus status information to the portable apparatus **100** through the communicator **230** in response to a request. The controller **110** of the portable apparatus **100** may store the received wearable apparatus status information in the storage unit **175**.

If the portable apparatus **100** and the wearable apparatus **200** are connected to each other, the controller **110** of the portable apparatus **100** may display the home screen **600** of the application.

According to an embodiment of the present disclosure, the controller **210** of the wearable apparatus **200** that is turned on may search for the portable apparatus **100** around the wearable apparatus **200** by using the communicator **230**. The portable apparatus **100** may be selected from a search list (not shown) corresponding to a search result of the portable apparatus **100** displayed on the display unit **290** of the wearable apparatus **200**. The portable apparatus **100** that is a connection target may be selected by the user or the controller **210**. If only the portable apparatus **100** that is the connection target is searched from the displayed search list, the controller **210** may select the portable apparatus **100** that is the connection target without a user input.

The controller **210** of the wearable apparatus **200** may be wirelessly connected to a communicator of the portable apparatus **100** by using the communicator **230** in response to the selection.

If the portable apparatus **100** and the wearable apparatus **200** are connected to each other, the controller **210** of the wearable apparatus **200** may store portable apparatus information received from the portable apparatus **100** in the storage unit **275**. The stored portable apparatus information may include wireless connection information (e.g., an SSID, an IP address, a channel number, a security key, or the like), a product name of the portable apparatus **100**, an ID of the portable apparatus **100**, an MAC address of the portable apparatus **100**, a type of the portable apparatus **100**, a profile of the portable apparatus **100**, a communication method of the portable apparatus **100**, etc.

In operation **S430** of FIG. **4**, the measuring of a visual fatigue starts.

A method of measuring and calculating the visual fatigue will be described in greater detail later.

Referring to FIG. 5B, the user may perform a third touch 503 on the button 602b corresponding to “start checking a visual fatigue . . .” on the home screen 600 of the application (e.g., Smart-eye).

The controller 110 may detect the third touch 503 by using the touch screen 190 and the touch screen controller 195. The controller 110 may calculate a third touch location 503a (e.g., X3 and Y3 coordinates) corresponding to the third touch 503 by using an electrical signal received from the touch screen controller 195.

The controller 110 may store third touch location information corresponding to the third touch location 503a in the storage unit 175. The stored third touch location information may include a touch ID for a history management, a touch location, a touch detection time, or touch information (e.g., a touch pressure, a touch direction, a touch duration time, or the like).

A detection of a third hovering performed in operation S430 of FIG. 4 is similar to the detection of the first hovering performed in operation S410 of FIG. 4, and thus a repeated description thereof is omitted.

The controller 110 may request a measurement of EEG of the user from the wearable apparatus 200 in response to a third touch. If the third touch is detected, the controller 110 may generate a control command (e.g., a control packet) corresponding to the measurement of the EEG of the user.

The controller 110 may transmit the generated control command to the wearable apparatus 200 through a communicator. The control command transmitted to the wearable apparatus 200 through the communicator may have a hierarchical structure.

The control packet corresponding to the control command may include three frames including a MAC header (not shown) corresponding to an address and a length of a receiver (e.g., a wearable apparatus), a payload (not shown) corresponding to an EEG measurement request of the wearable apparatus 200, and a cyclical redundancy check (CRC) (not shown) corresponding to a transmission error detection.

The storage unit 175 may store the control command, which is generated corresponding to a user EEG measurement request from the wearable apparatus 200, under control of the controller 110.

The controller 210 of the wearable apparatus 200 may receive the control command corresponding to the user EEG measurement request transmitted from the portable apparatus 100. The received control command may be stored in the storage unit 275 under control of the controller 210.

The controller 210 of the wearable apparatus 200 may start measuring EEG of the user in response to the received control command. The controller 210 of the wearable apparatus 200 may measure raw data corresponding to the EEG of the user by using the measurement electrode 271 and the reference electrode 272. The raw data corresponding to the measured EEG of the user may be stored in the storage unit 275 under control of the controller 210.

The controller 210 of the wearable apparatus 200 may convert the measured raw data into digital data. The converted digital data may be stored in the storage unit 275 under control of the controller 210.

The raw data may be stored as EEG information of the user, including an ID for a history management, a wearable apparatus name, the number of sensors, the number of electrodes, a measurement date, a measurement time, or raw data (or converted digital data), in the storage unit 275.

The controller 210 of the wearable apparatus 200 may transmit at least one selected from the raw data, the digital data, and EEG information of the user stored in the storage

unit 275 to the portable apparatus 100 through the communicator 230. The controller 210 of the wearable apparatus 200 may also transmit the EEG information of the user stored in the storage unit 275 to the portable apparatus 100 through the communicator 230.

In various embodiments of the present disclosure, the EEG information of the user may include the raw data or the converted digital data.

The controller 210 of the wearable apparatus 200 may periodically (e.g., 100 msec that is changeable by setting) transmit the stored raw data and/or digital data to the portable apparatus 100 through the communicator 230.

The controller 110 of the portable apparatus 100 may receive the EEG information of the user from the wearable apparatus 200 through a communicator. The storage unit 175 may store the received EEG information of the user under control of the controller 110.

In operation S440 of FIG. 4, a content is displayed on a screen of the portable apparatus.

Referring to FIG. 5C, the controller 110 of the portable apparatus 100 may display a content (e.g., a webpage 700) on the screen. That is, the user may touch a shortcut icon 193d of FIG. 5A corresponding to a web browser.

The controller 110 may detect a touch (not shown) by using the touch screen 190 and the touch screen controller 195. The controller 110 may calculate a touch location (e.g., X and Y coordinates (not shown)) corresponding to the touch by using an electrical signal received from the touch screen controller 195.

A detection of a touch on a shortcut icon corresponding to a web browser performed in operation S440 of FIG. 4 is similar to the detection of the first touch performed in operation S410 of FIG. 4, and thus a repeated description thereof is omitted.

Referring to FIG. 5C, the controller 110 may execute a web browser in response to the touch. The controller 110 may display the webpage 700 through the web browser executed in response to the touch. The user may perform web surfing by using the displayed web browser.

It will be easily understood by those skilled in the art that a web browser displaying a content (e.g., a webpage) is one of various embodiments of the present disclosure, and various types of applications displaying (or playing) various types of contents including a video player playing an audio file or a video file, a music player playing a music file, a photo gallery displaying a photo file, a word processor writing a document, etc. may be executed by an input of a user.

In operation S450 of FIG. 4, EEG information is received from the wearable apparatus.

Referring to FIG. 5D, the controller 110 of the portable apparatus 100 may receive EEG information of the user from the wearable apparatus 200 through a communicator. The received EEG information of the user may include raw data or converted digital data.

The EEG information of the user received from the wearable apparatus 200 may vary in response to the number of the measurement electrodes 271 of the wearable apparatus 200. If the number of measurement electrodes 271 of the wearable apparatus 200 is 2 (e.g., refer to FIG. 3A), the received EEG information of the user may correspond to 2 channels. If the number of measurement electrodes 271 of the wearable apparatus 200 is 3 (e.g., refer to FIG. 3B), the received EEG information of the user may correspond to 3 channels. In (a) of FIG. 5D, the EEG information of the user received from the wearable apparatus 200 may correspond to 4 channels.

The storage unit **175** may store the received EEG information of the user under control of the controller **110**.

The controller **110** may first calculate a visual fatigue of the user who is in a rest status, by using the wearable apparatus **200**.

A generation equation for calculating the visual fatigue of the user may be expressed as in Equation 1 below. The controller **110** may perform an operation by using Equation 1 below to calculate the visual fatigue of the user.

$$\text{Visual Fatigue} = \frac{(\theta + \alpha)}{\beta} \quad \text{Equation 1}$$

In Equation 1 above, θ denotes a size of a theta wave, α denotes a size of an alpha wave, and β denotes a size of a beta wave. The visual fatigue calculated by using Equation 1 above may have a range between 0.1 and 3.4. The visual fatigue in the rest status may be lower than or equal to 2.2. Also, if the visual fatigue is higher than or equal to 2.6, the controller **110** may determine an increase in the visual fatigue.

The controller **110** may determine a visual fatigue of the user in the rest status by using received user EEG and Equation 1. The controller **110** may also determine the visual fatigue of the user in the rest status by using user EEG received in a pre-stored user visual fatigue range (e.g., calculated by using Equation 1). For example, the user visual fatigue in the rest status may be lower than or equal to about 2.2. A threshold value corresponding to an increase in a visual fatigue may be 2.6. The threshold value may be changed by a body condition and/or a surrounding environment of the user.

The calculated user visual fatigue in the rest status may be stored in the storage unit **175** under control of the controller **110**.

It will be easily understood by those skilled in the art that the calculated user visual fatigue in the rest status may be changed by the body condition and/or the surrounding environment of the user.

The controller **110** may determine the increase in the visual fatigue of the user by using a pre-stored user visual fatigue in a rest status.

In operation **S460** of FIG. 4, the received EEG information of the user is analyzed.

Referring to FIG. 5D, the controller **110** may calculate the visual fatigue of the user by using the received EEG information of the user and a visual fatigue application. The controller **110** may analyze user EEG according to frequency bands by using the visual fatigue application. The controller **110** may perform fast fourier transform (FFT) on the received EEG information of the user to analyze the received EEG information of the user. For example, if an amplitude change is large on a horizontal axis (e.g., time) of (a) of FIG. 5D, a frequency component may be located in a high area of a vertical axis (e.g., power) of (b) of FIG. 5D.

The controller **110** may calculate the visual fatigue by using a difference in a latency of a peak value of two EEGs that are respectively measured by a measurement electrode **271** located in an occipital lobe accepting a visual stimulus from the received EEG information of the user and a measurement electrode **271** located in a frontal lobe processing the visual stimulus. The latency may refer to a time when waves of EEG greatly fluctuate after receiving a stimulus with an increase in the visual fatigue of the user.

The controller **110** may generate an average frequency component of EEG for a total period for which user EEG is collected through FFT.

The calculated visual fatigue may be stored in the storage unit **175** under control of the controller **110**.

In operation **S470** of FIG. 4, it is determined whether the visual fatigue increases.

As in (b1) and (b2) of FIG. 5D, the controller **110** may determine an increase in the visual fatigue. If the visual fatigue of the user increases, power of θ and a wave bands may increase. If power increases in a band between 6 Hz and 7 Hz, which is a θ wave, through an analysis of user EEG, the controller **110** may determine an occurrence of a visual fatigue of the user. Also, if power increases in a band between 8 Hz and 11 Hz, which is an α wave through a user EEG analysis, the controller **110** may determine an occurrence in the visual fatigue of the user.

The controller **110** may compare a pre-stored visual fatigue in a rest status and a visual fatigue calculated from the received EEG information of the user. If the visual fatigue calculated by using the received EEG information of the user and Equation 1 is higher than or equal to 2.6, the controller **110** may determine the increase in the visual fatigue of the user.

The controller **110** may determine the increase in the visual fatigue of the user by using one or both of a power increase of the θ wave band and a power increase of the α wave band.

If it is determined in operation **S470** of FIG. 4 that the visual fatigue does not occur, the method of changing the content screen of the portable apparatus ends.

On the other hand, if it is determined in operation **S470** that the visual fatigue does occur, a displayed content is changed in operation **S480**.

Referring to FIGS. 5E to 11B, the controller **110** may change a content (e.g., a webpage) displayed on a web browser.

Referring to FIG. 5E, the controller **110** may display a pop-up window **701** corresponding to an occurrence of a visual fatigue of the user. The controller **110** may display the pop-up window **701** to distinguish the pop-up window **701** from the webpage **700**. The controller **110** may display the pop-up window **701** having a transparency (e.g., a value between 0% and 100%). The transparency may be changed through an environment setting.

The controller **110** may display the pop-up window **701** so as to overlap the pop-up window **701** with the webpage **700**. The controller **110** may display the pop-up window **701** for a determined time (e.g., 1 sec that is changeable by an environment setting).

A size of the displayed pop-up window **701** is smaller than a size of the webpage **700**. For example, the size of the pop-up window **701** may include a range between 10% and 85% based on the size of the webpage **700**. Also, the size of the pop-up window **701** may include a range between 30% and 55% based on the size of the webpage **700**.

If an icon **701a** is selected, the controller **110** may enable the displayed pop-up window **701** to disappear.

Also, the controller **110** may change the content **700** displayed on the web browser into another content **710** without displaying the pop-up window **701**. The controller **110** may quickly (e.g., in response to a display time of the pop-up window **701**) change the content **700** displayed on the web browser into the other content **710** without displaying the pop-up window **701**.

If a preset time elapses or the icon **701a** is selected, the controller **110** may change the displayed webpage **700**. If the

preset time elapses or the icon **701a** is selected, the controller **110** may change the displayed webpage **700** by using an environment setting (e.g., a visual fatigue environment setting as shown in FIGS. **12A** to **12C**). If the preset time elapses or the icon **701a** is selected, the controller **110** may change the displayed webpage **700** by using an environment setting (e.g., a visual fatigue environment setting as shown in FIGS. **12A** to **12C**) and portable apparatus information (e.g., a resolution, a screen size, or the like).

Referring to FIG. **5F**, the controller **110** may change the webpage **700** into the other webpage **710** having a changed font size in response to the increase in the visual fatigue of the user. A font size of the changed webpage **710** may be larger than a font size of the original webpage **700**. For example, if the font size of the original webpage **700** is 20 pixels, the font size of the changed webpage **710** may be 40 pixels (e.g., may be two times larger than the font size of the original webpage **700**). A font size may include a scale-independent pixel (sp) or a device-independent pixel (dp).

It will be easily understood by those skilled in the art that a two-times increase in the font size of the changed webpage **710** is one embodiment, and the font size of the changed webpage **710** may be changed into other various types of font sizes.

The font size may be changed in response to an application executed in the portable apparatus **100**. If the visual fatigue of the user occurs, the controller **110** may differently change the font size in response to the application executed in the portable apparatus **100**. For example, if the visual fatigue of the user occurs, the controller **110** may differently change a font size of a webpage displayed on a web browser and a font size of a text displayed on a processor.

As shown in FIG. **5F**, the visual fatigue of the user may decrease by the webpage **710** having a changed font size.

If the content is changed into another content, the controller **110** may continuously calculate the visual fatigue by using the received EEG information of the user.

If the calculated visual fatigue of the user decreases, the controller **110** may restore the displayed other content **710** to the content **700** that is unchanged.

It will be easily understood by those skilled in the art that different font sizes displayed on a web browser and a word processor are one embodiment and may be changed in response to various types of applications. Also, it will be easily understood by those skilled in the art that the font size may be changed in response to the increase in the visual fatigue of the user so as to correspond to a screen size and/or a resolution of the portable apparatus **100**.

Referring to FIGS. **6A** to **6D**, the controller **110** may change the webpage **700** into a webpage **720** having a changed layout in response to an increase in a visual fatigue of the user. The changed layout of the webpage **720** may be a layout where the original webpage **700** is divided into three areas (e.g., as shown in FIGS. **6B**, **6C**, and **6D**) or four areas (e.g., as shown in FIG. **6A**). The changed layout of the webpage **720** may be divided into two areas (not shown) or five or more areas. A text, an image, or a moving image (e.g., a flash or the like) included in the webpage **700** may be displayed in the changed layout of the webpage **720**.

As shown in FIG. **6A**, the changed layout of the webpage **720** may include one horizontal area **720a** and three vertical areas **720b**, **720c**, and **720d**. Widths of spaces between the areas **720a** through **720d** may be smaller than one of a height and a width of each of the areas **720a** through **720d**. Also, areas of the three vertical areas **720b** through **720d** may be different from one another.

As shown in FIG. **6B**, the changed layout of a webpage **721** may include three vertical areas **721a**, **721b**, and **721c**. Widths of spaces between the areas **721a** through **721c** may be smaller than one of widths of the three areas **721a** through **721c**. Areas of the three vertical areas **721a** through **721c** may be different from one another. Areas of two of the three vertical areas **721a** through **721c** may be the same.

As shown in FIG. **6C**, a changed layout of a webpage **722** may include one horizontal area **722a** and two vertical areas **722b** and **722c**. Widths of spaces between the areas **722a** through **722c** may be smaller than one of a height and a width of each of the areas **722a** through **722c**. Areas of the two vertical areas **722b** and **722c** may be different from each other. Also, areas of two of the three areas **722a** through **722c** may be the same.

As shown in FIG. **6D**, a changed layout of a webpage **723** may include three horizontal areas **723a**, **723b**, and **723c**. Widths of spaces between the three horizontal areas **723a** through **723c** may be smaller than one of widths of the three horizontal areas **723a** through **723c**. Areas of the three horizontal areas **723a** through **723c** may be different from one another. Areas of two of the three horizontal areas **723a** through **723c** may be the same.

A visual fatigue of a user may decrease by a change in an ocular movement direction and/or a changing of a focus direction caused by the changed layout of the webpage **720** as shown in FIGS. **6A** to **6D**.

If a content is changed into another content, the controller **110** may continuously calculate the visual fatigue by using the received EEG information of the user.

If the calculated visual fatigue of the user decreases, the controller **110** may restore the displayed other contents **720** through **723** to the content **700**.

It will be easily understood by those skilled in the art that layouts as shown in FIGS. **6A** to **6D** are embodiments, and thus layouts, areas included in the layouts, and locations of the areas included in the layouts may be changed in response to various types of applications.

Referring to FIGS. **7A** and **7B**, the controller **110** may change (or add) a webpage **700** to a webpage including a color screen **730** or **731** in response to an increase in a visual fatigue of a user. The color screen **730** or **731** may include a green area or a greenish area (e.g., a yellowish green area, a dark green area, or the like) that does not give a great stimulus to eyes of the user. The color screen **730** or **731** may be alternatively be considered a "color filter".

The controller **110** may display the color screen **730** or **731** in an area set on the webpage **700**. The controller **110** may add the color screen **730** or **731** so as to overlap the color screen **730** or **731** with the webpage **700**. The color screen **730** or **731** may have a transparency (e.g., a value between 0% and 100% that is changeable by an environment setting).

An area of the color screen **730** may be between 30% and 50% of an area of the webpage **700**. An area of the color screen **731** may be the same as the area of the webpage **700**. The area of the color screen **731** may be an area except at least one selected from an address display bar **700a**, a tap icon **700b**, and a search icon **700c** on the webpage **700**. The area of the color screen **731** may also include a status bar **192** and the webpage **700**.

The displayed color screen **730** may include a polygonal, circular, or freestyle shape. The color screen **730** may be located in one of an upper area, a central area, and a lower area based on a central area of the webpage **700**.

Color screen information (e.g., an ID for a history management, a color of a color screen, a size of the color screen,

a storage location of the color screen, a location of the color screen in a webpage, or the like) corresponding to the color screen 730 or 731 may be stored in the storage unit 175 under control of the controller 110.

The controller 110 may change a background color of the webpage 700 into one of a green color and a greenish color so as to enable the background color of the webpage 700 to correspond to the color screen 730 or 731.

Referring to FIG. 7C, the controller 110 may change the webpage 700 into a webpage 700 including a visual fatigue relax video 732 in response to the increase in the visual fatigue of the user.

The visual fatigue relax video 732 may be a visual fatigue relax video (e.g., a forest landscape or the like) of a green color or a greenish color (e.g., a yellowish green color, a dark green color or the like) that does not give a great stimulus to the eyes of the user.

The controller 110 may display the visual fatigue relax video 732 so as to overlap with the webpage 700. The visual fatigue relax video 732 may have a transparency (e.g., a value between 0% and 100% that is changeable by an environment setting).

An area of the visual fatigue relax video 732 may be between 25% and 85% of an area of the webpage 700. The area of the visual fatigue relax video 732 may also be the same as the area of the webpage 700. The visual fatigue relax video 732 may be located in one of an upper area, a central area, and a lower area based on a central area of the webpage 700.

Visual fatigue relax video information (e.g., an ID for a history management, a visual fatigue relax video name, a visual fatigue relax video play time, a visual fatigue relax video storage location, a location of a visual fatigue relax video in a webpage, or the like) corresponding to the visual fatigue relax video 732 may be stored in the storage unit 175 under control of the controller 110.

The visual fatigue relax video 732 may include a text to speech (TTS) service. The controller 110 may convert a text included in the webpage 700 into a voice and output the voice in response to the increase in the visual fatigue of the user. If the text is converted into the voice and then output, the controller 110 may display a speaker icon 732a.

If the content is changed into another content, the controller 110 may continuously calculate the visual fatigue by using received EEG information of the user.

If the calculated visual fatigue of the user decreases, the controller 110 may restore displayed other contents 730 through 732 to the content 700 that is unchanged.

Referring to FIGS. 8A and 8B, a first e-book screen 740 may be displayed on a screen of the portable apparatus 100. If a current page 741 goes to the left by the user on the first e-book screen 740, the controller 110 may display a visual fatigue relax color screen 742a on a next page 742 of the first e-book screen 740 in response to an increase in a visual fatigue of a user.

If the current page 741 is modified into a convex shape and then goes to the left through a user input, the controller 110 may display the visual fatigue relax color screen 742a so as to overlap the visual fatigue relax color screen 742a with the next page 742. The visual fatigue relax color screen 742a may have a transparency (e.g., a value between 0% and 100% that is changeable by an environment setting).

If the current page 741 is modified into the convex shape and then goes to the left in response to a location of the user input (e.g., a touch or a touch gesture) (e.g., as shown in

FIGS. 8A and 8B), the controller 110 may differently display the visual fatigue relax color screen 742a displayed on the next page 742.

If the current page 741 is upwards modified into a convex shape through a user input and then gradually goes to the left, the controller 110 may display a larger part of the visual fatigue relax color screen 742a on the next page 742.

The controller 110 may change a background color of the next page 742 into one of a green color and a greenish color in response to the visual fatigue relax color screen 742a.

If the content is changed into another content, the controller 110 may continuously calculate the visual fatigue by using received EEG information of the user.

If the calculated visual fatigue of the user decreases, the controller 110 may restore the content 742 to the content 741.

Referring to FIGS. 9A to 9C, a second e-book screen 750 may be displayed on a screen of the portable apparatus 100. If a current page 751 goes to the left on the second e-book screen 750 by a user, the controller 110 may display a visual fatigue relax color screen 753 on a back surface 751a of the current page 751 on the second e-book screen 750 in response to an increase in a visual fatigue of the user. A next page 752 does not overlap with the visual fatigue relax color screen 753.

If the current page 751 is folded and then goes to the left through a user input, the controller 110 may display the visual fatigue relax color screen 753 so as to overlap the visual fatigue relax color screen 753 with the back surface 751a of the current page 751. The visual fatigue relax color screen 753 may have a transparency (e.g., a value between 0% and 100% that is changeable by an environment setting).

If the current page 751 is folded and then goes to the left (as shown in FIGS. 9A to 9C) in response to a location of the user input (e.g., a touch or a touch gesture), the controller 110 may differently display the back surface 751a of the current page 751.

If the current page 751 is folded and then gradually goes to the left through a user input, the controller 110 may display a larger part of the visual fatigue relax color screen 753 on the back surface 751a of the current page 751.

If a content is changed into another content, the controller 110 may continuously calculate the visual fatigue by using received EEG information of the user.

If the calculated visual fatigue of the user decreases, the controller 110 may restore the content 753 to the content 751.

Referring to FIG. 10A, a third e-book screen 760 may be displayed on a screen of the portable apparatus 100. If a current page 761 goes to the left on the third e-book screen 760 by a user, the controller 110 may display an ocular movement guide 763 on a back surface 761a of the current page 761 on the third e-book screen 760 in response to an increase in a visual fatigue of the user. For example, the ocular movement guide 763 may include "Please, blink eyes.", "Please, move eyes up and down.", "Please, move eyes from side to side.", or "Please, move eyes up, down, and from side to side."

The ocular movement guide 763 displayed on the back surface 761a of the current page 761 may be realized as one of a text, an image, and a moving image. For example, if the ocular movement guide 763 is the text, a font size of the displayed content may correspond to an area of the back surface 761a. For example, as shown in FIG. 10A, if the area of the back surface 761a of the current 761 is 20% of the current page 761, the font size of the text may be 20 pixels in the ocular movement guide 763. If the current page 761

goes to the left more, and thus the area of the back surface **761a** is 40% of the current page **761**, the font size of the text may be 35 pixels in the ocular movement guide **763** in response to the increased area of the back surface **761a**. As the area of the back surface **761a** increases, the font size of the text may increase in the ocular movement guide **763**.

The ocular movement guide **763** displayed on the back surface **761a** of the current page **761** does not overlap with a next page **762**.

If the current page **761** is folded and then goes to the left through a user input, the controller **110** may display the ocular movement guide **763** on the back surface **761a** of the current page **761**. Also, if the current page **761** is folded and then goes to the left through the user input, the controller **110** may display the ocular movement guide **763** so as to overlap the ocular movement guide **763** with the back surface **761a** of the current page **761**. If the ocular movement guide **763** overlaps with the back surface **761a** of the current page **761**, the ocular movement guide **763** may have a transparency (e.g., a value between 0% and 100% that is changeable by an environment setting).

As shown in FIG. 10A, if the third e-book screen **760** is displayed on the screen of the portable apparatus **100**, the controller **110** may execute a first camera **151**.

The controller **110** may detect whether an ocular movement of the user corresponding to the ocular movement guide **763** is performed, by using the first camera **151**. The controller **110** may detect whether the ocular movement of the user is performed, by using the first camera **151** and a face recognition. If the user blinks their eyes corresponding to the ocular movement guide **763**, the controller **110** may detect nictations of the user by using the first camera **151** and the face recognition. For example, if the displayed ocular movement guide **763** is "Please, blink eyes 10 times.", the controller **110** may count the number of nictations of the user by using the first camera **151** and the face recognition. If the number of nictations is lower than 10 times, the controller **110** may not turn the current page **761** but may keep the current page **761**.

The ocular movement guide **763** that is displayed in response to an increased degree of a visual fatigue may be changed (e.g., the number of nictations may increase with an increase in the number of nictations).

In various embodiments of the present disclosure, an ocular movement guide may be an ocular movement animation. Also, the ocular movement animation may include first through third exercise animations **764** of FIG. 10B, **771** of FIG. 11A, and **775** of FIG. 11B. An animation may refer to a moving image.

If a content is changed into another content, the controller **110** may continuously calculate a visual fatigue by using received EEG information of the user.

If the calculated visual fatigue of the user decreases, the controller **110** may restore the displayed content **761b** to the content **760**.

Referring to FIG. 10B, the third e-book screen **760** may be displayed on the screen of the portable apparatus **100**. If the current page **761** goes to the left on the third e-book screen **760** by the user, the controller **110** may display the first ocular movement animation **764** on the back surface **761a** of the current page **761** on the third e-book screen **760** in response to an increase in the visual fatigue of the user.

The first ocular movement animation **764** may be an animation corresponding to eye-tracking for tracking eyes of the user. For example, the controller **110** may detect user

eyes located in a first point **764a** that is an initial location in the first ocular movement animation **764** by using the first camera **151**.

If the eyes of the user are detected from the first point **764a**, the controller **110** may display a trajectory **764t** inducing the eyes of the user downwards. Also, the controller **110** may further display a direction symbol **765** that is adjacent to the trajectory **764t** and induces the eyes of the user downwards. The controller **110** may display the direction symbol **765** on the current page **761** or the next page **762**.

The trajectory **764t** may include intermediate points **764b** and **764c** from the first point **764a** and a fourth point **764d** that is a final location. The trajectory **764t** includes a plurality of points, and four points **764a** through **764d** are only an example.

The controller **110** may detect the eyes of the user following the trajectory **764t** by using the first camera **151** and eye-tracking. The controller **110** may detect the eyes of the user located in the fourth point **764d** that is the final location in the first ocular movement animation **764**, by using the first camera **151**. If the eyes of the user are detected from the fourth point **764d**, the controller **110** may repeat the first ocular movement animation **764**.

If the number of times the eyes of the user follow the trajectory is lower than the number of times the first ocular movement animation **764** is repeated or the eyes of the user starting from the first point **764a** are not detected from the fourth point **764d**, the controller **110** may not turn the current page **761** but may keep the current page **761**.

The first ocular movement animation **764** that is displayed in response to an increased degree of a visual fatigue may be changed (e.g., the trajectory **764t** may be more curved with an increase in the visual fatigue).

If the content is changed into another content, the controller **110** may continuously calculate the visual fatigue by using received EEG information of the user.

If the calculated visual fatigue of the user decreases, the controller **110** may restore the displayed content **764** to the content **760**.

Referring to FIG. 11A, the controller **110** may change the webpage **700** into a webpage **770** including a color screen **770a** in response to an increase in a visual fatigue of a user. The color screen **770a** may include a green or greenish area (e.g., a yellowish green area, a dark green area, or the like) that does not give a great stimulus to eyes of the user.

The controller **110** may display a second ocular movement animation **771** so as to overlap the second ocular movement animation **771** with the color screen **770a** of the webpage **770**. The second ocular movement animation **771** may have a transparency (e.g., a value between 0% and 100% that is changeable by an environment setting).

The second ocular movement animation **771** may be an animation corresponding to an iris recognition for recognizing irises of the user. For example, the controller **110** may detect irises of the user located in a first location **771a**, where eyes of the user are opened (e.g., the irises are recognized), from the second ocular movement animation **771** by using the first camera **151**.

If the irises of the user are detected from the first location **771a**, the controller **110** may display a direction symbol **772** that induces the eyes of the user downwards.

The controller **110** may detect nictations of the user corresponding to the direction symbol **772** by using the first camera **151** and the iris recognition. The controller **110** may detect eyelid closures of the user from a second location **771b** that is a final location, in the second ocular movement

animation 771 by using the first camera 151. If the eyelid closures are detected from the second location 771b, the controller 110 may repeat the second ocular movement animation 771.

The number of times the second ocular movement animation 771 being repeated may be displayed in a counter 773. The counter 773 may display the total number of repeated times and the current number of repeated times.

If the nictations of the user are lower than the total number of times the second ocular movement animation 764 is repeated, the controller 110 may not change the webpage 770 but may keep the webpage 770.

The second ocular movement animation 771 that is displayed in response to the increase in the visual fatigue may be changed (e.g., the number of repeated times the second ocular movement animation 771 being repeated may increase with the increase in the visual fatigue).

If a content is changed into another content, the controller 110 may continuously calculate the visual fatigue by using received EEG information of the user.

If the calculated visual fatigue of the user decreases, the controller 110 may restore the displayed contents 771, 772, and 773 to the content 770.

Referring to FIG. 11B, the controller 110 may change the webpage 700 into a webpage 770 including a color screen 770a in response to an increase in a visual fatigue of the user. The color screen 770a may include a green or greenish area (e.g., a yellowish green area, a dark green area, or the like) that does not give a great stimulus to the eyes of the user.

The controller 110 may display a third ocular movement animation 775 so as to overlap the third ocular movement animation 775 with the color screen 770a of the webpage 770. The third ocular movement animation 775 may have a transparency (e.g., a value between 0% and 100% that is changeable by an environment setting).

The third ocular movement animation 771 may be an animation corresponding to eye-tracking for tracking the eyes of the user. For example, the controller 110 may detect irises of the user corresponding to status 1, where both eyes of the user are moved to the left, from the third ocular movement animation 775.

If the irises of the user are detected in the status 1 where the both eyes of the user are moved to the left, the controller 110 may display a direction symbol 775a that induces the eyes of the user to the right.

The controller 110 may detect ocular movements of the user corresponding to the direction symbol 775a by using the first camera 151 and the iris recognition. The controller 110 may detect the irises of the user in a status 8, in which both eyes of the user are moved to the left and which is a final location, from the third ocular movement animation 771 by using the first camera 151. If the irises of the user are detected from the final location 8, the controller 110 may repeat the third ocular movement animation 775.

The number of times the third ocular movement animation 771 being repeated may be displayed in a counter 776. The counter 776 may display the total number of repeated times and the current number of repeated times.

If the total number of repeated times or the current number of repeated times is lower than the total number of the third ocular movement animation 775 being repeated, the controller 110 may not change the webpage 770 but may keep the webpage 770.

The third ocular movement animation 771 that is displayed in response to an increased degree of the visual fatigue may be changed (e.g., the number of repeated times

the third ocular movement animation 771 being repeated may increase with the increase in the visual fatigue).

If the content is changed into another content, the controller 110 may continuously calculate the visual fatigue by using received EEG information of the user.

If the calculated visual fatigue of the user decreases, the controller 110 may restore the other contents 775 and 776 to the content 770.

If the displayed content is changed in operation S480 of FIG. 4, the method of changing the content screen of the portable apparatus ends.

In various embodiments of the present disclosure, the portable apparatus 100 may infer a visual fatigue without bio-information of the user (e.g., EEG information).

The controller 110 of the portable apparatus 100 may store a visual fatigue DB in the storage unit 175, wherein the visual fatigue DB corresponds to a visual fatigue calculated based on the bio-information of the user (e.g., EEG information) received from the wearable apparatus 200. The controller 110 of the portable apparatus 100 may infer a visual fatigue occurrence start time by using the stored visual fatigue DB without the bio-information of the user received from the wearable apparatus 200.

Visual fatigue items included in the visual fatigue DB may include an ID for a history management, an application type (e.g., a web browser, a video player, a game, or the like) executed in the portable apparatus 100, a content type (e.g., a webpage, a video, a game, or the like), an application execution start time, a visual fatigue occurrence time, a visual fatigue duration time, a visual fatigue occurrence cycle, user fatigue bio-information (e.g. a heart rate, a temperature, or the like if a visual fatigue occurs), another content change information (e.g., another content type, another content change start time, or the like), etc.

The controller 110 may manage a visual fatigue history of the user by using the accumulated visual fatigue DB. The controller 110 may learn the visual fatigue of the user by using the stored visual fatigue DB and machine learning. The controller 110 may learn the visual fatigue of the user by using the stored visual fatigue DB, a statistical analysis, a big data analysis, or machine learning. The statistical analysis may refer to a regression analysis, a time-series analysis, or an analysis using an execution of a regular check or the like in statistical software. Also, a computing apparatus may extract (or search for), analyze, and determine a pattern of accumulated big data, and infer a result through machine learning. The controller 110 may infer a visual fatigue through an accumulation of visual fatigue learning. The controller 110 may infer a visual fatigue of the user by using a stored visual fatigue DB, a statistical analysis, a big data analysis, or machine learning.

For example, if the user executes a web browser, the controller 110 may infer a user visual fatigue occurrence time, a visual fatigue duration time, a visual fatigue occurrence cycle, etc. corresponding to the execution of the web browser by using a visual fatigue DB without bio-information of the user (e.g., EEG information) received from the wearable apparatus 200.

If the visual fatigue of the user increases, the controller 110 may provide the user with another content corresponding to a decrease in the visual fatigue as shown in FIGS. 5A and 11B.

The providing of the other content corresponding to the increase in the visual fatigue without receiving the bio-information of the user (e.g., EEG information) from the wearable apparatus 200 is similar to providing of another

content corresponding to the decrease in the visual fatigue as shown in FIGS. 5A and 11B, and thus a repeated description thereof is omitted.

According to another embodiment of the present disclosure, the server 300 that receives bio-information of the user (e.g., EEG information) transmitted from the wearable apparatus 200 may calculate a visual fatigue.

The wearable apparatus 200 may transmit detected bio-information of the user (e.g., EEG information) to the server 300. The portable apparatus 100 may transmit application information (e.g., an application type, a content type, an application execution start time, or the like) corresponding to an executed application to the server 300.

A controller (not shown) of the server 300 may calculate the visual fatigue based on the bio-information of the user (e.g., EEG information) received from the wearable apparatus 200 and the application information received from the portable apparatus 100. The controller may store a visual fatigue DB corresponding to the calculated visual fatigue in a storage unit (not shown) of the server 300. Visual fatigue items included in the visual fatigue DB may include an ID for a history management, an application type (e.g., a webpage, a video, a game, or the like) executed in the portable apparatus 100, a content type (e.g., a webpage, a video, a game, or the like), an application execution start time, a visual fatigue occurrence time, a visual fatigue duration time, a visual fatigue occurrence cycle, user fatigue bio-information (e.g., a heart rate, a temperature, of the like if a visual fatigue occurs), another content change information (e.g., another content type, another content change start time, or the like), etc.

The controller of the server 300 may manage a visual fatigue history of the user by using an accumulated visual fatigue DB. The controller of the server 300 may learn the visual fatigue of the user by using the stored visual fatigue DB and machine learning. The controller 110 may learn the visual fatigue of the user by using the stored visual fatigue DB, a statistical analysis, a big data analysis, or machine learning. The statistical analysis may refer to a regression analysis, a time-series analysis, or an analysis using an execution of a regular check or the like in statistical software. A computing apparatus may extract (or search for), analyze, and determine a pattern of accumulated big data, and infer a result through machine learning.

The controller (not shown) of the server 300 may infer a visual fatigue through an accumulation of visual fatigue learning. The controller of the server 300 may infer a visual fatigue of the user by using a stored visual fatigue DB, a statistical analysis, a big data analysis, or machine learning.

The controller of the server 300 may transmit visual fatigue information corresponding to the calculated visual fatigue to the portable apparatus 100 through a communicator (not shown). For example, the visual fatigue information may include an application type, a content type, a current visual fatigue index, a visual fatigue occurrence time, a visual fatigue duration time, etc.

If the calculated visual fatigue of the user increases (e.g., if the visual fatigue is higher than or equal to 2.6), the controller of the server 300 may transmit visual fatigue information corresponding to the increased visual fatigue of the user to the portable apparatus 100.

If the visual fatigue information corresponding to the increase in the visual fatigue is received from the server 300, the controller 110 of the portable apparatus 100 may provide the user with one of other contents corresponding to the increase in the visual fatigue as shown in FIGS. 5A and 11B.

The providing of the other contents corresponding to the visual fatigue information received from the server 300 is similar to the providing of other contents corresponding to the increase in the visual fatigue as shown in FIGS. 5A and 11B, and thus a repeated description thereof is omitted.

According to another embodiment of the present disclosure, the server 300 may infer a visual fatigue without bio-information of the user transmitted from the wearable apparatus 200.

The server 300 may not be connected to the wearable apparatus 200, which detects bio-information of the user (e.g., EEG information), through a communicator (not shown) but may receive application information (e.g., an application type, a content type, an application execution start time, or the like) corresponding to an application executed in the portable apparatus 100.

The controller may store a visual fatigue DB corresponding to a pre-calculated visual fatigue in a storage unit (not shown) of the server 300. Visual fatigue items included in the visual fatigue DB may include an ID for a history management, an application type (e.g., a web browser, a video player, a game, or the like) executed in the portable apparatus 100, a content type (e.g., a webpage, a video, a game, or the like), an application execution start time, a visual fatigue occurrence time, a visual fatigue duration time, a visual fatigue occurrence cycle, user fatigue bio-information (e.g., a heart rate, a temperature, or the like if a visual fatigue occurs), etc.

The controller of the server 300 may manage a visual fatigue history of the user by using an accumulated visual fatigue DB. The controller of the server 300 may learn a visual fatigue of the user by using a stored visual fatigue DB and machine learning without bio-information of the user (e.g., EEG information) received from the wearable apparatus 200. The controller may learn the visual fatigue of the user by using a stored visual fatigue DB, a statistical analysis, a big data analysis, or machine learning. The statistical analysis may refer to a regression analysis, a time-series analysis, or an analysis using an execution of a regular check or the like in statistical software. A computing apparatus may extract (or search for), analyze, and determine a pattern of bid data, and infer a result through machine learning.

The controller of the server 300 may infer the visual fatigue through an accumulation of visual fatigue learning. The controller of the server 300 may infer a visual fatigue of the user by using a stored visual fatigue DB, a statistical analysis, a big data analysis, or machine learning.

The controller of the server 300 may transmit visual fatigue information corresponding to the inferred visual fatigue to the portable apparatus 100 through a communicator (not shown). For example, the visual fatigue information may include an application type, a content type, a current visual fatigue index, a visual fatigue occurrence time, a visual fatigue duration time, etc.

If the calculated visual fatigue of the user increases (e.g., if the visual fatigue is higher than or equal to 2.6), the controller of the server 300 may transmit the visual fatigue information corresponding to the increased visual fatigue of the user to the portable apparatus 100 through the communicator (not shown).

If the visual fatigue information corresponding to the increase in the visual fatigue is received from the server 300, the controller 110 of the portable apparatus 100 may provide the user with one of other contents corresponding to the increase in the visual fatigue as shown in FIGS. 5A and 11B.

The providing of the other contents corresponding to the visual fatigue information received from the server 300 is similar to the providing of the other contents corresponding to the increase in the visual fatigue as shown in FIGS. 5A and 11B, and thus a repeated description thereof is omitted.

Methods according to various embodiments of the present disclosure may be embodied as a program code form that may be performed through various types of computer units and then may be recorded on a computer readable recording medium. The computer readable recording medium may include a program command, a data file, a data structure, or a combination thereof. Examples of the computer readable recording medium may include a volatile or nonvolatile storage device such as an ROM or the like regardless of being detectable or being rewritable, a memory such as an RAM, a memory chip, a device, or an integrated circuit (IC), and a storage medium on which recording may be optically or magnetically performed and which may be read in a machine language (e.g., a computer) such as a CD, a DVD, a magnetic disk, a magnetic tape, or the like.

A memory that may be included in a portable apparatus may be an example of a storage medium that may store a program including instructions embodying various embodiments of the present disclosure and may read in a machine language. Program commands recorded on the computer readable recording medium may be particularly designed and configured for the present disclosure or may be well known to and used by computer software developers.

While the present disclosure has been shown and described with reference to various embodiments thereof, it will be understood by those skilled in the art that various changes in form and details may be made therein without departing from the spirit and scope of the present disclosure as defined by the appended claims and their equivalents.

What is claimed is:

1. A method of changing a content screen of a portable apparatus, the method comprising:
 - connecting to a wearable apparatus using a communicator when a user command for determining a visual fatigue of a user is received;
 - displaying content;
 - receiving bio-information of the user from the wearable apparatus while the content is displayed;
 - determining whether the visual fatigue has increased based on the bio-information of the user; and
 - displaying other content comprising an ocular movement guide in response to a user input confirming a display indicating the determination of the visual fatigue and a request for the other content.
2. The method of claim 1, wherein the other content comprises at least one of a text, an image, or a moving image that is added to the content.
3. The method of claim 1, wherein the other content comprises at least one of a change in a font size of the content, a change in a layout of the content, or an addition of a color screen overlapping the content.
4. The method of claim 1, wherein the method further comprises detecting, by a camera, whether an ocular movement of the user corresponds to the ocular movement guide.
5. The method of claim 1, wherein the calculating of the visual fatigue is performed by a first application, wherein the content is displayed by a second application, and

wherein the other content is differently displayed in response to the second application displaying the content.

6. The method of claim 1, wherein the bio-information of the user comprises at least one of electroencephalogram (EEG) information, raw data detected from the wearable apparatus, or digital data generated by processing the raw data.
7. The method of claim 1, further comprising: displaying a pop-up window corresponding to the visual fatigue.
8. The method of claim 1, further comprising: providing a user feedback corresponding to the increase in the visual fatigue, wherein the user feedback comprises at least one of a visual feedback, an auditory feedback, or a haptic feedback.
9. The method of claim 1, further comprising: selecting a visual fatigue settings menu; and selecting, from the visual fatigue settings menu, at least one of an application setting or a time zone setting, wherein the other content is displayed according to the selection of the application setting or the time zone setting.
10. A portable apparatus comprising:
 - a display configured to display content;
 - a communicator configured to:
 - connect to a wearable apparatus when a user command for determining a visual fatigue of a user is received, and
 - receive bio-information of the user from the wearable apparatus while the content is displayed; and
 - at least one processor configured to:
 - determining whether the visual fatigue has increased based on the bio-information of the user, and
 - display other content comprising an ocular movement guide in response to a user input confirming the display indicating the determination of the visual fatigue and a request for the other content.
11. The portable apparatus of claim 10, wherein the at least one processor is further configured to request a detection of the bio-information of the user from the wearable apparatus through the communicator.
12. The portable apparatus of claim 10, further comprising:
 - a camera, wherein the camera is configured to detect whether an ocular movement of the user corresponds to the ocular movement guide.
13. The portable apparatus of claim 10, wherein the at least one processor is further configured to display a color screen in response to an application displaying the content.
14. The portable apparatus of claim 10, further comprising:
 - a camera, wherein the at least one processor is further configured to perform at least one of eye-tracking or iris recognition using the camera.
15. The portable apparatus of claim 10, wherein, in response to a decrease of the visual fatigue based on the other content, the at least one processor is further configured to restore the other content to the content.
16. The portable apparatus of claim 10, wherein the display is further configured to display a visual fatigue settings menu,

wherein the at least one processor is further configured to receive a selection, from the visual fatigue settings menu, of at least one of an application setting or a time zone setting, and

wherein the other content is displayed according to the selection of the application setting or the time zone setting.

* * * * *

专利名称(译)	便携式设备和改变其内容屏幕的方法		
公开(公告)号	US10130279	公开(公告)日	2018-11-20
申请号	US15/078445	申请日	2016-03-23
[标]申请(专利权)人(译)	三星电子株式会社		
申请(专利权)人(译)	SAMSUNG ELECTRONICS CO. , LTD.		
当前申请(专利权)人(译)	SAMSUNG ELECTRONICS CO. , LTD.		
[标]发明人	MOON SUN HO CHOI JONG HO KWAK SE JIN KIM SUNG SOO KIM HWA KYUNG RYU JONG YOUB LEE SANG HYUP		
发明人	MOON, SUN-HO CHOI, JONG-HO KWAK, SE-JIN KIM, SUNG-SOO KIM, HWA-KYUNG RYU, JONG-YOUB LEE, SANG-HYUP		
IPC分类号	A61B5/0482 G06F3/0488 A61B5/00 G06F3/01 G06F19/00 A61H5/00 G16H40/63 G06K9/00 A61B5/0478 A61B5/16 A61B5/048 A61B3/00 A61B3/113		
CPC分类号	A61B5/0482 A61B5/0478 A61B5/16 A61B5/6803 A61B5/6898 A61B5/742 A61B5/7475 A61H5/00 G06F3/013 G06F3/015 G06F3/04886 G06F19/00 G06K9/00496 G06K9/00597 G16H40/63 A61B5/0002 G06F2203/04806 A61B3/00 A61B3/113 A61B5/048		
优先权	1020150061725 2015-04-30 KR		
其他公开文献	US20160317056A1		
外部链接	Espacenet		

摘要(译)

提供了一种便携式设备和改变便携式设备的内容屏幕的方法。便携式设备包括响应于视觉疲劳的增加而改变显示的内容和改变便携式设备的内容屏幕的方法。所公开的一些实施例提供了一种便携式设备，其通过使用从可穿戴设备接收的用户脑电图 (EEG) 信息计算视觉疲劳，并且响应于计算的视觉疲劳的增加将显示的内容改变为另一内容，以及改变便携式设备的内容屏幕。

