



US010531819B2

(12) **United States Patent**
Diab et al.

(10) **Patent No.:** **US 10,531,819 B2**
(45) **Date of Patent:** ***Jan. 14, 2020**

(54) **HYPERSATURATION INDEX**
(71) Applicant: **Masimo Corporation**, Irvine, CA (US)
(72) Inventors: **Mohamed K. Diab**, Ladera Ranch, CA (US); **Prashanth Iyengar**, Irvine, CA (US); **Anand Sampath**, Irvine, CA (US); **Ammar Al-Ali**, San Juan Capistrano, CA (US)

(73) Assignee: **Masimo Corporation**, Irvine, CA (US)
(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 196 days.

This patent is subject to a terminal disclaimer.

(21) Appl. No.: **15/705,761**

(22) Filed: **Sep. 15, 2017**

(65) **Prior Publication Data**

US 2018/0055430 A1 Mar. 1, 2018

Related U.S. Application Data

(63) Continuation of application No. 14/852,356, filed on Sep. 11, 2015, now Pat. No. 9,775,546, which is a (Continued)

(51) **Int. Cl.**
A61B 5/1455 (2006.01)
A61B 5/00 (2006.01)
A61B 5/0205 (2006.01)

(52) **U.S. Cl.**
CPC **A61B 5/14552** (2013.01); **A61B 5/0205** (2013.01); **A61B 5/14551** (2013.01); (Continued)

(58) **Field of Classification Search**
CPC **A61B 5/1455**; **A61B 5/14551**; **A61B 5/14552**; **A61B 5/7282**; **A61B 5/7275**
See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

3,734,091 A 5/1973 Taplin
4,094,305 A 6/1978 Kessler
(Continued)

FOREIGN PATENT DOCUMENTS

EP 0329297 A2 8/1989
EP 0753320 A1 1/1997
(Continued)

OTHER PUBLICATIONS

US 8,845,543 B2, 09/2014, Diab et al. (withdrawn)
International Search Report and Written Opinion for PCT/US2013/037019 dated Oct. 25, 2013 in 18 pages.


Primary Examiner — Eric F Winakur

(74) *Attorney, Agent, or Firm* — Knobbe, Martens, Olson & Bear, LLP

(57) **ABSTRACT**

Embodiments of the present disclosure provide a hypersaturation index for measuring a patient's absorption of oxygen in the blood stream after a patient has reached 100% oxygen saturation. This hypersaturation index provides an indication of the partial pressure of oxygen of a patient. In an embodiment of the present invention, a hypersaturation index is calculated based on the absorption ratio of two different wavelengths of energy at a measuring site. In an embodiment of the invention, a maximum hypersaturation index threshold is determined such that an alarm is triggered when the hypersaturation index reaches or exceeds the threshold. In another embodiment, an alarm is triggered when the hypersaturation index reaches or falls below its starting point when it was first calculated.

18 Claims, 16 Drawing Sheets



Related U.S. Application Data

continuation of application No. 13/865,081, filed on Apr. 17, 2013, now Pat. No. 9,131,881.

(60) Provisional application No. 61/719,866, filed on Oct. 29, 2012, provisional application No. 61/703,087, filed on Sep. 19, 2012, provisional application No. 61/625,599, filed on Apr. 17, 2012.

(52) **U.S. Cl.**

CPC *A61B 5/7282* (2013.01); *A61B 5/743* (2013.01); *A61B 5/7405* (2013.01); *A61B 5/746* (2013.01); *A61B 5/6826* (2013.01); *A61B 2562/0238* (2013.01); *A61M 2230/205* (2013.01)

(56) **References Cited**

U.S. PATENT DOCUMENTS

4,333,473 A 6/1982 Eberhard et al.
 4,960,128 A 10/1990 Gordon et al.
 4,964,408 A 10/1990 Hink et al.
 5,041,187 A 8/1991 Hink et al.
 5,069,213 A 12/1991 Polczynski
 5,163,438 A 11/1992 Gordon et al.
 5,184,618 A 2/1993 Wider et al.
 5,319,355 A 6/1994 Russek
 5,337,744 A 8/1994 Branigan
 5,341,805 A 8/1994 Stavridi et al.
 5,355,880 A 10/1994 Thomas et al.
 D353,195 S 12/1994 Savage et al.
 D353,196 S 12/1994 Savage et al.
 5,377,676 A 1/1995 Vari et al.
 5,388,575 A 2/1995 Taube
 D359,546 S 6/1995 Savage et al.
 5,431,170 A 7/1995 Mathews
 D361,840 S 8/1995 Savage et al.
 D362,063 S 9/1995 Savage et al.
 5,452,717 A 9/1995 Branigan et al.
 D363,120 S 10/1995 Savage et al.
 5,456,252 A 10/1995 Vari et al.
 5,479,934 A 1/1996 Imran
 5,482,036 A 1/1996 Diab et al.
 5,490,505 A 2/1996 Diab et al.
 5,494,043 A 2/1996 O'Sullivan et al.
 5,533,511 A 7/1996 Kaspari et al.
 5,534,851 A 7/1996 Russek
 5,561,275 A 10/1996 Savage et al.
 5,562,002 A 10/1996 Lalin
 5,590,649 A 1/1997 Caro et al.
 5,602,924 A 2/1997 Durand et al.
 5,632,272 A 5/1997 Diab et al.
 5,638,816 A 6/1997 Kiani-Azarbayjany et al.
 5,638,818 A 6/1997 Diab et al.
 5,645,440 A 7/1997 Tobler et al.
 5,685,299 A 11/1997 Diab et al.
 D393,830 S 4/1998 Tobler et al.
 5,743,262 A 4/1998 Lepper, Jr. et al.
 5,752,509 A 5/1998 Lachmann et al.
 5,758,644 A 6/1998 Diab et al.
 5,760,910 A 6/1998 Lepper, Jr. et al.
 5,769,785 A 6/1998 Diab et al.
 5,782,757 A 7/1998 Diab et al.
 5,785,659 A 7/1998 Caro et al.
 5,791,347 A 8/1998 Flaherty et al.
 5,810,734 A 9/1998 Caro et al.
 5,823,950 A 10/1998 Diab et al.
 5,830,131 A 11/1998 Caro et al.
 5,833,618 A 11/1998 Caro et al.
 5,860,919 A 1/1999 Kiani-Azarbayjany et al.
 5,890,929 A 4/1999 Mills et al.
 5,904,654 A 5/1999 Wohltmann et al.
 5,919,134 A 7/1999 Diab
 5,934,925 A 8/1999 Tobler et al.

5,940,182 A 8/1999 Lepper, Jr. et al.
 5,987,343 A 11/1999 Kinast
 5,995,855 A 11/1999 Kiani et al.
 5,997,343 A 12/1999 Mills et al.
 6,002,952 A 12/1999 Diab et al.
 6,011,986 A 1/2000 Diab et al.
 6,027,452 A 2/2000 Flaherty et al.
 6,036,642 A 3/2000 Diab et al.
 6,045,509 A 4/2000 Caro et al.
 6,067,462 A 5/2000 Diab et al.
 6,081,735 A 6/2000 Diab et al.
 6,088,607 A 7/2000 Diab et al.
 6,110,522 A 8/2000 Lepper, Jr. et al.
 6,124,597 A 9/2000 Shehada
 6,128,521 A 10/2000 Marro et al.
 6,129,675 A 10/2000 Jay
 6,144,868 A 11/2000 Parker
 6,151,516 A 11/2000 Kiani-Azarbayjany et al.
 6,152,754 A 11/2000 Gerhardt et al.
 6,157,850 A 12/2000 Diab et al.
 6,165,005 A 12/2000 Mills et al.
 6,184,521 B1 2/2001 Coffin, IV et al.
 6,206,830 B1 3/2001 Diab et al.
 6,229,856 B1 5/2001 Diab et al.
 6,232,609 B1 5/2001 Snyder et al.
 6,236,872 B1 5/2001 Diab et al.
 6,241,683 B1 6/2001 Macklem et al.
 6,253,097 B1 6/2001 Aronow et al.
 6,256,523 B1 7/2001 Diab et al.
 6,263,222 B1 7/2001 Diab et al.
 6,278,522 B1 8/2001 Lepper, Jr. et al.
 6,280,213 B1 8/2001 Tobler et al.
 6,285,896 B1 9/2001 Tobler et al.
 6,301,493 B1 10/2001 Marro et al.
 6,308,089 B1 10/2001 Von Der Ruhr et al.
 6,317,627 B1 11/2001 Ennen et al.
 6,321,100 B1 11/2001 Parker
 6,325,761 B1 12/2001 Jay
 6,334,065 B1 12/2001 Al-Ali et al.
 6,343,224 B1 1/2002 Parker
 6,349,228 B1 2/2002 Kiani et al.
 6,360,114 B1 3/2002 Diab et al.
 6,368,283 B1 4/2002 Xu et al.
 6,371,921 B1 4/2002 Caro et al.
 6,377,829 B1 4/2002 Al-Ali
 6,388,240 B2 5/2002 Schulz et al.
 6,397,091 B2 5/2002 Diab et al.
 6,430,437 B1 8/2002 Marro
 6,430,525 B1 8/2002 Weber et al.
 6,463,311 B1 10/2002 Diab
 6,470,199 B1 10/2002 Kopotic et al.
 6,501,975 B2 12/2002 Diab et al.
 6,505,059 B1 1/2003 Kollias et al.
 6,515,273 B2 2/2003 Al-Ali
 6,519,487 B1 2/2003 Parker
 6,525,386 B1 2/2003 Mills et al.
 6,526,300 B1 2/2003 Kiani et al.
 6,541,756 B2 4/2003 Schulz et al.
 6,542,764 B1 4/2003 Al-Ali et al.
 6,580,086 B1 6/2003 Schulz et al.
 6,584,336 B1 6/2003 Ali et al.
 6,595,316 B2 7/2003 Cybulski et al.
 6,597,932 B2 7/2003 Tian et al.
 6,597,933 B2 7/2003 Kiani et al.
 6,606,511 B1 8/2003 Ali et al.
 6,632,181 B2 10/2003 Flaherty et al.
 6,639,668 B1 10/2003 Trepagnier
 6,640,116 B2 10/2003 Diab
 6,643,530 B2 11/2003 Diab et al.
 6,650,917 B2 11/2003 Diab et al.
 6,654,624 B2 11/2003 Diab et al.
 6,658,276 B2 12/2003 Kiani et al.
 6,661,161 B1 12/2003 Lanzo et al.
 6,671,531 B2 12/2003 Al-Ali et al.
 6,678,543 B2 1/2004 Diab et al.
 6,684,090 B2 1/2004 Ali et al.
 6,684,091 B2 1/2004 Parker
 6,697,656 B1 2/2004 Al-Ali
 6,697,657 B1 2/2004 Shehada et al.

(56)

References Cited

U.S. PATENT DOCUMENTS

6,697,658 B2	2/2004	Al-Ali	7,328,053 B1	2/2008	Diab et al.
RE38,476 E	3/2004	Diab et al.	7,332,784 B2	2/2008	Mills et al.
6,699,194 B1	3/2004	Diab et al.	7,340,287 B2	3/2008	Mason et al.
6,714,804 B2	3/2004	Al-Ali et al.	7,341,559 B2	3/2008	Schulz et al.
RE38,492 E	4/2004	Diab et al.	7,343,186 B2	3/2008	Lamego et al.
6,721,582 B2	4/2004	Trepagnier et al.	D566,282 S	4/2008	Al-Ali et al.
6,721,585 B1	4/2004	Parker	7,355,512 B1	4/2008	Al-Ali
6,725,075 B2	4/2004	Al-Ali	7,356,365 B2	4/2008	Schurman
6,728,560 B2	4/2004	Kollias et al.	7,371,981 B2	5/2008	Abdul-Hafiz
6,735,459 B2	5/2004	Parker	7,373,193 B2	5/2008	Al-Ali et al.
6,745,060 B2	6/2004	Diab et al.	7,373,194 B2	5/2008	Weber et al.
6,760,607 B2	7/2004	Al-Ali	7,376,453 B1	5/2008	Diab et al.
6,770,028 B1	8/2004	Ali et al.	7,377,794 B2	5/2008	Al Ali et al.
6,771,994 B2	8/2004	Kiani et al.	7,377,899 B2	5/2008	Weber et al.
6,792,300 B1	9/2004	Diab et al.	7,383,070 B2	6/2008	Diab et al.
6,813,511 B2	11/2004	Diab et al.	7,415,297 B2	8/2008	Al-Ali et al.
6,816,741 B2	11/2004	Diab	7,428,432 B2	9/2008	Ali et al.
6,822,564 B2	11/2004	Al-Ali	7,438,683 B2	10/2008	Al-Ali et al.
6,826,419 B2	11/2004	Diab et al.	7,440,787 B2	10/2008	Diab
6,830,711 B2	12/2004	Mills et al.	7,454,240 B2	11/2008	Diab et al.
6,850,787 B2	2/2005	Weber et al.	7,467,002 B2	12/2008	Weber et al.
6,850,788 B2	2/2005	Al-Ali	7,469,157 B2	12/2008	Diab et al.
6,852,083 B2	2/2005	Caro et al.	7,471,969 B2	12/2008	Diab et al.
6,861,639 B2	3/2005	Al-Ali	7,471,971 B2	12/2008	Diab et al.
6,898,452 B2	5/2005	Al-Ali et al.	7,483,729 B2	1/2009	Al-Ali et al.
6,920,345 B2	7/2005	Al-Ali et al.	7,483,730 B2	1/2009	Diab et al.
6,931,268 B1	8/2005	Kiani-Azarbayjany et al.	7,489,958 B2	2/2009	Diab et al.
6,934,570 B2	8/2005	Kiani et al.	7,496,391 B2	2/2009	Diab et al.
6,939,305 B2	9/2005	Flaherty et al.	7,496,393 B2	2/2009	Diab et al.
6,943,348 B1	9/2005	Coffin, IV	D587,657 S	3/2009	Al-Ali et al.
6,950,687 B2	9/2005	Al-Ali	7,499,741 B2	3/2009	Diab et al.
6,961,598 B2	11/2005	Diab	7,499,835 B2	3/2009	Weber et al.
6,970,792 B1	11/2005	Diab	7,500,950 B2	3/2009	Al-Ali et al.
6,979,812 B2	12/2005	Al-Ali	7,509,154 B2	3/2009	Diab et al.
6,985,764 B2	1/2006	Mason et al.	7,509,494 B2	3/2009	Al-Ali
6,993,371 B2	1/2006	Kiani et al.	7,510,849 B2	3/2009	Schurman et al.
6,996,427 B2	2/2006	Ali et al.	7,526,328 B2	4/2009	Diab et al.
6,999,904 B2	2/2006	Weber et al.	7,530,942 B1	5/2009	Diab
7,003,338 B2	2/2006	Weber et al.	7,530,949 B2	5/2009	Al Ali et al.
7,003,339 B2	2/2006	Diab et al.	7,530,955 B2	5/2009	Diab et al.
7,015,451 B2	3/2006	Dalke et al.	7,563,110 B2	7/2009	Al-Ali et al.
7,024,233 B2	4/2006	Ali et al.	7,596,398 B2	9/2009	Al-Ali et al.
7,027,849 B2	4/2006	Al-Ali	7,618,375 B2	11/2009	Flaherty
7,030,749 B2	4/2006	Al-Ali	D606,659 S	12/2009	Kiani et al.
7,039,449 B2	5/2006	Al-Ali	7,647,083 B2	1/2010	Al-Ali et al.
7,041,060 B2	5/2006	Flaherty et al.	D609,193 S	2/2010	Al-Ali et al.
7,044,918 B2	5/2006	Diab	D614,305 S	4/2010	Al-Ali et al.
7,048,687 B1	5/2006	Reuss et al.	RE41,317 E	5/2010	Parker
7,067,893 B2	6/2006	Mills et al.	7,729,733 B2	6/2010	Al-Ali et al.
7,096,052 B2	8/2006	Mason et al.	7,734,320 B2	6/2010	Al-Ali
7,096,054 B2	8/2006	Abdul-Hafiz et al.	7,761,127 B2	7/2010	Al-Ali et al.
7,132,641 B2	11/2006	Schulz et al.	7,761,128 B2	7/2010	Al-Ali et al.
7,142,901 B2	11/2006	Kiani et al.	7,764,982 B2	7/2010	Dalke et al.
7,149,561 B2	12/2006	Diab	D621,516 S	8/2010	Kiani et al.
7,186,966 B2	3/2007	Al-Ali	7,791,155 B2	9/2010	Diab
7,190,261 B2	3/2007	Al-Ali	7,801,581 B2	9/2010	Diab
7,215,984 B2	5/2007	Diab	7,822,452 B2	10/2010	Schurman et al.
7,215,986 B2	5/2007	Diab	RE41,912 E	11/2010	Parker
7,221,971 B2	5/2007	Diab	7,844,313 B2	11/2010	Kiani et al.
7,225,006 B2	5/2007	Al-Ali et al.	7,844,314 B2	11/2010	Al-Ali
7,225,007 B2	5/2007	Al-Ali	7,844,315 B2	11/2010	Al-Ali
RE39,672 E	6/2007	Shehada et al.	7,865,222 B2	1/2011	Weber et al.
7,239,905 B2	7/2007	Kiani-Azarbayjany et al.	7,873,497 B2	1/2011	Weber et al.
7,245,953 B1	7/2007	Parker	7,880,606 B2	2/2011	Al-Ali
7,254,429 B2	8/2007	Schurman et al.	7,880,626 B2	2/2011	Al-Ali et al.
7,254,431 B2	8/2007	Al-Ali	7,891,355 B2	2/2011	Al-Ali et al.
7,254,433 B2	8/2007	Diab et al.	7,894,868 B2	2/2011	Al-Ali et al.
7,254,434 B2	8/2007	Schulz et al.	7,899,507 B2	3/2011	Al-Ali et al.
7,272,425 B2	9/2007	Al-Ali	7,899,518 B2	3/2011	Trepagnier et al.
7,274,955 B2	9/2007	Kiani et al.	7,904,132 B2	3/2011	Weber et al.
D554,263 S	10/2007	Al-Ali	7,909,772 B2	3/2011	Popov et al.
7,280,858 B2	10/2007	Al-Ali et al.	7,910,875 B2	3/2011	Al-Ali
7,289,835 B2	10/2007	Mansfield et al.	7,919,713 B2	4/2011	Al-Ali et al.
7,292,883 B2	11/2007	De Felice et al.	7,937,128 B2	5/2011	Al-Ali
7,295,866 B2	11/2007	Al-Ali	7,937,129 B2	5/2011	Mason et al.
			7,937,130 B2	5/2011	Diab et al.
			7,941,199 B2	5/2011	Kiani
			7,951,086 B2	5/2011	Flaherty et al.
			7,957,780 B2	6/2011	Lamego et al.

(56)

References Cited

U.S. PATENT DOCUMENTS

7,962,188	B2	6/2011	Kiani et al.	8,457,707	B2	6/2013	Kiani
7,962,190	B1	6/2011	Diab et al.	8,463,349	B2	6/2013	Diab et al.
7,976,472	B2	7/2011	Kiani	8,466,286	B2	6/2013	Bellot et al.
7,988,637	B2	8/2011	Diab	8,471,713	B2	6/2013	Poeze et al.
7,990,382	B2	8/2011	Kiani	8,473,020	B2	6/2013	Kiani et al.
7,991,446	B2	8/2011	Ali et al.	8,483,787	B2	7/2013	Al-Ali et al.
8,000,761	B2	8/2011	Al-Ali	8,489,364	B2	7/2013	Weber et al.
8,008,088	B2	8/2011	Bellott et al.	8,498,684	B2	7/2013	Weber et al.
RE42,753	E	9/2011	Kiani-Azarbayjany et al.	8,504,128	B2	8/2013	Blank et al.
8,019,400	B2	9/2011	Diab et al.	8,509,867	B2	8/2013	Workman et al.
8,028,701	B2	10/2011	Al-Ali et al.	8,515,509	B2	8/2013	Bruinsma et al.
8,029,765	B2	10/2011	Bellott et al.	8,523,781	B2	9/2013	Al-Ali
8,036,727	B2	10/2011	Schurman et al.	8,529,301	B2	9/2013	Al-Ali et al.
8,036,728	B2	10/2011	Diab et al.	8,532,727	B2	9/2013	Ali et al.
8,046,040	B2	10/2011	Ali et al.	8,532,728	B2	9/2013	Diab et al.
8,046,041	B2	10/2011	Diab et al.	D692,145	S	10/2013	Al-Ali et al.
8,046,042	B2	10/2011	Diab et al.	8,547,209	B2	10/2013	Kiani et al.
8,048,040	B2	11/2011	Kiani	8,548,548	B2	10/2013	Al-Ali
8,050,728	B2	11/2011	Al-Ali et al.	8,548,549	B2	10/2013	Schurman et al.
RE43,169	E	2/2012	Parker	8,548,550	B2	10/2013	Al-Ali et al.
8,118,620	B2	2/2012	Al-Ali et al.	8,560,032	B2	10/2013	Al-Ali et al.
8,126,528	B2	2/2012	Diab et al.	8,560,034	B1	10/2013	Diab et al.
8,128,572	B2	3/2012	Diab et al.	8,570,167	B2	10/2013	Al-Ali
8,130,105	B2	3/2012	Al-Ali et al.	8,570,503	B2	10/2013	Vo et al.
8,145,287	B2	3/2012	Diab et al.	8,571,617	B2	10/2013	Reichgott et al.
8,150,487	B2	4/2012	Diab et al.	8,571,618	B1	10/2013	Lamego et al.
8,175,672	B2	5/2012	Parker	8,571,619	B2	10/2013	Al-Ali et al.
8,180,420	B2	5/2012	Diab et al.	8,584,345	B2	10/2013	Al-Ali et al.
8,182,443	B1	5/2012	Kiani	8,577,431	B2	11/2013	Lamego et al.
8,185,180	B2	5/2012	Diab et al.	8,581,732	B2	11/2013	Al-Ali et al.
8,190,223	B2	5/2012	Al-Ali et al.	8,588,880	B2	11/2013	Abdul-Hafiz et al.
8,190,227	B2	5/2012	Diab et al.	8,600,467	B2	12/2013	Al-Ali et al.
8,203,438	B2	6/2012	Kiani et al.	8,606,342	B2	12/2013	Diab
8,203,704	B2	6/2012	Merritt et al.	8,626,255	B2	1/2014	Al-Ali et al.
8,204,566	B2	6/2012	Schurman et al.	8,630,691	B2	1/2014	Lamego et al.
8,219,172	B2	7/2012	Schurman et al.	8,634,889	B2	1/2014	Al-Ali et al.
8,224,411	B2	7/2012	Al-Ali et al.	8,641,631	B2	2/2014	Sierra et al.
8,228,181	B2	7/2012	Al-Ali	8,652,060	B2	2/2014	Al-Ali
8,229,533	B2	7/2012	Diab et al.	8,663,107	B2	3/2014	Kiani
8,233,955	B2	7/2012	Al-Ali et al.	8,666,468	B1	3/2014	Al-Ali
8,244,325	B2	8/2012	Al-Ali et al.	8,667,967	B2	3/2014	Al-Ali et al.
8,255,026	B1	8/2012	Al-Ali	8,670,811	B2	3/2014	O'Reilly
8,255,027	B2	8/2012	Al-Ali et al.	8,670,814	B2	3/2014	Diab et al.
8,255,028	B2	8/2012	Al-Ali et al.	8,676,286	B2	3/2014	Weber et al.
8,260,577	B2	9/2012	Weber et al.	8,682,407	B2	3/2014	Al-Ali
8,265,723	B1	9/2012	McHale et al.	RE44,823	E	4/2014	Parker
8,274,360	B2	9/2012	Sampath et al.	RE44,875	E	4/2014	Kiani et al.
8,280,473	B2	10/2012	Al-Ali	8,690,799	B2	4/2014	Telfort et al.
8,301,217	B2	10/2012	Al-Ali et al.	8,700,112	B2	4/2014	Kiani
8,306,596	B2	11/2012	Schurman et al.	8,702,627	B2	4/2014	Telfort et al.
8,310,336	B2	11/2012	Muhsin et al.	8,706,179	B2	4/2014	Parker
8,315,683	B2	11/2012	Al-Ali et al.	8,712,494	B1	4/2014	MacNeish, III et al.
RE43,860	E	12/2012	Parker	8,715,206	B2	5/2014	Telfort et al.
8,337,403	B2	12/2012	Al-Ali et al.	8,718,735	B2	5/2014	Lamego et al.
8,346,330	B2	1/2013	Lamego	8,718,737	B2	5/2014	Diab et al.
8,353,842	B2	1/2013	Al-Ali et al.	8,718,738	B2	5/2014	Blank et al.
8,355,766	B2	1/2013	MacNeish, III et al.	8,720,249	B2	5/2014	Al-Ali
8,359,080	B2	1/2013	Diab et al.	8,721,541	B2	5/2014	Al-Ali et al.
8,364,223	B2	1/2013	Al-Ali et al.	8,721,542	B2	5/2014	Al-Ali et al.
8,364,226	B2	1/2013	Diab et al.	8,723,677	B1	5/2014	Kiani
8,374,665	B2	2/2013	Lamego	8,740,792	B1	6/2014	Kiani et al.
8,385,995	B2	2/2013	Al-Ali et al.	8,754,776	B2	6/2014	Poeze et al.
8,385,996	B2	2/2013	Smith et al.	8,755,535	B2	6/2014	Telfort et al.
8,388,353	B2	3/2013	Kiani	8,755,856	B2	6/2014	Diab et al.
8,399,822	B2	3/2013	Al-Ali	8,755,872	B1	6/2014	Marinow
8,401,602	B2	3/2013	Kiani	8,761,850	B2	6/2014	Lamego
8,405,608	B2	3/2013	Al-Ali et al.	8,764,671	B2	7/2014	Kiani
8,414,499	B2	4/2013	Al-Ali et al.	8,768,423	B2	7/2014	Shakespeare et al.
8,418,524	B2	4/2013	Al-Ali	8,771,204	B2	7/2014	Telfort et al.
8,423,106	B2	4/2013	Lamego et al.	8,777,634	B2	7/2014	Kiani et al.
8,428,967	B2	4/2013	Olsen et al.	8,781,543	B2	7/2014	Diab et al.
8,430,817	B1	4/2013	Al-Ali et al.	8,781,544	B2	7/2014	Al-Ali et al.
8,437,825	B2	5/2013	Dalvi et al.	8,781,549	B2	7/2014	Al-Ali et al.
8,455,290	B2	6/2013	Siskavich	8,788,003	B2	7/2014	Schurman et al.
8,457,703	B2	6/2013	Al-Ali	8,790,268	B2	7/2014	Al-Ali
				8,801,613	B2	8/2014	Al-Ali et al.
				8,821,397	B2	9/2014	Al-Ali et al.
				8,821,415	B2	9/2014	Al-Ali et al.
				8,830,449	B1	9/2014	Lamego et al.

(56)

References Cited

U.S. PATENT DOCUMENTS

8,831,700	B2	9/2014	Schurman et al.	9,323,894	B2	4/2016	Kiani
8,840,549	B2	9/2014	Al-Ali et al.	D755,392	S	5/2016	Hwang et al.
8,847,740	B2	9/2014	Kiani et al.	9,326,712	B1	5/2016	Kiani
8,849,365	B2	9/2014	Smith et al.	9,333,316	B2	5/2016	Kiani
8,852,094	B2	10/2014	Al-Ali et al.	9,339,220	B2	5/2016	Lamego et al.
8,852,994	B2	10/2014	Wojtczuk et al.	9,341,565	B2	5/2016	Lamego et al.
8,868,147	B2	10/2014	Stippick et al.	9,351,673	B2	5/2016	Diab et al.
8,868,150	B2	10/2014	Al-Ali et al.	9,351,675	B2	5/2016	Al-Ali et al.
8,870,792	B2	10/2014	Al-Ali et al.	9,364,181	B2	6/2016	Kiani et al.
8,886,271	B2	11/2014	Kiani et al.	9,368,671	B2	6/2016	Wojtczuk et al.
8,888,539	B2	11/2014	Al-Ali et al.	9,370,325	B2	6/2016	Al-Ali et al.
8,888,708	B2	11/2014	Diab et al.	9,370,326	B2	6/2016	McHale et al.
8,892,180	B2	11/2014	Weber et al.	9,370,335	B2	6/2016	Al-Ali et al.
8,897,847	B2	11/2014	Al-Ali	9,375,185	B2	6/2016	Ali et al.
8,909,310	B2	12/2014	Lamego et al.	9,386,953	B2	7/2016	Al-Ali
8,911,377	B2	12/2014	Al-Ali	9,386,961	B2	7/2016	Al-Ali et al.
8,912,909	B2	12/2014	Al-Ali et al.	9,392,945	B2	7/2016	Al-Ali et al.
8,920,317	B2	12/2014	Al-Ali et al.	9,397,448	B2	7/2016	Al-Ali et al.
8,921,699	B2	12/2014	Al-Ali et al.	9,408,542	B1	8/2016	Kinast et al.
8,922,382	B2	12/2014	Al-Ali et al.	9,436,645	B2	9/2016	Al-Ali et al.
8,929,964	B2	1/2015	Al-Ali et al.	9,445,759	B1	9/2016	Lamego et al.
8,942,777	B2	1/2015	Diab et al.	9,466,919	B2	10/2016	Kiani et al.
8,948,834	B2	2/2015	Diab et al.	9,474,474	B2	10/2016	Lamego et al.
8,948,835	B2	2/2015	Diab	9,480,422	B2	11/2016	Al-Ali
8,965,471	B2	2/2015	Lamego	9,480,435	B2	11/2016	Olsen
8,983,564	B2	3/2015	Al-Ali	9,492,110	B2	11/2016	Al-Ali et al.
8,989,831	B2	3/2015	Al-Ali et al.	9,510,779	B2	12/2016	Poeze et al.
8,996,085	B2	3/2015	Kiani et al.	9,517,024	B2	12/2016	Kiani et al.
8,998,809	B2	4/2015	Kiani	9,532,722	B2	1/2017	Lamego et al.
9,028,429	B2	5/2015	Telfort et al.	9,538,949	B2	1/2017	Al-Ali et al.
9,037,207	B2	5/2015	Al-Ali et al.	9,538,980	B2	1/2017	Telfort et al.
9,060,721	B2	6/2015	Reichgott et al.	9,549,696	B2	1/2017	Lamego et al.
9,066,666	B2	6/2015	Kiani	9,554,737	B2	1/2017	Schurman et al.
9,066,680	B1	6/2015	Al-Ali et al.	9,560,996	B2	2/2017	Kiani
9,072,474	B2	7/2015	Al-Ali et al.	9,560,998	B2	2/2017	Al-Ali et al.
9,078,560	B2	7/2015	Schurman et al.	9,566,019	B2	2/2017	Al-Ali et al.
9,084,569	B2	7/2015	Weber et al.	9,579,039	B2	2/2017	Jansen et al.
9,095,316	B2	8/2015	Welch et al.	9,591,975	B2	3/2017	Dalvi et al.
9,106,038	B2	8/2015	Telfort et al.	9,622,692	B2	4/2017	Lamego et al.
9,107,625	B2	8/2015	Telfort et al.	9,622,693	B2	4/2017	Diab
9,107,626	B2	8/2015	Al-Ali et al.	9,636,055	B2	5/2017	Al-Ali et al.
9,113,831	B2	8/2015	Al-Ali	9,636,056	B2	5/2017	Al-Ali
9,113,832	B2	8/2015	Al-Ali	9,649,054	B2	5/2017	Lamego et al.
9,119,595	B2	9/2015	Lamego	9,662,052	B2	5/2017	Al-Ali et al.
9,131,881	B2	9/2015	Diab et al.	9,668,679	B2	6/2017	Schurman et al.
9,131,882	B2	9/2015	Al-Ali et al.	9,668,680	B2	6/2017	Bruinsma et al.
9,131,883	B2	9/2015	Al-Ali	9,668,703	B2	6/2017	Al-Ali
9,131,917	B2	9/2015	Telfort et al.	9,675,286	B2	6/2017	Diab
9,138,180	B1	9/2015	Coverston et al.	9,687,160	B2	6/2017	Kiani
9,138,182	B2	9/2015	Al-Ali et al.	9,693,719	B2	7/2017	Al-Ali et al.
9,138,192	B2	9/2015	Weber et al.	9,693,737	B2	7/2017	Al-Ali
9,142,117	B2	9/2015	Muhsin et al.	9,697,928	B2	7/2017	Al-Ali et al.
9,153,112	B1	10/2015	Kiani et al.	9,717,425	B2	8/2017	Kiani et al.
9,153,121	B2	10/2015	Kiani et al.	9,717,458	B2	8/2017	Lamego et al.
9,161,696	B2	10/2015	Al-Ali et al.	9,724,016	B1	8/2017	Al-Ali et al.
9,161,713	B2	10/2015	Al-Ali et al.	9,724,024	B2	8/2017	Al-Ali
9,167,995	B2	10/2015	Lamego et al.	9,724,025	B1	8/2017	Kiani et al.
9,176,141	B2	11/2015	Al-Ali et al.	9,730,640	B2	8/2017	Diab et al.
9,186,102	B2	11/2015	Bruinsma et al.	9,743,887	B2	8/2017	Al-Ali et al.
9,192,312	B2	11/2015	Al-Ali	9,749,232	B2	8/2017	Sampath et al.
9,192,329	B2	11/2015	Al-Ali	9,750,442	B2	9/2017	Olsen
9,192,351	B1	11/2015	Telfort et al.	9,750,443	B2	9/2017	Smith et al.
9,195,385	B2	11/2015	Al-Ali et al.	9,750,461	B1	9/2017	Telfort
9,211,072	B2	12/2015	Kiani	9,775,545	B2	10/2017	Al-Ali et al.
9,211,095	B1	12/2015	Al-Ali	9,775,546	B2	10/2017	Diab et al.
9,218,454	B2	12/2015	Kiani et al.	9,775,570	B2	10/2017	Al-Ali
9,226,696	B2	1/2016	Kiani	9,778,079	B1	10/2017	Al-Ali et al.
9,241,662	B2	1/2016	Al-Ali et al.	9,782,077	B2	10/2017	Lamego et al.
9,245,668	B1	1/2016	Vo et al.	9,782,110	B2	10/2017	Kiani
9,259,185	B2	2/2016	Abdul-Hafiz et al.	9,787,568	B2	10/2017	Lamego et al.
9,267,572	B2	2/2016	Barker et al.	9,788,735	B2	10/2017	Al-Ali
9,277,880	B2	3/2016	Poeze et al.	9,788,768	B2	10/2017	Al-Ali et al.
9,289,167	B2	3/2016	Diab et al.	9,795,300	B2	10/2017	Al-Ali
9,295,421	B2	3/2016	Kiani et al.	9,795,310	B2	10/2017	Al-Ali
9,307,928	B1	4/2016	Al-Ali et al.	9,795,358	B2	10/2017	Telfort et al.
				9,795,739	B2	10/2017	Al-Ali et al.
				9,801,556	B2	10/2017	Kiani
				9,801,588	B2	10/2017	Weber et al.
				9,808,188	B1	11/2017	Perea et al.

(56)

References Cited

U.S. PATENT DOCUMENTS

9,814,418 B2	11/2017	Weber et al.	10,278,626 B2	5/2019	Schurman et al.
9,820,691 B2	11/2017	Kiani	10,278,648 B2	5/2019	Al-Ali et al.
9,833,152 B2	12/2017	Kiani et al.	10,279,247 B2	5/2019	Kiani
9,833,180 B2	12/2017	Shakespeare et al.	10,292,628 B1	5/2019	Poeze et al.
9,839,379 B2	12/2017	Al-Ali et al.	10,292,657 B2	5/2019	Abdul-Hafiz et al.
9,839,381 B1	12/2017	Weber et al.	10,292,664 B2	5/2019	Al-Ali
9,847,002 B2	12/2017	Kiani et al.	10,299,708 B1	5/2019	Poeze et al.
9,847,749 B2	12/2017	Kiani et al.	10,299,709 B2	5/2019	Perea et al.
9,848,800 B1	12/2017	Lee et al.	10,305,775 B2	5/2019	Lamego et al.
9,848,806 B2	12/2017	Al-Ali et al.	10,307,111 B2	6/2019	Muhsin et al.
9,848,807 B2	12/2017	Lamego	10,325,681 B2	6/2019	Sampath et al.
9,861,298 B2	1/2018	Eckerbom et al.	10,327,337 B2	6/2019	Triman et al.
9,861,304 B2	1/2018	Al-Ali et al.	10,327,713 B2	6/2019	Barker et al.
9,861,305 B1	1/2018	Weber et al.	10,332,630 B2	6/2019	Al-Ali
9,867,578 B2	1/2018	Al-Ali et al.	10,335,033 B2	7/2019	Al-Ali
9,872,623 B2	1/2018	Al-Ali	10,335,068 B2	7/2019	Poeze et al.
9,876,320 B2	1/2018	Coverston et al.	10,335,072 B2	7/2019	Al-Ali et al.
9,877,650 B2	1/2018	Muhsin et al.	10,342,470 B2	7/2019	Al-Ali et al.
9,877,686 B2	1/2018	Al-Ali et al.	10,342,487 B2	7/2019	Al-Ali et al.
9,891,079 B2	2/2018	Dalvi	10,342,497 B2	7/2019	Al-Ali et al.
9,895,107 B2	2/2018	Al-Ali et al.	10,349,895 B2	7/2019	Telfort et al.
9,913,617 B2	3/2018	Al-Ali et al.	10,349,898 B2	7/2019	Al-Ali et al.
9,924,893 B2	3/2018	Schurman et al.	10,354,504 B2	7/2019	Kiani et al.
9,924,897 B1	3/2018	Abdul-Hafiz	10,357,206 B2	7/2019	Weber et al.
9,936,917 B2	4/2018	Poeze et al.	10,357,209 B2	7/2019	Al-Ali
9,943,269 B2	4/2018	Muhsin et al.	10,366,787 B2	7/2019	Sampath et al.
9,949,676 B2	4/2018	Al-Ali	10,368,787 B2	8/2019	Reichgott et al.
9,955,937 B2	5/2018	Telfort	10,376,190 B1	8/2019	Poeze et al.
9,965,946 B2	5/2018	Al-Ali	10,376,191 B1	8/2019	Poeze et al.
9,980,667 B2	5/2018	Kiani et al.	10,383,520 B2	8/2019	Wojtczuk et al.
9,986,919 B2	6/2018	Lamego et al.	2005/0109340 A1	5/2005	Tehrani
9,986,952 B2	6/2018	Dalvi et al.	2005/0197551 A1	9/2005	Al-Ali et al.
9,989,560 B2	6/2018	Poeze et al.	2007/0282478 A1	12/2007	Al-Ali et al.
9,993,207 B2	6/2018	Al-Ali et al.	2008/0097173 A1	4/2008	Soyemi et al.
10,007,758 B2	6/2018	Al-Ali et al.	2009/0247984 A1	10/2009	Lamego et al.
10,010,276 B2	7/2018	Al-Ali et al.	2009/0275844 A1	11/2009	Al-Ali
10,032,002 B2	7/2018	Kiani et al.	2010/0004518 A1	1/2010	Vo et al.
10,039,482 B2	8/2018	Al-Ali et al.	2010/0030040 A1	2/2010	Poeze et al.
10,052,037 B2	8/2018	Kinast et al.	2010/0261979 A1	10/2010	Kiani
10,058,275 B2	8/2018	Al-Ali et al.	2010/0331639 A1	12/2010	O'Reilly
10,064,562 B2	9/2018	Al-Ali	2011/0001605 A1	1/2011	Kiani et al.
10,086,138 B1	10/2018	Novak, Jr.	2011/0082711 A1	4/2011	Poeze et al.
10,092,200 B2	10/2018	Al-Ali et al.	2011/0105854 A1	5/2011	Kiani et al.
10,092,249 B2	10/2018	Kiani et al.	2011/0208015 A1	8/2011	Welch et al.
10,098,550 B2	10/2018	Al-Ali et al.	2011/0213212 A1	9/2011	Al-Ali
10,098,591 B2	10/2018	Al-Ali et al.	2011/0230733 A1	9/2011	Al-Ali
10,098,610 B2	10/2018	Al-Ali et al.	2011/0237911 A1	9/2011	Lamego et al.
10,123,726 B2	11/2018	Al-Ali et al.	2011/0295093 A1	12/2011	Graboi et al.
10,130,289 B2	11/2018	Al-Ali et al.	2012/0059267 A1	3/2012	Lamego et al.
10,130,291 B2	11/2018	Schurman et al.	2012/0116175 A1	5/2012	Al-Ali et al.
10,149,616 B2	12/2018	Al-Ali et al.	2012/0179006 A1	7/2012	Jansen et al.
10,154,815 B2	12/2018	Al-Ali et al.	2012/0209082 A1	8/2012	Al-Ali
10,159,412 B2	12/2018	Lamego et al.	2012/0209084 A1	8/2012	Olsen et al.
10,188,296 B2	1/2019	Al-Ali et al.	2012/0227739 A1	9/2012	Kiani
10,188,331 B1	1/2019	Kiani et al.	2012/0283524 A1	11/2012	Kiani et al.
10,188,348 B2	1/2019	Al-Ali et al.	2012/0296178 A1	11/2012	Lamego et al.
10,194,847 B2	2/2019	Al-Ali	2012/0319816 A1	12/2012	Al-Ali
10,194,848 B1	2/2019	Kiani et al.	2012/0330112 A1	12/2012	Lamego et al.
10,201,298 B2	2/2019	Al-Ali et al.	2013/0023775 A1	1/2013	Lamego et al.
10,205,272 B2	2/2019	Kiani et al.	2013/0045685 A1	2/2013	Kiani
10,205,291 B2	2/2019	Scruggs et al.	2013/0046204 A1	2/2013	Lamego et al.
10,213,108 B2	2/2019	Al-Ali	2013/0041591 A1	3/2013	Lamego
10,219,706 B2	3/2019	Al-Ali	2013/0060147 A1	3/2013	Welch et al.
10,219,746 B2	3/2019	McHale et al.	2013/0096405 A1	4/2013	Garfio
10,226,187 B2	3/2019	Al-Ali et al.	2013/0096936 A1	4/2013	Sampath et al.
10,226,576 B2	3/2019	Kiani	2013/0109935 A1	5/2013	Al-Ali et al.
10,231,657 B2	3/2019	Al-Ali et al.	2013/0162433 A1	6/2013	Muhsin et al.
10,231,670 B2	3/2019	Blank et al.	2013/0190581 A1	7/2013	Al-Ali et al.
10,231,676 B2	3/2019	Al-Ali et al.	2013/0197328 A1	8/2013	Diab et al.
10,251,585 B2	4/2019	Al-Ali et al.	2013/0211214 A1	8/2013	Olsen
10,251,586 B2	4/2019	Lamego	2013/0243021 A1	9/2013	Siskavich
10,255,994 B2	4/2019	Sampath et al.	2013/0253334 A1	9/2013	Al-Ali et al.
10,258,265 B1	4/2019	Poeze et al.	2013/0274571 A1	10/2013	Diab et al.
10,258,266 B1	4/2019	Poeze et al.	2013/0296672 A1	11/2013	O'Neil et al.
10,271,748 B2	4/2019	Al-Ali	2013/0296713 A1	11/2013	Al-Ali et al.
			2013/0317370 A1	11/2013	Dalvi et al.
			2013/0324808 A1	12/2013	Al-Ali et al.
			2013/0331670 A1	12/2013	Kiani
			2013/0338461 A1	12/2013	Lamego et al.

(56)

References Cited

U.S. PATENT DOCUMENTS

2014/0012100	A1	1/2014	Al-Ali et al.	2015/0112151	A1	4/2015	Muhsin et al.
2014/0025306	A1	1/2014	Weber et al.	2015/0116076	A1	4/2015	Al-Ali et al.
2014/0034353	A1	2/2014	Al-Ali et al.	2015/0126830	A1	5/2015	Schurman et al.
2014/0051953	A1	2/2014	Lamego et al.	2015/0133755	A1	5/2015	Smith et al.
2014/0058230	A1	2/2014	Abdul-Hafiz et al.	2015/0140863	A1	5/2015	Al-Ali et al.
2014/0066783	A1	3/2014	Kiani et al.	2015/0141781	A1	5/2015	Weber et al.
2014/0077956	A1	3/2014	Sampath et al.	2015/0165312	A1	6/2015	Kiani
2014/0081100	A1	3/2014	Muhsin et al.	2015/0196237	A1	7/2015	Lamego
2014/0081175	A1	3/2014	Telfort	2015/0201874	A1	7/2015	Diab
2014/0094667	A1	4/2014	Schurman et al.	2015/0208966	A1	7/2015	Al-Ali
2014/0100434	A1	4/2014	Diab et al.	2015/0216459	A1	8/2015	Al-Ali et al.
2014/0114199	A1	4/2014	Lamego et al.	2015/0230755	A1	8/2015	Al-Ali et al.
2014/0120564	A1	5/2014	Workman et al.	2015/0238722	A1	8/2015	Al-Ali
2014/0121482	A1	5/2014	Merritt et al.	2015/0245773	A1	9/2015	Lamego et al.
2014/0121483	A1	5/2014	Kiani	2015/0245794	A1	9/2015	Al-Ali
2014/0127137	A1	5/2014	Bellott et al.	2015/0257689	A1	9/2015	Al-Ali et al.
2014/0128696	A1	5/2014	Al-Ali	2015/0272514	A1	10/2015	Kiani et al.
2014/0128699	A1	5/2014	Al-Ali et al.	2015/0351697	A1	12/2015	Weber et al.
2014/0129702	A1	5/2014	Lamego et al.	2015/0351704	A1	12/2015	Kiani et al.
2014/0135588	A1	5/2014	Al-Ali et al.	2015/0359429	A1	12/2015	Al-Ali et al.
2014/0142401	A1	5/2014	Al-Ali et al.	2015/0366472	A1	12/2015	Kiani
2014/0142402	A1	5/2014	Al-Ali et al.	2015/0366507	A1	12/2015	Blank
2014/0163344	A1	6/2014	Al-Ali	2015/0374298	A1	12/2015	Al-Ali et al.
2014/0163402	A1	6/2014	Lamego et al.	2015/0380875	A1	12/2015	Coverston et al.
2014/0166076	A1	6/2014	Kiani et al.	2016/0000362	A1	1/2016	Diab et al.
2014/0171763	A1	6/2014	Diab	2016/0007930	A1	1/2016	Weber et al.
2014/0180038	A1	6/2014	Kiani	2016/0029932	A1	2/2016	Al-Ali
2014/0180154	A1	6/2014	Sierra et al.	2016/0029933	A1	2/2016	Al-Ali et al.
2014/0194709	A1	7/2014	Al-Ali et al.	2016/0045118	A1	2/2016	Kiani
2014/0194711	A1	7/2014	Al-Ali	2016/0051205	A1	2/2016	Al-Ali et al.
2014/0194766	A1	7/2014	Al-Ali et al.	2016/0058338	A1	3/2016	Schurman et al.
2014/0206963	A1	7/2014	Al-Ali	2016/0058347	A1	3/2016	Reichgott et al.
2014/0213864	A1	7/2014	Abdul-Hafiz et al.	2016/0066823	A1	3/2016	Kind et al.
2014/0243627	A1	8/2014	Diab et al.	2016/0066824	A1	3/2016	Al-Ali et al.
2014/0266790	A1	9/2014	Al-Ali et al.	2016/0066879	A1	3/2016	Telfort et al.
2014/0275808	A1	9/2014	Poeze et al.	2016/0072429	A1	3/2016	Kiani et al.
2014/0275835	A1	9/2014	Lamego et al.	2016/0073967	A1	3/2016	Lamego et al.
2014/0275871	A1	9/2014	Lamego et al.	2016/0081552	A1	3/2016	Wojtczuk et al.
2014/0275872	A1	9/2014	Merritt et al.	2016/0095543	A1	4/2016	Telfort et al.
2014/0275881	A1	9/2014	Lamego et al.	2016/0095548	A1	4/2016	Al-Ali et al.
2014/0288400	A1	9/2014	Diab et al.	2016/0103598	A1	4/2016	Al-Ali et al.
2014/0296664	A1	10/2014	Bruinsma et al.	2016/0113527	A1	4/2016	Al-Ali et al.
2014/0303520	A1	10/2014	Telfort et al.	2016/0143548	A1	5/2016	Al-Ali
2014/0309506	A1	10/2014	Lamego et al.	2016/0166182	A1	6/2016	Al-Ali et al.
2014/0316217	A1	10/2014	Purdon et al.	2016/0166183	A1	6/2016	Poeze et al.
2014/0316218	A1	10/2014	Purdon et al.	2016/0166210	A1	6/2016	Al-Ali
2014/0316228	A1	10/2014	Blank et al.	2016/0196388	A1	7/2016	Lamego
2014/0323825	A1	10/2014	Al-Ali et al.	2016/0197436	A1	7/2016	Barker et al.
2014/0330092	A1	11/2014	Al-Ali et al.	2016/0213281	A1	7/2016	Eckerbom et al.
2014/0330098	A1	11/2014	Merritt et al.	2016/0228043	A1	8/2016	O'Neil et al.
2014/0330099	A1	11/2014	Al-Ali et al.	2016/0233632	A1	8/2016	Scruggs et al.
2014/0336481	A1	11/2014	Shakespeare et al.	2016/0234944	A1	8/2016	Schmidt et al.
2014/0343436	A1	11/2014	Kiani	2016/0270735	A1	9/2016	Diab et al.
2014/0357966	A1	12/2014	Al-Ali et al.	2016/0283665	A1	9/2016	Sampath et al.
2014/0371548	A1	12/2014	Al-Ali et al.	2016/0287090	A1	10/2016	Al-Ali et al.
2014/0371632	A1	12/2014	Al-Ali et al.	2016/0287786	A1	10/2016	Kiani
2014/0378784	A1	12/2014	Kiani et al.	2016/0296169	A1	10/2016	McHale et al.
2015/0005600	A1	1/2015	Blank et al.	2016/0310052	A1	10/2016	Al-Ali et al.
2015/0011907	A1	1/2015	Purdon et al.	2016/0314260	A1	10/2016	Kiani
2015/0012231	A1	1/2015	Poeze et al.	2016/0324488	A1	11/2016	Olsen
2015/0018650	A1	1/2015	Al-Ali et al.	2016/0327984	A1	11/2016	Al-Ali et al.
2015/0025406	A1	1/2015	Al-Ali	2016/0331332	A1	11/2016	Al-Ali
2015/0032029	A1	1/2015	Al-Ali et al.	2016/0367173	A1	12/2016	Dalvi et al.
2015/0038859	A1	2/2015	Dalvi et al.	2017/0000394	A1	1/2017	Al-Ali et al.
2015/0045637	A1	2/2015	Dalvi	2017/0007134	A1	1/2017	Al-Ali et al.
2015/0051462	A1	2/2015	Olsen	2017/0007198	A1	1/2017	Al-Ali et al.
2015/0080754	A1	3/2015	Purdon et al.	2017/0014083	A1	1/2017	Diab et al.
2015/0087936	A1	3/2015	Al-Ali et al.	2017/0014084	A1	1/2017	Al-Ali et al.
2015/0094546	A1	4/2015	Al-Ali	2017/0024748	A1	1/2017	Haider
2015/0097701	A1	4/2015	Al-Ali et al.	2017/0042488	A1	2/2017	Muhsin
2015/0099950	A1	4/2015	Al-Ali et al.	2017/0055851	A1	3/2017	Al-Ali
2015/0099951	A1	4/2015	Al-Ali et al.	2017/0055882	A1	3/2017	Al-Ali et al.
2015/0099955	A1	4/2015	Al-Ali et al.	2017/0055887	A1	3/2017	Al-Ali
2015/0101844	A1	4/2015	Al-Ali et al.	2017/0055896	A1	3/2017	Al-Ali et al.
2015/0106121	A1	4/2015	Muhsin et al.	2017/0079594	A1	3/2017	Telfort et al.
				2017/0086723	A1	3/2017	Al-Ali et al.
				2017/0143281	A1	5/2017	Olsen
				2017/0147774	A1	5/2017	Kiani
				2017/0156620	A1	6/2017	Al-Ali et al.

(56)

References Cited

U.S. PATENT DOCUMENTS

2017/0173632	A1	6/2017	Al-Ali	2018/0242923	A1	8/2018	Al-Ali et al.
2017/0187146	A1	6/2017	Kiani et al.	2018/0242924	A1	8/2018	Barker et al.
2017/0188919	A1	7/2017	Al-Ali et al.	2018/0242926	A1	8/2018	Muhsin et al.
2017/0196464	A1	7/2017	Jansen et al.	2018/0247353	A1	8/2018	Al-Ali et al.
2017/0196470	A1	7/2017	Lamego et al.	2018/0247712	A1	8/2018	Muhsin et al.
2017/0224262	A1	8/2017	Al-Ali	2018/0249933	A1	9/2018	Schurman et al.
2017/0228516	A1	8/2017	Sampath et al.	2018/0253947	A1	9/2018	Muhsin et al.
2017/0245790	A1	8/2017	Al-Ali et al.	2018/0256087	A1	9/2018	Al-Ali et al.
2017/0251974	A1	9/2017	Shreim et al.	2018/0256113	A1	9/2018	Weber et al.
2017/0251975	A1	9/2017	Shreim et al.	2018/0285094	A1	10/2018	Housel et al.
2017/0258403	A1	9/2017	Abdul-Hafiz et al.	2018/0289325	A1	10/2018	Poeze et al.
2017/0311851	A1	11/2017	Schurman et al.	2018/0289337	A1	10/2018	Al-Ali et al.
2017/0311891	A1	11/2017	Kiani et al.	2018/0296161	A1	10/2018	Shreim et al.
2017/0325728	A1	11/2017	Al-Ali et al.	2018/0300919	A1	10/2018	Muhsin et al.
2017/0332976	A1	11/2017	Al-Ali et al.	2018/0310822	A1	11/2018	Lndorf et al.
2017/0340293	A1	11/2017	Al-Ali et al.	2018/0310823	A1	11/2018	Al-Ali et al.
2017/0360310	A1	12/2017	Kiani et al.	2018/0317826	A1	11/2018	Muhsin
2017/0367632	A1	12/2017	Al-Ali et al.	2018/0317841	A1	11/2018	Novak, Jr.
2018/0008146	A1	1/2018	Al-Ali et al.	2018/0333055	A1	11/2018	Lamego et al.
2018/0013562	A1	1/2018	Haider et al.	2018/0333087	A1	11/2018	Al-Ali
2018/0014752	A1	1/2018	Al-Ali et al.	2019/0000317	A1	1/2019	Muhsin et al.
2018/0028124	A1	2/2018	Al-Ali et al.	2019/0000362	A1	1/2019	Kiani et al.
2018/0055385	A1	3/2018	Al-Ali	2019/0015023	A1	1/2019	Monfre
2018/0055390	A1	3/2018	Kiani et al.	2019/0021638	A1	1/2019	Al-Ali et al.
2018/0055430	A1	3/2018	Diab et al.	2019/0029574	A1	1/2019	Schurman et al.
2018/0064381	A1	3/2018	Shakespeare et al.	2019/0029578	A1	1/2019	Al-Ali et al.
2018/0069776	A1	3/2018	Lamego et al.	2019/0038143	A1	2/2019	Al-Ali
2018/0070867	A1	3/2018	Smith et al.	2019/0058280	A1	2/2019	Al-Ali et al.
2018/0082767	A1	3/2018	Al-Ali et al.	2019/0058281	A1	2/2019	Al-Ali et al.
2018/0085068	A1	3/2018	Telfort	2019/0069813	A1	3/2019	Al-Ali
2018/0087937	A1	3/2018	Al-Ali et al.	2019/0069814	A1	3/2019	Al-Ali
2018/0103874	A1	4/2018	Lee et al.	2019/0076028	A1	3/2019	Al-Ali et al.
2018/0103905	A1	4/2018	Kiani	2019/0082979	A1	3/2019	Al-Ali et al.
2018/0110478	A1	4/2018	Al-Ali	2019/0090748	A1	3/2019	Al-Ali
2018/0116575	A1	5/2018	Perea et al.	2019/0090760	A1	3/2019	Kinast et al.
2018/0125368	A1	5/2018	Lamego et al.	2019/0090764	A1	3/2019	Al-Ali
2018/0125430	A1	5/2018	Al-Ali et al.	2019/0104973	A1	4/2019	Poeze et al.
2018/0125445	A1	5/2018	Telfort et al.	2019/0110719	A1	4/2019	Poeze et al.
2018/0130325	A1	5/2018	Kiani et al.	2019/0117070	A1	4/2019	Muhsin et al.
2018/0132769	A1	5/2018	Weber et al.	2019/0117139	A1	4/2019	Al-Ali et al.
2018/0132770	A1	5/2018	Lamego	2019/0117140	A1	4/2019	Al-Ali et al.
2018/0146901	A1	5/2018	Al-Ali et al.	2019/0117141	A1	4/2019	Al-Ali
2018/0146902	A1	5/2018	Kiani et al.	2019/0117930	A1	4/2019	Al-Ali
2018/0153442	A1	6/2018	Eckerbom et al.	2019/0122763	A1	4/2019	Sampath et al.
2018/0153446	A1	6/2018	Kiani	2019/0133525	A1	5/2019	Al-Ali et al.
2018/0153447	A1	6/2018	Al-Ali et al.	2019/0142283	A1	5/2019	Lamego et al.
2018/0153448	A1	6/2018	Weber et al.	2019/0142344	A1	5/2019	Telfort et al.
2018/0161499	A1	6/2018	Al-Ali et al.	2019/0150800	A1	5/2019	Poeze et al.
2018/0168491	A1	6/2018	Al-Ali et al.	2019/0150856	A1	5/2019	Kiani et al.
2018/0174679	A1	6/2018	Sampath et al.	2019/0167161	A1	6/2019	Al-Ali et al.
2018/0174680	A1	6/2018	Sampath et al.	2019/0175019	A1	6/2019	Al-Ali et al.
2018/0182484	A1	6/2018	Sampath et al.	2019/0192076	A1	6/2019	McHale et al.
2018/0184917	A1	7/2018	Kiani	2019/0200941	A1	7/2019	Chandran et al.
2018/0192924	A1	7/2018	Al-Ali	2019/0201623	A1	7/2019	Kiani
2018/0192953	A1	7/2018	Shreim et al.	2019/0209025	A1	7/2019	Al-Ali
2018/0192955	A1	7/2018	Al-Ali et al.	2019/0214778	A1	7/2019	Scruggs et al.
2018/0199871	A1	7/2018	Pauley et al.	2019/0216319	A1	7/2019	Poeze et al.
2018/0206795	A1	7/2018	Al-Ali	2019/0216379	A1	7/2019	Al-Ali et al.
2018/0206815	A1	7/2018	Telfort	2019/0221966	A1	7/2019	Kiani et al.
2018/0213583	A1	7/2018	Al-Ali	2019/0223804	A1	7/2019	Blank et al.
2018/0214031	A1	8/2018	Kiani et al.	2019/0231199	A1	8/2019	Al-Ali et al.
2018/0214090	A1	8/2018	Al-Ali et al.	2019/0231241	A1	8/2019	Al-Ali et al.
2018/0216370	A1	8/2018	Ishiguro et al.	2019/0231270	A1	8/2019	Abdul-Hafiz et al.
2018/0218792	A1	8/2018	Muhsin et al.	2019/0239787	A1	8/2019	Pauley et al.
2018/0225960	A1	8/2018	Al-Ali et al.	2019/0239824	A1	8/2019	Muhsin et al.
2018/0238718	A1	8/2018	Dalvi	2019/0254578	A1	8/2019	Lamego
2018/0242853	A1	8/2018	Al-Ali				
2018/0242921	A1	8/2018	Muhsin et al.				

FOREIGN PATENT DOCUMENTS

JP	H06-181930	7/1994
JP	H09-024099	1/1997
WO	WO 2013/158791 A3	10/2013




FIG. 1




FIG. 2




FIG. 3A

PaO₂ vs SaO₂ sensitive to pH, Temp




FIG. 3B




FIG. 3C




FIG. 3D




FIG. 3E




FIG. 3F




FIG. 4




FIG. 5




FIG. 6





FIG. 8A






FIG. 8B




FIG. 9A




FIG. 9B




FIG. 10A




FIG. 10B




FIG. 11

HYPERSATURATION INDEXPRIORITY CLAIM TO RELATED
PROVISIONAL APPLICATIONS

The present application is a continuation of U.S. application Ser. No. 14/852,356, filed Sep. 11, 2015, entitled "Hypersaturation Index," now U.S. Pat. No. 9,775,546, which is a continuation of U.S. application Ser. No. 13/865,081, filed Apr. 17, 2013, entitled "Hypersaturation Index," now U.S. Pat. No. 9,131,881, which claims priority benefit under 35 U.S.C. § 119(e) of U.S. Provisional Application Ser. No. 61/719,866, filed Oct. 29, 2012, entitled "Noninvasive Partial Pressure of Oxygen Sensing System," U.S. Provisional Application Ser. No. 61/703,087, filed Sep. 19, 2012, entitled "Noninvasive Partial Pressure of Oxygen Sensing System," and U.S. Provisional Application Ser. No. 61/625,599, filed Apr. 17, 2012, entitled "Noninvasive Partial Pressure of Oxygen Sensing System," the disclosures of which are incorporated herein by reference.

FIELD OF THE INVENTION

The present invention relates to the field of noninvasive oxygen delivery measurement using optical based sensors.

BACKGROUND

The measurement of oxygen delivery to the body and the corresponding oxygen consumption by its organs and tissues is vitally important to medical practitioners in the diagnosis and treatment of various medical conditions. Oxygen delivery is useful, for example, during certain medical procedures, where artificially providing additional oxygen to the patient's blood stream may become necessary. For example, during an intubation procedure, the patient will stop breathing while the procedure is performed. The patient is typically provided with oxygen before the intubation procedure. Because the patient stops breathing during an intubation procedure, the patient's blood oxygen saturation level will fall. In that situation, the medical practitioner must ensure that the patient has sufficient reserves of oxygen in their system before intubation so that during the intubation procedure suffocation is avoided. At the same time, providing oxygen at a high pressure to a patient can cause damage to the alveoli of an adult patient. On the other hand, even normal oxygen levels can or cause blindness in neonatal patients.

The current standard of care is to measure oxygen delivery through the use of a pulse oximeter. Pulse oximeters measure oxygen saturation (SpO_2). SpO_2 represents the percent of available hemoglobin that can chemically bind with oxygen molecules.

Another indicator of oxygen delivery is the partial pressure of oxygen (PaO_2). However, there are currently no reliable ways to measure PaO_2 noninvasively. Invasive PaO_2 measurements require expensive sensors and are known to carry serious side effects that can harm the health of a patient.

SUMMARY

Embodiments of the present disclosure provide a hypersaturation index for measuring a patient's absorption of oxygen in the blood stream after a patient has reached 100% oxygen saturation. This hypersaturation index provides an indication of an increased level of dissolved oxygen in the

plasma. This is useful, for example, for patients that are on supplemental oxygen therapy or are on a ventilator or closed-loop positive pressure delivery device. An excessively high level of PaO_2 can be dangerous for most patients.

In some patients, for example neonates, a high level of PaO_2 can cause loss of eyesight. Significant damage can occur to the lungs, and in particular, to the alveoli structures in the lungs, if the PaO_2 level is too high.

In another embodiment, a timer is provided that indicates when a hypersaturated patient is likely to return to a baseline saturation level after oxygen administration is stopped. This is useful, for example, during an intubation procedure.

Pulse oximetry is a noninvasive technique which allows the continuous in vivo measurement of arterial oxygen saturation and pulse rate in conjunction with generation of a photoplethysmograph waveform. Measurements rely on sensors which are typically placed on the fingertip of an adult or the foot of an infant. As explained in detail below, the ratio of red and infrared light signals absorbed at the measuring site is calculated (R/IR ratio). Oxygen saturation level is determined using a lookup table that is based on empirical formulas that convert the ratio of red and infrared absorption rates to a SpO_2 value.

A correlation exists between the R/IR ratio and the level of PaO_2 . This relationship between R/IR ratio and PaO_2 levels, however, varies from patient to patient. For example, at the same PaO_2 level, one patient may have a R/IR ratio of 0.55 and another patient may have a reading of 0.45. Therefore, once the absorption level reaches 100%, it becomes difficult for the medical practitioner to assess the patient's condition with respect to PaO_2 and the potential dangers of a high level of PaO_2 . Without the ability to accurately measure the PaO_2 level, medical practitioners are in need of a noninvasive way to monitor a patient's hypersaturation status.

In an embodiment of the present invention, a hypersaturation index is calculated based on the reading of the R/IR ratio at the measurement site. In an embodiment of the invention, a maximum hypersaturation index threshold is determined such that an alarm is triggered when the hypersaturation index reaches or exceeds the threshold. In another embodiment, an alarm is triggered when the hypersaturation index reaches or falls below its starting point when it was first calculated.

BRIEF DESCRIPTION OF THE DRAWINGS

The drawings and following associated descriptions are provided to illustrate embodiments of the present disclosure and do not limit the scope of the claims. Corresponding numerals indicate corresponding parts, and the leading digit of each numbered item indicates the first figure in which an item is found.

FIG. 1 illustrates a perspective view of a patient monitoring system in accordance with an embodiment of the disclosure.

FIG. 2 illustrates a block drawing of a patient monitoring system in accordance with an embodiment of the disclosure.

FIG. 3A-3B illustrate graphs of SpO_2 versus PaO_2 .

FIG. 3C illustrates a saturation calibration curve.

FIG. 3D-3E illustrate graphs of the difference between arterial and venous saturation vs. perfusion index.

FIG. 3F illustrates the graph of the ratio of R/IR and PaO_2 vs. time.

FIG. 4 illustrates a graph of SpO_2 versus the R/IR ratio and a hypersaturation index versus the R/IR ratio.

FIG. 5 illustrates a flowchart depicting an embodiment of the invention.

FIG. 6 illustrates a flowchart depicting an embodiment of the invention.

FIG. 7 illustrates a visualization of an indication of hypersaturation according to an embodiment of the invention.

FIG. 8A-8B illustrate visualizations of indications of hypersaturation according to an embodiment of the invention.

FIGS. 9A and 9B illustrate a timer display illustrating when a hypersaturated patient will return to a normal saturation level.

FIGS. 10A and 10B illustrate an alternative embodiment of a timer display.

FIG. 11 illustrates another alternative embodiment of a timer display.

DETAILED DESCRIPTION

Aspects of the disclosure will now be set forth in detail with respect to the figures and various embodiments. One of skill in the art will appreciate, however, that other embodiments and configurations of the devices and methods disclosed herein will still fall within the scope of this disclosure even if not described in the same detail as some other embodiments. Aspects of various embodiments discussed do not limit the scope of the disclosure herein, which is instead defined by the claims following this description.

Turning to FIG. 1, a patient monitoring system 100 is illustrated. The patient monitoring system 100 includes a patient monitor 102 attached to a sensor 106 by a cable 104. The sensor monitors various physiological data of a patient and sends signals indicative of the parameters to the patient monitor 102 for processing. The patient monitor 102 generally includes a display 108, control buttons 110, and a speaker 112 for audible alerts. The display 108 is capable of displaying readings of various monitored patient parameters, which may include numerical readouts, graphical readouts, and the like. Display 108 may be a liquid crystal display (LCD), a cathode ray tube (CRT), a plasma screen, a Light Emitting Diode (LED) screen, Organic Light Emitting Diode (OLED) screen, or any other suitable display. A patient monitoring system 102 may monitor oxygen saturation (SpO₂), hypersaturation, perfusion index (PI), pulse rate (PR), hemoglobin count, and/or other parameters.

FIG. 2 illustrates details of a patient monitoring system 100 in a schematic form. Typically a sensor 106 includes energy emitters 216 located on one side of a patient monitoring site 218 and one or more detectors 220 located generally opposite. The patient monitoring site 218 is usually a patient's finger (as pictured), toe, ear lobe, or the like. Energy emitters 216, such as LEDs, emit particular wavelengths of energy, typically red and infrared light signals, through the flesh of a patient at the monitoring site 218, which attenuates the energy. The detector(s) 220 then detect the attenuated energy and send representative signals to the patient monitor 102 for processing. The patient monitor 102 includes processing board 222 and a host instrument 223. The processing board 222 includes a sensor interface 224, signal processor(s) 226, and an instrument manager 228.

The host instrument typically includes one or more displays 108, control buttons 110, a speaker 112 for audio messages, and a wireless signal broadcaster 234. Control buttons 110 may comprise a keypad, a full keyboard, a track wheel, and the like. A patient monitor 102 can include buttons, switches, toggles, check boxes, and the like imple-

mented in software and actuated by a mouse, trackball, touch screen, or other input device.

The sensor interface 224 receives the signals from the sensor 106 detector(s) 220 and passes the signals to the processor(s) 226 for processing into representations of physiological parameters. These are then passed to the instrument manager 228, which may further process the parameters for display by the host instrument 223. The processor(s) 226 may also communicate with a memory 230 located on the sensor 106; such memory typically contains information related to the properties of the sensor that may be useful in processing the signals, such as, for example, emitter 216 energy wavelengths. The elements of processing board 222 provide processing of the sensor 106 signals. Tracking medical signals is difficult because the signals may include various anomalies that do not reflect an actual changing patient parameter. Strictly displaying raw signals or even translations of raw signals could lead to inaccurate readings or unwarranted alarm states. The processing board 222 processing generally helps to detect truly changing conditions from limited duration anomalies. The host instrument 223 then is able to display one or more physiological parameters according to instructions from the instrument manager 228, and caregivers can be more confident in the reliability of the readings.

Physiology Background

When oxygen molecules come into contact with blood, the majority of the oxygen molecules are bound to the hemoglobin in red-blood cells and a small portion is dissolved directly in the blood plasma. Both of these processes are driven by the partial pressure of oxygen. In the lung, oxygen diffuses across the alveolar membrane, and then the red cell membrane in lung capillaries. When an oxygen molecule encounters a molecule of hemoglobin, it wedges itself between the iron atom and a nitrogen atom attached to the globin chain. This helps to hold the heme group in place in the protein. One molecule of hemoglobin with its four heme groups is capable of binding four molecules of diatomic oxygen, O₂. The pigment of the oxygen loaded heme group, which is called oxyhemoglobin, is a brilliant red color. This is typically the color of arterial blood. Pressure from dissolved oxygen in plasma and in the surroundings in the red cell helps to keep the oxygen on its binding site.

As the blood circulates to the periphery, the small amount of plasma dissolved oxygen is consumed first by cells in organs and tissues, which causes a drop in the partial pressure of oxygen. This release in pressure makes available the much larger reservoir of heme-bound oxygen which begins a sequential unloading of its four oxygen molecules. At the most, under normal circumstances only 3 molecules of oxygen are unloaded. Partially or fully unloaded hemoglobin is called deoxyhemoglobin. It is a dark blue to purplish color. This is also the typical color of venous blood.

There is a general relationship between the oxygen saturation in blood and the partial pressure of oxygen. This nonlinear relation is described by the oxygen dissociation curve as shown in FIG. 3A. FIG. 3A illustrates a graph of SaO₂ versus the partial pressure of oxygen dissolved in the arterial blood, PaO₂. As the partial pressure of oxygen in the arterial blood increases, the percentage of oxygen saturation of the hemoglobin will increase. After the SaO₂ level reaches 100%, the PaO₂ level continues to rise, but the SaO₂ level will not rise further. Thus, although it is possible to estimate PaO₂ levels when SaO₂ is below 100%, as illustrated in FIG. 3A, after a certain point, very large changes in the PaO₂ will produce little change in the SaO₂. A patient whose

physiology falls on the first part of the curve is commonly referred to as the Hypoxic. As can be seen from FIG. 3A, there is a high sensitivity around PaO₂=30 mmHg, i.e. the slope is large. A patient whose physiology falls on the second part of the curve where SaO₂ begins to level off is Normoxic. In the last portion of the curve, where SaO₂ has reached 100%, a patient is considered Hyperoxic.

FIG. 3B illustrates a graph showing the potential shift in the disassociation curve based on an individual patients response. For example a left shift may occur with decreased temperature, decreased 1,3-diphosphoglycerate (2,3DPG), increased pH, or higher CO in the blood. As another example, a right shift will occur with reduced affinity, increased temperature, increased 2,3-DPG and decreased pH. Thus, there is some-uncertainty when determining PaO₂ based on the SaO₂ measurement. This uncertainty can be reduced if the pH and temperature are given as inputs to the device where an appropriate curve may be selected.

Oxygen Consumption

The following oxygen content equation relates the amount of oxygen present in the blood given certain hemoglobin concentration (tHb) and partial pressure of oxygen (PaO₂)

$$\text{ContO}_2(\text{O}_2 \text{ mL/dL}) = t\text{Hb}(\text{gramHb/dL}) \cdot 1.34(\text{ml O}_2/\text{gramHb}) \cdot \text{SaO}_2 + 0.0031(\text{ml O}_2/\text{mmHg/dL}) \cdot \text{PaO}_2(\text{mmHg}) \quad \text{Eq. 1}$$

Alternatively, the Oxygen Content can be measured directly using a Masimo Rainbow Pulse Oximeter available from Masimo Corporation of Irvine, Calif.

Tissues need a requisite amount of O₂ molecules for metabolism. Under steady state conditions the O₂ consumption is fairly constant. In order to quantify the relationship between oxygen transport and its consumption the Fick principle can be applied. The essence of the Fick principle is that blood flow to an organ can be calculated using a marker substance if the following information is known:

- Amount of marker substance taken up by the organ per unit time
- Concentration of marker substance in arterial blood supplying the organ
- Concentration of marker substance in venous blood leaving the organ

In Fick's original method, the "organ" was the entire human body and the marker substance was oxygen.

This principle may be applied in different ways. For example, if the blood flow to an organ is known, together with the arterial and venous concentrations of the marker substance, the uptake of marker substance by the organ may then be calculated.

As discussed above, hemoglobin and plasma are the main oxygen vectors in the blood. The oxygen content equation can be combined with the Fick principle to describe oxygen consumption and its relationship to blood flow as shown below in Eq.2.

$$\text{OC} = \text{Ca} \cdot [1.34 \cdot t\text{Hb} \cdot (\text{SaO}_2 - \text{SvO}_2) + 0.0031 \cdot (\text{PaO}_2 - \text{PvO}_2)] \quad \text{Eq. 2}$$

Where OC is Oxygen consumption (mL/min), Ca is Cardiac output (i.e. local blood flow at the test site (dL/min)), tHb is the Total hemoglobin (gram/dL), SaO₂ is Arterial saturation fraction (0-1.0), SvO₂ is Venous saturation fraction (0-1.0), PaO₂ is the Partial pressure of oxygen in the arterial blood (mmHg), PvO₂ is the Partial pressure of oxygen in the venous blood (mmHg), 1.34 represents the HbO₂ carrying capacity (mL O₂/gram Hb), and 0.0031 represents O₂ solubility coefficient in blood (mL O₂/dL). Noninvasive Oxygen Saturation Measurement

Pulse oximetry was invented by Dr. Ayogi in the 1972 as a technique to measure arterial oxygen saturation noninvasively. Dr. Ayogi was able to isolate the arterial pulse absorption from tissue, bone and cartilage absorptions by looking at a signal synchronous with the heartbeat reflecting the local blood flow at the measurement site. This signal is called the photo-plethysmograph and it can be isolated by the use of a high-pass filter. By exploiting the predictable relationship between arterial oxygen saturation and light absorption through a vascular bed, the arterial blood oxygen saturation (SpaO₂) can be calculated noninvasively. Note that the addition of a small p to SaO₂ to denote calculation from an arterial pulse. It can be shown that the use of two distinct light sources, Red (R)=660 nm and Infrared (IR)=910 nm, a pulse oximeter can calculate the oxygen saturation noninvasively by relating a ratio=R (AC/DC)/IR (AC/DC) to the hemoglobin oxygen saturation through a typical pulse oximeter calibration curve shown in FIG. 3C. We will refer to this ratio as (R/IR) ratio.

Modifying Eq. 2, if (SaO₂-SvO₂) is replaced with ΔSat, (PaO₂-PvO₂) replaced with ΔP, Ca replaced with the local blood flow (BF), the oxygen consumption is set to a constant and the equation is solved for BF, Eq. 3 results:

$$\text{BF} = \text{Const} / [1.34 \cdot t\text{Hb} \cdot \Delta\text{Sat} + 0.0031 \cdot \Delta\text{P}] \quad \text{Eq. 3}$$

Eq. 3 shows an inverse relationship between blood flow and the arterio-venous saturation difference, ΔSat, as well as arterio-venous O₂ partial pressure difference (ΔP). At normal inspired oxygen levels, the majority of the oxygen is supplied by the hemoglobin. But when the concentration of inspired oxygen is raised, its partial pressure increases, hence ΔP, and more oxygen is delivered to the tissue through the O₂ dissolved in the plasma. Based on Eq. 3, if we consider a digit where a pulse oximeter probe is placed, the increase of inspired oxygen partial pressure will lead to a decrease in the arterio-venous ΔSat. This is true whenever the oxygen consumption is relatively constant.

In a vascular bed the arterial vasculature is coupled mechanically to the venous vasculature through the tissues. Although this coupling is small, the optical arterial pulse, e.g. photo-plethysmograph, has invariably a small venous component. This component is not fixed across subjects but its average is indirectly calibrated for in the saturation calibration curve. Its effect on the arterial pulse is proportional to the coupling size as well as the difference between the arterial and venous saturations at the site. Let us consider a typical subject at room-air saturation of 98%. Looking at the saturation calibration curve of FIG. 3C, a (R/IR) ratio of 0.53 corresponds to 98% saturation. If the inspired oxygen concentration is increased beyond the normal O₂=21%, the (R/IR) ratio continues to drop below 0.53. An example is shown in FIG. 3F where the ratio starts at 0.43 and goes down to 0.43. It can even reach a level as low as 0.3 on some subjects at an inspired O₂=100%.

This behavior may be explained by the reduction in the optical effect of venous coupling as the delta saturation between the arterial and the venous is reduced due to the increase in availability of plasma oxygen. Under this condition, the venous blood will look, optically, a lot like the arterial blood. Hence, the size of the Red photo-plethysmograph signal will shrink with respect to the IR indicating a shrinking ΔSat, i.e. higher venous saturation. In 1995, Masimo Corporation (Masimo) introduced a new technique for calculation the venous oxygen saturation (SpvO₂) by introducing an artificial pulse into the digit (see, e.g., U.S. Pat. No. 5,638,816, incorporated herein by reference). By using a pulse oximeter with a probe and a subject's digit, a

continuous measure of SpaO₂ and SpvO₂ can be calculated. The blood perfusion index (PI) is used as a proxy for the blood flow to the digit. FIG. 3D depicts such an inverse relationship between blood flow (BF) and arterio-venous saturation ΔSat.

FIG. 3E depicts the effect of increasing the inspired O₂ concentration on the calculated ΔSat. As expected there is a commensurate reduction in the ΔSat with the increase of oxygen concentration. The arterio-venous ΔSat will continue to decrease if the oxygen pressure is increased beyond atmospheric pressure. However, a point of diminishing return will be reached where no more change is possible. At that point the R/IR ratio will stop changing as shown in FIG. 3F. The increase in PaO₂ can be indirectly monitored beyond the normal 100 mmHg by looking at the effects of shrinking ΔSat. This cannot be done by looking at the SaO₂ as it will plateau at 100%.

FIG. 4 illustrates a graph of SpO₂ saturation percentage **400** versus the R/IR ratio **401** according to an embodiment of the invention. In the illustrated example, the R/IR ratio is at 0.5 when the SpO₂ maxes out at 100%. While the SpO₂ level will max out at 100% saturation, the R/IR ratio continues to drop when more oxygen is dissolved in the blood. An embodiment of the invention calls for calculating a hypersaturation index **402** based on the R/IR ratio after the point **403** where the R/IR ratio translates to a SpO₂ level of 100% saturation. This hypersaturation index **402** assists medical practitioners in exercising their judgment in ensuring that the patient's blood is not too oversaturated with oxygen. In another embodiment, the hypersaturation index is calculated in response to a user signal, i.e., not necessarily at the point where the SpO₂ level is at 100% saturation.

Determining a level of hypersaturation is particularly important in a variety of patient types. For example, patients on supplemental O₂ titration are at risk of complications caused by hypersaturation. Patients on a ventilator or where FiO₂ therapy is given to the patient are also at risk. Further, closed loop positive pressure O₂ delivery or FiO₂ delivery devices also place a patient at risk of hypersaturation. This may include, for example, CPAP machines or those suffering obstructive sleep apnea.

In an embodiment of the invention, the patient's oxygen saturation level SpO₂ is determined and monitored. When the saturation level reaches 100%, an indication of rising oxygen levels, such as a hypersaturation index, is calculated. The indication of rising oxygen levels may also be displayed on an output device such as the display **108** in FIG. 1. FIG. 5 is a flowchart that illustrates this embodiment of the invention. In this embodiment, the patient's blood oxygen saturation level SpO₂ is determined at step **500**. If the blood oxygen saturation level maxes out at 100% at step **520**, an indication of hypersaturation is calculated at step **530** and displayed at step **540**.

In another embodiment of the invention, illustrated in FIG. 6, the patient's oxygen saturation level SpO₂ is determined and stored at step **620** in response to a signal from the user at step **610**. The signal typically indicates that a medical procedure is about to begin. A base hypersaturation index value is then calculated at step **630** based on the stored oxygen saturation level and the R/IR ratio. The hypersaturation index is then monitored at step **640** as the patient's oxygen saturation level changes. Next, an alarm trigger is generated at step **660** when the hypersaturation index value is less than or equal to the base hypersaturation index value as determined in step **650**. Finally, an alarm is activated at step **670** in response to the alarm trigger.

In an alternative embodiment, the oximeter monitors a patient and automatically determines a baseline oxygen saturation level and/or baseline ratio from stable measurements taken when the oximeter first begins measurements. The oximeter can indicate that a baseline measurement has been determined or can indicate that it is unable to determine a baseline measurement if stable measurements cannot be obtained. Once a baseline measurement is obtained, the oximeter will monitor the patient for an inflection point in the saturation and ratio calculations. If the oximeter finds an inflection point where the patient's oxygen saturation begins to rise and/or ratios begin to fall, it will determine that oxygen is being administered to the patient. In this way, a caregiver is not required to push a button or otherwise indicate the start of a procedure or the start oxygen administration. Along the same lines, once a patient is hypersaturated, the oximeter will monitor the saturation level and/or ratio calculations of the patient for an inflection point indicating that oxygen is no longer being administered to the patient. Again the oximeter will alarm when the oxygen saturation values and/or ratios return to their normal baseline levels.

In yet another embodiment of the invention, a maximum hypersaturation index value is also calculated and stored in response to a user signal. In this embodiment, an alarm trigger is generated when the monitored hypersaturation index value is more than or equal to the maximum hypersaturation index value.

In an alternative embodiment, a visual oxygen hypersaturation alarm is activated. The oxygen hypersaturation alarm may include text that indicates that the oxygen hypersaturation index has dropped below the base hypersaturation index value. In another embodiment, the alarm may include text that indicates that the oxygen hypersaturation index has exceeded a threshold value. The visual oxygen hypersaturation alarm may be accompanied or replaced by an audio alarm in certain embodiments.

FIG. 7 illustrates an example of a visualization of an indication of hypersaturation according to an embodiment of the invention. This visualization can be displayed on a display, such as the display **108** in FIG. 1. In the illustrated embodiment, the indicator is displayed as a speedometer-type visualization. The display includes a pointer **700** that points to the current value of the hypersaturation indicator. The value, for example, can be on a scale of 0-100 or 0-10 to differentiate from oxygen saturation. In one embodiment, the spectrum of possible levels may be indicated by various shades or colors. For example, the low range of values may be indicated by an area **701** that is green in color, the medium range in values may be indicated by an area **702** that is orange in color, and the high range in values may be indicated by an area **703** that is red in color.

FIG. 8A illustrates another example of a visualization of an indication of hypersaturation according to an embodiment of the invention. This visualization can also be displayed on a display, such as the display **108** in FIG. 1. In the illustrated embodiment, the hypersaturation indicator is displayed as a bar **800**. In one embodiment, the size of the area of the bar that is shaded or colored depends on the value of the hypersaturation indicator. For example, a low value may be represented by a small shaded area below the "L" level **801**. A medium value may be represented by a larger shaded area that remains below the "M" level **802**. Finally, a high value may be represented by an even larger shaded area that can cover the entirety of the bar up to the "H" level **803**.

FIG. 8B illustrates yet another example of a visualization of an indication of hypersaturation. The displayed graph **820**

illustrates hypersaturation on a scale of 0-100%. The line **821** illustrates an estimated hypersaturation value. The shaded area **823** illustrates the variability of the hypersaturation index. In other words, each patient's physiology is different and depending patient, their hypersaturation may not exactly follow the population average. This is explained in more detail, for example, with respect to FIG. 3B. Thus, the shaded area **823** provides an indication of the uncertainty in the estimate **821**. This provides a care provider with a better indication of the actual hypersaturation that the patient is experiencing. In the embodiment of FIG. 8B, 0% represents no detectable oxygen reserve, or no indication of hypersaturation. 100% indicates a maximum detectable reserve or a maximum hypersaturation.

FIG. 9A illustrates an embodiment of a hypersaturation timer **900**. A hypersaturation timer **900** is useful, for example, during procedures such as a patient intubation when the patient is forced to stop breathing. The timer provides an indication of the amount of time a care giver has before the patient returns from a hypersaturated state to a baseline saturation state. The timer includes a countdown indications **901-905**. In the embodiment of FIG. 9A, the countdown begins at about 60 seconds and counts down to zero. When the counter is initially started, the amount of time a patient will take to return to a baseline saturation state is relatively difficult to determine. Thus, the timer **900** provides a range of time left which is illustrated by shaded area **907**. The shaded area moves clockwise around the timer indicating a range of time left before the patient reaches a baseline state. As time goes by, the amount of time a patient will take to return to a baseline saturation state becomes more predictable based on how quickly the ratios change. Thus, as illustrated in FIG. 9B, the range indicated by the shaded area **910** becomes smaller.

FIG. 10 illustrates another embodiment of a timer **1000**. Similar to FIGS. 9A and B, timer **1000** has a count-down range **1002** that decreases as time expires and the time in which a patient returns to their base line saturation becomes more certain.

In another embodiment not shown, a simple digital count-down clock could also be used to indicate the amount of time left for a hypersaturation patient to return to their baseline saturation level. The count-down clock can indicate a range or it can simply indicate a number and speed up or slow down based on the rate of return experienced by the patient.

FIG. 11 illustrates an embodiment count down display of an oxygen reserve, or the time left for a hypersaturation patient to return to baseline saturation. Put in other terms, the time in seconds starts increasing from zero as a subject transitions from normoxia to hyperoxia. The display then decreases when the subject transitions from the Hyperoxic state to the Normoxic state. The display of FIG. 11 includes an arc indicator, for example, arc indicators **1101**, **1102**, and **1103**. The indicators are arced in order to show the uncertainty range in the time left in the display. Although the arcs **1101**, **1102**, and **1103** are all illustrated on the display for illustration and explanation purposes, it is to be understood that during measurement, only a single arc is displayed which according to the relative time

Although the foregoing has been described in terms of certain specific embodiments, other embodiments will be apparent to those of ordinary skill in the art from the disclosure herein. Moreover, the described embodiments have been presented by way of example only, and are not intended to limit the scope of the disclosure. Indeed, the novel methods and systems described herein may be embodied in a variety of other forms without departing from the

spirit thereof. Accordingly, other combinations, omissions, substitutions, and modifications will be apparent to the skilled artisan in view of the disclosure herein. Thus, the present disclosure is not limited by the disclosed embodiments, but is defined by reference to the appended claims. The accompanying claims and their equivalents are intended to cover forms or modifications as would fall within the scope and spirit of the disclosure.

What is claimed is:

1. A noninvasive patient monitoring system for providing an indication of a patient's amount of oxygen reserves in the patient's body, the oxygen reserve being oxygen dissolved in the patient's blood during a hyperoxic state of the patient and different from a measure of a percentage of oxyhemoglobin in the blood at a time of measurement acquisition, the system comprising:

one or more light emitters configured to emit at least a plurality of wavelengths of light into a portion of the patient's body;

a light detector configured to detect the light after attenuation by the body and output one or more signals responsive to the attenuated light, the attenuation responsive to oxygenation of the patient's blood;

one or more signal processors configured to process the one or more signals to electronically calculate an indicator responsive to the oxygen reserve, wherein the indicator is calculated based on a ratio of information from at least a first of the plurality of wavelengths and information from at least a second of the plurality of wavelengths during the hyperoxic state of the patient; and

a display responsive to output of the one or more signal processors to electronically display a shaded or colored area responsive to the indicator, the amount of shading or coloring responsive to the patient's amount of oxygen reserve.

2. The patient monitoring system of claim 1, wherein the area comprises a bar.

3. The patient monitoring system of claim 1, wherein a greater amount of shading or coloring indicates a greater amount of oxygen reserve.

4. The patient monitoring system of claim 1, wherein the one or more processors are further configured to electronically calculate a second indicator responsive to the percentage of oxyhemoglobin in blood, the second indicator being the patient's oxygen saturation.

5. The patient monitoring system of claim 4, wherein the display is further configured to electronically display a value responsive to the second indicator.

6. The patient monitoring system of claim 1, wherein the display is further configured to generate an alarm in response to the indicator crossing a threshold.

7. A noninvasive method of providing an indication of a patient's oxygen state different from oxygen saturation, wherein the oxygen saturation is a measure of a percentage of oxyhemoglobin in the blood at a time of measurement acquisition, the method comprising:

using an electronic light source including one or more light emitters, emitting at least a plurality of wavelengths of light into a portion of the patient's body;

using an electronic light detector, detecting the light after attenuation by the body, the attenuation responsive to oxygenation of the patient's blood, and outputting one or more signals from the light detector, the one or more signals responsive to the attenuation;

processing the one or more signals using one or more signal processors to electronically calculate an indica-

11

tor responsive to a quantity of oxygen dissolved in the patient's blood and not bound to any hemoglobin while the patient is in a hyperoxic state, the indicator calculated based on a ratio of information from at least a first of the plurality of wavelengths and information from at least a second of the plurality of wavelengths during the hyperoxic state of the patient; and

electronically displaying a shaded or colored area responsive to the indicator, the amount of shading or coloring responsive to the quantity of oxygen dissolved in the patient's blood and not bound to any hemoglobin.

8. The method of claim 7, wherein the area comprises a bar.

9. The method of claim 7, wherein a greater amount of shading or coloring indicates a larger quantity of oxygen dissolved in the patient's blood and not bound to any hemoglobin.

10. The method of claim 7, wherein processing further comprises electronically calculating a second indicator responsive to the oxygen saturation.

11. The method of claim 10, further comprising electronically displaying a value responsive to the second indicator.

12. The method of claim 7, wherein electronically displaying further comprises generating an alarm in response to the indicator crossing a threshold.

13. A noninvasive patient monitoring system for providing an indication of a patient's amount of oxygen reserves in the patient's body, the oxygen reserve being oxygen dissolved in the patient's blood during a hyperoxic state of the patient and different from a measure of a percentage of oxyhemoglobin in the blood at a time of measurement acquisition, the system comprising:

an input of an electronic physiological monitor, the input configured to receive one or more signals responsive to light of at least a plurality of wavelengths attenuated by body tissue of the patient, the one or more signals output from a light detector configured to detect the attenuated light;

12

one or more physiological hardware processors of the electronic physiological monitor, the one or more processors configured to electronically calculate an indicator responsive to the oxygen reserve, wherein the indicator is responsive to a ratiometric calculation, the ratiometric calculation including a denominator responsive to portions of the one or more signals that were responsive to at least one of the plurality of wavelengths during the hyperoxic state of the patient and a numerator responsive to portions of the one or more signals that were responsive to at least another of the plurality of wavelengths during the hyperoxic state of the patient; and

a display responsive to output of the one or more signal processors to electronically display a shaded or colored area responsive to the indicator, the amount of shading or coloring responsive to the patient's amount of oxygen reserve.

14. The patient monitoring system of claim 13, wherein the area comprises a bar.

15. The patient monitoring system of claim 13, wherein a greater amount of shading or coloring indicates a greater amount of oxygen reserve.

16. The patient monitoring system of claim 13, wherein the one or more processors are further configured to electronically calculate a second indicator responsive to the percentage of oxyhemoglobin in the blood, the second indicator being the patient's oxygen saturation.

17. The patient monitoring system of claim 16, wherein the display is further configured to electronically display a value responsive to the second indicator.

18. The patient monitoring system of claim 13, wherein the display is further configured to generate an alarm in response to the indicator crossing a threshold.

* * * * *

专利名称(译)	过饱和指数		
公开(公告)号	US10531819	公开(公告)日	2020-01-14
申请号	US15/705761	申请日	2017-09-15
[标]申请(专利权)人(译)	梅西莫股份有限公司		
申请(专利权)人(译)	Masimo公司		
当前申请(专利权)人(译)	Masimo公司		
[标]发明人	DIAB MOHAMED K IYENGAR PRASHANTH SAMPATH ANAND AL ALI AMMAR		
发明人	DIAB, MOHAMED K. IYENGAR, PRASHANTH SAMPATH, ANAND AL-ALI, AMMAR		
IPC分类号	A61B5/1455 A61B5/00 A61B5/0205		
CPC分类号	A61B5/0205 A61B5/746 A61B5/7282 A61B5/14552 A61B5/7405 A61B5/14551 A61B5/743 A61B2562/0238 A61B5/6826 A61M2230/205		
优先权	61/719866 2012-10-29 US 61/703087 2012-09-19 US 61/625599 2012-04-17 US		
其他公开文献	US20180055430A1		
外部链接	Espacenet		

摘要(译)

本公开的实施例提供了一种过饱和指数，该过饱和指数用于在患者已经达到100%的氧饱和度之后测量患者对血流中的氧的吸收。该过饱和指数提供了患者氧分压的指示。在本发明的一个实施例中，过饱和指数是基于测量位置处两种不同波长的能量的吸收率来计算的。在本发明的一个实施例中，确定最大过饱和指数阈值，使得当过饱和指数达到或超过阈值时触发警报。在另一实施例中，当过饱和指数第一次被计算时，当过饱和指数达到或低于其起始点时，触发警报。

