



US008818753B2

(12) **United States Patent**
Yuen et al.

(10) **Patent No.:** **US 8,818,753 B2**
(45) **Date of Patent:** **Aug. 26, 2014**

(54) **METHODS AND SYSTEMS FOR
PROCESSING SOCIAL INTERACTIVE DATA
AND SHARING OF TRACKED ACTIVITY
ASSOCIATED WITH LOCATIONS**

(71) Applicant: **Fitbit, Inc.**, San Francisco, CA (US)

(72) Inventors: **Shelten Gee Jao Yuen**, Berkeley, CA
(US); **James Park**, Berkeley, CA (US);
Hans Christiansen Lee, Carmel, CA
(US)

(73) Assignee: **Fitbit, Inc.**, San Francisco, CA (US)

(*) Notice: Subject to any disclaimer, the term of this
patent is extended or adjusted under 35
U.S.C. 154(b) by 0 days.

(21) Appl. No.: **14/066,310**

(22) Filed: **Oct. 29, 2013**

(65) **Prior Publication Data**

US 2014/0052790 A1 Feb. 20, 2014

Related U.S. Application Data


(60) Continuation of application No. 13/959,706, filed on
Aug. 5, 2013, now Pat. No. 8,615,377, and a
continuation-in-part of application No. 13/693,334,
filed on Dec. 4, 2012, now Pat. No. 8,548,770, which is
a division of application No. 13/667,229, filed on Nov.
2, 2012, now Pat. No. 8,437,980, which is a division of
application No. 13/469,027, filed on May 10, 2012,
now Pat. No. 8,311,769, which is a division of
application No. 13/246,843, filed on Sep. 27, 2011,
now Pat. No. 8,180,591, which is a division of
application No. 13/156,304, filed on Jun. 8, 2011, said
application No. 13/959,706 is a continuation-in-part of
application No. 13/759,485, filed on Feb. 5, 2013, now
Pat. No. 8,543,351.

(60) Provisional application No. 61/680,230, filed on Aug.
6, 2012, provisional application No. 61/388,595, filed
on Sep. 30, 2010, provisional application No.
61/390,811, filed on Oct. 7, 2010.

(51) **Int. Cl.**
G06F 19/00 (2011.01)
G06F 15/00 (2006.01)
A63B 24/00 (2006.01)
A61B 5/145 (2006.01)
A63B 71/06 (2006.01)
A61B 5/11 (2006.01)
H04L 29/08 (2006.01)
G01C 21/00 (2006.01)
A61B 5/22 (2006.01)
A61B 5/00 (2006.01)
G01C 22/00 (2006.01)
A61B 5/024 (2006.01)
A61B 5/0205 (2006.01)
G01C 21/20 (2006.01)
A61B 5/021 (2006.01)

(52) **U.S. Cl.**
CPC **H04L 67/22** (2013.01); **A63B 2220/73**
(2013.01); **A63B 2230/06** (2013.01); **A61B**
5/4806 (2013.01); **G06F 15/00** (2013.01);
A63B 24/0062 (2013.01); **A61B 5/14546**
(2013.01); **A61B 5/744** (2013.01); **A61B**
2560/0242 (2013.01); **A61B 5/743** (2013.01);
A63B 2230/70 (2013.01); **A63B 71/0686**
(2013.01); **A61B 2562/0219** (2013.01); **A61B**
5/1123 (2013.01); **A61B 5/4809** (2013.01);
A61B 5/6838 (2013.01); **A61B 5/1112**
(2013.01); **A61B 5/14532** (2013.01); **A61B**
5/0002 (2013.01); **A61B 5/681** (2013.01); **G01C**
21/00 (2013.01); **G01C 22/006** (2013.01); **A63B**
2220/72 (2013.01); **A61B 5/7264** (2013.01);
A61B 5/7278 (2013.01); **A61B 5/4815**
(2013.01); **A61B 2560/045** (2013.01); **G06F**
19/00 (2013.01); **A61B 5/222** (2013.01); **A61B**
5/024 (2013.01); **A61B 5/6801** (2013.01);
A61B 5/4812 (2013.01); **A63B 2230/50**
(2013.01); **A61B 5/1118** (2013.01); **A61B**
5/02055 (2013.01); **G01C 21/20** (2013.01);
G06F 19/3481 (2013.01); **A61B 5/021**
(2013.01); **A63B 2230/75** (2013.01)
USPC **702/160**

(58) **Field of Classification Search**
CPC G06F 3/011; G06F 3/005; G06Q 30/02;
G02B 2027/0178; G02B 27/0093
USPC 702/160, 155, 182–185
See application file for complete search history.



(56)

References Cited

U.S. PATENT DOCUMENTS

| | | | | | |
|--------------|---------|--------------------|-----------------|---------|-----------------------------|
| 2,717,736 A | 9/1955 | Schlesinger | 7,200,517 B2 | 4/2007 | Darley et al. |
| 2,883,255 A | 4/1959 | Anderson | 7,246,033 B1 | 7/2007 | Kudo |
| 3,163,856 A | 12/1964 | Kirby | 7,261,690 B2 | 8/2007 | Teller et al. |
| 3,250,270 A | 5/1966 | Bloom | 7,272,982 B2 | 9/2007 | Neuhauser et al. |
| 3,918,658 A | 11/1975 | Beller | 7,373,820 B1 | 5/2008 | James |
| 4,192,000 A | 3/1980 | Lipsev | 7,443,292 B2 | 10/2008 | Jensen et al. |
| 4,244,020 A | 1/1981 | Ratcliff | 7,457,724 B2 | 11/2008 | Vock et al. |
| 4,281,663 A | 8/1981 | Pringle | 7,467,060 B2 | 12/2008 | Kulach et al. |
| 4,284,849 A | 8/1981 | Anderson et al. | 7,505,865 B2 | 3/2009 | Ohkubo et al. |
| 4,312,358 A | 1/1982 | Barney | 7,559,877 B2 | 7/2009 | Parks et al. |
| 4,367,752 A | 1/1983 | Jimenez et al. | 7,653,508 B1 | 1/2010 | Kahn et al. |
| 4,390,922 A | 6/1983 | Pelliccia | 7,690,556 B1 | 4/2010 | Kahn et al. |
| 4,407,295 A | 10/1983 | Steuer et al. | 7,713,173 B2 | 5/2010 | Shin et al. |
| 4,425,921 A | 1/1984 | Fujisaki et al. | 7,762,952 B2 | 7/2010 | Lee et al. |
| 4,575,804 A | 3/1986 | Ratcliff | 7,774,156 B2 | 8/2010 | Niva et al. |
| 4,578,769 A | 3/1986 | Frederick | 7,789,802 B2 | 9/2010 | Lee et al. |
| 4,617,525 A | 10/1986 | Lloyd | 7,881,902 B1 | 2/2011 | Kahn et al. |
| 4,887,249 A | 12/1989 | Thinesen | 7,927,253 B2 | 4/2011 | Vincent et al. |
| 4,977,509 A | 12/1990 | Pitchford et al. | 7,983,876 B2 | 7/2011 | Vock et al. |
| 5,058,427 A | 10/1991 | Brandt | 8,028,443 B2 | 10/2011 | Case, Jr. |
| 5,224,059 A | 6/1993 | Nita et al. | 8,055,469 B2 | 11/2011 | Kulach et al. |
| 5,295,085 A | 3/1994 | Hoffacker | 8,099,318 B2 | 1/2012 | Moukas et al. |
| 5,323,650 A | 6/1994 | Fullen et al. | 8,177,260 B2 | 5/2012 | Tropper et al. |
| 5,446,705 A | 8/1995 | Haas et al. | 8,180,591 B2 | 5/2012 | Yuen et al. |
| 5,456,648 A | 10/1995 | Edinburg et al. | 8,180,592 B2 | 5/2012 | Yuen et al. |
| 5,583,776 A | 12/1996 | Levi et al. | 8,311,769 B2 | 11/2012 | Yuen et al. |
| 5,671,162 A | 9/1997 | Werbin | 8,311,770 B2 | 11/2012 | Yuen et al. |
| 5,704,350 A | 1/1998 | Williams, III | 8,386,008 B2 | 2/2013 | Yuen et al. |
| 5,724,265 A | 3/1998 | Hutchings | 8,437,980 B2 | 5/2013 | Yuen et al. |
| 5,890,128 A | 3/1999 | Diaz et al. | 8,463,576 B2 | 6/2013 | Yuen et al. |
| 5,891,042 A | 4/1999 | Sham et al. | 8,463,577 B2 | 6/2013 | Yuen et al. |
| 5,894,454 A | 4/1999 | Kondo | 8,533,620 B2 * | 9/2013 | Hoffman et al. 715/772 |
| 5,899,963 A | 5/1999 | Hutchings | 8,543,185 B2 | 9/2013 | Yuen et al. |
| 5,947,868 A | 9/1999 | Dugan | 8,543,351 B2 | 9/2013 | Yuen et al. |
| 5,955,667 A | 9/1999 | Fyfe | 8,548,770 B2 | 10/2013 | Yuen et al. |
| 5,976,083 A | 11/1999 | Richardson et al. | 8,583,402 B2 | 11/2013 | Yuen et al. |
| 6,018,705 A | 1/2000 | Gaudet et al. | 8,597,093 B2 | 12/2013 | Engelberg et al. |
| 6,077,193 A | 6/2000 | Buhler et al. | 8,670,953 B2 | 3/2014 | Yuen et al. |
| 6,085,248 A | 7/2000 | Sambamurthy et al. | 2001/0055242 A1 | 12/2001 | Deshmukh et al. |
| 6,129,686 A | 10/2000 | Friedman | 2002/0013717 A1 | 1/2002 | Ando et al. |
| 6,145,389 A | 11/2000 | Ebeling et al. | 2002/0077219 A1 | 6/2002 | Cohen et al. |
| 6,183,425 B1 | 2/2001 | Whalen et al. | 2002/0082144 A1 | 6/2002 | Pfeffer |
| 6,213,872 B1 | 4/2001 | Harada et al. | 2002/0109600 A1 | 8/2002 | Mault et al. |
| 6,241,684 B1 | 6/2001 | Amino et al. | 2002/0178060 A1 | 11/2002 | Sheehan |
| 6,287,262 B1 | 9/2001 | Amano et al. | 2002/0198776 A1 | 12/2002 | Nara et al. |
| 6,301,964 B1 | 10/2001 | Fyfe et al. | 2003/0018523 A1 | 1/2003 | Rappaport et al. |
| 6,302,789 B2 | 10/2001 | Harada et al. | 2003/0050537 A1 | 3/2003 | Wessel |
| 6,305,221 B1 | 10/2001 | Hutchings | 2003/0065561 A1 | 4/2003 | Brown et al. |
| 6,309,360 B1 | 10/2001 | Mault | 2003/0131059 A1 | 7/2003 | Brown et al. |
| 6,469,639 B2 | 10/2002 | Tanenhaus et al. | 2004/0054497 A1 | 3/2004 | Kurtz |
| 6,478,736 B1 | 11/2002 | Mault | 2004/0061324 A1 | 4/2004 | Howard |
| 6,513,381 B2 | 2/2003 | Fyfe et al. | 2004/0117963 A1 | 6/2004 | Schneider |
| 6,513,532 B2 | 2/2003 | Mault et al. | 2004/0152957 A1 | 8/2004 | Stivoric et al. |
| 6,527,711 B1 | 3/2003 | Stivoric et al. | 2005/0037844 A1 | 2/2005 | Shum et al. |
| 6,529,827 B1 | 3/2003 | Beason et al. | 2005/0038679 A1 | 2/2005 | Short |
| 6,561,951 B2 | 5/2003 | Cannon et al. | 2005/0054938 A1 | 3/2005 | Wehman et al. |
| 6,571,200 B1 | 5/2003 | Mault | 2005/0102172 A1 | 5/2005 | Sirmans, Jr. |
| 6,585,622 B1 | 7/2003 | Shum et al. | 2005/0107723 A1 | 5/2005 | Wehman et al. |
| 6,607,493 B2 | 8/2003 | Song | 2005/0228244 A1 | 10/2005 | Banet |
| 6,620,078 B2 | 9/2003 | Pfeffer | 2005/0228692 A1 | 10/2005 | Hodgdon |
| 6,678,629 B2 | 1/2004 | Tsuji | 2005/0234742 A1 | 10/2005 | Hodgdon |
| 6,699,188 B2 | 3/2004 | Wessel | 2005/0248718 A1 | 11/2005 | Howell et al. |
| 6,761,064 B2 | 7/2004 | Tsuji | 2005/0272564 A1 | 12/2005 | Pyles et al. |
| 6,790,178 B1 | 9/2004 | Mault et al. | 2006/0020177 A1 | 1/2006 | Seo et al. |
| 6,808,473 B2 | 10/2004 | Hisano et al. | 2006/0025282 A1 | 2/2006 | Redmann |
| 6,811,516 B1 | 11/2004 | Dugan | 2006/0047208 A1 | 3/2006 | Yoon |
| 6,813,582 B2 | 11/2004 | Levi et al. | 2006/0047447 A1 | 3/2006 | Brady et al. |
| 6,813,931 B2 | 11/2004 | Yadav et al. | 2006/0089542 A1 | 4/2006 | Sands |
| 6,856,938 B2 | 2/2005 | Kurtz | 2006/0111944 A1 | 5/2006 | Sirmans, Jr. et al. |
| 6,862,575 B1 | 3/2005 | Anttila et al. | 2006/0129436 A1 | 6/2006 | Short |
| 7,062,225 B2 | 6/2006 | White | 2006/0143645 A1 | 6/2006 | Vock et al. |
| 7,162,368 B2 | 1/2007 | Levi et al. | 2006/0277474 A1 | 12/2006 | Robarts et al. |
| 7,171,331 B2 | 1/2007 | Vock et al. | 2006/0282021 A1 | 12/2006 | DeVault et al. |
| | | | 2006/0287883 A1 | 12/2006 | Turgiss et al. |
| | | | 2007/0050715 A1 | 3/2007 | Behar |
| | | | 2007/0051369 A1 | 3/2007 | Choi et al. |
| | | | 2007/0071643 A1 | 3/2007 | Hall et al. |
| | | | 2007/0123391 A1 | 5/2007 | Shin et al. |
| | | | 2007/0136093 A1 | 6/2007 | Rankin et al. |

2007/0155277 A1 7/2007 Amitai et al.
 2007/0159926 A1 7/2007 Prstojevich et al.
 2007/0179356 A1 8/2007 Wessel
 2007/0194066 A1 8/2007 Ishihara et al.
 2007/0197920 A1 8/2007 Adams
 2007/0208544 A1 9/2007 Kulach et al.
 2007/0276271 A1 11/2007 Chan
 2008/0093838 A1 4/2008 Tropper et al.
 2008/0125288 A1 5/2008 Case
 2008/0140163 A1 6/2008 Keacher et al.
 2008/0140338 A1 6/2008 No et al.
 2009/0018797 A1 1/2009 Kasama et al.
 2009/0043531 A1 2/2009 Kahn et al.
 2009/0048044 A1 2/2009 Oleson et al.
 2009/0054737 A1 2/2009 Magar et al.
 2009/0063193 A1 3/2009 Barton et al.
 2009/0171788 A1 7/2009 Tropper et al.
 2009/0271147 A1 10/2009 Sugai
 2010/0205541 A1 8/2010 Rapaport et al.
 2010/0217099 A1 8/2010 LeBoeuf et al.
 2011/0003665 A1 1/2011 Burton et al.
 2011/0009051 A1 1/2011 Khedouri et al.
 2011/0022349 A1 1/2011 Stirling et al.
 2011/0080349 A1 4/2011 Holbein et al.
 2011/0106449 A1 5/2011 Chowdhary et al.
 2011/0131005 A1 6/2011 Ueshima et al.
 2011/0193704 A1 8/2011 Harper et al.
 2011/0224508 A1 9/2011 Moon
 2011/0230729 A1 9/2011 Shirasaki et al.
 2012/0072165 A1 3/2012 Jallon
 2012/0083705 A1 4/2012 Yuen et al.
 2012/0083714 A1 4/2012 Yuen et al.
 2012/0083715 A1 4/2012 Yuen et al.
 2012/0083716 A1 4/2012 Yuen et al.
 2012/0084053 A1 4/2012 Yuen et al.
 2012/0084054 A1 4/2012 Yuen et al.
 2012/0092157 A1 4/2012 Tran
 2012/0183939 A1 7/2012 Aragonés et al.
 2012/0226471 A1 9/2012 Yuen et al.
 2012/0226472 A1 9/2012 Yuen et al.
 2012/0227737 A1 9/2012 Mastrototaro et al.
 2012/0265480 A1 10/2012 Oshima
 2012/0330109 A1 12/2012 Tran
 2013/0006718 A1 1/2013 Nielsen et al.
 2013/0072169 A1 3/2013 Ross et al.
 2013/0073254 A1 3/2013 Yuen et al.
 2013/0073255 A1 3/2013 Yuen et al.
 2013/0080113 A1 3/2013 Yuen et al.
 2013/0095459 A1 4/2013 Tran
 2013/0096843 A1 4/2013 Yuen et al.
 2013/0151196 A1 6/2013 Yuen et al.
 2013/0158369 A1 6/2013 Yuen et al.
 2013/0231574 A1 9/2013 Tran
 2013/0261475 A1 10/2013 Mochizuki
 2013/0267249 A1 10/2013 Rosenberg
 2013/0268199 A1 10/2013 Nielsen et al.
 2013/0268236 A1 10/2013 Yuen et al.
 2013/0296666 A1 11/2013 Kumar et al.
 2013/0296673 A1 11/2013 Thaveeprungsriporn et al.
 2013/0310896 A1 11/2013 Mass
 2013/0325396 A1 12/2013 Yuen et al.
 2014/0035761 A1 2/2014 Burton et al.
 2014/0039804 A1 2/2014 Park et al.
 2014/0039840 A1 2/2014 Yuen et al.
 2014/0077673 A1 3/2014 Garg et al.

FOREIGN PATENT DOCUMENTS

JP 11347021 12/1999
 WO WO 2008/038141 4/2008
 WO WO 2009/042965 4/2009

OTHER PUBLICATIONS

“Automatic classification of ambulatory movements and evaluation of energy consumptions utilizing accelerometers and barometer”, Ohtaki, et al, Microsystem Technologies, vol. 11, No. 8-10, Aug. 2005, pp. 1034-1040.

“Classification of Human Moving Patterns Using Air Pressure and Acceleration”, Sagawa, et al, Proceedings of the 24th Annual Conference of the IEEE Industrial Electronics Society, vol. 2, Aug.-Sep. 1998, pp. 1214-1219.

“Non-restricted measurement of walking distance”, Sagawa, et al, IEEE Int’l Conf. on Systems, Man, and Cybernetics, vol. 3, Oct. 2000, pp. 1847-1852.

“Activity Classification Using Realistic Data From Wearable Sensors”, Parkka, et al, IEEE Transactions on Information Technology in Biomedicine, vol. 10, No. 1, Jan. 2006, pp. 119-128.

“Indoor Navigation with MEMS Sensors”, Lammel, et al., Proceedings of the Eurosensors XIII conference, vol. 1, No. 1, Sep. 2009, pp. 532-535.

“Design of a Wireless Assisted Pedestrian Dead Reckoning System—The NavMote Experience”, Fang, et al, IEEE Transactions on Instrumentation and Measurement, vol. 54, No. 6, Dec. 2005, pp. 2342-2358.

“On Foot Navigation: When GPS alone is not Enough”, Ladetto, et al, Journal of Navigation, vol. 53, No. 2, Sep. 2000, pp. 279-285.

“A Hybrid Discriminative/Generative Approach for Modeling Human Activities”, Lester, et al., Proc. of the Int’l Joint Conf. Artificial Intelligence, 2005, pp. 766-772.

“Using MS5534 for altimeters and barometers”, Intersema App., Note AN501, Jan. 2006.

“Validated caloric expenditure estimation using a single body-worn sensor”, Lester, et al, Proc. of the Int’l Conf. on Ubiquitous Computing, 2009, pp. 225-234.

“Drift-free dynamic height sensor using MEMS IMU aided by MEMS pressure sensor”, Tanigawa, et al, Workshop on Positioning, Navigation and Communication, Mar. 2008, pp. 191-196.

“Improvement of Walking Speed Prediction by Accelerometry and Altimetry, Validated by Satellite Positioning”, Perrin, et al, Medical & Biological Engineering & Computing, vol. 38, 2000, pp. 164-168.

“An Intelligent Multi-Sensor system for Pedestrian Navigation”, Retscher, Journal of Global Positioning Systems, vol. 5, No. 1, 2006, pp. 110-118.

“Evaluation of a New Method of Heading Estimation of Pedestrian Dead Reckoning Using Shoe Mounted Sensors”, Stirling et al., Journal of Navigation, vol. 58, 2005, pp. 31-45.

“Direct Measurement of Human Movement by Accelerometry”, Godfrey, et al., Medical Engineering & Physics, vol. 30, 2008, pp. 1364-1386.

“Foot Mounted Inertia System for Pedestrian Navigation”, Godha et al., Measurement Science and Technology, vol. 19, No. 7, May 2008, pp. 1-9.

“Altimeter and Barometer System”, Clifford, et al., Freescale Semiconductor Application Note AN1979, Rev. 3, Nov. 2006.

“SCP 1000-D01/D11 Pressure Sensor as Barometer and Altimeter”, VTI Technologies Application, Jun. 2006, Note 33.

“Suunto LUMI User Guide”, Jun. and Sep. 1997.
 International Search Report issued on Aug. 15, 2008, in related application PCT/IB07/03617.

Deepak et al., Plug-and-Play, Single-Chip Photoplethysmography, 34th Annual International Conference of the IEEE EMBS, San Diego, California USA, Aug. 28-Sep. 1, 2012, 4 pages.

* cited by examiner

Primary Examiner — Edward Raymond

(74) Attorney, Agent, or Firm — Martine Penilla Group, LLP

(57)

ABSTRACT

A method includes determining a location of a first monitoring device used while performing an activity. The first monitoring device is worn by a first user. The method includes determining a location of a second monitoring device used while performing an activity. The second monitoring device is worn by a second user. The method further includes determining whether the locations of the first and second monitoring devices are within a range and whether the activities are similar. The method includes sending a prompt to the first

monitoring device upon determining that the activities are similar and the locations are within the range. The prompt includes a request for permission from a first user account to allow a second user account to access information from the

first user account regarding the activity performed using the first monitoring device.

27 Claims, 39 Drawing Sheets




FIG. 1A




FIG. 1B




FIG. 1C




FIG. 1D




FIG. 1E




FIG. 2A




FIG. 2B




FIG. 3A




FIG. 3B




FIG. 4A




FIG. 4B




FIG. 4C




FIG. 4D




FIG. 5




FIG. 6A




FIG. 6B




FIG. 6C




FIG. 6D




FIG. 6E





FIG. 6F






FIG. 7B




FIG. 7C





FIG. 7D







FIG. 7F






FIG. 7H




FIG. 71




FIG. 7J




FIG. 7K




FIG. 7L




FIG. 7M




FIG. 7N




FIG. 70




FIG. 7P




FIG. 7Q




FIG. 7R




FIG. 7S




FIG. 7U
USERS MOUSE
OVER FOR DETAILS

FIG. 7T




FIG. 7V




FIG. 8




FIG. 9A




FIG. 9B




FIG. 10




FIG. 11




FIG. 12

1

**METHODS AND SYSTEMS FOR
PROCESSING SOCIAL INTERACTIVE DATA
AND SHARING OF TRACKED ACTIVITY
ASSOCIATED WITH LOCATIONS**

CLAIM OF PRIORITY

This application is a continuation of U.S. patent application Ser. No. 13/959,706, filed on Aug. 5, 2013, titled "Methods and Systems for Processing Social Interactive Data and Sharing of Tracked Activity Associated with Locations", which is incorporated by reference herein in its entirety.

The application Ser. No. 13/959,706 claims the benefit of and priority, under 35 U.S.C. 119(e), to a Provisional Patent Application No. 61/680,230, filed on Aug. 6, 2012, and entitled "GPS ENABLED ACTIVITY AND SLEEP TRACKER," which is incorporated by reference herein in its entirety.

The application Ser. No. 13/959,706 is a continuation-in-part of U.S. patent application Ser. No. 13/693,334, published as U.S. Patent Application Publication No. 20130096843, filed on Dec. 4, 2012, titled "Portable Monitoring Devices and Methods for Operating Same", which is a divisional of U.S. patent application Ser. No. 13/667,229, filed on Nov. 2, 2012, titled "Portable Monitoring Devices and Methods for Operating Same", which is a divisional of U.S. patent application Ser. No. 13/469,027, now U.S. Pat. No. 8,311,769, filed on May 10, 2012, titled "Portable Monitoring Devices and Methods for Operating Same", which is a divisional of U.S. patent application Ser. No. 13/246,843, now U.S. Pat. No. 8,180,591, filed on Sep. 27, 2011, which is a divisional of U.S. patent application Ser. No. 13/156,304, filed on Jun. 8, 2011, titled "Portable Monitoring Devices and Methods for Operating Same", which claims the benefit of and priority to, under 35 U.S.C. 119(e), to U.S. Provisional Patent Application No. 61/388,595, filed on Sep. 30, 2010, and titled "Portable Monitoring Devices and Methods for Operating Same" and to U.S. Provisional Patent Application No. 61/390,811, filed on Oct. 7, 2010, and titled "Portable Monitoring Devices and Methods for Operating Same", all of which are hereby incorporated by reference in their entirety.

The application Ser. No. 13/959,706 is a continuation-in-part of U.S. patent application Ser. No. 13/759,485, published as U.S. Patent Application Publication No. 20130151196, filed on Feb. 5, 2013, titled "Portable Monitoring Devices and Methods for Operating Same", which is a divisional of U.S. patent application Ser. No. 13/667,229, filed on Nov. 2, 2012, titled "Portable Monitoring Devices and Methods for Operating Same", which is a divisional of U.S. patent application Ser. No. 13/469,027, now U.S. Pat. No. 8,311,769, filed on May 10, 2012, titled "Portable Monitoring Devices and Methods for Operating Same", which is a divisional of U.S. patent application Ser. No. 13/246,843, now U.S. Pat. No. 8,180,591, filed on Sep. 27, 2011, which is a divisional of U.S. patent application Ser. No. 13/156,304, filed on Jun. 8, 2011, titled "Portable Monitoring Devices and Methods for Operating Same", which claims the benefit of and priority to, under 35 U.S.C. 119(e), to U.S. Provisional Patent Application No. 61/388,595, filed on Sep. 30, 2010, and titled "Portable Monitoring Devices and Methods for Operating Same" and to U.S. Provisional Patent Application No. 61/390,811, filed on Oct. 7, 2010, and titled "Portable Monitoring Devices and Methods for Operating Same", all of which are hereby incorporated by reference in their entirety.

2

FIELD

The present disclosure relates to systems and methods for processing social interactive data and sharing of tracked activity associated with locations.

BACKGROUND

In recent years, the need for health and fitness has grown tremendously. The growth has occurred due to a better understanding of the benefits of good fitness to overall health and wellness. Unfortunately, although today's modern culture has brought about many new technologies, such as the Internet, connected devices and computers, people have become less active. Additionally, many office jobs require people to sit in front of computer screens for long periods of time, which further reduces a person's activity levels. Furthermore, much of today's entertainment options involve viewing multimedia content, computer social networking, and other types of computer involved interfacing. Although such computer activity can be very productive as well as entertaining, such activity tends to reduce a person's overall physical activity.

To provide users concerned with health and fitness a way of measuring or accounting for their activity or lack thereof, fitness tracker are often used. Fitness trackers are used to measure activity, such as walking, motion, running, sleeping, being inactive, bicycling, exercising on an elliptical trainer, and the like. Usually, the data collected by such fitness trackers can be transferred and viewed on a computing device. However, such data is often provided as a basic accumulation of activity data.

It is in this context that embodiments described herein arise.

SUMMARY

Embodiments described in the present disclosure provide systems, apparatus, computer readable media, and methods for segmenting a period of time into identification of locations of a user performing activities. This segmentation provides a way of identifying particular activities to particular locations. Using the segmentations, the systems and methods can identify one or more events that may have occurred during the period of time of activity. In one embodiment, the events can be displayed on a screen of a device, and a user is able to interactively view data concerning the events with contextual information, e.g., where certain events occurred.

In one embodiment, as described below, the events are automatically associated with locations, and the locations can be associated with contextual information concerning the locations. For instance, if a tracking device detects certain activity at a particular location (e.g., a map location), the mapping data or related databases can be queried to determine that the map location corresponds to a golf course. The system can then generate information that is graphically presented to the user, concerning the particular tracked activity as corresponding to golfing. In some embodiments, the locations can be identified over time, e.g., by received user feedback (e.g., this is my home, this is a coffee shop, this is my work).

In some embodiments, the locations can be inferred or learned based on the activities and times of day, and/or repeat activities over a period of time (e.g., based on an identifiable pattern). For example, if the user/tracker is typically experiencing low activity from 9:00 am and 11:55 am, Monday-Friday, it can be inferred using a rules database and learning logic that the user is at work or is working. In another embodi-

ment, the user can be asked, "are you at work?" via a computing device or a tracking device, and based on the user's response, a database can associate particular locations (e.g., geo-location) to a particular actual location (e.g., work), and collect the activity data for presentation along with the most appropriate location.

In some embodiments, an activity that is performed by a user is inferred based on geo-locations of a monitoring device or a computing device used by the user. For example, a processor of the monitoring device, of the computing device, of a server, or of a virtual machine determines based on the geo-locations that a user is at a location, e.g., a gym, home, work, etc. The processor retrieves from an activity-location database one or more activities that may be performed by the user at the location. For example, the activity-location database indicates that the user may be performing one or more activities, e.g., using a treadmill, using an elliptical trainer, lifting weights to build resistance, swimming laps, etc., while at a gym. As another example, the activity-location database indicates that the user may be performing one or more activities, e.g., walking, climbing stairs, descending stairs, sleeping, etc., while at home. The processor retrieves one or more of the activities from the activity-location database that correspond to the location and determines that the user is performing one or more of the activities.

Broadly speaking, the systems and methods facilitate determination of an activity level of an activity performed by a user at a location. For example, the systems and methods can determine that the user is sedentary for a particular period of time when the user is at work. As another example, the systems and methods can determine that the user is active when the user is at home. The activity or lack of activity is therefore contextually associated to a particular location. The systems and methods determine activity levels of one or more activities performed by the user during a period of time. The user can view the activity levels of an activity performed at a location and decide whether to perform a different activity at the location, to perform an activity at another location, or to continue performing the activity when at the location. By providing the user location context to activities, the user is able to better view his or her actual activity performance and better health decisions can be made regarding and/or adjustments can be made in lifestyle. For instance, a user may find that walking to the train station can significantly improve his/her health, over taking a bus to the train. These simple decisions in activity can act to significantly increase a person's activity, but providing context as to what and where activity is taking place can provide better understanding as to how simple changes can have large impacts in overall fitness.

In some embodiments, a method includes determining a location of a first monitoring device used while performing an activity. The first monitoring device is configured to be worn by a first user. The method includes determining a location of a second monitoring device used while performing an activity. The second monitoring device is configured to be worn by a second user. The method further includes determining whether the location of the first monitoring device is within a threshold distance of the location of the second monitoring device and determining whether the activity performed using the first monitoring device is similar to the activity performed using the second monitoring device. The method includes sending a notification to the first monitoring device upon determining that the activity performed using the first monitoring device is similar to the activity performed using the second monitoring device and that the location of the first monitoring device is within the threshold distance of the location of the second monitoring device. The notification

includes a request for permission from a first user account of the first user to allow a second user account of the second user to access information from the first user account regarding the activity performed using the first monitoring device.

In some embodiments, a method includes determining a location of a first monitoring device used while performing an activity. The first monitoring device is configured to be worn by a first user. The method includes determining a location of a second monitoring device used while performing an activity. The second monitoring device is configured to be worn by a second user. The method includes determining whether the location of the first monitoring device is within a defined distance range of the location of the second monitoring device. The method includes determining an activity level of the activity performed using the first monitoring device when the location of the first monitoring device is within the defined distance range of the location of the second monitoring device. The method includes determining whether the activity level is below a threshold and sending a recommendation to the first monitoring device upon determining that the activity level is below the threshold.

In various embodiments, a method includes determining a location of a first monitoring device used while performing an activity. The first monitoring device is configured to be worn by a first user. The method includes determining a location of a second monitoring device used while performing an activity. The second monitoring device is configured to be worn by a second user. The method further includes determining whether the location of the first monitoring device is within a threshold distance of the location of the second monitoring device. The method includes sending a prompt to the first monitoring device upon determining that the locations of the first monitoring device is within a defined distance range of the location of the second monitoring device. The prompt includes a request for permission from a first user account of the first user to allow a second user account of the second user to access information from the first user account regarding the activity performed using the first monitoring device.

Other aspects will become apparent from the following detailed description, taken in conjunction with the accompanying drawings, illustrating by way of example the principles of embodiments described in the present disclosure.

BRIEF DESCRIPTION OF THE DRAWINGS

Various embodiments described in the present disclosure may best be understood by reference to the following description taken in conjunction with the accompanying drawings in which:

FIG. 1A illustrates a variety of situations in which a system for segmenting a period of time into identification of locations of a user performing activities is used, in accordance with one embodiment described in the present disclosure.

FIG. 1B is a diagram of a method for determining an amount of a type of movement of a monitoring device over a period of time, in accordance with one embodiment described in the present disclosure.

FIG. 1C is a diagram of a method for determining an amount of another type movement of a monitoring device over a period of time, in accordance with one embodiment described in the present disclosure.

FIG. 1D is a diagram of a method for determining an amount of yet another type movement of a monitoring device over a period of time, in accordance with one embodiment described in the present disclosure.

FIG. 1E is a diagram of a method for determining an amount of another type movement of a monitoring device

5

over a period of time, in accordance with one embodiment described in the present disclosure.

FIG. 2A is a diagram of a system for transferring data between a monitoring device and a server via a computing device and a network, in accordance with one embodiment

FIG. 2B is a diagram of an embodiment of a system for transferring data between a monitoring device and the server via a mobile computing device and the network, in accordance with one embodiment described in the present disclosure.

FIG. 3A is a diagram of a system to illustrate components of a monitoring device, in accordance with one embodiment described in the present disclosure.

FIG. 3B is a diagram of a system to illustrate components of another monitoring device, in accordance with one embodiment described in the present disclosure.

FIG. 4A is an isometric view of a monitoring device that is worn around a hand of a user or around a leg of the user, in accordance with one embodiment described in the present disclosure.

FIG. 4B is an isometric view of another monitoring device that fits to an article of clothing or a belt worn by a user, in accordance with one embodiment described in the present disclosure.

FIG. 4C is a view of yet another monitoring device that fits to an article of clothing or a belt worn by a user, in accordance with one embodiment described in the present disclosure.

FIG. 4D is an isometric view of another monitoring device that fits to an arm of a user, in accordance with one embodiment described in the present disclosure.

FIG. 5 is a block diagram of a computing device, in accordance with one embodiment described in the present disclosure.

FIG. 6A is a flowchart of a method for segmenting a period of time into identification of locations of a user performing activities, in accordance with one embodiment described in the present disclosure.

FIG. 6B is a flowchart of another method for segmenting a period of time into identification of locations of a user performing activities, in accordance with one embodiment described in the present disclosure.

FIG. 6C is a flowchart of yet another method for segmenting a period of time into identification of locations of a user performing activities, in accordance with one embodiment described in the present disclosure.

FIG. 6D is a flowchart of a method for segmenting a period of time into identification of locations of a user performing activities, in accordance with one embodiment described in the present disclosure.

FIG. 6E is a flowchart of another method for segmenting a period of time into identification of locations of a user performing activities, in accordance with one embodiment described in the present disclosure.

FIG. 6F is a flowchart of a method for combining a map with event data, in accordance with one embodiment described in the present disclosure.

FIG. 7A is a graphical user interface (GUI) that displays one or more events and that is generated by executing the method of FIG. 6A, 6B, 6C, 6E, or 6F, in accordance with one embodiment described in the present disclosure.

FIG. 7B is a diagram of another GUI that displays one or more events and that is generated by executing the method of FIG. 6A, 6B, 6C, 6E, or 6F in accordance with one embodiment described in the present disclosure.

FIG. 7C is a diagram illustrating a method for establishing boundaries between two locations arrived at by a user over

6

one or more periods of time, in accordance with one embodiment described in the present disclosure.

FIG. 7D is a diagram of a GUI to illustrate a method of allowing a user to choose a location in case of common geo-locations between multiple locations, in accordance with one embodiment described in the present disclosure.

FIG. 7E is a diagram of a web page that includes a GUI that displays one or more events and that is generated by executing the method of FIG. 6A, 6B, 6C, 6E, or 6F, in accordance with one embodiment described in the present disclosure.

FIG. 7F is a zoom-in of a portion of a GUI to illustrate activity levels of one or activities performed by a user over a period of time and to illustrate activity levels associated with one or more locations at which the activities are performed, in accordance with one embodiment described in the present disclosure.

FIG. 7G is a diagram of a daily journal GUI that includes one or more GUIs that include event data for periods of time, in accordance with one embodiment described in the present disclosure.

FIG. 7H is a diagram of another daily journal GUI that includes one or more GUIs that include event data for periods of time, in accordance with one embodiment described in the present disclosure.

FIG. 7I is a GUI that provides an overview of one or more levels of one or more activities performed by a user at one or more locations over a period of time, in accordance with one embodiment described in the present disclosure.

FIG. 7J is a diagram of a GUI that includes a detailed view of activities displayed in the GUI of FIG. 7I, in accordance with one embodiment described in the present disclosure.

FIG. 7K is a diagram of a GUI that includes a more detailed view of activities displayed in the GUI of FIG. 7J, in accordance with one embodiment described in the present disclosure.

FIG. 7L is a diagram illustrating a method of combining activity levels over a period of time, in accordance with one embodiment described in the present disclosure.

FIG. 7M is a diagram of a GUI that describes an aggregate level of one or more activities performed by a user over a period of time, in accordance with one embodiment described in the present disclosure.

FIG. 7N is a diagram of a pie-chart of locations at which a user performs one or more activities and of percentages of activity levels at one or more locations over a period of time, in accordance with one embodiment described in the present disclosure.

FIG. 7O is a diagram of a GUI that includes an overlay of a map on one or more locations that a user visits during a period of time to perform one or more activities performed by the user during a period of time, in accordance with one embodiment described in the present disclosure.

FIG. 7P is a diagram of a web page that illustrates that a map is overlaid on an event region to indicate a geo-location of a user at a time within a time period in which the user performs one or more activities, in accordance with one embodiment described in the present disclosure.

FIG. 7Q is a diagram of a GUI that includes a map below an event region, in accordance with one embodiment described in the present disclosure.

FIG. 7R is a diagram of a web page that is used to illustrate an overlay of event data on a map, in accordance with one embodiment described in the present disclosure.

FIG. 7S is a diagram of a web page that is used to illustrate a zoom-in of a portion of the map of FIG. 7R and of activity

data of an activity performed by a user while the user is at the portion, in accordance with one embodiment described in the present disclosure.

FIG. 7T is a diagram of an embodiment of a web page that includes a GUI that further includes an overlay of a map on a user's path, in accordance with one embodiment described in the present disclosure.

FIG. 7U is a diagram of an embodiment of the web page of FIG. 7T to illustrate a zoom-in of a portion of the map of FIG. 7T and to illustrate activity data associated with the zoom-in, in accordance with one embodiment described in the present disclosure.

FIG. 7V is a diagram of an embodiment of a GUI that includes further details regarding the user's path of FIG. 7T, in accordance with one embodiment described in the present disclosure.

FIG. 8 is a diagram of one or more location identifiers and one or more activity identifiers, in accordance with one embodiment described in the present disclosure.

FIG. 9A is a diagram of a method for sharing information between various user accounts based on locations of users and activities performed by the users, in accordance with one embodiment described in the present disclosure.

FIG. 9B is a diagram of a method for sharing information between various user accounts based on locations of users, in accordance with one embodiment described in the present disclosure.

FIG. 10 is a flowchart of a method for recommending a change in activity performed by a user and/or a change in a location at which the activity is performed by the user based on an activity level of the user, in accordance with one embodiment described in the present disclosure.

FIG. 11 is a diagram of an embodiment of a system in which users are performing activities at a location and information is shared between the users, in accordance with one embodiment described in the present disclosure.

FIG. 12 is a diagram of a system for determining an activity level of a user based on activity and/or a location of the user, in accordance with one embodiment described in the present disclosure.

DETAILED DESCRIPTION

Embodiments described in the present disclosure provide systems, apparatus, computer readable media, and methods for analyzing tracked activity data and segmenting/associating the activity data to contextually identifiable locations where a user, wearing an activity tracker performed such activities. This segmentation provides a way of identifying events that associate the identified activities to particular locations. In one embodiment, the data is collected from an activity tracker and then transferred to a computing device. In some embodiments, the computing device can include a portable device, such as a smart phone, an internet connected watch, a tablet, a laptop, a desktop, etc. The computing device can then transfer the collected activity data to a server that is connected to the internet for processing.

In one embodiment, the term location refers to a geographic position. The geographic position can be identified on a map, identified on a coordinate identifier using global positioning data (e.g., GPS), identified using radio signal tower locator data (e.g., cell towers), identified using wireless internet router signal data (e.g., Wi-Fi signals), identified using router signal data for multi-floor identification (e.g., floor-to-floor locator data), or combinations thereof. In some embodiments, changes in location data include determining a difference between location identified data at various times (e.g.,

every minute, every few minutes, every half hour, every hour, at particular hour intervals or days). In some embodiments, the time at which location data is obtained can vary depending on sensed activity. For example, if less activity or motion is detected, fewer location data points need be taken.

The server can include one or more servers, which define a cloud processing system. The cloud processing system includes logic, code, programs and/or software for processing the activity data to produce the identifiable events. The cloud processing system can provide a system for creating user accounts for users and their activity trackers. The user accounts enable users to view graphical users interfaces (GUIs) that render and display the events identified using the tracked activity data and the location data (e.g., geo-location data). Processing logic on the servers associated with the cloud processing system can process the tracked data, can access other Internet services (e.g., mapping services, social networking services, location context services, etc., to enable formulation or identification of a location for particular activities, which define an event). Broadly speaking, an event is defined to include a location and an activity.

In one embodiment, the events can be displayed on a screen of a device, and a user is able to interactively view data concerning the events with contextual information, e.g., where certain events occurred.

In some embodiments, locations can be automatically identified by accessing mapping services and other online databases that identify locations. The online databases can include mapping programs, data from social networks, tagged data, crowd-sourced data, etc.

In some embodiments, the locations can be inferred or learned based on the activities and times of day, and/or repeat activities over a period of time (e.g., based on an identifiable pattern). Databases of rules are constructed and such rules are refined over time. The rules are used to enable the system to infer locations and provide appropriate contextual identification to the locations. In some embodiments, the rules can shape themselves using learning systems, and can be tailored for specific users. In still other embodiments, learned patterns and behaviors of other users can be used to collaboratively identify rules, shape rules or determine locations or identify locations. For instance, if multiple users tag a location as a coffee bar, this information can be used to associate "coffee bar" to some range of geo-location. If over time, the location starts to get tagged as a breakfast bar, the rules can be adjusted to now associate that geo-location as "breakfast bar." As businesses or location contexts change over time, so can the rules.

In various embodiments, the shape rules are used to associate one or more geo-locations with a location. For example, a shape, e.g., a circle, a polygon, an oval, a square, etc., is used to identify a location on a graphical user interface. The graphical user interface may include event data, a route, a map, or a combination thereof. A user changes a size via a user interface of a monitoring device or via an input device of a computing device of a shape to change a number of geo-locations associated with the location. For example, a user increases a size of a circle to include more geo-locations within a location that is identified by the circle. As another example, a user decreases a size of a polygon to exclude a number of geo-locations from within a location that is identified by the polygon. As another example, a center of a shape is changed to associate a different set of geo-locations with a location than that already associated with the location. For example, a user drags via a user interface of a monitoring device or via an input device of a computing device a point associated with, e.g., a center of, a vertex of, etc., a shape to a

different spot on a graphical user interface. When the point is dragged, the shape is also dragged to the difference spot and is associated with a difference set of geo-locations than that before the movement of the center. The graphical user interface may include event data, a route, a map, or a combination thereof.

In another embodiment, the user may be allowed to post details of particular locations. The user can identify locations with particular custom identifiers, e.g., "mom's house" or can select from predefined identifiers. In still other embodiments, the user can be asked to identify a location. In still another embodiment, the user can be asked via custom queries, such as: "Are you at work?"; "Is this your home?"; "Are you driving?"; "Do you need medical assistance? if so, say or type help" etc. Or, the queries can be presented to the user at a later time, such as when the user is viewing his or her past activity on a GUI. In some embodiments, the queries can be provided via a cloud program, when accessing a computer with cloud access, via push notifications, via voice requests, etc. Based on this returned feedback, the servers and databases of the cloud service can learn or associate location identification to particular locations, which are later identified by detecting the geo-location of the tracker.

In some embodiments, a user tags a location as being associated with a person known to the user. For example, a user logs into his/her user account and tags a location as being Mom's house, Eric's house, Jessica's house, Buddy's gym, etc. Examples of a person known to the user include a friend of the user, a work mate of the user, a special interest of the user, a relative of the user, an acquaintance of the user, or a family member of the user. The user tags via an input device of a computing device or via a user interface of a monitoring device. A processor, e.g., a processor of the monitoring device, a processor of the computing device, a processor of a server, a processor of a virtual machine, or a combination thereof, etc., determines that the tag indicates that the user knows the person. For example, the term "Mom" indicates that the person is a mom of the user. As another example, "Eric" indicates that the person is a friend, a relative, or an acquaintance of the user. The processor determines whether the person tagged has a user account. The user account is used to display event data that includes activities performed by the person and/or locations visited by the person while performing the activities, etc. The processor suggests to the user to add the person to a social group, e.g. a friend group, a work mate group, a special interest group, a relative group, an acquaintance group, a family member group, etc. When the user adds the person within the social group, the user account of the user indicates the addition of the person within the social group.

In general, the systems and methods facilitate determination of an activity level of an activity performed by a user at a location. For example, the systems and methods can determine that the user is sedentary for a particular period of time when the user is at work. As another example, the systems and methods can determine that the user is active when the user is at home. The activity or lack of activity is therefore contextually associated to a particular location. The location can be an address, map, or a combination of maps, addresses, activities, and/or predefined location identifiers or activities that occur at particular locations (e.g., golf occurs at a golf course, swimming occurs at a swimming pool, etc.). By providing the user location context to activities, the user is able to better view his or her actual activity performance and better health decisions can be made regarding and/or adjustments can be made in lifestyle.

In some instances, well known process operations have not been described in detail in order not to unnecessarily obscure various embodiments described in the present disclosure.

FIG. 1A illustrates a variety of situations/activities in which a system and/or method uses location data to segment a period of time into identifiable events, each event defining an activity for a period of time. In one embodiment, location data is obtained for a time when the activity is tracked, such as location data and/or characteristics of the activity used to identify an event. As noted in detail below, a period of time having associated tracking data can be segmented into one or more events.

In the example of FIG. 1A, a user 112A wears a monitoring device 114A on his arm while playing a sport, e.g., tennis. Other examples of a sport include badminton, golf, running, bicycling, vehicle racing, racquetball, squash, soccer, etc. It should be understood that the example of sports is provided, as such sports have particular identifiable activity patterns. However, any activity, whether sports related or not, can be tracked and associated to an event. For instance, another user 112B wears a monitoring device 114B on her arm while walking. Yet another user 112C wears a monitoring device 114C on his/her arm while doing yoga. Another user 112D wears a monitoring device 114D on his/her arm during sleep. Another user 112E wears a monitoring device 114E on his/her arm while playing golf. Yet another user 112F wears a monitoring device 114F on his/her clothing part while riding a bicycle. Another user 112G wears a monitoring device 114G on his/her foot while walking a user 112H, e.g., a dog. In some embodiments, the user 112G walks other animals, e.g., a tiger, a cat, etc. The user 112H also wears a monitoring device 114H on its arm. Another user 112I wears a monitoring device 114I on his arm during running.

In some embodiments, a user performs one or more of other activities, e.g., swimming, resistance training, rock climbing, skiing, snowboarding, hiking, skating, rollerblading, etc. It is noted that the activities described herein are not limiting and that other activities may be used.

It should be noted that in some embodiments, a user can wear, hold, append, strap-on, move, transport or carry a monitoring device while performing any type of activity, e.g., playing ping-pong, climbing stairs, descending stairs, hiking, sitting, resting, working, etc. Additionally, one user can be associated with more than one monitoring device, and such data can be processed and associated to the user's activity. In some embodiments, the data is selected from various devices of the user based on a priority algorithm. In some embodiments, data from more than one device can be blended or alternated together to define a more complete map of the activities.

Each monitoring device 114A, 114B, 114C, 114D, 114E, 114F, 114G, 114H, and 114I communicates with a network 176. In some embodiments, each monitoring device 114A, 114B, 114C, 114D, 114E, 114F, 114G, 114H, and 114I communicates with the network 176 via a computing device, e.g., a desktop computer, a laptop computer, a smart phone, a tablet, a smart watch, a smart television, etc.

Examples of the network 176 include the Internet and an Intranet. The network 176 may be a wide area network, a local area network, or a combination thereof. The network 176 may be coupled to one or more servers, one or more virtual machines, or a combination thereof.

A server, a virtual machine, a controller of a monitoring device, or a controller of a computing device is sometimes referred to herein as a computing resource. Examples of a controller include a processor and a memory device.

As used herein, a processor includes an application specific integrated circuit (ASIC), a programmable logic device (PLD), a processor, a central processing unit (CPU), or a combination thereof, etc. Examples of a memory device include a random access memory (RAM) and a read-only memory (ROM). A memory device may be a Flash memory, a redundant array of disks (RAID), a hard disk, or a combination thereof.

A computing resource performs data capture, which is reception of activity data from a monitoring device. Examples of activity data include, without limitation, calories burned by a user, blood pressure of the user, heart rate of the user, weight gained by a user, weight lost by a user, stairs ascended, e.g., climbed, etc., by a user, stairs descended by a user, steps taken by a user during walking or running, floors descended by a user, floors climbed by a user, a number of rotations of a bicycle pedal rotated by a user, sedentary activity data, a distance covered by a user during walking, running, or driving a vehicle, a number of golf swings taken by a user, a number of forehands of a sport played by a user, a number of backhands of a sport played by a user, or a combination thereof. In some embodiments, sedentary activity data is referred to herein as inactive activity data or as passive activity data. In some embodiments, when a user is not sedentary and is not sleeping, the user is active.

The data capture also includes capturing a geo-location of a monitoring device. For example, geographical location data 120A of the monitoring device 114A is determined by the monitoring device 114A and obtained by a computing resource. A geo-location is determined by a device locator, which is further described below. Examples of a geo-location include latitude, radius, longitude, altitude, landmark, city, country, state, county, village, eatery, commercial place, commercial building, province, public place, or a combination thereof. In some embodiments, the geo-location data is obtained not by the monitoring device, but by a companion device (e.g., such as a smart phone or other portable device with global positioning system (GPS) data collection capabilities).

In various embodiments, a device locator obtains a speed of a monitoring device or of a computing device. For example, a device locator of a computing device determines a speed of the computing device and a device locator of a monitoring device determines a speed of the monitoring device. In various embodiments, a device locator of a device, e.g., a monitoring device, a computing device, etc., obtains an orientation of the device. In various embodiments, an orientation of a device includes a degree of rotation of the device with respect to an x axis, a y axis, and a z axis.

Similarly, geographical location data 120B of the monitoring device 114B is determined by the monitoring device 114B and obtained by a computing resource, geographical location data 120C of the monitoring device 114C is determined by the monitoring device 114C and obtained by a computing resource, geographical location data 120D of the monitoring device 114D is determined by the monitoring device 114D and obtained by a computing resource, geographical location data 120E of the monitoring device 114E is determined by the monitoring device 114E and obtained by a computing resource, geographical location data 120F of the monitoring device 114F is determined by the monitoring device 114F and obtained by a computing resource, geographical location data 120G of the monitoring device 114G is determined by the monitoring device 114G and obtained by a computing resource, geographical location data 120H of the monitoring device 114H is determined by the monitoring device 114H and obtained by a computing resource, and geographical

location data 120I of the monitoring device 114I is determined by the monitoring device 114I and obtained by a computing resource.

A geo-location of a monitoring device is used in conjunction with activity data by a computing resource to perform data analysis. The data analysis is performed by a processor. For example, a level, e.g., an amount, etc., of an activity performed by a user at a geo-location is determined. Examples of activity level include a number of calories burned by a user, an amount of weight gained by a user, a heart rate of a user, an amount of blood pressure of a user, an amount of weight lost by a user, a number of stairs ascended by a user, a number of stairs descended by a user, a number of steps taken by a user during walking or running, a number of floors descended by a user, a number of floors climbed by a user, a number of rotations of a bicycle pedal rotated by a user, a distance covered by a vehicle operated by a user, a number of golf swings taken by a user, a number of forehands of a sport played by a user, a number of backhands of a sport played by a user, or a combination thereof, etc. The geo-location and the activity level are combined and displayed to a user to monitor activity and/or health of the user over a period of time. As another example, a geo-location is combined with an activity level to determine whether a user is still at a location, e.g., a house, a work place, an office, a gym, a sandwich shop, a coffee shop, etc. after performing the activity or has left the location after performing the activity. In this example, when it is determined that the user is at the location and the activity level has crossed from a first side of a threshold to a second side of the threshold, it is determined that the user has left the location. Moreover, in this example, when it is determined that the user is at the location and that the activity level has not crossed from the first side to the second side, it is determined that the user is still at the location. In some embodiments, the first side of the threshold is below the threshold and the second side of the threshold is above the threshold. In various embodiments, the first side of the threshold is above the threshold and the second side is below the threshold.

In some embodiments, a user indicates to a monitoring device or a computing device that the user has exited or entered a location. For example, the user logs into a user account and indicates via a user interface of a monitoring device or an input device of a computing device that the user is exiting or entering a location. A processor, e.g., a processor of a server, a processor of a virtual machine, a processor of the computing device, or a processor of the monitoring device, or a combination thereof, etc., receives the indication from the user. The processor determines a time at which the user indicates that the user is entering or exiting the location and indicates the time on a graphical user interface that includes event data. In various embodiments, upon determining that the user has entered a location, the processor accesses the activity-location database to determine one or more activities that may be performed by the user at the location and generates one or more activity identifiers of the activities.

In some embodiments, a computing resource performs data synchronization, which includes synchronization of activity data received from various users and synchronization of geo-locations of the users. For example, activity data from one user is displayed to another user when both the users are within one location. As another example, activity data of one user is displayed to another user when both users are performing the same activity, e.g., walking, running, etc. As yet another example, activity data of one user is displayed to another user when both users are performing the same activity at the same location. As another example, activity data is

13

displayed to two or more users who perform similar activities in disparate locations (e.g., a virtually shared walk).

In various embodiments, a computing resource recommends data to a user based on activity data received from a monitoring device used by the user and based on a location of the user. For example, when it is determined that a user is at a golf course and has not taken a number of golf swings, the recommendation data indicates to the user that the user may take an additional amount of golf swings to achieve a goal. As another example, when it is determined that a user is not going to (or is unlikely to based on knowledge of the user's historical activity patterns) reach his/her activity goal, e.g., walking a number of steps over a time period, running a distance over a time period, climbing or descending a number of stairs over a time period, bicycling for an amount of distance over a time period, bicycling for a number of pedal rotations of a bicycle over a time period, lifting a weight for a number of times over a time period, hitting a forehand for a number of times over a time period, hitting a backhand for a number of times over a time period, etc., and it is determined that the user is at a location, the computing resource generates the recommendation data to indicate to the user to perform an activity or to extend performing the activity at the location or at another location that is within a distance of the location. These recommendations can be provided as electronic notifications to the user's device, the user's smart phone, to the tracking device, or some other user interface. The recommendations can also be provided as voice notifications, in case the user is occupied in a task that limits viewing a screen, such as driving. The determination that the user is driving can be made using data regarding the speed/motion of the device, location data (e.g., in a car), etc.

In some embodiments, a user may stand on a monitoring device that determines a physiological parameter of the user. For example, a user stands on a scale that measures a weight, a body fat percentage, a biomass index, or a combination thereof, of the user.

FIG. 1B is a diagram of an embodiment of a method for determining an amount of movement **116A** of the monitoring device **114G**, e.g., a number of stairs ascended by the monitoring device **114G**, etc., over a period of time **t1**. The amount of movement **116A** occurs when the user **112A** is performing an activity of climbing stairs over the time period **t1**. A method of determining an amount of movement is performed by a position sensor of a monitoring device. Additionally, the method can simultaneously identify a location for the activity. The monitoring device **114G** may be worn on the leg or foot (as depicted in FIG. 1B), or elsewhere on the body such as the wrist, forearm, upper arm, head, chest, or waist, or as an article of clothing such as a shirt, hat, pants, blouse, glasses, and the like.

A position sensor determines an amount of linear or angular movement of an arm of a user or of another body part of a user. For example, a position sensor determines that the user **112A** wearing the monitoring device **114G** on his leg has climbed a number of stairs, e.g., four, twenty, forty, etc., between positions A and B over the time period **t1**.

In some embodiments, instead of a number of stairs ascended, a position sensor determines a number of stairs descended by the monitoring device **114G**.

FIG. 1C is a diagram of an embodiment of a method for determining an amount of movement **116B**, e.g., an amount of distance traveled, a number of steps traveled, etc., of the monitoring device **114E** over a period of time **t2**. For example, a position sensor determines that the user **112A** wearing the monitoring device **114E** on his hand has walked or ran a number of steps, e.g., four, fifty, hundred, etc.,

14

between positions C and D over the time period **t2**. The amount of movement **116B** occurs when the user **112A** is performing an activity of walking or running over the time period **t2**.

FIG. 1D is a diagram of an embodiment of a method for determining an amount of movement **116C**, e.g., an amount angular movement, etc., of the monitoring device **114E** over a period of time **t3**. For example, a position sensor determines that a hand of the user **112A** wearing the monitoring device **114E** on his/her hand is displaced by an angle over the time period **t3**. The amount of movement **116C** occurs when the user **112A** is performing a sports activity, e.g., golfing, playing tennis, playing ping-pong, resistance training, etc., over the time period **t3**.

In some embodiments, a position sensor measures an angular displacement of a leg of the user **112A** wearing the monitoring device **114G** on his leg.

In various embodiments, a position sensor infers an activity performed by a user over a period of time based on one or more positions of a monitoring device that has the position sensor and that is worn by the user. For example, upon determining that a difference between a first y position and a second y position within a xyz co-ordinate system is greater than an amount and that x positions between the two y positions indicate a curved movement, a position sensor of a monitoring device determines that the user **112A** is playing golf. As another example, upon determining that the user **112A** covers less than a distance along an x-axis over a period of time, a position sensor of a monitoring device worn by the user **112A** determines that the user **112A** is walking and upon determining that the user **112A** covers more than the distance along the x-axis over the period of time, the position sensor determines that the user **112A** is running.

FIG. 1E is a diagram of an embodiment of a method for determining an amount of movement **116D**, e.g., an amount angular movement, etc., of the monitoring device **114E** over a period of time **t4**. For example, a position sensor determines that the user **112A** wearing the monitoring device **114E** on his/her hand is displaced by an angle over the time period **t4**. The amount of movement **116D** occurs when the user **112A** is performing an activity, e.g., a sports activity, an exercise activity, etc., over the time period **t4**.

Examples of a period of time include a portion of a day, or a day, or a portion of a month, or a month, or a portion of a year, or a year, or a portion of a number of years, or a number of years.

FIG. 2A is a diagram of an embodiment of a system **250** for transferring data, e.g., activity data, geo-location data, etc., between the monitoring device **114E** and a server **228** via a computing device **164A** and the network **176**. A wireless link **168** establishes a connection between the monitoring device **114E** and the computing device **164A**. For example, a Bluetooth device located within the monitoring device **114E** establishes a Bluetooth connection with a Bluetooth dongle interfacing with the computing device **164A** via a Universal Serial Bus (USB) interface. As another example, an ad hoc Wi-Fi transmission and reception is established between a Wi-Fi adapter of the monitoring device **114E** and a Wi-Fi adapter of the computing device **164A**. The wireless link **168** may be a Bluetooth or a Wi-Fi connection. A connection between the monitoring device **114E** and the computing device **164A** is used to transfer data between the monitoring device **114E** and the computing device **164A**.

In some embodiments, a geo-location and/or a position determined by the monitoring device **114E** is sent from the monitoring device **114E** via the computing device **164A** to a server or a virtual machine for processing, e.g., analysis,

determining event data, etc. The server or the virtual machine processes the geo-location and/or the position and sends processed data, e.g., event data, maps, routes, etc., to the computing device 164A for display on the computing device 164A.

In some embodiments, instead of the wireless link 168, a wired connection is used between the monitoring device 114E and the computing device 164A.

Moreover, a wired connection 252 is established between the computing device 164A and the server 228 via the network 176. A wired connection includes network components, e.g., one or more routers, one or more switches, one or more hubs, one or more repeaters, one or more servers, one or more cables, or a combination thereof, etc.

The server 228 includes a processor 190, a network interface controller (NIC) 254 and a memory device 256. The processor 190 is coupled with the memory device 256 and the NIC 254. An example of a NIC includes a network interface card. In some embodiments, a modem is used instead of a NIC.

The memory device 256 includes a user account 174 of the user 112A. The user 112A accesses the user account 174 when authentication information, e.g., username, password, fingerprints, footprints, thumbprints, or a combination thereof, etc., is authenticated by the processor 190 or another server of the network 176. The authentication information is provided by the user 112A via an input device, e.g., a mouse, a stylus, a keyboard, a keypad, a button, a touch screen, or a combination thereof, etc., of a monitoring device or of a computing device.

The user account 174 is accessed by the user 112A to review graphical user interface (GUI) data 186 on a display device of the computing device 164A or of the monitoring device 114E. The GUI data 186 includes geo-location data, a map, location in the form of location/activity identifiers, activity data in the form of activity levels, and/or physiological parameter of the user 112A. The activity data represents activities performed by the monitoring device 114E. The processor 190 associates, e.g., links, establishes a relationship between, etc., geo-location data, location, activity data, and/or physiological parameter of the user 112A with the user account 174 to allow access of the geo-location data, activity data, a map, location, and/or physiological parameter upon access of the user account 174. This relationship provides context to the activity, both in terms of what the activity was and where the activity occurred. This context can be used to define events that occur over a period of time, and the events can be presented on a GUI of a device, to provide useful information to a user regarding his or her activity over that period of time. Not only is the user provide with activity data, but the activity data is displayed in a graphical or data organized manner that identifies segmented activity data and associates it to the proper or inferred context.

Similarly, a user account 912 is accessed by the user 112B when authentication information received from the user 112B is authenticated. For example, the user 112B logs into the account 912 when authentication information received from the user 112B via a user interface of the computing device 166 or via an input device of a monitoring device is authenticated. The user account 912 is stored within the memory device 256 of the server 228. The user 112B accesses the user account 912 to review a GUI that includes event data showing activity levels of one or more activities performed by the user 112B.

In some embodiments, instead of using the monitoring device 114E to establish the wireless connection 168, any other monitoring device, e.g. the monitoring device 114A (FIG. 1A) or a monitoring scale is used.

It should be noted that in several embodiments, data is transferred from a monitoring device via a computing device and the network 176 to a virtual machine instead of the server 228.

In some embodiments, instead of the wired connection 252, a combination of a wireless connection and a wired connection is established.

In various embodiments, a user account, e.g., the user account 174, the user account 912, etc., is stored in a memory device of a computing device or on a memory device of a monitoring device. In these embodiments, processing of a geo-location and/or position is not done on the server 228 or a virtual machine to generate processed data, e.g., event data, location identifier, activity identifier, etc. but is done by a processor of the computing device and/or by a processor of a monitoring device to generate the processed data.

FIG. 2B is a diagram of an embodiment of a system 260 for transferring data, e.g., activity data, geo-location data, etc., between the monitoring device 114E and the server 228 via a mobile computing device 164B and the network 176. A wireless link 170 establishes a connection between the monitoring device 114E and the mobile computing device 164B. The wireless link 170 may be a Bluetooth connection, a Wi-Fi connection, a near field connection, a radio frequency connection, or an optical connection, etc. In some embodiments, instead of the wireless link 168, a wired connection is used between the monitoring device 114E and the mobile computing device 164B. A connection is used to transfer data between the monitoring device 114E and the mobile computing device 164B.

Moreover, the server 228 and the mobile computing device 164B are coupled with each other via a wireless connection 262, e.g., a Wi-Fi connection, etc., the network 176, and a connection 264. The connection 264 between the server 228 and the network 176 may be a wired or a wireless connection.

FIG. 3A is a diagram of an embodiment of a system 270 to illustrate components of a monitoring device 108A. The system 270 includes the monitoring device 108A, a computing device 166, the network 176, and the server 228.

The monitoring device 108A is an example of any of the monitoring devices 114A, 114B, 114C, 114D, 114E, 114F, 114G, 114H, and 114I (FIG. 1A). The monitoring device 108A includes an environmental sensor 272, a position sensor 220, a time measurement device 232, a user interface 274, a device locator 222, a display device 276, a processor 234, a wireless communication device 278, and a memory device 280, all of which are coupled with each other.

Examples of the device locator 222 include a GPS transceiver, a mobile transceiver, etc. As used herein, a device locator may be referred to as a device or circuit or logic that can generate geo-location data. The geo-location data provides the appropriate coordinate location of the device or tracker, such as a location on a map or location in a room or building. In some embodiments, a GPS device provides the geo-location data. In other embodiments, the geo-location data can be obtained from various devices (e.g., cell towers, Wi-Fi device signals, other radio signals, etc., which can provide data points usable to locate or triangulate a location.

Examples of the environmental sensor 272 include a barometric pressure sensor, a weather condition sensor, a light exposure sensor, a noise exposure sensor, a radiation exposure sensor, and a magnetic field sensor. Examples of a weather condition include a temperature, humidity, a pollen count, air quality, rain conditions, snow conditions, wind speed, a combination thereof, etc. Examples of light exposure include ambient light exposure, ultraviolet (UV) light exposure, or a combination thereof, etc. Examples of air quality

include particulate counts for varying sized particles, or level of carbon dioxide in air, or level of carbon monoxide in air, or level of methane in air, or level of other volatile organic compounds in air, or a combination thereof.

Examples of the position sensor **220** include an accelerometer, a gyroscope, a rotary encoder, a calorie measurement sensor, a heat measurement sensor, a moisture measurement sensor, a displacement sensor, an ultrasonic sensor, a pedometer, an altimeter, a linear position sensor, an angular position sensor, a multi-axis position sensor, or a combination thereof, etc. In some embodiments, the position sensor **220** measures a displacement, e.g., angular displacement, linear displacement, a combination thereof, etc., of the monitoring device **108A** over a period of time with reference to an xyz coordinate system to determine an amount of activity performed by the user **112A** during the period of time. In some embodiments, a position sensor includes a biological sensor, which is further described below. In various embodiments, a position sensor includes a motion sensor.

Examples of the time measurement device **232** include a watch, an oscillator, a clock, an atomic clock, etc. Examples of the user interface **274** include an input device for interacting with the user **112A**. For example, the user interface **274** receives a selection of the GUI data **186** (FIG. **2A**) from the user **112A**. It should be noted that when the user interface **274** includes a touch screen, the touch screen **274** is integrated within the display device **276**.

Examples of a display device includes a liquid crystal display (LCD) device, a light emitting diode (LED) display device, a plasma display device, etc. As an example, the display device **276** displays the GUI data **186**. In some embodiments, all GUIs described herein are displayed by rendering the GUI data **186**.

Examples of the memory device **280** are provided above. Examples of the wireless communication device **278** include a Wi-Fi adapter, a Bluetooth device, etc.

In some embodiments, the processor **234** receives one or more geo-locations measured by the device locator **222** over a period of time and determines a location of the monitoring device **108A** based on the geo-locations and/or based on one or more selections made by the user **112A** via the user interface **274** and/or based on information available within a geo-location-location database of the network **176**. For example, the processor **234** determines that a location within the geo-location-location database corresponds to one or more geo-locations stored within the geo-location-location database. In this example, upon receiving the geo-locations from the device locator **222**, the processor **234** determines the location based on the correspondence between the geo-locations and the location in the geo-location-location database. In some embodiments, the geo-location-location database includes a map of a geographical region, e.g., a city, a state, a county, a country, a continent, a geographical area, world, etc. The map is generated by the server **228** or another server based on one or more geo-locations.

The environmental sensor **272** senses and determines an environmental parameter, e.g., a barometric pressure, a weather condition, an amount of light exposure, an amount of noise, an amount of radiation, an amount of magnetic field, or a combination thereof, etc., of an environment in which the monitoring device **108A** is placed. The device locator **222** determines a geo-location of the monitoring device **108A**.

The time measurement device **232** determines an amount of time associated with one or more positions sensed by the position sensor **220**, associated with one or more environmental parameters determined by the environmental sensor **272**, associated with one or more geo-locations determined

by the device locator **222**, and/or associated with one or more locations determined by the processor **234**. For example, the time measurement device **232** determines an amount of time for a number of positions that is reached by movement of the monitoring device **108A** and that is determined by the position sensor **220**. As another example, the time measurement device **232** determines an amount of time for a number of geo-locations reached by movement of the monitoring device **108A** and that is determined by the device locator **222**.

The wireless communication device **278** establishes a wireless link with the computing device **166** to send data, e.g., activity data, geo-location data, location data, a combination thereof, etc., to and/or receive the data and/or instructions from the computing device **166**. Each computing device **164A** and **164B** (FIGS. **2A** & **2B**) is an example of the computing device **166**. The instructions from the computing device **166** may be to send data, e.g., activity data, geo-location data, location data, a combination thereof, etc., to the computing device **166**.

In some embodiments, the monitoring device **108A** excludes the wireless communication device **278**. In these embodiments, the monitoring device **108A** communicates using a wired connection with the computing device **166**.

In various embodiments, the time measurement device **232** is integrated as a part of the position sensor **220** and/or as a part of the environmental sensor **272** and/or as a part of the device locator **222**.

In several embodiments, the monitoring device **108A** excludes the environmental sensor **272**.

In a number of embodiments, the monitoring device **108A** includes a biological sensor coupled to the environmental sensor **272**, the position sensor **220**, the time measurement device **232**, the user interface **274**, the device locator **222**, the display device **276**, the processor **234**, the wireless communication device **278**, and the memory device **280**. The biological sensor is further described below.

FIG. **3B** is a diagram of an embodiment of a system **290** to illustrate components of a monitoring device **108B**. The system **290** includes the monitoring device **108B**, the computing device **166**, the network **176**, and the server **228**. An example of the monitoring device **108B** includes a scale. The monitoring device **108B** is placed on a floor and the user **112A** stands on the monitoring device **108B**. The monitoring device **108B** includes an environmental sensor **292**, a biological sensor **294**, a time measurement device **295**, a user interface **296**, a device locator **306**, a display device **304**, a processor **302**, a wireless communication device **300**, and a memory device **298**.

The environmental sensor **292** performs the same functions as that of the environmental sensor **272** (FIG. **3A**) except that the environmental sensor **292** is of a different, e.g., larger, smaller, etc., size compared to a size of the environmental sensor **272**. In some embodiments, the environmental sensor **272** is used in the monitoring device **108B** instead of the environmental sensor **292**.

The biological sensor **294** senses and determines a physiological parameter of the user **112A**. For example, the biological sensor **294** determines a weight of the user **112A**. As another example, the biological sensor **294** determines a body mass index of the user **112A**. As yet another example, the biological sensor **294** determines a fingerprint or a footprint of the user **112A**. As another example, the biological sensor **294** determines a heart rate, a hydration level, a body fat, a bone density, and/or a bioimpedance of the user **112A**. Examples of the biological sensor **294** include a biometric sensor, a physiological parameter sensor, or a combination thereof.

The time measurement device **295** performs the same functions as that of the time measurement device **232** (FIG. 3A) except that the time measurement device **295** is different, e.g., larger, smaller, etc., in size compared to the time measurement device **232**. As an example, the time measurement device **295** determines an amount of time for a number of physiological parameters measured by the biological sensor **294**.

In some embodiments, the time measurement device **232** is used in the monitoring device **108B** instead of the time measurement device **295**.

Similarly, the user interface **296** performs the same functions as that of the user interface **274** (FIG. 3A) and is of a different size than that of the user interface **274**. In various embodiments, the user interface **274** is used in the monitoring device **108B** instead of the user interface **296**.

Moreover, the memory device **298** performs the same functions as that of the memory device **280** (FIG. 3A) and is of a different size than that of the memory device **280**. For example, the memory device **298** includes a different, e.g., larger, smaller, etc., number of memory cells compared to memory cells of the memory device **280**. In various embodiments, the memory device **280** is used in the monitoring device **108B** instead of the memory device **298**.

Also, the wireless communication device **300** performs the same functions as that of the wireless communication device **278** (FIG. 3A) and is of a different size than that of the wireless communication device **278**. For example, the wireless communication device **300** includes electrical components that allow a transfer data at a different, e.g., higher, lower, etc., rate with the computing device **166** compared to a rate of transfer of data between the wireless communication device **278** and the computing device **166**. In various embodiments, the wireless communication device **278** is used in the monitoring device **108B** instead of the wireless communication device **300**.

Furthermore, the processor **302** performs the same functions as that of the processor **234** (FIG. 3A) and is of a different, e.g., larger, smaller, etc., size than that of the processor **234**. For example, the processor **302** is of a size to achieve a different, e.g., higher, lower, etc., speed than that of the processor **234**. In various embodiments, the processor **234** is used in the monitoring device **108B** instead of the processor **302**.

Moreover, the display device **304** performs the same functions as that of the display device **276** (FIG. 3A) and is of a different, e.g., larger, smaller, etc., size than that of the display device **276**. In various embodiments, the display device **276** is used in the monitoring device **108B** instead of the display device **304**.

Also, the device locator **306** performs the same functions as that of the device locator **222** (FIG. 3A) and is of a different, e.g., larger, smaller, etc., size than that of the device locator **222**. In various embodiments, the device locator **222** is used in the monitoring device **108B** instead of the device locator **306**.

In some embodiments, the monitoring device **108B** includes a position sensor (not shown) that performs the same functions as that of the position sensor **220** (FIG. 3A). The position sensor of the monitoring device **108B** is coupled to the environmental sensor **292**, the biological sensor **294**, the time measurement device **295**, the user interface **296**, the device locator **306**, the display device **304**, the processor **302**, the wireless communication device **300**, and the memory device **298**. In various embodiments, the position sensor **220** is implemented within the monitoring device **108B**.

FIG. 4A is an isometric view of an embodiment of a monitoring device **110A** that is worn around a hand of a user or

around a leg of the user. For example, the monitoring device **110A** has a band that is unclashed to allow the monitoring device **110A** to extend around a wrist of a user or a leg of the user. After the monitoring device **110A** extends around the wrist, the band is clasped to fit the monitoring device **110A** to the wrist of the user or to the leg of the user. As another example, the monitoring device **110A** has an elastic band that is stretched to allow a grip of the monitoring device **110A** to expand. The monitoring device **110A** is then slipped around a palm of a user to a wrist of the user or is slipped around a foot of the user to an ankle of the user. The elastic band is then released to fit the monitoring device **110A** to the wrist of the user or the ankle of the user. In some embodiments, the monitoring device **110A** is worn on a forearm or an upper arm of a user. In other embodiments, the monitoring device can be carried, held, stored in a bag, attached to a shoe, attached to a shirt or pants, etc. In other embodiments, a single person can hold or wear multiple devices. The multiple devices can track the same body part or object or can track/monitor multiple body parts, or objects. For instance, the user can wear one on his/her wrist, one in a shoe, one on his pants, a hat, a visor, or any other object that can track some movement and/or location of the user.

The monitoring device **110A** includes a display screen **320** of a display device that displays activity data of one or more activities performed by a user over a period of time, chronological data, geo-location data, or a combination thereof. Examples of a display screen include an LCD screen, an LED screen, a plasma screen, etc. Examples of chronological data include a time of day, a day, a month, a year, etc. The monitoring device **110A** is an example of any of the monitoring devices **114A**, **114B**, **114C**, **114D**, **114E**, **114G**, **114H**, **114I** (FIG. 1A), and **108A** (FIG. 3A).

The monitoring device **110A** includes one or more input devices that allows a user to switch between displaying different types of data, e.g., from activity data to chronological data, from chronological data to activity data, from one type of activity data to another type of activity data, from geo-location data to activity data, from activity data to geo-location data, etc., and to adjust or set chronological data. Types of activity data include calories burned by a user, weight gained by a user, weight lost by a user, stairs ascended by a user, stairs descended by a user, steps taken by a user during walking or running, floors descended by a user, floors climbed by a user, rotations of a bicycle pedal rotated by a user, distance covered by a vehicle operated by a user, golf swings taken by a user, forehands of a sport played by a user, backhands of a sport played by a user, or a combination thereof, etc.

Again, it should be noted that in some embodiments, the monitoring device **110A** is implemented as a watch, a wrist-band, or a bracelet, that is worn/held by the user **112A**.

FIG. 4B is an isometric view of an embodiment of a monitoring device **110B** that fits to an article of clothing or a belt worn by a user. For example, the monitoring device **110B** has a pivoting clip that opens to allow the monitoring device **110B** to extend with respect to a pocket of a shirt worn by a user. After the monitoring device **110B** extends with respect to the pocket, the clip is retracted to fit the monitoring device **110B** to the pocket. The clip may be located between an upper portion **322** and a lower portion **324** of the monitoring device **110B** to allow the upper portion **322** to extend from and pivot with respect to the lower portion **324**.

The monitoring device **110B** includes a display screen **326** that displays activity data, chronological data, geo-location data, or a combination thereof. The monitoring device **110B** is an example of the monitoring device **108A** (FIG. 3A). The monitoring device **110B** includes one or more input devices

that allow a user to switch between displaying different types of data and to adjust or set chronological data.

FIG. 4C is a view of an embodiment of a monitoring device **110C** that fits to an article of clothing or a belt worn by a user. For example, the monitoring device **110C** has a flexible pivoting clip that opens to allow the monitoring device **110C** to extend with respect to a pocket of a pant worn by a user. After the monitoring device **110C** extends around the pocket, the clip is retracted to fit the monitoring device **110C** to the pocket. The clip may be located between an upper portion **328** and a lower portion **330** of the monitoring device **110C** to allow the upper portion **328** to extend from and pivot with respect to the lower portion **330**.

The monitoring device **110C** includes a display screen **332** that displays data, e.g., activity data, chronological data, geo-location data, or a combination thereof, etc. The monitoring device **110C** is an example of the monitoring device **108A** (FIG. 3A). The monitoring device **110C** includes one or more input devices that allow a user to switch between displaying different types of data and to adjust or set chronological data.

FIG. 4D is an isometric view of an embodiment of a monitoring device **110D** that fits with respect to an arm of a user. For example, the monitoring device **110D** includes a hook and loop clasp that is extended to loop around a wrist of a user and is then retracted to hook to the wrist. In some embodiments, the monitoring device **110D** is implemented within a wrist watch. The monitoring device **110D** includes a number of buttons **334A**, **334B**, and **334C** to allow the monitoring device **110D** to switch between different types of data, e.g., geo-location data, location, chronological data, activity data, physiological parameter, etc., and to adjust or set chronological data.

The monitoring device **110D** includes a display screen **336** that displays activity data, chronological data, geo-location data, physiological parameter, location data, the GUI data **186** (FIG. 2A), or a combination thereof. The monitoring device **110D** is an example of any of the monitoring devices **114A**, **114b**, **114C**, **114D**, **114E**, **114G**, **114H**, **114I** (FIG. 1A), and **108A** (FIG. 3A).

It should be noted that in some embodiments, instead of being implemented as a watch, the monitoring device **110D** is implemented as a wristband or a bracelet that is worn by the user **112A**.

Monitoring devices have shapes and sizes adapted for coupling to, e.g., secured to, worn, etc., the body or clothing of a user. The monitoring devices collect one or more types of physiological and/or environmental data from embedded sensors and/or external devices and communicate or relay the data to other devices, including devices capable of serving as an Internet-accessible data sources, thus permitting the collected data to be viewed, for example, using a web browser or network-based application. For example, while the user **112A** is wearing or holding a monitoring device, the monitoring device may calculate and store the user's step count using one or more sensors. The monitoring device then transmits data representative of the user's step count to an account on a virtual machine, a computer, or a mobile phone, where the data may be stored, processed, and visualized by the user **112A**.

Indeed, the monitoring device may measure or calculate a plurality of activity data and/or physiological parameters in addition to, or in place of, the user's step count. These activity data and/or physiological parameters include, but are not limited to, energy expenditure, e.g., calorie burn, etc., floors climbed, floors descended, heart rate, heart rate variability, heart rate recovery, geo-location, elevation, speed and/or distance traveled, swimming lap count, swimming stroke type

and count detected, bicycle distance and/or speed, blood pressure, blood glucose, skin conduction, skin temperature, body temperature, electromyography, electroencephalography, weight, body fat, caloric intake, nutritional intake from food, medication intake, sleep periods, sleep phases, sleep quality, pH levels, hydration levels, respiration rate, or a combination thereof. The monitoring device may also measure or calculate parameters related to an environment around the user **112A**, such as, e.g., barometric pressure, weather conditions (e.g., temperature, humidity, pollen count, air quality, rain/snow conditions, wind speed, etc.), light exposure (e.g., ambient light, UV light exposure, time and/or duration spent in darkness, etc.), noise exposure, radiation exposure, magnetic field, or a combination thereof.

In some embodiments, the monitoring device quantifies work productivity against noise levels and/or against air quality and/or against temperature and/or against pressure and/or against humidity and/or against pollen count and the quantification is identified as a level within event data. In several embodiments, the monitoring device quantifies stress levels against noise levels and/or against an amount of time spent by the user **112A** at work and/or against an amount of time spent by the user **112A** exercising outside a work location and/or against an amount of time spent by the user **112A** in a gym and/or an amount of time spent by the user **112A** at his parent's home, and the quantification is identified as a level within event data. In some embodiments, a stress level is quantified, e.g., measured, determined, etc., based on heart rate variability (HRV) and/or galvanic skin response (GSR). The HRV and/or the GSR are measured by a biological sensor.

Furthermore, a monitoring device or a computing device collating data streams may calculate parameters derived from the activity data and/or physiological parameters. For example, monitoring device or a computing device may calculate a user's stress and/or relaxation levels through a combination of heart rate variability, skin conduction, noise pollution, and sleep quality. In another example, a monitoring device or a computing device may determine an efficacy of a medical intervention (e.g., medication) through a combination of medication intake, sleep and/or activity data. In yet another example, the monitoring device or a computing device may determine an efficacy of an allergy medication through the combination of pollen data, medication intake, sleep and/or other activity data.

FIG. 5 is a block diagram of an embodiment of the computing device **166**. The computing device **166** includes a processor **226**, a memory device **338**, an input device **240**, an input/output interface (I/O) **342**, a device locator **344**, a wireless communication device **346**, an I/O **348**, a graphical processing unit (GPU) **350**, a display device **352**, an I/O **354**, a NIC **356**, and an I/O **358**, all of which are coupled to each other via a bus **360**.

An I/O is a parallel interface, a serial interface, or a USB interface between two devices that are coupled to the I/O. For example, the I/O **358** is an interface between the NIC **356** and the bus **360**.

Examples of the processor **226** and the memory device **338** are provided above. Moreover, examples of the input device **340** and the device locator **344** are provided above. Furthermore, examples of the wireless communication device **346**, the display device **352**, and the NIC **356** are provided above. The GPU **350** executes a rendering technique to display data, e.g., GUI, web page, etc., on the display device **352**.

The wireless communication device **346** receives geo-location data and activity data from the wireless communication device **278** (FIG. 3A) of the monitoring device **108A**

and/or the wireless communication device **300** (FIG. 3B) of the monitoring device **108B**. The processor **226** determines a group of activity data and a location/activity identifier based on the activity data and the geo-location data.

In some embodiments, the computing device **166** includes a wired communication device in addition to or instead of the wireless communication device **300**. Examples of the wired communication device include a USB interface, a parallel interface, and a serial interface.

In several embodiments, the user **112A** provides via the user interface **274** (FIG. 3A) of the monitoring device **108A** to the processor **234** or via the input device **340** (FIG. 5) of the computing device **166** to the processor **226** one or more locations, e.g., a home of the user **112A**, coffee shop, work, gym, a home of a friend of the user **112A**, a home of a family member of the user **112A**, a work place of the user **112A**, a place, a street, a building, etc., that the user **112A** visits over a period of time. In some embodiments, the user **112A** provides via the user interface **274** (FIG. 3A) of the monitoring device **108A** to the processor **234** or via the input device **340** (FIG. 5) of the computing device **166** to the processor **226** a size of a location and a type of a location, e.g., work place, sandwich place, pizza place, eatery, gym, golf course, park, running place, walking place, eating place, etc. Examples of a size of a location include a number of floors within the location, a square footage of a location, a number of offices in the location, a number of rooms in the location, a number of people that can fit in the location, a height of the location, a width of the location, a length of the location, a radius of a circle that identifies the location, a diameter of a circle that identifies the location, or a combination thereof.

The one or more locations, the type of location, and/or the size of the location received from the user **112A** are sent by the monitoring device **108A** or by the monitoring device **108B** via the computing device **166** and the network **176** to the server **228** to be stored in the geo-location-location database. In some embodiments, the one or more locations, the type of location, and/or the size of the location received from the user **112A** are sent by the monitoring device **108A** or by the monitoring device **108B** via the network **176** to the server **228** without using the computing device **166** to be stored in the geo-location-location database.

In some embodiments, upon accessing the geo-location-location database, the processor **226** or the processor **234** determines that the geo-location-location database does not include a location corresponding to one or more geo-locations visited by the user **112A** over a period of time. The processor **226** determines whether the user **112A** is within a radius that includes one or more geo-locations of the user **112A**. Upon determining that the user **112A** is within the radius for more than a number of instances of time, the processor **226** generates a prompt to provide to the user **112A** via the display device **352** or the processor **234** generates the prompt to provide to the user **112A** via the display device **276**. The prompt requests the user **112A** to provide the location corresponding to the one or more geo-locations that are within the radius and that are visited by the user **112A**.

In a number of embodiments, the processor **234** determines that among multiple locations, a location within the geo-location-location database is closest to a geo-location of the user **112A** wearing a monitoring device, and determines the location to correspond to the geo-location-location of the user **112A**.

In some embodiments, the processor **234** receives a selection, e.g., an expansion of a bubble-shaped or another shaped graphical element or displayed on the display device **276**, a contraction of a bubble-shaped or another shaped graphical

element displayed on the display device **276**, etc., from the user **112A** and the selection indicates that a location corresponds to a different set of geo-locations than that indicated by the geo-location-location database. Upon receiving the selection, the processor **234** determines that the location corresponds to the different set of geo-locations than that indicated by the geo-location-location database.

It should be noted that a graphical element has one or more graphical properties, e.g., a shape, a color, a shade, a texture, or a combination thereof. For example, a graphical element includes a block, a line, a box, a dot, a pin, a circle, a bubble, or a combination thereof.

FIG. 6A is a flowchart of an embodiment of a method **102** for segmenting a period of time into identification of locations of a user performing activities. The method **102** is executed by the monitoring device **108A** (FIG. 3A).

The method **102** includes detecting, in an operation **104**, an activity of the monitoring device **108A** when the monitoring device **108A** is worn by the user **112A** (FIG. 1A). It should be noted that when the monitoring device **108A** is worn by the user **112A**, the activity of the monitoring device **108A** is the same as that of the user **112A**. The activity includes an amount of movement of the monitoring device **108A** and is performed for a period of time. In some embodiments, the activity includes a number of calories burned by the user **112A**. Examples of the activity of the user **112A** detected by the monitoring device **108A** include running, or walking, or jogging, or sleeping, or moving around, or a sports activity, or sleep, or a combination thereof.

The amount of movement of the user **112A** includes an amount of movement of a body part of the user **112A**. For example, the amount of movement of the user **112A** includes an amount of stairs ascended by the user **112A**, or an amount of stairs descended by the user **112A**, a number of forehands of a sport played by the user **112A**, or a number of backhands of the sport, or a number of serves of the sport made by the user **112A**, or a number of times a golf swing is made by the user **112A**, or a number of times a soccer ball is kicked by the user **112A**, or a number of times a ball is thrown by the user **112A**, a number of rotations of a bicycle made by the user **112A**, or a number of times a paddle, e.g., a brake pedal, an accelerator pedal, etc., of a vehicle is pushed by the user **112A**, or a number of times a hand movement is made by the user **112A**, or a number of times a leg movement is made by the user **112A**, or a number of times a steering wheel of a vehicle is rotated partially or fully by the user **112A**, or an amount of calories burned by the user **112A**, or an amount of distance traveled by the user **112A**, an amount of steps walked or ran by the user **112A**, or an amount of hours slept by the user **112A**, or an amount of time for which the user **112A** is active, or a combination thereof.

The detection of the activity is performed by the position sensor **220** (FIG. 3A) of the monitoring device **108A**. For example, the position sensor **220** determines the amount of movement of the user **112A**. The position sensor **220** determines the amount of movement at each amount of time, e.g., second, minute, hour, a fraction of a second, a fraction of a minute, a fraction of an hour, etc., that is measured by the time measurement device **232** (FIG. 3A) of the monitoring device **108A**.

The method **102** further includes obtaining, in an operation **118**, geo-location data for the monitoring device **108A**. For example, the geo-location data includes a latitude, an altitude, and/or a longitude of the monitoring device **108A**. The geo-location data is obtained by the device locator **222** (FIG. 3A) of the monitoring device **108A**. For example, signals are sent between the device locator **222** and another device, e.g., a cell

tower, a satellite, etc., to determine a geo-location of the device locator **222**, and the geo-location of the device locator **222** is the same as a geo-location of the monitoring device **108A**. The geo-location of the monitoring device **108A** is the same as a geo-location of the user **112A** when the user **112A** is wearing the monitoring device **108A**.

The method **102** also includes storing, in an operation **122**, during the period of time of activity performed by the user **112A**, the activity that is detected in the operation **104** and the corresponding geo-location data that is obtained in the operation **118**. The geo-location data that is obtained in the operation **118** corresponds to the activity detected in the operation **104** when the geo-location is obtained and the activity is detected at the same time or during the same time period. For example, when the user **112A** wearing the monitoring device **108A** is performing an activity at a longitude 1 and a latitude 1, a geo-location that includes the longitude 1 and the latitude 1 corresponds to the activity. In this example, the position sensor **220** determines that the user **112A** is performing the activity and the device locator **222** determines that the user **112** is at the longitude 1 and latitude 1 at the same time the user **112A** is performing the activity. To further illustrate, the detected activity corresponds to the geo-location data when the activity is detected at a time the monitoring device **108A** is located at the geo-location.

The operation **122** of storing is performed by the memory device **280** (FIG. 3A) of the monitoring device **108A** or by a combination of the processor **234** of the monitoring device **108A** and the memory device **280** of the monitoring device **108A**. For example, the processor **234** writes, e.g., stores, etc., data to be stored in the memory device **280**.

The method **102** further includes analyzing, in an operation **124**, the activity detected in the operation **104** and the corresponding geo-location data obtained in the operation **118** to identify one or more events, e.g., an event **126₁**, an event **126₂**, an event **126₃**, an event **126₄**, an event **126₅**, an event **126₆**, an event **126₇**, an event **126₈**, an event **126₉**, an event **126₁₀**, an event **128₁**, an event **128₂**, an event **128₃**, an event **128₄**, an event **128₅**, an event **128₆**, etc., which are described with reference to FIGS. 7A and 7E. The events **126₁**, **126₂**, **126₃**, **126₄**, **126₅**, **126₆**, **126₇**, **126₈**, **126₉**, and **126₁₀** are displayed within an event region **730** of FIG. 7A. The events **128₁**, **128₂**, **128₃**, **128₄**, **128₅**, and **128₆** are displayed within a GUI **394** (FIG. 7E).

Each event occurs over a period of time. For example, the event **126₁** occurs over a time period, e.g., from 12 AM to 8 AM, etc., and the event **126₄** occurs over a time period, e.g., from a time between 8 AM and 9 AM to 3 PM, etc.

As further shown in FIG. 7A, each event **126₁**, **126₂**, **126₃**, **126₄**, **126₅**, **126₆**, **126₇**, **126₈**, **126₉**, and **126₁₀** is a portion of a GUI **370**, which is an example representation of the GUI data **186** (FIG. 2A). For example, each event **126₁**, **126₂**, **126₃**, **126₄**, **126₅**, **126₆**, **126₇**, **126₈**, **126₉**, and **126₁₀** includes a textual and/or a graphical data portion of the GUI **370**. To further illustrate, the event **126₄** includes a graphical data portion that shows activity levels, e.g., amounts, etc., of an activity performed by the user **112A**. Moreover, in this illustration, the event **126₄** includes a time period during which the activity is performed and indicates the activity, e.g., golfing, etc. In this illustration, the activity indicates a location, e.g., a golf course. As another illustration, the event **126₆** includes a graphical data portion that shows activity levels of an activity performed by the user **112A**. Moreover, in this illustration, the event **126₆** includes a time period during which the activity is performed and includes a location, e.g., a home of the user **112A**, etc., at which the activity is performed.

Each event is associated, e.g., linked, corresponded, related, etc., with a group of activity data and one or more of the groups of activity data is associated, e.g., linked, corresponded, etc., related, with a location/activity identifier. For example, referring to FIG. 7A, the event **126₄** includes a group **130A** of activity data and the event **126₆** includes a group **130B** of activity data. The group **130A** includes activity levels of an activity performed by the user **112A** during a period of time and the group **130A** is associated with a location/activity identifier **132D**. Similarly, the group **130B** includes activity levels of an activity performed by the user **112A** during a period of time, e.g., a time period between a time between 3 pm and 4 pm and a time between 5 pm and 6 pm, etc., and the group **130B** is associated with a location/activity identifier **132A**.

Moreover, similarly, a group of activity data of the event **126₁** is associated with the location/activity identifier **132A**, a group of activity data of the event **126₂** is associated with a location/activity identifier **132B**, a group of activity data of the event **126₃** is associated with a location/activity identifier **132C**, a group of activity data of the event **126₅** is associated with the location/activity identifier **132C**, a group of activity data of the event **126₇** is associated with the location/activity identifier **132C**, a group of activity data of the event **126₈** is associated with the location/activity identifier **132A**, a group of activity data of the event **126₉** is associated with a location/activity identifier **132C**, and a group of activity data of the event **126₁₀** is associated with a location/activity identifier **132A**. Furthermore, with reference to FIG. 7E, a group of activity data of the event **128₁** is associated with a location/activity identifier **134A** and a group of activity data of the event **128₃** is associated with a location/activity identifier **134B**. A group of activity data is associated with a location/activity identifier to provide a context as to which activity is performed and where. For example, an amount of calories burned by a user are displayed in a background in which an icon representing an activity of walking performed by the user is shown and/or an icon representing a public park is shown. The amount of calories is burned when the user is walking and/or in the public park and/or is walking in the public park.

Referring back to FIG. 6A, a location/activity identifier is generated by the processor **234** using the geo-location data, which is obtained in the operation **118**, and/or activity data, which is obtained in the operation **104**. For example, the processor **234** (FIG. 3A) of the monitoring device **108A** determines that the geo-location-database indicates a correspondence between a location of the user **112A** and a set that includes one or more longitudes at which an activity is performed by the user **112A**, one or more latitudes at which the activity is performed, and/or one or more altitudes at which the activity is performed, and assigns the location/activity identifier **132D** to represent the location. As another example, the processor **234** determines that a distance traveled by the user **112A** in a period of time is within an upper limit and a lower limit. The period of time is received from the time measurement device **232** of the monitoring device **108A**. The distance traveled by the user **112A** is received from the position sensor **220** and/or the device locator **222** of the monitoring device **108A**. As another example, the processor **234** receives a selection from the user **112A** via the user interface **274** (FIG. 3A) of the monitoring device **108A** that one or more geo-locations at which the user **112A** performs an activity correspond to a location of the user **112A**, and assigns a location/activity identifier to represent the location.

The operation **124** is performed by the processor **234** (FIG. 3A) based on the activity detected in the operation **104** and/or

the geo-location data obtained in the operation 118, and a time period during which the activity is performed. The processor 234 receives one or more amounts of time of performance of an activity during a time period from the time measurement device 232 (FIG. 3A), and/or receives one or more geo-locations at which the activity is performed during the time period from the device locator 222 (FIG. 3A), and receives one or more activity levels of the activity from the position sensor 220 (FIG. 3A) to perform the operation 124. For example, the processor 234 determines that the user 112A is in a vehicle upon determining that a speed of travel of the user 112A is greater than s_1 miles per hour. The speed s_1 is a running or walking speed of one or more users. The processor 234 determines a speed of travel of the user 112A based on geo-location data obtained in an hour of one or more geo-locations of the user 112. Geo-location data is received from the device locator 222 (FIG. 3A) of the monitoring device 108A and a measurement of the hour is received from the time measurement device 232 (FIG. 3A).

As another example, the processor 234 determines whether the user 112A is in a vehicle, or is riding a bicycle or a skateboard, or is undergoing ambulatory motion based on a speed of the user 112A and motion of a body portion of the user 112A. To illustrate, when the processor 234 determines that a speed of the user 112A is greater than a pre-determined number of miles per hour and motion of the body portion is less than a pre-determined amount of motion, the processor 234 determines that the user 112A is in a vehicle and is not walking or running. As another illustration, when the processor 234 determines that a speed of the user 112A is less than the pre-determined number of miles per hour and motion of the body portion is greater than the pre-determined amount of motion, the processor 234 determines that the user 112A is performing the ambulatory motion. Examples of ambulatory motion include walking, running, jogging, exercising, etc. An example of the body portion includes an arm of the user 112A. In various embodiments, a speed of the user 112A is determined by a device locator or a processor based on an amount of distance between two geo-locations and time of the user 112A at each of the geo-locations. In some embodiments, a speed of the user 112A is determined by a position sensor or a processor based on an amount of distance between two positions and time of occurrence of each of the positions.

As yet another example, the processor 234 determines that the user 112A is running upon determining that a speed of travel of the user 112A is greater than s_2 miles per hour and a number of steps taken by the user 112A is greater than ss_1 per hour. The speed s_2 is a walking speed of one or more users. A number of steps are received by the processor 234 from the position sensor 220 (FIG. 3A) of the monitoring device 108A. As another example, the processor 234 determines that the user 112A is walking upon determining that a number of steps taken by the user 112A is less than ss_1 per hour and greater than ss_2 per hour. As yet another example, the processor 234 determines that the user 112A is in a vehicle upon determining that a speed of travel of the user 112A is greater than s_3 miles per hour and a number of steps taken by the user 112A is less than ss_3 per hour.

As another example, the processor 234 determines that the user 112A is moving around upon determining that a number of steps taken by the user 112A is less than ss_4 per hour. As yet another example, the processor 234 determines that the user 112A is sedentary upon determining that the user 112A is not walking, running, not moving around, and not in a vehicle. As another example, the processor 234 determines that the user 112A is sleeping upon determining that the user 112A is sedentary for greater than an amount of time.

In some embodiments, the processor 234 determines a speed of travel of the user 112A based on geo-location data obtained over a period of time of one or more geo-locations of the user 112 and the period of time.

The time period during which the activity is performed at a location is determined by the processor 234 based on a sum of amounts of time measured by the time measurement device 232 for performing the activity at one or more geo-locations corresponding to, e.g., included within, linked with, etc., the location.

The operation 124 of analyzing the detected activity and the corresponding geo-location data during the period of time includes determining a time element of segregation of the activity detected at the operation 104. For example, a period of time during which an activity is performed is segmented into one or more time elements. As another example, a period of time during which an activity is performed is segmented into one or more time elements, and each time element includes a graphical property and/or text to represent the time element. Examples of a time element include a fraction of a minute, or a minute, or a fraction of an hour, or an hour, etc. Further examples of a time element are shown as a time element 144₁ and a time element 144₂ in FIG. 7A. The time element 144₁ is a time of day at which a golf activity having an activity level is performed by the user 112A. Moreover, the time element 144₂ is another time of day at which a golf activity having an activity level is performed by the user 112A. The activity level at the time element 144₂ is lower than the activity level at the time element 144₁. In some embodiments, the activity level at the time element 144₂ is higher than or the same as the activity level at the time element 144₁. The time element 144₁ includes text, e.g., 9 AM, etc.

The operation 124 of analyzing the detected activity and the corresponding geo-location data during the period of time further includes determining an activity level for each time element. For example, an activity level 146₁ (FIG. 7A) is determined as being performed at the time element 144₁ and an activity level 146₂ (FIG. 7A) is determined as being performed at the time element 144₂. As another example, the activity level 146₁ (FIG. 7A) is determined as being performed at the time element 144₁ and is determined to include text and/or a graphical property, e.g., a dark gray bar, etc., and the activity level 146₂ (FIG. 7A) is determined as being performed at the time element 144₂ and is determined to include text and/or a graphical property, a dark gray bar, etc.

The operation 124 of analyzing the detected activity and the corresponding geo-location data during the period of time also includes determining a location/activity identifier of a location and/or activity for each time element and for each activity level. For example, the processor 234 determines that an activity level that occurs at a time element is of an activity that occurs at one or more geo-locations that correspond to a location and/or that correspond to an activity, e.g., a home of the user 112, a building, a park, an office, golfing, walking, running, a commercial place, an eatery, a work place, a vehicle, a golf course, a sandwich shop, or any other location, etc., and determines a location/activity identifier that represents the location and/or activity.

As another example, the processor 234 determines that the activity level 146₁ is of an activity that occurs at one or more geo-locations of a golf course and determines the location/activity identifier 132D that represents golfing. In this example, the processor 234 accesses correspondence between geo-location data and location data stored within the geo-location-location database to determine whether the one or more geo-locations correspond to the golf course and/or also accesses position data of the monitoring device 108A

from the position sensor 220 to determine that the activity is golfing. As yet another example, the processor 234 determines that the activity level 146₂ is of an activity that occurs at one or more geo-locations of a golf course and determines the location/activity identifier 132D. In this example, the processor 234 applies a selection received from the user 112A via the user interface 274 (FIG. 3A) to determine that one or more geo-locations at which the activity level 146₂ occurs correspond to a golf course. In this example, the geo-locations at which the activity level 146₂ occurs are the same or different from one or more geo-locations determined by the processor 234 from the geo-location-location database to correspond to a golf course.

Examples of a location/activity identifier include a graphical element, e.g. an icon, an icon having a pointer, a symbol, a symbol having a pointer, a trademark, a trademark having a pointer, a registered mark, a registered mark having a pointer, an animation icon, an animation icon having a pointer, an animation, an animation having a pointer, a video icon, a video icon having a pointer, a video, a video having a pointer, an audio icon, an audio icon having a pointer, an audio, an audio having a pointer, a multimedia icon, a multimedia icon having a pointer, a multimedia, a multimedia having a pointer, or a combination thereof, etc., that represents a location at which the activity is performed.

A location/activity identifier has a graphical element and/or text. For example, the location/activity identifier 380B includes an icon of a person walking. As another example, the location/activity identifier 380D includes an icon of a person golfing with a golf club.

The operation 124 of analyzing the detected activity and the corresponding geo-location data during the period of time further includes associating the activity level with the time element and the location/activity identifier. Upon determining the location/activity identifier for each time element and for each activity level, the processor 234 associates, e.g., establishes a link between, establishes a correspondence between, etc., the time element and the activity level with the location/activity identifier. For example, the processor 234 establishes a link between the time element 144₁, the activity level 146₁, and the location/activity identifier 132D. As another example, the processor 234 establishes a link between the time element 144₂, the activity level 146₂, and the location/activity identifier 132D.

The operation 124 of analyzing the detected activity and the corresponding geo-location data during the period of time also includes aggregating the associated activity levels and time elements over the period of time to indicate, using the associated location/activity identifier, a location of occurrence of the activity levels and of a group of activity data. The group of activity data includes the activity levels and the period of time. The processor 234 aggregates, e.g., combines, accumulates, etc., over a period of time the activity levels and time elements that are associated with a location/activity identifier of an activity. The period of time over which the processor 234 aggregates is continuous, e.g., from 1 pm to 2 pm on a day, from January to February of a year, from year 2000 to year 2004 of a decade, etc.

The aggregated activity levels, time elements, and the associated location/activity identifier are represented, by the processor 234, within one or more graphical elements and/or text of a background that represent an event to generate or identify the event. For example, the processor 234 assigns one or more graphical elements to an area, within the GUI 370 (FIG. 7A), to generate the event 126₄ that includes the group 130A of activity data, the location/activity identifier 380D and a background 150, e.g., a gray-shaded area, a shaded area, an area

having a graphical property, etc. The group 130A of activity data and the location/activity identifier 380D are overlaid on the background 150. The event 126₄ includes the time element 144₁ aligned, e.g., vertically, horizontally, oblique, etc., with the activity level 146₁ and further includes the location/activity identifier 132D including or attached to a pointer 380D. The pointer 380D points to the event 126₄ that includes the activity level 146₁ and the time element 144₁. Similarly, as shown in FIG. 7A, a pointer 380A that is included within or is attached to the location/activity identifier 132A points to the event 126₁, a pointer 380B that is included within or is attached to the location/activity identifier 132B points to the event 126₂, and a pointer 380C that is included within or is attached to the location/activity identifier 132C points to the event 126₃.

It should be noted that in some embodiments, a location/activity identifier does not include and is not attached to a pointer. For example, the event 126₄ includes the location/activity identifier 132D without the pointer 380D.

In various embodiments, a group of activity data includes a location/activity identifier in addition to one or more activity levels and one or more time elements. For example, the group 130A of activity data includes one or more activity levels, one or more time elements, and the location/activity identifier 380D.

In several embodiments, each activity level is assigned a graphical property by the processor 234. For example, as shown in FIG. 7A, the activity level 146₁ is assigned a graphical property 148₁ and the activity level 146₂ is assigned a graphical property 148₂. The graphical property 148₂ may be the same or different from the graphical property 148₁. For example, the graphical property 148₂ has the same color as that of the graphical property 148₁. As another example, the graphical property 148₂ has the same texture and color as that of the graphical property 148₁.

In some embodiments, the method 102 is performed by the monitoring device 108B (FIG. 3B) except instead of the operation 104, the biological sensor 294 performs an operation of detecting a physiological parameter of the user 112A who is located on the monitoring device 108B. Moreover, in these embodiments, the operation 118 of obtaining geo-location data for the monitoring device 108B is performed by the device locator 306 (FIG. 3B). Further, in these embodiments, the operation 122 of storing the detected physiological parameter and the corresponding geo-location data is performed by the processor 302 (FIG. 3B) or by a combination of the processor 302 and the memory device 298 (FIG. 3B). In these embodiments, the operation 124 of analyzing the detected physiological parameter and the corresponding geo-location data during the period of time to identify one or more events is performed by the processor 302 (FIG. 3B) of the monitoring device 108B.

FIG. 6B is a flowchart of an embodiment of a method 160 for segmenting a period of time into identification of locations of a user performing activities. The method 160 is executed by the monitoring device 108A (FIG. 3A). In the method 160, the operations 104, 118, and 122 are performed.

The method 160 includes transferring, e.g., sending, etc., in an operation 162, from time to time, to the computing device 166 (FIG. 5) the activity that is detected at the operation 104 and that corresponds to the geo-location data that is obtained at the operation 118. For example, activity data is transferred periodically, e.g., every fraction of a second, every second, every minute, every fraction of a minute, etc., or aperiodically, e.g., randomly, etc., to the computing device 166 upon reception of request from the computing device 166.

The operation 162 of transferring is performed by the wireless communication device 278 (FIG. 3A) via a wireless link, e.g., the wireless link 168 (FIG. 2A), the wireless link 170 (FIG. 2B), etc., between the monitoring device 108A (FIG. 3A) and the computing device 166. For example, the wireless communication device 278 executes a Bluetooth or a Wi-Fi protocol to transfer data to the computing device 166 via a wireless link. In some embodiments in which a wired link is used between the monitoring device 108A and the computing device 166, the operation 162 of transferring is performed by a wired communication device of the monitoring device 108A and the wired communication device is connected via a wired link to the wired communication device of the computing device 166. In various embodiments, the wireless communication device 278 transfers data via a wireless communication link and the network 176 (FIG. 3A) to the server 228 (FIG. 3A) without transferring data via the computing device 166. In several embodiments, a wired communication device of the monitoring device 108A transfers via a wired communication link and the network 176 to the server 228 without transferring data via the computing device 166. For example, the wired communication device of the monitoring device 108A executes a communication protocol, e.g., a Transmission Control Protocol over Internet Protocol (TCP/IP), a User Datagram Protocol over Internet Protocol (UDP/IP), etc., to communicate data with the server 228 via the network 176.

In some embodiments, the operations 104, 118, and 112 are performed by the monitoring device 108B (FIG. 3B) with the changes described above with respect to the method 102 (FIG. 6A). Moreover, in these embodiments, the operation 162 of transferring, from time to time, the detected activity corresponding to the geo-location data to the computing device 166 is performed by the wireless communication device 300 of the monitoring device 108B or by a wired communication device of the monitoring device 108B.

FIG. 6C is a diagram of an embodiment of a method 170 for segmenting a period of time into identification of locations of a user performing activities. The method 170 is executed by the server 228 (FIGS. 2A & 2B). The method 170 includes an operation 172 of enabling access to the user account 174 (FIG. 2A) via the computing device 166 (FIG. 5) over the network 176 (FIG. 2A). The processor 190 (FIG. 2A) of the server 228 performs the operation 172 of enabling access to the user account 174.

The user 112A (FIG. 1A) uses the user interface 274 (FIG. 3A) of the monitoring device 108A or the input device 340 (FIG. 5) of the computing device 166 to provide the authentication information to access the user account 174. Upon receiving the authentication information via the network 176, the processor 190 (FIG. 2A) of the server 228 or another processor of another server determines whether the authentication information is authentic. Upon determining that the authentication information is authentic or upon receiving the determination from the other processor of the other server, the processor 190 enables access to the user account 174 to the user 112A. When access to the user account 174 is enabled, a representation of the user account 174 is rendered by the processor 234 on the display device 276 (FIG. 3A) of the monitoring device 108A or is rendered by the processor 226 of the computing device 166 on the display device 352 (FIG. 5) of the computing device 166.

The method 170 further includes receiving, in an operation 178, monitoring data for the user account 174. The monitoring data includes the activity detected at the operation 104 (FIGS. 6A & 6B) of the monitoring device 108A (FIG. 3A). The monitoring data includes geo-location data obtained at the operation 118 (FIG. 6A).

The operation of receiving 178 is performed by the NIC 254 (FIG. 2A) of the server 228. The monitoring data is received, via the network 176 (FIGS. 2A, 2B, & 3A), from the NIC 356 (FIG. 5) of the computing device 166 that has received the monitoring data from the wireless communication device 278 (FIG. 3A) of the monitoring device 108A or from a wired communication device of the monitoring device 108A. In some embodiments, the monitoring data is received from the wireless communication device 278 of the monitoring device 108A and the network 176 without use of the computing device 166.

In some embodiments, the NIC 254 applies a communication protocol to receive the monitoring data. For example, the NIC 254 depacketizes one or more packets to obtain the monitoring data.

The method 170 includes processing, in an operation 180, the monitoring data to identify one or more events. The operation 180 of processing is similar to the operation 124 (FIG. 6A) of analyzing the detected activity and the corresponding geo-location data during a period of time to identify one or more events. For example, the operation 180 is the same as the operation 124 except that the operation 180 is performed by the processor 190 (FIG. 2A) of the server 228. The operation 180 is performed to generate the GUI data 186 (FIG. 2A). The GUI data 186 includes event data of one or more events. For example, the GUI data 186 includes data that is rendered to display the GUI 370 (FIG. 7A). As another example, the GUI data 186 includes data that is rendered to display the GUI 394 (FIG. 7E).

The method 170 includes sending, in an operation 182, in response to a request from a consuming device the GUI data 186 (FIG. 2A). Examples of the consuming device include the computing device 166 (FIG. 5) or the monitoring device 108A (FIG. 3A). For example, when the user 112A is provided access to the user account 174 (FIG. 2A), a request is received from the NIC 356 (FIG. 5) to send the GUI data 186. Upon receiving the request, the NIC 254 (FIG. 2A) of the server 228 applies a communication protocol for sending the GUI data 186 via the network 176 to the NIC 356 of the computing device 166 for display on the display device 352 of the computing device 166. As another example, when the user 112A is provided access to the user account 174, a request is received from the wireless communication device 278 of the monitoring device 108A or a wired communication device of the monitoring device 108A via the network 176. Upon receiving the request, the NIC 254 (FIG. 2A) of the server 228 applies a communication protocol for sending the GUI data 186 via the network 176 to the wireless communication device 278 of the monitoring device 108A or to the wired communication device of the monitoring device 108A. The GUI data 186 is sent via the computing device 166 or without using the computing device 166.

The GUI data 186 includes graphics, e.g., graphical elements that represent the events 146₁ and 146₂ (FIG. 7A), that represent the background 150 (FIG. 7A), that represent the location/activity identifiers 132A, 132B, 132C, and 132D (FIG. 7A), etc. The GUI data 186 further includes text, e.g., text 188A ("e.g., HOME" in FIG. 7A) that describes, e.g., identifies, etc., a location that the user 112A has reached during a day, text 188B ("e.g., HANS' PARENTS HOUSE" in FIG. 7A) that describes another location that the user 112A has reached during the day another time of the day, text 188C (e.g., "1 AM" in FIG. 7A) that represents a time of the day, text 188D (e.g., "2 AM" in FIG. 7A) that represents yet another time of the day, etc.

The graphics and text segments a period of time over which one or more activities are performed into events that are

graphically distinct from each other. For example, as shown in FIG. 7A, the event **126₂** that includes activity data of an activity of walking is graphically distinct, e.g., has a lighter shade, etc., than the event **126₄** that includes activity data of an activity of golfing. As another example, as shown in FIG. 7A, an event includes activity data representing an activity is represented by different graphical elements than an event that includes activity data representing the same or a different activity.

FIG. 6D is a flowchart of an embodiment of a method **200** for segmenting a period of time into identification of locations of a user performing activities. The method **200** is executed by the monitoring device **108B** (FIG. 3B).

The method **200** includes determining, in an operation **202**, a geo-location of the monitoring device **108B** over a time period. The geo-location of the monitoring device **108B** is determined by the device locator **306** (FIG. 3B). The method **200** further includes determining, in an operation **204**, a physiological parameter of the user **112A** over a period of time. The operation **204** is performed by the biological sensor **294** (FIG. 3B) of the monitoring device **108B**. For example, the biological sensor **294** measures a change in weight of the user **112A** over a period of time for which the geo-location is determined in the operation **202**. As another example, the biological sensor **294** measures a change in BMI of the user **112A** over a period of time for which the geo-location is determined in the operation **202**. A period of time is measured by the time measurement device **395** (FIG. 3B).

The method **200** also includes associating, in an operation **206**, the geo-location determined in the operation **202** with the physiological parameter determined in the operation **204** to facilitate determination of a group of activity data and a location of the monitoring device **108B**. The processor **302** (FIG. 3B) of the monitoring device **108B** performs the operation **206**. For example, the processor **302** establishes a link between the geo-location data and the physiological parameter. The processor **302** determines a location of the monitoring device **108B** based on the geo-location data and the geo-location-location database. The processor **302** further determines a group of activity data that includes one or more amounts of a physiological parameter that provide a measure of an activity performed over a period of time. For example, when the user **112A** exercises over a period of time, the user **112A** may lose weight. As another example, when the user **112A** is sedentary over a period of time, the user **112A** may gain weight. The processor **302** then generates event data that includes a relation between the location and the group of activity data. For example, the processor **302** determines that one or more amounts of a physiological parameter occur at a location over a period of time and generates a relationship, e.g., correspondence, link, etc., between the amounts, the location, and the time period.

FIG. 6E is a flowchart of an embodiment of a method **210** for segmenting a period of time into identification of locations of a user performing activities. The method **210** is performed by one or more monitoring devices, e.g., the monitoring device **108A**, the monitoring device **108B**, a combination thereof, etc.

The method **210** includes an operation **212** of detecting an activity and/or a physiological parameter of the user **112A** with one or more monitoring devices for a period of time. For example, the position sensor **220** of the monitoring device **108A** (FIG. 3A) detects an activity performed by the user **112A** and the biological sensor **294** of the monitoring device **108B** (FIG. 3B) detects a physiological parameter of the user **112A**.

The method **210** further includes an operation **214** of obtaining geo-location data for the monitoring devices for the period of time for which the operation **212** is performed. For example, geo-location data of geo-location of the monitoring device **108A** is measured by the device locator **222** of the monitoring device **108A** (FIG. 3A) and geo-location data of geo-location of the monitoring device **108B** is measured by the device locator **306** of the monitoring device **108B** (FIG. 3B). A period of time is measured by the time measurement device **232** (FIG. 3A) of the monitoring device **108A** and by the time measurement device **295** of the monitoring device **108B** (FIG. 3B).

The method **210** includes an operation **216** of saving, in an operation **216**, the detected physiological parameter and the detected activity in the operation **212**. For example, the operation **216** of saving the detected activity is performed by the processor **234** of the monitoring device **108A** and/or by the processor **234** and the memory device **280** of the monitoring device **108A**. As another example, the operation **216** of saving the detected physiological parameter is performed by the processor **302** of the monitoring device **108B** and/or by the memory device **298** (FIG. 3B) of the monitoring device **108B**.

The method **210** includes an operation **218** of transferring, from time to time, the detected physiological parameter and the detected activity corresponding to the geo-location data to the computing device **166** (FIG. 5) and/or to the server **228**. For example, the operation **218** of transferring is performed by the wireless communication device **278** (FIG. 3A) of the monitoring device **108A** or by a wired communication device of the monitoring device **108A**. As another example, the operation **218** of transferring is performed by the wireless communication device **300** of the monitoring device **108B** or by a wired communication device of the monitoring device **108B**. The detected activity and the detected physiological parameter are transferred wirelessly to the wireless communication device **224** (FIG. 5) of the computing device **166**. In some embodiments, the detected activity and the detected physiological parameter are transferred via a wired link, e.g., a cable, a wire, etc., to the wired communication device (not shown) of the computing device **166**. In several embodiments, the detected activity and the detected physiological parameter are transferred via a wired link or a combination of a wireless link and a wired link and the network **176** to the server **228** without use of the computing device **166**.

Moreover, in some embodiments, the geo-location data is also transferred, from time to time, to the computing device **166** and/or to the server **228**. For example, the wireless communication device **278** (FIG. 3A) of the monitoring device **108A** transfers geo-location data to the wireless communication device **224** of the computing device **166** or a wired communication device of the monitoring device **108A** transfers the geo-location data to the wired communication device of the computing device **166**. As another example, the geo-location data is transferred wirelessly by the wireless communication device **300** of the monitoring device **108B** or by a wired communication device of the monitoring device **108B** to the computing device **166**. In several embodiments, the geo-location data is transferred via a wired link or a combination of a wireless link and a wired link and the network **176** to the server **228** without use of the computing device **166**.

FIG. 6F is a flowchart of an embodiment of a method **221** for segmenting a period of time into identification of locations of a user performing activities. The method **221** is performed by the monitoring device **108A**, the monitoring device **108B**, by the computing device **166**, or a combination thereof.

The method **221** includes receiving, in an operation **223**, detected activity and/or physiological parameter of the user

112A. For example, the processor 234 (FIG. 3A) of the monitoring device 108A receives detected activity from the position sensor 220 (FIG. 3A). As another example, the processor 302 of the monitoring device 108B receives detected physiological parameter from the biological sensor 294 (FIG. 3B) of the monitoring device 108B. As yet another example, the processor 226 of the computing device 166 (FIG. 5) receives the detected activity from the monitoring device 108A and/or receives the physiological parameter from the monitoring device 108B.

The method 221 includes an operation 227 of classifying detected activity and/or the physiological parameter. For example, the processor 234 (FIG. 3A) of the monitoring device 108A classifies the amount of movement into walking, running, sedentary, sleeping, moving around, or playing a sport. As another example, the processor 302 of the monitoring device 108B classifies the physiological parameter into a type of physiological parameter, e.g., BMI, heart rate, blood pressure, weight, etc. As another example, the processor 226 of the computing device 166 classifies the detected activity and/or the physiological parameter.

The method 221 further includes an operation 229 of determining a location of the user 112A. For example, the processor 234 of the monitoring device 108A determines a location of the user 112A based on geo-location data and/or based on detected activity and/or based on the geo-location-location database. The geo-location data is received by the processor 234 from the device locator 222 of the monitoring device 108A and the detected activity is received by the processor 234 from the position sensor 220 (FIG. 3A) of the monitoring device 108A. Moreover, a determination of a location based on the geo-location data is made by the processor 234 based on the geo-location data and/or the activity data and/or the geo-location-location database.

As another example, the processor 226 of the computing device 166 determines a location of the user 112A based on geo-location data and/or based on detected activity and/or based on a physiological parameter, and/or based on the geo-location-location database. The geo-location data is received by the processor 226 from the device locator 222 of the monitoring device 108A or from the device locator 306 of the monitoring device 108B and the detected activity is received by the processor 226 from the position sensor 220 (FIG. 3A) of the monitoring device 108A and/or a physiological parameter is received from the biological sensor 294 of the monitoring device 108B. Moreover, a determination of a location based on the geo-location data is made by the processor 234 based on the geo-location data and/or the activity data and/or the physiological parameter and/or the geo-location-location database. For example, upon determining that there is a lack of change beyond an amount in a physiological parameter over a period of time, the processor 234 determines that the user 112A has not left one or more geo-locations that corresponds to his/her home during the period of time.

In some embodiments, the processor 226 classifies an activity based on a physiological parameter of the user 112A, and/or a movement of the user 112A, and/or a location of the user 112A. For example, a heart rate of the user 112A is monitored, a movement of an arm of the user 112A is determined, and a location of the user 112A is determined to determine that the user 112A is training with weights in a gym and not swimming in the gym. As another example, an amount of calories burned by the user 112A is measured, a movement of an arm of the user 112A is determined, and a location of the user 112A is determined to indicate that the user 112A is swimming in a gym as opposed to running in the gym.

The method 221 further includes an operation 231 of overlaying of the classified activity performed by the user 112A and/or of the classified physiological parameter of the user 112A and/or of a location arrived at by the user 112A on a map. For example, the processor 234, the processor 302, or the processor 226 determines generates event data that includes the map, the classified activity, and/or the classified physiological parameter. In some embodiments, instead of the operation 231, an operation of overlaying the map is performed on the classified activity and/or the classified physiological parameter and/or the location arrived at by the user 112A.

In various embodiments, event data is generated based on positions that are obtained by a position sensor of a monitoring device and geo-locations obtained by a device locator of the computing device 166. The geo-locations are of the computing device 166 when carried by the user 112A. The computing device 166 transfers the geo-locations via a NIC and the network 176 to the server 228. Moreover, the monitoring device transfers the positions via a communication device and the network 176 to the server 228. The server 228 receives the geo-locations and the positions and generates the event data. In some embodiments, instead of the server 228, a virtual machine generates the event data.

In some embodiments, a monitoring device receives the geo-location data that is obtained by a device locator of the computing device 166 and generates event data based on positions and the geo-locations. The monitoring device includes a position sensor that determines the positions of the monitoring device. The monitoring device receives the geo-locations via a communication device of the monitoring device and a communication device of the computing device 166. The geo-locations are of the computing device 166 when carried by the user 112A.

In several embodiments, the computing device 166 receives positions that are obtained by a position sensor of a monitoring device and generates event data based on positions and the geo-locations. The geo-locations are of the computing device 166 when carried by the user 112A. The monitoring device includes a position sensor that determines the positions of the monitoring device.

In various embodiments, a portion of the event data is generated by a processor of a monitoring device and the remaining portion is generated by a processor of the computing device 166. In several embodiments, a portion of event data is generated by a processor of a monitoring device, another portion of the event data is generated by a processor of the computing device 166, and the remaining portion is generated by a processor of the server 228. In various embodiments, a portion of event data is generated by a processor of a monitoring device, another portion of the event data is generated by a processor of the computing device 166, and the remaining portion is generated by a virtual machine. In some embodiments, a portion of event data is generated by a processor of a monitoring device and the remaining portion is generated by a virtual machine or by the server 228. In various embodiments, a portion of event data is generated by a processor of the computing device 166 and the remaining portion is generated by a virtual machine or by the server 228.

FIG. 7A is an embodiment of the GUI 370 that displays the events 126₁ thru 126₁₀. In some embodiments, the processor 234 (FIG. 3A) highlights, e.g. bolds, colors, shades, etc., an activity level that is higher than or lower than the remaining activity levels by a threshold. The highlight distinguishes the activity level from one or more activity levels of one or more events that occur during a period of time. For example, the processor 234 provides a different color to an activity level

402 compared to remaining activity levels of the event 126₁₀ when the processor 234 determines that the activity level 402 is greater than the remaining activity levels by a threshold.

The GUI 370 is rendered by the processor 234 of the monitoring device 108A to be displayed on the display device 276 (FIG. 3A) of the monitoring device 108A or by the processor 226 (FIG. 5) of the computing device 166 to be displayed on the display device 352 (FIG. 5) of the computing device 166.

The processor 234 or the processor 226 combines amounts of time of a common activity over one or more periods of time to indicate a combined amount of time, e.g., a combined amount of time 138₁, a combined amount of time 138₂, a combined amount of time 138₃, a combined amount of time 138₄, etc., of performance of the common activity and a level, e.g., a level 140₁, a level 140₂, a level 140₃, a level 140₄, etc., of the common activity performed. For example, as shown in FIG. 7A, the user 112A drove a vehicle for 1 hour and 1 minute on a date 308 of March 1, Thursday. As another example, the processor 234 or the processor 226 sums periods of time for which the user 112A performed the common activity on the date 308. To illustrate, a period of time of occurrence of the event 126₂, a period of time of occurrence of the event 126₅, a period of time of occurrence of the event 126₇, and a period of time of occurrence of the event 126₉ are summed to determine a total time period of occurrence of a common activity of driving a vehicle.

Examples of a common activity are the same as that of an activity except that the common activity is the same over multiple periods of time. For example, a common activity is walking, running, golfing, etc.

In various embodiments, the processor 234 or the processor 226 combines activity levels of performance of the common activity over the combined amount of time to generate a combined activity level for each common activity. For example, activity levels of the event 126₂, activity levels of the event 126₅, activity levels of the event 126₇, and activity levels of the event 126₉ are summed to generate a combined activity level of a common activity of driving over the total time period to generate a combined activity level 140₄. Similarly, other combined activity levels 140₁, 140₂, and 140₃ are generated.

Moreover, in some embodiments, the processor 234 or the processor 226 combines amounts of time of one or more activities performed at a common location over one or more periods of time to generate a combined amount of time, e.g., a combined amount of time 138₅, a combined amount of time 138₆, a combined amount of time 138₇, etc., of performance of the one or more activities at the common location. For example, time of performance of all activities performed at a home of the user 112 on the date 308 are combined to generate the combined amount of time 138₅. As another example, time of performance of all activities performed at an office of the user 112 on March 1 are combined to generate the combined amount of time 138₆. A common location is a location at which one or more activities, e.g., a common activity, etc., are performed over one or more periods of time.

In several embodiments, the processor 234 or the processor 226 combines activity levels of performance of the one or more activities at the common location over a combined amount of time to generate a combined activity level, e.g., a combined activity level 140₅, a combined activity level 140₆, a combined activity level 140₇, etc., of one or more activities performed at the common location. For example, activity levels of an activity of walking done by the user 112A at a home of the user 112A on the date 308 are combined to generate the combined activity level 140₅. As another

example, activity levels of one or more activities performed during the events 126₁, 126₆, and 126₁₀ are combined to generate the combined activity level 140₅.

The GUI 370 further includes a reverse button 410 and a forward button 412. The user 112A selects the reverse button 410 via the user interface 274 (FIG. 3A) or via the input device 340 (FIG. 5) to view a GUI that displays one or more events, one or more combined activity levels, and/or one or more combined amounts of time on a date prior to the date 308. Similarly, the user 112A selects the forward button 412 via the user interface 274 (FIG. 3A) or via the input device 340 (FIG. 5) to view a GUI that displays one or more events, one or more combined activity levels, and/or one or more combined amounts of time on a date after the date 308.

In various embodiments, the GUI 370 includes a time at which there is a change in an activity level beyond a limit in an amount of time. For example, the GUI 370 includes a wake-up time 414 and a bed time 416. The position sensor 220 (FIG. 3A) determines an amount of activity and based on the amount, the processor 234 or the processor 226 determines whether the amount of activity has crossed the limit in an amount of time. Upon determining that the amount of activity has crossed the limit in an amount of time, the processor 234 or the processor 226 indicates, e.g., highlights, etc., a time at which the level is crossed on the GUI 370. For example, the processor 234 highlights the wake-up time 414 and the bed time 316.

It should be noted that a GUI generated by the processor 234 is displayed on the display device 276 (FIG. 3A), a GUI generated by the processor 302 is displayed on the display device 304 (FIG. 3B), and a GUI generated by the processor 226 is displayed on the display device 352 (FIG. 5).

It should further be noted that in some embodiments, any GUI described herein as being generated by the processor 234 or by the processor 226 for display may instead be generated by the processor 302 of the monitoring device 108B for display on the display device 304.

In some embodiments, event data includes an environmental parameter that is received from the environmental sensor 272 of the monitoring device 108A by the processor 234 (FIG. 3A) or from the environmental sensor 292 of the monitoring device 108B by the processor 302 (FIG. 3B) or from the environmental sensor 272 via the wireless communication device 278 (FIG. 3A) of the monitoring device 108A by the NIC 356 (FIG. 5) of the computing device 166 or from the environmental sensor 292 via the wireless communication device 300 (FIG. 3A) of the monitoring device 108B by the NIC 356 (FIG. 5) of the computing device 166.

In several embodiments, the processor 226 or the processor 234 does not generate event data when an activity of the event data occurs for less than a period of time, e.g., two minutes, three minutes, etc.

In a number of embodiments, the processor 226 or the processor 234 replaces a current location identifier with a previous and a future location identifier when the user 112A is at the previous, current, and future locations within a time limit and when the previous location identifier and the future location identifier are the same. The previous location is a location at which the user 112A was before arriving at the current location. The current location is a location at which the user 112A is before the user 112A arrives at the future location. For example, the processor 234 determines based on the correspondence between one or more geo-locations, one or more positions of the user 112A, and the previous location and based on the correspondence between one or more geo-

locations, one or more positions of the user 112A, and the future location that the previous location and the future location are the same.

In this example, the processor 234 further determines that the current location is different from the previous and future locations and the user 112A has arrived at the previous, current, and future locations within a time limit that is received from the time measurement device 232. In this example, the processor 234 determines that the current location is different from the previous locations based on the correspondence between one or more geo-locations, one or more positions of the user 112A, and the previous location and based on the correspondence between one or more geo-locations, one or more positions of the user 112A, and the future location and based on the correspondence between one or more geo-locations, one or more positions of the user 112A, and the current location. In this example, the processor 234 determines that the current location is the same as the previous and future locations upon determining that the previous and future locations are the same and that the user 112A arrives at the previous, current, and future locations within the time limit.

In several embodiments, the processor 226 or the processor 234 replaces a current activity identifier with a previous and a future activity identifier when the user 112A performs the previous, current, and future activities within a time limit and when the previous activity identifier and the future activity identifier are the same. The previous activity is an activity that the user 112A performs before performing the current activity and the current activity is an activity that the user 112A performs before performing the future activity. For example, the processor 234 determines based on positions of the user 112A and/or geo-location data of the user 112A that the previous activity and the future activity are the same and that the current activity is different from the previous and the future activities. In this example, the processor 234 further determines that the previous, current, and future activities are performed within a time limit that is received from the time measurement device 232. In this example, the processor 234 determines that the current activity is the same as the previous and future activities upon determining that the previous and future activities are the same and that the user 112A performs the previous, current, and future activities within the time limit.

In some embodiments, the processor 226 or the processor 234 applies a Markov model to determine whether to replace the current location identifier that is different from the previous and future location identifiers with the previous or future location identifier. In a number of embodiments, the processor 226 or the processor 234 applies a Markov model to determine whether to replace the current activity identifier that is different from the previous and future activity identifiers with the previous or future activity identifier.

In some embodiments, a user resizes and/or repositions an overlay, e.g., an activity identifier, a location identifier, etc., to improve the precision of an event. For example, an overlay indicates that the user 112A is performing an activity at a first activity level at a time. The user 112A changes a position and/or size of the overlay to indicate that the user 112A is performing the activity at a second activity level at the time. The first and second activity levels are displayed within the same GUI. The user 112A changes a position and/or size of an overlay via an input device of the computing device 166 or via a user interface of a monitoring device.

FIG. 7B is a diagram of a GUI 420 that is generated by executing the method 102 (FIG. 6A), 160 (FIG. 6B), 170 (FIG. 6C), 210 (FIG. 6E), or 221 (FIG. 6F). A map 422 includes a location, e.g., an aquarium, etc., visited by the user

112A and further includes a route to the location. The map 422 is displayed within the GUI 420. The map 422 is generated based on geo-location data. Moreover, the GUI 420 includes a timeline 423 of activities performed by the user 112A on a date 424 of Mar. 1, 2012. The date 424 is displayed within the GUI 420 on top of the map 422.

The user 112A selects the date 424 among multiple dates displayed on top of the map 422 via the user interface 274 (FIG. 3A) of the monitoring device 108A or via the input device 340 (FIG. 5) of the computing device 166. When the date 424 is selected, the processor 234 of the monitoring device 108A (FIG. 3A) generates the GUI 420 to display the GUI 420 on the display device 276 (FIG. 3A) or the processor 226 (FIG. 5) of the computing device 166 generates the GUI 420 to display the GUI 420 on the display device 352 (FIG. 5) of the computing device 166.

The GUI 420 includes events 424₁, 424₂, 424₃, 424₄, 424₅, 424₆, and 424₇. The event 424₄ includes activity levels of an activity performed at the aquarium by the user 112A.

FIG. 7C is a diagram illustrating a method for establishing boundaries between two locations over one or more periods of time. A boundary is a boundary of a location. A boundary also indicates a time at which the user 112A enters or exits a location having the boundary. For example, a boundary A includes outside walls of a home of the user 112A and a time at which the user 112A enters the home or exits the home. As another example, a boundary B includes outside walls of a building where the user 112A works and a time at which the user 112A enters the building or leaves the building. As yet another example, a boundary C includes outside walls of a sandwich shop and a time at which the user 112A enters the sandwich shop or leaves the sandwich shop. As another example, a boundary D includes a line that limits an area of a golf course and a time at which the user 112A enters the golf course or leaves the golf course. As an example, a boundary E includes a body of a vehicle and a time at which the user 112A enters the vehicle or leaves the vehicle.

The processor 234 of the monitoring device 108A (FIG. 3A) or the processor 226 (FIG. 5) of the computing device 166 determines boundaries where the user 112A arrives at, e.g., enters, etc., and departs from, e.g., exits, etc., a location. For example, the processor 234 receives from the device locator 222 (FIG. 3A) a geo-location 1 of the monitoring device 108A. Continuing with the example, the processor 234 determines that the geo-location 1 corresponds to a location 1, e.g., a street, a vehicle, etc., outside a location 2, e.g., a building, a street, etc. The location 2 corresponds to a geo-location 2. The processor 234 determines that the user 112A is at the location 1 at a time tx and at the location 2 at a time ty. In this example, the processor 226 receives the geo-location 1 from the device locator 222 and the geo-location 2 from the device locator 222 and the times tx and ty from the time measurement device 232 (FIG. 3A). In this example, there is a lack of geo-location data of the user 112A between the times tx and ty.

In the example, the processor 234 further determines a speed of an activity of the user 112A performed at the time tx or at the time ty. The processor 234 determines a speed of the user 112A between the times tx and ty. Further, in this example, the processor 234 calculates speed as a ratio of a distance between the geo-locations 2 and 1 and a difference between the times ty and tx. In this example, based on the speed, the processor 226 determines an amount of time taken by the user 112A to reach an entry of the location 2. A geo-location corresponding to the entry of the location 2 is obtained from the device locator 222 by the processor 234 and/or an amount of movement corresponding to the entry of

the location 2 is obtained from the position sensor 220 of the monitoring device 108A, and the entry is determined from geo-location, the amount of movement, and/or the geo-location-location database by the processor 234. In this example, the processor 234 adds the amount of time taken to reach the entry from the time tx to determine a time of entry by the user 112A into the location 2 from the location 1.

It should be noted that the processor 234 of the monitoring device 108A or the processor 226 of the computing device 166 determines geo-location data as located along a straight line between two boundaries. For example, geo-location data is located on a straight line 440 between the boundary A and the boundary B, geo-location data is located on a straight line 442 between the boundary B and the boundary C, and geo-location data is located on a straight line 444 between a point 448 and the boundary D.

In some embodiments, geo-location data is determined for minute time intervals, e.g., times between the times tx and ty, every minute, every fraction of a minute, etc., is compared to the geo-location data on a straight line between two boundaries or between a boundary and a point. The processor 234 or the processor 226 performs the comparison. The geo-location data determined for the minute time intervals may be decimated by the processor 234 or the processor 226. The processor 234 or the processor 226 determines whether a divergence between the geo-location data obtained at the minute time intervals and geo-location data on a straight line between two boundaries exceeds a value. Upon determining that the divergence exceeds the value, the processor 234 or the processor 226 determines that there is a boundary at a point of the divergence.

For example, a divergence between geo-location data on the straight line 440 and geo-location data, obtained at minute time intervals, on a curve 446 exceeds a value. In this example, the boundary A exists at a point of the divergence. On the other hand, upon determining that the divergence does not exceed the value, the processor 234 or the processor 226 determines that there is no boundary at the point of lack of divergence. For example, a divergence between geo-location data on the straight line 444 and geo-location data, obtained at minute time intervals, on a straight line 446 does not exceed the value. In this example, there is no boundary formed at the point 448 at which the lines 444 and 446 start to intersect.

FIG. 7D is a diagram of a GUI 460 to illustrate a method of allowing a user to choose a location in case of common geo-locations between multiple locations. The GUI 460 is generated by executing the method 221 (FIG. 6F). As shown in the GUI 460, the processor 234 or the processor 226 determines that a location 462 and a location 464 has one or more common geo-locations 466. The locations 462 and 464 may be determined by the processor 226 or the processor 234 based on the geo-location-location database. The processor 234 generates a prompt and displays the prompt via the display device 276 (FIG. 3A) to the user 112A. Similarly, the processor 226 generates the prompt to display via the display device 352 (FIG. 5). The prompt indicates to the user 112A to select the location 462 or the location 464 as a location corresponding to the geo-locations 466. The user 112 selects via the user interface 274 (FIG. 3A) or via the input device 340 (FIG. 5) the location 462 or the location 464 as corresponding to the geo-locations 466. Upon receiving the selection of the location 462 or the location 464, the processor 226 or the processor 234 associates the selected location to correspond to the geo-locations 466.

In various embodiments, instead of a prompt, a notification, e.g., a prompt, an email, an update, an increment in a number, a message, etc., is generated to display on a display device.

In several embodiments, a notification includes an invitation to meet at a location to perform one or more activities at the location. For example, an invitation is sent from the user account 912 to the user account 174 requesting the user 112A permission to meet at a location, e.g., park, gym, etc., to perform an activity, e.g., swim, run, walk, etc. The user 112A may accept or reject the invitation via the user account 174.

In various embodiments, a notification includes a request for permission to post data that the user 112B is performing an activity at a location with the user 112A. For example, the request includes a permission to indicate that user 112B is walking with the first user 112B at a park. As another example, the request includes a permission to indicate that user 112B is exercising with the first user 112B at a gym. The permission may include a website on which the data is to be posted. The website may be a social network website, a web site owned by the user 112B, or a website that is associated with maintaining event data, e.g., a website having the web address 1, a website having the web address 2, or a website having the web address 3, etc.

In some embodiments, the user 112A expands a size of the location 462 via the user interface 274 (FIG. 3A) to indicate to include one or more geo-locations within the location 466 to indicate to the processor 226 that the one or more geo-locations within the location 466 are within the location 462. The processor 226 then associates the one or more geo-locations with the location 462 instead of with the location 466.

In various embodiments, one or more geo-locations are located outside the location 466. The user 112A expands a size of the location 462 via the user interface 274 (FIG. 3A) to indicate to include the one or more geo-locations to indicate to the processor 226 that the one or more geo-locations are within the location 462. The processor 226 then associates the one or more geo-locations with the location 462.

FIG. 7E is a diagram of an embodiment of a web page 470 that includes the GUI 394 that further includes the events 128₁, 128₂, 128₃, 128₄, 128₅, and 128₆. The GUI 394 is similar to the GUI 370 (FIG. 7A) except that the GUI 394 is displayed within the web page 470 and the GUI 394 includes a time 337 of exit by the user 112A of his/her home. In some embodiments, the GUI 394 includes a time of entry or exit by the user 112A of a location.

A web page is displayed when the wireless communication device 278 (FIG. 3A) or a wired communication device of the monitoring device 108A sends a request for the web page to the server 228 via the network 176 without using the computing device 166 (FIG. 3A). In some embodiments, the request for a web page is sent from the NIC 356 of the computing device 166 via the network 176 to the server 228.

Upon receiving the request for a web page, the server 228 sends the web page via the network 176 to the computing device 166. The NIC 356 of the computing device receives a web page and the web page is displayed on the display device 352 (FIG. 5) of the computing device 166.

Similarly, in some embodiments, upon receiving the request for a web page, the server 228 sends the web page via the network 176 to the monitoring device 108A. The wireless communication device 278 (FIG. 3A) or a wired communication device of the monitoring device 108A receives a web page and the web page is displayed on the display device 276 (FIG. 3A) of the monitoring device 108A.

FIG. 7F is a diagram of an embodiment of a zoom-in 496 of a portion 502 of a GUI 498. The GUI 496 is generated by

executing the method 102 (FIG. 6A), 160 (FIG. 6B), 170 (FIG. 6C), or 210 (FIG. 6E). In some embodiments, the zoom-in 496 is displayed on the display device 276 (FIG. 3A) of the monitoring device 108A or on the display device 352 (FIG. 5) of the computing device 166. The zoom-in 496 is displayed when the user 112A selects the portion 502 via the user interface 274 (FIG. 3A) or via the input device 340 (FIG. 5).

FIG. 7G is a diagram of an embodiment of a daily journal GUI 510. The daily journal GUI 510 is generated when the processor 234 or the processor 226 combines one or more GUIs 512, 514, 516, and 518. Each GUI 512, 514, 516, and 518 is generated by executing the method 102 (FIG. 6A), 160 (FIG. 6B), 170 (FIG. 6C), or 210 (FIG. 6E). The GUIs 512, 514, 516, and 518 have chronologically-ordered dates of one or more activities performed by the user 112A at one or more locations over one or more periods of time. In some embodiments, the GUIs 512, 514, 516, and 518 have consecutive dates, which are dates of activities performed by the user 112A. The daily journal GUI 510 is displayed by the processor 234 on the display device 276 (FIG. 3A) of the monitoring device 108A or is displayed by the processor 226 on the display device 352 (FIG. 5) of the computing device 166.

Each GUI 512, 514, 516, and 518 is displayed in a row. In some embodiments, each GUI 512, 514, 516, and 518 is displayed in a column or parallel to an oblique line.

FIG. 7H is a diagram of an embodiment of a daily journal GUI 520. The daily journal GUI 520 is generated when the processor 234 or the processor 226 combines one or more GUIs 522, 524, 526, and 528. Each GUI 522, 524, 526, and 528 is generated by executing the method 102 (FIG. 6A), 160 (FIG. 6B), 170 (FIG. 6C), or 210 (FIG. 6E). The GUIs 522, 524, 526, and 528 have chronologically-ordered dates of one or more activities performed by the user 112A at one or more locations over one or more periods of time. In some embodiments, the GUIs 522, 524, 526, and 528 have consecutive dates, which are dates of activities performed by the user 112A. The daily journal GUI 520 is displayed by the processor 234 on the display device 276 (FIG. 3A) of the monitoring device 108A or is displayed by the processor 226 on the display device 352 (FIG. 5) of the computing device 166.

Each GUI 522, 524, 526, and 528 is displayed in an orderly fashion.

FIG. 7I is a diagram of an embodiment of a GUI 530 that provides an overview of one or more activities 538 performed by the user 112A at one or more locations 540 over a period of time. The activities 538 are graphical elements. Similarly, the locations 540 are graphical elements. The GUI 530 is generated by executing the method 102 (FIG. 6A), 160 (FIG. 6B), 170 (FIG. 6C), or 210 (FIG. 6E). The GUI 530 also includes a time line 542 that shows a relationship of time periods, e.g., a night time period, a day time period, etc., with performance of the activities 538 and the locations 540. The activities 538, the locations 540, and the time line 542 are aligned with respect to each other along a column 550. The locations 540 include one or more location/activity identifiers 544₁, 544₂, 544₃, and 544₄.

The activities 538 include a sedentary activity 546₁, a sedentary activity 546₂, a sedentary activity 546₃, a sedentary activity 546₄, a sedentary activity 546₅, a sedentary activity 546₆, a sedentary activity 546₇, and a sedentary activity 546₈. The activities 538 further include a lightly active activity 536₁, a lightly active activity 536₂, a lightly active activity 536₃, a lightly active activity 536₄, a lightly active activity 536₅, a lightly active activity 536₆, and a lightly active activity 536₇. The activities 538 further

includes a moderately active activity 534₁, a moderately active activity 534₂, a moderately active activity 534₃, and a highly active activity 532.

It should be noted that an activity level of the sedentary active activity is lower than an activity level of the lightly active activity. An activity level of the lightly active activity is lower than an activity level of the moderately active activity and an activity level of the moderately active activity is lower than an activity level of the highly active activity. For example, a number of calories burned during the sedentary active activity is lower than a number of calories burned during the lightly active activity, a number of calories burned during the lightly active activity is lower than a number of calories burned during the moderately active activity, and a number of calories burned during the moderately active activity is lower than a number of calories burned during the highly active activity. As another example, an amount of activity performed at the sedentary active activity is lower than an amount of activity performed at the lightly active activity, an amount of activity performed at the lightly active activity is lower than an amount of activity performed at the moderately active activity, and an amount of activity performed at the moderately active activity is lower than an amount of activity performed at the highly active activity.

Each activity is vertically aligned with a location. For example, the sedentary activity 546₁ is vertically aligned with the location 544₁. As another example, the lightly active activity 536₁ is vertically aligned with the locations 544₁ and 544₂.

In some embodiments, when an activity is aligned, e.g., vertically, horizontally, etc. with a location, the activity is performed at the location. For example, the monitoring device 108A worn by the user 112A captures positions used to determine an activity performed within a home of the user 112A.

Moreover, it should be noted that although four activities are shown in FIG. 7I, in some embodiments, any number of activities may be shown. Furthermore, in some embodiments, the activities 538, the locations 540, and the time line 542 are aligned with respect to each other along a row instead of the column 550. For example, each of the activities 538, the locations 540, and the time line 542 are made vertical instead of horizontal to be aligned with respect to each other along a row.

A cursor 552 is displayed on the GUI 530 by the processor 226 or by the processor 234. When the user 112A uses the user interface 274 (FIG. 3A) or the input device 340 (FIG. 5) to point the cursor 552 to a portion of the activities 538 and selects the portion, a progressively detailed GUI 560 is displayed. The GUI 560 is displayed in FIG. 7J.

FIG. 7J is a diagram of an embodiment of the GUI 560. The GUI 560 is generated by executing the method 102 (FIG. 6A), 160 (FIG. 6B), 170 (FIG. 6C), or 210 (FIG. 6E). The GUI 560 includes a detailed view of the activities 538 (FIG. 7I). The detailed view is shown as activities 580. For example, the GUI 560 includes a detailed view of each activity level of the GUI 530 (FIG. 7I). To illustrate, the highly active activity 532 (FIG. 7I) is detailed as one or more highly active activity levels 582₁ and 582₂ of the activity. As another illustration, the sedentary activities 546₁ thru 546₈ are detailed as one or more sedentary activity levels 562₁, 562₂, 562₃, 562₄, 562₅, 562₆, 562₇, and 562₈. As yet another illustration, the lightly active activities 536₁ thru 536₇ are detailed as one or more lightly active activity levels 564₁, 564₂, 564₃, 564₄, 564₅, 564₆, 564₇, and 564₈. As another illustration, the moderately active activities 534₁ thru 534₃ are detailed as one or more

moderately active activity levels **566**₁, **566**₂, **566**₃, and **566**₄. In some embodiments the activities **580** are graphical elements.

In some embodiments, each location/activity identifier of the GUI **530** is detailed by the processor **226** or by the processor **234** into a detailed location/activity identifier within the GUI **560**. For example, a building identifier within the GUI **530** is detailed, within the GUI **560** into one or more rooms of the building when the user **112A** uses the user interface **274** (FIG. 3A) or the input device **340** (FIG. 5) to point the cursor **552** to a portion of the locations **540** (FIG. 7I) and to select the portion.

In various embodiments, the GUI **560** includes a detailed view, which includes one or more activity levels, of an activity of the GUI **530**. The activity of the GUI **530** is one at which the user **112A** points to and selects with the pointer **552**. In some embodiments, the GUI **560** includes a detailed location/activity identifier of a location/activity identifier, on the GUI **530**, at which the user **112A** points to and selects with the pointer **552**.

FIG. 7K is a diagram of an embodiment of the GUI **574**. The GUI **574** is the same as the GUI **560** (FIG. 7J) except that the GUI **574** shows a more detailed view of one or more activities performed by the user **112A**, of a time period during which the activities are performed, and/or of a location at which the activities are performed, compared to that shown in the GUI **560**. For example, when the user **112A** uses the user interface **274** (FIG. 3A) or the input device **340** (FIG. 5) to point the cursor **552** to a portion, e.g., an activity level **582**₁ (FIG. 7J), etc., of the activities **580** (FIG. 7J) and to select the portion, a detailed view of the portion is displayed within the GUI **574**. To illustrate, the detailed view of the portion includes a graphical element **588** that displays a time at which the activity level **582**₁ occurs, a location/activity identifier **590** identifying an activity, e.g., walking, running, etc., performed at a location by the user **112A**. The activity level **582**₁ and an activity level **582**₂ are portions of an activity level **582**.

The detailed view further includes text **592** that describes the activity, having the activity level **582**₁, performed by the user **112A**, time of occurrence of the activity, and activity data, e.g., number of steps, calories burned, etc., of the activity. The detailed view further includes a location/activity identifier **594** that represents a location closest to a location of performance of the activity identified by the location/activity identifier **590**. For example, the location/activity identifier **594** is a home icon of a home of the user **112A** and the home is at a location closest to a location where the user **112A** walks a dog. The detailed view further includes text **596** describing a location identified by the location/activity identifier **594**. The graphical element **588**, the location/activity identifier **590**, and the location/activity identifier **594** are aligned along a line **598**. In some embodiments, the graphical element **588**, the location/activity identifier **590**, and the location/activity identifier **594** are not aligned with respect to each other. In various embodiments, the detailed view excludes the text **592** and/or excludes the text **596**. In several embodiments, the detailed view excludes the location/activity identifier **590** and/or excludes the location/activity identifier **596**. The GUI **574** is generated by executing the method **102** (FIG. 6A), **160** (FIG. 6B), **170** (FIG. 6C), or **210** (FIG. 6E).

FIG. 7L is a diagram illustrating an embodiment of a method of combining activity levels over a period of time. The method of combining activity levels over a period of time is performed by the processor **226** or by the processor **234**. In the method of combining activity levels, a GUI **602** is displayed by the processor **226** or by the processor **234**.

The GUI **602** includes a display **604**₁ of activity levels of a number of activities, e.g., an activity 1, an activity 2, and an activity 3, etc. performed by the user **112A** during a day 1. The activities shown in the display **604**₁ are performed in the order shown. For example, the activity 1 is performed during the day 1 before the activity 2 is performed during the day 1 and the activity 2 is performed during the day 1 before the activity 3 is performed during the day 1.

Moreover, the GUI **602** includes a display **604**₂ of activity levels of a number of activities, e.g., an activity 2, an activity 1, and an activity 3, etc. performed by the user **112A** during a day 2. The activities shown in the display **604**₂ are performed in the order shown. For example, the activity 2 is performed during the day 2 before the activity 1 is performed during the day 2 and the activity 1 is performed during the day 2 before the activity 3 is performed during the day 2.

The user **112A** uses the user interface **274** (FIG. 3A) or the input device **340** (FIG. 5) to point the cursor **552** to the activity 1 performed during the day 1 to select the activity 1 performed during the day 1 and drag the activity 1 performed during the day 1 to a GUI **606**, which is an activity filter. The user **112A** then uses the user interface **274** (FIG. 3A) or the input device **340** (FIG. 5) to point the cursor **552** to the activity 1 performed during the day 2 to select the activity 1 performed during the day 2 and drag the activity 1 performed during the day 2 to the GUI **606**. In some embodiments, the processor **226** or the processor **234** receives a selection from the user **112A** via the user interface **274** (FIG. 3A) or the input device **340** (FIG. 5) of the activity 1, the activity 2, or the activity 3 over a period of time, e.g., day 1, day 2, etc., within the GUI **602** and the processor **234** drags the activities performed during the period of time to present in the GUI **606**.

When the user **112A** uses the user interface **274** (FIG. 3A) or the input device **340** (FIG. 5) to point the cursor **552** to the activity 1 performed during the day 1 within the GUI **606** and selects the activity 1 performed during the day 1 or to point the cursor **552** to the activity 1 performed during the day 2 and selects the activity 1 performed during the day 2 within the GUI **606**, a GUI **608** is generated and displayed. The GUI **608** includes an aggregate, e.g., total, etc., activity level **609** of the activity 1 performed during the day 1 and includes an aggregate activity level **610** of the activity 1 performed during the day 2. Any aggregation of activity levels is performed by the processor **226** or by the processor **234**.

In some embodiments, upon receiving the selection of the activity 1, the activity 2, or the activity 3 over a period of time, e.g., day 1, day 2, etc., within the GUI **602**, the processor **226** or the processor **234** generates a GUI, e.g., the GUI **608**, having aggregate activity levels of the activity over the period of time for which the activity is selected.

FIG. 7M is a diagram of an embodiment of a GUI **614** that describes an aggregate level of one or more activities performed by the user **112A** over a period of time. The processor **226** or the processor **234** determines an aggregate amount of an activity performed by the user **112A** over a period of time. The processor **234** or the processor **234** generates a simplified description of the aggregate amount of the activity and displays the simplified description on a corresponding display device. For example, when the user **112A** selects a tab **616** via the user interface **274** (FIG. 3A) or the input device **340** (FIG. 5), simplified descriptions **620**, **622**, and **624** are displayed within the GUI **614** for one or more periods of time. The simplified description **620** is of activities performed by the user **112A** on Thursday, March 1, the simplified description **622** is of activities performed by the user **112A** on Friday, March 2, and the simplified description **624** is of activities performed by the user **112A** on Saturday, March 3.

Each simplified description of activities performed during a period of time is displayed besides a corresponding sequence of events occurring during the period of time. For example, the simplified description 620 of activities performed on Thursday, March 1 is displayed besides one or more events 626 occurring on Thursday, March 1.

FIG. 7N is a diagram of an embodiment of a pie-chart 650 of locations at which the user 112A performs one or more activities and of percentages of activity levels at the locations over a period of time. The period of time is represented by the pie-chart 650. The pie-chart 650 is generated by the processor 226 or the processor 234.

The pie-chart 650 is segmented into a location 652, a location 654, a location 656, an activity 658, an activity 660, an activity 662, and a location/activity 664. When the user 112A is at the location 652, the user 112A has an activity level of 666. Similarly, when the user 112A is at the location 654, the user 112A has an activity level of 668. When the user 112A is at the location 656, the user 112A has an activity level of 670. Moreover, when the user 112A is performing the activity 658, the user 112A has an activity level of 672. When the user 112A is performing the activity 660, the user 112A has an activity level of 674. Also, when the user 112A is performing the activity 662, the user 112A has an activity level of 676. When the user 112A is performing the activity 664 or is at the location 664, the user 112A has an activity level of 678.

In some embodiments, an activity level of an activity performed at a location by the user 112A is determined by the processor 226 or the processor 234 in terms of a percentage of an amount of activity that would have been performed at the location. For example, the processor 226 or 234 determines that a maximum amount of activity that can be performed by the user 112A or any other user at the location 652 is n . The processor 226 or 234 receives an amount of activity actually performed by the user 112A as m . The processor 226 or 234 determines a percentage $(m/n) \times 100$ as the activity level 666.

In various embodiments, any other type of graph, e.g., a bar graph, a line graph, etc., is generated by the processor 226 or the processor 234 instead of a pie chart.

FIG. 7O is a diagram of an embodiment of a GUI 690 that includes an overlay of a map 692 on one or more locations 696, 698, and 700 that the user 112A visits during a period of time to perform one or more activities 701, 702, 704, and 708 performed by the user 112A during the period of time. The GUI 690 is generated by the processor 226 or by the processor 234. The GUI 690 is generated by executing the method 221 (FIG. 6F).

The GUI 690 includes a map 692 of a path traveled by the user 112A during a period of time, text describing the locations 696, 698, and 700 and text describing the activities 701, 702, 704, and 708.

In some embodiments, instead of text describing the locations 696, 698, and 700, one or more graphical elements or a combination of the graphical elements and text describing the locations are used within the GUI 690 to indicate the locations. In various embodiments, instead of text describing the activities 701, 702, 704, and 708, one or more graphical elements or a combination of the graphical elements and text describing the activities are used within the GUI 690 to indicate the activities.

In a number of embodiments, the one or more locations 696, 698, and 700 are overlaid on the map 692.

FIG. 7P is a diagram of an embodiment of a web page 714 that illustrates that a map 732 is overlaid on the event region 730 to indicate a geo-location of the user 112A at a time, e.g., an hour, a minute, etc., within a time period in which the user 112A performs one or more activities. The web page 714

includes a GUI 716 that further includes the map 732 and the event region 730. When the user 112A selects a time, e.g., 11 AM, NOON, 1 PM, etc., on the GUI 370 (FIG. 7A) via the user interface 274 (FIG. 3A) or the input device 340 (FIG. 5), a map, e.g., the map 732, etc., is overlaid by the processor 226 or the processor 234 on the GUI 370 to indicate a geo-location of the user 112A at the time. For example, the geo-location is indicated by centering the map at the geo-location of the user 112A at the time.

The GUI 716 is generated by executing the method 102 (FIG. 6A), 160 (FIG. 6B), 170 (FIG. 6C), or 210 (FIG. 6E) in combination with the method 221 (FIG. 6F).

In some embodiments, the event region 730 is overlaid on the map 732.

FIG. 7Q is a diagram of an embodiment of a GUI 750 that includes a map 752 below an event region 754. The GUI 750 is generated by the processor 226 or the processor 234. The event region 754 includes one or more location/activity identifiers 754₁, 754₂, 754₃, 754₄, 754₅, and 754₆ of locations visited by the user 112A during a period of time. Moreover, the event region 754 includes graphical elements and/or text that represent one or more activities 756₁, 756₂, 756₃, 756₄, and 756₅ performed by the user 112A during the period of time.

The GUI 750 further includes links 758₁, 758₂, 758₃, 758₄, 758₅, 758₆, 758₇, 758₈, and 758₉ between a set including one or more geo-locations 760₁, one or more geo-locations 760₂, one or more geo-locations 760₃, one or more geo-locations 760₄, one or more geo-locations 760₅, and one or more geo-locations 760₆ on the map 752 and a set including one or more of the location/activity identifiers 754₁, 754₂, 754₃, 754₄, 754₅, and 754₆ and/or one or more of the activities 756₁, 756₂, 756₃, 756₄, and 756₅. For example, the link 758₁ is established between the one or more geo-locations 760₁ and the location 754₁.

The GUI 750 is generated by executing the method 102 (FIG. 6A), 160 (FIG. 6B), 170 (FIG. 6C), or 210 (FIG. 6E) in combination with the method 221 (FIG. 6F).

In some embodiments, a geo-location is represented as a graphical element and/or as text by the processor 226 or by the processor 234.

In some embodiments, the map 752 is placed by the processor 236 or the processor 234 at any other place, e.g., above, to the left of, to the right of, etc., with respect to the event region 754.

FIG. 7R is a diagram of an embodiment of a web page 770 that is used to illustrate an overlay of event data on a map 774. A map is accessed by the processor 234 of the monitoring device 108A via the wireless communication device 278 (FIG. 3A) or a wired communication device of the monitoring device 108A and the network 176 (FIG. 3A) from the geo-location-location database of the server 228 (FIG. 3A) or another server without using the computing device 166 (FIG. 3A). In some embodiments, the map 774 is accessed by the processor 234 of the monitoring device 108A via the wireless communication device 278 (FIG. 3A) or a wired communication device of the monitoring device 108A, the computing device 166, and the network 176 (FIG. 3A) from the geo-location-location database of the server 228 (FIG. 3A) or another server. In a number of embodiments, the map 774 is accessed by the processor 226 of the computing device 166 via the NIC 356 (FIG. 5) of the computing device 166 and via the network 176 (FIG. 3A) from the geo-location-location database of the server 228 (FIG. 3A) or another server.

The web page 770 includes a GUI 772 that is displayed by the processor 226 or the processor 234. The GUI 772 is generated by the processor 226 or the processor 234. The GUI

772 is generated by executing the method 102 (FIG. 6A), 160 (FIG. 6B), 170 (FIG. 6C), or 210 (FIG. 6E) in combination with the method 221 (FIG. 6F).

The map 774 includes one or more geo-locations, names of landmarks accessed from the geo-location-location database, names of public places accessed from the geo-location-location database, names of streets accessed from the geo-location-location database, names of geo-locations accessed from the geo-location-location database, or a combination thereof, etc.

The event data is overlaid on the map 774 by the processor 226 or by the processor 234. The event data includes one or more of a location/activity identifier 776₁, e.g., a home identifier, etc., a location/activity identifier 776₂, e.g., an identifier of a bus, etc., a location/activity identifier 776₃, e.g., an identifier of a railway station, etc., a location/activity identifier 776₄, e.g., a vehicle identifier, etc., a location/activity identifier 776₅, e.g., a work location/activity identifier, etc., of locations visited by the user 112A during a period of time and an activity identifier 778₁ of an activity, e.g., walking, etc., performed by the user 112A during the period of time. The event data further includes a path 780 taken by the user 112A during the period of time in visiting the locations having the location/activity identifiers 776₁, 776₂, 776₃, 776₄, and 776₅ and in performing an activity, e.g., walking, etc., represented by the activity identifier 778₁.

In some embodiments, the event data includes activity data of any number of activities performed by the user 112A.

In several embodiments, the map 774 is overlaid on the event data.

In various embodiments, the activity identifier 778₁, the path 780, and/or the location/activity identifiers 776₁, 776₂, 776₃, 776₄, and 776₅ are color-coded by the processor 226 or the processor 234. For example, the processor 226 or the processor 234 assigns a different color to the identifier 778₁, than to one or more of the location/activity identifiers 776₁, 776₂, 776₃, 776₄, and 776₅, and the path 780. As another example, the processor 226 or the processor 234 assigns a different color to the location/activity identifier 776₁ than to one or more of the location/activity identifiers 776₂, 776₃, 776₄, and 776₅. As another example, the processor 226 or the processor 234 assigns a different color to the path 780 than to one or more of the location/activity identifiers 776₁, 776₂, 776₃, 776₄, and 776₅.

In some embodiments, the activity identifier 778₁, the path 780, and/or the location/activity identifiers 776₁, 776₂, 776₃, 776₄, and 776₅ are coded by the processor 226 or the processor 234 by using graphical properties. For example, the processor 226 or the processor 234 assigns a different graphical property to the activity identifier 778₁ than to one or more of the location/activity identifiers 776₁, 776₂, 776₃, 776₄, and 776₅, and the path 780. As another example, the processor 226 or the processor 234 assigns a different graphical property to the location/activity identifier 776₁ than to one or more of the location/activity identifiers 776₂, 776₃, 776₄, and 776₅. As another example, the processor 226 or the processor 234 assigns a different graphical property to the path 780 than to one or more of the location/activity identifiers 776₁, 776₂, 776₃, 776₄, and 776₅.

FIG. 7S is a diagram of an embodiment of the web page 770 that is used to illustrate a zoom-in 790 of a portion of the map 774 and of event data of an event that occurs at the portion. When the user 112A uses the user interface 274 (FIG. 3A) or the input device 340 (FIG. 5) to point the cursor 552 to the activity identifier 778₁, the processor 226 or the processor 234 generates the zoom-in 790 to display the zoom-in 790. In some embodiments, a zoom-in is an example of a GUI.

The zoom-in 790 includes a detailed display 792 associated with the activity identifier 778₁ of an activity performed by the user 112A at one or more geo-locations close to, e.g., within a vicinity of, within a radius of, etc., a location having the location/activity identifier 776₅. The detailed display 792 includes a distance traveled by the user 112A close to a location having the location/activity identifier 776₅, a number of steps taken by the user 112A close to the location, and a textual description of an activity that is identified by the activity identifier 778₁ and that is close to, e.g., with a radius of, etc., the location.

In some embodiments, the zoom-in 790 includes any other activity data, e.g., a number of calories burned by the user 112A close to a location having the location/activity identifier 776₅, an amount of golf swings taken by the user 112A close to the location, etc.

FIG. 7T is a diagram of an embodiment of a web page 751 that includes a GUI 759. The GUI 759 includes an overlay of a map 753 on a user's path 755. The user's path 755 is a path traveled by the user 112A during a period of time. The user's path 755 is coded to distinguish various locations and/or activities along the user's path 755. For example, a bus station is provided a different color by the processor 234 or by the processor 226 than that provided to a railway station. As another example, a walking activity of the user 112A along the user's path 755 is provided a different shade, text, and/or color by the processor 234 or by the processor 226 than that provided to a running activity of the user 112A along the user's path 755. The GUI 759 is generated by executing the method 102 (FIG. 6A), 160 (FIG. 6B), 170 (FIG. 6C), or 210 (FIG. 6E) in combination with the method 221 (FIG. 6F).

In some embodiments, the user's path 755 is overlaid on the map 753.

FIG. 7U is a diagram of an embodiment of a zoom-in 757 that includes a zoom-in of a portion of the user's path 755. The zoom-in 757 is generated when the user 112A points the cursor 552 (FIG. 7I) on a portion of the user's path 755 and selects the portion. The zoom-in 757 is of the portion of the user's path 755. The zoom-in 757 includes activity data, e.g., number of steps walked by the user 112A within the portion, a distance covered by the user 112A within the portion, and a type of activity, e.g., walking, running, etc., performed by the user 112A within the portion.

FIG. 7V is a diagram of an embodiment of the GUI 759 except that the GUI 759 indicates that a portion of the user's path 758 at which the user 112A takes bus to a train is coded differently than a portion of the user's path 758 at which the user 112A is traveling to work on a train and differently than a portion of the user's path 758 where the user 112A is walking around near his/her office.

FIG. 8 is a diagram of an embodiment of one or more location/activity identifiers 802₁, 802₂, and 802₃, and one or more activity identifiers 804₁, 804₂, and 804₃. Each identifier 802₁, 802₂, 802₃, 804₁, 804₂, and 804₃ includes a pointer. For example, the identifier 802₁ includes a pointer 806. In some embodiments, each identifier excludes a pointer.

FIG. 9A is a diagram of an embodiment of a method 900 for sharing information between various user accounts based on locations and activities performed by users. The method 900 is performed by the server 228, or by a virtual machine, or a combination thereof.

The method 900 includes an operation 902 of determining a location of a first monitoring device used by the user 112A while the user 112A is performing an activity. For example, it is determined whether the user 112A is in a gym or at a park or at his home or at work. In some embodiments, the determination 902 is made based on one or more geo-locations of

the user 112A, an activity performed by the user 112A, or a combination thereof. The operation 902 is executed by a processor of the server 228.

The method 900 further includes an operation 904 of determining a location of a second monitoring device used by the user 112B while the user 112B is performing an activity. The operation 904 is executed by a processor of the server 228.

The method 900 further includes an operation 906 of determining whether the location of the first monitoring device is within a threshold distance of the location of the second monitoring device. For example, it is determined whether the user 112A and the user 112B are within the same gym. As another example, it is determined whether the user 112A and 112B are at a home of the user 112A. As yet another example, it is determined whether the user 112A and 112B are in the same park. As another example, it is determined whether a geo-location of the user 112A is within a threshold distance of a geo-location of the user 112B. As another example, it is determined whether the location of the first monitoring device is the same as the location of the second monitoring device. The operation 906 is performed by a processor of the server 228.

In some embodiments, a location of the first monitoring device is the same as the location of the second monitoring device when both the locations are located at the same address, or at the same cross streets, or include the same geo-locations, or a combination thereof.

Upon determining that the location of the first monitoring device is not within the threshold distance of the location of the second monitoring device, the method 900 ends. On the other hand, upon determining that the location of the first monitoring device is within the threshold distance of the location of the second monitoring device, an operation 908 of the method 900 is performed. The operation 908 is performed by a processor of the server 228.

In the operation 908, it is determined whether the activity performed by the user 112A using the first monitoring device is similar to the activity performed by the user 112B using the second monitoring device. For example, it is determined whether a combined activity level of the user 112A over a time period is within a pre-determined range of a combined activity level of the user 112B over the time period. To illustrate, it is determined whether a number of calories burnt by the user 112A within an hour is within a pre-determined range of a number of calories burnt by the user 112B within one hour. As another illustration, it is determined whether a number of steps taken by the user 112A within half an hour is within a pre-determined range of a number of steps taken by the user 112B within half an hour. As yet another illustration, it is determined whether a metric determined from an activity performed by the user 112A is within a pre-determined range of a metric determined from an activity performed by the user 112B.

In some embodiments, a combined activity level is generated by a processor of the server 228 by adding activity levels over a time period. In various embodiments, a combined activity level is generated by a processor of the server 228 by determining a maximum value of all activity levels within the time period. In several embodiments, a combined activity level is generated by a processor of the server 228 by determining an average of activity levels within the time period.

As another example of similarity between activities, it is determined whether both the users 112A and 112B are performing the same activity. To illustrate, it is determined whether both the users 112A and 112B are walking. As another illustration, it is determined whether both the users

112A and 112B are running or exercising. As yet another illustration, it is determined whether both the users 112A and 112B are swimming.

Upon determining that the activity performed by the user 112A while using the first monitoring device is not similar to the activity performed by the user 112B while using the second monitoring device, the method 900 ends. On the other hand, upon determining that the activity performed by the user 112A is similar to the activity performed by the user 112B, an operation 910 of the method 900 is performed. The operation 910 is performed by a processor of the server 228.

In the operation 910, a prompt is generated and provided to the first monitoring device to ask for permission from a first user account, e.g., the user account 174 of the user 112A, etc., to allow a second user account, e.g., the user account 912 (FIG. 2A) of the second user 112B, etc., to access information from the first user account regarding the activity of the user 112A. The activity is performed by the user 112A while the user 112A is wearing the first monitoring device. For example, a processor of the server 228 sends via a NIC of the server 228 and the network 176 (FIG. 2A) the prompt to the first monitoring device. In this example, the prompt requests that the user account 912 be provided access to activity levels of the user 112A. The activity levels are of the activity performed while the user 112A is at the location determined in the operation 902. As another example, a processor of the server 228 sends the prompt to the user account 174 displayed on the first monitoring device and the prompt requests permission from the user 112A to allow metrics of the activity performed by the user 112A to be displayed within the user account 912. The activity is performed by the user 112A at the location determined in the operation 902.

Examples of information regarding the activity of the user 112A includes an activity level of the activity, a metric of the activity, an activity identifier that identifies the activity performed by the user 112A, a location identifier that identifies a location of the first user 112A while performing the activity, or a combination thereof. Another example of information regarding the activity of the user 112A is information 916, which is shown in FIG. 11. Information 916 includes a number of steps taken by the user 112A.

Continuing further with FIG. 9A, when permission is received by the server 228 from the user 112A via the first user account, the information from the first user account is sent to the second user account for display via the second user account on the second monitoring device. For example, a processor of the server 228 receives the permission via a communication of a monitoring device and the network 176 and a NIC of the server 228. In this example, a processor of the server 228 sends the information regarding the activity performed by the user 112A from the first user account via a NIC of the server, the network 176 and a communication device of the second monitoring device to be displayed within a representation of the second user account on a display device of the second monitoring device. An example of the representation of the user account 912 is a representation 914 shown in FIG. 11.

Continuing with FIG. 9A, in some embodiments, when the users 112A and 112B are social network friends, the operation 910 may not be performed. For example, a processor of the server 228 requests a server of a social network to indicate whether the user 112A is a social network friend of the user 112B. Upon receiving a response from the social network server indicating that the user 112A and the user 112B are social network friends, the information regarding the activity performed by the user 112A from the first user account is sent to the second user account for display via the second user

53

account on the second monitoring device. The information is sent without requesting the permission from the first user account.

The method **900** ends after the operation **910**.

FIG. **9B** is a diagram of an embodiment of a method **922** for sharing information between various user accounts based on locations of users. The method **922** is performed by the server **228**, or by a virtual machine, or a combination thereof.

In the method **922**, the operations **902**, **904** and **906** are performed.

Moreover, the operation **910** is performed upon determining that the location of the first monitoring device is not within the threshold distance of the location of the second monitoring device.

FIG. **10** is a flowchart of an embodiment of a method **940** for recommending a change in activity performed by the user **112A** and/or a change to a location at which the activity is performed by the user **112A** based on an activity level of the user **112A**. The method **940** is performed by the server **228**, or a virtual machine, or a combination thereof.

In the method **940**, the operations **902**, **904**, and **906** are performed. Moreover, an operation **928** is performed by a processor of the server **228** upon determining that the location of the first monitoring device within the threshold distance of the location of the second monitoring device. In some embodiments, a threshold distance includes a defined distance. In the operation **928**, an activity level associated with the first monitoring device is determined. The activity level is of one or more activities performed by the user **112A** while the user **112A** is at the location determined in the operation **902** and is using the first monitoring device. For example, a number of steps of the user **112A** who wears the first monitoring device at the location determined in the operation **902** is determined. As another example, a number of calories burned by the user **112A** while wearing the first monitoring device is determined. As another example, a number of laps taken in a swimming pool by the user **112A** while wearing a monitoring device is determined. An example of the activity level determined in the operation **928** is illustrated as an activity level **936** in FIG. **12**.

Continuing further with FIG. **10**, the activity level is determined in the operation **928** over a period of time. For example, a statistical value of activity levels of one or more activities performed by the user **112A** over a period of time while the user **112A** is at the location is determined. In this example, the location is determined in the operation **902**. Examples of the statistical value of activity levels include an average of activity levels, or a maximum of activity levels, or a minimum of activity levels, or a median of activity levels, or a combination thereof.

In some embodiments, instead of determining an activity level, the activity level is received from a monitoring device by a processor of the server **228** via a communication device of the monitoring device, the network **176**, and a NIC of the server **228**.

In various embodiments, upon determining that the location of the first monitoring device is within the threshold distance of the second monitoring device, the operation **908** of determining whether the activity performed by the user **112A** using the first monitoring device is similar to the activity performed by the user **112B** using the second monitoring device is performed. Upon determining that the activities are not similar, the method **940** ends. On the other hand, upon determining that the activities are similar, the operation **928** is performed. In some embodiments, the operation **908** is performed before or simultaneous with performing the operation **906**.

54

The method **940** includes performing an operation **930** of determining whether the activity level determined in the operation **928** is below an activity level threshold. An example of the activity level threshold is shown as a threshold **938** in FIG. **12**. Referring back to FIG. **10**, the operation **930** is performed by a processor of the server **228**.

Upon determining that the activity level determined in the operation **928** is not below the activity level threshold, e.g., is equal to above the activity level threshold, etc., the method **940** ends. On the other hand, upon determining that the activity level of the operation **928** is below the activity level threshold, a recommendation is sent in an operation **942** of the method **940**. The operation **942** is performed by a NIC of the server **228**.

A processor of the server **228** generates the recommendation to increase the activity level determined in the operation **928**. For example, it is recommended that the user **112A** perform a different activity than that performed and used to determine the activity level of the operation **928**. To illustrate, it is recommended that the user **112A** run instead of walk. As another illustration, it is recommended that the user **112A** train using weights instead of doing push-ups.

As another example of the recommendation for increasing the activity level, it is recommended that the user **112A** perform an activity at a different location than at the location determined in the operation **902**. To illustrate, it is recommended that the user **112A** run at a park instead of running in a gym. In this illustration, a distance between the park and the gym is determined based on geo-locations of the park and the gym and/or by accessing information from the geo-location-location database and/or from a maps service. The distance is determined by a processor of the server **228**. Upon determining that the distance is less than a pre-determined distance, the park is recommended. As another illustration, it is recommended that the user **112A** swim in different gym than a gym at which the user **112A** swims.

As yet another example of the recommendation for increasing the activity level, it is recommended that the user **112A** perform the different activity at the different location. To illustrate, it is recommended that the user **112A** run at a park instead of walking at work. As another illustration, it is recommended that the user **112A** swim in a gym instead of run at a park. In this illustration, a distance between the park and the gym is determined based on geo-locations of the park and the gym and/or by accessing information from the geo-location-location database. The distance is determined by a processor of the server **228**. Upon determining that the distance is less than a pre-determined distance, the gym is recommended.

The method **940** ends after the operation **942**.

It should be noted that FIGS. **9A**, **9B**, and **10** include operations performed by the server **228** with respect to monitoring devices. In some embodiments, the operations of FIGS. **9A**, **9B**, and **10** apply to computing devices instead of monitoring devices. For example, in these embodiments, the operations described above using FIGS. **9A**, **9B**, and **10** are performed by the server **228** with respect to computing devices. As another example, in the operation **902** a location of a first computing device that is carried by the user **112A** is determined and in the operation **904**, a location of a second computing device that is carried by the user **112B** is determined.

In some embodiments, a monitoring device worn by the user **112B** is the first monitoring device and a monitoring device worn by the user **112A** is the second monitoring device. In these embodiments, the user account **912** of the

user **112B** is the first user account and the user account **174** of the user **112A** is the second user account.

FIG. **11** is a diagram of an embodiment of a system **1000** in which users **112A** and **112B** are performing activities at a location and information is shared between the users **112A** and **112B**. The user **112A** may or may not know the user **112B**. For example, the user **112B** is a friend, or a special interest, or a relative, or a family member, or a work mate, or an acquaintance, etc., of the user **112A**. As another example, the user **112A** meets the user **112B** for a first time at a location.

When the users **112A** and **112B** are performing similar activities at locations, e.g., park, or gym, or club, or dance club, or pub, work or place, or home, or theater, or college, or university, or landmark, etc., that are within a range of each other, the representation **914** is generated within the user account **912** of the user **112B**. The representation **914** includes the information **916** and a number of steps taken by the user **112B**. The display of the information **916** and the number of steps taken by the user **112B** helps determine how the user **112B** is performing with respect to the user **112A**. The users **112A** and **112B** may or may not be social network friends.

FIG. **12** is a diagram of an embodiment of a system **1010** for determining an activity level of the user **112A** based on activity and/or a location of the user **112A**. The system **1010** includes a GUI **1012** that is displayed within a representation of the user account **174** of the user **112A**.

Within the GUI **1012**, an activity level is plotted versus time. The GUI **1012** is displayed on a display device of a monitoring device that is worn by the user **112A** or on a display device of the computing device **166** that is carried by the user **112A**. As shown in the GUI **1012**, the activity level **936** is below the threshold **938** when the user **112A** is performing an activity at a location at which the user **112B** is performing an activity. The activity performed by the user **112A** may be the same or different from the activity performed by the user **112B**.

Moreover, in some embodiments, an aggregated activity level, which is sum of activity levels **936**, **1014**, and **1016** of one or more activities performed by the user **112A** within a time period **1018** is less than the threshold **938**. The aggregation, e.g., sum, etc., of activity levels is performed by a processor of the server **228**. The aggregated activity level is below the threshold **938** when the user **112A** is performing an activity at a location that is within the threshold distance of a location at which the user **112B** is performing an activity.

Comparatively, any of activity levels **1020**, **1022**, and **1024** of one or more activities performed by the user **112A** while the user **112A** is not at a location within the threshold distance of the location of the user **112B** and/or is not performing a similar activity to that performed by the user **112B** is greater than the threshold **938**.

Moreover, in some embodiments, an aggregated activity level, which is sum of activity levels **1020**, **1022**, and **1024** of one or more activities performed by the user **112A** within a time period **1026** is greater than or equal to the threshold **938**. The aggregation, e.g., sum, etc., of activity levels is performed by a processor of the server **228**. The aggregated activity level is at least equal to the threshold **938** when the user **112A** is performing an activity at a different location than one at which the user **112B** is performing an activity.

In various embodiments, a processor applies adaptive learning of locations. For example, a processor determines that a user is at a location and/or achieves an activity level of an activity at the location for a number of times greater than a pre-determined number. The processor further determines a

range of times at which the user is at the location for the number of times and/or achieves the activity level at the location. When the user visits the location on a day after the processor determines the range of times, the processor determines whether a time at which the user visits the location falls within the range of times. Upon determining that the time at which the user visits the location at a time that falls within the range of times, the processor determines that the user is at the location and/or will achieve the activity level at the location.

In several embodiments, a processor applies refined learning of location and size. For example, a processor determines that the user **112A** visits an inside the user's home and determines that one or more geo-locations within the inside of the home corresponds to the home. In this example, the processor determines that the one or more geo-locations within the inside of the home corresponds to the home based on the geo-location-location database or based on a selection received from the user indicating that the geo-locations correspond to the home. In this example, a processor determines that the user **112A** visits a backyard of the user's home and determines that one or more geo-locations of the backyard of the home correspond to the home. In this example, the processor determines that one or more geo-locations of the backyard corresponds to the home based on the geo-location-location database or based on a selection received from the user indicating that the geo-locations correspond to the home. When the user visits a geo-location within the backyard or the inside of the home for a next time, the processor determines that the user is at his/her home. It should be noted that although home is used as an example, in some embodiments, other locations, e.g., a gym, a work place, a golf course, a race track, etc., may be used.

In several embodiments, a processor determines a favorite route of a user based on a number of times the user follows the route. For example, a processor determines that a user follows a route for greater than a pre-determined number of times. In this example, the processor determines that the route is a favorite route of the user. In this example, the processor determines data associate with the route, e.g., a statistical amount of time taken to complete the route, or a location close to the route, or a destination of the route, or a combination thereof, etc. In some embodiments, the processor determines the destination of the route from a maps service or from the geo-location-location database. Examples of the statistical amount of time taken to complete the route include an average amount of time to complete the route, a maximum amount of time to complete the route, a minimum amount of time taken to complete the route, etc. In this example, the processor labels, within a GUI, the route with the data associated with the route. To illustrate, the processor labels a route as "walk to a train" instead of "walk". As another illustration, the processor labels a route as "morning walk to work" instead of "walk". As another illustration, the processor labels a route as "3 mile run down Cedar street" instead of "run". As another illustration, the processor labels a route as "6 mile beach run" instead of "run". Examples of the route include a dog walking route, a commute to work route, a running route, a route to a bus station, a route to a train station, a route to work, a route to home, a route to a friend's home, etc.

In some embodiments, a processor quantifies an emotional response when a user is responsive to a piece of entertainment. The emotional response includes a combination of the HRV and/or the GSR. Based on the emotional response, the processor assigns a rating to the piece of entertainment. For example, when the HRV and/or the GSR indicate to the processor that the user is sleeping during a movie, the processor assigns a low rating to the movie. On the other hand, when the

HRV and/or the GSR indicate to the processor that the user is excited during the movie, the processor assigns a high rating to the movie. Based on the HRV and/or the GSR, the processor determines a type of the piece of entertainment that the user likes. In some embodiments, the processor prompts a user to provide the rating. The piece of entertainment may be a movie, an opera, a ballet, a concert, a song, a multimedia presentation, a television show, news, etc. Examples of a type of the piece of entertainment include a horror piece, an action piece, a drama piece, a sad piece, a comedy piece, etc.

In various embodiments, a processor determines that a user is at a location at which the piece of entertainment is presented, e.g., publicly displayed, shown, etc., and displays within a GUI that includes event data information regarding the location. For example, a processor determines that a user is at a movie theater and populates a GUI with show times of movies at the theater. The show times of the movies are obtained from a website or a database that is used to present the show times. Other examples of information regarding the location include video games available at a theater, types of food available at a concert, etc.

In various embodiments, a processor determines motion and location features from users to build a network database. For example, the processor determines that a user performs an activity at a location for a number of times and performs a motion signature that identifies the activity for the number of times. The motion signature is a motion of a user that is substantially repeated over a time period. For example, a first swimming motion when the user is at a swimming pool in a gym is performed on day 1 and a second swimming motion when the user is at the swimming pool at the gym is performed on day 2. The first and second motions are within a standard deviation. When the user visits, e.g., enters, etc., the location at another time, e.g., day 3, etc., the processor determines that the user is going to perform the same activity that the user has performed for the number of times. For example, the processor determines based on the motion signature and the location visited for the number of times as soon as the user enters a gym that the user will swim at the gym. As another example, the processor determines that the user will do yoga at a yoga place based on the motion signature and the location visited for the number of times.

It should be noted that in some embodiments, any method or function or operation that is described herein as being performed by the processor 226 of the monitoring device 108A (FIG. 3A) or by the processor 234 of the computing device 166 (FIG. 5) may be performed by the processor 302 (FIG. 3B) of the monitoring device 108B or by the processor 190 (FIG. 2A) of the server 228.

In some embodiments, functions or methods or operations described herein as being performed by a processor of a device are performed by one or more processors of the device. For example, a function of displaying a GUI is performed by a GPU (not shown) of the monitoring device 108A instead of by the processor 234 (FIG. 3A).

In a number of embodiments, all GUIs, described herein, are accessed by the user 112A when the user 112A accesses the user account 174 (FIG. 2A).

It should be noted that several embodiments are described using a monitoring device. In some embodiments, embodiments that apply to the monitoring device also apply to the computing device 166. For example, instead of a geo-location of a monitoring device being obtained by the monitoring device, a geo-location of the computing device 166 is obtained by the computing device 166. As another example,

instead of event data determined by a processor of a monitoring device, event data is determined by a processor of the computing device 166.

In several embodiments, an activity level of a user is a level of a physiological parameter of the user.

In various embodiments, a web page is a GUI.

Embodiments described in the present disclosure may be practiced with various computer system configurations including hand-held devices, microprocessor systems, microprocessor-based or programmable consumer electronics, minicomputers, mainframe computers and the like. Several embodiments described in the present disclosure can also be practiced in distributed computing environments where tasks are performed by remote processing devices that are linked through a wire-based or wireless network.

With the above embodiments in mind, it should be understood that a number of embodiments described in the present disclosure can employ various computer-implemented operations involving data stored in computer systems. These operations are those requiring physical manipulation of physical quantities. Any of the operations described herein that form part of various embodiments described in the present disclosure are useful machine operations. Several embodiments described in the present disclosure also relates to a device or an apparatus for performing these operations. The apparatus can be specially constructed for a purpose, or the apparatus can be a computer selectively activated or configured by a computer program stored in the computer. In particular, various machines can be used with computer programs written in accordance with the teachings herein, or it may be more convenient to construct a more specialized apparatus to perform the required operations.

Various embodiments described in the present disclosure can also be embodied as computer-readable code on a non-transitory computer-readable medium. The computer-readable medium is any data storage device that can store data, which can be thereafter be read by a computer system. Examples of the computer-readable medium include hard drives, network attached storage (NAS), ROM, RAM, compact disc-ROMs (CD-ROMs), CD-recordables (CD-Rs), CD-rewritables (RWs), magnetic tapes and other optical and non-optical data storage devices. The computer-readable medium can include computer-readable tangible medium distributed over a network-coupled computer system so that the computer-readable code is stored and executed in a distributed fashion.

Although the method operations were described in a specific order, it should be understood that other housekeeping operations may be performed in between operations, or operations may be performed in an order other than that shown, or operations may be adjusted so that they occur at slightly different times, or may be distributed in a system which allows the occurrence of the processing operations at various intervals associated with the processing, as long as the processing of the overlay operations are performed in the desired way. For example, the operations 104 and 118 in FIG. 6A are performed simultaneously or the operation 118 is performed before the operation 104. As another example, the operations 202 and 204 of FIG. 6D are performed simultaneously or the operation 204 is performed before performing the operation 202. As yet another example, the operation 223 of FIG. 6F may be performed before, or after, or simultaneous with the performance of the operation 229. As yet another example, the operation 908 of FIG. 9A is performed simultaneous with or before performing the operation 906.

Although the foregoing embodiments have been described in some detail for purposes of clarity of understanding, it will

be apparent that certain changes and modifications can be practiced within the scope of the appended claims. Accordingly, the present embodiments are to be considered as illustrative and not restrictive, and the various embodiments described in the present disclosure is not to be limited to the details given herein, but may be modified within the scope and equivalents of the appended claims.

What is claimed is:

1. A method comprising:

determining a location of a first monitoring device used to produce activity data, the first monitoring device configured to be worn by a first user;

determining a location of a second monitoring device used to produce activity data, the second monitoring device configured to be worn by a second user;

determining whether the location of the first monitoring device is within a threshold distance of the location of the second monitoring device;

determining whether the activity data produced using the first monitoring device is similar to the activity data produced using the second monitoring device; and

sending a request to the first monitoring device to enable sharing of the activity data produced using the first monitoring device with the second monitoring device in response to determining that the location of the first monitoring device is within the threshold distance of the location of the second monitoring device and in response to determining that the activity data produced using the first monitoring device is similar to the activity data produced using the second monitoring device,

wherein the method is executed by a processor.

2. The method of claim 1, further comprising sending a notification to the second monitoring device regarding approval of the request received by the first monitoring device.

3. The method of claim 2, wherein the notification includes the activity data produced using the first monitoring device.

4. The method of claim 1, further comprising sending a request to the second monitoring device to enable sharing of the activity data produced using the second monitoring device with the first monitoring device in response to determining that the location of the first monitoring device is within the threshold distance of the location of the second monitoring device and in response to determining that the activity data produced using the first monitoring device is similar to the activity data produced using the second monitoring device.

5. The method of claim 3, further comprising sending a notification to the first monitoring device regarding approval of the request received by the second monitoring device.

6. The method of claim 1, further comprising:

determining whether the request to enable sharing of the activity data produced using the first monitoring device is approved; and

posting the activity data produced using the first monitoring device to a network account of the second user in response to determining that the request is approved.

7. The method of claim 1, further comprising:

determining whether the request to enable sharing of the activity data produced using the first monitoring device is approved; and

posting the activity data produced using the first monitoring device and the location of the first monitoring device to a network account of the second user in response to determining that the request is approved.

8. The method of claim 1, wherein the activity data produced using the first monitoring device includes a number of calories burned by the first user, or an amount of blood pres-

sure of the first user, or a heart rate of the first user, or an amount of weight gained by the first user, or an amount of weight lost by the first user, or a number of stairs ascended by the first user, or a number of stairs descended by the first user, or a number of steps taken by the first user, or a number of floors descended by the first user, or a number of floors climbed by the first user, or a number of rotations of a bicycle pedal rotated by the first user, or sedentary activity data associated with the first user, or an amount of distance covered by the first user, or a number of golf swings taken by the first user, or a number of forehands of a sport played by the first user, or a number of backhands of a sport played by the first user, or a combination thereof.

9. The method of claim 1, wherein the activity data produced using the second monitoring device includes a number of calories burned by the second user, or an amount of blood pressure of the second user, or a heart rate of the second user, or an amount of weight gained by the second user, or an amount of weight lost by the second user, or a number of stairs ascended by the second user, or a number of stairs descended by the second user, or a number of steps taken by the second user, or a number of floors descended by the second user, or a number of floors climbed by the second user, or a number of rotations of a bicycle pedal rotated by the second user, or sedentary activity data associated with the second user, or an amount of distance covered by the second user, or a number of golf swings taken by the second user, or a number of forehands of a sport played by the second user, or a number of backhands of a sport played by the second user, or a combination thereof.

10. The method of claim 1, wherein the location of the first monitoring device includes a home, or a place of work, or a park, or a gym, or a coffee shop, or a store.

11. The method of claim 1, wherein the location of the second monitoring device includes a home, or a place of work, or a park, or a gym, or a coffee shop, or a store.

12. The method of claim 1, wherein the first monitoring device is wearable as a watch, or a wrist band, or a clip, and the second monitoring device is wearable as a watch, or a wrist band, or a clip.

13. The method of claim 1, wherein the activity data produced using the first monitoring device is similar to the activity data produced using the second monitoring device when a combined activity level obtained using the first monitoring device over a time period is within a pre-determined range of a combined activity level obtained using the second monitoring device over the time period.

14. The method of claim 1, wherein the activity data produced using the first monitoring device is similar to the activity data produced using the second monitoring device when the activity data produced using the first monitoring device and the activity data produced using the second monitoring device correspond to the same activity.

15. A method comprising:

determining a location of a first monitoring device used to produce activity data, the first monitoring device configured to be worn by a first user;

determining a location of a second monitoring device used to produce activity data, the second monitoring device configured to be worn by a second user;

determining whether the location of the first monitoring device is within a threshold distance of the location of the second monitoring device;

determining whether the activity data produced using the first monitoring device is similar to the activity data produced using the second monitoring device;

61

posting the activity data produced using the first monitoring device to a user account of the first user to make the activity data produced using the first monitoring device available to a user account of the second user in response to determining that the location of the first monitoring device is within the threshold distance of the location of the second monitoring device and that the activity data produced using the first monitoring device is similar to the activity data produced using the second monitoring device.

16. The method of claim 15, further comprising posting the location of the first monitoring device to the user account of the first user for making the location of the first monitoring device available to the user account of the second user in response to determining that the location of the first monitoring device is within the threshold distance of the location of the second monitoring device and that the activity data produced using the first monitoring device is similar to the activity data produced using the second monitoring device.

17. The method of claim 15, wherein the activity data produced using the first monitoring device includes a number of calories burned by the first user, or an amount of blood pressure of the first user, or a heart rate of the first user, or an amount of weight gained by the first user, or an amount of weight lost by the first user, or a number of stairs ascended by the first user, or a number of stairs descended by the first user, or a number of steps taken by the first user, or a number of floors descended by the first user, or a number of floors climbed by the first user, or a number of rotations of a bicycle pedal rotated by the first user, or sedentary activity data associated with the first user, or an amount of distance covered by the first user, or a number of golf swings taken by the first user, or a number of forehands of a sport played by the first user, or a number of backhands of a sport played by the first user, or a combination thereof.

18. The method of claim 15, wherein the activity data produced using the second monitoring device includes a number of calories burned by the second user, or an amount of blood pressure of the second user, or a heart rate of the second user, or an amount of weight gained by the second user, or an amount of weight lost by the second user, or a number of stairs ascended by the second user, or a number of stairs descended by the second user, or a number of steps taken by the second user, or a number of floors descended by the second user, or a number of floors climbed by the second user, or a number of rotations of a bicycle pedal rotated by the second user, or sedentary activity data associated with the second user, or an amount of distance covered by the second user, or a number of golf swings taken by the second user, or a number of forehands of a sport played by the second user, or a number of backhands of a sport played by the second user, or a combination thereof.

19. The method of claim 15, wherein the location of the first monitoring device includes a home, or a place of work, or a park, or a gym, or a coffee shop, or a store.

20. The method of claim 15, wherein the location of the second monitoring device includes a home, or a place of work, or a park, or a gym, or a coffee shop, or a store.

21. The method of claim 15, wherein the first monitoring device is wearable as a watch, or a wrist band, or a clip, and the second monitoring device is wearable as a watch, or a wrist band, or a clip.

22. The method of claim 15, wherein the activity data produced using the first monitoring device is similar to the

62

activity data produced using the second monitoring device when a combined activity level obtained using the first monitoring device over a time period is within a pre-determined range of a combined activity level obtained using the second monitoring device over the time period.

23. The method of claim 15, wherein the activity data produced using the first monitoring device is similar to the activity data produced using the second monitoring device when the activity data produced using the first monitoring device and the activity data produced using the second monitoring device correspond to the same activity.

24. A system comprising:

a server configured to determine a location of a first monitoring device used to produce activity data, the first monitoring device configured to be worn by a first user, wherein the server is configured to determine a location of a second monitoring device used to produce activity data, the second monitoring device configured to be worn by a second user;

wherein the server is configured to determine whether the location of the first monitoring device is within a threshold distance of the location of the second monitoring device;

wherein the server is configured to determine whether the activity data produced using the first monitoring device is similar to the activity data produced using the second monitoring device; and

wherein the server is configured to send a request to the first monitoring device to enable sharing of the activity data produced using the first monitoring device with the second monitoring device in response to determining that the location of the first monitoring device is within the threshold distance of the location of the second monitoring device and in response to determining that the activity data produced using the first monitoring device is similar to the activity data produced using the second monitoring device.

25. The system of claim 24, wherein the server is further configured to:

determine whether the request to enable sharing of the activity data produced using the first monitoring device is approved; and

post the activity data produced using the first monitoring device to a network account of the second user in response to determining that the request is approved.

26. The system of claim 24, wherein the server is further configured to:

determine whether the request to enable sharing of the activity data produced using the first monitoring device is approved; and

post the activity data produced using the first monitoring device and the location of the first monitoring device to a network account of the second user in response to determining that the request is approved.

27. The system of claim 24, wherein the activity data produced using the first monitoring device is similar to the activity data produced using the second monitoring device when a combined activity level obtained using the first monitoring device over a time period is within a pre-determined range of a combined activity level obtained using the second monitoring device over the time period.

* * * * *

| | | | |
|----------------|---|---------|------------|
| 专利名称(译) | 用于处理社交互动数据和共享与位置相关联的跟踪活动的方法和系统 | | |
| 公开(公告)号 | US8818753 | 公开(公告)日 | 2014-08-26 |
| 申请号 | US14/066310 | 申请日 | 2013-10-29 |
| [标]申请(专利权)人(译) | 飞比特公司 | | |
| 申请(专利权)人(译) | FITBIT INC. | | |
| 当前申请(专利权)人(译) | FITBIT INC. | | |
| [标]发明人 | YUEN SHELTON GEE JAO PARK JAMES LEE HANS CHRISTIANSEN | | |
| 发明人 | YUEN, SHELTON GEE JAO PARK, JAMES LEE, HANS CHRISTIANSEN | | |
| IPC分类号 | G06F19/00 A61B5/00 A61B5/0205 A61B5/021 A61B5/024 A61B5/11 A61B5/145 A61B5/22 A63B24/00 A63B71/06 G01C21/00 G01C21/20 G01C22/00 G06F15/00 H04L29/08 | | |
| CPC分类号 | H04L67/22 G06F15/00 A63B24/0062 A61B5/14546 A61B5/743 A63B71/0686 A61B5/1123 A61B5/4809 A61B5/1112 A61B5/14532 A61B5/0002 G01C21/00 A61B5/7278 A61B5/4815 G06F19/00 A61B5/222 A61B5/6801 A61B5/4812 A61B5/1118 A63B2220/73 A63B2230/06 A61B5/4806 A61B5/744 A61B2560/0242 A63B2230/70 A61B2562/0219 A61B5/6838 A61B5/681 G01C22/006 A63B2220/72 A61B5/7264 A61B2560/045 A61B5/024 A63B2230/50 A61B5/02055 G01C21/20 G06F19/3481 A61B5/021 A63B2230/75 G01C23/00 G01P13/00 G16H20/30 G16H40/67 H04W4/023 A63B24/0075 A63B2024/0068 A63B2220/14 | | |
| 审查员(译) | RAYMOND , EDWARD | | |
| 优先权 | 13/667229 2013-05-07 US 13/469027 2012-11-13 US 13/246843 2012-05-15 US 61/680230 2012-08-06 US 61/388595 2010-09-30 US 61/390811 2010-10-07 US | | |
| 其他公开文献 | US20140052790A1 | | |
| 外部链接 | Espacenet USPTO | | |

摘要(译)

一种方法包括确定在执行活动时使用的第一监视设备的位置。第一监视设备由第一用户佩戴。该方法包括确定在执行活动时使用的第二监视设备的位置。第二监视设备由第二用户佩戴。该方法还包括确定第一和第二监测设备的位置是否在一定范围内以及活动是否相似。该方法包括在确定活动相似并且位置在该范围内时向第一监视设备发送提示。该提示包括来自第一用户帐户的许可请求，以允许第二用户帐户访问来自第一用户帐户的关于使用第一监视设备执行的活动的信息。

