



US00886271B2

(12) **United States Patent**
Kiani et al.

(10) **Patent No.:** **US 8,886,271 B2**
(45) **Date of Patent:** **Nov. 11, 2014**

(54) **NON-INVASIVE PHYSIOLOGICAL SENSOR COVER**

USPC 600/310, 323, 344
See application file for complete search history.

(71) Applicant: **Cercacor Laboratories, Inc.**, Irvine, CA (US)

(56) **References Cited**

(72) Inventors: **Abraham Mazda Kiani**, San Juan Capistrano, CA (US); **Massi Joe E. Kiani**, Laguna Niguel, CA (US)

U.S. PATENT DOCUMENTS

(73) Assignee: **Cercacor Laboratories, Inc.**, Irvine, CA (US)

4,960,128 A	10/1990	Gordon et al.
4,964,408 A	10/1990	Hink et al.
4,972,829 A	11/1990	Knerr
5,041,187 A	8/1991	Hink et al.
5,069,213 A	12/1991	Polczynski
5,163,438 A	11/1992	Gordon et al.
5,319,355 A	6/1994	Russek
5,337,744 A	8/1994	Branigan
5,341,805 A	8/1994	Stavridi et al.
D353,195 S	12/1994	Savage et al.
D353,196 S	12/1994	Savage et al.
5,377,676 A	1/1995	Vari et al.
D359,546 S	6/1995	Savage et al.
5,431,170 A	7/1995	Mathews
D361,840 S	8/1995	Savage et al.
D362,063 S	9/1995	Savage et al.

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 0 days.

(21) Appl. No.: **13/919,692**

(22) Filed: **Jun. 17, 2013**

(65) **Prior Publication Data**

US 2013/0345531 A1 Dec. 26, 2013

Related U.S. Application Data

(63) Continuation of application No. 12/844,720, filed on Jul. 27, 2010, now Pat. No. 8,473,020.

(60) Provisional application No. 61/229,682, filed on Jul. 29, 2009.

(51) **Int. Cl.**
A61B 5/02 (2006.01)
A61B 5/1455 (2006.01)
A61B 5/00 (2006.01)

(52) **U.S. Cl.**
CPC **A61B 5/14552** (2013.01); **A61B 5/6826** (2013.01); **A61B 5/6838** (2013.01)
USPC **600/344**; **600/323**

(58) **Field of Classification Search**
CPC **A61B 5/14552**

(Continued)

Primary Examiner — Clayton E Laballe


Assistant Examiner — Leon W Rhodes, Jr.

(74) *Attorney, Agent, or Firm* — Knobbe, Martens, Olson & Bear, LLP

(57) **ABSTRACT**

A sensor cover according to embodiments of the disclosure is capable of being used with a non-invasive physiological sensor, such as a pulse oximetry sensor. Certain embodiments of the sensor cover reduce or eliminate false readings from the sensor when the sensor is not in use, for example, by blocking a light detecting component of a pulse oximeter sensor when the pulse oximeter sensor is active but not in use. Further, embodiments of the sensor cover can prevent damage to the sensor. Additionally, embodiments of the sensor cover prevent contamination of the sensor.

18 Claims, 11 Drawing Sheets



(56)

References Cited

U.S. PATENT DOCUMENTS

5,452,717 A	9/1995	Branigan et al.	6,343,224 B1	1/2002	Parker
D363,120 S	10/1995	Savage et al.	6,349,228 B1	2/2002	Kiani et al.
5,456,252 A	10/1995	Vari et al.	6,360,114 B1	3/2002	Diab et al.
5,479,934 A	1/1996	Imran	6,368,283 B1	4/2002	Xu et al.
5,482,036 A	1/1996	Diab et al.	6,371,921 B1	4/2002	Caro et al.
5,490,505 A	2/1996	Diab et al.	6,377,829 B1	4/2002	Al-Ali
5,494,043 A	2/1996	O'Sullivan et al.	6,388,240 B2	5/2002	Schulz et al.
5,533,511 A	7/1996	Kaspari et al.	6,397,091 B2	5/2002	Diab et al.
5,534,851 A	7/1996	Russek	6,430,437 B1	8/2002	Marro
5,561,275 A	10/1996	Savage et al.	6,430,525 B1	8/2002	Weber et al.
5,562,002 A	10/1996	Lalin	6,463,311 B1	10/2002	Diab
5,590,649 A	1/1997	Caro et al.	6,470,199 B1	10/2002	Kopotic et al.
5,602,924 A	2/1997	Durand et al.	6,501,975 B2	12/2002	Diab et al.
5,619,992 A	4/1997	Guthrie et al.	6,505,059 B1	1/2003	Kollias et al.
5,632,272 A	5/1997	Diab et al.	6,515,273 B2	2/2003	Al-Ali
5,638,816 A	6/1997	Kiani-Azarbayjany et al.	6,519,487 B1 *	2/2003	Parker 600/344
5,638,818 A	6/1997	Diab et al.	6,525,386 B1	2/2003	Mills et al.
5,645,440 A	7/1997	Tobler et al.	6,526,300 B1	2/2003	Kiani et al.
5,685,299 A	11/1997	Diab et al.	6,541,756 B2	4/2003	Schulz et al.
D393,830 S	4/1998	Tobler et al.	6,542,764 B1	4/2003	Al-Ali et al.
5,743,262 A	4/1998	Lepper, Jr. et al.	6,580,086 B1	6/2003	Schulz et al.
5,758,644 A	6/1998	Diab et al.	6,584,336 B1	6/2003	Ali et al.
5,760,910 A	6/1998	Lepper, Jr. et al.	6,595,316 B2	7/2003	Cybulski et al.
5,769,785 A	6/1998	Diab et al.	6,597,932 B2	7/2003	Tian et al.
5,782,757 A	7/1998	Diab et al.	6,597,933 B2	7/2003	Kiani et al.
5,785,659 A	7/1998	Caro et al.	6,606,511 B1	8/2003	Ali et al.
5,791,347 A	8/1998	Flaherty et al.	6,632,181 B2	10/2003	Flaherty et al.
5,810,734 A	9/1998	Caro et al.	6,639,668 B1	10/2003	Trepagnier
5,823,950 A	10/1998	Diab et al.	6,640,116 B2	10/2003	Diab
5,830,131 A	11/1998	Caro et al.	6,643,530 B2	11/2003	Diab et al.
5,833,618 A	11/1998	Caro et al.	6,650,917 B2	11/2003	Diab et al.
5,860,919 A	1/1999	Kiani-Azarbayjany et al.	6,654,624 B2	11/2003	Diab et al.
5,890,929 A	4/1999	Mills et al.	6,658,276 B2	12/2003	Kiani et al.
5,904,654 A	5/1999	Wohltmann et al.	6,661,161 B1	12/2003	Lanzo et al.
5,919,134 A	7/1999	Diab	6,671,531 B2	12/2003	Al-Ali et al.
5,934,925 A	8/1999	Tobler et al.	6,671,532 B1 *	12/2003	Fudge et al. 600/344
5,940,182 A	8/1999	Lepper, Jr. et al.	6,678,543 B2	1/2004	Diab et al.
5,995,855 A	11/1999	Kiani et al.	6,684,090 B2	1/2004	Ali et al.
5,997,343 A	12/1999	Mills et al.	6,684,091 B2	1/2004	Parker
6,002,952 A	12/1999	Diab et al.	6,697,656 B1	2/2004	Al-Ali
6,011,986 A	1/2000	Diab et al.	6,697,657 B1	2/2004	Shehada et al.
6,027,452 A	2/2000	Flaherty et al.	6,697,658 B2	2/2004	Al-Ali
6,036,642 A	3/2000	Diab et al.	RE38,476 E	3/2004	Diab et al.
6,045,509 A	4/2000	Caro et al.	6,699,194 B1	3/2004	Diab et al.
6,067,462 A	5/2000	Diab et al.	6,714,804 B2	3/2004	Al-Ali et al.
6,081,735 A	6/2000	Diab et al.	RE38,492 E	4/2004	Diab et al.
6,088,607 A	7/2000	Diab et al.	6,721,582 B2	4/2004	Trepagnier et al.
6,110,522 A	8/2000	Lepper, Jr. et al.	6,721,585 B1	4/2004	Parker
6,124,597 A	9/2000	Shehada	6,725,075 B2	4/2004	Al-Ali
6,128,521 A	10/2000	Marro et al.	6,728,560 B2	4/2004	Kollias et al.
6,129,675 A	10/2000	Jay	6,735,459 B2	5/2004	Parker
6,140,549 A *	10/2000	Pompei, Jr. 602/57	6,745,060 B2	6/2004	Diab et al.
6,144,868 A	11/2000	Parker	6,760,607 B2	7/2004	Al-Ali
6,151,516 A	11/2000	Kiani-Azarbayjany et al.	6,770,028 B1	8/2004	Ali et al.
6,152,754 A	11/2000	Gerhardt et al.	6,771,994 B2	8/2004	Kiani et al.
6,157,850 A	12/2000	Diab et al.	6,792,300 B1	9/2004	Diab et al.
6,165,005 A	12/2000	Mills et al.	6,813,511 B2	11/2004	Diab
6,179,159 B1	1/2001	Gurley	6,816,741 B2	11/2004	Al-Ali
6,184,521 B1	2/2001	Coffin, IV et al.	6,822,564 B2	11/2004	Diab et al.
6,206,830 B1	3/2001	Diab et al.	6,826,419 B2	11/2004	Diab et al.
6,229,856 B1	5/2001	Diab et al.	6,830,711 B2	12/2004	Mills et al.
6,232,609 B1	5/2001	Snyder et al.	6,850,787 B2	2/2005	Weber et al.
6,236,872 B1	5/2001	Diab et al.	6,850,788 B2	2/2005	Al-Ali
6,241,683 B1	6/2001	Macklem et al.	6,852,083 B2	2/2005	Caro et al.
6,253,097 B1	6/2001	Aronow et al.	6,861,639 B2	3/2005	Al-Ali
6,256,523 B1	7/2001	Diab et al.	6,898,452 B2	5/2005	Al-Ali et al.
6,263,222 B1	7/2001	Diab et al.	6,920,345 B2	7/2005	Al-Ali et al.
6,278,522 B1	8/2001	Lepper, Jr. et al.	6,931,268 B1	8/2005	Kiani-Azarbayjany et al.
6,280,213 B1	8/2001	Tobler et al.	6,934,570 B2	8/2005	Kiani et al.
6,285,896 B1	9/2001	Tobler et al.	6,939,305 B2	9/2005	Flaherty et al.
6,301,493 B1	10/2001	Marro et al.	6,943,348 B1	9/2005	Coffin, IV
6,317,627 B1	11/2001	Ennen et al.	6,950,687 B2	9/2005	Al-Ali
6,321,100 B1	11/2001	Parker	6,961,598 B2	11/2005	Diab
6,325,761 B1	12/2001	Jay	6,970,792 B1	11/2005	Diab
6,334,065 B1	12/2001	Al-Ali et al.	6,979,812 B2	12/2005	Al-Ali
			6,985,764 B2	1/2006	Mason et al.
			6,993,371 B2	1/2006	Kiani et al.
			6,996,427 B2	2/2006	Ali et al.
			6,999,904 B2	2/2006	Weber et al.

(56)

References Cited

U.S. PATENT DOCUMENTS

7,003,338 B2	2/2006	Weber et al.	7,530,942 B1	5/2009	Diab
7,003,339 B2	2/2006	Diab et al.	7,530,949 B2	5/2009	Al Ali et al.
7,015,451 B2	3/2006	Dalke et al.	7,530,955 B2	5/2009	Diab et al.
7,024,233 B2	4/2006	Ali et al.	7,563,110 B2	7/2009	Al-Ali et al.
7,027,849 B2	4/2006	Al-Ali	7,574,245 B2	8/2009	Arizaga Ballesteros
7,030,749 B2	4/2006	Al-Ali	7,596,398 B2	9/2009	Al-Ali et al.
7,039,449 B2	5/2006	Al-Ali	7,618,375 B2	11/2009	Flaherty
7,041,060 B2	5/2006	Flaherty et al.	D606,659 S	12/2009	Kiani et al.
7,044,918 B2	5/2006	Diab	7,647,083 B2	1/2010	Al-Ali et al.
7,067,893 B2	6/2006	Mills et al.	D609,193 S	2/2010	Al-Ali et al.
7,096,052 B2	8/2006	Mason et al.	D614,305 S	4/2010	Al-Ali et al.
7,096,054 B2	8/2006	Abdul-Hafiz et al.	RE41,317 E	5/2010	Parker
7,132,641 B2	11/2006	Schulz et al.	7,729,733 B2	6/2010	Al-Ali et al.
7,142,901 B2	11/2006	Kiani et al.	7,734,320 B2	6/2010	Al-Ali
7,149,561 B2	12/2006	Diab	7,761,127 B2	7/2010	Al-Ali et al.
7,186,966 B2	3/2007	Al-Ali	7,761,128 B2	7/2010	Al-Ali et al.
7,190,261 B2	3/2007	Al-Ali	7,764,982 B2	7/2010	Dalke et al.
7,190,987 B2	3/2007	Lindekugel et al.	D621,516 S	8/2010	Kiani et al.
7,215,984 B2	5/2007	Diab	7,791,155 B2	9/2010	Diab
7,215,986 B2	5/2007	Diab	7,801,581 B2	9/2010	Diab
7,221,971 B2	5/2007	Diab	7,822,452 B2	10/2010	Schurman et al.
7,225,006 B2	5/2007	Al-Ali et al.	RE41,912 E	11/2010	Parker
7,225,007 B2	5/2007	Al-Ali	7,844,313 B2	11/2010	Kiani et al.
RE39,672 E	6/2007	Shehada et al.	7,844,314 B2	11/2010	Al-Ali
7,239,905 B2	7/2007	Kiani-Azarbayjany et al.	7,844,315 B2	11/2010	Al-Ali
7,245,953 B1	7/2007	Parker	7,865,222 B2	1/2011	Weber et al.
7,254,429 B2	8/2007	Schurman et al.	7,873,497 B2	1/2011	Weber et al.
7,254,431 B2	8/2007	Al-Ali	7,880,606 B2	2/2011	Al-Ali
7,254,433 B2	8/2007	Diab et al.	7,880,626 B2	2/2011	Al-Ali et al.
7,254,434 B2	8/2007	Schulz et al.	7,891,355 B2	2/2011	Al-Ali et al.
7,272,425 B2	9/2007	Al-Ali	7,894,868 B2	2/2011	Al-Ali et al.
7,274,955 B2	9/2007	Kiani et al.	7,899,507 B2	3/2011	Al-Ali et al.
D554,263 S	10/2007	Al-Ali	7,899,518 B2	3/2011	Trepagnier et al.
7,280,858 B2	10/2007	Al-Ali et al.	7,904,132 B2	3/2011	Weber et al.
7,289,835 B2	10/2007	Mansfield et al.	7,909,772 B2	3/2011	Popov et al.
7,292,883 B2	11/2007	De Felice et al.	7,910,875 B2	3/2011	Al-Ali
7,295,866 B2	11/2007	Al-Ali	7,919,713 B2	4/2011	Al-Ali et al.
7,328,053 B1	2/2008	Diab et al.	7,937,128 B2	5/2011	Al-Ali
7,332,784 B2	2/2008	Mills et al.	7,937,129 B2	5/2011	Mason et al.
7,340,287 B2	3/2008	Mason et al.	7,937,130 B2	5/2011	Diab et al.
7,341,559 B2	3/2008	Schulz et al.	7,941,199 B2	5/2011	Kiani
7,343,186 B2	3/2008	Lamego et al.	7,951,086 B2	5/2011	Flaherty et al.
D566,282 S	4/2008	Al-Ali et al.	7,957,780 B2	6/2011	Lamego et al.
7,355,512 B1	4/2008	Al-Ali	7,962,188 B2	6/2011	Kiani et al.
7,356,365 B2	4/2008	Schurman	7,962,190 B1	6/2011	Diab et al.
7,371,981 B2	5/2008	Abdul-Hafiz	7,976,472 B2	7/2011	Kiani
7,373,193 B2	5/2008	Al-Ali et al.	7,988,637 B2	8/2011	Diab
7,373,194 B2	5/2008	Weber et al.	7,990,382 B2	8/2011	Kiani
7,376,453 B1	5/2008	Diab et al.	7,991,446 B2	8/2011	Ali et al.
7,377,794 B2	5/2008	Al-Ali et al.	8,000,761 B2	8/2011	Al-Ali
7,377,899 B2	5/2008	Weber et al.	8,008,088 B2	8/2011	Bellott et al.
7,383,070 B2	6/2008	Diab et al.	RE42,753 E	9/2011	Kiani-Azarbayjany et al.
7,415,297 B2	8/2008	Al-Ali et al.	8,019,400 B2	9/2011	Diab et al.
7,428,432 B2	9/2008	Ali et al.	8,028,701 B2	10/2011	Al-Ali et al.
7,438,683 B2	10/2008	Al-Ali et al.	8,029,765 B2	10/2011	Bellott et al.
7,440,787 B2	10/2008	Diab	8,036,728 B2	10/2011	Diab et al.
7,454,240 B2	11/2008	Diab et al.	8,046,040 B2	10/2011	Ali et al.
7,467,002 B2	12/2008	Weber et al.	8,046,041 B2	10/2011	Diab et al.
7,469,157 B2	12/2008	Diab et al.	8,046,042 B2	10/2011	Diab et al.
7,471,969 B2	12/2008	Diab et al.	8,048,040 B2	11/2011	Kiani
7,471,971 B2	12/2008	Diab et al.	8,050,728 B2	11/2011	Al-Ali et al.
7,483,729 B2	1/2009	Al-Ali et al.	RE43,169 E	2/2012	Parker
7,483,730 B2	1/2009	Diab et al.	8,118,620 B2	2/2012	Al-Ali et al.
7,486,977 B2 *	2/2009	Sweitzer et al. 600/323	8,126,528 B2	2/2012	Diab et al.
7,489,958 B2	2/2009	Diab et al.	8,128,572 B2	3/2012	Diab et al.
7,496,391 B2	2/2009	Diab et al.	8,130,105 B2	3/2012	Al-Ali et al.
7,496,393 B2	2/2009	Diab et al.	8,145,287 B2	3/2012	Diab et al.
D587,657 S	3/2009	Al-Ali et al.	8,150,487 B2	4/2012	Diab et al.
7,499,741 B2	3/2009	Diab et al.	8,175,672 B2	5/2012	Parker
7,499,835 B2	3/2009	Weber et al.	8,180,420 B2	5/2012	Diab et al.
7,500,950 B2	3/2009	Al-Ali et al.	8,182,443 B1	5/2012	Kiani
7,509,154 B2	3/2009	Diab et al.	8,185,180 B2	5/2012	Diab et al.
7,509,494 B2	3/2009	Al-Ali	8,188,433 B2	5/2012	Gonopolskiy et al.
7,510,849 B2	3/2009	Schurman et al.	8,190,223 B2	5/2012	Al-Ali et al.
7,526,328 B2	4/2009	Diab et al.	8,190,227 B2	5/2012	Diab et al.
			8,203,438 B2	6/2012	Kiani et al.
			8,203,704 B2	6/2012	Merritt et al.
			8,224,411 B2	7/2012	Al-Ali et al.
			8,228,181 B2	7/2012	Al-Ali


(56)

References Cited

U.S. PATENT DOCUMENTS

8,229,533	B2	7/2012	Diab et al.	8,374,665	B2	2/2013	Lamego
8,233,955	B2	7/2012	Al-Ali et al.	8,385,995	B2	2/2013	Al-ali et al.
8,244,325	B2	8/2012	Al-Ali et al.	8,385,996	B2	2/2013	Smith et al.
8,255,026	B1	8/2012	Al-Ali	8,388,353	B2	3/2013	Kiani et al.
8,255,027	B2	8/2012	Al-Ali et al.	8,399,822	B2	3/2013	Al-Ali
8,255,028	B2	8/2012	Al-Ali et al.	8,401,602	B2	3/2013	Kiani
8,260,577	B2	9/2012	Weber et al.	8,405,608	B2	3/2013	Al-Ali et al.
8,265,723	B1	9/2012	McHale et al.	8,414,499	B2	4/2013	Al-Ali et al.
8,274,360	B2	9/2012	Sampath et al.	8,418,524	B2	4/2013	Al-Ali
8,301,217	B2	10/2012	Al-Ali et al.	8,423,106	B2	4/2013	Lamego et al.
8,310,336	B2	11/2012	Muhsin et al.	8,428,967	B2	4/2013	Olsen et al.
8,315,683	B2	11/2012	Al-Ali et al.	8,430,817	B1	4/2013	Al-Ali et al.
RE43,860	E	12/2012	Parker	8,437,825	B2	5/2013	Dalvi et al.
8,337,403	B2	12/2012	Al-Ali et al.	8,455,290	B2	6/2013	Siskavich
8,346,330	B2	1/2013	Lamego	8,457,703	B2	6/2013	Al-Ali
8,353,842	B2	1/2013	Al-Ali et al.	8,457,707	B2	6/2013	Kiani
8,355,766	B2	1/2013	MacNeish, III et al.	8,463,349	B2	6/2013	Diab et al.
8,359,080	B2	1/2013	Diab et al.	8,466,286	B2	6/2013	Bellott et al.
8,364,223	B2	1/2013	Al-Ali et al.	8,471,713	B2	6/2013	Poeze et al.
8,364,226	B2	1/2013	Diab et al.	8,473,020	B2	6/2013	Kiani et al.
				8,483,787	B2	7/2013	Al-Ali et al.
				8,489,364	B2	7/2013	Weber et al.
				8,498,684	B2	7/2013	Weber et al.

* cited by examiner

*FIG. 1*




FIG. 2B




FIG. 2A




FIG. 2C









FIG. 2D



*FIG. 3D**FIG. 3E*




FIG. 4B




FIG. 4C




FIG. 5A







FIG. 5B






FIG. 9B






FIG. 9A






FIG. 9D

1

**NON-INVASIVE PHYSIOLOGICAL SENSOR
COVER****CROSS-REFERENCE TO RELATED
APPLICATIONS**

The present application is a continuation of U.S. patent application Ser. No. 12/844,720, filed Jul. 27, 2010, entitled "NON-INVASIVE PHYSIOLOGICAL SENSOR COVER," which claims priority benefit under 35 U.S.C. § 119(e) from U.S. Provisional Application No. 61/229,682, filed Jul. 29, 2009, entitled "Non-invasive Physiological Sensor Cover." All of the above referenced applications are hereby incorporated by reference herein in their entireties.

FIELD OF THE DISCLOSURE

The present invention relates to a sensor for measuring oxygen content in the blood, and, in particular, relates to an apparatus and method for preventing sensor activity when the sensor is not in use.

BACKGROUND OF THE DISCLOSURE

Non-invasive physiological sensors are applied to the body for monitoring or making measurements indicative of a patient's health. One application for a non-invasive physiological sensor is pulse oximetry, which provides a noninvasive procedure for measuring the oxygen status of circulating blood. Oximetry has gained rapid acceptance in a wide variety of medical applications, including surgical wards, intensive care and neonatal units, general wards, and home care and physical training. A pulse oximetry system generally includes a patient monitor, a communications medium such as a cable, and a physiological sensor having light emitters and a detector, such as one or more LEDs and a photodetector. The sensor is attached to a tissue site, such as a finger, toe, ear lobe, nose, hand, foot, or other site having pulsatile blood flow which can be penetrated by light from the emitters. The detector is responsive to the emitted light after attenuation by pulsatile blood flowing in the tissue site. The detector outputs a detector signal to the monitor over the communication medium, which processes the signal to provide a numerical readout of physiological parameters such as oxygen saturation (SpO₂) and pulse rate.

High fidelity pulse oximeters capable of reading through motion induced noise are disclosed in U.S. Pat. Nos. 6,770,028, 6,658,276, 6,157,850, 6,002,952, 5,769,785, and 5,758,644, which are assigned to Masimo Corporation ("Masimo") and are incorporated by reference herein. Advanced physiological monitoring systems may incorporate pulse oximetry in addition to advanced features for the calculation and display of other blood parameters, such as carboxyhemoglobin (HbCO), methemoglobin (HbMet) and total hemoglobin (Hbt), total Hematocrit (Hct), oxygen concentrations and glucose concentrations, as a few examples. Advanced physiological monitors and corresponding multiple wavelength optical sensors capable of measuring parameters in addition to SpO₂, such as HbCO, HbMet and Hbt are described in at least U.S. patent application Ser. No. 11/367,013, filed Mar. 1, 2006, titled Multiple Wavelength Sensor Emitters and U.S. patent application Ser. No. 11/366,208, filed Mar. 1, 2006, titled Noninvasive Multi-Parameter Patient Monitor, assigned to Masimo Laboratories, Inc. and incorporated by reference herein. Further, noninvasive blood parameter monitors and optical sensors including Rainbow™ adhesive and reusable sensors and RAD-57™ and Radical-7™ monitors

2

capable of measuring SpO₂, pulse rate, perfusion index (PI), signal quality (SiQ), pulse variability index (PVI), HbCO and HbMet, among other parameters, are also commercially available from Masimo.

SUMMARY OF THE DISCLOSURE

Optical sensors are widely used across clinical settings, such as operating rooms, emergency rooms, post anesthesia care units, critical care units, outpatient surgery and physiological labs, to name a few. In some situations, such as in operating rooms, emergency rooms or critical care units, sensors can be kept attached to monitors to reduce the setup time needed to begin monitoring a patient. While attached, the sensor can generate false readings by detecting ambient light even though the sensor is not in use. The sensor can also cause the monitor to emit alarms or otherwise make noise due to false readings, which can be distracting to medical personnel.

As such, a method and apparatus for preventing false readings are desirable. A sensor cover, according to embodiments of the disclosure, prevents or reduces false readings until the sensor is in use.

Further, in certain embodiments, the sensor cover can prevent damage to the sensor. For example, the sensors cover can protect the emitters and the detector during shipment or prior to use. In certain embodiments, a sensor cover decreases the likelihood of contamination by keeping covered portions of the sensor clean. Sensors in hospitals and other clinical environments are subject to exposure to infectious agents, dust or other foreign matter from depositing on the emitters or detector. The sensor cover can reduce or prevent exposure to these contaminants.

BRIEF DESCRIPTION OF THE DRAWINGS

FIG. 1 illustrates a sensor cover attached to a sensor of a physiological measurement system according to an embodiment of the disclosure;

FIGS. 2A-2C are top cover-attached, top cover-detached, and bottom cover-attached perspective views, respectively, of the sensor cover and sensor of FIG. 1;

FIG. 2D illustrates a first and second sensor covers over the emitters and detector according to an embodiment of the disclosure;

FIG. 3A illustrates a non-protruding sensor cover according to an embodiment of the disclosure;

FIG. 3B illustrates a non-protruding sensor cover having an opaque border and a removable opaque center according to an embodiment of the disclosure;

FIG. 3C illustrates a sensor cover having a clear "window" according to an embodiment of the disclosure;

FIG. 3D illustrates a sensor cover integrated with an adhesive cover according to an embodiment of the disclosure;

FIG. 3E illustrates a sensor cover covering an adhesive sensor according to an embodiment of the disclosure;

FIGS. 4A-4B are a top view and a close up view, respectively, of an integrated sensor cover according to an embodiment of the disclosure;

FIG. 4C illustrates the sensor cover of FIGS. 4A-4B covering a sensor component;

FIG. 5A is a front view a sensor cover attachable to a reusable sensor according to an embodiment of the disclosure;

FIG. 5B illustrates the mating of the sensor cover of FIG. 5A with a sensor;

FIG. 6 illustrates a sensor cover attachable to a sensor via one or more tabs according to an embodiment of the disclosure;

FIG. 7 illustrates a sensor cover configured to block both the emitters and the detector according to an embodiment of the disclosure;

FIG. 8 illustrates a sensor cover attachable to a sensor via an attachment arm according to an embodiment of the disclosure; and

FIGS. 9A-9D illustrates embodiments of the sensor covers configured for attachment to a bioacoustic sensor, according to embodiments of the disclosure.

DETAILED DESCRIPTION OF THE PREFERRED EMBODIMENT

A sensor cover according to embodiments of the disclosure is capable of being used with a non-invasive physiological sensor. Certain embodiments of the sensor cover reduce or eliminate false readings from the sensor when the sensor is not in use. Further, embodiments of the sensor cover can prevent damage to the sensor. Additionally, embodiments of the sensor cover prevent contamination of the sensor.

The tissue site of the illustrated embodiments is a finger and the following description therefore refers specifically to the tissue site as a finger for the purposes of clarity. This is not intended to be limiting and, as described herein, the sensor cover of certain embodiments can be used with sensors attachable to other types of tissue sites, such as a toe, ear lobe, nose, hand, foot, forehead or the like.

FIG. 1 illustrates an embodiment of a sensor cover attached to a physiological measurement system 100 having a monitor 110 and an optical sensor 120. The optical sensor 120 comprises one or more light emitters and a detector. The optical sensor 120 is configured to plug into a monitor sensor port 112 via a patient cable 130. Monitor keys 114 provide control over operating modes and alarms, to name a few. A display 116 provides readouts of measured parameters, such as oxygen saturation, pulse rate, HbCO, HbMet and Hbt to name a few. Other blood parameters that can be measured to provide important clinical information are fractional oxygen saturation, bilirubin and blood glucose, to name a few.

In the illustrated embodiment of FIG. 1, the sensor cover 140 protrudes outside the sensor. The cover can be made from an opaque material, such as, for example, plastic, polyester, polypropylene, rubber, vinyl, cling vinyl and/or the like. The sensor cover 140 can obstruct the detector and prevent the detector from detecting light, thereby reducing or eliminating false readings. For example, the sensor 120 can sometimes be left attached to a monitor 110 to facilitate quick monitoring of a patient, even when not currently in use. The opaque cover 140 can prevent or reduce false readings caused by the emitters or the ambient light, even if the sensor is active, by preventing the sensor from receiving light. In an embodiment, the opaque material can block all wavelengths of light used by a particular sensor. Other embodiments can block different ranges of wavelengths depending on the type of sensor the cover is used for. In an embodiment, the sensor cover 140 is placed over the emitters to prevent the sensor from emitting light receivable by the detector. In an embodiment, both the detector and emitter are covered.

In some embodiments, the sensor cover 140 can be removed before placement at a measurement site. For example, once a patient arrives, medical personnel can remove the sensor cover 140 and attach the now fully operational sensor 120 to the patient. In some embodiments, the medical personnel can attach the sensor 120 with the cover

140 still in place. The opaque cover prevents measurements from being taken until the sensor 120 is generally secure and the medical personnel are ready to take measurements. For example, movement can generate artifacts for some sensors; therefore waiting until the patient is stable can reduce measurement of inaccurate data. Once the sensor 120 is generally secured to an attachment site, the cover 140 can be removed from the sensor. In some embodiments, the sensor cover 140 can be removed before and/or after placement at a measurement site. The sensor cover 140 can be removed by peeling it off from the sensor or by pulling on the protruding portion.

As will be appreciated by skilled artisans from the disclosure provided herein, various attachment mechanisms can be used. For example, the sensor cover can be attached with an adhesive. In certain embodiments, a restorable adhesive can be used to facilitate reattachments of the sensor cover. The restorable adhesive layer can be rejuvenated by application of alcohol to the adhesive. The cover can then be reattached to the sensor. This can be useful where the sensor is moved to a new location or tissue site because the cover can prevent the sensor from taking false readings while the sensor is moved. In some embodiments, no adhesive is used on the sensor cover to leave no residue. In some embodiments, the sensor cover can be made from static cling vinyl, plastic film, or other "clingy" material with no adhesive used. In some embodiments, the sensor cover can be attached through static electricity allowing the cover to cling to the sensor without any adhesive and/or allowing the sensor cover to be reapplied. In other configurations, the sensor cover can be attached with Velcro, fasteners, tabs, clips, slots, or the like.

As will also be appreciated by skilled artisans from the disclosure provided herein, the sensor cover can be detached in various ways. In some embodiments, the sensor cover can be peeled off from the sensor before the sensor is placed at a measurement site. In some embodiments, the sensor can be pulled off from the sensor after placement by pulling on a protruding portion. Depending on the attachment mechanism, the detachment of the sensor cover can expose an adhesive layer or can leave no adhesive residue on the sensor. In some embodiments, the sensor cover can be unclipped or unhooked.

In certain embodiments, the sensor covers are reusable. For example, the sensor cover can be reused if the sensor is temporarily removed for repositioning or for cleaning. The sensor cover can also be replaced on the sensor when the sensor is no longer in use. In some embodiments, the sensor covers are disposable and are disposed of once removed from the sensor.

Although disclosed with reference to the sensor of FIG. 1, an artisan will recognize from the disclosure herein a wide variety of oximeter sensors, optical sensors, noninvasive sensors, medical sensors, or the like that may benefit from the sensor cover disclosed herein. In various embodiments, the sensor can be adapted to receive a tissue site other than a finger such as a, toe, ear lobe, nose, hand, foot, neck, or other site having pulsatile blood flow which can be penetrated by light from the emitter. In addition, the sensor cover 140 can be used with a portable monitor and associated sensor components in certain embodiments. Such monitors, including the sensor components, can be integrated into a hand-held device such as a PDA and typically do not include cables or separate monitors. Portable monitors are often used by first responders in emergency situations, in part because of their portability and ease of use. As such, sensor covers 140 which can protect the sensor components according to embodiments herein can be of particular benefit when used with spot-check monitors.

5

FIGS. 2A-2C are top cover-attached, top cover-detached, and bottom cover-attached perspective views, respectively, of the sensor cover and sensor of FIG. 1. FIG. 2D illustrates a first 140 and second 240 sensor covers placed over the detector 210 and emitters 230, respectively. FIG. 2A illustrates a view of a side of the sensor placed in contact with a tissue site. In FIG. 2A, the sensor cover 140 attaches to the sensor 120 and covers the detector 210, with a protruding portion 220 extending past the sensor. The sensor cover 140 can be a generally elongated shape made of an opaque material. In an embodiment, one side of the sensor cover can include an adhesive layer over the portion of the cover designed to block the detector 210 while the remainder of the cover can be adhesive free. Thus, the cover 140 does not catch on other objects and cause the cover 140 to be prematurely removed. The cover 140 can be removed by pulling on the protruding portion 220 either before or after the sensor 120 has been placed onto a measurement site. FIG. 2B illustrates the sensor 120 with the sensor cover 140 removed. FIG. 2C illustrates a view of an opposite side of the sensor of FIG. 2A.

FIG. 3A illustrates a non-protruding sensor cover 310 according to an embodiment of the disclosure. The opaque sensor cover 310 fits within the sensor 120 and blocks a sensor component 210, such as the emitters or the detector. By staying within the sensor edges, the chance of accidental removal of the cover can be reduced. When the sensor 120 is ready for use, the sensor cover 310 can be removed.

FIG. 3B illustrates a non-protruding sensor cover having an opaque border 314 and a removable opaque center 312. The opaque center 312 can be removed separately from the opaque border 314, leaving an opaque material surrounding the sensor component 210. When the sensor is attached to the patient, the opaque border 314 can minimize light piping, thereby increasing accuracy of the readings. For example, the opaque border 314 can prevent reflected or scattered light that has not passed through tissue from entering into the detector and/or prevent the detector from picking up light from the emitters that fall around instead of on the detector. In an embodiment, the sensor cover can have adhesive on one both sides. Adhesive on both sides of the sensor cover allows the cover to stick to a patient, further preventing light piping or movement of the sensor. In an embodiment the sensor cover can have a clear window section in addition to or instead of a removable opaque center 312.

FIG. 3C illustrates a sensor cover 316 having a clear "window" 317 over the sensor component. In an embodiment, the sensor cover can be used to protect the sensor component, provide a new adhesive layer, and/or reduce light piping while allowing the light through the "window." By using a clear window, the sensor cover does not have to be removed when sensor is attached to the patient. In some embodiments, a removable opaque portion can be placed over the window.

FIG. 3D illustrates a sensor cover integrated with an opaque adhesive cover 320 for the sensor. An adhesive sensor generally has one or more adhesive covers 320 covering one or more adhesive portions 330 of the sensor. In FIG. 3D, the opaque adhesive cover 320 is extended to cover the sensor component 210. The adhesive cover 320 can be peeled off to reveal the adhesive layer 330 and uncover the sensor component 210.

FIG. 3E illustrates a sensor cover 340 covering an adhesive sensor. In FIG. 3E, the opaque sensor cover 340 has adhesive material on both sides of the sensor cover in order to allow reattachment of a sensor where the original adhesive material 330 has lost its adhesiveness. The sensor cover 340 can be placed on the sensor using a first adhesive layer 350 while the sensor is detached from a patient. An adhesive cover (not

6

shown) protects a second adhesive layer 360 and can be removed before the sensor is placed on the patient. The second adhesive layer allows the sensor to be reattached to the patient. The sensor cover can cover both the detector and emitters of the sensor. The sensor cover 322 can have removable or clear sections 370, 380 over the detector and/or emitters to allow light to pass through.

FIGS. 4A-4B are a top view and a close up view, respectively, of an integrated sensor cover according to an embodiment of the disclosure. FIG. 4A illustrates an embodiment of the sensor cover where the sensor cover 410 is integrated with the sensor 400. The sensor has a slot 420 positioned near an emitter or a detector. The slot allows an arm 410, 430 to be folded over a sensor component 435, which can be the emitters or the detector, thereby covering it. In certain embodiments, the sensor 400 is an adhesive sensor. The use of a slot allows an adhesive arm 410 to be used as a sensor cover without having to remove the arm's adhesive cover. Once a patient is available, the adhesive arm 410 can be removed from the slot, the adhesive cover can be removed, and the adhesive arms 410, 430 used to secure the adhesive sensor to the patient. FIG. 4B illustrates a close up view of the slot 420 and sensor cover 410 of FIG. 4A. FIG. 4C illustrates the sensor cover 410 folded over the sensor component 435 with the end of the sensor cover inserted into the slot. A portion of the sensor cover extends into the slot and to the back side of the sensor. The slot keeps the sensor cover 410 generally secure against the sensor component 435.

FIG. 5A is a front view a sensor cover 510 attachable to a reusable sensor according to an embodiment of the disclosure. The sensor cover 510 includes a recess 515 into which a sensor housing can be inserted. The sensor housing generally fits closely in the recess 515. Friction between the inner surfaces of the sensor cover 510 and the sensor housing generally secures the housing with the sensor cover 510. FIG. 5B illustrates the mating of the sensor cover 510 of FIG. 5A with a sensor 520. In the illustrated embodiment, the sensor 520 is a reusable clip-style sensor. The sensor cover 510 fits over a lower sensor housing 525. The sensor housings 525, 545 can contain sensor components 530, 540, such as the emitters or the detector. In certain embodiments, the sensor component 530 is a detector and the sensor cover 510 prevents the detector from receiving light. The sensor cover 510 can be removed when the sensor 520 is in use and reattached once the sensor 520 is not in use.

FIG. 6 illustrates a sensor cover 610 attachable to a sensor 520 via one or more tabs or attachment arms 620 according to an embodiment of the disclosure. The tabs 620 fit over the sides of an upper housing 545 of the sensor and generally secure the sensor cover 610 against the upper housing 545. The sensor cover 610 covers the sensor component, such as the emitters or the detector, located in the upper housing 545.

FIG. 7 illustrates an embodiment of the sensor cover 700 configured to block both the emitters and the detector. An upper arm 710 secures against an upper housing of a sensor. A lower arm 720 secures against a lower housing of a sensor. The upper 710 and lower 720 arms are connected by a hinge portion 725. The arms 710, 720 can be attached via a press fit. The lower arm 720 can also include an attachment arm 730 to better secure the sensor cover 700 against the lower housing of the sensor.

FIG. 8 illustrates an embodiment of the sensor cover 800 attachable to a sensor housing via an attachment arm 810. The attachment arm 810 is configured to secure the sensor cover 800 in place when applied to the sensor. Upon application to a sensor, the front portion of the sensor housing may occupy the space defined by the attachment arm 810 and the under-

side of the lower portion **805** of the sensor cover **800**. The attachment arm **810** helps to releasably secure the sensor, via a friction fit, for example. One or more other features, such as the lip **815** disposed on the side of the sensor cover proximal to the sensor can be included to further secure the sensor cover **800** in the sensor. Upon insertion of the sensor cover **800** into the sensor, the sides of the sensor housing abut the lip **815**. Accordingly, the lip **815** can help ensure that the sensor cover **800** is positioned appropriately deep within the sensor.

Although the above embodiments have been described with respect to an opaque material intended to optically insulate the optical sensor, as will be appreciated by skilled artisans from the disclosure provided herein, sensor covers made of different insulative materials can be used as appropriate for different types of sensors. For example, sonically insulative materials, such as foam, rubber, cotton, and/or other sound deadening materials can be used to cover sensors that employ sound, such as a bioacoustic or ultrasound sensor. In some embodiments, electrically insulative materials, such as rubber, polyethylene, silicone and/or other insulators can be used to cover sensors that employ electrical signals, such as bio-impedance sensors. In some embodiments, mechanically insulative materials, such as hard plastic, metal, rubber, silicone, and/or other rigid or dampening materials can be used to cover mechanical sensors to prevent sensor actuation. In some embodiments, chemically insulative material, such as plastic, metal, polyethylene or the like can be used to cover chemical sensors and prevent their exposure to the environment.

FIGS. 9A-9D illustrate embodiments of sensor covers for a bioacoustic sensor. FIG. 9A illustrates one embodiment of a bioacoustic sensor. The bioacoustic sensor **900** is configured for placement against a patient's skin. The contact surface **903** of the sensor **900** is placed against the skin. The bioacoustic sensor picks up sound waves from the patient's body and converts them into electrical signals for transmission to a monitoring device. In one embodiment, the bioacoustic sensor can use a piezoelectric transducer as the sensing element to detect sound waves. In FIG. 9A a sensor cover **905** made of a sound-deadening material, such as foam, rubber, and/or cotton, is attached to the contact surface to prevent sound waves from being detected by the bioacoustic sensor **900**. The sound-deadening material can be attached by adhesive, tabs, clips, friction fit, and/or other connection mechanism. In FIG. 9A, the bioacoustic sensor has a bump **910** on the contact surface **903** positioned to apply pressure to the sensing element so as to bias the sensing element in tension and improve the receptivity of the sensing element to sound waves. Where such a bump **910** exists on the contact surface **903** of the sensor, embodiments of sensor cover **905** can be provided with a corresponding recess.

FIG. 9B illustrates an embodiment of the sensor cover **920** made of shaped sound-deadening material to increase the surface area available to absorb sound. In one embodiment, a plurality of wedge shaped protrusions **925** is formed on the surface of the sensor cover **920**. In other embodiments, different shaped protrusions can be used, such as waveform, pyramid, egg crate, and/or other shapes to increase the surface area.

FIG. 9C illustrates a bioacoustic sensor cover having one or more attachment arms according to an embodiment of the disclosure. An attachment arm **935** is configured to releasably secure the sensor cover **930** when applied to the sensor via a friction fit, for example. A second attachment arm **936** can be provided to further secure the sensor cover **930** to the sensor **900**. A recess **940** can also be formed on the interior surface of the sensor cover **930** in order to conform to protrusions on the

contact surface of the sensor **900**. Where the contact surface of the sensor **900** is flat, the interior surface can also be flat.

FIG. 9D illustrates a bioacoustic sensor having conductive leads according to an embodiment of the disclosure. In FIG. 9D, the illustrated bioacoustic sensor **900** has one or more apertures **950**, **955** exposing the sensing element **960** to the contact surface **903**. In one embodiment, the sensor cover **962** prevents the bioacoustic sensor from taking readings by creating an electrical short in the sensor. One or more conductive leads or wires **965**, **970** configured to fit into the apertures **950**, **955** in the sensor housing are disposed on the sensor cover **962**. The conductive leads **965**, **970** abut the negative and positive electrical poles of the sensing element **960**. The conductive leads can be formed of copper or other conductive material. In one embodiment, the conductive leads **965**, **970** can abut internal wiring that connects to the negative and positive electrical poles, such that a direct connection is not required. The conductive leads **965**, **970** are joined by a connector lead or wire **975** to generate a short circuit in the sensor **900**. In an embodiment, the conductive leads **965**, **970** and connector lead **975** are a single connected structure. In an embodiment, the sensor cover **962** further comprises one or more attachment arms **980**, **982** for releasably securing the sensor cover **962** to the sensor **900**. In an embodiment, the sensor cover **962** further comprises a recess **985** to conform against a protrusion **910** on the contact surface **903** of the sensor. In one embodiment, the sensor cover **962** is formed out of a sound deadening material, such as foam or rubber. In one embodiment, the sensor cover **962** is made of hard plastic or other types of plastic materials.

Conditional language used herein, such as, among others, "can," "could," "might," "may," "e.g.," and the like, unless specifically stated otherwise, or otherwise understood within the context as used, is generally intended to convey that certain embodiments include, while other embodiments do not include, certain features, elements and/or states. Thus, such conditional language is not generally intended to imply that features, elements and/or states are in any way required for one or more embodiments or that one or more embodiments necessarily include logic for deciding, with or without author input or prompting, whether these features, elements and/or states are included or are to be performed in any particular embodiment.

Various sensor covers have been disclosed in detail in connection with various embodiments. These embodiments are disclosed by way of examples only and are not to limit the scope of the claims that follow. One of ordinary skill in the art will appreciate the many variations, modifications and combinations. For example, in various embodiments, adhesive, snap-fit, friction-fit, clips, tabs, and other attachment mechanisms can be employed. In addition, in various embodiments the sensor covers are used with a sensor that can measure any type of physiological parameter. In various embodiments, the sensor covers can be for any type of medical device or sensor. In various embodiments, adhesive can be placed on both sides of the sensor cover to aid in the reattachment of sensors where the sensor adhesive has grown weak. In various embodiments, sensors covers can be made in whole or in part of materials such as foam, polyester, polypropylene, rubber, vinyl, cling vinyl, urethane rubber plastic or other plastic materials, cloth, metal, combinations of the same or the like.

What is claimed is:

1. A method of blocking readings by a noninvasive optical physiological sensor, the method comprising:
 - providing a sensor cover comprising:
 - an opaque portion attachable to the sensor and configured to block readings by the sensor; and

9

a non-adhesive portion that protrudes from the sensor to facilitate removal of the sensor cover; and attaching the sensor cover to the sensor, the sensor cover blocking readings by the sensor and removable from the sensor,

wherein the sensor comprises:

a light source configured to emit light from one or more emitters of the sensor; and

a detector configured to receive at least a portion of the light emitted by the one or more emitters after the light has passed through a tissue site,

wherein the sensor cover is configured to prevent the detector from receiving light when the sensor is active.

2. The method of claim 1, wherein the non-adhesive portion that protrudes from the sensor comprises an elongate portion that extends past the sensor.

3. The method of claim 1, wherein the sensor is an adhesive sensor having a flexible substrate and an adhesive layer.

4. The method of claim 3, wherein at least the opaque portion comprises an adhesive cover attachable to the adhesive layer of the sensor.

5. The method of claim 1, wherein the sensor cover further comprises an adhesive layer on the opaque portion, the adhesive layer configured to removably attach over a sensing portion of the sensor.

6. The method of claim 1, further comprising: activating the light source of the sensor to emit light from the one or more emitters of the sensor; and blocking, with the sensor cover, the light from the one or more emitters from being received by the detector of the sensor.

7. The method of claim 1, wherein the opaque portion is attachable over at least one of the detector or the one or more emitters.

8. The method of claim 1, wherein the opaque portion is configured to block ambient light from a surrounding area.

9. The method of claim 1, wherein the sensor is a pulse oximeter sensor.

10

10. A sensor cover for use with a noninvasive optical physiological sensor, the sensor cover comprising:

an opaque portion attachable to the sensor and configured to block optical readings by the sensor; and

a non-adhesive portion that protrudes from the sensor to facilitate removal of the sensor cover,

wherein the sensor comprises:

a light source configured to emit light from one or more emitters of the sensor; and

a detector configured to receive at least a portion of the light emitted by the one or more emitters after the light has passed through a tissue site,

wherein the opaque portion is configured to prevent the detector from receiving light during sensor activation.

11. The sensor cover of claim 10, wherein the non-adhesive portion that protrudes from the sensor comprises an elongate portion that extends past the sensor.

12. The sensor cover of claim 10, wherein the sensor is an adhesive sensor having a flexible substrate and an adhesive layer.

13. The sensor cover of claim 12, wherein at least the opaque portion comprises an adhesive cover attachable to the adhesive layer of the sensor.

14. The sensor cover of claim 10, further comprising: an adhesive layer on the opaque portion, the adhesive layer configured to removably attach over a sensing portion of the sensor.

15. The sensor cover of claim 10, wherein the sensor cover is configured to block the light from the one or more emitters from being received by the detector.

16. The sensor cover of claim 10, wherein the opaque portion is attachable over at least one of the detector or the one or more emitters.

17. The sensor cover of claim 10, wherein the opaque portion is configured to block ambient light from a surrounding area.

18. The sensor cover of claim 10, wherein the sensor is a pulse oximeter sensor.

* * * * *

专利名称(译)	无创生理传感器盖		
公开(公告)号	US8886271	公开(公告)日	2014-11-11
申请号	US13/919692	申请日	2013-06-17
[标]申请(专利权)人(译)	CERCACOR LAB		
申请(专利权)人(译)	cercacor制药公司.		
当前申请(专利权)人(译)	CERCACOR LABORATORIES, INC.		
[标]发明人	KIANI ABRAHAM MAZDA KIANI MASSI JOE E		
发明人	KIANI, ABRAHAM MAZDA KIANI, MASSI JOE E.		
IPC分类号	A61B5/00 A61B5/1455 A61B5/02		
CPC分类号	A61B5/6826 A61B5/6838 A61B5/14552 A61B5/02416 A61B5/14532 A61B5/14546 A61B5/6816 A61B5/6819 A61B5/6829 A61B5/6832 A61B5/68335 A61B5/02427		
优先权	61/229682 2009-07-29 US		
其他公开文献	US20130345531A1		
外部链接	Espacenet USPTO		

摘要(译)

根据本公开的实施例的传感器盖能够与非侵入性生理传感器一起使用，例如脉搏血氧测量传感器。当传感器未使用时，传感器盖的某些实施例减少或消除来自传感器的错误读数，例如，当脉冲血氧计传感器激活但未使用时，通过阻挡脉冲血氧计传感器的光检测部件。此外，传感器盖的实施例可以防止对传感器的损坏。另外，传感器盖的实施例防止传感器的污染。

