



US009510385B2

(12) **United States Patent**
Singh

(10) **Patent No.:** **US 9,510,385 B2**
(45) **Date of Patent:** ***Nov. 29, 2016**

(54) **METHODS AND APPARATUS TO CONNECT WIRELESS-ENABLED DEVICES**

(71) Applicant: **BlackBerry Limited**, Waterloo (CA)
(72) Inventor: **Jasjit Singh**, New Delhi (IN)
(73) Assignee: **BlackBerry Limited**, Waterloo, Ontario (CA)

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 0 days.
This patent is subject to a terminal disclaimer.

(21) Appl. No.: **14/980,078**
(22) Filed: **Dec. 28, 2015**

(65) **Prior Publication Data**
US 2016/0135245 A1 May 12, 2016

Related U.S. Application Data
(63) Continuation of application No. 14/590,673, filed on Jan. 6, 2015, now Pat. No. 9,253,812, which is a continuation of application No. 13/635,326, filed as application No. PCT/US2011/025720 on Feb. 22, 2011, now Pat. No. 8,934,839.

(51) **Int. Cl.**
H04B 7/00 (2006.01)
H04W 76/02 (2009.01)
(Continued)

(52) **U.S. Cl.**
CPC **H04W 76/023** (2013.01); **A61B 5/0022** (2013.01); **A61B 5/0024** (2013.01); **H04L 9/0866** (2013.01); **H04L 63/0428** (2013.01); **H04L 63/0442** (2013.01); **H04L 63/0492** (2013.01); **H04L 63/0861** (2013.01); **H04M 1/67** (2013.01); **H04M 1/7253** (2013.01); **H04W 4/008** (2013.01); **H04W 8/005** (2013.01);
(Continued)

(58) **Field of Classification Search**
CPC H04W 76/023; A61B 5/0022; H04L 63/0442
USPC 455/41.2, 41.3, 39, 410, 411; 600/309, 600/509; 340/539.12
See application file for complete search history.

(56) **References Cited**
U.S. PATENT DOCUMENTS

5,634,468 A 6/1997 Platt et al.
6,385,318 B1 5/2002 Oishi
(Continued)

FOREIGN PATENT DOCUMENTS

WO 2009/032134 3/2009


OTHER PUBLICATIONS

Poon et al., "A Novel Biometrics Method to Secure Wireless Body Area Sensor Networks for Telemedicine and M-Health," IEEE Communications Magazine, Apr. 2006, 9 pages.
(Continued)

Primary Examiner — Sonny Trinh
(74) *Attorney, Agent, or Firm* — Fish & Richardson P.C.

(57) **ABSTRACT**
Examples to establish a connection between wireless-enabled devices involve collecting first biophysical signal data via a first wireless-enabled device, using the first biophysical signal data as a key to decrypt encrypted information received from a second wireless-enabled device to recover first information, and establishing a wireless connection between the first wireless-enabled device and the second wireless-enabled device based on a comparison of the first information and second information stored in the first wireless-enabled device.

20 Claims, 9 Drawing Sheets



(51) Int. Cl.		2009/0118595 A1	5/2009	Greiner et al.
H04L 29/06	(2006.01)	2010/0009628 A1	1/2010	Hebiguchi
H04M 1/67	(2006.01)	2010/0113950 A1	5/2010	Lin et al.
H04M 1/725	(2006.01)	2011/0071364 A1	3/2011	Kuo et al.
H04W 8/00	(2009.01)	2011/0221590 A1	9/2011	Baker et al.
A61B 5/00	(2006.01)	2013/0005266 A1	1/2013	Singh
H04W 12/04	(2009.01)			
H04W 12/06	(2009.01)			
H04L 9/08	(2006.01)			
H04W 4/00	(2009.01)			
A61B 5/024	(2006.01)			
H04L 29/08	(2006.01)			

OTHER PUBLICATIONS

Bao et al., "Physiological Signal Based Entity Authentication for Body Area Sensor Networks and Mobile Healthcare Systems," Engineering in Medicine and Biology Society, 2005, 4 pages.

Bao et al., "Using the Timing Information of Heartbeats as an Entity Identifier to Secure Body Sensor Network," IEEE Transactions on Information Technology in Biomedicine, vol. 12, No. 6, Nov. 2008, 8 pages.

Ullah et al., "On PHY and MAC Performance in Body Sensor Networks," EURASIP Journal on Wireless Communications and Networking, May 14, 2009, 7 pages.

Strogatz et al., "Coupled Oscillators and Biological Synchronization," Scientific American, Dec. 1993, 7 pages.

Tulyakov et al., "Identification Model with Independent Matching Scores," The Biometric Consortium Conference, Sep. 19-21, 2005, Arlington, VA, USA, [retrieved from http://www.biometrics.org/bc2005/Presentations/Conference/1%20Monday%20September%2019/Poster%20Session/Govindaraju_identification_model.pdf] 2 pages.

Deliot et al., "Self-Stabilizing Pulse Synchronization Inspired by Biological Pacemaker Networks," Mar. 13, 2003, 31 pages.

Patent Cooperation Treaty, "International Preliminary Report on Patentability," issued by the International Bureau in connection with PCT application No. PCT/US2011/025720, mailed Aug. 27, 2013 (6 pages).

Patent Cooperation Treaty, "International Search Report," issued by the International Searching Authority in connection with PCT application No. PCT/US2011/025720, mailed Dec. 6, 2011 (4 pages).

Patent Cooperation Treaty, "Written Opinion of the International Searching Authority," issued by the International Searching Authority in connection with PCT/US2011/025720, mailed Dec. 6, 2011 (7 pages).

(52) **U.S. Cl.**
 CPC **H04W12/04** (2013.01); **H04W 12/06** (2013.01); **A61B 5/024** (2013.01); **H04L 63/101** (2013.01); **H04L 67/12** (2013.01); **H04M 2250/12** (2013.01)

(56) **References Cited**

U.S. PATENT DOCUMENTS

6,558,320 B1	5/2003	Casey et al.	
6,774,796 B2	8/2004	Smith	
7,043,305 B2	5/2006	KenKnight et al.	
7,058,453 B2	6/2006	Nelson et al.	
7,171,177 B2	1/2007	Park et al.	
7,181,505 B2	2/2007	Haller et al.	
7,324,850 B2	1/2008	Persen et al.	
7,353,063 B2	4/2008	Simms, Jr.	
7,782,193 B2	8/2010	Goh et al.	
7,796,531 B2	9/2010	Jaatinen	
7,859,401 B2	12/2010	Falck et al.	
7,978,062 B2	7/2011	Lalonde et al.	
7,978,063 B2	7/2011	Baldus et al.	
8,291,220 B2	10/2012	Singh	
8,587,427 B2	11/2013	Lalonde et al.	
8,632,463 B2	1/2014	Drinan et al.	
8,934,839 B2	1/2015	Singh	
9,015,008 B2	4/2015	Geva et al.	
2008/0039140 A1	2/2008	Morris et al.	
2008/0208008 A1*	8/2008	Turner	A61B 5/0006 600/300

* cited by examiner




FIG. 1




FIG. 2




FIG. 3





FIG. 4



500 ↗

FIG. 5




FIG. 6




FIG. 7A




FIG. 7B




FIG. 8A




FIG. 8B

METHODS AND APPARATUS TO CONNECT WIRELESS-ENABLED DEVICES

RELATED APPLICATIONS

This patent arises from a continuation of U.S. patent application Ser. No. 14/590,673, filed on Jan. 6, 2015, which is a continuation of U.S. patent application Ser. No. 13/635,326, filed on Sep. 14, 2012, which is a national phase entry of PCT/US11/25720, filed on Feb. 22, 2011, all of which are hereby incorporated herein by reference in their entireties.

FIELD OF THE DISCLOSURE

The present disclosure relates generally to mobile communication devices and, more particularly, to methods and apparatus to connect wireless-enabled devices.

BACKGROUND

Wireless radio communication technologies are used in many devices to enable such devices to establish wireless connections with one another. Such wireless radio communication technologies include Bluetooth® wireless technology, IEEE® 802.11 wireless technology, and other wireless technologies capable of short-range wireless connections. Known techniques for establishing wireless connections between devices typically require users to enter passwords or pass codes and/or perform other user entry operations prior to making a successful connection to ensure that the connection is intended and that the user is aware of and consents to the connection being established. For example, synching or pairing of phones, smart phones, or other devices over wireless connections (e.g., Bluetooth® wireless connections) using known techniques involves a user-driven process in which a user is heavily involved throughout the process of establishing a connection. For example, user involvement in such known techniques for enabling Bluetooth® radios and/or other wireless technology radios to synch or connect mobile devices typically require users to activate a connecting/pairing process, initiate discovery of devices, and select discovered devices with which to connect. After a user has successfully navigated through several graphical user interfaces, provided the correct information, and made a number of selections, a wireless connection between two devices may be established.

BRIEF DESCRIPTION OF THE DRAWINGS

FIG. 1 depicts an example manner of using bio-certification processes to establish wireless connections between wireless-enabled devices.

FIG. 2 depicts an example wireless-enabled device of FIG. 1 configured to establish wireless connections with other wireless-enabled devices based on a bio-certification process.

FIG. 3 depicts an example graphical user interface for use with the example wireless-enabled device of FIGS. 1 and 2 to setup the wireless-enabled device for using a bio-certification process to establish wireless connections with other wireless-enabled devices.

FIG. 4 depicts an example graphical user interface for displaying a message via the example wireless-enabled device of FIGS. 1 and 2 requesting user-confirmation to establish a wireless connection with another wireless-enabled device.

FIG. 5 depicts an example apparatus to enable the example wireless-enabled device of FIGS. 1 and 2 to establish wireless connections based on bio-certification processes.

FIG. 6 depicts an example block diagram of the wireless-enabled device of FIGS. 1 and 2.

FIGS. 7A and 7B depict an example flow diagram representative of computer readable instructions that may be used to initiate a bio-certification process to establish a wireless connection between two wireless-enabled devices.

FIGS. 8A and 8B depict an example flow diagram representative of computer readable instructions that may be used to receive a request from a wireless-enabled device to establish a wireless connection based on a bio-certification process.

DETAILED DESCRIPTION

Although the following discloses example methods, apparatus, and articles of manufacture including, among other components, software executed on hardware, it should be noted that such methods, apparatus, and articles of manufacture are merely illustrative and should not be considered as limiting. For example, it is contemplated that any or all of these hardware and software components could be embodied exclusively in hardware, exclusively in software, exclusively in firmware, or in any combination of hardware, software, and/or firmware. Accordingly, while the following describes example methods, apparatus, and articles of manufacture, persons having ordinary skill in the art will readily appreciate that the examples provided are not the only way to implement such methods, apparatus, and articles of manufacture.

It will be appreciated that for simplicity and clarity of illustration, where considered appropriate, reference numerals may be repeated among the figures to indicate corresponding or analogous elements. In addition, numerous specific details are set forth in order to provide a thorough understanding of example embodiments disclosed herein. However, it will be understood by those of ordinary skill in the art that example embodiments disclosed herein may be practiced without these specific details. In other instances, well-known methods, procedures and components have not been described in detail so as not to obscure example embodiments disclosed herein. Also, the description is not to be considered as limiting the scope of example embodiments disclosed herein.

Example methods, apparatus, and articles of manufacture are disclosed herein in connection with wireless-enabled devices, which may be any mobile communication device, mobile computing device, or any other element, entity, device, or service capable of communicating wirelessly. Mobile devices, also referred to as terminals, wireless terminals, mobile stations, communication stations, or user equipment (UE), may include mobile smart phones (e.g., BlackBerry® smart phones), wireless personal digital assistants (PDA), laptop/notebook/netbook computers with wireless adapters, etc. Example methods, apparatus, and articles of manufacture are disclosed herein in connection with Bluetooth® wireless communication technologies. However, such disclosed example methods, apparatus, and articles of manufacture may additionally or alternatively be implemented in connection with other wireless communication standards including the wireless local area network (WLAN) communication standard known as IEEE® 802.11, ZIGBEE® radio technology, wireless USB radio technol-

ogy, and ultra-wideband (UWB) radio technology, or any other WLAN standards or personal area network (PAN) standards.

Example methods, apparatus, and articles of manufacture disclosed herein may be used to securely establish connections between devices based on bio-certification processes. Such example methods, apparatus, and articles of manufacture enable securely connecting two wireless-enabled devices by using biophysical signals generated by a person to confirm that both devices are in contact with the same person and, thus, within control of the same user. That is, known techniques require users to enter passwords and/or perform other user entry operations prior to making a successful connection to ensure that the connection is intended and that the user is aware of and consents to the connection being established. For example, synching or pairing of phones, smart phones, or other devices over wireless connections (e.g., Bluetooth® wireless connections) using known techniques involves a cumbersome user-driven process. User involvement in such known techniques for enabling Bluetooth® radios and/or other wireless technology radios to synch or connect mobile devices typically require users to activate a connecting/pairing process, initiate discovery of devices, and select discovered devices with which to connect. Such known connection processes burden users with a steep learning curve to understand how to properly navigate user interfaces and enter correct information (e.g., pass codes, device selections, etc.) to successfully establish device-to-device connections.

Unlike such known techniques that require much user involvement prior to making successful connections, example methods, apparatus, and articles of manufacture disclosed herein enable connections between devices based on those devices being in physical contact with the same person. That is, two devices in physical contact with the same person record and/or measure a biophysical signal of the person and compare collected biophysical signal data to confirm that the devices are actually in contact with the same person (e.g., being held by or worn by the same person). After both devices confirm that they have detected and/or measured the same biophysical signal, the devices can establish a connection between one another to transfer information therebetween (e.g., transfer files, exchange messages, stream audio and/or video, share an internet connection, etc.).

Example techniques disclosed herein enable users to use an intuitive, one-step or minimal-step process to establish device-to-device connections while allowing users to maintain control of specifying devices with which connections are permitted and when such connections are permitted. Example techniques disclosed herein also enable devices to be available at all times for establishing a connection in a secure manner. In this manner, operations such as synchronizing, exchanging, transferring, and/or streaming data can be automated without requiring users to perform a cumbersome manually-driven process to establish connections. Comparing collected biophysical signal data to confirm that connections can be made is referred to herein as bio-certification. Such bio-certification enables certifying that the same user is in control of two or more devices seeking to establish a connection(s) between one another.

FIG. 1 depicts an example manner of using example bio-certification processes to establish wireless connections between wireless-enabled devices. In the illustrated example, a person 100 holds example wireless-enabled mobile devices 102 and 104 and wears example wireless-enabled headphones 106. As discussed in detail below, the

example wireless-enabled devices 102, 104, and 106 are configured to use example bio-certification processes disclosed herein to establish wireless connections between one another.

In the illustrated example of FIG. 1, bio-certification processes use a heart rate generated by a beating heart 108 of the person 100. As the heart 108 pumps blood through the body of the person 100, biophysical signals 110 in the form of a heart pulse are generated by and travel through the body of the person 100. Such biophysical signals 110 can be detected and/or measured using sensors (e.g., biophysical signal sensors, biometric sensors, etc.). In the illustrated example of FIG. 1, each of the wireless-enabled devices 102, 104, and 106 is provided with a respective sensor to detect the biophysical signals 110 and collect/store biophysical signal data based on those biophysical signals 110. The wireless-enabled devices 102, 104, and 106 can then exchange the collected biophysical signal data and perform comparisons between received biophysical signal data and their locally collected biophysical signal data to determine whether such data matches to enable establishing wireless connections between one another.

As shown in the illustrated example of FIG. 1, the wireless-enabled device 102 can detect the biophysical signals 110 of the person 100 and collect biophysical signal data 112 to initiate a bio-certification process to establish a wireless connection 114 with the wireless-enabled device 104. In the illustrated example, the biophysical signal data 112 is a heart rate or heart frequency calculated by the wireless-enabled device 102. Additionally or alternatively, the biophysical signal data 112 may be a heartbeat wavelength or some other pattern(s) or number(s) calculated based on the pumping action of the heart 108. In some examples, the biophysical signal data 112 may be related to, based on, or otherwise indicative of other characteristics of the person 100 such as blood pressure, body temperature, etc.

To request the wireless connection 114, the wireless-enabled device 102 broadcasts or otherwise sends the biophysical signal data 112 to the wireless-enabled device 104 via a broadcast channel or any other suitable communication channel (e.g., an open communication channel) prior to establishing the wireless connection 114. When the wireless-enabled device 104 receives the biophysical signal data 112, it compares the biophysical signal data 112 to locally collected biophysical signal data 113 collected by the wireless-enabled device 104 based on its operations of detecting the biophysical signals 110. When the wireless-enabled device 104 confirms that the biophysical signal data 112 matches (or substantially matches within a difference threshold range defined by, for example, a matching score range or threshold) its locally collected biophysical signal data 113, the wireless-enabled device 104 can accept the request from the wireless-enabled device 102 to establish the wireless connection 114. A similar process can be used to establish a wireless connection between one or both of the wireless-enabled devices 102 and/or 104 and the wireless-enabled headphones 106. For example, the wireless-enabled headphones 106 may be provided with sensors to detect the biophysical signals 110 at an ear region of the person 100. In some examples, to establish wireless connections, the wireless-enabled devices 102, 104, and 106 send their respective biophysical signal data (e.g., the biophysical signal data 112 and 113) to a central location (e.g., another device or a server). The biophysical signal data can then be compared at the central location (rather than at the wireless-enabled devices that collected the biophysical signal data) to

confirm whether a match (or substantial match) is found. Comparison results or any other indications of whether a wireless connection can be established can then be communicated back to the wireless-enabled devices.

In the illustrated example, one or more of the wireless-enabled devices **102**, **104**, and **106** can initiate a request to establish a wireless connection (e.g., the wireless connection **114**) based on a user-input (e.g., a user depressing a hardware button on a respective device or a soft icon displayed by a respective device) or based on a user (e.g., the person **100**) coming into physical contact therewith. For example, any of the wireless-enabled devices **102**, **104**, and **106** may automatically begin a bio-certification process in response to detecting a biophysical signal **110** of the person **100** (e.g., when the person **100** picks up or puts on the wireless-enabled device). In some examples, the wireless-enabled devices **102**, **104**, and **106** may be configurable to initiate bio-certification processes based on automatic detection of biophysical signals **110** or based on user-input(s) requesting to initiate the bio-certification processes.

In the illustrated example, the wireless connection **114** remains established until the person **110** releases one or both of the wireless-enabled devices **102** and **104**. In some examples, the wireless connection **114** may remain established until a requested data transfer (e.g., a file transfer) or media stream is finished. In such examples, the wireless connection **114** may be re-established via a bio-certification process each time a new data transfer (e.g., a file transfer) or media stream is requested.

In the illustrated example, the wireless-enabled devices **102** and **104** may establish the wireless connection **114** using Bluetooth® wireless technology, Institute of Electrical and Electronics Engineers (IEEE®) 802.11 wireless technology, or any other wireless technology suitable for connecting devices. In addition, although the example of FIG. 1 shows the wireless-enabled device **102** connecting to the wireless-enabled device **104**, example techniques disclosed herein may also be used to establish wireless connections between any one or more of the wireless-enabled device **102**, the wireless-enabled device **104**, and/or the wireless-enabled headphones **106** and any other device not shown. Such other wireless-enabled devices may be tablet computing devices (e.g., the Research In Motion® BlackBerry® PlayBook™ tablet), personal computers, printers, projectors, or any other wireless-enabled device. Any such wireless-enabled device may be provided with a sensor to contact or engage a person (e.g., the person **100**) for detecting a biophysical signal (e.g., the biophysical signals **110**) of the person for use in establishing wireless connections (e.g., the wireless connection **114**) with other devices as disclosed herein. Sensors for detecting biophysical signals may be integrally formed with a housing of a wireless-enabled device or may be attachable as a peripheral to a wireless-enabled device. For example, a desktop or laptop personal computer may have a sensor connected thereto via a universal serial bus (USB) connection or other wired or wireless connection.

In the illustrated example, the wireless-enabled devices **102**, **104**, and **106** beneficially use instant or currently measured biophysical signal data (e.g., the biophysical signal data **112**) to enable establishing wireless connections (e.g., the wireless connection **114**) instead of using previously measured and stored biophysical signal data. Configuring the wireless-enabled devices **102**, **104**, and **106** to use instant or currently measured biophysical signal data to compare to received biophysical signal data (e.g., the biophysical signal data **112**) measured at and received from other devices increases the likelihood that two wireless-

enabled devices held by or in contact with the same person (e.g., the person **100**) will produce biophysical signal data resulting in an exact or near-exact match. For example, for instances in which the biophysical signal data **112** is based on heart-related signals (e.g., electrocardiogram (EKG) signals, heart rate, etc.) of the person **100**, comparing current heart-related signal data with previously measured and stored heart-related signal data is more likely to produce non-matching results because a person's heart rate can fluctuate significantly over time. Thus, although not necessary, the example wireless-enabled device **102** of the illustrated example of FIG. 1 measures and collects instant or current biophysical signal data (e.g., the biophysical signal data **112**) of the person **100** and sends the same to the wireless-enabled device **104**. The wireless-enabled device **104** also measures and collects instant or current biophysical signal data of the person **100** and compares the locally collected biophysical signal data **113** with the received biophysical signal data **112** to determine whether the same person **100** is holding (and, thus, in control of) both of the wireless-enabled devices **102** and **104**.

In some examples, wireless-enabled devices (e.g., the wireless-enabled devices **104** and/or **106**) receiving a request to establish a wireless connection (e.g., the wireless connection **114**) may compare received biophysical signal data (e.g., the biophysical signal data **112**) with locally stored historical biophysical signal data rather than instantaneous or currently collected biophysical signal data such as the locally collected biophysical signal data **113**. In such some examples, the historical biophysical signal data may be stored in association with location and time tags indicating a location at which a wireless-enabled device (e.g., the wireless-enabled device **104** or **106**) was located when the historical biophysical signal data was collected and a time of day when the data was collected. In this manner, the wireless-enabled device may store multiple sets of historical biophysical signal data, each tagged with corresponding location and time tags. When another wireless-enabled device (e.g., the wireless-enabled device **102**) sends a request for connection it sends current biophysical signal data (e.g., the biophysical signal data **112**) reflective of a person's current heart rate along with location and time tags indicating a current location of the wireless-enabled device and a current time of day. In this manner, a wireless-enabled device (e.g., the wireless-enabled device **104** or **106**) receiving the request for connection and the current biophysical signal data can use the received location and time tags to retrieve stored historical biophysical signal data having the same (or substantially the same within an acceptable tolerance or threshold) location and time tags. By retrieving historical biophysical signal data associated with the same location and time tags, there is a greater likelihood that the retrieved historical biophysical signal data will match (or substantially match) the current biophysical signal data received from the wireless-enabled device requesting a connection so long as the current biophysical signal data is collected from the same person from which the historical biophysical signal data was collected. That is, the person's heart rate will likely be influenced by the same environmental factors when the person is located at the same location (e.g., work, home, a gym, a shopping center, a coffee shop, a retail establishment, etc.) at the same time of day. Thus, the person's heart rate on any given day at a particular location at a particular time of day will be expected to vary by only some small amount, if at all, from that same person's heart rate on any prior day at the same location and time when historical biophysical signal data was collected. In some

examples, multiple sets of historical biophysical signal data collected on different days could be averaged (or processed using some other mathematical/statistical operation) to form a standard or average historical biophysical signal data for a particular time and location. In such some examples, an acceptable variation can be determined based on the average variation between multiple, separate historical biophysical signal data for a particular time and location. The acceptable variation can then be used to form a tolerance or threshold matching score that indicates an acceptable substantial match between current biophysical signal data and historical biophysical signal data. If at any subsequent time a wireless connection cannot be established due to the current biophysical signal data varying from the historical biophysical signal data by more than the determined acceptable variation, one or both of the wireless-enabled devices sought to be wirelessly connected can be configured to display icons on a graphical user interface that are selectable by the user to suggest activities that would affect the user's current heart rate (or a heart waveform such as an EKG waveform) to match the historical biophysical signal data. In this manner, a person's current biophysical signal data can match (or sufficiently match) that same person's stored historical biophysical signal data to allow establishing a wireless connection between wireless-enabled devices.

FIG. 2 depicts the example wireless-enabled device 102 of FIG. 1 configured to establish wireless connections (e.g., the wireless connection 114 of FIG. 1) with other wireless-enabled devices (e.g., one or both of the wireless-enabled devices 104 and 106 of FIG. 1) based on a bio-certification process as discussed above in connection with FIG. 1. In the illustrated example of FIG. 1, the wireless-enabled device 102 is depicted as a smart phone. However, the structures and features disclosed in connection with FIG. 2 to enable performing bio-certification processes may be implemented in connection with other types of wireless-enabled devices.

As shown in FIG. 2, the wireless-enabled device 102 is provided with a sensor 202 to detect the biophysical signals 110 of the person 100 shown in FIG. 1. In the illustrated example, the sensor 202 is configured to contact or engage one or more fingers of the person 100 and/or the palm of a hand of the person 100 when the person 100 holds the wireless-enabled device 102. Such surface contact with the person 100 facilitates detecting and measuring the biophysical signals 110 via the sensor 202. The example sensor 202 of FIG. 2 is connected to one or more circuits in the wireless-enabled device 102 that enable the wireless-enabled device 102 to measure the biophysical signals 110 and collect the biophysical signal data 112 (FIG. 1) based on the biophysical signals 110. In some examples, the wireless-enabled device 102 may be configured to automatically detect the biophysical signals 110 and automatically begin a bio-certification process in response to a user grabbing, holding, or wearing the wireless-enabled device 102 or otherwise physically contacting the sensor 202.

Although the sensor 202 is shown as protruding from the wireless-enabled device 102, in other examples, the sensor 202 may be flat, seamless, and/or unitarily formed with the housing 206. In some examples, the sensor 202 may be a substantially large portion of a surface area of the housing 206 to enable contacting a relatively larger surface area of the person 100. In some examples, the wireless-enabled device 102 may be provided with multiple sensors substantially similar or identical to the sensor 202 to facilitate measuring and collecting biophysical signal data 112 based on various techniques employed by the person 100 or any other person for holding or wearing the wireless-enabled

device 102. Sensors substantially similar to the sensor 202 of FIG. 2 may be adapted for use in connection with wireless-enabled devices that are wearable such as the wireless-enabled headphones 106 of FIG. 1. For example, sensors for wearable wireless-enabled devices may be structured and located on the devices in configurations that facilitate contact with body parts or body locations of users at which biophysical signals (e.g., the biophysical signals 110 of FIG. 1) can be detected.

Also shown in FIG. 2, the wireless-enabled device 102 is provided with a hardware button 204 (e.g., a convenience key that is user-programmable to start a particular process or application) located on and/or protruding from a housing 206 of the wireless-enabled device 102. The wireless-enabled device 102 is also shown displaying an icon 208 on a display 210 of the wireless-enabled device 102. In the illustrated example of FIG. 2, the hardware button 204 and the icon 208 are configured to receive user inputs to initiate bio-certification processes to establish wireless connections (e.g., the wireless connection 114 of FIG. 1) as described above in connection with FIG. 1. For example, when in physical contact with the sensor 202, the person 100 (FIG. 1) may depress the button 204 or select the icon 208 to initiate a bio-certification process during which the wireless-enabled device 102 measures and collects the biophysical signal data 112 via the sensor 202 based on the biophysical signals 110 of FIG. 1. In some examples, the wireless-enabled device 102 may be provided with only one of the button 204 or the icon 208 to initiate bio-certification processes.

FIG. 3 depicts an example bio-certification setup graphical user interface (GUI) 300 for use with the example wireless-enabled device 102 of FIGS. 1 and 2 to setup the wireless-enabled device 102 for using a bio-certification process to establish wireless connections (e.g., the wireless connection 114 of FIG. 1) with other wireless-enabled devices (e.g., the wireless-enabled devices 104 and 106 of FIG. 1). In the illustrated example, the bio-certification setup GUI 300 is provided with an approved-devices setup display area 302 and a user-confirmation setup display area 304. In the illustrated example, the approved-devices setup display area 302 enables users to specify devices with which the wireless-enabled device 102 may establish wireless connections (e.g., the wireless connection 114 of FIG. 1) using bio-certification processes. In the example of FIG. 3, a user has specified that the wireless-enabled device 102 may use bio-certification processes to establish wireless connections with a tablet device, headphones, a computer, a second phone, a watch, a car, an appliance. In other examples, fewer of the devices listed in FIG. 3 may be selected or approved by a user.

In the illustrated example, the user-confirmation setup display area 304 enables users to specify devices that require user-confirmation before successfully establishing wireless connections (e.g., the wireless connection 114 of FIG. 1) between the wireless-enabled device 102 and such devices specified in the user-confirmation setup display area 304. In the illustrated example of FIG. 3, a user has specified that user-confirmation is required before establishing a wireless connection with a 'computer,' a 'second phone,' and an 'appliance,' while user-confirmation is not required for a 'tablet device,' 'headphones,' a 'watch,' or a 'car.'

According to the user-specified setup shown in the user-confirmation setup display area 304, a bio-certification process between the wireless-enabled device 102 and the computer may be initiated, but will result in successfully establishing a wireless connection only if matching (or

substantially matching) biophysical signal data is found and if a user confirms that the wireless connection may be established. For devices not requiring user-confirmation based on the user-confirmation setup display area **304** of FIG. **3**, such devices can establish a wireless connection with the wireless-enabled device **102** without user confirmation. Thus, a bio-certification process between the wireless-enabled device **102** and the 'tablet device' listed in the user-confirmation setup display area **304** will result in successfully establishing a wireless connection if matching (or substantially matching) biophysical signal data is found without needing to receive user confirmation that the wireless connection may be established.

While the devices listed in FIG. **3** are indicated by generic device type names, in other examples the devices listed in FIG. **3** may be indicated by more specific identifiers (e.g., identifiers to uniquely identify particular devices discovered by the wireless-enabled device **102**). For example, instead of 'tablet device', a unique identifier may be 'Joe's BlackBerry® PlayBook™' and instead of 'appliance', a unique identifier may be 'family room television' or 'Acme-brand television.'

FIG. **4** depicts an example GUI message **400** to be displayed via the example wireless-enabled device **102** of FIGS. **1** and **2** (or any other wireless-enabled device) requesting user-confirmation to establish a wireless connection with another wireless-enabled device (e.g., the wireless-enabled device **104** or the wireless-enabled headphones **106** of FIG. **1**). In the illustrated example of FIG. **4**, the GUI message **400** requests a user to confirm whether the wireless-enabled device can proceed with establishing a wireless connection (e.g., the wireless connection **114** of FIG. **1**) with a computer. In some examples, the wireless-enabled device **102** displays the GUI message **400** of the illustrated example (or a similar GUI message) in response to receiving an acknowledgement from the discovered wireless-enabled device that biophysical signal data collected at the discovered wireless-enabled device matches (or substantially matches) biophysical signal data (e.g., the biophysical signal data **112** of FIG. **1**) collected at the wireless-enabled device **102**. If a user (e.g., the person **100** of FIG. **1**) selects a 'YES' option **402** of the GUI message **400**, the wireless-enabled device **102** and the discovered wireless-enabled device establish a wireless connection therebetween (provided matching (or substantially matching) biophysical signal data is found between the two wireless-enabled devices). If the user selects a 'NO' option **404** of the GUI message **400**, a wireless connection is not established between the wireless-enabled device **102** and the discovered wireless-enabled device.

FIG. **5** depicts an example apparatus **500** to enable the example wireless-enabled device **102** (and/or the wireless-enabled devices **104** and/or **106**) of FIGS. **1** and **2** to establish wireless connections (e.g., the wireless connection **114** of FIG. **1**) based on bio-certification processes. In some examples, the apparatus **500** of the illustrated example may be implemented using the example processor system described below in connection with FIG. **6**. In the illustrated example of FIG. **5**, the apparatus **500** is provided with a configuration data store **502**, a connection arbiter **504**, a biophysical signal data collector **506**, a comparator **508**, one or more communication interface(s) **510**, and an encryption codec **512**. The configuration data store **502**, the connection arbiter **504**, the biophysical signal data collector **506**, the comparator **508**, the communication interface(s) **510**, and/or the encryption codecs **512** may be implemented using any desired combination of hardware, firmware, and/or software.

For example, one or more integrated circuits, discrete semiconductor components, and/or passive electronic components may be used. Thus, for example, the configuration data store **502**, the connection arbiter **504**, the biophysical signal data collector **506**, the comparator **508**, the communication interface(s) **510**, and/or the encryption codec **512** or parts thereof, could be implemented using one or more circuit(s), programmable processor(s), application specific integrated circuit(s) (ASIC(s)), programmable logic device(s) (PLD(s)), field programmable logic device(s) (FPLD(s)), etc. The configuration data store **502**, the connection arbiter **504**, the biophysical signal data collector **506**, the comparator **508**, the communication interface(s) **510**, and/or the encryption codec **512** or parts thereof, may be implemented using instructions, code, and/or other software and/or firmware, etc. stored on a machine accessible medium and executable by, for example, a processor (e.g., the main processor **602** of FIG. **6**). When any of the appended claims are read to cover a purely software implementation, at least one of the configuration data store **502**, the connection arbiter **504**, the biophysical signal data collector **506**, the comparator **508**, the communication interface(s) **510**, or the encryption codec **512** is hereby expressly defined to include a tangible medium such as a solid state memory, a magnetic memory, a DVD, a CD, etc.

Turning in detail to FIG. **5**, the apparatus **500** is provided with the configuration data store **502** to store user-specified preferences associated with using bio-certification processes to connect with other wireless-enabled devices. In the illustrated example, the configuration data store **502** stores preferences specified by a user via the bio-certification setup GUI **300** of FIG. **3**. Additionally or alternatively, the configuration data store **502** may store preferences specified by a user through means other than the bio-certification setup GUI **300**. Such other means include one or more of, for example, other GUIs displayable by the wireless-enabled device **102**, a computer capable of communicating with the wireless-enabled device **102**, a web page, or any other suitable device and/or interface.

To determine whether wireless connections (e.g., the wireless connection **114** of FIG. **1**) are allowable and/or can be established, the apparatus **500** of the illustrated example is provided with the connection arbiter **504**. In the illustrated example, the connection arbiter **504** accesses the configuration data store **502** to determine which devices (e.g., devices listed in the bio-certification setup GUI **300**) a user has specified as approved for bio-certification and which devices the user has approved for automatically establishing wireless connections without requiring user confirmation. During a bio-certification process, the wireless-enabled device **102** performs a discovery process to find other wireless-enabled devices within communication proximity. When the wireless-enabled device **102** receives identities of nearby discovered devices, the connection arbiter **504** compares the discovered devices with devices approved for bio-certification in the configuration data store **502**.

The connection arbiter **504** also analyzes comparison results of locally collected biophysical signal data (e.g., the locally collected biophysical signal data **113** of FIG. **1**) with biophysical signal data (e.g., the biophysical signal data **112** of FIG. **1**) received from another wireless-enabled device. In this manner, if the connection arbiter **504** determines that the two sets of data match or substantially match, the connection arbiter **504** allows the bio-certification process to proceed. In the illustrated example, a substantial match occurs when two biophysical signal data sets match within an acceptable tolerance or threshold based on a matching score associated

with the compared biophysical signal data. In the illustrated example, the connection arbiter **504** stores or can access a stored matching score threshold indicative of a worst-case inexact match for which the connection arbiter **504** can approve establishing a wireless connection. In some examples, one or more matching score threshold(s) can be defined by a user, a device manufacturer, or a telecommunication system network operator to indicate worst-case inexact matches for which the connection arbiter **504** can allow establishing of wireless connections. In some examples, matching score thresholds are stored in the configuration data store **502**. In addition, respective matching score thresholds may be specified for different devices (e.g., the devices listed in the bio-certification setup GUI **300** of FIG. 3).

In addition, while performing a bio-certification process with an approved device and prior to successfully establishing a wireless connection, the connection arbiter **504** checks the configuration data store **502** to determine whether user-confirmation is required for the particular approved device before establishing the wireless connection. If user-confirmation is required, the connection arbiter **504** does not allow or permit establishing of the wireless connection until it has received user confirmation to allow the wireless connection. Such user confirmation may be solicited and received via the GUI message **400** of FIG. 4.

To collect biophysical signal data (e.g., the biophysical signal data **112** of FIG. 1), the apparatus **500** of the illustrated example is provided with the biophysical signal data collector **506**. In the illustrated example, the biophysical signal data collector **506** is in communication with a sensor (e.g., the sensor **202**) configured to engage or contact a person (e.g., the person **100** of FIG. 1) at a location on the person's body that provides access to detecting biophysical signals (e.g., the biophysical signals **110** of FIG. 1) of the person. The biophysical signal data collector **506** of the illustrated example receives signals (e.g., electrical signals) from the sensor **202** representative of the biophysical signals **110**, translates or converts the signals into a digital format, and measures the digital signals to collect biophysical signal data (e.g., the biophysical signal data **112** of FIG. 1). In the illustrated example, the biophysical signal data collector **506** analyzes the digital signals to determine a heart pulse rate or frequency. The biophysical signal data collector **506** then uses the heart pulse rate or frequency as the biophysical signal data **112**. In some examples, the biophysical signal data collector **506** may collect heart beat waveforms (e.g., EKG waveforms) and use such waveforms as the biophysical signal data **112**. In yet other examples, the biophysical signal data collector **506** may determine, form, or generate any other type of data (e.g., amplitudes of maximum or minimum heart beat pulses, quantity of maximum or minimum heart beat pulses above/below a threshold, encrypted or hash or random values using heart rates as seed values or keys or base values, etc.) based on the digital form of the detected biophysical signals **110** to generate the biophysical signal data **112** for purposes of performing comparisons during bio-certification processes.

To compare locally collected biophysical signal data (e.g., the locally collected biophysical signal data **113** of FIG. 1) to biophysical signal data (e.g., the biophysical signal data **112** of FIG. 1) received from other wireless-enabled devices, the apparatus **500** of the illustrated example is provided with a comparator **508**. In the illustrated example, the comparator **508** is configured to compare heart pulse rate or frequency data. Additionally or alternatively, the comparator **508** may be configured to compare any other type of data that is

represented in biophysical signal data (e.g., the biophysical signal data **112**) and may involve comparisons of values and/or comparisons of patterns or waveforms. Such other data may be, for example, heart beat waveforms (e.g., EKG waveforms), amplitudes of maximum or minimum heart beat pulses, quantity of maximum or minimum heart beat pulses above/below a threshold, encrypted or random values using heart rates as seed or base values, etc.

In the illustrated example of FIG. 5, the comparator **508** determines a matching score indicative of how comparatively close two compared data are to one another. For example, the comparator **508** of the illustrated example generates a match score of one (1) for an exact match between two compared biophysical signal data and produces match scores of less than one (1) for inexact matches. In the illustrated example, the comparator **508** sends match scores to the connection arbiter **504**, and the connection arbiter **504** compares the match scores to a match score threshold indicative of a worst-case inexact match for which the connection arbiter **504** can approve establishing a wireless connection.

In the illustrated example, the apparatus **500** is provided with one or more communication interface(s) **510** via which wireless connections (e.g., the wireless connection **114** of FIG. 1) are established. In the illustrated example, the communication interface(s) **510** are wireless. Example wireless communication technologies that may be employed to implement the one or more communication subsystem(s) **1012** include, for example, IEEE® 802.11 radio technology, BLUETOOTH® radio technology, ZIGBEE® radio technology, wireless USB radio technology, and ultra-wideband (UWB) radio technology. Although example methods, apparatus, and articles of manufacture are disclosed herein in connection with establishing wireless connections, such as the wireless connection **114**, between devices, such example methods, apparatus, and articles of manufacture disclosed herein may be similarly used to establish wired connections between devices based on bio-certification processes. In such examples, the communication interface(s) **510** may include one or more wired communication interfaces.

In some examples, the apparatus **500** is provided with the encryption codec **512** to generate, encipher or code hash values based on biophysical signal data (e.g., the biophysical signal data **112** of FIG. 1) to send to other wireless-enabled devices for establishing wireless connections based on bio-certification. The encryption codec **512** also enables the apparatus **500** to decode or decipher hash values received from other wireless-enabled devices based on locally collected biophysical signal data (e.g., the locally collected biophysical signal data **113** of FIG. 1). In such examples, the encryption codec **512** at the wireless-enabled device **102** of FIG. 1 uses the biophysical signal data **112** collected at the wireless-enabled device **102** as a private key to generate a hash of public or shared information (e.g., a value or information that is known to all wireless-enabled devices). The wireless-enabled device **102** then broadcasts the hash to all wireless-enabled devices in communication range. The wireless-enabled device **104** receives the broadcast hash and uses its encryption codec (which is substantially similar or identical to the encryption codec **512** of FIG. 5) to decode or decipher the received hash using the locally collected biophysical signal data **113** of FIG. 1 as the private key. If the biophysical signal data **112** and the locally collected biophysical signal data **113** corresponding to the same person as shown in FIG. 1, the private key used to decode the hash at the wireless-enabled device **104** is the same or substantially the same as the private key used to encode the

hash at the wireless-enabled device **102**. Thus, when the wireless-enabled device **104** decodes the hash, it will recover the same public or shared information. The wireless-enabled device **104** can then use its comparator (which is substantially the same or identical to the comparator **508**) to compare the recovered information to its locally stored public or shared information to confirm a match. A confirmed match informs a connection arbiter **504** of the wireless-enabled device **104** that a wireless connection (e.g., the wireless connection **114** of FIG. 1) is allowed or permissible.

FIG. 6 depicts a block diagram of an example implementation of a processor system that may be used to implement the wireless-enabled device **102**. Although the processor system of FIG. 6 is described as implementing the wireless-enabled device **102**, a processor system identical or similar to the processor system depicted in FIG. 6 may be used to implement the wireless-enabled device **104** of FIG. 1, the wireless-enabled headphones **106** of FIG. 1, and/or the apparatus **500** of FIG. 5. In the illustrated example, the wireless-enabled device **102** is a two-way communication device with advanced data communication capabilities including the capability to communicate with other wireless-enabled devices or computer systems through a network of transceiver stations. The wireless-enabled device **102** may also have the capability to allow voice communication. Depending on the functionality provided by the wireless-enabled device **102**, it may be referred to as a data messaging device, a two-way pager, a cellular telephone with data messaging capabilities, a smart phone, a wireless Internet appliance, or a data communication device (with or without telephony capabilities). To aid the reader in understanding the structure of the wireless-enabled device **102** and how it communicates with other devices and host systems, FIG. 6 will now be described in detail.

Referring to FIG. 6, the wireless-enabled device **102** includes a number of components such as a main processor **602** that controls the overall operation of the wireless-enabled device **102**. In the illustrated example, the sensor **202** and the button (convenience key) **204** described above in connection with FIG. 2 are connected to the main processor **602**. Communication functions, including data and voice communications, are performed through a communication subsystem **604**. The communication subsystem **604** receives messages from and sends messages to a wireless network **605**. In the illustrated example of the wireless-enabled device **102**, the communication subsystem **604** is configured in accordance with the Global System for Mobile Communication (GSM) and General Packet Radio Services (GPRS) standards. The GSM/GPRS wireless network is used worldwide and it is expected that these standards will be superseded eventually by Enhanced Data GSM Environment (EDGE) and Universal Mobile Telecommunications Service (UMTS). New standards are still being defined, but it is believed that they will have similarities to the network behavior described herein, and it will also be understood by persons skilled in the art that the example implementations described herein are intended to use any other suitable standards that are developed in the future. The wireless link connecting the communication subsystem **604** with the wireless network **605** represents one or more different Radio Frequency (RF) channels, operating according to defined protocols specified for GSM/GPRS communications. With newer network protocols, these channels are capable of supporting both circuit switched voice communications and packet switched data communications.

Although the wireless network **605** associated with the wireless-enabled device **102** is a GSM/GPRS wireless net-

work in one exemplary implementation, other wireless networks may also be associated with the wireless-enabled device **102** in variant implementations. The different types of wireless networks that may be employed include, for example, data-centric wireless networks, voice-centric wireless networks, and dual-mode networks that can support both voice and data communications over the same physical base stations. Combined dual-mode networks include, but are not limited to, Code Division Multiple Access (CDMA) or CDMA2000 networks, GSM/GPRS networks (as mentioned above), and future third-generation (3G) networks like EDGE and UMTS. Some other examples of data-centric networks include WiFi 802.11, MOBITECH[®] and DATATAC[®] network communication systems. Examples of other voice-centric data networks include Personal Communication Systems (PCS) networks like GSM and Time Division Multiple Access (TDMA) systems.

The main processor **602** also interacts with additional subsystems such as a Random Access Memory (RAM) **1106**, a persistent memory **608** (e.g., a non-volatile memory), a display **610**, an auxiliary input/output (I/O) subsystem **612**, a data port **614**, a keyboard **616**, a speaker **618**, a microphone **620**, short-range communications **622**, and other device subsystems **624**.

Some of the subsystems of the wireless-enabled device **102** perform communication-related functions, whereas other subsystems may provide "resident" or on-device functions. By way of example, the display **610** and the keyboard **616** may be used for both communication-related functions, such as entering a text message for transmission over the network **605**, and device-resident functions such as a calculator or task list.

The wireless-enabled device **102** can send and receive communication signals over the wireless network **605** after required network registration or activation procedures have been completed. Network access is associated with a subscriber or user of the wireless-enabled device **102**. To identify a subscriber, the wireless-enabled device **102** requires a SIM/RUIM card **626** (i.e. Subscriber Identity Module or a Removable User Identity Module) to be inserted into a SIM/RUIM interface **628** in order to communicate with a network. The SIM card or RUIM **626** is one type of a conventional "smart card" that can be used to identify a subscriber of the wireless-enabled device **102** and to personalize the wireless-enabled device **102**, among other things. Without the SIM card **626**, the wireless-enabled device **102** is not fully operational for communication with the wireless network **605**. By inserting the SIM card/RUIM **626** into the SIM/RUIM interface **628**, a subscriber can access all subscribed services. Services may include: web browsing and messaging such as e-mail, voice mail, Short Message Service (SMS), and Multimedia Messaging Services (MMS). More advanced services may include: point of sale, field service and sales force automation, bio-certification processes to establish wireless connections, such as the wireless connection **114** of FIG. 1. The SIM card/RUIM **626** includes a processor and memory for storing information. Once the SIM card/RUIM **626** is inserted into the SIM/RUIM interface **628**, it is coupled to the main processor **602**. In order to identify the subscriber, the SIM card/RUIM **626** can include some user parameters such as an International Mobile Subscriber Identity (IMSI). An advantage of using the SIM card/RUIM **626** is that a subscriber is not necessarily bound by any single physical mobile device. The SIM card/RUIM **626** may store additional subscriber information for a wireless-enabled device or mobile device as well, including datebook (or calendar) information and recent call

information. Alternatively, user identification information can also be programmed into the persistent memory 608.

The wireless-enabled device 102 is a battery-powered device and includes a battery interface 632 for receiving one or more rechargeable batteries 630. In at least some embodiments, the battery 630 can be a smart battery with an embedded microprocessor. The battery interface 632 is coupled to a regulator (not shown), which assists the battery 630 in providing power V+ to the wireless-enabled device 102. Although current technology makes use of a battery, future technologies such as micro fuel cells may provide the power to the wireless-enabled device 102.

The wireless-enabled device 102 also includes an operating system 634 and software components 636 to 646 which are described in more detail below. The operating system 634 and the software components 636 to 646 that are executed by the main processor 602 are typically stored in a persistent store such as the persistent memory 608, which may alternatively be a read-only memory (ROM) or similar storage element (not shown). Those skilled in the art will appreciate that portions of the operating system 634 and the software components 636 to 646, such as specific device applications, or parts thereof, may be temporarily loaded into a volatile store such as the RAM 606. Other software components can also be included, as is well known to those skilled in the art.

The subset of software applications 636 that control basic device operations, including data and voice communication applications, will normally be installed on the wireless-enabled device 102 during its manufacture. Other software applications include a message application 638 that can be any suitable software program that allows a user of the wireless-enabled device 102 to send and receive electronic messages. Various alternatives exist for the message application 638 as is well known to those skilled in the art. Messages that have been sent or received by the user are typically stored in the persistent memory 608 of the wireless-enabled device 102 or some other suitable storage element in the wireless-enabled device 102. In at least some embodiments, some of the sent and received messages may be stored remotely from the wireless-enabled device 102 such as in a data store of an associated host system that the wireless-enabled device 102 communicates with.

The software applications can further include a device state module 640, a Personal Information Manager (PIM) 642, and other suitable modules (not shown). The device state module 640 provides persistence (i.e., the device state module 640 ensures that important device data is stored in persistent memory, such as the persistent memory 608, so that the data is not lost when the wireless-enabled device 102 is turned off or loses power).

The PIM 642 includes functionality for organizing and managing data items of interest to the user, such as, but not limited to, e-mail, contacts, calendar events, voice mails, appointments, and task items. A PIM application has the ability to send and receive data items via the wireless network 605. PIM data items may be seamlessly integrated, synchronized, and updated via the wireless network 605 with the mobile device subscriber's corresponding data items stored and/or associated with a host computer system. This functionality creates a mirrored host computer on the wireless-enabled device 102 with respect to such items. This can be particularly advantageous when the host computer system is the mobile device subscriber's office computer system.

The wireless-enabled device 102 also includes a connect module 644, and an IT policy module 646. The connect

module 644 implements the communication protocols that are required for the wireless-enabled device 102 to communicate with the wireless infrastructure and any host system, such as an enterprise system, that the wireless-enabled device 102 is authorized to interface with.

The connect module 644 includes a set of APIs that can be integrated with the wireless-enabled device 102 to allow the wireless-enabled device 102 to use any number of services associated with the enterprise system. The connect module 644 allows the wireless-enabled device 102 to establish an end-to-end secure, authenticated communication pipe with the host system. A subset of applications for which access is provided by the connect module 644 can be used to pass IT policy commands from the host system (e.g., from an IT policy server of a host system) to the wireless-enabled device 102. This can be done in a wireless or wired manner. These instructions can then be passed to the IT policy module 646 to modify the configuration of the wireless-enabled device 102. Alternatively, in some cases, the IT policy update can also be done over a wired connection.

The IT policy module 646 receives IT policy data that encodes the IT policy. The IT policy module 646 then ensures that the IT policy data is authenticated by the wireless-enabled device 102. The IT policy data can then be stored in the flash memory 606 in its native form. After the IT policy data is stored, a global notification can be sent by the IT policy module 646 to all of the applications residing on the wireless-enabled device 102. Applications for which the IT policy may be applicable then respond by reading the IT policy data to look for IT policy rules that are applicable.

The IT policy module 646 can include a parser (not shown), which can be used by the applications to read the IT policy rules. In some cases, another module or application can provide the parser. Grouped IT policy rules, described in more detail below, are retrieved as byte streams, which are then sent (recursively, in a sense) into the parser to determine the values of each IT policy rule defined within the grouped IT policy rule. In at least some embodiments, the IT policy module 1146 can determine which applications (e.g., bio-certification processes to establish wireless communications based on comparisons of biophysical signal data, such as the biophysical signal data 112 of FIG. 1) are affected by the IT policy data and send a notification to only those applications. In either of these cases, for applications that aren't running at the time of the notification, the applications can call the parser or the IT policy module 646 when they are executed to determine if there are any relevant IT policy rules in the newly received IT policy data.

All applications that support rules in the IT Policy are coded to know the type of data to expect. For example, the value that is set for the "WEP User Name" IT policy rule is known to be a string; therefore the value in the IT policy data that corresponds to this rule is interpreted as a string. As another example, the setting for the "Set Maximum Password Attempts" IT policy rule is known to be an integer, and therefore the value in the IT policy data that corresponds to this rule is interpreted as such.

After the IT policy rules have been applied to the applicable applications or configuration files, the IT policy module 646 sends an acknowledgement back to the host system to indicate that the IT policy data was received and successfully applied.

Other types of software applications can also be installed on the wireless-enabled device 102. These software applications can be third party applications, which are added after

the manufacture of the wireless-enabled device **102**. Examples of third party applications include games, calculators, utilities, etc.

The additional applications can be loaded onto the wireless-enabled device **102** through at least one of the wireless network **605**, the auxiliary I/O subsystem **612**, the data port **614**, the short-range communications subsystem **622**, or any other suitable device subsystem **624**. This flexibility in application installation increases the functionality of the wireless-enabled device **102** and may provide enhanced on-device functions, communication-related functions, or both. For example, secure communication applications may enable electronic commerce functions and other such financial transactions to be performed using the wireless-enabled device **102**.

The data port **614** enables a subscriber to set preferences through an external device or software application and extends the capabilities of the wireless-enabled device **102** by providing for information or software downloads to the wireless-enabled device **102** other than through a wireless communication network. The alternate download path may, for example, be used to load an encryption key onto the wireless-enabled device **102** through a direct and thus reliable and trusted connection to provide secure device communication.

The data port **614** can be any suitable port that enables data communication between the wireless-enabled device **102** and another computing device. The data port **614** can be a serial or a parallel port. In some instances, the data port **614** can be a USB port that includes data lines for data transfer and a supply line that can provide a charging current to charge the battery **630** of the wireless-enabled device **102**.

The short-range communications subsystem **622** provides for communication between the wireless-enabled device **102** and different systems or devices, without the use of the wireless network **605**. For example, the subsystem **622** may include an infrared device and associated circuits and components for short-range communication. Examples of short-range communication standards include standards developed by the Infrared Data Association (IrDA), Bluetooth, and the 802.11 family of standards developed by IEEE.

In use, a received signal such as a text message, an e-mail message, web page download, media content, etc. will be processed by the communication subsystem **604** and input to the main processor **602**. The main processor **602** will then process the received signal for output to the display **610** or alternatively to the auxiliary I/O subsystem **612**. A subscriber may also compose data items, such as e-mail messages, for example, using the keyboard **616** in conjunction with the display **610** and possibly the auxiliary I/O subsystem **612**. The auxiliary subsystem **612** may include devices such as: a touch screen, mouse, track ball, infrared fingerprint detector, or a roller wheel with dynamic button pressing capability. The keyboard **616** is preferably an alphanumeric keyboard and/or telephone-type keypad. However, other types of keyboards may also be used. A composed item may be transmitted over the wireless network **605** through the communication subsystem **604**.

For voice communications, the overall operation of the wireless-enabled device **102** is substantially similar, except that the received signals are output to the speaker **618**, and signals for transmission are generated by the microphone **620**. Alternative voice or audio I/O subsystems, such as a voice message recording subsystem, can also be implemented on the wireless-enabled device **102**. Although voice or audio signal output is accomplished primarily through the speaker **618**, the display **610** can also be used to provide

additional information such as the identity of a calling party, duration of a voice call, or other voice call related information.

FIGS. **7A**, **7B**, **8A**, and **8B** depict example flow diagrams representative of processes that may be implemented using, for example, computer readable instructions stored on a computer-readable medium to implement bio-certification processes to establish wireless connections between wireless-enabled devices. The example processes of FIGS. **7A**, **7B**, **8A**, and **8B** may be performed using one or more processors, controllers, and/or any other suitable processing devices. For example, the example processes of FIGS. **7A**, **7B**, **8A**, and **8B** may be implemented using coded instructions (e.g., computer readable instructions) stored on one or more tangible computer readable media such as flash memory, read-only memory (ROM), and/or random-access memory (RAM). As used herein, the term tangible computer readable medium is expressly defined to include any type of computer readable storage and to exclude propagating signals. Additionally or alternatively, the example processes of FIGS. **7A**, **7B**, **8A**, and **8B** may be implemented using coded instructions (e.g., computer readable instructions) stored on one or more non-transitory computer readable media such as flash memory, read-only memory (ROM), random-access memory (RAM), cache, or any other storage media in which information is stored for any duration (e.g., for extended time periods, permanently, brief instances, for temporarily buffering, and/or for caching of the information). As used herein, the term non-transitory computer readable medium is expressly defined to include any type of computer readable medium and to exclude propagating signals.

Alternatively, some or all of the example processes of FIGS. **7A**, **7B**, **8A**, and **8B** may be implemented using any combination(s) of application specific integrated circuit(s) (ASIC(s)), programmable logic device(s) (PLD(s)), field programmable logic device(s) (FPLD(s)), discrete logic, hardware, firmware, etc. Also, some or all of the example processes of FIGS. **7A**, **7B**, **8A**, and **8B** may be implemented manually or as any combination(s) of any of the foregoing techniques, for example, any combination of firmware, software, discrete logic and/or hardware. Further, although the example processes of FIGS. **7A**, **7B**, **8A**, and **8B** are described with reference to the flow diagrams of FIGS. **7A**, **7B**, **8A**, and **8B**, other methods of implementing the processes of FIGS. **7A**, **7B**, **8A**, and **8B** may be employed. For example, the order of execution of the blocks may be changed, and/or some of the blocks described may be changed, eliminated, sub-divided, or combined. Additionally, any or all of the example processes of FIGS. **7A**, **7B**, **8A**, and **8B** may be performed sequentially and/or in parallel by, for example, separate processing threads, processors, devices, discrete logic, circuits, etc.

Now turning to FIGS. **7A** and **7B**, the depicted flow diagram is representative of an example process that may be used to initiate a bio-certification process to establish a wireless connection between two wireless-enabled devices. The example process is described below as being performed by the wireless-enabled device **102** as implemented using the apparatus **500** of FIG. **5** to establish a wireless connection (e.g., the wireless connection **114** of FIG. **1**) with the wireless-enabled device **104**. However, the example process may alternatively be performed by the wireless-enabled device **104** and/or the wireless-enabled headphones **106** (or any other device) to establish a wireless connection with the wireless-enabled device **102** (or any other device).

Referring to FIG. **7A**, initially, the wireless-enabled device **102** receives a user-request to establish a wireless

connection (e.g., the wireless connection **114** of FIG. 1) using a bio-certification process (block **702**). For example, the person **100** of FIG. 1 may press the button **204** or select the icon **208** of FIG. 2 (and/or pick up/hold/touch the wireless-enabled device **102** to engage the sensor **202** of FIG. 2) to initiate a bio-certification process.

The wireless-enabled device **102** performs a discovery process to discover nearby wireless-enabled device(s) (block **704**). For example, the wireless-enabled device **102** may use one of the communication interfaces **510** to perform a device discovery process (e.g., a Bluetooth® discovery process) to discover one or both of the wireless-enabled device **104** and/or the wireless-enabled headphones **106** of FIG. 1.

The wireless-enabled device **102** determines whether it found any other wireless-enabled device(s) (block **706**). If the wireless-enabled device **102** does not find any other wireless-enabled device(s), control advances to block **736** of FIG. 7B.

If the wireless-enabled device **102** finds at least one wireless-enabled device (e.g., the wireless-enabled device **104** of FIG. 1) (block **706**), the connection arbiter **504** (FIG. 5) determines whether one or more of the discovered devices is/are eligible to connect using a bio-certification process (block **708**). For example, the connection arbiter **504** can access a listing in the configuration data store **502** (FIG. 5) indicative of devices approved for bio-certification. If the connection arbiter **504** determines that no discovered devices is/are eligible to connect using a bio-certification process, control advances to block **736** of FIG. 7B.

If the connection arbiter **504** determines that at least one of the discovered devices is approved for establishing wireless connections based on bio-certification processes (block **708**), control advances to block **710**, at which the biophysical signal data collector **506** (FIG. 5) monitors for the presence of a biophysical signal (e.g., the biophysical signals **110** of FIG. 1) (block **710**).

If a biophysical signal **110** is not detected (block **712**), the connection arbiter **504** determines whether a timeout has been reached (block **714**). For example, the connection arbiter **504** may start a timeout timer providing sufficient time within which the biophysical signal data collector **506** should detect a biophysical signal **110** before timing out and informing a user that a wireless connection cannot be established because biophysical signals have not been detected. When the timeout has not expired at block **714**, control returns to the example operations of blocks **710** and **712** to determine whether the biophysical signal data collector **506** has detected a biophysical signal **110**. When the timeout has expired at block **714**, control advances to block **736** of FIG. 7B.

When the biophysical signal data collector **506** has detected a biophysical signal **110** (block **712**), control advances to block **716**, at which the biophysical signal data collector **506** collects biophysical signal data (e.g., the biophysical signal data **112** of FIG. 1) (block **716**). The encryption codec **512** (FIG. 5) determines whether to use hashing to request a wireless connection (block **718**). For example, the configuration data store **502** may store preferences or settings indicating whether hashing or encryption techniques should be used during bio-certification processes to establish wireless connections. If the encryption codec **512** determines that it should not use hashing, control advances to block **722** of FIG. 7B.

If the encryption codec **512** determines that it should use hashing, the encryption codec **512** generates a hash value based on the biophysical signal data collected at block **716**

(block **720**). In the illustrated example, the encryption codec **512** uses the biophysical signal data **112** collected at the wireless-enabled device **102** as a private key to generate a hash of public or shared information (e.g., a value or information that is known to all wireless-enabled devices).

After generating the hash value at block **720** or if the encryption codec **512** determines at block **718** that it should not use hashing, the wireless-enabled device **102** sends a device-request for a wireless connection and the collected biophysical signal data **112** (or a hash value generated at block **720**) to eligible ones of the wireless-enabled devices identified at block **708** (block **722**) (FIG. 7B). In the illustrated example, the wireless-enabled device **102** uses one of the communication interfaces **510** (FIG. 5) to send the device-request and the collected biophysical signal data **112** to the wireless-enabled device **104** via a broadcast channel or any other channel (e.g., an open channel) suitable for sending such a communication. In some examples, the wireless-enabled device **102** is not configured to generate hash values. In such some examples, the operations of blocks **718** and **720** may be omitted, and control advances from block **716** to block **722**.

After a predetermined amount of time has passed, the connection arbiter **504** determines whether it has received a connection acceptance message (block **724**) from, for example, the wireless-enabled device **104**. In the illustrated example, the connection arbiter **504** will receive a connection acceptance message from the wireless-enabled device **104** if the wireless-enabled device **104** has locally collected biophysical signal data **113** and confirmed a sufficient match between the locally collected biophysical signal data **113** and the biophysical signal data **112** received from the wireless-enabled device **102**. An example process that may be implemented by the wireless-enabled device **104** to perform biophysical signal data comparisons is described below in connection with the example flow diagram of FIGS. 8A and 8B. In some instances, a user will be in contact with only two wireless-enabled devices, one of which is the wireless-enabled device **102** that initiates and sends the device-request at block **722**. During such instances, the wireless-enabled device **102** typically will receive a connection acceptance from only one wireless-enabled device (e.g., the wireless-enabled device **104**). However, if the wireless-enabled device **102** receives connection acceptance messages from more than one wireless-enabled device (e.g., the wireless-enabled device **104** and the wireless-enabled headphones **106** of FIG. 1), the wireless-enabled device **102** may present a dialog message (e.g., via the display **610** of FIG. 6) to a user requesting the user to select a device with which to continue the bio-certification process to establish a wireless connection. In this manner, the wireless-enabled device **102** may ignore connection acceptance messages received from non-selected device(s). If the connection arbiter **504** determines that it has not received a connection acceptance message, control advances to block **736**.

If the connection arbiter **504** determines that it has received a connection acceptance message (block **724**), the connection arbiter **504** determines whether user confirmation is required to connect with the wireless-enabled device **104** (block **726**). For example, the connection arbiter **504** can access a listing in the configuration data store **502** (FIG. 5) indicative of devices that require user-confirmation prior to allowing or permitting a wireless connection. If the connection arbiter **504** determines that user confirmation is not required to connect with the wireless-enabled device **104**, control advances to block **732**.

If the connection arbiter **504** determines that user confirmation is required to connect with the wireless-enabled device **104**, the connection arbiter **504** requests a user confirmation (block **728**). In the illustrated example, the connection arbiter **504** causes the wireless-enabled device **102** to present a message (e.g., via the display **610** of FIG. **6**) similar to the GUI message **400** of FIG. **4** to request user confirmation that it is ok to establish a wireless connection (e.g., the wireless connection **114** of FIG. **1**) with the wireless-enabled device **104**.

If at block **730** the connection arbiter **504** receives a user confirmation accepting the establishing of the wireless connection **114**, the connection arbiter **504** allows or permits the establishing of the wireless connection **114** and control advances to block **732**.

At block **732**, the wireless-enabled device **102** establishes the wireless connection **114** with the wireless-enabled device **104** via, for example, one of the communication interfaces **510**.

Returning to block **730**, if the connection arbiter **504** determines that a user did not confirm acceptance to establish the wireless connection **114**, control advances to block **734**, at which the wireless-enabled device **102** sends a connection rejection response to the wireless-enabled device **104** via, for example, one of the communication interfaces **510**. In some examples, when the user does not confirm acceptance to establish the wireless connection **114**, the wireless-enabled device **102** may ignore the connection acceptance message received at block **724** instead of sending the rejection response at block **734**.

At block **736**, the wireless-enabled device **102** informs a user (e.g., the person **100** of FIG. **1**) that no eligible devices with which to establish a wireless connection were found (block **736**).

After informing a user that no eligible devices were found (block **736**), or after sending a connection rejection response (block **734**), or after establishing the wireless connection **114** (block **732**), the example process of FIGS. **7A** and **7B** is ended.

Now turning to FIGS. **8A** and **8B**, the depicted flow diagram is representative of an example process that may be implemented by a wireless-enabled device (e.g., the wireless-enabled device **104** or the wireless-enabled headphones **106** of FIG. **1**) to receive a request from another wireless-enabled device (e.g., the wireless-enabled device **102** of FIG. **1**) to establish a wireless connection (e.g., the wireless connection **114** of FIG. **1**) based on a bio-certification process. Although the example process is described as being performed by the wireless-enabled device **104** as implemented using an apparatus substantially similar or identical to the example apparatus **500** of FIG. **5**, the example process may instead be performed by any other device (e.g., the wireless-enabled device **102** and/or the wireless-enabled headphones **106** of FIG. **1**). In the illustrated example, the example process of FIGS. **8A** and **8B** is performed by the wireless-enabled device **104** in response to receiving a device-request for connection sent by the wireless-enabled device **102** at block **722** of the example process of FIGS. **7A** and **7B**.

Referring to FIG. **8A**, initially, the wireless-enabled device **104** receives a device-request for connection based on bio-certification (block **802**). In the illustrated example, the wireless-enabled device **104** receives the device-request for connection sent by the wireless-enabled device **102** at block **722** of the example process of FIGS. **7A** and **7B**. At

block **802**, the wireless-enabled device **104** also receives the biophysical signal data **112** (or a hash value generated at block **720** of FIG. **7A**).

The wireless-enabled device **104** determines whether it is eligible for establishing a wireless connection (e.g. the wireless connection **114**) with the wireless-enabled device **102** based on bio-certification (block **804**). For example, the wireless-enabled device **104** may use its connection arbiter **504** of FIG. **5** to access a listing in its configuration data store **502** (FIG. **5**) indicative of devices approved for bio-certification. If the wireless-enabled device **104** determines that it is not eligible for establishing a wireless connection with the wireless-enabled device **102** based on bio-certification, control advances to block **838** of FIG. **8B**, where the wireless-enabled device **104** ignores the device-request for connection received at block **802**.

If the connection arbiter **504** determines that the wireless-enabled device **102** is approved for connecting with based on bio-certification (block **804**), the wireless-enabled device **104** monitors for the presence of a biophysical signal **110** (FIG. **1**) (block **806**). For example, the wireless-enabled device **104** may use its biophysical signal data collector **506** to determine whether it can detect a biophysical signal **110**.

If a biophysical signal **110** is not detected (block **808**), the connection arbiter **504** determines whether a timeout has been reached (block **810**). For example, the connection arbiter **504** may start a timeout timer providing sufficient time within which the biophysical signal data collector **506** should detect a biophysical signal **110** before timing out. When the timeout has not expired at block **810**, control returns to the example operations of blocks **806** and **808** to determine whether the biophysical signal data collector **506** has detected a biophysical signal **110**. When the timeout has expired at block **810**, control advances to block **838** of FIG. **8B**.

When the biophysical signal data collector **506** has detected a biophysical signal **110** (block **808**), control advances to block **812**, at which the biophysical signal data collector **506** collects local biophysical signal data (e.g., the locally collected biophysical signal data **113** of FIG. **1**) (block **812**).

The encryption codec **512** (FIG. **5**) determines whether to decode a hash (block **814**). For example, if the encryption codec **512** receives a hash value (e.g., a hash value generated at block **720** of FIG. **7A**) from the device-request for connection received at block **802**, the encryption codec **512** determines at block **814** that it should decode the received hash. Otherwise, if no hash value was received at block **802**, then the encryption codec **512** need not decode a hash.

If the encryption codec **512** does determine at block **814** that it should decode a hash, the encryption codec **512** decodes a hash received at block **802** based on the locally collected biophysical signal data **113** collected at block **812** (block **816**). In the illustrated example, the encryption codec **512** uses the locally collected biophysical signal data **113** collected at the wireless-enabled device **104** as a private key to decode the hash and recover information hashed therein. If the locally collected biophysical signal data **113** corresponds to the same person (e.g., the person **100** of FIG. **1**) that is associated with the biophysical signal data **112** as shown in FIG. **1**, the encryption codec **512** will recover, at block **816**, the public or shared information (e.g., a value or information that is known to all wireless-enabled devices) that the wireless-enabled device **102** hashed at block **720** of FIG. **7A**. If the locally collected biophysical signal data **113** does not correspond to the same person that is associated with the biophysical signal data **112**, then the encryption

codec **512** will recover, at block **816**, information that is different from the public or shared information that the wireless-enabled device **102** hashed at block **720** of FIG. 7A.

After decoding the hash at block **816**, the comparator **508** compares the recovered information with locally stored public or shared information (e.g., a value or information that is known to all wireless-enabled devices) (block **818**).

The connection arbiter **504** determines whether there is a sufficient match (e.g., a match within an acceptable tolerance or threshold based on, for example, a matching score) between the recovered information (i.e., the information recovered at block **816**) and the locally stored public or shared information (block **820**). If a sufficient match is found at block **820**, control advances to block **826** shown in FIG. 8B. If a sufficient match is not found at block **820**, control advances to block **838** of FIG. 8B.

Returning to block **814**, if the encryption codec **512** determines that it should not decode a hash (e.g., a hash was not received at block **802**), control advances from block **814** to block **822**. In some examples, the wireless-enabled device **104** is not configured to monitor for hash values or decode hash values. In such some examples, the operations of blocks **814**, **816**, **818**, and **820** may be omitted, and control advances from block **812** to block **822**.

At block **822**, the wireless-enabled device **104** uses its comparator **508** (FIG. 5) to compare the biophysical signal data **112** received at block **802** with the locally collected biophysical signal data **113** (block **822**).

The connection arbiter **504** determines whether there is a sufficient match between the received biophysical signal data **112** and the locally collected biophysical signal data **113** (block **824**). The connection arbiter **504** may determine whether a sufficient match exists based on a comparison score generated by the comparator **508** and a matching score threshold as described above in connection with FIG. 5. If a sufficient match is not found at block **824**, control advances to block **838** of FIG. 8B.

If a sufficient match is found at block **824** or at block **820**, the wireless-enabled device **104** uses its connection arbiter **504** to determine whether user confirmation is required to connect with the wireless-enabled device **102** (block **826**) (FIG. 8B). For example, the connection arbiter **504** can access a listing in the configuration data store **502** (FIG. 5) of the wireless-enabled device **104** indicative of devices that require user-confirmation prior to allowing a wireless connection. If the connection arbiter **504** determines that user confirmation is not required to connect with the wireless-enabled device **102**, control advances to block **832**.

If the connection arbiter **504** determines that user confirmation is required to connect with the wireless-enabled device **102**, the connection arbiter **504** requests a user confirmation (block **828**). In the illustrated example, the connection arbiter **504** causes the wireless-enabled device **104** to present a message (e.g., via the display **610** of FIG. 6) similar to the GUI message **400** of FIG. 4 to request user confirmation indicating that it is ok to establish a wireless connection (e.g., the wireless connection **114** of FIG. 1) with the wireless-enabled device **102**.

If at block **830** the connection arbiter **504** receives a user confirmation accepting the establishing of the wireless connection **114**, control advances to block **832**. If at block **830** the connection arbiter **504** does not receive a user confirmation accepting the establishing of the wireless connection **114**, control advances to block **838**.

At block **832**, the wireless-enabled device **104** sends a connection acceptance message via one of its communica-

tion interfaces **510** (FIG. 5) to the wireless-enabled device **102**. In the illustrated example, the connection acceptance message sent by the wireless-enabled device **104** is the connection acceptance message received by the wireless-enabled device **102** at block **724** of FIG. 7B.

The connection arbiter **504** of the wireless-enabled device **104** then determines whether it should establish the wireless connection **114** (block **834**). For example, the connection arbiter **504** may establish the wireless connection **114** if it receives an acceptance or negotiation from the wireless-enabled device **102** to successfully establish the wireless connection **114** (e.g., see the operation of block **732** of FIG. 7B at which the wireless-enabled device **102** proceeds to successfully establish the wireless connection **114**). If the connection arbiter **504** determines at block **834** that it should allow or permit the wireless connection **114**, the wireless-enabled device **104** establishes the wireless connection **114** with the wireless-enabled device **102** via, for example, one of the communication interfaces **510** (block **836**).

If at block **834** the wireless-enabled device **104** receives a connection rejection response from the wireless-enabled device **102** (e.g., see block **734** of FIG. 7B) or does not receive any response or further negotiation from the wireless-enabled device **102**, the connection arbiter **504** determines that it should not allow the wireless connection **114** and control advances to block **838**.

At block **838**, the wireless-enabled device **104** ignores the device-request for connection received at block **802** (block **838**). After ignoring the device-request for connection at block **838** or after establishing the wireless connection **114** at block **836**, the example process of FIGS. 8A and 8B ends.

Although certain methods, apparatus, and articles of manufacture have been described herein, the scope of coverage of this patent is not limited thereto. To the contrary, this patent covers all methods, apparatus, and articles of manufacture fairly falling within the scope of the appended claims either literally or under the doctrine of equivalents.

What is claimed is:

1. A method of establishing a connection between wireless-enabled devices, comprising:
 - collecting first biophysical signal data via a first wireless-enabled device;
 - using the first biophysical signal data as a key to decrypt encrypted information received from a second wireless-enabled device to recover first information, wherein the encrypted information is generated using second biophysical signal data; and
 - establishing a wireless connection between the first wireless-enabled device and the second wireless-enabled device based on a comparison of the first information and second information stored in the first wireless-enabled device.
2. The method of claim 1, wherein the second biophysical signal data is collected at the second wireless-enabled device and the encrypted information is generated by the second wireless-enabled device using the second biophysical signal data as a second key.
3. The method of claim 1, wherein the first biophysical signal data is representative of a biophysical signal of a person in contact with the first wireless-enabled device.
4. The method of claim 3, wherein the biophysical signal comprises a heart rate of the person.
5. The method of claim 3, wherein the biophysical signal comprises information that indicates at least one of a heart-beat wavelength, a body temperature, or a blood pressure of the person.

6. The method of claim 1, further comprising, prior to establishing the wireless connection, confirming that the first wireless-enabled device is eligible to establish the wireless connection with the second wireless-enabled device using a biophysical signal process.

7. The method of claim 1, wherein collecting the first biophysical signal data at the first wireless-enabled device is performed in response to receiving a user request to establish the wireless connection based on a biophysical signal process.

8. The method of claim 1, further comprising:
 when the establishing of the wireless connection requires user confirmation, requesting user confirmation to establish the wireless connection; and
 establishing the wireless connection between the first and second wireless-enabled devices upon receipt of user confirmation to permit the establishing of the wireless connection.

9. The method of claim 8, wherein a requirement of the user confirmation to establish the wireless connection is indicated in a configuration data store of the first wireless-enabled device.

10. The method of claim 1, wherein at least one of the first wireless-enabled device or the second wireless-enabled device comprises a car.

11. The method of claim 1, wherein at least one of the first wireless-enabled device or the second wireless-enabled device comprises a watch.

12. The method of claim 1, wherein at least one of the first wireless-enabled device or the second wireless-enabled device comprises an appliance.

13. A device, comprising:
 a memory; and
 at least one hardware processor communicatively coupled with the memory and configured to:
 collect first biophysical signal data via a first wireless-enabled device;
 use the first biophysical signal data as a key to decrypt encrypted information received from a second wireless-enabled device to recover first information, wherein the encrypted information is generated using second biophysical signal data; and
 establish a wireless connection between the first wireless-enabled device and the second wireless-enabled device based on a comparison of the first information and second information stored in the first wireless-enabled device.

14. The device of claim 13, wherein the second biophysical signal data is collected at the second wireless-enabled device and the encrypted information is generated by the second wireless-enabled device using the second biophysical signal data as a second key.

15. The device of claim 13, wherein the first biophysical signal data is representative of a biophysical signal of a person in contact with the first wireless-enabled device.

16. The device of claim 15, wherein the biophysical signal comprises information that indicates at least one of a heart rate, a heartbeat wavelength, a body temperature, or a blood pressure of the person.

17. The device of claim 13, wherein collecting the first biophysical signal data at the first wireless-enabled device is performed in response to receiving a user request to establish the wireless connection based on a biophysical signal process.

18. The device of claim 13, wherein the at least one hardware processor is further configured to:

when the establishing of the wireless connection requires user confirmation, request user confirmation to establish the wireless connection; and
 establish the wireless connection between the first and second wireless-enabled devices upon receipt of user confirmation to permit the establishing of the wireless connection.

19. The device of claim 13, wherein at least one of the first wireless-enabled device or the second wireless-enabled device comprises at least one of a car, a watch, or an appliance.

20. A tangible, non-transitory computer-readable medium containing instructions which, when executed, cause a computing device to perform operations comprising:
 collecting first biophysical signal data via a first wireless-enabled device;
 using the first biophysical signal data as a key to decrypt encrypted information received from a second wireless-enabled device to recover first information, wherein the encrypted information is generated using second biophysical signal data; and
 establishing a wireless connection between the first wireless-enabled device and the second wireless-enabled device based on a comparison of the first information and second information stored in the first wireless-enabled device.

* * * * *

专利名称(译)	连接启用无线的设备的方法和装置		
公开(公告)号	US9510385	公开(公告)日	2016-11-29
申请号	US14/980078	申请日	2015-12-28
[标]申请(专利权)人(译)	捷讯研究有限公司		
申请(专利权)人(译)	黑莓公司		
当前申请(专利权)人(译)	黑莓公司		
[标]发明人	SINGH JASJIT		
发明人	SINGH, JASJIT		
IPC分类号	H04B7/00 H04W76/02 H04L29/06 H04M1/67 H04M1/725 H04W8/00 A61B5/00 H04W12/04 H04W12/06 H04W4/00 H04L9/08 A61B5/024 H04L29/08		
CPC分类号	H04W76/023 A61B5/0022 A61B5/0024 H04L9/0866 H04L63/0428 H04L63/0442 H04L63/0492 H04L63/0861 H04M1/67 H04M1/7253 H04W4/008 H04W8/005 H04W12/04 H04W12/06 A61B5/024 H04L63/101 H04L67/12 H04M2250/12 G16H40/67 H04W4/80 H04W12/003 H04W76/14		
代理机构(译)	FISH & RICHARDSON P.C.		
优先权	13/635326 2015-01-13 US PCT/US2011/025720 2011-02-22 WO		
其他公开文献	US20160135245A1		
外部链接	Espacenet USPTO		

摘要(译)

在启用无线的设备之间建立连接的示例涉及经由第一启用无线的设备采集第一生物物理信号数据，使用第一生物物理信号数据作为密钥来解密从第二启用无线的设备接收的加密信息，以恢复第一信息，以及基于所述第一信息和存储在所述第一启用无线的设备中的第二信息的比较，在所述第一启用无线的设备和所述第二启用无线的设备之间建立无线连接。

