



US 20160128600A1

(19) **United States**(12) **Patent Application Publication**
SU et al.(10) **Pub. No.: US 2016/0128600 A1**(43) **Pub. Date: May 12, 2016**(54) **MEDICAL ELECTRODE AND LIMB CLAMP
FOR AN ECG DEVICE***A61B 5/0402* (2006.01)*A61B 5/0408* (2006.01)(71) Applicant: **KONINKLIJKE PHILIPS N.V.**,
Eindhoven (NL)(52) **U.S. Cl.**CPC *A61B 5/04286* (2013.01); *A61B 5/0408*
(2013.01); *A61B 5/6824* (2013.01); *A61B*
5/6838 (2013.01); *A61B 5/6828* (2013.01);
A61B 5/04026 (2013.01); *A61B 2562/227*
(2013.01); *A61B 2562/222* (2013.01)(72) Inventors: **JIE SU, SHANGYU (CN);**
YUANCHAO ZHU, KUNSHAN (CN)(21) Appl. No.: **14/895,250**(22) PCT Filed: **May 30, 2014**(86) PCT No.: **PCT/IB2014/061829**


§ 371 (c)(1),

(2) Date: **Dec. 2, 2015**(30) **Foreign Application Priority Data**

Jun. 7, 2013 (CN) PCT/CN2013/076906

Publication Classification(51) **Int. Cl.***A61B 5/0428* (2006.01)*A61B 5/00* (2006.01)(57) **ABSTRACT**

The present invention provides a medical electrode comprising a conductive metal base comprising a plate element and a boss formed on the plate element and a conductive support cylinder separate from the conductive metal base. The conductive support cylinder is rotatably mounted to the conductive metal base while remaining in electrical communication with said conductive metal base. The present invention also provides a limb clamp for an ECG device. According to the present invention, it is possible to prevent bending of the cable connecting with the medical electrode, thereby avoiding cable failure.






FIG. 1




FIG. 2




FIG. 3A




FIG. 3B













FIG. 3C










FIG. 7




FIG. 8

MEDICAL ELECTRODE AND LIMB CLAMP FOR AN ECG DEVICE

FIELD OF THE INVENTION

[0001] The invention relates to an improved medical electrode, in particular to a medical electrode and a limb clamp for an ECG (electrocardiogram) device comprising such a medical electrode.

BACKGROUND OF THE INVENTION

[0002] An ECG device is widely used to obtain medical (i.e. biopotential) signals containing information indicative of electrical activity associated with the heart and pulmonary system. The signals obtained are one of the important bases for some disease diagnosis. The ECG device generally comprises a plurality (for example six) of torso electrodes which are applied to a torso portion of a patient and two pairs of limb electrodes which are mounted on a respective limb clamp and applied to the left and right limbs of the patient, respectively. These electrodes connect with an ECG module via the respective cables. In use, cable failure often occurs because of excessive bending cycles caused by various factors such as inappropriate placement of the electrodes, movement of the patient's body and/or their use model. Especially the cables connecting with the limb electrodes are easier subject to cable failure due to their unique use model.

[0003] FIG. 1 shows a conventional limb clamp 1 for an ECG device. The limb clamp 1 generally comprises a first clamp portion 3, a second clamp portion 5, a spring element 7 interconnecting the first clamp portion 3 and the second clamp portion 5, and a medical electrode 9 mounted at the first clamp portion 3. The medical electrode 9 generally comprises a conductive support cylinder 11 that is fixed relative to the first clamp portion 3. When a cable 13 is inserted into and fixed to the support cylinder 11 of the medical electrode 9 that is fixed relative to the first clamp portion 3, the movement of the medical electrode 3 directly results in bending of the respective cable 1, thereby possibly causing cable failure. Further, it is possible for the left and right limb clamps to be applied reversely to the right and left limbs, which causes worse bending of the respective cables as shown in FIG. 1 and thus results in cable failure. Cable failure contributes to wrong or inaccurate signals, which in turn result in wrong or inaccurate diagnosis. Replacing a failed cable not only increases total cost of ownership for the ECG device but also is a waste of time and causes the ECG device to be out of service for a period of time. All in all, this issue has a big impact on the ECG industry all the time.

[0004] Past efforts focused primarily on increasing the durability of the cable itself, for example, thickening the lead wire of the cable, which further increases the cost of the ECG device and makes the patient feel uncomfortable.

[0005] Thus, there is a need to make improvements on the conventional medical electrode.

SUMMARY OF THE INVENTION

[0006] Accordingly, it is desirable to provide a medical electrode which may prevent the cable connecting with the medical electrode from flexing, thereby avoiding cable failure.

[0007] It is also desirable to provide a limb clamp for an ECG device which may prevent the cable connecting with an electrode of the limb clamp from flexing, thereby avoiding cable failure.

[0008] According to one aspect of the present invention, the present invention provides a medical electrode comprising:

[0009] a conductive metal base comprising a plate element and a boss formed on the plate element; and

[0010] a conductive support cylinder separate from the conductive metal base;

[0011] wherein the conductive support cylinder is rotatably mounted to the conductive metal base while remaining in electrical communication with the conductive metal base.

[0012] Preferably, a recess is formed in one of the boss and a lower end of the conductive support cylinder, the other one of the boss and the lower end of the conductive support cylinder being rotatably mounted into the recess.

[0013] Preferably, a recess is formed in the boss and a lower end of the conductive support cylinder is rotatably mounted into the recess.

[0014] Preferably, a conductive bearing is disposed within the recess and the lower end of the conductive support cylinder is mounted into the conductive bearing.

[0015] Preferably, a plurality of conductive and elastic strips extending along the longitudinal axis of the conductive support cylinder and projecting radially outward are disposed on the circumferential surface of the lower end of the conductive support cylinder and the lower end of the conductive support cylinder is inserted snugly into the recess.

[0016] Preferably, the plurality of conductive and elastic strips are distributed evenly on the circumferential surface of the lower end of the conductive support cylinder.

[0017] Preferably, a spherical head is formed at the lower end of the conductive support cylinder, a corresponding spherical recess is formed in the boss, and the spherical head is received snugly in the spherical recess to form the universal joint knuckle.

[0018] Preferably, the conductive metal base comprises a first half portion and a second half portion.

[0019] Preferably, a flange is formed on an outer surface of the conductive support cylinder, a conductive spring is disposed between the flange and the boss, a nut having an inner flange is screwed to the boss to mount the conductive support cylinder to the conductive metal base.

[0020] Preferably, the medical electrode further comprises an electrolyte gel applied to the lower surface of the plate element.

[0021] Preferably, the conductive support cylinder comprises a through hole transverse to its longitudinal axis for receiving a cable.

[0022] Preferably, the conductive support cylinder further comprises a threaded hole formed along its longitudinal axis and communicating with the through hole.

[0023] According to the other aspect of the present invention, the invention provides a limb clamp for an ECG device comprising:

[0024] a first clamp portion;

[0025] a second clamp portion;

[0026] a spring element interconnecting the first clamp portion and the second clamp portion; and

[0027] an above-mentioned medical electrode mounted at the first clamp portion.

[0028] Preferably, an outer thread is formed on the outer surface of the boss, the boss passes through a through hole

formed in the first clamp portion and a nut is screwed onto the outer thread so that the medical electrode is mounted onto the first clamp portion.

[0029] Preferably, the nut for mounting the medical electrode onto the first clamp portion and the nut for mounting the conductive support cylinder to the conductive metal base are the same nut.

[0030] These and other objects, features and characteristics of the present invention, as well as the methods of operation and functions of the related elements of structure and the combination of parts and economies of manufacture, will become more apparent upon consideration of the following description and the appended claims with reference to the accompanying drawings, all of which form a part of this specification, wherein like reference numerals designate corresponding parts in the various figures. It is to be expressly understood, however, that the drawings are for the purpose of illustration and description only and are not intended as a definition of the limits of the invention.

BRIEF DESCRIPTION OF THE DRAWINGS

[0031] FIG. 1 is a perspective view of a conventional limb clamp for the ECG device showing a bend of a cable connecting with an electrode of the limb clamp.

[0032] FIG. 2 is an exploded perspective view of a limb clamp for the ECG device with a medical electrode according to a first embodiment of the present invention.

[0033] FIG. 3A is a top view of the limb clamp of FIG. 2 in an assembled state.

[0034] FIG. 3B is a cross sectional view taken along a line A-A of FIG. 3A.

[0035] FIG. 3C is an enlarged view of an encircled portion A of FIG. 3B.

[0036] FIG. 4A is a cross sectional view similar to FIG. 3B, showing a limb clamp for the ECG device with a medical electrode according to a second embodiment of the present invention.

[0037] FIG. 4B is an enlarged view of an encircled portion A of FIG. 4A.

[0038] FIG. 4C is a perspective view of a support cylinder shown in FIG. 4B.

[0039] FIG. 5A is a cross sectional view similar to FIG. 3B, showing a limb clamp for the ECG device with a medical electrode according to a third embodiment of the present invention.

[0040] FIG. 5B is an enlarged view of an encircled portion A of FIG. 5A.

[0041] FIG. 5C is an exploded perspective view of a medical electrode shown in FIG. 5B.

[0042] FIG. 6A is a cross sectional view similar to FIG. 3B, showing a limb clamp for the ECG device with a medical electrode according to a fourth embodiment of the present invention.

[0043] FIG. 6B is an enlarged view of an encircled portion A of FIG. 6A.

[0044] FIG. 6C is an exploded perspective view of a medical electrode shown in FIG. 6B.

[0045] FIG. 7 is a schematic view showing that the medical electrodes and the limb clamps according to the present invention connect with an ECG module via the respective cables and are applied to the patient to record ECG signals.

[0046] FIG. 8 is a perspective view of a limb clamp for the ECG device according to the present invention showing that there is no bending of the cable connecting with the electrode of the limb clamp.

DETAILED DESCRIPTION OF THE PREFERRED EMBODIMENTS

[0047] The preferred embodiments of the present invention will be described in detail with reference to the drawings.

[0048] FIG. 2 is an exploded perspective view of a limb clamp for the ECG device with a medical electrode according to a first embodiment of the present invention. FIG. 3A is a top view of the limb clamp of FIG. 2 in an assembled state. FIG. 3B is a cross sectional view taken along a line A-A of FIG. 3A. FIG. 3C is an enlarged view of an encircled portion A of FIG. 3B. The limb clamp for the ECG device with a medical electrode according to a first embodiment of the present invention is generally designated by reference numeral 100. As shown in FIGS. 2, 3A, 3B and 3C, the limb clamp 100 for the ECG generally comprises a first clamp portion 101, a second clamp portion 103, a spring element 105 interconnecting the first clamp portion 101 and the second clamp portion 103, and a medical electrode 107 mounted at the first clamp portion 101. The structure and the connection of the first clamp portion 101, the second clamp portion 103 and the spring element 105 are known in the art.

[0049] The medical electrode 107 according to the first embodiment of the present invention generally comprises a conductive metal base 109 and a conductive support cylinder 111. The conductive metal base 109 comprises a plate element 109a and a boss 109b formed on the plate element 109a. In use, the lower surface of the plate element 109a contacts the body of a patient. Of course, an electrolyte gel may be applied to the lower surface of the plate element 109a. Although the boss 109b is shown to be formed integrally with the plate element 109a, the boss 109b may be formed separately from and attached to the plate element 109a in a known way, for example, by means of gluing, welding, or a thread connection. A recess 109c is formed in the boss 109b. Although the conductive support cylinder 111 is shown to be substantially cylindrical in shape, it may be in any suitable shape. The conductive support cylinder 111 may comprise a through hole 111a transverse to its longitudinal axis for receiving a cable. Preferably, the conductive support cylinder 111 further comprises a threaded hole 111b formed along its longitudinal axis and communicating with the through hole 111a. When a cable is inserted into the through hole 111a, a thumb screw 113 may be screwed into the threaded hole 111b to keep the cable in place in a reliable manner. Of course, it is also feasible that the conductive support cylinder 111 does not have the through hole 111a and the threaded hole 111b. In this case, the cable is attached to the conductive support cylinder 111 directly or by means of a sheath.

[0050] A bearing 115 made from a conductive material is disposed within the recess 109c formed in the boss 109b. The lower end of the conductive support cylinder 111 is mounted into the bearing 115 so that the conductive support cylinder 111 may rotate relative to the conductive metal base 109. Although the lower end of the conductive support cylinder 111 is shown to be thinner than the other portion of the conductive support cylinder 111, the lower end of the conductive support cylinder 111 may be as thick as or thicker than the other portion of the conductive support cylinder 111. In the shown embodiment, the bearing 115 is disposed within

the recess **109c** formed in the boss **109b**. It should be understood that the bearing **115** alternatively may be disposed within a recess formed in the lower end of the conductive support cylinder **111**. In this case, the upper end of the boss **109b** is mounted into the bearing **115**. The conductive bearing **115** allows the conductive support cylinder **111** to be rotatable relative to the boss **109b** while keeping the conductive support cylinder **111** in electrical communication with the boss **109b**.

[0051] An outer thread **109d** is formed on an outer surface of the boss **109b**. The boss **109b** may pass through a through hole **101a** formed in the first clamp portion **101** and then a nut **117** may be screwed onto the outer thread **109d** of the boss **109b** so that the medical electrode **107** is mounted onto the first clamp portion **101**.

[0052] FIGS. 4A-4C illustrates a limb clamp for the ECG device with a medical electrode according to a second embodiment of the present invention. FIG. 4A is a cross sectional view similar to FIG. 3B. FIG. 4B is an enlarged view of an encircled portion A of FIG. 4A. FIG. 4C is a perspective view of a support cylinder shown in FIG. 4B. The limb clamp for the ECG device with a medical electrode according to a second embodiment of the present invention is generally designated by reference numeral **200**. Parts of the limb clamp for the ECG device with the medical electrode according to the second embodiment corresponding to parts of the limb clamp for the ECG device with the medical electrode according to the first embodiment are indicated by the same reference numerals, plus “**100**”. The description for the same parts is omitted for simplicity.

[0053] The limb clamp **200** for the ECG device with a medical electrode according to the second embodiment is substantially similar to the limb clamp **100** for the ECG device with the medical electrode according to the first embodiment, but does not include the bearing **115**. In this embodiment, a plurality of conductive and elastic strips **211c** extending along the longitudinal axis of the conductive support cylinder **211** and projecting radially outward are disposed on the circumferential surface of the lower end of the conductive support cylinder **211**. The lower end of the conductive support cylinder **211** is inserted snugly into the recess **209c** formed in the boss **209b**. The elasticity of the elastic strips **211c** allows the conductive support cylinder **211** to be rotatable relative to the boss **209b**, while keeping the conductive support cylinder **211** in electrical communication with the boss **209b**. Preferably, the plurality of conductive and elastic strips **211c** is distributed evenly on the circumferential surface of the lower end of the conductive support cylinder **211**. Further, the plurality of conductive and elastic strips **211c** may be formed integrally with or separately from the conductive support cylinder **211**. For example, a sleeve comprising the plurality of conductive and elastic strips **211c** may be attached to the lower end of the conductive support cylinder **211**.

[0054] FIGS. 5A-5C illustrate a limb clamp for the ECG device with a medical electrode according to a third embodiment of the present invention. FIG. 5A is a cross sectional view similar to FIG. 3B. FIG. 5B is an enlarged view of an encircled portion A of FIG. 5A. FIG. 5C is an exploded perspective view of a medical electrode shown in FIG. 5B. The limb clamp for the ECG device with a medical electrode according to a third embodiment of the present invention is generally designated by reference numeral **300**. Parts of the limb clamp for the ECG device with the medical electrode

according to the third embodiment corresponding to parts of the limb clamp for the ECG device with the medical electrode according to the first embodiment are indicated by the same reference numerals, plus “**200**”. The description for the same parts is omitted for simplicity.

[0055] The limb clamp **300** for the ECG device with a medical electrode according to the third embodiment is substantially similar to the limb clamp **100** for the ECG device with the medical electrode according to the first embodiment, but does not include the bearing **115**. In this embodiment, a universal joint knuckle is formed between the lower end of the conductive support cylinder **311** and the boss **309b**. Specifically, a spherical head **311c** is formed at the lower end of the conductive support cylinder **311** and a corresponding spherical recess **309c** is formed in the boss **309b**. The spherical head **311c** is received snugly in the spherical recess **309c** to form the universal joint knuckle. The universal joint knuckle allows the conductive support cylinder **311** to be rotatable relative to the boss **309b**, while keeping the conductive support cylinder **311** in electrical communication with the boss **309b**. To allow easy assembly of the medical electrode **307**, the conductive metal base **309** may comprise a first half portion **309d** and a second half portion **309e**.

[0056] FIGS. 6A-6C illustrate a limb clamp for the ECG device with a medical electrode according to a fourth embodiment of the present invention. FIG. 6A is a cross sectional view similar to FIG. 3B. FIG. 6B is an enlarged view of an encircled portion A of FIG. 6A. FIG. 6C is an exploded perspective view of a medical electrode shown in FIG. 6B. The limb clamp for the ECG device with a medical electrode according to a fourth embodiment of the present invention is generally designated by reference numeral **400**. Parts of the limb clamp for the ECG device with the medical electrode according to the fourth embodiment corresponding to parts of the limb clamp for the ECG device with the medical electrode according to the first embodiment are indicated by the same reference numerals, plus “**300**”. The description for the same parts is omitted for simplicity.

[0057] The limb clamp **400** for the ECG device with a medical electrode according to the fourth embodiment is substantially similar to the limb clamp **100** for the ECG device with the medical electrode according to the first embodiment, but does not include the bearing **115**. In this embodiment, a flange **411c** is formed on the outer surface of the conductive support cylinder **411**. When the lower end of the conductive support cylinder **411** is inserted loosely into the recess **409c** formed in the boss **409b**, a conductive spring **419** is disposed between the flange **411c** and the boss **409b**. Further, the nut **417** having an inner flange **417a** may be used to mount the conductive support cylinder **411** to the conductive metal base **409** and fix the metal electrode **407** to the first clamp portion **401**. The conductive spring **419** allows the conductive support cylinder **411** to be rotatable relative to the boss **409b**, while keeping the conductive support cylinder **411** in electrical communication with the boss **409b**.

[0058] FIG. 7 is a schematic view showing that the medical electrodes **107** and the limb clamps **100** according to the present invention connect with an ECG module **121** via the respective cables **123** and are applied to the patient to record ECG signals. The other pair of limb clamps **100** are not shown for simplicity. When the medical electrodes according to the present invention are applied to the patient's torso as torso electrodes, they are attached to the patient's torso by an adhesive plaster or a suction cup. The ECG module **121** connects

with a computer **125** to show and analyze the recorded ECG signals. FIG. **8** is a perspective view of a limb clamp for the ECG device according to the present invention showing no bending of the cable connecting with the electrode of the limb clamp. A cable post **127** connecting with the cable **123** is inserted into the through hole **111a** of the conductive support cylinder **111** of the medical electrode **107**. Because the conductive support cylinder **111** of the medical electrode **107** may rotate relative to the conductive metal base **109** of the medical electrode **107**, the cable **123** also rotates with the conductive support cylinder **111** as shown by a double-arrow line. Thus, no bending of the cable **123** connecting with the medical electrode **107** occurs irrespective of how the medical electrodes and the limb clamps move, thereby avoiding any cable failure.

[0059] In FIGS. **7** and **8**, as an example, the medical electrodes and the limb clamps are the medical electrodes **107** and the limb clamps **100** according to the first embodiment of the present invention. Obviously, the medical electrodes and the limb clamps may be the medical electrodes and the limb clamps according to any one of the other embodiments of the present invention.

[0060] While the medical electrode according to the present invention is explained as a part of the ECG device in the embodiments, it should be understood that the medical electrode may be used with other medical instruments and may comprise additional components for other functions. Although the invention has been described in detail for the purpose of illustration based on what are currently considered to be the most practical and preferred embodiments, it is to be understood that such detail is solely for that purpose and that the invention is not limited to the disclosed embodiments, but on the contrary, is intended to cover modifications and equivalent arrangements that are within the spirit and scope of the appended claims.

1. A medical electrode comprising:

a conductive metal base comprising a plate element and a boss formed on the plate element; and
a conductive support cylinder separate from the conductive metal base;

wherein the conductive support cylinder mounted to the conductive metal base and is rotatable relative to the conductive metal base while remaining in electrical communication with the conductive metal base.

2. The medical electrode according to claim 1, wherein a recess is formed in one of the boss and a lower end of the conductive support cylinder, the other one of the boss and the lower end of the conductive support cylinder being mounted into the recess and rotatable relative to the recess.

3. The medical electrode according to claim 1, wherein a recess is formed in the boss and a lower end of the conductive support cylinder is mounted into the recess and is rotatable relative to the recess.

4. The medical electrode according to claim 3, wherein a conductive bearing is disposed within the recess and the lower end of the conductive support cylinder is mounted into the conductive bearing.

5. The medical electrode according to claim 3, wherein a plurality of conductive and elastic strips extending along the longitudinal axis of the conductive support cylinder and projecting radially outward are disposed on the circumferential surface of the lower end of the conductive support cylinder and the lower end of the conductive support cylinder is inserted snugly into the recess.

6. The medical electrode according to claim 5, wherein the plurality of conductive and elastic strips are evenly distributed on the circumferential surface of the lower end of the conductive support cylinder.

7. The medical electrode according to claim 3, wherein a spherical head is formed at the lower end of the conductive support cylinder, a corresponding spherical recess is formed in the boss, and the spherical head is received snugly in the spherical recess to form the universal joint knuckle.

8. The medical electrode according to claim 7, wherein the conductive metal base comprises a first half portion and a second half portion.

9. The medical electrode according to claim 3, wherein a flange is formed on an outer surface of the conductive support cylinder, a conductive spring is disposed between the flange and the boss, a nut having an inner flange is screwed to the boss to mount the conductive support cylinder to the conductive metal base.

10. The medical electrode according to claim 1, further comprising an electrolyte gel applied to the lower surface of the plate element.

11. The medical electrode according to claim 1, wherein the conductive support cylinder comprises a through hole transverse to its longitudinal axis for receiving a cable.

12. The medical electrode according to claim 11, wherein the conductive support cylinder further comprises a threaded hole formed along its longitudinal axis and communicating with the through hole.

13. A limb clamp for an ECG device comprising:

a first clamp portion;

a second clamp portion;

a spring element connecting the first clamp portion and the second clamp portion; and

a medical electrode according to claim 1 mounted at the first clamp portion.

14. The limb clamp for an ECG device according to claim 13, wherein an outer thread is formed on the outer surface of the boss, the boss passes through a through hole formed in the first clamp portion and a nut is screwed onto the outer thread so that the medical electrode is mounted onto the first clamp portion.

15. The limb clamp for an ECG device according to claim 14, wherein the nut for mounting the medical electrode onto the first clamp portion and the nut for mounting the conductive support cylinder to the conductive metal base are the same nut when the medical electrode is a medical electrode.

* * * * *

专利名称(译)	用于ECG设备的医用电极和肢体夹		
公开(公告)号	US20160128600A1	公开(公告)日	2016-05-12
申请号	US14/895250	申请日	2014-05-30
[标]申请(专利权)人(译)	皇家飞利浦电子股份有限公司		
申请(专利权)人(译)	皇家飞利浦N.V.		
当前申请(专利权)人(译)	皇家飞利浦N.V.		
[标]发明人	SU JIE ZHU YUANCHAO		
发明人	SU, JIE ZHU, YUANCHAO		
IPC分类号	A61B5/0428 A61B5/00 A61B5/0402 A61B5/0408		
CPC分类号	A61B5/04286 A61B5/0408 A61B5/6824 A61B2562/222 A61B5/6828 A61B5/04026 A61B2562/227 A61B5/6838 A61B5/0424 A61N1/0452 A61N1/0456 A61N1/0472 A61N1/048 H01R4/48 H01R4/56 H01R2201/12 A61B5/0416		
优先权	PCT/CN2013/076906 2013-06-07 WO		
其他公开文献	US10182731		
外部链接	Espacenet USPTO		

摘要(译)

本发明提供一种医疗电极，其包括导电金属基底，该导电金属基底包括板元件和形成在该板元件上的凸台以及与导电金属基底分离的导电支撑圆筒。导电支撑圆筒可旋转地安装到导电金属基底，同时保持与所述导电金属基底电连通。本发明还提供了一种用于ECG装置的肢体夹具。根据本发明，可以防止与医用电极连接的电缆的弯曲，从而避免电缆故障。

