



US009192312B2

(12) **United States Patent**  
**Al-Ali**

(10) **Patent No.:** **US 9,192,312 B2**  
(45) **Date of Patent:** **\*Nov. 24, 2015**

(54) **PATIENT MONITOR FOR DETERMINING MICROCIRCULATION STATE**

(71) Applicant: **MASIMO CORPORATION**, Irvine, CA (US)

(72) Inventor: **Ammar Al-Ali**, San Juan Capistrano, CA (US)

(73) Assignee: **MASIMO CORPORATION**, Irvine, CA (US)

(\*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 0 days.

This patent is subject to a terminal disclaimer.

(21) Appl. No.: **14/160,316**

(22) Filed: **Jan. 21, 2014**

(65) **Prior Publication Data**

US 2014/0194711 A1 Jul. 10, 2014

**Related U.S. Application Data**

(63) Continuation of application No. 13/101,093, filed on May 4, 2011, now Pat. No. 8,666,468.

(60) Provisional application No. 61/332,155, filed on May 6, 2010.

(51) **Int. Cl.**

**A61B 5/1455** (2006.01)

**A61B 5/026** (2006.01)

**A61B 5/024** (2006.01)

**A61B 5/00** (2006.01)

(52) **U.S. Cl.**

CPC ..... **A61B 5/0261** (2013.01); **A61B 5/02427** (2013.01); **A61B 5/14551** (2013.01); **A61B 5/14552** (2013.01); **A61B 5/7282** (2013.01); **A61B 5/746** (2013.01)

(58) **Field of Classification Search**

CPC ..... **A61B 5/1455**  
See application file for complete search history.

(56) **References Cited**

**U.S. PATENT DOCUMENTS**

3,980,075 A	9/1976	Heule
4,960,128 A	10/1990	Gordon et al.
4,964,408 A	10/1990	Hink et al.
5,041,187 A	8/1991	Hink et al.
5,069,213 A	12/1991	Polczynski
5,163,438 A	11/1992	Gordon et al.
5,319,355 A	6/1994	Russek
5,337,744 A	8/1994	Branigan
5,341,805 A	8/1994	Stavridi et al.
D353,195 S	12/1994	Savage et al.
D353,196 S	12/1994	Savage et al.
5,377,676 A	1/1995	Vari et al.

(Continued)

*Primary Examiner* — Eric Winakur


*Assistant Examiner* — Marjan Fardanesh

(74) *Attorney, Agent, or Firm* — Knobbe, Martens, Olson & Bear LLP

(57) **ABSTRACT**

As placement of a physiological monitoring sensor is typically at a sensor site located at an extremity of the body, the state of microcirculation, such as whether vessels are blocked or open, can have a significant effect on the readings at the sensor site. It is therefore desirable to provide a patient monitor and/or physiological monitoring sensor capable of distinguishing the microcirculation state of blood vessels. In some embodiments, the patient monitor and/or sensor provide a warning and/or compensates a measurement based on the microcirculation state. In some embodiments, a microcirculation determination process implementable by the patient monitor and/or sensor is used to determine the state of microcirculation of the patient.

**21 Claims, 7 Drawing Sheets**



(56)

## References Cited

## U.S. PATENT DOCUMENTS

D359,546	S	6/1995	Savage et al.	6,334,065	B1	12/2001	Al-Ali et al.
5,431,170	A	7/1995	Mathews	6,343,224	B1	1/2002	Parker
D361,840	S	8/1995	Savage et al.	6,349,228	B1	2/2002	Kiani et al.
D362,063	S	9/1995	Savage et al.	6,360,114	B1	3/2002	Diab et al.
5,452,717	A	9/1995	Branigan et al.	6,368,283	B1	4/2002	Xu et al.
D363,120	S	10/1995	Savage et al.	6,371,921	B1	4/2002	Caro et al.
5,456,252	A	10/1995	Vari et al.	6,377,829	B1	4/2002	Al-Ali
5,479,934	A	1/1996	Imran	6,388,240	B2	5/2002	Schulz et al.
5,482,036	A	1/1996	Diab et al.	6,397,091	B2	5/2002	Diab et al.
5,490,505	A	2/1996	Diab et al.	6,430,437	B1	8/2002	Marro
5,494,043	A	2/1996	O'Sullivan et al.	6,430,525	B1	8/2002	Weber et al.
5,533,511	A	7/1996	Kaspari et al.	6,463,311	B1	10/2002	Diab
5,534,851	A	7/1996	Russek	6,470,199	B1	10/2002	Kopotic et al.
5,561,275	A	10/1996	Savage et al.	6,501,975	B2	12/2002	Diab et al.
5,562,002	A	10/1996	Lalin	6,505,059	B1	1/2003	Kollias et al.
5,590,649	A	1/1997	Caro et al.	6,515,273	B2	2/2003	Al-Ali
5,602,924	A	2/1997	Durand et al.	6,519,487	B1	2/2003	Parker
5,632,272	A	5/1997	Diab et al.	6,525,386	B1	2/2003	Mills et al.
5,638,816	A	6/1997	Kiani-Azarbayjany et al.	6,526,300	B1	2/2003	Kiani et al.
5,638,818	A	6/1997	Diab et al.	6,541,756	B2	4/2003	Schulz et al.
5,645,440	A	7/1997	Tobler et al.	6,542,764	B1	4/2003	Al-Ali et al.
5,685,299	A	11/1997	Diab et al.	6,580,086	B1	6/2003	Schulz et al.
D393,830	S	4/1998	Tobler et al.	6,584,336	B1	6/2003	Ali et al.
5,743,262	A	4/1998	Lepper, Jr. et al.	6,595,316	B2	7/2003	Cybulski et al.
5,758,644	A	6/1998	Diab et al.	6,597,932	B2	7/2003	Tian et al.
5,760,910	A	6/1998	Lepper, Jr. et al.	6,597,933	B2	7/2003	Kiani et al.
5,769,785	A	6/1998	Diab et al.	6,606,511	B1	8/2003	Ali et al.
5,782,757	A	7/1998	Diab et al.	6,632,181	B2	10/2003	Flaherty et al.
5,785,659	A	7/1998	Caro et al.	6,639,668	B1	10/2003	Trepagnier
5,791,347	A	8/1998	Flaherty et al.	6,640,116	B2	10/2003	Diab
5,810,734	A	9/1998	Caro et al.	6,643,530	B2	11/2003	Diab et al.
5,823,950	A	10/1998	Diab et al.	6,650,917	B2	11/2003	Diab et al.
5,830,131	A	11/1998	Caro et al.	6,654,624	B2	11/2003	Diab et al.
5,833,618	A	11/1998	Caro et al.	6,658,276	B2	12/2003	Kianl et al.
5,860,919	A	1/1999	Kiani-Azarbayjany et al.	6,661,161	B1	12/2003	Lanzo et al.
5,890,929	A	4/1999	Mills et al.	6,671,531	B2	12/2003	Al-Ali et al.
5,904,654	A	5/1999	Wohltmann et al.	6,678,543	B2	1/2004	Diab et al.
5,919,134	A	7/1999	Diab	6,684,090	B2	1/2004	Ali et al.
5,934,925	A	8/1999	Tobler et al.	6,684,091	B2	1/2004	Parker
5,940,182	A	8/1999	Lepper, Jr. et al.	6,697,656	B1	2/2004	Al-Ali
5,995,855	A	11/1999	Kiani et al.	6,697,657	B1	2/2004	Shehada et al.
5,997,343	A	12/1999	Mills et al.	6,697,658	B2	2/2004	Al-Ali
6,002,952	A	12/1999	Diab et al.	RE38,476	E	3/2004	Diab et al.
6,011,986	A	1/2000	Diab et al.	6,699,194	B1	3/2004	Diab et al.
6,027,452	A	2/2000	Flaherty et al.	6,714,804	B2	3/2004	Al-Ali et al.
6,036,642	A	3/2000	Diab et al.	RE38,492	E	4/2004	Diab et al.
6,045,509	A	4/2000	Caro et al.	6,721,582	B2	4/2004	Trepagnier et al.
6,067,462	A	5/2000	Diab et al.	6,721,585	B1	4/2004	Parker
6,081,735	A	6/2000	Diab et al.	6,725,075	B2	4/2004	Al-Ali
6,088,607	A	7/2000	Diab et al.	6,728,560	B2	4/2004	Kollias et al.
6,110,522	A	8/2000	Lepper, Jr. et al.	6,735,459	B2	5/2004	Parker
6,124,597	A	9/2000	Shehada	6,745,060	B2	6/2004	Diab et al.
6,128,521	A	10/2000	Marro et al.	6,760,607	B2	7/2004	Al-Ali
6,129,675	A	10/2000	Jay	6,770,028	B1	8/2004	Ali et al.
6,144,868	A	11/2000	Parker	6,771,994	B2	8/2004	Kiani et al.
6,151,516	A	11/2000	Kiani-Azarbayjany et al.	6,792,300	B1	9/2004	Diab et al.
6,152,754	A	11/2000	Gerhardt et al.	6,813,511	B2	11/2004	Diab et al.
6,157,850	A	12/2000	Diab et al.	6,816,741	B2	11/2004	Diab
6,165,005	A	12/2000	Mills et al.	6,822,564	B2	11/2004	Al-Ali
6,184,521	B1	2/2001	Coffin, IV et al.	6,826,419	B2	11/2004	Diab et al.
6,206,830	B1	3/2001	Diab et al.	6,830,711	B2	12/2004	Mills et al.
6,229,856	B1	5/2001	Diab et al.	6,850,787	B2	2/2005	Weber et al.
6,232,609	B1	5/2001	Snyder et al.	6,850,788	B2	2/2005	Al-Ali
6,236,872	B1	5/2001	Diab et al.	6,852,083	B2	2/2005	Caro et al.
6,241,683	B1	6/2001	Macklem et al.	6,861,639	B2	3/2005	Al-Ali
6,253,097	B1	6/2001	Aronow et al.	6,898,452	B2	5/2005	Al-Ali et al.
6,256,523	B1	7/2001	Diab et al.	6,920,345	B2	7/2005	Al-Ali et al.
6,263,222	B1	7/2001	Diab et al.	6,931,268	B1	8/2005	Kiani-Azarbayjany et al.
6,278,522	B1	8/2001	Lepper, Jr. et al.	6,934,570	B2	8/2005	Kiani et al.
6,280,213	B1	8/2001	Tobler et al.	6,939,305	B2	9/2005	Flaherty et al.
6,285,896	B1	9/2001	Tobler et al.	6,943,348	B1	9/2005	Coffin IV
6,301,493	B1	10/2001	Marro et al.	6,950,687	B2	9/2005	Al-Ali
6,317,627	B1	11/2001	Ennen et al.	6,961,598	B2	11/2005	Diab
6,321,100	B1	11/2001	Parker	6,970,792	B1	11/2005	Diab
6,325,761	B1	12/2001	Jay	6,979,812	B2	12/2005	Al-Ali
				6,985,764	B2	1/2006	Mason et al.
				6,993,371	B2	1/2006	Kiani et al.
				6,996,427	B2	2/2006	Ali et al.
				6,999,904	B2	2/2006	Weber et al.

(56)

## References Cited

## U.S. PATENT DOCUMENTS

7,003,338	B2	2/2006	Weber et al.	7,530,942	B1	5/2009	Diab
7,003,339	B2	2/2006	Diab et al.	7,530,949	B2	5/2009	Al Ali et al.
7,015,451	B2	3/2006	Dalke et al.	7,530,955	B2	5/2009	Diab et al.
7,024,233	B2	4/2006	Ali et al.	7,563,110	B2	7/2009	Al-Ali et al.
7,027,849	B2	4/2006	Al-Ali	7,596,398	B2	9/2009	Al-Ali et al.
7,030,749	B2	4/2006	Al-Ali	7,618,375	B2	11/2009	Flaherty
7,039,449	B2	5/2006	Al-Ali	D606,659	S	12/2009	Kiani et al.
7,041,060	B2	5/2006	Flaherty et al.	7,647,083	B2	1/2010	Al-Ali et al.
7,044,918	B2	5/2006	Diab	D609,193	S	2/2010	Al-Ali et al.
7,067,893	B2	6/2006	Mills et al.	D614,305	S	4/2010	Al-Ali et al.
7,096,052	B2	8/2006	Mason et al.	RE41,317	E	5/2010	Parker
7,096,054	B2	8/2006	Abdul-Hafiz et al.	7,729,733	B2	6/2010	Al-Ali et al.
7,132,641	B2	11/2006	Schulz et al.	7,734,320	B2	6/2010	Al-Ali
7,142,901	B2	11/2006	Kiani et al.	7,761,127	B2	7/2010	Al-Ali et al.
7,149,561	B2	12/2006	Diab	7,761,128	B2	7/2010	Al-Ali et al.
7,186,966	B2	3/2007	Al-Ali	7,764,982	B2	7/2010	Dalke et al.
7,190,261	B2	3/2007	Al-Ali	D621,516	S	8/2010	Kiani et al.
7,215,984	B2	5/2007	Diab	7,791,155	B2	9/2010	Diab
7,215,986	B2	5/2007	Diab	7,801,581	B2	9/2010	Diab
7,221,971	B2	5/2007	Diab	7,822,452	B2	10/2010	Schurman et al.
7,225,006	B2	5/2007	Al-Ali et al.	RE41,912	E	11/2010	Parker
7,225,007	B2	5/2007	Al-Ali	7,844,313	B2	11/2010	Kiani et al.
RE39,672	E	6/2007	Shehada et al.	7,844,314	B2	11/2010	Al-Ali
7,239,905	B2	7/2007	Kiani-Azarbayjany et al.	7,844,315	B2	11/2010	Al-Ali
7,245,953	B1	7/2007	Parker	7,865,222	B2	1/2011	Weber et al.
7,254,429	B2	8/2007	Schurman et al.	7,873,497	B2	1/2011	Weber et al.
7,254,431	B2	8/2007	Al-Ali	7,880,606	B2	2/2011	Al-Ali
7,254,433	B2	8/2007	Diab et al.	7,880,626	B2	2/2011	Al-Ali et al.
7,254,434	B2	8/2007	Schulz et al.	7,891,355	B2	2/2011	Al-Ali et al.
7,272,425	B2	9/2007	Al-Ali	7,894,868	B2	2/2011	Al-Ali et al.
7,274,955	B2	9/2007	Kiani et al.	7,899,507	B2	3/2011	Al-Ali et al.
D554,263	S	10/2007	Al-Ali	7,899,518	B2	3/2011	Trepagnier et al.
7,280,858	B2	10/2007	Al-Ali et al.	7,904,132	B2	3/2011	Weber et al.
7,289,835	B2	10/2007	Mansfield et al.	7,909,772	B2	3/2011	Popov et al.
7,292,883	B2	11/2007	De Felice et al.	7,910,875	B2	3/2011	Al-Ali
7,295,866	B2	11/2007	Al-Ali	7,919,713	B2	4/2011	Al-Ali et al.
7,328,053	B1	2/2008	Diab et al.	7,937,128	B2	5/2011	Al-Ali
7,332,784	B2	2/2008	Mills et al.	7,937,129	B2	5/2011	Mason et al.
7,338,447	B2	3/2008	Phillips	7,937,130	B2	5/2011	Diab et al.
7,340,287	B2	3/2008	Mason et al.	7,941,199	B2	5/2011	Kiani
7,341,559	B2	3/2008	Schulz et al.	7,951,086	B2	5/2011	Flaherty et al.
7,341,562	B2	3/2008	Pless et al.	7,957,780	B2	6/2011	Lamego et al.
7,343,186	B2	3/2008	Lamego et al.	7,962,188	B2	6/2011	Kiani et al.
D566,282	S	4/2008	Al-Ali et al.	7,962,190	B1	6/2011	Diab et al.
7,355,512	B1	4/2008	Al-Ali	7,976,472	B2	7/2011	Kiani
7,356,365	B2	4/2008	Schurman	7,988,637	B2	8/2011	Diab
7,371,981	B2	5/2008	Abdul-Hafiz	7,990,382	B2	8/2011	Kiani
7,373,193	B2	5/2008	Al-Ali et al.	7,991,446	B2	8/2011	Al-Ali et al.
7,373,194	B2	5/2008	Weber et al.	8,000,761	B2	8/2011	Al-Ali
7,376,453	B1	5/2008	Diab et al.	8,008,088	B2	8/2011	Bellott et al.
7,377,794	B2	5/2008	Al Ali et al.	RE42,753	E	9/2011	Kiani-Azarbayjany et al.
7,377,899	B2	5/2008	Weber et al.	8,019,400	B2	9/2011	Diab et al.
7,383,070	B2	6/2008	Diab et al.	8,028,701	B2	10/2011	Al-Ali et al.
7,415,297	B2	8/2008	Al-Ali et al.	8,029,765	B2	10/2011	Bellott et al.
7,428,432	B2	9/2008	Ali et al.	8,036,728	B2	10/2011	Diab et al.
7,438,683	B2	10/2008	Al-Ali et al.	8,046,040	B2	10/2011	Ali et al.
7,440,787	B2	10/2008	Diab	8,046,041	B2	10/2011	Diab et al.
7,454,240	B2	11/2008	Diab et al.	8,046,042	B2	10/2011	Diab et al.
7,467,002	B2	12/2008	Weber et al.	8,048,040	B2	11/2011	Kiani
7,469,157	B2	12/2008	Diab et al.	8,050,728	B2	11/2011	Al-Ali et al.
7,471,969	B2	12/2008	Diab et al.	RE43,169	E	2/2012	Parker
7,471,971	B2	12/2008	Diab et al.	8,118,620	B2	2/2012	Al-Ali et al.
7,483,729	B2	1/2009	Al-Ali et al.	8,126,528	B2	2/2012	Diab et al.
7,483,730	B2	1/2009	Diab et al.	8,128,572	B2	3/2012	Diab et al.
7,489,958	B2	2/2009	Diab et al.	8,130,105	B2	3/2012	Al-Ali et al.
7,496,391	B2	2/2009	Diab et al.	8,145,287	B2	3/2012	Diab et al.
7,496,393	B2	2/2009	Diab et al.	8,150,487	B2	4/2012	Diab et al.
D587,657	S	3/2009	Al-Ali et al.	8,175,672	B2	5/2012	Parker
7,499,741	B2	3/2009	Diab et al.	8,180,420	B2	5/2012	Diab et al.
7,499,835	B2	3/2009	Weber et al.	8,182,443	B1	5/2012	Kiani
7,500,950	B2	3/2009	Al-Ali et al.	8,185,180	B2	5/2012	Diab et al.
7,509,154	B2	3/2009	Diab et al.	8,190,223	B2	5/2012	Al-Ali et al.
7,509,494	B2	3/2009	Al-Ali	8,190,227	B2	5/2012	Diab et al.
7,510,849	B2	3/2009	Schurman et al.	8,203,438	B2	6/2012	Kiani et al.
7,526,328	B2	4/2009	Diab et al.	8,203,704	B2	6/2012	Merritt et al.
				8,224,411	B2	7/2012	Al-Ali et al.
				8,228,181	B2	7/2012	Al-Ali
				8,229,533	B2	7/2012	Diab et al.
				8,233,955	B2	7/2012	Al-Ali et al.

(56)

References Cited

U.S. PATENT DOCUMENTS

8,244,325 B2	8/2012	Al-Ali et al.	8,473,020 B2	6/2013	Kiani et al.
8,255,026 B1	8/2012	Al-Ali	8,483,787 B2	7/2013	Al-Ali et al.
8,255,027 B2	8/2012	Al-Ali et al.	8,489,364 B2	7/2013	Weber et al.
8,255,028 B2	8/2012	Al-Ali et al.	8,498,684 B2	7/2013	Weber et al.
8,260,577 B2	9/2012	Weber et al.	8,509,867 B2	8/2013	Workman et al.
8,265,723 B1	9/2012	McHale et al.	8,515,509 B2	8/2013	Bruinsma et al.
8,274,360 B2	9/2012	Sampath et al.	8,523,781 B2	9/2013	Al-Ali
8,301,217 B2	10/2012	Al-Ali et al.	8,529,301 B2	9/2013	Al-Ali et al.
8,310,336 B2	11/2012	Muhsin et al.	8,532,727 B2	9/2013	Ali et al.
8,315,683 B2	11/2012	Al-Ali et al.	8,532,728 B2	9/2013	Diab et al.
RE43,860 E	12/2012	Parker	D692,145 S	10/2013	Al-Ali et al.
8,337,403 B2	12/2012	Al-Ali et al.	8,547,209 B2	10/2013	Kiani et al.
8,346,330 B2	1/2013	Lamego	8,548,548 B2	10/2013	Al-Ali
8,353,842 B2	1/2013	Al-Ali et al.	8,548,550 B2	10/2013	Al-Ali et al.
8,355,766 B2	1/2013	MacNeish, III et al.	8,560,032 B2	10/2013	Al-Ali et al.
8,359,080 B2	1/2013	Diab et al.	8,560,034 B1	10/2013	Diab et al.
8,364,223 B2	1/2013	Al-Ali et al.	8,570,167 B2	10/2013	Al-Ali
8,364,226 B2	1/2013	Diab et al.	8,570,503 B2	10/2013	Vo et al.
8,374,665 B2	2/2013	Lamego	8,571,618 B1	10/2013	Lamego et al.
8,385,995 B2	2/2013	Al-ali et al.	8,571,619 B2	10/2013	Al-Ali et al.
8,385,996 B2	2/2013	Smith et al.	8,577,431 B2	11/2013	Lamego et al.
8,388,353 B2	3/2013	Kiani et al.	8,584,345 B2	11/2013	Al-Ali et al.
8,399,822 B2	3/2013	Al-Ali	8,588,880 B2	11/2013	Abdul-Hafiz et al.
8,401,602 B2	3/2013	Kiani	8,600,467 B2	12/2013	Al-Ali et al.
8,405,608 B2	3/2013	Al-Ali et al.	8,606,342 B2	12/2013	Diab
8,414,499 B2	4/2013	Al-Ali et al.	8,626,255 B2	1/2014	Al-Ali et al.
8,418,524 B2	4/2013	Al-Ali	8,630,691 B2	1/2014	Lamego et al.
8,423,106 B2	4/2013	Lamego et al.	8,634,889 B2	1/2014	Al-Ali et al.
8,428,967 B2	4/2013	Olsen et al.	8,641,631 B2	2/2014	Sierra et al.
8,430,817 B1	4/2013	Al-Ali et al.	8,652,060 B2	2/2014	Al-Ali
8,437,825 B2	5/2013	Dalvi et al.	8,663,107 B2	3/2014	Kiani
8,455,290 B2	6/2013	Siskavich	8,666,468 B1	3/2014	Al-Ali
8,457,703 B2	6/2013	Al-Ali	8,667,967 B2	3/2014	Al-Ali et al.
8,457,707 B2	6/2013	Kiani	8,670,811 B2	3/2014	O'Reilly
8,463,349 B2	6/2013	Diab et al.	8,670,814 B2	3/2014	Diab et al.
8,466,286 B2	6/2013	Bellott et al.	8,676,286 B2	3/2014	Weber et al.
8,471,713 B2	6/2013	Poeze et al.	2003/0069489 A1 *	4/2003	Abreu ..... 600/405
			2009/0143655 A1	6/2009	Shani

\* cited by examiner





FIG. 1



*FIG. 2*




FIG. 3A






FIG. 3B






FIG. 5A




FIG. 5B




FIG. 6




FIG. 7

## PATIENT MONITOR FOR DETERMINING MICROCIRCULATION STATE

### CROSS-REFERENCE TO RELATED APPLICATIONS

This application is a continuation of U.S. patent application Ser. No. 13/101,093, filed May 4, 2011, titled PATIENT MONITOR FOR DETERMINING MICROCIRCULATION STATE, which claims the benefit of priority under 35 U.S.C. §119(e) of U.S. Provisional Application No. 61/332,155, filed May 6, 2010, titled PATIENT MONITOR FOR DETERMINING MICROCIRCULATION STATE, the entire contents of each of which are hereby incorporated by reference herein in their entireties.

### FIELD OF THE DISCLOSURE

The present disclosure relates to medical sensors and specifically to a medical sensor and/or monitor for determining the circulation state in blood vessels.

### BACKGROUND OF THE DISCLOSURE

Patient monitoring of various physiological parameters of a patient is important to a wide range of medical applications. Oximetry is one of the techniques that has developed to accomplish the monitoring of some of these physiological characteristics. It was developed to study and to measure, among other things, the oxygen status of blood. Pulse oximetry—a noninvasive, widely accepted form of oximetry—relies on a sensor attached externally to a patient to output signals indicative of various physiological parameters, such as a patient's constituents and/or analytes, including for example a percent value for arterial oxygen saturation, carbon monoxide saturation, methemoglobin saturation, fractional saturations, total hematocrit, bilirubins, perfusion quality, or the like. A pulse oximetry system generally includes a patient monitor, a communications medium such as a cable, and/or a physiological sensor having light emitters and a detector, such as one or more LEDs and a photodetector. The sensor is attached to a tissue site, such as a finger, toe, ear lobe, nose, hand, foot, or other site having pulsatile blood flow which can be penetrated by light from the emitters. The detector is responsive to the emitted light after attenuation by pulsatile blood flowing in the tissue site. The detector outputs a detector signal to the monitor over the communication medium, which processes the signal to provide a numerical readout of physiological parameters such as oxygen saturation (SpO<sub>2</sub>) and/or pulse rate.

High fidelity pulse oximeters capable of reading through motion induced noise are disclosed in U.S. Pat. Nos. 7,096,054, 6,813,511, 6,792,300, 6,770,028, 6,658,276, 6,157,850, 6,002,952, 5,769,785, and 5,758,644, which are assigned to Masimo Corporation of Irvine, Calif. ("Masimo Corp.") and are incorporated by reference herein. Advanced physiological monitoring systems can incorporate pulse oximetry in addition to advanced features for the calculation and display of other blood parameters, such as carboxyhemoglobin (HbCO), methemoglobin (HbMet), total hemoglobin (Hbt), total Hematocrit (Hct), oxygen concentrations, glucose concentrations, blood pressure, electrocardiogram data, temperature, and/or respiratory rate as a few examples. Typically, the physiological monitoring system provides a numerical readout of and/or waveform of the measured parameter. Advanced physiological monitors and multiple wavelength optical sensors capable of measuring parameters in addition to SpO<sub>2</sub>,

such as HbCO, HbMet and/or Hbt are described in at least U.S. patent application Ser. No. 11/367,013, filed Mar. 1, 2006, titled Multiple Wavelength Sensor Emitters and U.S. patent application Ser. No. 11/366,208, filed Mar. 1, 2006, titled Noninvasive Multi-Parameter Patient Monitor, assigned to Masimo Laboratories, Inc. and incorporated by reference herein. Further, noninvasive blood parameter monitors and optical sensors including Rainbow™ adhesive and reusable sensors and RAD-57™ and Radical-7™ monitors capable of measuring SpO<sub>2</sub>, pulse rate, perfusion index (PI), signal quality (SiQ), pulse variability index (PVI), HbCO and/or HbMet, among other parameters, are also commercially available from Masimo Corp.

During blood circulation, arteries carry blood away from the heart in high volume and under high pressure. Arteries branch off into smaller blood vessels, called arterioles. Arterioles are well innervated, surrounded by smooth muscle cells, and are about 10-100 μm in diameter. Arterioles carry the blood to the capillaries, which are the smallest blood vessels, which are not innervated, have no smooth muscle, and are about 5-8 μm in diameter. Blood flows out of the capillaries into the venules, which have little smooth muscle and are about 10-200 μm in diameter. The blood flows from venules into the veins, which carry blood back to the heart.

Microcirculation generally refers to the vascular network lying between the arterioles and the venules, including the capillaries, as well as the flow of blood through this network. These small vessels can be found in the vasculature which are embedded within organs and are responsible for the distribution of blood within tissues as opposed to larger vessels in the macrocirculation which transport blood to and from the organs. One of the functions of microcirculation is to deliver oxygen and other nutrients to tissue. Sometimes, microcirculation in these small vessels can become blocked, interfering with the delivery of oxygen to the tissue.

### SUMMARY OF THE DISCLOSURE

As placement of a physiological monitoring sensor is typically at a sensor site located at an extremity of the body, the state of microcirculation, such as whether vessels are blocked or open, can have a significant effect on the readings at the sensor site. It is therefore desirable to provide a patient monitor and/or physiological monitoring sensor capable of distinguishing the microcirculation state of blood vessels. In some embodiments, the patient monitor and/or sensor provide a warning and/or compensates a measurement based on the microcirculation state. In some embodiments, a microcirculation determination process implementable by the patient monitor and/or sensor is used to determine the state of microcirculation of the patient.

### BRIEF DESCRIPTION OF THE DRAWINGS

Throughout the drawings, reference numbers may be used to indicate correspondence between referenced elements. The drawings are provided to illustrate embodiments of the disclosure described herein and not to limit the scope thereof.

FIG. 1 illustrates a block diagram of a patient monitor, such as a pulse oximeter, and associated sensor;

FIG. 2 illustrates an example graph depicting the optical absorption characteristic of normal blood and plasma;

FIGS. 3A and 3B illustrate graphs of oxygen saturation values for a normal microcirculation state data set;

FIGS. 4A and 4B illustrate graphs of oxygen saturation values for another normal microcirculation state data set;

FIGS. 5A and 5B illustrate graphs of oxygen saturation values for an anomalous microcirculation state data set;

FIG. 6 illustrates a flow diagram for a process for determining the state of microcirculation usable by a pulse oximeter; and

FIG. 7 illustrates a flow diagram for a process for determining the state of microcirculation wherein multiple data points are collected.

#### DETAILED DESCRIPTION

FIG. 1 illustrates a block diagram of a patient monitor 100, such as a pulse oximeter, and associated sensor 110. Generally, in the case of a pulse oximeter, the sensor 110 has LED emitters 112, generally one at a red wavelength and one at an infrared wavelength, and a photodiode detector 114. The sensor 110 is generally attached to an adult patient's finger or an infant patient's foot. For a finger, the sensor 110 is configured so that the emitters 112 project light through the fingernail and through the blood vessels and capillaries underneath. The LED emitters 112 are activated by drive signals 122 from the pulse oximeter 100. The detector 114 is positioned at the fingertip opposite the fingernail so as to detect the LED emitted light as it emerges from the finger tissues. The photodiode generated signal 124 is relayed by a cable to the pulse oximeter 100.

A pulse oximeter 100 determines oxygen saturation (SpO<sub>2</sub>) by computing the differential absorption by arterial blood of the two wavelengths emitted by the sensor 110. A typical pulse oximeter 100 contains a sensor interface 120, one or more processors 130, such as a SpO<sub>2</sub> processor, an instrument manager 140, a display 150, an audible indicator (tone generator) 160, and a keypad 170. The sensor interface 120 provides LED drive current 122 which alternately activates the sensor's red and infrared LED emitters 112. The sensor interface 120 also has input circuitry for amplification and filtering of the signal 124 generated by the photodiode detector 114, which corresponds to the red and infrared light energy attenuated from transmission through the patient tissue site. The SpO<sub>2</sub> processor 130 calculates a ratio of detected red and infrared intensities, and an arterial oxygen saturation value is empirically determined based on that ratio. The instrument manager 140 provides hardware and software interfaces for managing the display 150, audible indicator 160, and keypad 170. The display 150 shows the computed oxygen saturation status, as described above. Similarly, other patient parameters including HbCO, HbMet, Hbt, Hct, oxygen concentrations, glucose concentrations, pulse rate, PI, SiQ, and/or PVI can be computed. The audible indicator 160 provides the pulse beep as well as alarms indicating desaturation events. The keypad 170 provides a user interface for such things as alarm thresholds, alarm enablement, and/or display options.

Computation of SpO<sub>2</sub> relies on the differential light absorption of oxygenated hemoglobin, HbO<sub>2</sub>, and deoxygenated hemoglobin, Hb, to determine their respective concentrations in the arterial blood. Specifically, pulse oximetry measurements are made at red (R) and infrared (IR) wavelengths chosen such that deoxygenated hemoglobin absorbs more red light than oxygenated hemoglobin, and, conversely, oxygenated hemoglobin absorbs more infrared light than deoxygenated hemoglobin, for example 660 nm (R) and 905 nm (IR).

To distinguish between tissue absorption at the two wavelengths, the red and infrared emitters 112 are provided drive current 122 so that only one is emitting light at a given time. For example, the emitters 112 can be cycled on and off alter-

nately, in sequence, with each only active for a quarter cycle and with a quarter cycle separating the active times. This allows for separation of red and infrared signals and removal of ambient light levels by downstream signal processing.

Because only a single detector 114 is used, it responds to both the red and infrared emitted light and generates a time-division-multiplexed ("modulated") output signal 124. This modulated signal 124 is coupled to the input of the sensor interface 120.

In addition to the differential absorption of hemoglobin derivatives, pulse oximetry relies on the pulsatile nature of arterial blood to differentiate hemoglobin absorption from absorption of other constituents in the surrounding tissues. Light absorption between systole and diastole varies due to the blood volume change from the inflow and outflow of arterial blood at a peripheral tissue site. This tissue site might also comprise skin, muscle, bone, venous blood, fat, pigment, and/or the like, each of which absorbs light. It is assumed that the background absorption due to these surrounding tissues is invariant and can be ignored. Thus, blood oxygen saturation measurements are based upon a ratio of the time-varying or AC portion of the detected red and infrared signals with respect to the time-invariant or DC portion:  $R/IR = (Red_{AC}/Red_{DC}) / (IR_{AC}/IR_{DC})$ .

The desired SpO<sub>2</sub> measurement is then computed from this ratio. The relationship between R/IR and SpO<sub>2</sub> can be determined by statistical regression of experimental measurements obtained from human volunteers and calibrated measurements of oxygen saturation. In a pulse oximeter device, this empirical relationship can be stored as a "calibration curve" in a read-only memory (ROM) look-up table so that SpO<sub>2</sub> can be directly read-out of the memory in response to input R/IR measurements.

The pulse oximeter 100 can also measure perfusion index, PI, which is a numerical value that indicates the strength of the IR signal returned from a monitoring site and provides a relative assessment of the pulse strength at the monitoring site. The perfusion index can be defined as follows:  $PI = (IR_{max} - IR_{min}) / IR_{DC}$ , where  $IR_{max}$  is the maximum value,  $IR_{min}$  is the minimum value, and  $IR_{DC}$  is the average value of the invariant portion. As the light absorption characteristic of blood is typically "flatter" or less sensitive to oxygen saturation around the infrared wavelength, the infrared signal from a sensor is influenced primarily by the amount of the blood at the monitoring site, not by the level of oxygenation in the blood. Accordingly, the perfusion index, which is a numerical value that indicates the strength of the IR signal returned from a monitoring site, provides a relative assessment of the pulse strength at the monitoring site. PI values generally range from 0.02% (very weak pulse strength) to 20% (very strong pulse strength). In some embodiments, PI can be measured using other wavelengths. For example, red, near red, near IR, as well as other wavelengths can be used.

In an embodiment, the sensor 110 also includes a memory device 116. The memory 116 can include any one or more of a wide variety of memory devices known to an artisan from the disclosure herein, including erasable programmable read only memory (EPROM), electrically erasable programmable read-only memory (EEPROM), flash memory, other non-volatile memory, a combination of the same or the like. The memory 116 can include read-only memory such as read-only memory (ROM), a read and write device such as a random-access memory (RAM), combinations of the same, or the like. The remainder of the present disclosure will refer to such combination as simply EPROM for ease of disclosure; however, an artisan will recognize from the disclosure herein

that the memory can include ROM, RAM, single wire memory, other types of memory, combinations of the same, or the like.

The memory device **116** can advantageously store some or all of a wide variety of data and information, including, for example, information on the type or operation of the sensor, type of patient or body tissue, buyer or manufacturer information, sensor characteristics including the number of wavelengths capable of being emitted, emitter specifications, emitter drive requirements, demodulation data, calculation mode data, calibration data, software such as scripts, executable code, or the like, sensor electronic elements, sensor life data indicating whether some or all sensor components have expired and should be replaced, encryption information, monitor or algorithm upgrade instructions or data, or the like. In an embodiment, the memory device can also include oxygen saturation to perfusion index and R/IR ratio to perfusion index ratios and/or data.

In certain situations, pulse oximetry sensors may produce anomalous readings, such as when a patient suffers from cyanosis. In a patient suffering from cyanosis, blood cells are uncharacteristically low on oxygen, leading to oxygen deficiency and giving the patient's skin a bluish-hue. One potential cause is that the patient's body produces too much hemoglobin, making the blood "thicker" or slower flowing, making microcirculation vessels more prone to blockage. Thus, a "blocked" microcirculation state can indicate cyanosis.

A "blocked" microcirculation state can also indicate other medical conditions, such as sepsis, systemic inflammatory response syndrome (SIRS), or septicemia. Sepsis is a potentially deadly medical condition that is characterized by a whole-body inflammatory state (called SIRS) and the presence of a known or suspected infection. The body may develop this inflammatory response by the immune system to microbes in the blood, urine, lungs, skin, or other tissue. Septicemia is a related medical term referring to the presence of pathogenic organisms in the bloodstream, which can lead to sepsis. Sepsis can also be referred to as blood poisoning. During sepsis or SIRS, inflammation in the body can cause constriction in blood vessels, leading to low blood pressure or insufficient blood flow.

During a "blocked" microcirculation state, blood cells can get blocked in the microcirculation vessels, such as the arterioles and capillaries. Blood cells can clump together or otherwise catch against the wall of blood vessels, creating a blockage that prevents blood cells, including red blood cells carrying hemoglobin, from passing through the blockage. However, plasma, which is composed of mostly water and in which the blood cells are suspended, is generally able to flow through passages in the blockage. In some situations, some blood vessels at the monitoring site may continue to have normal flow while some vessels are blocked. Thus, a "blocked" microcirculation state can indicate that some microcirculation vessels in an area are blocked and not necessarily all vessels in the area are blocked.

With the blockage preventing most or all the red blood cells from passing a blood vessel, at most only a limited amount of hemoglobin passes through a blocked blood vessel. In some situations, the blood vessel may only be partially blocked, where some hemoglobin passes through but less than when the blood vessel is unblocked. Normally, blood is made up of about 40-50% of red blood cells, of which about 95% is hemoglobin. Plasma, which is about 95% water, normally constitutes about 55% of the blood's volume.

Accordingly, a pulse oximeter placed on a tissue site experiencing blockage in microcirculation vessels may detect mostly plasma passing through with no or only a small per-

centage of red blood cells, at least at part of the monitoring site. The resulting change in the normal composition of blood can cause anomalous readings in the pulse oximetry monitor. As plasma has generally different absorption characteristics for red and infrared wavelengths than normal blood, pulse oximetry readings may become skewed. Red<sub>AC</sub> and/or IR<sub>AC</sub> can be affected, causing measured R/IR ratio to change. For example, if Red<sub>AC</sub> rises or IR<sub>AC</sub> drops, the R/IR ratio increases. Alternatively, if Red<sub>AC</sub> drops or IR<sub>AC</sub> rises, the R/IR ratio decreases. Thus, the value of R/IR can change due to a change in the light absorption of blood even if the underlying oxygen saturation of the blood remains the same.

However, by comparing oxygen saturation and PI for normal microcirculation to the oxygen saturation and PI for blocked microcirculation, such as by calculating and comparing ratios, the monitor can determine the existence of an abnormal situation. Typically, SpO<sub>2</sub> is mostly independent of PI, with SpO<sub>2</sub> varying minimally as PI increases. However, SpO<sub>2</sub> varying by more than normal as PI increases can indicate an anomalous microcirculation state, such as a blockage. In one embodiment, by analyzing the measured ratios, the pulse oximeter **100** can determine the microcirculation state, such as whether a blocked vessel exists in the microcirculation vessels.

FIG. **2** illustrates an example graph depicting the optical absorption characteristic of normal blood and plasma. The graph depicts sampling wavelengths at 660 nm 220 and at 905 nm 225. As illustrated, IR absorption for plasma at a frequency of 905 nm is on a "steeper" section of the curve compared to the "flatter" section of the curve for normal blood. This can imply that readings for IR for plasma would be more sensitive to changes in the absorption quality of the blood. In contrast, the IR measurement for normal blood, for example at 905 nm, is usually insensitive to a change in oxygenation of normal blood, but more affected by change in the amount of blood. As illustrated in the graph, plasma can have a "flatter" section in its absorption curve at a different wavelength, for example at 970 nm 230.

FIGS. **3A** and **3B** illustrate graphs of oxygen saturation values for a normal microcirculation state data set. FIG. **3A** has an y-axis **305** corresponding to the measured ratio, R/IR, and an x-axis **310** corresponding to perfusion index, PI. FIG. **3B** has a y-axis **320** corresponding to measured oxygen saturation, and an x-axis **325** corresponding to perfusion index, PI. FIGS. **3A** and **3B** represent multiple data points with a best fit line **315**, **330** indicating the trend of the data points. Each data point represents a measurement. As illustrated, the best fit line for FIG. **3A** trends slightly downward and the best fit line for FIG. **3B** trends slightly upwards. However, there is generally only a small change in the y-axis for the best fit line as PI increases, with the change in FIG. **3A** around 0.1 and the change in FIG. **3B** around **4**.

FIGS. **4A** and **4B** illustrate graphs of oxygen saturation values for another normal microcirculation state data set. FIG. **4A** has a y-axis **405** corresponding to the measured ratio, R/IR, and an x-axis **410** corresponding to perfusion index, PI. FIG. **4B** has a y-axis **420** corresponding to measured oxygen saturation, and an x-axis **425** corresponding to perfusion index, PI. FIGS. **4A** and **4B** represent multiple data points with a best fit line **415**, **430** indicating the trend of the data points. Each data point represents a measurement. As illustrated, the best fit line for FIG. **4A** trends slightly upwards and the best fit line for FIG. **4B** trends slightly downwards. However, there is generally only a small change in the y-axis for the best fit line as PI increases, with the change in FIG. **4A** around 0.1 and the change in FIG. **4B** around **3**.

FIGS. 5A and 5B illustrate graphs of oxygen saturation values for an anomalous microcirculation state data set. FIG. 5A has a y-axis 505 corresponding to the measured ratio, R/IR, and an x-axis 510 corresponding to perfusion index, PI. FIG. 5B has a y-axis 520 corresponding to measured oxygen saturation, and an x-axis 525 corresponding to perfusion index, PI. FIGS. 5A and 5B represent multiple data points with a best fit line 515, 530 indicating the trend of the data points. Each data point represents a measurement. As illustrated, the best fit line for FIG. 5A trends significantly upwards on the y-axis by around 0.3 and the best fit line for FIG. 5B trends significantly downwards on the y-axis by around 13 as PI increases.

In comparison to FIGS. 3A and 4A, FIG. 5A shows a high R/IR ratio for low values of PI that becomes a high R/IR ratio as PI increases. In comparison to FIGS. 3B and 4B, FIG. 5B shows a high reading for low values of PI that becomes a low reading as PI increases. Differences between the graphs can be explained by the microcirculation state in FIGS. 5A and 5B being different from the microcirculation state in FIGS. 3A-4B. For example, FIGS. 5A and 5B can represent a “blocked” or partially blocked microcirculation state where the blood passing through the sensor includes mostly plasma. As discussed above, this can skew R/IR and the measured oxygen saturation derived from R/IR.

FIG. 6 illustrates a flow diagram for a process 600 for determining the state of microcirculation usable by a pulse oximeter. Microcirculation state can be determined by comparison with microcirculation data stored on a patient monitor, such as the pulse oximeter 100 of FIG. 1. The process 600 can be implemented by embodiments of the sensor 110 and/or patient monitor 100 of FIG. 1 or other suitable device.

While in conventional pulse oximetry, measurements are generally taken pulse-by-pulse and averaged over pulses, microcirculation measurements can be measured using only a single pulse or a portion of a single pulse. This can be done, for example, at the minimum and/or maximum blood flow of a pulse. Microcirculation measurements can also be determined over multiple pulses. In some embodiments, microcirculation measurements are taken during a portion of the normal measurement time used by a physiological sensor to take a measurement of a parameter, thereby allowing detection of aberrant parameter measurements using the microcirculation measurements. For example, while a pulse oximeter is measuring SpO<sub>2</sub> over several pulses, microcirculation measurements can be taken per pulse and a warning given if an irregular microcirculation state is detected, thereby notifying a user of a possible aberration in the current SpO<sub>2</sub> reading.

At block 610, oxygen saturation is measured at a tissue monitoring site. In one embodiment, oxygen saturation is determined using a pulse oximeter sensor.

At block 620, perfusion index or pulse strength is measured. In one embodiment, the perfusion index is determined using the same sensor used to measure oxygen saturation so that readings are taken at the same monitoring site.

At block 630, a ratio of oxygen saturation to perfusion index is determined. Oxygen saturation can be a SpO<sub>2</sub> value based on the measured R/IR ratio looked-up against a calibration curve. Alternatively, the ratio can be perfusion index to oxygen saturation. In other embodiments, the measured R/IR ratio can be used directly instead of SpO<sub>2</sub>.

In some embodiments, multiple readings of perfusion index and oxygen saturation can be taken and averaged together before determining the ratio in order to account for outliers. The multiple readings can be filtered before averaging. For example, readings can first be filtered based on closeness of PI values before the readings are averaged together.

At block 640, the determined ratio in block 630 is compared to stored microcirculation data. The stored data can be data sets for microcirculation states. In some embodiments, a ratio, a curve, a line, table, data points, or formula can be stored that corresponds to a data set. The measured perfusion index and oxygen saturation can then be compared to the stored data. In some embodiments, multiple readings are taken and a best fit line or curve is generated and compared to a stored best fit line or curve. In some embodiments, readings are collected at various PI values in order to generate a trend line.

At block 650, the microcirculation state is determined from comparison of the stored microcirculation data. For example, if the determined ratio is similar to a stored ratio corresponding to a data set for unblocked microcirculation, the microcirculation state is determined to be unblocked. Other data sets for other microcirculation states, such as blocked and/or partially blocked can also be stored. Where multiple data sets are stored, the state can be determined by selecting the state corresponding to the stored ratio closest to the measured ratio.

At block 660, the monitor can optionally generate an alarm and/or display the microcirculation state. For example, an alarm signal can be generated by the monitor to indicate that the readings may be anomalous, such as when a blocked or partially blocked microcirculation state is detected. The alarm can be a visual indicator (e.g., icon, message or image) and/or an audio indicator. In an embodiment, the alarm can indicate the detection of cyanosis, sepsis, SIRS or other medical condition based at least partly on the determined microcirculation state. In some situations, no action is taken, such as when readings are determined to be normal or non-threatening.

At block 670, the monitor can optionally compensate for the microcirculation state in order to improve accuracy of the readings. After the microcirculation state returns to normal, the compensation process can be ended.

In one embodiment, an offset can be added to the measured parameter value, such as SpO<sub>2</sub>. The offset can be calculated based on data sets for microcirculation state. Different microcirculation states can have different offsets. For example, if a “blocked” microcirculation state produces high readings for low PI values, a negative offset can be used. However, if a “blocked” state produces a low value for high PI values, then a positive offset can be used. In one embodiment, a varying offset can be used depending on the value of PI.

In one embodiment, a different wavelength emitter can be used to compensate for a microcirculation state. For example, rather than using a regular infrared emitter, typically 905 nm, an emitter with a different infrared wavelength, such as 970 nm can be used. In one embodiment, the different wavelength is selected such that the wavelength is at a “flat” section of the light absorption curve for plasma, that is, where the light absorption is not much affected by changes in oxygen saturation. In one embodiment, the selected wavelength with regards to plasma mimics the properties of the regular wavelength with regards to normal flowing blood. In some embodiments, a different wavelength red emitter can be used instead of the regular red wavelength emitter.

In some embodiments, the pulse oximeter sensor used to measure oxygen saturation and PI can be provided with an additional emitter at a different wavelength than the existing emitters. When a certain microcirculation state is detected, such as a “blocked” state, the additional emitter can be used. For example, a pulse oximetry sensor can be equipped with LED's capable of emitting at 660 nm, 905 nm, and at 970 nm wavelengths. Under normal operation, the 660 nm and 905 nm emitters are active. However, upon detecting a blocked

microcirculation state, the 905 nm emitter can be deactivated and the 970 nm emitter activated in its place. In some embodiments, a variable wavelength emitter can be used rather than separate emitters. In some embodiments, the additional emitter can be a red wavelength emitter.

FIG. 7 illustrates a flow diagram for a process 700 for determining the state of microcirculation wherein multiple data points are collected. The process 700 can be implemented by embodiments of the sensor 110 and/or patient monitor 100 of FIG. 1 or other suitable device.

At block 710 and block 720, oxygen saturation and perfusion index are measured. At block 725, measured values are stored in memory. Each paired measurement forms a data point.

At block 730, the number of stored data points is checked to determine if sufficient data has been collected to determine the microcirculation state. Data can be sufficient if a set number of data points have been collected, a set amount of time has passed, and/or a spectrum of data points have been collected, such as for differing values of PI.

At block 740, the stored measured data is compared with stored microcirculation data. Typically, the microcirculation data is pre-stored on the pulse oximeter before use, as opposed to collected during use. A comparison can involve generating a curve or line from the measured data, calculating a rate of change for the stored data, generating a trend line for the measured data or the like and comparing with the stored microcirculation data.

At block 750, the microcirculation state is determined from comparison of the stored microcirculation data. For example, if the measured data is similar to microcirculation data corresponding to a data set for unblocked microcirculation, the microcirculation state is determined to be unblocked. Other data sets for other microcirculation states, such as for blocked and/or partially blocked can also be stored. Where multiple data sets are stored, the state can be determined by selecting the state corresponding to the stored ratio closest to the measured ratio.

Blocks 760 and 770 are similar to steps 660 and 670 described in FIG. 6.

As will be apparent from the above description, the R/IR ratio corresponds to oxygen saturation or SpO2 and can be used in place of oxygen saturation or SpO2 for the above comparisons, and vice versa.

While the above systems and methods have been described in terms of oxygen saturation and PI, other physiological parameters can be measured in place of or in addition to oxygen saturation and/or perfusion index and used to determine microcirculation state. For example, perfusion index is an indication of amplitude and/or signal strength and other parameters or measurements indicating amplitude and/or signal strength can be used. In some embodiments, one or more different sensors can be used in place of or in addition to a pulse oximeter sensor.

Conditional language used herein, such as, among others, “can,” “could,” “might,” “may,” “e.g.,” and the like, unless specifically stated otherwise, or otherwise understood within the context as used, is generally intended to convey that certain embodiments include, while other embodiments do not include, certain features, elements and/or states. Thus, such conditional language is not generally intended to imply that features, elements and/or states are in any way required for one or more embodiments or that one or more embodiments necessarily include logic for deciding, with or without author input or prompting, whether these features, elements and/or states are included or are to be performed in any particular embodiment. The terms “comprising,” “including,”

“having,” and the like are synonymous and are used inclusively, in an open-ended fashion, and do not exclude additional elements, features, acts, operations, and so forth. Also, the term “or” is used in its inclusive sense (and not in its exclusive sense) so that when used, for example, to connect a list of elements, the term “or” means one, some, or all of the elements in the list.

Various systems and processes for determining microcirculation state have been disclosed in detail in connection with various embodiments. These embodiments are disclosed by way of examples only and are not to limit the scope of the claims that follow. Indeed, the novel methods and systems described herein can be embodied in a variety of other forms; furthermore, various omissions, substitutions and changes in the form of the methods and systems described herein can be made without departing from the spirit of the inventions disclosed herein. The claims and their equivalents are intended to cover such forms or modifications as would fall within the scope and spirit of certain of the inventions disclosed herein. One of ordinary skill in the art will appreciate the many variations, modifications and combinations. For example, the various embodiments of the microcirculation determination process can be used with other oxygen saturation sensors and with both disposable and reusable sensors. In some embodiments, the determination process can be applied to other blood vessels to detect a blockage, even in vessels not involved in microcirculation.

Furthermore, in certain embodiments, the systems and methods described herein can advantageously be implemented using computer software, hardware, firmware, or any combination of software, hardware, and firmware. In one embodiment, the system includes a number of software modules that comprise computer executable code for performing the functions described herein. In certain embodiments, the computer-executable code is executed on one or more general purpose computers or processors. However, a skilled artisan will appreciate, in light of this disclosure, that any module that can be implemented using software can also be implemented using a different combination of hardware, software or firmware. For example, such a module can be implemented completely in hardware using a combination of integrated circuits. Alternatively or additionally, such a module can be implemented completely or partially using specialized computers or processors designed to perform the particular functions described herein rather than by general purpose computers or processors.

Moreover, certain embodiments of the invention are described with reference to methods, apparatus (systems) and computer program products that can be implemented by computer program instructions. These computer program instructions can be provided to a processor of a general purpose computer, special purpose computer, or other programmable data processing apparatus to produce a machine, such that the instructions, which execute via the processor of the computer or other programmable data processing apparatus, create means for implementing the acts specified herein to transform data from a first state to a second state.

Each of the processes, methods, and algorithms described in the preceding sections may be embodied in, and fully or partially automated by, code modules executed by one or more computers or computer processors. The code modules may be stored on any type of non-transitory computer-readable medium or computer storage device, such as hard drives, solid state memory, optical disc, and/or the like. The processes and algorithms may be implemented partially or wholly in application-specific circuitry. The results of the disclosed processes and process steps may be stored, persis-

tently or otherwise, in any type of non-transitory computer storage such as, e.g., volatile or non-volatile storage.

The various features and processes described above may be used independently of one another, or may be combined in various ways. All possible combinations and subcombinations are intended to fall within the scope of this disclosure. In addition, certain method or process blocks may be omitted in some implementations. The methods and processes described herein are also not limited to any particular sequence, and the blocks or states relating thereto can be performed in other sequences that are appropriate. For example, described blocks or states may be performed in an order other than that specifically disclosed, or multiple blocks or states may be combined in a single block or state. The example blocks or states may be performed in serial, in parallel, or in some other manner. Blocks or states may be added to or removed from the disclosed example embodiments. The example systems and components described herein may be configured differently than described. For example, elements may be added to, removed from, or rearranged compared to the disclosed example embodiments.

While certain example embodiments have been described, these embodiments have been presented by way of example only, and are not intended to limit the scope of the inventions disclosed herein. Thus, nothing in the foregoing description is intended to imply that any particular feature, characteristic, step, module, or block is necessary or indispensable. Indeed, the novel methods and systems described herein may be embodied in a variety of other forms; furthermore, various omissions, substitutions and changes in the form of the methods and systems described herein may be made without departing from the spirit of the inventions disclosed herein. The accompanying claims and their equivalents are intended to cover such forms or modifications as would fall within the scope and spirit of certain of the inventions disclosed herein.

What is claimed is:

1. A patient monitor configured to determine a microcirculation state, the patient monitor comprising:

a sensor interface configured to receive a signal from a physiological sensor, the signal indicative of first and second measurement values corresponding to respective first and second physiological parameters, wherein the physiological sensor is configured to transmit light of at least one wavelength into tissue of a patient and to detect the light after it has been attenuated by the tissue, and wherein the second physiological parameter comprises a measure of perfusion; and

one or more processors configured to:

determine a relationship between the first and second physiological parameters; and  
compare the determined relationship between the first and second physiological parameters with stored lookup data indicative of a microcirculation state of blood vessels to determine if a blocked or partially blocked microcirculation state exists in at least a portion of blood vessels in the tissue;

wherein the one or more processors are further configured to generate a drive signal to configure the physiological sensor to measure a light absorption characteristic of the tissue at a different wavelength in response to the determination of the microcirculation state.

2. The patient monitor of claim 1, wherein the first physiological parameter comprises oxygen saturation.

3. The patient monitor of claim 2, wherein the measure of perfusion comprises a perfusion index.

4. The patient monitor of claim 3, wherein the physiological sensor comprises a pulse oximeter sensor.

5. The patient monitor of claim 1 further comprising an alarm configured to activate when a blocked or partially blocked microcirculation state is determined to exist.

6. The patient monitor of claim 5, wherein the alarm is configured to activate when the blocked or partially blocked microcirculation state is indicative of cyanosis.

7. The patient monitor of claim 5, wherein the alarm is configured to activate when the blocked or partially blocked microcirculation state is indicative of sepsis.

8. A method of non-invasively determining a microcirculation state, the method comprising:

obtaining, at a tissue site by a non-invasive physiological sensor, first and second measurement values corresponding to respective first and second physiological parameters, the second physiological parameter comprising a measure of perfusion;

determining a relationship between the first and second physiological parameters;

comparing the determined relationship between the first and second physiological parameters with stored lookup data indicative of a microcirculation state of blood vessels to determine if a blocked or partially blocked microcirculation state exists in at least a portion of blood vessels at the tissue site; and

applying an offset to at least one of the first physiological parameter or the second physiological parameter to compensate for a blocked or partially blocked microcirculation state.

9. The method of claim 8, wherein the first physiological parameter comprises oxygen saturation.

10. The method of claim 9, wherein the measure of perfusion comprises a perfusion index.

11. The method of claim 10, wherein the non-invasive physiological sensor comprises a pulse oximeter sensor.

12. The method of claim 8, wherein determining a relationship between the first and second physiological parameters comprises generating a ratio of the first measurement value to the second measurement value.

13. The method of claim 8, wherein determining a relationship between the first and second physiological parameters corresponds to generating a trend line based on the stored data points of the first and second physiological parameters.

14. The method of claim 8, wherein the stored lookup data comprises at least one lookup curve.

15. The method of claim 8 further comprising generating an alarm signal when a blocked or partially blocked microcirculation state is determined.

16. A patient monitor configured to determine a microcirculation state, the patient monitor comprising:

a sensor interface configured to receive a signal from a physiological sensor, the physiological sensor configured to transmit light of at least one wavelength into living tissue of a patient and to detect the light after it has been attenuated by the tissue; and

one or more processors configured to determine a microcirculation state of the tissue based on at least a first physiological parameter derived from an analysis of detected attenuated light, and at least a measurement of perfusion;

wherein the one or more processors are further configured to generate a drive signal to configure the physiological sensor to measure the light absorption characteristic of the tissue monitoring site at a different wavelength in response to the determination of the microcirculation state.

17. The patient monitor of claim 16, wherein the microcirculation state comprises one of an unblocked, a blocked, or a partially blocked state.

18. The patient monitor of claim 17 further comprising an alarm configured to activate when a blocked or partially blocked microcirculation state is detected. 5

19. The patient monitor of claim 16, wherein the physiological sensor comprises a pulse oximeter sensor.

20. The patient monitor of claim 16 further comprising an alarm configured to activate when cyanosis is detected based at least partly on the microcirculation state of the tissue. 10

21. The patient monitor of claim 16 further comprising an alarm configured to activate when sepsis is detected based at least partly on the microcirculation state of the tissue.

\* \* \* \* \*

专利名称(译)	用于确定微循环状态的患者监测器		
公开(公告)号	<a href="#">US9192312</a>	公开(公告)日	2015-11-24
申请号	US14/160316	申请日	2014-01-21
[标]申请(专利权)人(译)	梅西莫股份有限公司		
申请(专利权)人(译)	Masimo公司		
当前申请(专利权)人(译)	Masimo公司		
[标]发明人	AL ALI AMMAR		
发明人	AL-ALI, AMMAR		
IPC分类号	A61B5/1455 A61B5/00 A61B5/026 A61B5/024		
CPC分类号	A61B5/0261 A61B5/02427 A61B5/14551 A61B5/14552 A61B5/7282 A61B5/746 A61B5/02007 A61B5/6801 A61B5/7275		
代理机构(译)	KNOBBE, MARTENS, 奥尔森 & BEAR LLP		
优先权	61/332155 2010-05-06 US		
其他公开文献	US20140194711A1		
外部链接	<a href="#">Espacenet</a> <a href="#">USPTO</a>		

摘要(译)

由于生理监测传感器的放置通常位于位于身体末端的传感器位置处，微循环状态（例如血管是否被阻塞或打开）可对传感器部位处的读数产生显著影响。因此，希望提供一种能够区分血管微循环状态的患者监测器和/或生理监测传感器。在一些实施例中，患者监测器和/或传感器基于微循环状态提供警告和/或补偿测量。在一些实施例中，可由患者监测器和/或传感器实现的微循环确定过程用于确定患者的微循环状态。

