



US010357209B2

(12) **United States Patent**  
**Al-Ali**

(10) **Patent No.:** **US 10,357,209 B2**  
(45) **Date of Patent:** **Jul. 23, 2019**

(54) **BIDIRECTIONAL PHYSIOLOGICAL INFORMATION DISPLAY**

(71) Applicant: **MASIMO CORPORATION**, Irvine, CA (US)

(72) Inventor: **Ammar Al-Ali**, San Juan Capistrano, CA (US)

(73) Assignee: **MASIMO CORPORATION**, Irvine, CA (US)

(\* ) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 0 days.

(21) Appl. No.: **15/615,654**

(22) Filed: **Jun. 6, 2017**

(65) **Prior Publication Data**

US 2018/0110478 A1 Apr. 26, 2018

**Related U.S. Application Data**

(63) Continuation of application No. 14/444,705, filed on Jul. 28, 2014, now Pat. No. 9,668,703, which is a (Continued)

(51) **Int. Cl.**  
**A61B 5/08** (2006.01)  
**A61B 5/00** (2006.01)  
(Continued)

(52) **U.S. Cl.**  
CPC ..... **A61B 5/7445** (2013.01); **A61B 5/08** (2013.01); **A61B 5/0816** (2013.01);  
(Continued)

(58) **Field of Classification Search**  
CPC ..... **A61B 5/7445**; **A61B 5/08**  
See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

2,699,465 A 1/1955 Selden  
3,399,467 A 9/1968 Ravin  
(Continued)

FOREIGN PATENT DOCUMENTS

CA 2262236 4/2008  
CN 201497610 6/2010  
(Continued)

OTHER PUBLICATIONS

US 8,740,816 B2, 06/2014, Telfort et al. (withdrawn)  
(Continued)


*Primary Examiner* — Meredith Weare

(74) *Attorney, Agent, or Firm* — Knobbe, Martens, Olson & Bear, LLP

(57) **ABSTRACT**

A patient monitor for displaying a physiological signal can include a visual element having a middle portion indicative of a transition in the physiological signal between physiological states. The visual element can also include first and second extremity portions, the first extremity portion extending from the middle portion in a first direction and the second extremity portion extending from the middle portion in a second direction. The visual element can also include an actionable value indicator to specify a value about the middle portion and the first and second extremity portions. The patient monitor can also include a processor configured to cause the value indicator to actuate in both the first and second directions according to changes in the physiological signal.

**20 Claims, 15 Drawing Sheets**



**Related U.S. Application Data**

- continuation of application No. 12/904,823, filed on Oct. 14, 2010, now Pat. No. 8,790,268.
- (60) Provisional application No. 61/252,083, filed on Oct. 15, 2009, provisional application No. 61/288,843, filed on Dec. 21, 2009, provisional application No. 61/290,436, filed on Dec. 28, 2009, provisional application No. 61/331,087, filed on May 4, 2010.
- (51) **Int. Cl.**  
*A61B 7/00* (2006.01)  
*G16H 40/63* (2018.01)  
*G16H 50/20* (2018.01)  
*G06F 19/00* (2018.01)  
*G16H 15/00* (2018.01)
- (52) **U.S. Cl.**  
 CPC ..... *A61B 5/6833* (2013.01); *A61B 5/7435* (2013.01); *A61B 7/003* (2013.01); *G16H 40/63* (2018.01); *G16H 50/20* (2018.01); *G06F 19/3418* (2013.01); *G16H 15/00* (2018.01)

(56) **References Cited**

U.S. PATENT DOCUMENTS

3,682,161 A	8/1972	Alibert	
3,867,925 A	2/1975	Ersek	
3,951,230 A	4/1976	Littmann	
3,991,304 A *	11/1976	Hillsman	..... A61B 5/087 600/538
4,127,749 A	11/1978	Atoji et al.	
4,254,302 A	3/1981	Walshe	
4,326,143 A	4/1982	Guth et al.	
4,401,125 A	8/1983	Taylor et al.	
4,413,202 A	11/1983	Krempf et al.	
4,537,200 A	8/1985	Widrow	
4,576,179 A	3/1986	Manus et al.	
4,578,613 A	3/1986	Posthuma de Boer et al.	
4,634,917 A	1/1987	Dvorksy et al.	
4,653,498 A	3/1987	New, Jr. et al.	
4,672,976 A	6/1987	Kroll	
4,805,633 A	2/1989	Kotani et al.	
4,827,943 A	5/1989	Born et al.	
4,871,046 A	10/1989	Turner	
4,884,809 A	12/1989	Rowan	
4,924,876 A	5/1990	Cameron	
4,947,853 A	8/1990	Hon	
4,947,859 A	8/1990	Brewer et al.	
4,960,118 A	10/1990	Pennock	
4,960,128 A	10/1990	Gordon et al.	
4,964,408 A	10/1990	Hink et al.	
4,982,738 A	1/1991	Griebel	
5,003,605 A	3/1991	Phillipps et al.	
5,033,032 A	7/1991	Houghtaling	
5,036,857 A	8/1991	Semmlow et al.	
5,041,187 A	8/1991	Hink et al.	
5,069,213 A	12/1991	Polczynski	
5,078,151 A	1/1992	Laballery	
5,140,992 A	8/1992	Zuckerwar et al.	
5,143,078 A	9/1992	Mather et al.	
5,163,438 A	11/1992	Gordon et al.	
5,269,314 A	12/1993	Kendall et al.	
5,278,627 A	1/1994	Aoyagi et al.	
5,319,355 A	6/1994	Russek	
5,333,106 A *	7/1994	Lanpher	..... G09B 5/02 128/200.12
5,337,744 A	8/1994	Branigan	
5,341,805 A	8/1994	Stavridi et al.	
D353,195 S	12/1994	Savage et al.	
D353,196 S	12/1994	Savage et al.	
5,377,676 A	1/1995	Vari et al.	
5,394,877 A	3/1995	Orr et al.	
5,406,952 A	4/1995	Barnes et al.	
D359,546 S	6/1995	Savage et al.	
5,431,170 A	7/1995	Mathews	
D361,840 S	8/1995	Savage et al.	
D362,063 S	9/1995	Savage et al.	
5,448,996 A	9/1995	Bellin et al.	
5,452,717 A	9/1995	Branigan et al.	
D363,120 S	10/1995	Savage et al.	
5,456,252 A	10/1995	Vari et al.	
5,479,934 A	1/1996	Imran	
5,482,036 A	1/1996	Diab et al.	
5,490,505 A	2/1996	Diab et al.	
5,494,043 A	2/1996	O'Sullivan et al.	
5,533,511 A	7/1996	Kaspari et al.	
5,534,851 A	7/1996	Russek	
5,539,831 A	7/1996	Harley	
5,561,275 A	10/1996	Savage et al.	
5,562,002 A	10/1996	Lalin	
5,564,108 A	10/1996	Hunsaker et al.	
5,578,799 A	11/1996	Callahan et al.	
5,590,649 A	1/1997	Caro et al.	
5,602,924 A	2/1997	Durand et al.	
5,632,272 A	5/1997	Diab et al.	
5,638,816 A	6/1997	Kiani-Azarbayjany et al.	
5,638,818 A	6/1997	Diab et al.	
5,645,440 A	7/1997	Tobler et al.	
5,685,299 A	11/1997	Diab et al.	
5,730,140 A	3/1998	Fitch	
D393,830 S	4/1998	Tobler et al.	
5,738,106 A	4/1998	Yamamori et al.	
5,743,262 A	4/1998	Lepper, Jr. et al.	
5,758,644 A	6/1998	Diab et al.	
5,760,910 A	6/1998	Lepper, Jr. et al.	
5,769,785 A	6/1998	Diab et al.	
5,782,757 A	7/1998	Diab et al.	
5,785,659 A	7/1998	Caro et al.	
5,791,347 A	8/1998	Flaherty et al.	
5,810,734 A	9/1998	Caro et al.	
5,812,678 A	9/1998	Scalise et al.	
5,823,950 A	10/1998	Diab et al.	
5,825,895 A	10/1998	Grasfield et al.	
5,830,131 A	11/1998	Caro et al.	
5,833,618 A	11/1998	Caro et al.	
5,860,919 A	1/1999	Kiani-Azarbayjany et al.	
5,890,929 A	4/1999	Mills et al.	
5,904,654 A	5/1999	Wohlmann et al.	
5,912,656 A	6/1999	Tham et al.	
5,919,134 A	7/1999	Diab	
5,921,941 A	7/1999	Longobardo et al.	
5,934,925 A	8/1999	Tobler et al.	
5,940,182 A	8/1999	Lepper, Jr. et al.	
5,977,538 A	11/1999	Unger et al.	
5,987,343 A	11/1999	Kinast	
5,989,193 A	11/1999	Sullivan	
5,995,855 A	11/1999	Kiani et al.	
5,997,343 A	12/1999	Mills et al.	
6,002,952 A	12/1999	Diab et al.	
6,011,986 A	1/2000	Diab et al.	
6,027,452 A	2/2000	Flaherty et al.	
6,036,642 A	3/2000	Diab et al.	
6,045,509 A	4/2000	Caro et al.	
6,048,323 A	4/2000	Hon	
6,067,462 A	5/2000	Diab et al.	
6,081,735 A	6/2000	Diab et al.	
6,083,156 A	7/2000	Lisiecki	
6,088,607 A	7/2000	Diab et al.	
6,106,481 A	8/2000	Cohen	
6,110,522 A	8/2000	Lepper, Jr. et al.	
6,124,597 A	9/2000	Shehada	
6,128,521 A	10/2000	Marro et al.	
6,129,675 A	10/2000	Jay	
6,144,868 A	11/2000	Parker	
6,151,516 A	11/2000	Kiani-Azarbayjany et al.	
6,152,754 A	11/2000	Gerhardt et al.	
6,157,850 A	12/2000	Diab et al.	
6,165,005 A	12/2000	Mills et al.	
6,168,568 B1	1/2001	Gavriely	
6,184,521 B1	2/2001	Coffin, IV et al.	
6,206,830 B1	3/2001	Diab et al.	

(56)

## References Cited

## U.S. PATENT DOCUMENTS

6,210,344	B1	4/2001	Perin et al.	6,714,804	B2	3/2004	Al-Ali et al.
6,229,856	B1	5/2001	Diab et al.	RE38,492	E	4/2004	Diab et al.
6,232,609	B1	5/2001	Snyder et al.	6,721,582	B2	4/2004	Trepagnier et al.
6,236,872	B1	5/2001	Diab et al.	6,721,585	B1	4/2004	Parker
6,241,683	B1	6/2001	Macklem et al.	6,725,074	B1	4/2004	Kästle
6,248,083	B1	6/2001	Smith et al.	6,725,075	B2	4/2004	Al-Ali
6,253,097	B1	6/2001	Aronow et al.	6,728,560	B2	4/2004	Kollias et al.
6,256,523	B1	7/2001	Diab et al.	6,735,459	B2	5/2004	Parker
6,261,237	B1	7/2001	Swanson et al.	6,745,060	B2	6/2004	Diab et al.
6,263,222	B1	7/2001	Diab et al.	6,760,607	B2	7/2004	Al-Ali
6,271,760	B1	8/2001	Watanabe et al.	6,770,028	B1	8/2004	Ali et al.
6,275,594	B1	8/2001	Senoo et al.	6,771,994	B2	8/2004	Kiani et al.
6,278,522	B1	8/2001	Lepper, Jr. et al.	6,792,300	B1	9/2004	Diab et al.
6,280,213	B1	8/2001	Tobler et al.	6,813,511	B2	11/2004	Diab et al.
6,285,896	B1	9/2001	Tobler et al.	6,816,741	B2	11/2004	Diab
6,295,365	B1	9/2001	Ota	6,816,744	B2	11/2004	Garfield et al.
6,301,493	B1	10/2001	Marro et al.	6,822,564	B2	11/2004	Al-Ali
6,308,089	B1	10/2001	von der Ruhr et al.	6,826,419	B2	11/2004	Diab et al.
6,317,627	B1	11/2001	Ennen et al.	6,830,711	B2	12/2004	Mills et al.
6,321,100	B1	11/2001	Parker	6,850,787	B2	2/2005	Weber et al.
6,325,761	B1	12/2001	Jay	6,850,788	B2	2/2005	Al-Ali
6,334,065	B1	12/2001	Al-Ali et al.	6,852,083	B2	2/2005	Caro et al.
6,343,224	B1	1/2002	Parker	6,861,639	B2	3/2005	Al-Ali
6,349,228	B1	2/2002	Kiani et al.	6,898,452	B2	5/2005	Al-Ali et al.
6,360,114	B1	3/2002	Diab et al.	6,920,345	B2	7/2005	Al-Ali et al.
6,368,283	B1	4/2002	Xu et al.	6,931,268	B1	8/2005	Kiani-Azarbayjany et al.
6,371,921	B1	4/2002	Caro et al.	6,934,570	B2	8/2005	Kiani et al.
6,377,829	B1	4/2002	Al-Ali	6,937,736	B2	8/2005	Toda
6,388,240	B2	5/2002	Schulz et al.	6,939,305	B2	9/2005	Flaherty et al.
6,397,091	B2	5/2002	Diab et al.	6,943,348	B1	9/2005	Coffin, IV
6,411,014	B1	6/2002	Toda	6,950,687	B2	9/2005	Al-Ali
6,415,033	B1	7/2002	Halleck et al.	6,954,971	B1	10/2005	Bryant et al.
6,423,013	B1	7/2002	Bakker et al.	6,961,598	B2	11/2005	Diab
6,430,437	B1	8/2002	Marro	6,970,792	B1	11/2005	Diab
6,430,525	B1	8/2002	Weber et al.	6,979,812	B2	12/2005	Al-Ali
6,438,238	B1	8/2002	Callahan	6,985,764	B2	1/2006	Mason et al.
6,463,311	B1	10/2002	Diab	6,993,371	B2	1/2006	Kiani et al.
6,470,199	B1	10/2002	Kopotic et al.	6,996,427	B2	2/2006	Ali et al.
6,486,588	B2	11/2002	Doron et al.	6,999,904	B2	2/2006	Weber et al.
6,501,975	B2	12/2002	Diab et al.	7,003,338	B2	2/2006	Weber et al.
6,505,059	B1	1/2003	Kollias et al.	7,003,339	B2	2/2006	Diab et al.
6,515,273	B2	2/2003	Al-Ali	7,015,451	B2	3/2006	Dalke et al.
6,517,497	B2	2/2003	Rymut et al.	7,020,508	B2	3/2006	Stivoric et al.
6,519,487	B1	2/2003	Parker	7,024,233	B2	4/2006	Ali et al.
6,525,386	B1	2/2003	Mills et al.	7,027,849	B2	4/2006	Al-Ali
6,526,300	B1	2/2003	Kiani et al.	7,030,749	B2	4/2006	Al-Ali
6,541,756	B2	4/2003	Schulz et al.	7,035,684	B2	4/2006	Lee
6,542,764	B1	4/2003	Al-Ali et al.	7,039,449	B2	5/2006	Al-Ali
6,560,470	B1	5/2003	Pologe	7,041,060	B2	5/2006	Flaherty et al.
6,571,113	B1	5/2003	Fein	7,044,918	B2	5/2006	Diab
6,580,086	B1	6/2003	Schulz et al.	7,048,687	B1	5/2006	Reuss et al.
6,584,336	B1	6/2003	Ali et al.	7,067,893	B2	6/2006	Mills et al.
6,595,316	B2	7/2003	Cybulski et al.	7,096,052	B2	8/2006	Mason et al.
6,597,932	B2	7/2003	Tian et al.	7,096,054	B2	8/2006	Abdul-Hafiz et al.
6,597,933	B2	7/2003	Kiani et al.	7,096,060	B2	8/2006	Arand et al.
6,606,511	B1	8/2003	Ali et al.	7,110,804	B2	9/2006	Baumer et al.
6,632,181	B2	10/2003	Flaherty et al.	7,132,641	B2	11/2006	Schulz et al.
6,639,668	B1	10/2003	Trepagnier	7,142,901	B2	11/2006	Kiani et al.
6,640,116	B2	10/2003	Diab	7,149,561	B2	12/2006	Diab
6,643,530	B2	11/2003	Diab et al.	7,186,966	B2	3/2007	Al-Ali
6,650,917	B2	11/2003	Diab et al.	7,190,261	B2	3/2007	Al-Ali
6,654,624	B2	11/2003	Diab et al.	7,215,984	B2	5/2007	Diab
6,658,276	B2	12/2003	Kiani et al.	7,215,986	B2	5/2007	Diab
6,661,161	B1*	12/2003	Lanzo ..... A61B 7/00 310/334	7,221,971	B2	5/2007	Diab
6,671,531	B2	12/2003	Al-Ali et al.	7,225,006	B2	5/2007	Al-Ali et al.
6,678,543	B2	1/2004	Diab et al.	7,225,007	B2	5/2007	Al-Ali
6,684,090	B2	1/2004	Ali et al.	RE39,672	E	6/2007	Shehada et al.
6,684,091	B2	1/2004	Parker	7,239,905	B2	7/2007	Kiani-Azarbayjany et al.
6,697,656	B1	2/2004	Al-Ali	7,245,953	B1	7/2007	Parker
6,697,657	B1	2/2004	Shehada et al.	7,246,069	B1	7/2007	O'Hanlon et al.
6,697,658	B2	2/2004	Al-Ali	7,254,429	B2	8/2007	Schurman et al.
RE38,476	E	3/2004	Diab et al.	7,254,431	B2	8/2007	Al-Ali
6,699,194	B1	3/2004	Diab et al.	7,254,433	B2	8/2007	Diab et al.
6,702,755	B1	3/2004	Stasz et al.	7,254,434	B2	8/2007	Schulz et al.
				7,270,126	B2	9/2007	Wallace et al.
				7,272,425	B2	9/2007	Al-Ali
				7,274,955	B2	9/2007	Kiani et al.
				D554,263	S	10/2007	Al-Ali
				7,280,858	B2	10/2007	Al-Ali et al.

(56)

## References Cited

## U.S. PATENT DOCUMENTS

7,289,835	B2	10/2007	Mansfield et al.	7,880,606	B2	2/2011	Al-Ali
7,292,883	B2	11/2007	De Felice et al.	7,880,626	B2	2/2011	Al-Ali et al.
7,295,866	B2	11/2007	Al-Ali	7,891,355	B2	2/2011	Al-Ali et al.
7,328,053	B1	2/2008	Diab et al.	7,894,868	B2	2/2011	Al-Ali et al.
7,332,784	B2	2/2008	Mills et al.	7,899,507	B2	3/2011	Al-Ali et al.
7,340,287	B2	3/2008	Mason et al.	7,899,518	B2	3/2011	Trepagnier et al.
7,341,559	B2	3/2008	Schulz et al.	7,903,825	B1	3/2011	Melanson
7,343,186	B2	3/2008	Lamego et al.	7,904,132	B2	3/2011	Weber et al.
D566,282	S	4/2008	Al-Ali et al.	7,909,772	B2	3/2011	Popov et al.
7,355,512	B1	4/2008	Al-Ali	7,910,875	B2	3/2011	Al-Ali
7,356,365	B2	4/2008	Schurman	7,919,713	B2	4/2011	Al-Ali et al.
7,361,148	B2	4/2008	Narimatsu	7,937,128	B2	5/2011	Al-Ali
7,368,855	B2	5/2008	Orten	7,937,129	B2	5/2011	Mason et al.
7,371,981	B2	5/2008	Abdul-Hafiz	7,937,130	B2	5/2011	Diab et al.
7,373,193	B2	5/2008	Al-Ali et al.	7,940,937	B2	5/2011	Smith
7,373,194	B2	5/2008	Weber et al.	7,941,199	B2	5/2011	Kiani
7,376,453	B1	5/2008	Diab et al.	7,951,086	B2	5/2011	Flaherty et al.
7,377,794	B2	5/2008	Al Ali et al.	7,957,780	B2	6/2011	Lamego et al.
7,377,899	B2	5/2008	Weber et al.	7,962,188	B2	6/2011	Kiani et al.
7,383,070	B2	6/2008	Diab et al.	7,962,190	B1	6/2011	Diab et al.
7,415,297	B2	8/2008	Al-Ali et al.	7,976,472	B2	7/2011	Kiani
7,428,432	B2	9/2008	Ali et al.	7,976,480	B2	7/2011	Grajales et al.
7,438,683	B2	10/2008	Al-Ali et al.	7,988,637	B2	8/2011	Diab
7,440,787	B2	10/2008	Diab	7,988,688	B2	8/2011	Webb et al.
7,454,240	B2	11/2008	Diab et al.	7,990,382	B2	8/2011	Kiani
7,467,002	B2	12/2008	Weber et al.	7,991,165	B2	8/2011	Kassal et al.
7,469,157	B2	12/2008	Diab et al.	7,991,446	B2	8/2011	Al-Ali et al.
7,469,158	B2	12/2008	Cutler et al.	8,000,761	B2	8/2011	Al-Ali
7,471,969	B2	12/2008	Diab et al.	8,008,088	B2	8/2011	Bellott et al.
7,471,971	B2	12/2008	Diab et al.	RE42,753	E	9/2011	Kiani-Azarbayjany et al.
7,483,729	B2	1/2009	Al-Ali et al.	8,019,400	B2	9/2011	Diab et al.
7,483,730	B2	1/2009	Diab et al.	8,028,701	B2	10/2011	Al-Ali et al.
7,489,958	B2	2/2009	Diab et al.	8,029,765	B2	10/2011	Bellott et al.
7,496,391	B2	2/2009	Diab et al.	8,036,727	B2	10/2011	Schurman et al.
7,496,393	B2	2/2009	Diab et al.	8,036,728	B2	10/2011	Diab et al.
D587,657	S	3/2009	Al-Ali et al.	8,046,040	B2	10/2011	Ali et al.
7,499,741	B2	3/2009	Diab et al.	8,046,041	B2	10/2011	Diab et al.
7,499,835	B2	3/2009	Weber et al.	8,046,042	B2	10/2011	Diab et al.
7,500,950	B2	3/2009	Al-Ali et al.	8,048,040	B2	11/2011	Kiani
7,509,154	B2	3/2009	Diab et al.	8,050,728	B2	11/2011	Al-Ali et al.
7,509,494	B2	3/2009	Al-Ali	8,092,396	B2	1/2012	Bagha et al.
7,510,849	B2	3/2009	Schurman et al.	8,108,039	B2	1/2012	Saliga et al.
7,515,044	B2	4/2009	Welch et al.	RE43,169	E	2/2012	Parker
7,526,328	B2	4/2009	Diab et al.	8,118,620	B2	2/2012	Al-Ali et al.
7,530,942	B1	5/2009	Diab	8,121,673	B2	2/2012	Tran
7,530,949	B2	5/2009	Al Ali et al.	8,126,528	B2	2/2012	Diab et al.
7,530,955	B2	5/2009	Diab et al.	8,128,572	B2	3/2012	Diab et al.
7,563,110	B2	7/2009	Al-Ali et al.	8,130,105	B2	3/2012	Al-Ali et al.
7,596,398	B2	9/2009	Al-Ali et al.	8,145,287	B2	3/2012	Diab et al.
7,618,375	B2	11/2009	Flaherty	8,150,487	B2	4/2012	Diab et al.
D606,659	S	12/2009	Kiani et al.	8,175,672	B2	5/2012	Parker
7,625,117	B2	12/2009	Haslett et al.	8,180,420	B2	5/2012	Diab et al.
7,647,083	B2	1/2010	Al-Ali et al.	8,182,443	B1	5/2012	Kiani
D609,193	S	2/2010	Al-Ali et al.	8,185,180	B2	5/2012	Diab et al.
7,662,105	B2	2/2010	Hatlestad	8,190,223	B2	5/2012	Al-Ali et al.
D614,305	S	4/2010	Al-Ali et al.	8,190,227	B2	5/2012	Diab et al.
RE41,317	E	5/2010	Parker	8,203,438	B2	6/2012	Kiani et al.
7,729,733	B2	6/2010	Al-Ali et al.	8,203,704	B2	6/2012	Merritt et al.
7,734,320	B2	6/2010	Al-Ali	8,204,566	B2	6/2012	Schurman et al.
7,761,127	B2	7/2010	Al-Ali et al.	8,219,172	B2	7/2012	Schurman et al.
7,761,128	B2	7/2010	Al-Ali et al.	8,224,411	B2	7/2012	Al-Ali et al.
7,764,982	B2	7/2010	Dalke et al.	8,228,181	B2	7/2012	Al-Ali et al.
D621,516	S	8/2010	Kiani et al.	8,229,533	B2	7/2012	Diab et al.
7,783,056	B2	8/2010	Wilmink	8,233,955	B2	7/2012	Al-Ali et al.
7,791,155	B2	9/2010	Diab	8,241,223	B2	8/2012	Gavriely et al.
7,801,581	B2	9/2010	Diab	8,244,325	B2	8/2012	Al-Ali et al.
7,806,226	B2	10/2010	Drummong et al.	8,255,026	B1	8/2012	Al-Ali
7,822,452	B2	10/2010	Schurman et al.	8,255,027	B2	8/2012	Al-Ali et al.
RE41,912	E	11/2010	Parker	8,255,028	B2	8/2012	Al-Ali et al.
7,844,313	B2	11/2010	Kiani et al.	8,260,577	B2	9/2012	Weber et al.
7,844,314	B2	11/2010	Al-Ali	8,265,291	B2	9/2012	Bridger et al.
7,844,315	B2	11/2010	Al-Ali	8,265,723	B1	9/2012	McHale et al.
7,860,553	B2	12/2010	Goveri et al.	8,274,360	B2	9/2012	Sampath et al.
7,865,222	B2	1/2011	Weber et al.	8,275,140	B2	9/2012	Smith
7,873,497	B2	1/2011	Weber et al.	8,280,473	B2	10/2012	Al-Ali
				8,301,217	B2	10/2012	Al-Ali et al.
				8,306,596	B2	11/2012	Schurman et al.
				8,310,336	B2	11/2012	Muhsin et al.
				8,315,683	B2	11/2012	Al-Ali et al.

(56)

References Cited

U.S. PATENT DOCUMENTS

8,320,576 B1	11/2012	Abbruscato	8,676,286 B2	3/2014	Weber et al.	
RE43,860 E	12/2012	Parker	8,682,407 B2	3/2014	Al-Ali	
8,337,403 B2	12/2012	Al-Ali et al.	RE44,823 E	4/2014	Parker	
8,346,330 B2	1/2013	Lamego	RE44,875 E	4/2014	Kiani et al.	
8,353,842 B2	1/2013	Al-Ali et al.	8,688,189 B2	4/2014	Shennib	
8,355,766 B2	1/2013	MacNeish, III et al.	8,690,799 B2	4/2014	Telfort et al.	
8,359,080 B2	1/2013	Diab et al.	8,700,112 B2	4/2014	Kiani	
8,364,223 B2	1/2013	Al-Ali et al.	8,702,627 B2 *	4/2014	Telfort	A61B 7/003
8,364,226 B2	1/2013	Diab et al.				29/594
8,374,665 B2	2/2013	Lamego	8,706,179 B2	4/2014	Parker	
8,385,995 B2	2/2013	Al-ali et al.	8,712,494 B1	4/2014	MacNeish, III et al.	
8,385,996 B2	2/2013	Smith et al.	8,715,206 B2	5/2014	Telfort et al.	
8,388,353 B2	3/2013	Kiani et al.	8,718,735 B2	5/2014	Lamego et al.	
8,396,228 B2	3/2013	Bilan	8,718,737 B2	5/2014	Diab et al.	
8,399,822 B2	3/2013	Al-Ali	8,718,738 B2	5/2014	Blank et al.	
8,401,602 B2	3/2013	Kiani	8,720,249 B2	5/2014	Al-Ali	
8,403,865 B2	3/2013	Halperin et al.	8,721,541 B2	5/2014	Al-Ali et al.	
8,405,608 B2	3/2013	Al-Ali et al.	8,721,542 B2	5/2014	Al-Ali et al.	
8,414,499 B2	4/2013	Al-ali et al.	8,723,677 B1	5/2014	Kiana	
8,418,524 B2	4/2013	Al-Ali	8,740,792 B1	6/2014	Kiana et al.	
8,423,106 B2	4/2013	Lamego et al.	8,754,776 B2	6/2014	Poeze et al.	
8,428,967 B2	4/2013	Olsen et al.	8,755,535 B2	6/2014	Telfort et al.	
8,430,817 B1	4/2013	Al-Ali et al.	8,755,856 B2	6/2014	Diab et al.	
8,437,825 B2	5/2013	Dalvi et al.	8,755,872 B1	6/2014	Marinow	
8,449,469 B2	5/2013	Banet et al.	8,761,850 B2	6/2014	Lamego	
8,455,290 B2	6/2013	Siskavich	8,764,671 B2	7/2014	Kiani	
8,457,703 B2	6/2013	Al-Ali	8,768,423 B2	7/2014	Shakespeare et al.	
8,457,707 B2	6/2013	Kiani	8,771,204 B2	7/2014	Telfort et al.	
8,463,349 B2	6/2013	Diab et al.	8,777,634 B2	7/2014	Kiani et al.	
8,466,286 B2	6/2013	Bellot et al.	8,781,543 B2	7/2014	Diab et al.	
8,471,713 B2	6/2013	Poeze et al.	8,781,544 B2	7/2014	Al-Ali et al.	
8,473,020 B2	6/2013	Kiani et al.	8,781,549 B2	7/2014	Al-Ali et al.	
8,483,787 B2	7/2013	Al-Ali et al.	8,788,003 B2	7/2014	Schurman et al.	
8,489,364 B2	7/2013	Weber et al.	8,790,268 B2 *	7/2014	Al-Ali	A61B 5/08
8,491,489 B2	7/2013	Shin et al.				600/529
8,498,684 B2	7/2013	Weber et al.	8,801,613 B2	8/2014	Al-Ali et al.	
8,504,128 B2	8/2013	Blank et al.	8,821,397 B2	9/2014	Al-Ali et al.	
8,509,867 B2	8/2013	Workman et al.	8,821,415 B2	9/2014	Al-Ali et al.	
8,515,509 B2	8/2013	Bruinsma et al.	8,830,449 B1	9/2014	Lamego et al.	
8,517,981 B2	8/2013	Zornow	8,831,700 B2	9/2014	Schurman et al.	
8,523,781 B2 *	9/2013	Al-Ali	8,840,549 B2	9/2014	Al-Ali et al.	
			8,847,740 B2	9/2014	Kiani et al.	
			8,849,365 B2	9/2014	Smith et al.	
			8,852,094 B2	10/2014	Al-Ali et al.	
			8,852,994 B2	10/2014	Wojtczuk et al.	
			8,868,147 B2	10/2014	Stippick et al.	
			8,868,150 B2	10/2014	Al-Ali et al.	
			8,870,792 B2	10/2014	Al-Ali et al.	
			8,886,271 B2	11/2014	Kiani et al.	
			8,888,539 B2	11/2014	Al-Ali et al.	
			8,888,708 B2	11/2014	Diab et al.	
			8,892,180 B2	11/2014	Weber et al.	
			8,897,847 B2	11/2014	Al-Ali	
			8,909,310 B2	12/2014	Lamego et al.	
			8,911,377 B2	12/2014	Al-Ali	
			8,912,909 B2	12/2014	Al-Ali et al.	
			8,920,317 B2	12/2014	Al-Ali et al.	
			8,921,699 B2	12/2014	Al-Ali et al.	
			8,922,382 B2	12/2014	Al-Ali et al.	
			8,929,964 B2	1/2015	Al-Ali et al.	
			8,942,777 B2	1/2015	Diab et al.	
			8,948,834 B2	2/2015	Diab et al.	
			8,948,835 B2	2/2015	Diab	
			8,961,413 B2	2/2015	Teller et al.	
			8,965,471 B2	2/2015	Lam ego	
			8,983,564 B2	3/2015	Al-Ali	
			8,989,831 B2	3/2015	Al-Ali et al.	
			8,996,085 B2	3/2015	Kiani et al.	
			8,998,809 B2	4/2015	Kiani	
			9,028,429 B2	5/2015	Telfort et al.	
			9,037,207 B2	5/2015	Al-Ali et al.	
			9,060,721 B2	6/2015	Reichgott et al.	
			9,066,666 B2	6/2015	Kiani	
			9,066,680 B1	6/2015	Al-Ali et al.	
			9,072,474 B2	7/2015	Al-Ali et al.	
			9,078,560 B2	7/2015	Schurman et al.	
			9,084,569 B2	7/2015	Weber et al.	
			9,095,316 B2	8/2015	Welch et al.	
			9,106,038 B2	8/2015	Telfort et al.	

(56)

## References Cited

## U.S. PATENT DOCUMENTS

9,107,625 B2	8/2015	Telfort et al.	9,622,693 B2	4/2017	Diab
9,107,626 B2	8/2015	Al-Ali et al.	D788,312 S	5/2017	Al-Ali et al.
9,113,831 B2	8/2015	Al-Ali	9,636,055 B2	5/2017	Al-Ali et al.
9,113,832 B2	8/2015	Al-Ali	9,636,056 B2	5/2017	Al-Ali
9,119,595 B2	9/2015	Lamego	9,649,054 B2	5/2017	Lamego et al.
9,131,881 B2	9/2015	Diab et al.	9,662,052 B2	5/2017	Al-Ali et al.
9,131,882 B2	9/2015	Al-Ali et al.	9,668,679 B2	6/2017	Schurman et al.
9,131,883 B2	9/2015	Al-Ali	9,668,680 B2	6/2017	Bruinsma et al.
9,131,917 B2	9/2015	Telfort et al.	9,668,703 B2 *	6/2017	Al-Ali ..... A61B 5/08
9,138,180 B1	9/2015	Coverston et al.	9,675,286 B2	6/2017	Diab
9,138,182 B2	9/2015	Al-Ali et al.	9,687,160 B2	6/2017	Kiani
9,138,192 B2	9/2015	Weber et al.	9,693,719 B2	7/2017	Al-Ali et al.
9,142,117 B2	9/2015	Muhsin et al.	9,693,737 B2	7/2017	Al-Ali
9,153,112 B1	10/2015	Kiani et al.	9,697,928 B2	7/2017	Al-Ali et al.
9,153,121 B2	10/2015	Kiani et al.	9,717,425 B2	8/2017	Kiani et al.
9,161,696 B2	10/2015	Al-Ali et al.	9,717,458 B2	8/2017	Lamego et al.
9,161,713 B2	10/2015	Al-Ali et al.	9,724,016 B1	8/2017	Al-Ali et al.
9,167,995 B2	10/2015	Lamego et al.	9,724,024 B2	8/2017	Al-Ali
9,176,141 B2	11/2015	Al-Ali et al.	9,724,025 B1	8/2017	Kiani et al.
9,186,102 B2	11/2015	Bruinsma et al.	9,730,640 B2	8/2017	Diab et al.
9,192,312 B2	11/2015	Al-Ali	9,743,887 B2	8/2017	Al-Ali et al.
9,192,329 B2	11/2015	Al-Ali	9,749,232 B2	8/2017	Sampath et al.
9,192,351 B1	11/2015	Telfort et al.	9,750,442 B2	9/2017	Olsen
9,195,385 B2	11/2015	Al-Ali et al.	9,750,443 B2	9/2017	Smith et al.
9,211,072 B2	12/2015	Kiani	9,750,461 B1	9/2017	Telfort
9,211,095 B1	12/2015	Al-Ali	9,775,545 B2	10/2017	Al-Ali et al.
9,218,454 B2	12/2015	Kiani et al.	9,775,546 B2	10/2017	Diab et al.
9,226,696 B2	1/2016	Kiani	9,775,570 B2	10/2017	Al-Ali
9,241,662 B2	1/2016	Al-Ali et al.	9,778,079 B1	10/2017	Al-Ali et al.
9,245,668 B1	1/2016	Vo et al.	9,782,077 B2	10/2017	Lamego et al.
9,259,185 B2	2/2016	Abdul-Hafiz et al.	9,782,110 B2	10/2017	Kiani et al.
9,267,572 B2	2/2016	Barker et al.	9,787,568 B2	10/2017	Lamego et al.
9,277,880 B2	3/2016	Poeze et al.	9,788,735 B2	10/2017	Al-Ali
9,289,167 B2	3/2016	Diab et al.	9,788,768 B2	10/2017	Al-Ali et al.
9,295,421 B2	3/2016	Kiani et al.	9,795,300 B2	10/2017	Al-Ali
9,307,928 B1	4/2016	Al-Ali et al.	9,795,310 B2	10/2017	Al-Ali
9,323,894 B2	4/2016	Kiani	9,795,358 B2	10/2017	Telfort et al.
D755,392 S	5/2016	Hwang et al.	9,795,739 B2	10/2017	Al-Ali et al.
9,326,712 B1	5/2016	Kiani	9,801,556 B2	10/2017	Kiani
9,333,316 B2	5/2016	Kiani	9,801,588 B2	10/2017	Weber et al.
9,339,220 B2	5/2016	Lamego et al.	9,808,188 B1	11/2017	Perea et al.
9,341,565 B2	5/2016	Lamego et al.	9,814,418 B2	11/2017	Weber et al.
9,351,673 B2	5/2016	Diab et al.	9,820,691 B2	11/2017	Kiani
9,351,675 B2	5/2016	Al-Ali et al.	9,833,152 B2	12/2017	Kiani et al.
9,364,181 B2	6/2016	Kiani et al.	9,833,180 B2	12/2017	Shakespeare et al.
9,368,671 B2	6/2016	Wojtczuk et al.	9,839,379 B2	12/2017	Al-Ali et al.
9,370,325 B2	6/2016	Al-Ali et al.	9,839,381 B1	12/2017	Weber et al.
9,370,326 B2	6/2016	McHale et al.	9,847,002 B2	12/2017	Kiani et al.
9,370,335 B2	6/2016	Al-Ali et al.	9,847,749 B2	12/2017	Kiani et al.
9,375,185 B2	6/2016	Ali et al.	9,848,800 B1	12/2017	Lee et al.
9,386,953 B2	7/2016	Al-Ali	9,848,806 B2	12/2017	Al-Ali et al.
9,386,961 B2	7/2016	Al-Ali et al.	9,848,807 B2	12/2017	Lamego
9,392,945 B2	7/2016	Al-Ali et al.	9,861,298 B2	1/2018	Eckerbom et al.
9,397,448 B2	7/2016	Al-Ali et al.	9,861,304 B2	1/2018	Al-Ali et al.
9,408,542 B1	8/2016	Kinast et al.	9,861,305 B1	1/2018	Weber et al.
9,436,645 B2	9/2016	Al-Ali et al.	9,867,578 B2	1/2018	Al-Ali et al.
9,445,759 B1	9/2016	Lamego et al.	9,955,937 B2	5/2018	Telfort et al.
9,466,919 B2	10/2016	Kiani et al.	2003/0135087 A1	7/2003	Hickle
9,474,474 B2	10/2016	Lamego et al.	2003/0149349 A1	8/2003	Jensen
9,480,422 B2	11/2016	Al-Ali	2003/0196660 A1	10/2003	Haveri
9,480,435 B2	11/2016	Olsen	2004/0133087 A1	7/2004	Ali
9,492,110 B2	11/2016	Al-Ali et al.	2004/0215094 A1	10/2004	Baumer et al.
9,510,779 B2	12/2016	Poeze et al.	2004/0228494 A1	11/2004	Smith
9,517,024 B2	12/2016	Kiani et al.	2005/0033128 A1	2/2005	Ali
9,532,722 B2	1/2017	Lamego et al.	2005/0065417 A1	3/2005	Ali
9,538,949 B2	1/2017	Al-Ali et al.	2006/0047215 A1	3/2006	Newman et al.
9,538,980 B2	1/2017	Telfort et al.	2006/0059324 A1	3/2006	Simske et al.
9,549,696 B2	1/2017	Lamego et al.	2006/0094943 A1	5/2006	Van Slyke
9,554,737 B2	1/2017	Schurman et al.	2006/0161054 A1	7/2006	Reuss et al.
9,560,996 B2	2/2017	Kiani	2006/0184052 A1 *	8/2006	Iwasawa ..... A61B 5/022 600/485
9,560,998 B2	2/2017	Al-Ali et al.	2006/0190051 A1	8/2006	Gerber et al.
9,566,019 B2	2/2017	Al-Ali et al.	2006/0198533 A1	9/2006	Wang
9,579,039 B2	2/2017	Jansen et al.	2006/0264767 A1	11/2006	Shennib
9,591,975 B2	3/2017	Dalvi et al.	2007/0016030 A1	1/2007	Stringer
9,622,692 B2	4/2017	Lamego et al.	2007/0049837 A1	3/2007	Shertukde et al.
			2007/0056582 A1 *	3/2007	Wood ..... A61B 5/0059 128/200.24
			2007/0058818 A1	3/2007	Yoshimine

(56)

## References Cited

## U.S. PATENT DOCUMENTS

2007/0106179	A1	5/2007	Bagha et al.		2012/0209084	A1	8/2012	Olsen et al.
2007/0147639	A1	6/2007	Richardson et al.		2012/0227739	A1	9/2012	Kiani
2007/0165872	A1	7/2007	Bridger et al.		2012/0230523	A1	9/2012	Ehrlund
2007/0167855	A1*	7/2007	Shin .....	A61B 5/0878 600/533	2012/0232427	A1	9/2012	Bakema et al.
2007/0173730	A1	7/2007	Bikko		2012/0265039	A1	10/2012	Kiani
2007/0208262	A1	9/2007	Kovacs		2012/0283524	A1	11/2012	Kiani et al.
2007/0255153	A1	11/2007	Kumar et al.		2012/0286955	A1	11/2012	Welch et al.
2007/0282174	A1	12/2007	Sabatino		2012/0296178	A1	11/2012	Lamego et al.
2007/0282478	A1	12/2007	Al-Ali et al.		2012/0302920	A1	11/2012	Bridger et al.
2008/0039735	A1	2/2008	Hickerson		2012/0319816	A1	12/2012	Al-Ali
2008/0076972	A1	3/2008	Dorogusker et al.		2012/0330112	A1	12/2012	Lamego et al.
2008/0077026	A1	3/2008	Banet et al.		2013/0023775	A1	1/2013	Lamego et al.
2008/0077435	A1	3/2008	Muradia		2013/0338461	A1	1/2013	Lamego et al.
2008/0093157	A1	4/2008	Drummond et al.		2013/0041591	A1	2/2013	Lamego
2008/0097249	A1	4/2008	Pool et al.		2013/0045685	A1	2/2013	Kiani
2008/0139953	A1	6/2008	Baker et al.		2013/0046204	A1	2/2013	Lamego et al.
2008/0143496	A1	6/2008	Linjama		2013/0060108	A1	3/2013	Schurman et al.
2008/0188733	A1	8/2008	Al-Ali et al.		2013/0060147	A1	3/2013	Welch et al.
2008/0188760	A1	8/2008	Al-Ali		2013/0079610	A1	3/2013	Al-Ali
2008/0219464	A1	9/2008	Smith		2013/0096405	A1	4/2013	Garfio
2008/0251313	A1	10/2008	Knight et al.		2013/0096936	A1	4/2013	Sampath et al.
2008/0281219	A1	11/2008	Glickman et al.		2013/0109935	A1	5/2013	Al-Ali et al.
2009/0076363	A1	3/2009	Bly et al.		2013/0162433	A1	6/2013	Muhsin et al.
2009/0093687	A1	4/2009	Telfort et al.		2013/0178749	A1	7/2013	Lamego
2009/0170664	A1*	7/2009	Shirasaki .....	A61B 5/0816 482/13	2013/0190581	A1	7/2013	Al-Ali et al.
2009/0247924	A1	10/2009	Lamego et al.		2013/0197328	A1	8/2013	Diab et al.
2009/0247984	A1	10/2009	Lamego et al.		2013/0211214	A1	8/2013	Olsen
2009/0275813	A1	11/2009	Davis		2013/0243021	A1	9/2013	Siskavich
2009/0275844	A1	11/2009	Al-Ali		2013/0253334	A1	9/2013	Al-Ali et al.
2009/0299157	A1	12/2009	Telfort et al.		2013/0262730	A1	10/2013	Al-Ali et al.
2009/0299742	A1	12/2009	Toman et al.		2013/0267804	A1	10/2013	Al-Ali
2009/0316925	A1	12/2009	Eisenfeld et al.		2013/0274571	A1	10/2013	Diab et al.
2010/0004518	A1	1/2010	Vo et al.		2013/0274572	A1	10/2013	Al-Ali et al.
2010/0030040	A1	2/2010	Poeze et al.		2013/0296672	A1	11/2013	O'Neil et al.
2010/0069725	A1	3/2010	Al-Ali		2013/0296713	A1	11/2013	Al-Ali et al.
2010/0090901	A1	4/2010	Smith et al.		2013/0317327	A1	11/2013	Al-Ali et al.
2010/0094096	A1	4/2010	Petruzzelli et al.		2013/0317370	A1	11/2013	Dalvi et al.
2010/0204996	A1	8/2010	Zeng et al.		2013/0324808	A1	12/2013	Al-Ali et al.
2010/0261979	A1	10/2010	Kiani		2013/0324817	A1	12/2013	Diab
2010/0274099	A1*	10/2010	Telfort .....	A61B 5/6843 600/300	2013/0331660	A1	12/2013	Al-Ali et al.
2010/0305416	A1	12/2010	Bédard et al.		2013/0331670	A1	12/2013	Kiani
2010/0317936	A1	12/2010	Al-Ali et al.		2014/0012100	A1	1/2014	Al-Ali et al.
2011/0001605	A1	1/2011	Kiani et al.		2014/0025306	A1	1/2014	Weber et al.
2011/0028802	A1	2/2011	Addison		2014/0034353	A1	2/2014	Al-Ali et al.
2011/0034831	A1	2/2011	Christensen et al.		2014/0051952	A1	2/2014	Reichgott et al.
2011/0082711	A1	4/2011	Poeze et al.		2014/0051953	A1	2/2014	Lamego et al.
2011/0087083	A1	4/2011	Poeze et al.		2014/0051954	A1	2/2014	Al-Ali et al.
2011/0105854	A1	5/2011	Kiani et al.		2014/0058230	A1	2/2014	Abdul-Hafiz et al.
2011/0125060	A1	5/2011	Telfort et al.		2014/0066783	A1	3/2014	Kiani et al.
2011/0172561	A1	7/2011	Kiani et al.		2014/0077956	A1	3/2014	Sampath et al.
2011/0172967	A1	7/2011	Al-Ali et al.		2014/0081097	A1	3/2014	Al-Ali et al.
2011/0196211	A1	8/2011	Al-Ali		2014/0081100	A1	3/2014	Muhsin et al.
2011/0208015	A1	8/2011	Welch et al.		2014/0094667	A1	4/2014	Schurman et al.
2011/0209915	A1	9/2011	Fechter et al.		2014/0100434	A1	4/2014	Diab et al.
2011/0213212	A1	9/2011	Al-Ali		2014/0114199	A1	4/2014	Lamego et al.
2011/0213271	A1*	9/2011	Telfort .....	A61B 7/003 600/586	2014/0120564	A1	5/2014	Workman et al.
2011/0213273	A1	9/2011	Telfort et al.		2014/0121482	A1	5/2014	Merritt et al.
2011/0230733	A1	9/2011	Al-Ali		2014/0121483	A1	5/2014	Kiani
2011/0237911	A1	9/2011	Lamego et al.		2014/0125495	A1	5/2014	Al-Ali
2011/0237969	A1	9/2011	Eckerbom et al.		2014/0127137	A1	5/2014	Bellott et al.
2011/0288383	A1	11/2011	Diab		2014/0128696	A1	5/2014	Al-Ali
2011/0288431	A1	11/2011	Alshaer et al.		2014/0128699	A1	5/2014	Al-Ali et al.
2011/0301444	A1	12/2011	Al-Ali		2014/0129702	A1	5/2014	Lamego et al.
2012/0041316	A1	2/2012	Al-Ali et al.		2014/0135588	A1	5/2014	Al-Ali et al.
2012/0046557	A1	2/2012	Kiani		2014/0142399	A1	5/2014	Al-Ali et al.
2012/0059267	A1	3/2012	Lamego et al.		2014/0142401	A1	5/2014	Al-Ali et al.
2012/0088984	A1	4/2012	Al-Ali et al.		2014/0142402	A1	5/2014	Al-Ali et al.
2012/0116175	A1	5/2012	Al-Ali et al.		2014/0163344	A1	6/2014	Al-Ali
2012/0165629	A1	6/2012	Merritt et al.		2014/0163402	A1	6/2014	Lamego et al.
2012/0179006	A1	7/2012	Jansen et al.		2014/0166076	A1	6/2014	Kiani et al.
2012/0209082	A1	8/2012	Al-Ali		2014/0171763	A1	6/2014	Diab
					2014/0180038	A1	6/2014	Kiani
					2014/0180154	A1	6/2014	Sierra et al.
					2014/0180160	A1	6/2014	Brown et al.
					2014/0187973	A1	7/2014	Brown et al.
					2014/0194709	A1	7/2014	Al-Ali et al.
					2014/0194711	A1	7/2014	Al-Ali
					2014/0194766	A1	7/2014	Al-Ali et al.
					2014/0200420	A1	7/2014	Al-Ali

(56)

References Cited

U.S. PATENT DOCUMENTS

2014/0200422 A1	7/2014	Weber et al.	2016/0029932 A1	2/2016	Al-Ali
2014/0206963 A1	7/2014	Al-Ali	2016/0029933 A1	2/2016	Al-Ali et al.
2014/0213864 A1	7/2014	Abdul-Hafiz et al.	2016/0045118 A1	2/2016	Kiani
2014/0243627 A1	8/2014	Diab et al.	2016/0051205 A1	2/2016	Al-Ali et al.
2014/0266790 A1	9/2014	Al-Ali et al.	2016/0058338 A1	3/2016	Schurman et al.
2014/0275808 A1	9/2014	Poeze et al.	2016/0058347 A1	3/2016	Reichgott et al.
2014/0275835 A1	9/2014	Lamego et al.	2016/0066823 A1	3/2016	Kind et al.
2014/0275871 A1	9/2014	Lamego et al.	2016/0066824 A1	3/2016	Al-Ali et al.
2014/0275872 A1	9/2014	Merritt et al.	2016/0066879 A1	3/2016	Telfort et al.
2014/0275881 A1	9/2014	Lamego et al.	2016/0072429 A1	3/2016	Kiani et al.
2014/0276115 A1	9/2014	Dalvi et al.	2016/0073967 A1	3/2016	Lamego et al.
2014/0288400 A1	9/2014	Diab et al.	2016/0081552 A1	3/2016	Wojtczuk et al.
2014/0309506 A1	10/2014	Lamego et al.	2016/0095543 A1	4/2016	Telfort et al.
2014/0316217 A1	10/2014	Purdon et al.	2016/0095548 A1	4/2016	Al-Ali et al.
2014/0316218 A1	10/2014	Purdon et al.	2016/0103598 A1	4/2016	Al-Ali et al.
2014/0316228 A1	10/2014	Blank et al.	2016/0113527 A1	4/2016	Al-Ali et al.
2014/0323825 A1	10/2014	Al-Ali et al.	2016/0143548 A1	5/2016	Al-Ali
2014/0323897 A1	10/2014	Brown et al.	2016/0166182 A1	6/2016	Al-Ali et al.
2014/0323898 A1	10/2014	Purdon et al.	2016/0166183 A1	6/2016	Poeze et al.
2014/0330092 A1	11/2014	Al-Ali et al.	2016/0166188 A1	6/2016	Bruinsma et al.
2014/0330098 A1	11/2014	Merritt et al.	2016/0166210 A1	6/2016	Al-Ali
2014/0330099 A1	11/2014	Al-Ali et al.	2016/0192869 A1	7/2016	Kiani et al.
2014/0333440 A1	11/2014	Kiana	2016/0196388 A1	7/2016	Lam ego
2014/0336481 A1	11/2014	Shakespeare et al.	2016/0197436 A1	7/2016	Barker et al.
2014/0343436 A1	11/2014	Kiani	2016/0213281 A1	7/2016	Eckerbom et al.
2014/0357966 A1	12/2014	Al-Ali et al.	2016/0228043 A1	8/2016	O'Neil et al.
2014/0371548 A1	12/2014	Al-Ali et al.	2016/0233632 A1	8/2016	Scruggs et al.
2014/0378784 A1	12/2014	Kiani et al.	2016/0234944 A1	8/2016	Schmidt et al.
2015/0005600 A1	1/2015	Blank et al.	2016/0270735 A1	9/2016	Diab et al.
2015/0011907 A1	1/2015	Purdon et al.	2016/0283665 A1	9/2016	Sampath et al.
2015/0012231 A1	1/2015	Poeze et al.	2016/0287090 A1	10/2016	Al-Ali et al.
2015/0018650 A1	1/2015	Al-Ali et al.	2016/0287786 A1	10/2016	Kiani
2015/0025406 A1 *	1/2015	Al-Ali ..... A61B 5/08 600/529	2016/0296169 A1	10/2016	McHale et al.
2015/0032029 A1	1/2015	Al-Ali et al.	2016/0310052 A1	10/2016	Al-Ali et al.
2015/0038859 A1	2/2015	Dalvi	2016/0314260 A1	10/2016	Kiani
2015/0045637 A1	2/2015	Dalvi	2016/0324486 A1	11/2016	Al-Ali et al.
2015/0051462 A1	2/2015	Olsen	2016/0324488 A1	11/2016	Olsen
2015/0080754 A1	3/2015	Purdon et al.	2016/0327984 A1	11/2016	Al-Ali et al.
2015/0087936 A1	3/2015	Al-Ali et al.	2016/0328528 A1	11/2016	Al-Ali et al.
2015/0094546 A1	4/2015	Al-Ali	2016/0331332 A1	11/2016	Al-Ali
2015/0097701 A1	4/2015	Al-Ali et al.	2016/0367173 A1	12/2016	Dalvi et al.
2015/0099950 A1	4/2015	Al-Ali et al.	2017/0007134 A1	1/2017	Fletcher et al.
2015/0099951 A1	4/2015	Al-Ali et al.	2017/0007198 A1	1/2017	Al-Ali et al.
2015/0099955 A1	4/2015	Al-Ali et al.	2017/0014083 A1	1/2017	Diab et al.
2015/0099998 A1	4/2015	Christensen et al.	2017/0014084 A1	1/2017	Al-Ali et al.
2015/0101844 A1	4/2015	Al-Ali et al.	2017/0027456 A1	2/2017	Kinast et al.
2015/0106121 A1	4/2015	Muhsin et al.	2017/0042488 A1	2/2017	Muhsin
2015/0112151 A1	4/2015	Muhsin et al.	2017/0055847 A1	3/2017	Kiani et al.
2015/0116076 A1	4/2015	Al-Ali et al.	2017/0055851 A1	3/2017	Al-Ali
2015/0126830 A1	5/2015	Schurman et al.	2017/0055882 A1	3/2017	Al-Ali et al.
2015/0133755 A1	5/2015	Smith et al.	2017/0055887 A1	3/2017	Al-Ali
2015/0140863 A1	5/2015	Al-Ali et al.	2017/0055896 A1	3/2017	Al-Ali et al.
2015/0141781 A1	5/2015	Weber et al.	2017/0079594 A1	3/2017	Telfort et al.
2015/0165312 A1	6/2015	Kiani	2017/0086723 A1	3/2017	Al-Ali et al.
2015/0196237 A1	7/2015	Lamego	2017/0143281 A1	5/2017	Olsen
2015/0196249 A1	7/2015	Brown et al.	2017/0147774 A1	5/2017	Kiani
2015/0201874 A1	7/2015	Diab	2017/0156620 A1	6/2017	Al-Ali et al.
2015/0208966 A1	7/2015	Al-Ali	2017/0173632 A1	6/2017	Al-Ali
2015/0216459 A1	8/2015	Al-Ali et al.	2017/0187146 A1	6/2017	Kiani et al.
2015/0230755 A1	8/2015	Al-Ali et al.	2017/0188919 A1	7/2017	Al-Ali et al.
2015/0238722 A1	8/2015	Al-Ali	2017/0196464 A1	7/2017	Jansen et al.
2015/0245773 A1	9/2015	Lamego et al.	2017/0196470 A1	7/2017	Lamego et al.
2015/0245794 A1	9/2015	Al-Ali	2017/0202490 A1	7/2017	Al-Ali et al.
2015/0257689 A1	9/2015	Al-Ali et al.	2017/0224231 A1	8/2017	Al-Ali
2015/0272514 A1	10/2015	Kiani et al.	2017/0224262 A1	8/2017	Al-Ali
2015/0351697 A1	12/2015	Weber et al.	2017/0228516 A1	8/2017	Sampath et al.
2015/0351704 A1	12/2015	Kiani et al.	2017/0245790 A1	8/2017	Al-Ali et al.
2015/0359429 A1	12/2015	Al-Ali et al.	2017/0251974 A1	9/2017	Shreim et al.
2015/0366472 A1	12/2015	Kiani	2017/0251975 A1	9/2017	Shreim et al.
2015/0366507 A1	12/2015	Blank	2017/0258403 A1	9/2017	Abdul-Hafiz et al.
2015/0374298 A1	12/2015	Al-Ali et al.	2017/0311891 A1	11/2017	Kiani et al.
2015/0380875 A1	12/2015	Coverston et al.	2017/0325728 A1	11/2017	Al-Ali et al.
2016/0000362 A1	1/2016	Diab et al.	2017/0332976 A1	11/2017	Al-Ali et al.
2016/0007930 A1	1/2016	Weber et al.	2017/0340293 A1	11/2017	Al-Ali et al.
			2017/0360310 A1	12/2017	Kiani et al.
			2017/0367632 A1	12/2017	Al-Ali et al.
			2018/0125445 A1	5/2018	Telfort et al.
			2018/0153446 A1	6/2018	Kiani
			2018/0206815 A1	7/2018	Telfort

(56)

**References Cited**

## U.S. PATENT DOCUMENTS

## FOREIGN PATENT DOCUMENTS

CN	202005761	10/2011
EP	0716628	12/1998
EP	0659058	1/1999
EP	1518442	3/2005
EP	2 014 234	1/2009
EP	1207536	2/2010
EP	2488106	8/2012
EP	2488978	8/2012
FR	2 847 796	6/2004
GB	2358546	7/2001
JP	S56-031742 A	3/1961
JP	S53-094482 A	8/1978
JP	60059900	4/1985
JP	6214898	1/1987
JP	01-309872	12/1989
JP	H04-317637 A	11/1992
JP	10-155755	6/1998
JP	2001-50713	2/2001
JP	2003-329719	11/2003
JP	2005-531230 A	10/2005
JP	2012-513872	6/2012
JP	2013-508029	3/2013
JP	2013-508030	3/2013
NO	20040819	2/2004
WO	WO 1994/005207	3/1994
WO	WO 1994/013207	6/1994
WO	WO 1995/029632	11/1995
WO	WO 1999/053277	10/1999
WO	WO 2000/010462	3/2000
WO	WO 2001/034033	5/2001
WO	WO 2001/097691	12/2001
WO	WO 2001/078059	3/2002
WO	WO 2002/003042	12/2002
WO	WO 2003/058646	7/2003
WO	WO 2003/087737	10/2003
WO	WO 2004/000111	12/2003
WO	WO 2004/004411	1/2004
WO	WO 2004/078038	9/2004
WO	WO 2005/096931	10/2005
WO	WO 2005/099562	10/2005
WO	WO 2008/017246	2/2008
WO	WO 2008/148172	12/2008
WO	WO 2009/137524	11/2009

WO	WO 2010/078168	7/2010
WO	WO 2011/047213	4/2011
WO	WO 2011/047207	9/2011
WO	WO 2011/047209	3/2012

## OTHER PUBLICATIONS

US 8,845,543 B2, 09/2014, Diab et al. (withdrawn)

Analog Devices, 12-Bit Serial Input Multiplying D/A Converter, Product Data Sheet, 2000.

Eldor et al., "A device for monitoring ventilation during anesthesia; the paratracheal audible respiratory monitor", Canadian Journal of Anesthesia, 1990, vol. 9, No. 1, p. 95-98.

Sierra et al., Monitoring Respiratory Rate Based on Tracheal Sounds. First Experiences, Proceedings of the 26th Annual Int'l Conf. of the IEEE EMBS (Sep. 2004), 317-320.

International Search Report & Written Opinion, PCT Application PCT/US2010/052758, dated Feb. 10, 2011; 12 pages.

International Search Report & Written Opinion, PCT Application PCT/US2010/058981, dated Feb. 17, 2011; 11 pages.

International Search Report, PCT Application PCT/CA2003/000536, dated Dec. 11, 2003; 2 pages.

International Search Report & Written Opinion for PCT/US2010/052756, dated Feb. 6, 2012; 17 pages.

Avago Technologies, "HCNR200 and HCNR201, High-Linearity Analog Optocouplers," Data Sheet, Avago Technologies, Nov. 18, 2008.

Images showing tear down of a Measurement Specialties' stethoscope, Images taken on Sep. 7, 2007, in 38 pages.

WelchAllyn OEM Technologies, ECG ASIC, ECG 3-lead, 5-lead, 12-lead and RESP Signal Processing, ECG ASIC Part No. 000. 91163 (2001).

White, "Advanced Compression Techniques, Tips & Tricks", Part 1 and Part 2, Dec. 2000 and Jan. 2001 in 11 pages.

Oversampling by Wikipedia, the free encyclopedia, pub. Online Oct. 7, 2012 at "<https://wikipedia.org/w/index.php?title=Oversampling&oldid=516454012>", accessed Sep. 3, 2015.

Pseudorandom noise by Wikipedia, the free encyclopedia, pub. Online Jul. 25, 2012 at "[https://wikipedia.org/w/index.php?title=Pseudorandom\\_noise&oldid=504121479](https://wikipedia.org/w/index.php?title=Pseudorandom_noise&oldid=504121479)", accessed Sep. 3, 2015.

Noise generator by Wikipedia, the free encyclopedia, pub. Online May 6, 2012 at "[https://wikipedia.org/w/index.php?title=Noise\\_generator&oldid=490897729](https://wikipedia.org/w/index.php?title=Noise_generator&oldid=490897729)", accessed Sep. 3, 2015.

\* cited by examiner




FIG. 1




FIG. 2




FIG. 3





FIG. 4A

*FIG. 4B*




FIG. 5A




FIG. 5B




FIG. 6




FIG. 7A




FIG. 7B




FIG. 8A




FIG. 8B




FIG. 9




FIG. 10




FIG. 11




FIG. 12

**BIDIRECTIONAL PHYSIOLOGICAL INFORMATION DISPLAY**

RELATED APPLICATIONS

This application is a continuation of U.S. patent application Ser. No. 14/444,705, filed Jul. 28, 2014, and entitled "Bidirectional Physiological Information Display," which is a continuation of U.S. patent application Ser. No. 12/904,823, now U.S. Pat. No. 8,790,268, filed Oct. 14, 2010, and entitled "Bidirectional Physiological Information Display," which claims priority from U.S. Provisional Patent Application No. 61/252,083 filed Oct. 15, 2009, and entitled "Displaying Physiological Information," U.S. Provisional Patent Application No. 61/288,843 filed Dec. 21, 2009, and entitled "Acoustic Respiratory Monitor," U.S. Provisional Patent Application No. 61/290,436 filed Dec. 28, 2009, and entitled "Acoustic Respiratory Monitor," and from U.S. Provisional Patent Application No. 61/331,087, filed May 4, 2010, entitled "Acoustic Respiration Display," the disclosures of which are hereby incorporated by reference in their entirety.

This application also relates to the following U.S. patent applications, the disclosures of which are incorporated in their entirety by reference herein:

App. No.	Filing Date	Title
60/893,853	Mar. 8, 2007	MULTI-PARAMETER PHYSIOLOGICAL MONITOR
60/893,850	Mar. 8, 2007	BACKWARD COMPATIBLE PHYSIOLOGICAL SENSOR WITH INFORMATION ELEMENT
60/893,858	Mar. 8, 2007	MULTI-PARAMETER SENSOR FOR PHYSIOLOGICAL MONITORING
60/893,856	Mar. 8, 2007	PHYSIOLOGICAL MONITOR WITH FAST GAIN ADJUST DATA ACQUISITION
12/044,883	Mar. 8, 2008	SYSTEMS AND METHODS FOR DETERMINING A PHYSIOLOGICAL CONDITION USING AN ACOUSTIC MONITOR
61/141,584	Dec. 30, 2008	ACOUSTIC SENSOR ASSEMBLY
61/252,076	Oct. 15, 2009	ACOUSTIC SENSOR ASSEMBLY
12/643,939	Dec. 21, 2009	ACOUSTIC SENSOR ASSEMBLY
14/259,527	Apr. 23, 2014	ACOUSTIC SENSOR ASSEMBLY
14/671,367	Mar. 27, 2015	ACOUSTIC SENSOR ASSEMBLY
14/820,376	Aug. 6, 2015	ACOUSTIC SENSOR ASSEMBLY
61/313,645	Mar. 12, 2010	ACOUSTIC RESPIRATORY MONITORING SENSOR HAVING MULTIPLE SENSING ELEMENTS
12/904,931	Oct. 14, 2010	ACOUSTIC RESPIRATORY MONITORING SENSOR HAVING MULTIPLE SENSING ELEMENTS
14/247,120	Apr. 7, 2014	ACOUSTIC RESPIRATORY MONITORING SENSOR HAVING MULTIPLE SENSING ELEMENTS
15/366,899	Dec. 1, 2016	ACOUSTIC RESPIRATORY MONITORING SENSOR HAVING MULTIPLE SENSING ELEMENTS
12/904,890	Oct. 14, 2010	ACOUSTIC RESPIRATORY MONITORING SENSOR HAVING MULTIPLE SENSING ELEMENTS
12/904,938	Oct. 14, 2010	ACOUSTIC RESPIRATORY MONITORING SENSOR HAVING MULTIPLE SENSING ELEMENTS
12/904,907	Oct. 14, 2010	ACOUSTIC PATIENT SENSOR
61/252,099	Oct. 14, 2009	ACOUSTIC RESPIRATORY MONITORING SYSTEMS AND METHODS
12/904,789	Oct. 14, 2010	ACOUSTIC RESPIRATORY MONITORING SYSTEMS AND METHODS

-continued

App. No.	Filing Date	Title
5 61/252,062	Oct. 15, 2009	PULSE OXIMETRY SYSTEM WITH LOW NOISE CABLE HUB
61/265,730	Dec. 1, 2009	PULSE OXIMETRY SYSTEM WITH ACOUSTIC SENSOR
12/904,775	Oct. 14, 2010	PULSE OXIMETRY SYSTEM WITH LOW NOISE CABLE HUB
10 12/905,036	Oct. 14, 2010	PHYSIOLOGICAL ACOUSTIC MONITORING SYSTEM
61/391,098	Oct. 8, 2010	ACOUSTIC MONITOR

Many of the embodiments described herein are compatible with embodiments described in the above related applications. Moreover, some or all of the features described herein can be used or otherwise combined with many of the features described in the applications listed above.

BACKGROUND

Monitoring of respiratory activity in a patient is desirable in clinical situations since death or brain damage can occur within minutes of respiratory failure. As respiratory failure can be difficult to predict, continuous monitoring of respiratory activity is particularly beneficial in high-risk situations. Appropriate monitoring equipment saves lives. Moreover, respiratory monitoring equipment can also be useful for non-critical care, including exercise testing and different types of cardiac investigations.

A patient's respiratory activity can be monitored by an acoustic respiratory monitor. An acoustic respiratory monitor can include one or more acoustic sensors that can be positioned on a patient's body to obtain acoustic respiratory information from a patient for analysis. In some cases, the acoustic sensors may be positioned to detect tracheal sounds, which can be heard at the suprasternal notch or at the lateral neck near the pharynx or at another location on the patient.

SUMMARY

In certain embodiments, a patient monitor for displaying a physiological signal includes a visual element having a middle portion indicative of a transition in the physiological signal between physiological states. The visual element can also include first and second extremity portions, the first extremity portion extending from the middle portion in a first direction and the second extremity portion extending from the middle portion in a second direction. The visual element can also include an actionable value indicator to specify a value about the middle portion and the first and second extremity portions. The patient monitor can also include a processor configured to cause the value indicator to actuate in both the first and second directions according to changes in the physiological signal.

In certain embodiments, a method of displaying physiological information, implemented by a processor, includes providing a value of a physiological parameter to a display of a patient monitor, where the physiological parameter value reflects physiological information obtained from a physiological sensor coupled to a patient. The method can further include calculating a freshness of the physiological parameter value and adjusting an output associated with the parameter value based at least in part on the calculated freshness.

In certain embodiments, a method of displaying physiological information, implemented by a processor, includes outputting a value of a physiological parameter to a display of a patient monitor, where the physiological parameter value reflects physiological information obtained from a physiological sensor coupled to a patient. The method can further include outputting a signal quality indicator reflecting a quality of the physiological information obtained from the physiological sensor, determining whether the value of the physiological parameter is valid, and adjusting the signal quality indicator responsive to said determination.

In certain embodiments, a method of displaying physiological information, implemented by a processor, can include providing a value of a physiological parameter to a display of a patient monitor, where the physiological parameter value reflects physiological information obtained from a physiological sensor coupled to a patient. The method can further include determining whether the value of the physiological parameter is valid, freezing an output associated with the physiological parameter value, calculating a freshness of the physiological parameter value, in response to said freezing, and adjusting the output associated with the parameter value based at least in part on the calculated freshness.

Further, in some embodiments, a method is provided for displaying physiological information on a physiological monitor that can be coupled to a patient sensor that can detect a physiological signal. The method, implemented by a processor, can include outputting a value indicator to a display of the patient monitor, expanding the value indicator in two directions simultaneously in response to increasing values in a parameter measured from the physiological signal, and contracting the value indicator opposite the two directions simultaneously in response to falling values of the measured parameter.

In certain embodiments, a method of displaying physiological information on a physiological monitor, implemented by a processor, can include receiving a physiological signal from a sensor coupled to a patient, where the physiological signal reflects a physiological parameter of the patient. The method can further include activating a visual indicator of a visual element to cause the visual indicator to illuminate from a central region outwards toward both a first end region and a second end region of the visual element and then inwards from the first and second end regions toward the central region, responsive to changes in the physiological parameter.

A physiological monitor can include, in certain embodiments, a processor that can receive physiological information from one or more sensors coupled with a patient and a display having a visual element for representing values of a physiological parameter responsive to the physiological information. The visual element can include a middle portion representing an initial position, first and second extremity portions, the first extremity portion extending from the middle portion in a first direction, and the second extremity portion extending from the middle portion in a second direction, and a value indicator that can illuminate starting from the initial position and expanding both to the first and second extremity portions, followed by contracting at least partway toward the middle portion, responsive to changes in the physiological parameter.

For purposes of summarizing the disclosure, certain aspects, advantages and novel features of the inventions have been described herein. It is to be understood that not necessarily all such advantages can be achieved in accordance with any particular embodiment of the inventions

disclosed herein. Thus, the inventions disclosed herein can be embodied or carried out in a manner that achieves or optimizes one advantage or group of advantages as taught herein without necessarily achieving other advantages as can be taught or suggested herein.

#### BRIEF DESCRIPTION OF THE DRAWINGS

Throughout the drawings, reference numbers can be re-used to indicate correspondence between referenced elements. The drawings are provided to illustrate embodiments of the inventions described herein and not to limit the scope thereof.

FIG. 1 is a depiction of an embodiment of a patient monitoring system for acquiring, processing, and displaying physiological information (e.g., respiratory-related information);

FIG. 2 is a schematic representation of an embodiment of a visual element for use with the system of FIG. 1 to display a physiological signal (e.g., a respiratory signal);

FIG. 3 is a schematic representation of an embodiment of a visual element for use with the system of FIG. 1 to display a physiological signal (e.g., a respiratory signal);

FIG. 4A is an embodiment of a series of depictions of the visual element of FIG. 2 shown at different times as a physiological signal (e.g., a respiratory signal) fluctuates;

FIG. 4B is an embodiment of a flowchart that further describes the illustrations in FIG. 4A;

FIG. 5A is an embodiment of a series of depictions of the visual element of FIG. 2 shown at different times as a physiological signal (e.g., a respiratory signal) fluctuates;

FIG. 5B is an embodiment of a flowchart that further describes the illustrations in FIG. 5A;

FIG. 6 is an embodiment of a schematic representation of a visual element capable of simultaneously displaying a plurality of values associated with a physiological signal (e.g., a respiratory signal) at a plurality of times;

FIG. 7A is an embodiment of a schematic representation of a visual element, which includes peak indicators, for displaying a physiological signal (e.g., a respiratory signal);

FIG. 7B is an embodiment of a flowchart that further describes the illustrations in FIG. 7A;

FIG. 8A is an embodiment of a schematic representation of a visual element, which includes goal indicators, for displaying a physiological signal (e.g., a respiratory signal)

FIG. 8B is an embodiment of a flowchart that further describes the illustrations in FIG. 8A; and

FIG. 9 is an embodiment of a schematic representation of a visual element, which includes a plurality of types of indicators, for displaying a physiological signal (e.g., a respiratory signal).

FIG. 10 is an embodiment of a top perspective view illustrating an embodiment of a sensor assembly and cable.

FIG. 11 illustrates an embodiment of a respiratory analysis system.

FIG. 12 illustrates an embodiment of a physiological monitor having a respiration display.

#### DETAILED DESCRIPTION

Systems and methods of visually communicating information about physiological signals (e.g., respiratory signals) to an observer are described herein. In one embodiment, a physiological monitoring system includes one or more sensors to detect a physiological signal from a patient. For example, the physiological signal can be an acoustic representation of a respiratory signal detected by an acoustic

sensor in the vicinity of a patient. The physiological monitoring system can also include a display for communicating information about the physiological signal to an observer, as well as a processor for processing the physiological signal and controlling the display.

In some embodiments, the display includes a visual element with a value indicator for visually communicating a value associated with a physiological signal to an observer. The value indicator can have an initial position and can expand or contract in a first portion of the visual element during a first physiological state. The first physiological state can, for example, correspond to patient inspiration (or inhalation). The value indicator can expand or contract in a second portion of the visual element during a second physiological state, which can correspond, for example, to patient expiration (or exhalation). In other embodiments, the value indicator expands from a reference position in at least two directions simultaneously, the reference position being representative of a transition between first and second physiological states, such as patient inspiration and expiration.

#### Multidirectional Display

FIG. 1 illustrates a respiratory monitoring system **105** for monitoring the respiratory activity of a patient **100**. The respiratory monitoring system **105** includes a respiratory monitor **110** communicatively coupled to a sensor **120**. The sensor **120** is positioned on the patient's body to detect respiratory sounds. In one embodiment, the sensor **120** includes a piezoelectric crystal transducer to transform sound vibrations in the patient's body into electrical signals. Other types of sensors can also be used. The resulting electrical respiratory signal can be transferred to the respiratory monitor **110** via electrical leads **130**, by wireless transmission, or any other appropriate method. Various sensors and monitors adaptable to be used with any of the embodiments described herein, have been described in the following applications and issued patents: U.S. Provisional No. 60/893,853, filed Mar. 8, 2007; U.S. Provisional No. 60/893,850, filed Mar. 8, 2007; U.S. Provisional No. 60/893,858, filed Mar. 8, 2007; U.S. Provisional No. 60/893,856, filed Mar. 8, 2007; U.S. application Ser. No. 11/547,570, filed Oct. 6, 2006; U.S. application Ser. No. 12/643,939, filed Dec. 21, 2009, and U.S. Pat. No. 6,661,161 (see also FIG. 10). Each of these references is hereby incorporated by reference in its entirety.

The respiratory monitor **110** can include circuitry to convert the respiratory signal into a digital format, as well as a processor (not shown) to analyze the respiratory signal. For example, the respiratory signal can be processed or analyzed with a Fourier transform or other mathematical transform to determine or analyze the frequency content of the signal. The signal can also be time-averaged, filtered, amplified, or otherwise conditioned or analyzed using the processor. For example, the processor can be configured to determine a patient's inspiratory time, expiratory time, inspiratory to expiratory ratio, inspiratory flow, expiratory flow, tidal volume, minute volume, apnea duration, breath sounds—including rales, rhonchi, or stridor, changes in breath sounds, etc. Regardless of whether the acquired signal is in analog or digital form, has been conditioned, transformed, or otherwise analyzed or altered, it can generally be referred to as a respiratory signal or acoustic signal throughout this disclosure.

Once the respiratory signal has been acquired by the sensor **120** and transferred to the respiratory monitor **110**, the signal, or aspects of it, can be communicated to an observer by a visual element **150** of the respiratory monitor display **140**. FIGS. 2-9 illustrate various embodiments of the

visual element **150**. While certain embodiments can be described primarily in the context of displaying respiratory signals, the same principles can be applied to display other types of physiological signals as well, such as heart rate, blood pressure, blood oxygen saturation, etc.

FIG. 2 illustrates a visual element **250**, in this case a bar graph, which can be displayed on a patient monitor to communicate to a user certain aspects of a physiological signal. In some embodiments, the visual element **250** is a color or monochrome segmented LED, LCD, and/or a bit-mapped type display. Other types of displays are also possible and can be used equally well. The bar graph **250** can include a plurality of segments **258**, or any other type of sub-division. In certain embodiments, each segment **258** has an inactive state, such as a dark state, and an active state, such as one or more lit states of varying brightness, or vice versa. In certain embodiments, the lit state includes one or more colors. The segments **258** can be transitioned between dark and lit states, or between colors, in order to convey information about a physiological signal to a user.

One or more segments **258** can make up a middle portion **252** of the bar graph **250**. Other groupings of segments **258** can make up a first extremity portion **254** (e.g., an upper extremity portion) and a second extremity portion **256** (e.g., a lower extremity portion) of the bar graph **250**. In some embodiments, the upper **254** and lower **256** extremity portions of the bar graph **250** are each indicative of relatively larger magnitudes of values of an acquired physiological signal, or some characteristic derived from the acquired physiological signal, than is the middle portion **252**. In other embodiments, however, one of the extremity portions may represent lesser magnitudes than the other, while the middle portion can represent magnitudes between the greater and lesser magnitudes represented by the extremity portions.

In some embodiments, the bar graph **250** is calibrated. For example, the bar graph **250** can be calibrated in units of energy in a physiological signal or, in the case of respiratory signals, in units of respiratory volume. Other calibration units are also possible. In some embodiments, a calibration scale is explicitly indicated on or near the bar graph **250** to communicate quantitative information to an observer about the strength of a physiological signal. In certain embodiments, the calibration scale of the bar graph **250** is reconfigurable, whether manually or automatically, according to the ranges of values present in the physiological signal. For example, in the case of a respiratory signal of a patient with relatively shallow breathing, the dynamic range of the calibration scale can be decreased so that the signal extends over a greater portion of the bar graph **250**. In cases where a patient is breathing very deeply, the dynamic range of the calibration scale can be increased to avoid clipping of the visual depiction of the respiratory signal.

The bar graph **260** can also include a value indicator **260** which actuates in time, e.g. by transitioning bar graph segments **258** between dark and lit states, as the physiological signal changes. In some embodiments, the value indicator **260** is a grouping of one or more segments **258**, the number of which changes as the value indicator **260** actuates, of the visual element **250**. The value indicator **260** can be indicative of any characteristic of an acquired physiological signal and can actuate anywhere along the bar graph **250**. For example, the value indicator **260** can represent the amplitude of a physiological waveform at a point in time, the amplitude of a selected frequency range of the physiological signal over a specified time period, or the intensity of the physiological signal at a point in time.

Other characteristics of a physiological signal can also be represented by the value indicator **260**. For example, in the case of a respiratory signal, the value indicator **260** can represent an indication of the acoustic volume of breathing sounds picked up by an acoustic sensor **120**. In some embodiments, an indication of the acoustic volume of a patient's respiratory sounds is related to the amplitude of a relatively low frequency envelope of a sound waveform detected by the sensor **120**. The value indicator **260** can also represent the respiratory rate of a patient, the depth of breathing, or any other type of information related to a respiratory signal, including a quality of a respiratory signal (see FIG. **11**).

It should be understood that while FIG. **2** illustrates one embodiment of a value indicator, many different types of value indicators can be used in various embodiments. The value indicator **260** illustrated in FIG. **2** is one that is well-suited to embodiments where the visual element **150** includes a bar graph. However, other types of value indicators may be better-suited to other types of visual elements **150**. The term "value indicator," in addition to having its ordinary meaning, is intended to refer to any type of visual indicator capable of graphically communicating to a user a value associated with a physiological signal, including amplitude, frequency, etc. related to a physiological signal.

In certain embodiments, the value indicator **260** expands in length to indicate increases in the value or magnitude of a selected characteristic of the physiological signal. Conversely, the value indicator may contract in length to indicate decreases in the value or magnitude of the signal. While the value indicator **260** is shown in FIG. **1** as only extending from the middle portion **252** into the upper extremity portion **254** of the bar graph **250**, in other embodiments, it may extend into both extremity portions **254**, **256** simultaneously.

The value indicator **260** can change colors and/or flash as it actuates as an additional method of conveying information to a user. For example, the value indicator **260** could be displayed in red for relatively small values or magnitudes of a respiratory signal, which may correspond to shallow breathing by a patient. In other embodiments, the value indicator **260** flashes between dark and lit states to indicate shallow breathing. If the patient's breathing increases to normal levels, however, the value indicator **260** may change to green or cease flashing. Similar methods of changing colors of the value indicator **260** or causing it to flash can be used to indicate other aspects of a respiratory signal, such as if the patient's respiratory rate drops below a predetermined or user-selected threshold.

In certain embodiments, the middle portion **252** of the bar graph indicates a transition between two or more different physiological states. The states can, for example, be any detectable or distinct physiological event, phase, or condition. In some, but not all, embodiments, a transition between physiological states represents the occurrence or presence of a distinct physiological event or condition, rather than simply a greater or lesser degree of a continuing physiological event or condition. In embodiments where the bar graph **260** is used to communicate values of an acquired patient respiratory signal, the middle portion **252** of the bar graph **250** can indicate a transition between inspiration and expiration in the patient's respiratory activity, each of which is a distinct phase of respiratory activity. In other words, when a value in the middle portion **252** of the bar graph is marked, it is an indication of the patient transitioning between inspiration and expiration. In other embodiments, the middle portion **252** marks a transition of a physiological signal between normal and abnormal values. For example, the

middle portion **252** could mark where a patient's blood oxygen saturation transitions between healthy and dangerous levels.

In addition to the generally rectangular shaped bar graph shown in FIG. **2**, other bar graph shapes are also possible. For example, FIG. **3** illustrates a diamond-shaped visual element **350**. Much like the bar graph **250**, the diamond-shaped visual element **350**, or diamond graph, can include a plurality of segments **358**, one or more of which can make up a middle portion **352** as well as upper **354** and lower **356** extremity portions. The diamond graph can also include an actionable value indicator **360**. It should be understood that, while the bar graph **250** and the diamond graph **360** are each shown as comprising of a number of discrete segments **258**, **358**, this is not required. Furthermore, those of skill in the art can recognize a wide variety of variations in shapes, sizes, colors, etc. of the visual elements disclosed in this specification which can be used in various embodiments.

While the visual element **150** of FIG. **1** may be a bar graph, as described herein, many other shapes and embodiments are also possible. For example, the visual element **150** can be any graphical shape or symbol with a reference point about which the graphical shape or symbol extends, expands, or otherwise modulates in at least two directions. In one embodiment, the visual element **150** is a circle (not shown), though other shapes can also be used, whose size increases and decreases in response to changes in a physiological signal, such as a respiratory signal. For example, the circle may have an initial diameter that is indicative of a transition between two or more physiological states. In one embodiment, the diameter of the circle increases during a first physiological state, such as patient inspiration, while the diameter decreases during a second physiological state, such as patient expiration. Therefore, when the diameter of the circle is larger than the initial diameter, an observer can see that the patient is in a first physiological state. When the diameter of the circle is smaller than the initial diameter, an observer can see that the patient is in a second physiological state. Many other types of visual elements **150** are also possible.

FIG. **4A** is a series of depictions of the visual element of FIG. **2** shown at different times as a physiological signal (e.g., a respiratory signal) fluctuates. FIG. **4A** includes still frames of a bar graph **450** at times **t1**, **t2**, **t3**, **t4**, and **t5** as the value indicator **460** actuates in response to changes in a patient's respiratory signal. In this example, the value indicator **460** represents the acoustic volume of the respiratory sounds picked up by the acoustic sensor **120**.

FIG. **4B** is a flowchart that further describes the illustrations in FIG. **4A**. At block **482**, a processor (not shown) in a physiological monitoring system (e.g., **105**) receives physiological information from a patient sensor (e.g., **120**). At block **484**, the processor determines the value of the physiological signal at a selected time. At block **486**, the processor causes the value of the physiological signal at the selected time to be displayed on a patient monitor (e.g., **110**) by actuating a value indicator in at least two directions, relative to a reference point, simultaneously. This process can be performed repeatedly for each of a plurality of selected times, as seen in FIG. **4A**.

Returning now to FIG. **4A**, at time **t1**, the value indicator **460** shows that the acoustic volume of the patient's breathing is relatively small. This can occur in a respiratory signal during an instant between inspiration and expiration (or between expiration and inspiration) by a patient where substantially no breathing sound is detected. At time **t2**, the value indicator **460** has expanded to indicate the detection of

a greater acoustic volume. In this embodiment, both the upper and lower extremity portions of the bar graph 450 are representative of relatively greater magnitudes of the acoustic volume of the respiratory signal than is the middle portion of the bar graph 450. Thus, the value indicator expands both in the direction of the upper extremity portion of the bar graph 450 as well as the lower extremity portion, in this case, by a substantially equal amount. At time t3, the value indicator 460 expands even further in both directions and indicates a relatively loud acoustic respiratory sound. Relatively large acoustic respiratory sounds, such as this, are typically detected during the middle portion of a patient inspiratory or expiratory phase. At time t4, the value indicator 460 has contracted somewhat, representing a decrease in the acoustic volume of the patient's respiratory signal. Finally, at time t5, the value indicator 460 contracts to the middle portion of the bar graph 450, indicating that the patient has completed one inspiratory phase and is transitioning to an expiratory phase, or vice versa.

In the embodiment illustrated in FIG. 4A, the middle portion of the bar graph 450 is indicative of a transition between inspiratory and expiratory phases in the patient's respiratory activity. As the patient inhales, the acoustic volume of the patient's breathing sounds increases, causing the value indicator to expand in the direction of both extremity portions of the bar graph 450 until such time as the acoustic volume reaches its peak and begins to taper off, causing the value indicator to contract back toward the middle portion of the bar graph 450. The patient can then begin to exhale, at which point the acoustic volume of the patient's breathing sounds can increase once again and the cycle shown in FIG. 4 can generally repeat itself, though the maximum value detected during inspiratory and expiratory phases, as well as the time to complete each phase, may not be equal. The series of bar graphs 450 shown in FIG. 4 can, therefore, be representative of patient inspiration or expiration. In certain cases it may be desirable to distinguish patient inspiration from expiration. For example, the value indicator 460 could be displayed in green during inspiration and in blue during expiration. In other embodiments, the value indicator 460 could blink during one respiratory phase while remaining solid during the other. Other mechanisms for distinguishing between patient inspiration and expiration in this embodiment are also possible.

A multi-directional visual element such as illustrated and described with respect to FIGS. 2-8A provides several clinical advantages in certain embodiments. For example, clinical monitors typically display a multitude of data related to many different physiological parameters of a patient. Some monitors display several numerical values related to a patient's overall health, such as blood pressure, pulse rate, blood oxygen concentration or saturation, etc. Monitors also often display several graphical images, or waveforms, as well. Although such information can be clinically useful to a medical provider, in some cases the quantity of information provided on a physiological monitor's display can cause confusion. For example, a clinician may be overwhelmed with the quantity of information provided and may not find the particular information desired when quickly glancing at the monitor's display. In such cases it is particularly useful to provide certain types of physiological information with a unique visual element that can be quickly discerned by a clinician. By doing so, the medical practitioner can become accustomed to visualizing particular physiological information (e.g., respiratory information) with a particular visual element (e.g., those described with respect to FIGS. 2-8A).

This can allow the medical practitioner to quickly find the information of interest from an information-rich visual display.

FIG. 5A is another example of a series of depictions of the visual element of FIG. 2 shown at different times as a physiological signal (e.g., a respiratory signal) fluctuates. The value indicator 560 indicates the acoustic volume of the respiratory sounds detected by the acoustic sensor 120. Both extremity portions of the bar graph 550 are representative of relatively larger magnitude values of the acoustic volume of the respiratory signal than is the middle portion of the bar graph. However, the value indicator 560 in this embodiment actuates in the region of one of the extremity portions of the bar graph 550 at a time. For example, the upper extremity portion of the bar graph 550 can correspond to a first phase of a physiological event (e.g., the respiratory signal which correspond to a patient inspiratory phase), while the lower extremity portion of the bar graph can correspond to a second phase of a physiological event (e.g., an expiratory phase). Therefore, the value indicator 560 represents different physiological states, phases, conditions, activities, etc. along different directions, or in different regions.

FIG. 5B is a flowchart that further describes the illustrations in FIG. 5A. At block 582, a processor (not shown) in a physiological monitoring system (e.g., physiological monitoring system 105 or any other system described herein) receives physiological information from a patient sensor (e.g., patient sensor 120 or any other sensor described herein). At block 584, the processor determines the value of the physiological signal at a selected time. At block 586, the processor determines a physiological state of the patient at the selected time, as represented by the value of the physiological signal at that time. If the patient is in a first physiological state (e.g., inspiration) at decision block 588, then the processor causes the value of the physiological signal to be displayed in a first portion of a visual element. If the patient is in a second physiological state (e.g., expiration) at decision block 592, then the processor causes the value of the physiological signal to be displayed in the second portion of the visual element. If the patient is not in either of the first or second physiological states, then, in some embodiments, it can be assumed that the patient is transitioning between the first and second physiological states, and the value of the physiological signal is displayed accordingly at block 596. This process can be performed repeatedly for each of a plurality of selected times, as seen in FIG. 5A.

Returning now to FIG. 5A, at time t1, the value indicator 560 shows that a relatively small acoustic volume has been detected. Again, during normal respiratory activity this corresponds to a transition between patient inspiration and expiration. At time t2, the value indicator 560 expands in the region of the upper extremity portion of the bar graph 550 to indicate the detection of relatively loud patient inspiration sounds. At time t3, the value indicator 560 contracts back to the middle portion of the bar graph 550, indicating the end of the inspiratory phase. The position of the value indicator 560 at time t4 corresponds to the detection of a moderately loud expiratory signal. Later, at time t5, the acoustic volume of the patient's expiratory action is shown to have decreased somewhat before it can eventually return back to the middle portion of the bar graph 550, indicating the completion of the patient's expiratory phase. As illustrated in FIG. 5A, the acoustic volume of a patient's breathing sounds during inspiratory and expiratory phases does not necessarily reach the same maximum value. Nor are the two respiratory phases necessarily of equal duration.

FIGS. 4A, 4B, 5A, and 5B merely represent two examples of ways in which a value indicator can actuate in response to changes in a patient's respiratory, or other physiological, signal according to different embodiments. In this way, a patient's respiratory activity can be easily monitored by a caregiver observing the respiratory monitor 110. As discussed previously, a patient's respiratory activity can be continuously monitored by an acoustic sensor 120 and transmitted to the patient respiratory monitor 110. The respiratory monitor 110 can include circuitry to sample the acquired continuous time respiratory signal and convert it into a digital representation. This operation results in a discrete series of time samples which approximate the continuous-time respiratory signal. The respiratory monitor 110 can also include a processor to analyze the respiratory signal and to cause a value indicator to actuate in accordance with changes in the respiratory signal over time, as illustrated in FIGS. 4A, 4B, 5A, and 5B.

In some embodiments, one respiratory data point is displayed by a visual element (e.g., visual element 150 or other visual elements described herein) for every time sample of the continuous-time signal. In other words, the value indicator actuation refreshes once for each time sample of the respiratory signal, e.g., if the continuous-time respiratory signal is sampled 60 times per second, the value indicator refreshes 60 times per second as well. However, the series of respiratory data points displayed by a visual element can also be different than the number of time samples that are taken from the continuous-time signal. For example, if the continuous-time respiratory signal is sampled 60 times per second, the value indicator may be configured to only refresh for every third time sample. In other embodiments, a plurality of time samples are combined to form a single value in the series of data points displayed by the visual element. For example, the value indicator can be configured to display a series of data points where each data point represents the average (e.g., a moving average) or median of a group of time samples in order to smooth the actuation of the value indicator. It is also possible for the value indicator to be configured to actuate at a higher rate than the sampling rate of the continuous-time respiratory signal by interpolating between time samples.

Some embodiments can be configured to display more than one data point (e.g., a value) at a time. For example, FIG. 6 is a schematic representation of a visual element capable of simultaneously displaying a plurality of values associated with a physiological signal (e.g., a respiratory signal). The visual element 650 includes an array of segments 658. The visual element 650 also includes a middle portion 652, as well as upper 654 and lower 656 extremity portions which are indicative of differing values of a respiratory, or other physiological, signal. Each of the five columns of segments represents a separate value in a series of data points displayed on the visual element 650. For example, the first column of segments can represent the value of a physiological signal at time t1, the second column can represent the value at time t2, etc.

In addition, each column of segments 658 includes a value indicator 660, which actuates in response to changes in a physiological signal as described above. The value indicators 660 in FIG. 6 only have their end points illuminated, rather than all intervening segments 658 as well. In other embodiments, end points and intervening segments 658 are both illuminated. Other types of value indicators are also possible. Each value indicator 660 can be configured to refresh in turn one after another until an end column, e.g., the right-most column, in the visual element 650 has been

reached. At this point the pattern may repeat and the value indicator in the opposite end column, e.g., the left-most column, can be refreshed. Other patterns for refreshing the value indicators 660 are also possible. For example, the value indicators 660 can be configured to all refresh simultaneously and hold their respective values until the next refresh time. Since the value indicator 650 shows a plurality of values, it can be configured to show an entire inspiratory or expiratory phase. In other embodiments, the visual element 650 can be configured to display entire respiratory periods, i.e., one inspiratory phase and one expiratory phase, or even several respiratory periods, at once.

In some embodiments, a visual element (e.g., 150) also includes separate indicators to communicate additional information to an observer. For example, FIG. 7A is a schematic representation of a visual element, which includes peak indicators, for displaying a physiological signal (e.g., a respiratory signal). The bar graph 750 includes a middle portion 752, an upper extremity portion 754, and a lower extremity portion 756. The bar graph 750 also includes a value indicator 760 which can be configured to actuate in response to changes in a detected respiratory signal. The bar graph 750 also includes an inspiration peak indicator 770 as well as an expiration peak indicator 772. The peak indicators 770, 772 can be configured to communicate to an observer the maximum magnitude that a patient's respiratory signal has reached during inspiratory and expiratory phases over a pre-determined time period. The peak indicators 770, 772 may be useful to a caregiver as an indication of the history of the patient's breathing activity and may aid in diagnoses or in decision making related to the patient's care.

In one embodiment, the peak indicators 770, 772 of FIG. 7A are portions of the bar graph 750 which have been configured to remain activated (e.g., in a lit up state) to show the maximum values or magnitudes attained by the patient's respiratory signal over a period of time. For example, the peak indicators 770, 772 remain activated even when the current value shown by the value indicator 760 is other than the peak value, or values, represented by the peak indicators 770, 772. For example, in FIG. 7A, the value indicator 760 shows a current inspiratory signal value of a moderate level. The inspiration peak indicator 770, however, shows that the patient's inspiratory signal reached a maximum value represented by the upper most segment of the bar graph 750 within some pre-determined period of time in its history. Likewise, the expiration peak indicator 772 shows the maximum value reached by the patient's expiratory signal over a period of time. In other embodiments, the peak indicator 772 illuminates to a different color than the physiological signal portion displayed on the bar graph 750.

The peak indicators 770, 772 can be configured to actuate to higher levels when new peak values in the patient's respiratory signal are attained. Similarly, the peak indicators 770, 772 may actuate to show smaller values if the patient's breathing activity has trended downward and previously reached peak values have not been met within the most recent pre-determined period of time.

The peak indicators 770, 772 can be configured to show the maximum values or magnitudes attained by a patient's respiratory signal over any period of time in the history of the signal. In one embodiment, for example, the peak indicators 770, 772 show the maximum acoustic volumes reached by a patient's respiratory signal over the course of the past five minutes. In some embodiments, the time period is configured to be adjustable by a caregiver.

FIG. 7B is a flowchart that further describes the illustrations in FIG. 7A. At block 782, a processor (not shown) in

a physiological monitoring system (e.g., 105) receives physiological information from a patient sensor (e.g., 120). At block 784, the processor determines the value of the physiological signal at a selected time. At block 786, the processor compares the value of the physiological signal at the selected time to previous values over a predetermined period of time. If the value of the physiological signal at the selected time reflects a new peak value, then the processor proceeds from decision block 788 to block 790 where it actuates a corresponding peak indicator 770, 772 to reflect the new peak value. Otherwise, at block 792, the processor does not change the peak indicator 770, 772. This process can be performed over for each new value of the physiological signal.

As illustrated in FIG. 7A, the peak indicators 770, 772 may be a segment, or other portion, of the bar graph 750. In these embodiments, the peak indicators 770, 772 can be displayed in different colors from the value indicator 760 for clarity in identifying the peak values or magnitudes. In other embodiments, the peak indicators 770, 772 may be configured to blink on and off. In still other embodiments, the peak indicators 770, 772 may be located adjacent the bar graph rather than being a part of the bar graph and may include an icon, arrow, or other graphical element. Other arrangements are also possible and can be recognized by those of skill in the art.

Some embodiments include additional types of indicators. For example, FIG. 8A is a schematic representation of a visual element, which includes goal indicators, for displaying a physiological signal (e.g., a respiratory signal). The bar graph 850 includes goal indicators 874, 876 which represent a value of a respiratory, or other physiological, signal for which a patient is to strive to reach. In the case of respiratory signals, this type of goal indicator can be beneficial to patients in need of exercising their lungs while recovering from surgery or as therapy for some other medical condition. Certain embodiments include an inspiratory goal indicator 874 and an expiratory goal indicator 876. Each of these goal indicators 874, 876 is a visual cue that indicates to a patient a target value to try to reach in his or her breathing.

In FIG. 8A, for example, if the value indicator 860 is understood to show the instant where the patient's inspiratory phase has reached its peak value or magnitude, which in this case is relatively low, the patient can see from the bar graph that he or she must breathe more deeply in order to reach the target value represented by the inspiratory goal indicator 874. Thus, the goal indicators 874, 876 help a patient strive to reach a desired level of breathing activity, whether for the purposes of recovery, testing, or some other reason. In some embodiments, the goal indicators 874, 876 are set and reconfigured by a caregiver, such as a doctor or nurse, or by the patient himself.

The goal indicators 874, 876 can be a segment, or other portion, of the bar graph 850, such as an LED, LCD, and/or an icon, color, sound, or combination thereof. In such cases it may be desirable to display the goal indicators in a color other than that used for the value indicator 860. In some embodiments, the goal indicators 874, 876 are configured to blink, for example, when the patient achieves the targeted value of the physiological signal. In still other embodiments, the goal indicators 874, 876 are accompanied by an audible indicator which sounds when the patient reaches the targeted goal. Many other configurations for displaying the goal indicators and signaling when the goal has been met are possible as well.

FIG. 8B is a flowchart that further describes the illustrations in FIG. 8A. At block 882, a processor (not shown) in

a physiological monitoring system receives physiological information from a patient sensor. At block 884, the processor determines the value of the physiological signal at a selected time. At block 886, the processor compares the value of the physiological signal at the selected time to a goal value that has been previously inputted by a caregiver or by the patient. If the value of the physiological signal at the selected time meets or exceeds the goal value, then the processor proceeds from decision block 888 to block 890 where it causes an acknowledgement that the goal has been reached to be given. This acknowledgement can be, for example, an audible sound. Otherwise, at block 892, the processor causes no such acknowledgement to be given. This process can be performed over for each new value of the physiological signal.

Some embodiments include more than one type of additional indicator beyond a value indicator. This is represented in FIG. 9, which is a schematic representation of a visual element that includes a plurality of types of indicators for displaying a physiological signal (e.g., a respiratory signal). The bar graph 950 includes peak indicators 970, 972, as well as goal indicators 974, 976. The bar graph 950 also includes a middle portion 952, an upper extremity portion 954, a lower extremity portion 956, and a value indicator 960 which is configured to actuate in response to changes in a detected physiological signal. In FIG. 9, it can be seen that the patient's respiratory signal has reached a peak value or magnitude marked by the peak indicators 970, 972 that still falls short of the patient's targeted goal, as marked by the goal indicators 974, 976. Thus the patient, or a caregiver, can recognize that the patient should continue to strive to breathe more deeply.

Additional types of indicators can also be included in various embodiments. As is described herein, these indicators can be configured as portions of a bar graph, for example. They may also be numbers, letters, or symbols located adjacent a visual element such as a bar graph. In some embodiments, indicators described herein are actionable in response to changes in a physiological signal. For example, in addition to the peak and goal indicators described above, a bar graph 950, or other type of visual element (e.g., visual element 150 or any other visual element described herein), can include indicators to show average values of a patient's respiratory signal during inspiratory or expiratory phases. The bar graph 950 could also include short-term peak indicators which are configured to represent value or magnitude peaks attained during a relatively short-term history of the patient's respiratory activity as well as long-term peak indicators which are configured to represent value or magnitude peaks attained over the course of a longer period of time. It should be apparent to those of skill in the art that the bar graph 950, or other type of visual element, can also include many other types of indicators to communicate to an observer any type of information related to a physiological signal.

Some embodiments include visual elements with additional information in the form of text, numbers, images, icons, or symbols, for example. In one embodiment, a visual element includes numbers which indicate the respiratory rate (e.g., breaths per minute) and/or respiratory period (e.g., seconds per breath) of a patient. A visual element can also include a numerical depiction of a value related to a physiological signal or an indication of signal quality (see FIG. 11). Other types of information that would be recognized by those in the skill as having a relationship to a physiological signal or of being of some benefit to a caregiver can also be included with the visual element.

In some embodiments, the patient monitor **110** also includes a speaker or other device capable of producing audible sounds. The patient monitor **110** can be configured to output a sound that varies in response to changes in a physiological signal. For example, the patient monitor **110** can output a sound that increases and decreases in volume in response to changes in a physiological signal. In one embodiment, the sound increases as the value or magnitude of the signal increases, and decreases as the value or magnitude of the signal decreases. In some embodiments, the pitch of the sound varies in response to changes in the physiological signal. For example, the pitch of the sound may increase as the value or magnitude of the signal increases, and may decrease as the value or magnitude of the signal decreases. Some embodiments produce “beeps” or other sounds that occur closer together or further apart in time in response to changes in the physiological signal. Some embodiments of the physiological monitor **110** output one sound during inspiration and a different sound during expiration of a respiratory signal as a non-visual indication of the different phases of the respiratory signal.

In some embodiments, the speaker is also configured to emit alarms when a patient enters into a dangerous or undesirable condition. For example, if the physiological monitor **110** detects a temporary cessation in the patient’s breathing, such as might occur in a patient with apnea, the speaker can emit an alarm. The speaker may also be configured to emit an alarm if the patient’s respiratory rate or depth of respiration decreases beyond a certain threshold.

FIG. **10** illustrates an embodiment of a sensor system **1000** including a sensor assembly **1001** and a monitor cable **1011** suitable for use with any of the physiological monitors and cables described herein. The sensor assembly **1001** includes a sensor **1015**, a cable assembly **1017**, and a connector **1005**. The sensor **1015**, in one embodiment, includes a sensor subassembly **1002** and an attachment subassembly **1004**. The cable assembly **1017** of one embodiment includes a sensor **1007** and a patient anchor **1003**. A sensor connector subassembly **1005** is connected to the sensor cable **1007**.

The sensor connector subassembly **1005** can be removably attached to an instrument cable **1011** via an instrument cable connector **1009**. The instrument cable **1011** can be attached to a cable hub **1020**, which includes a port **1021** for receiving a connector **1012** of the instrument cable **1011** and a second port **1023** for receiving another cable. The hub **1020** is an example of the splitter cable described above, and as such, can include decoupling circuitry. In certain embodiments, the second port **1023** can receive a cable connected to an optical sensor (e.g., a pulse oximetry sensor) or other sensor. In addition, the cable hub **1020** could include additional ports in other embodiments for receiving additional cables. The hub includes a cable **1022** which terminates in a connector **1024** adapted to connect to a physiological monitor (not shown).

The sensor connector subassembly **1005** and connector **1009** can be configured to allow the sensor connector **1005** to be straightforwardly and efficiently joined with and detached from the connector **1009**. Embodiments of connectors having connection mechanisms that can be used for the connectors **1005**, **1009** are described in U.S. patent application Ser. No. 12/248,856 (hereinafter referred to as “the ‘856 application”), filed on Oct. 9, 2008, which is incorporated in its entirety by reference herein. For example, the sensor connector **1005** could include a mating feature (not shown) which mates with a corresponding feature (not shown) on the connector **1009**. The mating feature can

include a protrusion which engages in a snap fit with a recess on the connector **1009**. In certain embodiments, the sensor connector **1005** can be detached via one hand operation, for example. Examples of connection mechanisms can be found specifically in paragraphs [0042], [0050], [0051], [0061]-[0068] and [0079], and with respect to FIGS. 8A-F, 13A-E, 19A-F, 23A-D and 24A-C of the ‘856 application, for example.

The sensor connector subassembly **1005** and connector **1009** can reduce the amount of unshielded area in and generally provide enhanced shielding of the electrical connection between the sensor and monitor in certain embodiments. Examples of such shielding mechanisms are disclosed in the ‘856 application in paragraphs [0043]-[0053], [0060] and with respect to FIGS. 9A-C, 11A-E, 13A-E, 14A-B, 15A-C, and 16A-E, for example.

In an embodiment, the acoustic sensor assembly **1001** includes a sensing element, such as, for example, a piezoelectric device or other acoustic sensing device. The sensing element can generate a voltage that is responsive to vibrations generated by the patient, and the sensor can include circuitry to transmit the voltage generated by the sensing element to a processor for processing. In an embodiment, the acoustic sensor assembly **1001** includes circuitry for detecting and transmitting information related to biological sounds to a physiological monitor. These biological sounds can include heart, breathing, and/or digestive system sounds, in addition to many other physiological phenomena. The acoustic sensor **1015** in certain embodiments is a biological sound sensor, such as the sensors described herein. In some embodiments, the biological sound sensor is one of the sensors such as those described in the ‘883 application. In other embodiments, the acoustic sensor **1015** is a biological sound sensor such as those described in U.S. Pat. No. 6,661,161, which is incorporated by reference herein in its entirety. Other embodiments include other suitable acoustic sensors.

The attachment sub-assembly **1004** includes first and second elongate portions **1006**, **1008**. The first and second elongate portions **1006**, **1008** can include patient adhesive (e.g., in some embodiments, tape, glue, a suction device, etc.). The adhesive on the elongate portions **1006**, **1008** can be used to secure the sensor subassembly **1002** to a patient’s skin. One or more elongate members **1010** included in the first and/or second elongate portions **1006**, **1008** can beneficially bias the sensor subassembly **1002** in tension against the patient’s skin and reduce stress on the connection between the patient adhesive and the skin. A removable backing can be provided with the patient adhesive to protect the adhesive surface prior to affixing to a patient’s skin.

The sensor cable **1007** can be electrically coupled to the sensor subassembly **1002** via a printed circuit board (“PCB”) (not shown) in the sensor subassembly **1002**. Through this contact, electrical signals are communicated from the multi-parameter sensor subassembly to the physiological monitor through the sensor cable **1007** and the cable **1011**.

In various embodiments, not all of the components illustrated in FIG. **10** are included in the sensor system **1000**. For example, in various embodiments, one or more of the patient anchor **1003** and the attachment subassembly **1004** are not included. In one embodiment, for example, a bandage or tape is used instead of the attachment subassembly **1004** to attach the sensor subassembly **1002** to the measurement site. Moreover, such bandages or tapes can be a variety of different shapes including generally elongate, circular and oval, for example. In addition, the cable hub **1020** need not

be included in certain embodiments. For example, multiple cables from different sensors could connect to a monitor directly without using the cable hub **1020**.

Additional information relating to acoustic sensors compatible with embodiments described herein, including other embodiments of interfaces with the physiological monitor, are included in U.S. patent application Ser. No. 12/044,883, filed Mar. 7, 2008, entitled "Systems and Methods for Determining a Physiological Condition Using an Acoustic Monitor," (hereinafter referred to as "the '883 application"), the disclosure of which is hereby incorporated by reference in its entirety. An example of an acoustic sensor that can be used with the embodiments described herein is disclosed in U.S. patent application Ser. No. 12/643,939, incorporated above.

#### Freshness Indicator

Referring to FIG. **11**, a respiratory analysis system **1100** is shown. The respiratory analysis system **1100** can calculate one or more parameters related to an acoustic signal obtained from a patient. The respiratory analysis system **1100** can calculate, among other parameters, respiratory rate (sometimes referred to as RR), respiratory signal quality (RSQ), and freshness of the respiratory rate calculation. Advantageously, in certain embodiments, the respiratory analysis system **1100** can output data and/or indicators reflecting one or more of these parameters, thereby assisting clinicians with assessing a health status of a patient.

The respiratory analysis system **1100** includes three example modules in the depicted embodiment. These modules include a respiratory rate calculator **1110**, an RSQ calculator **1120**, and a freshness calculator **1130**. Each of these modules can include hardware and/or software for performing certain tasks. An acoustic signal **1102** is received by the respiratory analysis system **1100** and is used by one or more of the modules to perform these tasks. The acoustic signal **1102** can be obtained from an acoustic sensor, such as any of the sensors described above, coupled to a living patient.

The respiratory rate calculator **1100** can analyze the acoustic signal **1102** to determine a respiratory rate measurement for the patient. The respiratory rate measurement can vary with time. The respiratory rate calculator **1100** can output the respiratory rate measurements **1142** for presentation to a clinician. For example, the respiratory rate calculator **1100** can output the respiratory rate measurements **1142** to a display or to another clinician device over a network (such as a nurse's station computer in a hospital).

The RSQ calculator **1120** can calculate an objective measure of the quality of the acoustic signal **1102**. The RSQ calculator **1120** can, for instance, quantitatively determine how corrupted the acoustic signal **1102** is by noise, how similar the acoustic signal **1102** is to known waveform characteristics of respiratory signals, and the like. Based at least in part on this analysis, the RSQ calculator **1120** can output an RSQ indicator **1144** that reflects the calculated quality of the acoustic signal **1102**. The RSQ calculator **1120** can output the RSQ indicator **1144** to a display or to another clinician device over a network. Advantageously, in certain embodiments, the RSQ indicator **1144** can be implemented as any of the visual indicators or elements described above. For instance, the RSQ indicator **1144** can be a bidirectional bar graph. As signal quality changes, the bidirectional bar graph could change accordingly.

The RSQ indicator **1144** could be a unidirectional bar graph instead of a bidirectional bar graph. The RSQ indicator **1144** can also be a binary indicator, indicating low or high RSQ. The RSQ indicator **1144** could also be a numeri-

cal value, such as a percentage or the like. In another embodiment, the RSQ indicator **1144** can be an occurrence indicator, such as the occurrence indicator described in U.S. Pat. No. 6,996,427, titled "Pulse Oximetry Data Confidence Indicator," filed Dec. 18, 2003, the disclosure of which is hereby incorporated by reference in its entirety. Any combination of the indicators described herein and/or other types of indicators could be used.

The freshness calculator **1130** calculates a freshness or relevance of the respiratory rate measurement **1142**. In some situations, the respiratory rate calculator **1110** and/or the RSQ calculator **1120** might determine that a calculated respiratory rate measurement **1142** is invalid, of low quality, or cannot be measured. An invalid respiratory rate measurement **1142** can be, for example, a measurement that is not physiological possible (such as a measurement that is too high). An invalid measurement can also be a measurement that changes rapidly over a short period of time. One option when invalid or other low quality measurements occur is to discard the invalid or low quality respiratory rate value and not display a new measurement until a valid or higher quality value is obtained. However, not displaying a respiratory rate value (or showing zero) can confuse a clinician if the patient is still breathing.

Thus, instead of displaying no (or zero) value in low quality signal conditions, the respiratory rate calculator **1110** can continue to output the previous respiratory rate measurement **1142** for a certain amount of time. This amount of time can be determined by the freshness calculator **1130**. The freshness calculator **1130** can include a counter, timer, or the like that increments (or decrements) as soon as a low or invalid signal condition is detected by the respiratory rate calculator **1110** or the RSQ calculator **1120**. When the freshness calculator **1130** determines that a certain amount of time has elapsed, for example, by comparison with a predetermined threshold time value, the freshness calculator **1130** can cause the respiratory rate calculator **1110** to output a zero or no respiratory rate value. Conversely, if while the freshness calculator **1130** is incrementing (or decrementing) the counter the respiratory rate calculator **1110** produces a valid or higher quality respiratory rate measurement **1142**, the freshness calculator **1130** can reset the counter.

The amount of time elapsed before the freshness calculator **1130** outputs a zero or no respiratory rate value can be user-configurable. The respiratory analysis system **1100** can, for instance, output a user interface control on a display of a patient monitor that enables a clinician to adjust the freshness period. This input by a clinician can then be updated in the freshness calculator **1130**. The respiratory analysis system **1100** can provide a user interface element on a display or the like for the clinician to input the freshness timer input **1104**.

The freshness calculator **1130** can output a freshness indicator **1146** that reflects a freshness of the respiratory rate measurement **1142**. The freshness calculator **1130** can output the freshness indicator **1146** to a display or to another clinician device over a network. The freshness indicator **1146** can be a light, for instance, that turns on when the freshness calculator **1130** is incrementing (or decrementing) the counter. The light could also change color as the counter is incremented (or decremented). The freshness indicator **1146** could also be a bar, a number, or any other visual element. The freshness indicator **1146** could also be an audible indicator, such as an audible alarm. The audible indicator can increase in intensity as the counter is incremented (or decremented).

In another embodiment, the freshness indicator **1146** can be implemented as a flashing version of a parameter value or other value indicator. For example, any numeric value of a parameter can flash to reflect lack of, or a decrease in, freshness. The bidirectional display bar described above can also flash to reflect the lack of freshness. The flashing of the parameter or other value indicator can increase (or decrease) in rate until a defined time period has expired. After this time period has expired, a zero value can be displayed for the parameter. Moreover, when the freshness period has expired, an alarm can be triggered.

In yet another embodiment, the freshness indicator **1146** and the RSQ indicator **1144** are implemented together, for example, as follows. The RSQ indicator **1144** can generally indicate changes in signal quality of a respiration or acoustic signal. The freshness of a respiratory rate measurement **1142** can be calculated as described above. Instead of outputting a separate indicator, the calculated freshness can be used to adjust the output of the RSQ indicator **1144**. If a respiratory rate measurement **1142** is less fresh, for instance, the RSQ indicator **1144** can reflect this as a lower value, a lower bar (or bars), or the like. In one embodiment, the RSQ indicator **1144** is lowered by some percentage, such as 5%, 10%, 20%, or some other percentage. In other embodiments, the RSQ indicator **1144** gradually drops toward some minimum value (such as zero) as the freshness decreases.

Any combination of these features can be used for the freshness indicator **1146**, as well as others.

FIG. **12** illustrates an embodiment of a patient monitor **1200** having a respiration display. The patient monitor **1200** can include any of the features described above. Further, the patient monitor **1200** can implement any of the displays or other features described above. In the depicted embodiment, the patient monitor **1200** displays an example respiration waveform.

The patient monitor **1200** displays parameter indicators for several physiological parameters in the depicted embodiment. Some of these parameter indicators include an oxygen saturation indicator **1210**, hemoglobin, perfusion index, plethysmograph variability index, and other indicators **1220**, and an occurrence graph **1225** reflecting signal quality for an optical signal.

Further, the patient monitor **1200** displays an example respiratory rate indicator **1230** that reflects values of a patient's respiratory rate. This value can be obtained using any of the respiratory rate measurement methods described above. Advantageously, in the depicted embodiment, the patient monitor **1200** also includes a respiration waveform **1240**. This respiration waveform **1240** can represent a patient's time-domain respiration signal or an envelope of the respiration signal over a period of time. The respiration waveform **1240** can be bidirectional or unidirectional in some embodiments. The depicted patient monitor **1200** illustrates a bidirectional respiration waveform **1240**. A unidirectional respiration waveform **1240** might include excursions in a single direction (e.g., positive or negative) from an axis.

The respiration waveform **1240** can reflect an actual respiration signal, providing a clinician with more information about a patient's breathing pattern than just the respiratory rate indicator **1230** alone. The respiration waveform **1240** can enable a clinician to diagnose patient problems by observing, for instance, heights and widths of peaks in the respiratory waveform **1240**, irregularities in the respiratory waveform **1240**, spikes of activity in the respiratory waveform **1240**, general low activity in the respiratory waveform **1240**, some combination of the same, or the like.

It should be noted that although several embodiments herein have described a bidirectional display, a unidirectional display can be used instead to represent respiratory parameters.

Conditional language used herein, such as, among others, "can," "could," "might," "may," "e.g.," and the like, unless specifically stated otherwise, or otherwise understood within the context as used, is generally intended to convey that certain embodiments include, while other embodiments do not include, certain features, elements and/or states. Thus, such conditional language is not generally intended to imply that features, elements and/or states are in any way required for one or more embodiments or that one or more embodiments necessarily include logic for deciding, with or without author input or prompting, whether these features, elements and/or states are included or are to be performed in any particular embodiment.

Depending on the embodiment, certain acts, events, or functions of any of the methods described herein can be performed in a different sequence, can be added, merged, or left out all together (e.g., not all described acts or events are necessary for the practice of the method). Moreover, in certain embodiments, acts or events can be performed concurrently, e.g., through multi-threaded processing, interrupt processing, or multiple processors or processor cores, rather than sequentially.

The various illustrative logical blocks, modules, circuits, and algorithm steps described in connection with the embodiments disclosed herein can be implemented as electronic hardware, computer software, or combinations of both. To clearly illustrate this interchangeability of hardware and software, various illustrative components, blocks, modules, circuits, and steps have been described above generally in terms of their functionality. Whether such functionality is implemented as hardware or software depends upon the particular application and design constraints imposed on the overall system. The described functionality can be implemented in varying ways for each particular application, but such implementation decisions should not be interpreted as causing a departure from the scope of the disclosure.

The various illustrative logical blocks, modules, and circuits described in connection with the embodiments disclosed herein can be implemented or performed with a general purpose processor, a digital signal processor (DSP), an application specific integrated circuit (ASIC), a field programmable gate array (FPGA) or other programmable logic device, discrete gate or transistor logic, discrete hardware components, or any combination thereof designed to perform the functions described herein. A general purpose processor can be a microprocessor, but in the alternative, the processor can be any conventional processor, controller, microcontroller, or state machine. A processor can also be implemented as a combination of computing devices, e.g., a combination of a DSP and a microprocessor, a plurality of microprocessors, one or more microprocessors in conjunction with a DSP core, or any other such configuration.

The blocks of the methods and algorithms described in connection with the embodiments disclosed herein can be embodied directly in hardware, in a software module executed by a processor, or in a combination of the two. A software module can reside in RAM memory, flash memory, ROM memory, EPROM memory, EEPROM memory, registers, a hard disk, a removable disk, a CD-ROM, or any other form of computer-readable storage medium known in the art. An exemplary storage medium is coupled to a processor such that the processor can read information from, and write information to, the storage medium. In the alter-

native, the storage medium can be integral to the processor. The processor and the storage medium can reside in an ASIC. The ASIC can reside in a user terminal. In the alternative, the processor and the storage medium can reside as discrete components in a user terminal.

While the above detailed description has shown, described, and pointed out novel features as applied to various embodiments, it can be understood that various omissions, substitutions, and changes in the form and details of the devices or algorithms illustrated can be made without departing from the spirit of the disclosure. As can be recognized, certain embodiments of the inventions described herein can be embodied within a form that does not provide all of the features and benefits set forth herein, as some features can be used or practiced separately from others. The scope of certain inventions disclosed herein is indicated by the appended claims rather than by the foregoing description. All changes which come within the meaning and range of equivalency of the claims are to be embraced within their scope.

What is claimed is:

1. A system comprising:

one or more respiratory sensors configured to be coupled with a patient and to generate a respiration waveform representing inspiration and expiration cycles of the patient;

a processor configured to receive the respiration waveform from the one or more respiratory sensors; and

a display configured to display a visual element for representing values of an amplitude of the respiration waveform, the visual element comprising:

a middle portion corresponding to a reference position representative of a transition between the inspiration and the expiration,

a first extremity portion extending from the middle portion in a first direction,

a second extremity portion extending from the middle portion in a second direction,

a value indicator configured to visually depict values of the amplitude of the respiration waveform during the inspiration and the expiration cycles, wherein the amplitude of the respiration waveform comprises an acoustic volume of the patient's respiratory sounds, and

first and second goal indicators positioned between the reference position and the first and second extremity portions, respectively, the first and second goal indicators visually indicating a goal value of the amplitude of the respiration waveform that the patient is to strive to reach during inspiration, wherein the goal value of the amplitude of the respiration waveform comprises a desired acoustic volume of the patient's respiratory sounds;

wherein the processor is configured to:

illuminate the value indicator responsive to changes in the amplitude of the respiration waveform to expand at least partway toward ends of both the first and second extremity portions during inspiration and to contract at least partway toward the reference position during expiration, and

illuminate the first and second goal indicators.

2. The system of claim 1, wherein the first and second goal indicators are configured to blink when the amplitude of the respiration waveform achieves the goal value.

3. The system of claim 1, wherein the processor is configured to:

determine a value of the amplitude of the respiration waveform at a time corresponding to when an inspiratory phase of the patient has reached its peak value; and compare the peak value to the goal value.

4. The system of claim 3, wherein the processor is configured to, in response to determining that the peak value exceeds the goal value, output an acknowledgement that the goal value has been reached.

5. The system of claim 4, wherein the acknowledgement comprises an audible sound.

6. The system of claim 4, wherein the acknowledgement comprises a change in appearance to one or both of the first and second goal indicators.

7. The system of claim 3, wherein the processor is configured to, in response to determining that the peak value does not equal or exceed the goal value, expand the value indicator toward the first and second goal indicators.

8. The system of claim 1, wherein the visual element comprises a bar graph, and wherein the first and second goal indicators each comprise a segment of the bar graph.

9. The system of claim 1, wherein the processor is configured to illuminate the first and second goal indicators using a different color than that used for the value indicator.

10. The system of claim 1, wherein the processor is configured to illuminate the value indicator and the first and second goal indicators while the patient is conducting breathing exercises.

11. A physiological monitor comprising:

a processor configured to receive physiological information comprising a respiration waveform from one or more sensors coupled with a patient; and

a display configured to display a visual element for representing values of an amplitude of the respiration waveform, the visual element comprising:

a middle portion corresponding to a reference position representative of a transition between inspiration and expiration cycles of the patient,

first and second extremity portions, the first extremity portion extending from the middle portion in a first direction, and the second extremity portion extending from the middle portion in a second direction,

a value indicator configured to visually depict values of the amplitude of the respiration waveform, wherein the amplitude of the respiration waveform comprises an acoustic volume of the patient's respiratory sounds,

a first goal indicator positioned along the first extremity portion, and

a second goal indicator positioned along the extremity portion, the first and second goal indicators visually indicating a goal value of the amplitude of the respiration waveform during inspiration, wherein the goal value of the amplitude of the respiration waveform comprises a desired acoustic volume of the patient's respiratory sounds;

wherein the processor is configured to:

illuminate the value indicator responsive to changes in the amplitude of the respiration waveform to expand at least partway toward ends of both the first and second extremity portions during inspiration and to contract at least partway toward the reference position during expiration, and

illuminate the first and second goal indicators.

12. The physiological monitor of claim 11, wherein the first and second goal indicators are configured to blink when the amplitude of the respiration waveform achieves the goal value.

13. The physiological monitor of claim 11, wherein the processor is configured to:  
 determine a value of the amplitude of the respiration waveform at a time corresponding to when an inspiratory phase of the patient has reached its peak value; and  
 compare the peak value to the goal value. 5
14. The physiological monitor of claim 13, wherein the processor is configured to, in response to determining that the peak value exceeds the goal value, output an acknowledgement that the goal value has been reached. 10
15. The physiological monitor of claim 14, wherein the acknowledgement comprises an audible sound.
16. The physiological monitor of claim 14, wherein the acknowledgement comprises a change in appearance to one or both of the first and second goal indicators. 15
17. The physiological monitor of claim 13, wherein the processor is configured to, in response to determining that the peak value does not equal or exceed the goal value, expand the value indicator toward the first and second goal indicators. 20
18. The physiological monitor of claim 11, wherein the visual element comprises a bar graph, and wherein the first and second goal indicators each comprise a segment of the bar graph.
19. The physiological monitor of claim 11, wherein the processor is configured to illuminate the first and second goal indicators using a different color than that used for the value indicator. 25
20. The physiological monitor of claim 11, wherein the processor is configured to illuminate the value indicator and the first and second goal indicators while the patient is conducting breathing exercises. 30

\* \* \* \* \*

专利名称(译)	双向生理信息显示		
公开(公告)号	<a href="#">US10357209</a>	公开(公告)日	2019-07-23
申请号	US15/615654	申请日	2017-06-06
[标]申请(专利权)人(译)	梅西莫股份有限公司		
申请(专利权)人(译)	Masimo公司		
当前申请(专利权)人(译)	Masimo公司		
[标]发明人	AL ALI AMMAR		
发明人	AL-ALI, AMMAR		
IPC分类号	A61B5/08 A61B5/00 A61B7/00 G16H50/20 G16H40/63 G16H15/00		
CPC分类号	A61B5/7445 A61B5/08 A61B5/0816 A61B5/7435 A61B7/003 G16H40/63 G16H50/20 A61B5/6833 G16H40/67 G16H15/00 G06F19/3418		
优先权	61/252083 2009-10-15 US 61/288843 2009-12-21 US 61/290436 2009-12-28 US 61/331087 2010-05-04 US		
其他公开文献	US20180110478A1		
外部链接	<a href="#">Espacenet</a>		

摘要(译)

用于显示生理信号的患者监测器可以包括视觉元件，该视觉元件具有指示生理状态之间的生理信号的转变的中间部分。视觉元件还可包括第一和第二末端部分，第一末端部分沿第一方向从中间部分延伸，第二末端部分沿第二方向从中间部分延伸。视觉元素还可以包括可动作值指示符，以指定关于中间部分以及第一和第二末端部分的值。患者监测器还可以包括处理器，该处理器被配置为根据生理信号的变化使值指示器在第一和第二方向上致动。

