



US010169561B2

(12) **United States Patent**
Razouane et al.

(10) **Patent No.:** **US 10,169,561 B2**
(45) **Date of Patent:** ***Jan. 1, 2019**

(54) **BIOMETRIC INTERFACE SYSTEM AND METHOD**

(71) Applicant: **BRAGI GmbH**, München (DE)

(72) Inventors: **Mohamed Ali Razouane**, München (DE); **Peter Vincent Boesen**, München (DE)

(73) Assignee: **BRAGI GmbH**, München (DE)

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 0 days.

This patent is subject to a terminal disclaimer.

(21) Appl. No.: **15/951,063**

(22) Filed: **Apr. 11, 2018**

(65) **Prior Publication Data**

US 2018/0232512 A1 Aug. 16, 2018

Related U.S. Application Data

(63) Continuation of application No. 15/497,065, filed on Apr. 25, 2017.

(Continued)

(51) **Int. Cl.**

G06F 21/32 (2013.01)

A61B 5/1172 (2016.01)

(Continued)

(52) **U.S. Cl.**

CPC **G06F 21/32** (2013.01); **A61B 5/02416** (2013.01); **A61B 5/117** (2013.01);

(Continued)

(58) **Field of Classification Search**

CPC G06F 21/32; G06F 21/40; G06F 21/83;
G06F 17/30294; G06F 17/30595;
(Continued)

(56) **References Cited**

U.S. PATENT DOCUMENTS

2,325,590 A 8/1943 Carlisle et al.
2,430,229 A 11/1947 Kelsey

(Continued)

FOREIGN PATENT DOCUMENTS

CN 204244472 U 4/2015
CN 104683519 A 6/2015

(Continued)

OTHER PUBLICATIONS

Stretchgoal—The Carrying Case for the Dash (Feb. 12, 2014).

(Continued)


Primary Examiner — Mohamed Barakat

(74) *Attorney, Agent, or Firm* — Goodhue, Coleman & Owens, P.C.

(57) **ABSTRACT**

A system includes a wearable device having at least one sensor configured to determine a user's fingerprint data, at least one data storage device containing authentication data, and at least one processor configured to compare the user's fingerprint data with the authentication data to authenticate a user. A method of authenticating a wearable device includes producing a fingerprint, determining fingerprint data derived from the fingerprint with one or more sensors, comparing the fingerprint data with authentication data on one or more data storage devices, and authenticating the user if the fingerprint data and the authentication data match.

19 Claims, 2 Drawing Sheets



Related U.S. Application Data

- (60) Provisional application No. 62/328,915, filed on Apr. 28, 2016.

(51) Int. Cl.

G07C 9/00 (2006.01)
G06F 21/83 (2013.01)
A61B 5/117 (2016.01)
A61B 5/00 (2006.01)
H04R 1/10 (2006.01)
G06F 21/40 (2013.01)
H04R 5/04 (2006.01)
G06F 17/30 (2006.01)
H04Q 9/00 (2006.01)
A61B 5/024 (2006.01)
A61B 5/11 (2006.01)
G06F 3/01 (2006.01)
G05B 19/00 (2006.01)
G06F 21/34 (2013.01)

(52) U.S. Cl.

CPC **A61B 5/1172** (2013.01); **A61B 5/6803** (2013.01); **G06F 17/30289** (2013.01); **G06F 21/40** (2013.01); **G06F 21/83** (2013.01); **G07C 9/00071** (2013.01); **G07C 9/00158** (2013.01); **H04R 1/1016** (2013.01); **H04R 5/04** (2013.01); **A61B 5/02405** (2013.01); **A61B 5/11** (2013.01); **G05B 19/00** (2013.01); **G06F 3/017** (2013.01); **G06F 17/30294** (2013.01); **G06F 17/30595** (2013.01); **G06F 21/34** (2013.01); **G06F 2221/2147** (2013.01); **H04Q 9/00** (2013.01)

(58) Field of Classification Search

CPC **G06F 21/34**; **G06F 2221/2147**; **A61B 5/1172**; **G07C 9/00071**; **G07C 9/00158**; **H04R 5/04**; **G05B 19/00**; **H04Q 9/00**

See application file for complete search history.

(56) References Cited

U.S. PATENT DOCUMENTS

3,047,089	A	7/1962	Zwislocki	5,347,584	A	9/1994	Narisawa
D208,784	S	10/1967	Sanzone	5,363,444	A	11/1994	Norris
3,586,794	A	6/1971	Michaelis	5,444,786	A	8/1995	Raviv
3,696,377	A	10/1972	Wall	D367,113	S	2/1996	Weeks
3,934,100	A	1/1976	Harada	5,497,339	A	3/1996	Bernard
3,983,336	A	9/1976	Malek et al.	5,606,621	A	2/1997	Reiter et al.
4,069,400	A	1/1978	Johanson et al.	5,613,222	A	3/1997	Guenther
4,150,262	A	4/1979	Ono	5,654,530	A	8/1997	Sauer et al.
4,334,315	A	6/1982	Ono et al.	5,692,059	A	11/1997	Kruger
D266,271	S	9/1982	Johanson et al.	5,721,783	A	2/1998	Anderson
4,375,016	A	2/1983	Harada	5,748,743	A	5/1998	Weeks
4,588,867	A	5/1986	Konomi	5,749,072	A	5/1998	Mazurkiewicz et al.
4,617,429	A	10/1986	Bellafigore	5,771,438	A	6/1998	Palermo et al.
4,654,883	A	3/1987	Iwata	D397,796	S	9/1998	Yabe et al.
4,682,180	A	7/1987	Gans	5,802,167	A	9/1998	Hong
4,791,673	A	12/1988	Schreiber	5,844,996	A	12/1998	Enzmann et al.
4,852,177	A	7/1989	Ambrose	D410,008	S	5/1999	Almqvist
4,865,044	A	9/1989	Wallace et al.	5,929,774	A	7/1999	Charlton
4,984,277	A	1/1991	Bisgaard et al.	5,933,506	A	8/1999	Aoki et al.
5,008,943	A	4/1991	Arndt et al.	5,949,896	A	9/1999	Nageno et al.
5,185,802	A	2/1993	Stanton	5,987,146	A	11/1999	Pluvinage et al.
5,191,602	A	3/1993	Regen et al.	6,021,207	A	2/2000	Puthuff et al.
5,201,007	A	4/1993	Ward et al.	6,054,989	A	4/2000	Robertson et al.
5,201,008	A	4/1993	Amdt et al.	6,081,724	A	6/2000	Wilson
D340,286	S	10/1993	Seo	6,084,526	A	7/2000	Blotky et al.
5,280,524	A	1/1994	Norris	6,094,492	A	7/2000	Boesen
5,295,193	A	3/1994	Ono	6,111,569	A	8/2000	Brusky et al.
5,298,692	A	3/1994	Ikeda et al.	6,112,103	A	8/2000	Puthuff
5,343,532	A	8/1994	Shugart	6,157,727	A	12/2000	Rueda
				6,167,039	A	12/2000	Karlsson et al.
				6,181,801	B1	1/2001	Puthuff et al.
				6,185,152	B1	2/2001	Shen
				6,208,372	B1	3/2001	Barracough
				6,230,029	B1	5/2001	Yegiazaryan et al.
				6,275,789	B1	8/2001	Moser et al.
				6,339,754	B1	1/2002	Flanagan et al.
				D455,835	S	4/2002	Anderson et al.
				6,408,081	B1	6/2002	Boesen
				6,424,820	B1	7/2002	Burdick et al.
				D464,039	S	10/2002	Boesen
				6,470,893	B1	10/2002	Boesen
				D468,299	S	1/2003	Boesen
				D468,300	S	1/2003	Boesen
				6,542,721	B2	4/2003	Boesen
				6,560,468	B1	5/2003	Boesen
				6,563,301	B2	5/2003	Gventer
				6,654,721	B2	11/2003	Handelman
				6,664,713	B2	12/2003	Boesen
				6,690,807	B1	2/2004	Meyer
				6,694,180	B1	2/2004	Boesen
				6,718,043	B1	4/2004	Boesen
				6,738,485	B1	5/2004	Boesen
				6,748,095	B1	6/2004	Goss
				6,754,358	B1	6/2004	Boesen et al.
				6,784,873	B1	8/2004	Boesen et al.
				6,823,195	B1	11/2004	Boesen
				6,852,084	B1	2/2005	Boesen
				6,879,698	B2	4/2005	Boesen
				6,892,082	B2	5/2005	Boesen
				6,920,229	B2	7/2005	Boesen
				6,952,483	B2	10/2005	Boesen et al.
				6,987,986	B2	1/2006	Boesen
				7,010,137	B1	3/2006	Leedom et al.
				7,113,611	B2	9/2006	Leedom et al.
				D532,520	S	11/2006	Kampmeier et al.
				7,136,282	B1	11/2006	Rebeske
				7,203,331	B2	4/2007	Boesen
				7,209,569	B2	4/2007	Boesen
				7,215,790	B2	5/2007	Boesen et al.
				D549,222	S	8/2007	Huang
				D554,756	S	11/2007	Sjursen et al.
				7,403,629	B1	7/2008	Aceti et al.
				D579,006	S	10/2008	Kim et al.
				7,463,902	B2	12/2008	Boesen
				7,508,411	B2	3/2009	Boesen
				7,532,901	B1	5/2009	LaFranchise et al.
				D601,134	S	9/2009	Elabidi et al.
				7,825,626	B2	11/2010	Kozisek
				7,859,469	B1	12/2010	Rosener et al.

(56)

References Cited

U.S. PATENT DOCUMENTS

7,965,855 B1	6/2011	Ham	2006/0220915 A1	10/2006	Bauer	
7,979,035 B2	7/2011	Griffin et al.	2006/0258412 A1	11/2006	Liu	
7,983,628 B2	7/2011	Boesen	2007/0102009 A1	5/2007	Wong et al.	
D647,491 S	10/2011	Chen et al.	2007/0239225 A1	10/2007	Saringer	
8,095,188 B2	1/2012	Shi	2007/0269785 A1	11/2007	Yamanoi	
8,108,143 B1	1/2012	Tester	2008/0076972 A1	3/2008	Dorogusker et al.	
8,140,357 B1	3/2012	Boesen	2008/0090622 A1	4/2008	Kim et al.	
D666,581 S	9/2012	Perez	2008/0102424 A1	5/2008	Holljes	
8,300,864 B2	10/2012	Müllernborn et al.	2008/0146890 A1	6/2008	LeBoeuf et al.	
8,406,448 B2	3/2013	Lin	2008/0187163 A1	8/2008	Goldstein et al.	
8,430,817 B1	4/2013	Al-Ali et al.	2008/0215239 A1	9/2008	Lee	
8,436,780 B2	5/2013	Schantz et al.	2008/0253583 A1	10/2008	Goldstein et al.	
D687,021 S	7/2013	Yuen	2008/0254780 A1	10/2008	Kuhl et al.	
8,679,012 B1	3/2014	Kayyali	2008/0255430 A1	10/2008	Alexandersson et al.	
8,719,877 B2	5/2014	VonDoenhoff et al.	2008/0298606 A1	12/2008	Johnson et al.	
8,774,434 B2	7/2014	Zhao et al.	2009/0003620 A1	1/2009	McKillop et al.	
8,831,266 B1	9/2014	Huang	2009/0008275 A1	1/2009	Ferrari et al.	
8,891,800 B1	11/2014	Shaffer	2009/0017881 A1	1/2009	Madrigal	
8,994,498 B2	3/2015	Agrafioti et al.	2009/0041313 A1 *	2/2009	Brown	H04M 1/05
D728,107 S	4/2015	Martin et al.	2009/0073070 A1	3/2009	Rofougaran	382/124
9,013,145 B2	4/2015	Castillo et al.	2009/0097689 A1	4/2009	Prest et al.	
9,037,125 B1	5/2015	Kadous	2009/0105548 A1	4/2009	Bart	
D733,103 S	6/2015	Jeong et al.	2009/0154739 A1	6/2009	Zellner	
9,081,944 B2	7/2015	Camacho et al.	2009/0191920 A1	7/2009	Regen et al.	
9,461,403 B2	10/2016	Gao et al.	2009/0226017 A1	9/2009	Abolfathi et al.	
9,510,159 B1	11/2016	Cuddihy et al.	2009/0240947 A1	9/2009	Goyal et al.	
D773,439 S	12/2016	Walker	2009/0245559 A1	10/2009	Boltyenkov et al.	
D775,158 S	12/2016	Dong et al.	2009/0261114 A1	10/2009	McGuire et al.	
D777,710 S	1/2017	Palmborg et al.	2009/0296968 A1	12/2009	Wu et al.	
9,544,689 B2	1/2017	Fisher et al.	2009/0303073 A1	12/2009	Gilling et al.	
D788,079 S	5/2017	Son et al.	2009/0304210 A1	12/2009	Weisman	
9,684,778 B2	6/2017	Tharappel et al.	2010/0033313 A1	2/2010	Keady et al.	
9,711,062 B2	7/2017	Ellis et al.	2010/0075631 A1 *	3/2010	Black	H04M 1/05
9,729,979 B2	8/2017	Özden	2010/0166206 A1	7/2010	Macours	455/410
9,767,709 B2	9/2017	Ellis	2010/0203831 A1	8/2010	Muth	
9,848,257 B2	12/2017	Ambrose et al.	2010/0210212 A1	8/2010	Sato	
2001/0005197 A1	6/2001	Mishra et al.	2010/0290636 A1	11/2010	Mao et al.	
2001/0027121 A1	10/2001	Boesen	2010/0320961 A1	12/2010	Castillo et al.	
2001/0043707 A1	11/2001	Leedom	2011/0018731 A1	1/2011	Linsky et al.	
2001/0056350 A1	12/2001	Calderone et al.	2011/0103609 A1	5/2011	Pelland et al.	
2002/0002413 A1	1/2002	Tokue	2011/0137141 A1	6/2011	Razoumov et al.	
2002/0007510 A1	1/2002	Mann	2011/0140844 A1	6/2011	McGuire et al.	
2002/0010590 A1	1/2002	Lee	2011/0239497 A1	10/2011	McGuire et al.	
2002/0030637 A1	3/2002	Mann	2011/0286615 A1	11/2011	Olodort et al.	
2002/0046035 A1	4/2002	Kitahara et al.	2011/0293105 A1	12/2011	Arie et al.	
2002/0057810 A1	5/2002	Boesen	2012/0057740 A1	3/2012	Rosal	
2002/0076073 A1	6/2002	Taenzer et al.	2012/0155670 A1	6/2012	Rutschman	
2002/0118852 A1	8/2002	Boesen	2012/0159617 A1	6/2012	Wu et al.	
2003/0002705 A1	1/2003	Boesen	2012/0163626 A1	6/2012	Booij et al.	
2003/0065504 A1	4/2003	Kraemer et al.	2012/0197737 A1	8/2012	LeBoeuf et al.	
2003/0100331 A1	5/2003	Dress et al.	2012/0235883 A1	9/2012	Border et al.	
2003/0104806 A1	6/2003	Ruef et al.	2012/0309453 A1	12/2012	Maguire	
2003/0115068 A1	6/2003	Boesen	2013/0106454 A1	5/2013	Liu et al.	
2003/0125096 A1	7/2003	Boesen	2013/0154826 A1	6/2013	Ratajczyk	
2003/0218064 A1	11/2003	Conner et al.	2013/0178967 A1	7/2013	Mentz	
2004/0070564 A1	4/2004	Dawson et al.	2013/0200999 A1 *	8/2013	Spodak	G05B 1/01
2004/0102931 A1	5/2004	Ellis et al.	2013/0204617 A1	8/2013	Kuo et al.	340/5.65
2004/0160511 A1	8/2004	Boesen	2013/0293494 A1	11/2013	Reshef	
2005/0017842 A1	1/2005	Dematteo	2013/0316642 A1	11/2013	Newham	
2005/0043056 A1	2/2005	Boesen	2013/0346168 A1	12/2013	Zhou et al.	
2005/0094839 A1	5/2005	Gwee	2014/0004912 A1	1/2014	Rajakarunanayake	
2005/0125320 A1	6/2005	Boesen	2014/0014697 A1	1/2014	Schmierer et al.	
2005/0148883 A1	7/2005	Boesen	2014/0020089 A1	1/2014	Perini, II	
2005/0165663 A1	7/2005	Razoumov	2014/0072136 A1	3/2014	Tenenbaum et al.	
2005/0196009 A1	9/2005	Boesen	2014/0072146 A1	3/2014	Itkin et al.	
2005/0197063 A1	9/2005	White	2014/0073429 A1	3/2014	Meneses et al.	
2005/0212911 A1	9/2005	Marvit et al.	2014/0079257 A1	3/2014	Ruwe et al.	
2005/0251455 A1	11/2005	Boesen	2014/0106677 A1	4/2014	Altman	
2005/0266876 A1	12/2005	Boesen	2014/0122116 A1	5/2014	Smythe	
2006/0029246 A1	2/2006	Boesen	2014/0146973 A1	5/2014	Liu et al.	
2006/0073787 A1	4/2006	Lair et al.	2014/0153768 A1	6/2014	Hagen et al.	
2006/0074671 A1	4/2006	Farmaner et al.	2014/0163771 A1	6/2014	Demeniuk	
2006/0074808 A1	4/2006	Boesen	2014/0185828 A1	7/2014	Helbling	
2006/0166715 A1	7/2006	Engelen et al.	2014/0219467 A1	8/2014	Kurtz	
2006/0166716 A1	7/2006	Seshadri et al.	2014/0222462 A1	8/2014	Shakil et al.	
			2014/0235169 A1	8/2014	Parkinson et al.	

(56)

References Cited

U.S. PATENT DOCUMENTS

2014/0270227	A1	9/2014	Swanson	
2014/0270271	A1	9/2014	Dehe et al.	
2014/0276227	A1	9/2014	Pérez	
2014/0310595	A1	10/2014	Acharya et al.	
2014/0321682	A1	10/2014	Kofod-Hansen et al.	
2014/0335908	A1	11/2014	Krisch et al.	
2014/0348367	A1	11/2014	Vavrus et al.	
2015/0028996	A1	1/2015	Agrafioti et al.	
2015/0035643	A1	2/2015	Kursun	
2015/0036835	A1	2/2015	Chen	
2015/0056584	A1	2/2015	Boulware et al.	
2015/0110587	A1	4/2015	Hori	
2015/0148989	A1	5/2015	Cooper et al.	
2015/0181356	A1	6/2015	Krystek et al.	
2015/0230022	A1	8/2015	Sakai et al.	
2015/0245127	A1	8/2015	Shaffer	
2015/0256949	A1	9/2015	Vanpoucke et al.	
2015/0264472	A1	9/2015	Aase	
2015/0264501	A1	9/2015	Hu et al.	
2015/0317565	A1	11/2015	Li et al.	
2015/0358751	A1	12/2015	Deng et al.	
2015/0359436	A1	12/2015	Shim et al.	
2015/0364058	A1	12/2015	Lagree et al.	
2015/0373467	A1	12/2015	Gelter	
2015/0373474	A1	12/2015	Kraft et al.	
2015/0379251	A1 *	12/2015	Komaki	G06F 21/32 726/19
2016/0033280	A1	2/2016	Moore et al.	
2016/0034249	A1	2/2016	Lee et al.	
2016/0071526	A1	3/2016	Wingate et al.	
2016/0072558	A1	3/2016	Hirsch et al.	
2016/0073189	A1	3/2016	Lindén et al.	
2016/0094550	A1 *	3/2016	Bradley	H04W 4/80 726/7
2016/0100262	A1	4/2016	Inagaki	
2016/0119737	A1	4/2016	Mehnert et al.	
2016/0124707	A1	5/2016	Ermilov et al.	
2016/0125892	A1	5/2016	Bowen et al.	
2016/0140870	A1	5/2016	Connor	
2016/0142818	A1	5/2016	Park	
2016/0162259	A1	6/2016	Zhao et al.	
2016/0209691	A1	7/2016	Yang et al.	
2016/0253994	A1	9/2016	Panchapagesan et al.	
2016/0324478	A1	11/2016	Goldstein	
2016/0353196	A1	12/2016	Baker et al.	
2016/0360350	A1	12/2016	Watson et al.	
2017/0021257	A1	1/2017	Gilbert et al.	
2017/0046503	A1	2/2017	Cho et al.	
2017/0059152	A1	3/2017	Hirsch et al.	
2017/0060262	A1	3/2017	Hviid et al.	
2017/0060269	A1	3/2017	Förstner et al.	
2017/0061751	A1	3/2017	Loermann et al.	
2017/0061817	A1	3/2017	Mettler May	
2017/0062913	A1	3/2017	Hirsch et al.	
2017/0064426	A1	3/2017	Hviid	
2017/0064428	A1	3/2017	Hirsch	
2017/0064432	A1	3/2017	Hviid et al.	
2017/0064437	A1	3/2017	Hviid et al.	
2017/0078780	A1	3/2017	Qian et al.	
2017/0078785	A1	3/2017	Qian et al.	
2017/0100277	A1	4/2017	Ke	
2017/0108918	A1	4/2017	Boesen	
2017/0109131	A1	4/2017	Boesen	
2017/0110124	A1	4/2017	Boesen et al.	
2017/0110899	A1	4/2017	Boesen	
2017/0111723	A1	4/2017	Boesen	
2017/0111725	A1	4/2017	Boesen et al.	
2017/0111726	A1	4/2017	Martin et al.	
2017/0111740	A1	4/2017	Hviid et al.	
2017/0127168	A1	5/2017	Briggs et al.	
2017/0131094	A1	5/2017	Kulik	
2017/0142511	A1	5/2017	Dennis	
2017/0146801	A1	5/2017	Stempora	
2017/0150920	A1	6/2017	Chang et al.	
2017/0151085	A1	6/2017	Chang et al.	

2017/0151447	A1	6/2017	Boesen
2017/0151668	A1	6/2017	Boesen
2017/0151918	A1	6/2017	Boesen
2017/0151930	A1	6/2017	Boesen
2017/0151957	A1	6/2017	Boesen
2017/0151959	A1	6/2017	Boesen
2017/0153114	A1	6/2017	Boesen
2017/0153636	A1	6/2017	Boesen
2017/0154532	A1	6/2017	Boesen
2017/0155985	A1	6/2017	Boesen
2017/0155992	A1	6/2017	Perianu et al.
2017/0155993	A1	6/2017	Boesen
2017/0155997	A1	6/2017	Boesen
2017/0155998	A1	6/2017	Boesen
2017/0156000	A1	6/2017	Boesen
2017/0164890	A1	6/2017	Leip et al.
2017/0178631	A1	6/2017	Boesen
2017/0180842	A1	6/2017	Boesen
2017/0180843	A1	6/2017	Perianu et al.
2017/0180897	A1	6/2017	Perianu
2017/0188127	A1	6/2017	Perianu et al.
2017/0188132	A1	6/2017	Hirsch et al.
2017/0193978	A1	7/2017	Goldman
2017/0195829	A1	7/2017	Belverato et al.
2017/0208393	A1	7/2017	Boesen
2017/0214987	A1	7/2017	Boesen
2017/0215016	A1	7/2017	Dohmen et al.
2017/0230752	A1	8/2017	Dohmen et al.
2017/0251933	A1	9/2017	Braun et al.
2017/0257698	A1	9/2017	Boesen et al.
2017/0258329	A1	9/2017	Marsh
2017/0263236	A1	9/2017	Boesen et al.
2017/0263376	A1	9/2017	Verschuere et al.
2017/0266494	A1	9/2017	Crankson et al.
2017/0273622	A1	9/2017	Boesen
2017/0280257	A1	9/2017	Gordon et al.
2017/0301337	A1	10/2017	Golani et al.
2017/0361213	A1	12/2017	Goslin et al.
2017/0366233	A1	12/2017	Hviid et al.
2018/0007994	A1	1/2018	Boesen et al.
2018/0008194	A1	1/2018	Boesen
2018/0008198	A1	1/2018	Kingscott
2018/0009447	A1	1/2018	Boesen et al.
2018/0011006	A1	1/2018	Kingscott
2018/0011682	A1	1/2018	Milevski et al.
2018/0011994	A1	1/2018	Boesen
2018/0012228	A1	1/2018	Milevski et al.
2018/0013195	A1	1/2018	Hviid et al.
2018/0014102	A1	1/2018	Hirsch et al.
2018/0014103	A1	1/2018	Martin et al.
2018/0014104	A1	1/2018	Boesen et al.
2018/0014107	A1	1/2018	Razouane et al.
2018/0014108	A1	1/2018	Dragicevic et al.
2018/0014109	A1	1/2018	Boesen
2018/0014113	A1	1/2018	Boesen
2018/0014140	A1	1/2018	Milevski et al.
2018/0014436	A1	1/2018	Milevski
2018/0034951	A1	2/2018	Boesen
2018/0040093	A1	2/2018	Boesen
2018/0042501	A1	2/2018	Adi et al.

FOREIGN PATENT DOCUMENTS

CN	104837094	A	8/2015
EP	1469659	A1	10/2004
EP	1017252	A3	5/2006
EP	2903186	A1	8/2015
GB	2074817		4/1981
GB	2508226	A	5/2014
JP	06292195		10/1998
WO	2008103925	A1	8/2008
WO	2008113053	A1	9/2008
WO	2007034371	A3	11/2008
WO	2011001433	A2	1/2011
WO	2012071127	A1	5/2012
WO	2013134956	A1	9/2013
WO	2014046602	A1	3/2014
WO	2014043179	A3	7/2014
WO	2015061633	A2	4/2015

(56)

References Cited

FOREIGN PATENT DOCUMENTS

WO	2015110577	A1	7/2015
WO	2015110587	A1	7/2015
WO	2016032990	A1	3/2016
WO	2016187869	A1	12/2016

OTHER PUBLICATIONS

Stretchgoal—Windows Phone Support (Feb. 17, 2014).

The Dash + The Charging Case & The BRAGI News (Feb. 21, 2014).

The Dash—A Word From Our Software, Mechanical and Acoustics Team + An Update (Mar. 11, 2014).

Update From BRAGI—\$3,000,000—Yipee (Mar. 22, 2014).

Weisiger, “Conjugated Hyperbilirubinemia”, Jan. 5, 2016.

Wertner et al., “Analysis of fundamental frequency, jitter, shimmer and vocal intensity in children with phonological disorders”, V. 71, n.5, 582-588, Sep./Oct. 2005; Brazilian Journal of Othrinolaryngology.

Wikipedia, “Gamebook”, <https://en.wikipedia.org/wiki/Gamebook>, Sep. 3, 2017, 5 pages.

Wikipedia, “Kinect”, <https://en.wikipedia.org/wiki/Kinect>, 18 pages, (Sep. 9, 2017).

Wikipedia, “Wii Balance Board”, https://en.wikipedia.org/wiki/Wii_Balance_Board, 3 pages, (Jul. 20, 2017).

Akermans, “Acoustic Ear Recognition for Person Identification”, Automatic Identification Advanced Technologies, 2005 pp. 219-223.

Alzahrani et al: “A Multi-Channel Opto-Electronic Sensor to Accurately Monitor Heart Rate against Motion Artefact during Exercise”, Sensors, vol. 15, No. 10, Oct. 12, 2015, pp. 25681-25702, XPO55334602, DOI: 10.3390/s151025681 the whole document.

Announcing the \$3,333,333 Stretch Goal (Feb. 24, 2014).

Ben Coxworth: “Graphene-based ink could enable low-cost, foldable electronics”, “Journal of Physical Chemistry Letters”, Northwestern University, (May 22, 2013).

Blain: “World’s first graphene speaker already superior to Sennheiser MX400”, <http://www.gizmag.com/graphene-speaker-beats-sennheiser-mx400/31660>, (Apr. 15, 2014).

BMW, “BMW introduces BMW Connected—The personalized digital assistant”, <http://bmwblog.com/2016/01/05/bmw-introduces-bmw-connected-the-personalized-digital-assistant/>, (Jan. 5, 2016).

BRAGI is on Facebook (2014).

BRAGI Update—Arrival of Prototype Chassis Parts—More People—Awesomeness (May 13, 2014).

BRAGI Update—Chinese New Year, Design Verification, Charging Case, More People, Timeline (Mar. 6, 2015).

BRAGI Update—First Sleeves From Prototype Tool—Software Development Kit (Jun. 5, 2014).

BRAGI Update—Lets Get Ready to Rumble, A Lot to Be Done Over Christmas (Dec. 22, 2014).

BRAGI Update—Memories From April—Update on Progress (Sep. 16, 2014).

BRAGI Update—Memories from May—Update on Progress—Sweet (Oct. 13, 2014).

BRAGI Update—Memories From One Month Before Kickstarter—Update on Progress (Jul. 10, 2014).

BRAGI Update—Memories From the First Month of Kickstarter—Update on Progress (Aug. 1, 2014).

BRAGI Update—Memories From the Second Month of Kickstarter—Update on Progress (Aug. 22, 2014).

BRAGI Update—New People @BRAGI—Prototypes (Jun. 26, 2014).

BRAGI Update—Office Tour, Tour to China, Tour to CES (Dec. 11, 2014).

BRAGI Update—Status on Wireless, Bits and Pieces, Testing—Oh Yeah, Timeline (Apr. 24, 2015).

BRAGI Update—The App Preview, The Charger, The SDK, BRAGI Funding and Chinese New Year (Feb. 11, 2015).

BRAGI Update—What We Did Over Christmas, Las Vegas & CES (Jan. 19, 2014).

BRAGI Update—Years of Development, Moments of Utter Joy and Finishing What We Started (Jun. 5, 2015).

BRAGI Update—Alpha 5 and Back to China, Backer Day, On Track (May 16, 2015).

BRAGI Update—Beta2 Production and Factory Line (Aug. 20, 2015).

BRAGI Update—Certifications, Production, Ramping Up.

BRAGI Update—Developer Units Shipping and Status (Oct. 5, 2015).

BRAGI Update—Developer Units Started Shipping and Status (Oct. 19, 2015).

BRAGI Update—Developer Units, Investment, Story and Status (Nov. 2, 2015).

BRAGI Update—Getting Close (Aug. 6, 2015).

BRAGI Update—On Track, Design Verification, How It Works and What’s Next (Jul. 15, 2015).

BRAGI Update—On Track, On Track and Gems Overview.

BRAGI Update—Status on Wireless, Supply, Timeline and Open House @BRAGI (Apr. 1, 2015).

BRAGI Update—Unpacking Video, Reviews on Audio Perform and Boy Are We Getting Close (Sep. 10, 2015).

Healthcare Risk Management Review, “Nuance updates computer-assisted physician documentation solution” (Oct. 20, 2016).

Hoffman, “How to Use Android Beam to Wirelessly Transfer Content Between Devices”, (Feb. 22, 2013).

Hoyt et. al., “Lessons Learned from Implementation of Voice Recognition for Documentation in the Military Electronic Health Record System”, The American Health Information Management Association (2017).

Hyundai Motor America, “Hyundai Motor Company Introduces a Health + Mobility Concept for Wellness in Mobility”, Fountain Valley, California (2017).

International Search Report & Written Opinion, PCT/EP16/70245 (dated Nov. 16, 2016).

International Search Report & Written Opinion, PCT/EP2016/070231 (dated Nov. 18, 2016).

International Search Report & Written Opinion, PCT/EP2016/070247 (dated Nov. 18, 2016).

International Search Report & Written Opinion, PCT/EP2016/07216 (dated Oct. 18, 2016).

International Search Report and Written Opinion, PCT/EP2016/070228 (dated Jan. 9, 2017).

Jain A et al: “Score normalization in multimodal biometric systems”, Pattern Recognition, Elsevier, GB, vol. 38, No. 12, Dec. 31, 2005, pp. 2270-2285, XPO27610849, ISSN: 0031-3203.

Last Push Before the Kickstarter Campaign Ends on Monday 4pm CET (Mar. 28, 2014).

Lovejoy: “Touch ID built into iPhone display one step closer as third-party company announces new tech”, <http://9to5mac.com/2015/07/21/virtualhomebutton/> (Jul. 21, 2015).

Nemanja Paunovic et al, “A methodology for testing complex professional electronic systems”, Serbian Journal of Electrical Engineering, vol. 9, No. 1, Feb. 1, 2012, pp. 71-80, XPO55317584, YU.

Nigel Whitfield: “Fake tape detectors, ‘from the stands’ footie and UGH? Internet of Things in my set-top box”, http://www.theregister.co.uk/2014/09/24/ibc_round_up_object_audio_dlna_iot/ (Sep. 24, 2014).

Nuance, “ING Netherlands Launches Voice Biometrics Payment System in the Mobile Banking App Powered by Nuance”, <https://www.nuance.com/about-us/newsroom/press-releases/ing-netherlands-launches-nuance-voice-biometrics.html>, 4 pages (Jul. 28, 2015).

Staab, Wayne J., et al., “A One-Size Disposable Hearing Aid is Introduced”, The Hearing Journal 53(4):36-41 Apr. 2000.

Stretchgoal—Its Your Dash (Feb. 14, 2014).

* cited by examiner




FIG. 1




FIG. 2

BIOMETRIC INTERFACE SYSTEM AND METHOD**PRIORITY STATEMENT**

This application is a continuation of and claims priority to U.S. patent application Ser. No. 15/497,065 filed on Apr. 25, 2017 titled Biometric Interface System and Method which claims priority to U.S. Provisional Patent Application No. 62/328,915 filed on Apr. 28, 2016 titled Biometric Interface System and Method all of which are hereby incorporated by reference in their entireties.

FIELD OF THE INVENTION

The present invention relates to wearable devices especially earpieces. More particularly, but not exclusively, the present invention relates to authentication of such devices.

BACKGROUND

Data authentication for wearable devices remains a challenge. The limited size of most wearable devices makes it difficult to design a sound and effective user-friendly data authentication system. One possible method to overcome this relates to the use of fingerprint analysis.

SUMMARY

It is a primary object, feature, or advantage to improve over the state of the art.

It is a further object, feature, or advantage to use fingerprint analysis to provide data authentication for wearable devices including earpieces.

It is a further object, feature, or advantage to provide for fingerprint analysis and verification using a contact surface of an earpiece wearable.

It is another object, feature, or advantage to use ultrasound, infrared, or radar sensor units to determine a fingerprint analysis on the surface of the device and in performing the analysis to use data stored on the device or stored elsewhere.

It is a further object, feature, or advantage to allow for access to programming on a device or access to remote programming provided through a device to only be accessible once a verification of identity is provided.

It is a still further object, feature, or advantage to allow for coordination of fingerprint identification with other biometric identity criteria.

Another object, feature, or advantage is to allow for storage of fingerprints in an isolated segment of the device away from capturable data.

Yet another object, feature, or advantage is to allow for biometric data to be stored in the cloud for verification of user identity.

A further object, feature, or advantage is to allow for a split verification scheme for user identity so neither the cloud nor the device alone verify, only the combination of the two can be used to identify a user.

One or more of these and/or other objects, features, or advantages of the present invention will become apparent from the specification and following claims. No single embodiment need provide every object, feature, or advantage. Different embodiments may have different objects, features, or advantages. Therefore, the present invention is not to be limited to or by any object, feature, or advantage stated herein.

According to another aspect, an earpiece is provided. The earpiece includes an earpiece housing, a processor disposed within the earpiece, and a fingerprint sensor operatively connected to the processor. The processor is configured to receive fingerprint data from the fingerprint sensor and compare the fingerprint data to stored fingerprint data and/or to provide authentication of a user of the earpiece.

According to another aspect, an earpiece wearable includes an earpiece housing, at least one speaker, at least one microphone, a processor disposed within the earpiece housing and operatively connected to the at least one speaker and the at least one microphone, and a sensor operatively connected to the processor. The processor is configured to receive fingerprint data from the sensor at a contact surface on the earpiece housing and analyze the fingerprint data using stored fingerprint authentication data to make an authentication decision based on the fingerprint data. The earpiece may further include a data storage device disposed within the ear piece housing and operatively connected to the processor, wherein the stored fingerprint authentication data is stored within the data storage device. The earpiece may further include a radio transceiver disposed within the earpiece housing and operatively connected to the processor, wherein the stored fingerprint authentication data is stored at a remote location and accessible over a network through the radio transceiver. The earpiece may include both a data storage device disposed within the ear piece housing and operatively connected to the processor, wherein a first portion of the stored fingerprint authentication data is stored within the data storage device and a radio transceiver disposed within the earpiece housing and operatively connected to the processor, wherein a second portion of the stored fingerprint authentication data is stored at a remote location and accessible over a network through the radio transceiver. Both the first portion of the stored fingerprint authentication data and the second portion of the stored fingerprint authentication data may be needed by the processor to make the authentication decision based on the fingerprint data. The earpiece may further include a gesture control interface operatively connected to the processor, wherein the gesture control interface is configured to receive gestures. The sensor may be an optical sensor and the optical sensor may be used by the gesture control interface to receive the gestures and to sense the fingerprint data. The sensor may be an ultrasound sensor, radar sensor or other type of sensor. The processor may be further configured to process audio data from the at least one microphone and wherein the authentication decision is based on the fingerprint data and the audio data. The processor may also be further configured to process pulse oximetry data from a pulse oximeter disposed within the housing and operatively connected to the processor and the authentication decision may be based on the fingerprint data and the pulse oximetry data.

According to another aspect, a method is provided for authenticating a user of an earpiece having an earpiece housing, at least one speaker, at least one microphone, a processor disposed within the earpiece housing and operatively connected to the at least one speaker and the at least one microphone, and a sensor operatively connected to the processor. The method includes acquiring fingerprint data using the sensor from a finger of a user contacting a fingerprint contact area on the earpiece housing and analyzing the fingerprint data using stored fingerprint authentication data to make an authentication decision based on the fingerprint data. The stored fingerprint authentication data may be stored within the data storage device. The earpiece

may further include a radio transceiver disposed within the earpiece housing and operatively connected to the processor, and the method may include accessing the stored fingerprint authentication data from a remote location over a network and through the radio transceiver. The method may further provide for accessing a first portion of the stored fingerprint authentication from the data storage device and accessing a second portion of the stored fingerprint authentication data from a remote location over a network and through the radio transceiver.

BRIEF DESCRIPTION OF THE DRAWINGS

FIG. 1 illustrates one example of a system including an earpiece wearable with a fingerprint sensor used for authentication.

FIG. 2 is another block diagram illustrating an earpiece wearable.

DETAILED DESCRIPTION

A wearable device and related systems and methods are shown which allow for the authentication of a user's identity using fingerprint data alone and/or in combination with additional biometric data. FIG. 1 illustrates a wearable device or system which includes a first earpiece 10A with an earpiece housing 12A and a second earpiece 10B with an earpiece housing 12B. A fingerprint contact area 13A is shown for the first earpiece 10A and a fingerprint contact area 13B is shown for the second earpiece 10B. When a finger of a user is presented at one of the finger contact areas 13A, 13B, fingerprint data is acquired which may then be used to perform authentication of a user. One or more sensors are associated with each fingerprint contact area 13A, 13B. Such sensors may also be used for other purposes as well.

To perform authentication, the fingerprint data obtained from a user at the one or more finger contact areas 13A, 13B, may be compared with data stored within the first earpiece 10A or the second earpiece 10B. The data may be stored in an isolated segment of the device away from capturable data to enhance security. The data may be encrypted to enhance security. Alternatively, the fingerprint data may be compared with data stored on another device such as a mobile device 11, or data stored remotely such as in a database 17 in operative communication with a server platform 15 which may be accessible through network 19 such as the Internet. Fingerprint data or other authentication data may be stored either at the wearable device(s) 10, a mobile device 11, at a remote database 17, or at a combination of locations. For example, a portion of the authentication data may be stored at the wearable device 10A, 10B and another portion of the authentication data may be stored at the mobile device 11 or the remote database 17 to provide additional security. In this type of split verification scheme for user identity neither the cloud nor the device alone can provide verification, instead only a combination of the two would allow for verification or authentication of a user. Once authentication occurs all or portions of device operations or programming may become accessible to a user.

FIG. 2 illustrates a wearable device such as an earpiece 10 with an ear piece housing 12. A plurality of sensors 14 are operatively connected to one or more processors 18. The sensors 14 may include an ultrasound sensor 34, an infrared sensor 36, a radar sensor unit 38, or other types of sensors. In addition, one or more microphones 20 may be present. The microphones 20 may include one or more bone micro-

phones and/or one or more air conduction microphones. One or more speakers 24 are also present and are operatively connected to the processor(s) 18. A data storage device 16 may also be operatively connected to the processor(s) 18 and may be used for storing fingerprint data or other biometric data which is used as a part of an authentication processor. A gesture control interface 22 may also be operatively connected to the processor(s) 18. The gesture control interface 22 may include one or more emitters 42 and detectors 44. For example, the gesture control interface 22 may include optical emitters and detectors which are used to determine gestures made by a user of the earpiece. Thus, for example, the user may tap the earpiece, with a single tap or multiple taps, swipe across the ear piece, or tap and hold their finger at a surface of the earpiece. The same fingerprint contact area may be used for receiving gestures as well as for reading a fingerprint of a user. The same sensors such as optical emitters and detectors may be used to sense gestures as well as to sense fingerprints.

Instead of using the emitters 42 and detectors 44 of the gesture control interface 22, fingerprints may be detected using other types of sensors such as the ultrasound sensor 34, the infrared sensor 36, or the radar sensor 38. Each of these sensors may also be used for other purposes as well in addition to detecting fingerprints.

One or more LEDs 30 may be operatively connected to the processor(s) 18 and used for conveying information to a user or others. In addition, one or more transceivers may be present and operatively connected to the processor(s) 18. A first transceiver 26 may be a near field magnetic induction (NFMI) or other type of transceiver. One use of such a transceiver is for communication between wearable devices, such as communication between a left earpiece and a right earpiece. A radio transceiver 28 is also present and operatively connected to the processor(s) 18. The radio transceiver 28 may be a Bluetooth transceiver, Wi-Fi transceiver, or other type of radio transceiver.

Returning to the sensors 14, one or more biometric sensors may be present such as a pulse oximeter 35. The pulse oximeter 35 may be used to measure pulse of a user. It is to be further understood characteristics of the pulse of a user may be used to further authenticate a user. For example, heart rate variability as determined using the pulse oximeter 35 or otherwise may be used to authenticate a user. An inertial sensor 37 is also shown. It is also to be understood the inertial sensor 37 may be used to detect gait of a user or other motion of a user which may be used in authenticating a user. It is to be further understood voice samples of a user received at one or more of the microphones 20 may be used to authenticate a user through voice analysis. Thus, in addition to fingerprint data other types of biometric data may be used to provide for further authentication of a user. Although various types of biometric sensors are shown and described, it is to be understood other types of biometric sensors may be used.

It is to be further understood additional or secondary authentication may be performed in several different ways depending upon the type of wearable device and the sensors present. For example, where voice is used as a type of secondary authentication, a determination can be made as to whether the voice of the user matches the voice of the known user. Alternatively, or in addition, the user may be asked to provide a passphrase. Similarly, where gestures are used, a user may be asked to input a series of gestures which serves as a password or passphrase to authenticate the user. Thus, it is to be understood voice detection, heart rate variability, predetermined vocal passwords, audio playback tonal pass-

5

word selections, or other types of authentication may be used in addition to the fingerprint analysis. It is to be further understood different levels of access to data or programming within the earpiece or functionality provided by the earpiece may be provided with different types of authentication. It is further to be understood user verification at an earpiece or other wearable device may be used within a connected environment.

In operation, a fingerprint is sensed with one or more sensors. For example, a user may press their finger against a fingerprint contact area of an earpiece. Sensors such as optical sensors may be used to acquire fingerprint data such as data sufficient to define an image of a fingerprint or to describe fingerprint features. Once acquired, this data may be compared to other data identifying one or more authorized users of the earpiece. Such data may be present within the earpiece such as in a segregated portion of a memory not generally otherwise accessible. If the fingerprint data is a match to an authorized user then the user may be authenticated and provided access to the earpiece, be allowed to modify operational states of the earpiece such as to access a program or perform functions. If not, then the user will not be able to use the earpiece, have limited access to the earpiece, or be required to otherwise authenticate themselves. The fingerprint authentication may serve as an initial authentication and additional authentication may be required. In addition, a user may be required to re-authenticate when performing various functions if additional security requirements are associated with those functions. Where the gesture interface is used in providing for the fingerprint sensing, at times when the gesture interface is used to provide a gesture, fingerprint data may be collected at this time to re-authenticate a user via fingerprint in the background without requiring any additional activity from the user unless the authentication process fails.

Therefore, various methods, systems, and apparatus have been shown and described. Although various embodiments have been shown the present invention contemplates numerous options, variations, and alternatives including variations in the type of wearable device, whether authentication occurs on board the wearable device or at a remote location, the type of authentication data included such as fingerprint, voiceprint, gesture or gesture sequence, or other type of authentication data, plus other options, variations, and alternatives.

What is claimed is:

1. An earpiece for authenticating users using stored fingerprint authentication data, the earpiece comprising:

an earpiece housing;

at least one speaker;

at least one microphone;

a processor disposed within the earpiece housing and operatively connected to the at least one speaker and the at least one microphone, wherein once authentication occurs all or portions of earpiece operation or programming become accessible to a user;

a plurality of sensors operatively connected to the processor;

a data storage device disposed within the earpiece housing and operatively connected to the processor, wherein a first portion of the stored fingerprint authentication data is stored on the data storage device;

a radio transceiver disposed within the earpiece housing and operatively connected to the processor, wherein a second portion of the stored fingerprint authentication data is stored at a remote location and accessible over a network through the radio transceiver;

6

wherein the processor is configured to receive fingerprint data from a first sensor at a fingerprint contact surface on the earpiece housing and analyze the fingerprint data using the first portion of the stored fingerprint authentication data and the second portion of the stored fingerprint authentication data; and

wherein the processor is configured to receive users biometric data from a second sensor and make an authentication decision based on the fingerprint data and the biometric data.

2. The earpiece of claim 1 further comprising a gesture control interface operatively connected to the processor, wherein the gesture control interface is configured to receive gestures.

3. The earpiece of claim 2 wherein the first sensor is an optical sensor and wherein the optical sensor is used by the gesture control interface to receive the gestures and to sense the fingerprint data.

4. The earpiece of claim 1 wherein the first sensor is an ultrasound sensor.

5. The earpiece of claim 1 wherein the processor is further configured to process audio data from the at least one microphone and wherein the authentication decision is based on the fingerprint data and the audio data.

6. The earpiece of claim 1 wherein the processor is further configured to process pulse oximetry data from a pulse oximeter disposed within the earpiece housing and operatively connected to the processor and wherein the authentication decision is based on the fingerprint data and the pulse oximetry data.

7. A method for authenticating a user of an earpiece comprising an earpiece housing, a processor disposed within the earpiece housing, a plurality of sensors operatively connected to the processor, at least one speaker operatively connected to the processor, at least one microphone operatively connected to the processor, a data storage device disposed within the earpiece housing and operatively connected to the processor, and a radio transceiver disposed within the earpiece housing and operatively connected to the processor, the method comprising:

acquiring fingerprint data using a first sensor from a finger of the user contacting a fingerprint contact area on the earpiece housing;

acquiring biometric data of the user using a second sensor;

accessing a first portion of stored fingerprint authentication data stored on the data storage device;

accessing a second portion of stored fingerprint authentication data stored at a remote location and accessible over a network through the radio transceiver;

accessing stored user biometric data stored on the data storage device; and

analyzing the fingerprint data using the first and second stored fingerprint authentication data and analyzing the biometric data using the stored biometric data to make an authentication decision based on the fingerprint data and the biometric data.

8. The method of claim 7, wherein the second sensor is a pulse oximeter.

9. The method of claim 7, wherein the second sensor is an inertial sensor.

10. The method of claim 7, wherein the second sensor is a microphone.

11. The method of claim 7, wherein the first sensor is an ultrasound sensor.

12. The method of claim 7, wherein the first sensor is a radar sensor.

7

13. The method of claim 7, wherein the first sensor is an infrared sensor.

14. An earpiece for authenticating a user, the earpiece comprising:

an earpiece housing;

at least one speaker;

at least one microphone;

a processor disposed within the earpiece housing and operatively connected to the at least one speaker and the at least one microphone;

a first and second sensor operatively connected to the processor;

a data storage device disposed within the earpiece housing and operatively connected to the processor, wherein a first portion of stored finger print authentication data and biometric authentication data is stored on the data storage device;

a radio transceiver disposed within the earpiece housing and operatively connected to the processor, wherein a second portion of the stored fingerprint authentication data is stored at a remote location and accessible over a network through the radio transceiver;

wherein the processor is configured to receive fingerprint data from a first sensor and analyze the fingerprint data using the first portion of the stored fingerprint authentication data and the second portion of the stored fingerprint authentication data;

8

wherein the processor is configured to receive biometric data from a second sensor and analyze the biometric data using the stored biometric authentication data; and wherein the processor allows access to the earpiece if the processor authenticates a user's identity by both the first and second portion of the stored fingerprint data and the biometric data.

15. The earpiece of claim 14 further comprising a gesture control interface operatively connected to the processor, wherein the gesture control interface is configured to receive gestures.

16. The earpiece of claim 15 wherein the first sensor is an optical sensor and wherein the optical sensor is used by the gesture control interface to receive the gestures and to sense the first and second portion of the stored fingerprint data.

17. The earpiece of claim 14 wherein the first sensor is an ultrasound sensor.

18. The earpiece of claim 14 wherein the processor is further configured to process audio data from the at least one microphone and wherein the authentication decision is based on the fingerprint data, biometric data and the audio data.

19. The earpiece of claim 14 wherein the processor is further configured to process pulse oximetry data from a pulse oximeter disposed within the earpiece housing and operatively connected to the processor and wherein the authentication decision is based on the fingerprint data and the pulse oximetry data.

* * * * *

专利名称(译)	生物识别界面系统和方法		
公开(公告)号	US10169561	公开(公告)日	2019-01-01
申请号	US15/951063	申请日	2018-04-11
申请(专利权)人(译)	BRAGI GMBH		
当前申请(专利权)人(译)	BRAGI GMBH		
[标]发明人	RAZOUANE MOHAMED ALI BOESEN PETER VINCENT		
发明人	RAZOUANE, MOHAMED ALI BOESEN, PETER VINCENT		
IPC分类号	G06F21/32 H04R1/10 G06F21/40 G07C9/00 A61B5/1172 G06F21/83 H04R5/04 A61B5/117 A61B5/00 H04Q9/00 G06F21/34 G05B19/00 G06F3/01 A61B5/11 A61B5/024		
CPC分类号	G06F21/32 A61B5/117 A61B5/1172 A61B5/6803 G06F17/30289 G06F21/40 G06F21/83 G07C9/00071 G07C9/00158 H04R1/1016 H04R5/04 A61B5/02416 H04Q9/00 A61B5/02405 A61B5/11 G05B19/00 G06F3/017 G06F17/30294 G06F17/30595 G06F21/34 G06F2221/2147 G06F16/21 G06F16/212 G06F16/284 G07C9/25 G07C9/37		
审查员(译)	BARAKAT , MOHAMED		
优先权	62/328915 2016-04-28 US		
其他公开文献	US20180232512A1		
外部链接	Espacenet		

摘要(译)

一种系统，包括：可穿戴设备，具有至少一个传感器，被配置为确定用户的指纹数据；至少一个数据存储设备，包含认证数据；以及至少一个处理器，被配置为将用户的指纹数据与认证数据进行比较以认证用户。一种认证可穿戴设备的方法包括：产生指纹，利用一个或多个传感器确定从指纹导出的指纹数据，将指纹数据与一个或多个数据存储设备上的认证数据进行比较，以及如果指纹数据和指纹数据，则认证用户。验证数据匹配。

