



US010194807B2

(12) **United States Patent**
Okamura

(10) **Patent No.:** **US 10,194,807 B2**
(45) **Date of Patent:** **Feb. 5, 2019**

(54) **BODY SURFACE THERMOMETER AND WEARABLE TEMPERATURE MEASURING DEVICE**

(71) Applicant: **BOE TECHNOLOGY GROUP CO., LTD.**, Beijing (CN)

(72) Inventor: **Masakazu Okamura**, Beijing (CN)

(73) Assignee: **BOE TECHNOLOGY GROUP CO., LTD.**, Beijing (CN)

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 421 days.

(21) Appl. No.: **14/443,807**

(22) PCT Filed: **Sep. 30, 2014**

(86) PCT No.: **PCT/CN2014/087901**

§ 371 (c)(1),

(2) Date: **May 19, 2015**

(87) PCT Pub. No.: **WO2015/192539**

PCT Pub. Date: **Dec. 23, 2015**

(65) **Prior Publication Data**

US 2016/0256055 A1 Sep. 8, 2016

(30) **Foreign Application Priority Data**

Jun. 20, 2014 (CN) 2014 1 0281370

(51) **Int. Cl.**
A61B 5/01 (2006.01)
A61B 5/00 (2006.01)

(Continued)

(52) **U.S. Cl.**
CPC **A61B 5/01** (2013.01); **A61B 5/0075** (2013.01); **A61B 5/6831** (2013.01);
(Continued)

(58) **Field of Classification Search**

None

See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

4,797,840 A * 1/1989 Fraden G01J 5/0022
374/133
5,316,854 A * 5/1994 Lin C03C 17/007
106/287.13

(Continued)

FOREIGN PATENT DOCUMENTS

CN 1113319 A 12/1995
CN 101999887 A 4/2011

(Continued)

OTHER PUBLICATIONS

Third Chinese Office Action dated Jul. 25, 2016; Appln. No. 201410281370.7.

(Continued)

Primary Examiner — Michael Carey


Assistant Examiner — Farouk Bruce

(74) *Attorney, Agent, or Firm* — Ladas & Parry LLP

(57) **ABSTRACT**

A body surface thermometer and a wearable temperature measuring device are disclosed. The body surface thermometer includes an infrared temperature sensor and a shielding protective hood disposed outside the infrared temperature sensor, and the shielding protective hood is an infrared ray shielding protective hood. With the body surface thermometer, the measuring precision of surface temperature of a target object can be promoted, thereby raising the freedom degree of test.

6 Claims, 3 Drawing Sheets



- (51) **Int. Cl.**
G01J 5/04 (2006.01)
G01J 5/00 (2006.01)
G02B 5/20 (2006.01)
G01K 13/00 (2006.01)
G01J 5/06 (2006.01)

- (52) **U.S. Cl.**
 CPC *G01J 5/0025* (2013.01); *G01J 5/048*
 (2013.01); *A61B 5/6824* (2013.01); *A61B*
5/742 (2013.01); *A61B 2562/0271* (2013.01);
A61B 2562/185 (2013.01); *G01J 2005/065*
 (2013.01); *G01K 13/004* (2013.01); *G02B*
5/208 (2013.01)

(56) **References Cited**

U.S. PATENT DOCUMENTS

- 5,645,349 A 7/1997 Fraden
 5,672,931 A * 9/1997 Kiss F21V 13/08
 313/24
 5,693,942 A * 12/1997 Endo G01J 5/20
 250/338.1
 5,860,740 A * 1/1999 Fujima G01J 5/02
 368/11
 5,893,643 A * 4/1999 Kumar H01L 21/67248
 118/712
 6,585,684 B1 * 7/2003 Hughett A61N 5/1007
 604/131
 6,846,106 B1 1/2005 Chen et al.
 2007/0118045 A1 5/2007 Naghavi et al.
 2007/0293792 A1 * 12/2007 Sliwa A61B 5/11
 600/587

- 2011/0030728 A1 * 2/2011 Semmer B08B 3/02
 134/18
 2011/0228811 A1 * 9/2011 Fraden G01J 5/061
 374/130
 2012/0101350 A1 4/2012 Bychkov
 2012/0316459 A1 12/2012 Abreu
 2013/0308676 A1 11/2013 Ha
 2014/0018686 A1 1/2014 Medelius et al.

FOREIGN PATENT DOCUMENTS

- CN 102141442 A 8/2011
 CN 102940494 A 2/2013
 CN 103054560 A 4/2013
 CN 104000571 A 8/2014
 CN 104055502 A 9/2014
 EP 1061348 A2 12/2000
 JP 0454935 A 2/1992
 JP 2012-098041 A 5/2012
 WO 2011057089 A1 5/2011

OTHER PUBLICATIONS

- International Search Report & Written Opinion Appln. No. PCT/
 CN2014/087901; dated Mar. 27, 2015.
 First Chinese Office Action Appln. No. 201410281370.7; dated
 Aug. 25, 2015.
 Second Chinese Office Action Appln. No. 201410281370.7; dated
 Mar. 10, 2016.
 Extended European Search Report dated Feb. 26, 2018; Appln. No.
 14859313.0.

* cited by examiner




FIG.1




FIG.2




FIG.3




FIG.4




Fig. 5

1

BODY SURFACE THERMOMETER AND WEARABLE TEMPERATURE MEASURING DEVICE

TECHNICAL FIELD

Embodiments of the present invention relate to a body surface thermometer and a wearable temperature measuring device.

BACKGROUND

In the field of health and medicine, body temperature or body surface temperature is a piece of important information for human signs.

In the past, people designed and used various kinds of thermometers. However, in order that the influence of ambient temperature can be avoided so as to measure the temperature more accurately, it usually takes a very long time to conduct measurements. As temperature measuring methods, there are contact type and non-contact type. For a contact type, the body temperature is measured by allowing a temperature sensor unit of a thermometer and the body surface temperature to reach an equilibrium state. In such a case, in order not to receive the image of surroundings, the measurement will be generally made in a mouth, or under an armpit. For non-contact type, infrared rays radiated from the body surface are detected and converted into the body temperature. In such a case, in order to avoid the influence of the surrounding infrared rays, the measurement will usually be made in an ear.

Along with the continued research, for the sake of clearly understanding the state of a body, people begin to consider measuring the body surface temperature at the wrist or the like, and put forward a wrist type thermometer. When the wrist type thermometer is compared with common thermometers used in a mouth, under an armpit and in an ear, there are many situations of incomplete contact with the body surface in its actual use. Furthermore, because it is worn at the wrist and is easily affected by the surroundings, the measuring precision is not high.

SUMMARY

According to embodiments of the present invention, there is provided a body surface thermometer, which includes an infrared temperature sensor and a shielding protective hood disposed outside the infrared temperature sensor, and the shielding protective hood is an infrared ray shielding protective hood.

For example, the shielding protective hood has an opening on one side acting to cover over a body surface whose temperature is to be measured, and the infrared temperature sensor is located on an inner wall of the shielding protective hood that directly faces the opening.

For example, the shielding protective hood is made of quartz glass.

For example, an outer surface of the shielding protective hood is coated with an ultraviolet ray transmission proofing layer.

For example, an outer surface of the shielding protective hood is coated with a visible light transmission proofing layer.

For example, the body surface thermometer further includes a measurement display unit, connected to the infrared temperature sensor, which acts to display measured results of the body surface temperature.

2

According to an embodiment of the invention, there is further provided a wearable temperature measuring device, which includes a wearing body and a body surface thermometer disposed on the wearing body, the body surface thermometer being the body surface thermometer as any of above-mentioned items, with the measurement display unit connected to the infrared temperature sensor being mounted on the wearing body.

For example, the wearing body is a flexible circular ring.

BRIEF DESCRIPTION OF THE DRAWINGS

In order to illustrate the technical solution of the embodiments of the invention more clearly, the drawings of the embodiments will be briefly described below; it is obvious that the drawings as described below are only related to some embodiments of the invention, but not limitative of the invention.

FIG. 1 is a schematic diagram illustrating the transmissivity-wavelength characteristics of different materials with regard to glass;

FIG. 2 is a structurally schematic view illustrating a body surface thermometer according to an embodiment of the invention;

FIG. 3 is a schematic view illustrating application of a body surface thermometer to the measurement of the body surface temperature according to an embodiment of the invention;

FIG. 4 is a flowchart illustrating the temperature measurement of a body surface thermometer according to an embodiment of the invention; and

FIG. 5 is a schematic view illustrating a structure of a wearable temperature measuring device according to an embodiment of the invention.

DETAILED DESCRIPTION

In order to make objects, technical details and advantages of the embodiments of the invention apparent, hereinafter, the technical solutions of the embodiments of the invention will be described in a clearly and fully understandable way in connection with the drawings related to the embodiments of the invention. It is obvious that the described embodiments are just a part but not all of the embodiments of the invention. Based on the described embodiments of the invention, those ordinarily skilled in the art can obtain other embodiment(s), without any inventive work, which should be within the scope sought for protection by the invention.

According to the relationship between an absolute temperature T and the wavelength λ of radiated infrared rays:

$$\lambda(\mu\text{m})=2897/T$$

If the body temperature is 35°C , the wavelength of radiated infrared rays is about $9.4\mu\text{m}$; when the body temperature is 4°C , the wavelength of radiated infrared rays is about $9.2\mu\text{m}$; and when the normal temperature value of the human body's surface is between 36°C and 37°C , infrared rays at $9.5\mu\text{m}$ or so will be radiated.

Referring to that shown in FIG. 1, for common quartz glass, light in the ultraviolet domain or visible light domain are easy to be transmitted through it, and with respect to far infrared rays above $5\mu\text{m}$, it has such a light transmission characteristics that rays are not easy to be transmitted through it.

Referring to that shown in FIG. 2, a body surface thermometer according to an embodiment includes an infrared temperature sensor 10 and a shielding protective hood 20

3

disposed outside the infrared temperature sensor **10**, and the shielding protective hood is an infrared-ray shielding protective hood. For example, the shielding protective hood **20** surrounds the infrared temperature sensor **10**, but a measuring opening is set aside. For example, the shielding protective hood **20** is arranged to be a tank-shaped structure that is opened on one side, and the infrared temperature sensor **10** is disposed on an inner wall of the shielding protective hood **20**. When it is used for measurement of body surface temperature, the opening is made to cover a body surface, and the infrared temperature sensor does not contact with the body surface, so as to make a non-contact type measurement.

For example, in order to enhance the precision of the temperature measurement, the infrared temperature sensor **10** is preferably disposed on an inner wall of the shielding protective hood **20** that directly faces the opening. Thus, it is can be realized that, upon measurement of the body surface temperature, the opening covers over a body surface, and the infrared temperature sensor **10** directly faces the measured body surface. The infrared temperature sensor **10** can fully receive infrared rays emitted from the measured site, thereby enhancing the precision of temperature measurement.

In the above-described body surface thermometer, because non-contact type measurement is performed, the freedom degree of measurement is higher, and to make a temperature measurement by utilizing infrared rays radiated by a body surface saves more time than that for a commonly used measuring mode of being performed in a mouth, under an armpit or in an ear. The shielding protective hood **20** can act to prevent the leakage of infrared rays emitted from the body surface, so that external infrared rays are prevented from affecting the measurement for body surface temperature, and also can act to block the effects of ambient air convection on the body surface temperature, so that the precision of measurement is enhanced.

For example, on the grounds that the shielding characteristic of quartz glass against infrared rays is somewhat more superior, quartz glass can be selected for producing the shielding protective hood according to the embodiment. The shielding protective hood may be of any shape (e.g., circular, square, or the like), as long as the influence of surroundings can be reduced and the site to be measured can be shielded favorably.

For example, in order to avoid the interference from ultraviolet rays in the neighborhood of a test environment, an UV light transmission proofing layer may be further coated on an outer surface of the shielding protective hood according to the embodiment; and in order to avoid the interference from visible light in the neighborhood of the test environment, a visible light transmission proofing layer may be coated on an outer surface of the shielding protective hood.

The body surface thermometer according to the embodiment may further include a measurement display unit connected to the infrared temperature sensor, and the measuring results of body surface temperature are displayed by the measurement display unit. For example, referring to that shown in FIG. 4, after the infrared rays emitted from a body surface at a measured site are received by the infrared temperature sensor, they are filtered by a filter, amplified by an amplifier, and supplied to an A/D converter for data conversion sequentially. With the use of the information for comparison stored in a memory, the wavelength value is calculated by the voltage, then the temperature is calculated

4

by the wavelength value, and finally, display of the temperature is conducted by the measurement display unit.

Based on the above body surface thermometer, according to an embodiment of the invention, there is further provided a wearable temperature measuring device. As shown in FIG. 3, the wearable display device includes a wearing body **30** and a body surface thermometer (as represented by an infrared temperature sensor **10** and a shielding protective hood **20** in FIG. 3) disposed on the wearing body **30**, and a measurement display unit is mounted on the wearing body. The wearing body **30** is made to be a flexible circular ring, so as to form a wrist type body surface thermometer. While the wearable temperature measuring device is used for measurement of body surface temperature, the wearing body **30** is fixed at a body-surface measuring site **40**, so that the infrared temperature sensor **10** is located directly above the body-surface measuring site **40**, a temperature measuring function is started, and further, the measured temperature is displayed by the measurement display unit mounted on the wearing body **30**.

FIG. 5 illustrates a structure of a wearable temperature measuring device **200** and the connection relationship of elements of the wearable temperature measuring device **200**.

As illustrated, the wearable temperature measuring device **200** comprises a wearing body **30** and a body surface thermometer **100** disposed on the wearing body **30**. A measurement display unit **60** is mounted on a wearing body **30**, and is connected to an infrared temperature sensor **10** in the body surface thermometer **100**.

As can be seen from the above, according to at least an embodiment of the invention, with the aid of an infrared-ray shielding function possessed by the shielding protective hood, surrounding far infrared rays are blocked, and moreover, the effect of ambient air convection on the measurement of the infrared temperature sensor is blocked. Thus, the influence of far infrared rays in the surrounding environment on the temperature measurement is reduced, and the measuring precision of surface temperature of a target object is promoted. The infrared temperature sensor is involved in a non-contact type measurement relative to a surface of the target object, so as to raise the freedom degree of test.

Descriptions made above are merely exemplary embodiments of the present invention, but are not used to limit the protection scope of the invention. The protection scope of the invention is determined by the attached claims.

This application claims the benefit of priority from Chinese patent application No. 201410281370.7, filed on Jun. 20, 2014, the disclosure of which is incorporated herein in its entirety by reference as a part of the present application.

What is claimed is:

1. A body surface thermometer, comprising an infrared temperature sensor and a shielding protective hood disposed outside the infrared temperature sensor and enclosing the infrared temperature sensor, the shielding protective hood being an infrared ray shielding protective hood;

wherein the shielding protective hood is made of quartz glass and an outer surface of the shielding protective hood is coated with an ultraviolet ray transmission proofing layer.

2. The body surface thermometer claimed as claim 1, wherein the shielding protective hood has an opening on one side, the infrared temperature sensor is located on an inner wall of the shielding protective hood, and the opening is disposed directly over the infrared temperature sensor.

3. The body surface thermometer claimed as claim 2, further comprising a measurement display unit, connected to

the infrared temperature sensor, which acts to display measured results of the body surface temperature.

4. The body surface thermometer claimed as claim 3, wherein an outer surface of the shielding protective hood is further coated with a visible light transmission proofing layer. 5

5. The body surface thermometer claimed as claim 1, further comprising a measurement display unit, connected to the infrared temperature sensor, which acts to display measured results of the body surface temperature. 10

6. The body surface thermometer claimed as claim 1, wherein an outer surface of the shielding protective hood is coated with a visible light transmission proofing layer.

* * * * *

专利名称(译)	体表温度计和耐磨温度测量装置		
公开(公告)号	US10194807	公开(公告)日	2019-02-05
申请号	US14/443807	申请日	2014-09-30
[标]申请(专利权)人(译)	京东方科技集团股份有限公司		
申请(专利权)人(译)	京东方科技集团股份有限公司.		
当前申请(专利权)人(译)	京东方科技集团股份有限公司.		
[标]发明人	OKAMURA MASAKAZU		
发明人	OKAMURA, MASAKAZU		
IPC分类号	A61B5/01 A61B5/00 G01J5/04 G01J5/00 G02B5/20 G01K13/00 G01J5/06		
CPC分类号	A61B5/01 A61B5/0075 A61B5/6831 G01J5/0025 G01J5/048 G02B5/208 A61B5/742 A61B2562/0271 A61B2562/185 G01J2005/065 G01K13/004 A61B5/6824		
代理机构(译)	LADAS & PARRY LLP		
审查员(译)	CAREY , MICHAEL		
优先权	201410281370.7 2014-06-20 CN		
其他公开文献	US20160256055A1		
外部链接	Espacenet		

摘要(译)

公开了一种体表温度计和可穿戴温度测量装置。体表温度计包括红外温度传感器和设置在红外温度传感器外部的屏蔽保护罩，屏蔽保护罩是红外线屏蔽保护罩。利用体表温度计，可以提高目标物体表面温度的测量精度，从而提高测试的自由度。

