



(19) **United States**

(12) **Patent Application Publication**  
**Vaitaitis**

(10) **Pub. No.: US 2018/0008195 A1**

(43) **Pub. Date: Jan. 11, 2018**

(54) **METHOD AND SYSTEM OF ATTACHMENT AND DETECTION OF ATTACHMENT OF A WEARABLE SENSOR TO CLOTHING MATERIAL**

(71) Applicant: **MONDEVICES, INC**, New York, NY (US)

(72) Inventor: **Arturas Henrikas Vaitaitis**, North Bergen, NJ (US)

(21) Appl. No.: **15/694,312**

(22) Filed: **Sep. 1, 2017**

**Related U.S. Application Data**

(63) Continuation-in-part of application No. 14/578,904, filed on Dec. 22, 2014, now Pat. No. 9,750,456.

(60) Provisional application No. 61/923,460, filed on Jan. 3, 2014.


**Publication Classification**

(51) **Int. Cl.**  
*A61B 5/00* (2006.01)  
*A61B 5/0205* (2006.01)  
*A41D 1/00* (2006.01)  
*A61B 5/024* (2006.01)  
*A61B 5/021* (2006.01)  
*A61B 5/053* (2006.01)

(52) **U.S. Cl.**  
 CPC ..... *A61B 5/6804* (2013.01); *A61B 5/02055* (2013.01); *A41D 1/002* (2013.01); *A61B 5/021* (2013.01); *A61B 5/053* (2013.01); *A61B 2562/0219* (2013.01); *A61B 5/024* (2013.01)

(57) **ABSTRACT**  
 A method and system of universal, secure attachment with attachment detection mechanism, of a wearable sensor-unit to any article of clothing worn around the body in order to measure vital signals of a person, such as motion, movements and activity levels. The method and system permits: reliable attachment to any article of clothing; an attachment in any position to clothing or fabric worn by a person; and detection for the wearable sensor attachment to an article of clothing to minimize false alarms.

10






FIG. 1




FIG. 2




FIG. 3




FIG. 4




FIG. 5




FIG. 6




FIG. 7

**METHOD AND SYSTEM OF ATTACHMENT  
AND DETECTION OF ATTACHMENT OF A  
WEARABLE SENSOR TO CLOTHING  
MATERIAL**

**CROSS REFERENCE TO RELATED  
APPLICATIONS**

[0001] This application claims priority from U.S. Provisional Application Ser. No. 61/923,460 filed Jan. 3, 2014, and U.S. patent application Ser. No. 14/578,904 filed on Dec. 22, 2014, the entire contents of which are incorporated herein by reference.

**BACKGROUND**

**Technical Field**

[0002] The present principles relate to wearable sensors. More particularly, it relates to a method of universal attachment of a wearable sensor to articles of clothing worn around the subject's body in order to measure body movement, motion and activity level by such a sensor or plurality of sensors. The invention also relates to a method of detecting the attachment of wearable sensor to clothing.

**Related Art**

[0003] Previous known approaches in the area of medical portable devices addressed the problem of measuring health status of adults through the use of restrictive and intrusive attachments of devices, fixed to body via tight straps and adhesive materials that are not applicable for infant and newborn care, as they restrict blood flow and irritate the fragile skin of subjects. Existing approaches presume that the signal coming of the sensor is reliable and do not deal with a method of improving the signal strength by finding the best position of the sensor.

[0004] An invention described in this art introduces a novel design for universal attachment of a non-restrictive wearable sensor to any article of clothing in a position best suited for measurement of vital health signals, such as but not limited to body movements, sound, light, pressure, proximity, conductance, activity levels, heart rate, blood oxygen level and temperature. The sensor unit is worn on clothing without restricting the blood flow through the extremities of the subject.

[0005] Existing approaches require a specific static placement of wearable sensors, such as into pockets or on wristbands, or special clothing with embedded sensors. Existing approaches also do not ensure safeguards against incorrect placement. Incorrect placement of the sensor will result in false alarms or aberrant measurements. Some embodiments of invention described here include a method for detection if the sensor is attached to the clothing in a secure manner and ready for operation or if it is detached, thus providing some safeguards against incorrect attachment and minimizing amount of false alarms.

[0006] Methods and devices for clothing detection about a wearable electronic device—U.S. Pat. No. 8,541,745 B2. This publication is materially and significantly different from the art described in this invention, as it deals with the devices worn in pockets and around wristbands and do not address universal placement of a sensor anywhere on article of clothing, nor with detection of such attachment.

[0007] Wearable electronic system—WO2009148595 A2. This art is sufficiently different from the art of this invention, as it focuses on plurality of wearable components into a single assembly.

[0008] Wearable system for monitoring parameters of four vital signs of human bodies in real time—CN102018504 B. This art is sufficiently different from this invention, as it describes placement of sensors on a wristwatch, a belt and on specific places on clothing.

**SUMMARY**

[0009] According to an implementation, the method for attaching and securing a wearable sensor to an article of clothing includes providing a sensor enclosure having a surface defining an opening and providing a sensor configured to be received into the opening of the enclosure. An article of clothing is positioned between the opening of the sensor enclosure and the sensor, and the sensor is squeezed or pushed into the opening of the sensor enclosure such that the article of clothing is sandwiched between the sensor and the sensor enclosure.

[0010] According to another implementation, the wearable sensor includes an outer enclosure having an opening, and a sensor assembly configured to be received and secured into the outer enclosure opening. When an article of clothing is positioned between the outer enclosure and the sensor before they are press fit together such that the same results in a secure fit between enclosure and sensor.

[0011] These and other aspects, features and advantages of the present principles will become apparent from the following detailed description of exemplary embodiments, which is to be read in connection with the accompanying drawings.

**BRIEF DESCRIPTION OF THE DRAWINGS**

[0012] The present principles may be better understood in accordance with the following exemplary figures, in which:

[0013] FIG. 1 is an exploded cross-sectional view of the wearable sensor not attached to an article of clothing, according to an embodiment of the invention;

[0014] FIG. 2 is a cross-sectional view of the wearable sensor attached to an article of clothing, according to an embodiment of the invention;

[0015] FIG. 3 is a schematic depiction of sensor-unit device, a subject of health monitoring, of a mobile reader device and their interactions according to an embodiment of the invention;

[0016] FIG. 4 is a block diagram of another implementation of the wearable sensor with mobile reader and an external health monitoring system, according to an embodiment of the invention;

[0017] FIG. 5 is an exploded cross-sectional view of the wearable sensor not attached to an article of clothing, according to an embodiment of the invention;

[0018] FIG. 6 is a cross-sectional view of the wearable sensor attached to an article of clothing, according to an embodiment of the invention; and

[0019] FIG. 7 is a cross-sectional view of the wearable sensor attached to an article of clothing, according to an embodiment of the invention.

## DETAILED DESCRIPTION

[0020] The present principles are directed to wearable sensors and the attachment of the same to clothing of a wearer

[0021] The present description illustrates the present principles. It will thus be appreciated that those skilled in the art will be able to devise various arrangements that, although not explicitly described or shown herein, embody the present principles and are included within its spirit and scope.

[0022] All examples and conditional language recited herein are intended for pedagogical purposes to aid the reader in understanding the present principles and the concepts contributed by the inventor(s) to furthering the art, and are to be construed as being without limitation to such specifically recited examples and conditions.

[0023] Moreover, all statements herein reciting principles, aspects, and embodiments of the present principles, as well as specific examples thereof, are intended to encompass both structural and functional equivalents thereof. Additionally, it is intended that such equivalents include both currently known equivalents as well as equivalents developed in the future, i.e., any elements developed that perform the same function, regardless of structure.

[0024] Thus, for example, it will be appreciated by those skilled in the art that the block diagrams presented herein represent conceptual views of illustrative circuitry embodying the present principles. Similarly, it will be appreciated that any flow charts, flow diagrams, state transition diagrams, pseudocode, and the like represent various processes which may be substantially represented in computer readable media and so executed by a computer or processor, whether or not such computer or processor is explicitly shown.

[0025] The functions of the various elements shown in the figures may be provided through the use of dedicated hardware as well as hardware capable of executing software in association with appropriate software. When provided by a processor, the functions may be provided by a single dedicated processor, by a single shared processor, or by a plurality of individual processors, some of which may be shared. Moreover, explicit use of the term “processor” or “controller” should not be construed to refer exclusively to hardware capable of executing software, and may implicitly include, without limitation, digital signal processor (“DSP”) hardware, read-only memory (“ROM”) for storing software, random access memory (“RAM”), and non-volatile storage.

[0026] Other hardware, conventional and/or custom, may also be included. Similarly, any switches shown in the figures are conceptual only. Their function may be carried out through the operation of program logic, through dedicated logic, through the interaction of program control and dedicated logic, or even manually, the particular technique being selectable by the implementer as more specifically understood from the context.

[0027] In the claims hereof, any element expressed as a means for performing a specified function is intended to encompass any way of performing that function including, for example, a) a combination of circuit elements that performs that function or b) software in any form, including, therefore, firmware, microcode or the like, combined with appropriate circuitry for executing that software to perform the function. The present principles as defined by such claims reside in the fact that the functionalities provided by the various recited means are combined and brought

together in the manner which the claims call for. It is thus regarded that any means that can provide those functionalities are equivalent to those shown herein.

[0028] Reference in the specification to “one embodiment” or “an embodiment” of the present principles, as well as other variations thereof, means that a particular feature, structure, characteristic, and so forth described in connection with the embodiment is included in at least one embodiment of the present principles. Thus, the appearances of the phrase “in one embodiment” or “in an embodiment”, as well as any other variations, appearing in various places throughout the specification are not necessarily all referring to the same embodiment.

[0029] FIG. 1 depicts a wearable sensor-unit 10 before attachment to an article of clothing. This figure demonstrates a method of universal attachment. As shown, the sensor unit 10 includes a sensor part 12 and an enclosure 20. The sensor 12 includes a bottom or lower surface 14, contoured lower corners 18, and an optical sensor 16. The enclosure 20 includes a window or opening 22 in a top surface thereof and a side surface 24. The bottom of the side surface 24 is slightly curved in portions 28 configured to frictionally grip onto the lower corners 18 of the sensor 12. Examples of materials that can be used for the enclosure 20 and/or the sensor part 12 are any materials that have been considered safe for children, such as, for example, ABS plastic (i.e., Acrylonitrile Butadiene Styrene). Those of skill in the art will appreciate that other materials could be used for the enclosure 20 and/or the sensor 12 without departing from the intended scope of the present disclosure.

[0030] The sensor 12 includes an optical sensor 16 in an upper surface thereof and a corresponding window or opening 22 in the enclosure 20. Thus, when the sensor 12 is either not fastened to the enclosure 20, or is fastened therein without being attached to an article of clothing, light will pass unimpeded to optical sensor 16, thus indicating that the same is not attached to an article of clothing. As will be discussed further below, sensor 12 will transmit a signal to a remote device (e.g., computing device such as a smartphone, or other computing device) thus indicating that the same is not attached to an article of clothing. Further details on the internal workings of sensor 12 are discussed below with reference to FIG. 4.

[0031] FIG. 2 shows the wearable sensor unit 10 attached to an article of clothing 30. To achieve that state, a user-operator has to place clothing material 30 in between the external enclosure 20 and an internal housing containing sensor 12. Then a user-operator presses the internal housing containing sensor 12 into the external enclosure 20 until the surface 24 snap over the lower corners they will securely fasten, confining clothing material in between. Thickness of clothing material will diminish margins within the attachment and add to the strength of attachment by making it more securely held. As shown, when the clothing 30 is sandwiched between the sensor 12 and enclosure 20, curved portions 28 frictionally engage the lower corners 18 and “snap” the sensor onto the clothing in a secure manner.

[0032] The thickness of the clothing 30 increases the friction between the enclosure 20 and sensor 12, thus providing for a very secure attachment. This method of attachment provides for either continuous contact or intermittent contact (e.g., resulting from movement of clothing 30 when a user moves) with the skin of a user, and the sensor-unit 10 is configured to function completely with

either continuous or intermittent contact with the skin of a user. The sensor unit **10** may also be positioned adjacent to the skin of a user in accordance with various embodiments.

**[0033]** Once the sensor **12** is inserted into the enclosure **20**, the clothing **30** will operate to block light from passing to optical sensor **16**. In this manner, the sensor **12** will transmit a signal to the remote device (e.g., computing device such as a smartphone, or other computing device), thus indicating that the sensor has been attached to an article of clothing.

**[0034]** FIG. **3** shows a schematic diagram of the operation of a wearable sensor unit **10**. The user **1** attaches the sensor unit **10** to an article of their clothing (not shown). The sensor unit **10** is in remote communication with a mobile computing/reading device **102**, such as, for example, a smartphone, a tablet, a laptop or any other suitable computing device. For home applications, the computing device need not be mobile, but it is preferred that computing device **102** is a mobile device.

**[0035]** The mobile reader device **102** is configured to measure, for example, a health status signal provide by the sensor. This health status signal can then be transmitted to a health status database **210**. The health status database **210** can operate in many ways in accordance with the present principles. For example, health status database **210** can respond to the health status signal by sending a signal back to the mobile computing/reader device. This response can be an "all is ok" signal indicating that the health status of the individual has not changed in a manner that warrants any concern (e.g., signal received indicates that the monitored conditions are still within predetermined ranges for the same). Alternatively, the response could be "heart rate is high", "blood pressure" is low, or any other health related type of warning indicating that the monitored condition is now outside the predetermined ranges for that individual. In this case, an alert or trigger would be sent to the mobile reader **102**. In this situation, a mobile reader device detects a transmitted alert, triggering an alarm within a mobile reader device environment. Alarm in a mobile reader device may be audible, visual or a combination of both, and may also include an audible and/or visual alert notification to a third party, such as hospital. In other alternatives, the mobile reader could send a text message or call a third party with a prerecorded message.

**[0036]** As illustrated in FIG. **4**, the sensor unit **20** consists of a micro-controller or processor **201**, a low energy wireless transmitter **202**, at least one sensor or array of sensors **203** and a power source **204** that powers the device and all sensor unit components. The mobile reader/computing device **102** consists of several components specific for a mobile device, however, only those of relevance to the present invention are disclosed. By way of example, the mobile device **201** includes a low energy reader **206**, a processing application **207** running within a processor and to be displayed on a user interface **208** as a front end to show health status signal and alerts, and a wireless transmitter/receiver **209**. As shown in the present example, mobile device **102** detects and reads sensor unit **20** by receiving wireless low energy signals transmitted from the sensor. The mobile device **102** may re-transmit the signal further via the wireless transmitter **209** to a third-party, such as the health status database server located off-site **210**. Those of skill in the art will appreciate that the wireless transmitter/receiver **209** of the mobile

device can be WiFi based, or RF based depending on the transmitting/receiving necessary.

**[0037]** According to one implementation, the sensor unit MCU **201** will store and run some software that uses the signal measured by an optical sensor **16** in order to detect if a wearable sensor is attached to clothing material. In this regard, those of skill in the art will appreciate that MCU **201** will either include its own memory, or the sensor unit **20** will have a memory component operating in conjunction with the MCU **201**.

**[0038]** With respect to the one or more specific sensors **203** contained in the sensor device **20**, a non-limiting list of examples of such sensors could be, for example, blood pressure, heart rate, temperature, sound, light, pressure, conductance etc. According to other contemplated embodiments, one sensor can measure and transmit a signal that is processed by the mobile device or health database to derive multiple sensed conditions from the received signal. By way of further example, through the use of accelerometers, the transmitted signal can include multiple readings which when deciphered/decoded by the mobile device or connected health database, things like position, movement (or lack thereof), activity levels, fall detection, tremors, etc. can all be derived and detected from the transmitted signal.

**[0039]** Referring now to FIG. **5**, a wearable sensor-unit **500** shown before attachment to an article of clothing is illustratively depicted in accordance with an embodiment of the present principles. This figure demonstrates a system and method of universal attachment of the wearable sensor-unit **500** to an article of clothing **516**. As shown, the sensor-unit **500** includes a sensor part **502** and an enclosure **510**. The sensor **502** includes a bottom or lower surface **504**, contoured lower corners **508**, and a piezoelectric sensor **506**.

**[0040]** The enclosure **510** further includes a side surface **512**. The bottom of the side surface **512** has slightly curved portions **514** configured to frictionally grip onto the lower corners **508** of the sensor **502**. Examples of materials that can be used for the enclosure **510** and/or the sensor part **502** are any materials that have been considered safe for children, such as, for example, ABS plastic (i.e., Acrylonitrile Butadiene Styrene). Those of skill in the art will appreciate that other materials could be used for the enclosure **510** and/or the sensor **502** without departing from the intended scope of the present disclosure.

**[0041]** In one embodiment, the sensor **502** further includes a piezoelectric sensor **506** to detect whether the sensor-unit **500** is attached onto clothing **516**. The piezoelectric sensor **506** may be configured to measure, store/transmit, and analyze piezo disc resonant frequency changes to determine whether the sensor-unit **500** is attached (e.g., snapped) onto clothing **516**. The piezoelectric sensor **516** may be supplied with a fixed frequency and the voltage measured across the piezoelectric sensor **516** using, for example, an analog-to-digital converter (ADC) (not shown). A voltage may be applied to the piezoelectric sensor **506** when not attached to clothing **516** and when attached to clothing **516** on input, and the output measured to determine a maximum voltage in each scenario. The measured voltages (e.g. when attached to clothing and when not attached to clothing) are stored in a storage medium for later access.

**[0042]** The piezoelectric sensor **516** is configured to detect, store, and/or transmit statistically significant differences in detected voltage, which can be caused by differences in physical tension (e.g., deformation/expansion of

enclosure 510 when connected to clothing 516). The voltage detected by the piezoelectric sensor 516 is compared with the stored voltages (e.g., voltage when connected to clothing and voltage when not connected to clothing) to determine whether the sensor-unit 500 is attached to clothing.

[0043] For example, if a current voltage is now showing a statistically significant difference from the voltage value stored in memory for “not connected to clothing”, the resonant frequency has changed, which indicates that the sensor-unit 500 is now attached to clothing 516. In some embodiments, such an indication automatically activates the sensor-unit 500. The sensor-unit 500 may also be automatically deactivated when removed from clothing 516 based on a measurement showing a current voltage value showing a statistically significant difference from the voltage value stored in memory for “connected to clothing”.

[0044] Thus, changes in the piezo disc resonant frequency indicate whether the sensor 502 is either not fastened to the enclosure 510, or is fastened therein without being attached to an article of clothing.

[0045] In some embodiments, voltage measurements to determine whether the sensor-unit 500 is connected to clothing may be performed continuously, or may be performed at any of a plurality of time intervals (e.g., 1 second, 1 minute, 30 minutes, 1 hour, etc.). These time intervals may be preset, or may be set by an end user using, for example, an application on a mobile computing/reading device 102 in accordance with the present principles.

[0046] As discussed above with reference to FIG. 3, sensor 502 will transmit a signal to a remote device 102 (e.g., computing device such as a smartphone, or other computing device) thus indicating that the same is attached or not attached to an article of clothing. Further details on the functionality and internal workings of sensor 502 are discussed above with reference to FIG. 4.

[0047] Referring now to FIG. 6, a wearable sensor unit 500 shown attached to an article of clothing 614 is illustratively depicted in accordance with an embodiment of the present principles. To achieve that state, a user-operator has to place clothing material 614 in between the external enclosure 610 and an internal housing containing sensor 602. Then a user-operator presses the internal housing containing sensor 602, which includes a piezoelectric sensor 606, into the external enclosure 610 until the surface 616 snaps over the lower corners 608 they will securely fasten, confining clothing material 614 in between.

[0048] Thickness of clothing material 614 will diminish margins within the attachment and add to the strength of attachment by making it more securely held. As shown, when the clothing 614 is sandwiched between the sensor 602 and enclosure 610, curved portions 612 frictionally engage the lower corners 608 and “snap” the sensor 602 onto the clothing 614 in a secure manner. The thickness of the clothing 614 increases the friction/tension between the enclosure 610 and sensor 602, thus providing for a very secure attachment.

[0049] This method of attachment provides for either continuous contact or intermittent contact (e.g., resulting from movement of clothing 614 when a user moves) with the skin of a user, and the sensor-unit 500 is configured to function completely with either continuous or intermittent contact with the skin of a user. The sensor-unit 500 may also be positioned adjacent to the skin of a user in accordance with various embodiments.

[0050] Once the sensor 602 is inserted into the enclosure 610, the clothing 614 will operate to cause a change in physical tension of the enclosure 610 from, for example, deformation of the enclosure 610 when the clothing is “snapped” in between the enclosure 610 and the sensor 602. In this manner, the sensor 602 will transmit a signal to a remote device, such as a smartphone, or other computing device (e.g., element 102 from FIG. 3), thus indicating that the sensor has been attached to an article of clothing 614 in accordance with the present principles.

[0051] Referring now to FIG. 7, a wearable sensor unit 700 shown attached to an article of clothing 714 is illustratively depicted in accordance with an embodiment of the present principles. To achieve that state, a user-operator has to place clothing material 714 in between the external enclosure 710 and an internal housing containing sensor 702. Then a user-operator presses the internal housing containing sensor 702 into the external enclosure 710 until the surface 716 snaps over the lower corners 708 they will securely fasten, confining clothing material 714 in between. The sensor 702 may include a piezoelectric sensor 706, an optical sensor 703 in an upper surface of the sensor 702 with a corresponding window or opening 701 in the external enclosure 710. The functionality of the piezoelectric sensor 706 and the optical sensor 703 are described in further detail above with reference to FIGS. 1, 2, 5, and 6.

[0052] In accordance with various embodiments, the optical sensor 703 and piezoelectric sensor 706 can function in combination with each other (e.g., simultaneously) to detect attachment of the wearable sensor unit 700 to an article of clothing 714. The sensors 703, 706 may also function individually to detect attachment of the wearable sensor unit 700 to an article of clothing 714. In some embodiments, the sensors 703, 706 are configured as backup sensors to provide continuous detection in the event of a failure of either one of the sensors 703, 706 in accordance with the present principles.

[0053] Thickness of clothing material 714 will diminish margins within the attachment and add to the strength of attachment by making it more securely held. As shown, when the clothing 714 is sandwiched between the sensor 702 and enclosure 710, curved portions 712 frictionally engage the lower corners 708 and “snap” the sensor 702 onto the clothing 714 in a secure manner. The thickness of the clothing 714 increases the friction/tension between the enclosure 710 and sensor 702, thus providing for a very secure attachment.

[0054] These and other features and advantages of the present principles may be readily ascertained by one of ordinary skill in the pertinent art based on the teachings herein. It is to be understood that the teachings of the present principles may be implemented in various forms of hardware, software, firmware, special purpose processors, or combinations thereof.

[0055] Most preferably, the teachings of the present principles are implemented as a combination of hardware and software. Moreover, the software may be implemented as an application program tangibly embodied on a program storage unit. The application program may be uploaded to, and executed by, a machine comprising any suitable architecture. Preferably, the machine is implemented on a computer platform having hardware such as one or more central processing units (“CPU”), a random access memory (“RAM”), and input/output (“I/O”) interfaces. The computer

platform may also include an operating system and micro-instruction code. The various processes and functions described herein may be either part of the microinstruction code or part of the application program, or any combination thereof, which may be executed by a CPU. In addition, various other peripheral units may be connected to the computer platform such as an additional data storage unit and a printing unit.

**[0056]** It is to be further understood that, because some of the constituent system components and methods depicted in the accompanying drawings are preferably implemented in software, the actual connections between the system components or the process function blocks may differ depending upon the manner in which the present principles are programmed. Given the teachings herein, one of ordinary skill in the pertinent art will be able to contemplate these and similar implementations or configurations of the present principles.

**[0057]** Although the illustrative embodiments have been described herein with reference to the accompanying drawings, it is to be understood that the present principles is not limited to those precise embodiments, and that various changes and modifications may be effected therein by one of ordinary skill in the pertinent art without departing from the scope or spirit of the present principles. All such changes and modifications are intended to be included within the scope of the present principles as set forth in the appended claims.

What is claimed is:

1. A method for attaching and securing a wearable sensor to an article of clothing, the method comprising:
  - providing a sensor enclosure having a surface defining an opening;
  - providing a sensor configured to be received into the opening of the enclosure;
  - positioning an article of clothing between the opening of the sensor enclosure and the sensor; and
  - squeezing the sensor into the opening sensor enclosure such that the article of clothing is sandwiched between the sensor and the sensor enclosure.
2. The method according to claim 1, further comprising detecting whether the wearable sensor is attached to an article of clothing.
3. The method according to claim 1, wherein the sensor includes a piezoelectric sensor.
4. The method according to claim 2, wherein said detecting comprises:
  - detecting a change in voltage across the wearable sensor based on a change in physical tension of the enclosure using a piezoelectric sensor, wherein:
    - when a measured voltage including a statistically significant change from an initial voltage is detected, transmitting a signal to a remote device indicating that the wearable sensor is attached to an article of clothing; and
    - when a measured voltage including a statistically significant change from an initial voltage is not detected, transmitting a signal to a remote device indicating that the wearable sensor is not attached to an article of clothing.
5. The method according to claim 1, further comprising providing a remote computing device configured to read signals transmitted by the sensor.

6. The method according to claim 5, further comprising providing an off-site health database in communication with the remote computing device, said off side health database being configured to:

- receive sensor signals from the remote computing device;
- compare the received signals to predetermined ranges of data relating to the user and the sensed condition relating to the received signal; and
- transmit response signals to the remote computing device based on such comparison.

7. A wearable sensor comprising:

- an outer enclosure having an opening; and
- a sensor assembly configured to be received and secured into the outer enclosure opening;
  - wherein an article of clothing is positioned between the outer enclosure and the sensor such that the same results in a secure fit between enclosure and sensor.

8. The wearable sensor according to claim 7, wherein said sensor assembly further comprises:

- a micro-controller;
- a transmitter in signal communication with the micro-controller;
- at least one sensor in signal communication with the micro-controller; and
- a power source connected to the micro-controller, transmitter and the at least one condition specific sensor.

9. The wearable sensor according to claim 8, wherein the at least one sensor comprises one or more accelerometers.

10. The wearable sensor according to claim 8, wherein the at least one sensor comprises at least one of a piezoelectric sensor, a blood pressure sensor, a light sensor, a sound sensor, a pressure sensor, a proximity sensor, a conductance sensor, a heart rate sensor and a temperature sensor.

11. The wearable sensor according to claim 8, further comprising a mobile computing device in signal communication with the sensor, the mobile computing device configured to receive transmitted signals from the wearable sensor.

12. The wearable sensor according to claim 11, further comprising a remotely located health status database in signal communication with the mobile device, said health status database being configured to analyze transmitted signals received from the mobile device relating to sensor measurements and provide status indications back to the mobile device relating to the same.

13. The wearable sensor according to claim 7, wherein the sensor assembly further comprises a piezoelectric sensor.

14. The wearable sensor according to claim 7, wherein the sensor assembly further comprises a piezoelectric sensor, the piezoelectric sensor being configured to:

- detect a change in voltage across the wearable sensor based on a change in physical tension of the enclosure, wherein:
  - when a measured voltage including a statistically significant change from an initial voltage is detected, a signal is transmitted to a remote device indicating that the wearable sensor is attached to an article of clothing; and
  - when a measured voltage including a statistically significant change from an initial voltage is not detected, a signal is transmitted to a remote device indicating that the wearable sensor is not attached to an article of clothing.

专利名称(译)	连接和检测可穿戴传感器与衣服材料的连接的方法和系统		
公开(公告)号	<a href="#">US20180008195A1</a>	公开(公告)日	2018-01-11
申请号	US15/694312	申请日	2017-09-01
[标]申请(专利权)人(译)	MONDEVICES		
[标]发明人	VAITAITIS ARTURAS HENRIKAS		
发明人	VAITAITIS, ARTURAS HENRIKAS		
IPC分类号	A61B5/00 A61B5/0205 A41D1/00 A61B5/021 A61B5/024 A61B5/053		
CPC分类号	A61B5/6804 A41D1/002 A61B5/02055 A61B5/021 A61B5/024 A61B5/053 A61B2562/0219 A61B2560/0266 A61B2562/16 G08B13/2434 G08B21/0453 Y10T29/49826		
优先权	61/923460 2014-01-03 US		
其他公开文献	US10182761		
外部链接	<a href="#">Espacenet</a> <a href="#">USPTO</a>		

摘要(译)

一种具有附件检测机构的通用安全附件的方法和系统，可穿戴传感器单元用于佩戴在身体周围的任何衣物上，以便测量人的生命信号，例如运动，运动和活动水平。该方法和系统允许：可靠地附着到任何衣物上；在任何位置附着于某人所穿的衣服或布料；检测可穿戴传感器与衣物的连接，以最大限度地减少误报。

