



US009192318B2

(12) **United States Patent**
Scharf et al.

(10) **Patent No.:** **US 9,192,318 B2**
(45) **Date of Patent:** ***Nov. 24, 2015**

(54) **DEVICE AND METHOD FOR THE GEOMETRIC DETERMINATION OF ELECTRICAL DIPOLE DENSITIES ON THE CARDIAC WALL**

5/04005 (2013.01); *A61B 5/0432* (2013.01);
A61B 5/4836 (2013.01); *A61B 5/6852*
(2013.01); *A61B 6/032* (2013.01); *A61B 8/13*
(2013.01); *A61B 18/0206* (2013.01); *A61B*
18/18 (2013.01); *A61N 7/00* (2013.01)

(71) Applicant: **Christoph Scharf**, Horgen, Zurich (CH)
(72) Inventors: **Christoph Scharf**, Zurich (CH); **Gunter Scharf**, Zurich (CH)

(58) **Field of Classification Search**
CPC A61B 5/0402; A61B 5/4005
See application file for complete search history.

(73) Assignee: **Christoph Scharf** (CH)

(56) **References Cited**

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 89 days.

This patent is subject to a terminal disclaimer.

U.S. PATENT DOCUMENTS

5,555,883 A 9/1996 Avitall
5,740,808 A 4/1998 Panescu et al.

(Continued)

FOREIGN PATENT DOCUMENTS

EP 1166714 1/2002
EP 1760661 3/2007

(Continued)

OTHER PUBLICATIONS

P. Della Bella, Non-Contact Mapping to Guide Catheter Ablation of Untolerated Ventricular Tachycardia, *European Heart Journal* (2002) 23, p. 742-752.

(Continued)

Primary Examiner — Eric D. Bertram

(74) *Attorney, Agent, or Firm* — Onello & Mello, LLP

(21) Appl. No.: **13/946,712**

(22) Filed: **Jul. 19, 2013**

(65) **Prior Publication Data**

US 2014/0024910 A1 Jan. 23, 2014

Related U.S. Application Data

(63) Continuation of application No. 12/863,411, filed as application No. PCT/IB2009/000071 on Jan. 16, 2009, now Pat. No. 8,512,255.

(30) **Foreign Application Priority Data**

Jan. 17, 2008 (CH) 68/08

(51) **Int. Cl.**

A61B 5/04 (2006.01)
A61B 5/042 (2006.01)
A61B 5/0402 (2006.01)

(Continued)


(52) **U.S. Cl.**

CPC *A61B 5/0422* (2013.01); *A61B 5/02028*
(2013.01); *A61B 5/0402* (2013.01); *A61B*

(57) **ABSTRACT**

Disclosed are devices, a systems, and methods for determining the dipole densities on heart walls. In particular, a triangularization of the heart wall is performed in which the dipole density of each of multiple regions correlate to the potential measured at various locations within the associated chamber of the heart.

41 Claims, 2 Drawing Sheets



- (51) **Int. Cl.**
A61B 5/02 (2006.01)
A61B 5/0432 (2006.01)
A61B 5/00 (2006.01)
A61B 6/03 (2006.01)
A61B 8/13 (2006.01)
A61B 18/02 (2006.01)
A61B 18/18 (2006.01)
A61N 7/00 (2006.01)

WO	99/05971	2/1999
WO	00/07501	2/2000
WO	2008014629	2/2008
WO	2009090547	7/2009
WO	2011136867	11/2011
WO	2012100185	7/2012
WO	2014036439	3/2014

OTHER PUBLICATIONS

Gupta, et al., "Point of View Cardiac Mapping: Utility or Futility?"; Indian Pacing and Electrophysiology Journal, vol. 2, No. 1, Jan. 1, 2002, pp. 20-32.
 European SR dated Sep. 29, 2014, issued in European Application No. 13176658.6.
 International Search Report and Written Opinion dated Mar. 5, 2013, issued in related International Application No. PCT/US2012/028593.
 Christoph Scharf, et al., Declaration under 37 C.F.R. 1.132, Nov. 15, 2012.
 Pullan, Andrew, et al., "The Inverse Problem of Electrocardiography;" Northeastern University Electrical and Computer Engineering, Feb. 23, 2007.
 He, et al., "An Equivalent Body Surface Charge Model Representing Three-Dimensional Bioelectrical Activity;" IEEE Transactions on Biomedical Engineering, 42.7 (1995), pp. 637-646.
 International Search Report issued in related International Application No. PCT/CH2007/000380.
 International Search Report dated Oct. 7, 2009 issued in corresponding International Application No. PCT/IB2009/000071.
 Della Bella P., et al., "Non-contact mapping to guide catheter ablation of intolerated ventricular tachycardia;" European Heart Journal, May 2002, vol. 23, No. 9, pp. 742-752.
 "Device and Method for the Geometric Determination of Electrical Dipole Densities on the Cardiac Wall" Specification, Drawings, Claims and Prosecution History of U.S Appl. No. 12/863,411, filed Jul. 16, 2010 by Christoph Scharf.
 ISRWO issued on May 20, 2014 in International application No. PCT/US14/15261.
 International Search Report and Written Opinion issued Jun. 5, 2014, International Application No. PCT/US2013/057579.
 Invitation to Pay Additional Fees issued on Jan. 8, 2014 in corresponding International Application No. PCT/US2013/057579.
 Partial European Search Report issued on Apr. 29, 2014 in corresponding European Application No. EP 13176658.
 Article 94(3) Communication dated Apr. 28, 2014 in corresponding European Application No. EP 09702094.
 International Search Report and Written Opinion dated Jun. 26, 2015 issued in International Application No. PCT/US2015/022187.
 International Search Report dated Mar. 10, 2015 issued in corresponding International Application No. PCT/US14/54942.

(56) **References Cited**

U.S. PATENT DOCUMENTS

5,795,298	A	8/1998	Vesely et al.	
6,066,096	A	5/2000	Smith et al.	
6,240,307	B1	5/2001	Beatty et al.	
6,301,496	B1	10/2001	Reisfeld	
6,400,981	B1	6/2002	Govari	
6,640,119	B1	10/2003	Budd et al.	
6,728,562	B1	4/2004	Budd et al.	
6,826,420	B1	11/2004	Beatty et al.	
6,826,421	B1	11/2004	Beatty et al.	
6,990,370	B1	1/2006	Beatty et al.	
7,289,843	B2	10/2007	Beatty et al.	
7,505,810	B2	3/2009	Harley et al.	
7,841,986	B2	11/2010	He et al.	
7,918,793	B2	4/2011	Altmann et al.	
7,953,475	B2	5/2011	Harley et al.	
8,147,486	B2	4/2012	Honour et al.	
8,417,313	B2*	4/2013	Scharf et al.	600/374
8,512,255	B2*	8/2013	Scharf et al.	600/508
8,700,119	B2	4/2014	Scharf et al.	
2002/0128565	A1	9/2002	Rudy	
2002/0165441	A1	11/2002	Coleman et al.	
2003/0231789	A1	12/2003	Willis et al.	
2003/0236466	A1	12/2003	Tarjan et al.	
2007/0106146	A1	5/2007	Altmann et al.	
2008/0009758	A1	1/2008	Voth	
2009/0024086	A1	1/2009	Zhang et al.	
2009/0131930	A1	5/2009	Gelbart et al.	
2009/0264781	A1*	10/2009	Scharf	600/509
2010/0298690	A1	11/2010	Scharf	
2011/0172658	A1	7/2011	Gelbart et al.	
2011/0270237	A1	11/2011	Werneth et al.	
2012/0143298	A1	6/2012	Just et al.	
2013/0226017	A1	8/2013	Scharf et al.	
2014/0180150	A1	6/2014	Scharf et al.	

FOREIGN PATENT DOCUMENTS

EP	1779787	5/2007
WO	94/06349	3/1994

* cited by examiner

Fig. 1






Fig. 2





**DEVICE AND METHOD FOR THE
GEOMETRIC DETERMINATION OF
ELECTRICAL DIPOLE DENSITIES ON THE
CARDIAC WALL**

CROSS REFERENCE TO RELATED
APPLICATIONS

The present application is a continuation application of U.S. patent application Ser. No. 12/836,411, filed on Jul. 16, 2010, now U.S. Pat. No. 8,512,255, which is a 371 national stage application of Patent Cooperation Treaty Application No. PCT/IB2009/000071 filed Jan. 16, 2009, entitled A DEVICE AND METHOD FOR THE GEOMETRIC DETERMINATION OF ELECTRICAL DIPOLE DENSITIES ON THE CARDIAC WALL, which is incorporated herein by reference, which in turn claims priority to Swiss Patent Application 00068/08 filed Jan. 17, 2008.

FIELD OF THE INVENTION

The present invention relates generally to the localization and treatment of cardiac arrhythmias, and more particularly to devices and methods for the geometric determination of electrical dipole densities on the cardiac wall.

BACKGROUND

Systems used to localize the origin of cardiac arrhythmias measure potentials (e.g. in millivolts) in the cardiac chambers and localize them on a three dimensional representation of the cardiac chamber wall. The measurement of the electrical activity present on the cardiac walls is called mapping. For this purpose, a multiple electrode mapping catheter may be positioned within the heart such that multiple potentials can be simultaneously measured at different locations on the wall of the cardiac chamber without having direct wall contact (non-contact mapping). The cardiac chamber is visualized as a three dimensional structure, either directly by moving one or more mapping electrodes within the corresponding heart chamber or by importing an anatomical geometry of the cardiac chamber from an imaging device (e.g. Computed Tomography, MRI, or ultrasound). The electrical activity within the heart can be measured with the multi-electrode mapping catheter, which may be able to simultaneously measure potentials at different points in three dimensional space. In the current systems, the measured potentials from the non-contact multi-electrode mapping catheter do not directly correspond to the electrical activity on the cardiac wall as measured with an electrode with direct wall contact (contact mapping). The measured potentials of the non-contact mapping system have to be converted with computer programs and extrapolated into virtual electrograms projected on the heart chamber of the mapping system.

The current conversion methods are inaccurate, and further processing, termed regularization methods, have to be used. These regularization methods decrease spatial resolution. Another limitation of the current methods is that the provided potentials represent only the mean electrical activity that emanates from different cells, consisting of membranes separating electrical dipoles.

Since the localization of cardiac arrhythmias by the use of potentials is imprecise, the successful treatment of cardiac arrhythmias has been difficult and has demonstrated limited success and reliability. There is, therefore, a need for improved methods of localizing cardiac arrhythmias.

SUMMARY OF THE INVENTION

Several unique devices, systems, and methods for creating a database of dipole densities at a surface of a patient's heart are provided. Dipole density information can be used by a clinician to diagnose and treat heart diseases such as arrhythmias. The dipole density information is based on anatomical models of the patient's heart and mapping information recorded by multiple electrodes, such as electrodes included on the distal end of a three dimensional mapping catheter.

According to a first aspect of the invention, a device for creating a database of dipole densities at the surface of one or more cardiac chambers of a patient is provided. The device includes a first receiver that receives mapping information from multiple electrodes included in one or more mapping catheters. The electrodes are placed in a cardiac chamber of the patient's heart. The device further includes a second receiver that receives anatomical information. The anatomical information may be a generic heart model, or more preferably tissue contour and other anatomical information recorded from the patient's own heart. A dipole density module determines the database of dipole densities, in the table form $d(y)$, where y represents the location on the heart tissue including that particular dipole density. The potential at various locations x , within a cardiac chamber and termed $V(x)$, are recorded by the multiple electrodes. Solid angle $\omega(x,y)$ represents the solid angle for a triangle projection between location x (electrode location in chamber) and y (triangle location on chamber wall). The dipole density module determines the dipole density for individual triangle shaped projections onto the cardiac chamber wall based on the following: each triangle projection at location y contributes $\omega(x,y)$ times the dipole density $d(y)$ to the potential $V(x)$ at the point x .

In a preferred embodiment, the device comprises a software program, e.g., such as a software program loaded onto a personal computer; an ECG system; a cardiac tissue ablation system and/or an imaging system. The number of triangles determined by the dipole density module is sufficiently large (triangle area small enough) such that the dipole density for each triangle projection is relatively constant. Typically 1000 or more triangles are used in the calculations, such as a calculation based on a standard sized Left Atrium. Larger numbers of triangles are used for larger sized chambers.

In another preferred embodiment, the patient is being diagnosed and/or treated for a heart condition, such as an arrhythmia. The electrodes are included at the distal end of one or more mapping catheters and are placed into a chamber of the patient's heart to record potentials. An imaging instrument, such as an instrument that provides a generic model of a heart, or an instrument which provides an anatomical model of the patient's heart, delivers the anatomical information to the second receiver. In a preferred embodiment, the imaging instrument is one or more of: Computed Tomography; MRI; ultrasound; and an ECG system with mapping catheter.

In another preferred embodiment, the dipole density module implements an algorithm configured to assist in the creation of the database of dipole densities. The algorithm may be a progressive algorithm configured to be modified or refined to improve spatial and/or time resolution of the database. The dipole density module may determine a map of dipole densities at corresponding time intervals. A synthesis of maps represents a cascade of activation sequences of each corresponding heart beat.

In another preferred embodiment, the device includes a third receiver. The third receiver receives mapping information from one or more skin electrodes. The dipole density

module uses the skin electrode signals to calculate or recalculate the database of dipole densities, using equations listed herebelow.

According to another aspect of the invention, a system for creating a database of dipole densities at the surface of one or more cardiac chambers of a patient's heart is provided. In addition to the device of the present invention, the system includes one or more of a multiple electrode catheter; an imaging instrument; an ablation device; and at least one surface or skin electrode. In a preferred embodiment, the mapping catheter is also used for ablating tissue identified by the database of dipole densities. The system includes a monitor to display the dipole density information, such as information displayed in relative geometry to the chamber of the patient's heart.

According to another aspect of the invention, a method of creating a database of dipole densities at the surface of one or more cardiac chambers of a patient's heart is provided. The method can be used to diagnose and/or treat cardiac disease. In a preferred embodiment, the method is used to diagnose and treat Atrial Fibrillation (AF). In another preferred embodiment, the method is used to detect ventricular ischemia and/or quantify myocardial function. The method includes placing an array of multiple electrodes within a chamber of the patient's heart to measure potentials. The array of multiple electrodes may or may not be repositioned to determine dipole densities.

In another preferred embodiment, the method further includes placing one or more skin electrodes. The information recorded by the skin electrodes is used to determine the database of dipole densities.

BRIEF DESCRIPTION OF THE DRAWINGS

The accompanying drawings, which are incorporated in and constitute a part of this specification, illustrate various embodiments in accordance with the present invention, and, together with the description, serve to explain the principles of the invention. In the drawings:

FIG. 1 illustrates a schematic view of an embodiment of a device for determining a database table of dipole densities of at least one heart chamber, consistent with aspects of the present invention.

FIG. 2 illustrates a flow chart of an embodiment of a preferred method for determining a database table of dipole densities of at least one heart chamber, consistent with aspects of the present invention.

FIG. 3 illustrates a schematic view of an embodiment of a system for determining a database table of dipole densities of at least one heart chamber with help of the solid angle $\omega(x,y)$, consistent with aspects of the present invention.

DESCRIPTION OF THE EMBODIMENTS

Reference will now be made in detail to the embodiments in accordance with aspects of the present invention, examples of which are illustrated in the accompanying drawings. Wherever possible, the same reference numbers will be used throughout the drawings to refer to the same or like parts.

A device for calculating surface charge densities has been described in detail in PCT International Application Number PCT/CH2007/000380 (hereinafter the '380 patent application) naming Scharf as inventor, filed Aug. 3, 2007, and entitled METHOD AND DEVICE FOR DETERMINING AND PRESENTING SURFACE CHARGE AND DIPOLE DENSITIES ON CARDIAC WALLS, and is incorporated by reference herein in its entirety. The present invention provides

an improved device, system and method for calculating and visualizing the distribution and activity of dipole charge densities on a cardiac wall. The dipole densities are directly determined geometrically, avoiding the errors encountered using previous extrapolation algorithms.

In accordance with the present invention, provided is a device that measures and calculates a database of dipole densities $d(y)$ on the cardiac wall. The actual measured potentials in the heart result from electrical activity of cells, which can be regarded as dipoles. The dipoles consist of ion charges on both sides of biological membranes. The use of dipole densities offers a precise representation of the electrical activity. Systems and methods in accordance with the present invention efficiently and effectively calculate the dipole densities utilizing one or more mathematical theorems. This calculation is significantly more precise than calculations of virtual potentials produced by current systems, which lose spatial precision because of the required numerical methods and the use of potentials instead of dipole densities. Systems and methods in accordance with the present invention are efficient in calculating dipole densities geometrically, such as through the use of computer systems, or similar microcontroller and/or mathematical processing equipment.

DEFINITIONS

To facilitate an understanding of the invention, a number of terms are defined below.

As used herein, the terms "subject" and "patient" refer to any animal, such as a mammal like livestock, pets, and preferably a human. Specific examples of "subjects" and "patients" include, but are not limited, to individuals requiring medical assistance, and in particular, patients with an arrhythmia such as atrial fibrillation (AF).

As used herein, the term "solid angle" is the angle subtended by a triangle on the heart wall at the position x of observation. When viewed from location x , straight lines are drawn from point x to the boundaries of the triangle, and a sphere is constructed of radius $r=1$ with center of x . The straight lines then define the spherical triangle on the surface of the sphere. The solid angle is proportional to the surface area of the projection of that object onto a sphere centered at the point x .

The methods and devices of the present invention have advantages over previous prior art devices. FIGS. 1-3 illustrate various preferred embodiments of devices, systems and methods in accordance with aspects of the present invention. However, the present invention is not limited to these particular configurations.

Referring now to FIG. 1, a schematic view of an embodiment of a device for determining a database table of dipole densities of at least one heart chamber of a patient is illustrated. Device **100** includes a first receiver **110** configured to receive electrical potentials from a separate device, such as a device including a multi-electrode mapping catheter placed in the circulating blood within a chamber of the patient's heart. Device **100** further includes a second receiver **120** configured to receive cardiac geometry information (e.g. the geometric contour of the cardiac chamber wall), such as from an instrument including, but not limited to: Computed Tomography; MRI; Ultrasound; a multi-electrode mapping catheter; and combinations of these. Alternatively, a standard geometry can be loaded representing a model of the cardiac chamber. Device **100** further includes a dipole density module **130** which comprises mathematical processing element, such as a computer or other electronic module including software and/or hardware for performing mathematical or

other calculations. Dipole density module **130** receives mapping information from first receiver **110** and cardiac geometry information from second receiver **120**. Dipole density module **130** preferably uses one or more algorithms to process the received mapping and geometry information to produce a database table of dipole densities.

The geometrical model of the cardiac chamber is processed by dipole density module **130** into multiple small triangles (triangularization). When the triangles are sufficiently small, the dipole density at each triangle can be regarded as constant. In a preferred embodiment, a standard cardiac chamber of 4-6 cm diameter is divided up into over 1000 triangles. In another preferred embodiment, the number of triangles determined by dipole density module **130** is based on the size of the heart chamber. With the electrodes positioned in a cardiac chamber by a clinician, such as an electrophysiologist, the potentials at each electrode are recorded. Each triangle is seen by the corresponding electrode under a certain solid angle. The dipole density module **130** computes the solid angle subtended by each triangle at position y on each electrode at position x on the multi-electrode catheter. If the dipole density at the triangle is d(y), the triangle contributes $\omega(x,y)$ times d(y) to the potential V(x) at the position x on the multi-electrode catheter. The total measured potential V(x) is the sum resulting from all the triangles. A detailed description is provided in reference to FIG. **3** herebelow.

In a preferred embodiment, dipole density module **130** implements a progressive algorithm that can be modified and/or refined in order to improve spatial and/or time resolution of the database of dipole densities that are produced. The dipole densities d(y) are obtained by solving a linear system of equations. This calculation requires some care to avoid numerical instabilities. Thereby a map of dipole densities can be created at each corresponding time interval. The synthesis of the maps generates a cascade of the activation sequence of each corresponding heart beat that can be used to define the origin of the electrical activity, arrhythmias or diagnose cardiac disease.

The measuring electrodes used in the present invention are placed in the blood flow in a heart chamber, a relatively homogeneous condition, such that the mathematical analysis of the present invention is well applicable. In a preferred embodiment, skin electrodes are also implemented such that dipole density module **130** can use the information received from the skin electrodes to calculate and/or recalculate the dipole densities for the cardiac wall. The spatial resolution which can be obtained by invasive (i.e., placed in the heart chamber) multi-electrode potential measurements is limited by the number of electrodes that can be placed in any cardiac chamber, such as the Left Atrium (LA). Skin placed electrodes, such as electrodes placed on the thorax, are not as space limited. However, due mainly to the inhomogeneous structure of the body, it is difficult to localize the actual sources of the skin electrode measured potentials. A highly complicated boundary value problem must be solved with boundary conditions that are poorly known, and previous attempts at determining the "action potential" from body surface ECG (alone) have not been very successful.

The badly defined boundary value problem can be avoided by an additional measurement (in addition to the skin electrode measurements) of the multi-electrode array of the present invention. A small sinusoidal voltage V_l is applied to each electrode $l=1, \dots, L$ on the electrode array in the heart, and the resulting voltages $W_k, k=1, \dots, K$ is measured at the surface electrodes. This yields the $K \times L$ transition matrix A_{kl}

$$W_k = \sum_{l=1}^L A_{kl} V_l. \quad (1)$$

Calculating solid angles produces the linear transformation B_m between the electrode array potentials V_l and the dipole densities $d_n, n=1, \dots, N$ of N regions of the heart wall:

$$V_l = \sum_{n=1}^N B_{ln} d_n. \quad (2)$$

N is chosen to be $N=K+L$ where K is the number of surface electrodes and L is the number of internally placed array electrodes.

Substituting equation (2) into (1) we have:

$$W_k = \sum_{l=1}^L \sum_{n=1}^N A_{kl} B_{ln} d_n. \quad (3)$$

Therefore, by simultaneous measuring of the potentials of the cardiac activity with all $K+L$ electrodes, $N=K+L$ dipole densities of N regions on the heart wall can be calculated. This method yields a higher spatial resolution than the L array electrodes alone. In the solution of the linear system of equations (2)+(3), regularization techniques must be used (e.g. Tikhonov regularization and its modifications) in order to avoid numerical instabilities.

Referring now to FIG. **2**, an embodiment of a preferred method for determining a database table of dipole densities of at least one heart chamber of a patient is illustrated. In Step **10**, a multi-electrode array is placed within the corresponding heart chamber. In Step **20**, the geometry of the corresponding heart chamber is obtained in relation to the multi-electrode array position, such as by moving around a second mapping electrode or by importing a geometry model from an imaging study (e.g. using computed tomography, MRI or ultrasound before or after the multi-electrode array of electrodes has been placed in the heart chamber). The surface of the geometry of the corresponding heart chamber is divided into small triangles, typically at least 1000 small triangles.

In Step **30**, the dipole density d(y) can be calculated from the measured potential values and the calculated solid angles. The measurements can be repeated successively during the cardiac cycle giving a high timely resolution during each millisecond. The information of the timely dependent dipole densities can be depicted as an activation map of the corresponding heart chamber for the given heart beat. The information can be used to diagnose and/or treat a patient with a cardiac arrhythmia, such as an atrial fibrillation patient.

In a preferred embodiment, the information is used to determine cardiac wall treatment locations for lesion creation, such as a lesion created in the Left or Right atrium, by an RF, ultrasound or cryogenic ablation catheter. In another preferred embodiment, the multiple electrode mapping array is placed in a ventricle and the dipole densities are determined for the ventricular wall, such as to detect ischemia or quantify myocardial function.

Referring now to FIG. **3**, an embodiment of a system for determining a database table of dipole densities of at least one heart chamber of a patient is illustrated. System **500** includes device **100**, which is configured to create a database table of

dipole densities $d(y)$ based on voltage potential measurements within the heart chamber and image information relating to the heart chamber, as has been described hereabove. System 500 further includes imaging unit 220, which is configured to provide a two or three-dimensional image of the heart chamber to device 100. Imaging unit 220 may perform at least one of Computed Tomography, MRI and/or ultrasound imaging. Imaging unit 220 may produce any form of real or virtual models of the cardiac chambers, such that a triangularization analysis is possible.

System 500 further includes mapping catheter 310, which includes shaft 311, shown inserted into a chamber of a patient's heart, such as the Left Atrium (LA). At the distal end of shaft 311 is an electrode array 315 including multiple electrodes 316. Electrode array 315 is shown in a basket construction, but numerous other constructions can be used including multiple independent arms, spiral arrays, electrode covered balloons, and other constructions configured to place multiple electrodes into a three-dimensional space. In a preferred embodiment, any catheter with a three-dimensional array of electrodes can be used to supply the mapping information to device 100.

In this embodiment, electrodes 316 are connected to wires, not shown, but traveling proximally to cable 317, which is electrically connected to a mapping unit 210, such as an electrocardiogram (ECG) unit. ECG unit 210 includes a monitor for displaying information, such as the potentials recorded by electrodes 316, as well as the dipole density information produced by device 100. In an alternative embodiment, device 100 further includes a monitor, not shown, but configured to display one or more of: dipole density information; potentials recorded by electrodes 316; and cardiac chamber contours and other geometry information. In a preferred embodiment, dipole density and recorded potentials information is shown in reference to a three-dimensional representation of the heart chamber into which catheter 310 is inserted. In an alternative embodiment, imaging unit 220 may include a device configured to create an image of the cardiac chamber from signals recorded from an electrode catheter, such as catheter 310.

System 500 may include a device for treating a cardiac arrhythmia, such as ablation source 230, which is electrically attached to electrodes 316 via cable 318. Alternatively or additionally, ablation source 230 can be attached to a different ablation catheter, such as a single or multiple ablation element catheter configured to deliver ablation energy such as RF energy, cryogenic energy, or other tissue disrupting energy.

As shown in FIG. 3, triangle T1, defined by device 100, is at location Y. Electrode 316a of catheter 310 is at location X. The geometric relationship between triangle T1 and Location X is defined by the solid angle, angle $\omega(X, Y)$. Device 100 includes dipole density module 130 such that each triangle at location y contributes $\omega(x, y)$ times the dipole density $d(y)$ to the potential $V(x)$ at the position x on a multi-electrode. Solid angle $\omega(x, y)$, as defined above, corresponds to the triangle at a location y and the electrode at positions x on the multi-electrode array. The dipole density module 130 of device 100 determines from the total measured potential $V(x)$, which is the sum resulting from all the triangles defined by device 100, the desired dipole density $d(y)$.

When sufficient potentials values $V(x)$ are measured (e.g. from 10 to 10,000 with increasing number of measured potentials providing more accurate results), the dipole density $d(y)$ at many equally distributed regions y on the cardiac wall is calculated by solving a linear equation system. By interpolation of the measured potentials (e.g. with help of splines) their number can be increased to a higher number of regions. The

solid angle $\omega(x, y)$ of a region is the sum of the solid angles of the individual triangles in the region on the cardiac wall. This calculation of dipole density results, such as via an automatic computer program forming at least part of dipole density module 130.

In a preferred embodiment, the results are presented in a visual, anatomical format, such as depicting the dipole densities on a geometric image of the cardiac wall in relation to time (t). This format allows a clinician, such as an electrophysiologist, to determine the activation sequence on the cardiac wall, such as to determine treatment locations for a cardiac arrhythmia. The results may be shown on a display of mapping unit 210, or on a separate unit such as a display included with device 100, display not shown but preferably a color monitor. In a preferred embodiment, the device of the present invention is implemented as, or includes, a software program that is executable by at least one processor. The software program can be integrated into one or more of: an ECG system; a cardiac tissue ablation system; an imaging system; a computer; and combinations of these.

In a preferred embodiment, the multi-electrode catheter includes at least 10 electrodes, configured to represent a three dimensional body with known geometry. The electrodes are preferably positioned in a spherical geometry, such as a spherical geometry created in a basket catheter. Elliptical electrode array geometries may be used, such as those provided in the Ensight Array Catheter, manufactured by St. Jude Medical of St. Paul Minn. In an alternative embodiment, multiple catheters are inserted into the heart chamber to provide the multiple electrodes.

In an alternative embodiment, the electrodes of the multi-electrode mapping array are repositioned during the method of determining dipole densities. Repositioning of electrodes can be beneficial to increase the number of measured potential values, if electrode positions are known. Therefore, repositioning is in concordance with adjustment of the geometry map in relation to the multi-electrode mapping catheter.

Other embodiments of the invention will be apparent to those skilled in the art from consideration of the specification and practice of the embodiments disclosed herein. It is intended that the specification and examples be considered as exemplary only, with a true scope and spirit of the invention being indicated by the following claims. In addition, where this application has listed the steps of a method or procedure in a specific order, it may be possible, or even expedient in certain circumstances, to change the order in which some steps are performed, and it is intended that the particular steps of the method or procedure claims set forth herebelow not be construed as being order-specific unless such order specificity is expressly stated in the claim.

We claim:

1. A method of diagnosing a cardiac condition of a patient, comprising:
 - inserting multiple electrodes into one or more cardiac chambers of a patient and recording mapping information;
 - obtaining cardiac geometry information of the one or more cardiac chambers;
 - creating a database of dipole densities $d(y)$ at the surface of the one or more cardiac chambers based on the mapping information and the geometrical depiction of the one or more cardiac chambers;
 - further comprising moving the multiple electrodes and producing the database of dipole densities $d(y)$ based on potentials measured before and after movement; and
 - diagnosing cardiac wall tissue based on the database of dipole densities $d(y)$.

2. The method of claim 1, wherein the database of dipole densities $d(y)$ represents a distribution and activity of dipole charge densities on a cardiac wall.

3. The method of claim 1, wherein the diagnosing of the cardiac wall tissue comprises selecting one or more cardiac wall locations for creation of one or more lesions.

4. The method of claim 3, further comprising delivering energy to create the one or more lesions.

5. The method of claim 4, wherein the delivered energy comprises energy selected from the group consisting of:

- RF energy;
- ultrasound energy;
- cryogenic energy; and
- combinations thereof.

6. The method of claim 3, wherein the one or more lesions are created on the cardiac wall of at least one of the left atrium and the right atrium.

7. The method of claim 1, wherein the diagnosing of the cardiac wall tissue comprises defining an origin of electrical activity on a cardiac wall.

8. The method of claim 1, wherein the diagnosing of the cardiac wall tissue comprises diagnosing an arrhythmia.

9. The method of claim 1, wherein the diagnosing of the cardiac wall tissue comprises diagnosing a cardiac disease.

10. The method of claim 1, wherein the diagnosing of the cardiac wall tissue comprises detecting an ischemia.

11. The method of claim 1, wherein the diagnosing of the cardiac wall tissue comprises quantifying a myocardial function.

12. The method of claim 1, wherein the database of dipole densities $d(y)$ comprises data representing multiple time intervals of a cardiac cycle.

13. The method of claim 1, wherein creating the database of dipole densities $d(y)$ includes using between about 10 and about 10,000 measured potentials $V(x)$.

14. The method of claim 1, further comprising providing a visual representation of the database of dipole densities $d(y)$.

15. The method of claim 14, wherein the visual representation comprises an activation map.

16. The method of claim 15, wherein the activation map includes information indicating a diagnosis of an arrhythmia of the patient.

17. The method of claim 14, wherein the visual representation further represents at least one of a contour of the cardiac wall anatomy or a display of potentials recorded by the multiple electrodes.

18. The method of claim 1, wherein the multiple electrodes are located on one or more catheters.

19. The method of claim 1, wherein the multiple electrodes are positioned on one or more of:

- a basket;
- multiple arms;
- a spiral array; and
- a balloon.

20. The method of claim 1, wherein the multiple electrodes comprise at least 10 electrodes.

21. The method of claim 1, wherein the multiple electrodes are arranged in a spherical geometry within the one or more cardiac chambers.

22. The method of claim 1, wherein the multiple electrodes are arranged in an elliptical geometry within the one or more cardiac chambers.

23. The method of claim 1, wherein the geometrical depiction is produced based on at least one of a two-dimensional (2D) or three-dimensional (3D) image.

24. The method of claim 1, wherein the geometrical depiction is produced from image data provided by an assembly selected from the group consisting of:

- a CT imaging device;
- an MRI;
- an ultrasound imaging device; and
- combinations thereof.

25. A method of diagnosing a cardiac condition of a patient, comprising:

inserting multiple electrodes into one or more cardiac chambers of a patient and recording mapping information;

obtaining cardiac geometry information of the one or more cardiac chambers;

creating a database of dipole densities $d(y)$ at the surface of the one or more cardiac chambers based on the mapping information and the geometrical depiction of the one or more cardiac chambers, including determining a dipole density for a plurality of individual triangle-shaped projections made onto the cardiac chamber wall,

wherein each triangle-shaped projection at a location y contributes $\omega(x,y)$ times the dipole density $d(y)$ to a potential $V(x)$ at a point x , and

wherein $\omega(x,y)$ is a solid angle for a respective triangle projection and where:

- (a) x represents a series of locations within one or more cardiac chambers; and
- (b) $V(x)$ is a measured potential at the point x , said measured potential recorded by the multiple electrodes, and

diagnosing cardiac wall tissue based on the database of dipole densities $d(y)$.

26. The method of claim 25, wherein the creating of the database of dipole densities $d(y)$ comprises determining a dipole density for at least 1,000 individual triangle-shaped projections made onto the cardiac chamber wall.

27. The method of claim 25, wherein the diagnosing of the cardiac wall tissue comprises selecting one or more cardiac wall locations for creation of one or more lesions.

28. The method of claim 27, further comprising delivering energy to create the one or more lesions.

29. The method of claim 25, wherein the diagnosing of the cardiac wall tissue comprises diagnosing an arrhythmia.

30. The method of claim 25, wherein the diagnosing of the cardiac wall tissue comprises diagnosing a cardiac disease.

31. The method of claim 25, wherein the diagnosing of the cardiac wall tissue comprises detecting an ischemia.

32. The method of claim 25, wherein the diagnosing of the cardiac wall tissue comprises quantifying a myocardial function.

33. The method of claim 25, further comprising providing a visual representation of the database of dipole densities $d(y)$.

34. A method of diagnosing a cardiac condition of a patient, comprising:

inserting multiple electrodes into one or more cardiac chambers of a patient and recording mapping information;

obtaining cardiac geometry information of the one or more cardiac chambers;

creating a database of dipole densities $d(y)$ at the surface of the one or more cardiac chambers based on the mapping information and the geometrical depiction of the one or more cardiac chambers, wherein creating the database of dipole densities $d(y)$ includes determining a set of calculated values by interpolating a set of measured potentials $V(x)$; and

11

diagnosing cardiac wall tissue based on the database of dipole densities $d(y)$.

35. The method of claim 34, wherein the measured potentials $V(x)$ comprise a first quantity of values, and the calculated values comprises a second quantity of values greater than the first quantity of values.

36. The method of claim 34, wherein the interpolation includes using splines.

37. The method of claim 34, wherein the diagnosing of the cardiac wall tissue comprises diagnosing an arrhythmia.

38. The method of claim 34, wherein the diagnosing of the cardiac wall tissue comprises diagnosing a cardiac disease.

39. The method of claim 34, wherein the diagnosing of the cardiac wall tissue comprises detecting an ischemia.

40. The method of claim 34, wherein the diagnosing of the cardiac wall tissue comprises quantifying a myocardial function.

12

41. A method of diagnosing a cardiac condition of a patient, comprising:

inserting multiple electrodes into one or more cardiac chambers of a patient and recording mapping information;

obtaining cardiac geometry information of the one or more cardiac chambers;

creating a database of dipole densities $d(y)$ at the surface of the one or more cardiac chambers based on the mapping information and the geometrical depiction of the one or more cardiac chambers, including recording signals from one or more skin electrodes and at least one of calculating or recalculating $d(y)$ based on recorded signals from the one or more skin electrodes; and

diagnosing cardiac wall tissue based on the database of dipole densities $d(y)$.

* * * * *

专利名称(译)	用于几何确定心壁上的电偶极子密度的装置和方法		
公开(公告)号	US9192318	公开(公告)日	2015-11-24
申请号	US13/946712	申请日	2013-07-19
[标]申请(专利权)人(译)	克里斯托夫		
申请(专利权)人(译)	SCHARF , CHRISTOPH		
当前申请(专利权)人(译)	SCHARF , CHRISTOPH		
[标]发明人	SCHARF CHRISTOPH SCHARF GUNTER		
发明人	SCHARF, CHRISTOPH SCHARF, GUNTER		
IPC分类号	A61B5/04 A61N7/00 A61B18/18 A61B18/02 A61B8/13 A61B6/03 A61B5/00 A61B5/0432 A61B5/042 A61B5/0402 A61B5/02		
CPC分类号	A61B5/0422 A61B5/02028 A61B5/0402 A61B5/04005 A61B5/0432 A61B5/4836 A61B5/6852 A61B6 /032 A61B8/13 A61B18/0206 A61B18/18 A61N7/00 A61B5/0036 A61B5/04012 A61B5/044 A61B5/046 A61B18/02 A61B18/12 A61B2018/00351 A61B2018/00577		
优先权	2008000068 2008-01-17 CH PCT/IB2009/000071 2009-01-16 WO		
其他公开文献	US20140024910A1		
外部链接	Espacenet USPTO		

摘要(译)

公开了用于确定心壁上的偶极密度的装置，系统和方法。特别地，进行心脏壁的三角化，其中多个区域中的每一个的偶极子密度与在心脏的相关腔室内的各个位置处测量的电势相关。

