



US009131882B2

(12) **United States Patent**
Al-Ali et al.

(10) **Patent No.:** **US 9,131,882 B2**
(45) **Date of Patent:** ***Sep. 15, 2015**

(54) **NONINVASIVE MULTI-PARAMETER
PATIENT MONITOR**

(71) Applicant: **Cercacor Laboratories, Inc.**, Irvine, CA
(US)

(72) Inventors: **Ammar Al-Ali**, San Juan Capistrano,
CA (US); **Massi Joe E. Kiani**, Laguna
Niguel, CA (US); **Mohamed K. Diab**,
Ladera Ranch, CA (US); **Roger Wu**,
Irvine, CA (US); **Rick Fishel**, Orange,
CA (US)

(73) Assignee: **Cercacor Laboratories, Inc.**, Irvine, CA
(US)

(*) Notice: Subject to any disclaimer, the term of this
patent is extended or adjusted under 35
U.S.C. 154(b) by 0 days.

This patent is subject to a terminal dis-
claimer.

(21) Appl. No.: **14/052,604**

(22) Filed: **Oct. 11, 2013**

(65) **Prior Publication Data**

US 2014/0142402 A1 May 22, 2014

Related U.S. Application Data

(63) Continuation of application No. 13/477,975, filed on
May 22, 2012, now Pat. No. 8,560,032, which is a

(Continued)

(51) **Int. Cl.**
A61B 5/1455 (2006.01)
G06F 19/00 (2011.01)

(Continued)

(52) **U.S. Cl.**
CPC **A61B 5/14551** (2013.01); **A61B 5/0205**
(2013.01); **A61B 5/0261** (2013.01);
(Continued)

(58) **Field of Classification Search**

CPC A61B 5/1455
USPC 600/310-344
See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

3,910,701 A 10/1975 Henderson et al.
3,998,550 A 12/1976 Konishi et al.

(Continued)

FOREIGN PATENT DOCUMENTS

DE 3244695 C2 10/1985
EP 0419 223 3/1991

(Continued)

OTHER PUBLICATIONS

Burritt, Mary F.; Current Analytical Approaches to Measuring Blood
Analytes; vol. 36; No. 8(B); 1990.

(Continued)

Primary Examiner — Eric Winakur


Assistant Examiner — Marjan Fardanesh

(74) *Attorney, Agent, or Firm* — Knobbe Martens Olson &
Bear LLP

(57) **ABSTRACT**

Embodiments of the present disclosure include a handheld multi-parameter patient monitor capable of determining multiple physiological parameters from the output of a light sensitive detector capable of detecting light attenuated by body tissue. For example, in an embodiment, the monitor is capable of advantageously and accurately displaying one or more of pulse rate, plethysmograph data, perfusion quality, signal confidence, and values of blood constituents in body tissue, including for example, arterial carbon monoxide saturation ("HbCO"), methemoglobin saturation ("HbMet"), total hemoglobin ("Hbt"), arterial oxygen saturation ("SpO₂"), fractional arterial oxygen saturation ("SpaO₂"), or the like. The monitor can determine which a plurality of light emitting sources and which of a plurality of parameters to measure based on the signal quality and resources available.

18 Claims, 18 Drawing Sheets



Related U.S. Application Data

- continuation of application No. 11/367,014, filed on Mar. 1, 2006, now Pat. No. 8,224,411.
- (60) Provisional application No. 60/657,596, filed on Mar. 1, 2005, provisional application No. 60/657,281, filed on Mar. 1, 2005, provisional application No. 60/657,268, filed on Mar. 1, 2005, provisional application No. 60/657,759, filed on Mar. 1, 2005.
- (51) **Int. Cl.**
A61B 5/0205 (2006.01)
A61B 5/145 (2006.01)
A61B 5/00 (2006.01)
A61B 5/026 (2006.01)
A61B 5/0295 (2006.01)
A61B 5/024 (2006.01)
- (52) **U.S. Cl.**
 CPC *A61B5/0295* (2013.01); *A61B 5/02416* (2013.01); *A61B 5/1455* (2013.01); *A61B 5/14532* (2013.01); *A61B 5/14546* (2013.01); *A61B 5/14552* (2013.01); *A61B 5/6826* (2013.01); *A61B 5/7221* (2013.01); *A61B 5/7246* (2013.01); *A61B 5/742* (2013.01); *A61B 5/7405* (2013.01); *A61B 5/746* (2013.01); *A61B 5/7475* (2013.01); *G06F 19/3418* (2013.01); *A61B 5/02427* (2013.01); *A61B 2562/08* (2013.01); *A61B 2562/085* (2013.01); *A61B 2562/222* (2013.01); *Y10S 439/909* (2013.01)
- (56) **References Cited**
 U.S. PATENT DOCUMENTS
- | | | | | | | | |
|-----------|---|---------|-------------------|-----------|---|---------|--------------------|
| 4,014,321 | A | 3/1977 | March | 4,964,010 | A | 10/1990 | Miyasaka et al. |
| 4,157,708 | A | 6/1979 | Imura | 4,964,408 | A | 10/1990 | Hink et al. |
| 4,167,331 | A | 9/1979 | Nielsen | 4,967,571 | A | 11/1990 | Sporri |
| 4,266,554 | A | 5/1981 | Hamaguri | 4,975,581 | A | 12/1990 | Robinson et al. |
| 4,267,844 | A | 5/1981 | Yamanishi | 4,975,647 | A | 12/1990 | Downer et al. |
| 4,446,871 | A | 5/1984 | Imura | 4,986,665 | A | 1/1991 | Yamanishi et al. |
| 4,531,527 | A | 7/1985 | Reinhold et al. | 4,996,975 | A | 3/1991 | Nakamura |
| 4,586,513 | A | 5/1986 | Hamaguri | 4,997,769 | A | 3/1991 | Lundsgaard |
| 4,621,643 | A | 11/1986 | New et al. | 5,025,791 | A | 6/1991 | Niwa |
| 4,653,498 | A | 3/1987 | New et al. | RE33,643 | E | 7/1991 | Isaacson et al. |
| 4,655,225 | A | 4/1987 | Dahne et al. | 5,028,787 | A | 7/1991 | Rosenthal et al. |
| 4,685,464 | A | 8/1987 | Goldberger et al. | 5,033,472 | A | 7/1991 | Sato et al. |
| 4,694,833 | A | 9/1987 | Hamaguri | 5,041,187 | A | 8/1991 | Hink et al. |
| 4,700,708 | A | 10/1987 | New et al. | 5,054,495 | A | 10/1991 | Uemura et al. |
| 4,714,341 | A | 12/1987 | Hamaguri et al. | 5,058,588 | A | 10/1991 | Kaestle |
| 4,770,179 | A | 9/1988 | New et al. | 5,069,213 | A | 12/1991 | Polczynski |
| 4,773,422 | A | 9/1988 | Isaacson et al. | 5,077,476 | A | 12/1991 | Rosenthal |
| 4,781,195 | A | 11/1988 | Martin | 5,078,136 | A | 1/1992 | Stone et al. |
| 4,800,885 | A | 1/1989 | Johnson | 5,137,023 | A | 8/1992 | Mendelson et al. |
| 4,805,623 | A | 2/1989 | Jobsis | 5,155,697 | A | 10/1992 | Bunsen |
| 4,822,997 | A | 4/1989 | Fuller et al. | 5,162,725 | A | 11/1992 | Hodson et al. |
| 4,832,484 | A | 5/1989 | Aoyagi et al. | 5,163,438 | A | 11/1992 | Gordon et al. |
| 4,846,183 | A | 7/1989 | Martin | 5,189,609 | A | 2/1993 | Tivig et al. |
| 4,854,328 | A | 8/1989 | Pollack | 5,190,040 | A | 3/1993 | Aoyagi |
| 4,863,265 | A | 9/1989 | Flower et al. | 5,209,230 | A | 5/1993 | Swedlow et al. |
| 4,867,571 | A | 9/1989 | Frick et al. | 5,226,053 | A | 7/1993 | Cho et al. |
| 4,868,476 | A | 9/1989 | Respaut | 5,246,002 | A | 9/1993 | Prosser |
| 4,869,254 | A | 9/1989 | Stone et al. | 5,247,931 | A | 9/1993 | Norwood |
| 4,890,306 | A | 12/1989 | Noda | 5,259,381 | A | 11/1993 | Cheung et al. |
| 4,907,876 | A | 3/1990 | Suzuki et al. | 5,267,562 | A | 12/1993 | Ukawa et al. |
| 4,911,167 | A | 3/1990 | Corenman et al. | 5,267,563 | A | 12/1993 | Swedlow et al. |
| 4,934,372 | A | 6/1990 | Corenman et al. | 5,278,627 | A | 1/1994 | Aoyagi |
| 4,938,218 | A | 7/1990 | Goodman et al. | 5,297,548 | A | 3/1994 | Pologe |
| 4,942,877 | A | 7/1990 | Sakai et al. | 5,313,940 | A | 5/1994 | Fuse et al. |
| 4,955,379 | A | 9/1990 | Hall | 5,319,355 | A | 6/1994 | Russek |
| 4,960,126 | A | 10/1990 | Conlon et al. | 5,331,549 | A | 7/1994 | Crawford, Jr. |
| 4,960,128 | A | 10/1990 | Gordon et al. | 5,335,659 | A | 8/1994 | Pologe et al. |
| | | | | 5,337,744 | A | 8/1994 | Branigan |
| | | | | 5,337,745 | A | 8/1994 | Benaron |
| | | | | 5,341,805 | A | 8/1994 | Stavridi et al. |
| | | | | 5,348,004 | A | 9/1994 | Hollub |
| | | | | 5,351,685 | A | 10/1994 | Potratz |
| | | | | 5,355,129 | A | 10/1994 | Baumann |
| | | | | 5,355,880 | A | 10/1994 | Thomas et al. |
| | | | | 5,355,882 | A | 10/1994 | Ukawa et al. |
| | | | | 5,361,758 | A | 11/1994 | Hall et al. |
| | | | | 5,368,224 | A | 11/1994 | Richardson et al. |
| | | | | D353,195 | S | 12/1994 | Savage et al. |
| | | | | D353,196 | S | 12/1994 | Savage et al. |
| | | | | 5,377,676 | A | 1/1995 | Vari et al. |
| | | | | 5,383,874 | A | 1/1995 | Jackson et al. |
| | | | | 5,385,143 | A | 1/1995 | Aoyagi |
| | | | | 5,387,122 | A | 2/1995 | Goldberger et al. |
| | | | | 5,392,777 | A | 2/1995 | Swedlow et al. |
| | | | | 5,400,267 | A | 3/1995 | Denen et al. |
| | | | | 5,413,101 | A | 5/1995 | Sugiura |
| | | | | D359,546 | S | 6/1995 | Savage et al. |
| | | | | 5,421,329 | A | 6/1995 | Casciani et al. |
| | | | | 5,425,362 | A | 6/1995 | Siker et al. |
| | | | | 5,425,375 | A | 6/1995 | Chin et al. |
| | | | | 5,427,093 | A | 6/1995 | Ogawa et al. |
| | | | | 5,429,128 | A | 7/1995 | Cadell et al. |
| | | | | 5,431,170 | A | 7/1995 | Mathews |
| | | | | 5,435,309 | A | 7/1995 | Thomas et al. |
| | | | | D361,840 | S | 8/1995 | Savage et al. |
| | | | | D362,063 | S | 9/1995 | Savage et al. |
| | | | | 5,452,717 | A | 9/1995 | Branigan et al. |
| | | | | D363,120 | S | 10/1995 | Savage et al. |
| | | | | 5,456,252 | A | 10/1995 | Vari et al. |
| | | | | RE35,122 | E | 12/1995 | Corenman et al. |
| | | | | 5,479,934 | A | 1/1996 | Imran |
| | | | | 5,482,036 | A | 1/1996 | Diab et al. |
| | | | | 5,487,386 | A | 1/1996 | Wakabayashi et al. |
| | | | | 5,490,505 | A | 2/1996 | Diab et al. |
| | | | | 5,490,523 | A | 2/1996 | Isaacson et al. |
| | | | | 5,494,032 | A | 2/1996 | Robinson et al. |
| | | | | 5,494,043 | A | 2/1996 | O'Sullivan et al. |
| | | | | 5,503,148 | A | 4/1996 | Pologe et al. |
| | | | | 5,520,177 | A | 5/1996 | Ogawa |

(56)

References Cited

U.S. PATENT DOCUMENTS

5,528,519 A	6/1996	Ohkura et al.	5,810,734 A	9/1998	Caro et al.
5,533,507 A	7/1996	Potratz	5,817,010 A	10/1998	Hibl
5,533,511 A	7/1996	Kaspari et al.	5,818,985 A	10/1998	Merchant et al.
5,534,851 A	7/1996	Russek	5,823,950 A	10/1998	Diab et al.
5,551,423 A	9/1996	Sugiura	5,823,952 A	10/1998	Levinson et al.
5,553,615 A	9/1996	Carim et al.	5,827,182 A	10/1998	Raley
5,555,882 A	9/1996	Richardson et al.	5,830,121 A	11/1998	Enomoto et al.
5,561,275 A	10/1996	Savage et al.	5,830,131 A	11/1998	Caro et al.
5,562,002 A	10/1996	Lalin	5,830,137 A	11/1998	Scharf
5,575,284 A	11/1996	Athan et al.	5,833,618 A	11/1998	Caro et al.
5,577,500 A	11/1996	Potratz	5,839,439 A	11/1998	Nierlich et al.
5,584,299 A	12/1996	Sakai et al.	RE36,000 E	12/1998	Swedlow et al.
5,588,427 A	12/1996	Tien	5,842,979 A	12/1998	Jarman
5,590,649 A	1/1997	Caro et al.	5,850,443 A	12/1998	Van Oorschot et al.
5,590,652 A	1/1997	Inai	5,851,178 A	12/1998	Aronow
5,595,176 A	1/1997	Yamaura	5,851,179 A	12/1998	Ritson et al.
5,596,992 A	1/1997	Haaland et al.	5,853,364 A	12/1998	Baker, Jr. et al.
5,602,924 A	2/1997	Durand et al.	5,857,462 A	1/1999	Thomas et al.
5,603,323 A	2/1997	Pflugrath et al.	5,860,099 A	1/1999	Milios et al.
5,603,623 A	2/1997	Nishikawa et al.	5,860,919 A	1/1999	Kiani/Azarbayjany et al.
5,615,672 A	4/1997	Braig et al.	5,865,736 A	2/1999	Baker, Jr. et al.
5,617,857 A	4/1997	Chader et al.	5,876,348 A	3/1999	Sugo
5,630,413 A	5/1997	Thomas et al.	5,885,213 A	3/1999	Richardson et al.
5,632,272 A	5/1997	Diab et al.	5,890,929 A	4/1999	Mills et al.
5,638,816 A	6/1997	Kiani/Azarbayjany et al.	5,891,022 A	4/1999	Pologe
5,638,818 A	6/1997	Diab et al.	5,891,024 A	4/1999	Jarman et al.
5,645,059 A	7/1997	Fein et al.	5,900,632 A	5/1999	Sterling et al.
5,645,060 A	7/1997	Yorkey	5,904,654 A	5/1999	Wohlmann et al.
5,645,440 A	7/1997	Tobler et al.	5,910,108 A	6/1999	Solenberger
5,651,780 A	7/1997	Jackson et al.	5,916,154 A	6/1999	Hobbs et al.
5,658,248 A	8/1997	Klein et al.	5,919,133 A	7/1999	Taylor
5,660,567 A	8/1997	Nierlich et al.	5,919,134 A	7/1999	Diab
5,662,106 A	9/1997	Swedlow et al.	5,921,921 A	7/1999	Potratz et al.
5,676,139 A	10/1997	Goldberger et al.	5,934,277 A	8/1999	Mortz
5,676,141 A	10/1997	Hollub	5,934,925 A	8/1999	Tobler et al.
5,678,544 A	10/1997	DeLonzor et al.	5,939,609 A	8/1999	Knapp et al.
5,685,299 A	11/1997	Diab et al.	5,940,182 A	8/1999	Lepper, Jr. et al.
5,685,301 A	11/1997	Klomhaus	5,954,644 A	9/1999	Dettling
5,687,719 A	11/1997	Sato et al.	5,978,691 A	11/1999	Mills
5,687,722 A	11/1997	Tien et al.	5,983,122 A	11/1999	Jarman et al.
5,690,104 A	11/1997	Kanemoto et al.	5,987,343 A	11/1999	Kinast
5,692,503 A	12/1997	Kuenstner	5,991,355 A	11/1999	Dahlke
5,697,371 A	12/1997	Aoyagi	5,995,855 A	11/1999	Kiani et al.
5,713,355 A	2/1998	Richardson et al.	5,995,856 A	11/1999	Mannheimer et al.
5,719,589 A	2/1998	Norman et al.	5,995,859 A	11/1999	Takahashi
5,720,284 A	2/1998	Aoyagi et al.	5,997,343 A	12/1999	Mills et al.
5,720,293 A	2/1998	Quinn et al.	5,999,841 A	12/1999	Aoyagi et al.
5,720,293 A	2/1998	Quinn et al.	6,002,952 A	12/1999	Diab et al.
D393,830 S	4/1998	Tobler et al.	6,006,119 A	12/1999	Soller et al.
5,742,718 A	4/1998	Harman et al.	6,011,986 A	1/2000	Diab et al.
5,743,262 A	4/1998	Lepper, Jr. et al.	6,014,576 A	1/2000	Raley
5,743,263 A	4/1998	Baker, Jr.	6,018,673 A	1/2000	Chin et al.
5,746,206 A	5/1998	Mannheimer	6,018,674 A	1/2000	Aronow
5,746,697 A	5/1998	Swedlow et al.	6,023,541 A	2/2000	Merchant et al.
5,752,914 A	5/1998	Delonzor et al.	6,027,452 A	2/2000	Flaherty et al.
5,755,226 A	5/1998	Carim et al.	6,036,642 A	3/2000	Diab et al.
5,758,644 A	6/1998	Diab et al.	6,045,509 A	4/2000	Caro et al.
5,760,910 A	6/1998	Lepper, Jr. et al.	6,064,898 A	5/2000	Aldrich
5,769,785 A	6/1998	Diab et al.	6,067,462 A	5/2000	Diab et al.
5,772,587 A	6/1998	Gratton et al.	6,068,594 A	5/2000	Schloemer et al.
5,779,630 A	7/1998	Fein et al.	6,073,037 A	6/2000	Alam et al.
5,782,237 A	7/1998	Casciani et al.	6,081,735 A	6/2000	Diab et al.
5,782,756 A	7/1998	Mannheimer	6,083,172 A	7/2000	Baker, Jr. et al.
5,782,757 A	7/1998	Diab et al.	6,088,607 A	7/2000	Diab et al.
5,785,659 A	7/1998	Caro et al.	6,094,592 A	7/2000	Yorkey et al.
5,790,729 A	8/1998	Pologe et al.	6,104,938 A	8/2000	Huiku
5,791,347 A	8/1998	Flaherty et al.	6,110,522 A	8/2000	Lepper, Jr. et al.
5,792,052 A	8/1998	Isaacson et al.	6,112,107 A	8/2000	Hannula
5,793,485 A	8/1998	Gourley	6,122,042 A	9/2000	Wunderman et al.
5,800,348 A	9/1998	Kaestle et al.	6,124,597 A	9/2000	Shehada
5,800,349 A	9/1998	Isaacson et al.	6,128,521 A	10/2000	Marro et al.
5,803,910 A	9/1998	Potratz	6,129,675 A	10/2000	Jay
5,807,246 A	9/1998	Sakaguchi et al.	6,132,363 A	10/2000	Freed et al.
5,807,247 A	9/1998	Merchant et al.	6,144,868 A	11/2000	Parker
5,810,723 A	9/1998	Aldrich	6,149,588 A	11/2000	Noda et al.
5,810,724 A	9/1998	Gronvall	6,151,516 A	11/2000	Kiani/Azarbayjany et al.
			6,151,518 A	11/2000	Hayashi
			6,152,754 A	11/2000	Gerhardt et al.
			6,154,667 A	11/2000	Miura et al.

(56)

References Cited

U.S. PATENT DOCUMENTS

6,157,041	A	12/2000	Thomas et al.	6,490,684	B1	12/2002	Fenstermaker et al.
6,157,850	A	12/2000	Diab et al.	6,497,659	B1	12/2002	Rafert
6,163,715	A	12/2000	Larsen et al.	6,501,974	B2	12/2002	Huiku
6,165,005	A	12/2000	Mills et al.	6,501,975	B2	12/2002	Diab et al.
6,165,173	A	12/2000	Kamdar et al.	6,504,943	B1	1/2003	Sweatt et al.
6,174,283	B1	1/2001	Nevo et al.	6,505,059	B1	1/2003	Kollias et al.
6,175,752	B1	1/2001	Say et al.	6,505,060	B1	1/2003	Norris
6,184,521	B1	2/2001	Coffin, IV et al.	6,505,061	B2	1/2003	Larson
6,192,261	B1	2/2001	Gratton et al.	6,505,133	B1	1/2003	Hanna
6,206,830	B1	3/2001	Diab et al.	6,510,329	B2	1/2003	Heckel
6,226,539	B1	5/2001	Potratz	6,515,273	B2	2/2003	Al/Al
6,229,856	B1	5/2001	Diab et al.	6,519,486	B1	2/2003	Edgar, Jr. et al.
6,230,035	B1	5/2001	Aoyagi et al.	6,519,487	B1	2/2003	Parker
6,232,609	B1	5/2001	Snyder et al.	6,522,398	B2	2/2003	Cadell et al.
6,236,872	B1	5/2001	Diab et al.	6,525,386	B1	2/2003	Mills et al.
6,237,604	B1	5/2001	Burnside et al.	6,526,300	B1	2/2003	Kiani et al.
6,241,683	B1	6/2001	Macklem et al.	6,526,301	B2	2/2003	Larsen et al.
6,253,097	B1	6/2001	Aronow et al.	6,528,809	B1	3/2003	Thomas et al.
6,256,523	B1	7/2001	Diab et al.	6,537,225	B1	3/2003	Mills
6,262,698	B1	7/2001	Blum	6,541,756	B2	4/2003	Schulz et al.
6,263,222	B1	7/2001	Diab et al.	6,542,763	B1	4/2003	Yamashita et al.
6,266,551	B1	7/2001	Osadchy et al.	6,542,764	B1	4/2003	Al/Al et al.
6,272,363	B1	8/2001	Casciani et al.	6,545,652	B1	4/2003	Tsuji
6,278,522	B1	8/2001	Lepper, Jr. et al.	6,546,267	B1	4/2003	Sugiura
6,280,213	B1	8/2001	Tobler et al.	6,553,241	B2	4/2003	Mannheimer et al.
6,285,895	B1	9/2001	Ristolainen et al.	6,564,077	B2	5/2003	Mortara
6,285,896	B1	9/2001	Tobler et al.	6,571,113	B1	5/2003	Fein et al.
6,295,330	B1	9/2001	Skog et al.	6,580,086	B1	6/2003	Schulz et al.
6,298,252	B1	10/2001	Kovach et al.	6,582,964	B1	6/2003	Samsoondar et al.
6,298,255	B1	10/2001	Cordero et al.	6,584,336	B1	6/2003	Ali et al.
6,301,493	B1	10/2001	Marro et al.	6,584,413	B1	6/2003	Keenan et al.
6,304,675	B1	10/2001	Osbourne et al.	6,591,123	B2	7/2003	Fein et al.
6,304,767	B1	10/2001	Soller et al.	6,594,511	B2	7/2003	Stone et al.
6,317,627	B1	11/2001	Ennen et al.	6,595,316	B2	7/2003	Cybulski et al.
6,321,100	B1	11/2001	Parker	6,597,932	B2	7/2003	Tian et al.
6,325,761	B1	12/2001	Jay	6,597,933	B2	7/2003	Kiani et al.
6,330,468	B1	12/2001	Scharf	6,600,940	B1	7/2003	Fein et al.
6,334,065	B1	12/2001	Al/Al et al.	6,606,509	B2	8/2003	Schmitt
6,336,900	B1	1/2002	Alleckson et al.	6,606,510	B2	8/2003	Swedlow et al.
6,339,715	B1	1/2002	Bahr et al.	6,606,511	B1	8/2003	Ali et al.
6,341,257	B1	1/2002	Haaland	6,611,698	B1	8/2003	Yamashita et al.
6,343,224	B1	1/2002	Parker	6,614,521	B2	9/2003	Samsoondar et al.
6,349,228	B1	2/2002	Kiani et al.	6,615,064	B1	9/2003	Aldrich
6,351,658	B1	2/2002	Middleman et al.	6,615,151	B1	9/2003	Seccina et al.
6,356,774	B1	3/2002	Bernstein et al.	6,618,602	B2	9/2003	Levin
6,360,113	B1	3/2002	Dettling	6,622,095	B2	9/2003	Kobayashi et al.
6,360,114	B1	3/2002	Diab et al.	6,628,975	B1	9/2003	Fein et al.
6,363,269	B1	3/2002	Hanna et al.	6,631,281	B1	10/2003	Kastle
6,368,283	B1	4/2002	Xu et al.	6,632,181	B2	10/2003	Flaherty et al.
6,371,921	B1	4/2002	Caro et al.	6,639,668	B1	10/2003	Trepagnier
6,374,129	B1	4/2002	Chin et al.	6,640,116	B2	10/2003	Diab
6,377,828	B1	4/2002	Chaiken et al.	6,643,530	B2	11/2003	Diab et al.
6,377,829	B1	4/2002	Al/Al	6,645,142	B2	11/2003	Braig et al.
6,388,240	B2	5/2002	Schulz et al.	6,650,917	B2	11/2003	Diab et al.
6,393,310	B1	5/2002	Kuenstner	6,654,623	B1	11/2003	Kastle
6,397,091	B2	5/2002	Diab et al.	6,654,624	B2	11/2003	Diab et al.
6,397,092	B1	5/2002	Norris et al.	6,657,717	B2	12/2003	Cadell et al.
6,397,093	B1	5/2002	Aldrich	6,658,276	B2	12/2003	Kiani et al.
6,408,198	B1	6/2002	Hanna et al.	6,658,277	B2	12/2003	Wasserman
6,411,833	B1	6/2002	Baker, Jr. et al.	6,661,161	B1	12/2003	Lanzo et al.
6,415,166	B1	7/2002	Van Hoy et al.	6,662,033	B2	12/2003	Casciani et al.
6,415,233	B1	7/2002	Haaland	6,665,551	B1	12/2003	Suzuki
6,415,236	B2	7/2002	Kobayashi et al.	6,668,183	B2	12/2003	Hicks et al.
6,430,437	B1	8/2002	Marro	6,671,526	B1	12/2003	Aoyagi et al.
6,430,525	B1	8/2002	Weber et al.	6,671,531	B2	12/2003	Al/Al et al.
6,434,408	B1	8/2002	Heckel	6,675,031	B1	1/2004	Porges et al.
6,441,388	B1	8/2002	Thomas et al.	6,675,106	B1	1/2004	Keenan et al.
6,453,184	B1	9/2002	Hyogo et al.	6,676,600	B1	1/2004	Conero et al.
6,455,340	B1	9/2002	Chua et al.	6,678,543	B2	1/2004	Diab et al.
6,463,310	B1	10/2002	Swedlow et al.	6,681,126	B2	1/2004	Solenberger
6,463,311	B1	10/2002	Diab	6,684,090	B2	1/2004	Ali et al.
6,466,824	B1	10/2002	Struble	6,684,091	B2	1/2004	Parker
6,470,199	B1	10/2002	Kopotic et al.	6,687,620	B1	2/2004	Haaland et al.
6,480,729	B2	11/2002	Stone	6,690,466	B2	2/2004	Miller et al.
6,490,466	B1	12/2002	Fein et al.	6,694,157	B1	2/2004	Stone et al.
				6,697,655	B2	2/2004	Sueppel et al.
				6,697,656	B1	2/2004	Al/Al
				6,697,657	B1	2/2004	Shehada et al.
				6,697,658	B2	2/2004	Al/Al

(56)

References Cited

U.S. PATENT DOCUMENTS

RE38,476 E	3/2004	Diab et al.	6,939,305 B2	9/2005	Flaherty et al.
6,699,194 B1	3/2004	Diab et al.	6,943,348 B1	9/2005	Coffin, IV
6,701,170 B2	3/2004	Stetson	6,944,487 B2	9/2005	Maynard et al.
6,708,049 B1	3/2004	Berson et al.	6,950,687 B2	9/2005	Al/Ali
6,711,503 B2	3/2004	Haaland	6,961,598 B2	11/2005	Diab
6,714,803 B1	3/2004	Mortz	6,970,792 B1	11/2005	Diab
6,714,804 B2	3/2004	Al-Ali et al.	6,975,891 B2	12/2005	Pawluczyk
6,714,805 B2	3/2004	Jeon et al.	6,979,812 B2	12/2005	Al/Ali
RE38,492 E	4/2004	Diab et al.	6,985,764 B2	1/2006	Mason et al.
6,719,705 B2	4/2004	Mills	6,987,994 B1	1/2006	Mortz
6,720,734 B2	4/2004	Norris	6,993,371 B2	1/2006	Kiani et al.
6,721,582 B2	4/2004	Trepagnier et al.	6,996,427 B2	2/2006	Ali et al.
6,721,584 B2	4/2004	Baker, Jr. et al.	6,999,904 B2	2/2006	Weber et al.
6,721,585 B1	4/2004	Parker	7,001,337 B2	2/2006	Dekker
6,725,074 B1	4/2004	Kastle	7,003,338 B2	2/2006	Weber et al.
6,725,075 B2	4/2004	Al/Ali	7,003,339 B2	2/2006	Diab et al.
6,726,634 B2	4/2004	Freeman	7,006,856 B2	2/2006	Baker, Jr. et al.
6,728,560 B2	4/2004	Kollias et al.	7,015,451 B2	3/2006	Dalke et al.
6,735,459 B2	5/2004	Parker	7,024,233 B2	4/2006	Ali et al.
6,741,875 B1	5/2004	Pawluczyk et al.	7,027,849 B2	4/2006	Al/Ali
6,741,876 B1	5/2004	Seccina et al.	7,030,749 B2	4/2006	Al/Ali
6,743,172 B1	6/2004	Blike	7,039,449 B2	5/2006	Al/Ali
6,745,060 B2	6/2004	Diab et al.	7,041,060 B2	5/2006	Flaherty et al.
6,745,061 B1	6/2004	Hicks et al.	7,044,918 B2	5/2006	Diab
6,748,253 B2	6/2004	Norris et al.	7,067,893 B2	6/2006	Mills et al.
6,748,254 B2	6/2004	O'Neil et al.	7,096,052 B2	8/2006	Mason et al.
6,754,515 B1	6/2004	Pologe	7,096,054 B2	8/2006	Abdul/Hafiz et al.
6,754,516 B2	6/2004	Mannheimer	7,132,641 B2	11/2006	Schulz et al.
6,760,607 B2	7/2004	Al/Ali	7,142,901 B2	11/2006	Kiani et al.
6,760,609 B2	7/2004	Jacques	7,149,561 B2	12/2006	Diab
6,770,028 B1	8/2004	Ali et al.	7,186,966 B2	3/2007	Al/Ali
6,771,994 B2	8/2004	Kiani et al.	7,190,261 B2	3/2007	Al/Ali
6,773,397 B2	8/2004	Kelly	7,215,984 B2	5/2007	Diab
6,778,923 B2	8/2004	Norris et al.	7,215,986 B2	5/2007	Diab
6,780,158 B2	8/2004	Yarita	7,221,971 B2	5/2007	Diab
6,788,849 B1	9/2004	Pawluczyk	7,225,006 B2	5/2007	Al/Ali et al.
6,792,300 B1	9/2004	Diab et al.	7,225,007 B2	5/2007	Al/Ali
6,800,373 B2	10/2004	Gorzycza	RE39,672 E	6/2007	Shehada et al.
6,801,797 B2	10/2004	Mannheimer et al.	7,239,905 B2	7/2007	Kiani/Azarbayjany et al.
6,801,799 B2	10/2004	Mendelson	7,245,953 B1	7/2007	Parker
6,810,277 B2	10/2004	Edgar, Jr. et al.	7,254,429 B2	8/2007	Schurman et al.
6,813,511 B2	11/2004	Diab et al.	7,254,431 B2	8/2007	Al/Ali
6,816,741 B2	11/2004	Diab	7,254,433 B2	8/2007	Diab et al.
6,819,950 B2	11/2004	Mills	7,254,434 B2	8/2007	Schulz et al.
6,822,564 B2	11/2004	Al/Ali	7,272,425 B2	9/2007	Al/Ali
6,825,619 B2	11/2004	Norris	7,274,955 B2	9/2007	Kiani et al.
6,826,419 B2	11/2004	Diab et al.	D554,263 S	10/2007	Al/Ali
6,829,496 B2	12/2004	Nagai et al.	7,280,858 B2	10/2007	Al/Ali et al.
6,829,501 B2	12/2004	Nielsen et al.	7,289,835 B2	10/2007	Mansfield et al.
6,830,711 B2	12/2004	Mills et al.	7,292,883 B2	11/2007	De Felice et al.
6,836,679 B2	12/2004	Baker, Jr. et al.	7,295,866 B2	11/2007	Al/Ali
6,839,579 B1	1/2005	Chin	7,299,080 B2	11/2007	Acosta et al.
6,839,580 B2	1/2005	Zonios et al.	7,328,053 B1	2/2008	Diab et al.
6,839,582 B2	1/2005	Heckel	7,332,784 B2	2/2008	Mills et al.
6,842,702 B2	1/2005	Haaland et al.	7,340,287 B2	3/2008	Mason et al.
6,845,256 B2	1/2005	Chin et al.	7,341,559 B2	3/2008	Schulz et al.
6,847,835 B1	1/2005	Yamanishi	7,343,186 B2	3/2008	Lamego et al.
6,850,787 B2	2/2005	Weber et al.	D566,282 S	4/2008	Al/Ali et al.
6,850,788 B2	2/2005	Al/Ali	7,355,512 B1	4/2008	Al/Ali
6,852,083 B2	2/2005	Caro et al.	7,356,365 B2	4/2008	Schurman
6,861,639 B2	3/2005	Al/Ali	7,371,981 B2	5/2008	Abdul/Hafiz
6,861,641 B1	3/2005	Adams	7,373,193 B2	5/2008	Al/Ali et al.
6,869,402 B2	3/2005	Arnold	7,373,194 B2	5/2008	Weber et al.
6,882,874 B2	4/2005	Huiku	7,376,453 B1	5/2008	Diab et al.
6,898,452 B2	5/2005	Al/Ali et al.	7,377,794 B2	5/2008	Al/Ali et al.
6,912,049 B2	6/2005	Pawluczyk et al.	7,377,899 B2	5/2008	Weber et al.
6,917,422 B2	7/2005	Samsoondar et al.	7,383,070 B2	6/2008	Diab et al.
6,919,566 B1	7/2005	Cadell	7,415,297 B2	8/2008	Al/Ali et al.
6,920,345 B2	7/2005	Al/Ali et al.	7,428,432 B2	9/2008	Ali et al.
6,921,367 B2	7/2005	Mills	7,438,683 B2	10/2008	Al/Ali et al.
6,922,645 B2	7/2005	Haaland et al.	7,440,787 B2	10/2008	Diab
6,928,311 B1	8/2005	Pawluczyk et al.	7,454,240 B2	11/2008	Diab et al.
6,931,268 B1	8/2005	Kiani/Azarbayjany et al.	7,467,002 B2	12/2008	Weber et al.
6,931,269 B2	8/2005	Terry	7,469,157 B2	12/2008	Diab et al.
6,934,570 B2	8/2005	Kiani et al.	7,471,969 B2	12/2008	Diab et al.
			7,471,971 B2	12/2008	Diab et al.
			7,483,729 B2	1/2009	Al/Ali et al.
			7,483,730 B2	1/2009	Diab et al.
			7,489,958 B2	2/2009	Diab et al.

(56)

References Cited

U.S. PATENT DOCUMENTS

7,496,391	B2	2/2009	Diab et al.	8,130,105	B2	3/2012	Al/Ali et al.
7,496,393	B2	2/2009	Diab et al.	8,145,287	B2	3/2012	Diab et al.
D587,657	S	3/2009	Al/Ali et al.	8,150,487	B2	4/2012	Diab et al.
7,499,741	B2	3/2009	Diab et al.	8,175,672	B2	5/2012	Parker
7,499,835	B2	3/2009	Weber et al.	8,180,420	B2	5/2012	Diab et al.
7,500,950	B2	3/2009	Al/Ali et al.	8,182,443	B1	5/2012	Kiani
7,509,154	B2	3/2009	Diab et al.	8,185,180	B2	5/2012	Diab et al.
7,509,494	B2	3/2009	Al/Ali	8,190,223	B2	5/2012	Al/Ali et al.
7,510,849	B2	3/2009	Schurman et al.	8,190,227	B2	5/2012	Diab et al.
7,526,328	B2	4/2009	Diab et al.	8,203,438	B2	6/2012	Kiani et al.
7,530,942	B1	5/2009	Diab	8,224,411	B2	7/2012	Al/Ali et al.
7,530,949	B2	5/2009	Al/Ali et al.	8,228,181	B2	7/2012	Al/Ali
7,530,955	B2	5/2009	Diab et al.	8,229,533	B2	7/2012	Diab et al.
7,563,110	B2	7/2009	Al/Ali et al.	8,233,955	B2	7/2012	Al/Ali et al.
7,596,398	B2	9/2009	Al/Ali et al.	8,244,325	B2	8/2012	Al/Ali et al.
7,606,861	B2	10/2009	Killcommons et al.	8,255,026	B1	8/2012	Al/Ali
7,618,375	B2	11/2009	Flaherty	8,255,027	B2	8/2012	Al/Ali et al.
D606,659	S	12/2009	Kiani et al.	8,255,028	B2	8/2012	Al/Ali et al.
7,647,083	B2	1/2010	Al/Ali et al.	8,260,577	B2	9/2012	Weber et al.
D609,193	S	2/2010	Al/Ali et al.	8,265,723	B1	9/2012	McHale et al.
D614,305	S	4/2010	Al/Ali et al.	8,274,360	B2	9/2012	Sampath et al.
RE41,317	E	5/2010	Parker	8,301,217	B2	10/2012	Al/Ali et al.
7,729,733	B2	6/2010	Al/Ali et al.	8,310,336	B2	11/2012	Muhsin et al.
7,734,320	B2	6/2010	Al/Ali	8,315,683	B2	11/2012	Al/Ali et al.
7,761,127	B2	7/2010	Al/Ali et al.	RE43,860	E	12/2012	Parker
7,761,128	B2	7/2010	Al/Ali et al.	8,337,403	B2	12/2012	Al/Ali et al.
7,764,982	B2	7/2010	Dalke et al.	8,346,330	B2	1/2013	Lamego
D621,516	S	8/2010	Kiani et al.	8,353,842	B2	1/2013	Al/Ali et al.
7,791,155	B2	9/2010	Diab	8,355,766	B2	1/2013	MacNeish, III et al.
7,801,581	B2	9/2010	Diab	8,359,080	B2	1/2013	Diab et al.
7,822,452	B2	10/2010	Schurman et al.	8,364,223	B2	1/2013	Al/Ali et al.
RE41,912	E	11/2010	Parker	8,364,226	B2	1/2013	Diab et al.
7,844,313	B2	11/2010	Kiani et al.	8,374,665	B2	2/2013	Lamego
7,844,314	B2	11/2010	Al/Ali	8,385,995	B2	2/2013	Al/Ali et al.
7,844,315	B2	11/2010	Al/Ali	8,385,996	B2	2/2013	Smith et al.
7,865,222	B2	1/2011	Weber et al.	8,388,353	B2	3/2013	Kiani et al.
7,873,497	B2	1/2011	Weber et al.	8,399,822	B2	3/2013	Al/Ali
7,880,606	B2	2/2011	Al/Ali	8,401,602	B2	3/2013	Kiani
7,880,626	B2	2/2011	Al/Ali et al.	8,405,608	B2	3/2013	Al/Ali et al.
7,891,355	B2	2/2011	Al/Ali et al.	8,414,499	B2	4/2013	Al/Ali et al.
7,894,868	B2	2/2011	Al/Ali et al.	8,418,524	B2	4/2013	Al/Ali
7,899,507	B2	3/2011	Al/Ali et al.	8,423,106	B2	4/2013	Lamego et al.
7,899,518	B2	3/2011	Trepagnier et al.	8,428,967	B2	4/2013	Olsen et al.
7,904,132	B2	3/2011	Weber et al.	8,430,817	B1	4/2013	Al/Ali et al.
7,909,772	B2	3/2011	Popov et al.	8,437,825	B2	5/2013	Dalvi et al.
7,910,875	B2	3/2011	Al/Ali	8,455,290	B2	6/2013	Siskavich
7,919,713	B2	4/2011	Al/Ali et al.	8,457,703	B2	6/2013	Al/Ali
7,937,128	B2	5/2011	Al/Ali	8,457,707	B2	6/2013	Kiani
7,937,129	B2	5/2011	Mason et al.	8,463,349	B2	6/2013	Diab et al.
7,937,130	B2	5/2011	Diab et al.	8,466,286	B2	6/2013	Bellott et al.
7,941,199	B2	5/2011	Kiani	8,471,713	B2	6/2013	Poeze et al.
7,951,086	B2	5/2011	Flaherty et al.	8,473,020	B2	6/2013	Kiani et al.
7,957,780	B2	6/2011	Lamego et al.	8,483,787	B2	7/2013	Al/Ali et al.
7,962,188	B2	6/2011	Kiani et al.	8,489,364	B2	7/2013	Weber et al.
7,962,190	B1	6/2011	Diab et al.	8,498,684	B2	7/2013	Weber et al.
7,976,472	B2	7/2011	Kiani	8,509,867	B2	8/2013	Workman et al.
7,988,637	B2	8/2011	Diab	8,515,509	B2	8/2013	Bruinsma et al.
7,990,382	B2	8/2011	Kiani	8,523,781	B2	9/2013	Al/Ali
7,991,446	B2	8/2011	Al/Ali et al.	8,529,301	B2	9/2013	Al/Ali et al.
8,000,761	B2	8/2011	Al/Ali	8,532,727	B2	9/2013	Ali et al.
8,008,088	B2	8/2011	Bellott et al.	8,532,728	B2	9/2013	Diab et al.
RE42,753	E	9/2011	Kiani/Azarbayjany et al.	D692,145	S	10/2013	Al-Ali et al.
8,019,400	B2	9/2011	Diab et al.	8,547,209	B2	10/2013	Kiani et al.
8,028,701	B2	10/2011	Al/Ali et al.	8,548,548	B2	10/2013	Al/Ali
8,029,765	B2	10/2011	Bellott et al.	8,548,550	B2	10/2013	Al/Ali et al.
8,036,728	B2	10/2011	Diab et al.	8,560,032	B2	10/2013	Al/Ali et al.
8,046,040	B2	10/2011	Ali et al.	8,560,034	B1	10/2013	Diab et al.
8,046,041	B2	10/2011	Diab et al.	8,570,167	B2	10/2013	Al-Ali
8,046,042	B2	10/2011	Diab et al.	8,570,503	B2	10/2013	Vo et al.
8,048,040	B2	11/2011	Kiani	8,571,617	B2	10/2013	Reichgott et al.
8,050,728	B2	11/2011	Al/Ali et al.	8,571,618	B1	10/2013	Lamego et al.
RE43,169	E	2/2012	Parker	8,571,619	B2	10/2013	Al-Ali et al.
8,118,620	B2	2/2012	Al/Ali et al.	8,577,431	B2	11/2013	Lamego et al.
8,126,528	B2	2/2012	Diab et al.	8,581,732	B2	11/2013	Al-Ali et al.
8,128,572	B2	3/2012	Diab et al.	8,584,345	B2	11/2013	Al-Ali et al.
				8,588,880	B2	11/2013	Abdul-Hafiz et al.
				8,600,467	B2	12/2013	Al-Ali et al.
				8,606,342	B2	12/2013	Diab
				8,626,255	B2	1/2014	Al-Ali et al.

(56)

References Cited

U.S. PATENT DOCUMENTS

8,630,691	B2	1/2014	Lamego et al.	2002/0156353	A1	10/2002	Larson
8,634,889	B2	1/2014	Al-Ali et al.	2002/0159002	A1	10/2002	Chang
8,641,631	B2	2/2014	Sierra et al.	2002/0161291	A1	10/2002	Kianl et al.
8,652,060	B2	2/2014	Al-Ali	2002/0165440	A1	11/2002	Mason et al.
8,663,107	B2	3/2014	Kiani	2002/0183819	A1	12/2002	Struble
8,666,468	B1	3/2014	Al-Ali	2003/0045784	A1	3/2003	Palatnik et al.
8,667,967	B2	3/2014	Al-Ali et al.	2003/0045785	A1	3/2003	Diab et al.
8,670,811	B2	3/2014	O'Reilly	2003/0049232	A1	3/2003	Page et al.
8,670,814	B2	3/2014	Diab et al.	2003/0109775	A1	6/2003	O'Neil et al.
8,676,286	B2	3/2014	Weber et al.	2003/0116769	A1	6/2003	Song et al.
8,682,407	B2	3/2014	Al-Ali	2003/0117296	A1	6/2003	Seely
RE44,823	E	4/2014	Parker	2003/0120160	A1	6/2003	Yarita
RE44,875	E	4/2014	Kiani et al.	2003/0120164	A1	6/2003	Nielsen et al.
8,690,799	B2	4/2014	Telfort et al.	2003/0135099	A1	7/2003	Al-Ali
8,700,112	B2	4/2014	Kiani	2003/0139657	A1	7/2003	Solenberger
8,702,627	B2	4/2014	Telfort et al.	2003/0160257	A1	8/2003	Bader et al.
8,706,179	B2	4/2014	Parker	2003/0195402	A1	10/2003	Fein et al.
8,712,494	B1	4/2014	MacNeish, III et al.	2004/0006261	A1	1/2004	Swedlow et al.
8,715,206	B2	5/2014	Telfort et al.	2004/0033618	A1	2/2004	Haass et al.
8,718,735	B2	5/2014	Lamego et al.	2004/0034898	A1	2/2004	Bruegl
8,718,737	B2	5/2014	Diab et al.	2004/0059209	A1	3/2004	Al-Ali et al.
8,718,738	B2	5/2014	Blank et al.	2004/0064259	A1	4/2004	Haaland et al.
8,720,249	B2	5/2014	Al-Ali	2004/0081621	A1	4/2004	Arndt et al.
8,721,541	B2	5/2014	Al-Ali et al.	2004/0092805	A1	5/2004	Yarita
8,721,542	B2	5/2014	Al-Ali et al.	2004/0133087	A1	7/2004	Ali et al.
8,723,677	B1	5/2014	Kiani	2004/0138538	A1	7/2004	Stetson
8,740,792	B1	6/2014	Kiani et al.	2004/0138540	A1	7/2004	Baker, Jr. et al.
8,754,776	B2	6/2014	Poeze et al.	2004/0147822	A1	7/2004	Al-Ali et al.
8,755,535	B2	6/2014	Telfort et al.	2004/0147823	A1	7/2004	Kiani et al.
8,755,856	B2	6/2014	Diab et al.	2004/0158132	A1	8/2004	Zaleski
8,755,872	B1	6/2014	Marinow	2004/0158134	A1	8/2004	Diab et al.
8,761,850	B2	6/2014	Lamego	2004/0158135	A1	8/2004	Baker, Jr. et al.
8,764,671	B2	7/2014	Kiani	2004/0162472	A1	8/2004	Berson et al.
8,768,423	B2	7/2014	Shakespeare et al.	2004/0167382	A1	8/2004	Gardner et al.
8,771,204	B2	7/2014	Telfort et al.	2004/0176670	A1	9/2004	Takamura et al.
8,777,634	B2	7/2014	Kiani et al.	2004/0181134	A1	9/2004	Baker, Jr. et al.
8,781,543	B2	7/2014	Diab et al.	2004/0199063	A1	10/2004	O'Neil et al.
8,781,544	B2	7/2014	Al-Ali et al.	2004/0204639	A1	10/2004	Casciani et al.
8,781,549	B2	7/2014	Al-Ali et al.	2004/0204868	A1	10/2004	Maynard et al.
8,788,003	B2	7/2014	Schurman et al.	2004/0229391	A1	11/2004	Ohya et al.
8,790,268	B2	7/2014	Al-Ali	2004/0262046	A1	12/2004	Simond et al.
8,801,613	B2	8/2014	Al-Ali et al.	2004/0267103	A1	12/2004	Li et al.
8,821,397	B2	9/2014	Al-Ali et al.	2004/0267140	A1	12/2004	Ito et al.
8,821,415	B2	9/2014	Al-Ali et al.	2005/0011488	A1	1/2005	Doucet
8,830,449	B1	9/2014	Lamego et al.	2005/0043902	A1	2/2005	Haaland et al.
8,831,700	B2	9/2014	Schurman et al.	2005/0049469	A1	3/2005	Aoyagi et al.
8,840,549	B2	9/2014	Al-Ali et al.	2005/0054908	A1	3/2005	Blank et al.
8,847,740	B2	9/2014	Kiani et al.	2005/0070773	A1	3/2005	Chin et al.
8,849,365	B2	9/2014	Smith et al.	2005/0070775	A1	3/2005	Chin et al.
8,852,094	B2	10/2014	Al-Ali et al.	2005/0075546	A1	4/2005	Samsoondar et al.
8,852,994	B2	10/2014	Wojtczuk et al.	2005/0085704	A1	4/2005	Schulz et al.
8,868,147	B2	10/2014	Stippick et al.	2005/0085735	A1	4/2005	Baker, Jr. et al.
8,868,150	B2	10/2014	Al-Ali et al.	2005/0124871	A1	6/2005	Baker, Jr. et al.
8,870,792	B2	10/2014	Al-Ali et al.	2005/0143634	A1	6/2005	Baker, Jr. et al.
8,886,271	B2	11/2014	Kiani et al.	2005/0143943	A1	6/2005	Brown
8,888,539	B2	11/2014	Al-Ali et al.	2005/0148834	A1	7/2005	Hull et al.
8,888,708	B2	11/2014	Diab et al.	2005/0184895	A1	8/2005	Petersen et al.
8,892,180	B2	11/2014	Weber et al.	2005/0187447	A1	8/2005	Chew et al.
8,897,847	B2	11/2014	Al-Ali	2005/0187448	A1	8/2005	Petersen et al.
8,909,310	B2	12/2014	Lamego et al.	2005/0187449	A1	8/2005	Chew et al.
2001/0044700	A1	11/2001	Kobayashi et al.	2005/0187450	A1	8/2005	Chew et al.
2001/0045532	A1	11/2001	Schulz et al.	2005/0187452	A1	8/2005	Petersen et al.
2002/0021269	A1	2/2002	Rast	2005/0187453	A1	8/2005	Petersen et al.
2002/0026107	A1	2/2002	Kiani et al.	2005/0197549	A1	9/2005	Baker, Jr.
2002/0035318	A1	3/2002	Mannheimer et al.	2005/0197579	A1	9/2005	Baker, Jr.
2002/0038078	A1	3/2002	Ito	2005/0197793	A1	9/2005	Baker, Jr.
2002/0038081	A1	3/2002	Fein et al.	2005/0203357	A1	9/2005	Debreczeny et al.
2002/0059047	A1	5/2002	Haaland	2005/0209515	A1	9/2005	Hockersmith et al.
2002/0068858	A1	6/2002	Braig et al.	2005/0228253	A1	10/2005	Debreczeny
2002/0082488	A1	6/2002	Al-Ali et al.	2005/0250997	A1	11/2005	Takeda et al.
2002/0095077	A1	7/2002	Swedlow et al.	2006/0030764	A1	2/2006	Porges et al.
2002/0095078	A1	7/2002	Mannheimer et al.	2006/0210120	A1	9/2006	Rowe et al.
2002/0111748	A1	8/2002	Kobayashi et al.	2006/0211922	A1	9/2006	Al-Ali et al.
2002/0115919	A1	8/2002	Al-Ali	2006/0211923	A1	9/2006	Al-Ali et al.
2002/0154665	A1	10/2002	Funabashi et al.	2006/0211924	A1	9/2006	Smith et al.
				2006/0211925	A1	9/2006	Lamego et al.
				2006/0211932	A1	9/2006	Al-Ali et al.
				2006/0226992	A1	10/2006	Al-Ali et al.
				2006/0229509	A1	10/2006	Al-Ali et al.

(56)

References Cited

U.S. PATENT DOCUMENTS

2006/0238358 A1 10/2006 Al-Ali et al.
 2006/0241358 A1 10/2006 Al-Ali et al.
 2006/0241363 A1 10/2006 Al-Ali et al.
 2009/0247984 A1 10/2009 Lamego et al.
 2009/0275844 A1 11/2009 Al-Ali
 2009/0299157 A1 12/2009 Telfort et al.
 2010/0004518 A1 1/2010 Vo et al.
 2010/0030040 A1 2/2010 Poeze et al.
 2010/0069725 A1 3/2010 Al-Ali
 2010/0261979 A1 10/2010 Kiani
 2010/0317936 A1 12/2010 Al-Ali et al.
 2011/0001605 A1 1/2011 Kiani et al.
 2011/0009719 A1 1/2011 Al-Ali et al.
 2011/0082711 A1 4/2011 Poeze et al.
 2011/0105854 A1 5/2011 Kiani et al.
 2011/0172967 A1 7/2011 Al-Ali et al.
 2011/0208015 A1 8/2011 Welch et al.
 2011/0209915 A1 9/2011 Telfort et al.
 2011/0213212 A1 9/2011 Al-Ali
 2011/0230733 A1 9/2011 Al-Ali
 2011/0237911 A1 9/2011 Lamego et al.
 2011/0237914 A1 9/2011 Lamego
 2012/0059267 A1 3/2012 Lamego et al.
 2012/0116175 A1 5/2012 Al-Ali et al.
 2012/0179006 A1 7/2012 Jansen et al.
 2012/0209082 A1 8/2012 Al-Ali
 2012/0209084 A1 8/2012 Olsen et al.
 2012/0227739 A1 9/2012 Kiani
 2012/0265039 A1 10/2012 Kiani
 2012/0283524 A1 11/2012 Kiani et al.
 2012/0286955 A1 11/2012 Welch et al.
 2012/0296178 A1 11/2012 Lamego et al.
 2012/0319816 A1 12/2012 Al-Ali
 2012/0330112 A1 12/2012 Lamego et al.
 2013/0023775 A1 1/2013 Lamego et al.
 2013/0041591 A1 2/2013 Lamego
 2013/0045685 A1 2/2013 Kiani
 2013/0046204 A1 2/2013 Lamego et al.
 2013/0060108 A1 3/2013 Schurman et al.
 2013/0060147 A1 3/2013 Welch et al.
 2013/0079610 A1 3/2013 Al-Ali
 2013/0096405 A1 4/2013 Garfio
 2013/0096936 A1 4/2013 Sampath et al.
 2013/0109935 A1 5/2013 Al-Ali et al.
 2013/0162433 A1 6/2013 Muhsin et al.
 2013/0178749 A1 7/2013 Lamego
 2013/0190581 A1 7/2013 Al-Ali et al.
 2013/0197328 A1 8/2013 Diab et al.
 2013/0211214 A1 8/2013 Olsen
 2013/0243021 A1 9/2013 Siskavich
 2013/0253334 A1 9/2013 Al-Ali et al.
 2013/0274571 A1 10/2013 Diab et al.
 2013/0296672 A1 11/2013 O'Neil et al.
 2013/0317327 A1 11/2013 Al-Ali et al.
 2013/0317370 A1 11/2013 Dalvi et al.
 2013/0324808 A1 12/2013 Al-Ali et al.
 2013/0324817 A1 12/2013 Diab
 2013/0331670 A1 12/2013 Kiani
 2013/0338461 A1 12/2013 Lamego et al.
 2014/0012100 A1 1/2014 Al-Ali et al.
 2014/0025306 A1 1/2014 Weber et al.
 2014/0034353 A1 2/2014 Al-Ali et al.
 2014/0051952 A1 2/2014 Reichgott et al.
 2014/0051953 A1 2/2014 Lamego et al.
 2014/0051954 A1 2/2014 Al-Ali et al.
 2014/0058230 A1 2/2014 Abdul-Hafiz et al.
 2014/0066783 A1 3/2014 Kiani et al.
 2014/0077956 A1 3/2014 Sampath et al.
 2014/0081097 A1 3/2014 Al-Ali et al.
 2014/0081100 A1 3/2014 Muhsin et al.
 2014/0081175 A1 3/2014 Telfort
 2014/0094667 A1 4/2014 Schurman et al.
 2014/0100434 A1 4/2014 Diab et al.
 2014/0114199 A1 4/2014 Lamego et al.
 2014/0120564 A1 5/2014 Workman et al.

2014/0121482 A1 5/2014 Merritt et al.
 2014/0121483 A1 5/2014 Kiani
 2014/0125495 A1 5/2014 Al-Ali
 2014/0127137 A1 5/2014 Bellott et al.
 2014/0128696 A1 5/2014 Al-Ali
 2014/0128699 A1 5/2014 Al-Ali et al.
 2014/0129702 A1 5/2014 Lamego et al.
 2014/0135588 A1 5/2014 Al-Ali et al.
 2014/0142399 A1 5/2014 Al-Ali et al.
 2014/0142401 A1 5/2014 Al-Ali et al.
 2014/0142402 A1 5/2014 Al-Ali et al.
 2014/0163344 A1 6/2014 Al-Ali
 2014/0163402 A1 6/2014 Lamego et al.
 2014/0166076 A1 6/2014 Kiani et al.
 2014/0171763 A1 6/2014 Diab
 2014/0180038 A1 6/2014 Kiani
 2014/0180154 A1 6/2014 Sierra et al.
 2014/0194709 A1 7/2014 Al-Ali et al.
 2014/0194711 A1 7/2014 Al-Ali
 2014/0194766 A1 7/2014 Al-Ali et al.
 2014/0200420 A1 7/2014 Al-Ali
 2014/0200422 A1 7/2014 Weber et al.
 2014/0206963 A1 7/2014 Al-Ali
 2014/0213864 A1 7/2014 Abdul-Hafiz et al.
 2014/0243627 A1 8/2014 Diab et al.
 2014/0266790 A1 9/2014 Al-Ali et al.
 2014/0275808 A1 9/2014 Poeze et al.
 2014/0275835 A1 9/2014 Lamego et al.
 2014/0275871 A1 9/2014 Lamego et al.
 2014/0275872 A1 9/2014 Merritt et al.
 2014/0275881 A1 9/2014 Lamego et al.
 2014/0288400 A1 9/2014 Diab et al.
 2014/0296664 A1 10/2014 Bruinsma et al.
 2014/0303520 A1 10/2014 Telfort et al.
 2014/0309506 A1 10/2014 Lamego et al.
 2014/0309559 A1 10/2014 Telfort et al.
 2014/0316228 A1 10/2014 Blank et al.
 2014/0323825 A1 10/2014 Al-Ali et al.
 2014/0330092 A1 11/2014 Al-Ali et al.
 2014/0330098 A1 11/2014 Merritt et al.
 2014/0330099 A1 11/2014 Al-Ali et al.
 2014/0333440 A1 11/2014 Kiani
 2014/0336481 A1 11/2014 Shakespeare et al.
 2014/0343436 A1 11/2014 Kiani

FOREIGN PATENT DOCUMENTS

EP 0569 670 2/1993
 EP 0675541 10/1995
 EP 0469395 B1 2/1996
 EP 0417447 B1 10/1997
 EP 0606356 B1 6/1998
 EP 0734221 B1 7/1998
 EP 1895892 5/2010
 EP 2305104 4/2011
 JP 61/28172 2/1986
 JP 62/000324 1/1987
 JP 63/275327 11/1988
 JP 64/500495 2/1989
 JP 2/145457 12/1990
 JP 05/207993 8/1993
 JP H06-178776 6/1994
 JP 6/505903 7/1994
 JP 6/237013 8/1994
 JP H07-391 1/1995
 JP H07-171089 7/1995
 JP H07-171090 7/1995
 JP 7/281618 10/1995
 JP 07/325546 12/1995
 JP 9/192120 7/1997
 JP 10/500026 6/1998
 JP 10/216112 8/1998
 JP 10/509352 9/1998
 JP 10/269344 10/1998
 JP 10/295676 11/1998
 JP 10/305026 11/1998
 JP 11/163412 6/1999
 JP 11/164826 6/1999
 JP 11/506834 6/1999

(56)

References Cited

FOREIGN PATENT DOCUMENTS

JP	11/183377	7/1999
JP	2000/116625	4/2000
JP	2001-504256	3/2001
JP	2002/516689	6/2002
JP	2002/228579	8/2002
JP	2002/525151	8/2002
JP	2002/315739	10/2002
JP	2003/507718	2/2003
JP	2003/084108	3/2003
JP	2003/521985	7/2003
JP	2004/070179	3/2004
JP	2004/226277	8/2004
JP	2004/510467	8/2004
JP	2004/296736	10/2004
JP	2004/532526	10/2004
JP	2004/327760	11/2004
JP	2005/501589	1/2005
JP	2005/253478	9/2005
JP	4879913	12/2011
WO	WO 88/01150	2/1988
WO	WO 88/02020	2/1988
WO	WO 92/16142	10/1992
WO	WO 93/06776	4/1993
WO	WO 95/16387	6/1995
WO	WO 96/13208	5/1996
WO	WO 97/01985	1/1997
WO	WO 97/29678	8/1997
WO	WO 97/29710	8/1997
WO	WO 98/43071	10/1998
WO	WO 00/18290	4/2000
WO	WO 00/42911	7/2000
WO	WO 00/59374	10/2000
WO	WO 01/13790	3/2001
WO	WO 01/30414	5/2001
WO	WO 01/58347	8/2001
WO	WO 02/17780	3/2002
WO	WO 02/17780	3/2002
WO	WO 02/26123	4/2002
WO	WO 02/089664	11/2002
WO	WO 03/020129	3/2003
WO	WO 03/068060	8/2003
WO	WO 2004/034898	4/2004
WO	WO 2005/011488	2/2005
WO	WO 2006/094168	9/2006

OTHER PUBLICATIONS

European Examination Report dated Apr. 1, 2010, re EP App. No. 08 744 412.1 / 2319.

European Examination Report dated Mar. 18, 2011, re EP App. No. 08 744 412.1 / 2319.

European Examination Report dated Sep. 2, 2010, re EP App. No. 08 744 412.1 / 2319.

European Extended Search Report re EPO App. No. 10162402.1, SR dated Aug. 9, 2010.

Hall, et al., Jeffrey W.; Near-Infrared Spectrophotometry: A New Dimension in Clinical Chemistry; vol. 38; No. 9; 1992.

International Search Report for PCT/US2006/007516, mailed on Jan. 11, 2007, in 4 pages.

Japanese First Office Action (Notice of Reasons for Rejection), re JP App. No. 2007/558207, dated Jun. 28, 2011.

Japanese First Office Action (Notice of Reasons for Rejection), re JP App. No. 2007/558247, dated Jun. 28, 2011.

Japanese Office Action (Notice of Allowance), re JP App. No. 2007/558247, dated Oct. 24, 2011.

Japanese Office Action (Notice of Reasons for Rejection) re JP App. No. 2007/558246, dated Jun. 28, 2011.

Japanese Office Action (Notice of Reasons for Rejection), re JP App. No. 2007/558238, dated Jun. 28, 2011.

Japanese Office Action re JP Application No. 2007/558249, dated Jul. 13, 2011.

Japanese Office Action re JP Application No. 2007/558249, dated Nov. 8, 2011.

Japanese Office Action re JP Application No. JP 2007/558208, dated Aug. 23, 2011.

Japanese Office Action re JP Application No. JP 2007/558248, dated Nov. 8, 2011.

Japanese Office Action re JP Application No. 2007/558209, dated Oct. 25, 2011.

Japanese Office Action re JP Application No. 2007/558245, dated Oct. 25, 2011.

Japanese Office Action, re JP Application No. 2007/558237, dated Aug. 1, 2011.

Kuenstner, et al., J. Todd; Measurement of Hemoglobin in Unlysed Blood by Near-Infrared Spectroscopy; vol. 48; No. 4, 1994.

Manzke, et al., B., Multi Wavelength Pulse OXimetry in the Measurement of Hemoglobin Fractions; vol. 2676, date unknown.

Naumenko, E. K.; Choice of Wavelengths for Stable Determination of Concentrations of Hemoglobin Derivatives from Absorption Spectra of Erythrocytes; vol. 63; No. 1; pp. 60/66 Jan. / Feb. 1996; Original article submitted Nov. 3, 1994.

Patent Cooperation Treaty (PCT) International Search Report; PCT/US 2006/007389; Date of Mailing Jul. 17, 2006; pp. 1/9.

PCT International Search Report; PCT/US2006/007387; Date of Mailing Jul. 17, 2006; pp. 1/9.

PCT International Search Report; PCT/US2006/007388; Date of Mailing Jul. 17, 2006; pp. 1/9.

PCT International Search Report; PCT/US2006/007506; Date of Mailing Jul. 17, 2006; pp. 1/10.

PCT International Search Report; PCT/US2006/007536; Date of Mailing Jul. 17, 2006; pp. 1/9.

PCT International Search Report; PCT/US2006/007537; Date of Mailing Jul. 17, 2006; pp. 1/10.

PCT International Search Report; PCT/US2006/007538; Date of Mailing Jul. 17, 2006; pp. 1/9.

PCT International Search Report; PCT/US2006/007539; Date of Mailing Jul. 17, 2006; pp. 1/9.

PCT International Search Report; PCT/US2006/007540; Date of Mailing Jul. 17, 2006; pp. 1/9.

PCT International Search Report; PCT/US2006/007958; Date of Mailing Jul. 17, 2006; pp. 1/8.

PCT Search Report of International Application No. PCT/US2008/058327, Mailing Date of Jun. 30, 2009, in 12 pages.

PCT Search Report of International Application No. PCT/US2008/058327, Mailing Date of Aug. 12, 2008, in 6 pages.

Schmitt, Joseph M.; Simple Photon Diffusion Analysis of the Effects of Multiple Scattering on Pulse Oximetry; Mar. 14, 1991; revised Aug. 30, 1991.

Schmitt, Joseph M.; Zhou, Guan/Xiong; Miller, Justin, *Measurement of Blood Hematocrit by Dual/wavelength Near-IR Photoplethysmography*, published May 1992, Proc. SPIE vol. 1641, p. 150/161, Physiological Monitoring and Early Detection Diagnostic Methods, Thomas S. Mang; Ed. (SPIE homepage), in 12 pages.

Schnapp, et al., L.M.; Pulse Oximetry: Uses and Abuses; Chest 1990; 98; 1244/1250001 10.1378/Chest.98.5.1244.

US 8,845,543, 09/2014, Diab et al. (withdrawn).

"Application Note 84 Use of Add-Only Memory for Secure Storage of Monetary Equivalent Data," Dallas Semiconductor, in 5 pages.


Dallas Semiconductor Corp: DS2430A Announcement, retrieved Jun. 10, 1998, in 2 pages. <https://web.archive.org/web/19980610045525/http://dalsemi.com/News_Center/New_Products/1996/2430a.html>.

Favennec, J.M. "Smart sensors in industry." J. Phys. E: Sci. Instrum. 20 (1987): pp. 1087-1090.

Jones, K.L., et al. "A Protocol for Automatic Sensor Detection and Identification in a Wireless Biodevice Network." 1998, 6 pages.

"Medical." 50 Ways to Touch Memory. 3rd ed. Dallas: Dallas Semiconductor Corporation, 1994: pp. 24-25. Print.

Subramanian, S., et al. "Design for Constraint Violation Detection in Safety-Critical Systems." 1998: pp. 1-8.






FIG. 2




FIG. 3




FIG. 4





FIG. 5






FIG. 7




FIG. 8




FIG. 9




FIG. 10




FIG. 11A




FIG. 11B




FIG. 11C




FIG. 11D




FIG. 11E




FIG. 11F




FIG. 11G




FIG. 11H

NONINVASIVE MULTI-PARAMETER PATIENT MONITOR

PRIORITY CLAIM TO RELATED PROVISIONAL APPLICATIONS

The present application is a continuation of U.S. patent application Ser. No. 13/477,975, filed on May 22, 2012, which is a continuation of U.S. patent application Ser. No. 11/367,014, filed on Mar. 1, 2006, which claims priority benefit under 35 U.S.C. §119(e) to U.S. Provisional Patent Application Ser. No. 60/657,596, filed Mar. 1, 2005, entitled “Multiple Wavelength Sensor,” No. 60/657,281, filed Mar. 1, 2005, entitled “Physiological Parameter Confidence Measure,” No. 60/657,268, filed Mar. 1, 2005, entitled “Configurable Physiological Measurement System,” and No. 60/657,759, filed Mar. 1, 2005, entitled “Noninvasive Multi-Parameter Patient Monitor.” The present application incorporates the foregoing disclosures herein by reference.

INCORPORATION BY REFERENCE OF RELATED UTILITY APPLICATIONS

The present application is related to the following copending U.S. utility applications:

	App. Sr. No.	Filing Date	Title
1	11/367,013	Mar. 1, 2006	Multiple Wavelength Sensor Emitters
2	11/366,995	Mar. 1, 2006	Multiple Wavelength Sensor Equalization
3	11/366,209	Mar. 1, 2006	Multiple Wavelength Sensor Substrate
4	11/366,210	Mar. 1, 2006	Multiple Wavelength Sensor Interconnect
5	11/366,833	Mar. 1, 2006	Multiple Wavelength Sensor Attachment
6	11/366,997	Mar. 1, 2006	Multiple Wavelength Sensor Drivers
7	11/367,034	Mar. 1, 2006	Physiological Parameter Confidence Measure
8	11/367,036	Mar. 1, 2006	Configurable Physiological Measurement System
9	11/367,033	Mar. 1, 2006	Noninvasive Multi-Parameter Patient Monitor
10	11/367,014	Mar. 1, 2006	Noninvasive Multi-Parameter Patient Monitor
11	11/366,208	Mar. 1, 2006	Noninvasive Multi-Parameter Patient Monitor
12	13/412,428	Mar. 5, 2012	Noninvasive Multi-Parameter Patient Monitor
13	12/949,271	Nov. 18, 2010	Physiological Measurement System with Automatic Wavelength Adjustment

The present application incorporates the foregoing disclosures herein by reference.

FIELD OF THE DISCLOSURE

The present disclosure relates to the field of noninvasive patient monitors. More specifically, the disclosure relates to monitors displaying measurements derived using signals from optical sensors.

BACKGROUND

Spectroscopy is a common technique for measuring the concentration of organic and some inorganic constituents of a solution. The theoretical basis of this technique is the Beer-Lambert law, which states that the concentration c_i of an absorbent in solution can be determined by the intensity of light transmitted through the solution, knowing the path-length d_λ , the intensity of the incident light $I_{0,\lambda}$, and the extinction coefficient $\epsilon_{i,\lambda}$ at a particular wavelength λ . In generalized form, the Beer-Lambert law is expressed as:

$$I_\lambda = I_{0,\lambda} e^{-d_\lambda \cdot \mu_{0,\lambda}} \quad (1)$$

$$\mu_{0,\lambda} = \sum_{i=1}^n \epsilon_{i,\lambda} \cdot c_i \quad (2)$$

where $\mu_{0,\lambda}$ is the bulk absorption coefficient and represents the probability of absorption per unit length. The minimum number of discrete wavelengths that are required to solve Equations 1-2 are the number of significant absorbers that are present in the solution.

A practical application of this technique is pulse oximetry, which utilizes a noninvasive sensor to measure oxygen saturation (SpO_2) and pulse rate. In general, the sensor has light emitting diodes (LEDs) that transmit optical radiation of red and infrared wavelengths into a tissue site and a detector that responds to the intensity of the optical radiation after absorption (e.g., by transmission or transreflectance) by pulsatile arterial blood flowing within the tissue site. Based on this response, a processor determines measurements for SpO_2 , pulse rate, and can output representative plethysmographic waveforms. Thus, “pulse oximetry” as used herein encompasses its broad ordinary meaning known to one of skill in the art, which includes at least those noninvasive procedures for measuring parameters of circulating blood through spectroscopy. Moreover, “plethysmograph” as used herein (commonly referred to as “photoplethysmograph”), encompasses its broad ordinary meaning known to one of skill in the art, which includes at least data representative of a change in the absorption of particular wavelengths of light as a function of the changes in body tissue resulting from pulsing blood.

Pulse oximeters capable of reading through motion induced noise are available from Masimo Corporation (“Masimo”) of Irvine, Calif. Moreover, portable and other oximeters capable of reading through motion induced noise are disclosed in at least U.S. Pat. Nos. 6,770,028, 6,658,276, 6,157,850, 6,002,952, and 5,769,785. Read which are owned by Masimo, and are incorporated by reference herein. Such reading through motion oximeters have gained rapid acceptance in a wide variety of medical applications, including surgical wards, intensive care and neonatal units, general wards, home care, physical training, and virtually all types of monitoring scenarios.

SUMMARY OF THE DISCLOSURE

Despite the success of read through motion oximeter systems, there is a need to provide patient monitors capable of displaying multiple physiological parameters, other than or in addition to SpO_2 , plethysmograph waveforms, or pulse rates. For example, in accessing a patient’s condition, caregivers often desire knowledge of other blood constituents, including for example, a percent value for arterial carbon monoxide saturation (“HbCO”) or a percent value for methemoglobin

saturation ("HbMet") or the like. For example, in an embodiment, the display advantageously displays one or more of the following: pulse rate, plethysmograph waveform data, perfusion index, values of blood constituents in body tissue, including for example, HbCO, HbMet, total hemoglobin ("Hbt"), arterial oxygen saturation ("SpO₂"), fractional arterial oxygen saturation ("SpaO₂"), or the like. In other embodiments, the monitor may advantageously and accurately determine values for one or more of HbO₂, Hb, blood glucose, water, the presence or absence of therapeutic drugs (aspirin, Dapson, nitrates, or the like) or abusive/recreational drugs (methamphetamine, alcohol, steroids, or the like), concentrations of carbon dioxide ("CO₂") or oxygen ("O"), pH levels, bilirubin, perfusion quality, signal quality or the like. Accordingly, the present disclosure includes a multi-parameter patient monitor capable of determining one or more of the foregoing parameters, other than or in addition to, SpO₂, plethysmograph waveforms, or perfusion quality index.

In an embodiment, the display of a noninvasive multi-parameter patient monitor advantageously includes a plurality of display modes enabling more parameter data to be displayed than the available physical display area or real estate. In an embodiment, a user may cycle different parameter values through an area of the display common to both parameters even when one parameter is shifted, through, for example, actuation of a user input key. The patient monitor may also display different parameters as color-coded. For example, when the following measured parameters are within "normal" ranges, SpO₂ may be displayed red, pulse rate (BPM) may be displayed green, HbCO may be displayed orange, HbMet may be displayed blue, or the like. In an embodiment, measured values of SpO₂ may be displayed in white, BPM may be displayed in yellow green or aquamarine, PTTTM may be displayed in violet, Hbt may be displayed in grass green, HbMet may be displayed in blue or light blue, HbCO may be displayed in orange, and SpaO₂ may be displayed in electric blue.

Moreover, parameter trend data may also be displayed using the same or similar color coding, especially when multiple trends are displayed on one or more display graphs. In addition, more coarse or gross parameter indications may be displayed for quick reference to indicate to a caregiver whether any of a variety of monitored parameters, such as, for example, SpO₂, HbCO or HbMet is within acceptable ranges. The monitor may advantageously include additional display information, such as, for example, parametric displays where one parameter is displayed as a function of another, three dimensional displays (for example, extending a parametric display along time or an additional parameter), directional indicators predicting where a parameter is likely heading or reporting a general direction a parameters has been trending, or the like.

In addition to the foregoing, caregivers often desire to more closely monitor parameters that are close to, approaching, or beyond normal safe thresholds. In an embodiment, the patient monitor provides an indication that the caregiver should change display modes to view more critical monitored parameters. In alternative embodiments, the patient monitor automatically changes display modes to show parameters moving closer to or beyond normal thresholds.

In an embodiment, the patient monitor includes an audible or visual indication of a type of sensor communicating with the monitor. For example, the monitor may determine how many wavelengths a particular attached sensor will emit through communication with memory devices associated with the attached sensor or cable.

Additional embodiments include audio or visual alarms for each of multiple monitored parameters, combinations of parameters, an indication of perfusion in the tissue of the measurement site, an indication of the confidence the signal processing has in its output measurements, or the like.

In an embodiment, a method of determining which of a plurality of physiological measurements to measure based on the signal quality of the signal is disclosed. The method includes using a sensor configured to measure at least two different physiological measurements to obtain a signal from a light sensitive detector, the sensor including at least three different light emitters emitting at least three different wavelengths of light through tissue of a living patient and detecting the light after attenuation of the tissue, determining a signal quality of the signal, determining which of the at least two different physiological measurements are capable of being measured based on the signal quality determination, and activating only enough of the at least three different light emitters necessary to obtain the measurements capable of being measured.

In an embodiment, if the signal quality is high, all of the at least three different emitters are activated. In an embodiment, if the signal quality is low, only two of the at least three different emitters are activated. In an embodiment, if the signal quality is low, fewer different physiological measurements are measured. In an embodiment, a method of informing a user of a patient monitor about one of a type of sensor communicating with the patient monitor and a type of physiological parameter determinable using the sensor communicating with the patient monitor is disclosed. The method includes receiving information from an information element associated with one of an optical sensor and a communication cable between a patient monitor and an optical sensor, determining a number of wavelengths emitted by the optical sensor from the information, determining a signal quality of a signal received by the optical sensor, and activating an indicator of the type of physiological parameters determinable based on the number wavelengths emitted by the optical sensor and the signal quality of the signal. In an embodiment, the indicator comprises a display of data determined using signals from the optical sensor. In an embodiment, the indicator comprises a visual indicator. In an embodiment, the visual indicator comprises a color. In an embodiment, the visual indicator comprises an LED. In an embodiment, the LED changes color based on which of the first and second sensors is attached. In an embodiment, the LED color comprises red when the first sensor is attached and another color when another sensor is attached. In an embodiment, the indicator comprises an audible indicator. In an embodiment, the audible indicator comprises one or more tones. In an embodiment, the audible indicator emits a first tone when the first sensor is attached and a different second tone when the second sensor is attached.

For purposes of summarization, certain aspects, advantages and novel features are described herein. Of course, it is to be understood that not necessarily all such aspects, advantages or features need to be present in any particular embodiment.

BRIEF DESCRIPTION OF THE DRAWINGS

The drawings and the associated descriptions are provided to illustrate embodiments of the disclosure and not to limit the scope of the claims.

FIG. 1 illustrates a block diagram of an exemplary embodiment of a patient monitoring system including a sensor and a multi-parameter patient monitor.

FIG. 2 illustrates a top elevation view of an exemplary handheld noninvasive multi-parameter patient monitor capable of displaying at least HbCO, such as, for example, the patient monitor of FIG. 1.

FIG. 3 illustrates an exemplary display of the patient monitor of FIG. 2.

FIG. 4 illustrates the display of FIG. 3 showing measured values of SpO₂, BPM, perfusion, and type of sensor according to an exemplary embodiment of the patient monitor of FIG. 1.

FIG. 5 illustrates the display of FIG. 3 showing measured values of HbCO, perfusion, and type of sensor according to an exemplary embodiment of the patient monitor of FIG. 1.

FIG. 6 illustrates the display of FIG. 3 showing measured values of SpO₂, HbCO, BPM, perfusion, and type of sensor, according to an exemplary embodiment of the patient monitor of FIG. 1.

FIG. 7 illustrates a top elevation view of an exemplary handheld noninvasive multi-parameter patient monitor capable of displaying at least HbCO and HbMet, such as, for example, the patient monitor of FIG. 1.

FIG. 8 illustrates an exemplary display of the patient monitor of FIG. 7.

FIG. 9 illustrates the display of FIG. 8 showing measured values of SpO₂, BPM, HbCO, HbMet, and type of sensor according to an exemplary embodiment of the patient monitor of FIG. 1.

FIG. 10 illustrates the display of FIG. 8 showing measured values of HbCO, HbMet, and type of sensor according to an exemplary embodiment of the patient monitor of FIG. 1.

FIG. 11A illustrates a perspective view of an exemplary noninvasive multi-parameter patient monitor such as, for example, the patient monitor of FIG. 1.

FIGS. 11B-11H illustrate display screens of the patient monitor of FIG. 11A.

DETAILED DESCRIPTION OF PREFERRED AND ALTERNATIVE EMBODIMENTS

Embodiments of the present disclosure include a portable or other multi-parameter patient monitor capable of determining multiple physiological parameters from one or more signals output from one or more light sensitive detectors capable of detecting light attenuated by body tissue carrying pulsing blood. For example, in an embodiment, the monitor advantageously and accurately determines a wide variety of physiological parameters or other calculations as discussed above.

In an embodiment, the display of patient monitor advantageously includes a plurality of display modes enabling more parameter data to be displayed than the available physical display real estate. For example, the patient monitor may include one or more user input keys capable of toggling through measurement data. In an embodiment, the displays include mode indicators providing caregivers easily identifiable visual queues, such as LED's, text, icons, or other indicia providing readily identifiable queues as to which parameter is being displayed. In an embodiment, the display may shift, may be parameter color-coded, or the like to further ensure quick comprehension of which measured parameter is the displayed parameter. For example, in an embodiment, the monitor displays SpO₂ in white, pulse rate (BPM) in green, HbCO in orange, and HbMet in blue when the respective measured parameter is within a "normal" range.

In an embodiment, the patient monitor provides an indication that the caregiver should change display modes to view more critical or time sensitive measured parameters, specific

caregiver selected parameters, or the like. For example, the patient monitor may advantageously sound audio or visual alarms that alert the caregiver to particular one or more of worsening parameters, parameters changing in a predetermined pattern or rate, parameters stabilizing below user defined or safe thresholds, caregiver selected parameters, or the like. The monitor may also use alerts that provide audio or visual indications of the severity of the condition, severity of the change, or the like. In alternative embodiments, the patient monitor may automatically change display modes when a particular parameter crosses one or more thresholds. For example, a patient monitor may be displaying a first parameter, such as a plethysmograph, and upon determining measurements indicating that HbMet is trending toward an alarm condition, the monitor may automatically switch from displaying the first parameter to the alarming parameter, or in this case, a trend of the alarming parameter.

In an embodiment, a switch is provided to allow a user to switch displays to view an alarming measurement. In an embodiment, during an alarm condition, a parameter display may switch to a trend graph in the same or different color, line weight, flash, flash rate, intensity, size, or the like.

The patient monitor may also include one or more displays capable of displaying trend data for any one or more of the monitored or derived patient parameters. For example, the trend data may be displayed in graph form, may include multiple trend lines, each representing a different monitored or derived patient parameter. Moreover, each trend line may be color-coded to facilitate quick comprehension of which trend line represents which measured parameter. However, an artisan will recognize from the disclosure herein a large number of identification techniques including color-coding, identifying text, or the like. Additionally, user input may toggle displayed trend data, may select which parameters to display simultaneously, or the like.

In an embodiment, the patient monitor includes an audible or visual indication of a type of sensor communicating with the monitor. For example, the patient monitor may provide a particular audio or visual indication, such as a beep, LED activation, graphic activation, text messages, voice messages, or the like, to indicate communication with or connection to an approved sensor, patient cable, combination, or the like. In an embodiment, the indication may change based on the manufacturer, type of sensor recognized or not recognized, type of patient, type of physiological parameters measurable with the attached sensor, or the like. Additional embodiments include an indication of perfusion in the tissue of the measurement site and an indication of the confidence the signal processing has in its output measurements or input signal quality.

To facilitate an understanding of the disclosure, the remainder of the description references exemplary embodiments illustrated in the drawings. Moreover, in this application, reference is made to many blood parameters. Some references that have common shorthand designations are referenced through such shorthand designations. For example, as used herein, HbCO designates carboxyhemoglobin, HbMet designates methemoglobin, and Hbt designates total hemoglobin. Other shorthand designations such as COHb, MetHb, and tHb are also common in the art for these same constituents. These constituents are generally reported herein in terms of a percentage, often referred to as saturation, relative concentration or fractional saturation. Total hemoglobin is generally reported as a concentration in g/dL. The use of the particular shorthand designators presented in this application does not restrict the term to any particular manner in which the designated constituent is reported.

FIG. 1 illustrates a block diagram of an exemplary embodiment of a patient monitoring system 100. As shown in FIG. 1, the system 100 includes a patient monitor 102 comprising a processing board 104 and a host instrument 108. The processing board 104 communicates with a sensor 106 to receive one or more intensity signal(s) indicative of one or more parameters of tissue of a patient. The processing board 104 also communicates with a host instrument 108 to display determined values calculated using the one or more intensity signals. According to an embodiment, the board 104 comprises processing circuitry arranged on one or more printed circuit boards capable of installation into the monitor 102, or capable of being distributed as some or all of one or more OEM components for a wide variety of host instruments monitoring a wide variety of patient information. In an embodiment, the processing board 102 comprises a sensor interface 110, a digital signal processor and signal extractor ("DSP" or "processor") 112, and an instrument manager 114. In general, the sensor interface 110 converts digital control signals into analog drive signals capable of driving sensor emitters, and converts composite analog intensity signal(s) from light sensitive detectors into digital data.

In an embodiment, the sensor interface 110 manages communication with external computing devices. For example, in an embodiment, a multipurpose sensor port (or input/output port) is capable of connecting to the sensor 106 or alternatively connecting to a computing device, such as a personal computer, a PDA, additional monitoring equipment or networks, or the like. When connected to the computing device, the processing board 104 may upload various stored data for, for example, off-line analysis and diagnosis. The stored data may comprise trend data for any one or more of the measured parameter data, plethysmograph waveform data acoustic sound waveform, or the like. Moreover, the processing board 104 may advantageously download from the computing device various upgrades or executable programs, may perform diagnosis on the hardware or software of the monitor 102. In addition, the processing board 104 may advantageously be used to view and examine patient data, including raw data, at or away from a monitoring site, through data uploads/downloads, or network connections, combinations, or the like, such as for customer support purposes including software maintenance, customer technical support, and the like. Upgradable sensor ports are disclosed in copending U.S. application Ser. No. 10/898,680, filed on Jul. 23, 2004, titled "Multipurpose Sensor Port," incorporated by reference herein.

As shown in FIG. 1, the digital data is output to the DSP 112. According to an embodiment, the DSP 112 comprises a processing device based on the Super Harvard ARCHitecture ("SHARC"), such as those commercially available from Analog Devices. However, a skilled artisan will recognize from the disclosure herein that the DSP 112 can comprise a wide variety of data and/or signal processors capable of executing programs for determining physiological parameters from input data. In particular, the DSP 112 includes program instructions capable of receiving multiple channels of data related to one or more intensity signals representative of the absorption (from transmissive or reflective sensor systems) of a plurality of wavelengths of emitted light by body tissue. In an embodiment, the DSP 112 accepts data related to the absorption of eight (8) wavelengths of light, although an artisan will recognize from the disclosure herein that the data can be related to the absorption of two (2) to sixteen (16) or more wavelengths.

FIG. 1 also shows the processing board 104 including the instrument manager 114. According to an embodiment, the

instrument manager 114 may comprise one or more microcontrollers controlling system management, including, for example, communications of calculated parameter data and the like to the host instrument 108. The instrument manager 114 may also act as a watchdog circuit by, for example, monitoring the activity of the DSP 112 and resetting it when appropriate.

The sensor 106 may comprise a reusable clip-type sensor, a disposable adhesive-type sensor, a combination sensor having reusable and disposable components, or the like. Moreover, an artisan will recognize from the disclosure herein that the sensor 106 can also comprise mechanical structures, adhesive or other tape structures, Velcro wraps or combination structures specialized for the type of patient, type of monitoring, type of monitor, or the like. In an embodiment, the sensor 106 provides data to the board 104 and vice versa through, for example, a patient cable. An artisan will also recognize from the disclosure herein that such communication can be wireless, over public or private networks or computing systems or devices, or the like.

As shown in FIG. 1, the sensor 106 includes a plurality of emitters 116 irradiating the body tissue 118 with differing wavelengths of light, and one or more detectors 120 capable of detecting the light after attenuation by the tissue 118. In an embodiment, the emitters 116 comprise a matrix of eight (8) emission devices mounted on a flexible substrate, the emission devices being capable of emitting eight (8) differing wavelengths of light. In other embodiments, the emitters 116 may comprise twelve (12) or sixteen (16) emitters, although other numbers of emitters are contemplated, including two (2) or more emitters. As shown in FIG. 1, the sensor 106 may include other electrical components such as, for example, a memory device 122 comprising an EPROM, EEPROM, ROM, RAM, microcontroller, combinations of the same, or the like. In an embodiment, other sensor components may include a temperature determination device 123 or other mechanisms for, for example, determining real-time emission wavelengths of the emitters 116.

The memory 122 may advantageously store some or all of a wide variety of data and information, including, for example, information on the type or operation of the sensor 106; type or identification of sensor buyer or distributor or groups of buyer or distributors, sensor manufacturer information, sensor characteristics including the number of emitting devices, the number of emission wavelengths, data relating to emission centroids, data relating to a change in emission characteristics based on varying temperature, history of the sensor temperature, current, or voltage, emitter specifications, emitter drive requirements, demodulation data, calculation mode data, the parameters for which the sensor is capable of supplying sufficient measurement data (e.g., HpCO, HpMet, HbT, or the like), calibration or parameter coefficient data, software such as scripts, executable code, or the like, sensor electronic elements, whether the sensor is a disposable, reusable, multi-site, partially reusable, partially disposable sensor, whether it is an adhesive or non-adhesive sensor, whether the sensor is a reflectance, transmittance, or transreflectance sensor, whether the sensor is a finger, hand, foot, forehead, or ear sensor, whether the sensor is a stereo sensor or a two-headed sensor, sensor life data indicating whether some or all sensor components have expired and should be replaced, encryption information, keys, indexes to keys or hash functions, or the like, monitor or algorithm upgrade instructions or data, some or all of parameter equations, information about the patient, age, sex, medications, and other information that may be useful for the accuracy or alarm settings and sensitivities, trend history, alarm history, or the like. In an embodiment, the

monitor may advantageously store data on the memory device, including, for example, measured trending data for any number of parameters for any number of patients, or the like, sensor use or expiration calculations, sensor history, or the like.

FIG. 1 also shows the patient monitor 102 including the host instrument 108. In an embodiment, the host instrument 108 communicates with the board 104 to receive signals indicative of the physiological parameter information calculated by the DSP 112. The host instrument 108 preferably includes one or more display devices 124 capable of displaying indicia representative of the calculated physiological parameters of the tissue 118 at the measurement site. In an embodiment, the host instrument 108 may advantageously comprise a handheld housing capable of displaying one or more of a pulse rate, plethysmograph data, perfusion quality such as a perfusion quality index ("PITM"), signal or measurement quality ("SQ"), values of blood constituents in body tissue, including for example, SpO₂, HbCO, HbMet, Hbt, or the like. In other embodiments, the host instrument 108 is capable of displaying values for one or more of Hbt, Hb, blood glucose, bilirubin, or the like. The host instrument 108 may be capable of storing or displaying historical or trending data related to one or more of the measured values, combinations of the measured values, plethysmograph data, or the like. The host instrument 108 also includes an audio indicator 126 and user input device 128, such as, for example, a keypad, touch screen, pointing device, voice recognition device, or the like.

In still additional embodiments, the host instrument 108 includes audio or visual alarms that alert caregivers that one or more physiological parameters are falling below predetermined safe thresholds. The host instrument 108 may include indications of the confidence a caregiver should have in the displayed data. In a further embodiment, the host instrument 108 may advantageously include circuitry capable of determining the expiration or overuse of components of the sensor 106, including, for example, reusable elements, disposable elements, or combinations of the same.

Although described in terms of certain embodiments, other embodiments or combination of embodiments will be apparent to those of ordinary skill in the art from the disclosure herein. For example, the monitor 102 may comprise one or more monitoring systems monitoring parameters, such as, for example, vital signs, blood pressure, ECG or EKG, respiration, glucose, bilirubin, or the like. Such systems may combine other information with intensity-derived information to influence diagnosis or device operation. Moreover, the monitor 102 may advantageously include an audio system, preferably comprising a high quality audio processor and high quality speakers to provide for voiced alarms, messaging, or the like. In an embodiment, the monitor 102 may advantageously include an audio out jack, conventional audio jacks, headphone jacks, or the like, such that any of the display information disclosed herein may be audibilized for a listener. For example, the monitor 102 may include an audible transducer input (such as a microphone, piezoelectric sensor, or the like) for collecting one or more of heart sounds, lung sounds, trachea sounds, or other body sounds and such sounds may be reproduced through the audio system and output from the monitor 102. Also, wired or wireless communications (such as Bluetooth or WiFi, including IEEE 801.11a, b, or g), mobile communications, combinations of the same, or the like, may be used to transmit the audio output to other audio transducers separate from the monitor 102.

For example, patterns or changes in the continuous noninvasive monitoring of intensity-derived information may

cause the activation of other vital sign measurement devices, such as, for example, blood pressure cuffs.

FIG. 2 illustrates a perspective view of an exemplary handheld noninvasive multi-parameter patient monitor 200, such as, for example, the patient monitor 102 of FIG. 2. Patient monitors 200 exhibiting combinations of many of the features described herein are advantageously commercially available from Masimo under the brand name "Rad 57c." As shown in FIG. 1, the monitor 200 includes a patient cable connector 202 capable of mechanical mating with a patient cable to establish communication between the board 104 and the sensor 106. In an embodiment, the connector 202 comprises a multipurpose cable connector such as that disclosed in the incorporated U.S. application Ser. No. 10/898,680, titled "Multipurpose Sensor Port," disclosing communication between the board 104 and an external computing device.

The monitor 200 also comprises a HbCO indicator 204 advantageously providing a visual queue that a HbCO capable sensor is properly connected through the connector 202. For example, the HbCO indicator 204 may advantageously activate when a sensor is connected that communicates sufficient information to determine HbCO, such as, for example, a sensor capable of emitting sufficient different wavelengths of light, a sensor storing sufficient data on the memory 122, a sensor having appropriate encryption data or key, combinations of the same, or the like. For example, in an embodiment, the processor 112 may receive information from a memory 122 indicating a number of available LED wavelengths for the attached sensor. Based on the number of wavelengths, or other information stored on the memory 122, the processor 112 may determine whether an HbCO-ready sensor has been attached to the monitor 200. An artisan will also recognize from the disclosure herein that the HbCO indicator 204 may advantageously comprise a HbMet indicator, Hbt indicator, or the like, which activates to a predetermined color associated with a parameter, or any color, or deactivates the same, to convey a type of attached sensor. Moreover, the artisan will recognize from the disclosure herein other parameters that may use other sensor components and the monitor 200 may include indicators capable of indicating communication with those types of sensors.

In an embodiment, the monitor 200 may also audibly indicate the type of sensor connected. For example, the monitor 200 may emit predetermined number or frequency of beeps associated with recognition of a particular sensor, a particular manufacturer, failure to recognize the sensor, or the like. Moreover, the sensor type may be indicative of the componentry, such as, for example, whether the sensor produces sufficient data for the determination of HbCO, HbMet, Hbt and SpO₂, SpO₂ only, SpO₂ and HbMet, any combination of the foregoing or other parameters, or the like. Additionally, the sensor type may be indicative of specific sensors designed for a type of patient, type of patient tissue, or the like. In other embodiments, the monitor 200 may announce the type of connector through speaker 236.

An artisan will also recognize from the disclosure herein that other mechanical (such as keys), electrical, or combination devices may inform the monitor 202 of the type of attached sensor. In an embodiment, the processor 112 also may select to drive less emitters that are currently available, such as, for example, in the presence of low noise and when power consumption is an issue.

The monitor 200 also comprises a multi-mode display 206 capable of displaying, for example, measurements of SpO₂ and HbCO (or alternatively, HbMet). In an embodiment, the display 206 has insufficient space or display real estate to display the many parameters capable of being measured by

11

the monitor **200**. Thus, the multi-mode display **206** may advantageously cycle through two or more measured parameters in an area common to both parameters even when shifted. In such embodiments, the monitor **200** may also advantageously include parameter indicators **208**, **210**, providing additional visual queues as to which parameter is currently displayed. In an embodiment, the display may also cycle colors, flash rates, or other audio or visual queues providing readily identifiable information as to which measured parameter is displayed. For example, when the multi-mode display **206** displays measured values of SpO₂ that are normal, the numbers may advantageously appear in green, while normal measured values of HbCO may advantageously appear in orange, and normal measured values of HbMet may appear in blue. Moreover, in an embodiment, the display **206** flashes at a predefined rate when searching for saturation and at another predefined rate when a signal quality is below a predetermined threshold.

The monitor **200** also comprises a HbCO bar **212** where in an embodiment a plurality of LED's activate from a bottom toward a top such that the bar "fills" to a level proportional to the measured value. For example, the bar **212** is lowest when the dangers from carbon monoxide poisoning are the least, and highest when the dangers are the greatest. The bar **212** includes indicia **214** that provide an indication of the severity of carbon monoxide saturation in a patient's blood. As shown in FIG. 2, the bar **212** and the indicia **214** continuously indicate the concentration of HbCO in about 5% increments. The indicia **214** indicate a measurement of HbCO saturation percentage between about 0 and about 50% with a granularity of about 5%. However, an artisan will also recognize from the disclosure herein a wide variety of ranges and granularities could be used, the indicia **214** could be electronically displayed in order to straightforwardly increase or decrease resolution, or the like. For example, HbCO may advantageously be displayed with greater resolution than about 5% in a lower portion of the scale. For example, an HbCO bar may advantageously include a scale of about <3%, about 6%, about 9%, about 12%, about 15%, about 20%, about 25%, about 30%, about 35%, and about >40%.

As is known in the art, carbon monoxide in the blood can lead to serious medical issues. For example and depending upon the particular physiology of a patient, about 10% carbon monoxide saturation can lead to headaches, about 20% can lead to throbbing headaches, or dyspnea on exertion, about 30% can lead to impaired judgment, nausea, dizziness and/or vomiting, visual disturbance, or fatigue, about 40% can lead to confusion and syncope, and about 50% and above can lead to comas, seizures, respiratory failure and even death.

In an embodiment, the bar **212** is the same or similar color as the multi-mode display **206** when displaying HbCO. In other embodiments, the bar **212** is lowest and green when the dangers from carbon monoxide poisoning are the least, and highest and red when the dangers are the greatest. In an embodiment, as HbCO increases, the entire bar **212** may advantageously change color, such as, for example, from green to red, to provide a clear indication of deepening severity of the condition. In other embodiments, the bar **212** may advantageously blink or flash, an audio alarm may beep or provide a continuation or rise in pitch or volume, or the like to alert a caregiver of deepening severity. Moreover, straightforward to complex alarm rules may be implemented to reduce false alarms based on, for example, knowledge of the physiological limitations on the rate of change in HbCO or the like.

Additionally, the monitor **200** may be capable of storing and outputting historical parameter data, display trend traces or data, or the like. Although the foregoing bar **212** has been

12

described in terms of certain preferred embodiments, other embodiments will be apparent to those of ordinary skill in the art from the disclosure herein.

FIG. 2 also shows the monitor **200** including a pulse display **216** displaying measured pulse rate in beats per minute ("BPM"). In an embodiment, the display **212** flashes when searching for a pulse. The pulse display **216** advantageously displays measured pulse rates from about zero (0) to about two hundred and forty (240) BPM. Moreover, when the measured pulse rates are considered normal, the pulse display **216** is advantageously green. Similar to other displays associated with the monitor **200**, the pulse display **216** may employ a variety of color changes, audio alarms, or combinations of the same to indicate measured BPM below predetermined safe thresholds. In an embodiment, the pulse rate display **216** displays the measured pulse rate during the display of SpO₂ and displays message data during the display of other parameters. For example, during the display of HbCO, the display **216** may advantageously display the term "CO." In an embodiment, the display of the message data may be in the same or similar color as the other displays. For example, in an embodiment, the multi-mode display **206**, the bar **212**, and the pulse display **216** may all display data or messages in orange when the multi-mode display **206** displays measured HbCO values.

FIG. 2 also illustrates the monitor **200** comprising user input keys **218**, including a HbCO button **220**, mode/enter button **222**, next button **224**, power on/off button **226**, up/down button **228**, and alarm silence button **230**. In an embodiment, activation of the HbCO button **220** toggles the measured value displayed in the multi-mode display **206**. For example, activation of the HbCO button **220** toggles the multi-mode display **206** from displaying measured values of SpO₂ to HbCO for about ten (10) seconds. Activation of the mode/enter button **222** or the next button **224** during the ten (10) second period returns the multi-mode display **206** back to SpO₂. A skilled artisan will also recognize that activation of the HbCO button **220** may advantageously toggle through a plurality of measured values, and that such values may be displayed for short segments and then return to SpO₂, may remain displayed until further activation of the button **220**, or the like.

Activation of the mode/enter button **222** cycles through various setup menus allowing a caregiver to select or activate certain entries within the menu setup system, including alarm threshold customizations, or the like. Activation of the next button **224** can move through setup options within the menu setup system and in an embodiment is not active during normal patient monitoring. For example, a caregiver may activate the mode/enter button **222** and the next button **224** to specify high and low alarm thresholds for one or more of the measured parameters, to specify device sensitivity, trend settings, display customizations, color code parameters, or the like. In an embodiment, the high alarm setting for SpO₂ can range from about two percent (2%) to about one hundred percent (100%) with a granularity of about one percent (1%). The low alarm setting for SpO₂ can range from about one percent (1%) to about one hundred percent (100%) with a granularity of about one percent (1%). Moreover, the high alarm setting for pulse rate can range from about thirty (30) BPM to about two hundred and forty (240) BPM with a granularity of about five (5) BPM. The low alarm setting for pulse rate can range from about twenty five (25) BPM to about two hundred and thirty five (235) BPM with a granularity of about five (5) BPM. Other high and low ranges for other measured parameters will be apparent to one of ordinary skill in the art from the disclosure herein.

In a further embodiment, a caregiver may activate the mode/enter button **222** and the next button **224** to specify device sensitivity, such as, for example, device averaging times, probe off detection, whether to enable fast saturation calculations, or the like. Various embodiments of fast saturation calculations are disclosed in U.S. patent application Ser. No. 10/213,270, filed Aug. 5, 2002, titled "Variable Indication Estimator" and incorporated by reference herein. Using the menus, a caregiver may also advantageously enter appropriate information governing trend collection on one or more of the measured parameters, input signals, or the like.

FIG. 2 also shows the power on/off button **226**. Activation of the power on/off button **226** activates and deactivates the monitor **200**. In an embodiment, press-and-hold activation for about two (2) seconds shuts the monitor **200** off. In an additional embodiment, activation of the on/off button **226** advantageously initiates detection of a type of attached sensor. For example, activation of the on/off button **226** may advantageously cause the monitor **200** to read information from a memory on an attached sensor and determine whether sufficient wavelengths exist on the sensor to determine one or more the physiological parameters discussed in the foregoing.

An artisan will recognize from the disclosure herein that the on/off button **226** may advantageously cause an electronic determination of whether to operate in at powers consisted with the U.S. (60 Hz) or another nationality (50 Hz). In an embodiment, such automatic determination and switching is removed from the monitor **200** in order to reduce a likelihood of problematic interfering crosstalk caused by such power switching devices.

Activation of the up/down button **228** may advantageously adjust the volume of the pulse beep tone. Additionally, activation of the up/down button **228** within the menu setup system, causes the selection of values with various menu options.

Moreover, activation of the alarm silence button **230** temporarily silences audio alarms for a predetermined period, such as, for example, about one hundred and twenty (120) seconds. A second activation of the alarm silence button **230** mutes (suspends) the alarm indefinitely, while a third activation returns the monitor **200** to standard alarm monitoring. FIG. 2 also shows the alarm silence button **230** includes an alarm silenced indicator **232**. The alarm silenced indicator **232** may advantageously flash to indicate one or more alarms are temporarily silenced, may illuminate solid to indicate the alarms have been muted, or the like. Moreover, an artisan will recognize from the disclosure herein a wide variety of alarm silencing methodologies.

The monitor **200** also includes a battery level indicator **234** indicating remaining battery life. In the illustrated embodiment, four LED's indicate the status of the battery by incrementally deactivating to indicate proportionally decreasing battery life. In an embodiment, the four LED's may also change color as the battery charge decreases, and the final LED may begin to flash to indicate that the caregiver should replace the batteries.

FIG. 2 also shows the monitor **200** including an audio transducer or speaker **236**. The speaker **236** advantageously provides audible indications of alarm conditions, pulse tone and feedback for key-presses, or the like. Moreover, the monitor **202** includes a low signal quality indicator ("SQ" or "SIQ™") **238**. The signal IQ indicator **238** activates to inform a caregiver that a measured value of the quality of the incoming signal is below predetermined threshold values. For example, in an embodiment, the measured value for signal IQ is at least partially based on an evaluation of the plethysmo-

graph data's correspondence to predetermined models or characteristics of physiological signals. In an embodiment, the signal IQ indicator **238** output may be associated with the displayed parameter. For example, the output may be associated with one threshold for the display of SpO₂ and another for the display of other parameter data.

The monitor **200** also comprises a perfusion quality index ("PI™") bar **240** (which quantifies the measure of perfusion of the patient) where in an embodiment a plurality of LED's activate from a bottom toward a top such that the bar "fills" to a level proportional to the measured value. In one embodiment, the PI™ bar **240** shows a static value of perfusion for a given time period, such as, for example, one or more pulses. In another embodiment, or functional setting, the PI™ bar **240** may advantageously pulse with a pulse rate, may hold the last reading and optionally fade until the next reading, may indicate historical readings through colors or fades, or the like. Additionally, the PI™ bar **240** may advantageously change colors, flash, increasingly flash, or the like to indicate worsening measured values of perfusion.

The PI™ bar **240** can be used to simply indicate inappropriate occlusion due, for example, to improper attachment of the sensor **106**. The PI™ bar **240** can also be used as a diagnostic tool during low perfusion for the accurate prediction of illness severity, especially in neonates. Moreover, the rate of change in the PI™ bar **240** can be indicative of blood loss, sleep arousal, severe hypertension, pain management, the presence or absence of drugs, or the like. According to one embodiment, the PI™ bar **240** values may comprise a measurement of the signal strength of the arterial pulse as a percentage of the total signal received. For example, in one preferred embodiment, the alternating portion of at least one intensity signal from the sensor **106** may advantageously be divided by the static portion of the signal. For example, an infrared intensity signal may advantageously be used as it is less subjective to noise.

In an embodiment, a measurement below about 1.25% may indicate medical situations in need of caregiver attention, specifically in monitored neonates. Because of the relevance of about 1.25%, the PI™ bar **240** may advantageously include level indicia **242** where the indicia **242** swap sides of the PI™ bar **240**, thus highlighting any readings below about that threshold. Moreover, behavior of the PI™ bar **240**, as discussed above, may advantageously draw attention to monitored values below such a threshold.

As discussed above, the monitor **200** may include output functionality that outputs, for example, trend perfusion data, such that a caregiver can monitor measured values of perfusion over time. Alternatively or additionally, the monitor **200** may display historical trace data on an appropriate display indicating the measured values of perfusion over time. In an embodiment, the trend data is uploaded to an external computing device through, for example, the multipurpose sensor connector **202** or other input output systems such as USB, serial or parallel ports or the like.

The monitor **200** also includes an alarm indicator **244** capable of providing visual queues of the status of one or more of the measured parameters. For example, the alarm indicator **244** may advantageously be green when all of the measured parameters are within normal conditions, may gradually fade to red, may flash, increasing flash, or the like, as one or more of the measured values approaches or passes predetermined thresholds. In an embodiment, the alarm indicator **244** activates when any parameter falls below an associated threshold, thereby advantageously informing a caregiver that perhaps a nondisplayed parameters is at an alarm condition. In another embodiment, the alarm indicator **244**

may indicate the status of the parameter displayed on the multi-mode display **206**. In an embodiment, the speaker **236** may sound in conjunction with and/or in addition to the indicator **244**. Moreover, in an embodiment, an alarming parameter may automatically be displayed, may be emphasized, flashed, colored, combinations of the same or the like to draw a user's attention to the alarming parameter.

Although the foregoing invention has been described in terms of certain preferred embodiments, other embodiments will be apparent to those of ordinary skill in the art from the disclosure herein.

FIG. **3** illustrates an exemplary display of the patient monitor **200**. As shown in FIG. **3**, the display includes the multi-mode display **206**, the pulse rate display **216**, parameter indicators **208**, **210**, the HbCO bar **212** and indicator **204**, the P_{ITM} bar **240**, and the alarm indicator **244**. In an embodiment, the multi-mode display **206** and the pulse rate display **216** each comprise a plurality of seven segment displays **302** capable of displaying alpha-numeric information. As disclosed in the foregoing, the exemplary display may advantageously include color-coded parameter displays. Moreover, the exemplary display may include color progressions, flashing, flashing progressions, audible alarms, audible progressions, or the like, indicating worsening measured values of physiological data. In addition, in an embodiment, some or all of the displays may flash at a first rate to indicate attempts to acquire data when actual measured values are unavailable. Moreover, some or all of the display may flash at a second rate to indicate low signal quality where confidence is decreasing that the measured values reflect actual physiological conditions.

FIG. **4** illustrates the display of FIG. **3** showing measured values of SpO₂, BPM, perfusion, and type of sensor, according to an exemplary embodiment of the patient monitor of FIG. **1**. As shown in FIG. **4**, the multi-mode display **206** is displaying a percentage value of SpO₂, and the pulse rate display **216** is displaying a pulse rate in beats per minute. Accordingly, the parameter indicator **210** is activated to confirm the display of measured values of SpO₂. As disclosed in the foregoing, in an embodiment, the multi-mode display **206** is red, indicating blood oxygen measurements while the pulse rate display **216** is green, indicating normal values of a patient's pulse.

FIG. **4** also shows the P_{ITM} bar **240** almost fully activated, representing good perfusion. In addition, the HbCO indicator **204** is showing communication with a sensor producing insufficient data to determine measured values of additional parameters, such as, HbCO. In an embodiment, such sensors may comprise sensors capable of emitting light at about two (2) different wavelengths, may comprise sensors with insufficient data stored on a memory associated therewith, or the like.

FIG. **5** illustrates the display of FIG. **3** showing measured values of HbCO, perfusion, and type of sensor, according to an exemplary embodiment of the patient monitor of FIG. **1**. As shown in FIG. **5**, the multi-mode display **206** is displaying a percentage value of HbCO, and the pulse rate display **216** is displaying an appropriate message indicating the HbCO measurement, such as, for example, "CO". Also, the multi-mode display **206** has shifted the data to the left to quickly and efficiently indicate that the displayed parameter is other than SpO₂. Accordingly, the parameter indicator **208** is also activated to confirm the display of measured values of HbCO. As disclosed in the foregoing, in an embodiment, the multi-mode display **206** and pulse rate display message **216** are orange.

FIG. **5** also shows the P_{ITM} bar **240** almost fully activated, representing good perfusion. In addition, the activation of the HbCO indicator **204** represents communication with a sensor

capable of producing sufficient data to determine measured values of HbCO. In an embodiment, such sensors may comprise sensors capable of emitting light at about eight (8) or more different wavelengths; however, such sensors may comprise about two (2) or more different wavelengths. Moreover, such sensors may have appropriate data stored on a memory associated therewith, or the like. FIG. **5** also shows the HbCO measurement being about 20% (as illustrated on the HbCO bar **212** and multi-mode display **206**) thereby indicating a potentially dangerous situation that if exacerbated, will become quite problematic. Therefore, the alarm indicator **244** is also activated, and in some embodiments, the speaker **236** as well.

FIG. **6** illustrates the display of FIG. **3** showing measured values of SpO₂, HbCO, BPM, perfusion, and type of sensor, according to an exemplary embodiment of the patient monitor of FIG. **1**. In contrast to FIG. **4**, FIG. **6** shows that the monitor **200** is communicating with a sensor capable of producing sufficient data to determine measured values of HbCO, even though the displayed values are that of SpO₂ and BPM. Thus, FIG. **6** shows the activation of the HbCO indicator **204**, and the continuous monitoring of HbCO by the HbCO bar **212**. FIG. **6** also shows a high value of HbCO, and therefore, the indication of an alarm condition by activation of the alarm indicator **244**. In an embodiment, upon determination of an alarm condition on a nondisplayed parameter, the monitor **200** may advantageously provide an alarm indication through speaker and alarm indicator activation, automatic toggle to the nondisplayed parameter on the multi-mode display **206** for a defined or undefined time, or the like.

FIG. **7** illustrates a top elevation view of an exemplary handheld noninvasive multi-parameter patient monitor **700** capable of displaying at least HbCO and HbMet, such as, for example, the patient monitor of FIG. **1**. Patient monitors exhibiting combinations of many of the features described herein are advantageously commercially available from Masimo under the brand name "Rad 57 cm." As shown in FIG. **7**, the monitor **700** comprises a monitor similar to monitor **200** disclosed with reference to FIG. **2**. Moreover, monitor **700** further includes a multi-mode display **706** capable of displaying, for example, measurements of HbMet and BPM. In an embodiment, the display **706** has insufficient space or display real estate to display the many parameters capable of being measured by the monitor **700**. Thus, the multi-mode display **706** may advantageously cycle through two or more measured parameters. In such embodiments, the monitor **700** may also advantageously include parameter indicators **708**, **710**, providing additional visual queues as to which parameter is currently displayed. In an embodiment, the display **706** may also cycle colors, flash rates, or other audio or visual queues providing readily identifiable information as to which measured parameter is displayed. For example, when the multi-mode display **706** displays measured values of BPM that are normal, the numbers may advantageously appear in green, while normal measured values of HbMet may appear in blue. Moreover, in an embodiment, the display **706** may flash at a predefined rate when searching for saturation and at another predefined rate when a signal quality is below a predetermined threshold.

FIG. **7** also illustrates the monitor **700** comprising user input keys **718**, including an HbCO/HbMet button **720**. In an embodiment, activation of the HbCO/HbMet button **720** toggles the measured value displayed in the multi-mode display **706**. For example, activation of the HbCO/HbMet button **720** toggles the multi-mode display **206** from displaying measured values of SpO₂ and BPM, to HbCO and HbMet for about ten (10) seconds. Activation of the mode/enter button

222 or the next button 224 during the ten (10) second period returns the multi-mode display 706 back to SpO₂ and BPM. A skilled artisan will also recognize that activation of the HbCO/HbMet button 720 may advantageously toggle through a plurality of measured values, and that such values may be displayed for short segments and then return to SpO₂ and BPM, may remain displayed until further activation of the button 720, or the like.

The monitor 700 also comprises a coarser indication of HbMet through an HbMet bar 740. In an embodiment, a plurality of LED's activate from a bottom toward a top such that the bar "fills" to a level proportional to the measured value, with increments at about 0.5%, about 1%, about 2%, about 3%, about 4%, about 5%, about 7.5%, about 10%, about 15% and greater than about 20%, although an artisan will recognize from the disclosure herein other useful delineations. Additionally, the HbMet bar 740 may advantageously change colors, flash, increasingly flash, or the like to indicate worsening measured values of perfusion.

Although disclosed with reference to the HbMet bar 740, an artisan will recognize from the disclosure herein other coarse or even gross indications of HbMet, or any measured parameter. For example, a single LED may advantageously show green, yellow, and red, to indicate worsening coarse values of HbMet. Alternatively, a single LED may simply light to indicate an alarm or approaching alarm condition.

FIG. 8 illustrates an exemplary display of the patient monitor 700 of FIG. 7. As shown in FIG. 8, the display includes the multi-mode displays 206, 706, parameter indicators 208, 210, 708, 710, the HbCO bar 212 and indicator 204, the HbMet bar 740, and the alarm indicator 244. In an embodiment, the multi-mode display 706 is similar to multi-mode display 206, comprising a plurality of seven segment displays 302 capable of displaying alpha-numeric information, and capable of altering its display characteristics or aspects in a wide variety of configurations discussed with reference to the display 206.

FIG. 9 illustrates the display of FIG. 8 showing measured values of SpO₂, BPM, HbCO, HbMet, and type of sensor according to an exemplary embodiment of the patient monitor of FIG. 1. FIG. 9 also shows the HbMet bar 740 near the bottom and corresponding to about 1%, representing acceptable HbMet, while the HbCO bar 212 hovers at a dangerous near 20%. In addition, the HbCO indicator 204 is showing communication with a sensor producing sufficient data to determine measured values of additional parameters, such as, HbMet, HbCO or the like. In an embodiment, such sensors may comprise sensors capable of emitting light of more than two (2) different wavelengths, preferably more than four (4) different wavelengths, and more preferably eight (8) or more different wavelengths.

FIG. 10 illustrates the display of FIG. 8 showing measured values of HbCO, HbMet, and type of sensor according to an exemplary embodiment of the patient monitor of FIG. 1. As shown in FIG. 10, the multi-mode display 706 is displaying a percentage value of HbMet that is shifted using the parameter indicator 708. The data has been advantageously shifted to the left to quickly and efficiently indicate that the displayed parameter is other than BPM. Accordingly, the parameter indicator 708 is also activated to confirm the display of measured values of HbMet. As disclosed in the foregoing, in an embodiment, the multi-mode display 706 is blue.

FIG. 10 also shows the HbMet bar 740 nearly empty, representing acceptable HbMet. In addition, the activation of the HbCO indicator 204 represents communication with a sensor capable of producing sufficient data to determine measured values of HbCO. In an embodiment, such sensors may have appropriate data stored on a memory associated there-

with, or the like. FIG. 10 also shows the HbCO measurement being about 20% (as illustrated on the HbCO bar 212 and multi-mode display 206) thereby indicating a potentially dangerous situation that if exacerbated, will become quite problematic. Therefore, the alarm indicator 244 is also activated, and in some embodiments, the speaker 236 as well.

FIG. 11A illustrates a perspective view of an exemplary noninvasive multi-parameter patient monitor 1000, such as, for example, the patient monitor of FIG. 1. Moreover, FIGS. 11B-11E illustrate exemplary display screens of the patient monitor of FIG. 11A. As shown in FIGS. 11A-11B, an embodiment of the monitor 1000 includes a display 1101 showing a plurality of parameter data. For example, the display may advantageously comprise a CRT or an LCD display including circuitry similar to that available on oximeters commercially available from Masimo Corporation of Irvine, Calif. sold under the name Radical™, and disclosed in the U.S. patents referenced above and incorporated above. However, an artisan will recognize from the disclosure herein many commercially available display components capable of displaying multiple parameter data along with the ability to display graphical data such as plethysmographs, trend traces, and the like.

In an embodiment, the display includes a measured value of SpO₂ 1102, a measured value of pulse rate 1104 in BPM, a plethysmograph 1106, a measured value of HbCO 1108, a measured value of HbMet 1110, a measured value of a perfusion quality 1112, a measured value of Hbt 1114, and a derived value of fractional saturation "SpaO₂" 1116. In an embodiment, SpaO₂ comprises HbO₂ expressed as a percentage of the four main hemoglobin species, i.e., HbO₂, Hb, HbCO, and HbMet.

In an embodiment, one or more of the foregoing parameter includes trending or prediction indicators 1118 showing the current trend or prediction for that corresponding parameter. In an embodiment, the indicators 1118 may advantageously comprise an up arrow, a down arrow, and a hyphen bar to indicate up trending/prediction, down trending/prediction, or neutral trending/prediction.

FIG. 11C illustrates an exemplary display screen showing trend graph 1140 including trend line 1142 for HbMet. In an embodiment, the trend line 1142 may be advantageously colored for quick straightforward recognition of the trending parameter, may be associated with any one or more of the foregoing alarm attributes, may include trending lines for other parameters, or the like. The display screen also shows trending directional indicators 1142, 1144 for many of the displayed physiological parameters. In an embodiment, the directional indicators 1142, 1144 may advantageously comprises arrows showing the recent trend, predicted trend, user-customizable trend, combinations thereof, or the like for the associated parameters. In an embodiment, the directional indicators 1142, 1144 comprises an up arrow indicating a rising trend/predicted trend, a middle bar indicating a somewhat stable trend/predicted trend, and a down arrow indicating a lowering trend/predicted trend. An artisan will recognize a wide variety of other directional indicators 1142, 1144 from the disclosure herein.

FIG. 11D shows an exemplary display screen in vertical format. Such vertical format could be user actuated or based on a gravity switch. FIGS. 11E-11F illustrate additional displays of various physiological parameters similar to those discussed in the foregoing. As shown in FIG. 11G, the display includes a measured value of SpO₂ 1162, a measured value of pulse rate 1164 in BPM, a plethysmograph 1166, a HbCO bar 1168, and a HbMet bar 1170. In an embodiment, the HbCO bar 1168 and HbMet bar 1170 may advantageously

behave the same or similarly to the HbCO bar **212** and HbMet bar **712**. Moreover, similar bars may advantageously display any of the physiological parameters discussed herein using display indicia appropriate to that parameter. For example, a SpO₂ or SpaO₂ bar may advantageously range from about 0% to about 100%, and more preferably range from about 50% to about 100%, while a Hbt bar may advantageously range from about 0 to about 30.

Moreover, similar to the disclosure above, the measured value of SpO₂ **1162** may advantageously toggle to measured values of HbCO, HbMet, Hbt, or the like based on, for example, actuation of user input keys, or the like.

In addition to the foregoing, the display may also include graphical data showing one or more color-coded or other identifying indicia for traces of trend data. Moreover, other graphical presentations may advantageously provide readily identifiable indications of monitored parameters or combinations of monitored parameters of the patient. For example, in an embodiment, the display includes a SpaO₂ graph **1172**. The SpaO₂ graph **1172** plots SpO₂ as a function of other blood analytes (1-SpaO₂), where SpaO₂ comprises HbO₂ expressed as a percentage of the four main hemoglobin species, i.e., HbO₂, Hb, HbCO, and HbMet. Thus, as shown in FIG. **11C**, as the slope of the displayed line or arrow increases, the caregiver can readily note that the majority of hemoglobin carriers are being used to carry oxygen, and not, for example, harmful carbon monoxide. On the other hand, as the slope decreases, the caregiver can readily and advantageously note that the number of hemoglobin species available to carry oxygen is decreasing, regardless of the current value of SpO₂. Moreover, the length of the arrow or line also provides an indication of wellness, e.g., the higher the line the more oxygen saturation, the lower the line, the more likely there may be desaturation event, or the like.

Thus, the SpaO₂ graph **1172** provides the caregiver with the ability to recognize that even though the measured value of SpO₂ may be within acceptable ranges, there are potentially an unacceptable number of hemoglobin carriers unavailable for carrying oxygen, and that other potential problems may exist, such as, for example, harmful carbon monoxide levels, or the like. In an embodiment, various alarm conditions may cause the graph **1172** to change color, flash, or any combination of alarm indications discussed in the foregoing. Moreover, FIG. **11I** illustrates yet an additional display of the foregoing parameters.

An embodiment may also include the monitor **1000** advantageously defining regions of wellness/severity of the monitored patient. For example, because the graph **1172** comprises two dimensions, the monitor **1000** may advantageously define regions where the patient's measured physiological parameters are considered acceptable, regions where the patient is considered at risk, regions where the patient is critical, and the like. For example, one region of acceptability may include a high SpO₂ and a low 1-SpaO₂, another region of risk may include a high SpO₂ and a high 1-SpaO₂, and another critical region may include a low SpO₂ and a high 1-SpaO₂. Moreover, an artisan will recognize from the disclosure herein that different parameters may also be combined to provide readily identifiable indications of patient wellness.

In addition to or as an alternative to the two dimensional SpaO₂ graph **1172**, the monitor **1000** may also include a three dimensional graph, such as, for example, extending the graph **1172** along the variable of time. In this embodiment, the foregoing regions advantageously become three dimensional surfaces of wellness. Moreover, trend data may also be advantageously added to the surface to provide a history of when

particular monitored parameters dipped in and out of various surfaces of wellness, risk, criticality, or the like. Such trend data could be color-coded, text identified, or the like. An artisan will also recognize that such surfaces may be dynamic. For example, measurements of HbCO >about 5 may dictate that trend data showing SpO₂ <about 90% should be considered critical; however, measurements of HbCO <about 5 may dictate only SpO₂ <about 85% would be critical. Again, an artisan will recognize from the disclosure herein other parameter combinations to create a wide variety of wellness/critical regions or surfaces that provide readily available visual or audio indications of patient well being, trigger specific alarms, or the like.

Moreover, the monitor **1000** may advantageously employ enlargement or reorganization of parameter data based on, for example, the severity of the measurement. For example, the monitor **1000** may display values for HbCO in a small portion of the screen or in the background, and when HbCO begins to approach abnormal levels, the small portion may advantageously grown as severity increases, even in some embodiments to dominate the display. Such visual alarming can be combined with audio alarms such as announcements, alarms, rising frequencies, or the like, and other visual alarms such as flashing, coloration, or the like to assist a caregiver in noticing the increasing severity of a monitored parameter. In an embodiment, a location of the display of an alarming value is changed to be displayed in a larger display area, such as **1102**, so as to be readily noticeable and its display values readily ascertainable.

Although the foregoing invention has been described in terms of certain preferred embodiments, other embodiments will be apparent to those of ordinary skill in the art from the disclosure herein. For example, the monitor **100** may advantageously be adapted to monitor or be included in a monitor capable of measuring physiological parameters other than those determined through absorption spectroscopy, such as, for example, blood pressure, ECG, EKG, respiratory rates, volumes, inputs for blood pressure sensors, acoustical sensors, and the like. Moreover, the monitor **100** may be adapted for wireless communication to and from the sensor **106**, and/or to and from other monitoring devices, such as, for example, multi-parameter or legacy monitoring devices.

Also, other combinations, omissions, substitutions and modifications will be apparent to the skilled artisan in view of the disclosure herein. Accordingly, the present invention is not intended to be limited by the reaction of the preferred embodiments, but is to be defined by reference to the appended claims.

Additionally, all publications, patents, and patent applications mentioned in this specification are herein incorporated by reference to the same extent as if each individual publication, patent, or patent application was specifically and individually indicated to be incorporated by reference.

What is claimed is:

1. A method of determining which of a plurality of physiological measurements to measure based on the signal quality of the signal, the method comprising:

using a sensor configured to measure at least two different physiological measurements to obtain a signal from a light sensitive detector, the sensor including at least three different light emitters emitting at least three different wavelengths of light through tissue of a living patient and detecting the light after attenuation of the tissue;
determining a signal quality of the signal;

21

driving less than said at least 3 different light emitters to emit light, said driving responsive to the signal quality determination; and

determining an output value for one of the at least two different measurements responsive to said emitted light.

2. The method of claim 1, wherein if the signal quality is low, only two of the at least three different emitters are activated.

3. The method of claim 1, wherein if the signal quality is low, fewer different physiological measurements are measured.

4. A method of informing a user of a patient monitor about one of a type of sensor communicating with the patient monitor and a type of physiological parameter determinable using the sensor communicating with the patient monitor, the method comprising:

receiving information from an information element associated with one of an optical sensor and a communication cable between a patient monitor and an optical sensor;

determining a number of wavelengths capable of being emitted by the optical sensor from the information;

determining a signal quality of a signal received by the optical sensor; and

activating an indicator of the type of physiological parameters determinable;

driving less than the number of wavelengths capable of being emitted by the optical sensor based on the number wavelengths emitted by the optical sensor and the signal quality of the signal.

5. The method of claim 4, wherein the indicator comprises a display of data determined using signals from the optical sensor.

6. The method of claim 4, wherein the indicator comprises a visual indicator.

7. The method of claim 6, wherein the visual indicator comprises a color.

22

8. The method of claim 6, wherein the visual indicator comprises an LED.

9. The method of claim 8, wherein the LED changes color based on which of the first and second sensors is attached.

10. The method of claim 8, wherein the LED color comprises red when the first sensor is attached and another color when another sensor is attached.

11. The method of claim 4, wherein the indicator comprises an audible indicator.

12. The method of claim 11, wherein the audible indicator comprises one or more tones.

13. The method of claim 11, wherein the audible indicator emits a first tone when the first sensor is attached and a different second tone when the second sensor is attached.

14. A physiological parameter monitor capable of improving performance by activating less light emission sources of an optical sensor, the monitor comprising a processor capable of determining a number of light emission sources available for activation on an attached sensor and capable of activating two of the plurality of light emission sources and capable of activating more than two of the plurality of light emission sources based on a signal quality received from the optical sensor.

15. The monitor of claim 14, wherein the processor activates two of the plurality of light emission sources to measure a first physiological parameter under low signal quality conditions.

16. The monitor of claim 15, wherein the processor activates more than two of the plurality of light emission sources to measure a second physiological parameter under high signal quality conditions.

17. The monitor of claim 15, wherein the processor activates more than two of the plurality of light emission sources to more accurately measure the first physiological parameter.

18. The monitor of claim 14, wherein the processor activates more than two of the plurality of light emission sources to measure a second physiological parameter.

* * * * *

专利名称(译)	无创多参数病人监护仪		
公开(公告)号	US9131882	公开(公告)日	2015-09-15
申请号	US14/052604	申请日	2013-10-11
[标]申请(专利权)人(译)	CERCACOR LAB		
申请(专利权)人(译)	CERCACOR LABORATORIES , INC.		
当前申请(专利权)人(译)	CERCACOR LABORATORIES , INC.		
[标]发明人	AL ALI AMMAR KIANI MASSI JOE E DIAB MOHAMED K WU ROGER FISHEL RICK		
发明人	AL-ALI, AMMAR KIANI, MASSI JOE E. DIAB, MOHAMED K. WU, ROGER FISHEL, RICK		
IPC分类号	A61B5/1455 A61B5/0295 A61B5/145 A61B5/00 A61B5/026 A61B5/0205 G06F19/00 A61B5/024		
CPC分类号	A61B5/0261 A61B5/0295 A61B5/02416 A61B5/1455 A61B5/14532 A61B5/14546 A61B5/14552 A61B5/6826 A61B5/7221 A61B5/7246 A61B5/742 A61B5/7405 A61B5/746 A61B5/7475 A61B5/14551 A61B5/0205 G06F19/3418 A61B5/02427 A61B2562/08 A61B2562/085 A61B2562/222 Y10S439/909 A61B5/6832 G16H10/40 G16H40/67 A61B1/00 A61B5/0022 A61B5/1495 A61B5/6815 A61B5/6829 A61B5/6838 A61B5/7275 A61B5/7278 H05K999/99		
优先权	11/367014 2012-07-17 US 60/657596 2005-03-01 US 60/657281 2005-03-01 US 60/657268 2005-03-01 US 60/657759 2005-03-01 US		
其他公开文献	US20140142402A1		
外部链接	Espacenet USPTO		

摘要(译)

本公开的实施例包括手持式多参数患者监视器，其能够从能够检测由身体组织衰减的光的光敏检测器的输出确定多个生理参数。例如，在一个实施例中，监视器能够有利且准确地显示脉搏率，体积描记器数据，灌注质量，信号置信度和身体组织中血液成分的值中的一个或多个，包括例如动脉一氧化碳饱和度（“HbCO”），高铁血红蛋白饱和度（“HbMet”），总血红蛋白（“Hbt”），动脉血氧饱和度（“SpO₂”），分数动脉血氧饱和度（“SpaO₂”）等。监视器可以基于可用的信号质量和资源来确定要测量多个发光源中的哪个以及多个参数中的哪个参数。

