



(19) **United States**

(12) **Patent Application Publication**  
**Oleson et al.**

(10) **Pub. No.: US 2019/0254379 A1**  
(43) **Pub. Date: Aug. 22, 2019**

(54) **SYSTEM AND METHOD FOR CONTROLLING ACTIVE RECOVERY BASED ON DETECTED PARAMETER**

*A43B 13/20* (2006.01)  
*A61B 5/021* (2006.01)  
*A61B 5/0205* (2006.01)  
*A61B 5/00* (2006.01)

(71) Applicant: **Under Armour, Inc.**, Baltimore, MD (US)

(52) **U.S. Cl.**  
CPC ..... *A43B 3/0005* (2013.01); *G05B 15/02* (2013.01); *A61B 5/0024* (2013.01); *A61B 5/021* (2013.01); *A61B 5/02055* (2013.01); *A43B 13/20* (2013.01)

(72) Inventors: **Mark A. Oleson**, Baltimore, MD (US);  
**F. Grant Kovach**, Baltimore, MD (US);  
**Nathan Dau**, Baltimore, MD (US);  
**Jeffrey Allen**, Baltimore, MD (US)

(21) Appl. No.: **16/399,572**

(22) Filed: **Apr. 30, 2019**

**Related U.S. Application Data**


(63) Continuation of application No. 15/213,749, filed on Jul. 19, 2016, now Pat. No. 10,327,499.

**Publication Classification**

(51) **Int. Cl.**  
*A43B 3/00* (2006.01)  
*G05B 15/02* (2006.01)

(57) **ABSTRACT**

A shoe is provided for use by a user and for use with a communication device that transmits a physiological signal based on a detected physiological parameter of the user. The shoe includes a sole, a force actuating mechanism, a receiver and a controller. The sole has a top surface for supporting the foot of the user when being worn by the user. The force actuating mechanism provides a force to the top surface of the sole and is disposed at the sole so as to provide the force to a plantar venous plexus of the foot. The receiver receives the physiological parameter signal. The controller generates a control signal to control the force actuating mechanism. The controller further modifies the control signal based on the received physiological parameter signal.






FIG. 1A





FIG. 1B






FIG. 3

FIG. 3 is a side view of a shoe, likely a sneaker, showing its sole assembly. The shoe features a collar (212) at the top and laces (302) on the side. The sole assembly includes a heel counter (216) and a heel portion (308). A dashed line (104) is shown within the sole, possibly representing a cushioning element. The sole assembly is divided into a midsole (206) and a forefoot portion (210). A layer (214) is positioned above the forefoot portion. A label 204 points to the overall sole structure.




FIG. 4A




FIG. 4B




FIG. 5




FIG. 6

## SYSTEM AND METHOD FOR CONTROLLING ACTIVE RECOVERY BASED ON DETECTED PARAMETER

### CROSS-REFERENCE TO RELATED APPLICATIONS

[0001] This document is a continuation of U.S. patent application Ser. No. 15/213,749, filed Jul. 19, 2016, the entire contents of which are incorporated by reference herein.

### BACKGROUND

[0002] The present invention generally relates to devices and methods to improve blood flow and recovery.

[0003] There exists a need for a device and method to improve blood flow and speed recovery based on detected parameters.

### BRIEF SUMMARY OF THE DRAWINGS

[0004] The accompanying drawings, which are incorporated in and form a part of the specification, illustrate example embodiments and, together with the description, serve to explain the principles of the invention. In the drawings:

[0005] FIGS. 1A-B illustrate the plantar venous plexus, wherein FIG. 1A illustrates a bottom view of a foot and FIG. 1B illustrates a side view of the foot;

[0006] FIG. 2 illustrates a shoe in accordance with aspects of the present invention;

[0007] FIG. 3 illustrates another shoe in accordance with other aspects of the present invention;

[0008] FIGS. 4A-B illustrate a force actuating mechanism in retracted and extended states in accordance with aspects of the present invention;

[0009] FIG. 5 illustrates a force actuating mechanism in retracted and extended states over time in accordance with aspects of the present invention; and

[0010] FIG. 6 illustrates a process by which active recovery is achieved in response to a detected parameter in accordance with aspects of the present invention.

### DETAILED DESCRIPTION

#### Overview

[0011] A shoe is provided for use by a user and for use with a communication device that is operable to transmit a physiological parameter signal (e.g., a blood pressure signal) based on a detected physiological parameter (e.g., a detected blood pressure) of the user. The shoe includes a sole, a force actuating mechanism, a receiver and a controller. The sole has a top surface for supporting the foot of the user when being worn by the user. The force actuating mechanism provides a force normal to the top surface of the sole. The force actuating mechanism is disposed at the sole so as to provide the force to a plantar venous plexus of the foot. The receiver receives the physiological parameter signal. The controller generates a control signal to control the force actuating mechanism. The controller is further operable to modify the control signal based on the received physiological parameter signal.

#### Example Embodiments

[0012] FIGS. 1A-B illustrate the plantar venous plexus, wherein FIG. 1A illustrates a bottom view of a foot and FIG. 1B illustrates a side view of the foot.

[0013] As shown in the figures, a plantar venous plexus **104** is generally located in the central portion of the plantar side of a foot **102**.

[0014] Plantar venous plexus **104** is an area of foot **102** that functions to pump blood back up the leg from the foot and is also known as the venous foot pump. Typically, plantar venous plexus **104** is directly involved with the action of walking, with the pressures exerted on the foot during the walking cycle serving to effectively pump the blood. The purpose is to pump deoxygenated blood up the leg to the next stage pump, called the calf pump. The pumping action serves to take blood that has delivered nutrients to the foot and move the blood back toward the heart and lungs, taking all the waste products with it.

[0015] Problems may arise, though, after a person has a strenuous workout and desires to rest and recover. While the person is resting, plantar venous plexus **104** is not effectively pumping blood and is therefore ineffectively disposing of waste products. As such, the waste products pool in the foot and lower leg. There exists a need for a device and method to effectively pump blood through the plantar venous plexus and support recovery after engaging in athletic activity.

[0016] FIG. 2 illustrates a shoe in accordance with aspects of the present invention.

[0017] As shown in the figure, a system **200** includes a shoe **202** and a communication device **218**. Shoe **202** further includes a force actuating mechanism **206**, a receiver **208**, a controller **210** and a sole **204**. Sole **204** further includes a top surface **212**. Communication device **218** can be any device that can detect a parameter and transmit signals based on the detected parameter including, but not limited to, an activity monitoring device, a smartwatch, a cellular telephone and a tablet computer. Transmitting data may be accomplished via wireless means including, but not limited to, Bluetooth and WiFi.

[0018] Communication device **218** detects a parameter and wirelessly transmits signals based on the parameter to receiver **208**. The detected parameter can be any number of physiological parameters including, but not limited to, blood pressure, heart rate, temperature, moisture, salinity and breathing rate.

[0019] Receiver **208** receives signals from communication device **218** and sends those signals to controller **210** via line **214**.

[0020] Controller **210** receives communications from receiver **208** via line **214**, and provides instructions to force actuating mechanism **206** via line **216**. The instructions provided to force actuating mechanism **206** are based on the communications from receiver **208**.

[0021] Force actuating mechanism **206** receives instructions from controller **210** via line **216** and executes those instructions received from controller **210**, resulting in force actuating mechanism **206** extending or retracting. Force actuating mechanism **206** is in contact with top surface **212**. As force actuating mechanism **206** extends, it exerts a force on plantar venous plexus **104** and as it retracts, it releases the force exerted on plantar venous plexus **104**. Force actuating mechanism **206** can be any type of known actuator that can extend or retract, including, but not limited to, hydraulic, pneumatic, electric, thermal, magnetic or mechanical.

[0022] As shown in the figure, force actuating mechanism 206, receiver 208 and controller 210 are shown as separate elements. However, in some embodiments, at least two of force actuating mechanism 206, receiver 208 and controller 210 may be combined as a unitary device.

[0023] In some embodiments, at least one of force actuating mechanism 206, receiver 208 and controller 210 may be implemented as a computer having tangible computer-readable media for carrying or having computer-executable instructions or data structures stored thereon. Such tangible computer-readable media can be any available media that can be accessed by a general purpose or special purpose computer. Non-limiting examples of tangible computer-readable media include physical storage and/or memory media such as RAM, ROM, EEPROM, CD-ROM or other optical disk storage, magnetic disk storage or other magnetic storage devices, or any other medium which can be used to carry or store desired program code means in the form of computer-executable instructions or data structures and which can be accessed by a general purpose or special purpose computer. For information transferred or provided over a network or another communications connection (either hardwired, wireless, or a combination of hardwired or wireless) to a computer, the computer may properly view the connection as a computer-readable medium. Thus, any such connection may be properly termed a computer-readable medium. Combinations of the above should also be included within the scope of computer-readable media.

[0024] The operation of system 200 will be further described with reference to FIG. 6.

[0025] FIG. 3 illustrates another shoe in accordance with other aspects of the present invention;

[0026] As shown in the figure, a shoe 302 includes a detector 308.

[0027] Detector 308 detects a parameter, generates a signal based on the parameter and provides the signal to controller 210 via line 214.

[0028] In some embodiments, at least one of force actuating mechanism 206, detector 308 and controller 210 may be implemented as a computer having tangible computer-readable media for carrying or having computer-executable instructions or data structures stored thereon. Such tangible computer-readable media can be any available media that can be accessed by a general purpose or special purpose computer.

[0029] The operation of shoe 302 will be further described with reference to FIG. 6.

[0030] FIGS. 4A-B illustrate a force actuating mechanism in retracted and extended states in accordance with aspects of the present invention.

[0031] As shown in the figures, force actuating mechanism 206 includes a surface 402 and an extending mechanism 404. Surface 402 is in contact with both extending mechanism 404 and top surface 212.

[0032] As shown in FIG. 4A, force actuating mechanism 206 is in a retracted state with the height of extending mechanism 404 denoted by height  $h_{min}$ . In this configuration, surface 402 is not pushing against sole 212 and sole 212 is not pushing against the foot of the wearer. With extending mechanism 404 not pushing against the foot of the wearer, plantar venous plexus 104 is not compressed, meaning that force actuating mechanism 206 is not acting to pump blood through plantar venous plexus 104.

[0033] As shown in FIG. 4B, force actuating mechanism 206 is in an extended state with the height of extending mechanism 404 denoted by height  $h_{max}$ . In this configuration, surface 402 is pushing against sole 212 and sole 212 is pushing against the bottom of the foot of the wearer. With extending mechanism 404 pushing against the foot of the wearer, plantar venous plexus 104 is compressed, meaning that force actuating mechanism 206 is acting to pump blood through plantar venous plexus 104.

[0034] The operation of force actuating mechanism 206 moving from a retracted to an extended state will be further described with reference to FIGS. 5-6.

[0035] FIG. 5 illustrates a force actuating mechanism in retracted and extended states over time in accordance with aspects of the present invention.

[0036] As shown in the figure, at time  $t_1$  extending mechanism 404 is at height  $h_{min}$ , indicating that extending mechanism 404 is in the fully retracted state. At some time later,  $t_2$ , extending mechanism 404 has moved to height  $h_1$ , pushing surface 402 into sole 212 and as sole 212 is forced upwards, it pushes against plantar venous plexus 104, aiding blood flow. At a later time,  $t_3$ , extending mechanism 404 is once again at height  $h_{min}$ , the fully retracted state, wherein plantar venous plexus 104 is not acting to aid blood flow. At a further later time,  $t_4$ , extending mechanism 404 is at height  $h_{max}$ , indicating that extending mechanism 404 is in the fully extended state. In the fully extended state, sole 212 is forced against plantar venous plexus 104 to the maximum allowable amount, aiding blood flow during active recovery. At a later time,  $t_5$ , extending mechanism 404 is at height  $h_2$ , forcing sole 212 against plantar venous plexus 104, aiding blood flow.

[0037] The process by which extending mechanism 404 moves between  $h_{min}$  and  $h_{max}$  will be further described with reference to FIG. 6.

[0038] FIG. 6 illustrates a process by which active recovery is achieved in response to a detected parameter in accordance with aspects of the present invention.

[0039] As shown in the figure, process 600 starts (S602), and a parameter is detected (S604).

[0040] For example, returning to FIG. 2, the user has finished a strenuous exercise and desires to engage in active recovery. The user puts on shoe 202 to begin active recovery. In this example, the active recovery is based on a parameter detected by communication device 218, which the user is wearing. For purposes of discussion, communication device 218 is detecting the user's blood pressure.

[0041] Referring back to FIG. 5, the time when the user puts on shoe 202 corresponds with time  $t_1$  where extending mechanism 404 is fully retracted.

[0042] Returning to FIG. 2, communication device 218 detects the user's blood pressure.

[0043] In an alternate embodiment, and with reference to FIG. 3, the user may put on shoe 302 to engage in active recovery. When the user puts on shoe 302, detector 308 detects the user's blood pressure.

[0044] Referring back to FIG. 6, the parameter control signal is generated and transmitted (S606).

[0045] Returning to FIG. 2, after communication device 218 detects the user's blood pressure, communication device 218 generates a parameter control signal based on the user's blood pressure. Communication device 218 then wirelessly

transmits the parameter control signal to receiver **208**. Receiver **208** then transmits the parameter control signal to controller **210** via line **214**.

[0046] In an alternate embodiment, and with reference to FIG. 3, after detector **308** detects user's blood pressure, detector **308** generates a parameter control signal based on the user's blood pressure. Detector **308** then transmits the parameter control signal to controller **210** via line **214**.

[0047] Returning to FIG. 6, the mechanism control signal is generated (S608).

[0048] Referring back to FIGS. 2-3, controller **210** receives the parameter control signal from either receiver **208** or detector **308**. Controller **210** then uses the data contained in the parameter control signal to generate a mechanism control signal that is based on the user's blood pressure.

[0049] In an example embodiment, controller **210** has a memory therein (not shown) that is operable to store blood pressure relationship data to be used for determining active foot recovery parameters. For example, controller **210** may have any known data structure, a non-limiting example of which includes a look up table, wherein a blood pressure is associated with a predetermined prescribed active foot recovery.

[0050] Non-limiting examples of predetermined prescribed active foot recovery include total time of active recovery as applied by force actuating mechanism **206**, duty cycle of force actuating mechanism **206** during active foot recovery, maximum height of force actuating mechanism **206** during active foot recovery, minimum height of force actuating mechanism **206** during active foot recovery, frequency of force actuating mechanism **206** during active foot recovery and combinations thereof.

[0051] For example, and for purposes of discussion, controller **210** may include data associating a systolic blood pressure of 121 mm Hg and a diastolic blood pressure of 83 mm Hg to require active foot recovery to be performed such that force actuating mechanism **206** has a 50/50 duty cycle, with a minimum height of 0 mm, a maximum height of 15 mm and a frequency of 30 Hz for a time period of 20 minutes.

[0052] Controller **310** uses the blood pressure information within the parameter control signal and the corresponding relationship data stored therein to generate the mechanism control signal. The mechanism control signal will instruct force actuating mechanism **206** how to operate during active recovery. Controller **210** transmits the mechanism control signal to force actuating mechanism **206** via line **216**.

[0053] Returning to FIG. 6, active recovery is performed (S610).

[0054] Returning to FIGS. 2-3, force actuating mechanism **206** receives the mechanism control signal from controller **210** via line **216** and begins active recovery.

[0055] Referring back to FIG. 5, at time  $t_1$  let the user's blood pressure be  $p_1$ , and the mechanism control signal instructs force actuating mechanism **206** to raise extending mechanism **404** from height  $h_{min}$  at time  $t_1$  to height  $h_1$  at time  $t_2$ . During this time, sole **212** is being forced into plantar venous plexus **104**, causing blood to flow and aid in active recovery.

[0056] At time  $t_2$ , the mechanism control signal instructs force actuating mechanism **206** to lower extending mechanism **404** from height  $h_1$  at time  $t_2$  to height  $h_{min}$  at time  $t_3$ .

Force actuating mechanism **206** then cycles the states shown at times  $t_1$ - $t_3$ , to aid in active foot recovery in response to the user's blood pressure  $p_1$ .

[0057] Suppose, for purposes of discussion, that after performing some active recovery by cycling through the states shown at times  $t_1$ - $t_3$  of FIG. 5, that a new blood pressure  $p_2$  is detected.

[0058] Again, controller **310** uses the blood pressure information within the parameter control signal and the corresponding relationship data stored therein to generate the mechanism control signal. The mechanism control signal will instruct force actuating mechanism **206** how to operate during active recovery. Controller **210** transmits the mechanism control signal to force actuating mechanism **206** via line **216**.

[0059] In this example, suppose that for the new blood pressure  $p_2$ , the prescribed active recovery requires extending mechanism **404** to extend to a greater height. In such a case, the mechanism control signal instructs force actuating mechanism **206** to raise extending mechanism **404** from height  $h_{min}$  at time  $t_3$  to height  $h_{max}$  at time  $t_4$ .

[0060] Further, force actuating mechanism **206** then cycles the states shown at times  $t_3$  and  $t_4$ , for example passing through the state shown at time  $t_5$  to aid in active foot recovery in response to the user's blood pressure  $p_2$ .

[0061] Returning to FIG. 6, the user may choose to stop monitoring blood pressure to help perform active recovery (NO at S612). If the user does so, process **600** ends (S614).

[0062] If, however, the user chooses to continue monitoring blood pressure to help perform active recovery (YES at S612), the process of detecting the blood pressure, generating and transmitting the blood pressure signal, generating and transmitting the mechanism control signal and performing active recovery continues.

[0063] This feedback loop will continue until the user's active recovery is complete.

[0064] To change the distance by which extending mechanism **404** is extended or retracted, controller **210** may modify the pulse width, pulse number or pulse amplitude of the mechanism control signal it sends to force actuating mechanism **206**.

[0065] The time intervals between  $t_1$  and  $t_2$ ,  $t_2$  and  $t_3$ ,  $t_3$  and  $t_4$ , and  $t_4$  and  $t_5$  may all be equal, but they may also all be different in order to accomplish an effective active recovery session. Controller **210** may change the time intervals directly by modifying the mechanism control signal it sends to force actuating mechanism **206**. Controller **210** may also change the time intervals indirectly by modifying the pulse width, pulse number or pulse amplitude of the mechanism control signal it sends to force actuating mechanism **206**.

[0066] Controller **210** may also change the speed at which force actuating mechanism **206** extends or retracts, which will also alter the time intervals. Further, controller **210** may modify how long force actuating mechanism **206** remains in a given position, thus altering the overall time intervals between cycles.

[0067] The foregoing description of various preferred embodiments have been presented for purposes of illustration and description. It is not intended to be exhaustive or to limit the invention to the precise forms disclosed, and obviously many modifications and variations are possible in light of the above teaching. The example embodiments, as described above, were chosen and described in order to best explain the principles of the invention and its practical

application to thereby enable others skilled in the art to best utilize the invention in various embodiments and with various modifications as are suited to the particular use contemplated. It is intended that the scope of the invention be defined by the claims appended hereto.

What is claimed is:

1. A shoe for use by a user and for use with a communication device operable to transmit a physiological parameter signal based on a detected physiological parameter of the user, said shoe comprising:

- a sole having a top surface for supporting a foot of the user when being worn by the user;
- a force actuating mechanism operable to provide a force to said top surface of said sole, said force actuating mechanism being disposed at said sole so as to provide the force to a plantar venous plexus of the foot;
- a receiver operable to receive the physiological parameter signal, and
- a controller operable to generate a control signal to control said force actuating mechanism, wherein said controller is further operable to modify the control signal based on the received physiological parameter signal.

2. The shoe of claim 1,

- wherein said force actuating mechanism comprises a surface portion and an extending mechanism, wherein said extending mechanism is operable to extend said surface portion from a first position to a second position, and
- wherein the second position is separated from the first position by a distance and in a direction normal to said top surface of said sole.

3. The shoe of claim 2,

- wherein said controller is operable to generate the control signal so as to set the distance between the first position and the second position,
- wherein said controller is operable to modify the control signal, based on the received physiological parameter signal, so as to change the distance between the first position and the second position.

4. The shoe of claim 3,

- wherein said controller is operable to generate the control signal so as to be a digital signal having a pulse width, wherein said controller is operable to modify the control signal, based on the received physiological parameter signal, so as to change the pulse width to change the distance between the first position and the second position.

5. The shoe of claim 3,

- wherein said controller is operable to generate the control signal so as to be a digital signal having a pulse number, wherein said controller is operable to modify the control signal, based on the received physiological parameter signal, so as to change the pulse number to change the distance between the first position and the second position.

6. The shoe of claim 3,

- wherein said controller is operable to generate the control signal so as to be a digital signal having a pulse amplitude,
- wherein said controller is operable to modify the control signal, based on the received physiological parameter

signal, so as to change the pulse amplitude to change the distance between the first position and the second position.

7. The shoe of claim 2,

- wherein said controller is operable to generate the control signal so as to set a time for the extending mechanism to extend said surface portion from the first position to the second position,
- wherein said controller is operable to modify the control signal, based on the received physiological parameter signal, so as to change the time for the extending mechanism to extend said surface portion from the first position to the second position.

8. The shoe of claim 7,

- wherein said controller is operable to generate the control signal so as to be a digital signal having a pulse width, wherein said controller is operable to modify the control signal, based on the received physiological parameter signal, so as to change the pulse width to change the time for the extending mechanism to extend said surface portion from the first position to the second position.

9. The shoe of claim 7,

- wherein said controller is operable to generate the control signal so as to be a digital signal having a pulse number, wherein said controller is operable to modify the control signal, based on the received physiological parameter signal, so as to change the pulse number to change the time for the extending mechanism to extend said surface portion from the first position to the second position.

10. The shoe of claim 7,

- wherein said controller is operable to generate the control signal so as to be a digital signal having a pulse amplitude,
- wherein said controller is operable to modify the control signal, based on the received physiological parameter signal, so as to change the pulse amplitude to change the time for the extending mechanism to extend said surface portion from the first position to the second position.

11. The shoe of claim 1,

- wherein said physiological parameter signal is a first physiological parameter signal defining a blood pressure signal,
- wherein said receiver is further operable to receive a second physiological parameter signal after said controller modifies the control signal based on the received physiological parameter signal, and
- wherein said controller is further operable to further modify the previously modified control signal based on the received second physiological parameter signal.

12. A shoe for use by a user, said shoe comprising:

- a sole having a top surface for supporting a foot of the user when being worn by the user;
- a force actuating mechanism operable to provide a force to said top surface of said sole, said force actuating mechanism being disposed at said sole so as to provide the force to a plantar venous plexus of the foot;
- a physiological parameter detector operable to generate a physiological parameter signal, and
- a controller operable to generate a control signal to control said force actuating mechanism,

wherein said controller is further operable to receive the physiological parameter signal and modify the control signal based on the received physiological parameter signal.

**13.** The shoe of claim **12**,

wherein said force actuating mechanism comprises a surface portion and an extending mechanism,

wherein said extending mechanism is operable to extend said surface portion from a first position to a second position, and

wherein the second position is separated from the first position by a distance and in a direction normal to said top surface of said sole.

**14.** The shoe of claim **13**,

wherein said controller is operable to generate the control signal so as to set the distance between the first position and the second position,

wherein said controller is operable to modify the control signal, based on the received blood pressure signal, so as to change the distance between the first position and the second position.

**15.** The shoe of claim **13**,

wherein said controller is operable to generate the control signal so as to set a time for the extending mechanism to extend said surface portion from the first position to the second position,

wherein said controller is operable to modify the control signal, based on the received physiological parameter signal, so as to change the time for the extending mechanism to extend said surface portion from the first position to the second position.

**16.** The shoe of claim **12**,

wherein said physiological parameter signal is a first physiological parameter signal defining a blood pressure signal,

wherein said controller is further operable to receive a second physiological parameter signal after said controller modifies the control signal based on the received physiological parameter signal, and

wherein said controller is further operable to further modify the previously modified control signal based on the received second physiological parameter signal.

**17.** A non-transitory, tangible, computer-readable media having computer-readable instructions stored thereon and for use with a wireless communication device operable to transmit a physiological parameter signal based on a physiological parameter of a user, the computer-readable instructions being capable of being read by a computer and being capable of instructing the computer to perform the method comprising:

receiving the physiological parameter signal via a receiver in a shoe comprising a sole, a force actuating mechanism, the receiver and a controller, the sole having a top surface for supporting a foot of the user when being worn by the user, the force actuating mechanism being operable to provide a force to the top surface of the

sole, the force actuating mechanism being disposed at the sole so as to provide the force to a plantar venous plexus of the foot;

generating, via the controller, a control signal to control the force actuating mechanism; and

modifying, via the controller, the control signal based on the received physiological parameter signal.

**18.** The non-transitory, tangible, computer-readable media of claim **17**, the computer-readable instructions being capable of being read by a computer and being capable of instructing the computer to perform the method,

wherein the force actuating mechanism comprises a surface portion and an extending mechanism,

wherein the extending mechanism is operable to extend the surface portion from a first position to a second position,

wherein the second position is separated from the first position by a distance and in a direction normal to the top surface of the sole, and

wherein said modifying the control signal comprises modifying the control signal so as to change the distance between the first position and the second position based on the received physiological parameter signal.

**19.** The non-transitory, tangible, computer-readable media of claim **17**, the computer-readable instructions being capable of being read by a computer and being capable of instructing the computer to perform the method,

wherein the force actuating mechanism comprises a surface portion and an extending mechanism,

wherein the extending mechanism is operable to extend the surface portion from a first position to a second position,

wherein the second position is separated from the first position by a distance and in a direction normal to the top surface of the sole, and

wherein said modifying the control signal comprises modifying the control signal so as to change the time for the extending mechanism to extend the surface portion from the first position to the second position based on the received physiological parameter signal.

**20.** The non-transitory, tangible, computer-readable media of claim **17**, wherein the physiological parameter signal is a first physiological parameter signal defining a blood pressure signal, the computer-readable instructions being capable of being read by a computer and being capable of instructing the computer to perform the method further comprising:

receiving, via the receiver, a second physiological parameter signal after the controller modifies the control signal based on the received physiological parameter signal; and

modifying, via the controller, the previously modified control signal based on the received second physiological parameter signal.

\* \* \* \* \*

