



(12) **Patent Application Publication**  
**Al-Ali et al.**

(10) **Pub. No.: US 2015/0359429 A1**  
(43) **Pub. Date: Dec. 17, 2015**

(60) Provisional application No. 61/703,713, filed on Sep. 20, 2012, provisional application No. 61/625,584, filed on Apr. 17, 2012, provisional application No. 61/597,126, filed on Feb. 9, 2012.

(72) Inventors: **Ammar Al-Ali**, San Juan Capistrano, CA (US); **Eric Karl Kinast**, Santa Ana, CA (US); **Bilal Muhsin**, San Clemente, CA (US); **Chad A. DeJong**, Los Angeles, CA (US)

### Publication Classification

(51) **Int. Cl.**  
**A61B 5/00** (2006.01)

(52) **U.S. Cl.**  
CPC ..... *A61B 5/0024* (2013.01); *A61B 5/7445*  
(2013.01); *A61B 5/002* (2013.01); *A61B*  
*5/0022* (2013.01); *A61B 5/0059* (2013.01);  
*A61B 2560/0214* (2013.01); *A61B 2560/0475*  
(2013.01)


(22) Filed: **Aug. 24, 2015**

### Related U.S. Application Data

(62) Division of application No. 13/762,270, filed on Feb. 7, 2013.

(57) **ABSTRACT**

A device for obtaining physiological information of a medical patient and wirelessly transmitting the obtained physiological information to a wireless receiver.






FIG. 1A





FIG. 1B



*FIG. 1C*




FIG. 1D





FIG. 1E






FIG. 2B






FIG. 3A







FIG. 3B





*FIG. 5*




FIG. 6A




FIG. 6B




FIG. 6C







FIG. 7





*FIG. 9A*





*FIG. 9B*




FIG. 9C




FIG. 9D





FIG. 10



*FIG. 11*





FIG. 12

*FIG. 13*





FIG. 14



*FIG. 15*





FIG. 16A



*FIG. 16B*






FIG. 16C



*FIG. 16D*



*FIG. 16E*




FIG. 16F




FIG. 16G






FIG. 17A







FIG. 17B




*FIG. 17C*



*FIG. 18A*



*FIG. 18B*



*FIG. 18C*

## WIRELESS PATIENT MONITORING DEVICE

### CROSS-REFERENCE TO RELATED APPLICATIONS

**[0001]** The present application is a divisional of U.S. application Ser. No. 13/762,270, filed Feb. 7, 2013, titled Wireless Patient Monitoring System, which claims priority benefit under 35 U.S.C. §119(e) to U.S. Provisional Patent Application Ser. No. 61/597,126, filed Feb. 9, 2012, titled Wireless Patient Monitoring System, U.S. Provisional Patent Application Ser. No. 61/625,584, filed Apr. 17, 2012, titled Wireless Patient Monitoring Device, and U.S. Provisional Patent Application Ser. No. 61/703,713, filed Sep. 20, 2012, titled Wireless Patient Monitoring Device, all of which applications are hereby incorporated by reference in their entirety.

### BACKGROUND

**[0002]** 1. Field

**[0003]** In general, the disclosure relates to methods and apparatuses for wirelessly monitoring a patient's physiological information.

**[0004]** 2. Description of the Related Art

**[0005]** Hospitals, nursing homes, and other patient care facilities typically include patient monitoring devices at one or more bedsides in the facility. Patient monitoring devices generally include sensors, processing equipment, and displays for obtaining and analyzing a medical patient's physiological parameters such as blood oxygen saturation level, respiratory rate, and the like. Clinicians, including doctors, nurses, and other medical personnel, use the physiological parameters obtained from patient monitors to diagnose illnesses and to prescribe treatments. Clinicians also use the physiological parameters to monitor patients during various clinical situations to determine whether to increase the level of medical care given to patients.

**[0006]** For example, the patient monitoring devices can be used to monitor a pulse oximeter. Pulse oximetry is a widely accepted noninvasive procedure for measuring the oxygen saturation level of arterial blood, an indicator of a person's oxygen supply. A typical pulse oximetry system utilizes an optical sensor clipped onto a fingertip to measure the relative volume of oxygenated hemoglobin in pulsatile arterial blood flowing within the fingertip. Oxygen saturation ( $\text{SpO}_2$ ), pulse rate, a plethysmograph waveform, perfusion index (PI), pleth variability index (PVI), methemoglobin (MetHb), carboxy-hemoglobin (CoHb), total hemoglobin (tHb), glucose, and/or otherwise can be displayed on a monitor accordingly.

**[0007]** The patient monitoring devices can also communicate with an acoustic sensor comprising an acoustic transducer, such as a piezoelectric element. The acoustic sensor can detect respiratory and other biological sounds of a patient and provide signals reflecting these sounds to a patient monitor. An example of such an acoustic sensor, which can implement any of the acoustic sensing functions described herein, is described in U.S. application Ser. No. 12/643,939, filed Dec. 21, 2009, titled "Acoustic Sensor Assembly," and in U.S. Application No. 61/313,645, filed Mar. 12, 2010, titled "Acoustic Respiratory Monitoring Sensor Having Multiple Sensing Elements," the disclosures of which are hereby incorporated by reference in their entirety.

**[0008]** Blood pressure is another example of a physiological parameter that can be monitored. Many devices allow blood pressure to be measured by sphygmomanometer sys-

tems that utilize an inflatable cuff applied to a person's arm. The cuff is inflated to a pressure level high enough to occlude a major artery. When air is slowly released from the cuff, blood pressure can be estimated by detecting "Korotkoff" sounds using a stethoscope or other detection means placed over the artery. Other Examples of physiological parameters that can be measured include respiration rate, blood analyte measurements, such as oxygen saturation, and ECG.

### SUMMARY

**[0009]** One aspect of the disclosure is a wireless patient monitoring device including one or more sensors configured to obtain physiological information. The one or more sensors can include an optical sensor, an acoustic respiratory sensor, and/or a blood pressure measurement device. Other sensors, including but not limited to, an EEG, ECG, and/or a sedation state sensor can also be used with the present disclosure. The one or more sensors are connected to a wireless monitor configured to receive the sensor data and to wirelessly transmit sensor data or physiological parameters reflective of the sensor data to a bedside monitor. The bedside monitor can be configured to output the physiological parameters, communication channel, and/or communication status.

**[0010]** Another aspect of the disclosure is directed toward a system configured to wirelessly communicate physiological information, the system including a battery, a housing, a rechargeable electrical storage module, and a memory module configured to store wireless communication information.

**[0011]** In some aspects of the disclosure, the wireless communication information stored on the data storage component facilitates communication between the wireless monitor and the bedside monitor. The information may be a unique identifier used to pair the wireless monitor with the bedside monitor. The information may be a password used to make sure only the correct receiver has access to the transmitted physiological data. The information may be channel information to make certain the wireless monitor and bedside monitor communicate on the same channel.

**[0012]** In some aspects of the disclosure, the bedside monitor can be configured to receive and recharge the removable battery. The battery may include a data storage component configured to store wireless communication information. In some embodiments, the bedside monitor communicates wireless communication information to the battery through a hard wired connection, and the battery stores the information. In some embodiments, the battery communicates wireless communication information to the bedside monitor through a hard wired connection.

**[0013]** Another aspect of the disclosure is directed toward a bedside monitor configured to receive the wireless monitor. In some embodiments, the bedside monitor communicates wireless communication information to the wireless monitor when the wireless monitor is physically and electrically connected with the bedside monitor. In some embodiments, the wireless monitor communicates information to the bedside monitor when the wireless monitor is physically and electrically connected with the bedside monitor.

**[0014]** In another aspect of the disclosure, the wireless monitor can be configured to transmit physiological data over a first wireless technology when a signal strength of the first wireless technology is sufficiently strong and transmit physiological data over a second wireless technology when the signal strength of the first wireless technology is not sufficiently strong.

**[0015]** In yet another aspect of the disclosure, the wireless monitor can be configured to transmit physiological data over a first wireless technology when the wireless monitor is within a pre-determined distance from the wireless receiver and transmit physiological data over a second wireless technology when the wireless monitor is not within a pre-determined distance from the bedside monitor.

**[0016]** In another aspect of the disclosure, the battery includes a display. The display can be configured to activate when the wireless transmitter transmits physiological data over a first wireless technology and deactivate when the wireless transmitter transmits physiological data over a second wireless technology.

**[0017]** One aspect of the disclosure is a method of wirelessly monitoring physiological information. The method includes providing a battery including a data storage component, physically connecting the battery to a bedside monitor, storing data on the data storage component of the battery, connecting the battery to a wireless monitor, and transmitting physiological data from the wireless monitor to the bedside monitor.

**[0018]** In another aspect of the disclosure, transmitting physiological data from the wireless monitor to the bedside monitor includes transmitting physiological data over a first wireless technology when the wireless monitor is within a pre-determined distance from the bedside monitor and transmitting physiological data over a second wireless technology when the wireless monitor is not within a pre-determined distance from the bedside monitor. In some embodiments of the disclosure, the first wireless technology is Bluetooth or ZigBee, and the second wireless technology is Wi-Fi or cellular telephony.

**[0019]** In yet another aspect of the disclosure, transmitting physiological data from the wireless monitor to the bedside monitor includes transmitting physiological data over a first wireless technology when a signal strength of the first wireless technology is sufficiently strong and transmitting physiological data over a second wireless technology when the signal strength of the first wireless technology is not sufficiently strong.

**[0020]** In some aspects of the disclosure, the wireless monitor can be configured to be coupled to an arm band attached to the patient. Alternatively, the wireless monitor can be configured to be coupled to a patient's belt, can be carried by the patient (e.g., via a shoulder strap or handle), or can be placed on the patient's bed next to the patient, among other locations.

**[0021]** In another aspect of the disclosure, the wireless monitor battery includes a display screen. When the wireless monitor is within a pre-determined distance from the bedside monitor and transmits data over Bluetooth or Zigbee, the display screen deactivates. When the wireless monitor is not within a pre-determined distance from the bedside monitor and transmits data over Wi-Fi or cellular telephony, the display screen activates. Alternatively, independent of the communication protocol used by the device, when the wireless monitor is a pre-determined distance from the bedside monitor, the display screen activates. Similarly when the wireless monitor is within a pre-determined distance to the bedside monitor, the display screen deactivates.

**[0022]** In certain aspects of the disclosure, a blood pressure device can be used. The blood pressure device can be coupled to a medical patient and a wireless transceiver electrically coupled with the blood pressure device. The wireless transceiver can wirelessly transmit blood pressure data received by

the blood pressure device and physiological data received from one or more physiological sensors coupled to the blood pressure device. To further increase patient mobility, in some embodiments, a single cable can be provided for connecting multiple different types of sensors together.

**[0023]** In certain aspects of the disclosure, a wireless patient monitoring device for measuring one or more parameters can be secured to an arm of the patient. For example, a wireless measurement device for measuring oxygen saturation and respiration rate can be secured to the arm of a patient. The wireless monitoring device can connect to an oximeter probe and an acoustic respiration probe. The monitor can have a display screen and/or can transmit wireless information to a bedside monitor. In an embodiment, a docking station can be provided for the wireless monitoring device to dock it to a docking station forming a bedside monitor.

**[0024]** In some aspects of the disclosure, the patient monitoring devices can be coupled to a blood pressure cuff and measure blood pressure.

**[0025]** In some aspects of the disclosure, the patient monitoring system can include a sensor configured to obtain physiological information, an anchor connected to the sensor, and a wireless transceiver connected to the anchor. A first cable can connect the sensor to the anchor and a second cable can connect the anchor to the wireless transceiver. In certain aspects, the anchor can adhere to the patient or be carried by the patient in any manner discussed herein.

**[0026]** In some aspects of the disclosure, the patient monitoring system can include one or more sensors configured to obtain physiological information and a wireless transceiver configured to receive the physiological information. The wireless transceiver can include a housing having a first side and a second side. At least one connector can be positioned on the first side and at least one connector can be positioned on the second side. In certain aspects, the first side of housing can be opposite the second side of the housing.

**[0027]** In some aspects of the disclosure, a docking station can include a bedside monitor having a docking port configured to receive a first patient monitor and a docking station adapter configured to adapt the docking port to receive a second patient monitor. The second patient monitor can be a different size than the first patient monitor. In certain aspects, the first patient monitor can communicate with the bedside monitor over a wired connection when the first patient monitor is connected to the docking port. In certain aspects, the second patient monitor can communicate with the bedside monitor over a wired connection when the second patient monitor is connected to the docking station adapter and the docking station adapter is connected to the docking port.

**[0028]** In some aspects of the disclosure, a patient monitoring system can include a first sensor, a second sensor, and a wireless patient monitor configured to receive physiological information from the first sensor and the second sensor. The patient monitoring system can include a single cable connecting the first sensor and the second sensor to the wireless patient monitor. In certain aspects, the single cable can include a first cable section connecting the wireless patient monitor and the first sensor and a second cable section connecting the first sensor and the second sensor. In certain aspects, the first sensor and the second sensor can be powered by a shared power line and/or can transmit signals over a shared signal line.

**[0029]** In some aspects of the disclosure, a patient monitoring system can include one or more sensors configured to

obtain physiological information, a patient monitor configured to receive the physiological information, and a cable hub having one or more inlet connectors connected to the one or more sensors and an outlet connector connected to the patient monitor. In certain aspects, the one or more inlet connectors can be positioned on a first end of the cable hub and the outlet connector can be positioned on a second end of the cable hub, opposite the first end. In certain aspects, the patient monitor can include a wireless transceiver. In certain aspects, the patient monitor can be configured to be worn by the patient. In certain aspects, the cable hub can be configured to adhere to the patient. In certain aspects, a first cable extends from at least one of the one or more sensors to one of the one or more inlet connectors, and a second cable extends from the outlet connector to the patient monitor.

**[0030]** Some aspects of the disclosure describe a method of using a patient monitoring system. The method can include providing a wireless transceiver having a first end and a second end opposite the first end, a first connector positioned on the first end, and a second connector positioned on the second end. The method can include connecting a first end of a first cable to the first connector, and connecting a first end of a second cable to the second connector. In certain aspects, the method can include connecting a second end of the first cable to a first sensor. In certain aspects, the method can include connecting a second end of the second cable to a second sensor or a cable hub connected to one or more sensors. In certain aspects, the method can include connecting a third sensor and/or anchor to the second cable. In certain aspects, the method can include connecting a third cable to a third connector on the second end of the wireless transceiver.

**[0031]** Certain aspects of this disclosure are directed toward a wireless monitor including a housing, a battery, and a strap. The housing can include one or more outlets configured to receive one or more sensors. The battery can be configured to removably engage the housing. A portion of the strap can be disposed between the housing and the battery when the housing is engaged with the battery. In certain aspects, the portion of the strap disposed between the housing and the battery can be a separately formed component from a remainder of the strap. In certain aspects, the portion of the strap can include one or more mating features configured to mate with corresponding features of the housing. In certain aspects, the one or more mating features are flush with the corresponding features of the housing. In certain aspects, the housing can include a recessed portion for receiving the strap.

**[0032]** For purposes of summarizing the disclosure, certain aspects, advantages and novel features of the inventions have been described herein. It is to be understood that not necessarily all such advantages can be achieved in accordance with any particular embodiment of the inventions disclosed herein. Thus, the inventions disclosed herein can be embodied or carried out in a manner that achieves or optimizes one advantage or group of advantages as taught herein without necessarily achieving other advantages as can be taught or suggested herein.

#### BRIEF DESCRIPTION OF THE DRAWINGS

**[0033]** Various embodiments will be described hereinafter with reference to the accompanying drawings. These embodiments are illustrated and described by example only, and are not intended to limit the scope of the disclosure. In the drawings, similar elements have similar reference numerals.

**[0034]** FIGS. 1A and 1B illustrate embodiments of wireless patient monitoring systems.

**[0035]** FIGS. 1C and 1D illustrate further embodiments of wireless patient monitoring systems.

**[0036]** FIG. 1E illustrates the embodiment of the wireless patient monitoring system illustrated in FIGS. 1A-1B in schematic form.

**[0037]** FIGS. 2A and 2B illustrate embodiments of wireless patient monitoring systems having a single cable connection system.

**[0038]** FIGS. 3A and 3B illustrate additional embodiment of patient monitoring systems.

**[0039]** FIGS. 4A and 4B illustrate embodiments of an optical ear sensor and an acoustic sensor connected via a single cable connection system.

**[0040]** FIG. 5 illustrates an embodiment of a wireless transceiver that can be used with any of the patient monitoring systems described above.

**[0041]** FIGS. 6A through 6C illustrate additional embodiments of patient monitoring systems.

**[0042]** FIG. 7 illustrates an embodiment of a physiological parameter display that can be used with any of the patient monitoring systems described above.

**[0043]** FIG. 8 illustrates a further embodiment of a patient monitoring system.

**[0044]** FIGS. 9A-9D illustrate an embodiment of a wireless patient monitoring system.

**[0045]** FIG. 10 illustrates the embodiment of the wireless patient monitoring system illustrated in FIGS. 9A-9D in schematic form.

**[0046]** FIG. 11 illustrates one embodiment of a method of using a wireless patient monitoring system.

**[0047]** FIG. 12 illustrates a wireless monitor having a display screen.

**[0048]** FIGS. 13-15 illustrate methods of using a wireless monitor having a display screen.

**[0049]** FIGS. 16A-16G illustrate another embodiment of a wireless patient monitoring system.

**[0050]** FIGS. 17A-17C illustrate another embodiment of a wireless patient monitoring system.

**[0051]** FIGS. 18A-18C illustrate an animation of patient movement created using a wireless patient monitor.

#### DETAILED DESCRIPTION

**[0052]** In clinical settings, medical sensors are often attached to patients to monitor physiological parameters of the patients. Some examples of medical sensors include, but are not limited to, blood oxygen sensors, such as pulse oximetry sensors, acoustic respiratory sensors, EEGs, ECGs, blood pressure sensors, sedation state sensors, etc. Typically, each sensor attached to a patient is connected to a bedside monitoring device with a cable. The cables limit the patient's freedom of movement and impede a care providers access to the patient. The cables connecting the patient to the bedside monitoring device also make it more difficult to move the patient from room to room or switch to different bedside monitors.

**[0053]** This disclosure describes embodiments of wireless patient monitoring systems that include a wireless device coupled to a patient and to one or more sensors. In one embodiment, the wireless device transmits sensor data obtained from the sensors to a patient monitor. By transmitting the sensor data wirelessly, these patient monitoring systems can advantageously replace some or all cables that con-

nect patients to bedside monitoring devices. To further increase patient mobility and comfort, in some embodiments, a single cable connection system is also provided for connecting multiple different types of sensors together.

**[0054]** These patient monitoring systems are primarily described in the context of an example blood pressure cuff that includes a wireless transceiver. The blood pressure cuff and/or wireless transceiver can also be coupled to additional sensors, such as optical sensors, acoustic sensors, and/or electrocardiograph sensors. The wireless transceiver can transmit blood pressure data and sensor data from the other sensors to a wireless receiver, which can be a patient monitor. These and other features described herein can be applied to a variety of sensor configurations, including configurations that do not include a blood pressure cuff. In an embodiment, an arm band without a blood pressure cuff can be used to secure a wireless patient monitor connected to various sensors.

**[0055]** FIGS. 1A and 1B illustrate embodiments of wireless patient monitoring systems **100A**, **100B**, respectively. In the wireless patient monitoring systems **100** shown, a blood pressure device **110** is connected to a patient **101**. The blood pressure device **110** includes a wireless transceiver **116**, which can transmit sensor data obtained from the patient **101** to a wireless transceiver **120**. Thus, the patient **101** is advantageously not physically coupled to a bedside monitor in the depicted embodiment and can therefore have greater freedom of movement.

**[0056]** Referring to FIG. 1A, the blood pressure device **110a** includes an inflatable cuff **112**, which can be an oscillometric cuff that is actuated electronically (e.g., via intelligent cuff inflation and/or based on a time interval) to obtain blood pressure information. The cuff **112** is coupled to a wireless transceiver **116**. The blood pressure device **110a** is also coupled to a fingertip optical sensor **102** via a cable **107**. The optical sensor **102** can include one or more emitters and detectors for obtaining physiological information indicative of one or more blood parameters of the patient **101**. These parameters can include various blood analytes such as oxygen, carbon monoxide, methemoglobin, total hemoglobin, glucose, proteins, glucose, lipids, a percentage thereof (e.g., concentration or saturation), and the like. The optical sensor **102** can also be used to obtain a photoplethysmograph, a measure of plethysmograph variability, pulse rate, a measure of blood perfusion, and the like.

**[0057]** Additionally, the blood pressure device **110a** is coupled to an acoustic sensor **104a** via a cable **105**. The cable **105** connecting the acoustic sensor **104a** to the blood pressure device **110** includes two portions, namely a cable **105a** and a cable **105b**. The cable **105a** connects the acoustic sensor **104a** to an anchor **104b**, which is coupled to the blood pressure device **110a** via the cable **105b**. The anchor **104b** can be adhered to the patient's skin to reduce noise due to accidental tugging of the acoustic sensor **104a**.

**[0058]** The acoustic sensor **104a** can be a piezoelectric sensor or the like that obtains physiological information reflective of one or more respiratory parameters of the patient **101**. These parameters can include, for example, respiratory rate, inspiratory time, expiratory time, inspiration-to-expiration ratio, inspiratory flow, expiratory flow, tidal volume, minute volume, apnea duration, breath sounds, rales, rhonchi, stridor, and changes in breath sounds such as decreased volume or change in airflow. In addition, in some cases the respiratory sensor **104a**, or another lead of the respiratory sensor **104a** (not shown), can measure other physiological

sounds such as heart rate (e.g., to help with probe-off detection), heart sounds (e.g., S1, S2, S3, S4, and murmurs), and changes in heart sounds such as normal to murmur or split heart sounds indicating fluid overload. In some implementations, a second acoustic respiratory sensor can be provided over the patient's **101** chest for additional heart sound detection. In one embodiment, the acoustic sensor **104** can include any of the features described in U.S. patent application Ser. No. 12/643,939, filed Dec. 21, 2009, titled "Acoustic Sensor Assembly," the disclosure of which is hereby incorporated by reference in its entirety.

**[0059]** The acoustic sensor **104** can be used to generate an exciter waveform that can be detected by the optical sensor **102** at the fingertip, by an optical sensor attached to an ear of the patient (see FIGS. 2A, 3), by an ECG sensor (see FIG. 2C), or by another acoustic sensor (not shown). The velocity of the exciter waveform can be calculated by a processor (such as a processor in the wireless transceiver **120**, described below). From this velocity, the processor can derive a blood pressure measurement or blood pressure estimate. The processor can output the blood pressure measurement for display. The processor can also use the blood pressure measurement to determine whether to trigger the blood pressure cuff **112**.

**[0060]** In another embodiment, the acoustic sensor **104** placed on the upper chest can be advantageously combined with an ECG electrode (such as in structure **208** of FIG. 2B), thereby providing dual benefit of two signals generated from a single mechanical assembly. The timing relationship from fiducial markers from the ECG signal, related cardiac acoustic signal and the resulting peripheral pulse from the finger pulse oximeters produces a transit time that correlates to the cardiovascular performance such as blood pressure, vascular tone, vascular volume and cardiac mechanical function. Pulse wave transit time or PWTT in currently available systems depends on ECG as the sole reference point, but such systems may not be able to isolate the transit time variables associated to cardiac functions, such as the pre-ejection period (PEP). In certain embodiments, the addition of the cardiac acoustical signal allows isolation of the cardiac functions and provides additional cardiac performance metrics. Timing calculations can be performed by the processor in the wireless transceiver **120** or a in distributed processor found in an on-body structure (e.g., such as any of the devices herein or below: **112**, **210**, **230**, **402**, **806**).

**[0061]** In certain embodiments, the wireless patient monitoring system **100** uses some or all of the velocity-based blood pressure measurement techniques described in U.S. Pat. No. 5,590,649, filed Apr. 15, 1994, titled "Apparatus and Method for Measuring an Induced Perturbation to Determine Blood Pressure," or in U.S. Pat. No. 5,785,659, filed Jan. 17, 1996, titled "Automatically Activated Blood Pressure Measurement Device," the disclosures of which are hereby incorporated by reference in their entirety. An example display related to such blood pressure calculations is described below with respect to FIG. 7.

**[0062]** The wireless transceiver **116** can transmit data using any of a variety of wireless technologies, such as Wi-Fi (802.11x), Bluetooth (802.15.2), Zigbee (802.15.4), cellular telephony, infrared, RFID, satellite transmission, proprietary protocols, combinations of the same, and the like. The wireless transceiver **116** can perform solely telemetry functions, such as measuring and reporting information about the patient **101**. Alternatively, the wireless transceiver **116** can be



a transceiver that also receives data and/or instructions, as will be described in further detail below.

**[0063]** The wireless receiver **120** receives information from and/or sends information to the wireless transceiver via an antenna **122**. In certain embodiments, the wireless receiver **120** is a patient monitor. As such, the wireless receiver **120** can include one or more processors that process sensor signals received from the wireless transceiver **116** corresponding to the sensors **102a**, **102b**, **104**, and/or **106** in order to derive any of the physiological parameters described above. The wireless transceiver **120** can also display any of these parameters, including trends, waveforms, related alarms, and the like. The wireless receiver **120** can further include a computer-readable storage medium, such as a physical storage device, for storing the physiological data. The wireless transceiver **120** can also include a network interface for communicating the physiological data to one or more hosts over a network, such as to a nurse's station computer in a hospital network.

**[0064]** Moreover, in certain embodiments, the wireless transceiver **116** can send raw data for processing to a central nurse's station computer, to a clinician device, and/or to a bedside device (e.g., the receiver **116**). The wireless transceiver **116** can also send raw data to a central nurse's station computer, clinician device, and/or to a bedside device for calculation, which retransmits calculated measurements back to the blood pressure device **110** (or to the bedside device). The wireless transceiver **116** can also calculate measurements from the raw data and send the measurements to a central nurse's station computer, to a pager or other clinician device, or to a bedside device (e.g., the receiver **116**). Many other configurations of data transmission are possible.

**[0065]** In addition to deriving any of the parameters mentioned above from the data obtained from the sensors **102a**, **102b**, **104**, and/or **106**, the wireless transceiver **120** can also determine various measures of data confidence, such as the data confidence indicators described in U.S. Pat. No. 7,024, 233 entitled "Pulse oximetry data confidence indicator," the disclosure of which is hereby incorporated by reference in its entirety. The wireless transceiver **120** can also determine a perfusion index, such as the perfusion index described in U.S. Pat. No. 7,292,883 entitled "Physiological assessment system," the disclosure of which is hereby incorporated by reference in its entirety. Moreover, the wireless transceiver **120** can determine a plethysmograph variability index (PVI), such as the PVI described in U.S. Publication No. 2008/0188760 entitled "Plethysmograph variability processor," the disclosure of which is hereby incorporated by reference in its entirety.

**[0066]** In addition, the wireless transceiver **120** can send data and instructions to the wireless transceiver **116** in some embodiments. For instance, the wireless transceiver **120** can intelligently determine when to inflate the cuff **112** and can send inflation signals to the transceiver **116**. Similarly, the wireless transceiver **120** can remotely control any other sensors that can be attached to the transceiver **116** or the cuff **112**. The transceiver **120** can send software or firmware updates to the transceiver **116**. Moreover, the transceiver **120** (or the transceiver **116**) can adjust the amount of signal data transmitted by the transceiver **116** based at least in part on the acuity of the patient, using, for example, any of the techniques described in U.S. Patent Publication No. 2009/0119330, filed Jan. 7, 2009, titled "Systems and Methods for Storing, Ana-

lyzing, and Retrieving Medical Data," the disclosure of which is hereby incorporated by reference in its entirety.

**[0067]** In alternative embodiments, the wireless transceiver **116** can perform some or all of the patient monitor functions described above, instead of or in addition to the monitoring functions described above with respect to the wireless transceiver **120**. In some cases, the wireless transceiver **116** might also include a display that outputs data reflecting any of the parameters described above (see, e.g., FIG. 5). Thus, the wireless transceiver **116** can either send raw signal data to be processed by the wireless transceiver **120**, can send processed signal data to be displayed and/or passed on by the wireless transceiver **120**, or can perform some combination of the above. Moreover, in some implementations, the wireless transceiver **116** can perform at least some front-end processing of the data, such as bandpass filtering, analog-to-digital conversion, and/or signal conditioning, prior to sending the data to the transceiver **120**. An alternative embodiment may include at least some front end processing embedded in any of the sensors described herein (such as sensors **102**, **104**, **204**, **202**, **208**, **412**, **804**, **840**, **808**) or cable hub **806** (see FIG. 8).

**[0068]** In certain embodiments, the cuff **112** is a reusable, disposable, or resposable device. Similarly, any of the sensors **102**, **104a** or cables **105**, **107** can be disposable or resposable. Resposable devices can include devices that are partially disposable and partially reusable. Thus, for example, the acoustic sensor **104a** can include reusable electronics but a disposable contact surface (such as an adhesive) where the sensor **104a** comes into contact with the patient's skin. Generally, any of the sensors, cuffs, and cables described herein can be reusable, disposable, or resposable.

**[0069]** The cuff **112** can also have its own power (e.g., via batteries) either as extra power or as a sole source of power for the transceiver **116**. The batteries can be disposable or reusable. In some embodiments, the cuff **112** can include one or more photovoltaic solar cells or other power sources. Likewise, batteries, solar sources, or other power sources can be provided for either of the sensors **102**, **104a**.

**[0070]** Referring to FIG. 1B, another embodiment of the system **100B** is shown. In the system **100B**, the blood pressure device **110b** can communicate wirelessly with the acoustic sensor **104a** and with the optical sensor **102**. For instance, wireless transceivers (not shown) can be provided in one or both of the sensors **102**, **104a**, using any of the wireless technologies described above. The wireless transceivers can transmit data using any of a variety of wireless technologies, such as Wi-Fi (802.11x), Bluetooth (802.15.2), Zigbee (802.15.4), cellular telephony, infrared, RFID, satellite transmission, proprietary protocols, combinations of the same, and the like. The wireless transceivers can transmit data, raw signals, processed signals, conditioned signals, or the like to the blood pressure device **110b**. The blood pressure device **110b** can transmit these signals on to the wireless transceiver **120**. In addition, in some embodiments, the blood pressure device **110b** can also process the signals received from the sensors **102**, **104a** prior to transmitting the signals to the wireless transceiver **120**. The sensors **102**, **104a** can also transmit data, raw signals, processed signals, conditioned signals, or the like directly to the wireless transceiver **120** or patient monitor. In one embodiment, the system **100B** shown can be considered to be a body LAN, piconet, or other individual network.

**[0071]** FIGS. 1C and 1D illustrate another embodiment in which a wireless monitor **150** is secured to the arm of the patient. The wireless monitor **150** is a fully functional stand-

alone monitor capable of various physiological measurements. The wireless monitor is small and light enough to comfortably be secured to and carried around on the arm of a patient. In the embodiment shown in FIG. 1C, the wireless monitor **150** connects to an acoustic respiration sensor **104A** on a first side of patient monitor **150** and an oximeter sensor **102** on a second side of patient monitor **150**. This configuration of connected sensors to opposite sides of the monitor prevents cable clutter and entanglements. The wireless monitor **150** includes a screen **154**. The wireless monitor **150** couples to and is held to the arm of the patient by arm band **152**. In FIG. 1C, the arm band is not an inflatable blood pressure cuff, however, as described with respect to the other figures, the arm band **152** can incorporate a blood pressure cuff for blood pressure readings.

[0072] The wireless monitor **150** can transmit data to a bedside monitor using any of a variety of wireless technologies, such as Wi-Fi (802.11x), Bluetooth (802.15.2), Zigbee (802.15.4), cellular telephony, infrared, RFID, satellite transmission, proprietary protocols, combinations of the same, and the like.

[0073] In an embodiment shown in FIG. 1D, the monitor **150** can be docked to a docking station **163**. The docking station **163** includes a bedside monitor **164** and docking station adapter **160**. Docking station adapter **160** adapts an otherwise incompatible docking port of bedside monitor **164** so that patient monitor **150** can dock. The docking station adapter **162** includes a port **162** for docking with the patient monitor **150**. When the patient monitor **150** is physically docked in the docking station adapter **160**, the patient monitor **150** can communicate with the bedside monitor **164** over a wired connection.

[0074] Also shown in FIG. 1D is handheld patient monitor **166**. Handheld monitor **166** is configured to dock directly to bedside monitor **164** without the need for a docking station adapter **162**. When the handheld monitor **166** is physically docked in the bedside monitor **164**, the handheld monitor **166** can communicate with the bedside monitor **164** over a wired connection.

[0075] FIG. 1E illustrates details of an embodiment of the wireless monitoring system **100A** in a schematic form. Although other types of sensors can be used, the wireless monitoring system **100A** is drawn in connection with the acoustic sensor **104a** and the optical sensor **102**. The system **100A** sends signals from the acoustic sensor **104a** and the optical sensor **102** to the sensor interface **170** and passes the signals to the DSP **172** for processing into representations of physiological parameters. In some embodiments, the DSP also communicates with a memory or information element, such as a resistor or capacitor, located on one of the sensors, such memory typically contains information related to the properties of the sensor that may be useful in processing the signals, such as, for example, emitter energy wavelengths.

[0076] In some embodiments, the physiological parameters are passed to an instrument manager **174**, which may further process the parameters for display. The instrument manager **174** may include a memory buffer **176** to maintain this data for processing throughout a period of time. Memory buffer **176** may include RAM, Flash or other solid state memory, magnetic or optical disk-based memories, combinations of the same or the like.

[0077] The wireless transceiver **120** is capable of wirelessly receiving the physiological data and/or parameters from DSP **172** or instrument manager **174**. The bedside monitor **916** can

include one or more displays **178**, control buttons, a speaker for audio messages, and/or a wireless signal broadcaster. The wireless transceiver **120** can also include a processor **180** to further process the data and/or parameters for display.

[0078] FIGS. 2A and 2B illustrate additional embodiments of patient monitoring systems **200A** and **200B**, respectively. In particular, FIG. 2A illustrates a wireless patient monitoring system **200A**, while FIG. 2B illustrates a standalone patient monitoring system **200B**.

[0079] Referring specifically to FIG. 2A, a blood pressure device **210a** is connected to a patient **201**. The blood pressure device **210a** includes a wireless transceiver **216a**, which can transmit sensor data obtained from the patient **201** to a wireless receiver at **220** via antenna **218**. The wireless transceiver **216a** can transmit data using any of a variety of wireless technologies, such as Wi-Fi (802.11x), Bluetooth (802.15.2), Zigbee (802.15.4), cellular telephony, infrared, RFID, satellite transmission, proprietary protocols, combinations of the same, and the like.

[0080] In the depicted embodiment, the blood pressure device **210a** includes an inflatable cuff **212a**, which can include any of the features of the cuff **112** described above. Additionally, the cuff **212a** includes a pocket **214**, which holds the wireless transceiver **216a** (shown by dashed lines). The wireless transceiver **216a** can be electrically connected to the cuff **212a** via a connector (see, e.g., FIG. 5) in some embodiments. As will be described elsewhere herein, the form of attachment of the wireless transceiver **216a** to the cuff **212a** is not restricted to a pocket connection mechanism and can vary in other implementations.

[0081] The wireless transceiver **216a** is also coupled to various sensors in FIGS. 2A, including an acoustic sensor **204a** and/or an optical ear sensor **202a**. The acoustic sensor **204a** can have any of the features of the acoustic sensor **104** described above. The ear clip sensor **202a** can be an optical sensor that obtains physiological information regarding one or more blood parameters of the patient **201**. These parameters can include any of the blood-related parameters described above with respect to the optical sensor **102**. In one embodiment, the ear clip sensor **202a** is an LNOP TC-I ear reusable sensor available from Masimo® Corporation of Irvine, Calif. In some embodiments, the ear clip sensor **202a** is a concha ear sensor (see FIGS. 4A and 4B).

[0082] Advantageously, in the depicted embodiment, the sensors **202a**, **204a** are coupled to the wireless transceiver **216a** via a single cable **205**. The cable **205** is shown having two sections, a cable **205a** and a cable **205b**. For example, the wireless transceiver **216a** is coupled to an acoustic sensor **204a** via the cable **205b**. In turn, the acoustic sensor **204a** is coupled to the optical ear sensor **202a** via the cable **205a**. Advantageously, because the sensors **202a**, **204a** are attached to the wireless transceiver **216** in the cuff **212** in the depicted embodiment, the cable **205** is relatively short and can thereby increase the patient's **201** freedom of movement. Moreover, because a single cable **205** is used to connect two or more different types of sensors, such as sensors **202a**, **204a**, the patient's mobility and comfort can be further enhanced.

[0083] In some embodiments, the cable **205** is a shared cable **205** that is shared by the optical ear sensor **202a** and the acoustic sensor **204a**. The shared cable **205** can share power and ground lines for each of the sensors **202a**, **204a**. Signal lines in the cable **205** can convey signals from the sensors **202a**, **204a** to the wireless transceiver **216** and/or instructions from the wireless transceiver **216** to the sensors **202a**, **204a**.

The signal lines can be separate within the cable **205** for the different sensors **202a**, **204a**. Alternatively, the signal lines can be shared as well, forming an electrical bus.

[0084] The two cables **205a**, **205a** can be part of a single cable or can be separate cables **205a**, **205b**. As a single cable **205**, in one embodiment, the cable **205a**, **205b** can connect to the acoustic sensor **204a** via a single connector. As separate cables, in one embodiment, the cable **205b** can be connected to a first port on the acoustic sensor **204a** and the cable **205a** can be coupled to a second port on the acoustic sensor **204a**.

[0085] FIG. 2B further illustrates an embodiment of the cable **205** in the context of a standalone patient monitoring system **200B**. In the standalone patient monitoring system **200B**, a blood pressure device **210b** is provided that includes a patient monitor **216b** disposed on a cuff **212b**. The patient monitor **216b** includes a display **219** for outputting physiological parameter measurements, trends, waveforms, patient data, and optionally other data for presentation to a clinician. The display **219** can be an LCD display, for example, with a touch screen or the like. The patient monitor **216b** can act as a standalone device, not needing to communicate with other devices to process and measure physiological parameters. In some embodiments, the patient monitor **216b** can also include any of the wireless functionality described above. For example, the patient monitor **216b** can transmit data using any of a variety of wireless technologies, such as Wi-Fi (802.11x), Bluetooth (802.15.2), Zigbee (802.15.4), cellular telephony, infrared, RFID, satellite transmission, proprietary protocols, combinations of the same, and the like.

[0086] The patient monitor **216b** can be integrated into the cuff **212b** or can be detachable from the cuff **212b**. In one embodiment, the patient monitor **216b** can be a readily available mobile computing device with a patient monitoring software application. For example, the patient monitor **216b** can be a smart phone, personal digital assistant (PDA), or other wireless device. The patient monitoring software application on the device can perform any of a variety of functions, such as calculating physiological parameters, displaying physiological data, documenting physiological data, and/or wirelessly transmitting physiological data (including measurements or uncalculated raw sensor data) via email, text message (e.g., SMS or MMS), or some other communication medium. Moreover, any of the wireless transceivers or patient monitors described herein can be substituted with such a mobile computing device.

[0087] In the depicted embodiment, the patient monitor **216b** is connected to three different types of sensors. An optical sensor **202b**, coupled to a patient's **201** finger, is connected to the patient monitor **216b** via a cable **207**. In addition, an acoustic sensor **204b** and an electrocardiograph (ECG) sensor **206** are attached to the patient monitor **206b** via the cable **205**. The optical sensor **202b** can perform any of the optical sensor functions described above. Likewise, the acoustic sensor **204b** can perform any of the acoustic sensor functions described above. The ECG sensor **206** can be used to monitor electrical activity of the patient's **201** heart.

[0088] Advantageously, in the depicted embodiment, the ECG sensor **206** is a bundle sensor that includes one or more ECG leads **208** in a single package. For example, the ECG sensor **206** can include one, two, or three or more leads. One or more of the leads **208** can be an active lead or leads, while another lead **208** can be a reference lead. Other configurations are possible with additional leads within the same package or at different points on the patient's body. Using a bundle ECG

sensor **206** can advantageously enable a single cable connection via the cable **205** to the cuff **212b**. Similarly, an acoustical sensor can be included in the ECG sensor **206** to advantageously reduce the overall complexity of the on-body assembly.

[0089] The cable **205a** in FIG. 2B can connect two sensors to the cuff **212b**, namely the ECG sensor **206** and the acoustic sensor **204b**. Although not shown, the cable **205a** can further connect an optical ear sensor to the acoustic sensor **204b** in some embodiments, optionally replacing the finger optical sensor **202b**. The cable **205a** shown in FIG. 2B can have all the features described above with respect to cable **205a** of FIG. 2A.

[0090] Although not shown, in some embodiments, any of the sensors, cuffs, wireless sensors, or patient monitors described herein can include one or more accelerometers or other motion measurement devices (such as gyroscopes). For example, in FIG. 2B, one or more of the acoustic sensor **204b**, the ECG sensor **206**, the cuff **212b**, the patient monitor **216b**, and/or the optical sensor **202b** can include one or more motion measurement devices. A motion measurement device can be used by a processor (such as in the patient monitor **216b** or other device) to determine motion and/or position of a patient. For example, a motion measurement device can be used to determine whether a patient is sitting up, lying down, walking, or the like.

[0091] Movement and/or position data obtained from a motion measurement device can be used to adjust a parameter calculation algorithm to compensate for the patient's motion. For example, a parameter measurement algorithm that compensates for motion can more aggressively compensate for motion in response to high degree of measured movement. When less motion is detected, the algorithm can compensate less aggressively. Movement and/or position data can also be used as a contributing factor to adjusting parameter measurements. Blood pressure, for instance, can change during patient motion due to changes in blood flow. If the patient is detected to be moving, the patient's calculated blood pressure (or other parameter) can therefore be adjusted differently than when the patient is detected to be sitting.

[0092] A database can be assembled that includes movement and parameter data (raw or measured parameters) for one or more patients over time. The database can be analyzed by a processor to detect trends that can be used to perform parameter calculation adjustments based on motion or position. Many other variations and uses of the motion and/or position data are possible.

[0093] Although the patient monitoring systems described herein, including the systems **100A**, **100B**, **200A**, and **200B** have been described in the context of blood pressure cuffs, blood pressure need not be measured in some embodiments. For example, the cuff can be a holder for the patient monitoring devices and/or wireless transceivers and not include any blood pressure measuring functionality. Further, the patient monitoring devices and/or wireless transceivers shown need not be coupled to the patient via a cuff, but can be coupled to the patient at any other location, including not at all. For example, the devices can be coupled to the patient's belt (see FIGS. 3A and 3B), can be carried by the patient (e.g., via a shoulder strap or handle), or can be placed on the patient's bed next to the patient, among other possible locations.

[0094] Additionally, various features shown in FIGS. 2A and 2B can be changed or omitted. For instance, the wireless transceiver **216** can be attached to the cuff **212** without the use

of the pocket **214**. For example, the wireless transceiver can be sewn, glued, buttoned or otherwise attached to the cuff using any various known attachment mechanisms. Or, the wireless transceiver **216** can be directly coupled to the patient (e.g., via an armband) and the cuff **212** can be omitted entirely. Instead of a cuff, the wireless transceiver **216** can be coupled to a non-occlusive blood pressure device. Many other configurations are possible.

[0095] FIGS. 3A and 3B illustrate further embodiments of a patient monitoring system **300A**, **300B** having a single cable connecting multiple sensors. FIG. 3A depicts a tethered patient monitoring system **300A**, while FIG. 3B depicts a wireless patient monitoring system **300B**. The patient monitoring systems **300A**, **300B** illustrate example embodiments where a single cable **305** can be used to connect multiple sensors, without using a blood pressure cuff.

[0096] Referring to FIG. 3A, the acoustic and ECG sensors **204b**, **206** of FIG. 2 are again shown coupled to the patient **201**. As above, these sensors **204b**, **206** are coupled together via a cable **205**. However, the cable **250** is coupled to a junction device **230a** instead of to a blood pressure cuff. In addition, the optical sensor **202b** is coupled to the patient **201** and to the junction device **230a** via a cable **207**. The junction device **230a** can anchor the cable **205b** to the patient **201** (such as via the patient's belt) and pass through any signals received from the sensors **202b**, **204b**, **206** to a patient monitor **240** via a single cable **232**.

[0097] In some embodiments, however, the junction device **230a** can include at least some front-end signal processing circuitry. In some embodiments, the junction device **230a** also includes a processor for processing physiological parameter measurements. Further, the junction device **230a** can include all the features of the patient monitor **216b** in some embodiments, such as providing a display that outputs parameters measured from data obtained by the sensors **202b**, **204b**, **206**.

[0098] In the depicted embodiment, the patient monitor **240** is connected to a medical stand **250**. The patient monitor **240** includes parameter measuring modules **242**, one of which is connected to the junction device **230a** via the cable **232**. The patient monitor **240** further includes a display **246**. The display **246** is a user-rotatable display in the depicted embodiment.

[0099] Referring to FIG. 3B, the patient monitoring system **300B** includes nearly identical features to the patient monitoring system **300A**. However, the junction device **230b** includes wireless capability, enabling the junction device **230b** to wirelessly communicate with the patient monitor **240** and/or other devices. The wireless patient monitoring system **300B** can transmit data using any of a variety of wireless technologies, such as Wi-Fi (802.11x), Bluetooth (802.15.2), Zigbee (802.15.4), cellular telephony, infrared, RFID, satellite transmission, proprietary protocols, combinations of the same, and the like.

[0100] FIGS. 4A and 4B illustrate embodiments of patient monitoring systems **400A**, **400B** that depict alternative cable connection systems **410** for connecting sensors to a patient monitor **402**. Like the cable **205** described above, these cable connection systems **410** can advantageously enhance patient mobility and comfort.

[0101] Referring to FIG. 4A, the patient monitoring system **400A** includes a patient monitor **402a** that measures physiological parameters based on signals obtained from sensors **412**, **420** coupled to a patient. These sensors include an opti-

cal ear sensor **412** and an acoustic sensor **420** in the embodiment shown. The optical ear sensor **412** can include any of the features of the optical sensors described above. Likewise, the acoustic sensor **420** can include any of the features of the acoustic sensors described above.

[0102] The optical ear sensor **412** can be shaped to conform to the cartilaginous structures of the ear, such that the cartilaginous structures can provide additional support to the sensor **412**, providing a more secure connection. This connection can be particularly beneficial for monitoring during pre-hospital and emergency use where the patient can move or be moved. In some embodiments, the optical ear sensor **412** can have any of the features described in U.S. application Ser. No. 12/658,872, filed Feb. 16, 2010, entitled "Ear Sensor," the disclosure of which is hereby incorporated by reference in its entirety.

[0103] An instrument cable **450** connects the patient monitor **402a** to the cable connection system **410**. The cable connection system **410** includes a sensor cable **440** connected to the instrument cable **250**. The sensor cable **440** is bifurcated into two cable sections **416**, **422**, which connect to the individual sensors **412**, **420** respectively. An anchor **430a** connects the sensor cable **440** and cable sections **416**, **422**. The anchor **430a** can include an adhesive for anchoring the cable connection system **410** to the patient, so as to reduce noise from cable movement or the like. Advantageously, the cable connection system **410** can reduce the number and size of cables connecting the patient to a patient monitor **402a**. The cable connection system **410** can also be used to connect with any of the other sensors, patient-worn monitors, or wireless devices described above.

[0104] FIG. 4B illustrates the patient monitoring system **400B**, which includes many of the features of the monitoring system **400A**. For example, an optical ear sensor **412** and an acoustic sensor **420** are coupled to the patient. Likewise, the cable connection system **410** is shown, including the cable sections **416**, **422** coupled to an anchor **430b**. In the depicted embodiment, the cable connection system **410** communicates wirelessly with a patient monitor **402b**. For example, the anchor **430b** can include a wireless transceiver, or a separate wireless dongle or other device (not shown) can couple to the anchor **430b**. The anchor **430b** can be connected to a blood pressure cuff, wireless transceiver, junction device, or other device in some embodiments. The wireless transceiver, wireless dongle, or other device can transmit data using any of a variety of wireless technologies, such as Wi-Fi (802.11x), Bluetooth (802.15.2), Zigbee (802.15.4), cellular telephony, infrared, RFID, satellite transmission, proprietary protocols, combinations of the same, and the like.

[0105] FIG. 5 illustrates a more detailed embodiment of a wireless transceiver **516**. The wireless transceiver **516** can have all of the features of the wireless transceiver **516** described above. For example, the wireless transceiver **516** can connect to a blood pressure cuff and to one or more physiological sensors, and the transceiver **516** can transmit sensor data to a wireless receiver. The wireless transceiver **516** can transmit data using any of a variety of wireless technologies, such as Wi-Fi (802.11x), Bluetooth (802.15.2), Zigbee (802.15.4), cellular telephony, infrared, RFID, satellite transmission, proprietary protocols, combinations of the same, and the like.

[0106] The depicted embodiment of the transceiver **516** includes a housing **530**, which includes connectors **552** for sensor cables (e.g., for optical, acoustic, ECG, and/or other

sensors) and a connector **560** for attachment to a blood pressure cuff or other patient-wearable device. The transceiver **516** further includes an antenna **518**, which although shown as an external antenna, can be internal in some implementations.

[0107] The transceiver **516** can include one or more connectors on one or more sides of the housing **530**. Providing connectors on different sides of the housing **530** allows for convenient sensor connection and prevents the sensor cables from tangling. For example, as shown in FIG. 5, the housing can include two connectors **552** on a first side of the housing **530** and an additional connector **560** on a second side of the housing **530**.

[0108] In addition, the transceiver **516** includes a display **554** that depicts values of various parameters, such as systolic and diastolic blood pressure, SpO<sub>2</sub>, and respiratory rate (RR). The display **554** can also display trends, alarms, and the like. The transceiver **516** can be implemented with the display **554** in embodiments where the transceiver **516** also acts as a patient monitor. The transceiver **516** further includes controls **556**, which can be used to manipulate settings and functions of the transceiver **516**.

[0109] FIGS. 6A through 6C illustrate embodiments of wireless patient monitoring systems **600**. These wireless patient monitoring systems can transmit data using any of a variety of wireless technologies, such as Wi-Fi (802.11x), Bluetooth (802.15.2), Zigbee (802.15.4), cellular telephony, infrared, RFID, satellite transmission, proprietary protocols, combinations of the same, and the like.

[0110] FIG. 6A illustrates a patient monitoring system **600A** that includes a wireless transceiver **616**, which can include the features of any of the transceivers **216**, **216** described above. The transceiver **616** provides a wireless signal over a wireless link **612** to a patient monitor **620**. The wireless signal can include physiological information obtained from one or more sensors, physiological information that has been front-end processed by the transceiver **616**, or the like.

[0111] The patient monitor **620** can act as the wireless receiver **220** of FIG. 2. The patient monitor **620** can process the wireless signal received from the transceiver **616** to obtain values, waveforms, and the like for one or more physiological parameters. The patient monitor **620** can perform any of the patient monitoring functions described above with respect to FIGS. 2 through 5.

[0112] In addition, the patient monitor **620** can provide at least some of the physiological information received from the transceiver **616** to a multi-patient monitoring system (MMS) **640** over a network **630**. The MMS **640** can include one or more physical computing devices, such as servers, having hardware and/or software for providing the physiological information to other devices in the network **630**. For example, the MMS **640** can use standardized protocols (such as TCP/IP) or proprietary protocols to communicate the physiological information to one or more nurses' station computers (not shown) and/or clinician devices (not shown) via the network **630**. In one embodiment, the MMS **640** can include some or all the features of the MMS described in U.S. Publication No. 2008/0188760, referred to above.

[0113] The network **630** can be a LAN or WAN, wireless LAN ("WLAN"), or other type of network used in any hospital, nursing home, patient care center, or other clinical location. In some implementations, the network **210** can interconnect devices from multiple hospitals or clinical locations,

which can be remote from one another, through the Internet, one or more Intranets, a leased line, or the like. Thus, the MMS **640** can advantageously distribute the physiological information to a variety of devices that are geographically co-located or geographically separated.

[0114] FIG. 6B illustrates another embodiment of a patient monitoring system **600B**, where the transceiver **616** transmits physiological information to a base station **624** via the wireless link **612**. In this embodiment, the transceiver **616** can perform the functions of a patient monitor, such as any of the patient monitor functions described above. The transceiver **616** can provide processed sensor signals to the base station **624**, which forwards the information on to the MMS **640** over the network **630**.

[0115] FIG. 6C illustrates yet another embodiment of a patient monitoring system **600B**, where the transceiver **616** transmits physiological information directly to the MMS **640**. The MMS **640** can include wireless receiver functionality, for example. Thus, the embodiments shown in FIGS. 6A through 6C illustrate that the transceiver **616** can communicate with a variety of different types of devices.

[0116] FIG. 7 illustrates an embodiment of a physiological parameter display **700**. The physiological parameter display **700** can be output by any of the systems described above. For instance, the physiological parameter display **700** can be output by any of the wireless receivers, transceivers, or patient monitors described above. The parameter display **700** can be output over a variety of wireless technologies, such as Wi-Fi (802.11x), Bluetooth (802.15.2), Zigbee (802.15.4), cellular telephony, infrared, RFID, satellite transmission, proprietary protocols, combinations of the same, and the like. Advantageously, in certain embodiments, the physiological parameter display **700** can display multiple parameters, including non-invasive blood pressure (NIBP) obtained using both oscillometric and non-oscillometric techniques.

[0117] The physiological parameter display **700** can display any of the physiological parameters described above, to name a few. In the depicted embodiment, the physiological parameter display **700** is shown displaying oxygen saturation **702**, heart rate **704**, and respiratory rate **706**. In addition, the physiological parameter display **700** displays blood pressure **708**, including systolic and diastolic blood pressure.

[0118] The display **700** further shows a plot **710** of continuous or substantially continuous blood pressure values measured over time. The plot **710** includes a trace **712a** for systolic pressure and a trace **712b** for diastolic pressure. The traces **712a**, **712b** can be generated using a variety of devices and techniques. For instance, the traces **712a**, **712b** can be generated using any of the velocity-based continuous blood pressure measurement techniques described above and described in further detail in U.S. Pat. Nos. 5,590,649 and 5,785,659, referred to above.

[0119] Periodically, oscillometric blood pressure measurements (sometimes referred to as Gold Standard NIBP) can be taken, using any of the cuffs described above. These measurements are shown by markers **714** on the plot **710**. By way of illustration, the markers **714** are "X's" in the depicted embodiment, but the type of marker **714** used can be different in other implementations. In certain embodiments, oscillometric blood pressure measurements are taken at predefined intervals, resulting in the measurements shown by the markers **714**.

[0120] In addition to or instead of taking these measurements at intervals, oscillometric blood pressure measure-

ments can be triggered using ICI techniques, e.g., based at least partly on an analysis of the noninvasive blood pressure measurements indicated by the traces **712a**, **712b**. Advantageously, by showing both types of noninvasive blood pressure measurements in the plot **710**, the display **700** can provide a clinician with continuous and oscillometric blood pressure information.

[0121] FIG. 8 illustrates another embodiment of a patient monitoring system **800**. The features of the patient monitoring system **800** can be combined with any of the features of the systems described above. Likewise, any of the features described above can be incorporated into the patient monitoring system **800**. Advantageously, in the depicted embodiment, the patient monitoring system **800** includes a cable hub **806** that enables one or many sensors to be selectively connected and disconnected to the cable hub **806**.

[0122] Like the patient monitoring systems described above, the monitoring system **800** includes a cuff **810** with a patient device **816** for providing physiological information to a monitor **820** or which can receive power from a power supply (**820**). The cuff **810** can be a blood pressure cuff or merely a holder for the patient device **816**. The patient device **816** can instead be a wireless transceiver having all the features of the wireless devices described above. The wireless transceiver can transmit data using any of a variety of wireless technologies, such as Wi-Fi (802.11x), Bluetooth (802.15.2), Zigbee (802.15.4), cellular telephony, infrared, RFID, satellite transmission, proprietary protocols, combinations of the same, and the like.

[0123] The patient device **816** is in coupled with an optical finger sensor **802** via cable **807**. Further, the patient device **816** is coupled with the cable hub **806** via a cable **805a**. The cable hub **806** can be selectively connected to one or more sensors. In the depicted embodiment, example sensors shown coupled to the cable hub **806** include an ECG sensor **808a** and a brain sensor **840**. The ECG sensor **808a** can be single-lead or multi-lead sensor. The brain sensor **840** can be an electroencephalography (EEG) sensor and/or an optical sensor. An example of EEG sensor that can be used as the brain sensor **840** is the SEDLine™ sensor available from Masimo® Corporation of Irvine, Calif., which can be used for depth-of-anesthesia monitoring among other uses. Optical brain sensors can perform spectrophotometric measurements using, for example, reflectance pulse oximetry. The brain sensor **840** can incorporate both an EEG/depth-of-anesthesia sensor and an optical sensor for cerebral oximetry.

[0124] The ECG sensor **808a** is coupled to an acoustic sensor **804** and one or more additional ECG leads **808b**. For illustrative purposes, four additional leads **808b** are shown, for a 5-lead ECG configuration. In some embodiments, one or two additional leads **808b** are used instead of four additional leads. In some embodiments, up to at least 12 leads **808b** can be included. Acoustic sensors can also be disposed in the ECG sensor **808a** and/or lead(s) **808b** or on other locations of the body, such as over a patient's stomach (e.g., to detect bowel sounds, thereby verifying patient's digestive health, for example, in preparation for discharge from a hospital). Further, in some embodiments, the acoustic sensor **804** can connect directly to the cable hub **806** instead of to the ECG sensor **808a**.

[0125] As mentioned above, the cable hub **806** can enable one or many sensors to be selectively connected and disconnected to the cable hub **806**. This configurability aspect of the cable hub **806** can allow different sensors to be attached or

removed from a patient based on the patient's monitoring needs, without coupling new cables to the monitor **820**. Instead, a single, light-weight cable **832** couples to the monitor **820** in certain embodiments, or wireless technology can be used to communicate with the monitor **820** (see, e.g., FIG. 1). A patient's monitoring needs can change as the patient is moved from one area of a care facility to another, such as from an operating room or intensive care unit to a general floor. The cable configuration shown, including the cable hub **806**, can allow the patient to be disconnected from a single cable to the monitor **820** and easily moved to another room, where a new monitor can be coupled to the patient. Of course, the monitor **820** may move with the patient from room to room, but the single cable connection **832** rather than several can facilitate easier patient transport.

[0126] Further, in some embodiments, the cuff **810** and/or patient device **816** need not be included, but the cable hub **806** can instead connect directly to the monitor wirelessly or via a cable. Additionally, the cable hub **806** or the patient device **816** may include electronics for front-end processing, digitizing, or signal processing for one or more sensors. Placing front-end signal conditioning and/or analog-to-digital conversion circuitry in one or more of these devices can make it possible to send continuous waveforms wirelessly and/or allow for a small, more user-friendly wire (and hence cable **832**) routing to the monitor **820**.

[0127] The cable hub **806** can also be attached to the patient via an adhesive, allowing the cable hub **806** to become a wearable component. Together, the various sensors, cables, and cable hub **806** shown can be a complete body-worn patient monitoring system. The body-worn patient monitoring system can communicate with a patient monitor **820** as shown, which can be a tablet, handheld device, a hardware module, or a traditional monitor with a large display, to name a few possible devices.

[0128] FIGS. 9A-9D illustrate another embodiment of a wireless monitoring system **900** including a wireless monitor **902** coupled to a sensor **930**. The wireless monitoring system **900** is configured to connect to one or more sensors and/or a bedside monitor. The features of the wireless monitoring system **900** can be combined with any of the features of the systems described above. Likewise, any of the features described above can be incorporated into the patient monitoring system **900**. The wireless monitor **902** includes a removable battery **904** having a data storage component. The removable battery **904** can be used to pair the wireless monitor **902** with the correct bedside monitor as described below. The battery **904** is positioned on the front side of the wireless monitor **902**, so the battery **904** can be replaced without disconnecting a wireless monitor housing from the patient. Further details of these drawings are described below.

[0129] FIG. 10 illustrates details of an embodiment of the wireless monitoring system **900** in a schematic form. Typically, the sensor **930** includes energy emitters **1016** located on one side of a patient monitoring site **1018** and one or more detectors **1020** located generally opposite. The patient monitoring site **1018** is usually a patient's finger (as pictured), toe, ear lobe, or the like. Energy emitters **1016**, such as LEDs, emit particular wavelengths of energy through the flesh of a patient at the monitoring site **1018**, which attenuates the energy. The detector(s) **1020** then detect the attenuated energy and send representative signals to the wireless monitor **902**.

[0130] The wireless monitor **902** can include a sensor interface **1024** and a digital signal processor (DSP) **1026**. The

sensor interface **1024** receives the signals from the sensor **930** detector(s) **1020** and passes the signals to the DSP **1026** for processing into representations of physiological parameters. In some embodiments, the DSP **1026** also communicates with a memory or information element, such as a resistor or capacitor, **1030** located on the sensor **930**, such memory typically contains information related to the properties of the sensor that may be useful in processing the signals, such as, for example, emitter **1016** energy wavelengths.

[**0131**] In some embodiments, the physiological parameters are passed to an instrument manager **1028**, which may further process the parameters for display by a bedside monitor **916**. The instrument manager **1028** may include a memory buffer **1034** to maintain this data for processing throughout a period of time. Memory buffer **1034** may include RAM, Flash or other solid state memory, magnetic or optical disk-based memories, combinations of the same or the like.

[**0132**] In some embodiments, the wireless monitor is able to display one or more physiological parameters. The wireless monitor **902** can include one or more displays **1036**, control buttons **1040**, one or more speakers **1038** for audio messages. Control buttons **1040** may comprise a keypad, a full keyboard, a touch screen, a track wheel, and the like.

[**0133**] The wireless monitor **902** is powered by a battery **904**. In some embodiments, the battery **904** directly or indirectly powers the sensor interface **1024**, DSP **1026**, and the instrument manager **1028**.

[**0134**] The battery **904** includes memory **932**, such memory stores wireless communication information needed for the wireless monitor **902** to wirelessly communicate with bedside monitor **916**. The battery **904** can communicate the information stored on the memory **932** to the wireless monitor **902** or bedside monitor **916**, and the memory **932** can store information received from the wireless monitor **902** or bedside monitor **916**.

[**0135**] The bedside monitor **916** wirelessly receives the physiological data and/or parameters from the wireless monitor **902** and is able to display one or more physiological parameters. The bedside monitor **916** can include one or more displays **1008**, control buttons **1010**, a speaker **1012** for audio messages, and/or a wireless signal broadcaster. Control buttons **1010** may comprise a keypad, a full keyboard, a track wheel, and the like.

[**0136**] As shown in FIG. **10**, the wireless monitor **902** can include an optional internal battery **905** capable of powering the wireless monitor **902** when the battery **904** is disconnected from the wireless monitor **902**. The internal battery **905** can include additional backup memory **933** to store information when the battery **904** is disconnected from the wireless monitor **902**. The internal battery **905** can be useful when a caregiver replaces the battery **904** with a different, fully-charged battery. While the battery **904** is disconnected from the wireless monitor **902**, the wireless monitor **902** can continue to display and communicate information.

[**0137**] In several embodiments, the wireless patient monitoring system includes one or more sensors, including, but not limited to, a sensor **930** to monitor oxygen saturation and pulse rate. These physiological parameters can be measured using a pulse oximeter. In general, the sensor **930** has light emitting diodes that transmit optical radiation of red and infrared wavelengths into a tissue site and a detector that responds to the intensity of the optical radiation after absorption (e.g. by transmission or transreflectance) by pulsatile arterial blood flowing within the tissue site. Based on this

response, a processor determines measurements for SpO<sub>2</sub>, pulse rate, and can output representative plethsmographic waveforms. Thus, “pulse oximetry” as used herein encompasses its broad ordinary meaning known to one of skill in the art, which includes at least those noninvasive procedures for measuring parameters of circulating blood through spectroscopy.

[**0138**] The wireless monitoring system **900** can include any of the sensors described herein in addition to or in alternative to the pulse oximeter. For example, the wireless monitoring system **900** can also include sensors for monitoring acoustics, sedation state, blood pressure, ECG, body temperature, and/or cardiac output. The wireless monitor may also include an accelerometer or gyroscope. The wireless patient monitoring system may include any of the above-mentioned sensors alone or in combination with each other.

[**0139**] In several embodiments, the wireless monitor **902** includes a wireless transmitter to transmit sensor data and/or a wireless receiver to receive data from another wireless transmitter or transceiver. By transmitting the sensor data wirelessly, the wireless monitor **902** can advantageously replace some or all cables that connect patients to bedside monitoring devices. Alternatively, the wireless monitor **902** calculates physiological parameters based on the sensor data and wirelessly transmits the physiological parameters and/or the sensor data itself to the bedside monitor. The physiological parameter can be numerical information, such as oxygen saturation (SpO<sub>2</sub>) or pulse rate, or a graphical depiction of the sensor data. The data processors can be positioned in the wireless monitor housing or the battery. By configuring the wireless monitor **902** to calculate the physiological parameter, less data transfer is required to transmit information from the wireless monitor to the bedside monitor. Processing the sensor data in the wireless monitor **902** also improves the quality of the signal transferred to the bedside monitor.

[**0140**] As shown in FIGS. **9B-9C**, the wireless monitor **902** includes a removable battery **904** and a base **906**. The base **906** can include processing and wireless transmission capabilities and/or share processing function with the battery **904**. Removable battery **904** includes a release mechanism **912** to release the battery **904** from the base **906**. As depicted in FIG. **9B**, the base **906** can include a battery receiving portion **914** and a notch **917** to lock the removable battery **904** in place. Wireless monitor **902** can have one or more outlets **910** to plug in the sensor **930**, such as the pulse oximeter, acoustic respiratory sensor, ECG, sedation sensor, blood pressure cuff, or any other sensor. In some embodiments, one or more outlets **910** can be positioned on one or more sides of the wireless monitor **902**. For example, the wireless monitor can include an outlet on one side for an acoustic respiratory sensor and an outlet on an opposite side for a pulse oximeter.

[**0141**] Wireless monitor **902** can include an opening **908** through which an arm band **934** can be passed to secure the wireless monitor **902** to the arm of the patient, as shown in FIG. **9A**. The arm band **934** can be reusable, disposable or resposable. Similarly, any of the sensors **930** can be disposable or resposable. Resposable devices can include devices that are partially disposable and partially reusable. Thus, for example, the acoustic sensor can include reusable electronics, but a disposable contact surface (such as an adhesive) where the sensor comes into contact with the patient's skin.

[**0142**] The sensors **930** and/or wireless monitor **902** need not be worn around the patient's arm, but can be worn at any other location, including not at all. The sensors **930** and/or



wireless monitor **902** need not be coupled to an arm band, but can be coupled to a patient's belt or a chest strap, can be carried by the patient (e.g., via a shoulder strap or handle), or can be placed on the patient's bed next to the patient, among other locations.

[0143] FIG. 9D illustrates the battery **904** docked with a bedside monitor **916**. Bedside monitor **916** has a battery charging station **922** for receiving and charging removable battery **904**. When the wireless monitor **902** is using a first battery, the battery charging station **922** can charge a second battery, so when the battery levels of the first battery are low, a second battery is readily available. Each battery is capable of powering the wireless monitor **902** for at least one nursing shift, so each nurse only has to replace the battery once either at the beginning or end of each shift.

[0144] An adaptor **918** can be integrated with the bedside monitor or separately connected to bedside monitor **916**. The bedside monitor **916** includes a release mechanism **926** to release the adaptor **918** from the bedside monitor **916**. Adaptor **918** includes docking station **920** to receive the entire wireless monitor (not shown). Locking mechanism **924** holds the wireless monitor **902** in place. Other components may be connected to the bedside monitor **916** instead of the adaptor **918**, such as a handheld patient monitor device.

[0145] In some embodiments, the adaptor **918** includes a docking station **920** to receive the entire wireless monitor **902**. The wireless monitor **902** can be placed in the docking station **920** when it is not in use to prevent the wireless monitor **902** from being lost. The bedside monitor **916** can charge the battery **904** when the wireless monitor **902** is connected to the bedside monitor **916**. In certain aspects, the bedside monitor **916** can communicate a password, unique identifier, appropriate channel information, or other wireless communication information to the wireless monitor **902**, and vice versa, when the wireless monitor **902** is connected to the bedside monitor **916**.

[0146] As shown in FIG. 9D, the bedside monitor **916** is capable of simultaneously receiving a first battery and a wireless monitor **902** having a second battery. The bedside monitor **916** is configured to charge and sync both the first and second batteries. When the first battery and/or the wireless monitor **902** and second battery are physically docked in the bedside monitor **916**, the first and/or second battery can communicate with the bedside monitor **916** over a wired connection.

[0147] The bedside monitor **916** can include a display screen **928** for displaying the physiological parameters, including trends, waveforms, related alarms, and the like. In certain aspects, the bedside monitor **916** can display the appropriate channel for communication and/or whether the wireless monitor **902** is properly communicating with the bedside monitor **916**.

[0148] The bedside monitor **916** can include a computer-readable storage medium, such as a physical storage device, for storing the physiological data. In certain aspects, the bedside monitor can include a network interface for communicating the physiological data to one or more hosts over a network, such as to a nurse's station computer in a hospital network.

[0149] The wireless monitor **902** can transmit data to the bedside monitor **916** using any of a variety of wireless technologies, such as Wi-Fi (802.11x), Bluetooth, ZigBee, cellular telephony, infrared, RFID, satellite transmission, proprietary protocols, combinations of the same, and the like. The

wireless monitor **902** can perform solely telemetry functions, such as measuring and reporting information about the patient.

[0150] The wireless monitor **902**, or any of the wireless monitor embodiments discussed herein, can be configured to utilize different wireless technologies. In certain scenarios, it may be desirable to transmit data over Bluetooth or ZigBee, for example, when the distance between the wireless monitor **902** and the bedside monitor **916** is within range of Bluetooth or ZigBee communication. Transmitting data using Bluetooth or ZigBee is advantageous because these technologies require less power than other wireless technologies. In other scenarios, it may be desirable to transmit data using Wi-Fi or cellular telephony, for example, when the wireless monitor is out of range of communication for Bluetooth or ZigBee. A wireless monitor **902** may be able to transmit data over a greater distance using Wi-Fi or cellular telephony than other wireless technologies. In still other scenarios, it may be desirable to transmit data using a first wireless technology and automatically switch to a second wireless technology in order to maximize data transfer and energy efficiency.

[0151] In some embodiments, the wireless monitor **902** automatically transmits data over Bluetooth or ZigBee when the wireless monitor **902** is within a pre-determined distance from bedside monitor **916**. The wireless transmitter **902** automatically transmits data over Wi-Fi or cellular telephony when the wireless monitor **902** is beyond a pre-determined distance away from the bedside monitor **916**. In certain embodiments, the wireless monitor **902** can automatically convert from Bluetooth or ZigBee to Wi-Fi or cellular telephony, and vice versa, depending on the distance between the wireless monitor **902** and bedside monitor **916**.

[0152] In some embodiments, the wireless monitor **902** automatically transmits data over Bluetooth or ZigBee when the Bluetooth or ZigBee signal strength is sufficiently strong or when there is interference with Wi-Fi or cellular telephony. The wireless monitor **902** automatically transmits data over Wi-Fi or cellular telephony when the Bluetooth or ZigBee signal strength is not sufficiently strong. In certain embodiments, the wireless monitor **902** can automatically convert from Bluetooth or ZigBee to Wi-Fi or cellular telephony, and vice versa, depending on signal strength.

[0153] Existing wireless bedside monitoring devices can be difficult to use because it can be difficult to pair the wireless device with the correct bedside monitor, making it difficult to switch wireless devices or switch bedside monitors. Some wireless systems require the care provider to program the wireless device to communicate with the correct patient monitor. Other wireless systems require a separate token or encryption key and several steps to pair the wireless device with the correct bedside monitors. Some systems require the token to be connected to the bedside monitor, then connected to the wireless device, and then reconnected to the bedside monitor.

[0154] In certain scenarios, it may be desirable to share wireless communication information between a wireless monitor **902** and a bedside monitor **916** without a separate token or encryption key. In some embodiments, the removable battery **904** includes a data storage component, such as memory **932**, capable of storing wireless communication information. The battery **904** is configured to connect to both the wireless monitor **902** and the bedside monitor **916**. Combining the battery **904** with a data storage component can decrease the total number of components and decrease the



number of steps it takes to transfer wireless communication information between the wireless monitor **902** and bedside monitor **916** because a separate token or encryption key is not needed. This method of data transfer also eliminates user input errors arising from users having to program the wireless monitor **902** and/or bedside monitor **916** and allows for easy transfer of wireless communication information between the wireless monitor **902** and bedside monitor **916**.

[0155] For security purposes, it may be desirable to use security tokens to ensure that the correct bedside monitor **916** receives the correct wirelessly transmitted data. Security tokens prevent the bedside monitor **916** from accessing the transmitted data unless wireless monitor **902** and bedside monitor **916** share the same password. The password may be a word, passphrase, or an array of randomly chosen bytes.

[0156] When the battery **904** is connected to the bedside monitor **916**, the bedside monitor **916** can communicate a password to the battery **904**, and the battery **904** stores the password on its data storage component. The battery **904** can communicate a password for the wireless monitor **902** to the bedside monitor **916**. The battery **904** can then be disconnected from the bedside monitor **916** and connected to the wireless monitor **902**. When the battery **904** is connected to the wireless monitor **902**, the battery **904** can communicate the password to the wireless monitor **902**. The wireless monitor **902** can then communicate wirelessly with the correct bedside monitor **916**.

[0157] In some scenarios, it may be desirable to pair the wireless monitor **902** with the bedside monitor **916** to avoid interference from other wireless devices. When the removable battery **904** is connected to the bedside monitor **916**, the bedside monitor **916** communicates a unique identifier to the battery **904**, and the battery **904** stores the unique identifier on its data storage component. The battery **904** can communicate a unique identifier for the wireless monitor **902** to the bedside monitor **916**. The battery **904** can then be disconnected from the bedside monitor **916** and connected to the wireless monitor **902**. When the battery **904** is connected to the wireless monitor **902**, the battery **904** can communicate the unique identifier to the wireless monitor **902**, so that the wireless monitor **902** can transmit data to the correct bedside monitor **916**.

[0158] In some scenarios, it is desirable for the wireless monitor **902** to be configured to transmit data over the correct channel. Channels provide a mechanism to avoid sources of wireless interference. When the removable battery **904** is connected to the bedside monitor **916**, the bedside monitor **916** communicates the appropriate channel to the battery **904**, and the battery **904** stores the channel information on its data storage component. If necessary, the battery **904** can communicate a wireless monitor channel to the bedside monitor **916**. The battery **904** is then disconnected from the bedside monitor **916** and connected to the wireless monitor **902**. When the battery **904** is connected to the wireless monitor **902**, the battery **904** can communicate the appropriate channel information to the wireless monitor **902**, thereby ensuring the wireless monitor **902** transmits data over the correct channel.

[0159] The battery **904**, or any battery embodiment described herein, can receive or communicate any one or combination of passwords, tokens, or channels as described above. The wireless communication information can include information to communicate over each protocol the wireless monitor **902** is configured to communicate over. For example, if the wireless monitor **902** is capable of communicating over

Wi-Fi and Bluetooth, then the battery **904** is capable of receiving wireless communication information to communicate over both Wi-Fi and Bluetooth.

[0160] In some scenarios, the method in any of the above mentioned methodologies may be reversed. For example, in some embodiments, the battery **904** is initially connected to the wireless monitor **902**. When the battery **904** is connected to the wireless monitor **902**, the wireless monitor **902** can communicate wireless communication information identifying the wireless monitor **902** to the battery **904**, and the battery **904** can store the information on its data storage component. The battery can communicate wireless communication information identifying the bedside monitor **916** to the wireless monitor **902**. After the battery **904** is disconnected from the wireless monitor **902**, the battery **904** is connected to the bedside monitor **916**. The battery **904** can then communicate wireless communication information stored on the data storage component to the bedside monitor **916**, such as a password, unique identifier, channel, or other data information.

[0161] FIG. 11 illustrates an embodiment for using the wireless patient monitoring system that can be used in connection with any wireless patient monitoring system described herein. The operator connects the removable battery to the bedside monitor (block **1102**) and the bedside monitor and the battery communicate wireless communication information with each other (block **1104**). The operator then disconnects the battery from the bedside monitor (block **1106**) and connects the battery to the wireless monitor (block **1108**). The battery and the wireless monitor communicate wireless communication information with each other (block **1110**). After the wireless monitor receives data from the one or more sensors (block **1112**), the wireless monitor processes the sensor data into representations of physiological parameters (block **1114**). The wireless monitor then wirelessly communicates the physiological parameters and/or the sensor data to the bedside monitor (block **1116**).

[0162] In some embodiments, the data storage component of the battery **904** stores wireless communication information related to the wireless monitor **902**. The wireless communication information can be a password, unique identifier, channel, etc. When the battery **904** is engaged with the bedside monitor **916**, the bedside monitor **916** can communicate wireless communication information to the battery **904**, and the battery **904** can communicate wireless communication information to the bedside monitor **916**. The battery **904** is then disconnected from the bedside monitor **916** and connected to the wireless monitor **902**. Since the battery **904** already communicated the wireless communication information to the bedside monitor **916**, the battery **904** provides all remaining wireless communication information to the wireless monitor. The wireless monitor reconfigures itself according to the information on the battery and no further information is required to be communicated with the bedside monitor **916**. This reduces the total number of steps necessary to pair the wireless monitor **902** with the correct bedside monitor **916**.

[0163] FIG. 12 illustrates another embodiment of the wireless patient monitor **1202**. The features of the wireless patient monitor **1202** can be combined with any of the features of the systems described above. Likewise, any of the features described above can be incorporated into the patient monitor **1202**.

[0164] As shown in FIG. 12, the wireless patient monitor **1202** can include a housing **1205** that removably engages a

battery **1204**. The monitor **1202** can include a release mechanism **1212** for releasing the battery **1204** from the housing **1206** and/or one or more outlets **1210** for engaging one or more sensors.

[0165] The wireless patient monitor **1202** can include a wireless transceiver capable of transmitting data using any of a variety of wireless technologies, such as Wi-Fi (802.11x), Bluetooth (802.15.2), Zigbee (802.15.4), cellular telephony, infrared, RFID, satellite transmission, proprietary protocols, combinations of the same, and the like.

[0166] As shown in FIG. 12, the battery **1204** can include a display screen **1240**. The display screen **1240** can indicate any number of parameters, including, but not limited to, physiological parameters, battery levels, and wireless signal strength. Positioning the display screen **1240** on the battery **1204** helps reduce the size of the housing.

[0167] The display screen **1240** can include a touch interface to permit a user to access different parameters or settings (e.g., display settings, connectivity settings, etc.). In certain aspects, the display screen **1240** can rotate depending on the orientation of the battery **1204**.

[0168] To save energy, the display screen **1240** can selectively display certain parameters depending on the location of the battery **1204**. For example, if the battery is connected to the bedside monitor or disconnected from the wireless monitor, the battery may only display battery levels. If the battery is connected to the wireless monitor, then the battery may display additional parameters other than battery levels.

[0169] The display screen **1240** can selectively display certain parameters depending on the distance between the wireless monitor **1202** and the bedside monitor **1216**. Referring to FIG. 13, if the wireless monitor **1202** is within a predetermined distance from the bedside monitor—(block **1300**), then the display screen **1240** deactivates (block **1302**). If the wireless monitor **1202** is not within a predetermined distance from the bedside monitor (block **1300**), then the display screen **1240** initializes (block **1304**). The display screen **1240** only needs to be active when the patient is not close to the bedside monitor.

[0170] The display screen **1240** can selectively display certain parameters depending on the type of wireless connection between the wireless monitor **1202** and the bedside monitor and/or hospital IT infrastructure. Referring to FIG. 14, if the wireless monitor **1202** wirelessly communicates physiological parameters and/or sensor data over Bluetooth (block **1410**), then the display screen deactivates (block **1412**). If the wireless monitor **1202** wirelessly communicates physiological parameters and/or sensor data over Wi-Fi (block **1414**), then the display screen **1240** initializes (block **1416**).

[0171] The wireless monitor **1202** can selectively transmit information over different wireless connections and display certain parameters depending on the distance between the wireless monitor **1202** and the bedside monitor. Referring to FIG. 15, if the wireless monitor **1202** is within a predetermined distance from the bedside monitor (block **1520**), then the wireless monitor **1202** wirelessly communicates physiological parameters and/or sensor data to the bedside monitor over Bluetooth (block **1522**). If the wireless monitor **1202** wirelessly communicates to the bedside monitor over Bluetooth (block **1522**), then the display screen **1240** deactivates (block **1524**). The display screen **1240** does not need to be active since the bedside monitor is nearby.

[0172] If the wireless monitor **1202** is not within a predetermined distance from the bedside monitor (block **1520**),

then the wireless monitor **1202** wirelessly communicates physiological parameters and/or sensor data to the bedside monitor over Wi-Fi (block **1526**). If the wireless monitor **1202** wirelessly communicates to the bedside monitor over Wi-Fi (block **1526**), then the display screen **1240** initializes (block **1528**). If the wireless monitor **1202** is communicating over Wi-Fi, then it is more likely that the patient is not in the patient room. In that case, it is necessary to have a secondary display screen available to monitor the patient's physiological parameters.

[0173] Although FIGS. 14 and 15 were discussed in reference to Bluetooth and Wi-Fi, the system can wirelessly communicate information over ZigBee or cellular telephony. Also, the system may convert from a first wireless technology (e.g., Bluetooth) to a second wireless technology (Wi-Fi) based on signal strength rather than distance.

[0174] The wireless monitor **1202** can help the hospital staff monitor the patient when the patient is not close to the bedside monitor. When the patient is close to the bedside monitor, the bedside monitor will notify the staff if any of the patient's physiological parameters are irregular by activating an audible alarm and/or by alerting a staff member using the hospital IT infrastructure. When the patient is more than a pre-determined distance from the bedside monitor, the wireless monitor **1202** can send the physiological parameters and/or sensor data directly over the hospital IT infrastructure, so the hospital staff can continuously monitor the patient at the nurse's station or any other location. If the patient exhibits any irregular physiological parameters, the wireless monitor **1202** can activate an audible alarm and/or alert a staff member using the hospital IT infrastructure. The wireless monitor **1202** can use triangulation to provide the location of the patient, so the staff member can quickly find the patient. By configuring the wireless monitor **1202** to process the sensor data, the wireless monitor **1202** is capable of communicating physiological parameters over the hospital IT infrastructure without the bedside monitor.

[0175] Any of the systems described herein can include a display screen and can be configured to carry out any of the methods described in FIGS. 13-15.

[0176] FIGS. 16A-F illustrate another embodiment of a wireless patient monitoring system. The features of the wireless patient monitoring system can be combined with any of the features of the systems described above. Likewise, any of the features described above can be incorporated into the wireless patient monitoring system.

[0177] FIG. 16A illustrates the wireless monitor **1602** with the battery **1604** detached from the base **1606**. The base **1606** can include processing and wireless transmission capabilities and/or share processing function with the battery **1604**. The battery **1602** removably engages an anterior surface of the base **1606**. The battery **1602** can engage the housing **1602** via a magnet, a clip, a band, a snap fit, a friction fit, or otherwise. The housing **1602** can include one or more outlets **1610** for engaging one or more sensors **1630**. As shown in FIG. 16A, the housing **1206** can include an outlet on one end of the housing and another outlet on the opposite end of the housing. Disposing outlets on opposite ends of the housing can be useful to prevent sensor cables from tangling.

[0178] The battery **1604** can include a display screen **1640** and a user input device **1644**. The user input device can activate the screen, adjust display settings, select physiological parameters to display, and/or otherwise control the display screen **1640**. As shown in FIG. 16A, the user input device

**1644** can be a touch pad. A user can tap the touch pad to select a feature and/or swipe in different directions to change selections. For example, the user can swipe right or left to change the parameters displayed on the display screen. Other functions can also be performed using the three inputs of the touch pad—left swipe, right swipe, and tap. Other user input devices **1644** can include one or more buttons, switches, or other control. In certain aspects, the display screen can be the user input device.

[0179] FIG. 16B illustrates a strap **1646** for securing the wireless monitor **1602** to the patient. The strap **1646** can include any fabric, elastic, or otherwise flexible material. In certain aspects, the strap **1646** can be waterproof. One or both ends of the strap **1646** can be tapered. One or both ends of the strap **1646** can include a covering to protect the strap ends.

[0180] The strap **1646** can be secured to the patient as an arm band, a shoulder strap, a belt, or in any other configuration. A portion of the strap **1646** can be secured to another portion of the strap **1646** using Velcro **1660**, clasps, adhesive, snap-fits, or any other connector. The strap **1646** can include a band (not shown) for securing an excess portion of the strap **1646**.

[0181] As shown in FIG. 16B, the strap **1646** can include a connector **1650** for engaging the wireless monitor **1602** and an adjustment mechanism **1648** to adjust the length of the strap **1646** and/or secure any excess strap **1646**. The connector **1650** can be an integral portion of the strap **1646** or a separately formed component secured to the strap **1646**. As shown in FIG. 16B, the connector **1650** can include an opening **1656** on opposite sides of the connector **1650** for securing either end of the strap **1646**. One or both ends of the strap **1646** can be removably secured to the connector **1650**.

[0182] In certain aspects, the connector **1650** engages the housing by being disposed between the base **1606** and the battery **1604**. At least a portion of the connector **1650** can overlay a portion of the housing. The connector **1650** can include certain features to mate with a corresponding feature of the base **1606** and/or battery **1604**. For example, the connector **1650** can include one or more recesses **1652** configured to mate with one or more protrusions **1658** on the base **1606**. As shown in FIG. 16C, the connector **1650** can include a recess **1652** on opposite ends of the connector **1650** that mate with protrusions **1658** on opposite ends of the base **1606**. The connector **1650** can be flush with the protrusions **1658** to provide a flat surface for the battery **1604**.

[0183] In other aspects, the connector **1650** can pass through an opening of the wireless monitor. For example, as shown in FIG. 12, the wireless monitor can include an opening **1208** for engaging the strap **1646**. In still other aspects, the connector **1650** can engage the wireless monitor **1602** using clips, ties, buckles, buttons, or any other connector.

[0184] The wireless monitor **1602** can include a wireless transceiver capable of transmitting data using any of a variety of wireless technologies, such as Wi-Fi (802.11x), Bluetooth (802.15.2), Zigbee (802.15.4), cellular telephony, infrared, RFID, satellite transmission, proprietary protocols, combinations of the same, and the like.

[0185] FIGS. 16D-16F illustrate a bedside monitor **1616** configured to receive the wireless monitor **1602**. The bedside monitor can include one or more input ports **1627** configured to receive cables. In certain aspects, the bedside monitor **1616** can include a port **1617** configured to receive a handheld device, such as the handheld monitor **166** shown in FIG. 1D. Further details about the handheld device can be found in U.S.

application Ser. No. 13/651,167, filed Oct. 12, 2012, entitled “Medical Monitoring Hub,” which is hereby incorporated by reference in its entirety.

[0186] The port **1617** can removably engage an adapter **1618**. For example, the adapter **1618** can include a release mechanism **1626** to release the adapter **1618** from the port **1617**. In certain aspects, the release mechanism **1626** is studed, so a user must use one or more tools to release the release mechanism **1626**.

[0187] The adapter **1618** can be configured to receive a battery **1604** and/or a wireless monitor **1602**. The adapter **1618** can include a docking adaptor door **1620** configured to receive the stand alone battery **1604** and/or a port for receiving a the wireless monitor **1602** including a battery **1604**. In certain aspects, as shown in FIG. 16F, the docking adaptor door **1620** can pivot to facilitate insertion and removal of the wireless monitor **1602**. When the battery **1604** and/or wireless monitor **1602** having a battery **1604** is physically connected to the adapter **1618**, the batteries **1606** can charge and can communicate and/or receive information from the bedside monitor **1616** over a wired connection.

[0188] FIGS. 17A-17C illustrate another embodiment of a wireless monitor **1702**. The wireless monitor **1702** can include any of the other wireless monitor features described herein. Likewise, any of the other wireless monitor embodiments discussed herein can include any of the features of the wireless monitor **1702**.

[0189] The wireless monitor **1702** can include a battery **1704** removably engaged with a base **1706**. The base **1706** can include processing and wireless transmission capabilities and/or share processing function with the battery **1704**. FIG. 17A illustrates an exploded view of the wireless monitor **1702**. The housing can include one or more outlets **1710** configured to connect to one or more sensors (not shown). The battery can include a display **1740** capable of displaying physiological parameters, connectivity information, and/or other content. The battery **1704** can include a touch pad **1744** or other user input device. The touch pad **1744** can permit the user to swipe right, swipe left, or tap to control the wireless monitor **1702**. The battery **1704** can include an additional user input device (e.g., button **1745**) that can activate/deactivate the wireless monitor or provide other functionality.

[0190] The battery can include one or more protrusions, ribs, struts, detents, or the like configured to be received in corresponding grooves, notches, recesses, openings, or the like in the base **1706**. FIG. 17B illustrates views of an inner portion of the battery **1704** and an inner portion of the housing. The battery **1704** can include two protrusions **1741** on each end of the battery **1704** and along an inner portion of the battery **1704**. One or more of the protrusions **1741** can be a different size or shape from the other protrusions **1741**. The base **1706** can include two grooves **1743** on each end of the base **1706** and along an inner portion of the base **1706**. Each of the grooves **1743** can be configured to receive one of the protrusions **1741**. One or more of the grooves **1743** can be a different size or shape from the other grooves **1743**. FIG. 17C illustrates a perspective view of the battery **1704** engaged with the base **1706**.

[0191] The wireless monitor **1702** can include a wireless transceiver capable of transmitting data using any of a variety of wireless technologies, such as Wi-Fi (802.11x), Bluetooth (802.15.2), Zigbee (802.15.4), cellular telephony, infrared, RFID, satellite transmission, proprietary protocols, combinations of the same, and the like.

**[0192]** As described above, any of the wireless monitoring systems described herein can include an accelerometer or gyroscope that can be used to detect one or more of patient orientation, patient movement, whether the patient is falling, or the like. In certain aspects, the wireless monitoring system can include an alert system to alert the care giver that the patient is falling, getting out of bed, or otherwise moving in a prohibited manner. The alert can be an audible and/or visual alarm on the monitoring system or transmitted to a caregiver (e.g., nurses' station, pager, home computer, or otherwise).

**[0193]** In certain aspects, the information received by the accelerometer or gyroscope can be used to create an indication and/or animation of patient movement. This animation can be displayed on the patient monitor or transmitted to a nurses station or other off-site location to enable the care giver to monitor the patient. The animation can be viewed real time and/or be recorded for playback. For example, if an alarm alerts the care giver that the patient has fallen out of bed, the care giver can be presented playbacks of one or more of the patient's movement during that period of time.

**[0194]** FIGS. 18A-18C illustrate examples of the animation that can be displayed on a bedside monitor, nurses' station monitor, or other display screen. FIG. 18A illustrates a patient lying in bed 1801, and the patient rolling over 1803. FIG. 18B illustrates the patient lying in bed 1805, and the patient sitting up 1807. FIG. 18C illustrates the patient lying in bed 1809, and the patient getting out of bed 1811. Other patient movements can also be illustrated, such as a patient falling, walking, or otherwise. Depending on the embodiment, certain acts, events, or functions of any of the methods described herein can be performed in a different sequence, can be added, merged, or left out altogether (e.g., not all described acts or events are necessary for the practice of the method). Moreover, in certain embodiments, acts or events can be performed concurrently, e.g., through multi-threaded processing, interrupt processing, or multiple processors, rather than sequentially.

**[0195]** The various illustrative logical blocks, modules, circuits, and algorithm steps described in connection with the embodiments disclosed herein can be implemented as electronic hardware, computer software, or combinations of both. To clearly illustrate this interchangeability of hardware and software, various illustrative components, blocks, modules, circuits, and steps have been described above generally in terms of their functionality. Whether such functionality is implemented as hardware or software depends upon the particular application and design constraints imposed on the overall system. The described functionality can be implemented in varying ways for each particular application, but such implementation decisions should not be interpreted as causing a departure from the scope of the disclosure.

**[0196]** The various illustrative logical blocks, modules, and circuits described in connection with the embodiments disclosed herein can be implemented or performed with a general purpose processor, a digital signal processor (DSP), an application specific integrated circuit (ASIC), a field programmable gate array (FPGA) or other programmable logic device, discrete gate or transistor logic, discrete hardware components, or any combination thereof designed to perform the functions described herein. A general purpose processor can be a microprocessor, but in the alternative, the processor can be any conventional processor, controller, microcontroller, or state machine. A processor can also be implemented as a combination of computing devices, e.g., a combination of a

DSP and a microprocessor, a plurality of microprocessors, one or more microprocessors in conjunction with a DSP core, or any other such configuration.

**[0197]** The steps of a method or algorithm described in connection with the embodiments disclosed herein can be embodied directly in hardware, in a software module executed by a processor, or in a combination of the two. A software module can reside in RAM memory, flash memory, ROM memory, EPROM memory, EEPROM memory, registers, hard disk, a removable disk, a CD-ROM, or any other form of storage medium known in the art. An exemplary storage medium is coupled to the processor such the processor can read information from, and write information to, the storage medium. In the alternative, the storage medium can be integral to the processor. The processor and the storage medium can reside in an ASIC. The ASIC can reside in a user terminal. In the alternative, the processor and the storage medium can reside as discrete components in a user terminal.

**[0198]** Conditional language used herein, such as, among others, "can," "may," "might," "could," "e.g.," and the like, unless specifically stated otherwise, or otherwise understood within the context as used, is generally intended to convey that certain embodiments include, while some embodiments do not include, certain features, elements and/or steps. Thus, such conditional language is not generally intended to imply that features, elements and/or steps are in any way required for one or more embodiments or that one or more embodiments necessarily include logic for deciding, with or without author input or prompting, whether these features, elements and/or steps are included or are to be performed in any particular embodiment.

**[0199]** While the above detailed description has shown, described, and pointed out novel features as applied to various embodiments, it will be understood that various omissions, substitutions, and changes in the form and details of the device or process illustrated can be made without departing from the spirit of the disclosure. As will be recognized, certain embodiments of the inventions described herein can be embodied within a form that does not provide all of the features and benefits set forth herein, as some features can be used or practiced separately from others. The scope of the inventions is indicated by the appended claims rather than by the foregoing description. All changes which come within the meaning and range of equivalency of the claims are to be embraced within their scope.

1-9. (canceled)

**10.** A method of wirelessly monitoring physiological information, the method comprising:

- providing a battery including a data storage component;
- connecting the battery to a bedside monitor;
- transferring data from the bedside monitor to the data storage component;
- connecting the battery to a wireless monitor;
- obtaining physiological information from one or more optical sensors; and
- transmitting physiological data reflective of the physiological information from the wireless monitor to the bedside monitor.

**11.** The method of claim 10, wherein the transferred data is a unique identifier.

**12.** The method of claim 10, wherein the transferred data is a password.

**13.** The method of claim 10, wherein the transferred data is channel information.

**14.** The method of claim **10**, wherein transmitting physiological data from the wireless monitor to the bedside monitor comprises:

transmitting physiological data over a first wireless technology when the wireless monitor is within a pre-determined distance from the bedside monitor; and  
transmitting physiological data over a second wireless technology when the wireless monitor is not within a pre-determined distance from the bedside monitor.

**15.** The method of claim **14**, wherein the first wireless technology is Bluetooth or ZigBee.

**16.** The method of claim **14**, wherein the second wireless technology is Wi-Fi or cellular telephony.

**17.** The method of claim **10**, wherein transmitting physiological data from the wireless monitor to the bedside monitor comprises:

transmitting physiological data over the first wireless technology when a signal strength of the first wireless technology is sufficiently strong; and  
transmitting physiological data over the second wireless technology when the signal strength of the first wireless technology is not sufficiently strong.

**18.** The method of claim **14**, wherein transmitting physiological data over the second wireless technology activates a display on the battery.

**19.** The method of claim **17**, wherein transmitting physiological data over the second wireless technology activates a display on the battery.

**20.** A system configured to wirelessly communicate physiological information including a battery, the battery comprising:

a housing;  
a rechargeable electrical storage module; and  
a memory module configured to store wireless communication information.

**21.** The system of claim **20**, wherein the wireless communication information pairs a wireless monitor with a bedside monitor.

**22.** The system of claim **20**, wherein the rechargeable electric storage module includes a display.

**23.-55.** (canceled)

\* \* \* \* \*

专利名称(译)	无线患者监护设备		
公开(公告)号	<a href="#">US20150359429A1</a>	公开(公告)日	2015-12-17
申请号	US14/834169	申请日	2015-08-24
[标]申请(专利权)人(译)	梅西莫股份有限公司		
申请(专利权)人(译)	Masimo公司		
当前申请(专利权)人(译)	Masimo公司		
[标]发明人	AL ALI AMMAR KINAST ERIC KARL MUHSIN BILAL DEJONG CHAD A		
发明人	AL-ALI, AMMAR KINAST, ERIC KARL MUHSIN, BILAL DEJONG, CHAD A.		
IPC分类号	A61B5/00		
CPC分类号	A61B5/0024 A61B5/7445 A61B5/002 A61B2560/0475 A61B5/0059 A61B2560/0214 A61B5/0022 A61B5/02416 A61B5/14551 A61B2560/0266 G16H10/60 G16H40/20 G16H40/63 A61B5/0261 A61B5/ /0295 A61B5/14552 A61B5/6826 A61B5/6831 A61B5/6833 A61B5/725 A61B5/7405 A61B5/7425 A61B5/746		
优先权	61/703713 2012-09-20 US 61/625584 2012-04-17 US 61/597126 2012-02-09 US		
其他公开文献	US10188296		
外部链接	<a href="#">Espacenet</a> <a href="#">USPTO</a>		

#### 摘要(译)

一种用于获得医疗患者的生理信息并将获得的生理信息无线发送到无线接收器的设备。

