



US 20160364036A1

(19) **United States**

(12) **Patent Application Publication**
Deng et al.

(10) **Pub. No.: US 2016/0364036 A1**
(43) **Pub. Date: Dec. 15, 2016**

(54) **MOBILE TERMINAL**

A61B 5/1172 (2006.01)

(71) Applicant: **SHENZHEN HUIDING TECHNOLOGY CO., LTD.**, Shenzhen (CN)

A61B 5/145 (2006.01)

G06K 9/00 (2006.01)

A61B 5/024 (2006.01)

(72) Inventors: **Gengchun Deng**, SHENZHEN (CN);
Wei Long, SHENZHEN (CN)

(52) **U.S. Cl.**
CPC *G06F 3/041* (2013.01); *G06K 9/00013* (2013.01); *A61B 5/02438* (2013.01); *A61B 5/1172* (2013.01); *A61B 5/14542* (2013.01); *A61B 5/6898* (2013.01); *G06F 2203/04103* (2013.01)

(21) Appl. No.: **15/249,997**

(22) Filed: **Aug. 29, 2016**

(57) **ABSTRACT**

Related U.S. Application Data

(63) Continuation of application No. PCT/CN2014/088291, filed on Oct. 10, 2014.


The present invention discloses a mobile terminal, including a touch screen, the touch screen including a touch cover plate. The touch screen further includes a sensing identification module, the touch cover plate covering the sensing identification module. In the embodiments of the present invention, the sensing identification module is integrated into a touch screen, and a full touch panel is used. In this way, the problem of sense of difference which is brought by the independently assembled sensing identification module is solved from the visual and tactile perspectives, the manufacturing procedure is simplified, production and utilization efficiencies are improved, and user's satisfaction is enhanced.

Foreign Application Priority Data

Jun. 16, 2014 (CN) 2014102685893

Publication Classification

(51) **Int. Cl.**
G06F 3/041 (2006.01)
A61B 5/00 (2006.01)






FIG. 1




FIG. 2




FIG. 3




FIG. 4




FIG. 5




FIG. 6




FIG. 7




FIG. 8




FIG. 9

MOBILE TERMINAL

CROSS-REFERENCE TO RELATED APPLICATIONS

[0001] This application is a continuation of International Patent Application No. PCT/CN2014/088291, with an international filing date of Oct. 10, 2014, designating the United States, now pending, which is based on Chinese Patent Application No. 2014102685893, filed Jun. 16, 2014. The contents of these specifications are incorporated herein by reference.

BACKGROUND OF THE INVENTION

[0002] Field of the Invention

[0003] The present invention relates to the technical field of mobile terminals, and in particular, to a mobile terminal with a touch screen equipped with a sensing identification module.

[0004] Description of the Related Art

[0005] At present, a press-type capacitive sensing identification module of the latest generation of smart handheld devices at home and abroad is embedded into a slot opened on a touch screen such that the sensing identification module is exposed to a user's fingers for touches. Such design not only increases manufacturing difficulty of the touch screen, but also enhances sense of difference which is brought by the independently assembled sensing identification module from the visual and tactile perspectives. This affects the entire structure, appearance and user experience of the device.

SUMMARY OF THE INVENTION

[0006] The present invention is intended to solve at least one of the above problems in the related art.

[0007] To this end, one objective of the present invention is to provide a mobile terminal, where a sensing identification module is integrated into a touch screen thereof. With this technical solution, the problem of sense of difference which is brought by the independently assembled sensing identification module is solved from the visual and tactile perspectives, the manufacturing procedure is simplified, production and utilization efficiencies are improved, and user's satisfaction of is bettered.

[0008] The present invention is implemented by: a mobile terminal, including a touch screen, the touch screen including a touch cover plate. The touch screen further includes a sensing identification module, the touch cover plate covers the sensing identification module.

[0009] To be specific, the touch cover plate includes a first part and a second part, a thickness of the second part being less than a thickness of the first part, the second part entirely or partially covers the sensing identification module.

[0010] In one embodiment, an upper surface of the touch cover plate is partially recessed downwardly to form the second part of the touch cover plate.

[0011] In another embodiment, a lower surface of the touch cover plate is partially recessed upwardly to form the second part of the touch cover plate, the sensing identification module is entirely or partially located inside the second part.

[0012] Further, the touch screen further comprises a touch sensor, the touch sensor is located beneath the touch cover plate.

[0013] In one embodiment, a through hole is arranged between an upper surface and a lower surface of the touch sensor, the sensing identification module is placed in the through hole.

[0014] Further, the touch screen further includes a reinforcing layer, the reinforcing layer is located beneath the touch cover plate.

[0015] In one embodiment, a through hole is arranged between an upper surface and a lower surface of the reinforcing layer, the sensing identification module is placed in the through hole.

[0016] Further, a lower surface of the touch cover plate is further provided with a silk screen layer.

[0017] Preferably, the sensing identification module includes at least one of a fingerprint identification module, a heartbeat identification module and a blood oxygen identification module.

[0018] The additional aspects and advantages of the present invention are partially illustrated in the following description, and the other portions would become more obvious from the following description or would be known from the practice of the present invention.

BRIEF DESCRIPTION OF THE DRAWINGS

[0019] FIG. 1 is a schematic three-dimensional exploded view of a mobile terminal according to an embodiment of the present invention;

[0020] FIG. 2 is a schematic section view of the mobile terminal as illustrated in FIG. 1;

[0021] FIG. 3 is another schematic section view of the mobile terminal as illustrated in FIG. 1;

[0022] FIG. 4 is still another schematic section view of the mobile terminal as illustrated in FIG. 1;

[0023] FIG. 5 is yet still another schematic section view of the mobile terminal as illustrated in FIG. 1;

[0024] FIG. 6 is yet still another schematic section view of the mobile terminal as illustrated in FIG. 1;

[0025] FIG. 7 is yet still another schematic section view of the mobile terminal as illustrated in FIG. 1;

[0026] FIG. 8 is another schematic three-dimensional exploded view of the mobile terminal according to an embodiment of the present invention; and

[0027] FIG. 9 is a schematic section view of the mobile terminal as illustrated in FIG. 7.

DETAILED DESCRIPTION OF THE EMBODIMENTS

[0028] The embodiments of the present invention are described in detail hereinafter. Examples of the described embodiments are given in the accompanying drawings, wherein the identical or similar reference numerals constantly denote the identical or similar elements or elements having the identical or similar functions. The specific embodiments described with reference to the attached drawings are all exemplary, and are intended to illustrate and interpret the present invention, which shall not be construed as causing limitations to the present invention.

[0029] In the description of the present invention, it should be understood that the terms "thickness", "upper", "lower", "front", "rear", "left", "right", "vertical", "horizontal", "top", "bottom", "inner", "outer" and the like indicate orientations and position relationships which are based on the illustrations in the accompanying drawings, and these

terms are merely for ease and brevity of the description, instead of indicating or implying that the devices or elements shall have a particular orientation and shall be structured and operated based on the particular orientation. Accordingly, these terms shall not be construed as limiting the present invention.

[0030] In the description of the present invention, it should be noted that unless otherwise specified and defined, the terms “mounted”, “coupled”, “connected” and “fixed” and derivative forms thereof shall be understood in a broad sense, which, for example, may be understood as fixed connection, detachable connection or integral connection; may be understood as mechanical connection or electrical connection, or understood as direct connection, indirect connection via an intermediate medium, or communication between the interiors of two elements or interactions between two elements. Persons of ordinary skill in the art may understand the specific meanings of the above terms in the present invention according to the actual circumstances and contexts.

[0031] As illustrated in FIG. 1 and FIG. 2, this embodiment discloses a mobile terminal, including a touch screen. The touch screen includes a touch cover plate 10 and a sensing identification module 11. The touch cover plate 10 covers the sensing identification module 11. Preferably, the sensing identification module 11 is one or more of a fingerprint identification module, a heartbeat identification module and a blood oxygen identification module.

[0032] In this embodiment, the touch cover plate 10 includes a first part 101 and a second part 102, a thickness of the second part 102 is less than a thickness of the first part 101, and the second part 102 entirely or partially covers the sensing identification module 11. Objectives of such design are to reduce the thickness of the touch cover plate 10 in a region where the sensing identification module 11 is located, enhance signal strength, and facilitate the sensing identification module 11 in data acquisition. Moreover, such design can also indicate the location where the sensing identification module 11 is located, and give convenience to user's operations.

[0033] As illustrated in FIG. 3, a lower surface of the touch cover plate 10 is further provided with a reinforcing layer 14. In one embodiment, a through hole is arranged between an upper surface and a lower surface of the reinforcing layer 14, and the sensing identification module 11 is placed in the through hole.

[0034] The lower surface of the touch cover plate 10 is further provided with a silk screen layer (not labeled with reference numeral), and the silk screen layer is configured to indicate the location where the sensing identification module 11 is located, and give convenience to user's operations.

[0035] Several embodiments of the touch cover plate are specifically described hereinafter.

Embodiment 1

[0036] As illustrated in FIG. 4 and FIG. 5, an upper surface of the touch cover plate 10 is partially recessed downwardly to form the second part 102 of the touch cover plate 10. The rest part of the touch cover plate 10, except the recess part, is the first part 101, and the sensing identification module 11 is located beneath the second part 102. This reduces the thickness of the touch cover plate in a region where the sensing identification module is located, enhances

signal strength, and facilitates the sensing identification module 11 in data acquisition.

Embodiment 2

[0037] As illustrated in FIG. 6 and FIG. 7, a lower surface of the touch cover plate 10 may be partially recessed upwardly to form the second part 102 of the touch cover plate 10. The rest part of the touch cover plate 10, except the recess part, is the first part 101, and the sensing identification module 11 is partially or entirely received inside the second part 102.

[0038] As illustrated in FIG. 8 and FIG. 9, the touch screen further comprises a touch sensor 12, where the touch sensor 12 is located beneath the touch cover plate 10. Preferably, a through hole 13 may be arranged between an upper surface and a lower surface of the touch sensor 12, and the sensing identification module 11 is placed in the through hole. Nevertheless, the sensor 12 may alternatively be placed in a side-by-side manner with the sensing identification module 11, and beneath the touch cover plate 10.

[0039] It should be noted that all control circuits, sensing circuits, memory circuits, and filters and boost circuits may be integrated in the sensing identification module 11. The location of the sensing identification module 11 is not specifically limited. For example, the sensing identification module 11 may be arranged at the location of a control board close to a physical HOME key or a virtual HOME key.

[0040] The touch cover plate 10 may be made from material with a high dielectric constant, high hardness and high durability, for example, the touch cover plate 10 may be made from a tempered glass sheet or a sapphire glass sheet.

[0041] In the embodiments of the present invention, the sensing identification module 11 is integrated into a touch screen assembly, and a full touch panel is used. In this way, the problem of sense of difference which is brought by the independently assembled sensing identification module 11 is solved from the visual and tactile perspectives, the manufacturing procedure is simplified, production and utilization efficiencies are improved, and user's satisfaction is enhanced.

[0042] In addition, it should be noted that the thickness of the touch cover plate 10 depends on material properties, for the reason that the touch performance of the sensor 12 is affected if the touch cover plate 10 is too thin.

[0043] When the sensing identification module is a fingerprint identification module, the fingerprint identification module includes a series of complicated circuits, including: a fingerprint identification sensor circuit, a control circuit, a memory circuit, a filter circuit, and the like, which are devices capable of implement fingerprint image acquisition. The fingerprint identification sensor circuit is formed by a series of analog circuit matrixes having a signal acquisition function. The fingerprint identification module is internally provided with a dust-proof cushion, which is configured to fix the fingerprint identification module, isolate dust, sweat, water and the like from entering the interior of the fingerprint identification module.

[0044] The fingerprint identification module uses the multi-chip package technology, and interconnection is achieved through a circuit substrate. The fingerprint identification sensor circuit is arranged on the front side of the entire fingerprint identification module, and the control circuit and the like on the rear side thereof are all protected by a filled plastic encapsulation body. The plastic encapsu-

lation body may be provided in a complete mold process, or may be formed through the drop glue protection technique. During the process of the plastic encapsulation, epoxy resins (compound) or other materials similar to high temperature resistance and scratch resistance materials may be used. Nevertheless, the process of the plastic encapsulation is not limited herein, as long as the circuits are protected from damages.

[0045] It should be noted that the mobile terminal herein may be a mobile phone, a tablet computer, or any device having a touch function.

[0046] In the description of the present specification, reference terms such as “an embodiment”, “some embodiments”, “examples”, “specific examples”, “some examples”, or the like are intended to refer to that the specific features, structures, materials, or characteristics which are described in combination with the embodiments or examples are comprised in at least one embodiment or example of the present invention. In this specification, schematic expressions of the above terms do not necessarily indicate the same embodiments or examples. In addition, the described specific features, structures, materials, or characteristics may be combined in any one or multiple embodiments or examples in a suitable way. In addition, in case of no contradiction, a person skilled in the art may incorporate or combine different embodiments or examples and features of different embodiments or examples described in this specification.

[0047] Although the above description illustrates the embodiments of the present invention, it can be understood that the embodiments are merely exemplary, and shall not be construed as limitations to the present invention. Persons of ordinary skill in the art may derive variations, modifications, and replacements to the above embodiments within the scope of the present invention.

INDUSTRIAL PRACTICABILITY

[0048] According to embodiments of the present invention, the touch cover plate and the induction identification module are integrated on the touch screen, a full touch panel is adopted, the problem of the sense of difference caused by independent assembly of the induction identification module in vision and touch is solved, the processing procedure is reduced, the efficiency of production and utilization is improved, and the satisfaction degree of users is improved.

What is claimed is:

1. A mobile terminal, comprising:
 - a touch screen, the touch screen comprising a touch cover plate,
 - wherein the touch screen further comprises a sensing identification module, the touch cover plate covers the sensing identification module.
2. The mobile terminal according to claim 1, wherein the touch cover plate comprises a first part and a second part, a thickness of the second part is less than a thickness of the first part, the second part entirely or partially covers the sensing identification module.
3. The mobile terminal according to claim 2, wherein an upper surface of the touch cover plate is partially recessed downwardly to form the second part of the touch cover plate.
4. The mobile terminal according to claim 2, wherein a lower surface of the touch cover plate is partially recessed upwardly to form the second part of the touch cover plate, the sensing identification module is entirely or partially located inside the second part.

5. The mobile terminal according to claim 1, wherein the touch screen further comprises a touch sensor, the touch sensor is located beneath the touch cover plate.

6. The mobile terminal according to claim 5, wherein a through hole is arranged between an upper surface and a lower surface of the touch sensor, the sensing identification module is placed in the through hole.

7. The mobile terminal according to claim 1, wherein the touch screen further comprises a reinforcing layer, the reinforcing layer is located beneath the touch cover plate.

8. The mobile terminal according to claim 7, wherein a through hole is arranged between an upper surface and a lower surface of the reinforcing layer, the sensing identification module is placed in the through hole.

9. The mobile terminal according to claim 1, wherein a lower surface of the touch cover plate is further provided with a silk screen layer.

10. The mobile terminal according to claim 1, wherein the sensing identification module comprises at least one of a fingerprint identification module, a heartbeat identification module and a blood oxygen identification module.

11. An apparatus, comprising:

a cover plate; and

a sensing identification module arranged beneath the cover plate;

wherein the cover plate comprises a main part and a sensing part having a thickness less than the main part, the sensing identification module is at least partly covered by the sensing part of the cover plate.

12. The apparatus according to claim 11, wherein the sensing identification module comprises a fingerprint identification module.

13. The apparatus according to claim 12, wherein the sensing identification module further comprises at least one of a heartbeat identification module and a blood oxygen identification module.

14. The apparatus according to claim 11, wherein the cover plate comprises a top touch surface and a bottom surface opposite to the top touch surface, the sensing identification module is arranged adjacent to the bottom surface of the cover plate.

15. The apparatus according to claim 14, wherein the top touch surface is recessed at the sensing part of the cover plate for reducing a thickness of the sensing part and enhancing signal strength of the sensing identification module.

16. The apparatus according to claim 14, wherein the bottom surface is recessed at the sensing part of the cover plate to form a receiving recess, and the sensing identification module is at least partly received in the receiving recess.

17. The apparatus according to claim 14, further comprising a reinforcing layer arranged on the bottom surface of the cover plate, wherein a through hole is formed in the reinforcing layer at a region corresponding to the sensing part of the cover plate, and the sensing identification module is received in the through hole.

18. The apparatus according to claim 14, further comprising a silk screen layer arranged on the bottom surface of the cover plate, wherein the silk screen layer is configured for indicating a location of the sensing identification module.

19. The apparatus according to claim 11, further comprising a touch panel arranged beneath the cover plate, wherein the touch panel comprises a through hole formed at a region

corresponding to the sensing part of the cover plate, and the sensing identification module is received in the through hole.

20. The apparatus according to claim **12**, wherein the fingerprint identification module comprises a fingerprint identification sensor circuit with a series of analog circuit matrixes for providing a signal acquisition function, and a dust-proof cushion is provided in the fingerprint identification module for fixing the fingerprint identification module and isolating undesired object from entering an interior of the fingerprint identification module.

* * * * *

专利名称(译)	移动终端		
公开(公告)号	US20160364036A1	公开(公告)日	2016-12-15
申请号	US15/249997	申请日	2014-10-10
[标]申请(专利权)人(译)	深圳市汇顶科技股份有限公司		
申请(专利权)人(译)	深圳市HUIDING TECHNOLOGY CO., LTD.		
当前申请(专利权)人(译)	深圳市HUIDING TECHNOLOGY CO., LTD.		
[标]发明人	DENG GENGCHUN LONG WEI		
发明人	DENG, GENGCHUN LONG, WEI		
IPC分类号	G06F3/041 A61B5/00 A61B5/1172 A61B5/145 G06K9/00 A61B5/024		
CPC分类号	G06F3/041 G06K9/00013 A61B5/02438 G06F2203/04103 A61B5/14542 A61B5/6898 A61B5/1172 A61B5/117 G06F1/1643 G06F1/1684 G06K9/00053		
优先权	201410268589.3 2014-06-16 CN		
其他公开文献	US10139938		
外部链接	Espacenet USPTO		

摘要(译)

本发明公开了一种移动终端，包括触摸屏，该触摸屏包括触摸盖板。触摸屏还包括感应识别模块，触摸盖板覆盖感应识别模块。在本发明的实施例中，感测识别模块集成在触摸屏中，并且使用全触摸面板。这样，从视觉和触觉的角度解决了独立组装的传感识别模块带来的差异感问题，简化了制造过程，提高了生产和利用效率，提高了用户的满意度。

