



US009125587B2

(12) **United States Patent**  
**Hawkins et al.**

(10) **Patent No.:** **US 9,125,587 B2**  
(45) **Date of Patent:** **Sep. 8, 2015**

(54) **SURGICAL RETRACTORS**

(71) Applicant: **DePuy Synthes Products, Inc.**,  
Raynham, MA (US)

(72) Inventors: **John Riley Hawkins**, Cumberland, RI  
(US); **Nicholas Pavento**, North  
Attleboro, MA (US); **Sean P. Selover**,  
Westport, MA (US); **Michele LeClerc**,  
Raynham, MA (US)

(73) Assignee: **DePuy Synthes Products, Inc.**,  
Raynham, MA (US)

(\*) Notice: Subject to any disclaimer, the term of this  
patent is extended or adjusted under 35  
U.S.C. 154(b) by 0 days.

(21) Appl. No.: **13/832,727**

(22) Filed: **Mar. 15, 2013**

(65) **Prior Publication Data**

US 2014/0275792 A1 Sep. 18, 2014

(51) **Int. Cl.**

**A61B 1/32** (2006.01)  
**A61B 1/06** (2006.01)  
**A61B 17/02** (2006.01)

(Continued)

(52) **U.S. Cl.**

CPC ..... **A61B 1/06** (2013.01); **A61B 5/6847**  
(2013.01); **A61B 17/02** (2013.01); **A61B**  
**17/0206** (2013.01); **A61B 5/01** (2013.01); **A61B**  
**5/14503** (2013.01); **A61B 5/14539** (2013.01);  
**A61B 5/14542** (2013.01); **A61B 5/14546**  
(2013.01); **A61B 17/0218** (2013.01); **A61B**  
**17/0293** (2013.01); **A61B 19/52** (2013.01);  
**A61B 2017/00092** (2013.01); **A61B 2017/00946**  
(2013.01); **A61B 2019/465** (2013.01); **A61B**  
**2019/521** (2013.01)

(58) **Field of Classification Search**

CPC ..... **A61B 1/32**; **A61B 17/206**; **A61B 17/02**  
USPC ..... **600/201, 202, 203-234**  
See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

4,945,896 A 8/1990 Gade  
5,928,137 A \* 7/1999 Green ..... 600/160

(Continued)

FOREIGN PATENT DOCUMENTS

WO 2007/085909 A2 8/2007  
WO 2007/121271 A2 10/2007

OTHER PUBLICATIONS

[No Author Listed] SynFrame Access and Retractor System Assem-  
bly Guide. Synthes Spine. Aug. 2010. (12 pages).

(Continued)

*Primary Examiner* — Jerry Cumberledge


*Assistant Examiner* — Tessa Matthews

(74) *Attorney, Agent, or Firm* — Nutter McClennen & Fish  
LLP

(57) **ABSTRACT**

The present disclosure relates to methods and devices for  
surgically manipulating tissue. In general, the methods and  
devices can include an elongate retractor shaft having a distal  
retractor tip that is configured to manipulate tissue, for  
example the tip can be configured to separate muscle and  
nerve fibers surrounding a vertebra. The elongate retractor  
shaft can include an illumination source such that at least a  
portion of the surgical field is illuminated by the device when  
the device is used in the body. A sensor can also or alterna-  
tively be included on the elongate retractor shaft, for example  
on the blunt retraction tip, such that the sensor can monitor  
physiological parameters of the tissue in or adjacent to the  
surgical field.

**17 Claims, 13 Drawing Sheets**



(51)	<p><b>Int. Cl.</b></p> <p><i>A61B 5/00</i> (2006.01)</p> <p><i>A61B 19/00</i> (2006.01)</p> <p><i>A61B 17/00</i> (2006.01)</p> <p><i>A61B 5/01</i> (2006.01)</p> <p><i>A61B 5/145</i> (2006.01)</p>	<p>2005/0131457 A1* 6/2005 Douglas et al. .... 606/205</p> <p>2007/0010716 A1 1/2007 Malandain et al.</p> <p>2007/0208226 A1* 9/2007 Grey et al. .... 600/212</p> <p>2008/0319290 A1* 12/2008 Mao et al. .... 600/323</p> <p>2009/0163943 A1* 6/2009 Cavanaugh et al. .... 606/180</p> <p>2010/0174146 A1* 7/2010 Miles et al. .... 600/202</p> <p>2011/0144640 A1* 6/2011 Heinrich et al. .... 606/41</p> <p>2011/0144687 A1* 6/2011 Kleiner ..... 606/192</p> <p>2011/0184245 A1* 7/2011 Xia et al. .... 600/202</p> <p>2011/0190588 A1* 8/2011 McKay ..... 600/202</p> <p>2011/0301421 A1* 12/2011 Michaeli et al. .... 600/211</p> <p>2012/0116170 A1 5/2012 Vayser et al.</p>
(56)	<p style="text-align: center;"><b>References Cited</b></p> <p style="text-align: center;">U.S. PATENT DOCUMENTS</p> <p>6,139,489 A * 10/2000 Wampler et al. .... 600/109</p> <p>7,166,073 B2 1/2007 Ritland</p> <p>8,055,349 B2 11/2011 Gharib et al.</p> <p>8,202,216 B2 6/2012 Melkent et al.</p> <p>8,382,666 B1 2/2013 Mao et al.</p> <p>2003/0088157 A1* 5/2003 Vassiliades et al. .... 600/202</p> <p>2005/0080320 A1* 4/2005 Lee et al. .... 600/214</p>	<p style="text-align: center;">OTHER PUBLICATIONS</p> <p>International Search Report for PCT/US14/018988 mailed Sep. 8, 2014 (6 pages).</p> <p>* cited by examiner</p>

FIG. 1A




FIG. 1B




FIG. 2




FIG. 3




FIG. 4




FIG. 5




FIG. 6




FIG. 7A




FIG. 7B




FIG. 7C




FIG. 7D




FIG. 8A




FIG. 8B




FIG. 8C




FIG. 9




FIG. 10




FIG. 11




FIG. 12





FIG. 13



**SURGICAL RETRACTORS**

## FIELD

The present disclosure relates generally to surgical retractor devices and methods for manipulating tissue.

## BACKGROUND

Surgical procedures for accessing tissue located deep within the body can pose a risk of trauma to the intervening tissue, particularly when the tissue includes neural tissue. During a surgical procedure where access to the spine is required, the final layers of tissue, those most proximate to the spine, are densely populated with large nerve fibers. Since the tissue is nerve-dense, the surgeon must take the greatest care when manipulating the tissue as the deep nerve fibers are remote from the surgeon, follow only general anatomic patterns, and are beneath, within, or above sensitive layers of tissue.

Various configurations of access devices have been developed to gain and maintain access to surgical fields, such as the spinal column, through deep access portals in tissue. For example, Penfield devices have been used in surgical procedures to manipulate muscular and neural tissue. However, the use of a Penfield device requires extending the tip of the Penfield device deep into the access portal to the surgical field. As the Penfield device is disposed within the deep access cavity, the surgeon typically loses visual contact of tissue that is adjacent to the distal tip of the Penfield device. As the surgeon loses sight of the working area, often due to a lack of light in the deep access portal, the likelihood of inadvertent contact and damage of sensitive neural tissue increases.

Accordingly, there remains a need for improved methods and devices for safely performing the surgical retraction of tissue.

## SUMMARY

Devices and method are provided for surgically manipulating tissue, such as muscle fibers, including embedded neural tissue within a deep access portal in a body. Specifically, the methods and devices described herein can provide an effective means to manipulate tissue with an increased field of vision for a surgeon. The methods and devices can also provide for monitoring of physical parameters.

In one embodiment, a surgical device for surgically manipulating tissue is provided and can include an elongate retraction shaft having a proximal end with a handle portion, and a distal end having a blunt retraction tip configured to retract tissue within a body without appreciably severing the tissue. The surgical device can also include an illumination source disposed on the elongate retraction shaft and configured to illuminate at least a portion of tissue being manipulated by the retraction tip. Furthermore, the device can have a sensor disposed on the retraction tip that can be configured to sense at least one physiological parameter of tissue being manipulated by the retraction tip. A connector can be coupled to the handle and electrically coupled to at least one of the illumination source and the sensor.

In one embodiment, the connector can be electrically coupled to the sensor and it can be configured to transfer a signal between the sensor and an external signal processor. The device can include an internal power source disposed within the handle portion that can be configured to provide power to at least one of the illumination source and the sensor.

The blunt retraction tip can have a variety of configurations. In one embodiment, the tip can have a concave surface configured to conform to a bone surface. The elongate retraction shaft can be linear or in other embodiments it can be non-linear with at least one bend formed therein such that the blunt retraction tip extends along a central longitudinal axis that is transverse to a central longitudinal axis of the handle portion. In certain embodiments the blunt retraction tip is in the shape of a dissector, such as a Penfield dissector. The elongate retraction shaft can have a lumen extending through at least a portion thereof. In certain embodiments, the connector can extend through the lumen, the illumination source can be at least partially disposed within the lumen, and/or the sensor can be at least partially disposed within the lumen. In some embodiments, the sensor can be laminated to an external surface of the elongate retraction shaft or molded/inserted within the retraction shaft and exposed at a distal portion thereof. Embodiments of an elongate retraction shaft having at least a portion that is malleable are also provided.

The illumination source can include a light emitting diode. While the location can vary, in one embodiment, the illumination source can be disposed proximally adjacent to the retraction tip. The sensor can also have various configurations and can be configured to sense at least one physiological parameter such as temperature, pressure, blood oxygen level, neuro conductivity, or combinations thereof. In another embodiment, the retraction tip can be removably coupled to the elongate retraction shaft.

In one embodiment, a signal processor can be disposed within the handle portion and coupled to the connector. The signal processor can be configured to monitor the at least one physiological parameter and to communicate to a user when the parameter falls outside of a preset range.

In another embodiment, a surgical system for manipulating tissue within a body is provided and includes a handle having an elongate shaft extending distally therefrom. The system can include a support ring coupled to a distal end of the elongate shaft. The system can also have a plurality of blades removably mated to the support ring and configured to retract tissue. An illumination source can be disposed on at least one of the elongate shaft and the support ring and the illumination source can be configured to illuminate tissue being retracted. The system can include a sensor disposed on at least one of the elongate shaft, the support ring, and the plurality of blades and configured to monitor at least one physiological parameter of a body tissue. In one embodiment, the plurality of blades can be configured to snap-fit onto the support ring.

A surgical kit is also provided. In one embodiment, the kit can include at least one retractor having a proximal end, a distal end, and an illumination source to illuminate an area surrounding the distal end. The distal end can have a blunt dissecting tip and a sensor disposed thereon to monitor at least one physiological parameter of a body tissue. The kit can also include at least one modular tip configured to be disposed over the blunt dissecting tip of the at least one retractor, and at least one support ring configured to support the retractor at the proximal end of the retractor when the retractor is disposed within the body.

## BRIEF DESCRIPTION OF DRAWINGS

This invention will be more fully understood from the following detailed description taken in conjunction with the accompanying drawings, in which:

FIG. 1A is a perspective view of one embodiment of a tissue retractor;

FIG. 1B is a perspective view of the distal end of the retractor of FIG. 1A;

FIG. 2 is a side view of one embodiment of a tissue retractor having an S-shaped bend in the shaft;

FIG. 3 is side view of one embodiment of a tissue retractor having an L-shaped bend in the shaft;

FIG. 4 is a cross-sectional view of a distal end of another embodiment of a tissue retractor;

FIG. 5 is a cross-sectional view of a distal end of another embodiment of a tissue retractor;

FIG. 6 is a schematic of one embodiment of an illumination source power circuit;

FIG. 7A is a partial schematic of one embodiment of a lab-on-a-chip sensor disposed on a retractor tip;

FIG. 7B is a partial schematic of one embodiment of a pressure sensor disposed on a retractor tip;

FIG. 7C is a partial schematic of one embodiment of a temperature sensor disposed on a retractor tip;

FIG. 7D is a partial schematic of one embodiment of a conductivity sensor disposed on a blunt retractor tip;

FIG. 8A is a top view of one embodiment of a retractor including a modular ring retractor;

FIG. 8B is a perspective view of one embodiment of a removable blade for use with the ring retractor of FIG. 8A;

FIG. 8C is a perspective view of the ring retractor of FIG. 8A shown with only three blades mated thereto;

FIG. 9 is a top view of one embodiment of a surgical kit;

FIG. 10 is a perspective view of one embodiment of a tissue retractor disposed within a deep access portal;

FIG. 11 is a cross-sectional view of one embodiment of a tissue retractor disposed in a body;

FIG. 12 is a perspective view of two malleable retractors disposed within a deep access portal and coupled to a support structure, according to another embodiment; and

FIG. 13 is a perspective view of two malleable retractors disposed within a deep access portal and coupled to one another, according to another embodiment.

#### DETAILED DESCRIPTION

Certain exemplary embodiments will now be described to provide an overall understanding of the principles of the structure, function, manufacture, and use of the devices and methods disclosed herein. One or more examples of these embodiments are illustrated in the accompanying drawings. Those skilled in the art will understand that the devices and methods specifically described herein and illustrated in the accompanying drawings are non-limiting exemplary embodiments and that the scope of the present invention is defined solely by the claims. The features illustrated or described in connection with one exemplary embodiment may be combined with the features of other embodiments. Such modifications and variations are intended to be included within the scope of the present invention

Further, like-numbered components of the embodiments disclosed herein generally have similar features, and thus within a particular embodiment each feature of each like-numbered component is not necessarily fully elaborated upon. Additionally, to the extent that linear or circular dimensions are used in the description of the disclosed systems, devices, and methods, such dimensions are not intended to limit the types of shapes that can be used in conjunction with such systems, devices, and methods. A person skilled in the art will recognize that an equivalent to such linear and circular dimensions can easily be determined for any geometric shape. Sizes and shapes of the systems and devices, and the components thereof, can depend at least on the anatomy of the subject in which the systems and devices will be used, the size and shape of components with which the systems and devices

will be used, and the methods and procedures in which the systems and devices will be used.

Minimally invasive surgical procedures have been developed to minimize the risk of trauma to surrounding tissue during surgical procedures. For example, lateral approach thoracic surgery is now a common method of performing spinal surgery. However, in performing minimally invasive surgeries, visibility of the surgical field is significantly reduced, thus leading to an increased risk of traumatic contact with neural tissue. Thus, to safely and reliably perform surgical procedures, such as lateral approach thoracic procedures, increased fields of vision and monitoring capabilities are necessary.

The present invention relates to methods and devices for surgically manipulating tissue, such as muscle fibers including embedded neural tissue within a deep access portal in a body. In general, the methods and devices include an elongate retractor shaft having a distal retractor tip that is configured to manipulate tissue, for example the tip can be configured to separate muscle and nerve fibers surrounding a vertebra. The elongate retractor shaft can include an illumination source such that at least a portion of the surgical field is illuminated by the device when the device is used in the body. A sensor can also or alternatively be included on the elongate retractor shaft, for example on the blunt retraction tip, such that the sensor can monitor physiological parameters of the tissue in or adjacent to the surgical field. The device can include various features to allow for mating with support structures, retraction of tissue, modularity, etc., exemplary embodiments of which are discussed in detail below. A person skilled in the art will appreciate that a device can have any combination of features disclosed herein. The devices disclosed herein can also be configured for use in any procedure in which it is necessary to manipulate tissue, including both open surgery and minimally invasive procedures. In certain exemplary embodiments, the methods and devices disclosed herein can be particularly useful in minimally invasive procedures where access to the surgical field is through a small portal or cannula with limited vision. As mentioned, one such use is in spinal surgeries, such as minimally invasive lateral approach thoracic procedures.

FIGS. 1A and 1B illustrate one embodiment of the surgical retraction device 100. As shown, the surgical retraction device 100 is in the form of a generally elongate retraction shaft 112 having a proximal end 114 and a distal end 116. The proximal end 114 can include a handle portion 118 configured to be grasped by a user, and the distal end 116 can include a tissue retraction tip 120. An illumination source 122 can be disposed on the elongate retraction shaft 112 for illuminating tissue surrounding the device. The device 100 can also include a sensor 126 disposed thereon and configured to monitor physiological parameters, e.g., neural and myo monitoring, temperature, pressure, and blood oxygen levels, of the tissue contacted by the tip. A connector 128 can be coupled to the proximal end 114 of the device and it can be electrically or fiber optically coupled to at least one of the illumination source 122 and the sensor 126. In some embodiments, the connector 128 can be formable to hold the retractor in place.

As indicated above, the proximal end 114 of the elongate retraction shaft 112 can include a handle portion 118 that is configured to be grasped by a surgeon. The handle portion 118 can have any shape and size, and it can merely be a portion of the shaft configured to be grasped. In the illustrated embodiment, the handle portion 118 includes gripping features, which can be in the form of one or more ridges or surface protrusions extending around the shaft, to facilitate

grasping by a user. The ridges can also facilitate mating of the device to a support member, such as a snap-fitting on a support ring. In other embodiments, a handle can be formed on or coupled to the shaft and it can have an ergonomic shape designed to allow a user to grip the device **100** comfortably while allowing for optimum manipulation of the blunt retraction tip **120**. While not shown in FIG. 1A, the handle portion **118** can also include features for facilitating mating to another device, such as a support ring, wrench, or a robotic arm. For example, the handle portion **118** can include a central aperture that allows for attachment to a mechanical arm or device.

The handle portion **118** can also include a variety of other features, such as a display for communicating sensed physiological parameters of the tissue being manipulated, or for displaying tissue imaged by a distal end of the device. In other embodiments, the handle portion **118** can be configured to couple to various external devices, such as an image guidance system or an external power supply. In another embodiment, the handle portion **118** can house an internal power supply, such as a battery, and any electrical circuitry required to control and power the illumination source **122** and/or the sensor **126**. For example, the circuitry can include an internal signal processor for monitoring the sensor **126** signal. While not shown, the handle portion **118** can also include a switch for allowing a user to activate at least one of the illumination source and the sensor. Various switches known in the art can be used.

The elongate shaft **112** extends distally from the handle portion **118** and is preferably dimensioned so as to allow the distal end **116** of the elongate retraction shaft to be disposed within a body cavity for manipulating tissue, while the proximal end **114** is positioned outside of the patient's body for allowing the handle portion **118** to be grasped by a user. While the length can vary depending on the intended use, in one embodiment the length of the elongate shaft **112** can be in the range of about 30 mm to about 200 mm. The diameter of the shaft, as well as the diameter of the handle portion **118**, can vary depending on the intended use, and the shaft and handle can have the same or different diameters. In one embodiment, the handle portion **118** can have a diameter that is greater than a diameter of the shaft **112** to facilitate gripping of the device. By way of non-limiting example, the diameter of the handle can be in the range of about 5 mm to about 25 mm, and the diameter of the shaft can be in the range of about 3 mm to about 12 mm. The shaft **112** can also be generally rigid and linear, extending along a single longitudinal axis, or in other embodiments the shaft can be non-linear and/or flexible or malleable.

As indicated above, the retraction tip **120** is formed on the distal end **116** of the elongate shaft **112**. The retraction tip **120** can have various configurations for manipulating tissue in the body, and the particular configuration can depend on the intended use. For example, the retraction tip **120** can be in the form of a blunt tip configured to allow a surgeon to separate muscle and neural fibers near the spinal column and to retract and retain the tissue out of the surgical field giving access to vertebral bone tissue under the retracted muscle and neural tissue, such as a Penfield dissector as known in the art. In the illustrated embodiment, the retraction tip **120** can have a generally flattened configuration such that a width extending in a first direction perpendicular to a longitudinal axis of the shaft is greater than a depth extending in a second opposite direction perpendicular to the longitudinal axis. The generally flattened tip can have a distal-most portion with a reduced diameter so as to form a pointed cylindrical tip portion **121**. In other embodiments, however, the retraction tip can be cylindrical, concave along any one or more surfaces, rectangular,

spherical, etc. The tip can include a groove or central lumen to aid in the positioning of additional tools such as a surgical wire or a fixation pin. The tip can be sufficiently narrow to penetrate and anchor in a bone surface with the aid of a surgeon or it can be anchored with a screw or pin. The central lumen can also be used to provide aspiration when a vacuum source is connected to the handle **118**. Additionally, the blunt retraction tip **120** can be configured to removably mate to the elongate shaft and a plurality of modular tips having various shapes and sizes can be provided, as will be discussed in detail below.

As mentioned above, the retractor **100** can also include an illumination source **122** for illuminating tissue surrounding the distal retraction tip **120**. The illumination source can include a plurality of light sources, for example two light emitting diodes. Alternatively, the illumination source can be a singular light source. The illumination source can produce a diffuse light field radiating from the light source so as to light the general working area. Alternatively, the illumination source can be configured to produce a targeted light field that shines directly onto a desired area, for example the illumination source can be directed to shine toward the cylindrical tip portion **121** of the retractor **100**. In some embodiments, the targeted light field is the result of divergent or convergent configuration of the illumination sources balancing the light about the tip portion and the adjacent tissue. The illumination source can be any known light source that is capable of providing illumination to a cavity. For example, the illumination source can be a light emitting diode, an organic light emitting diode, a fiber optic lighting system such as those including polymeric light pipes, and/or chemical luminescent strips.

The illumination source can be disposed at any location along the elongate shaft **112** such that when the device is disposed within a patient's body, e.g., within a deep access portal, the illumination source will illuminate at least a portion of the surgical field, such as tissue surrounding a vertebra. The location of the illumination source can vary depending on the quantity of illumination sources as well as the intended use. In the embodiment shown in FIG. 1A, the illumination source **122** is positioned proximally adjacent to the distal end **116**, and more particularly proximal to the cylindrical tip portion **121**. This will allow the illumination source **122** to illuminate tissue being manipulated by the retraction tip **120**. A person skilled in the art will appreciate that the illumination source **122** can be positioned at any location along the length of the shaft **112**, including along the handle portion **118** or at the cylindrical tip portion **121**. Moreover, the device **100** can include multiple illumination sources. In certain exemplary embodiments, the illumination source **122** is positioned a distance from the distal-most end of the shaft **112** that is in the range of about 10 mm to about 100 mm.

The illumination source can be coupled to the retractor device **100** using a variety of techniques. In the illustrated embodiment, the illumination source **122** is in the form of a light emitting diode that is disposed within a bore **123** formed in the shaft **112**. While not shown, the bore can extend into an inner lumen that extends through the shaft **112** for allowing the illumination source **122** to be coupled to a power source disposed within the handle, or through an electrical connector **128** extending from a proximal end of the handle portion **118**. In some embodiments, the illumination source **122** can be fiber optically connected with connector **128**.

As indicated above, the device **100** can also include a sensor for sensing one or more physiological parameters of tissue being manipulated by the retraction tip **120**. FIG. 1B

illustrates the retraction tip **120** of the device **100** in more detail. While the sensor **126** can be positioned at various locations along the shaft **112**, in the illustrated embodiment the sensor **126** is disposed on an external surface and extends longitudinally along the retraction tip **120** such that the sensor **126** will come into contact with tissue being manipulated. The sensor **126** can be disposed on the same side or on an opposite side of the shaft **112** as the illumination source **122**. The sensor **126** can be mated to the retraction tip **120** for instance by laminating the sensor **126** to the distal end **116**. Alternatively, the sensor **126** can be disposed within a bore or lumen in the blunt retraction tip **120**, or a portion of the tip itself can be configured to function as a sensor, for example surfaces of the retraction tip **120** can function as a thermocouple to measure temperature. In some embodiments, the retraction tip **120** can include a single sensor to monitor a single parameter, multiple sensors for monitoring a number of different parameters, or a single sensor that can monitor more than one parameter. In use, the sensor(s) can be configured to measure a variety of physiological parameters, as will be discussed in more detail below.

FIG. 2 illustrates another embodiment of a tissue retractor **200**, which can be similar to the retractor **100** of FIG. 1, but which has a non-linear shaft **210**. As shown, the retractor **200** generally includes a handle portion **212** at a proximal end **214** of the shaft **212** and a retractor tip **216** at a distal end **216** of the shaft. The retractor **200** also includes an illumination source **222** disposed on the shaft **212** at a location proximally adjacent to the distal retractor tip **226**. While not shown, the retractor can further include a sensor, as discussed above with respect to FIG. 1.

As indicated above, in this embodiment the retractor shaft **212** is non-linear. While the non-linear shape can vary and the shaft **212** can include any number of bends or curves formed therein, in the illustrated embodiment the shaft includes an S-shaped bend **224** formed at a general mid-portion thereof. This S-shaped bend **224** preserves a surgeon's line of sight to the tip **216** by having the handle portion **212** extend along a longitudinal axis  $A_h$  that is offset from along a longitudinal axis  $A_r$  of the portion containing the retractor tip **226**. The surgeon's view is thus unobstructed by the surgeon's hands or other support structure supporting the handle portion **218**. The elongate retractor shaft can optionally be malleable such that the location of any bends can be adjusted and the shaft can be oriented in a desired configuration. In other embodiments, the shaft can be formed from a shape-memory material such that the curvature changes in response to change in temperature or other outside stimulus.

FIG. 3 illustrates another embodiment of a tissue retractor **300** having a handle portion **318** and a non-linear elongate retractor shaft **312** extending distally from the handle **318**. In this embodiment, the handle **318** is shown having a switch **316**, a power source **332**, a signal processor **330**, and a connector **329** extending between the signal processor **330** and a sensor **326** located in the retraction tip **320**, and more particularly in the distal-most tip **321**. The power source **332** can be in the form of a battery and the switch **316** can be coupled to the battery and to the signal processor **330**. As a result, when the switch **316** is activated, power is delivered from the power source **332** to the signal processor **330**, which in turn sends a signal through the connector **329** to at least one of the sensor **326** and first and second illumination sources **322a**, **322b**. FIG. 3 further illustrates an L-shaped bend **324** formed at a substantial mid-portion of the shaft **312** between proximal and distal ends **314**, **316** thereof. As a result, a longitudinal axis through the retraction tip **320** is substantially transverse to a longitudinal axis through the handle portion **318**.

FIG. 4 illustrates a distal portion of another embodiment of an elongate retractor shaft **400** having a first aperture **410** and a second aperture **412** formed in the retractor shaft through which first and second illumination sources (not shown) can be at least partially disposed. As further shown in FIG. 4, the shaft **400** can include an inner lumen **413** extending there-through for receiving one or more electrical or fiber optic connectors (not shown) for connecting the illumination sources to a power source or fiber optic system. In this embodiment, the apertures **410**, **412** are formed in a first surface **414** having a substantially convex shape, and the retractor shaft **400** includes a second, opposite surface **416** that is substantially concave. The illumination sources can be seated within the apertures **410**, **412** and retained therein using various techniques, such as threads, adhesives, welding, etc. Alternatively, the illumination source can be laminated onto an outer surface **414**, **416** of the elongate retractor shaft.

FIG. 5 illustrates a distal portion of another embodiment of an elongate retractor shaft **500** having a first aperture **510** and a second aperture **512** formed in a first substantially convex surface **518** of the retractor shaft **500**. The first and second apertures **512** can be configured to seat first and second illumination sources (not shown). In some embodiments, the retractor **500** can have another, third aperture **514** on a second or opposite substantially concave surface **516**. One or more additional illumination sources can be disposed within the third aperture **514** for illuminating tissue in a direction opposite to the direction of illumination provided by the illumination sources disposed within the first and second apertures **510**, **512**. As with the previous embodiment, the elongate shaft **500** can include a lumen **522** extending therethrough and configured to provide access, e.g., for one or more electrical or fiber optic connectors, from a proximal end (not shown) of the shaft **500** to the apertures **510**, **512**, **514**.

As indicated above, in some embodiments, such as those shown in FIGS. 4 and 5, the lumen **413**, **522** extending there-through can house an electrical coupling for the illumination source. Additionally or alternatively, the lumen **413**, **522** can house a fiber optic coupling for the illumination source. The lumen can extend from the proximal end of the elongate shaft to the distal end, or can only extend through a portion of the shaft, e.g., terminating proximal to the distal-most end. The lumen can be so dimensioned as to allow an electrical or fiber optic coupling to extend from the proximal end of the shaft to the illumination source, the sensor, or both. Additionally, the shaft can have more than one lumen, for instance the shaft can include a first lumen housing a first electrical coupling and a second lumen designed to deliver surgical accessories or tools, such as bone screws, to the surgical field (not shown). Additionally, the second lumen can also be configured to provide aspiration with a vacuum system. The electrical coupling can be any known coupling mechanism, such as a conductive wire.

FIG. 6 illustrates an exemplary circuit **600** to power first and second illumination sources **610**, **610'**. The illumination sources **610**, **610'** can be powered by an internal power source **612**. The power source **612** can be disposed on or within the device, for instance in a cavity within the handle (for example in FIG. 3, power source **332** is disposed within handle **312**). Alternatively, the power source **612** can be external to the device and electrically connected to the proximal end of the handle through a connector, such as an electrical cord or cable as shown in FIG. 1. The power source **612** can include a battery or series of batteries as is known in the art or can include any other known power source, such as a standard wall outlet.

As shown in FIG. 6, the power source 612 can be electrically coupled to the illumination sources 610, 610' by a circuit 600 that includes a switch 614 and a fuse or diode 616. The switch 614 can be configured to control power to the illumination source 610, 610' such that a user can control the optical output of the illumination source 610, 610'. The switch 614 can be any mechanism capable of controlling power to the illumination source 610, 610', including on/off switches or dimmer-type switches to give a range of light outputs. In one embodiment, the switch 614 can be a physical switch disposed on the handle that is configured to be manipulated by a surgeon. For example, the switch 614 can be a touch-sensitive surface that is toggled as a surgeon touches any portion of the surface of the handle (for example, the switch 316 in FIG. 3). In other embodiments, the switch 614 can be a depressible button-type switch disposed on the handle. In some embodiments, the switch 614 can be a one-way on switch that is activated as soon as the device is removed from a sterile package (not shown).

FIGS. 7A-7D illustrate various types of exemplary sensors for use on any of the retraction tips disclosed herein. The sensor can be configured to measure any parameter that has physiological significance to one skilled in the art. For example, the physiological parameters monitored by exemplary sensors can include temperature, pressure, blood oxygen levels, and electrical conductivity. As shown in FIG. 7A, the sensor 810 is in the form of a lab-on-a-chip sensor 810 that is disposed on a retractor tip 800 having a generally concave distal-facing surface so as to conform to bone 820 as shown. The lab-on-a-chip sensor can be as small as a few millimeters and can utilize micro fluidics to analyze physiological parameters of the adjacent tissue. For example, a lab-on-a-chip sensor can monitor the blood oxygen levels in the adjacent tissue. FIG. 7B illustrates another tip 900 having a concave surface that conforms to a surface of a bone 920. The sensor 910 in this embodiment is a pressure sensor 910 for sensing applied pressure. The pressure sensor can be any type of pressure sensor known in the art, for example a force sensing resistor, resistive strain gauge, dielectric pressure sensitive film, piezoelectric type sensor, capacitive, electromagnetic, potentiometric, resonant, and thermal type pressure sensors. In another embodiment, shown in FIG. 7C, tip 1000 includes a temperature sensor 1010, such as a thermocouple. As with the tips shown in FIGS. 7A and 7C, tip 1000 includes a distal-facing concave surface configured to conform to bone 1020. FIG. 7D illustrates yet another embodiment of a tip 1100 that is configured to have a concave surface that conforms to a surface of a bone 1120. In this embodiment, the sensor is in the form of an electrical conductivity meter 1110, such as that commonly used in neural and myo monitoring systems.

The various sensors disclosed herein can be configured to monitor real-time data during a surgical process and can be coupled to computational devices such that a surgeon can be alerted if the monitored parameter is outside of a preset range. Computational devices can include known patient monitoring systems that are in an operating room or procedure room, or alternatively or additionally can include a signal processor and computational device stored directly in the elongate retraction shaft of a retractor device. If stored directly in the shaft, the computational device or signal processor can be disposed anywhere in the shaft (for example, as shown in FIG. 3, the signal processor 330 is disposed within the handle 318 adjacent the power source 332).

The sensor(s) can be in communication with neural and myo monitoring systems known in the art. For example, the sensor(s) can be configured to monitor conductivity of the

contacted tissue in order to sense when neural tissue is near and/or when the adjacent neural tissue is active. The sensor(s) can be coupled to the illumination source coupled to the shaft for illuminating tissue, or to a separate illumination source or other indicator provided elsewhere on the device, e.g., on the handle. When a parameter monitored by the sensor is outside of a preset range, the illumination source can alert the surgeon, for instance by flashing, blinking, turning off, or changing color when the temperature of the tissue is outside of a desired range. To achieve this communication between the sensor and the illumination source, the sensor and illumination source can be electrically coupled in a circuit that is housed within the device, or that includes components that are external to the device (such as an external signal processor).

FIGS. 8A-8C illustrate another embodiment of a tissue retractor. The retractor 1200 can include a handle 1210 and an elongate shaft 1220 extending distally from the handle 1210. The system 1200 can also include a support ring 1230 coupled to a distal end 1222 of the elongate shaft. The support ring 1230 can be configured to removably mate to a plurality of blades 1240. As shown, the ring 1230 can have an oblong or oval shape. Alternatively, the ring can have a circle, pentagon, octagon, or any other geometric shape. One or more blades 1240 can be mated to the support ring 1230 to retract tissue surrounding the blades 1240.

FIG. 8B illustrates one of the removable blades 1240 in more detail. The blade 1240 can have proximal and distal ends 1242, 1244. The distal end 1244 can be configured to be disposed in and to retract tissue. The proximal end 1242 can be configured to snap into the support ring 1230. While the blades 1240 can be removably attached to the ring 1230 using various techniques, in one embodiment a snap-fit engagement can be utilized. For example, the blade can include an elongate surface protrusion (not shown) extending laterally across a proximal end 1242 thereof, and the ring 1230 can include an elongate groove (not shown) that is configured to seat and engage the protrusion on the blade 1240.

FIG. 8B further illustrates an insertion handle 1250 that can be connected to the proximal end 1242 of the blade 1240 and that can be manipulated to twist the blade 1240 into engagement within the ring 1230. Such a configuration can allow the blades 1240 to be attached to the ring 1230 intraoperatively. As further shown in FIG. 8A, the blade 1240 can have an aperture 1246 form on an inwardly facing surface thereof that can be designed to receive a bone anchor or other surgical implement.

FIG. 8C illustrates the exemplary retractor 1200 having three blades 1240, 1240', 1240" snapped into place in the support ring 1230 in a configuration that will retract tissue and define a deep access portal or cavity in tissue. As shown, the ring 1230 need not have blades 1240, 1240', 1240" mated in a full circle around the ring 1230, rather, a portion of the ring 1230 can be free of blades 1240 as shown. Additionally, any one or more of the ring 1230, the blades 1240, 1240', 1240", and elongate shaft 1220 can include an illumination source disposed thereon or therein to illuminate the deep access portal or cavity created by the system, and/or a sensor as described herein to monitor at least one parameter of the retracted tissue.

FIG. 9 illustrates an exemplary surgical kit 1500 for retracting tissue. An exemplary kit 1500 can include any tools necessary for performing any type of surgery, such as spinal surgery, and in particular thoracic surgery. As shown, the kit 1500 can include a combination of devices, such as illuminating retractors 1510, 1520, 1530, 1540, 1550. With reference to retractor 1510, each illuminating retractor can have a

proximal end **1560**, a distal end **1570**, and an elongate intermediate portion **1580**. The distal end **1570** can have a retraction tip **1590** and a sensor (not shown) disposed thereon to monitor at least one physiological parameter of a body tissue. The elongate intermediate portion **1580** can include an illumination source **1592** as described herein to illuminate an area surrounding the distal end. A person skilled in the art will appreciate that the kit can include any combination of retractors having any combination of features disclosed herein.

The kit can also include one or more modular tips **1594** configured to be removably disposed over any one of the blunt retracting tips on retractors **1510**, **1520**, **1530**, **1540**, **1550**. Each modular tip can be in the form of a cap having a shape that is different from the shape of the other modular tips and the shape of the retractor tips so as to allow the tip of the retractor to be modified as may be desired based on the intended use. The tips can be of a different material such as absorptive polymer/sponge/cloth **1594**. This can allow the retractor blade to perform various other functions, such as the function of a Kittner dissector. The kit can further include at least one support ring **1596** configured to support one or more of the retractors **1510**, **1520**, **1530**, **1540**, **1550** at the proximal end of a retractor when the retractor **1510**, **1520**, **1530**, **1540**, **1550** is disposed within the body. For example, proximal end **1560** of retractor **1510** can be configured to mate to the support ring **1596**. Some of the retractors, e.g., retractors **1540** and **1550**, can include a malleable connector **1598** extending from a proximal end thereof that is configured to be wrapped around the ring for mating the retractor to the support ring.

A person skilled in the art will appreciate that the systems and devices disclosed herein can be formed of any known biologically compatible material that is suitable for the given component's described properties, function, and design. For example, the elongate retraction shaft, support ring, and blades can be formed of any biocompatible rigid or semi-rigid material, such as stainless steel, nitinol, platinum, tungsten, polytetrafluoroethylene (PTFE), polyamides, polyethers, polyurethanes, polyvinylchloride, silicones, and various other metals, metal alloys, polymers, and copolymers known to those skilled in the art to have the desired mechanical properties. The blunt retraction tip can be formed from the same or different materials as the elongate retraction shaft and can include various coatings to provide additional beneficial material properties. For example, the tip can have a low-durometer coating, such as silicone or Teflon. The handle can also have a coating thereon, for instance a non-conductive, non-slip coating such as rubber or silicone.

FIG. 10 illustrates one exemplary use of a tissue retractor. In this embodiment, two retractors **1610**, **1610'** are placed within a deep access portal **1612** in a body and are configured to manipulate tissue. Manipulating tissue can include separating, retracting, distracting, dilating, or otherwise moving tissue within the body. Manipulating can also include cutting or severing tissue, such as with a beveled knife blade (not shown), or alternatively can include retracting and distracting tissue without cutting the tissue, for example with a blunt retraction tip **1614**, **1614'**. The devices can hold muscle **1616** and nerve fibers **1618** away from the portal **1612** thus giving access to the underlying bone **1620** and preventing the sensitive neural **1618** and muscular tissues **1616** from being unnecessarily contacted during procedures involving the bone.

The devices **1610**, **1610'** are shown in cut-away with the internally powered handles and surgeon's hands represented by **1626** and **1626'**. Alternatively the devices can include connectors **1622**, **1622'** extending from a proximal end **1624**, **1624'** of the devices **1610**, **1610'**. The connectors can be

coupled to an external power supply or signal processor in the location of **1626**, **1626'**. The external power supply or signal processor **1626** can be configured to power or otherwise communicate with the illumination sources **1628**, **1628'** and/or with one or more sensors (not shown) disposed on the devices **1610**, **1610'**.

FIG. 11 illustrates another embodiment of a retractor **1710** disposed within a cannula **1712** defining an access portal through tissue. The surgical field **1714** can be the area near the thoracic region of the spinal column **1716** that is dense with nerve fibers. A distal tip **1718** of the retractor **1710** can be used to retract tissue to form a cavity giving access to the surgical field **1714**. The retractor can include a connector **1720** extending from the proximal end **1722** of the retractor **1710** that includes a handle portion **1724**.

FIG. 12 illustrates retractors **1800**, **1800'** disposed in a deep access portal **1802** with connectors **1810**, **1810'** extending from a proximal portion **1812**, **1812'** of the elongate retraction shafts **1814**, **1814'**. The connectors **1810**, **1810'** can be configured to be operatively coupled, i.e., electrically, optically, and/or physically, to the proximal end **1812**, **1812'** of the elongate retractor shafts **1814**, **1814'**. The connectors **1810**, **1810'** can be configured to electrically connect at least one of the illumination source **1816**, **1816'** and a sensor (not shown) to an external signal processor such as a myo monitor. All or a portion of each connector **1810**, **1810'** can also be malleable **1818**, **1818'** to allow the connectors to wrap around and mate to a support structure **1820**.

FIG. 13 illustrates another embodiment showing malleable connectors **1910**, **1910'** on two retractors **1900**, **1900'** tied or otherwise coupled to one another such that when the retractors **1900**, **1900'** disposed within a body **1920**, they are maintained in a stable position. As with the previous embodiment, the connectors **1910**, **1910'** can be formed of any known articulatable and/or malleable wire or sheath. For example, the connectors **1910**, **1910'** can be a segmented, articulatable sheath with a conductive wire or fiber optic cable running therethrough to electrically or fiber optically connect the device to an external system. The connectors **1910**, **1910'** can thus mate to the proximal end **1930**, **1930'** of the retractors **1900**, **1900'** and can extend through a lumen in the device to make an electrical connection with at least one of the illumination source and the sensor.

A person skilled in the art will appreciate that the present disclosure has application in conventional minimally-invasive and open surgical instrumentation as well application in robotic-assisted surgery. The devices disclosed herein can also be designed to be disposed of after a single use, or they can be designed to be used multiple times. In either case, however, the device can be reconditioned for reuse after at least one use. Reconditioning can include any combination of the steps of disassembly of the device, followed by cleaning or replacement of particular pieces and subsequent reassembly. In particular, the device can be disassembled, and any number of the particular pieces or parts of the device can be selectively replaced or removed in any combination. Upon cleaning and/or replacement of particular parts, the device can be reassembled for subsequent use either at a reconditioning facility, or by a surgical team immediately prior to a surgical procedure. Those skilled in the art will appreciate that reconditioning of a device can utilize a variety of techniques for disassembly, cleaning/replacement, and reassembly. Use of such techniques, and the resulting reconditioned device, are all within the scope of the present application.

One skilled in the art will appreciate further features and advantages of the invention based on the above-described embodiments. Accordingly, the invention is not to be limited

by what has been particularly shown and described, except as indicated by the appended claims. All publications and references cited herein are expressly incorporated herein by reference in their entirety.

What is claimed is:

1. A surgical device for surgically retracting muscle fibers including embedded neural tissue within a deep access portal in a body, comprising:

an elongate retractor shaft having a proximal end with a handle portion and a distal end having a blunt retraction tip configured to manipulate tissue within a body without appreciably severing the tissue;

an illumination source disposed on the elongate retractor shaft and configured to illuminate tissue;

a connector coupled to the handle and operatively coupled to the illumination source;

a sensor disposed on the retraction tip and configured to sense at least one physiological parameter of tissue being manipulated by the retraction tip;

a signal processor; and

a power source, wherein power is delivered from the power source and delivered to the signal processor which delivers power to at least one of the sensor and the illumination source through the connector;

wherein, when a parameter monitored by the sensor is outside a preset range, the signal processor is configured to activate the illumination source to alert a user;

wherein the illumination source, connector, sensor, signal processor and power source are all disposed within the elongate retractor shaft.

2. The device of claim 1, wherein the power source is disposed within the handle portion.

3. The device of claim 1, wherein the blunt retraction tip has a concave surface configured to conform to a bone surface.

4. The device of claim 1, wherein the elongate retractor shaft is non-linear with at least one bend formed therein such that the blunt retraction tip extends along a central longitudinal axis that is transverse to a central longitudinal axis of the handle portion.

5. The device of claim 1, wherein the elongate retractor shaft has a lumen extending through at least a portion thereof.

6. The device of claim 5, wherein the connector extends through the lumen.

7. The device of claim 5, wherein the illumination source is at least partially disposed within the lumen.

8. The device of claim 1, wherein the elongate retractor shaft has a lumen extending through at least a portion thereof, and the sensor is at least partially disposed within the lumen.

9. The device of claim 1, wherein the illumination source is disposed proximally adjacent to the retraction tip.

10. The device of claim 1, wherein the illumination source includes a fiber optic lighting system.

11. The device of claim 1, wherein the illumination source includes a light emitting diode.

12. The device of claim 1, wherein the blunt retraction tip is configured to anchor into bone.

13. The device of claim 1, wherein the sensor is configured to sense at least one physiological parameter selected from the group consisting of a temperature, a pressure, a blood oxygen level, neuro conductivity, or combinations thereof.

14. The device of claim 1, wherein at least a portion of the elongate retraction shaft is malleable.

15. The device of claim 1, wherein the sensor is laminated to an external surface of the elongate retractor shaft.

16. A surgical kit, comprising:

at least one retractor having a proximal end, a distal end, and an illumination source to illuminate an area surrounding the distal end, the distal end having a blunt dissecting tip and a sensor disposed thereon to monitor at least one physiological parameter of a body tissue; wherein the at least one retractor further comprises a signal processor and a power source, wherein power is delivered from the power source and delivered to the signal processor which delivers power to at least one of the sensor and the illumination source through a connector; and

wherein the illumination source, connector, sensor, signal processor and power source are all disposed within the at least one retractor;

at least one modular tip configured to be disposed over the blunt dissecting tip of the at least one retractor; and at least one support ring configured to support the retractor at the proximal end of the retractor when the retractor is disposed within the body,

wherein, when a parameter monitored by the sensor is outside a preset range, the signal processor is configured to activate the illumination source to alert a user.

17. The device of claim 1, where the illumination source is configured to alert the user by flashing, blinking, turning off, or changing color.

\* \* \* \* \*

专利名称(译)	手术牵开器		
公开(公告)号	<a href="#">US9125587</a>	公开(公告)日	2015-09-08
申请号	US13/832727	申请日	2013-03-15
[标]申请(专利权)人(译)	霍金斯约翰雷利 PAVENTO NICHOLAS SELOVER SEAN P LECLERC MICHELE		
申请(专利权)人(译)	霍金斯, JOHN RILEY PAVENTO, NICHOLAS SELOVER, SEAN P. 勒克莱尔MICHELE		
当前申请(专利权)人(译)	DePuy公司SYNTHES PRODUCTS, INC.		
[标]发明人	HAWKINS JOHN RILEY PAVENTO NICHOLAS SELOVER SEAN P LECLERC MICHELE		
发明人	HAWKINS, JOHN RILEY PAVENTO, NICHOLAS SELOVER, SEAN P. LECLERC, MICHELE		
IPC分类号	A61B1/32 A61B5/00 A61B1/06 A61B17/02 A61B19/00 A61B17/00 A61B5/145 A61B5/01		
CPC分类号	A61B1/06 A61B5/6847 A61B17/02 A61B17/0206 A61B5/01 A61B5/14503 A61B5/14539 A61B5/14542 A61B5/14546 A61B17/0218 A61B17/0293 A61B19/52 A61B2017/00092 A61B2017/00946 A61B2019/465 A61B2019/521 A61B90/36 A61B2090/065 A61B2090/309 A61B90/06 A61B2090/064 A61B1/0684 A61B1/07 A61B1/32 A61B5/04001 A61B5/746 A61B17/025 A61B2017/00473 A61B2017/0225 A61B2017/0262		
其他公开文献	US20140275792A1		
外部链接	<a href="#">Espacenet</a> <a href="#">USPTO</a>		

摘要(译)

本公开涉及用于手术操纵组织的方法和装置。通常，所述方法和装置可包括细长牵开器轴，所述细长牵开器轴具有远侧牵开器尖端，所述远侧牵开器尖端构造造成操纵组织，例如，所述尖端可构造成分离围绕椎骨的肌肉和神经纤维。细长牵开器轴可包括照明源，使得当装置用于体内时，手术区域的至少一部分被装置照射。传感器也可以或替代地包括在细长牵开器轴上，例如在钝回缩尖端上，使得传感器可以监测手术区域中或附近的组织的生理参数。

