



(19) **United States**

(12) **Patent Application Publication**  
**Kordis et al.**

(10) **Pub. No.: US 2019/0239767 A1**  
(43) **Pub. Date: Aug. 8, 2019**

(54) **BASKET STYLE CARDIAC MAPPING CATHETER HAVING AN ATRAUMATIC, METALLIC TWO-PART DISTAL TIP FOR DETECTION OF CARDIAC RHYTHM DISORDERS**

continuation of application No. 13/409,263, filed on Mar. 1, 2012, now Pat. No. 8,346,339.

(60) Provisional application No. 61/555,190, filed on Nov. 3, 2011, provisional application No. 61/478,340, filed on Apr. 22, 2011.

(71) Applicant: **Topera, Inc.**, Menlo Park, CA (US)

**Publication Classification**

(72) Inventors: **Thomas F. Kordis**, San Diego, CA (US); **Ruchir Sehra**, Scottsdale, AZ (US); **Eric T. Johnson**, Temecula, CA (US); **Darrin J. Kent**, Murrieta, CA (US); **Robert Ryan Ragland**, Temecula, CA (US)

(51) **Int. Cl.**  
*A61B 5/042* (2006.01)  
*A61B 5/00* (2006.01)  
*A61B 18/14* (2006.01)

(73) Assignee: **Topera, Inc.**, Menlo Park, CA (US)

(52) **U.S. Cl.**  
CPC ..... *A61B 5/0422* (2013.01); *A61B 5/6859* (2013.01); *A61B 5/042* (2013.01); *A61B 2018/00267* (2013.01); *A61B 18/1492* (2013.01); *Y10T 29/49117* (2015.01); *A61B 5/6858* (2013.01)

(21) Appl. No.: **16/270,719**


(22) Filed: **Feb. 8, 2019**

(57) **ABSTRACT**

**Related U.S. Application Data**

A system for sensing multiple local electric voltages from endocardial surface of a heart, includes: an elongate tubular member having a lumen, a proximal end and a distal end; a plurality of flexible splines; an anchor for securably affixing the proximal portions of the splines, where the anchor is securably affixed within the lumen of the elongate tubular member at the distal end of the elongate tubular member; and a metallic tip for securably affixing the distal portions of the splines.

(63) Continuation of application No. 14/595,306, filed on Jan. 13, 2015, now Pat. No. 10,244,960, which is a continuation of application No. 13/929,838, filed on Jun. 28, 2013, now Pat. No. 9,504,399, which is a continuation of application No. 13/687,274, filed on Nov. 28, 2012, now Pat. No. 8,504,133, which is a






FIG. 1






FIG. 5




FIG. 6




FIG. 7




FIG. 8




FIG. 9




FIG. 10




FIG. 11




FIG. 12




FIG. 13




FIG. 15




FIG. 14




FIG. 16




FIG. 17




FIG. 20

FIG. 18




FIG. 19




FIG. 21





FIG. 22A

FIG. 22B




FIG. 22C




FIG. 22D




FIG. 23A




FIG. 23B




FIG. 24

FIG. 25




FIG. 26B




FIG. 26A




FIG. 26C




FIG. 26D




FIG. 26E




FIG. 26F




FIG. 27B




FIG. 27C




FIG. 27A




FIG. 27E




FIG. 27D




FIG. 28A




FIG. 28B




FIG. 28C




FIG. 28D




FIG. 30A




FIG. 30B




FIG. 29




FIG. 31A




FIG. 31B




FIG. 31C




FIG. 31D




FIG. 32A




FIG. 32C




FIG. 32B







FIG. 33A

FIG. 33B






FIG. 34D




FIG. 34F




FIG. 34E




FIG. 34G




FIG. 34H





FIG. 34I






FIG. 35C




FIG. 35D




FIG. 35E




FIG. 35F




FIG. 35G







FIG. 35H






FIG. 36D




FIG. 36E







FIG. 36F






FIG. 38A




FIG. 38B






FIG. 39






FIG. 41A




FIG. 41B




FIG. 42A




FIG. 42C




FIG. 42B




FIG. 43A




FIG. 43B

**BASKET STYLE CARDIAC MAPPING  
CATHETER HAVING AN ATRAUMATIC,  
METALLIC TWO-PART DISTAL TIP FOR  
DETECTION OF CARDIAC RHYTHM  
DISORDERS**

**CROSS-REFERENCE TO RELATED  
APPLICATIONS**

[0001] This application is a continuation of U.S. application Ser. No. 14/595,306, filed Jan. 13, 2015, which is a continuation of U.S. application Ser. No. 13/929,838, filed Jun. 28, 2013, now U.S. Pat. No. 9,504,399, which is a continuation of U.S. application Ser. No. 13/687,274, filed Nov. 28, 2012, now U.S. Pat. No. 8,504,133, which is a continuation of U.S. application Ser. No. 13/409,263, filed Mar. 1, 2012, now U.S. Pat. No. 8,346,339, which claims the benefit of U.S. Provisional Application No. 61/555,190, filed Nov. 3, 2011, and U.S. Provisional Application No. 61/478,340, filed Apr. 22, 2011, the contents of all of which are incorporated by reference herein.

**FIELD OF THE INVENTION**

[0002] The present invention is related to the detection of cardiac rhythm disorders by use of basket style cardiac mapping catheters. The present invention is further related to cardiac spline baskets having flexible spline tube assemblies with electrodes.

**BACKGROUND OF THE INVENTION**

[0003] Heart rhythm disorders are very common in the United States, and are significant causes of morbidity, lost days from work, and death. Heart rhythm disorders exist in many forms, of which the most complex and difficult to treat are atrial fibrillation (AF), ventricular tachycardia (VT) and ventricular fibrillation (VF). Other rhythms may be easier to treat, but may also be clinically significant including supraventricular tachycardia (SVT), atrial tachycardia (AT), atrial flutter (AFL), premature atrial complexes/beats (PAC, APC) and premature ventricular complexes/beats (PVC). Under certain conditions, rapid activation of the normal sinus node can even cause a heart rhythm disorder such as inappropriate sinus tachycardia or sinus node reentry.

[0004] Definitive diagnosis has often been performed using electrode-bearing catheters placed within the heart chambers. Electrodes have been positioned along a catheter shaft or basket splines in an attempt to analyze or map the electrical activity within a heart chamber. Mapping typically involves the use or formation external (patches on skin) of electrograms and internal (catheters with electrodes) electrograms. A typical electrocardiogram of the cardiac cycle (heartbeat) consists of a P wave, a QRS complex and a T wave. During normal atrial depolarization, the main electrical vector is directed from the SA node, and spreads from the right atrium to the left atrium. Atrial depolarization is represented by the P wave on the electrocardiogram. The QRS complex reflects the rapid depolarization of the right and left ventricles. The T wave represents the repolarization (or recovery) of the ventricles.

[0005] Devices of the prior art, however, often do not provide a complete and stable map of the electrical activity within a heart chamber (recording electrograms). In particular, electrical activity in certain portions of the right atrium and the left atrium (e.g. atrial septum, region of right

pulmonary veins) are often difficult to map because of the inability of devices of the prior art to adequately conform to the irregular shape of the atria and their varying shapes during beating of the heart. Further, devices of the prior art do not provide dimensionally and/or spatially stable and complete electrograms as the prior art devices often move as the heart beats, thereby moving some or all of the electrodes away from the heart tissue and making the relative position of the electrodes variable to corresponding position of atrial tissue.

[0006] Thus, there is a need in the art for a cardiac mapping catheter that is capable of providing improved and dimensionally and/or spatially stable signals for diagnosis, and more complete coverage of the heart tissue, typically in the form of electrograms.

**SUMMARY OF THE INVENTION**

[0007] The present invention provides devices, systems and methods for the detection of cardiac rhythm disorders by use of a percutaneous catheter designed to permit acquisition of numerous, simultaneous endocardial electrograms from a three dimensional array of surface electrodes, herein referred to as "a basket style cardiac mapping catheter."

[0008] In one embodiment of the present invention, a system for sensing multiple local electric voltages from endocardial surface of a heart, includes: an elongate tubular member having a lumen, a proximal end and a distal end; a plurality of flexible splines having proximal portions, distal portions and medial portions therein between, wherein the splines comprise an outer surface, an inner surface and two side surfaces; an anchor for securably affixing the proximal portions of the splines, wherein the anchor is securably affixed within the lumen of the elongate tubular member at the distal end of the elongate tubular member; a tip for securably affixing the distal portions of the splines; and a polymeric member including opposed a first open end and a second open end defining an open lumen therein between and an inner member surface and an outer member surface, wherein at least one of the plurality of flexible splines is at least partially disposed within the lumen of the polymeric member; a flexible electrode assembly strip with one or more exposed electrodes disposed on at least a portion of the outer surface of the polymeric member; wherein the flexible electrode assembly strip includes: a polymeric substrate having an inner surface and an opposed outer surface; the one or more exposed electrodes disposed over at least part of the outer surface of the polymeric substrate; and one or more electrical traces disposed over at least a portion of the inner surface of the polymeric substrate or over at least a portion of the outer surface of the polymeric substrate, the one or more electrical traces being in electrical communication with the one or more exposed electrodes; wherein a portion of the flexible electrode assembly transitions from the outer surface of the polymeric member towards the inner surface of the polymeric member prior to the anchor; and wherein another portion of the flexible electrode assembly extends through at least a portion of the anchor and into the lumen of the elongate tubular member.

[0009] In one embodiment of the present invention, a system for sensing multiple local electric voltages from endocardial surface of a heart, includes: an elongate tubular member having a lumen, a proximal end and a distal end; a plurality of flexible splines having proximal portions, distal portions and medial portions therein between, wherein the

splines comprise an outer surface, an inner surface and two side surfaces; an anchor for securably affixing the proximal portions of the splines, wherein the anchor is securably affixed within the lumen of the elongate tubular member at the distal end of the elongate tubular member; a tip for securably affixing the distal portions of the splines; and a polymeric member including opposed first and second open ends defining an open lumen therein between and an inner member surface and an outer member surface, wherein at least one of the plurality of flexible splines is at least partially disposed within the lumen of the polymeric member; a flexible electrode assembly strip with one or more exposed electrodes disposed on at least a portion of the outer surface of the polymeric member; wherein the flexible electrode assembly strip includes: a polymeric substrate having an inner surface and an opposed outer surface; the one or more exposed electrodes disposed over at least part of the outer surface of the polymeric substrate; and one or more electrical traces disposed over at least a portion of the inner surface of the polymeric substrate or over at least a portion of the outer surface of the polymeric substrate, the one or more electrical traces being in electrical communication with the one or more exposed electrodes; wherein the first opposed open end of the polymeric member is secured to the distal spline portion of the at least one of the plurality of flexible splines at a position near to the distal tip and the second opposed open end of the polymeric member is secured to the proximal spline portion of the at least one of the plurality of flexible splines at a position near to the anchor; and wherein medial portions of the polymeric member between the first opposed open end and the second opposed open end of the polymeric member are not secured to the medial portions of the at least one of the plurality of flexible splines.

**[0010]** In one embodiment of the present invention, a system for sensing multiple local electric voltages from endocardial surface of a heart, includes: an elongate tubular member having a lumen, a proximal end and a distal end; a plurality of flexible splines having proximal portions, distal portions and medial portions therein between, wherein the splines comprise an outer surface, an inner surface and two side surfaces, wherein the inner and outer spline surfaces have a substantially flat portion with the substantially flat portions being parallel to one and the other, and further wherein the two side spline surfaces are convexly rounded to define a rounded-rectangular shape; an anchor for securably affixing the proximal portions of the splines, wherein the anchor is securably affixed within the lumen of the elongate tubular member at the distal end of the elongate tubular member; a tip for securably affixing the distal portions of the splines; and a plurality of polymeric members each having opposed first and second open ends defining an open lumen therein between, wherein the polymeric members comprise an outer surface, an inner surface and two side surfaces where a cross-sectional profile of the polymeric members is elliptical to match a cross-sectional profile of the rounded-rectangular shape of the splines and is slightly larger than the cross-sectional profile of the rounded-rectangular shape of the splines and wherein each of the plurality of flexible splines is at least partially disposed within the lumen of a different one of the plurality of polymeric members; a flexible electrode assembly strip with one or more exposed electrodes disposed on at least a portion of the outer surface of the polymeric members;

wherein the flexible electrode assembly strip includes: a polymeric substrate having an inner surface and an opposed outer surface; the one or more exposed electrodes disposed over at least part of the outer surface of the polymeric substrate; and one or more electrical traces disposed over at least a portion of the inner surface of the polymeric substrate or over at least a portion of the outer surface of the polymeric substrate, the one or more electrical traces being in electrical communication with the one or more exposed electrodes; wherein a portion of the flexible electrode assembly strip extends through at least a portion of the anchor and into the lumen of the elongate tubular member.

**[0011]** In one embodiment of the present invention, a system for sensing multiple local electric voltages from endocardial surface of a heart, includes: an elongate tubular member having a lumen, a proximal end and a distal end; a plurality of flexible splines having proximal portions, distal portions and medial portions therein between, wherein the splines comprise an outer surface, an inner surface and two side surfaces; an anchor for securably affixing the proximal portions of the splines, wherein the anchor is securably affixed within the lumen of the elongate tubular member at the distal end of the elongate tubular member; a tip for securably affixing the distal portions of the splines; and a plurality of polymeric members each having opposed first and second open ends defining an open lumen therein between and an outer surface and an inner surface, wherein each of the plurality of flexible splines is at least partially disposed within the lumen of a different one of the plurality of polymeric members; a flexible electrode assembly strip with one or more exposed electrodes disposed on at least a portion of the outer surface of the polymeric members; wherein the flexible electrode assembly strip includes: a polymeric substrate having an inner surface and an opposed outer surface; the one or more exposed electrodes disposed over at least part of the outer surface of the polymeric substrate; and one or more electrical traces disposed over at least a portion of the inner surface of the polymeric substrate or over at least a portion of the outer surface of the polymeric substrate, the one or more electrical traces being in electrical communication with the one or more exposed electrodes; wherein the flexible electrode assembly strip is compressed into the outer surface of the polymeric member; and wherein the flexible electrode assembly strip is thermally or adhesively bonded to the outer surface of the polymeric member.

**[0012]** These and other features and advantages of the present invention will become apparent from the following detailed description of illustrative embodiments thereof, which is to be read in connection with the accompanying drawings. Corresponding reference element numbers or characters indicate corresponding parts throughout the several views of the drawings.

#### BRIEF DESCRIPTION OF THE DRAWINGS

**[0013]** FIG. 1 is a perspective view of the basket style cardiac mapping catheter system of the present invention.

**[0014]** FIG. 2 is a side elevational view of the basket style cardiac mapping catheter system of FIG. 1, according to the present invention.

**[0015]** FIG. 3 is a schematic view of an introducing catheter of the prior art useful for delivery of the basket style cardiac mapping catheter of FIG. 1 and guide catheter of FIG. 4 into a bodily lumen or organ.

[0016] FIG. 4 is a schematic view of a guide catheter of the prior art useful for delivery of the basket style cardiac mapping catheter of FIG. 1 into a bodily lumen or organ.

[0017] FIG. 5 is an expanded, partial cross-sectional view of a portion of the basket of the system of FIG. 1 showing an expanded basket beyond and outside a hemostat penetrator and/or a guide catheter, according to the present invention.

[0018] FIG. 6 is an expanded, partial cross-sectional view of a portion of the basket of the system of FIG. 1 showing a radially compressed basket within a hemostat penetrator and/or a guide catheter, according to the present invention.

[0019] FIG. 7 is an expanded side view of a portion of the basket of the system of FIG. 1 showing M-shaped, symmetric distal splines, according to the present invention.

[0020] FIG. 8 is a perspective view of the M-shaped basket embodiment of FIG. 7, according to the present invention.

[0021] FIG. 9 is a right side view of the M-shaped basket embodiment of FIG. 7 depicting symmetric spline angles, according to the present invention.

[0022] FIG. 10 is a perspective view of the basket of the system of FIG. 1 showing M-shaped, non-symmetric distal splines according to a basket embodiment of the present invention.

[0023] FIG. 11 is a right side view of the M-shaped basket embodiment of FIG. 10 depicting non-symmetric spline angles, according to the present invention.

[0024] FIG. 12 is a side elevational view of one of the splines of the M-shaped basket of FIG. 7 showing proximal spline recurves, according to the present invention.

[0025] FIG. 13 is a perspective view of the spline of FIG. 12, according to the present invention.

[0026] FIG. 14 is an exploded side view of a distal portion of the spline of FIG. 12, according to the present invention.

[0027] FIG. 15 is an exploded side view of a proximal portion of the spline of FIG. 12, according to the present invention.

[0028] FIG. 16 is an exploded right side view of a portion of the distal portion of the spline of FIG. 12 showing a distal thinned portion, according to the present invention.

[0029] FIG. 17 is an expanded side view of another embodiment of a basket of the system of FIG. 1 showing M-shaped distal spline portion and proximal tangential spline curves, according to the present invention.

[0030] FIG. 18 is an expanded side view of another embodiment of a basket of the system of FIG. 1 showing a distal spline D-shaped curve and proximal recurves, according to the present invention.

[0031] FIG. 19 is a perspective view of the spline of FIG. 18, according to the present invention.

[0032] FIG. 20 is an exploded view of a distal portion of the spline of FIG. 18, according to the present invention.

[0033] FIG. 21 is an expanded side view of another embodiment of a basket of the system of FIG. 1 showing a distal spline D-shaped curve and proximal tangential spline curves, according to the present invention.

[0034] FIGS. 22A through 22D depict thinned side view spline portions, according to the present invention.

[0035] FIG. 23A depicts side view of a portion of a spline in a neutral position having buckle points, according to the present invention.

[0036] FIG. 23B depicts side view of a portion of a spline in a deflected position having buckle points, according to the present invention.

[0037] FIG. 24 is a schematic illustration of a spline emerging from a distal tip at an acute angle, according to the present invention.

[0038] FIG. 25 is a schematic illustration of a spline emerging from a distal tip at a substantially perpendicular angle, according to the present invention.

[0039] FIG. 26A is a front perspective view of a two-part, welded distal tip, according to the present invention.

[0040] FIG. 26B is a rear perspective view of the distal tip of FIG. 26A, according to the present invention.

[0041] FIG. 26C is a front perspective view of a top part of the distal tip of FIG. 26A, according to the present invention.

[0042] FIG. 26D is a bottom view of the top part of the distal tip of FIG. 26A, according to the present invention.

[0043] FIG. 26E is a front perspective view of a bottom top part of the distal tip of FIG. 26A, according to the present invention.

[0044] FIG. 26F is a front perspective view of another embodiment of a two-part, welded distal tip having a rounded or domed upper portion, according to the present invention.

[0045] FIG. 27A is a front perspective view of an encapsulated, filament wound distal tip, according to the present invention.

[0046] FIG. 27B is a side elevation view of the distal tip of FIG. 27A, according to the present invention.

[0047] FIG. 27C is a rear perspective view of the distal tip of FIG. 27A, according to the present invention.

[0048] FIG. 27D is a top perspective view of the filament wrapping of the distal tip of FIG. 27A, according to the present invention.

[0049] FIG. 27E is a rear perspective view of the filament wrapping of the distal tip of FIG. 27A, according to the present invention.

[0050] FIG. 28A is a side cross-sectional view of another embodiment of a two-part distal tip with half splines, according to the present invention.

[0051] FIG. 28B is a side cross-sectional view of another embodiment of a two-part distal tip with half splines, according to the present invention.

[0052] FIG. 28C is a side cross-sectional view of another embodiment of a two-part riveted distal tip with full splines, according to the present invention.

[0053] FIG. 28D is a top view of aligned splines useful with the distal tip of FIG. 28C, according to the present invention.

[0054] FIG. 29 is a side elevational view of an encapsulated distal tip, according to the present invention.

[0055] FIG. 30A is a top view of a membrane distal tip, according to the present invention.

[0056] FIG. 30B is a partial cross-sectional view of the membrane tip of FIG. 30A.

[0057] FIG. 31A is a perspective view of a slotted proximal anchor, according to the present invention.

[0058] FIG. 31B is a right cross-sectional view of the slotted anchor of FIG. 31A, according to the present invention.

[0059] FIG. 31C is an exploded, partial side elevation view of the slotted anchor of FIG. 31A, according to the present invention.

[0060] FIG. 31D is a partial cross-sectional view of the slotted anchor of FIG. 31A securable disposed with a portion of the catheter body of the system of FIG. 1, according to the present invention.

[0061] FIG. 32A is a depiction of a proximal portion of a spline having a spline notch, according to the present invention.

[0062] FIG. 32B is a schematic illustration of an anchor useful for securing the spline of FIG. 32A, according to the present invention.

[0063] FIG. 32C is a partial exploded view of the anchor of FIG. 32B according to the present invention.

[0064] FIG. 33A is an exploded, perspective of the basket of the system of FIG. 1 showing splines with spline tube assemblies, according to the present invention.

[0065] FIG. 33B is a side elevational view of the basket of FIG. 33A, according to the present invention.

[0066] FIGS. 34A and 34B are cross-sectional views of a portion of the spline tube assembly of FIG. 33A, according to the present invention.

[0067] FIG. 34C is an exploded cross-section view of the spline of FIGS. 34A and 34B, according to the present invention.

[0068] FIG. 34D is a cross-sectional view of a spline tube assembly with a radiopaque marker, according to the present invention.

[0069] FIG. 34E is a cross-sectional view of the radiopaque marker of FIG. 34D, according to the present invention.

[0070] FIG. 34F is a partial cross-sectional view of a spline tube assembly along the length of the spline tube assembly with a radiopaque marker, according to the present invention.

[0071] FIG. 34G is a representation of a fluoroscopic image of a side elevation view of a basket with radiopaque marker arrangement to depict spline and electrode locations, according to the present invention.

[0072] FIG. 34H is a representation of a fluoroscopic image of a perspective view of the basket of FIG. 34G, according to the present invention.

[0073] FIG. 34I is a representation of a fluoroscopic image of a rotated side view of the basket of FIG. 34G, according to the present invention.

[0074] FIG. 35A is a perspective view of spline tube assembly, according to the present invention.

[0075] FIG. 35B is another perspective views of spline tube assembly, according to the present invention.

[0076] FIG. 35C is an exploded perspective view of a spline tube assembly, according to the present invention.

[0077] FIG. 35D is an exploded, partial cross-sectional view of a proximal portion of the spline tube assembly, according to the present invention.

[0078] FIG. 35E is an exploded, partial cross-sectional view of a distal portion of the spline tube assembly, according to the present invention.

[0079] FIG. 35F is an exploded, partial cross-sectional view of a proximal portion of the spline tube assembly showing two flex circuits embedded with a wall of the spline tube assembly, according to the present invention.

[0080] FIG. 35G is an exploded, partial cross-sectional view of a proximal portion of the spline tube assembly showing one flex circuit embedded with a wall of the spline tube assembly, according to the present invention.

[0081] FIG. 35H is an exploded, partial cross-sectional view of a portion of the spline tube assembly showing a flex circuit transitioning into an inner lumen of the spline tube assembly, according to the present invention.

[0082] FIG. 36A is a top view of a flex circuit, according to the present invention.

[0083] FIG. 36B is a bottom view of the flex circuit of FIG. 36A, according to the present invention.

[0084] FIG. 36C is an exploded, right bottom view of a portion of the flex circuit of FIG. 36A, according to the present invention.

[0085] FIG. 36D is an exploded, left top view of a portion of the flex circuit of FIG. 36A, according to the present invention.

[0086] FIG. 36E is an exploded, left bottom view of a portion of the flex circuit of FIG. 36A, according to the present invention.

[0087] FIG. 36F is schematic, cross-sectional view of a portion of the flex circuit of FIG. 36A, according to the present invention.

[0088] FIG. 37A is a top view of another embodiment of a flex circuit, according to the present invention.

[0089] FIG. 37B is an exploded, right top view of a portion of the flex circuit of FIG. 37A, according to the present invention.

[0090] FIG. 37C is an exploded, right bottom view of a portion of the flex circuit of FIG. 37A, according to the present invention.

[0091] FIG. 38A is a perspective view of a flex circuit embedded or pressed into a substrate, according to the present invention.

[0092] FIG. 38B is a partial, side cross-sectional view of the flex circuit of FIG. 38A, according to the present invention.

[0093] FIG. 39 is a top view of another embodiment of a flex circuit, according to the present invention.

[0094] FIG. 40A is a partial perspective view of a quad wire assembly with a flex circuit, according to the present invention.

[0095] FIG. 40B is a partial cross-sectional view of the quad wire assembly with a flex circuit of FIG. 40A, according to the present invention.

[0096] FIG. 41A is a partial cut-away perspective view of a catheter shaft with a braided shield and anti-kink beading, according to the present invention.

[0097] FIG. 41B is a partial cut-away perspective view of another embodiment of a catheter shaft with a braided shield and anti-kink beading, according to the present invention.

[0098] FIG. 42A is a side elevational view of asymmetric catheter basket FIG. 13, according to the present invention.

[0099] FIG. 42B is a front elevational view of a symmetric basket, according to the present invention.

[0100] FIG. 42C is a front elevational view of an asymmetric basket, according to the present invention.

[0101] FIG. 43A is an electrogram obtained with the catheter basket system of the present invention.

[0102] FIG. 43B is an electrogram obtained with a catheter basket system of the prior art.

#### DETAILED DESCRIPTION OF THE PREFERRED EMBODIMENTS

[0103] FIG. 1 is a perspective view of basket style cardiac mapping system or assembly 10 of the present invention, and FIG. 2 is a side elevation view of the catheter system or

assembly 10 of FIG. 1. As depicted in FIGS. 1 and 2, the catheter system or assembly 10 consists of three subassemblies: the mapping catheter assembly 8, including hemostat penetrator assembly 25, and the extension cable assembly 31. The mapping catheter assembly 8 includes a spline basket 12, which includes splines 14 with spline tube assemblies (not shown) having electrodes (not shown); a catheter body or shaft 20; a hemostat penetrator assembly 25 (comprised of a hemostat penetrator tube 22 and hemostat penetrator handles 24); a handle strain relief 26; a handle 28, with an integral connector (not shown). The extension cable assembly 31 includes a mating connector 30 and an extension cable 32; interrelated as shown. The catheter assembly 8 allows ease of operation and precise positioning and control of the basket 12 within a patient. Desirably, connector 30 is round so there is no rotational bias as the basket 12 is disposed within a patient. A non-round connector grip, for example a rectangular connector grip (not shown) may provide a rotational bias which, if desired, may be used with the present invention. The mating connector cable assembly 31 is useful for connecting the catheter assembly 8 to external devices (not shown), such as devices that receive and analyze electrical signals from the catheter system 10. The strain relief section 26 is useful in providing kink resistance to the catheter body 20 especially when the catheter assembly 8 is disposed within a patient.

[0104] The splines 14 of the spline basket 12 are secured by a distal tip 16 at one end, i.e. the distal end, of the basket 12, and are further secured by a proximal anchor 18 at an opposed end, i.e. the proximal end, of the basket 12. The anchor 18 is secured to a distal end 20B of the catheter body 20 and/or within a lumen 20C of the catheter body 20 of the catheter 8 of the present invention. The proximal end 20A of the catheter body 20 is secured to the strain relief section 26 of the handle 28.

[0105] The spline basket 12 is deliverable through and into bodily organs, such as but not limited to the right atrium of a heart. One useful delivery technique includes the Seldinger delivery technique. The Seldinger techniques uses a short introducing catheter, such as the introducing catheter 34 as depicted in FIG. 3, and a longer catheter, such as the catheter 46, which may also be referred to as an guide catheter or delivery sheath when described with the system 10 of the present invention, as depicted in FIG. 4. The introducing catheter or introducer 34 is typically fairly short at about six inches in length and is used to navigate through muscle and into a desired vein. The catheter 46 is typically a long guide sheath, typically 60 mm to 80 long. In a typical Seldinger technique, a vessel or cavity is punctured with a sharp hollow needle or trocar (not shown). If desired, a guidewire (not shown) may be then advanced through the lumen of the trocar, and the trocar is withdrawn. The introducing catheter 34 may then be passed over the guidewire into the cavity or vessel. The introducing catheter 34 includes a hollow introducer lumen 36. The distal end 42 of the introducing catheter 34 is positioned with a vessel or cavity. The proximal end 44 of the introducing catheter 34 remains outside of the patient so as to allow a practitioner to control the position of the distal end of the introducing catheter 42. The proximal end 44 of the introducing catheter 34 may include a hemostat valve 38 and a saline flush lumen 40. The catheter lumen 48 of the guide catheter 46 is deliverable through the lumen 36 of the introducing catheter 34 to a desired bodily site. The guide catheter 46 includes a distal end 54 and a proximal end

56. The guide catheter 46 may also include a proximal hemostat valve 50 and a saline flush lumen 52.

[0106] As used herein the term “proximal” generally refers to a location or direction towards the practitioner. The term “distal” generally refers to a location or direction away from the practitioner. Further, the terms inner, inward and the like generally refer to a direction toward the inside of the basket 12, for example towards a longitudinal axis L between the distal tip 16 and the proximal anchor 18. The terms outer, outward and the like generally refer to a direction away from the inside of the basket 12, for example away from a longitudinal axis L between the distal tip 16 and the proximal anchor 18.

[0107] In preparation for insertion of the basket catheter 8, the basket 12 is collapsed within the hemostat penetrator tube 22 of the hemostat penetrator assembly 25. The distal end 23 of the hemostat penetrator is insertable through the hemostat valve 50 of the Guide catheter 46. The basket 12 and a portion of the catheter body 20 are advanced and deliverable through lumen 48 and past the distal end 54 of the catheter 46. Typically, the strain relief portion 26, the handle 28, the mating connector 30 and the connector 32 of the system 10 of the present invention remain outside of the body or proximally past the proximal end 56 of the catheter 46. Upon withdrawal of the hemostat penetrator tube 22 from the guide sheath hemostat valve 50, the guide sheath hemostat valve with create a leak-proof seal against the outer wall of the catheter body 20, preventing the loss of blood through the introducer system.

[0108] FIGS. 5 and 6 depict an embodiment of the distal end of the basket style cardiac mapping catheter 8 of the present invention. As depicted in FIG. 5 the spline basket 12 is deliverable through and past the distal end 54 of the lumen 48 of the catheter 46 and deliverable through and past the distal end 23 of the hemostat penetrator 25, which also has an open lumen. The distal end 23 of the hemostat penetrator 25 is useful for penetrating the hemostat valve 56 on the proximal end of the guide catheter 46.

[0109] As depicted in FIG. 5, the splines 14 of the spline basket 12 are in an expanded state, such as a radially expanded state. The overall shape of the expanded basket 14 is depicted as being an expanded, non-cylindrical shape. While the expanded splines 14 are depicted in a spherical or somewhat spherical orientation, the present invention is not so limited. Indeed, in preferred embodiments of the present invention the expanded splines 14 assume a non-spherical or substantially non-spherical shape, preferably asymmetric, especially but not limited to the spline portions near the distal tip 16 and/or the spline portions near the proximal anchor 18. Such overall shapes are non-limiting, and other overall basket shapes, including substantially spherical shapes, asymmetric spherical shapes, non-spherical shapes, non-spherical asymmetric shapes and the like may suitably be used.

[0110] As depicted in FIG. 6, the splines 14 of the spline basket 12 may be in a compressed state within the lumen 48 of the guide catheter 46 and/or of the lumen of the hemostat penetrator tube 22. The splines 14 are depicted in FIG. 6 as being in a compressed approximate or substantial elongate cylindrical shape. In such a compressed state the effective length of the splines 14 between the distal tip 16 and the proximal anchor 18 are substantially the same. Effective spline lengths between the distal tip 16 and the proximal anchor 18 in the expanded basket shape of, for example,

FIG. 5 are not so limited and, if desired, may vary as described in further detail below.

[0111] FIG. 7 is an expanded side view of a portion of the basket 12 of the system 8 of FIG. 1 showing M-shaped, symmetric distal splines, according to the present invention. The distal basket portion 70 has distal spline portions 66 secured to one and the other by the distal tip 16. The proximal basket portion 68 contains proximal spline portions 62. The proximal spline ends 60 are secured by the proximal anchor 18 (not shown). Medial basket portions 72 and medial spline portions 64 are disposed between the respective ends.

[0112] As depicted in FIG. 7, the splines 14, including medial portions 64 of the splines 14, expand or bow outwardly to assume an expanded, non-cylindrical shape, with the basket 12 having a proximal basket portion 68, a distal basket portion 70 and a medial basket portion 72 there between. While the expanded splines are depicted in a spherical or somewhat spherical orientation, the present invention is not so limited. Indeed, in preferred embodiments of the present invention the expanded splines 14 assume a non-spherical or substantially non-spherical shape, preferably asymmetric.

[0113] FIG. 8 is a perspective view of the basket 12 of FIG. 7. Although eight splines 14 are depicted, the basket 12 of the present invention may have any useful number of splines. FIG. 9 is a right side view of the M-shaped basket embodiment of FIG. 7 depicting symmetric spline angles. As depicted in FIG. 9, the angles,  $\theta 1$  through  $\theta 8$ , are all approximately equal at  $45^\circ$ . Such a relationship is a predetermined angular relationship to offer a symmetric or substantially symmetric basket 12 as viewed from a cross-sectional plane of the basket 12.

[0114] The present invention, however, is not so limited. For example, as depicted in FIGS. 10 and 11, a predetermined angular relationship where the angles,  $\theta 1$  through  $\theta 8$ , may vary may suitably be used. As depicted in FIG. 11, the angles  $\theta 1$  and  $\theta 5$  are approximately  $90^\circ$ , and the angles  $\theta 2$  through  $\theta 4$  and  $\theta 6$  through  $\theta 8$  are approximately  $30^\circ$ . These angles are non-limiting and any suitable arrangement of angles may be used. Such a non-symmetric angular relationship as depicted in FIGS. 10 and 11 may be useful, if desired, to concentrate a greater number of splines 14 at a particular location within the body, for example the right atrium of the heart.

[0115] FIG. 12 is a side elevational view of one of the splines 14 of FIG. 7 showing the M-shaped distal curve 74 of basket 12 at the distal spline portion 66. The spline 14 also contains a proximal recurve 76 at the proximal spline portion 62. Further the spline 14 is also depicted as being symmetric in its expanded state about a longitudinal axis L, which is determined by the line segment axis from the proximal anchor 18 to the distal tip 16. FIG. 13 is a perspective view of the spline 14 of FIG. 12, further depicting the spline curvatures at the proximal spline portion 62 and the distal spline portion 66.

[0116] FIG. 14 is an exploded view of the distal M-shaped spline curve 74. The M-shaped spline curve 74 contains distal incurvate inward bends 78 and excurvate outward bends 80. Bend 78 is described as incurvate and/or inward because an apex 79 is directed towards the interior of the basket 12. Bend 80 is described as excurvate and/or outward because apex 81 is directed away from the interior of the basket 12. Bends 78 are useful in controlling angles from

which splines 14 exit from or emerge into the distal tip 16, i.e., directed toward the exterior of basket 12. The bends 80 turn the splines 14 back in a proximal direction towards the proximal anchor 18.

[0117] FIG. 15 is an exploded view of the proximal spline portion 62 of the spline 14 of FIG. 12. The proximal spline portions 62 contain proximal recurves 76. The proximal recurves 76 include proximal incurvate bends 82 having apices 83 and proximal excurvate bends 84 having apices 85. The proximal recurves 76 impart several important features to the basket 12 of the present invention. The proximal recurves 76 allow for the geometry and flexibility of individual splines 14 to vary at the proximal end 62 which allows the basket 12 to become asymmetric and to better conform to the contours of the right atrium, as described in conjunction with FIG. 42A below. Further, the proximal recurves 76 allow for better placement of electrodes (not shown) at the proximal atrial tissue. Baskets common in the prior art do not often have good contact with proximal atrial tissue, thereby adversely effecting electrical activity detection thereat. Furthermore, the flexibility and geometry of the recurves 76 also permit enhanced electrode-tissue contact for the electrodes placed not only on the proximal spline portions 62, but also on the medial spline portions 64 and distal spline portions 66.

[0118] FIG. 16 is an exploded view of the distal spline portion 66. The splines 14 may contain portions of reduced spline widths 88 as compared to normal or non-reduced spline widths 86. Here the reduced spline widths 88 are depicted as being near the distal spline portion 66. Such reduced widths 88 may increase spline flexibility, as these spline portions are proximal to the distal tip 16 (not shown). The distal spline portion 66 may also include an alignment member 89 which, as described further below, is useful for aligning and/or securing the splines 14 within the distal tip 16 (not shown). The reduced width portions 88 at the spline distal portions also allows for less force to compress the basket 12, as depicted in FIG. 6, during removal of the basket 12 from the patient. Further, the reduced spline widths 88 aid in the basket 12 in achieving the substantially cylindrical shape, as depicted in FIG. 6. In other words, as compression of the basket 12 within a lumen 22, 48 goes from the medial basket portions 72 towards the distal basket portions 70, the reduced spline widths 88 allows the distal incurvate bends 78 to flex outward or away from the compression force so that the distal spline portions 66 do not retain the inward bends 78, or simply stated the bends 78 pop outward during radial compression of the basket 12. Another advantage of the distal M-Shaped spline curve 74 is that the distal tip 16 is directed towards the interior of the basket 12 when the basket 12 is deployed or is in its radially expanded state. This feature, if desired, keep the distal tip 16 away from distal heart tissue as the distal spline portions 66 may extend beyond the distal tip 16 in the longitudinal direction of the basket 14.

[0119] FIG. 17 is another embodiment of the spline 14 of FIG. 12. The spline 14 of FIG. 17 contains proximal tangential curves 90. While the tangential curve 90 may not offer the same degree of spline flexibility and basket stability as offered by the proximal spline recurve 76, such a proximal tangential curve 90 may be preferred by some practitioners in certain atrial procedures.

[0120] FIG. 18 is a side elevational view of another spline 14 useful with the present invention. The spline 14 in FIG.

**18** has a similar proximal spline recurve **76** as the spline **14** of FIG. **12**. However, the spline **14** of FIG. **18** has a D-shaped **92** distal end portion **66**. Such a D-shaped distal end **92** is useful with certain embodiments of distal tips **16** that are described below. FIG. **19** is a perspective view of the spline of FIG. **18** showing spline curvatures in further detail. FIG. **20** is an exploded view of the D-shaped spline portion **92** of FIG. **18**. The distal spline portion **66** has substantially flat portions **94** followed by the curved portions **96**. The curved portions **96** merge into the normal curvature of the overall basket shape. The substantially straight portion **94** are useful with certain distal tip **14** designs and where spline emergence or entrance angles at the distal tip **14** are desired to be about  $90^\circ$ .

[0121] FIG. **21** depicts yet another spline **14** embodiment. The spline **14** of FIG. **21** contains D-shaped distal portions **94**, **96** at the distal spline portion **66** and proximal tangential curves **90** at the proximal spline portion **62**. Thus, the assembly **10** of the present invention may use any combination of the above-described spline geometries.

[0122] Splines **14** may be flattened splines through the body of the spline **14** having a substantial rectangular shape with rounded sides (see, e.g., FIG. **34C**). Throughout at least a major portion of the splines **14**, the splines **14** may be about 0.013 to about 0.035 inches wide (**W1**) and about 0.002 to about 0.012 inches thick (**T1**), as depicted in FIGS. **22A** through **22D**. A preferred width (**W1**) is about 0.022 inches. Spline thickness (**T1**) may depend on the overall size of the basket **12** with small sized baskets, for example less than 60 mm in nominal diameter, the thickness may range from about 0.002 inches to about 0.010 inches, with 0.004 inches being preferred. For larger size baskets, for example greater than 60 mm in nominal diameter, the thickness may range from about 0.002 inches to about 0.012 inches, with 0.006 inches being preferred. These dimensions are not limiting and represent normal or typical spline width portions **86** and spline thickness portions **98**.

[0123] Some portions of the splines **14** may have reduced width portions **88** and/or reduced thickness portions **100**. Typically, these portions **88**, **100** are disposed at distal spline portions **66** near or at the distal tip **16**. However, the present invention is not so limited at these reduced portions **88**, **100** may be present in proximal spline portions **62** and medial spline portions **64**. The thinned spline portions **88**, **100** may have a reduction in width and or thickness of several thousands of an inch. For example, the thickness (**T2**) of certain spline portions **100** may be thinned down to several thousands of an inch or to a thickness of about 0.003 inches to 0.004 inches, or less. Such thinning of the distal spline segments **66** near the membrane tip **14** reduces stresses during capture of the splines **14** within the guide catheter **34**. Low stress is an advantageous feature during collapse for introduction, repositioning and withdrawal of the spline basket. The width (**W2**) of the narrowed spline segments **88** may be narrowed from about 0.013 to 0.035 inches to about 0.008 to 0.014 inches. Such thinning aids the splines **14**, when they fold up or collapse into the guide catheter **34**, to overcome their tendency to push themselves apart and avoid them occupying more space in the catheter **34**. Thus, a low profile catheter system **10** may be provided according to the present invention.

[0124] FIGS. **23A** and **23B** depict a spline portion, such as spline portion **86**, having a buckle point **102**. The buckle point **102** may be ground into the spline **14** or formed by any

other suitable technique. The buckle point **102** is depicted as an inwardly curved notch, but other designs may suitably be used. As depicted in FIGS. **23A** and **23B**, the buckle points **102** provide the splines **14** with curvature inflection points, which provide the basket **12** with improved matching of the contours of the interior of the heart. The buckle points **102** may be disposed at any location along the proximal spline portions **62**, the medial spline portions **64** and/or the distal spline portions **66** shown in FIG. **21**. Further, the number or frequency of buckle points **102** may also vary.

[0125] As depicted in FIGS. **24** and **25**, the splines **14** may emerge from the distal tip **16** at any useful emergence angle,  $\alpha$ , with respect to the longitudinal axis **L**, which is defined by a line segment from the proximal anchor **18** to the distal tip **16**. For example, as depicted in FIG. **24**, the emergence angle  $\alpha$  may be about  $45^\circ$  or less than about  $45^\circ$ . As depicted in FIG. **25**, the emergence angle  $\alpha$  may be about  $90^\circ$ . The splines **14** may include a bend **78** which is useful for, among things, controlling the shape of the expanded splines **14** or basket **12**. The distal tip **16** shown in FIGS. **24** and **25** is merely a schematic depiction of a general tip. Any of the below-described distal tips of the present invention may be used with any of the emergence angles described in conjunction with FIGS. **24** to **25**. The angles are non-limiting, and any suitable emergence angle or combination of emergence angles may be used.

[0126] FIGS. **26A** through **26F** depict a two-part welded distal tip **16**, according to the present invention. FIG. **26A** is a front perspective of distal tip **16**; FIG. **26B** is a back or rear perspective of distal tip **16**; FIG. **26C** is perspective view of a top part of the distal tip **16**; FIG. **26D** is a bottom view of the top part of the distal tip **16**; FIG. **26E** is a top perspective view of the bottom part of distal tip **16**; and FIG. **26F** depicts an alternate embodiment of the distal tip **16**.

[0127] As depicted in FIGS. **26A** through **26E**, distal tip **16** may include a top part **104** and a bottom part **108**. The distal portions **66** of the splines **14** are securably disposed within the distal tip **16**. The top surface **106** of the top part **104** may have any suitable shape, such as a substantially flat surface **106** with rounded edges so that the distal tip **16** is an atraumatic tip, i.e., a tip that will not cause damage to atrial tissue. The bottom part **108** likewise should be free of any sharp edges or projections to avoid atrial tissue damage. The top part **104** and the bottom part **108** are secured to one and the other by any suitable means. One non-limiting means and useful means is welding the two parts together to provide a unitary distal tip **16**. Such securement is typically performed after proper placement of the distal spline portions **66** within the distal tip **16**.

[0128] As depicted in FIGS. **26C** through **26D**, the top part **104** of the distal tip **16** may include spline alignment posts **110**. The spline alignment posts **110** are spaced apart so that the splines **14** may fit between the spline alignment channels **112**. The spline alignment posts **110** do not extend completely into the center of the distal tip **16**, but terminate to provide a center spline alignment portion **114** of the top part **104** of the distal tip **16**. The center spline alignment portion **114** is useful for receiving the spline alignment members **89** of the distal portions **66** of the splines **14** into that region **114** of the distal tip **16**. The combination of the center spline alignment portion **114** and the spline alignment channels **112** provide for, among other things, securably holding the splines **14** in any desired predetermined angular relationship. The number of spline alignment posts **110** may vary as

the number of splines 14 may vary within the distal tip 16. The bottom part 108 of the distal tip 16 may contain flat top and inner surface 116. The surface 116 may generally correspond to the bottom surfaces of the spline alignment posts 110. The bottom part 108 may also include a raised central portion 118. Desirably this raised central portion 118 is substantially flat. The raised portion 118 is sized so that it can be disposed within the center spline alignment portion 114 of the top part 104 of the distal spline 16.

[0129] While the splines are securably held within the distal tip 16, the spline alignment channels 112 allow some movement of the spline 14. For example, spline portions may move upward and or downward with the spline alignment channel 112 to provide flexibility of the splines 14 at the distal tip 16. If desired, an elastomeric material may also be placed within the two-part distal tip 16 to minimize tip voids and open spaces.

[0130] As depicted in FIG. 26F, the two-part distal tip 16 may include a rounded or domed upper 106' of the top part 104'. Such a rounded or domed design may be useful in providing more rounded surfaces for the atraumatic distal tip 16.

[0131] The distal tip 16 of FIGS. 26A through 26F may be made of any suitable biocompatible material. Although metal materials are preferred, plastic materials may be used.

[0132] FIGS. 27A through 27C depict an alternate embodiment of the distal tip 16 of the present invention, i.e., a filament wound and encapsulated distal tip 120, in which FIG. 27A is a front perspective view of the filament wound and encapsulated distal tip 120; FIG. 27B is a side view of the filament wound and encapsulated distal tip 120; and FIG. 27C is a back or rear perspective view of the filament wound and encapsulated distal tip 120. FIGS. 27D and 27E are exploded views of the filament wrapping for the filament wound and encapsulated distal tip 120, in which FIG. 27D is a top perspective view thereof and FIG. 27E is a back or rear perspective view thereof. The filament 124 is wrapped over, under and between the splines 14 and over and under the spline alignment members 89 to secure the splines 14 in any desired predetermined angular relationship.

[0133] The splines 14 are secured to each other at the filament wound and encapsulated distal tip 120. Tip 120 may be described as being a "filament wrapped and encapsulated" or a "suture wrapped and encapsulated" tip 16. Tip 120 is not limited to the use of suture materials and any suitable filaments, threads, wires and the like may be suitably used. Advantageously, the filament wound and encapsulated distal tip 120 is a low profile tip. Further, filament wound and encapsulated distal tip 120 has no open spaces, such as slots or holes, common with some basket catheters of the prior art. Such open spaces or holes present in tips of the prior art allow for entry of blood cells, thereby causing or having the potential to cause blood clot formation or thrombogenesis. As described below, the splines 14 are secured to each other at their circular alignment members 89 by the use of a suture(s) 124, filament(s) 124, wire(s) 124 or thread(s) 124. Multiple sutures 124, filaments 124, wires 124 or threads 124 may be used. After the splines 14 are so secured, the circular alignment members 89 of the splines 14, including the securing suture(s) 124, filament(s) 124, wire(s) 124 or thread(s) 124 are fully or substantially or partially encapsulated with an encapsulant 122 to provide the filament wound and encapsulated distal tip 120.

[0134] As depicted in FIGS. 27D and 27E, the circular tip spline alignment portions 89 of the splines 14 are aligned or substantially aligned with each other. Filament(s) 124 are laced, looped or wound between, over and under the splines 14 at the circular tip spline alignment portions 89. A single filament or multiple filaments 124 may be used. Advantageously, the filament(s) 124 is laced, looped or wound between every adjacent spline portion. As depicted in FIGS. 27D and 27E, the filament(s) 124 is laced, looped or wound about opposite spline intersections or alternating spline intersections and then is crisscrossed in a similar fashion until all or substantially all of the spline intersection locations are secured.

[0135] The filament 124 may include any suitable material. The use of high tensile strength fibers, such as electrospun, braided or monofilament may be used. Some non-limiting examples include, but are not limited to, for example: Dyneema Purity® (Ultra High Molecular Weight Polyethylene or UHMWPE), Spectra® fiber (UHMWPE), Polyethyleneterephthalate or PET, polypropylene, etc. Metallic wires, such as stainless steel or nitinol, may also be used, but non-metallic fibers are preferred for their greater flexibility. The filament(s) 124 may be tied or twisted together to secure the circular tip or alignment portions 89 of the splines 14. The filament(s) 124 may be twisted or tied together at locations interior to the spline basket 12. The tied together circular tip or alignment portions 89 and the filament(s) 124 are then encapsulated with an encapsulant 122. One useful encapsulant 122 is polyurethane, but other biocompatible encapsulants may suitably be used. The encapsulant 122 is also disposed between the spline intersection points to provide the tip 120 of the present invention.

[0136] Some advantages of the filament wound and encapsulated distal tip 120 of the present invention include, but are not limited to improved flexibility over tips of the prior art; reduced thrombogenicity; significantly smaller overall tip size; transparency under fluoroscopy; no MR artifacts; superior strength, i.e., equal to or greater than 15 times the strength of steel of the same diameter; superior adhesive bond strength; resistance to cutting (scissor action); and very small diameters, as low as 25 decitex (dtex).

[0137] As depicted in FIGS. 27A through 27C, the filament wound and encapsulated distal tip 120 has an atraumatic profile with a smooth, somewhat rounded upper surface, an inwardly contoured bottom surface and smooth side surfaces. The amount of encapsulant 122 may be minimized to provide maximum spline flexibility.

[0138] FIG. 28A depicts another embodiment of the distal tip 16 in which two-part welded distal tip 126 with half splines is provided. As depicted in FIG. 28A, two-part tip 126 includes a top portion 128 insertable through a bottom portion 130. A space or detent is provided in either or both portions 128, 130 so that distal ends 67 of the splines 14 may be securably inserted therein. The portions 128, 130 of the two-part tip 126 are securably joined together to securably affix the distal spline ends 67 therein. The portions 128, 130 of the two-part tip 126 may be secured to each other by spot welds 132, but other securing techniques may suitably be used. Although the splines 14 are depicted as emerging from the sidewall of the two-part tip 126, the present invention is not so limited. If desired, the splines 14 may emerge from the top portion 128 (not shown) and/or the bottom portion 130 (not shown). The emergence angle of the splines 14 from the two-part tip 126 may include any of the above-

described emergence angles. The splines **14** depicted in FIG. **28A** may be referred to as half-splines because these splines have both distal spline ends **67** and proximal spline ends **60**.

[0139] FIG. **28B** depicts another embodiment of the distal tip **16**, in which a nitinol shrink ring tip **134** according to another aspect of the present invention. Spline ends **67** may be disposed within the tip **134**. The tip **134** has a compression ring **138** and a core post **136**. The spline ends **67** are disposed within and secured by the tip **134**. The ring **138** may be made from metallic, nitinol shape memory metal, shrink tubes. It may be machined at room temperature to design specifications, and then chilled so it can be expanded and stored. One may slip the ring **138** over the mated spline ends **67** and post **136** and assemble quickly. As the ring **138** comes up to room temperature it shrinks and provides a very strong compression fitting to secure the spline **14** within the tip **134**.

[0140] FIG. **28C** depicts a tip **140** which may also be used with the present invention. A cap **144** and a base **146** may be secured to each other, by for example spot welding, via a square rivet **142**. The square rivet **142** is passed through alignment square holes **148** punched in splines **14**, as depicted in FIG. **28D**. The splines **14** do not directly pass through the distal tip members **144**, **146**. In other words, the splines **14** do not pass through a sidewall of tip **140**, as no sidewall is present between the distal tip members **144**, **146**.

[0141] In another embodiment of the present invention, the tips of the present invention may include a magnetic tip (not shown). With previously described constraining tips spline lengths should be about identical in order for the basket to collapse evenly into guide catheter. If atrium outline shape deviates from approximately cylindrical or oval, then equal length splines may not contact all endocardial surfaces. A way to circumvent this problem is to allow the splines to be of different lengths (to match the atria), and allow the tip to “assemble” itself in situ when deploying. The tip may also “disassemble” itself when being captured into the guide catheter. This design may be achieved by using a small magnetic portion on each spline that “self assemble” themselves into a tip when deployed from the guide catheter, and disassemble themselves (i.e., magnets pull apart) when the basket is collapsed into the guide catheter. It may be necessary to place an elastic thread between each magnet, pulling them close enough for magnetic force to pull into assembly. If the splines follow the inside wall of the heart during diastole, then the splines need to buckle or deform during systole. The buckling will bring parts of the spline out of contact with the endocardium. Deformation will move the electrodes to different locations on the endocardium, confusing the mapping software. Note that, during atrial fibrillation, the heart remains close to its diastolic dimensions during its entire contraction cycle. This reduces the significance of this effect, making the basket design easier. In order for the basket to collapse into the guide catheter the splines need to be the same length but would need to be different lengths in order to follow locally distended parts of the atrium. A magnetic tip would disassemble as the catheter goes into the guide catheter. An elastic thread could be used between them so that the magnetic field then grabs them the rest of the way.

[0142] FIG. **29** depicts another embodiment of a distal tip **16**, in which an encapsulated tip **150** is provided. The encapsulated tip may include any suitable flexible and/or elastomeric material. The overall profile of the tip **150** may

be larger than for the filament and encapsulated tip **120** as tip **150** may not contain any filament wrapping or securement means. The encapsulated or molded tip **150** may be made from any suitable material. In one embodiment of the present invention, the encapsulated or molded tip **150** may be made from polyurethane, polyester block amide or silicone.

[0143] FIGS. **30A** and **30B** depict another embodiment of the distal tip **16**, in which a membrane distal tip **152** is provided. The membrane tip **152** may include an inner membrane or film **156** and an outer membrane or film **154** for securing the distal portions **66** of the splines **14**. The distal portions **66** of the splines **14** may simply cross each other between the two membranes **154**, **156**. The membranes **154**, **156** may be bonded, for example adhesive bonding, thermal bonding, and the like, together to provide the membrane tip **152**.

[0144] The splines **14** may simply cross within the membrane tip **152**. No separate connection between the splines **14** within the membrane **152** is needed. If desired, a connection (not shown) between the splines **14** may be provided. The inner membrane **156** and the outer membrane **154** may be adhesively bonded to all splines **14** within the membrane tip **152**. Further, the inner membrane **156** and outer membrane **154** may be adhesively bonded to each other at locations between the splines **14**. All elements may then be placed into fixture (not shown) so as to ensure the proper linear and angular orientation of the elements and then heat bonded together.

[0145] The present invention is not limited to the use of the inner membrane **156** and outer membrane **154** to form the membrane tip **152**. Additional membrane layers or films may be used. The membrane tip **152** may have any suitable shape, for example a circular shape, an octagonal shape, and the like. Further, matched diameter adhesive pads (not shown) may be placed between splines **14** to add additional support beyond just membranes **154**, **156**. The adhesive pads between the splines **14** at the membrane tip **152** may fill in gaps between splines **14**, thereby providing a slightly larger area for adhesive bonding, if desired. Thus, in either embodiment the width and/or thickness of the tip membrane **152** is minimal, i.e., less than the thickness of the splines **14**, or about the same thickness of the splines **14** or even just slightly larger than the thickness of the splines **14**. In any case, the tip membrane **152** does not have an appreciable sidewall as compared to the tips of the prior art.

[0146] Further, the tip membrane **152**, including the inner membrane **156** and outer membrane **154**, may be made from any suitable polymeric material, preferably non-elastic polymeric material, including flexible non-elastic polymeric material. In one embodiment the membranes **154**, **156** may be made from a polyimide material. Desirably, the membranes **154**, **156** are not made from polytetrafluoroethylene, i.e., PTFE, including expanded polytetrafluoroethylene, i.e., ePTFE.

[0147] FIGS. **31A** through **31D** depict an embodiment of the proximal anchor **18** of the present invention, in which a slotted proximal anchor is provided. FIG. **31A** is a perspective view of the proximal end **160** of the slotted anchor **158**. FIG. **31B** is a cross-section view of the distal end **162** of the slotted anchor **158** taken along the **31B-31B** axis. Slotted anchor **158** has an open diameter or open lumen **164**. The open diameter or lumen **164** allows wires, flex circuits, etc. from the spline basket **12** to pass through the anchor **158**.

The proximal end **160** of the slotted anchor **158** presses into an inner diameter or lumen of a catheter shaft **20C** or is otherwise connected to the catheter shaft **20**. Anchor **158** also includes spline-receiving slots **168**. The number of spline-receiving slots **168** typically is equal to the number of proximal spline end portions **60**, and is shown in these drawings as a quantity of eight. As depicted in FIGS. **31A** and **31B**, the spline-receiving slots **168** may be evenly spaced to allow for the basket splines **14** to be equally spaced in the desired angular position. The present invention, however, is not so limited, and any number of proximal spline end portions **60** and spline-receiving slots **168**, oriented at any desired relative angles may suitably be used.

[**0148**] One function of the anchor **158** is to attach the basket splines **14** to the catheter **20** and orient the splines **14** to give the basket **12** the proper shape and ensure it remains straight (not bent) upon collapse into the guide catheter **46**. The anchor device **158** is a means by which to orient the basket splines **14** on the proximal end **68** of the spline basket **12** and to fasten them together. Additionally, the anchor **158** affixes the basket splines **14** to the catheter shaft **20**. The anchor **158** may be fabricated from a single piece of material, e.g., a hypotube, or multiple sections that are attached (i.e. welded, glued, etc.) together. The slots **168** are sized to fit the basket splines **14** and the slot length ensures splines **14** are positioned accurately, which aids in even collapsing of the basket **12**. The slots **168** have adequate length to allow for the variable positioning of the basket splines **14**. The basket splines **14** may be attached to the anchor **158** by adhering with glue, welding, crimping or the like. Additionally, a ring (not shown) may be slid over the anchor **158** to hold the basket splines **14** in place. The outer ring (not shown) may be crimped, swaged, welded, glued, etc. to the outside **166** of the anchor **158** or the outside of the catheter shaft **20**. The angular spacing of the slots **168** may be varied to accommodate the amount or number of basket splines **14** to be attached as well as to get the desired spacing of basket splines **14**. As depicted in FIG. **31B**, one typical angular spacing is 45° degrees. The proximal end **160** of the anchor **158** is sized to press fit into a catheter shaft. It can be changed to accommodate any desired catheter dimensions. Additionally, the proximal end **160** can have geometry to mechanically lock the anchor into the catheter shaft (i.e., barb(s), serrated edges, ribs, etc.). The inner diameter or lumen **164** of the anchor **158** is open to allow for catheter wiring, flex circuits, etc. to pass through the catheter shaft. Additionally, the wiring, flex circuits, etc. could be, if desired, run on the outer diameter of the anchor device **158**. Additionally, when the splines **14** are inserted into the anchor **158** and it is press fitted into the catheter shaft **20C**, the anchor **158** locks into the catheter shaft **20C** to enable the shaft **20** to be rotated without the basket **12** slipping inside the catheter shaft **20C**. Some non-limiting advantages of the anchor **158** of the present invention include, but are not limited to, ease of allowing fastening or gathering of basket splines **14** made of any material; may be fabricated from any suitable material or multiple materials; allows for variable positioning (length and angular) of the basket splines **14** to ensure even collapsing into the recovery sheath device; and provides sufficient clearance for device wiring. Further, as depicted in FIG. **31D**, the anchor **158** may include a hemostat plug **170** into which a spline tube **172**, which may contain a spline **14**, passes to provide a sealed proximal

spline tube lumen. The hemostat plug **170** may also be useful in securing the slotted anchor **158** to the catheter shaft **20**. [**0149**] FIGS. **32A** through **32C** depict another embodiment of a proximal anchor **18** of the present invention, in which an anchor **176** is provided. The spline **14** may contain a notch **174** at the spline proximal end **60**. The anchor **176** includes an inner ring **181** having spline alignment slots **180** through which the spline ends **60** may pass. The spline ends **60** are interlocked with the anchor **176** via the spline notch **174** and alignment detent **184**. This interlock provides both excellent pull out retention and automatic, accurate alignment of all splines **14** with respect to each other so that they collapse neatly and reliably into the guide catheter **46** during introduction and removal of the catheter **20**. Once the splines **14** interlock with the anchor **176**, a second thin-walled tubing **178** is inserted over the anchor **176**. This tube **178** prevents the splines **14** from disengaging their interlocks in the anchor **181**. A complete lack of applicable forces on the internal anchor ring, adhesive and a slight interference fit between the external anchor and internal anchor rings prevents pull out of the inner anchor during use.

[**0150**] FIG. **33A** is a perspective view of the basket **12** showing spline tubes **172** having spline tube assemblies **185** and exposed electrodes **186**. FIG. **33B** is a side elevational view of the basket **12** of FIG. **33A**. The spline tubes **172** are disposed over the splines **14** except at distal basket portion **70** where the splines **14** emerge from the distal tip **16**. The exposed electrodes **186** are spaced along spline distal portions **66**, spline medial portions **64** and spline proximal portions **62**. The number of exposed electrodes **186** may vary. The electrodes **186** are part of a flex electrode circuit **188**, which will be described in further detail below.

[**0151**] FIGS. **34A** and **34B** are exploded partial cross-sectional views of the spline tubes **172** and spline tube assemblies **185**. The splines are disposed within a lumen **208** of the spline tubes **172**. As depicted in FIGS. **34A** and **34B** the splines **14** are not fixed to lumen **208** of the spline tube **172**. The spline tube **172** may be slidably assembled over the spline **14** to provide some interference there between. The spline tube **172** may desirably include a flexible material so that the lumen **208** of the spline tube **172** takes an elliptical shape substantially matching the cross-sectional extents of the spline **14**.

[**0152**] FIG. **34C** depicts a cross-section of the spline **14** of the present invention. As depicted in FIG. **10**, spline **14** may have a flat or substantially flat upper surface **190**, a flat or substantially flat lower surface **192**, and rounded sidewalls **194**, **196**. The present invention, however is not so limited, and the upper surface **190** and/or the lower surface **192** may be rounded or otherwise have curvature, including concave and/or convex curvatures. The splines **14** desirably include and/or are made of a super-elastic material so that the splines bow outwardly into the basket shape **12**, including asymmetric basket shapes. Any suitably super-elastic material may be used. Preferably, the splines include or are made of nitinol. If desired, the spline material may also be a shape memory material, such as but not limited to shape memory nitinol. Further, the splines **14** may be about 0.013 to about 0.025 inches wide and about 0.002 to about 0.010 inches thick. These dimensions are non-limiting and other dimensions may suitably be used.

[**0153**] FIGS. **34D** through **34F** depict radiopaque markers **198** useful with the spline tubes **172** and spline tube assemblies **185** of the present invention. As depicted in these

figures, the radiopaque marker **198** may be disposed over a portion of the spline **14** that is near an electrode **186**. Desirably, the radiopaque marker **198** is securably fixed to the spline **14**. A significant useful feature of the current design over prior art is the radiotransparency of the flex circuit electrodes **186** (described below). This feature allows the separation of the fluoroscopic images of the splines and electrodes provided by the radiopaque markers **198** from the signal gathering function of the electrodes. This feature allows distinguishable patterns of electrode markings to be produced under fluoroscopy without modifying or compromising the electrogram gathering performance of the electrodes **186**.

[0154] FIGS. **34G** through **34H** depict a non-limiting arrangement of radiopaque markers **198** with the spline basket **12** of the present invention. The number of radiopaque markers **198** may vary along each spline **14** and may vary from spline to spline. These figures represent the two-dimensional shadowgraphs produced by fluoroscopy. FIG. **34G** is a side perspective view of the basket **12** under fluoroscopy. Each spline **14** has four radiopaque markers **198** identifying a particular electrode on a particular spline **14**. For example, the four radiopaque markers **198** at **S1E8** refers to the unique combination set of {spline **1**, electrode **8**}; at **S2E7** refers to {spline **2**, electrode **7**}; at **S3E6** refers to {spline **3**, electrode **6**}; at **S4E5** refers to {spline **4**, electrode **5**}; at **S5E4** refers to {spline **5**, electrode **4**}; at **S6E3** refers to {spline **6**, electrode **3**}; at **S7E2** refers to {spline **7**, electrode **2**}; and at **S8E1** refers to {spline **8**, electrode **1**}. In addition other electrodes **186** are marked with one marker **198** or two markers **198**. Generally, even numbered splines have two markers **198** at each electrode position, and the odd numbered splines have one marker **198** at each electrode position not marked with the four markers. Such an arrangement, as depicted in FIG. **34H** allows a practitioner to easily note the orientation of the basket **12** under fluoroscopy, including the location of the distal tip **16** and all of the electrodes **198**. FIG. **34I** depicts that when the basket **12** of FIG. **34G** is rotated, individual splines **14** and electrodes **186** become apparent with the placement of the radiopaque markers **198**. For example, in FIG. **34I**, the identity of each pair of crossed splines (**S7** & **S8**, **S1** & **S6**, **S2** & **S5**, **S3** & **S4**) would be ambiguous on one side of the crossing if each electrode were marked with a single RO marker. Further, a portion of the catheter body **20** (not shown) may also include radiopaque markers (not shown) to further aid the practitioner under fluoroscopy.

[0155] FIGS. **35A** through **35H** depict the spline tubes **172** with the spline tube assemblies **185** of the present invention. As depicted in FIG. **35A**, the spline tube **172** is an elongate tubular member. The spline tube **172** or spline tube assembly **185** includes a proximal end **200** and a distal end **202**. As depicted in FIG. **35A**, a portion of the spline **14** may emerge from the tube distal end **202**, where it may engage the distal tip **16**. The present invention, however, is not limited to flexible tube assemblies **185** only with the use of the basket **12**. The flexible spline tube assemblies **185** may be used by them themselves or with any other device where electrical activity within a body is to be monitored. In some cases spline tube assembly **185a** may not need to have a spline portion **14** or similar component exiting from the distal end **202**. The spline tube assembly **185** of FIG. **35A** has two flex circuits **188**, each with four electrodes **186**, mounted sequentially on the spline tube **172**, while the spline tube assembly

of FIG. **35B** has one flex circuit **188** with eight electrodes **186**. These numbers of flex circuits and electrodes are non-limiting.

[0156] FIG. **35C** is a partial exploded view of the spline tube assemblies **185**, **185a** of FIGS. **35A** and **35B**. As depicted in FIG. **35C**, the spline tube assemblies **185**, **185a** may include a first flex circuit **188a** having electrodes **186** and a second flex circuit **188c** also having electrodes **186**. The first flex circuit **188a** may have a transition portion **188b** where the first flex circuit **188a** transitions to a position on the tube **173** below that of the second flex circuit **188c**. In such a manner, multiple flex circuits may be placed on the tubes **172**, while still orienting the electrodes **186** in substantially one direction, typically in an outward direction from the spline basket **12**.

[0157] As depicted in FIGS. **35D** and **35E**, the proximal end **200** of the spline tube **172** may be sealed with a plug **204** of material. The material may be an adhesive, polymer or any other useful material having sealing characteristics. The distal end **202** of the tube **172** may also be sealed with a plug **206** of material. Such sealing closes the internal lumen **208** of the spline tube **172** against the flow of fluids, including body fluids, such as blood. Such sealing also secures the spline tube **172** to the spline **14**. The present invention, however, is not limited to having just the proximal end and/or distal end so sealed or secured and intermediate portions may also be so sealed or secured.

[0158] As depicted in FIGS. **35F** and **35G**, the flex circuit portions **188a**, **188b** and **188** exiting the spline tubes **172** may be embedded into the wall of the spline tube **172**. The present invention is, however, not so limited and as depicted in FIG. **35H**, a portion of the flex circuit **188** may transition from the outer surface **208A** and past the inner surface **208B** so that it is disposed within the lumen **208** of the tube **172**. The spline tube **172** and the spline tube assembly **185** may comprise a biocompatible polymer such as a polyether block amide material, such as Pebax®. Other flexible biocompatible polymers, such as polyesters, silicones (e.g. Silastic®), silicone rubber, urethanes (e.g. Texin® and Pellethane®), and the like may suitably be used.

[0159] FIGS. **36A** through **36E** depict an embodiment of the flex circuit **188** as a flex circuit strip **212** of the present invention. The flex circuit **212** includes a proximal end **214** and a distal end **216**. Towards the distal end **216** is an electrode-containing portion **218**. The medial portion **220** may be free of electrodes. The flex circuit strip **212** may contain wings **222**. These wings are useful in securing the flex circuit **212** to tubular members, such as spline tubes **172**, especially where it is desirable to keep the electrodes **186** as substantially unidirectional flat electrodes. The flex circuit or electrode assembly strip **188** may have a thickness from about 0.001 inches to about 0.010 inches, more desirably from about 0.005 inches to about 0.008 inches.

[0160] FIG. **36A** is a top view of the flex circuit strip **212** showing electrodes **186** disposed on the upper surface **224** of the flex circuit substrate **236**. The flex circuit substrate or polymeric substrate **236** may comprise a polyimide material, such as KAPTON polyimide available from DuPont, which is suitable for short term (single use medical device) or long term (medical implant) contact with skin, tissue or blood, depending on the intended application, but other suitable materials may be used, such as the above-described materials for the spline tube **172** or the spline tube assembly **185**. At the proximal end **214** electrical pads are disposed on the

upper surface 224. FIG. 36B is a bottom view of the flex circuit strip 212. Electrical traces 228 are disposed on the bottom surface 226 of the substrate 236. The traces run from location underneath the electrodes 186 to locations underneath the electrical pads 232. As depicted in FIGS. 36C through 36E, metal plated holes or vias 230 electrically connect individual traces to individual electrodes 186. In a similar fashion vias 234 connect individual electrical traces 228 to individual electrical pads 232.

[0161] As depicted in FIG. 36F, the flex circuit 212 may contain upper surface coverlays 238 to cover those areas of the upper substrate surface 236A not having electrodes 186 or connection pads 232. Likewise, if desired, bottom surface coverlays 240 may cover part or all of the electrical traces 228. Upper coverlays 238 and lower coverlays 240 are bonded to the substrate 236 with the use of suitable adhesive 239, usually acrylic adhesive. Desirably, the upper flex circuit axis S is substantially smooth, i.e., the coverlays 238 and the electrodes 186 being substantially the same height. The present invention, however, is not so limited, and electrodes may be raised slightly above the substrate surface with the use, for example, of strips of material disposed between the substrate 236 and the electrodes 186. Alternatively, the electrodes may be depressed slightly below the substrate surface, as shown in FIG. 36F. The coverlays 238, 240 may comprise a similar material as the substrate 236, but different materials may suitably be used.

[0162] FIGS. 37A through 37C depict an alternate embodiment of the flex circuit 188.

[0163] As depicted, electrical traces may run on both sides of the flex circuit substrate 236. For example, four electrodes, 186a, 186b, 186c and 186d are depicted in FIG. 37A. In the top view of FIGS. 37A and 37B no electrical traces run on the upper surface 224 between the electrodes 186. However, proximal to the electrodes, electrical traces 228 for two electrodes 186c, 186d run on the upper surface 224, and the electrical traces for the other electrodes 186a, 186b run on the bottom surface 226 of the flex circuit substrate. The electrical trace 228 for electrode 186c transitions from the bottom surface 226 to the upper surface 224 by means of a trace-to-trace via 244. Such an arrangement of electrical traces 228 as depicted in FIGS. 37A through 37C may make for a more overall compact flex circuit.

[0164] FIGS. 38A and 38B depict a flexible electrode assembly strip 247. The flexible electrode assembly strip includes a flex circuit or electrode assembly strip 188, 236 pressed into the substrate 246 of a flexible polymeric material, such as any of the above-described materials for the spline tube 172 or the spline tube assembly 185. The flex circuit or electrode assembly strip 188, 236 may also be thermally, compressively and/or adhesively bonded onto or into the substrate 246. While the substrate 246 is depicted as being a strip or being planar, the present invention is not so limited. The substrate could be tubular with or without an open lumen. As depicted in FIG. 38B the electrode assembly strip 188, 236 is pressed into the substrate wall 246b while leaving a substantially smooth upper surface 246A and lower surface 246C. If desired portions of the flex circuit 188, 236, for example those portions not containing electrodes, may be disposed between multiple two or more substrates 246, either in planar or tubular form. When covering the electrodes with a cover or substrate of polymeric material, it is desirable to remove cover or substrate material so that the electrodes 186 remain exposed.

[0165] All components, i.e., splines, electrode flex circuits, electrode elevation strips (used to raise the surface of the electrodes above the substrate, if desired; not shown), radiopaque marker strips are desirably thin, flat, planar elements. In a simple design, these elements may be stacked and adhesively bonded to each other. Alternately, a length of flexible tubing or membrane can be slid over the bonded spline/radiopaque marker/flex circuit/electrode elevation strip in order to contain all parts within a single body. This tube or membrane can be shrunk in place for a tight, contained fit using either heat shrink tubing or tubing that is chemically expanded (e.g., by absorption of alcohol or other chemical) for assembly, and then contracts when the chemical evaporates.

[0166] FIG. 39 depicts yet another alternate embodiment of a flex circuit 188 having laterally staggered electrodes 186.

[0167] FIGS. 40A and 40B depict the use of quad wires 248 which connect proximal end 214 of the flex circuit 188. Individual quad wires 248 are connected to individual electrical pads 232 at the proximal ends 214 of the flex circuits. The quad wires 248 then are routed through the catheter body 20 and handle 28 to the catheter connector located at the proximal end of the handle 28.

[0168] FIGS. 41A and 41B depict a portion of the catheter shaft 20 as having a braided shield 250 that minimizes possible electro-magnetic interference from outside sources. The catheter 20 may also have anti-kink beading sections 252 or 254, which provide greater support to prevent kinking of the catheter 20. Flexibility of the catheter body 20 may also be controlled which advantageously aids in having the basket 12 more closely match the contours of the heart.

[0169] FIGS. 42A through 42C further depict asymmetric basket shapes for basket 12. FIG. 42A is a side view of the asymmetric basket shape is depicted. The basket shape is asymmetric in this view in that, among other things, the basket shape is not spherical and/or the proximal spline portions 62 may contain different degrees of curvature or bends 82, 84. These bends 82, 84, also known as a dimple end and/or a puckered end, allows the basket 12 to compress when the heart contracts. In other words, the proximal portion 68 of the basket 12 is designed with greater flexibility to ensure, among other things, improved contact of the splines 14 with interior surfaces of the heart wall.

[0170] While one overall basket shape is depicted in FIG. 42A, it may be desirable to have different basket shapes, for example, a right atrial basket shape and a left atrial basket shape. These different baskets may have different basket outline shapes and therefore different compliances of the individual splines. These differences may allow each shape to optimally conform to the differently shaped left atrium and right atrium. In addition, each shape may come in several different overall sizes. Note that the specific shape shown in FIG. 42 is not intended to represent an "atrial shaped basket", but is instead an arbitrary shape that illustrates the design features required to fabricate an asymmetric basket that will successfully collapse within a guide catheter.

[0171] FIGS. 42B and 42C are an end views of the basket 12 of FIG. 42A. As depicted in FIG. 42B, all spline portions are substantially equidistant from the center longitudinal axis L and/or tip 16 or are substantially in the center of the overall basket outline C as depicted. As depicted in FIG. 42C, all spline portions are not substantially equidistant from the center longitudinal axis L and/or tip 16 or are not

substantially in the center of the overall basket outline C as depicted. Such asymmetry provides for improved basket performance by more closely matching the shape of the atria of the heart. The splines 14 in FIG. 42A have an equal or substantially equal longitudinal length. The varying distances of the medial portions 64 of the splines from the center longitudinal axis L results from, in part, the flexibility of the splines 14 at the proximal spline portions 62 due to the inclusion of the bends 82, 84. While the longitudinal lengths of the splines 14 are equal or substantially equal in FIG. 42A if the basket 12 is in its compressed state, the present invention is not so limited, and splines 14 of varying lengths may be suitably used. Such varying lengths may be achieved by imparting geometries to different bends 82, 84. For example, some bends may have greater inward longitudinal extents than other bends such that, when compressed with the guide catheter 46, all the splines 14 of the basket 12 have an equal or substantially equal net line segment between the anchor 18 and the tip 16. When the basket 12 is expanded, the bends 82, 84 may “relax” and provide a basket assembly 12 with splines 14 of net different lengths, for example spline 14a having an effective longer length than spline 14b. Such asymmetry provided by, in part, splines 14 of varying lengths provide for a closer matching of the shape of the basket 12 with interior portions of the heart, i.e., the atria, as the heart is beating.

[0172] In a similar fashion, the bends 78, 80 at the distal basket portion 70 also provide for asymmetry, if desired. As depicted, both proximal and distal spline portions 62, 66 may have different recurves or incurvate bends to more effectively match the shape of a typical atrium. Different proximal recurves with different lengths and/or angles compensate for different spline lengths so that the basket may be disposed within the guide catheter where the splines would have the same or about the same effective length when the basket is compressed, but will have different effective lengths when the basket is expanded.

[0173] The apparatus, system or devices of the present invention may include electrodes are configured as Monophasic Action Potential (MAP) electrodes, where a single electrode at each site is configured to intimately contact the tissue, and a second electrode at each site is configured to face away from the tissue, acting as an MAP “reference” electrode. An electronic Data Acquisition System may be configured to record the electrograms produced by the catheter as MAP electrograms. The electronics Data Acquisition System may also be selected to record the electrograms produced by the catheter as either standard unipolar electrograms, bipolar electrograms or as MAP electrograms. Further, the electrodes may be configured as Modified Monophasic Action Potential (m-MAP) electrodes, where a single electrode at each site is configured to intimately contact the tissue, and a second electrode placed intermediate between two or more sensing (i.e., tissue facing) electrodes, which is configured to face away from the tissue, acting as an MAP “reference” electrode for multiple sensing electrodes. The curvature of the splines is specifically chosen to match the curvature of a “typical” atrium for the purpose of enhancing electrode to tissue contact, producing the contact force required for quality MAP mapping. The splines may be curved at the proximal end with different length segments in order to compensate for the different spline lengths that result from matching the splines to the shape of a typical atrium; where equal spline total length

(tissue contact segment plus recurve segment) is required to allow collapsibility for introduction and withdrawal of the catheter through the second elongate tube.

[0174] FIGS. 43A and 43B are bipolar electrograms 262, 264 obtained from animal studies. In FIG. 43A the electrograms 262 were obtained from the use of the system 10 of the present invention. In FIG. 43A, the atrial signals 258 are much larger than the ventricular signals 260 on electrodes A3, A5, A7, B7 and C3. Further in FIG. 43A, the atrial signals 258 are approximately equal to the ventricular signals 260 on electrodes B5, C1 and C5. Moreover, in FIG. 43A, the electrogram traces I, aVF and V1 are not basket signals. In general the atrial signals 258 are much larger than or equal to the ventricular signals 260. This allows a practitioner to more easily map the atrial signals within the heart to locate heart tissue causing heart fibrillations. The practitioner may suitably ablate such areas.

[0175] FIG. 43B depicts electrograms 264 obtained from animal studies using a commercially available prior art basket catheter. In FIG. 43B, atrial signals 258 are absent on electrodes A1, A5 and A7. Also in FIG. 43B, the atrial signals 258 are smaller than the ventricular signals 260 on electrodes A3, B5 and B7. Further in FIG. 43B, the atrial signals 258 are approximately equal to the ventricular signals 260 on electrode B3. Still further in FIG. 43B, the atrial signal 258 are larger than ventricular signals 260 on electrodes B1, C1, C3 and C5. Moreover, in FIG. 43B, the electrogram traces I, aVF and V1 are not basket signals. In general, the atrial signals 258, when present, are much smaller than ventricular signals 260 on some electrodes, but may also be larger on other electrodes. The recorded signals of FIG. 43A represent a significant improvement over the recorded signals of FIG. 34B. While not being bound by any theory, it is believed that the substantially flat, single sided flex electrodes 186 of the present invention with the described flex circuits and spline tube assemblies, superior contact and contact force generate higher atrial signals from the heart while reducing the ventricular signals from the heart.

[0176] Further, the improved basket geometries of the present invention also contribute to improve mapping of the atrial signals as the baskets of the present invention are not only more stable within the atrium of the beating heart, but also can flex and contour to the varying complexities of the beating heart.

[0177] The devices of the present invention may suitably be used to detect or map cardiac rhythm disorders. Details of methods for detecting or mapping cardiac rhythm disorders may be found in U.S. Provisional Application No. 61/342,016, filed on Apr. 8, 2010, entitled “Methods, System And Apparatus For The Detection, Diagnosis And Treatment Of Biological Rhythm Disorders”, which published as U.S. Patent Application Publication No. 2011/0251505 A1 for its corresponding Non-Provisional application Ser. No. 13/081,411, the contents of all which are incorporated herein by reference.

[0178] The following aspects, embodiments, and the like are part of the detailed description for the present invention. Embodiments directed to distal tip embodiments include, but are not limited to, as follows:

[0179] In one embodiment, a system (10) for sensing multiple local electric voltages from endocardial surface of a heart is provided. The system may comprise a first elongate tubular member (20) having a lumen (20C), a proximal end

(20A) and a distal end (20B); and a basket assembly (12) comprising: a plurality of flexible splines (14) for guiding a plurality of exposed electrodes (186), the splines (14) having proximal portions (62) and distal portions (66); an anchor (18) for securably affixing the proximal portions (62) of the splines (14); said anchor (18) being secured at the distal end (20B) of the first elongate tubular member (20); an encapsulated and filament-wrapped distal tip (16, 120) comprising an encapsulant (122) and a filament (124) for securably affixing the distal portions (66) of the splines (14) in a predetermined angular relationship at said distal tip (16, 120); wherein the splines (14) comprise a superelastic material; and wherein the basket assembly (12) has a radially expanded non-cylindrical shape. The system (10) of may further comprise: a second elongate tubular member (46) having a lumen (48), a proximal end (56) and a distal end (54); wherein the basket assembly (12) is slidably compressible to fit within the lumen (48) of the second elongate tubular member (46); wherein the basket assembly (12) has a substantially cylindrical shape when compressed within the lumen (48) of the second elongate tubular member (46); and wherein the basket assembly (12) has said radially expanded non-cylindrical shape when not compressed within the lumen (48) of the second elongate tubular member (46) and disposed past the distal end (54) of the second elongate tubular member (46). The encapsulant may have a smooth, non-thrombogenic outer surface free of voids and slots which would permit the passage or entry of blood thereto. The encapsulant (122) may comprise a thermoplastic material. The encapsulant (122) may also comprise a polyurethane material. The filament (124) may comprise a polymeric filament, a metallic filament or combinations thereof. The filament (124) may be laced, looped or wound between, over and under the splines (14) to substantially align and secure the distal portions (66) of the splines (14) in said predetermined angular relationship. The flexible splines (14) may further comprise alignment members (89) at the distal portions (66) of the splines (14); and wherein the filament (124) is also laced, looped or wound between, over and under the alignment members (89). The alignment members (89) may comprise circular portions at the distal spline portions (66). The angles ( $\theta_1$ - $\theta_8$ ) between said splines (14) at said distal tip (16, 120) forming said predetermined angular relationship may be all substantially equal to each other. Alternatively, at least one angle ( $\theta_1$ - $\theta_8$ ) between said splines (14) at said distal tip (16, 120) forming said predetermined angular relationship may be different from another angle ( $\theta_1$ - $\theta_8$ ) between said splines (14) at said distal tip (16, 120). When basket assembly (12) is in said radially expanded non-cylindrical shape, the splines (14) may extend beyond the distal tip (16, 120) and may comprise excurvate bends (80) beyond the distal tip (16) to bend the splines (14) back towards the anchor (18).

[0180] In one embodiment, a system (10) for sensing multiple local electric voltages from endocardial surface of a heart, may comprise: a first elongate tubular member (20) having a lumen (20C), a proximal end (20A) and a distal end (20B); and a basket assembly (12) comprising: a plurality of flexible splines (14) for guiding a plurality of exposed electrodes (186), the splines (14) having proximal portions (62) and distal portions (66); an anchor (18) for securably affixing the proximal portions (62) of the splines (14); said anchor (18) being secured at the distal end (20B) of the first elongate tubular member (20); a distal tip (16, 150) com-

prising an elastomeric material for securably affixing the distal portions of the splines (14) in a predetermined relationship at said distal tip (16, 150); wherein the splines (14) comprise a superelastic material; and wherein the basket assembly (12) has a radially expanded non-cylindrical shape. The system may further comprise: a second elongate tubular member (46) having a lumen (48), a proximal end (56) and a distal end (54); wherein the basket assembly (12) is slidably compressible to fit within the lumen (48) of the second elongate tubular member (46); wherein the basket assembly (12) has a substantially cylindrical shape when compressed within the lumen (48) of the second elongate tubular member (46); and wherein the basket assembly (12) has said radially expanded non-cylindrical shape when not compressed within the lumen (48) of the second elongate tubular member (46) and disposed past the distal end (54) of the second elongate tubular member (46). The distal tip (16, 150) may have a smooth, non-thrombogenic outer surface free of voids and slots which would permit the passage or entry of blood there into. Angles ( $\theta_1$ - $\theta_8$ ) between said splines (14) at said distal tip (16, 150) forming said predetermined angular relationship may be all substantially equal to each other. Alternatively, at least one angle ( $\theta_1$ - $\theta_8$ ) between said splines (14) at said distal tip (16, 150) forming said predetermined angular relationship is different from another angle ( $\theta_1$ - $\theta_8$ ) between said splines (14) at said distal tip (16, 150). The elastomeric material may comprise polyurethane, silicone and combinations thereof.

[0181] In one embodiment, a system (10) for sensing multiple local electric voltages from endocardial surface of a heart, may comprise: a first elongate tubular member (20) having a lumen (20C), a proximal end (20A) and a distal end (20B); a basket assembly (12) comprising: a plurality of flexible splines (14) for guiding a plurality of exposed electrodes (186), the splines (14) having proximal portions (62) and distal portions (66); an anchor (18) for securably affixing the proximal portions (62) of the splines (14); said anchor (18) being secured at the distal end (20B) of the first elongate tubular member (20); a distal tip (16, 150) comprising a flexible material for securably affixing the distal portions of the splines (14); wherein the basket assembly (12) has a radially expanded non-cylindrical shape; wherein the splines (14) comprise a superelastic material; wherein said flexible material comprises a material selected from the group consisting of an elastomeric material, a non-elastic polymeric material, a thermoplastic material and combinations thereof; and wherein the splines (14) approach the tip (16) at an angle (a) of less than about 45° as measured from a line segment between the anchor (18) and the tip (16) along a longitudinal axis (L) between the proximal anchor (18) and the distal tip (16, 150). The system (10) of embodiment 19, may further comprise: a second elongate tubular member (46) having a lumen (48), a proximal end (56) and a distal end (54); wherein the basket assembly (12) is slidably compressible to fit within the lumen (48) of the second elongate tubular member (46); wherein the basket assembly (12) has a substantially cylindrical shape when compressed within the lumen (48) of the second elongate tubular member (46); and wherein the basket assembly (12) has said radially expanded non-cylindrical shape when not compressed within the lumen (48) of the second elongate tubular member (46) and disposed past the distal end (54) of the second elongate tubular member (46). When basket assembly (12) is in said radially expanded non-cylindrical

shape, the splines (14) may extend beyond the distal tip (16, 150) and may comprise excurvate bends (80) beyond the distal tip (16) to bend the splines (14) back towards the anchor (18). The angles ( $\theta 1-08$ ) between said splines (14) at said distal tip (16, 150) forming said predetermined angular relationship may be all substantially equal to each other. Alternatively, at least one angle ( $\theta 1-08$ ) between said splines (14) at said distal tip (16) forming said predetermined angular relationship may be different from another angle ( $\theta 1-08$ ) between said splines (14) at said distal tip (16, 150).

[0182] In one embodiment, a system (10) for sensing multiple local electric voltages from endocardial surface of a heart, may comprise: a first elongate tubular member (20) having a lumen (20C), a proximal end (20A) and a distal end (20B); a basket assembly comprising: a plurality of flexible splines (14) for guiding a plurality of exposed electrodes (186), the splines (14) having proximal portions (62) and distal portions (66); an anchor (18) for securably affixing the proximal portions (62) of the splines (14); said anchor (18) being secured at the distal end (20B) of the first elongate tubular member (20); a distal tip (16, 104, 104', 126, 134, 140, 152) for comprising a first part and a second part that are securably affixed to one and the other; wherein the distal portions (66) of the splines (14) are securably and non-slidingly disposed within said distal tip (16) in a predetermined angular relationship; wherein the splines (14) approach the distal tip (16) at an angle ( $\alpha$ ) of about  $90^\circ$  or less than about  $90^\circ$  as measured from a line segment between the anchor (18) and the tip (16) along the longitudinal axis (L); wherein the basket assembly (12) has a radially expanded non-cylindrical shape; and wherein the splines (14) comprise a superelastic material. The system (10) may further comprise: a second elongate tubular member (46) having a lumen (48), a proximal end (56) and a distal end (54); wherein the basket assembly (12) is slidingly compressible to fit within the lumen (48) of the second elongate tubular member (46); wherein the basket assembly (12) has a substantially cylindrical shape when compressed within the lumen (48) of the second elongate tubular member (46); and wherein the basket assembly (12) has said radially expanded non-cylindrical shape when not compressed within the lumen (48) of the second elongate tubular member (46) and disposed past the distal end (54) of the second elongate tubular member (46). Angles ( $\theta 1-08$ ) between said splines (14) at said distal tip (16, 104, 104', 126, 134, 140, 152) forming said predetermined angular relationship may be all substantially equal to each other. Alternatively, at least one angle ( $\theta 1-08$ ) between said splines (14) at said distal tip (16) forming said predetermined angular relationship may be different from another angle ( $\theta 1-08$ ) between said splines (14) at said distal tip (16, 104, 104', 126, 134, 140, 152). When basket assembly (12) is in said radially expanded non-cylindrical shape, the splines (14) may extend beyond the distal tip (16, 104, 104', 126, 134, 140, 152) and may comprise excurvate bends (80) beyond the distal tip (16, 104, 104', 126, 134, 140, 152) to bend the splines (14) back towards the anchor (18). The splines (14) may have distal end portions (67); and further wherein the distal spline end portions (67) may be securably and non-slidingly disposed within said distal tip (16, 104, 104', 126, 134, 140). The splines (14) may approach said distal tip (16) at an angle ( $\alpha$ ) of less than  $45^\circ$  as measured

from a line segment between said anchor (18) and said distal tip (16, 104, 104', 126, 134, 140) along the longitudinal axis (L).

[0183] Embodiments directed to spline bends and recurves embodiments include, but are not limited to, as follows:

[0184] A system (10) for sensing multiple local electric voltages from endocardial surface of a heart, may comprise: a first elongate tubular member (20) having a lumen (20C), a proximal end (20A) and a distal end (20B); a basket assembly (12) comprising: a plurality of flexible splines (14) for guiding a plurality of exposed electrodes (186), the splines (14) having proximal portions (62), distal portions (66) and medial portions (64) therein between; a proximal anchor (18) for securably affixing the proximal portions (62) of the splines (14); said proximal anchor (18) being secured at the distal end (20B) of the first elongate tubular member (20); a distal tip (16) for securably affixing the distal portions (66) of the splines (14), said proximal anchor (18) and said distal tip (16) defining a longitudinal axis (L) therein between about which the splines (14) are disposed; wherein the splines (14) approach the distal tip (18) at an angle ( $\alpha$ ) of about  $90^\circ$  or less than about  $90^\circ$  as measured from a line segment between the proximal anchor (18) and the distal tip (16) along the longitudinal axis (L); wherein the splines (14) comprise a superelastic material such that the basket assembly (12) exhibits a substantially cylindrical shape when radially compressed and exhibits a radially expanded non-spherical shape when not radially compressed; and wherein at least some of the splines (14) in the radially expanded non-spherical shape contain a distal excurvate outward bend (80) disposed at the distal portion (66) of the spline (14) at a location near to the distal tip (16) of the basket assembly (12) to bend the splines (14) back towards the proximal anchor (18). The system may further comprise: a second elongate tubular member (46) having a lumen (48), a proximal end (56) and a distal end (54); wherein the basket assembly (12) is slidingly compressible to fit within the lumen (48) of the second elongate tubular member (46); wherein the basket assembly (12) has said substantially cylindrical shape when compressed within the lumen (48) of the second elongate tubular member (46); and wherein the basket assembly (12) has said radially expanded non-spherical shape when not compressed within the lumen (48) of the second elongate tubular member (46) and disposed past the distal end (54) of the second elongate tubular member (46). When basket assembly (12) is in said radially expanded non-spherical shape, the splines (14) may extend beyond the distal tip (16); and, when basket assembly (12) is in said radially expanded non-spherical shape, apices (81) of the distal excurvate bends (80) may be disposed beyond the distal tip (16). The distal spline portions (66) may be securably and non-slidingly disposed within said distal tip (16). The distal spline portions (66) may be securably and non-slidingly disposed within said distal tip (16) in a predetermined angular relationship, wherein angles ( $\theta 1-08$ ) between said splines (14) at said distal tip (16) forming said predetermined angular relationship may be all substantially equal to each other; or wherein at least one angle ( $\theta 1-08$ ) between said splines (14) at said distal tip (16) forming said predetermined angular relationship may be different from another angle ( $\theta 1-08$ ) between said splines (14) at said distal tip (16). The splines (14) have distal end portions (67); and further wherein the distal spline end portions (67) may be securably and non-slidingly disposed within said distal tip

(16). The splines (14) may approach said distal tip (16) at an angle ( $\alpha$ ) of less than about  $45^\circ$  as measured from the line segment between said proximal anchor (18) and said distal tip (16) along the longitudinal axis (L). The splines (14) may have a distal incurvate inward bend (78) between said distal tip (16) and said distal excurve outward bends (80). The distal tip (16) may have a non-thrombogenic outer surface free of voids and slots that would permit the passage or entry of blood thereinto. The splines (14) may have reduced widths at said distal portions (66) near the tip (16) as compared to spline widths at said medial portions (64).

[0185] A system (10) for sensing multiple local electric voltages from endocardial surface of a heart, may comprise: a first elongate tubular member (20) having a lumen (20C), a proximal end (20A) and a distal end (20B); a basket assembly (12) comprising: a plurality of flexible splines (14) for guiding a plurality of exposed electrodes (186), the splines (14) having proximal portions (62), distal portions (66) and medial portions (64) therein between; a proximal anchor (18) for securably affixing the proximal portions (62) of the splines (14); said anchor (18) being secured at the distal end (20B) of the first elongate tubular member (20); a distal tip (16) for securably affixing the distal portions (66) of the splines (14), said proximal anchor (18) and said distal tip (16) defining a longitudinal axis (L) about which the splines (14) are disposed; wherein the splines (14) approach the distal tip (16) at an angle ( $\alpha$ ) of about  $90^\circ$  or less than about  $90^\circ$  as measured from a line segment between the proximal anchor (18) and the distal tip (16) along the longitudinal axis (L); wherein the splines (14) comprise a superelastic material such that the basket assembly (12) exhibits a substantially cylindrical shape when radially compressed and exhibits a radially expanded non-spherical shape when not radially compressed; and wherein each of the splines (14) in the radially expanded non-spherical shape contain a proximal recurve (76) in the proximate portion (62) of the spline (14) at a location near to the proximal anchor (18) of the basket assembly (12), the proximal recurve (76) comprises a proximal excurve outward bend (84) and a proximal incurvate inward bend (82) between said proximal excurve outward bend (84) and said proximal anchor (18), where an apex (83) of the proximal incurvate inward bend (82) is disposed in a direction toward the distal tip (16) and is further disposed inwardly closer toward the distal tip (16) than the proximal excurve outward bend (84). The system (10) may further comprise: a second elongate tubular member (46) having a lumen (48), a proximal end (56) and a distal end (54); wherein the basket assembly (12) is slidably compressible to fit within the lumen (48) of the second elongate tubular member (46); wherein the basket assembly (12) has said substantially cylindrical shape when compressed within the lumen (48) of the second elongate tubular member (46); and wherein the basket assembly (12) has said radially expanded non-spherical shape when not compressed within the lumen (48) of the second elongate tubular member (46) and disposed past the distal end (54) of the second elongate tubular member (46). The splines (14) may approach said distal tip (16) at an angle ( $\alpha$ ) of less than about  $45^\circ$  as measured from the line segment between said proximal anchor (18) and said distal tip (16) along the longitudinal axis (L). The splines (14) in the radially expanded non-spherical shape may contain a distal excurve outward bend (80) disposed at the distal portion (66) of the spline (14) at a location near to the distal tip (16)

of the basket assembly (12) to bend the splines (14) back towards the proximal anchor (18); wherein the splines (14) may have a distal incurvate inward bend (78) between said distal tip (16) and said distal excurve outward bends (80); and wherein, when basket assembly (12) is in said radially expanded non-spherical shape, the splines (14) may extend beyond the distal tip (16) and, when basket assembly (12) is in said radially expanded non-spherical shape, apices (81) of the distal excurve bends (80) may be disposed beyond the distal tip (16). The distal tip (16) may have a non-thrombogenic outer surface free of voids and slots that would permit the passage or entry of blood thereinto. The splines (14) may have reduced widths at said distal portions near the distal tip (16) as compared to spline widths at said medial portions (64). Each of the splines (14) have a length between said apex (83) of said proximal incurvate inward bend (82) and said proximal excurve outward bend (84); and further wherein said length of at least one spline (14) may be different from said length of another of said splines (14). Alternatively, each of the splines (14) may have a substantially equal overall length between said proximal anchor (18) and said distal tip (16). Alternatively, each of the splines (14) may have a substantially equal overall length from said proximal anchor (18) and to said distal tip (16); and further wherein a length from said proximal excurve outward bend (84) to said distal tip (16) for at least one of said splines (14) may be different from said length for another one of said splines (14).

[0186] A system (10) for sensing multiple local electric voltages from endocardial surface of a heart, may comprise: a first elongate tubular member (20) having a lumen (20C), a proximal end (20A) and a distal end (20B); a basket assembly (12) comprising: a plurality of flexible splines (14) for guiding a plurality of exposed electrodes (186), the splines (14) having proximal portions (62) and distal portions (66); a proximal anchor (18) for securably affixing the proximal portions (62) of the splines (14); said proximal anchor (18) being secured at the distal end (20B) of the first elongate tubular member (20); a distal tip (16) for securably affixing the distal portions (66) of the splines (14), said proximal anchor (18) and said distal tip (16) defining a longitudinal axis (L) about which the splines (14) are disposed; wherein the splines (14) approach the distal tip (16) at an angle ( $\alpha$ ) of less than about  $45^\circ$  as measured from a line segment between the proximal anchor (18) and the distal tip (16) along the longitudinal axis (L); wherein the splines (14) comprise a superelastic material such that the basket assembly (12) exhibits a substantially cylindrical shape when radially compressed and exhibits a radially expanded non-spherical shape when not radially compressed; wherein the splines (14) in the radially expanded non-spherical shape contain a distal excurve outward bend (80) disposed at the distal portion of the spline (14) at a location near to the distal tip (16) of the basket assembly (12) to bend the splines (14) back towards the proximal anchor (18); wherein the splines (14) have a distal incurvate inward bend (78) between said distal tip (16) and said distal excurve outward bends (80); wherein, when basket assembly (12) is in said radially expanded non-spherical shape, the splines (14) extend beyond the distal tip (16) and, when basket assembly (12) is in said radially expanded non-spherical shape, apices (80) of the distal excurve bends (80) are disposed beyond the distal tip (16); and wherein each of the splines (14) in the radially expanded non-

spherical shape contain a proximal recurve (76) in the proximate portion (62) of the spline (14) at a location near to the proximal anchor (18) of the basket assembly (12), the proximal recurve (76) comprises a proximal incurvate outward bend (84) and a proximal incurvate inward bend (82) between said proximal incurvate outward bend (84) and said proximal anchor (18), where an apex (83) of the proximal incurvate inward bend (82) is disposed in a direction toward the distal tip (16) and is further disposed inwardly closer toward the distal tip (16) than the proximal incurvate outward bend (84). The system (10) may further comprise: a second elongate tubular member (46) having a lumen (48), a proximal end (56) and a distal end (54); wherein the basket assembly (12) is slidably compressible to fit within the lumen (48) of the second elongate tubular member (46); wherein the basket assembly (12) has said substantially cylindrical shape when compressed within the lumen (48) of the second elongate tubular member (46); and wherein the basket assembly (12) has said radially expanded non-spherical shape when not compressed within the lumen (48) of the second elongate tubular member (46) and disposed past the distal end (54) of the second elongate tubular member (46). The distal spline portions (66) may be securably and non-slidingly disposed within said distal tip (16). The splines (14) may have distal end portions (67); and further wherein the distal spline end portions (67) may be securably and non-slidingly disposed within said distal tip (16). Each of the splines (14) may have a substantially equal overall length from said proximal anchor (18) and to said distal tip (16); and further wherein a length from said proximal incurvate outward bend (84) to said distal tip (16) is for at least one of said splines (14) is different from said length for another one of said splines (14).

[0187] A system (10) for sensing multiple local electric voltages from endocardial surface of a heart, may comprise: a first elongate tubular (20) member having a lumen (20C), a proximal end (20A) and a distal end (20B); a basket assembly (12) comprising: a plurality of flexible splines (14) for guiding a plurality of exposed electrodes (186), the splines (14) having proximal portions (62) and distal portions (66); a proximal anchor (18) for securably affixing the proximal portions (62) of the splines (14); said proximal anchor (18) being secured at the distal end (20B) of the first elongate tubular member (20); a distal tip (16) for securably affixing the distal portions (66) of the splines (14), said proximal anchor (18) and said tip (16) defining a longitudinal axis (L) about which the splines (14) are disposed; wherein the splines (14) comprise a superelastic material such that the basket assembly (12) exhibits a substantially cylindrical shape when radially compressed and exhibits a radially expanded non-spherical shape when not radially compressed; wherein each of the splines (14) in the radially expanded non-spherical shape contain a proximal recurve (76) in the proximate portion of the spline (14) at a location near to the anchor (18) of the basket assembly (12), the proximal recurve (76) comprises a proximal incurvate outward bend (84) and a proximal incurvate inward bend (82) between said proximal incurvate outward bend (84) and said proximal anchor (18), where an apex (83) of the proximal incurvate inward bend (82) is disposed in a direction toward the distal tip (16) and is further disposed inwardly closer toward the distal tip (16) than the proximal incurvate outward bend (84); and wherein the proximal incurvate inward bends (82) of some splines (14) have a different

geometry from the proximal incurvate inward bends (82) of other splines (14); and wherein one or more tissue-contacting portions of the individual splines (14) are of unequal length with respect to each other, and each of the proximal incurvate inward bend portions (82) of the splines (14) possess compensating lengths such that the sum of the tissue facing portion plus proximal incurvate inward bend portion (82) of all splines (14) are substantially the same. The system (10) may further comprise: a second elongate tubular member (46) having a lumen (48), a proximal end (56) and a distal end (54); wherein the basket assembly (12) is slidably compressible to fit within the lumen (48) of the second elongate tubular member (46); wherein the basket assembly (12) has said substantially cylindrical shape when compressed within the lumen (48) of the second elongate tubular member (46); and wherein the basket assembly (12) has said radially expanded non-spherical shape when not compressed within the lumen (48) of the second elongate tubular member (46) and disposed past the distal end (54) of the second elongate tubular member (46). The splines (14) may have distal end portions (67); and further wherein the distal spline end portions (67) may be securably and non-slidingly disposed within said distal tip (16). The splines (14) in the radially expanded non-spherical shape may contain a distal incurvate outward bend (80) disposed at the distal portion (66) of the spline (14) at a location near to the distal tip (16) of the basket assembly (12) to bend the splines (14) back towards the proximal anchor (18); wherein the splines (14) may have a distal incurvate inward bend (78) between said distal tip (16) and said distal incurvate outward bends (80); and wherein, when basket assembly (12) is in said radially expanded non-spherical shape, the splines (14) may extend beyond the distal tip (16) and, when basket assembly (12) is in said radially expanded non-spherical shape, apices (81) of the distal incurvate bends (80) are disposed beyond the distal tip (16).

[0188] Embodiments directed to spline assemblies for basket catheters include, but are not limited to, as follows:

[0189] A system (10) for sensing multiple local electric voltages from endocardial surface of a heart, may comprise: an elongate tubular member (20) having a lumen (20C), a proximal end (20A) and a distal end (20B); a plurality of flexible splines (14) having proximal portions (62), distal portions (66) and medial portions (64) therein between, wherein the splines (14) comprise an outer surface (190), an inner surface (192) and two side surfaces (194, 196); an anchor (18) for securably affixing the proximal portions (62) of the splines (14), wherein the anchor (18) is securably affixed within the lumen (20C) of the elongate tubular member (20) at the distal end (20B) of the elongate tubular member (20); a tip (16) for securably affixing the distal portions (66) of the splines (14); and a polymeric member (185) comprising opposed a first open end (202) and a second open end (200) defining an open lumen (208) therein between and an inner member surface (208B) and an outer member surface (208A), wherein at least one of the plurality of flexible splines (14) is at least partially disposed within the lumen (208) of said polymeric member; a flexible electrode assembly strip (188) with one or more exposed electrodes (186) disposed on at least a portion of the outer surface (208A) of said polymeric member (185); wherein the flexible electrode assembly strip (188) comprises: a polymeric substrate (236) having an inner surface (236B) and an opposed outer surface (236A); said one or more

exposed electrodes (186) disposed over at least part of the outer surface (236A) of the polymeric substrate (236); and one or more electrical traces (228) disposed over at least a portion of the inner surface (236B) of the polymeric substrate (236) or over at least a portion of the outer surface (236A) of the polymeric substrate (236), said one or more electrical traces (228) being in electrical communication with said one or more exposed electrodes (186); wherein a portion of the flexible electrode assembly (188) transitions from the outer surface (208A) of said polymeric member (185) towards the inner surface (208B) of said polymeric member (185) prior to said anchor (18); and wherein another portion of the flexible electrode assembly (188) extends through at least a portion of said anchor (18) and into said lumen (20C) of said elongate tubular member (20). The system (10) may further comprise: a plurality of polymeric members (185) each comprising said flexible electrode assembly strip (188); wherein each of said plurality of flexible splines (14) are at least partially disposed within a different one of said plurality of polymeric members (185). The one or more electrical traces (228) may be disposed over at least a portion of the inner surface (236B) of the polymeric substrate (236) and may further comprise vias (230) to provide said electrical communication between said one or more electrical traces (228) and said one or more exposed electrodes (186). The one or more electrical traces (228) may be disposed over at least a portion of the outer surface (236A) of the polymeric substrate (236) and further comprising a polymeric covering (238, 240) over the outer surface (236A) of the polymeric substrate (236) and said electrical traces (228) with the one or more exposed electrodes (186) being substantially free of the polymeric covering (238, 240). The first opposed open end (202) of the polymeric member (185) may be secured to the distal spline portion (66) of said at least one of the plurality of flexible splines (14) at a position near to the distal tip (16) and the second opposed open end (200) of the polymeric member (185) may be secured to the proximal spline portion (62) of said at least one of the plurality of flexible splines (14) at a position near to the anchor (18). The first opposed open end (202) of the polymeric member (185) may be sealingly secured to the distal spline portion (66) at the position near to the distal tip (16) by a seal (206). Medial portions of the polymeric member (185) between said first opposed open end (202) and said second opposed open end (200) of the polymeric member (185) may not be secured to said medial portions (64) of said at least one of the plurality of flexible splines (14). At least one intermediate medial portion of the polymeric member (185) between said first opposed open end (202) and said second opposed open end (200) of the polymeric member (185) may be secured to at least one intermediate portion of said medial portions (64) of said at least one of the plurality of flexible splines (14). The one or more exposed electrodes (186) may comprise copper, gold, platinum, platinum black, platinum-iridium and combinations thereof. The outer surface (190) and the inner surface (192) of said plurality of flexible splines (14) may be substantially flat surfaces and the two side surfaces (194, 196) of said plurality of flexible splines (14) may be convexly rounded surfaces. The one or more exposed electrodes (186) may have a substantially flat upper surface.

[0190] A system (10) for sensing multiple local electric voltages from endocardial surface of a heart, may comprise: an elongate tubular member (20) having a lumen (20C), a

proximal end (20A) and a distal end (20B); a plurality of flexible splines (14) having proximal portions (62), distal portions (66) and medial portions (64) therein between, wherein the splines (14) comprise an outer surface (190), an inner surface (192) and two side surfaces (194, 196); an anchor (18) for securably affixing the proximal portions (62) of the splines (14), wherein the anchor (18) is securably affixed within the lumen (20C) of the elongate tubular member (20) at the distal end (20B) of the elongate tubular member (20); a tip (16) for securably affixing the distal portions (66) of the splines (14); and a polymeric member (185) comprising opposed first (202) and second (200) open ends defining an open lumen (208) therein between and an inner member surface (208B) and an outer member surface (208A), wherein at least one of the plurality of flexible splines (14) is at least partially disposed within the lumen (208) of said polymeric member (185); a flexible electrode assembly strip (188) with one or more exposed electrodes (186) disposed on at least a portion of the outer surface (208A) of said polymeric member (185); wherein the flexible electrode assembly strip (188) comprises: a polymeric substrate (236) having an inner surface (236B) and an opposed outer surface (236A); said one or more exposed electrodes (186) disposed over at least part of the outer surface (236A) of the polymeric substrate (236); and one or more electrical traces (228) disposed over at least a portion of the inner surface (236B) of the polymeric substrate (236) or over at least a portion of the outer surface (236A) of the polymeric substrate (236), said one or more electrical traces (228) being in electrical communication with said one or more exposed electrodes (186); wherein the first opposed open end (202) of the polymeric member (185) is secured to the distal spline portion (66) of said at least one of the plurality of flexible splines (14) at a position near to the distal tip (16) and the second opposed open end (200) of the polymeric member (185) is secured to the proximal spline portion (62) of said at least one of the plurality of flexible splines (14) at a position near to the anchor (18); and wherein medial portions of the polymeric member (185) between said first opposed open end (202) and said second opposed open end (200) of the polymeric member (185) are not secured to said medial portions (64) of said at least one of the plurality of flexible splines (14). The system (10) may further comprise a seal (206) for sealingly engaging said first opposed open end (202) of the polymeric member (185) and said distal spline portion (66). A portion of the flexible electrode assembly (188) may extend through at least a portion of said anchor (18) and into said lumen (20C) of said elongate tubular member (20). The system (10) may further comprise: a plurality of polymeric members (185) each comprising said flexible electrode assembly strip (188); wherein each of said plurality of flexible splines (14) may be at least partially disposed within a different one of said plurality of polymeric members (185). The one or more electrical traces (228) may be disposed over at least a portion of the inner surface (236B) of the polymeric substrate (236) and may further comprise vias (230) to provide said electrical communication between said one or more electrical traces (228) and said one or more exposed electrodes (186). The one or more electrical traces (228) may be disposed over at least a portion of the outer surface (236A) of the polymeric substrate (236) and may further comprise a polymeric covering (238, 240) over the outer surface (236A) of the polymeric substrate (236) and said electrical traces (228)

with the one or more exposed electrodes (186) being substantially free of the polymeric covering (238, 240). The one or more exposed electrodes (186) may comprise copper, gold, platinum, platinum black, platinum-iridium and combinations thereof. The outer surface (190) and the inner surface (192) of said plurality of flexible splines (14) may be substantially flat surfaces and the two side surfaces (194, 196) of said plurality of flexible splines (14) may be convexly rounded surfaces. The one or more exposed electrodes (186) have a substantially flat upper surface.

[0191] A system (10) for sensing multiple local electric voltages from endocardial surface of a heart, may comprise: an elongate tubular member (20) having a lumen (20C), a proximal end (20A) and a distal end (20B); a plurality of flexible splines (14) having proximal portions (62), distal portions (66) and medial portions (64) therein between, wherein the splines (14) comprise an outer surface (190), an inner surface (192) and two side surfaces (194, 196), wherein said inner and outer spline surfaces (190, 192) have a substantially flat portion with the substantially flat portions being parallel to one and the other, and further wherein the two side spline surfaces (194, 196) are convexly rounded to define a rounded-rectangular shape; an anchor (18) for securably affixing the proximal portions (62) of the splines (14), wherein the anchor (18) is securably affixed within the lumen (20C) of the elongate tubular member (20) at the distal end (20B) of the elongate tubular member (20); a tip (16) for securably affixing the distal portions (66) of the splines (14); and a plurality of polymeric members (185) each having opposed first (202) and second (200) open ends defining an open lumen (208) therein between, wherein the polymeric members (185) comprise an outer surface (208A), an inner surface (208B) and two side surfaces where a cross-sectional profile of the polymeric members is elliptical to match a cross-sectional profile of the rounded-rectangular shape of the splines (14) and is slightly larger than the cross-sectional profile of the rounded-rectangular shape of the splines (14) and wherein each of the plurality of flexible splines (14) is at least partially disposed within the lumen (208) of a different one of said plurality of polymeric members (185); a flexible electrode assembly strip (188) with one or more exposed electrodes (186) disposed on at least a portion of the outer surface (208A) of said polymeric members (185); wherein the flexible electrode assembly strip (188) comprises: a polymeric substrate (236) having an inner surface (236B) and an opposed outer (236A) surface; said one or more exposed electrodes (186) disposed over at least part of the outer surface (236A) of the polymeric substrate (236); and one or more electrical traces (228) disposed over at least a portion of the inner surface (236B) of the polymeric substrate (236) or over at least a portion of the outer surface (236A) of the polymeric substrate (236), said one or more electrical traces (228) being in electrical communication with said one or more exposed electrodes (186); wherein a portion of said flexible electrode assembly strip (188) extends through at least a portion of said anchor (18) and into said lumen (20C) of said elongate tubular member (20). The one or more electrical traces (228) may be disposed over at least a portion of the inner surface (236B) of the polymeric substrate (236) and may further comprise vias (230) to provide said electrical communication between said one or more electrical traces (228) and said one or more exposed electrodes (186). The one or more electrical traces (228) may be disposed over at least a portion of the outer

surface (236A) of the polymeric substrate (236) and may further comprise a polymeric covering (238, 240) over the outer surface (236A) of the polymeric substrate (236) and said electrical traces (228) with the one or more exposed electrodes (186) being substantially free of the polymeric covering (238, 240). The first opposed open end (202) of the polymeric member (185) may be sealingly secured to the distal spline portion (66) of said at least one of the plurality of flexible splines (14) at a position near to the distal tip (16) and the second opposed open end (200) of the polymeric member (185) may be secured to the proximal spline portion (62) of said at least one of the plurality of flexible splines (14) at a position near to the anchor (18). Medial portions of the polymeric member between said first opposed open end (202) and said second opposed open end (200) of the polymeric member (185) may not be secured to said medial portions (64) of said at least one of the plurality of flexible splines (14). At least one intermediate medial portion of the polymeric member (185) between said first opposed open end (202) and said second opposed open end (200) of the polymeric member (185) may be secured to at least one intermediate portion of said medial portions (64) of said at least one of the plurality of flexible splines (14). The one or more exposed electrodes (186) may comprise copper, gold, platinum, platinum black, platinum-iridium and combinations thereof. The one or more exposed electrodes (186) may have a substantially flat upper surface.

[0192] A system (10) for sensing multiple local electric voltages from endocardial surface of a heart, may comprise: an elongate tubular member (20) having a lumen (20C), a proximal end (20A) and a distal end (20B); a plurality of flexible splines (14) having proximal portions (62), distal portions (66) and medial portions (64) therein between, wherein the splines (14) comprise an outer surface (190), an inner surface (192) and two side surfaces (194, 196); an anchor (18) for securably affixing the proximal portions (62) of the splines (14), wherein the anchor (18) is securably affixed within the lumen (20C) of the elongate tubular member (20) at the distal end (20B) of the elongate tubular member (20); a tip (16) for securably affixing the distal portions (66) of the splines (14); and a plurality of polymeric members (185) each having opposed first (202) and second (200) open ends defining an open lumen (208) therein between and an outer surface (208A) and an inner surface (208B), wherein each of the plurality of flexible splines (14) is at least partially disposed within the lumen (208) of a different one of said plurality of polymeric members (185); a flexible electrode assembly strip (188) with one or more exposed electrodes (186) disposed on at least a portion of the outer surface (208A) of said polymeric members (185); wherein the flexible electrode assembly strip (188) comprises: a polymeric substrate (236) having an inner surface (236B) and an opposed outer surface (236A); said one or more exposed electrodes (186) disposed over at least part of the outer surface (236A) of the polymeric substrate (236); and one or more electrical traces (228) disposed over at least a portion of the inner surface (236B) of the polymeric substrate (236) or over at least a portion of the outer surface (236A) of the polymeric substrate (236), said one or more electrical traces (228) being in electrical communication with said one or more exposed electrodes (186); wherein the flexible electrode assembly strip (188) is compressed into the outer surface (208A) of the polymeric member (185); and wherein the flexible electrode assembly strip (188) is

thermally or adhesively bonded to the outer surface (208A) of the polymeric member (185).

[0193] Embodiments directed to flex circuits and flexible electrode assemblies include, but are not limited to, as follows:

[0194] A device for insertion into a body lumen, may comprise: an electrode assembly strip (188) with exposed electrodes (186) comprising: a polymeric substrate (236) having an upper surface (236A) and an opposed lower surface (236B); one or more electrodes (186) disposed over a portion of the upper surface (236A) of the polymeric substrate (236); one or more electrical traces (228) disposed over a portion of the lower surface (236B) of the polymeric substrate (236) in electrical communication with the one or more electrodes (186) by way of metal plated holes (230) through the substrate (236); and a flexible polymeric substrate (246) having a substrate surface (246A) and a substrate wall (246C); wherein the electrode assembly strip (188) is compressingly and thermally bonded to the substrate surface (246A) of the flexible polymeric substrate (246) to define a flexible electrode assembly strip (247); and wherein the electrode assembly strip (188) has a thickness from about 0.0005 inches to about 0.008 inches. The electrode assembly strip (188) may have a thickness from about 0.002 inches to about 0.004 inches. The device may further comprise: a first polymeric covering (238) disposed portions of the substrate surface (236A) of the polymeric substrate (236) not having the one or more electrodes (186) thereon, said first polymeric covering (238) having holes disposed over the one or more electrodes (186) thereby defining one or more exposed electrodes (186); and a second polymeric covering (240) disposed over the one or more electrical traces (228) and portions of the lower surface (236B) of the substrate (236) not having the one or more electrical traces (228) thereon. The polymeric substrate (236), the first polymeric covering (238) and the second polymeric covering (240) may comprise a biocompatible polyimide material. The flexible polymeric substrate (236) may comprise a biocompatible polyether block amide material. The flexible polymeric substrate (236) may comprise a biocompatible polymer selected from the group consisting of polyesters, silicones, silicone rubbers, urethanes and combinations thereof. The flexible polymeric substrate (236) may be a sheet. Alternatively, the flexible polymeric substrate (236) may be an extruded tube having an open lumen.

[0195] A device for insertion into a body lumen, may comprise: an electrode assembly strip (188) with exposed electrodes (186) comprising: a polymeric substrate (236) having an upper surface (236A) and an opposed lower surface (236B); at least two electrodes (186) disposed over a portion of the upper surface (236A) of the polymeric substrate (236); at least two electrical traces (228) disposed over a portion of the lower surface (236B) of the polymeric substrate (236) in electrical communication with the at least two electrodes by way of metal plated holes (230) through the substrate (236); a first polymeric covering (238) disposed portions of the upper surface (236A) of the polymeric substrate (236) not having the at least two of said electrodes (186) thereon, said first polymeric covering (238) having holes disposed over the at least two of said electrodes (186) thereby defining at least two exposed electrodes (186); a second polymeric covering (240) disposed over the at least two of the electrical traces (228) and portions of the lower surface of the substrate not having the at least two electrical

traces (228) thereon; a first flexible polymeric tube (185) having opposed open ends (200, 202) defining an open lumen (208) therein between and an inner tubular surface (208B) and an outer tubular surface (208A); wherein the electrode assembly strip (188) is disposed over the outer surface (208A) of the first flexible polymeric tube (185); and a second flexible polymeric tube (185) having opposed open ends (200, 202) defining an open lumen (208) therein between and an inner tubular surface (208B) and an outer tubular surface (208A), wherein the second flexible polymeric tube (185) is disposed over portions of the electrode assembly strip (188) not having the exposed electrodes (186); wherein the electrode assembly strip (188), the first flexible polymeric tube (185) and the second flexible polymeric tube (185) are compressingly and thermally bonded to each other to define a flexible electrode assembly strip (247); and wherein the electrode assembly strip (188) has a thickness from about 0.0005 inches to about 0.008 inches. The polymeric substrate (236), the first polymeric covering (238) and the second polymeric covering (240) may comprise a biocompatible polyimide material. The first and second flexible polymeric tubes (185) may comprise a polyether block amide material. The first flexible polymeric tube (185) may be an extruded tube. The flexible electrode assembly strip (247) may have a substantially smooth and atraumatic overall outer surface (246A). The device may further comprise: an elongate tubular member (20) having a lumen (20C), a proximal end (20A) and a distal end (20B); a plurality of flexible splines (14) having proximal portions (62), distal portions (66) and medial portions (64) therein between, wherein the splines (14) comprise an outer surface (190), an inner surface (192) and two side surfaces (194, 196); an anchor (18) for securably affixing the proximal portions (62) of the splines (14), wherein the anchor (18) is securably affixed within the lumen (20C) of the elongate tubular member (20) at the distal end (20B) of the elongate tubular member (20); and a tip (16) for securably affixing the distal portions (66) of the splines (14); wherein the flexible electrode assembly strip (247) is disposed over at least one of the plurality of splines (14). The device may further comprise a plurality of flexible electrode assembly strips (247), wherein each of said plurality of splines (14) has at least one of said plurality of flexible electrode assembly strips (247) disposed there over.

[0196] A device for insertion into a body lumen, may comprise: an electrode assembly strip (188) with exposed electrodes (186) comprising: a polymeric substrate (236) having an upper surface (236A) and an opposed lower surface (236B); one or more of substantially flat electrodes (186) disposed over a portion of the upper surface (236A) of the polymeric substrate (236); one or more of electrical traces (228) disposed over a portion of the lower surface (236B) of the polymeric substrate (236) in electrical communication with the one or more electrodes (186) by way of metal plated holes (230) through the substrate (236); a first polymeric covering (238) disposed portions of the upper surface (236A) of the polymeric substrate (236) not having the one or more of the electrodes (186) thereon, said first polymeric covering (238) having holes disposed over the one or more electrodes (186) thereby defining one or more exposed electrodes (186); a second polymeric covering (240) disposed over the over the one or more electrical traces (228) and portions of the lower surface (236B) of the substrate (236) not having the one or more electrical traces

(228) thereon; and a flexible polymeric tube (185) having opposed open ends (200, 202) defining an open lumen (208) therein between and an inner tubular surface (208B) and an outer tubular surface (208A) defining a tubular wall (210) therein between; wherein the electrode assembly strip (188) is compressingly and thermally bonded to the outer surface (208A) of the flexible polymeric tube (185) to define a flexible electrode assembly strip (247); wherein substantial portions of the substantially flat electrodes (186) remain substantially flat to provide substantially flat exposed electrodes (186); and wherein the electrode assembly strip (188) has a thickness from 0.0005 inches to about 0.008 inches. The polymeric substrate (236) may comprise a polyimide material. The first polymeric covering (238) and the second polymeric covering (240) may comprise a polyimide material. The flexible polymeric tube (185) may comprise a polyether block amide material. The flexible polymeric tube (185) may be an extruded tube. The electrode assembly strip (188) may be compressed into the tubular wall (210) of the flexible polymeric tube (185) to provide a substantially smooth and atraumatic overall outer surface for the flexible electrode assembly strip. The device may further comprise: an elongate tubular member (20) having a lumen (20C), a proximal end (20A) and a distal end (20B); one or more flexible splines (14) having proximal portions (62), distal portions (66) and medial portions (64) therein between, wherein the one or more splines (14) comprise an outer surface (190), an inner surface (192) and two side surfaces (194, 196); an anchor (18) for securably affixing the proximal portions (62) of the one or more splines (14), wherein the anchor (18) is securably affixed within the lumen (20C) of the elongate tubular member (20) at the distal end (20B) of the elongate tubular member (20); and a tip (16) for securably affixing the distal portions (66) of the one or more splines (14); wherein the flexible electrode assembly strip (247) is disposed over at least one of the one or more splines (14). The device may further comprise one or more of flexible electrode assembly strips (247), wherein each of said one or more of the splines (14) may have at least one of said one or more of the flexible electrode assembly strips (247) disposed there over.

[0197] A device for insertion into a body lumen, may comprise an electrode assembly strip (188) with exposed electrodes (186) comprising: a polymeric substrate (236) having an upper surface (236A) and an opposed lower surface (236B); at least two substantially flat electrodes (186) disposed over a portion of the upper surface (236A) of the polymeric substrate (236); at least two electrical traces (228) disposed over a portion of the lower surface (236B) of the polymeric substrate (236) in electrical communication with the at least two electrodes (186) by way of metal plated holes (230) through the substrate (236); a first polymeric covering (238) disposed portions of the upper surface (236A) of the polymeric substrate (236) not having the at least two of said electrodes (186) thereon, said first polymeric covering (238) having holes disposed over the at least two of said electrodes (186) thereby defining at least two exposed electrodes (186); a second polymeric covering (240) disposed over the over the plurality of electrical traces (228) and portions of the lower surface (236B) of the substrate (236) not having electrical traces (228) thereon; a first flexible polymeric tube (185) having opposed open ends (200, 202) defining an open lumen (208) therein between and an inner tubular surface (208B) and an outer tubular

surface (208A); wherein the electrode assembly strip (188) is disposed over the outer surface (208A) of the first flexible polymeric tube (185); and a second flexible polymeric tube (185) having opposed open ends (200, 202) defining an open lumen (208) therein between and an inner tubular surface (208B) and an outer tubular surface (208A), wherein the second flexible polymeric tube (185) is disposed over portions of the electrode assembly strip (188) not having the exposed electrodes (186), wherein the electrode assembly strip (188), the first flexible polymeric tube (185) and the second flexible polymeric tube (185) are compressingly and thermally bonded to each other to define a flexible electrode assembly strip (247); wherein substantial portions of the at least two substantially flat electrodes (186) remain substantially flat to provide at least two substantially flat exposed electrodes (186); and wherein the electrode assembly strip (188) has a thickness from about 0.0005 inches to about 0.008 inches. The polymeric substrate (236) may comprise a polyimide material. The first polymeric covering (238) and the second polymeric covering (240) may comprise a polyimide material. The first and second flexible polymeric tubes (185) may comprise a polyether block amide material. The first flexible polymeric tube (185) may be an extruded tube. The flexible electrode assembly strip (247) may have a substantially smooth and atraumatic overall outer surface. The device may further comprise: an elongate tubular member (20) having a lumen (20C), a proximal end (20A) and a distal end (20B); one or more flexible splines (14) having proximal portions (62), distal portions (66) and medial portions (64) therein between, wherein the splines (14) comprise an outer surface (190), an inner surface (192) and two side surfaces (194, 196); an anchor (18) for securably affixing the proximal portions (62) of the splines (14), wherein the anchor (18) is securably affixed within the lumen (20C) of the elongate tubular member (20) at the distal end (20B) of the elongate tubular member (20); and a tip (16) for securably affixing the distal portions (66) of the one or more splines (14); wherein the flexible electrode assembly strip (247) is disposed over at least one of the one or more of the splines (14).

[0198] Embodiments directed to methods for sensing multiple local electric voltages from endocardial surface of a heart include, but are not limited to, as follows:

[0199] A method for sensing multiple local electric voltages from endocardial surface of a heart, may comprise: providing a system (10) for sensing multiple local electric voltages from endocardial surface of a heart, comprising: a first elongate tubular member (20) having a lumen (20C), a proximal end (20A) and a distal end (20B); a basket assembly (12) comprising: a plurality of flexible splines (14) for guiding a plurality of exposed electrodes (186), the splines (14) having proximal portions (62), distal portions (66) and medial portions (64) therein between, wherein the electrodes (186) are substantially flat electrodes and are substantially unidirectionally oriented towards a direction outside of the basket assembly (12); a proximal anchor (18) for securably affixing the proximal portions (62) of the splines (14); said anchor (18) being secured at the distal end (20B) of the first elongate tubular member (20); a distal tip (16) for securably affixing the distal portions (66) of the splines (14), said proximal anchor (18) and said distal tip (16) defining a longitudinal axis (L) about which the splines (14) are disposed; wherein the splines (14) approach the distal tip (16) at an angle ( $\alpha$ ) of about 90° or less than about 90° as

measured from a line segment between the proximal anchor (18) and the distal tip (16) along the longitudinal axis (L); wherein the splines (14) comprise a superelastic material such that the basket assembly (12) exhibits a substantially cylindrical shape when radially compressed and exhibits a radially expanded non-spherical shape when not radially compressed; and wherein each of the splines (14) in the radially expanded non-spherical shape contain a proximal recurve (76) in the proximate portion (62) of the spline (14) at a location near to the proximal anchor (18) of the basket assembly (12), the proximal recurve (76) comprises a proximal excurve outward bend (84) and a proximal incurve inward bend (82) between said proximal excurve outward bend (84) and said proximal anchor (18), where an apex (83) of the proximal incurve inward bend (82) is disposed in a direction toward the distal tip (16) and is further disposed inwardly closer toward the distal tip (16) than the proximal excurve outward bend (84); delivering the system (10) to the heart so that the basket assembly (12) is disposed within the right atrium of the heart; contacting proximal atrial tissue with the electrodes (186) disposed on the proximal spline portions (62) to detect multiple local electric voltages from endocardial surface thereat; and contacting atrial tissue with the electrodes (186) disposed on the medial spline portions (64) and the distal spline portions (66) to detect multiple local electric voltages from endocardial surface thereat. The splines (14) of the basket assembly (12) may be flexible to match the contours of the right atrium. Substantially all of the electrodes (186) may contact atrial tissue. Substantially all of the electrodes (186) may remain substantially spatially fixed with respect to atrial tissue. A substantial portion of atrial signals detected by the system (10) may have larger amplitudes than ventricular signals detected by the system (10). The splines (14) in the radially expanded non-spherical shape may contain a distal excurve outward bend (80) disposed at the distal portion (66) of the spline (14) at a location near to the distal tip (16) of the basket assembly (12) to bend the splines (14) back towards the proximal anchor (18); and wherein the splines (14) have a distal incurve inward bend (78) between said distal tip (16) and said distal excurve outward bends (80). The splines (14) of the basket assembly (12) may be flexible to match the contours of the right atrium.

[0200] While various embodiments of the present invention are specifically illustrated and/or described herein, it will be appreciated that modifications and variations of the present invention may be effected by those skilled in the art without departing from the spirit and intended scope of the invention. Further, any of the embodiments or aspects of the invention as described in the claims or in the specification may be used with one and another without limitation.

1.-31. (canceled)

32. A device for insertion into a body lumen, comprising: an electrode assembly strip comprising:

a polymeric substrate having an upper surface and an opposed lower surface;

one or more electrodes disposed over a portion of the upper surface of the polymeric substrate; and

one or more electrical traces disposed over a portion of the lower surface of the polymeric substrate in electrical communication with the one or more electrodes by way of metal plated holes through the substrate; and

a polymeric member having an outer surface and a substrate wall;

wherein the electrode assembly strip is securably disposed at the outer surface of the polymeric member.

33. The device of claim 32, wherein the electrode assembly strip is compressingly and thermally bonded to the outer surface of the polymeric member.

34. The device of claim 32, wherein the electrode assembly strip has a thickness from about 0.0005 inches to about 0.008 inches.

35. The device of claim 32 further comprising:

an upper polymeric layer covering portions of the substrate surface of the polymeric substrate not having the one or more electrodes thereon.

36. The device of claim 32 further comprising:

a lower polymeric layer covering the one or more electrical traces and portions of the lower surface of the substrate not having the one or more electrical traces thereon.

37. The device of claim 32, wherein the polymeric substrate comprises a biocompatible polyimide material.

38. The device of claim 32, wherein the polymeric substrate comprises a biocompatible polyether block amide material.

39. The device of claim 32, wherein the polymeric member comprises a biocompatible polymer selected from the group consisting of polyesters, silicones, silicone rubbers, urethanes and combinations thereof.

40. The device of claim 32, wherein the polymeric substrate is a sheet.

41. The device of claim 32, wherein the polymeric member is an extruded tube having an open lumen.

42. The device of claim 32, wherein the one or more electrodes comprise copper; gold, platinum, platinum black, platinum-iridium and combinations thereof.

43. The device of claim 32, wherein the electrode assembly strip has a substantially smooth and atraumatic overall outer surface.

44. The device of claim 32 further comprising:

a spline;

wherein the electrode assembly strip is disposed over the spline.

45. The device of claim 44, wherein the spline comprises a shape memory material.

46. The device of claim 45, wherein the shape memory material comprises nitinol.

47. The device of claim 32 further comprising:

a spline;

wherein the polymeric member is an extruded tube having an open lumen; and

wherein the spline is disposed within the extruded tube.

48. A device for insertion into a body lumen, comprising: an elongate tubular member having a lumen, a proximal end and a distal end;

at least two flexible splines having proximal portions, distal portions and medial portions therein between;

an anchor for guiding the proximal portions of the splines into the lumen of the elongate tubular member at the distal end of the elongate tubular member;

a tip for receiving the distal portions of the splines; and an electrode assembly disposed over at least one of the splines.

49. The device of claim 48, wherein the electrode assembly comprises:

a polymeric substrate having an upper surface and an opposed lower surface;

one or more electrodes disposed over a portion of the upper surface of the polymeric substrate; and one or more electrical traces disposed over a portion of the lower surface of the polymeric substrate in electrical communication with the one or more electrodes by way of metal plated holes through the substrate.

**50.** A device for insertion into a body lumen, comprising: an elongate tubular member having a lumen, a proximal end and a distal end;

at least one flexible spline having opposed spline ends and a medial portion therein between;

an anchor for guiding proximal portions of the spline near the spline ends into the lumen of the elongate tubular member at the distal end of the elongate tubular member;

a tip for receiving the medial portion of the spline;

a polymeric tube disposed over a portion of the spline; and an electrode assembly disposed over a portion of the polymeric tube.

**51.** The device of claim **48**, wherein the electrode assembly comprises:

a polymeric substrate having an upper surface and an opposed lower surface;

one or more electrodes disposed over a portion of the upper surface of the polymeric substrate; and

one or more electrical traces disposed over a portion of the lower surface of the polymeric substrate in electrical communication with the one or more electrodes by way of metal plated holes through the substrate.

\* \* \* \* \*

专利名称(译)	篮式心脏标测导管，具有无创伤，金属两部分远端尖端，用于检测心律失常		
公开(公告)号	<a href="#">US20190239767A1</a>	公开(公告)日	2019-08-08
申请号	US16/270719	申请日	2019-02-08
[标]申请(专利权)人(译)	托佩拉公司		
申请(专利权)人(译)	TOPERA INC.		
当前申请(专利权)人(译)	TOPERA INC.		
[标]发明人	KORDIS THOMAS F SEHRA RUCHIR JOHNSON ERIC T KENT DARRIN J RAGLAND ROBERT RYAN		
发明人	KORDIS, THOMAS F. SEHRA, RUCHIR JOHNSON, ERIC T. KENT, DARRIN J. RAGLAND, ROBERT RYAN		
IPC分类号	A61B5/042 A61B5/00 A61B18/14		
CPC分类号	A61B5/0422 A61B5/6859 A61B5/042 A61B5/6858 A61B18/1492 Y10T29/49117 A61B2018/00267 A61B2018/00351 F04C2270/0421 A61B2562/17 A61B2018/0016		
优先权	61/555190 2011-11-03 US 61/478340 2011-04-22 US		
外部链接	<a href="#">Espacenet</a> <a href="#">USPTO</a>		

摘要(译)

一种用于从心脏的心内膜表面感测多个局部电压的系统，包括：细长管状构件，具有内腔，近端和远端；多个柔性花键；用于固定地固定花键的近端部分的锚固件，其中锚固件牢固地固定在细长管状构件的远端处的细长管状构件的内腔中；金属尖端用于固定地固定花键的远端部分。

