



(19) **United States**

(12) **Patent Application Publication**
SHINAR et al.

(10) **Pub. No.: US 2019/0254570 A1**

(43) **Pub. Date: Aug. 22, 2019**

(54) **MONITORING A SLEEPING SUBJECT**

(71) Applicant: **EARLYSENSE LTD.**, Ramat Gan (IL)

(72) Inventors: **Zvika SHINAR**, Binyamina (IL);
Maayan DAVIDOVICH, Haifa (IL);
Tal KLAP, Ramat Gan (IL); **Smadar**
HOFFERT, Givat Shmuel (IL); **Guy**
MEGER, Haifa (IL)

(73) Assignee: **EARLYSENSE LTD.**

(21) Appl. No.: **16/398,572**

(22) Filed: **Apr. 30, 2019**

Related U.S. Application Data

(63) Continuation of application No. 14/474,357, filed on Sep. 2, 2014, now Pat. No. 10,292,625, which is a continuation-in-part of application No. 13/906,325, filed on May 30, 2013, now Pat. No. 8,882,684, which is a continuation-in-part of application No. 13/389,200, filed on Jun. 13, 2012, now abandoned, filed as application No. PCT/IL2011/050045 on Dec. 7, 2011, said application No. 13/906,325 is a continuation-in-part of application No. PCT/IL2013/050283, filed on Mar. 24, 2013, said application No. 14/474,357 is a continuation-in-part of application No. PCT/IL2014/050644, filed on Jul. 17, 2014.

(60) Provisional application No. 61/420,402, filed on Dec. 7, 2010, provisional application No. 61/439,971, filed on Feb. 7, 2011, provisional application No. 61/561,962, filed on Nov. 21, 2011, provisional application No. 61/618,792, filed on Apr. 1, 2012, provisional application No. 61/696,326, filed on Sep. 4, 2012, provisional application No. 61/698,736, filed on Sep. 10, 2012, provisional application No. 61/722,810, filed on Nov. 6, 2012, provisional application No. 61/725,513, filed on Nov. 13, 2012, provisional application No. 61/739,033, filed on Dec. 19, 2012, provisional application No. 61/748,081, filed on Jan. 1, 2013, provisional application No. 61/756,003, filed

on Jan. 24, 2013, provisional application No. 61/757,739, filed on Jan. 29, 2013, provisional application No. 61/764,541, filed on Feb. 14, 2013, provisional application No. 61/772,553, filed on Mar. 5, 2013, provisional application No. 61/847,579, filed on Jul. 18, 2013, provisional application No. 61/926,499, filed on Jan. 13, 2014.

Publication Classification

- (51) **Int. Cl.**
A61B 5/11 (2006.01)
A61B 5/00 (2006.01)
G08B 21/02 (2006.01)
G08B 25/00 (2006.01)
G08B 21/04 (2006.01)
A61B 5/0205 (2006.01)
- (52) **U.S. Cl.**
 CPC *A61B 5/1102* (2013.01); *A61B 5/746* (2013.01); *G08B 21/0211* (2013.01); *A61B 5/6892* (2013.01); *A61B 5/002* (2013.01); *A61B 5/4815* (2013.01); *A61B 5/4809* (2013.01); *G08B 21/0461* (2013.01); *A61B 5/6891* (2013.01); *A61B 5/11* (2013.01); *A61B 5/02055* (2013.01); *A61G 2203/36* (2013.01); *A61B 5/1115* (2013.01); *G08B 25/006* (2013.01)

(57) **ABSTRACT**

Apparatus and methods are described, including apparatus for use with a subject who shares a bed with a second person. A motion sensor detects motion of the subject and motion of the second person, and generates a motion signal in response thereto. A control unit identifies components of the motion signal that were generated in response to motion of the subject, by distinguishing between components of the motion signal that were generated in response to motion of the subject, and components of the motion signal that were generated in response to motion of the second person. The control unit analyzes the components of the motion signal that were generated in response to motion of the subject and generates an output in response thereto. Other applications are also described.








FIG. 1










FIG. 6A





FIG. 5







FIG. 7







FIG. 9A

FIG. 9B









FIG. 11




FIG. 12




FIG. 13




FIG. 14




FIG. 15





FIG. 16






FIG. 18




FIG. 19




FIG. 20




FIG. 21





FIG. 22






FIG. 24





FIG. 25






FIG. 27A




FIG. 27B




FIG. 28






FIG. 29









FIG. 32






FIG. 33A




FIG. 33B

MONITORING A SLEEPING SUBJECT**CROSS-REFERENCE TO RELATED APPLICATIONS**

[0001] The present application is a continuation of U.S. application Ser. No. 14/474,357, which is a continuation-in-part of:

[0002] (a) U.S. application Ser. No. 13/906,325 to Halperin, issued as U.S. Pat. No. 8,882,684, filed May 30, 2013, which is a continuation-in-part of:

[0003] (i) U.S. patent application Ser. No. 13/389,200, filed Jun. 13, 2012 (published as US 2012/0253142, now abandoned), which is a US national phase of International Application PCT/IL2011/050045 (published as WO 12/077113), filed Dec. 7, 2011, which claims the benefit of the following U.S. provisional patent applications:

[0004] U.S. Provisional Application 61/420,402, filed Dec. 7, 2010;

[0005] U.S. Provisional Application 61/439,971, filed Feb. 7, 2011; and

[0006] U.S. Provisional Application 61/561,962, filed Nov. 21, 2011; and

[0007] (ii) International Application PCT/IL2013/050283 (published as WO 13/150523), filed Mar. 24, 2013, which claims priority from the following U.S. provisional patent applications:

[0008] U.S. Provisional Patent Application No. 61/618,792, filed Apr. 1, 2012;

[0009] U.S. Provisional Patent Application No. 61/696,326, filed Sep. 4, 2012;

[0010] U.S. Provisional Patent Application No. 61/698,736, filed Sep. 10, 2012;

[0011] U.S. Provisional Patent Application No. 61/722,810, filed Nov. 6, 2012;

[0012] U.S. Provisional Patent Application No. 61/725,513, filed Nov. 13, 2012;

[0013] U.S. Provisional Patent Application No. 61/739,033, filed Dec. 19, 2012;

[0014] U.S. Provisional Patent Application No. 61/748,081, filed Jan. 1, 2013;

[0015] U.S. Provisional Patent Application No. 61/756,003, filed Jan. 24, 2013;

[0016] U.S. Provisional Patent Application No. 61/757,739, filed Jan. 29, 2013;

[0017] U.S. Provisional Patent Application No. 61/764,541, filed Feb. 14, 2013; and

[0018] U.S. Provisional Patent Application No. 61/772,553, filed Mar. 5, 2013; and

[0019] (b) International Application PCT/IL2014/050644 (published as WO 15/008285), filed Jul. 17, 2014, which claims the benefit of (i) U.S. Provisional Application 61/847,579, filed Jul. 18, 2013, and (ii) U.S. Provisional Application 61/926,499, filed Jan. 13, 2014.

[0020] Each of the above-referenced applications is assigned to the assignee of the present application and is incorporated herein by reference.

FIELD OF THE INVENTION

[0021] The present invention relates generally to monitoring subjects and predicting and monitoring abnormal physiological conditions and treating those conditions, and specifically to methods and apparatus for predicting and

monitoring abnormal physiological conditions by non-contact measurement and analysis of characteristics of physiological and/or physical parameters.

BACKGROUND

[0022] Chronic diseases are often expressed by episodic worsening of clinical symptoms. Preventive treatment of chronic diseases reduces the overall dosage of required medication and associated side effects, and lowers mortality and morbidity. Generally, preventive treatment should be initiated or intensified as soon as the earliest clinical symptoms are detected, in order to prevent progression and worsening of the clinical episode and to stop and reverse the pathophysiological process. Therefore, the ability to accurately monitor pre-episodic indicators increases the effectiveness of preventive treatment of chronic diseases.

[0023] Many chronic diseases cause systemic changes in vital signs, such as breathing and heartbeat patterns, through a variety of physiological mechanisms. For example, common respiratory disorders, such as asthma, chronic obstructive pulmonary disease (COPD), sleep apnea and cystic fibrosis (CF), are direct modifiers of breathing and/or heartbeat patterns. Other chronic diseases, such as diabetes, epilepsy, and certain heart conditions (e.g., congestive heart failure (CHF)), are also known to modify cardiac and breathing activity. In the case of certain heart conditions, such modifications typically occur because of pathophysiologicals related to fluid retention and general cardiovascular insufficiency. Other signs such as coughing and sleep restlessness are also known to be of importance in some clinical situations.

[0024] Many chronic diseases induce systemic effects on vital signs. For example, some chronic diseases interfere with normal breathing and cardiac processes during wakefulness and sleep, causing abnormal breathing and heartbeat patterns.

[0025] Breathing and heartbeat patterns may be modified via various direct and indirect physiological mechanisms, resulting in abnormal patterns related to the cause of modification. Some respiratory diseases, such as asthma, and some heart conditions, such as CHF, are direct breathing modifiers. Other metabolic abnormalities, such as hypoglycemia and other neurological pathologies affecting autonomic nervous system activity, are indirect breathing modifiers.

SUMMARY OF THE INVENTION

[0026] Some applications of the present invention provide methods and systems for monitoring subjects for the occurrence or recurrence of a physiological event, for example, a chronic illness or ailment. This monitoring assists the subject or healthcare provider in treating the ailment or mitigating the effects of the ailment. Some applications of the present invention provide techniques for monitoring vital and non-vital signs using automated sensors and electronic signal processing, in order to detect and characterize the onset of a physiological event, and, for some applications, to treat the event, such as with therapy or medication.

[0027] In some cases, a subject is monitored not to predict or track disease situations, but rather, in order to allow the subject to optimize long term health and fitness as part of a 'wellness' approach, and/or in order to control household devices (e.g., bedside lamps, mobile phones, alarm clocks,

etc.) in a manner that increases their usefulness and/or minimizes the disturbances caused by these devices.

[0028] There is therefore provided, in accordance with some applications of the present invention, apparatus for use with a subject who shares a bed with a second person, the apparatus including:

[0029] a motion sensor configured to:

[0030] detect motion of the subject without contacting the subject, without contacting clothes the subject is wearing, without viewing the subject, and without viewing clothes the subject is wearing,

[0031] detect motion of the second person without contacting the second person, without contacting clothes the second person is wearing, without viewing the second person, and without viewing clothes the second person is wearing, and

[0032] generate a motion signal in response to detecting motion of the subject and motion of the second person; and

[0033] a control unit configured to:

[0034] identify components of the motion signal that were generated in response to motion of the subject, by distinguishing between components of the motion signal that were generated in response to motion of the subject, and components of the motion signal that were generated in response to motion of the second person,

[0035] analyze the components of the motion signal that were generated in response to motion of the subject, and

[0036] generate an output in response thereto.

[0037] In some applications, the control unit is configured to identify components of the motion signal that were generated in response to motion of the subject, by identifying components of the motion signal that have a signal strength that is a characteristic signal strength of a motion signal of the subject.

[0038] In some applications, the control unit is configured to identify components of the motion signal that were generated in response to motion of the subject by identifying components of the motion signal that have a pattern that is a characteristic pattern of motion of the subject.

[0039] In some applications, the apparatus further includes a weight sensor that is configured to detect when the subject is lying above the motion sensor, and the control unit is configured to identify the components of the motion signal that were generated in response to motion of the subject, in response to a signal that is generated by the weight sensor.

[0040] In some applications, the motion sensor is configured to facilitate the identification of components of the motion signal that were generated in response to motion of the subject, by strengthening a signal strength of the components of the motion signal that are generated in response to motion of the subject.

[0041] In some applications, the apparatus is for use with a subject who lies on a mattress, and the sensor is configured to be placed at a position selected from the group consisting of: underneath the mattress at a position that is higher than a head of the subject is typically placed, and adjacent to and in contact with a side of the mattress.

[0042] In some applications, the sensor is configured such as to facilitate identification, by the control unit, of components of the motion signal that were generated in response to a longitudinal cardio-ballistic effect of the subject.

[0043] In some applications, the control unit is configured to identify components of the motion signal that were generated in response to respiratory motion of the subject.

[0044] In some applications, the control unit is configured to identify components of the motion signal that were generated in response to cardiac motion of the subject.

[0045] In some applications, the control unit is configured to identify components of the motion signal that were generated in response to large body-movement of the subject.

[0046] In some applications, the control unit is further configured to:

[0047] analyze the motion signal,

[0048] in response thereto, identify an effect of large body-movement of the second person on sleep of the subject, and

[0049] in response thereto, generate a sleep-disturbance output.

[0050] In some applications, the sleep-disturbance output includes an assessment of an effectiveness of a parameter at reducing the effect of the large body-movement of the second person on the sleep of the subject, the control unit being configured to generate the assessment of the effectiveness of the parameter.

[0051] In some applications, the parameter is selected from the group consisting of: a parameter of a mattress on which the subject is sleeping, a parameter of the bed, a sleeping arrangement of the subject and the second person, and a room-environment parameter, the control unit being configured to generate the assessment of the effectiveness of the selected parameter.

[0052] In some applications, the sleep-disturbance output includes a recommendation to reduce the effect of the large body-movement of the second person on the sleep of the subject by adjusting an adjustable parameter, the control unit being configured to generate the recommendation.

[0053] In some applications, the adjustable parameter is selected from the group consisting of: a parameter of a mattress on which the subject is sleeping, a parameter of the bed, a sleeping arrangement of the subject and the second person, and a room-environment parameter, the control unit being configured to generate the recommendation to adjust the selected parameter.

[0054] In some applications, the sleep-disturbance output includes instructions to a device to adjust an adjustable parameter, the control unit being configured to generate the instructions.

[0055] In some applications, the adjustable parameter is selected from the group consisting of: a parameter of a mattress on which the subject is sleeping, a parameter of the bed, a sleeping arrangement of the subject and the second person, and a room-environment parameter, the control unit being configured to generate the instructions to the device to adjust the selected parameter.

[0056] In some applications,

[0057] the motion sensor includes a mechanical-filtering element configured to reduce a response of the motion sensor to motion of the second person, relative to motion of the subject, and

[0058] the control unit is further configured to:

[0059] by analyzing the motion signal, assess an effectiveness of the mechanical-filtering element at reducing the response of the motion sensor to motion of the second person, and

[0060] generate an output in response thereto.

[0061] In some applications, the control unit is configured to identify that a portion of the motion signal was generated in response to motion of the second person, and not in response to motion of the subject, by identifying that the portion exhibits ringing.

[0062] In some applications, the motion sensor consists of a single motion sensor.

[0063] The present invention will be more fully understood from the following detailed description of embodiments thereof, taken together with the drawings, in which:

BRIEF DESCRIPTION OF THE DRAWINGS

[0064] FIG. 1 is a schematic illustration of a system for monitoring a chronic medical condition of a subject, in accordance with some applications of the present invention;

[0065] FIG. 2 is a schematic block diagram illustrating components of a control unit of the system of FIG. 1, in accordance with some applications of the present invention;

[0066] FIG. 3 is a schematic block diagram illustrating a breathing pattern analysis module of the control unit of FIG. 2, in accordance with some applications of the present invention;

[0067] FIG. 4 is a schematic block diagram illustrating additional components of a pattern analysis module of the control unit of FIG. 2, in accordance with some applications of the present invention;

[0068] FIG. 5 is a schematic illustration of a semi-rigid sensor plate that is used as a motion sensor, in accordance with some applications of the present invention;

[0069] FIGS. 6A-B are schematic illustrations of a motion sensor coupled to a chair, in accordance with some applications of the present invention;

[0070] FIG. 7 is a schematic illustration of apparatus for identifying inefficient respiration of a subject, in accordance with some applications of the present invention;

[0071] FIG. 8 is a schematic illustration of a method for detecting ectopic heartbeats, in accordance with some applications of the present invention;

[0072] FIGS. 9A-B are schematic illustrations of a motion sensor comprising a sensor plate, in accordance with some applications of the present invention;

[0073] FIGS. 10A-D are schematic illustrations of a sensor-holding plate, in accordance with some applications of the present invention;

[0074] FIG. 11 is a schematic illustration of apparatus comprising a motion sensor, control unit, and speaker, in accordance with some applications of the present invention;

[0075] FIG. 12 is a schematic illustration of apparatus comprising a motion sensor, control unit, and alarm clock, in accordance with some applications of the present invention;

[0076] FIG. 13 is a schematic illustration of a motion sensor powered by a power supply and rechargeable battery, in accordance with some applications of the present invention;

[0077] FIG. 14 is a schematic illustration of apparatus for controlling a thermoregulation device, in accordance with some applications of the present invention;

[0078] FIG. 15 is a schematic illustration of a sensor configured to be placed within a pillow, in accordance with some applications of the present invention;

[0079] FIG. 16 is a schematic illustration of ballistocardiographic signals used for calculating an indication of a

left-ventricular-ejection-time, in accordance with some applications of the present invention;

[0080] FIG. 17 is a schematic illustration of apparatus for use with a plurality of sleeping subjects, in accordance with some applications of the present invention;

[0081] FIG. 18 is a schematic illustration of apparatus for activating a medical device for a subject who is sleeping in proximity to at least one other person, in accordance with some applications of the present invention;

[0082] FIGS. 19-20 are schematic illustrations of apparatus for use with a person who is on a resting surface and for use with an illuminator, in accordance with some applications of the present invention;

[0083] FIG. 21 is a schematic illustration of apparatus for use with a waking mechanism that executes a waking routine to wake a subject who is sleeping near a second person, in accordance with some applications of the present invention;

[0084] FIG. 22 is a schematic illustration of apparatus for use with a waking mechanism that executes a waking routine to wake a subject who is on a resting surface, in accordance with some applications of the present invention;

[0085] FIG. 23 is a schematic illustration of apparatus for use with (i) a waking mechanism that executes a waking routine to wake a subject who is on a resting surface, and (ii) an output unit, in accordance with some applications of the present invention;

[0086] FIG. 24 is a schematic illustration of apparatus for identifying a posture of a subject, in accordance with some applications of the present invention;

[0087] FIG. 25 is a schematic illustration of apparatus for monitoring a subject, in accordance with some applications of the present invention; and

[0088] FIG. 26 is a schematic illustration of apparatus for monitoring a subject, in accordance with some applications of the present invention.

[0089] FIG. 27A is a schematic illustration of apparatus comprising a motion sensor, a mains-power-connection device, and a control unit, in accordance with some applications of the present invention;

[0090] FIG. 27B is a schematic illustration of a mains-power-connection device, in accordance with some applications of the present invention;

[0091] FIGS. 28 and 29 are schematic illustrations of apparatus for use with a burglar alarm, in accordance with some applications of the present invention;

[0092] FIG. 30 is a schematic illustration of apparatus for use with a burglar alarm, in accordance with some applications of the present invention;

[0093] FIG. 31 is a schematic illustration of various apparatus for use with a subject who shares a bed with a second person, in accordance with some applications of the present invention;

[0094] FIG. 32 is a plot of a motion signal that includes a portion thereof that exhibits ringing, as analyzed in accordance with some applications of the present invention; and

[0095] FIGS. 33A-B are schematic illustrations of respective views of a motion sensor, in accordance with some applications of the present invention.

DETAILED DESCRIPTION OF APPLICATIONS

[0096] FIG. 1 is a schematic illustration of a system 10 for monitoring a chronic medical condition of a subject 12, in accordance with some applications of the present invention.

System 10 typically comprises a motion sensor 30, a control unit 14, and a user interface (U/I) 24. System 10 is generally similar to system 10 described in US 2011/0112442 to Meger and in US 2012/0253142 to Meger, both of which applications are incorporated herein by reference, except for differences described herein. For some applications, user interface 24 is integrated into control unit 14, as shown in the figure, while for other applications, the user interface and the control unit are separate units. Typically, user interface 24 includes a display. For some applications, motion sensor 30 is integrated into control unit 14, in which case user interface 24 is either also integrated into control unit 14 or remote from control unit 14. For some applications, control unit 14 and/or user interface 24 of system 10 are implemented in a mobile device (such as a cellular phone, a pager, and/or a tablet computer).

[0097] In some applications of the present invention, motion sensor 30 is a “non-contact sensor,” that is, a sensor that does not contact the body of subject 12 or clothes subject 12 is wearing. In other applications, motion sensor 30 does contact the body of subject 12 or clothes subject 12 is wearing. In the former applications, because motion sensor 30 does not come in contact with subject 12, motion sensor 30 detects motion of subject 12 without discomforting or inconveniencing subject 12. For some applications, motion sensor 30 performs sensing without the knowledge of subject 12, and even, for some applications, without the consent of subject 12. For some applications, motion sensor 30 does not have a direct line of sight with subject 12 or the clothes subject 12 is wearing.

[0098] (It is noted that generally, in the present description, the term “motion sensor 30” is used to refer to a sensor that does not contact or view the subject or clothes the subject is wearing, while the term “sensor 316” refers more generally to any type of sensor, e.g., a sensor that includes an electromyographic sensor and/or an imaging sensor. Thus, a phrase such as “sensor 316 (e.g., motion sensor 30)” should be construed to mean that the scope of the described invention includes the use of any type of sensor, but specifically, a non-contact and non-viewing sensor may be used.)

[0099] Motion sensor 30 may comprise a ceramic piezoelectric sensor, vibration sensor, pressure sensor, or strain sensor, for example, a strain gauge, configured to be installed under a resting surface 37, and to sense motion of subject 12. The motion of subject 12 sensed by sensor 30, during sleep, for example, may include regular breathing movement, heartbeat-related movement, and other, unrelated body movements, as discussed below, or combinations thereof. For some applications, sensor 30 comprises a standard communication interface (e.g. USB), which enables connection to standard monitoring equipment.

[0100] As shown in FIG. 2 (described hereinbelow), for some applications, in addition to wirelessly-enabled motion sensor 30, control unit 14 is coupled to one or more additional sensors 60 applied to subject 12, such as a blood oxygen monitor 86 (e.g., a pulse oximeter/photoplethysmograph), an ECG monitor 62, weight sensor 81 (e.g. a weight sensor embedded into a bed as manufactured by Stryker Inc. of Kalamazoo, Mich.), a moisture sensor 85, an angle sensor 87, and/or a temperature sensor 80. In accordance with respective applications, one or more of sensors 60 is a contact sensor or a contact-less sensor.

[0101] Most of the experimental results presented in the present application were measured using one or more piezoelectric sensors. Nevertheless, the scope of the present invention includes performing measurements with other motion sensors 30, such as other pressure gauges or accelerometers.

[0102] Motion sensor 30 is typically coupled to a resting surface 37 upon which the subject rests. For example, as shown in FIG. 1, motion sensor 30 may be placed under a mattress of a bed, and may sense motion of the subject while the subject is in the bed, and generate a motion sensor signal in response thereto. Alternatively or additionally, as shown in FIGS. 6A-B and as described in further detail in US 2013/0267791 to Halperin, which is incorporated herein by reference, motion sensor 30 may be coupled to a chair (e.g., a wheelchair) upon which the subject sits, and may sense motion of the subject while the subject is sitting in the chair, and generate a motion sensor signal in response thereto. For some applications, system 10 includes a first motion sensor which is under the mattress of the subject’s bed, and a second motion sensor 30, which is coupled to a chair in the subject’s room. The first sensor senses motion of the subject while the subject is in the bed, and the second motion sensor senses motion of the subject while the subject is in the chair. System 10 monitors the subject responsively to both the first and the second sensor signals, as described in US 2013/0267791 to Halperin, which is incorporated herein by reference. For some applications, a plurality of motion sensors are coupled to a single resting surface, and are used as motion sensor 30. For example, two or more motion sensors that are disposed under the subject’s mattress may be used as motion sensor 30. Alternatively, only a single sensor is coupled to a given resting surface.

[0103] FIG. 2 is a schematic block diagram illustrating components of control unit 14 in accordance with some applications of the present invention. Control unit 14 typically comprises a motion data acquisition module 20 and a pattern analysis module 16. Pattern analysis module 16 typically comprises one or more of the following modules: a breathing pattern analysis module 22, a heartbeat pattern analysis module 23, a cough analysis module 26, a restlessness analysis module 28, a blood pressure analysis module 29, and an arousal analysis module 31. For some applications, pattern analysis module 16 includes additional modules and/or functionalities to those shown in FIG. 2. For example, pattern analysis module 16 may include one or more of the additional modules and/or functionalities shown in FIG. 4. For some applications, two or more of analysis modules 20, 22, 23, 26, 28, 29, and 31 (and/or the additional modules and/or functionalities) are packaged in a single housing. For other applications, the modules are packaged separately (for example, so as to enable remote analysis, by one or more of the pattern analysis modules, of breathing signals acquired locally by data acquisition module 20).

[0104] User interface 24 typically comprises a dedicated display unit, such as an LCD or CRT monitor. Alternatively or additionally, the user interface 24 comprises a wireless or wired communication port for relaying the acquired raw data and/or processed data to a remote site for further analysis, interpretation, expert review, and/or clinical follow-up. For example, the data may be transferred over a telephone line, and/or over the Internet or another wide-area network, either wirelessly or via wires.

[0105] Breathing pattern analysis module 22 is configured to extract breathing patterns from the motion data, as described hereinbelow with reference to FIG. 3, and heartbeat pattern analysis module 23 is configured to extract heartbeat patterns from the motion data. Alternatively or additionally, system 10 comprises another type of sensor, such as an acoustic or air-flow sensor attached or directed at the subject's face, neck, chest, and/or back, or placed under the mattress.

[0106] FIG. 3 is a schematic block diagram illustrating components of breathing pattern analysis module 22, in accordance with some applications of the present invention. Breathing pattern analysis module 22 analyzes changes in breathing patterns, typically during sleep. Breathing pattern analysis module 22 typically comprises a digital signal processor (DSP) 41, a dual port RAM (DPR) 42, an EEPROM 44, and an I/O port 46. Modules 23, 26, 28, 29, and 31 may be similar to module 22 shown in FIG. 3. For example, modules 23, 26, 28, 29, and 31 may include a digital signal processor, a dual port RAM, an EEPROM, and an I/O port similar to digital signal processor 41, dual port RAM 42, EEPROM 44, and I/O port 46. Breathing pattern analysis module 22 may be used (e.g., to facilitate ascertaining a sleep stage of a subject) with various apparatus and methods described herein, such as, for example, apparatus 334, described hereinbelow with reference to FIGS. 19-20.

[0107] In some applications of the present invention, data acquisition module 20 is configured to non-invasively monitor breathing and heartbeat patterns of subject 12. Breathing pattern analysis module 22 and heartbeat pattern analysis module 23 are configured to extract breathing patterns and heartbeat patterns respectively from the raw data generated by data acquisition module 20, and to perform processing and classification of the breathing patterns and the heartbeat patterns, respectively. Breathing pattern analysis module 22 and heartbeat pattern analysis module 23 are configured to analyze the respective patterns in order to (a) predict an approaching clinical episode, such as an asthma attack, heart condition-related lung fluid buildup, sepsis, cardiac arrest, or respiratory depression, and/or (b) monitor the severity and progression of a clinical episode as it occurs. User interface 24 is configured to notify subject 12 and/or a clinician of the predicted or occurring episode. Prediction of an approaching clinical episode facilitates early preventive treatment, which generally improves outcomes, e.g., by lowering required dosages of medication, and/or lowering mortality and morbidity. When treating a hospitalized subject in a general care ward, for example, an earlier identification of subject deterioration may prevent the need to admit the subject to the ICU, shorten his length of stay, and increase the likelihood for successful recovery to discharge.

[0108] Breathing pattern analysis module 22 and heartbeat pattern analysis module typically derive breathing patterns and heartbeat patterns from the raw data in accordance with the techniques described in US 2011/0112442 to Meger and in US 2012/0253142 to Meger, both of which applications are incorporated herein by reference. In general, system 10 is configured to monitor clinical parameters of the subject, and to generate alerts and/or reports in response thereto, in a generally similar manner to system 10 described US 2011/0112442 to Meger and in US 2012/0253142 to Meger, both of which applications are incorporated herein by reference.

[0109] Reference is now made to FIG. 4, which is a schematic illustration of functionalities and/or modules that are included in pattern analysis module 16, in addition to the modules of the pattern analysis module that are shown in FIG. 2, in accordance with some applications of the present invention. Typically, pattern analysis module includes signal analysis functionality 90. The signal analysis functionality is configured to analyze the signals received from the sensors that provide input to control unit 14 and to determine a condition of the subject and/or generate an output (e.g., an alert), in response thereto. Many of the functionalities of control unit 14 that are described herein as being performed by pattern analysis module 16 are performed by the signal analysis functionality of the pattern analysis module. Pattern analysis module typically further includes alert-generation-functionality 92 that is configured to generate an alert in response to the signal analysis that is performed by the signal analysis functionality. For example, alerts may be generated on pagers of clinicians, at user interface (e.g., display) 24, and/or at a central monitoring system user interface (e.g., display). For some applications, pattern analysis module includes score calculating functionality 100 configured to calculate a score in response to the signal analysis that is performed by the signal analysis functionality. In accordance with some applications, pattern analysis module includes additional functionalities and/or modules, such as a shallow-breathing-pattern-identification functionality 101, a subject identification module 102, a subject-position-identification functionality 104, an irregular-sleep-detection functionality 106, a decreasing-cardiobalistic-amplitude-detection functionality 108, a cardiac-arrhythmia-detection functionality 110, an inefficient respiration identification functionality 111, a cardiac-risk-detection functionality 112, protocol input functionality 114, athletic-exercise-receiving functionality 116, and/or nutrition-receiving functionality 118. The functions of at least some of the additional functionalities and/or modules are described in further detail hereinbelow.

[0110] For some applications, the pattern analysis module includes subject identification module 102. The subject identification module is configured to determine which motion signals detected by motion sensor 30 were generated by the subject. For example, in cases in which the subject who is being monitored is sharing a bed with a second person (e.g., the subject's partner), the subject identification module determines which components of the motion signal detected by the motion sensor were generated by the subject and which were generated by the second person. The pattern analysis module then analyzes the components of the signal that were generated by the subject, and generates outputs (such as alerts), as described herein, in response thereto. For some applications, the subject identification module is configured to determine when the subject is out of bed by determining that the motion signal detected by the motion detector is being generated by the second person. For some applications, the subject identification module is configured to determine which components of the motion signal detected by the motion sensor were generated by the subject even when the subject is smaller than the second person.

[0111] For some applications, subject identification module 102 is configured to determine which components of the motion signal detected by motion sensor 30 were generated by the subject using one or more of the following techniques:

[0112] a. The subject identification module identifies patterns (e.g., a respiratory pattern, a heart rate pattern, and/or a motion pattern, e.g., a large body-movement pattern) that are characteristic of, respectively, the subject and the second person. The subject identification module then determines that components of the signal that correspond to the characteristic patterns of the subject have been generated by the subject. For some applications, the subject identification module learns characteristic patterns of the subject by utilizing a weight sensor (e.g., as described hereinbelow), and/or or utilizing long term average patterns of the subject. For some applications, in response to an input to system **10**, the pattern identification module operates in a learning mode, in which the module learns characteristic patterns of the subject.

[0113] b. The subject identification module identifies characteristic signal strengths generated, respectively, by the subject and by the second person. For example, the sensor may be disposed underneath the subject who lies on a first side of the bed and the second person may typically lie on the second side of the bed. In such cases, signals generated by the subject are typically characterized as being of greater strength than those generated by the second person. Alternatively, the subject may be smaller than the second person, and may therefore generate signals that are characterized as being weaker than signals generated by the second person.

[0114] Reference is now made to FIGS. **33A-B**, which are schematic illustrations of respective views of motion sensor **30**, in accordance with some applications of the present invention. For some applications, motion sensor **30** is configured to facilitate determination by subject identification module **102** of which components of the motion signal were generated by the subject. For example, the sensor may be placed in a position, and/or shaped, such as to strengthen the signal that is received from the subject. For some applications, the sensor is placed underneath the subject's mattress at a position higher than where the subject rests his/her head, such that the strongest signals that the sensor receives are those generated by the longitudinal cardio-ballistic effect of the subject. Alternatively or additionally, at least a portion of the sensor is placed adjacent to and in contact with a side of the subject's mattress (e.g., the head of the subject's mattress), and not underneath the mattress. For some applications, the motion sensor comprises at least a portion of an L-shaped structure, as shown in FIGS. **33A-B**. The structure is shaped to define horizontal and vertical portions that form approximately (or precisely) a right angle with one another. The horizontal portion of the structure is placed underneath the subject's mattress, and the vertical portion of the structure is placed adjacent to and in contact with a side of the subject's mattress (e.g., the head of the subject's mattress). For some applications, the horizontal portion of the structure does not perform any sensing functionalities but acts as a support element **49** for supporting the vertical portion adjacent to and in contact with a side of the subject's mattress (e.g., the head of the subject's mattress), the vertical portion acting as sensor **30**.

[0115] Alternatively or additionally, a different support element is used to support sensor **30** at a position adjacent to and in contact with a side of the subject's mattress (e.g., the head of the subject's mattress). For example, a compressible member (such as a cushion) may be placed between the side of the mattress and a surface (e.g., a wall or a headboard) that is adjacent to the side of the mattress,

and may be configured to hold the sensor against the head of the mattress, by expanding against the side of the mattress. For some applications, the sensor is disposed on a stretchable band (e.g., an elastic band). The band is stretched in order to facilitate placement of the band around the sides of the subject's mattress, and the band then shrinks, such as to maintain the sensor adjacent to and in contact with a side of the subject's mattress (e.g., the head of the subject's mattress). For some applications, the sensor is not disposed on a stretchable band, but the sensor is maintained adjacent to and in contact with a side of the subject's mattress (e.g., the head of the subject's mattress), using a stretchable band.

[0116] For some applications, the motion sensor includes a weight sensor that is configured to measure a weight that is placed on top of the weight sensor, and to identify that the subject is lying above the motion sensor in response thereto. The subject identification module identifies signals from the motion sensor as having been generated by the subject, in response to the signal generated by the weight sensor. For some applications, the weight sensor is used to determine when the subject is directly on top of the weight sensor. In response to determining that the subject is directly on top of the weight sensor, the pattern identification module operates in a learning mode, in which the module learns characteristic patterns of the subject, as described hereinabove. For some applications, respective first and second motion sensors are placed underneath the subject and the second person who uses the bed. Subject identification module **102** determines which components of the motion signal were generated by the subject in response to the signals from both the first and the second motion sensors.

[0117] The above-described apparatus and techniques for subject identification may be utilized in combination with other apparatus and techniques described herein, such as, for example, apparatus and techniques described with reference to FIG. **32**.

[0118] Reference is now made to FIG. **7**, which is a schematic illustration of apparatus for identifying inefficient respiration of a subject **234**, in accordance with some applications of the present invention. Inefficient respiration may be indicative of a clinical episode related to a respiratory disorder such as obstructive apnea or asthma. Inefficient respiration corresponds to a situation in which the respiration movements are large relative to the volume of respiration flow. This phenomenon may occur in one of the two following ways:

[0119] 1) Respiration movements are normal, but the volume of respiration flow is abnormally low.

[0120] 2) The volume of respiration flow is normal, but respiration movements are abnormally large, such as where the subject needs to use upper-body muscles that are normally not used for respiration.

[0121] Reference is now made to FIGS. **4** and **7**. In some applications, pattern analysis module **16** of control unit **14** comprises inefficient respiration identification functionality **111**, as described hereinabove with respect to FIG. **4**. The identification of inefficient respiration typically proceeds according to the following steps:

[0122] 1. A respiration-related motion signal is identified in the mechanical sensor signal that is detected by sensor **30**. The amplitude of this signal corresponds to the respiration movements of the subject.

[0123] 2. The volume of respiration flow is measured, e.g., using a respiration flow meter **236** or sensor **30**. (Respiration

flow meter **236** may be handled by the subject, or alternatively, by a caregiver, e.g., a physician or nurse.)

[0124] 3. The inefficient respiration identification functionality calculates a relationship of the amplitude of the respiration-related motion signal to the volume of respiration flow, and inefficient respiration is identified in response to this relationship. For example, the relationship may comprise the quotient of the quantities, e.g., Amplitude of Signal/Volume of Flow. The quotient is compared to a baseline value, and inefficient respiration is identified in response to this comparison. For example, inefficient respiration may be identified if the quotient of Amplitude/Volume is increased by a factor of at least 1.5 relative to the baseline value (e.g., the factor may be 2).

[0125] Identifying the inefficient respiration in response to a relationship between the quantities, rather than based on the absolute values of the quantities, helps facilitate the identification of inefficient respiration even if one of the quantities is normal, as described hereinabove.

[0126] Reference is now made to FIG. 8, which is a schematic illustration of a method for detecting ectopic heartbeats, e.g., premature ventricular contractions, in accordance with some applications of the present invention. For some applications, heartbeat pattern analysis module **23** (FIG. 2) is configured to detect ectopic beats of a subject. The cardiac signal component of the sensor signal generated by sensor **30** is filtered into a high-frequency component **206** and a low-frequency component **204**. (Components **204** and **206** are shown plotted in arbitrary units in FIG. 8.) Since both normal and ectopic beats exhibit high-frequency characteristics indicative of ventricular contraction, the high frequency component indicates both normal and ectopic beats. On the other hand, ectopic beats lack some low-frequency characteristics indicative of blood flow; consequently, the low frequency component generally indicates normal (but not ectopic) beats. Portions **200** of the high-frequency component, corresponding to ventricular contractions of the subject, are identified by heartbeat pattern analysis module **23**; a pair of such portions typically indicates a single heartbeat. For each pair of portions **200**, a corresponding portion of the low-frequency component is analyzed. If this corresponding portion is indicative of blood flow, e.g., as shown in portions **202** (solid line), the heartbeat is determined to be a normal beat. Conversely, if the corresponding portion is not indicative of blood flow, e.g., as shown in portions **208** (dashed line), the heartbeat is determined to be an ectopic beat. For example, as shown in FIG. 8, a pair **201** of portions **200** corresponds to a portion **202** indicative of blood flow, while a pair **210** of portions **200** corresponds to a portion **208** which is not indicative of blood flow.

[0127] In some applications, the time between the two elements of a pair of portions **200** is used to diagnose cardiac conditions such as early heartbeats, missing heartbeats, and low stroke volume.

[0128] Filtering of the signal into high-frequency and low-frequency components is typically done using band-pass filters. In some applications, the lower cutoff frequency for the low-frequency band-pass filter may be, for example, at least 1.5 and/or less than 4 Hz (e.g., 2 Hz), while the higher cutoff frequency may be, for example, at least 4.1 and/or less than 7.5 Hz (e.g., 5 Hz). The lower cutoff frequency for the high-frequency band-pass filter may be, for example, at least 6.5 and/or less than 11.5 Hz (e.g., 9 Hz),

while the higher cutoff frequency may be, for example, at least 11.6 and/or less than 16.5 Hz (e.g., 14 Hz). In other applications, the lower cutoff frequency for the low-frequency band-pass filter may be, for example, at least 2.5 and/or less than 3.5 Hz, while the higher cutoff frequency may be, for example, at least 4.5 and/or less than 5.5 Hz. The lower cutoff frequency for the high-frequency band-pass filter may be, for example, at least 8.5 and/or less than 9.5 Hz, while the higher cutoff frequency may be, for example, at least 13.5 and/or less than 14.5 Hz.

[0129] Reference is now made to FIG. 5, which is a schematic illustration of a semi-rigid sensor plate **140** that is used as motion sensor **30**, in accordance with some applications of the present invention. For some applications, the sensor is designed and/or placed under the subject's bed such as to detect only motion of the subject who is lying on the side closer to the sensor. The sensor mechanical properties are designed to collect the vibration mechanical signal only locally from the subject lying directly on top or very close to the sensor. This allows mechanical filtering of signals coming from the partner, and detection of only the signal of the subject on top of the sensor. For some applications, edges **142** of the sensor plate are hardened with respect to a central portion **144** of the sensor plate. Typically, this prevents torque from the side of the sensor plate from bending the sensor plate, and allows only direct forces generated from on top of the sensor to affect the plate such as to generate a sensor signal. In some applications, the sensor hardening on the circumference is achieved by mechanically preventing a 2-5 mm rim of the semi-rigid sensing plate from vibrating. This typically substantially reduces the signal generated by the second person as compared to that generated by the subject.

[0130] Reference is now made to FIGS. 9A-B, which are schematic illustrations of motion sensor **30** comprising a sensor plate **238**, in accordance with some applications of the present invention. Sensor plate **238** is typically for use with a subject who shares a bed with a second person, e.g., as shown in FIG. 21. As shown in FIG. 9A, sensor plate **238** comprises an edge region **227** that is more rigid than a central portion **221** of the sensor plate, such as to reduce movement of the plate in response to motion of the second person, relative to if edge region **227** of the sensor plate were not more rigid than central portion **221**. As described hereinbelow, edge region **227** may take the form of a rigid noise filter rim **228**, and/or a rigid sensor-holding-plate rim **220**.

[0131] Motion sensor **30** is configured to be placed on the bed such that when the subject and the second person are on the bed (e.g., as in FIG. 21), sensor plate **238** is disposed underneath the subject and not disposed underneath the second person. When a sensor element **366** (e.g., a piezoelectric sensor element) is being held by a sensor-holding plate **218** of sensor plate **238**, motion sensor **30** detects motion of the subject, by sensor-holding plate **218** moving in response to motion of the subject. (The motion signal generated by motion sensor **30** is then analyzed by control unit **14**, as described throughout the present application.) The relative rigidity of edge region **227** generally reduces the extent to which motion of the second person is detected by motion sensor **30**, relative to motion of the subject. (In the present description, the word "sensor" may sometimes be used to refer to sensor element **366**.)

[0132] In some applications, a thickness of the edge region (e.g., thickness t described hereinbelow), measured between

an inner perimeter of the edge region and an outer perimeter of the edge region, is at least 2 mm and/or less than 20 mm, e.g., less than 8 mm.

[0133] In some applications, as shown in FIG. 9B, sensor plate 238 comprises sensor-holding plate 218 and a noise filter plate 226 that is distinct from sensor-holding plate 218. In such applications, noise filter plate 226 is typically shaped to define a noise filter rim 228. Noise filter rim 228 is more rigid than central portion 221 of the sensor-holding plate, such as to reduce movement of the sensor-holding plate in response to motion of the second person, relative to if the noise filter rim were not more rigid than the central portion of the sensor-holding plate. Thus, noise filter rim 228 allows for mechanical filtering of signals coming from the partner, in a manner generally described hereinabove with respect to edges 142 of sensor plate 140 (FIG. 5). Alternatively or additionally, sensor-holding plate 218 may be shaped to define a rigid sensor-holding-plate rim 220 (which is more rigid than central portion 221), the function of which is generally similar to that of noise filter rim 228. Typically, a thickness t_2 of the sensor-holding-plate rim, measured between an inner perimeter of the sensor-holding-plate rim and an outer perimeter of the sensor-holding-plate rim, is at least 2 mm and/or less than 8 mm, or alternatively, at least 8 mm and/or less than 20 mm.

[0134] In some applications, the top of noise filter rim 228 is generally level with the top of sensor-holding plate 218, while in other applications, the top of noise filter rim 228 is higher, e.g., it is greater than 1 and/or less than 5 mm higher. In some applications, a thickness t of noise filter rim 228, measured between an inner perimeter of the noise filter rim and an outer perimeter of the noise filter rim, is at least 2 mm and/or less than 8 mm, e.g., 5 mm.

[0135] Typically, sensor-holding plate 218 is shaped to hold sensor element 366, e.g., via a sensor receptacle 222, thus allowing for the sensor element to be coupled to the sensor plate. In some applications, the sensor-holding plate further comprises an electronics receptacle 224, configured to hold electronic circuitry which may include, for example, an amplifier, analog to digital converter, and/or a communication element. In other applications, the sensor-holding plate does not comprise electronics receptacle 224, and the circuitry is disposed outside of the sensor-holding plate.

[0136] In some applications, sensor-holding plate 218 is reversibly coupleable to noise filter plate 226. The coupling may be effected, for example, by means of sensor-holding-plate rim 220, which is disposed along the perimeter of sensor-holding plate 218 and is configured to fit into a groove 230 disposed along the inside perimeter of noise filter plate 226. In some applications, a width of groove 230, measured in a direction from an outer perimeter of the groove toward an inner perimeter of the groove, is greater than 0.05 and/or less than 2 mm greater than thickness t_2 of rim 220.

[0137] Reference is now made to FIGS. 10A-D, which are schematic illustrations of sensor-holding plate 218, in accordance with some applications of the present invention. FIG. 10A shows sensor-holding plate 218 with a continuous rim 220 which appears generally as shown in FIG. 9B. The inventors hypothesize that for some applications, continuous rim 220 facilitates generally isotropic focusing of motion sensor 30, in that continuous rim 220 is generally equally effective at blocking motion from all lateral directions.

[0138] FIG. 10B shows sensor-holding plate 218 with a discontinuous rim 225, shaped to define a plurality of slots (i.e., openings, or gaps) 223 therein, disposed around rim 225. Slots 223 create a “defocusing” effect, i.e., they facilitate the sensing of motion from areas which are not directly above sensor-holding plate 218. By varying the location, number, and size of slots 223, sensor-holding plate 218 can be configured for different beds sizes.

[0139] FIG. 10C shows sensor-holding plate 218 with a discontinuous rim 211, shaped to define one or more anisotropically-arranged slots 219 therein. Proper orientation of slots 219 may facilitate the sensing of motion originating from one or more particular areas not directly above sensor-holding plate 218. For example, the sensor-holding plate of FIG. 10C may be placed at the head of the bed, oriented such that slot 219 is directed toward the legs of the subject. In this manner, rim 211 will generally prevent the partner’s motion from being sensed, while generally allowing the subject’s motion to be sensed.

[0140] Although FIGS. 10B-C show the sensor-holding-plate rim shaped to define slots therein, the scope of the present invention includes rims which comprise thinned portions which function in a manner generally similar to slots 223 and 219.

[0141] In some applications, as shown in FIG. 10D, the rim 229 of sensor-holding plate 218 may comprise one or more detachable parts 209. The detachment of parts 209 results in the opening of slots such as slots 223 and slots 219. Detachable parts 209 allow for reducing the manufacturing cost of sensor-holding plate 218, since the desired slots can generally be opened post-manufacture. For example, if the subject is sleeping alone and the bed is relatively large, the subject may decide to detach a plurality of small detachable parts 209 to create slots 223, as shown in FIG. 10B, such that motion of the subject is detected even when the subject is not directly over sensor-holding plate 218. In some applications, parts 209 which have been detached may subsequently be re-attached.

[0142] When anisotropically-arranged slots, e.g., slots 219, are used, sensor-holding plate 218 may need to be fixed in place, such that its orientation remains generally constant. For example, in the case in which sensor-holding plate FIG. 10C is to be placed under the head of the bed with a slot 219 directed towards the subject’s legs, sensor-holding plate 218 may be fixed in place within the subject’s pillow, which in general tends to be perpendicular to the subject’s longitudinal axis.

[0143] In general, the various applications shown in FIGS. 10A-D may be practiced in combination with the applications shown in FIGS. 9A-B. For example, the various rims that are shown in FIGS. 10A-D may be more rigid than central portion 221, as described hereinabove.

[0144] In some applications, as shown in FIGS. 9A-B, sensor-holding plate 218 is circular; a sensor-holding plate shaped in this manner has been found by the inventors to be generally effective in transmitting mechanical forces to the sensor coupled to the center thereof. In some applications, the sensor element coupled to sensor-holding plate 218, e.g., via sensor receptacle 222, is also circular. It has been found by the inventors that the ratio of sensor element diameter (which is generally similar to diameter D_0 of sensor receptacle 222 shown in FIG. 9B) to sensor-holding plate diameter D_1 is a relevant factor for effective transmission of mechanical forces to the sensor. In some applications of the

present invention, the ratio of sensor element diameter to sensor-holding plate diameter $D1$ is greater than 0.1 and/or less than 0.6. In other applications, sensor-holding plate **218** is not circular, e.g., it may be square or another shape. In these applications, noise filter plate **226** is shaped accordingly, such that the noise filter is configured to be reversibly coupleable to the sensor-holding plate as generally described with respect to FIGS. **9A-B**, *mutatis mutandis*.

[0145] In some applications, sensor plate **238** is used in combination with subject identification module **102**, described hereinabove with respect to FIG. **4**. Although sensor plate **238** reduces the degree to which motion sensor **30** detects motion of the second person, it is possible that the sensor will nonetheless detect some of this motion. Subject identification module **102** therefore identifies components of the motion signal from sensor **30** that were generated by the subject, by distinguishing between components of the motion signal that were generated respectively by the subject and by the second person, e.g., as described hereinabove. In other applications, subject identification module **102** is used without sensor plate **238**.

[0146] Reference is now made to FIG. **31**, which is a schematic illustration of various apparatus **500a-e** for use with a subject **12** who shares a bed with a second person **502**, in accordance with some applications of the present invention. In all of apparatus **500a-e**, motion sensor **30** detects motion of subject **12** and motion of second person **502**, and generates a motion signal **504** in response thereto. (Motion sensor **30** is typically a single motion sensor that does not contact or view the subject, clothes the subject is wearing, the second person, or clothes the second person is wearing.) Furthermore, another common element in apparatus **500a-e** is that control unit **14** (e.g., via subject identification module **102** (FIG. **4**)) distinguishes between motion of the subject and motion of the second person, i.e., it may identify a particular portion of motion signal **504** as coming from the subject or from the second person. On the other hand, apparatus **500a-e** differ from each other in the technique(s) used to perform the distinguishing/subject-identification, in the analysis that is performed pursuant to the distinguishing/subject-identification, and/or in the output that is generated.

[0147] In apparatus **500a**, control unit **14** is configured to identify that a portion of the motion signal was generated in response to motion of the second person, and not in response to motion of the subject, by identifying that the portion exhibits ringing. Reference is made to FIG. **32**, which is a plot of motion signal **504** that includes a portion **506** thereof that exhibits ringing, as analyzed in accordance with some applications of the present invention. Motion signal **504** includes portions **501a** and **501b** that, respectively, precede and follow portion **506**. Portions **501a** and **501b** exhibit a generally regular, cyclical pattern that is typically indicative of the cardiac and respiratory motion of the subject. Portion **506**, on the other hand, has more of a step-response profile, which is typically indicative of large body-movement. The ringing in portion **506** indicates that the source of the large body-movement is the second person, who is not directly above the sensor.

[0148] To identify the ringing, control unit **14** ascertains that portion **506** includes a set of at least three consecutive extrema **508** (i.e., three consecutive maxima, or three consecutive minima), each of which (following the first extremum of the set) is separated from the preceding extremum of the set by a time $T0$ that falls within a given time range

(e.g., 0.15-0.45 seconds). (In FIG. **32**, two such sets of consecutive extrema are shown.) Typically, to identify the ringing, control unit **14** further ascertains that respective differences between (i) magnitudes of consecutive extrema **508**, and (ii) a magnitude of an extremum **510** that precedes the set of consecutive extrema (typically an initial “spike” that precedes the set), fall within a given amplitude range. For example, the control unit may identify that the respective differences are between 10%-150% of the magnitude of extremum **510**. Typically, the control unit further ascertains that a difference between (i) a smallest magnitude **512** of the consecutive extrema, and (ii) a largest magnitude **514** of the consecutive extrema, is less than a threshold (e.g., 30% of smallest magnitude **512**).

[0149] Although FIG. **32** shows the ringing phenomenon only for large body-movement, ringing may also be exhibited in portions of signal **504** that reflect other types of motion, such as respiratory motion or cardiac motion. Apparatus **500a** is configured to identify the second person as the source of these other types of motion, by performing the ringing-identification techniques described hereinabove.

[0150] Apparatus **500b** uses a different technique to identify that a given portion of the motion signal was generated in response to large body-movement of the second person, and not in response to motion of the subject. In apparatus **500b**, control unit **14** is configured to “learn” an amplitude threshold Th by analyzing a portion of the motion signal (e.g., portion **501a**) that was generated in response to motion (e.g., cardiac and/or respiratory motion) of the subject, and calculating threshold Th based on the analysis. (For example, Th may be a multiple of amplitude $A4$ of portion **501a**.) If the amplitude of a given portion of the motion signal is less than the amplitude threshold, the control unit identifies that the given portion of the motion signal was generated in response to large body-movement of the second person, and not in response to motion of the subject. For example, in FIG. **32**, extremum **510** is less than Th , such that portion **506** is determined to have been generated by large body-movement of the second person.

[0151] Apparatus **500c** uses yet another technique for distinguishing between motion of the subject and motion of the second person. In apparatus **500c**, control unit **14** identifies a subject-motion component of the motion signal that was generated in response to motion of the subject, e.g., portions **501a** and **501b** of FIG. **32**. To identify whether a given portion, e.g., portion **506**, of the motion signal was generated in response to large body-movement of the subject, and not in response to motion of the second person, control unit **14** compares the amplitude $A3$ of the subject-motion component following the given portion, relative to the amplitude $A4$ before the given portion. If the amplitude has changed by a threshold amount, it is likely the subject moved relative to the sensor, and thus, the large body-movement is likely that of the subject. (FIG. **32** shows $A4$ being different from $A3$, but not by more than the threshold amount, such that portion **506** is determined to have been generated by motion of the second person.)

[0152] In general, the distinguishing/subject-identification techniques of apparatus **500a-c** are typically combined, i.e., the control unit is typically configured to use any of the techniques described hereinabove, separately or in combination.

[0153] Apparatus **500d** also comprises motion sensor **30** and control unit **14**, and also distinguishes between motion

of the subject and motion of the second person, e.g., using some or all of the techniques of apparatus 500a-c. In apparatus 500d, control unit 14 is configured to, by analyzing the signal from motion sensor 30 in an analysis step 518, identify an effect of large body-movement of the second person on sleep of the subject, and in response thereto, generate a sleep-disturbance output 516. Output 516 may include a report (e.g., a digital, and/or printed, and/or audio report), which may include alphanumeric and/or graphical content. Alternatively or additionally, as further described hereinbelow, output 516 may include a recommendation to change a parameter, and/or instructions to a device to change a parameter. In general, output 516 facilitates the reduction of the extent to which movement by second person 502 disturbs the sleep of subject 12.

[0154] In some applications, output 516 includes an assessment of an effectiveness of a parameter at reducing the effect of the large body-movement of the second person on the sleep of the subject. For example, the control unit may assess one or more parameters 520 such as:

[0155] (a) a parameter (e.g., a firmness, or a width) of a mattress 522 on which the subject is sleeping,

[0156] (b) a parameter (e.g., a tilt angle) of bed 37,

[0157] (c) a sleeping arrangement of (e.g., a distance between) the subject and the second person, and/or

[0158] (d) a room-environment parameter (e.g., a level of light or sound, or a temperature, in the room).

[0159] Some of parameter types (a)-(d) (e.g., a level of light in the room) may be detected by control unit 14, while other parameter types (e.g., a firmness of mattress 522) are typically received as manual inputs to the control unit.

[0160] Typically, in analysis step 518, the control unit analyzes motion signal 504 in light of the parameter(s), and generates the assessment in response to the analysis. For example, the control unit may compare data from several nights of sleep, and/or compare the data from the given pair of sleepers with data from other pairs of sleepers, to ascertain how the parameter(s) affect the level of sleep disturbance. Output 516 may include, for example, an assessment message such as “A temperature between 23-25 C in the room is more effective at reducing sleep disturbance, relative to other temperatures.” Alternatively or additionally, output 516 may include a recommendation to reduce the effect of the large body-movement of the second person on the sleep of the subject, by adjusting an adjustable parameter such as any of parameters (a)-(d) listed above. For example, output 516 may include a recommendation message such as “To reduce sleep disturbance, you may wish to reduce the tilt angle of your bed.”

[0161] In some applications, apparatus 500d is used (e.g., by a mattress provider or consumer) to compare between different types of mattresses. For example, output 516 may include a comparison between (a) the effectiveness of a parameter of one given type of mattress, and (b) the effectiveness of the parameter of a different type of mattress. For example, output 516 may show a consumer that a firmer mattress is more effective than a less-firm mattress at reducing sleep disturbance, and based on this comparison, the consumer may decide to purchase the firmer mattress.

[0162] In some applications, output 516 includes instructions to a device 524 to adjust an adjustable parameter, e.g., any of (a)-(d) listed above. For example, FIG. 31 shows output 516 including instructions to a controller 526 to adjust a tilt angle of bed 37.

[0163] Apparatus 500e also comprises motion sensor 30 and control unit 14, and also distinguishes between motion of the subject and motion of the second person, e.g., using some or all of the techniques of apparatus 500a-c. In apparatus 500e, motion sensor 30 comprises a mechanical-filtering element, such as noise filter rim 228 (described hereinabove with reference to FIGS. 9A-B), which is configured to reduce a response of the motion sensor to motion of the second person, relative to motion of the subject. Control unit 14 analyzes motion signal 504, assesses an effectiveness of the mechanical-filtering element at reducing the response of the motion sensor to motion of the second person, and generates an output in response thereto. For example, if control unit 14 identifies a relatively large number of portions of the signal coming from motion of the second person, control unit 14 may make an assessment that the mechanical-filtering element is relatively ineffective. In such a case, output 516 may include, for example, a recommendation to replace the current noise filter rim with a thicker noise filter rim.

[0164] It is noted that there is a “philosophical” difference between apparatus 500d and apparatus 500e, in that a typical objective in using apparatus 500e is to improve the filtering out of motion from the second person (perhaps to the point of near-complete filtering), whereas apparatus 500d requires that sensor 30 detect at least some of the motion from the second person. Nevertheless, apparatus 500d and 500e may be combined, such that a single control unit 14 is configured to perform both the functions of apparatus 500d and the functions of apparatus 500e.

[0165] Reference is now made to FIG. 15, which is a schematic illustration of a sensor 30 configured to be placed within a pillow 301, in accordance with some applications of the present invention. In some applications, motion sensor 30 is configured to be placed within pillow 301 of subject 12.

[0166] Reference is now made to FIG. 11, which is a schematic illustration of apparatus comprising a motion sensor 30, control unit 14, and speaker 232, in accordance with some applications of the present invention. In some applications of the present invention, motion sensor 30 and a speaker 232 are configured to be placed under the head of a subject who shares a bed with another person. (Thus, FIG. 11 depicts resting surface 37 as a double bed.) For example, sensor 30 may be placed within the pillow of the subject. Speaker 232 is configured to play music responsively to output from control unit 14, for example, in order to help the subject fall asleep or use biofeedback techniques to relax. In some applications, sensor plate 238, described hereinabove with respect to FIGS. 9A-B, is used. The use of sensor plate 238, which, as explained above, comprises a more rigid edge region 227 (FIG. 9B), provides that speaker 232 responds largely to the sleep stage and physiological condition of the subject, rather than also to motion from the other person. In some applications, control unit 14 may eliminate artifacts generated by speaker 232 by subtracting the signal generated by the speaker from the motion signal. The signal generated by speaker 232 may be received, for example, from the speaker controlling circuit or from another sensor on the speaker.

[0167] Reference is now made to FIG. 14, which is a schematic illustration of apparatus for controlling a thermo-regulation device 240, in accordance with some applications of the present invention. Studies show that dynamically regulating the temperature of a subject's sleep environment

may improve the subject's sleep quality. For example, maintaining a steady temperature may increase the deep sleep (SWS) ratio, and cooling the bed during REM may increase the REM sleep share rate. In some applications, control unit **14** is connected to a thermoregulation device **240** located, for example, in the subject's bed or elsewhere in the subject's bedroom. Control unit **14** monitors the subject's sleep stages and controls thermoregulation device **240** accordingly. Examples of thermoregulation devices which may be configured to be controlled by control unit **14** include air-conditioning units, electric heaters, radiators, bed coolers, and electric blankets.

[0168] Reference is now made to FIG. 12, which is a schematic illustration of apparatus comprising a motion sensor **30**, control unit **14**, and alarm clock **212**, in accordance with some applications of the present invention. For some applications, an alarm clock **212** is configured to receive an output from control unit **14**. The output is generated in response to a signal from motion sensor **30**, and indicates whether a resting surface **37**, e.g., a bed, is occupied by a subject. In response to the output indicating that resting surface **37** is unoccupied, alarm clock **212** inhibits itself from sounding. This reduces the likelihood of an alarm waking other members of the household, in cases where the subject arose from resting surface **37** without taking measures to ensure that the alarm would not subsequently begin or continue to sound. In some applications, as shown in FIG. 12, alarm clock **212** and control unit **14** are integrated into a common unit **213**. In other applications, alarm clock **212** is separate from control unit **14**, and communicates therewith by wired or wireless communication means.

[0169] In some cases, the individual might arise from bed at the sounding of an alarm, but return to bed thereafter. Alternatively, the individual might not arise from bed, even though the alarm has sounded. In some applications, alarm clock **212** is configured to sound after a delay, in response to the output from control unit **14** indicating that the bed is occupied following a previous sounding of the alarm clock.

[0170] Reference is now made to FIG. 13, which is a schematic illustration of a motion sensor **30** powered by an external power supply **216** (i.e., a power supply that is external to the motion sensor), and a rechargeable battery **214**, in accordance with some applications of the present invention. In some applications, motion sensor **30** may be powered by an external power supply **216**, which draws current via a power cord **217** connected to a wall outlet. Since some subjects are uncomfortable with power being drawn from the wall and conveyed to a device which is underneath them, motion sensor **30** is configured to not draw power from power supply **216**, in response to output from control unit **14** indicating that resting surface **37** is occupied by the subject. In some applications, sensor **30** is configured to draw power from a rechargeable battery **214**, in response to the output indicating that resting surface **37** is occupied. Rechargeable battery **214** is configured to draw power from a power supply, e.g., power supply **216**, in response to the output from the control unit indicating that the resting surface is unoccupied, and to not draw power from the power supply, in response to the output indicating that the resting surface is occupied.

[0171] In some applications, system **10** is configured to analyze sleep patterns of a subject and, in response thereto, produce a sleep report which can be used, for example, for clinical sleep-study purposes.

[0172] In some applications, system **10** is configured to monitor subjects who are generally healthy, in order to help the subjects maintain or improve their state of well-being. For example, system **10** may be configured to help a healthy subject avoid unhealthful conditions or improve sleep quality.

[0173] In some applications, system **10** is configured to be used in combination with home-based appliances. For example, system **10** may be configured to transmit a signal to a coffee-maker, the signal indicating that the subject has woken up and/or has left the bed and might soon wish to drink a cup of coffee.

[0174] In some applications, a resting surface, e.g., a mattress, is configured to be used with motion sensor **30**, such that motion sensor **30** may be disposed within the mattress. For example, the mattress may have an opening at its side configured to receive motion sensor **30**, as well as a receptacle contained within the mattress configured to hold the sensor. Configuring a mattress in this manner allows for the sensor to be disposed closer to the subject, relative to applications in which the sensor is disposed underneath the mattress.

[0175] In some applications, control unit **14** is configured to receive mattress-related parameters such as thickness and resilience, and to analyze the signal from motion sensor **30** in light of the parameters. The mattress-related parameters may facilitate the quantification of signal amplitude on more of an absolute scale, thus facilitating a more effective response to the signal. For example, if the signal from sensor **30** indicates a weak heartbeat, but the mattress is relatively thick and resilient, control unit **14** may withhold the output unit from generating an alert.

[0176] Reference is made to FIGS. 1, 2, 4, and 16. In some applications, control unit **14** (e.g., via heartbeat pattern analysis module **23**) is further configured to calculate an indication of a left-ventricle-ejection-time (LVET) of subject **12**. LVET is the time from the opening of the aortic valve during a heartbeat to the closing of the aortic valve during the heartbeat. A decrease in LVET may be indicative of a clinical condition, such as hypovolemia and/or hemorrhaging, that requires immediate medical attention. Reference is made to FIG. 16, which is a schematic illustration of ballistocardiographic (BCG) signals **300**, **302**, and **304** (in arbitrary units) used for calculating the indication of the LVET, in accordance with some applications of the present invention. Signal **300** is a heartbeat-related signal that is extracted by heartbeat pattern analysis module **23** from the raw motion signal generated by sensor **30**. Signal **300** is typically extracted by means of spectral filtering in the range of about 0.8 to about 5.0 Hz, as described hereinabove. (A matched filter may be used to extract signal **302**.) Signal **300** is typically smoothed by a low-pass filter to yield signal **302**. (In FIG. 16, signal **300** is generally smooth, such that signal **302** appears substantially identical to signal **300**.) The derivative of signal **302** is calculated by module **23**, after which the derivative is typically smoothed with a low-pass filter, yielding signal **304**. Each of signals **300**, **302**, and **304** is marked in FIG. 16 to show an indication of aortic valve openings (AO) and closings (AC). As described above, the time between these events is the LVET of the subject.

[0177] Heartbeat pattern analysis module **23** is configured to calculate an indication of the LVET by analyzing signal **304**. (In some applications, the unsmoothed derivative of signal **302**, instead of signal **304**, is analyzed.) For example,

heartbeat pattern analysis module **23** may be configured to identify the most prominent positive peaks **308** in signal **304**. Following the identification of peaks **308**, module **23** identifies the positive peaks **306** that immediately precede peaks **308**, which correspond to AO, and the negative peaks **310** that immediately follow peaks **308**, which correspond to AC. As appropriate, techniques described in Alametsa et al, "Ballistocardiographic studies with acceleration and electro-mechanical film sensors", Medical Engineering & Physics, 2009, which is incorporated herein by reference, may be applied to calculating the LVET. The time between peaks **306** and **310**, and/or another indication of the LVET, is then calculated by module **23**, and control unit **14** drives an output device, e.g., user interface (U/I) **24**, to generate an output, such as an audio and/or visual output, in response to the calculated indication. Typically, calculating the indication involves averaging one or more parameters, such as the time between peaks **306** and **310**, over several heartbeats.

[0178] In some applications, control unit **14** (e.g., via module **23**) is further configured to identify a risk of hypovolemia of the subject, in response to the calculated indication of the LVET. For example, module **23** may determine that the LVET has decreased, relative to previously-calculated LVETs and/or to a subject-baseline LVET or a population-baseline LVET, such that the subject is at risk of hypovolemia. For example, the subject may be experiencing hypovolemia and/or hemorrhaging. Control unit **14** drives U/I **24** to generate the output in response to the identified risk of hypovolemia. Typically, the generated output includes an alert to a physician or other caregiver.

[0179] In some applications, control unit **14** (e.g., via module **23**) is further configured to identify a change in stroke volume of subject **12**. Typically, this is done by using the amplitude **312** of heartbeat signal **302** as an indication of the subject's stroke volume, as amplitude **312** is typically positively correlated to stroke volume. Typically, while amplitude **312** is being monitored by module **23**, raw signal **300** is also being processed by system **10** to identify any posture changes of the subject. For example, the system may identify a posture change using techniques as described in US 2011/0112442 to Meger, which is incorporated herein by reference. If no posture change has been identified, a change in amplitude **312** is likely indicative of a change in stroke volume, since the change in amplitude cannot be attributed to a posture change of the subject. Control unit **14** drives the output device (e.g., U/I **24**) to generate an output, in response to the identified change in stroke volume.

[0180] In some applications, the control unit is further configured to identify a risk of hypovolemia of the subject, in response to the identified change in stroke volume. For example, the control unit may identify a risk of hypovolemia (e.g., of hemorrhaging), in response to the stroke volume dropping below a specified absolute or percentage threshold. Control unit **14** drives U/I **24** to generate the output in response to the identified risk of hypovolemia. Typically, the generated output will include an alert to a physician or other caregiver. In some applications, the risk of hypovolemia is identified in response to both the change in stroke volume and a change in LVET. For example, a slight decrease in stroke volume may be cause for alarm only if it is accompanied by a decrease in LVET.

[0181] Reference is now made to FIG. 17, which is a schematic illustration of apparatus for use with a plurality of sleeping subjects **314**, in accordance with some applications

of the present invention. The apparatus comprises at least one sensor **316** (e.g., at least two sensors **316**, e.g., exactly two sensors **316**) configured to monitor each of subjects **314** while the subjects sleep. For example, as shown in FIG. 17, sensors **316** may comprise non-contact motion sensors **30**, configured to sense motion of the subjects while the subjects sleep. (Typically, to help reduce contamination of the motion signal by motion of the other subject, each sensor **30** is placed underneath the outer shoulder of the subject being sensed.) Alternatively or additionally, sensors **316** may comprise at least one sensor of another type, such as an electromyographic sensor and/or an imaging sensor. In response to the monitoring, sensors **316** generate a respective signal for each of the subjects. Control unit **14** is configured to analyze the signals, and, based on the analyzing, identify at least one sleep-related parameter for each of the subjects. For example, for each of the subjects, the control unit may be configured to identify one or more of the following parameters:

[0182] (i) A length of time for which the subject has been sleeping, e.g., a length of time for which the subject has been in a deep sleep;

[0183] (ii) A number of prior awakenings of the subject, e.g., a number of prior awakenings during the present sleeping period and/or during a previous sleeping period;

[0184] (iii) A stage of a sleep cycle of the subject.

[0185] In identifying the sleep-related parameter(s), as well as generally, in identifying that a person is sleeping and/or in identifying a sleep stage of the person (e.g., as described below with reference to numerous figures), the control unit may use one or more of the techniques described in (a) US 2007/0118054 to Pinhas (now abandoned), (b) Shinar et al., Computers in Cardiology 2001; Vol. 28: 593-596, and (c) Shinar Z et al., "Identification of arousals using heart rate beat-to-beat variability," Sleep 21(3 Suppl): 294 (1998), each of which is incorporated herein by reference.

[0186] At least in response to the identified sleep-related parameters, and typically further in response to receiving an input from a second sensor **318**, control unit **14** identifies at least one of the subjects for waking, and at least one of the subjects not for waking. Typically, the apparatus further comprises a waking device **324**, and the control unit is configured to drive waking device **324** to wake the subject(s) identified for waking.

[0187] A typical situation in which the described apparatus may be used is shown in FIG. 17. Two parents **314** of a baby **320** are sleeping on a bed **37**, while baby **320** sleeps in a different room. Second sensor **318** comprises, for example, an audio sensor **322**, configured to communicate (e.g., wirelessly) a signal to control unit **14** in response to sounds made by baby **320**. (In other applications, sensor **318** may comprise a different type of sensor, such as non-contact motion sensor **30** and/or an image sensor.) In response to receiving the input from sensor **318**, the control unit identifies that baby **320** is crying, such that one of parents **314** should be wakened. Based on the sleep-related parameters, the control unit identifies the parent to be wakened. For example, if one parent is in a deep sleep while the other is not, the latter may be identified for waking. Similarly, if one parent awoke in response to the previous crying episode, the other parent may be wakened in response to the current episode. In some applications, as shown in FIG. 17, waking device **324** comprises a separate unit (e.g., a separate

alarm-generating mechanism) for each of the sleeping subjects, such that one subject can be woken with minimal disturbance to the other. In other applications, wakening device 324 comprises a single unit. For example, in some applications, wakening device 324 may be integrated with U/I 24 (FIG. 2).

[0188] Although FIG. 17 shows two sensors 316, it is noted that the scope of the present invention includes the use of exactly one sensor 316 (e.g., exactly one motion sensor 30) to monitor both subjects 314. It is further noted that the apparatus described with reference to FIG. 17 may be used in combination with subject identification module 102 (FIG. 4), which helps differentiate between the motion of the first subject and the motion of the second subject, and/or in combination with one or more of the mechanical filtering applications described hereinabove. For example, sensor plate 140 with hardened edges 142 (FIG. 5), sensor plate 238 with rigid edge region 227 (FIG. 9A), etc. may be used in order to reduce contamination of one subject's motion signal by the other subject. Similarly, other "two-person" applications described hereinbelow with reference to FIGS. 18, 20, 21, and 22 may be practiced in combination with subject identification module 102 and/or one or more of the mechanical filtering applications described herein.

[0189] Other situations in which the described apparatus may be used include a situation in which a plurality (e.g., three or more) doctors or other caregivers are sleeping in a room, e.g., a resting room in a hospital. Sensor 318 senses a physiological parameter of a patient, and communicates the parameter to the control unit. In this situation, sensor 318 typically comprises a "dedicated" physiological sensor, such as an electrocardiograph, blood pressure monitor, etc., although sensor 318 may also comprise a sensor of the type described above, e.g., non-contact motion sensor 30. In response to the input from the sensor, the control unit determines that at least one, but not all, of the doctors should be woken, in order to tend to the patient. Based on the sleep-related parameters, as described above with respect to the parents of baby 320, the control unit identifies at least one of the doctors for wakening, and at least one of the doctors not for wakening. (In this situation, subjects 314 will typically be sleeping on multiple respective beds, and the apparatus may comprise more than one control unit, e.g., one control unit per bed, in communication with each other.)

[0190] In some applications, the control unit is further configured to generate a report that shows a history of the at least one sleep-related parameter for each of the subjects. The report may be generated at regular intervals, such as after every night. The generation of such a report may be helpful in avoiding conflicts. For example, in the parenting situation described above, the parent who was woken may feel less resentful if the report shows that despite being woken to tend to the crying baby, he/she slept better and/or longer overall, relative to the other parent.

[0191] Reference is now made to FIG. 18, which is a schematic illustration of apparatus for activating a medical device 326 (e.g., a continuous positive airway pressure (CPAP) device) for a subject 12 who is sleeping in proximity to at least one other person 328, in accordance with some applications of the present invention. The apparatus comprises at least one sensor 316 (e.g., at least two sensors 316, e.g., exactly two sensors 316) configured to monitor subject 12 and person 328. For example, as shown in FIG. 18, sensors 316 may comprise non-contact motion sensors 30,

configured to sense motion of subject 12 and person 328 while they sleep. Alternatively or additionally, sensors 316 may comprise at least one sensor of another type, such as an electromyographic sensor and/or an imaging sensor. In response to the monitoring, sensors 316 generate a respective signal for each of subject 12 and person 328. Control unit 14 analyzes the signal for the subject, and, based on the analyzing, identifies at least one physiological parameter of the subject that relates to whether or not the device should be activated. For example, the control unit may identify a respiration-related parameter of subject 12 that is indicative of an occurring or expected episode of apnea, e.g., as described in US 2013/0281866 to Shinar, which is incorporated herein by reference. Alternatively or additionally, the control unit may identify a sleep-related parameter of subject 12 (e.g., how deeply the subject is sleeping) that relates to whether or not the device should be activated.

[0192] If subject 12 were sleeping alone, the identification of the physiological parameter might be sufficient cause to activate medical device 326. For example, if subject 12 were sleeping alone, the respiration-related parameter predictive of an apnea episode might be sufficient cause for the control unit to activate the CPAP device. However, given that subject 12 is not sleeping alone, the control unit also analyzes the signal for the other person, identifies at least one sleep-related parameter of the other person based on the analyzing, and activates the medical device further in response to the sleep-related parameter. For example, the sleep-related parameter may include a stage of sleep of the other person. If the other person is in a deep sleep, for example, the medical device may be activated, since the activation of the device is unlikely to disturb the other person. Conversely, if the other person is awake, the medical device may not be activated, since activation of the device may prevent the person from falling asleep. (If the other person is in a light sleep, the medical device may or may not be activated, depending on the application and possibly also on other factors, as further described immediately hereinbelow.) In some applications, the sleep-related parameter includes an indication of whether the other person is trying to fall asleep, and the control unit is configured to activate (or not activate) the medical device based on the indication. For example, if the parameter indicates that the other person is awake but is not trying to fall asleep (e.g. the other person is sitting in bed, and/or reading while lying in bed), the device may be activated. Conversely, if the parameter indicates that the other person is trying to fall asleep (e.g., the person is lying in a sleeping position) the device may not be activated. In some applications, an override feature is provided, whereby the medical device may be activated regardless of the sleep-related parameter of the other person.

[0193] In some applications, the control unit identifies one or more other factors, and in response to those factors, activates (or does not activate) the medical device. For example, in some applications, the control unit is further configured, based on the analyzing of the subject's signal, to identify a likelihood of an upcoming occurrence of a clinical episode of the subject. For example, the control unit may identify that there is high chance that the subject will soon experience an episode of apnea. In response to this likelihood, the control unit may activate the CPAP device, even if the other person is likely to be disturbed. In some applications, the control unit is further configured to, based on the analyzing of the subject's signal, identify an expected

severity of the upcoming occurrence, and to activate (or not activate) the medical device in response to the expected severity. For example, if the predicted apnea episode is expected to be severe, the control unit may be configured to activate the medical device, even if the other person is likely to be disturbed.

[0194] In some applications, the control unit is configured to activate the medical device, further in response to an input that includes a history of awakenings of the subject and/or of the other person in response to previous activations of the medical device. For example, if the history shows that the other person is typically woken when the device is activated, the control unit may activate the device less readily, e.g., only if the other person is in a deep sleep. In some applications, the control unit is configured to track the history of awakenings of the subject and/or of the other person, thus allowing the control unit to learn the proper threshold to use when determining whether or not to activate the device. In some applications, the control unit is configured to activate the medical device, further in response to an input indicative of a sleep-disturbance tolerance of the subject, and/or an input indicative of a sleep-disturbance tolerance of the at least one other person. This input may be received, for example, via U/I **24** (FIG. 2). If the tolerance is low (i.e., if the input indicates that the subject and/or the other person is a light sleeper), the control unit will activate the device less readily.

[0195] In some applications, as shown in FIG. 18, the control unit is further configured to activate a noise-cancellation device **330** (e.g., noise-canceling headphones) for the at least one other person, upon activating the medical device. For example, if the control unit has determined that the medical device should be activated, but the other person is likely to be disturbed by the activation of the device, the control unit may activate the medical device while also activating noise-cancellation device **330**.

[0196] Although FIG. 18 shows two sensors **316**, it is noted that the scope of the present invention includes the use of exactly one sensor **316** (e.g., exactly one motion sensor **30**) to monitor both subject **12** and other person **328**. In such applications, subject identification module **102** (FIG. 4) may be used to differentiate between the motion of the subject and the motion of the other person.

[0197] Reference is now made to FIG. 19, which is a schematic illustration of apparatus **334** for use with a person **338** who is on a resting surface **37** (e.g., a bed) and for use with an illuminator **332**, in accordance with some applications of the present invention. (Illuminator **332** may be integrated with resting surface **37**, as shown in FIG. 19, or disposed at the side of the resting surface, e.g., on a night table.) Apparatus **334** comprises a sensor **316** configured to monitor person **338** and generate a signal in response thereto. Sensor **316** may comprise, for example, non-contact motion sensor **30**, configured to sense motion on resting surface **37** and generate a motion signal in response thereto. Alternatively or additionally, sensor **316** may comprise at least one sensor of another type, such as an electromyographic sensor and/or an imaging sensor.

[0198] Control unit **14** is configured to analyze the signal from the sensor, and, in response thereto, calculate a bed-exit likelihood, which is a likelihood that the person has left the resting surface and/or a likelihood that the person is preparing to leave the resting surface. ("Preparing to leave the resting surface" may be defined, for example, as "intending

to leave the resting surface within a given period of time, e.g., 2 minutes".) In response to the bed-exit likelihood, control unit **14** selects an illumination intensity value from a set of at least three values, and sets an illumination intensity of illuminator **332** to the selected illumination intensity value. For example, from a set of "high", "low", and "off", control unit may select "high" in response to a relatively high likelihood, "low" in response to a lower likelihood, and "off" in response to a relatively low likelihood. (The set of "high", "low", and "off" is being used here as an example only. In practice, the set of values may contain any number of values that is at least three.) The control unit sets the illumination intensity by sending a wired or wireless signal to the illuminator. (Similarly, with respect to all descriptions herein of the control unit controlling a device, e.g., the communication device, waking mechanism, etc. shown in any of FIGS. 20-23, it is noted that the control unit controls the device by sending a wired or wireless signal to the device.) In calculating the likelihood that the person has left the resting surface, the control unit may, for example, use one or more of the bed-exit-detection techniques described in US 2013/0267791 to Halperin, which is incorporated herein by reference.

[0199] Typically, in response to analyzing the signal, control unit **14** calculates a likelihood that the person is awake (e.g., using one or more of the awakening-detection techniques described in US 2013/0267791 to Halperin, which is incorporated herein by reference), and calculates the bed-exit likelihood in response thereto. For example, if the motion signal from motion sensor **30** is indicative of the person being awake, the control unit may calculate a relatively high likelihood that the person is awake, and, in response thereto, a relatively high likelihood that the person is preparing to leave the resting surface. Alternatively or additionally, the control unit calculates a likelihood that the person is sitting (e.g., using one or more of the techniques described in US 2013/0267791 to Halperin, which is incorporated herein by reference), and calculates the bed-exit likelihood in response thereto. For example, the control unit may calculate a relatively high likelihood that the person is sitting, and, in response thereto, a relatively high likelihood that the person is preparing to leave the resting surface. Alternatively or additionally, the control unit calculates a signal-to-noise ratio (SNR) of the signal (e.g., by using a real-time noise estimator, and/or as described in US 2013/0267791 to Halperin, which is incorporated herein by reference), and calculates the bed-exit likelihood in response thereto. Typically, a relatively high signal-to-noise ratio is indicative that the person is in bed, whereas a relatively low signal-to-noise ratio is indicative that the person has left the bed. Therefore, the control unit typically calculates a higher bed-exit likelihood in response to calculating a first signal-to-noise ratio, relative to calculating a second signal-to-noise ratio that is higher than the first signal-to-noise ratio.

[0200] In some applications, the control unit calculates both types of bed-exit likelihood, i.e., both the likelihood that the person has left the resting surface, and the likelihood that the person is preparing to leave the resting surface. In response to the likelihood that the person has left the resting surface, the control unit identifies a first illumination intensity value from the set of values, and in response to the likelihood that the person is preparing to leave the resting surface, the control unit identifies a second illumination intensity value from the set of values. The control unit then

selects a maximum value of the first illumination intensity value and the second illumination intensity value, and sets the illumination intensity of the illuminator to the maximum value. For example, referring again to the set of “high”, “low”, and “off”, if there is a relatively low likelihood that the person has left the bed, such that the first selected value is “off”, but there is a relatively high likelihood that the person is preparing to leave the bed, such that the second selected value is “high”, the control unit will set the illuminator to “high”. Alternatively, for example, if there is a relatively high likelihood that the person has left the bed, such that the first selected value is “high”, the control unit will set the illuminator to “high”, regardless of the likelihood that the person is preparing to leave the bed.

[0201] Typically, control unit 14 selects the illumination intensity value by applying to the bed-exit likelihood a function that is generally monotonically increasing with respect to the bed-exit likelihood, and selecting the output of the function as the illumination intensity value. (In the context of the present application, a function that is generally monotonically increasing is a function for which at least 90% of the output values are not less than the preceding output value. The same definition applies to generally monotonically decreasing, *mutatis mutandis*.) Typically, the control unit selects a zero illumination intensity value (i.e., “off”), in response to the bed-exit likelihood being less than a threshold. For example, the control unit may select a “high” intensity in response to likelihoods above 90%, a “low” intensity in response to likelihoods between 30% and 90%, and “off” in response to likelihoods below 30%.

[0202] In some applications, the control unit selects the illumination intensity value further in response to a time of day, a date, a geographical location, a sunrise time, and/or a sunset time. For example, if the person usually sleeps between 11 pm and 6 am, the control unit may select a “high” intensity in response to a likelihood of 90% at 7 am, but a “low” intensity in response to a likelihood of 90% at 3 am. Alternatively or additionally, apparatus 334 further comprises an ambient light detector 336 configured to detect a level of ambient light, and the control unit selects the illumination intensity value further in response to the level of ambient light. For example, in response to a likelihood of 90%, the control unit may select a “high” intensity if there is a relatively low level of ambient light, but only a “low” intensity if there is a relatively high level of ambient light.

[0203] In some applications, the control unit is further configured to, in response to the bed-exit likelihood and/or a time of day, select an illumination color value from a set of at least two color values, and set an illumination color of the illuminator to the selected illumination color value. For example, the control unit may select a red color in response to a relatively low bed-exit likelihood, and a blue color in response to a relatively high bed-exit likelihood; alternatively or additionally, the control unit may select a red color during typical sleeping hours, and a blue color otherwise. For at least some people, red illumination is more conducive to sleep than is blue illumination. Thus, the selection of the red color during typical sleeping hours, rather than the blue color, helps the person fall asleep upon returning to bed. Furthermore, the selection of the red color in response to a relatively low bed-exit likelihood helps minimize the disturbance to the person in the event of a “false positive”, i.e., in the event that the person is not actually preparing to leave the bed.

[0204] In some applications, control unit 14 is configured to identify a sleep stage of person 338. In such applications, the control unit may ascertain, in response to analyzing the signal, that person 338 is in a light sleep stage on the resting surface, and in response thereto, drive illuminator 332 to wake the person by illuminating. Waking the person in this manner may be helpful, for example, if the person shares a bed and/or a room with a second person (as described hereinbelow with reference to FIG. 20), since an increase in illumination may be less disturbing to the second person than the sounding of an alarm. Since, however, the increase in illumination may be insufficient to wake person 338 if (s)he is in a relatively deep sleep, illumination is used to wake the person only if the person is in a light sleep stage.

[0205] Reference is now made to FIG. 20, which is a schematic illustration of apparatus 334, in accordance with some applications of the present invention. In some applications, first person 338 shares a sleeping area (e.g., a bed, and/or a room) with a second person 340. In such applications, the control unit identifies a second-person-sleeping likelihood, which is a likelihood that the second person is sleeping, and selects the illumination intensity value further in response to the second-person-sleeping likelihood. For example, in response to a bed-exit likelihood of 90%, the control unit may select a “high” intensity if the second-person-sleeping likelihood is relatively low, but only a “low” intensity if the second-person-sleeping likelihood is relatively high. Typically, the control unit applies to the second-person-sleeping likelihood a function that is generally monotonically decreasing with respect to the second-person-sleeping likelihood, and selects the output of the function as the illumination intensity value. The control unit may apply a two-variable function to (a) the bed-exit likelihood and (b) the second-person-sleeping likelihood, where the two-variable function is generally monotonically increasing with respect to the bed-exit likelihood, and generally monotonically decreasing with respect to the second-person-sleeping likelihood. An example of such a function, for each of the two types of bed-exit likelihood, is shown in the tables below. (For simplicity and ease of illustration, the second-person-sleeping likelihood is shown as having one of only two values: “low”, and “high”, even though, in practice, it can take on any number of values between 0 and 100%.)

TABLE 1

Likelihood that the first person has exited the bed	Lighting intensity	
	High second-person- sleeping likelihood	Low second-person- sleeping likelihood
0%	0%	0%
10%	0%	0%
20%	0%	10%
30%	10%	20%
40%	10%	30%
50%	20%	40%
60%	30%	40%
70%	50%	60%
80%	60%	80%
90%	80%	100%
99%	80%	100%

TABLE 2

Likelihood that the first person is preparing to exit the bed	Lighting intensity	
	High second-person-sleeping likelihood	Low second-person-sleeping likelihood
0%	0%	0%
10%	0%	0%
20%	0%	0%
30%	0%	0%
40%	10%	0%
50%	10%	10%
60%	20%	10%
70%	20%	10%
80%	20%	20%
90%	20%	20%
99%	30%	20%

[0206] As described hereinabove with reference to FIG. 19, the control unit may select two intensity values in response to, respectively, the two types of bed-exit likelihood, and select the maximum of the two values as the illuminator intensity. For example, if the likelihood that the first person has exited the bed is 30%, the likelihood that the first person is preparing to exit the bed is 60%, and the second-person-sleeping likelihood is “low”, the control unit may select (per Tables 2 and 3 above) the maximum of a 20% intensity and a 10% intensity, which is 20%.

[0207] In some applications, the control unit selects a zero illumination intensity value (i.e., an “off” value), in response to the second-person-sleeping likelihood exceeding a threshold. This selection may also be in response to other factors, e.g., the bed-exit likelihood. For example, if the bed-exit likelihood is relatively high, the control unit may not select a zero illumination intensity value, even though the second-person-sleeping likelihood exceeds the threshold.

[0208] In some applications, a single sensor 316 senses the motion of both persons. This may be the case, for example, when the first and second persons share a bed, and a single motion sensor 30 is used to sense motion on the bed. The control unit analyzes the motion signal from the single sensor, and calculates the second-person-sleeping likelihood in response thereto. (When a single motion sensor 30 is used, subject identification module 102 (FIG. 4) may be used to differentiate between the motion of the first person and the motion of the second person.) In other applications, such as the application shown in FIG. 20, a first sensor 316a (e.g., a first motion sensor 30a) monitors first person 338, while a second sensor 316b (e.g., a second motion sensor 30b) monitors second person 340. (The two persons may be on the same bed, or on different beds.) The control unit analyzes the signal (e.g., a motion signal) from second sensor 316b, and in response thereto, calculates the second-person-sleeping likelihood.

[0209] Alternatively or additionally, the control unit identifies the second-person-sleeping likelihood in response to a time of day. For example, if the second person usually sleeps between 11 pm and 6 am, the control unit may identify a higher second-person-sleeping likelihood between 11 pm and 6 am, relative to other times of the day. Alternatively or additionally, apparatus 334 further comprises an input unit 342, and the control unit identifies the second-person-sleeping likelihood in response to an input thereto. For example, the second person may use input unit 342 to indicate that (s)he is going to sleep, and the control unit will, in response

to the input, begin to identify a higher second-person-sleeping likelihood. Input unit 342 may be part of user interface (U/I) 24, described hereinabove with reference to FIG. 1, or may be a separate unit, such as the input unit of a mobile phone that is in communication with the control unit.

[0210] In some applications, as shown in FIG. 20, apparatus 334 is for use with both first illuminator 332 and a second illuminator 344, where the illuminators are located such that, when the first and second persons are on resting surface 37 (or on separate resting surfaces 37), first illuminator 332 is closer to the first person than to the second person, and second illuminator 344 is closer to the second person than to the first person. The control unit is configured to set an illumination intensity of the second illuminator to be different from the illumination intensity of the first illuminator, in response to (a) a likelihood that the second person has left resting surface 37, and/or a likelihood that the second person is preparing to leave resting surface 37 (i.e., the bed-exit likelihood for the second person), and (b) a likelihood that the first person is sleeping (i.e., a first-person-sleeping likelihood).

[0211] Reference is now made to FIG. 21, which is a schematic illustration of apparatus 346 for use with a waking mechanism 348 (e.g., an alarm clock, a mobile phone, an illuminator, and/or a vibrating element) that executes a waking routine to wake a subject 12 (e.g., first person 338) who is sleeping near second person 340, in accordance with some applications of the present invention. Apparatus 346 comprises a sensor 316, configured to monitor second person 340 and generate a signal in response thereto. Sensor 316 may comprise, for example, motion sensor 30, configured to sense motion on the resting surface 37 on which the second person is resting and generate a motion signal in response thereto. Alternatively or additionally, sensor 316 may comprise at least one sensor of another type, such as an electromyographic sensor and/or an imaging sensor.

[0212] Prior to execution of the waking routine, control unit 14 analyzes the signal from sensor 316. In response to analyzing the signal, the control unit identifies a likelihood that the second person is sleeping, and in response to the likelihood, sets an intensity of the waking routine by sending a signal to the waking mechanism. For example, in response to a relatively high likelihood, the control unit will set the intensity of the waking routine (e.g., the volume of an alarm) to be relatively low, so as to reduce disturbance to the second person. Following the beginning of the execution of the waking routine, the control unit analyzes the signal. If, in response to analyzing the signal, the control unit identifies that the subject has not woken, the control unit increases the intensity of the waking routine, e.g., increases the volume of an alarm. These steps may be repeated several times, until the control unit identifies that the subject has woken. In this manner, the chances of waking the second person are reduced. Alternatively or additionally, in response to a relatively high likelihood that the second person is sleeping, the control unit may activate an alternate waking mechanism that is less potentially disturbing to the second person, such as an illuminator (FIG. 20).

[0213] In some applications, control unit 14 further identifies a sleep stage of the second person, and sets the intensity of the waking routine in response to the identified sleep stage. For example, if the second person is in a deep

sleep, and therefore less likely to be disturbed by the waking routine, the control unit may set the waking routine to a relatively high intensity.

[0214] FIG. 21 also shows apparatus 376 for use with a communication device 378 belonging to a first person 338, in accordance with some applications of the present invention. (It is noted that communication device 378 may be identical to waking mechanism 348.) Communication device 378 generates an alert upon receiving an incoming communication; for example, communication device 378 may include a mobile phone that rings upon receiving an incoming call.

[0215] In response to analyzing the signal from sensor 316, the control unit identifies a likelihood that the second person is sleeping, and controls an intensity of the alert in response to the identified likelihood. For example, in response to identifying that there is a relatively high likelihood that the second person is sleeping, the control unit may lower the intensity of the alert (e.g., lower the volume of the ring), or inhibit the communication device from activating the alert (e.g., mute the phone). In some applications, the control unit continually identifies the likelihood that the second person is sleeping, and continually controls the communication device in response thereto. (For example, the control unit may continually adjust the volume of the ringer of the phone, regardless of whether there is an incoming call.) In other applications, the control unit controls the intensity of the alert further in response to the communication device receiving the incoming communication, e.g., the control unit adjusts the volume of the ringer only upon the phone receiving an incoming call.

[0216] In some applications, the control unit controls the intensity of the alert in response to the identified sleep stage of second person 340. For example, if the second person is sleeping lightly (and is therefore relatively likely to be disturbed by the alert), the control unit may lower the volume of the ring more than if the second person were sleeping deeply or were awake.

[0217] FIG. 21 also shows apparatus 386 for use with a mechanism 388 (e.g., a toilet-flushing mechanism a window-opening mechanism) that is activated by a first person 338, in accordance with some applications of the present invention. In response to analyzing the signal from sensor 316 (e.g., motion sensor 30), the control unit identifies a likelihood that the second person is sleeping, and delays the activation of the mechanism, and/or inhibits (e.g., prevents) the activation of the mechanism, in response to the identified likelihood. For example, if the control unit identifies a high likelihood that second person 340 is sleeping, the control unit may delay the flushing of the toilet until the likelihood is reduced. (This may be effected, for example, by communicating a signal to a “smart” toilet flusher of the toilet.) In some applications, the control unit further identifies a sleep stage of the second person, and delays the activation of the mechanism in response to the identified sleep stage. For example, the flushing of the toilet may be delayed if the second person is sleeping lightly, but not if the second person is sleeping deeply or is awake.

[0218] In order to reduce contamination of the motion signal from second person 340, the applications shown in FIG. 21 may be practiced in combination with subject identification module 102 (FIG. 4), and/or in combination with mechanical filtering provided by, for example, sensor

plate 140 with hardened edges 142 (FIG. 5), sensor plate 238 with rigid edge region 227 (FIG. 9A), etc., as described hereinabove.

[0219] Reference is now made to FIG. 22, which is a schematic illustration of apparatus 350 for use with a waking mechanism 348 (e.g., an alarm clock, a mobile phone, an illuminator, and/or a vibrating element) that executes a waking routine to wake a subject 12 (e.g., a first person 338) who is on a resting surface 37, in accordance with some applications of the present invention. Apparatus 350 comprises a sensor 316, configured to monitor subject 12 and generate a signal in response thereto. Sensor 316 may comprise, for example, non-contact motion sensor 30, configured to sense motion on the resting surface 37 on which the subject is resting and generate a motion signal in response thereto. Alternatively or additionally, sensor 316 may comprise at least one sensor of another type, such as an electromyographic sensor and/or an imaging sensor. Prior to execution of the waking routine, control unit 14 analyzes the signal from the sensor. If the control unit identifies, in response to the analyzing, that the subject is not on the resting surface, the control unit inhibits waking mechanism 348 from executing the waking routine.

[0220] In some applications, control unit 14 is further configured to identify a likelihood that a second person 340 is sleeping near the subject, and set an intensity of the waking routine in response to the likelihood by sending a signal to the waking mechanism. Generally, this is done as described hereinabove with reference to FIG. 21; for example, the control unit may increase the intensity of the waking routine one or more times, until the subject is woken. Furthermore, in some applications, the control unit changes an angle of the resting surface (e.g., as described in US 2013/0267791 to Halperin, which is incorporated herein by reference), in response to identifying that the waking routine has not woken the subject. The change in angle of the resting surface may facilitate the waking of the subject, while causing only a relatively small disturbance to other individuals in the area, e.g., second person 340. In some applications, the control unit identifies a sleep stage of the subject, and changes the angle of the resting surface in response to the identified sleep stage. For example, if the subject is in a deep sleep, the control unit may change the angle by a relatively large amount, such as to increase the probability that the subject will wake up.

[0221] In some applications, if control unit 14 identifies, in response to analyzing the signal following the beginning of execution of the waking routine, that the subject has woken, the control unit changes the angle of the resting surface. For example, the control unit may move the upper portion of the bed to a more upright position, in order to facilitate the subject's exit from bed.

[0222] Although FIG. 22 shows two sensors 316, it is noted that the scope of the present invention includes the use of exactly one sensor 316 (e.g., exactly one motion sensor 30) to monitor both first person 338 and second person 340. In such applications, subject identification module 102 (FIG. 4) may be used to differentiate between the motion of the first person and the motion of the second person.

[0223] Reference is now made to FIG. 23, which is a schematic illustration of apparatus 352 for use with (i) a waking mechanism 348 that executes a waking routine to wake a subject 12 who is on a resting surface 37, and (ii) an output unit 354, in accordance with some applications of the

present invention. (In some applications, as shown in FIG. 23, a single device, such as a mobile phone, may include both waking mechanism 348 and output unit 354.) Apparatus 350 comprises a sensor 316, configured to monitor subject 12 and generate a signal in response thereto. Sensor 316 may comprise, for example, motion sensor 30, configured to sense motion on the resting surface 37 on which the subject is resting and generate a motion signal in response thereto. Alternatively or additionally, sensor 316 may comprise at least one sensor of another type, such as an electromyographic sensor and/or an imaging sensor.

[0224] Prior to execution of the waking routine, control unit 14 analyzes the signal from sensor 316, and, in response to analyzing the signal, identifies a sleep stage of the subject. Upon the subject waking, the control unit drives output unit 354 to output the identified sleep stage to the subject, only if the identified sleep stage is a slow-wave (i.e., deep) sleep stage. (The output may include a technical description of the sleep stage, e.g., “NREM stage 3”, and/or a non-technical description, e.g., “deep sleep”.) Alternatively or additionally, the control unit drives output unit 354 to output a recommendation to the subject to perform a wakefulness-inducing activity, only if the identified sleep stage is a slow-wave sleep stage. For example, the control unit may drive the output unit to output an audio and/or visual message such as “You were just woken from a deep sleep. Consider doing some light exercise, or drinking a coffee.” Alternatively or additionally, the control unit drives the output unit to output a recommendation to the subject to refrain from operating a vehicle for a specific period of time, only if the identified sleep stage is a slow-wave sleep stage.

[0225] In some applications, in response to analyzing the signal prior to the execution of the waking routine, the control unit identifies at least one physiological parameter of the subject, such as the subject’s heart rate, heart rate variability, respiration rate, respiration rate variability, and/or blood pressure. The control unit then drives the output unit to output the physiological parameter, upon the subject waking. In some applications, the control unit drives the output unit to output the physiological parameter, only if the physiological parameter deviates from a baseline value. The output of the physiological parameter may help the subject manage his/her post-waking activities. For example, if the subject sees that his/her heart rate is relatively high, the subject may refrain from drinking coffee. In some applications, in response to the physiological parameter deviating from the baseline value, the control unit drives the output unit to output a recommendation to the subject to perform a specific activity (e.g., exercise), and/or a recommendation to refrain from performing a specific activity (e.g., drinking coffee).

[0226] FIG. 23 also shows apparatus 380 for use with communication device 378 (e.g., a mobile phone). In response to analyzing the signal from sensor 316 (e.g., motion sensor 30), control unit 14 identifies a sleep stage of subject 12, and controls an intensity of the alert that is generated by communication device 378 in response to the identified sleep stage. In some applications, the control unit lowers the intensity of the alert in response to a relatively light sleep stage, relative to a deeper sleep stage. For example, the subject may indicate before going to sleep that (s)he wishes to be woken upon receiving a call, but in a manner that generally minimizes potential disturbances to others. By providing for an alert intensity that is generally

increasing with the deepness of the subject’s sleep, the control unit generally provides for the ring volume to be loud enough to wake the subject up, but not significantly louder than necessary. In other applications, the control unit controls the intensity in the opposite manner, i.e., it raises the intensity of the alert in response to a relatively light sleep stage, relative to a deeper sleep stage. (For example, the control unit may inhibit the communication device from activating the alert, in response to the identified sleep stage being a slow-wave sleep stage, but allow the alert to be activated in response to a light sleep stage.) This behavior may be in response to the subject indicating before going to sleep that (s)he does not wish to be woken from a deep sleep, but does not mind being woken from a light sleep.

[0227] In some applications, as described hereinabove with reference to FIG. 21, the control unit controls the intensity of the alert further in response to the communication device receiving the incoming communication. In some applications, apparatus 380 further includes elements of apparatus 376, described hereinabove with reference to FIG. 21. For example, the control unit may be further configured to identify a likelihood that a second person 340 (FIG. 21) is sleeping near the subject, and control the intensity of the alert, further in response to the likelihood.

[0228] FIG. 23 also shows apparatus 382 for inhibiting outgoing communication from communication device 378 (e.g., a mobile phone). In response to analyzing the signal from sensor 316 (e.g., motion sensor 30), control unit 14 identifies that the subject is sleeping, and, in response thereto, inhibits (e.g., prevents) outgoing communication from the communication device. By doing so, the control unit may at least partially prevent “sleeptexting” by subject 12, and/or may at least partially prevent another user (e.g., a mischievous child) from using the subject’s device without the subject’s permission. In inhibiting the outgoing communication, the control unit may at least partially disable the communication device (e.g., disable the texting and/or calling functionality of a mobile phone). In some applications, the control unit drives the communication device to prompt the user to input an answer to an objective question (e.g., “What is the capital of Kansas?”), and allows outgoing communication from the communication device only if the answer is correct. In this manner, outgoing communication from a sleeping subject 12 (e.g., “sleeptexting”) may be at least partially prevented.

[0229] FIG. 23 also shows apparatus 384 for use with a subject 12 who is on a resting surface 37, in accordance with some applications of the present invention. In response to analyzing the signal from sensor 316 (e.g., motion sensor 30), the control unit identifies a likelihood that the subject has left the resting surface, and/or a likelihood that the subject is preparing to leave the resting surface. In response to the likelihood(s), and in response to the control unit further identifying that the subject is sleeping, the control unit generates a “sleepwalking” alert. For example, if the signal gave no indication that the subject woke prior to the indication that the subject left the bed, an alert will be generated. In response to the alert, a caregiver may come to the subject’s aid.

[0230] Reference is now made to FIG. 24, which is a schematic illustration of apparatus 356 for identifying a posture of a subject 12, in accordance with some applications of the present invention. Apparatus 356 comprises a single motion sensor 30, configured to sense motion of a

person (e.g., the subject, or any other person) without contacting or viewing the person or clothes the person is wearing, and generate a motion signal in response thereto.

[0231] During a learning stage 357, a person adopts a number of different lying postures at respective times, while being monitored by motion sensor 30. Control unit 14 receives a plurality of inputs indicative of postures of the person at the respective times. For example, for each posture that the person adopts, the control unit may receive an input that describes (or “classifies”) the posture, e.g., “supine”, “prone”, etc. By using the plurality of inputs and by analyzing the motion signal at the respective times, the control unit learns a posture-identification technique. For example, the control unit may identify various features of the motion signal, such as amplitude, dominant frequencies, etc. that discriminate between the various postures. Then, during an operative stage 359 that follows learning stage 357, when the subject is lying on resting surface 37 (e.g., a hospital bed) and being monitored by sensor 30, the control unit uses the learned posture-identification technique to identify the posture of the subject. For example, by analyzing the motion signal, the control unit may identify particular features of the signal that, during the learning stage, were found to be indicative of a particular posture. The control unit then identifies that particular posture as being the posture of the subject.

[0232] Preferably, in order to improve the efficacy of the learned posture-identification technique, learning stage 357 is performed with the subject lying on resting surface 37, rather than with a different person and/or a different resting surface. However, in some applications (e.g., when the physical condition of subject 12 does not allow for the subject to participate in the learning stage), control unit 14 uses a more “generic” posture-identification technique that was learned (e.g., by the control unit) from one or more other persons lying on the same, or a different, resting surface. In using this technique, the control unit may make use of parameters relating to the subject’s physical condition (e.g., the subject’s body mass index), and/or the resting surface (e.g., a thickness of a mattress), in order to more effectively perform the posture identification.

[0233] In some applications, the control unit is further configured to verify compliance of a healthcare provider for the subject with a pressure-ulcer-prevention protocol, in response to identifying the posture.

[0234] Reference is now made to FIG. 25, which is a schematic illustration of apparatus 358 for monitoring a subject 12, in accordance with some applications of the present invention. Apparatus 358 comprises a motion sensor 30, configured to sense motion of the subject on resting surface 37 and generate a motion signal in response thereto. Control unit 14 analyzes the motion signal (analysis step 361), and, in response thereto, identifies that the subject has lain on the resting surface (first identification step 363). Subsequently to the subject lying on the resting surface, the control unit identifies a physiological parameter relating to a physiological slowing time of the subject (second identification step 365). For example, the control unit may identify a parameter relating to a slowing of a heart rate of the subject, such as the time for the heart rate to slow to a normal resting value. Alternatively or additionally, the control unit may identify a parameter relating to a slowing of a respiratory rate of the subject, such as the time for the respiratory rate to slow to a normal resting value. If the control unit

identifies that the physiological parameter may be indicative of a physiological deterioration of the subject, the control unit generates an output (output generation step 367).

[0235] In some applications, the control unit identifies that the physiological parameter may be indicative of a physiological deterioration of the subject by identifying that the physiological parameter deviates from a baseline value. For example, if, in a healthy person, the heart rate generally slows to a normal resting value within 1-5 minutes, but the subject’s heart rate slowed to a normal resting value within more than 10 minutes (or did not slow to a normal resting value at all, within a given period of time), the control unit generates an output, e.g., a warning to a physician. The baseline may be with reference to the subject, rather than with reference to a healthy person. For example, the baseline heart-rate slowing time may be the average slowing time for the subject during the previous 7 days. In some applications, the control unit is further configured to calculate the baseline value by analyzing the motion signal following each of a plurality of instances of a person (e.g., any healthy person, or the subject) lying on a resting surface.

[0236] Alternatively or additionally, the control unit identifies that the physiological parameter may be indicative of a physiological deterioration of the subject by identifying a deteriorating trend in the physiological parameter. For example, if, over the last several days, the heart-rate slowing time of the subject has been steadily increasing, the control unit may identify this as a deteriorating trend, and may generate an output, e.g., a warning, in response thereto.

[0237] In some applications, the control unit identifies a possible physiological condition of the subject, in response to identifying that the physiological parameter may be indicative of a physiological deterioration of the subject, and generates an output in response thereto. For example, (a) in response to a deteriorating (e.g., increasing) trend in heart-rate slowing time, and/or a heart-rate slowing time that deviates from (e.g., is greater than) a baseline value, the control unit may identify that the subject possibly suffers from clinical anxiety, or (b) in response to a deteriorating (e.g., increasing) trend in respiratory-rate slowing time, and/or a respiratory-rate slowing time that deviates from (e.g., is greater than) a baseline value, the control unit may identify that the subject possibly suffers from asthma. In some applications, the control unit identifies an activity level of the subject, in response to analyzing the motion signal, and regulates the output in response to the identified activity level. Typically, the control unit regulates the output by generating the output only if an adjusted physiological parameter deviates from the baseline value, or if the physiological parameter deviates from an adjusted baseline value. For example, in response to identifying a relatively high activity level, the control unit may adjust a baseline heart-rate slowing time of 5 minutes to 7 minutes, and hence, may not generate the output unless the heart-rate slowing time of the subject exceeds 7 minutes. Alternatively or additionally, the control unit withholds generating the output if the identified activity level is greater than a threshold, and/or does not begin measuring the slowing time until the activity level of the subject falls below a threshold. By regulating the output in this manner, the control unit may at least partially avoid generating false alarms.

[0238] Reference is now made to FIG. 26, which is a schematic illustration of apparatus 360 for monitoring a subject (e.g., subject 12), in accordance with some applica-

tions of the present invention. Apparatus 360 comprises a sensor plate 362 comprising an upper surface 364 that is configured to deflect in response to motion of the subject. Apparatus 360 also comprises a sensor 366, such as a ceramic piezoelectric sensor, vibration sensor, pressure sensor, or strain sensor disposed underneath upper surface 364. Sensor 366 generates a motion signal in response to the deflection of upper surface 364, and control unit 14 analyzes the motion signal and generates an output indicative of a condition of the subject, in response thereto. Motion sensor 30, described throughout the present application, may comprise sensor plate 362 and sensor 366.

[0239] Center 368 of sensor 366 is typically disposed at a distance D from a center 370 of sensor plate 362 that is at least 30% and/or less than 70%, e.g., between 30% and 70%, of a length L of a line 372 drawn from center 370 of the sensor plate to a perimeter 374 of the sensor plate, through center 368 of the sensor. (In this context, the “center” of the sensor is the centroid of a surface of the sensor, and similarly, the “center” of the sensor plate is the centroid of a surface of the sensor plate.) Generally, the disposition of sensor 366 in this manner is advantageous in at least two ways:

[0240] (i) The sensor is more sensitive to deflections of the sensor plate at frequencies between 1 and 100 Hz, relative to if the sensor were disposed more toward the center or the perimeter of the sensor plate. The range of 1-100 Hz is significant, at least in that heartbeat-related signals and, to a lesser extent, respiratory-related signals from the subject include harmonic frequencies of interest that are within this range. (These harmonic frequencies may be used, for example, to predict a physiological condition of the subject, as described in U.S. Pat. No. 8,679,034, which is incorporated herein by reference.) The greater sensitivity to the aforementioned range of frequencies is due at least to (a) the asymmetric configuration of the sensor and sensor plate, and (b) the relative stiffness of upper surface 364 at the location at which sensor 366 is disposed.

[0241] (ii) For cases in which subject 12 shares a bed with a partner, sensor plate 362 may be placed underneath the subject such that sensor 366 faces toward the near edge of the bed, i.e., away from the partner. In this manner, sensor 366 will be less affected by signals from the partner, relative to if it were disposed closer to the center of the sensor plate. In this regard, it is noted that sensor plate 362 may also include elements of sensor plate 238, described hereinabove with reference to FIGS. 9A-B and 10A-D. For example, sensor plate 362 may include noise filter plate 226 (FIG. 9B), which, as described hereinabove, allows for mechanical filtering of signals coming from the partner. Alternatively or additionally, for example, sensor plate 362 may include a slot 219 (as shown in FIG. 26), for improved sensing of the subject's signal and filtering of the partner's signal, as described hereinabove with reference to FIG. 10C.

[0242] Typically, the upper surface area A2 of the sensor is between 0.2 and 30 cm². (FIG. 25 shows the lower surface area of the sensor, which is typically very close or identical to the upper surface area.) Further typically, the upper surface area A1 of the sensor plate is between 20 and 200 cm² or between 200 and 710 cm². In some applications, upper surface area A1 of the sensor plate is between 2 and 8 times greater, or between 8 and 30 times greater, than upper surface area A2 of the sensor.

[0243] Reference is now made to (a) FIG. 27A, which is a schematic illustration of apparatus 600 comprising motion sensor 30, a mains-power-connection device 602, and control unit 14, and (b) FIG. 27B, which is a schematic illustration of mains-power-connection device 602, in accordance with some applications of the present invention. Mains-power-connection device 602 comprises electrically-conductive protrusions (e.g., prongs) 604 that are configured to fit into holes in an electric socket. The mains-power-connection device receives electricity through electrically-conductive protrusions 604, and uses the electricity to deliver power to motion sensor 30. Control unit 14 is disposed within the mains-power-connection device such that, whenever the protrusions are placed inside the holes, the control unit is at least partially within 20 cm of the electric socket. For example, the control unit may be at least partially within 10 cm of the electric socket, i.e., distance D2 in FIG. 27A is less than 10 cm. As shown in FIG. 27B, mains-power-connection device 602 typically comprises a rigid housing 606, from which the electrically-conductive protrusions protrude, and inside of which the control unit is disposed. In general, the disposition of control unit 14 within mains-power-connection device 602 is advantageous, especially in a home setting, in that it is less noticeable to an observer that the patient/subject is being monitored. Typically, control unit 14 communicates wirelessly with a server, and/or with a mobile electronic device. For example, output from the control unit may be communicated to a physician's mobile electronic device.

[0244] Reference is now made to FIGS. 28 and 29, which are schematic illustrations of apparatus 420 for use with a burglar alarm 422, in accordance with some applications of the present invention. Burglar alarm 422 includes a detector 424 (e.g., a motion detector) configured to detect activity (e.g., motion) and to generate an activity-detection signal in response thereto. Apparatus 420 comprises a sensor 316 (e.g., motion sensor 30), and control unit 14. Control unit 14 identifies a correspondence between (a) the activity-detection signal, and (b) the signal that is generated by sensor 30, and inhibits burglar alarm 422 from being triggered, in response to the correspondence. For example, if a person 426 is moving on resting surface 37, sensor 30 will generate a signal indicative of the movement. If this signal corresponds to the activity-detection signal of detector 424, e.g., detector 424 detects activity on resting surface 37, control unit 14 inhibits the burglar alarm from being triggered. On the other hand, the burglar alarm will not be inhibited if the two signals don't correspond, e.g., it can be inferred that detector 424 is detecting activity outside of resting surface 37. Another example is shown in FIG. 28. In FIG. 28, person 426 is shown as having left resting surface 37. In response to analyzing the signal from sensor 30, the control unit ascertains that the person has left the resting surface, and in response thereto, inhibits the burglar alarm from being triggered, since it is likely that the detector is detecting activity of person 426.

[0245] In some applications, the control unit inhibits the burglar alarm from being triggered at a given time only if the person left the resting surface more than a threshold amount of time prior to the given time. For example, as shown in FIG. 29, detector 424 may be disposed outside of the bedroom, e.g., near the entrance to the house, and it typically takes a threshold amount of time for the person to walk from the bedroom to the area in which the detector is disposed. If

the threshold amount of time has not passed, it is likely that detector **424** is detecting activity of an entity other than person **426**. The threshold amount of time is typically an input to the control unit, and is typically a function of the speed at which person **426** typically moves. In some applications, burglar alarm **422** includes a motion-detection-based alarm, i.e., burglar alarm **422** includes motion detector **424**, and the control unit inhibits the motion-detection-based alarm. In some applications, burglar alarm **422** also includes a perimeter alarm **428**, and the control unit is configured to not inhibit perimeter alarm **428** from being triggered, while inhibiting the motion-detection-based alarm from being triggered.

[0246] Reference is now made to FIG. **30**, which is a schematic illustration of apparatus **430** for use with burglar alarm **422**, in accordance with some applications of the present invention. Apparatus **430** comprises sensor **316** (e.g., motion sensor **30**), and control unit **14**. Control unit **14** analyzes the signal from sensor **316**. In response to the analyzing, the control unit ascertains that person **426** is on the resting surface, and in response thereto, places burglar alarm **422** in an armed state. In general, apparatus **430** may comprise more than one sensor, and/or more than one control unit. For example, FIG. **30** shows an application in which respective sensors and control units are disposed in respective rooms. In response to the control units ascertaining that all of the resting surfaces are occupied, burglar alarm **422** is placed in an armed state.

[0247] The arming of burglar alarm **422**, as described hereinabove, is but an example of many related actions that control unit **14** can perform (e.g., via wireless communication), upon ascertaining that a person, or all of the persons in the household, is/are likely to be going to sleep. For example, control unit **14** may lock a door **432**, reduce an intensity of (e.g., turn off) a light **434**, turn off a device **436**, and/or turn off an appliance **438**. Alternatively or additionally, control unit **14** may generate a notification that (a) door **432** is unlocked, (b) light **434** is on, (c) device **436** is on, and/or (d) appliance **438** is on.

[0248] In general, control unit **14** may be embodied as a single control unit **14**, or a cooperatively networked or clustered set of control units. Control unit **14** is typically a programmed digital computing device comprising a central processing unit (CPU), random access memory (RAM), non-volatile secondary storage, such as a hard drive or CD ROM drive, network interfaces, and/or peripheral devices. Program code, including software programs, and data are loaded into the RAM for execution and processing by the CPU and results are generated for display, output, transmittal, or storage, as is known in the art. Typically, control unit **14** is connected to one or more sensors via one or more wired or wireless connections. Control unit **14** is typically configured to receive signals (e.g., motions signals) from the one or more sensors, and to process these signals as described herein. In the context of the claims and specification of the present application, the term "motion signal" is used to denote any signal that is generated by a sensor, upon the sensor sensing motion. Such motion may include, for example, respiratory motion, cardiac motion, or other body motion, e.g., large body-movement. Similarly, the term "motion sensor" is used to denote any sensor that senses motion, including the types of motion delineated above.

[0249] Techniques described herein may be practiced in combination with techniques described in one or more of the

following patents and patent applications, which are incorporated herein by reference. In some applications, techniques and apparatus described in one or more of the following applications are combined with techniques and apparatus described herein:

- [0250] U.S. patent application Ser. No. 11/048,100, filed Jan. 31, 2005, which issued as U.S. Pat. No. 7,077,810;
- [0251] U.S. patent application Ser. No. 11/197,786, filed Aug. 3, 2005, which issued as U.S. Pat. No. 7,314,451;
- [0252] U.S. patent application Ser. No. 11/446,281, filed Jun. 2, 2006, which issued as U.S. Pat. No. 8,376,954;
- [0253] U.S. patent application Ser. No. 11/552,872, filed Oct. 25, 2006, now abandoned, which published as US 2007/0118054;
- [0254] U.S. patent application Ser. No. 11/755,066, filed May 30, 2007, now abandoned, which published as US 2008/0114260;
- [0255] U.S. patent application Ser. No. 11/782,750, filed Jul. 25, 2007, which issued as U.S. Pat. No. 8,403,865;
- [0256] U.S. patent application Ser. No. 12/113,680, filed May 1, 2008, which published as US 2008/0275349;
- [0257] U.S. patent application Ser. No. 12/842,634, filed Jul. 23, 2010, which issued as U.S. Pat. No. 8,517,953;
- [0258] U.S. patent application Ser. No. 12/938,421, filed Nov. 3, 2010, which issued as U.S. Pat. No. 8,585,607;
- [0259] U.S. patent application Ser. No. 12/991,749, filed Nov. 9, 2010, which published as US 2011/0112442;
- [0260] U.S. patent application Ser. No. 13/107,772, filed May 13, 2011, which issued as U.S. Pat. No. 8,491,492;
- [0261] U.S. patent application Ser. No. 13/305,618, filed Nov. 28, 2011, which published as US 2012/0132211;
- [0262] U.S. patent application Ser. No. 13/389,200, filed Jun. 13, 2012, which published as US 2012/0253142;
- [0263] U.S. patent application Ser. No. 13/750,957, filed Jan. 25, 2013, which issued as U.S. Pat. No. 8,603,010;
- [0264] U.S. patent application Ser. No. 13/750,962, filed Jan. 25, 2013, which issued as U.S. Pat. No. 8,679,034;
- [0265] U.S. patent application Ser. No. 13/863,293, filed Mar. 15, 2013, now abandoned, which published as US 2013/0245502;
- [0266] U.S. patent application Ser. No. 13/906,325, filed May 30, 2013, which published as US 2013/0267791;
- [0267] U.S. patent application Ser. No. 13/921,915, filed Jun. 19, 2013, which issued as U.S. Pat. No. 8,679,030;
- [0268] U.S. patent application Ser. No. 14/019,371, filed Sep. 5, 2013, which published as US 2014/0005502;

[0269] U.S. patent application Ser. No. 14/020,574, filed Sep. 6, 2013, which issued as U.S. Pat. No. 8,731,646;

[0270] U.S. patent application Ser. No. 14/054,280, filed Oct. 15, 2013, which issued as U.S. Pat. No. 8,734,360;

[0271] U.S. patent application Ser. No. 14/150,115, filed Jan. 8, 2014, which published as US 2014/0171816;

[0272] International Patent Application PCT/IL2005/000113, which published as WO 2005/074361;

[0273] International Patent Application PCT/IL2006/000727, which published as WO 2006/137067;

[0274] International Patent Application PCT/IL2009/000473, which published as WO 2009/138976;

[0275] International Patent Application PCT/IL2011/050045, which published as WO 2012/077113;

[0276] International Patent Application PCT/IL2013/050283, which published as WO 2013/150523;

[0277] International Patent Application PCT/M2006/002998, which published as WO 2007/052108; and

[0278] International Patent Application PCT/IL2008/000601, which published as WO 2008/135985.

[0279] It will be appreciated by persons skilled in the art that the present invention is not limited to what has been particularly shown and described hereinabove. Rather, the scope of the present invention includes both combinations and subcombinations of the various features described hereinabove, as well as variations and modifications thereof that are not in the prior art, which would occur to persons skilled in the art upon reading the foregoing description.

1. Apparatus for use with a subject who is a first person, who shares a bed with a second person, the apparatus comprising:

a thin, flat motion sensor configured to be placed underneath a portion of the bed, and, while disposed underneath the portion of the bed, to:

detect motion of the subject without contacting the subject, without contacting clothes the subject is wearing, without viewing the subject, and without viewing clothes the subject is wearing,

detect motion of the second person without contacting the second person, without contacting clothes the second person is wearing, without viewing the second person, and without viewing clothes the second person is wearing, and

generate a motion signal in response to detecting motion of the subject and motion of the second person; and

a control unit configured to:

identify components of the motion signal that were generated in response to motion of the subject, by distinguishing between components of the motion signal that were generated in response to motion of the subject, and components of the motion signal that were generated in response to motion of the second person,

analyze the components of the motion signal that were generated in response to motion of the subject, and generate an output in response thereto.

2. The apparatus according to claim 1, wherein the control unit is configured to identify components of the motion signal that were generated in response to motion of the subject, by identifying components of the motion signal that

have a signal strength that is a characteristic signal strength of a motion signal of the subject.

3. The apparatus according to claim 1, wherein the control unit is configured to identify components of the motion signal that were generated in response to motion of the subject by identifying components of the motion signal that have a pattern that is a characteristic pattern of motion of the subject.

4. The apparatus according to claim 1, further comprising a weight sensor that is configured to detect when the subject is lying above the motion sensor, wherein the control unit is configured to identify the components of the motion signal that were generated in response to motion of the subject, in response to a signal that is generated by the weight sensor.

5. The apparatus according to claim 1, wherein the motion sensor is configured to facilitate the identification of components of the motion signal that were generated in response to motion of the subject, by strengthening a signal strength of the components of the motion signal that are generated in response to motion of the subject.

6. The apparatus according to claim 5, wherein the apparatus is for use with a subject who lies on a mattress, and wherein the sensor is configured to be placed at a position selected from the group consisting of: underneath the mattress at a position that is higher than a head of the subject is typically placed, and adjacent to and in contact with a side of the mattress.

7. The apparatus according to claim 6, wherein the sensor is configured such as to facilitate identification, by the control unit, of components of the motion signal that were generated in response to a longitudinal cardio-ballistic effect of the subject.

8. The apparatus according to claim 1, wherein the control unit is configured to identify components of the motion signal that were generated in response to respiratory motion of the subject.

9. The apparatus according to claim 1, wherein the control unit is configured to identify components of the motion signal that were generated in response to cardiac motion of the subject.

10. The apparatus according to claim 1, wherein the control unit is configured to identify components of the motion signal that were generated in response to large body-movement of the subject.

11. The apparatus according to claim 1, wherein the control unit is further configured to:

analyze the motion signal,

in response thereto, identify an effect of large body-movement of the second person on sleep of the subject, and

in response thereto, generate a sleep-disturbance output.

12. The apparatus according to claim 11, wherein:

(A) the sleep-disturbance output includes an assessment of an effectiveness of a parameter at reducing the effect of the large body-movement of the second person on the sleep of the subject, the control unit being configured to generate the assessment of the effectiveness of the parameter, and

(B) the parameter is selected from the group consisting of: a parameter of a mattress on which the subject is sleeping, a parameter of the bed, a sleeping arrangement of the subject and the second person, and a room-environment parameter, the control unit being

configured to generate the assessment of the effectiveness of the selected parameter.

13. The apparatus according to claim **11**, wherein:

- (A) the sleep-disturbance output includes a recommendation to reduce the effect of the large body-movement of the second person on the sleep of the subject by adjusting an adjustable parameter, the control unit being configured to generate the recommendation, and
- (B) the adjustable parameter is selected from the group consisting of: a parameter of a mattress on which the subject is sleeping, a parameter of the bed, a sleeping arrangement of the subject and the second person, and a room-environment parameter, the control unit being configured to generate the recommendation to adjust the selected parameter.

14. The apparatus according to claim **11**, wherein:

- (A) the sleep-disturbance output includes instructions to a device to adjust an adjustable parameter, the control unit being configured to generate the instructions, and
- (B) the adjustable parameter is selected from the group consisting of: a parameter of a mattress on which the subject is sleeping, a parameter of the bed, a sleeping arrangement of the subject and the second person, and a room-environment parameter, the control unit being configured to generate the instructions to the device to adjust the selected parameter.

15. The apparatus according to claim **1**, wherein the motion sensor consists of a single motion sensor.

16. The apparatus according to claim **1**, wherein the control unit is configured to identify that a portion of the motion signal was generated in response to motion of the

second person, and not in response to motion of the subject, by identifying that the portion exhibits ringing.

17. The apparatus according to claim **16**, wherein the control unit is configured to identify that the portion of the motion signal generated in response to motion of the second person exhibits ringing by ascertaining that the portion includes a set of at least three consecutive extrema each of which is separated from the preceding extremum of the set by a time that falls within a given time range.

18. The apparatus according to claim **17**, wherein the time range is 0.15-0.45 seconds.

19. The apparatus according to claim **16**, wherein the control unit is configured to identify that the portion of the motion signal generated in response to motion of the second person exhibits ringing by:

ascertaining that the portion includes a set of at least three consecutive extrema each of which is separated from the preceding extremum of the set by a time that falls within a given time range, and

further ascertaining that respective differences between (i) magnitudes of the set of consecutive extrema, and (ii) a magnitude of an extremum that precedes the set of consecutive extrema, fall within a given amplitude range.

20. The apparatus according to claim **19**, wherein the given amplitude range is 10%-150% of the magnitude of the extremum that precedes the set of consecutive extrema.

* * * * *

专利名称(译)	监控睡眠主题		
公开(公告)号	US20190254570A1	公开(公告)日	2019-08-22
申请号	US16/398572	申请日	2019-04-30
[标]申请(专利权)人(译)	EARLYSENSE		
申请(专利权)人(译)	EARLYSENSE LTD.		
当前申请(专利权)人(译)	EARLYSENSE LTD.		
[标]发明人	SHINAR ZVIKA DAVIDOVICH MAAYAN KLAP TAL HOFFERT SMADAR MEGER GUY		
发明人	SHINAR, ZVIKA DAVIDOVICH, MAAYAN KLAP, TAL HOFFERT, SMADAR MEGER, GUY		
IPC分类号	A61B5/11 A61B5/00 G08B21/02 G08B25/00 G08B21/04 A61B5/0205		
CPC分类号	A61B5/1102 A61B5/746 G08B21/0211 A61B5/6892 A61B5/002 A61B5/4815 G08B25/006 G08B21/0461 A61B5/6891 A61B5/11 A61B5/02055 A61G2203/36 A61B5/1115 A61B5/4809		
优先权	13/389200 2012-06-13 US PCT/IL2011/050045 2011-12-07 WO 61/420402 2010-12-07 US 61/439971 2011-02-07 US 61/561962 2011-11-21 US 61/618792 2012-04-01 US 61/696326 2012-09-04 US 61/698736 2012-09-10 US 61/722810 2012-11-06 US 61/725513 2012-11-13 US 61/739033 2012-12-19 US 61/748081 2013-01-01 US 61/756003 2013-01-24 US 61/757739 2013-01-29 US 61/764541 2013-02-14 US 61/772553 2013-03-05 US 61/847579 2013-07-18 US 61/926499 2014-01-13 US		
外部链接	Espacenet USPTO		

摘要(译)

描述了装置和方法，包括与第二人共用床的受试者一起使用的装置。运动传感器检测对象的运动和第二人的运动，并响应于此产生运动信号。控制单元通过区分响应于对象的运动而产生的运动信号的分量，以及响应于对象产生的运动信号的分量来识别响应于对象的运动而生成的运动信号的分量。对第二人的动议。控制单元分析响应于对象的运动而产生的运动信号的分量，并响应于此产生输出。还描述了其他应用。

