



(19) **United States**

(12) **Patent Application Publication**
de la Rama et al.

(10) **Pub. No.: US 2020/0138378 A1**
(43) **Pub. Date: May 7, 2020**

(54) **FLEXIBLE HIGH-DENSITY MAPPING CATHETER TIPS AND FLEXIBLE ABLATION CATHETER TIPS WITH ONBOARD HIGH-DENSITY MAPPING ELECTRODES**

A61B 18/14 (2006.01)
A61B 5/0408 (2006.01)

(52) **U.S. Cl.**
CPC *A61B 5/6852* (2013.01); *A61B 5/0422* (2013.01); *A61B 18/1492* (2013.01); *A61B 2018/00351* (2013.01); *A61B 5/6869* (2013.01); *A61B 5/6859* (2013.01); *A61B 5/0408* (2013.01)

(71) Applicant: **St. Jude Medical, Cardiology Division, Inc., St. Paul, MN (US)**

(72) Inventors: **Alan de la Rama, Cerritos, CA (US); Cary K. Hata, Irvine, CA (US); Don Curtis Deno, Andover, MN (US); Carlo Pappone, Cernusco Lombardone (IT)**

(57) **ABSTRACT**

Flexible high-density mapping catheter tips and flexible ablation catheter tips with onboard high-density mapping electrodes are disclosed. These tips can be used for diagnosing and treating cardiac arrhythmias. The flexible, distal tips are adapted to conform to tissue and comprise a plurality of microelectrodes mounted to permit relative movement among at least some of the microelectrodes. The flexible tip portions may comprise a flexible framework forming a flexible array of microelectrodes (for example, a planar or cylindrical array) adapted to conform to tissue and constructed at least in part from nonconductive material in some embodiments. The flexible array of microelectrodes may be formed from a plurality of rows of longitudinally-aligned microelectrodes. The flexible array may further comprise, for example, a plurality of electrode-carrying arms or electrode-carrier bands. Multiple flexible frameworks may be present on a single device. A delivery adapter having an internal compression cone is also disclosed.

(21) Appl. No.: **16/670,678**

(22) Filed: **Oct. 31, 2019**


Related U.S. Application Data

(63) Continuation of application No. 14/760,682, filed on Jul. 13, 2015, now Pat. No. 10,492,729, filed as application No. PCT/US2014/011940 on Jan. 16, 2014.

(60) Provisional application No. 61/753,429, filed on Jan. 16, 2013.

Publication Classification

(51) **Int. Cl.**
A61B 5/00 (2006.01)
A61B 5/042 (2006.01)






FIG. 1




FIG. 2




FIG.3




FIG. 4




FIG. 5




FIG. 6




FIG. 7




FIG. 8







FIG. 9






FIG. 13




FIG. 14




FIG.15




FIG.16






FIG. 17






FIG. 20




FIG. 21




FIG. 22




FIG. 23




FIG. 24




FIG. 26

FIG. 25




FIG. 27




FIG. 28




FIG. 29




FIG. 30




FIG. 31




FIG. 32




FIG.33




FIG.34




FIG.35




FIG.36




FIG. 37




FIG. 38




FIG. 39




FIG. 40




FIG. 41




FIG. 42




FIG. 43




FIG.44




FIG.45




FIG.46




FIG.47




FIG. 48A



FIG. 48B




FIG. 48C




FIG. 48D




FIG. 48E




FIG. 48F

**FLEXIBLE HIGH-DENSITY MAPPING
CATHETER TIPS AND FLEXIBLE
ABLATION CATHETER TIPS WITH
ONBOARD HIGH-DENSITY MAPPING
ELECTRODES**

**CROSS-REFERENCE TO RELATED
APPLICATIONS**

[0001] This application is a continuation of U.S. application Ser. No. 14/760,682, filed 13 Jul. 2015, which is a national stage filing based upon international application no. PCT/US2014/011940, filed 16 Jan. 2014 and published in English on 24 Jul. 2014 under international publication no. WO 2014/113612 A1, which claims priority to U.S. provisional application No. 61/753,429, filed 16 Jan. 2013. This application is related to U.S. provisional application No. 60/939,799, filed 23 May 2007; U.S. application Ser. No. 11/853,759, filed 11 Sep. 2007, now U.S. Pat. No. 8,187,267, issued 29 May 2012; U.S. provisional application No. 60/947,791, filed 3 Jul. 2007; U.S. application Ser. No. 12/167,736, filed 3 Jul. 2008, now U.S. Pat. No. 8,206,404, issued 26 Jun. 2012; U.S. application Ser. No. 12/667,338, filed 20 Jan. 2011 (371 date), published as U.S. patent application publication no. US 2011/0118582 A1, now U.S. Pat. No. 8,827,910, issued 9 Sep. 2014; U.S. application Ser. No. 12/651,074, filed 31 Dec. 2009, published as U.S. patent application publication no. US 2010/0152731 A1, now U.S. Pat. No. 8,979,837, issued 17 Mar. 2015; U.S. application Ser. No. 12/436,977, filed 7 May 2009, published as U.S. patent application publication no. US 2010/0286684 A1; U.S. application Ser. No. 12/723,110, filed 12 Mar. 2010, published as U.S. patent application publication no. US 2010/0174177 A1, now U.S. Pat. No. 8,734,440, issued 27 May 2014; U.S. provisional application No. 61/355,242, filed 16 Jun. 2010; U.S. application Ser. No. 12/982,715, filed 30 Dec. 2010, published as U.S. patent application publication no. US 2011/0288392 A1, now U.S. Pat. No. 8,974,454, issued 10 Mar. 2015; U.S. application Ser. No. 13/159,446, filed 14 Jun. 2011, published as U.S. patent application publication no. US 2011/0313417 A1; international application no. PCT/US2011/040629, filed 16 Jun. 2011, published as international publication no. WO 2011/159861 A2; U.S. application Ser. No. 13/162,392, filed 16 Jun. 2011, published as U.S. patent application publication no. US 2012/0010490 A1; and U.S. application Ser. No. 13/704,619, filed 16 Dec. 2012 (371 date), which is a national phase of international patent application no. PCT/US2011/040781, filed 16 Jun. 2011, published as international publication no. WO 2011/159955 A1. Each of these applications is hereby incorporated by reference as though fully set forth herein.

BACKGROUND

a. Field

[0002] The instant disclosure relates to high-density mapping catheter tips and to map-ablate catheter tips for diagnosing and treating cardiac arrhythmias via, for example, radiofrequency (RF) ablation. In particular, the instant disclosure relates to flexible high-density mapping catheter tips, and to flexible ablation catheter tips that also have onboard high-density mapping electrodes.

b. Background Art

[0003] Catheters have been used for cardiac medical procedures for many years. Catheters can be used, for example, to diagnose and treat cardiac arrhythmias, while positioned at a specific location within a body that is otherwise inaccessible without a more invasive procedure.

[0004] Conventional mapping catheters may include, for example, a plurality of adjacent ring electrodes encircling the longitudinal axis of the catheter and constructed from platinum or some other metal. These ring electrodes are relatively rigid. Similarly, conventional ablation catheters may comprise a relatively rigid tip electrode for delivering therapy (e.g., delivering RF ablation energy) and may also include a plurality of adjacent ring electrodes. It can be difficult to maintain good electrical contact with cardiac tissue when using these conventional catheters and their relatively rigid (or nonconforming), metallic electrodes, especially when sharp gradients and undulations are present.

[0005] Whether mapping or forming lesions in a heart, the beating of the heart, especially if erratic or irregular, complicates matters, making it difficult to keep adequate contact between electrodes and tissue for a sufficient length of time. These problems are exacerbated on contoured or trabeculated surfaces. If the contact between the electrodes and the tissue cannot be sufficiently maintained, quality lesions or accurate mapping are unlikely to result.

[0006] The foregoing discussion is intended only to illustrate the present field and should not be taken as a disavowal of claim scope.

BRIEF SUMMARY

[0007] The instant disclosure relates to high-density mapping catheter tips and to map-ablate catheter tips for diagnosing and treating cardiac arrhythmias via, for example, RF ablation. In particular, the instant disclosure relates to flexible high-density mapping catheter tips, and to flexible ablation catheter tips that also have onboard high-density mapping electrodes. Some embodiments include irrigation.

[0008] In one embodiment, a high-density mapping catheter comprises an elongated catheter body comprising a proximal end and a distal end, and defining a catheter longitudinal axis extending between the proximal and distal ends; and a flexible, distal tip assembly at the distal end of the catheter body and adapted to conform to tissue, the flexible distal tip assembly comprising a plurality of microelectrodes mounted so that at least some of the microelectrodes are moveable relative to other of the microelectrodes.

[0009] In another embodiment, a high-density mapping catheter comprises the following: (i) a catheter shaft comprising a proximal end and a distal end, the catheter shaft defining a catheter shaft longitudinal axis extending between the proximal end and the distal end; (ii) a flexible tip portion located adjacent to the distal end of the catheter shaft, the flexible tip portion comprising a flexible framework comprising nonconductive material; and (iii) a plurality of microelectrodes mounted on the flexible framework and forming a flexible array of microelectrodes adapted to conform to tissue; wherein the flexible framework is configured to facilitate relative movement among at least some of the microelectrodes relative to other of the microelectrodes; and wherein the nonconductive material insulates each microelectrode from other microelectrodes. The flexible array of microelectrodes may be, for example, a planar

or cylindrical array of microelectrodes formed from a plurality of rows of longitudinally-aligned microelectrodes. The flexible array may further comprise, for example, a plurality of electrode-carrying arms or electrode-carrier bands.

[0010] In yet another embodiment, a flexible, high-density mapping-and-ablation catheter comprising the following: (a) a catheter shaft comprising a proximal end and a distal end, the catheter shaft defining a catheter shaft longitudinal axis; (b) a first plurality of microelectrodes mounted on a first flexible framework of nonconductive material and forming a first flexible array of microelectrodes adapted to conform to tissue; wherein the first flexible framework is configured to facilitate relative movement among at least some of the microelectrodes; and wherein the nonconductive material insulates each microelectrode from other microelectrodes; and (c) a flexible tip portion located adjacent to the distal end of the catheter shaft, the flexible tip portion comprising a second flexible framework constructed from conductive material.

[0011] In another embodiment, a flexible, high-density mapping-and-ablation catheter comprising the following: (i) a catheter shaft comprising a proximal end and a distal end, the catheter shaft defining a catheter shaft longitudinal axis; (ii) a first plurality of microelectrodes mounted on a first flexible framework of nonconductive material and forming a first flexible array of microelectrodes adapted to conform to tissue; wherein the first flexible framework is configured to facilitate relative movement among at least some of the microelectrodes in the first plurality of microelectrodes relative to other of the microelectrodes in the first plurality of microelectrodes; and wherein the nonconductive material insulates each microelectrodes in the first plurality of microelectrodes from other microelectrodes in the first plurality of microelectrodes; (iii) a second plurality of microelectrodes mounted on a second flexible framework of nonconductive material and forming a second flexible array of microelectrodes adapted to conform to tissue; wherein the second flexible framework is configured to facilitate relative movement among at least some of the microelectrodes in the second plurality of microelectrodes relative to other of the microelectrodes in the second plurality of microelectrodes; and wherein the nonconductive material insulates each microelectrodes in the second plurality of microelectrodes from other microelectrodes in the second plurality of microelectrodes; and (iv) an ablation region located between the first flexible framework and the second flexible framework.

[0012] In still another embodiment, a delivery adapter comprises a body that comprises a dilator support pocket, an internal compression cone, and a guide sheath connector. The delivery adapter body may be separable or splittable into a first portion and a second portion.

[0013] The foregoing and other aspects, features, details, utilities, and advantages of the present disclosure will be apparent from reading the following description and claims, and from reviewing the accompanying drawings.

BRIEF DESCRIPTION OF THE DRAWINGS

[0014] FIG. 1 is a fragmentary, isometric view of a high-density mapping catheter according to a first embodiment.

[0015] FIG. 2 is an isometric, fragmentary view of the catheter shown in FIG. 1 depicted in a flexed configuration, representing contact between the catheter tip and cardiac tissue.

[0016] FIG. 3 is a fragmentary view of the flat pattern design of an electrode carrier band (or ‘carrier band’) according to the first embodiment shown in FIGS. 1 and 2.

[0017] FIG. 4 is a fragmentary, isometric view of a high-density mapping catheter according to a second embodiment.

[0018] FIG. 5 is a fragmentary, isometric view of the catheter depicted in FIG. 4 shown in a flexed configuration, representing contact between the catheter tip and cardiac tissue.

[0019] FIG. 6 is a fragmentary, isometric view of a catheter ablation tip having distal high-density mapping electrodes according to a third embodiment.

[0020] FIG. 7 is an enlarged, fragmentary view of the circled portion of FIG. 6.

[0021] FIG. 8 is a fragmentary, isometric view of an ablation and high-density mapping catheter tip according to a fourth embodiment.

[0022] FIG. 9 is a fragmentary, isometric view of the catheter tip depicted in FIG. 8 shown in a partially-flexed or bent configuration, simulating contact between the catheter tip and cardiac tissue.

[0023] FIG. 10 is a fragmentary, isometric view of a catheter tip of a high-density mapping catheter according to a fifth embodiment.

[0024] FIG. 11 is a fragmentary, side view of the catheter tip depicted in FIG. 10.

[0025] FIG. 12 is a flat pattern design of the materials forming a portion of the catheter tip depicted in FIGS. 10 and 11, clearly showing alternating electrode-carrier bands (or ‘carrier bands’) separated by a plurality of linking bands.

[0026] FIG. 13 depicts an isolated pad structure from a carrier band depicted in FIG. 12 and shows the bowtie or hourglass configuration, including a microelectrode mounting aperture.

[0027] FIG. 14 depicts two pad structures from one of the carrier bands depicted in FIG. 12 including a circumferential connector extending between the pad structures.

[0028] FIG. 15 is a fragmentary view of the distal end of the catheter depicted in, for example, FIGS. 10 and 11, with portions of the catheter removed to reveal internal structures.

[0029] FIG. 16 is similar to FIG. 15, revealing additional internal structures of the catheter tip depicted in, for example, FIGS. 10, 11, and 15.

[0030] FIG. 17 is a fragmentary view of the tip portion of a high-density mapping catheter according to a sixth embodiment, before the microelectrodes (or ‘button electrodes’) are mounted.

[0031] FIG. 18 is similar to FIG. 12, but depicts the flat pattern design used to create the catheter tip depicted in FIG. 17, including electrode-carrier bands (or ‘carrier bands’), and linking bands that are slightly different from the corresponding structures depicted in FIG. 12.

[0032] FIG. 19 is similar to FIG. 14, but depicts the pad structures according to the sixth embodiment, including inter-band bridges.

[0033] FIG. 20 is a fragmentary view of one tab structure from a linking band depicted in, for example, FIG. 18.

[0034] FIG. 21 depicts two tab structures comprising part of a linking band depicted in FIG. 18, including a tab-structure connector extending between the depicted adjacent tab structures.

[0035] FIG. 22 depicts a single linking band (on the left) inter-connected with a single carrier band (on the right) of the design depicted in FIG. 18.

[0036] FIG. 23 is a fragmentary, isometric view of the tip of a high-density mapping catheter according to the sixth embodiment, shown with the thirty-two microelectrodes mounted in the electrode apertures depicted in FIG. 17.

[0037] FIG. 24 is an isometric view of the catheter tip depicted in FIG. 23, but shown in a flexed configuration, simulating contact between the catheter tip and a cardiac wall.

[0038] FIG. 25 depicts an entire high-density mapping catheter according to the sixth embodiment, including an electrical connector and a control handle toward the proximal end of the catheter.

[0039] FIG. 26 is similar to FIGS. 23 and 24, and shows an enlarged view of the circled portion of FIG. 25.

[0040] FIG. 27 is a fragmentary, isometric view of the tip portion of a high-density mapping catheter according to a seventh embodiment.

[0041] FIG. 28 depicts the distal tip of a high-density mapping catheter according to an eighth embodiment, and includes multiple ring electrodes adjacent to a flexible array of microelectrodes.

[0042] FIG. 29 is a fragmentary, isometric view of the tip portion of a map-and-ablate catheter according to a ninth embodiment, including a flexible array of microelectrodes for mapping and a flexible ablation tip located distal of the flexible array of microelectrodes.

[0043] FIG. 30 depicts the catheter tip of FIG. 29 in a partially-flexed configuration, simulating contact between the ablation tip and cardiac tissue.

[0044] FIG. 31 depicts the tip portion of a map-and-ablate catheter according to a tenth embodiment, including an ablation section straddled by flexible arrays of microelectrodes, and further including two ring electrodes.

[0045] FIG. 32 is another view of the catheter tip depicted in FIG. 31.

[0046] FIG. 33 is a fragmentary, isometric view depicting the tip portion of a high-density mapping catheter according to an eleventh embodiment.

[0047] FIG. 34 is a plan view of the catheter tip depicted in FIG. 33.

[0048] FIG. 35 is an elevational view of the catheter tip depicted in FIGS. 33 and 34.

[0049] FIG. 36 is a fragmentary, isometric view of the catheter tip depicted in FIGS. 33-35, showing a flexible array of electrodes in a slightly-flexed configuration, simulating contact between the array of electrodes and a cardiac wall.

[0050] FIG. 37 depicts the catheter shown in FIGS. 33-36 with the array of electrodes riding against trabeculated tissue.

[0051] FIG. 38 depicts the distal tip of a high-density mapping catheter according to a twelfth embodiment.

[0052] FIG. 39 depicts the distal portion of the high-density mapping catheter also shown in FIG. 38, but overlying vasculature.

[0053] FIG. 40 depicts a tip portion of a high-density mapping catheter according to a thirteenth embodiment.

[0054] FIG. 41 depicts the distal portion of the high-density mapping catheter also shown in FIG. 40, but overlying vasculature.

[0055] FIG. 42 is an isometric view of a high-density mapping catheter similar to that shown in FIGS. 40 and 41, but also comprising two tethers.

[0056] FIG. 43 depicts the distal tip of a high-density mapping catheter according to a fourteenth embodiment.

[0057] FIG. 44 depicts a high-density mapping catheter most similar to the catheter depicted in FIG. 43, but also comprising an irrigation port near a distal edge of a proximal bushing.

[0058] FIG. 45 is an enlarged, fragmentary view of a portion of the high-density mapping catheter depicted in FIG. 44, clearly showing the irrigation port.

[0059] FIG. 46 is an enlarged, isometric view of an embodiment of a high-density mapping catheter comprising a location sensor mounted in the catheter shaft proximal to a proximal bushing.

[0060] FIG. 47 is an exploded, isometric view of a delivery adapter and a guiding sheath.

[0061] FIGS. 48A-48F depict a series of views showing how a delivery adapter such as the one depicted in FIG. 47 may be used with a dilator for delivering a paddle catheter into a guiding sheath.

DETAILED DESCRIPTION OF EMBODIMENTS

[0062] Several embodiments of flexible, high-density mapping catheters and map-ablate catheters are disclosed herein. In general, the tip portions of these various catheters comprise an underlying support framework that is adapted to conform to and remain in contact with tissue (e.g., a beating heart wall). Details of the various embodiments of the present disclosure are described below with specific reference to the figures.

[0063] FIGS. 1 and 2 depict, and FIG. 3 relates to, a tip portion 10^d of a high-density mapping catheter according to a first embodiment. As shown in FIG. 1, the tip portion 10^d includes interlocking rings or bands 12 of nonconductive material (e.g., polyether-etherketone or PEEK) forming the underlying support framework for a plurality of microelectrodes. In this embodiment, a circumferential or helical through-cut pattern 14 defines a plurality of dovetail surfaces 16. Each dovetail surface has a microelectrode 18 attached to it, thereby defining a flexible array of microelectrodes that are arranged in circumferential rings or bands. The electrodes 18 are also aligned in longitudinally-extending (e.g., parallel to a catheter longitudinal axis 20) rows of electrodes that are able to flex or move slightly relative to each other during use of the catheter. The nonconductive material individually insulates each microelectrode.

[0064] The nonconductive substrate on which the button electrodes 18 are mounted may comprise PEEK. The tip 10^d includes a radiopaque tip cap 22 that facilitates fluoroscopy visualization. The tip cap may be domed shaped, hemispherical, flat-topped, tapered, or any other desired general shape.

[0065] In this embodiment of the tip portion 10A, there are sixty-four discrete microelectrodes 18, and a separate lead (shown in, for example, FIGS. 15 and 16) wire extends to each of these electrodes from the proximal end of the catheter. In a preferred version of this catheter, the catheter is either 7 F or 7.5 F. The flexible tip helps to facilitate and ensure stability during, for example, cardiac motion, which in turn makes it possible to accurately map cardiac electrical activity because of the sustained electrode contact that is possible. The circumferential or helical cuts 14, which may

be formed by a laser, create a plurality of serpentine gaps that permit the tip to flex as the cardiac wall moves in a beating heart. When a plurality of circumferential through-cuts are used, this creates a plurality of dovetailed (or 'saw-toothed') bands 12. FIG. 3 depicts the flat-pattern design for one of these bands 12 according to the first embodiment. As clearly shown in FIG. 3, the pattern includes a circumferential waistline or ring 24 defined between a circumferentially-extending proximal edge 26 and a circumferentially-extending distal edge 28. Each of these edges is interrupted by a plurality of proximally-extending pads 30 or distally-extending pads 32. Each pad in this embodiment has the shape of a truncated isosceles triangle with sides S and a base B. Two adjacent proximally-extending pads define a proximally-opening pocket 34 between them. Similarly, on the opposite side of the circumferential waistline 24, two distally-extending pads 32 that are adjacent to each other define a distally-opening pocket 36.

[0066] As may be clearly seen in FIGS. 1 and 2, when two of these dovetailed bands are connected, each distally-extending pad 32 flexibly interlocks in a proximally-opening dovetailed pocket 34, and each proximally-extending pad 30 flexibly interlocks in a distally-opening dovetail pocket 36. It is also shown in FIG. 3, each pad 30, 32, in this embodiment, includes an aperture 38 in which a microelectrode will be mounted. Each aperture extends through a pad, from a pad outer surface to a pad inner surface.

[0067] Rather than having circumferential through-cuts 14, which define a plurality of individual electrode-carrier bands, the flexible tip depicted in FIGS. 1 and 2 could be formed by a continuous helical cut.

[0068] FIGS. 4 and 5 are similar to FIGS. 1 and 2, respectively, but depict a tip portion 10^B of a high-density mapping catheter according to a second embodiment. In this embodiment, circumferential through-cuts 40 define a plurality of discs 42 on which microelectrodes 18 are mounted. Alternatively, a helical cut could be used to form the flexible tip configuration shown in FIGS. 4 and 5. As with the embodiment shown in FIGS. 1 and 2, in the embodiment depicted in FIGS. 4 and 5, the microelectrodes 18 are mounted in a nonconductive material such as PEEK.

[0069] A third embodiment of a tip portion 10^C is depicted in FIGS. 6 and 7. In this embodiment, however, unlike the embodiment 10^A shown in FIGS. 1 and 2, the interlocking, dovetailed pattern is formed from conductive material since this is an ablation tip. As shown to best advantage in FIG. 7, the distal end 44 of this flexible ablation tip includes a pair of symmetrically-placed, high-density microelectrodes 46 for mapping. As also shown to best advantage in FIG. 7, this configuration includes two front-facing irrigation ports 48, and a thermocouple or a temperature sensor 50. The mapping electrodes 46 are mounted in a nonconductive insert 52 to electrically insulate these mapping electrodes from the remainder of the ablation tip. In this particular configuration, the flexible ablation tip is 4 millimeters long. It should also be noted that, in this embodiment, the pads and pockets defined by the serpentine cuts 54 are smaller than the corresponding pads and pockets depicted in, for example, FIGS. 1 and 2. In this ablation tip embodiment 10^C, the individual pads 56 do not carry microelectrodes and, therefore, the pads can be smaller in this configuration of the ablation tip than they are in the high-density mapping tips.

[0070] FIGS. 8 and 9 depict an ablation tip portion 10^D and high-density mapping electrode according to a fourth embodiment. This embodiment is a 7.5 Fr catheter having a 4.0 millimeters long, flexible ablation electrode manufactured from, for example, platinum. In this design, four high-density mapping electrodes 58 are mounted through the distal pads 60 of pad structures. Also, each pad structure includes a larger distal pad and a smaller proximal pad 62; and each microelectrode 58 is mounted through an aperture 64 extending through a distal pad 60. In this configuration 10^D, two carrier bands are interconnected by a linking band 66, a most-proximal carrier band 62 is connected with the distal end 68 of the catheter shaft 70, and a most-distal carrier band is connected to an end cap 72. In this embodiment, each of the four mapping electrodes is individually insulated and has its own lead wire (shown in, for example, FIGS. 5 and 6) extending from the electrode 58 out the proximal end of the catheter. Similar to what occurs in each of the embodiments already discussed, this is an irrigated configuration. Thus, during use of the catheter, irrigant (e.g., cooled saline) is routed from the proximal end of the catheter, through the catheter shaft, and out of the serpentine gaps formed in the tip.

[0071] FIGS. 10-16 provide details concerning the tip portion 10^E of a high-density mapping catheter according to a fifth embodiment. As shown to good advantage in FIG. 11, this catheter tip 10^E gets its flexibility from a plurality of circumferential, dovetail cuts that define a plurality of serpentine gaps 74 between alternating electrode-carrier bands (or carrier bands) 76 and linking bands 78. The working portion of the embodiment 10^E depicted in FIG. 11 is approximately 20 millimeters long (see dimension L in FIGS. 11 and 12) and has a diameter of 7 Fr to 7.5 Fr (see dimension D in FIG. 11). In this embodiment, the longitudinal electrode spacing between adjacent microelectrode (see dimension S_L in FIGS. 11 and 12) is approximately 1.8 millimeters, and the circumferential electrode spacing between adjacent microelectrode (see dimension S_C in FIG. 12) is also approximately 1.8 millimeters. An end cap 104 may also be present as shown in, for example, FIGS. 10 and 11.

[0072] As shown to good advantage in FIG. 12, the fifth embodiment 10^E shows a plurality of electrode-carrier bands 76 separated by a plurality of linking bands 78. Thus, there is one linking band between directly adjacent pairs of carrier bands. In this configuration, each carrier band includes a plurality of bowtie-shaped or hourglass-shaped structures 80 (see for example, FIGS. 13 and 14). Further, in this configuration, each of these bowtie-shaped structures 80 comprises a distal pad 82 and a proximal pad 84, separated by a narrowed region or waist 86. In this configuration, each distal pad 82 of each carrier band 76 has an electrode-mounting aperture 88 (e.g., 0.9 mm diameter) through it.

[0073] Further, as shown to best advantage in FIGS. 12 and 14, there is a circumferential connector 90 between each pair of adjacent pad structures. The circumferential connectors 90, along with the waist 86 of each pad structure 80, together define a circumferential ring. In this embodiment, the bowtie-shaped or hourglass-shaped pad structures 80 are essentially symmetrical about the waist 86 except for the existence of an electrode-mounting aperture 88 in each of the distal pads 82.

[0074] As shown in FIG. 14, a distally-opening slot 92 is present between adjacent, distally-extending pads 82. Simi-

larly, a proximally-opening slot **94** is present between adjacent, proximally-extending pads **84**. Looking at a single electrode-carrier band, the circumferentially-extending pad connectors **90**, together with the waists **86** of each pad structure **80**, define a carrier band waistline that extends around the circumference of the tip portion 10^E of the catheter.

[0075] In this configuration, as shown in FIG. 12, each linking band **78** also comprises a connected series of bowtie-shaped structures **96**. In this particular embodiment, the bowtie-shaped pad structures **96** of the linking bands **78** are larger than the bowtie-shaped pad structures **80** of the carrier bands **76**.

[0076] FIGS. 15 and 16 are views with portions of the catheter removed to show inner details of the catheter tip portion of 10^E . In FIG. 15, it is possible to see the individual lead wires **98** extending longitudinally through the catheter shaft and connecting with each of the microelectrodes **18**. It is also possible to see an internal spring **100** in this figure. This spring helps the tip portion 10^E of the catheter maintain its flexibility, and it helps create the gaps between adjacent carrier bands **76** and linking bands **78**. FIG. 16 depicts an internal irrigation lumen **102** that acts as an irrigant distribution manifold.

[0077] The button electrodes or microelectrodes **18** may have a diameter between 0.7 and 0.9 millimeters. The lead wires extending through the catheter shaft to each of these electrodes may comprise 38 AWG wire. As previously described in connection with other embodiments, an end cap **104** may be metallic, or otherwise radiopaque, to facilitate visualization of the catheter tip during use of a fluoroscope.

[0078] FIGS. 17-26 depict aspects of a sixth embodiment of a tip portion 10^F . FIG. 17 depicts a cylindrical-shaped portion **106** of nonconductive material that has been laser cut to define an interlocking, but flexible pattern **108** (see FIG. 18). FIG. 18 shows what that pattern **108** looks like when it is laid out flat rather than having the cylindrical shape depicted in FIG. 17.

[0079] In this embodiment, a plurality of electrode-carrier bands (or carrier bands) **110** and a plurality of linking bands **112** are present. FIG. 19 is similar to FIG. 14, but shows adjacent pad structures **113** according to the sixth embodiment, as also shown in FIGS. 17 and 18. In this configuration, the carrier bands **110** are not completely separate from the adjacent linking bands **112**. In particular, as may be clearly seen in FIGS. 17 and 18, this embodiment includes a plurality of inter-band bridges or connectors **114**. All of the bands **110**, **112** are thereby loosely interconnected, and one band cannot move completely independently of any other band comprising the working portion of the high-density mapping catheter tip 10^F .

[0080] As also clearly shown in FIGS. 17-19, in this embodiment, each pad structure **113** is not the symmetrical bowtie-shaped structure **80** depicted in, for example, FIG. 12. Rather, in the sixth embodiment, the distal tabs **116** of each pad structure **113** are larger than the corresponding proximal pads **118** of the pad structure **113**. The electrode apertures **120** extend through this larger distal pad **116**.

[0081] As shown to good advantage in FIG. 19, slots are formed between adjacent pad structures **113**. In particular, a relatively shallow, proximally-opening tab slot **122** is formed between adjacent proximal pads **118**. Similarly, a relatively deep, distally-opening tab slot **124** is formed between adjacent pairs of distal pads **116**. As described

above with reference to FIG. 14, circumferentially-extending connectors **126** are again present between adjacent pad structures **113**. All of these connectors on a single carrier band **110**, together with the waists **128** of each pad structure comprising part of that same carrier band, form a carrier band waistline.

[0082] FIG. 20 depicts a tab structure **130** from a linking band **112**. Each linking band comprises a plurality of these tab structures. Each tab structure includes a relatively-longer, proximally-extending tab (or 'proximal tab') **132** in a relatively-shorter, distally-extending tab (or 'distal tab') **134**. FIG. 21 depicts two adjacent tab structures **130** of a single linking band **112**. A proximally-opening pocket **136** is defined between adjacent proximal tabs **134**. Similarly, a distally-opening pocket is defined between adjacent distal tabs. A circumferentially-extending, tab-structure connector **140** connects adjacent tab structures **130** and helps to form the proximally-opening pocket **136** and a distally-opening pocket **138**. In other words, each linking band **112** includes a circumferentially-extending proximal edge **142** and a circumferentially-extending distal edge **144**. The proximal edge defines a series of proximally-extending tabs **132** and proximally-opening pockets **136**, and the distal edge **144** of each linking band **112** forms a plurality of distally-extending tabs and distally-opening pockets **138**.

[0083] FIG. 22 also relates to the sixth embodiment. In particular, FIG. 22 depicts a single linking band **112** (on the left) flexibly interlocked with a single carrier band **110** (on the right). As shown, each proximally-extending tab **132** is flexibly interlocked in a corresponding distally-opening slot **124** in a carrier band **110**. Similarly, each distally-extending pad **116** of the carrier band is flexibly interlocked in a corresponding proximally-opening pocket **136** in the linking band **112**.

[0084] Each tab structure of the linking band is an asymmetrical bowtie configuration. Similarly, each pad structure **113** of the carrier band **110** is also an asymmetrical bowtie configuration. The serpentine gap extending between the linking band **112** and the carrier band **110** (e.g., a laser cut gap) defines the tabs and the pockets of the linking band, and define the complementary pads and slots, respectively, of the carrier bands.

[0085] FIG. 23 depicts a fully-assembled tip portion 10^F of a high-density mapping catheter according to the sixth embodiment. The fully assembled tip includes a most-proximal band (or shaft-transition band) **146**, and a most-distal band (or end-cap-transition band) **148**. An end cap **150** may be platinum or some other radiopaque material to facilitate visualization on a fluoroscopy screen. As may be seen in FIG. 23, the button electrodes or microelectrodes **18** are slightly raised off the outer surface of the laser cut PEEK material. This is also clearly visible in FIG. 24, which shows the catheter tip in a slightly-flexed configuration. With the electrodes raised slightly as shown, better electrical contact can be maintained between the electrodes and the tissue. In the embodiment depicted in FIGS. 17-26, there are thirty-two mapping electrodes **18** mounted in the laser-cut PEEK material. In this particular design, the catheter shaft is 7 Fr or 7.5 Fr.

[0086] FIGS. 25 and 26 also depict the sixth embodiment. In particular, FIG. 25 shows an entire catheter **152**, including an electrical connector **154** and a control handle **156** near the proximal portion of the catheter and a flexible high-density

mapping tip 10^E at the distal end of the catheter **152**. FIG. **26** is an enlarged view of the circled portion of FIG. **25**.

[0087] FIG. **27** depicts the distal tip portion 10^G of a high-density mapping catheter according to a seventh embodiment. Similar to some of the configurations discussed above, this tip portion includes a metallic cap (e.g., a platinum cap) **158** or otherwise radiopaque cap to facilitate visualization on fluoroscopy. This specific embodiment 10^G is different from the embodiment 10^F depicted, for example, in FIG. **23**, since the electrode apertures **160** in this embodiment are located through the distal pads **162** of pad structures of electrode carrier bands **164** that are relatively smaller than the tab structures of the linking bands **166**. In this seventh embodiment, each electrode-carrier band **164** includes a plurality of bowtie-shaped pad structures that are circumferentially arranged around the longitudinal axis of the catheter. Similarly, each linking band **166** comprises a plurality of bowtie-shaped tab structures also arranged circumferentially around the catheter longitudinal axis. In this particular configuration of the tip portion 10^G , however, the bowtie-shaped tab structures are relatively larger than the bowtie-shaped pad structures of the electrode-carrier bands **164**. By changing the relative size of the distal and proximal tabs, and the relative size of the corresponding or related distal and proximal pads, the performance characteristics of the tip portion of the high-density mapping catheter can be adjusted.

[0088] FIG. **28** depicts an eighth embodiment of a high-density mapping tip portion 10^H . In this embodiment, a 7 Fr catheter includes a flexible array of microelectrodes **18** that is similar to, but shorter than, the flexible array of microelectrodes depicted in, for example, FIGS. **23-26**. In this particular design, however, 1.0 mm ring electrodes **168**, **170**, **172** are located at each longitudinal end of the flexible array of 0.9 mm diameter microelectrodes **18**. In the depicted embodiment, the most-proximal circumferential ring of microelectrodes **18** is located approximately 1.2 mm (see dimension S_R in FIG. **28**) from the most-proximal circumferential edge **171** of array. As shown, there are six microelectrodes arranged in four longitudinally-extending rows of four electrodes, each row radially offset from the next row by 90° . The longitudinal spacing between adjacent microelectrodes may be, for example, 1.8 mm. There are two ring electrodes **168**, **170** spaced 1.0 mm from each other and located proximal to the most-proximal circumferential edge **171** of the flexible array of microelectrodes. There is a third 1.0 mm ring electrode **172** located distal of the most-distal edge **173** of the flexible array of microelectrodes. In this particular configuration, there is also a 1.0 mm long metal tip **174** that could be used as an additional electrode.

[0089] FIGS. **29** and **30** depict the distal portion 10^I of a map-and-ablate catheter according to a ninth embodiment. Similar to what is shown in FIG. **28**, the ninth embodiment shown in FIGS. **29** and **30** includes a flexible array of microelectrodes **18** comprising sixteen microelectrodes arranged in four longitudinally extending rows of four where each of these rows is radially offset by 90° from the next adjacent row of electrodes. In this embodiment, however, the most-distal end of the catheter comprises a flexible ablation tip **176**. This ablation tip may be, for example, a Cool Flex™ ablation tip sold by St. Jude Medical, Inc. of St. Paul, Minn. During use, irrigant would flow down the catheter shaft and exit through the serpentine gaps in the flexible array of microelectrodes and through the openings

in the flexible ablation tip. This tip would advantageously conform to the cardiac tissue during both mapping and ablation procedures.

[0090] FIGS. **31** and **32** depict a tip portion 10^J of a map-and-ablate catheter according to a tenth embodiment. Moving distally down the catheter shaft toward the most-distal end, two 1.0 mm ring electrodes are encountered, including a most-proximal ring **170** electrode and a most-distal ring electrode **168**. Next, a proximal short flexible array **178** of eight 0.9 mm diameter microelectrodes, mounted in four rows of two microelectrodes, is encountered. In this embodiment, these microelectrodes project from the outer surface of the catheter approximately 0.18 mm and are longitudinally spaced from each other by approximately 1.8 mm. Connected to the distal-side of this short flexible array of microelectrodes is an ablation region **180** that is approximately 3.5 mm long and that includes a plurality of irrigation holes **182**. Distal of the ablation region is another, rather short flexible array **184** of microelectrodes. In this particular configuration, the distal flexible array **184** of microelectrodes is similar to the proximal, flexible array **178** of microelectrodes. Finally, in this map ablate catheter, the distal end includes a metallic cap **186** that may be used for mapping, ablation, and/or visualization on fluoroscopy.

[0091] FIGS. **33-37** depict a tip portion 10^K comprising a flexible array of microelectrodes according to an eleventh embodiment. This planar array (or 'paddle' configuration) of microelectrodes comprises four side-by-side, longitudinally-extending arms **188**, **190**, **192**, **194** forming the flexible framework on which the thirty-two 1.0 mm long \times 0.8 mm diameter ring electrodes **196** are carried. As discussed further below, a few of these ring electrodes (see, for example, rings **198** and **200** in FIG. **33**) may be slightly longer. The four ring-electrode-carrier arms comprise a first outboard arm **188**, a second outboard arm **190**, a first inboard arm **192**, and a second inboard arm **194**. These arms are laterally separated from each other by approximately 3.3 mm in this embodiment. Each of the four arms carries eight small ring electrodes **196**, spaced along its length. In the depicted embodiment, these small ring-shaped microelectrodes are longitudinally separated from each other by approximately 1.0 mm. Although each of the paddle catheters depicted in FIGS. **33-42** shows four arms, the paddle could comprise more or fewer arms.

[0092] FIG. **33** is an isometric, fragmentary view of the planar array. As shown to best advantage in FIG. **34**, the most-distal ring electrode on the first outboard arm **188** is slightly enlarged as is the most-proximal ring electrode **220** on the second outboard arm **190**. These slightly enlarged electrodes **198**, **200** (e.g., in the depicted embodiment, these microelectrodes are slightly longer than the other ring electrodes) can be used, for example, for more precise localization of the flexible array in mapping and navigation systems. It is also possible to drive ablation current between these enlarged electrodes, if desired, for bipolar ablation, or, alternatively to drive ablation current in unipolar mode between one or both of these enlarged ring electrodes and, for example a patch electrode located on a patient (e.g., on the patient's back). Similarly, the microelectrodes **196** (on this or any of the other paddle catheters) can be used to perform unipolar or bipolar ablation. Alternatively or concurrently, current could travel between one or more of the enlarged electrodes and any one or all of the microelectrodes. This unipolar or bipolar ablation can create specific

lines or patterns of lesions. As also may be seen in FIG. 34, there may be a distal member (or 'button') 202 where one or more of the arms come together. This distal member may be constructed from metal or some other radiopaque material to provide fluoroscopy visualization and semi-independent planar movement between the outer and inner arms.

[0093] As shown to best advantage in FIG. 37, the planar, flexible arms conform to trabeculated tissue 204, enabling a physician to maintain contact between several of the electrodes and the tissue. This enhances the accuracy, and the corresponding diagnostic value, of the recorded information concerning the heart's electrical activity.

[0094] FIGS. 38 and 39 depict a flexible array of microelectrodes at the tip portion 10^L of a high-density mapping catheter according to a twelfth embodiment. In this configuration, there are four 1.0 mm ring electrodes (depicted with a 2.0 mm longitudinal spacing) mounted on the distal end of the catheter shaft, proximal to a proximal bushing 206 and to the proximal ends of ring electrode carrier arms 188', 190', 192', 194'. In this embodiment, each of the four electrode carrying arms has eight small ring electrodes 196 (microelectrodes) mounted on it. The four arms are designed to maintain the thirty-two small ring electrodes in a spaced relationship so that each small ring electrode can capture separate data about the electrical activity of the cardiac tissue adjacent to the microelectrodes.

[0095] FIGS. 40-42 depict two variations 10^M, 10^N of a similar tip portion comprising a flexible array of microelectrodes 196'. In both variations of this particular configuration, there are sixteen small ring electrodes 196' mounted on four small arms 188", 190", 192", 194" rather than the thirty-two ring electrodes 196 depicted in FIGS. 38 and 39. These small ring electrodes (1.0 mm long×0.8 mm diameter) are longitudinally separated from each other by approximately 3.0 mm in this embodiment, and the electrode carrying arms are laterally separated from each other by approximately 4.0 mm. Further, in the variation 10^N depicted in FIG. 42, the high-density mapping catheter also includes two tethers 210 extending transverse across and interconnecting the four electrode carrying arms. Although two tethers are shown in FIG. 42, any number of tethers could be used, including a single tether. The tether or tethers 210 help maintain a predictable relationship between the electrode carrying arms 188", 190", 192", 194" by controlling, for example, how each electrode carrying arm may move relative to the other electrode carrying arms. Each tether 210 may comprise a tensile element, such as slender mono- or multi-filament nylon thread or suture-like material. The tethers may be connected with or to the electrode carrying arm in a variety of ways. In FIG. 42, for example, the tethers 210 have been adhered or ultrasonically welded to each of the electrode carrying arms 188", 190", 192", 194". Alternatively, a tether could be tied to or looped around the arms. Reflowing the device during the manufacturing process may allow the tether or tethers to become incorporated into the arms polymer insulation, thereby securing the tether to the arms and minimizing the need for tying, looping, gluing, or otherwise attaching the tethers to the arms. The tethers 210 are configured to also collapse or fold during insertion of the catheter into a delivery sheath or introducer.

[0096] FIG. 43 depicts yet another embodiment of a tip portion 10^O comprising a flexible array of microelectrodes. This configuration is most similar to the first variation 10^M of the thirteenth embodiment, which is depicted in FIGS. 40

and 41. However, in the fourteenth embodiment, there are two additional ring electrodes 212 mounted near the distal end of each outboard arm.

[0097] FIG. 44 depicts an alternative variation of the high-density mapping catheter embodiment 108 depicted in FIG. 43. In particular, in FIG. 44, an irrigation port 214 is present at the distal end of a proximal bushing 206', and the irrigation port is positioned to deliver irrigant to or near the point where the electrode carrying arms exit from the distal end of the proximal bushing that is mounted on the distal end of the catheter shaft in this embodiment. If desired, a second irrigation port (not shown) may be located near the distal intersection of the electrode carrying arms. In fact, if desired, multiple irrigation ports (not shown) could be present at various positions along the electrode carrying arms 188", 190", 192", 194". FIG. 45 is an enlarged, fragmentary view of the irrigation port 214 on the proximal bushing 206'. Further, while only one irrigation port 214 is illustrated on the proximal bushing 206', multiple irrigation ports could be present on the proximal bushing (e.g., one or more on each side of the planar array of microelectrodes) to provide more uniform irrigant distribution at or near the proximal apex of the arms 188", 190", 192", 194". Likewise, a distal irrigation port set (not shown) comprising multiple ports could be included at or near the distal apex of the arms 188", 190", 192", 194".

[0098] FIG. 46 is a fragmentary, isometric view of the distal portion of the catheter shaft of a high-density mapping catheter. In this view, portions of the catheter shaft have been removed to reveal a sensor 216 located just proximal to the proximal bushing. A variety of sensors may be incorporated at this location, or at similar locations, in the high-density mapping catheters described herein. These sensors may be mounted in the catheter shaft, as shown in FIG. 46, or they may be mounted at other locations (e.g., along the electrode carrying arms of the high-density mapping paddle and/or at the distal apex or joint of the tip portion). In one embodiment, the sensor 216 is a magnetic field sensor configured for use with an electromagnetic localization system such as the MediGuide™ System sold by St. Jude Medical, Inc. of St. Paul, Minn.

[0099] FIG. 47 is an exploded, isometric view of one embodiment of a delivery adapter 218 designed to facilitate delivery of a paddle catheter into and through a guiding sheath or introducer 220 having a circular cross section. As depicted in this figure, the delivery adapter 218 comprises a first portion 218A having pins 222 extending therefrom, and a second portion 218B having complementary pin-receiving holes 224 therein. When these portions 218A, 218B are assembled, a proximal pocket configured to support or hold the distal end of a dilator hub 228 (labeled in FIGS. 48A and 48B) is formed. In particular, the first portion 218A of the delivery adapter includes a first part 226A of that pocket, and the second portion 218B of the delivery adapter comprises a second part 226B of the pocket. In this particular embodiment, a dilator shaft channel is also present and comprises a first trough 230A formed in the first portion 218A of the delivery adapter 218 and a second trough 230B formed in the second portion 218B of the delivery adapter 218. Also, the distal side of the delivery adapter, in this embodiment, comprises a threaded hole (e.g., a female luer lock) 232A, 232B adapted to thread onto a shaft or fitting (e.g., a male luer lock) 234 extending proximally from the proximal end of the guiding sheath 220.

[0100] As best seen in FIG. 47, the interior of the delivery adapter, between the proximal pocket 226A, 226B and the threaded hole 232A, 232B defines a hollow compression or folding cone 236A, 236B. In one embodiment, for example, the lateral cross-sectional shape of the proximal end of this compression cone is elliptical or nearly elliptical, and the lateral cross-sectional shape of the distal-most portion of the compression cone is circular or near circular, matching the channel through a hub 238 of the guiding sheath 220. The compression cone is thereby configured or adapted to compress the relatively flat paddle of the high-density mapping catheter into a configuration having a substantially circular cross-sectional shape or other shape that fits into the proximal opening in the guiding sheath hub 238. It should also be noted that the delivery adapter may be splittable for easy removal when used with a splittable guiding sheath.

[0101] Referring now most specifically to the various views comprising FIGS. 48A-48F, one use of the delivery adapter 218 just described in connection with FIG. 47 is described next. In this use, a dilator 240 is inserted into and through the delivery adapter 218 and seated in the pocket 226A, 226B formed in the proximal side of the assembled delivery adapter. The assembled delivery adapter 218, with the dilator 240 in place, is then mounted to the guiding sheath 220 as shown in FIG. 48A. The dilator 240, shown by itself in FIG. 48B, is then removed from the delivery adapter 218 and guiding sheath 220, as may be seen in the left-hand portion of FIG. 48C.

[0102] Next, as also shown in view FIG. 48C, the paddle 242 of a high-density mapping catheter is inserted into the proximal end of the compression cone 236A, 236B of the delivery adapter. In FIG. 48D, the electrode carrying arms of the paddle have been inserted further into the compression cone. As the electrode carrying arms of the panel impact the angled side surfaces of the compression cone formed in the delivery adapter 218, the electrode carrying arms are compressed towards each other. When the arms have been sufficiently compressed together (i.e., into a side-by-side, touching or near-touching configuration), the paddle then fits into the proximal end of the port through the guiding sheath or introducer 220 and may be pushed through the hemostasis valve (not shown) in the hub 238 at the proximal end of the guiding sheath 220. As shown in FIG. 48E, as the paddle portion 242 of the high-density mapping catheter exits from the distal end of the guiding sheath 220, the electrode carrying arms comprising the paddle remain compressed together. Once the electrode carrying arms of the paddle exit from the distal end of the shaft or tube of the guiding sheath, the electrode carrying arms expand back into the paddle configuration, as best shown in FIG. 48F.

[0103] In each of the embodiments depicted in, for example, FIGS. 33-46, one or more of the ring electrodes 208 could be used to send pacing signals to, for example, cardiac tissue. Further, the arms (or the understructure of the arms) comprising the paddle structure (or multi-arm, electrode-carrying, flexible framework) at the distal end of the catheters depicted in FIGS. 33-46 are preferably constructed from a flexible or spring-like material such as Nitinol. The construction (including, for example, the length and/or diameter of the arms) and material of the arms can be adjusted or tailored to be created, for example, desired resiliency, flexibility, foldability, conformability, and stiffness characteristics, including one or more characteristics that may vary from the proximal end of a single arm to the

distal end of that arm, or between or among the plurality of arms comprising a single paddle structure. The foldability of materials such as Nitinol provide the additional advantage of facilitating insertion of the paddle structure into a delivery catheter or introducer, whether during delivery of the catheter into the body or removal of the catheter from the body at the end of a procedure. Although a short guide sheath 220 (used, for example, for epicardial access) is depicted in FIGS. 47 and 48A-48F, a longer guide sheath (used, for example, to access the heart from a femoral access point) could be used to introduce the flexible high-density mapping and ablation tips described herein.

[0104] Among other things, the disclosed catheters, with their plurality of microelectrodes, are useful to (1) define regional propagation maps on one centimeter square areas within the atrial walls of the heart; (2) identify complex fractionated atrial electrograms for ablation; (3) identify localized, focal potentials between the microelectrodes for higher electrogram resolution; and/or (4) more precisely target areas for ablation. These mapping catheters and ablation catheters are constructed to conform to, and remain in contact with, cardiac tissue despite potentially erratic cardiac motion. Such enhanced stability of the catheter on a heart wall during cardiac motion provides more accurate mapping and ablation due to sustained tissue-electrode contact. Additionally, the catheters described herein may be useful for epicardial and/or endocardial use. For example, the planar array embodiments depicted in FIGS. 33-48F may be used in an epicardial procedure where the planar array of microelectrodes is positioned between the myocardial surface and the pericardium. Alternatively the planar array embodiments may be used in an endocardial procedure to quickly sweep and/or analyze the inner surfaces of the myocardium and quickly create high-density maps of the heart tissue's electrical properties.

[0105] Although several embodiments have been described above with a certain degree of particularity, those skilled in the art could make numerous alterations to the disclosed embodiments without departing from the spirit of the present disclosure. It is intended that all matter contained in the above description or shown in the accompanying drawings shall be interpreted as illustrative only and not limiting. Changes in detail or structure may be made without departing from the present teachings. The foregoing description and following claims are intended to cover all such modifications and variations.

[0106] Various embodiments are described herein of various apparatuses, systems, and methods. Numerous specific details are set forth to provide a thorough understanding of the overall structure, function, manufacture, and use of the embodiments as described in the specification and illustrated in the accompanying drawings. It will be understood by those skilled in the art, however, that the embodiments may be practiced without such specific details. In other instances, well-known operations, components, and elements have not been described in detail so as not to obscure the embodiments described in the specification. Those of ordinary skill in the art will understand that the embodiments described and illustrated herein are non-limiting examples, and thus it can be appreciated that the specific structural and functional details disclosed herein may be representative and do not necessarily limit the scope of the embodiments, the scope of which is defined solely by the appended claims.

[0107] Reference throughout the specification to “various embodiments,” “some embodiments,” “one embodiment,” “an embodiment,” or the like, means that a particular feature, structure, or characteristic described in connection with the embodiment is included in at least one embodiment. Thus, appearances of the phrases “in various embodiments,” “in some embodiments,” “in one embodiment,” “in an embodiment,” or the like, in places throughout the specification are not necessarily all referring to the same embodiment. Furthermore, the particular features, structures, or characteristics may be combined in any suitable manner in one or more embodiments. Thus, the particular features, structures, or characteristics illustrated or described in connection with one embodiment may be combined, in whole or in part, with the features structures, or characteristics of one or more other embodiments without limitation.

[0108] It will be appreciated that the terms “proximal” and “distal” may be used throughout the specification with reference to a clinician manipulating one end of an instrument used to treat a patient. The term “proximal” refers to the portion of the instrument closest to the clinician and the term “distal” refers to the portion located furthest from the clinician. It will be further appreciated that for conciseness and clarity, spatial terms such as “vertical,” “horizontal,” “up,” and “down” may be used herein with respect to the illustrated embodiments. However, surgical instruments may be used in many orientations and positions, and these terms are not intended to be limiting and absolute.

[0109] Any patent, publication, or other disclosure material, in whole or in part, that is said to be incorporated by reference herein is incorporated herein only to the extent that the incorporated materials does not conflict with existing definitions, statements, or other disclosure material set forth in this disclosure. As such, and to the extent necessary, the disclosure as explicitly set forth herein supersedes any conflicting material incorporated herein by reference. Any material, or portion thereof, that is said to be incorporated by reference herein, but which conflicts with existing definitions, statements, or other disclosure material set forth herein will only be incorporated to the extent that no conflict arises between that incorporated material and the existing disclosure material.

1.-46. (canceled)

47. A high-density mapping catheter comprising:

- a catheter shaft comprising a proximal end and a distal end, the catheter shaft defining a catheter shaft longitudinal axis extending between the proximal end and the distal end;
- a flexible tip portion fixed adjacent to the distal end of the catheter shaft, the flexible tip portion comprising a flexible framework comprising nonconductive material forming a plurality of electrode-carrying arms;
- a plurality of microelectrodes mounted on the flexible framework and forming a flexible, planar array of microelectrodes adapted to conform to tissue, wherein the flexible framework is configured to facilitate relative movement among at least some of the plurality of microelectrodes relative to other of the plurality of microelectrodes, and wherein the nonconductive material insulates each of the plurality of microelectrodes from other of the plurality of microelectrodes; and

a proximal bushing mounted on the distal end of the catheter shaft, wherein a proximal portion of each of the electrode-carrying arms extends through the proximal bushing.

48. The high-density mapping catheter of claim **47**, wherein the plurality of microelectrodes mounted on the flexible framework are arranged in a plurality of groups.

49. The high-density mapping catheter of claim **48**, wherein two microelectrodes of the plurality of microelectrodes are placed and configured as localization microelectrodes to enable more precise localization of the planar array of microelectrodes during a medical procedure, and wherein each of these two localization microelectrodes is placed among a different group of the plurality of groups of microelectrodes.

50. The high-density mapping catheter of claim **48**, wherein each group of the plurality of groups of microelectrodes comprises a row of longitudinally-aligned microelectrodes aligned parallel to the catheter shaft longitudinal axis.

51. The high-density mapping catheter of claim **50**, wherein the flexible, planar array of microelectrodes comprises the plurality of rows of longitudinally-aligned microelectrodes.

52. The high-density mapping catheter of claim **50**, wherein each of the plurality of electrode-carrying arms has a group from the plurality of groups of microelectrodes distributed thereon.

53. The high-density mapping catheter of claim **47**, wherein the microelectrodes comprising the plurality of microelectrodes are all the same size.

54. The high-density mapping catheter of claim **47**, wherein the plurality of microelectrodes comprise between four and sixty-four individual microelectrodes.

55. The high-density mapping catheter of claim **47**, wherein a separate electrical lead wire is electrically coupled to each microelectrode in the plurality of microelectrodes.

56. The high-density mapping catheter of claim **47** further comprising at least one ring electrode mounted on the catheter shaft adjacent to the flexible, planar array of microelectrodes.

57. The high-density mapping catheter of claim **47** further comprising a location sensor.

58. The high-density mapping catheter of claim **47**, wherein the microelectrodes are ring electrodes.

59. The high-density mapping catheter of claim **47**, wherein the flexible, planar array of microelectrodes comprises a two-sided planar array of microelectrodes, wherein the microelectrodes are configured for contacting tissue on a front side and a back side of the planar array.

60. A catheter comprising:

- an elongated catheter body comprising a proximal end and a distal end, and defining a catheter longitudinal axis extending between the proximal and distal ends; and
- a flexible tip assembly fixed at the distal end of the catheter body, the flexible tip assembly comprising a flexible framework of nonconductive material, wherein the flexible framework comprises a plurality of electrode-carrying arms adapted to conform to tissue, the flexible tip assembly further comprising:
 - a plurality of microelectrodes arranged in a planar array comprising a plurality of rows of longitudinally-aligned microelectrodes aligned parallel to the catheter longitudinal axis and mounted on the plurality of

electrode-carrying arms so that at least some of the plurality of microelectrodes are moveable relative to other of the plurality of microelectrodes, wherein each row of microelectrodes is distributed along a different one of the plurality of electrode-carrying arms; and

a proximal bushing mounted on the distal end of the catheter body, wherein each electrode-carrying arm exits from a distal end of the proximal bushing.

61. The catheter of claim **60**, wherein the plurality of microelectrodes are distributed uniformly.

62. The catheter of claim **60**, wherein the distal end of the proximal bushing comprises a slot-like opening configured to hold the plurality of electrode-carrying arms in the plane of the planar array of microelectrodes.

63. The catheter of claim **60**, wherein the plurality of longitudinally-aligned arms comprises a first outboard arm and a second outboard arm, each having a localization microelectrode longer than the other microelectrodes for more precise localization of the flexible array in mapping and navigation systems, and wherein the two localization microelectrodes are adapted for use for bipolar ablation.

64. The catheter of claim **63** further comprising a temperature sensor.

65. The catheter of claim **63** further comprising an irrigation port adapted to deliver an irrigant on or adjacent to the planar array of microelectrodes.

66. The catheter of claim **63** further comprising an internal fluid delivery lumen adapted to be fluidly coupled to a source of irrigant and adapted to deliver the irrigant to the flexible tip assembly.

* * * * *

专利名称(译)	带有板载高密度标测电极的柔性高密度标测导管尖端和柔性消融导管尖端		
公开(公告)号	US20200138378A1	公开(公告)日	2020-05-07
申请号	US16/670678	申请日	2019-10-31
[标]申请(专利权)人(译)	圣犹达医疗用品心脏病学部门有限公司		
申请(专利权)人(译)	ST.犹达医疗用品, 心脏病DIVISION, INC.		
当前申请(专利权)人(译)	ST.犹达医疗用品, 心脏病DIVISION, INC.		
[标]发明人	DE LA RAMA ALAN HATA CARY K DENO DON CURTIS PAPPONE CARLO		
发明人	DE LA RAMA, ALAN HATA, CARY K. DENO, DON CURTIS PAPPONE, CARLO		
IPC分类号	A61B5/00 A61B5/042 A61B18/14 A61B5/0408		
CPC分类号	A61B2018/00351 A61B5/6859 A61B5/0408 A61B2218/002 A61B5/6869 A61B5/0422 A61B2034/2051 A61B5/6852 A61B18/1492 A61B2018/00839 A61B2090/3966 A61B2018/00577 A61B2217/007 A61N1/0476 A61N1/0551 A61N1/36071 A61N1/0553		
优先权	14/760682 2015-07-13 US PCT/US2014/011940 2014-01-16 WO 61/753429 2013-01-16 US		
外部链接	Espacenet USPTO		

摘要(译)

公开了具有板载高密度标测电极的柔性高密度标测导管尖端和柔性消融导管尖端。这些技巧可用于诊断和治疗心律不齐。柔性的远侧末端适于适应组织并且包括安装多个微电极以允许至少一些微电极之间的相对运动。柔性末端部分可包括柔性框架，该柔性框架形成微电极的柔性阵列（例如，平面或圆柱形阵列），该微阵列适于与组织一致并且在一些实施例中至少部分地由非导电材料构成。微电极的柔性阵列可以由多排纵向排列的微电极形成。柔性阵列可以进一步包括例如多个电极承载臂或电极载带。单个设备上可以存在多个灵活框架。还公开了具有内部压缩锥的输送适配器。

