

(56)

References Cited

U.S. PATENT DOCUMENTS

1,798,902 A	3/1931	Raney	5,147,380 A	9/1992	Hernandez et al.
1,881,250 A	10/1932	Tomlinson	5,151,085 A	9/1992	Sakurai et al.
2,031,682 A	2/1936	Wappler et al.	5,151,102 A	9/1992	Kamiyama et al.
2,433,067 A	12/1947	Russell	5,171,251 A	12/1992	Bregen et al.
2,448,741 A	9/1948	Scott et al.	5,173,133 A	12/1992	Morin et al.
2,926,232 A	2/1960	Gard	5,207,691 A	5/1993	Nardella
3,042,101 A	6/1962	Spunt	5,217,460 A	6/1993	Knoepfler
3,460,539 A	8/1969	Anhalt, Sr.	5,221,279 A	6/1993	Cook et al.
3,651,811 A	3/1972	Hildebrandt et al.	5,221,281 A	6/1993	Klicek
3,685,518 A	8/1972	Beuerle et al.	5,250,047 A	10/1993	Rydell
3,730,188 A	5/1973	Ellman	5,251,613 A	10/1993	Adair
3,768,482 A	10/1973	Shaw	5,254,117 A	10/1993	Rigby et al.
3,826,263 A	7/1974	Cage et al.	5,267,997 A	12/1993	Farin et al.
3,858,586 A	1/1975	Lessen	5,267,998 A	12/1993	Hagen
3,920,021 A	11/1975	Hiltebrandt	5,269,780 A	12/1993	Roos
3,934,115 A	1/1976	Peterson	5,269,782 A	12/1993	Sutter
3,952,748 A	4/1976	Kaliher et al.	5,273,524 A	12/1993	Fox et al.
3,970,088 A	7/1976	Morrison	5,277,696 A	1/1994	Hagen
3,987,795 A	10/1976	Morrison	5,281,216 A	1/1994	Klicek
RE29,088 E	12/1976	Shaw	5,282,799 A	2/1994	Rydell
4,003,380 A	1/1977	Wien	5,290,287 A	3/1994	Boebel et al.
4,016,881 A	4/1977	Rioux et al.	5,295,990 A	3/1994	Levin
4,016,886 A	4/1977	Doss et al.	5,300,087 A	4/1994	Knoepfler
4,033,351 A	7/1977	Hetzel	5,304,124 A	4/1994	Essig et al.
4,041,952 A	8/1977	Morrison, Jr. et al.	5,305,121 A	4/1994	Moll
4,043,342 A	8/1977	Morrison, Jr.	5,308,311 A	5/1994	Eggers et al.
4,085,756 A	4/1978	Weaver	5,318,564 A	6/1994	Eggers
4,092,986 A	6/1978	Schneiderman	5,320,627 A	6/1994	Sorensen et al.
4,128,099 A	12/1978	Bauer	5,322,055 A	6/1994	Davison et al.
4,161,950 A	7/1979	Doss et al.	5,324,289 A	6/1994	Eggers
4,207,896 A	6/1980	Shaw	5,330,471 A	7/1994	Eggers
4,220,154 A	9/1980	Semm	5,342,359 A	8/1994	Rydell
4,228,800 A	10/1980	Degler, Jr. et al.	5,342,381 A	8/1994	Tidemand
4,232,676 A	11/1980	Herczog	5,344,420 A	9/1994	Hilal et al.
4,248,231 A	2/1981	Herczog et al.	5,352,222 A	10/1994	Rydell
4,334,539 A	6/1982	Childs et al.	5,352,235 A	10/1994	Koros et al.
4,353,371 A	10/1982	Cosman	5,356,408 A	10/1994	Rydell
4,370,980 A	2/1983	Lottick	5,366,476 A	11/1994	Noda
4,402,311 A	9/1983	Hattori	5,368,015 A	11/1994	Wilk
4,483,338 A	11/1984	Bloom et al.	5,383,874 A	1/1995	Jackson et al.
4,492,231 A	1/1985	Auth	5,383,876 A	1/1995	Nardella
4,494,549 A	1/1985	Namba et al.	5,383,880 A	1/1995	Hooven
4,566,456 A	1/1986	Koning et al.	5,387,196 A	2/1995	Green et al.
4,590,934 A	5/1986	Malis et al.	5,391,166 A	2/1995	Eggers
4,593,679 A	6/1986	Collins	5,395,369 A	3/1995	McBrayer et al.
4,655,216 A	4/1987	Tischer	5,396,900 A	3/1995	Slater et al.
4,657,017 A	4/1987	Sorochenko	5,403,312 A	4/1995	Yates et al.
4,671,274 A	6/1987	Sorochenko	5,409,487 A	4/1995	Jalbert et al.
4,672,961 A	6/1987	Davies	5,417,687 A	5/1995	Nardella et al.
4,674,498 A	6/1987	Stasz	5,423,814 A	6/1995	Zhu et al.
4,674,499 A	6/1987	Pao	5,443,463 A	8/1995	Stern et al.
4,674,515 A	6/1987	Andou et al.	5,445,638 A	8/1995	Rydell et al.
4,682,596 A	7/1987	Bales et al.	5,451,224 A	9/1995	Goble et al.
4,732,156 A	3/1988	Nakamura	5,456,684 A	10/1995	Schmidt et al.
4,785,807 A	11/1988	Blanch	5,460,182 A	10/1995	Goodman et al.
4,819,633 A	4/1989	Bauer et al.	5,462,546 A	10/1995	Rydell
4,848,337 A	7/1989	Shaw et al.	5,464,404 A	11/1995	Abela et al.
4,850,353 A	7/1989	Stasz et al.	5,482,054 A	1/1996	Slater et al.
4,928,699 A	5/1990	Sasai	5,484,435 A	1/1996	Fleenor et al.
4,931,047 A	6/1990	Broadwin et al.	5,484,436 A	1/1996	Eggers et al.
4,955,882 A	9/1990	Hakky	5,496,312 A	3/1996	Klicek
4,969,885 A	11/1990	Farin	5,496,317 A	3/1996	Goble et al.
4,985,030 A	1/1991	Melzer et al.	5,514,134 A	5/1996	Rydell et al.
4,994,060 A	2/1991	Rink et al.	5,527,313 A	6/1996	Scott et al.
5,007,908 A	4/1991	Rydell	5,531,744 A	7/1996	Nardella et al.
5,009,656 A	4/1991	Reimels	5,540,684 A	7/1996	Hassler, Jr.
5,015,227 A	5/1991	Broadwin et al.	5,540,685 A	7/1996	Parins et al.
5,035,696 A	7/1991	Rydell	5,542,916 A	8/1996	Hirsch et al.
5,047,026 A	9/1991	Rydell	5,542,945 A	8/1996	Fritzsche
5,080,660 A	1/1992	Buelna	5,549,606 A	8/1996	McBrayer et al.
5,084,045 A	1/1992	Helenowski	5,558,100 A	9/1996	Cox
5,098,431 A	3/1992	Rydell	5,558,671 A	9/1996	Yates
5,108,391 A	4/1992	Flachenecker et al.	5,569,243 A	10/1996	Kortenbach et al.
5,147,356 A	9/1992	Bhatta	5,571,100 A	11/1996	Goble et al.
5,147,357 A	9/1992	Rose et al.	5,573,534 A	11/1996	Stone
			5,573,535 A	11/1996	Viklund
			5,599,347 A	2/1997	Hart et al.
			5,599,350 A	2/1997	Schulze et al.
			5,603,711 A	2/1997	Parins et al.

(56)

References Cited

U.S. PATENT DOCUMENTS

5,609,560 A 3/1997 Ichikawa et al.
 5,611,803 A 3/1997 Heaven et al.
 5,624,452 A 4/1997 Yates
 5,626,578 A 5/1997 Tihon
 5,637,110 A 6/1997 Pennybacker et al.
 5,651,780 A 7/1997 Jackson et al.
 5,658,281 A 8/1997 Heard
 5,665,085 A 9/1997 Nardella
 5,665,100 A 9/1997 Yoon
 5,667,526 A 9/1997 Levin
 5,669,907 A 9/1997 Platt, Jr. et al.
 5,674,184 A 10/1997 Hassler, Jr.
 5,674,220 A 10/1997 Fox et al.
 5,681,282 A 10/1997 Eggers et al.
 5,683,385 A 11/1997 Kortenbach et al.
 5,683,388 A 11/1997 Slater
 5,688,269 A 11/1997 Newton et al.
 5,688,270 A 11/1997 Yates et al.
 5,693,051 A 12/1997 Schulze et al.
 5,697,949 A 12/1997 Giurtino et al.
 5,700,261 A 12/1997 Brinkerhoff
 5,702,390 A 12/1997 Austin et al.
 5,707,369 A 1/1998 Vaitekunas et al.
 5,709,680 A 1/1998 Yates et al.
 5,713,896 A 2/1998 Nardella
 5,718,703 A 2/1998 Chin
 5,733,283 A 3/1998 Malis et al.
 5,735,848 A 4/1998 Yates et al.
 5,735,849 A 4/1998 Baden et al.
 5,743,906 A 4/1998 Parins et al.
 5,749,893 A 5/1998 Vidal et al.
 5,755,717 A 5/1998 Yates et al.
 5,810,811 A 9/1998 Yates et al.
 5,833,690 A 11/1998 Yates et al.
 5,852,238 A 12/1998 Vaitkus
 5,891,142 A 4/1999 Eggers et al.
 5,893,835 A * 4/1999 Witt et al. 601/2
 5,920,390 A 7/1999 Farahi et al.
 5,925,055 A 7/1999 Adrian et al.
 5,931,848 A 8/1999 Saadat
 5,935,143 A 8/1999 Hood
 5,951,549 A 9/1999 Richardson et al.
 5,957,882 A 9/1999 Nita et al.
 5,964,758 A 10/1999 Dresden
 5,968,060 A 10/1999 Kellogg
 5,984,919 A 11/1999 Hilal et al.
 5,989,274 A 11/1999 Davison et al.
 5,993,378 A 11/1999 Lemelson
 6,004,335 A 12/1999 Vaitekunas et al.
 6,010,512 A 1/2000 Chu et al.
 6,015,969 A 1/2000 Nathel et al.
 6,024,741 A 2/2000 Williamson, IV et al.
 6,027,515 A 2/2000 Cimino
 6,030,384 A 2/2000 Nezhat
 6,056,735 A 5/2000 Okada et al.
 6,068,647 A 5/2000 Witt et al.
 6,069,689 A 5/2000 Zeng et al.
 6,077,285 A 6/2000 Boukhny
 6,083,191 A 7/2000 Rose
 6,090,120 A 7/2000 Wright et al.
 6,096,033 A 8/2000 Tu et al.
 6,099,537 A 8/2000 Sugai et al.
 6,110,188 A 8/2000 Narciso, Jr.
 6,117,152 A 9/2000 Huitema
 6,124,597 A 9/2000 Shehada et al.

6,134,003 A 10/2000 Tearney et al.
 6,139,561 A 10/2000 Shibata et al.
 6,159,196 A 12/2000 Ruiz
 6,159,225 A 12/2000 Makower
 6,162,220 A 12/2000 Nezhat
 6,162,235 A 12/2000 Vaitekunas
 6,165,191 A 12/2000 Shibata et al.
 6,174,324 B1 1/2001 Egan et al.
 6,179,837 B1 1/2001 Hooven
 6,217,591 B1 4/2001 Egan et al.
 6,231,587 B1 5/2001 Makower
 6,237,605 B1 5/2001 Vaska et al.
 6,238,386 B1 5/2001 Muller et al.
 6,240,305 B1 5/2001 Tsuchiya
 6,241,692 B1 6/2001 Tu et al.
 6,251,110 B1 6/2001 Wampler
 6,334,860 B1 1/2002 Dorn
 6,361,534 B1 3/2002 Chen et al.
 6,436,920 B1 8/2002 Fujimura et al.
 6,494,897 B2 12/2002 Sterman et al.
 6,582,451 B1 6/2003 Marucci et al.
 6,648,883 B2 11/2003 Francischelli et al.
 6,656,175 B2 12/2003 Francischelli et al.
 6,663,627 B2 12/2003 Francischelli et al.
 6,689,128 B2 2/2004 Sliwa, Jr. et al.
 6,701,931 B2 3/2004 Sliwa, Jr. et al.
 6,723,092 B2 4/2004 Brown et al.
 6,786,905 B2 9/2004 Swanson et al.
 6,913,600 B2 7/2005 Valley et al.
 6,926,712 B2 8/2005 Phan
 6,989,010 B2 1/2006 Francischelli et al.
 7,029,470 B2 4/2006 Francischelli et al.
 8,226,675 B2 * 7/2012 Houser et al. 606/169
 8,292,888 B2 10/2012 Whitman
 2002/0017306 A1 2/2002 Cox et al.
 2002/0128639 A1 9/2002 Pless et al.

FOREIGN PATENT DOCUMENTS

EP 0572131 A1 12/1993
 EP 0598579 A1 5/1994
 EP 0653922 A1 5/1995
 EP 0878169 A1 11/1998
 EP 0717966 B1 4/2003
 FR 598149 A 12/1925
 FR 2355521 A1 1/1978
 FR 2647683 A1 12/1990
 GB 1546624 A 5/1979
 GB 2037167 A 7/1980
 GB 2066104 A 7/1981
 GB 2128881 A 5/1984
 GB 2133290 A 7/1984
 WO 9308754 A1 5/1993
 WO 9717033 A2 5/1997
 WO 0000992 A2 1/2000
 WO 0110291 A1 2/2001
 WO 01/17448 3/2001
 WO 02058539 A2 8/2002

OTHER PUBLICATIONS

D. Lang Stevenson, "Combined Biathermy Forceps and Scissors", The Lancet, Oct. 1959.
 S. L. Corson, M.D., "Two New Laparoscopic Instruments: Bipolar Sterilizing Forceps and Uterine Manipulator", Journal of Association for the Advancement of Medical Instrumentation, Jan. 1977.

* cited by examiner




FIG. 1a




FIG. 1b




FIG. 1c




FIG. 1d




FIG. 1e




FIG. 1f




FIG. 1g




FIG. 1h




FIG. 2a




FIG. 2b





FIG. 2C



2020-01-11




FIG. 2e





FIG. 2f



29
G.
—
L




FIG. 2h




FIG. 2i




FIG. 2j




FIG. 2k




FIG. 3a







FIG. 3d






FIG. 4a




FIG. 4b




FIG. 5a




FIG. 5b




FIG. 6




FIG. 7




FIG. 8




FIG. 9




FIG. 10




FIG. 11

**BIPOLAR OR ULTRASONIC SURGICAL
DEVICE****CROSS-REFERENCES TO RELATED
APPLICATIONS**

This application is a continuation application claiming the benefit of and priority to U.S. patent application Ser. No. 13/611,273, filed on Sep. 12, 2012, now U.S. Pat. No. 8,523,890, issued on Sep. 3, 2013, which is a divisional application claiming the benefit of and priority to U.S. patent application Ser. No. 10/128,768, filed on Apr. 22, 2002, now U.S. Pat. No. 8,292,888, issued on Oct. 23, 2012, which claims the benefit of and priority to U.S. Provisional Patent Application Serial No. 60/285,113, filed on Apr. 20, 2001, and U.S. Provisional Patent Application Serial No. 60/289,370, filed on May 8, 2001, each of which is expressly incorporated herein in its entirety by reference thereto.

U.S. patent application Ser. No. 10/128,768 also expressly incorporates in its entirety by reference thereto International Published Patent Application No. WO 00/72765, filed on Jun. 2, 2000. U.S. patent application Ser. No. 10/128,768 also expressly incorporates in its entirety by reference thereto U.S. patent application Ser. No. 09/723,715, filed on Nov. 28, 2000, now U.S. Pat. No. 6,793,652, issued on Sep. 21, 2004, which is a continuation-in-part of U.S. patent application Ser. No. 09/324,451, filed on Jun. 2, 1999, now U.S. Pat. No. 6,315,184, issued on Nov. 13, 2001, which is a continuation-in-part of U.S. patent application Ser. No. 09/324,452, filed on Jun. 2, 1999, now U.S. Pat. No. 6,443,973, issued on Sep. 3, 2002, which is a continuation-in-part of U.S. patent application Ser. No. 09/351,534, filed on Jul. 12, 1999, now U.S. Pat. No. 6,264,087, issued on Jul. 24, 2001, which is a continuation-in-part of U.S. patent application Ser. No. 09/510,923, filed on Feb. 22, 2000, now U.S. Pat. No. 6,517,565, issued on Feb. 11, 2003, which is a continuation-in-part of U.S. patent application Ser. No. 09/510,927, filed on Feb. 22, 2000, now U.S. Pat. No. 6,716,233, issued on Apr. 6, 2004, which is a continuation-in-part of U.S. patent application Ser. No. 09/324,452, filed on Jun. 2, 1999, now U.S. Pat. No. 6,443,973, issued on Sep. 3, 2002, which is a continuation-in-part of U.S. patent application Ser. No. 09/510,932, filed on Feb. 22, 2000, now U.S. Pat. No. 6,491,201, issued on Dec. 10, 2002, each of which is expressly incorporated in U.S. patent application Ser. No. 10/128,768 in its entirety by reference thereto.

FIELD OF THE INVENTION

The present invention relates to a bipolar and/or ultrasonic surgical device.

BACKGROUND INFORMATION

Various bipolar, ultrasonic, and/or electro-mechanical surgical devices exist which are used to cauterize and coagulate tissue in a surgical procedure. Some devices use bipolar electrical energy in order to cut and/or coagulate tissue. Generally, bipolar surgical instruments clamp the tissue prior to the application of the electro surgical energy. Some devices provide opposing jaws to perform the clamping or grasping procedure where an electrode(s) is disposed on the inner surface of the jaws. These bipolar surgical instruments coagulate, cut and separate tissue by charging the electrode(s) to apply heat to the tissue between the jaws.

During the use of bipolar surgical instruments, the heat generated by the electrodes causes the desired coagulation

and cutting of tissue. Several of the bipolar surgical instruments may encounter problems with the application of the heat of the tissue. Adjacent tissue may be damaged due to application of excessive heat. Conversely, where less energy is applied to the electrodes in order to prevent over heating, the coagulation of the tissue may require more time than desired.

Fully mechanical surgical devices are also available in order to perform the above procedure. The mechanical devices require the application of force to staple and cut the tissue. Many of the existing mechanical devices use four rows of staples in order to ensure the proper results. Due to the cutting and stapling functions, many of these mechanical surgical instruments require an excessive amount of force in order to effectively perform their functions.

Therefore, an object of the present invention provides an electro-mechanical that allows greater control of heat applied to the tissue by the bipolar electrodes and allows the use of less mechanical force when incorporating the use of mechanical force.

SUMMARY

The above and other beneficial objects and advantages of the present invention may be effectively attained by providing a bipolar, ultrasonic and/or electro-mechanical surgical device as described herein.

In an example embodiment and/or example method, the present invention provides for an electro-mechanical surgical device including a housing, at least two opposing jaw, and at least one electrical contact associated with at least one of the jaws. In a further example embodiment of the present invention, the electrical contact is at least one of a bipolar electrical contact and an ultrasonic electrical contact.

In a further example embodiment and/or example method of the present invention, the surgical device includes a row of electrical contacts associated with the at least one of the opposing jaws. In a further example embodiment and/or example method of the present invention, the surgical device includes at least two rows of electrical contacts associated with at least one of the opposing jaws.

In a further example embodiment and/or example method of the present invention, the surgical device includes a sensor configured and arranged to sense temperature of tissue disposed between the upper jaw and the lower jaw. In a further example embodiment and/or example method of the present invention, the sensor may be configured to transmit a signal to the surgical device via, e.g., a data transfer cable, the signal indicating the temperature of the tissue disposed between the upper jaw and the lower jaw. Further, the signal transmitted by the sensor may effect a movement of the jaw(s) and/or a change in the heating effect of the electrode(s) on the tissue.

In a further example embodiment and/or example method of the present invention, the surgical device includes, on at least one of the jaws, at least one pierceable ampulla containing fluid so that the fluid is releasable when the upper jaw and the lower jaw are in the closed position and so that the electrode passes through the tissue disposed between the upper jaw and the lower jaw into the at least one pierceable ampulla. That fluid may include, for example, a variety of fluids or matters or dyes, for example, collagen, fibrin, dye, matter configured to effect anastomosis, matter configured to seal tissue and matter configured to effect hemostasis, etc. In a further example embodiment and/or example method of the present invention, the electrode and/or row(s) of electrodes may be activated so that the tissue is coagulated to induce hemostasis.

In a further example embodiment and/or example method of the present invention, an electro-mechanical surgical system may include a surgical device and a surgical instrument. The surgical device may include a housing, an elongated shaft extending from the housing, a distal end of the elongated shaft configured to detachably couple with a surgical instrument, a steering arrangement, the steering arrangement configured to steer the distal end of the elongated shaft, and a motor system disposed within the housing, the motor system configured to drive the drive shafts and the steering arrangement. The surgical instrument may include an upper jaw, a lower jaw, the lower jaw opposing the upper jaw and the lower jaw configured to detachably couple with the distal end of the elongated shaft of the surgical device, and an electrode or row(s) of electrodes provided on at least one of the lower jaw and the upper jaw. The electrode(s) may be associated with any one of more of the jaws, such as, for example, the inner surface of an upper jaw of two opposing jaws.

In a further example embodiment and/or example method of the present invention, one of the opposing jaws, e.g., the lower jaw, includes at least two rows of staples and a cutting device.

In further example embodiments and/or example methods of the present invention, there may be a reduced number of staples and thus less mechanical force to form staples and transect tissue. Further, example embodiments and/or example methods may use bipolar radio-frequency (RF) energy and/or staples to coagulate and cut tissue. Further, example embodiments and/or example methods may include one row of staples or no staples. Further, example embodiments may include an energy surgical attachment (DLU) which consists of two opposing jaws where the two opposing jaws may include, e.g., one or two, rows of bipolar electrical contacts.

BRIEF DESCRIPTION OF THE DRAWINGS

FIG. 1a is a perspective view of an electro-mechanical driver device, which may be coupled to the surgical device according to the present invention.

FIG. 1b is a detailed view of the interior of a flexible shaft of the electro-mechanical surgical device illustrated in FIG. 1a.

FIG. 1c is a schematic top view of a remote control unit of the electro-mechanical surgical device.

FIG. 1d is a perspective view of a surgical device according to one embodiment of the present invention.

FIG. 1e is an example embodiment of a memory device according to the present invention.

FIG. 1f is an end view of an example embodiment of a coupling.

FIG. 1g is a front end view of a second coupling

FIG. 1h is a schematic top view of another example embodiment of a remote control unit.

FIG. 2a illustrates an example embodiment of parallel expanding jaws in a closed position.

FIG. 2b illustrates an example embodiment of parallel expanding jaws in an open position.

FIG. 2c illustrates an example embodiment of the components of the parallel expanding jaws in a closed position.

FIG. 2d illustrates an example embodiment of the components of the parallel expanding jaws in an open position.

FIG. 2e is cross-sectioned view of the parallel expanding jaws.

FIG. 2f illustrates an example embodiment of the parallel expanding jaws where the lower jaw includes electrodes.

FIG. 2g illustrates an example embodiment of the parallel expanding jaws where the lower jaw includes electrodes and a stapling mechanism.

FIG. 2h illustrates another example embodiment of the parallel expanding jaws where the lower jaw includes electrodes.

FIG. 2i illustrates another example embodiment of the parallel expanding jaws where the lower jaw includes electrodes and a stapling mechanism.

FIG. 2j illustrates an example embodiment of the parallel expanding jaws which includes ultrasonic pins.

FIG. 2k illustrates an example embodiment of the parallel expanding jaws which includes surgical barb pins.

FIG. 3a illustrates an example embodiment of an electrode and staple configuration according to the present invention.

FIG. 3b illustrates an example embodiment of an electrode and staple configuration disposed on a lower jaw.

FIG. 3c illustrates an example embodiment of an electrode configuration disposed on a lower jaw.

FIG. 3d illustrates an example embodiment of an electrode configuration according to the present invention.

FIG. 3e illustrates an example embodiment of an electrode configuration disposed on a lower jaw.

FIG. 4a illustrates an example embodiment of scissor-like jaws in a closed position.

FIG. 4b illustrates an example embodiment of scissor-like jaws in an open position.

FIG. 5a illustrates a perspective view of an example embodiment of the present invention.

FIG. 5b illustrates an example embodiment of a front panel of an electro-mechanical device.

FIG. 6 illustrates an example embodiment of an electrode arrangement according to the present invention.

FIG. 7 illustrates another example embodiment of an electrode arrangement according to the present invention.

FIG. 8 is a side view of an example electrode configuration according to the present invention.

FIG. 9 illustrates an example embodiment of an electrode configuration according to the present invention.

FIG. 10 illustrates an example embodiment of the present invention which includes the use of ultrasonic technology.

FIG. 11 illustrates an example embodiment where surgical barbs are used as electrodes.

DETAILED DESCRIPTION

Referring to FIG. 1a, a perspective view of an electro-mechanical driver device 101 according to one example embodiment of the present invention is illustrated. Such an electro-mechanical driver device is described in, for example, U.S. patent application Ser. No. 09/723,715, entitled "Electro-Mechanical Surgical Device," now U.S. Pat. No. 6,793,652, which is expressly incorporated herein in its entirety by reference thereto. Electro-mechanical driver device 101 may include, for example, a remote power console 102, which includes a housing 104 having a front panel 103. Mounted on front panel 103 are a display device 106 and indicators 108a and 108b. A flexible shaft 105 may extend from housing 104 and may be detachably secured thereto via a first coupling 107. The distal end 109 of flexible shaft 105 may include a second coupling 106 adapted to detachably secure a surgical instrument or attachment to the distal end 109 of the flexible shaft 105. In accordance with the example embodiment of the present invention, the surgical instrument or attachment may be, for example, a surgical stapler and cutter device that utilizes electrical energy to cut and/or coagulate tissue. Other surgical instruments are described, for example, in U.S.

patent application Ser. No. 09/324,451, entitled "A Stapling Device for Use with an Electro-mechanical Driver Device for Use with Anastomosing, Stapling, and Resecting Instruments," now U.S. Pat. No. 6,315,184, U.S. patent application Ser. No. 09/324,452, entitled "Electro-mechanical Driver Device for Use with Anastomosing, Stapling, and Resecting Instruments," now U.S. Pat. No. 6,443,973, U.S. patent application Ser. No. 09/351,534, entitled "Expanding Parallel Jaw Device For Use With An Electromechanical Driver Device," now U.S. Pat. No. 6,264,087, U.S. patent application Ser. No. 09/510,926, entitled "A Vessel and Lumen Expander Attachment for Use with an Electro-mechanical Driver Device," now U.S. Pat. No. 6,348,061, U.S. patent application Ser. No. 09/510,927, entitled "Electro-mechanical Driver and Remote Surgical Instruments Attachment Having Computer Assisted Control Capabilities," now U.S. Pat. No. 6,716,233, U.S. patent application Ser. No. 09/510,931, entitled "A Tissue Stapling Attachment for Use with an Electro-mechanical Driver Device," now U.S. Pat. No. 6,533,157, U.S. patent application Ser. No. 09/510,932, entitled "A Fluid Delivery Mechanism for Use with Anastomosing, Stapling, and Resecting Instruments," now U.S. Pat. No. 6,491,201, and U.S. patent application Ser. No. 09/510,933, entitled "A Fluid Delivery Device for Use with Anastomosing, Resecting and Stapling Instruments," now U.S. Pat. No. 6,488,197, each of which is expressly incorporated herein in its entirety by reference thereto.

According to a further example embodiment, flexible shaft **105** may include a tubular outer sheath, which may include a coating or other sealing arrangement to provide a fluid-tight seal between the interior channel thereof and the environment. The sheath may be formed of a tissue-compatible, sterilizable elastomeric material. The sheath may also be formed of a material that is autoclavable. An example embodiment of such a flexible shaft, is described, for example, in U.S. patent application Ser. No. 10/099,634, entitled "Moisture-Detecting Shaft For Use With An Electro-Mechanical Surgical Device," now U.S. Pat. No. 7,951,071, which is expressly incorporated herein in its entirety by reference thereto.

As illustrated in FIG. **1b**, disposed within the interior channel **150** of the flexible shaft **105**, and extending along the length thereof, may be a first rotatable drive shaft **152**, a second rotatable drive shaft **154**, a first steering cable **156**, a second steering cable **158**, a third steering cable **160**, a fourth steering cable **162**, one or more data transfer cables **164**, and/or two leads **166** and **168**, all terminating at the second coupling **106**, at the distal end **109** of the flexible shaft **105**. The leads **166** and **168** may be provided to, for example, transmit current to and/or from an attached surgical instrument or attachment. The remote power console **102** may include a motor system, which includes one or more motors configured to rotate the first and second rotatable drive shafts **152**, **154** and to apply tension or otherwise drive the steering cables to thereby steer the distal end **109** of the flexible shaft **105**. An example embodiment of a motor arrangement is described, for example, in U.S. patent application Ser. No. 09/510,923, entitled "A Carriage Assembly For Controlling A Steering Wire Steering Mechanism Within A Flexible Shaft," now U.S. Pat. No. 6,517,565, which is expressly incorporated herein in its entirety by reference thereto.

Referring to FIG. **1c**, there is shown a top schematic view of a remote control unit ("RCU") **130** for remotely controlling the electro-mechanical driver device **101** illustrated in FIG. **1a**. The RCU **130** may be, for example, a wired remote control unit, a wireless remote control unit, a hybrid remote control unit, etc. The RCU **130** may include a number of

operable control elements **300**, **312**, **314**, **320** and **346** which may be, for example, toggle switches, button switches, analog switches, control knobs, potentiometers, etc. The RCU **130** may also include indicators **108a'**, **108b'** and a display device **110'**. Although FIG. **1c** illustrates five control elements **300**, **312**, **314**, **320** and **346**, any appropriate number of control elements may be provided. In a further example embodiment of the present invention, RCU **130** may be configured to clamp onto the sheath of the flexible shaft **105**.

Referring to FIG. **1d**, there is illustrated a perspective view of a further example embodiment of the surgical device according to the present invention. The surgical device **200** may be used in combination with the electro-mechanical driver device **101** illustrated in FIG. **1a**. The surgical device **200** may also be used in combination with a manually-operable driver device.

The surgical device **200** according to the example embodiment includes a coupling **11** adapted and configured to detachably couple the surgical device **200** with the second coupling device **106** of the flexible shaft **105** of the driver device **101** illustrated in FIG. **1a**. The couplings **11**, **106** may include a quick-connect type fitting, such as a rotary quick-connect type fitting, a bayonet type fitting, etc. The couplings **11** and **106** may also be threaded couplings. In an alternative example embodiment, the surgical device **200** is permanently connected to or integral with the driver device, electro-mechanical or manual, for example.

The surgical device **200** includes an upper jaw **4a** and a lower jaw **4b**. In the example embodiment illustrated in FIG. **1d**, the lower jaw **4b** is connected to coupling **11**.

Electrodes **3a**, **3b** may be provided on an inner surface of lower jaw **4b**. In alternative example embodiments, electrodes may be provided on the upper jaw **4a**, or on both the upper jaw **4a** and the lower jaw **4b**. In this alternative example embodiment, the lower jaw **4b** may also include two rows of staples **201**, **202** and a cutting device **203**.

The surgical device **200** may also include sensors **205**, **206**. These sensors may be configured and arranged to, for example, sense the temperature of tissue disposed between jaws **4a** and **4b**. When coupled to the driver device **101** of FIG. **1a**, for example, signals from the sensors **205**, **206** may be transmitted to the driver device, e.g., via data transfer cables.

The upper jaw **4a** illustrated in FIG. **1d** may include pierceable ampullae **5**, which may contain fluid or matter to induce hemostasis. The fluid may include, for example, collagen, fibrin, etc. The use of other fluids or matters is, of course, possible. This fluid or matter, for example, collagen, fibrin, dye, matter configured to effect anastomosis, matter configured to seal tissue and matter configured to effect hemostasis, etc. may be released when the jaws **4a**, **4b** are closed and the electrodes **3a**, **3b** pass through the tissue and into the ampullae **5**, releasing the fluid or matter. Simultaneously, the electrodes **3a**, **3b** are activated and tissue may be coagulated to induce hemostasis. Sensors **205**, **206** monitor the amount of heat provided and duration of application. While the current passes between the electrodes **3a**, **3b**, a driver may advance to eject two rows of staples **201**, **202** on either side of the cutting device **203**. In a further example embodiment, the stapling mechanism includes a replaceable tray or cartridge of open staples set within the lower jaw **4b** and a set of corresponding staple guides within the upper jaw **4a**, such that when the surgical device **200** is in a closed position, the open staples are arranged to oppose the corresponding staple guides. The stapling mechanism may also include a wedge pushing system whereby once the linear clamping mechanism is in a closed position, a wedge arranged in a channel below the tray of open staples is pushed through the channel. As the wedge moves

through the channel, a sloping surface of the wedge pushes the open staples against the corresponding staple guides, thereby closing the staples. After the staples have been closed, the wedge is pulled back through the channel. The second drive extension pushes or pulls the wedge through the channel, depending on the turning direction of the corresponding motor in the, for example, electro-mechanical driver device, by engaging a threaded horizontal shaft upon which the wedge, having a matching inner thread, rides. An example embodiment of such a stapling device is described, for example, in U.S. patent application Ser. No. 09/324,451, entitled "A Stapling Device For Use With An Electromechanical Driver Device For Use With Anastomosing, Stapling, and Resecting Instruments," now U.S. Pat. No. 6,315,184, and in U.S. patent application Ser. No. 09/999,546, entitled "Surgical Device," now U.S. Pat. No. 7,695,485, each of which is expressly incorporated herein in its entirety by reference thereto.

In a further example embodiment of the present invention, the surgical device **200** includes a memory device **204**. The memory device **204** may be, for example, a read-only memory, a programmable memory, a random access memory, etc. The memory device **204** may be configured and arranged to store, for example, a unique serial number of the surgical device **200**, and/or a device type indication. The memory device **204** may also be configured and arranged to store counter data indicating how many times the surgical device **200** has been used. When coupled to the driver device **101** illustrated in FIG. **1a**, for example, this memory device **204** may be read by the driver device **101**, e.g., via a data transfer cable. In operation, the surgical device **200** is first connected to the electro-mechanical driver device **101** illustrated in FIG. **1a** via coupling **11**. A driver device may read the memory device **204** to determine, for example, the device type, so that the driver device may execute the movements of the surgical device **200** in a suitable fashion.

FIG. **1e** is a schematic view of memory unit **204**. As illustrated, data connector **742** includes contacts **744**, each electrically and logically connected to memory unit **204** via a respective line **748**. Memory unit **204** is configured to store, for example, a serial number data **715**, an attachment type identifier (ID) data **725** and a usage data **735**. Memory unit **204** may additionally store other data. Both the serial number data **715** and the ID data **725** may be configured as read-only data. In the example embodiment, serial number data **715** is data uniquely identifying the particular surgical instrument or attachment, whereas the ID data **725** is data identifying the type of the attachment, such as, for example, a bipolar surgical device, an ultrasonic surgical device, a circular surgical stapler attachment, a linear surgical stapler attachment, etc. The usage data **735** represents usage of the particular attachment, such as, for example, the number of times that jaws **4a**, **4b** of surgical device **200** have been actuated.

Each type of surgical instrument or attachment attachable to the distal end **109** of the flexible shaft **105** may be designed and configured to be used a single time or multiple times. The surgical instrument or attachment may also be designed and configured to be used a predetermined number of times. Accordingly, the usage data **735** may be used to determine whether the surgical instrument or attachment has been used and whether the number of uses has exceeded the maximum number of permitted uses. In a further example embodiment, an attempt to use a surgical instrument or attachment after the maximum number of permitted uses has been reached may generate an ERROR condition.

A controller within the electro-mechanical device **101**, for example, as illustrated in FIG. **1a**, may be configured to

execute an operating program or algorithm based on the read ID data **725**. Such a controller is described, for example, in U.S. patent application Ser. No. 09/723,715, entitled "Electro-Mechanical Surgical Device," now U.S. Pat. No. 6,793,652, and U.S. patent application Ser. No. 09/836,781 entitled "Electro-Mechanical Surgical Device," now U.S. Pat. No. 6,981,941, each of which is expressly incorporated herein in its entirety by reference thereto. The remote power console **102**, for example, as illustrated in FIG. **1a**, may include a memory unit which may be configured to store the operating programs or algorithms for each available type of surgical instrument or attachment, the controller selects and/or reads the operating program or algorithm from the memory unit in accordance with the ID data **725** read from the memory unit **204** of an attached surgical instrument or attachment. The operating programs or algorithms stored in the memory unit may be updated, added, deleted, improved or otherwise revised as necessary. In a further example embodiment, the serial number data **715** and/or usage data **735** may also be used to determine which of a plurality of operating programs or algorithms is read or selected from the memory unit. In a further example embodiment, the operating program or algorithm may alternatively be stored in the memory unit **204** of the surgical instrument or attachment and transferred to the controller via the data transfer cables **164**. Once the appropriate operating program or algorithm is read or selected by, or transmitted to, the controller, the controller may cause the operating program or algorithm to be executed in accordance with operations performed by the user, e.g., via the RCU **130**. The controller may be electrically and logically connected with one or more motors arranged in the remote power console **102**, for example, as illustrated in FIG. **1a**, and may be configured to control these motors in accordance with the read, selected or transmitted operating program or algorithm.

According to a further example embodiment of the present invention, surgical device **200** includes a system configured to open and close the jaws **4a**, **4b** relative to one another, and a system configured to drive the staples **201**, **202** and to drive the cutting device **203**. Examples of such systems are described in detail in U.S. patent application Ser. No. 09/324,421, entitled "Alignment Device And Lithographic Apparatus Comprising Such A Device," now U.S. Pat. No. 6,417,922, U.S. patent application Ser. No. 09/324,451, entitled "A Stapling Device For Use With An Electromechanical Driver Device For Use With Anastomosing, Stapling, and Resecting Instruments," now U.S. Pat. No. 6,315,184, U.S. patent application Ser. No. 09/351,534, entitled "Expanding Parallel Jaw Device For Use With An Electromechanical Driver Device," now U.S. Pat. No. 6,264,087, each of which is expressly incorporated herein in its entirety by reference thereto.

FIG. **1f** is an end view of an example embodiment of coupling **107** illustrated in FIG. **1a**. The coupling **107** includes a first connector **444**, a second connector **448**, a third connector **452** and a fourth connector **456**, each rotatably secured to the coupling **107**. Each of the connectors **444**, **448**, **452** and **456** includes a respective recess **446**, **450**, **454** and **458**. As illustrated in FIG. **1f**, each recess **446**, **450**, **454** and **458** may be hexagonally shaped. It should be appreciated, however, that the recesses **446**, **450**, **454** and **458** may have any shape and configuration to non-rotatably couple and rigidly attach the connectors **444**, **448**, **452**, **456** to respective drive shafts of a motor arrangement contained within driver device **101** illustrated in FIG. **1a**. Complementary projections may be provided on respective drive shafts of the motor arrangement to thereby drive the drive elements of the flexible shaft **105**. It should also be appreciated that the recesses may be provided on the drive shafts and complementary projec-

tions may be provided on the connectors **444**, **448**, **452**, **456**. Any other coupling arrangement configured to non-rotatably and releasably couple the connectors **444**, **448**, **452**, **456** and the drive shafts of the motor arrangement may be provided. Coupling **107** also includes contacts **500**, **501** configured to transfer additional voltage from the remote power console **102** through flexible shaft **105**.

One of the connectors **444**, **448**, **452**, **456** is non-rotatably secured to the first drive shaft **152**, and another one of the connectors **444**, **448**, **452**, **456** is non-rotatably secured to the second drive shaft **154**. The remaining two of the connectors engage with transmission elements configured to apply tensile forces on the steering cables **156**, **158**, **160** and **162** to thereby steer the distal end **109** of the flexible shaft **205**. The data transfer cable **164** is electrically and logically connected with data connector **460**. Data connector **460** includes, for example, electrical contacts **462**, corresponding to and equal in number to the number of individual wires contained in the data cable **164**. First coupling **422** includes a key structure **442** to properly orient the first coupling **422** to a mating and complementary coupling arrangement disposed on the housing **104**. Such key structure **442** may be provided on either one, or both, of the first coupling **422** and the mating and complementary coupling arrangement disposed on the housing **104**. First coupling **422** may include a quick-connect type connector, which may be configured, for example, so that a simple pushing motion engages the first coupling **422** to the housing **104**. Seals may be provided in conjunction with any of the several connectors to provide a fluid-tight seal between the interior of first coupling **422** and the environment.

FIG. **1g** is a front end view of the second coupling **106** of flexible shaft **105**. Second coupling **106** includes a first connector **660** and a second connector **680**, each rotatably secured to the second coupling **106** and each non-rotatably secured to a distal end of a respective one of the first and second drive shafts **152**, **154**. A quick-connect type fitting **645** is provided on the second coupling **106** to detachably secure a surgical instrument or attachment thereto. The quick-connect type fitting **645** may include, for example, a rotary quick-connect type fitting, a bayonet type fitting, etc. A key structure **740** is provided on the second coupling **106** to properly align the surgical instrument or attachment to the second coupling **106**. The key structure or other arrangement to properly align the surgical instrument or attachment to the flexible shaft **105** may be provided on either one, or both, of the second coupling **106** and the surgical instrument or attachment. In addition, the quick-connect type fitting may be provided on the surgical instrument or attachment. A data connector **700**, having electrical contacts **720**, is also provided in the second coupling **106**. Like the data connector **60** of first coupling **422**, the data connector **700** of second coupling **106** includes contacts **720** electrically and logically connected to the respective wires of data transfer cable **164** and contacts **462** of data connector **460**. Seals may be provided in conjunction with the connectors **660**, **680**, **700** to provide a fluid-tight seal between the interior of second coupling **106** and the environment. In a further example embodiment, electrical contacts **620**, **640** receive any additional voltage that may be sent from the remote power console **102** to the surgical instrument or device. In a further example embodiment, the surgical instrument or device may use the additional voltage provided by electrical contacts **620**, **640** to charge electrodes that may be included within the surgical instrument or device.

FIG. **1h** illustrates an example embodiment of a wireless RCU **130** which provides the user with controls for the electro-mechanical device **101** and the surgical device **200**. Wireless RCU **130** includes a steering engage/disengage switch

312, the operation of which controls the operation of one or more motors in order to selectively engage and disengage the steering mechanism. Wireless RCU **130** also may include a two-way rocker **314** having first and second switches **316**, **318** operable thereby. The operation of these switches **316**, **318** controls certain functions of the electro-mechanical surgical device **101** and any surgical instrument or attachment attached to the flexible shaft **105** in accordance with the operating program or algorithm corresponding to the attached surgical instrument or attachment, if any. For example, operation of the two-way rocker **314** may control the advancement and retraction of the flexible shaft **105**. Wireless RCU **130** is provided with yet another switch **320**, the operation of which may further control the operation of the electro-mechanical surgical device **101** and any surgical instrument or attachment attached to the flexible shaft **20** in accordance with the operating program or algorithm corresponding to the attached surgical instrument or attachment, if any. For example, when the surgical device **200** is attached to the flexible shaft **105**, operation of the switch **320** may initiate the advancement of staples into tissue between jaws **4a**, **4b**.

Wireless RCU **130** may also include a controller **322**, which is electrically and logically connected with the switches **302**, **304**, **306**, **308** via line **324**, with the switches **316**, **318** via line **326**, with switch **312** via line **328** and with switch **320** via line **330**. Wireless RCU **130** may include indicators **108a'**, **108b'**, corresponding to the indicators **108a**, **108b** of front panel **103**, and a display device **110'**, corresponding to the display device **110** of the front panel **103**. If provided, the indicators **108a'**, **108b'** are electrically and logically connected to controller **322** via respective lines **332**, **334**, and the display device **110'** is electrically and logically connected to controller **322** via line **336**. Controller **322** is electrically and logically connected to a transceiver **338** via line **340**, and transceiver **338** is electrically and logically connected to a receiver/transmitter **342** via line **344**. A power supply, for example, a battery, may be provided in wireless RCU **130** to power the same. Thus, the wireless RCU **130** may be used to control the operation of the electro-mechanical surgical device **101** and any surgical instrument or attachment attached to the flexible shaft **105** via wireless link **160**.

Wireless RCU **130** may include a switch **346** connected to controller **322** via line **348**. Operation of switch **346** transmits a data signal to the transmitter/receiver **146** of the remote power console **102**, for example as illustrated in FIG. **1a**, via wireless link **160**. The data signal may include, for example, identification data uniquely identifying the wireless RCU **130**. This identification data may be used by a controller within the electro-mechanical surgical or driver device **101** to prevent unauthorized operation of the electro-mechanical driver device **101** and to prevent interference with the operation of the electro-mechanical driver device **101** by another wireless RCU. Each subsequent communication between the wireless RCU **130** and the electro-mechanical driver device **101** may include the identification data. Thus, the controller may discriminate between wireless RCUs and thereby allow only a single, identifiable wireless RCU **130** to control the operation of the electro-mechanical driver device **101** and any surgical instrument or attachment attached to the flexible shaft **105**. In another example embodiment, RCU **130** is connected to remote power console **102**, for example, as illustrated in FIG. **1a**, via wires or an optical connection.

FIGS. **2a** to **2e** illustrates further example embodiments of a surgical device **200'** having expandable jaws that remain parallel. In such example embodiments, surgical device **200'** includes a parallel separable jaw system that has a lower jaw **40b** and an upper jaw **40a** having a proximal end **220**.

Referring to FIGS. 2c, 2d and 2e, the proximal end 220 of the upper jaw 40a has a pair of threaded vertical bores 225, through which extend a corresponding pair of vertical shafts 227. Inner threads 226 of the vertical bores 225 match outer threads 228 of the vertical shafts 227. The vertical shafts 227 engage a threaded upper horizontal shaft 235 at a distal end 240 of the upper horizontal shaft 235. Outer threads 237 of the upper horizontal shaft 235 interlock with the outer threads 228 of the vertical shafts 227. The upper horizontal shaft 235 has at a proximal end 242, an upper drive socket 244.

The example embodiments of the surgical device 200' as illustrated in FIGS. 2a to 2e attaches to coupling 106 of the electro-mechanical driver device 101 such that an upper drive socket 244 and a lower drive socket 272, illustrated in FIG. 2e, engages the flexible shaft 105 at the distal end 109. Thus, rotation of the upper horizontal shaft 235 is effected by rotation of the upper drive socket 244 which is effected by rotation of the corresponding flexible drive shaft of flexible shaft 105. Clockwise or counter-clockwise rotation is achieved depending on the direction of the corresponding motor within the remote power console 102. Similarly, rotation of the lower horizontal shaft 287 is effected by rotation of the lower drive socket 272 which is effected by rotation of the corresponding flexible drive shaft of flexible shaft 105. Also, the clockwise or counter-clockwise rotation of the lower horizontal shaft 287 is achieved depending on the direction of the corresponding motor within remote power console 102. Surgical device 200' also includes contact nodes 254', 256' which transfer additional voltage to surgical device 200'.

As illustrated in FIGS. 2c and 2d, the surgical device 200' further includes a first sensor electrode 250 configured to electrically communicate via communication wires with a first contact pad 251, which is configured to electrically communicate with a second contact pad via direct contact, which is configured to electrically communicate via communications wires with a first contact node 254, as illustrated in FIGS. 2c and 2d. Similarly, the surgical device 200' further includes a second sensor electrode 252 configured to electrically communicate via communication wires with a second contact node 256. The contact nodes 254, 256 are configured to electrically communicate with communication wires in the electro-mechanical driver device 101 to form a sensor circuit, such that when the upper jaw 40a and the lower jaw 40b are clamped together, the sensor electrodes 250, 252 are in contact, the sensor circuit is closed, and the surgeon is alerted via other circuit components to the clamped position of the jaws 40a, 40b, and is therefore informed that it is safe and/or appropriate to active the stapling mechanism.

The example embodiment illustrated may include a wedge pushing system within lower jaw 40b. FIGS. 2c and 2d show the wedge pushing system including a replaceable tray or cartridge 275 housing one or more fastening staples, and an upper jaw 40a one or more staple guides 284 corresponding to the staples 280. Each of the staples 280 has a butt 282 protruding below the tray 275 and a pair of prongs 284 extending to the top of the tray 275. The wedge pushing system further includes a wedge guide, or channel 286, illustrated in FIG. 2e, extending beneath the tray 275. Within the channel 286 extends a threaded lower horizontal shaft 287 having outer threads 288. Upon the lower horizontal shaft 287 is arranged a wedge 289 having a sloped top face 290, a horizontal threaded bore 292 coaxial with the channel 286, having inner threads 293 matching the outer threads 288 of the lower horizontal threaded shaft 287, and an upwardly extending cutting member 277.

FIGS. 2f to 2k illustrate various electrode and/or stapling mechanism configurations associated with the surgical

device 200' illustrated in FIGS. 2a to 2e. FIG. 2f is a side view of the jaws 40a, 40b. As illustrated in FIG. 2f, the surgical device 200' includes electrodes 30 disposed over lower jaw 40b, a pierceable ampullae 32c, which may be similar to pierceable ampullae 5 described above, and sensors 250, 252. Electrodes 30 protrude from the lower jaw 40b and are applied to and may pierce tissue placed between the jaws in order to anastomose the tissue. Accordingly, the electrodes 30 may be rigid and conductive in regard to the material used for their construction. The electrodes 30 may also have features that may enhance tissue penetrating attributes and electrical contact between any opposing electrodes. Various configurations may be provided to enhance contact with tissue where electrode height, width and density of spacing are adjusted in order to accommodate various tissue thickness and texture. The electrodes 30 are charged through voltage sent from remote power console 102 through leads 166, 168 of flexible shaft 105. Contact nodes 254', 256' electrically connect to electrical contacts 620, 640 of coupling 106 and current flows through to electrodes 30. As described above, electrical contacts 620, 640 are electrically connected to leads 166, 168 of the flexible shaft 105. Sensors 250, 252 monitor the amount of heat generated by the charging of electrodes 30 and duration of application. Sensors 250, 252 transfer signals to the remote power console 102 which provides the user with information regarding current conditions related to the operation of the surgical device 200'.

FIG. 2g illustrates the electrodes 30 used in conjunction the wedge pushing system as described above. In this example embodiment, the wedge pushing system is similar the wedge pushing system as described with reference to FIGS. 2e to 2d. The wedge pushing system is operated in conjunction with the electrodes 30 in order to coagulate and/or anastomose tissue between the parallel jaws 40a, 40b.

FIG. 2h illustrates an electrode configuration of another example embodiment of the present invention. As illustrated electrodes 30 are disposed over the inner face of the lower jaw 40b. The electrodes 30 are charged positively and receptacles 20 are negatively charged (ground) and configured for alignment with electrodes 30. This configuration induces current to flow from lower jaw 40b to the upper jaw 40a when the jaws 40a, 40b are closed. The amount of RF energy transferred between jaws 40a, 40b may be varied depending upon whether staples are used in conjunction with the electrodes, as illustrated in FIG. 2i, or if the anastomose is performed solely through the use of the electrode configuration. In an example embodiment, the electrodes 30 and receptacles 20 electrically communicate with the remote power console 102 through contact nodes 254', 256' as described above in reference to FIGS. 2f and 2g. As described above with reference to FIG. 2g, FIG. 2i illustrates the electrode configuration illustrated in FIG. 2h used in conjunction with the wedge pushing system which provides a stapling mechanism.

FIG. 2j illustrates yet another example embodiment of the present invention is illustrated. The electrode configuration illustrated in FIG. 2j provides ultrasonic energy which is transmitted through ultrasonic resonator pins 27 which are configured on the inner surface of the lower jaw 4b. Similar to the electrode configurations described above, the ultrasonic pins 27 may be configured in various formations conducive to the type and form of the tissue which is placed between the jaws for coagulation, anastomosing and/or cutting. In addition to the ultrasonic resonator pins 27, the lower jaw 4b also includes an ultrasonic transducer 25. The ultrasonic transducer 25 generates the ultrasonic energy that resonates through the pins 27. The ultrasonic resonator pins 27 may be used with or without staples, as described with regard to the

electrode configurations above, enable the reduction of the number of staples used or the elimination thereof and lessen the mechanical force needed in order to complete coagulation and cutting. The ultrasonic energy use in this example embodiment may be transmitted through contact nodes **254'**, **256'** as described in the foregoing example embodiments.

FIG. **2k** illustrates yet another example embodiment of the present invention in which electrodes **29** are configured as surgical barbs. The configuration of electrodes **29** provide for an improved configuration for penetrating tissue. The electrodes **29** may follow the polarity schemes described above in order to apply RF energy to the tissue. The electrodes **29** may be used as illustrated with electrodes arranged on the lower jaw **40b** only. However this surgical barb type electrode may also be arranged on the inner surface of the upper jaw **40a** in order to provide even more effective penetrating results. Furthermore, as described above with reference to FIG. **2f**, a pierceable ampulla **32c** may be incorporated in the upper jaw **40a** and used to induce hemostasis. The electrodes **29** receive the RF energy through contact nodes **254'**, **256'** as described in the foregoing example embodiments.

FIG. **3a** is a view of an example electrode/staple configuration which may be disposed on the inner surface of lower jaw **4a** or lower jaw **40a**. As illustrated, in this example embodiment, this configuration includes two rows of electrodes **30a**, **30b**, two rows of staples **32a**, **32b** and a cutting device **34**. The cutting device **34** is between the rows of staples **32a**, **32b**, and electrodes **30a**, **30b** is outside of the rows of staples **32a**, **32b**. The polarities **36** associated with the respective electrodes are indicated to the left of electrodes **30a**. In this example embodiment, the polarities **36** of the electrodes alternate between positive (“+”) and negative (“-”) along the vertical row of electrodes. In operation, the RF energy applied to the electrodes corresponds the polarities as indicated. The alternating polarities allow for current to pass from one electrode to another where the current travels parallel to the electrode members **30a**, **30b**. In an alternative example embodiment, each row of electrodes may be either all positive or all negative. In this example embodiment, corresponding contacts of opposite polarity may be provided on the upper jaw **4b**.

FIG. **3b** illustrates the electrode and staple configuration of FIG. **3a** on the lower jaw **40b**. The example embodiment illustrated in FIG. **3b** includes the rows of electrodes **30a** and **30b** which during operation receive their charge via current supplied through leads **166**, **168** of flexible shaft **105** from the remote power console **102**, as described above. The polarities associated with the rows of electrodes **30a**, **30b** may vary as described above and illustrated in FIG. **3a**. In one example embodiment, the user controls the movement of flexible shaft **105**, the actuation of jaws, the movement of staples and the polarities and charge associated with the electrodes by using RCU **130** in conjunction with remote power console **102**.

The configuration illustrated in FIG. **3a** may be placed on the inner surface of the lower jaw **4b**, **40b** or disposed on both jaws of surgical device **200**. The electrodes **30a**, **30b** provided may be bipolar and may be arranged in various configurations which create either alternating or opposing polarities as explained below in the various example embodiments described. In operation, the present invention may be used with one row of staples or no staples to enable the closure of tissue.

If the configuration illustrated in FIG. **3a** is used on the inner surfaces of both jaws **4a**, **4b**, the polarities of electrodes may be the same for both jaws **4a**, **4b** which may allow current to flow parallel to the respective columns of electrodes. Alternatively, the polarities of the electrodes may be switch

between the jaws **4a**, **4b**, where opposite polarities may exist for the respective corresponding electrode columns between the jaws **4a**, **4b** which may allow current to flow between jaws **4a**, **4b** once they are in a closed position.

Another example embodiment is illustrated in FIG. **3c**, in which two rows of electrodes **30a** and **30b** are illustrated without any staples or stapling configuration. The example embodiment illustrated in FIG. **3c** solely involves the use of electrodes which may induce an appropriate level of heat in order to coagulate tissue during operation. FIG. **3d** illustrates an alternative electrode configuration. The electrodes are arranged with two electrode rows on each side of cutting device **34**. FIG. **3e** illustrates the dual row of electrode configuration **30a**, **30b** on the inner surface of lower jaw **40b**.

In another example embodiment of the present invention, staple lines may be removed from the electrode configuration as illustrated in FIGS. **3c** and **3d**. FIG. **3d** illustrates four rows of electrodes **30a**, **30b** where two columns are placed on each side of the cutting device **34**. The electrodes may have alternating polarities of RF energy applied in order to produce a current flow. Polarities may alternate vertically, or an entire column of electrodes may be positively charged and the respective adjacent column may be negatively charged in order to induce current flow between the two columns on each respective side of cutting device **34**. As described with the electrode configuration illustrated in FIG. **3a**, the electrode configurations illustrated in FIGS. **3c** and **3d** may be placed on both inner surfaces of jaws **4a**, **4b**. Also, the upper jaw **4a** may incorporate pierceable ampulla and function, as described above, with electrodes **30** as illustrated in FIG. **2f**. In the example embodiments, described above, electrodes configured to pierce tissue are illustrated. Of course, it is also possible to use surface-type electrodes to perform coagulation and/or anastomosing.

FIGS. **4a** and **4b** illustrate two alternative example embodiments of surgical device **200** according to the present invention. The first example embodiment, illustrated in FIG. **4a**, includes a separating jaw system including a lower jaw **4b**, an upper jaw **4a** and a coupling **11**. Coupling **11** includes two hexagonal shaped sockets **556a**, **556b** into which coupling **106** of flexible shaft **105** fits. Each of the sockets is formed in the end of a corresponding horizontal turning shaft **558a**, **558b**. The upper horizontal turning shaft **558a** is coupled, by a transverse gearing member, to a threaded vertical shaft **560** which extends through a correspondingly threaded bore **562** of the upper jaw **4a**. The upper jaw **4a** has a linear track coupling means **566** which corresponds and couples to a linear track **568** formed in the side of the interface end member **554** which is opposite the driver coupling sockets **556a**, **556b**. Subsequent turning of the upper horizontal turning shaft **558a** causes the vertical turning shaft **560** to turn. As this shaft **560** turns, the upper jaw **4a** rides up and down within the track of the end member **554**.

The lower horizontal turning shaft **558b** extends axially through the lower jaw **4b**, which, in turn is fixed to the proximal end member **554**. Mounted around this axially extending shaft **558b** is a wedge driver mechanism **566** which includes a threaded bore. This threaded member **566** is locked within a track **567**, which prevents the member **566** from rotating when the shaft **558b** turns. Rather, the wedge member **566** rides linearly along the track **567** and along the threading of the shaft **558b**. Mounted within a recess **568** in the face of the lower jaw **4b** which opposes the upper jaw **4a** directly above the wedge member **566** is a replaceable tray of staples. The wedge driver has a sloped frontal surface **572** which contacts the staples **282** and causes it to be driven upwardly. When the upper jaw **4a** is in close proximity to the lower jaw **4b**, the

15

staples are closed when they contact the opposing face of the upper jaw **4a** by the action of staple closing guide recesses **576** formed therein.

At the distal tip of the upper and lower jaws are two opposing magnetic sensors **578a**, **578b**, each coupled to a circuit component which connects to the electro-mechanical driver **102** via flexible shaft **105**. When the jaws come together, the circuit is closed, and indicators **108a** and **108b** provide a signal indicating that the staples may be safely fired.

Referring now FIG. **4b**, another example embodiment of the surgical device **200** of the present invention is described. In the example embodiment, the coupling **11** is substantially equivalent to the first example embodiment. As before, the shafts of the driver component turn rotating members within the attachment. In this example embodiment however, both turning members **558a**, **558b** are horizontal. Mounted to the shaft interfacing member is a fixed lower jaw **4b** and a moving upper jaw **4a**. In this example embodiment, the upper jaw **4a** is mounted to the lower jaw **4b** by a spring loaded pivot, which biases the upper jaw **4a** into an open disposition relative to the lower jaw **4b**. Mounted to the upper turning shaft however, is a linearly tracked cuff **587** which seats around the upper and lower jaw, the advancement of which causes the jaws to come together. The lower jaw includes the same staple **574** tray recess and linearly driven threaded wedge staple pushing mechanism **566**. Also, the electromagnetic sensor and circuit of the first example embodiment is included to indicate to the surgeon when the section of tissue has been fully clamped and the staples should be driven.

More particularly, after the surgeon has resected the diseased portion of the tissue, the end of the tissue is placed between the jaws of the attachment. By actuating a trigger and driving the upper shaft, the cuff member **587** advances axially along the outside of the upper and lower jaws **4a**, **4b**, thus closing the upper jaw onto the tissue and lower jaw. Once fully closed, the electromagnetic sensor circuit indicates to the surgeon operator that the staples may be fired, and correspondingly, actuation of the second trigger causes the wedge driver to advance and drive the staples through the tissue section. Reverse rotation of the motor for the upper turning shaft causes the cuff to retract and the upper jaw to open, thus releasing the now-sealed tissue end.

The surgical device **200** as illustrated in FIGS. **4a** and **4b** may also include electrodes used either in conjunction with the stapling mechanism or alone. FIG. **4b** illustrates a row of electrodes **30** disposed along the lower jaw **4b**. The electrodes **30** may receive RF energy through contacts **553**, **555**, similar to the energy transfer to the electrodes of the surgical device **200'** as described above. Furthermore, the example embodiments illustrated in FIGS. **4a** and **4b** may include pierceable ampullae as described above with reference to FIGS. **1d** and **2f**. The surgical device **200** as illustrated in FIGS. **4a** and **4b**, may incorporate the various electrode and/or stapling configurations described above with reference to FIGS. **3a** to **3e**.

FIG. **5a** is a perspective view of the present invention. Upper jaw **4a** and lower jaw **4b** are attached to a shaft **11** which connects to an electro-mechanical device **6**. In operation, these jaws **4a**, **4b** are closed in order to coagulate and cut tissue positioned between them. As illustrated, the jaws **4a**, **4b** are attached to a first end of shaft **11** wherein the second end of shaft **11** connects to the electro-mechanical device **6**. The electro-mechanical device **6** controls the movement of shaft **11** and jaws **4a**, **4b**. The shaft **11** may be flexible or rigid and may enable the mechanical actuation of the jaws **4a**, **4b**. The jaws **4a**, **4b** may include electrode members **3a**, **3b** on the inner surface of lower jaw **4b**, or the electrode members **3a**, **3b** may be provided on both jaws **4a** and **4b**. The electrode

16

members **3a**, **3b** provided on the lower jaw **4b** may be bipolar and may be arranged in various configurations which create either alternating or opposing polarities. In operation, the present invention may be used with one row of staples or no staples to enable the closure of tissue. The jaws **4a**, **4b** mechanically and electrically accomplish the desired functions, i.e., cutting and coagulating tissue.

The second end of the shaft **11**, illustrated in FIG. **5a**, connects to electro-mechanical device **6**, illustrated in FIG. **5b**, at a shaft connection **7**. The shaft **11** includes cables which transmit signals that control the movement of the DLU and the actuation of jaws **4a**, **4b**.

FIG. **5b** illustrates other components of front panel **9**, including a display device **8** and indicators **10a**, **10b** which provide positioning information to the user.

FIG. **6** illustrates an electrode configuration according to the present invention. This electrode configuration may be provided on the inner surface of lower jaw **4b** or on both jaws **4a**, **4b**. The inner surface of lower jaw **4b** includes two columns of electrode members **3a**, **3b**, two staple lines **2a**, **2b** and a cutting blade **12**. The cutting blade **12** is between the staple lines **2a**, **2b** and electrode members **3a**, **3b** is outside of the staple lines **2a**, **2b**. The polarities associated with the respective electrodes are indicated to the left of electrode members **3a**. The polarities of the electrodes alternate between + and - along the vertical column of electrodes. In operation, the RF energy applied to the electrodes corresponds to the polarities as indicated. The alternating polarities allow for current to pass from one electrode to another where the current travels parallel to the electrode members **3a**, **3b**.

The upper jaw **4a** may incorporate pierceable ampulla **5**, shown in FIG. **5a**, which may contain fluid for hemostasis. This fluid or matter, e.g., collagen, fibrin, dye, matter configured to effect anastomosis, matter configured to seal tissue and matter configured to effect hemostasis, etc., may be released when the jaws **4a**, **4b** are closed and the electrode members **3a**, **3b** pass through the tissue and into the ampulla **5** thus releasing the fluid. Simultaneously, the electrode members **3a**, **3b** are activated and tissue may be coagulated to induce hemostasis. Sensors may be configured and arranged to monitor the amount of heat provided and duration of application. In another example embodiment, while the current is passing between the electrode members **3a**, **3b**, a driver may advance to form two single rows of staples **2a**, **2b** on either side of the cutting blade **12**. In each of these example embodiments, the stapling mechanism includes a replaceable tray of open staples set within the lower jaw **4b** and a set of corresponding staple guides within the upper jaw **4a**, such that when the linear clamping mechanism is in a closed position, the open staples immediately oppose the corresponding staple guides. The stapling mechanism further includes a wedge pushing system whereby once the linear clamping mechanism is in a closed position, a wedge riding in a channel below the tray of open staples is pushed through the channel. As the wedge moves through the channel, a sloping surface of the wedge pushes the open staples against the corresponding staple guides, thereby closing the staples. After the staples have been closed, the wedge is pulled back through the channel. The second drive extension pushes or pulls the wedge through the channel, depending on the turning direction of the corresponding motor in the electro-mechanical driver, by engaging a threaded horizontal shaft upon which the wedge, having a matching inner thread, rides.

If the configuration illustrated in FIG. **6** is provided on the inner surfaces of both jaws **4a**, **4b**, the polarities of electrode members may be the same for both jaws **4a**, **4b** which may allow current to flow parallel to the respective columns of

electrodes. Alternatively, the polarities of the electrode members may be switch between the jaws **4a**, **4b**, where opposite polarities would exist for the respective corresponding electrode columns between the jaws **4a**, **4b** which would allow current to flow between jaws **4a**, **4b** once they are in a closed position.

In another example embodiment of the present invention, staple lines may be removed from the electrode configuration as illustrated in FIG. 7. FIG. 7 illustrated four rows of electrode members **3a**, **3b**, including two columns are placed on each side of the cutting blade **12**. The electrode members may have alternating polarities of RF energy applied in order to produce a current flow. Polarities may alternate vertically or an entire column of electrodes may be positively charged and the respective adjacent column may be negatively charged in order to induce current flow between the two columns on each respective side of cutting blade **12**. As described with reference to the electrode configuration illustrated in FIG. 6, the electrode configuration illustrated in FIG. 7 may be placed on both inner surfaces of jaws **4a**, **4b**. Also, the upper jaw **4a** may incorporate pierceable ampulla and function, as described above, with electrode members **3a**, **3b** as illustrated in FIG. 7.

FIG. 8 is a side view of the jaws **4a**, **4b**. The electrode members **3** protrude from the lower jaw **4b** and are applied to tissue placed between the jaws in order to perform anastomosing, sealing and/or stapling. Accordingly, the electrodes may be rigid, flexible, elastic, inelastic, planar, non-planar, etc., with regard to the material used for their construction. The electrode members **3** may also have features that may enhance tissue penetrating attributes and electrical contact between any opposing electrodes. Various configurations may be employed to enhance contact with tissue where electrode height, width and density of spacing are adjusted in order to accommodate various tissue thickness and texture.

FIG. 9 illustrates an electrode configuration of another example embodiment of the present invention. As illustrated electrode members **15** are disposed over the inner face of the lower jaw **4b**. The electrodes **15** are charged positively and receptacles **20** are negatively charged (ground) and configured to align with electrodes **15**. This configuration induces current to flow from lower jaw **4b** to the upper jaw **4a** when the jaws **4a**, **4b** are closed. The amount of RF energy transferred between jaws **4a**, **4b** may be varied depending upon whether staples are used in conjunction with the electrodes or if the anastomose is performed solely through the use of the electrode configuration.

FIG. 10 illustrates another example embodiment of the present invention. The electrode configuration illustrated in FIG. 10 provides ultrasonic levels of energy which are transmitted through ultrasonic resonator pins **27** which are configured on the inner surface of the lower jaw **4b**. Similar to the electrodes described above, the ultrasonic pins **27** may be configured in various formations conducive to the type and form of the tissue which is placed between the jaws for coagulation, anastomosing and/or cutting. In addition to the ultrasonic resonator pins **27**, the lower jaw **4b** also includes an ultrasonic transducer **25**. The ultrasonic transducer **25** is configured to generate the ultrasonic energy that resonates through the pins **27**. The ultrasonic resonator pins **27** may be used with or without staples and as described above with reference to the electrode configurations, enable the reduction of the number of staples used and lessen the mechanical force necessary in order to complete coagulation and cutting.

FIG. 11 illustrates another example embodiment of the present invention. The electrodes **29** are configured as surgical barbs. The configuration of electrodes **29** provide for an improved configuration for penetrating tissue. The electrodes

29 may follow the polarity schemes described above in order to apply RF energy to the tissue. The electrodes **29** may be used as illustrated with electrodes arranged on the lower jaw **4b** only, however this surgical barb type electrode may be arranged on the inner surface of the upper jaw **4a** in order to provide even more effective penetrating results. Furthermore, as described above, pierceable ampulla **5** may be provided in the upper jaw **4a** and used to induce hemostasis.

Those skilled in the art will appreciate that numerous modifications of the example embodiment described hereinabove may be made without departing from the spirit and scope of the invention. Although example embodiments and/or example methods of the present invention have been described and disclosed in detail herein, it should be understood that this invention is in no sense limited thereby and that its scope is to be determined by that of the appended claims.

What is claimed is:

1. A method for performing a procedure on tissue of a body, comprising:

providing an electro-mechanical surgical device, including:

a first jaw;

a second jaw opposing the first jaw, the first jaw and the second jaw configured to clamp tissue therebetween;

a plurality of ultrasonic resonator pins arranged on at least one of the first jaw and the second jaw; and

an ultrasonic transducer configured to supply ultrasonic energy to the plurality of ultrasonic resonator pins;

relatively moving the first jaw and the second jaw to clamp tissue therebetween and to bring the plurality of ultrasonic resonator pins into contact with the tissue clamped between the first jaw and the second jaw; and

supplying electrical energy to the plurality of ultrasonic resonator pins to at least one of coagulate, anastomose and cut the tissue clamped between the first jaw and the second jaw.

2. The method according to claim 1, wherein the step of supplying electrical energy includes supplying ultrasonic energy.

3. The method according to claim 2, wherein the plurality of ultrasonic resonator pins are arranged on the second jaw, and wherein the second jaw of the electro-mechanical surgical device includes the ultrasonic transducer, the method further comprising the step of the ultrasonic resonator generating the ultrasonic energy.

4. The method according to claim 3, further comprising the step of resonating the ultrasonic energy through the plurality of resonator pins.

5. The method according to claim 1, wherein the electro-mechanical surgical device further includes at least one sensor, and wherein the method further includes the step of sensing a temperature of the tissue.

6. The method according to claim 5, further comprising the step of the sensor transmitting a signal to indicate the temperature of the tissue.

7. The method according to claim 1, further comprising the step of adjusting at least one of a height, a width and a density of a spacing of the plurality of resonator pins.

8. A method for performing a procedure on tissue of a body, comprising:

providing an electro-mechanical surgical device, including:

a first jaw;

a second jaw opposing the first jaw, the first jaw and the second jaw configured to clamp tissue therebetween; and

19

a plurality of ultrasonic resonator pins arranged on at least one of the first jaw and the second jaw; relatively moving the first jaw and the second jaw to clamp tissue therebetween and to bring the plurality of ultrasonic resonator pins into contact with the tissue clamped between the first jaw and the second jaw; and supplying electrical energy to the plurality of ultrasonic resonator pins to at least one of coagulate, anastomose and cut the tissue clamped between the first jaw and the second jaw.

9. The method according to claim 8, wherein the step of supplying electrical energy includes supplying ultrasonic energy.

10. The method according to claim 9, wherein the plurality of ultrasonic resonator pins are arranged on the second jaw, and wherein the second jaw of the electro-mechanical surgical device includes an ultrasonic transducer configured to supply ultrasonic energy to the plurality of ultrasonic resonator pins; the method further comprising the step of the ultrasonic resonator generating the ultrasonic energy.

20

11. The method according to claim 10, further comprising the step of resonating the ultrasonic energy through the plurality of resonator pins.

12. The method according to claim 8, wherein the electro-mechanical surgical device includes an ultrasonic transducer configured to supply ultrasonic energy to the plurality of ultrasonic resonator pins.

13. The method according to claim 8, wherein the electro-mechanical surgical device further includes at least one sensor, and wherein the method further includes the step of sensing a temperature of the tissue.

14. The method according to claim 13, further comprising the step of the sensor transmitting a signal to indicate the temperature of the tissue.

15. The method according to claim 8, further comprising the step of adjusting at least one of a height, a width and a density of a spacing of the plurality of resonator pins.

* * * * *

专利名称(译)	双极或超声手术装置		
公开(公告)号	US8845665	公开(公告)日	2014-09-30
申请号	US13/967441	申请日	2013-08-15
[标]申请(专利权)人(译)	柯惠有限合伙公司		
申请(专利权)人(译)	COVIDIEN LP		
当前申请(专利权)人(译)	COVIDIEN LP		
[标]发明人	WHITMAN MICHAEL P		
发明人	WHITMAN, MICHAEL, P.		
IPC分类号	A61B17/32 A61B18/14 A61B17/3201 A61B5/00 A61B5/01 A61B17/072 A61B17/28 A61B17/285 A61B18/00 A61B18/12 A61B19/00 A61N7/02		
CPC分类号	A61B18/1442 A61N7/02 A61B5/01 A61B17/320068 A61B5/4836 A61B2018/1425 A61B17/320092 A61B2019/448 A61B17/07207 A61B18/1477 A61B2018/145 A61B17/285 A61B17/068 A61B90/98 A61B2017/320069 A61B2017/320071 A61B2017/320094 A61B2017/320095 A61B2017/320097		
优先权	60/285113 2001-04-20 US 60/289370 2001-05-08 US		
其他公开文献	US20140018802A1		
外部链接	Espacenet USPTO		

摘要(译)

机电手术装置，系统和/或方法可包括壳体，至少两个相对的钳口，以及与至少一个钳口相关联的至少一个电触头。电触头可以包括双极电触头和超声电触头中的至少一个。电触点可以是位于一个或所有钳口上的一排电极。传感器还可以与位于钳口之间的任何组织相关联，以感测和报告该组织的温度。包含流体的可刺穿壶液也可以放置在至少一个钳口上，使得当钳口处于闭合位置时，流体可释放，并且电极穿过组织进入可刺穿的壶腹。

