




US 20190282161A1


(19) **United States**(12) **Patent Application Publication**
Johnson et al.(10) **Pub. No.: US 2019/0282161 A1**(43) **Pub. Date: Sep. 19, 2019**(54) **METHOD OF SAMPLING SYSTEMIC
BIOMARKERS**(71) Applicant: **Bohnas Innovations LLC**, Coeur
d'Alene, ID (US)(72) Inventors: **Casey Johnson**, Coeur d'Alene, ID
(US); **Doran Thomas**, Post Falls, ID
(US); **Greg Bauer**, Post Falls, ID (US)(73) Assignee: **Bohnas Innovations LLC**(21) Appl. No.: **16/433,904**(22) Filed: **Jun. 6, 2019****Related U.S. Application Data**(63) Continuation of application No. 16/422,447, filed on
May 24, 2019, which is a continuation of application
No. 14/726,322, filed on May 29, 2015.**Publication Classification**(51) **Int. Cl.****A61B 5/00** (2006.01)**A61B 5/083** (2006.01)**A61B 5/097** (2006.01)(52) **U.S. Cl.**CPC **A61B 5/4821** (2013.01); **A61B 5/097**
(2013.01); **A61B 5/0836** (2013.01)





(57)

ABSTRACT

A method including a step of preparing a sampling apparatus for use. The sampling apparatus includes a tubular member having an opening on a distal end thereof. An orientation of the distal end of the tubular member is shapeable. The distal end is substantially rigid so as to maintain a manipulated shape after a direct application of a threshold level of force on the distal end of the tubular member. The tubular member also includes a joint member disposed on a proximal end of the tubular member. The joint member is configured to connect the tubular member to a systemic biomarker sampling device.










FIG. 3A




FIG. 4A




FIG. 3B




FIG. 4B




FIG. 3C




FIG. 4C




FIG. 3D




FIG. 4D




FIG. 3E




FIG. 4E





FIG. 5







FIG. 6B






FIG. 8




FIG. 9A




FIG. 9B




FIG. 9C




FIG. 9D




FIG. 10

METHOD OF SAMPLING SYSTEMIC BIOMARKERS

RELATED APPLICATIONS

[0001] This application claims priority to and is a continuation of U.S. patent application Ser. No. 16/422,447, filed on May 24, 2019, which is a continuation of U.S. patent application Ser. No. 14/726,322, filed on May 29, 2015, the entire contents of which are incorporated herein by reference.

BACKGROUND

[0002] In dental procedures during which either sedation or General Anesthesia (GA) is required, a patient may wear a nasal mask or hood via which a gas, such as oxygen or nitrous oxide, is administered to the patient. The nasal mask or hood may be a non-latex, soft, thermal plastic elastomer that covers the nose and is secured to the face via a gravitational pull of a bilateral inspiratory and gas scavenging suction system that hangs from around the patient's head and over the nose while in the recumbent position. Alternatively, other methods of sedation are accomplished without a nasal hood, such as a combination of nasal cannula for oxygen with oral, intramuscular, or submucosal modes of anesthetic delivery. During procedures that deliver anesthetics, it is important that the patient's airway and the delivery of gases are monitored closely because, in some instances, the effects of sedatives, narcotics, and the majority of general anesthetics decrease respiratory drive and can cause brief or prolonged periods of apnea.

[0003] It is well documented and widely accepted that the implementation of capnography increases the margin of safety for delivery of anesthesia. Capnography is the monitoring of the concentration of end tidal carbon dioxide ("ETCO₂") or exhaled carbon dioxide ("CO₂") of a patient in order to assess the physiological status and/or determine the adequacy of ventilation when under anesthesia. Nevertheless, due to the currently existing difficulties associated with monitoring ETCO₂, particularly within dentistry due to the tools and work occurring in the mouth of the patient, practitioners do not commonly monitor ETCO₂.

[0004] In addition to monitoring ETCO₂, operators may be further interested in accurately sampling for and/or detecting the levels of other systemic biomarkers found within exhaled breath of a person under sedation or GA in order to assess a patient's status. Therefore, a means to accurately detect and monitor systemic biomarkers, such as ETCO₂, within exhaled breath is desirable.

BRIEF DESCRIPTION OF THE DRAWINGS

[0005] The Detailed Description is set forth with reference to the accompanying figures. In the figures, the left-most digit(s) of a reference number identifies the figure in which the reference number first appears. The use of the same reference numbers in different figures indicates similar or identical items. Furthermore, the drawings may be considered as providing an approximate depiction of the relative sizes of the individual components within individual figures. However, the drawings are not to scale, and the relative sizes of the individual components, both within individual figures and between the different figures, may vary from what is depicted. In particular, some of the figures may depict components as a certain size or shape, while other figures

may depict the same components on a larger scale or differently shaped for the sake of clarity.

[0006] FIG. 1A illustrates a side view of an example of an exhaled breath sampling apparatus.

[0007] FIG. 1B illustrates a front cross-sectional view at line I-I of the tubular member of the example exhaled breath sampling apparatus in FIG. 1A.

[0008] FIG. 1C illustrates a side view of another example of an exhaled breath sampling apparatus.

[0009] FIG. 1D illustrates a front cross-sectional view at line II-II of the tubular member of the example exhaled breath sampling apparatus in FIG. 1D.

[0010] FIG. 2A illustrates a side view of another example of an exhaled breath sampling apparatus.

[0011] FIG. 2B illustrates a side view of another example of an exhaled breath sampling apparatus.

[0012] FIG. 2C illustrates a side view of another example of an exhaled breath sampling apparatus.

[0013] FIG. 2D illustrates a side view of another example of an exhaled breath sampling apparatus.

[0014] FIG. 3A illustrates an exploded, side view of an example of a proximal end of a tubular member of an exhaled breath sampling apparatus.

[0015] FIG. 3B illustrates an exploded, partial-cross-sectional side view of another example of a proximal end of a tubular member of an exhaled breath sampling apparatus.

[0016] FIG. 3C illustrates an exploded, partial-cross-sectional side view of another example of a proximal end of a tubular member of an exhaled breath sampling apparatus.

[0017] FIG. 3D illustrates an exploded, side view of another example of a proximal end of a tubular member of an exhaled breath sampling apparatus.

[0018] FIG. 3E illustrates an exploded, side view of yet another example of a proximal end of a tubular member of an exhaled breath sampling apparatus.

[0019] FIG. 4A illustrates an exploded, side view of an example of a distal end of a tubular member of an exhaled breath sampling apparatus.

[0020] FIG. 4B illustrates an exploded, partial-cross-sectional side view of another example of a distal end of a tubular member of an exhaled breath sampling apparatus.

[0021] FIG. 4C illustrates an exploded, partial-cross-sectional side view of another example of a distal end of a tubular member of an exhaled breath sampling apparatus.

[0022] FIG. 4D illustrates an exploded, partial-cross-sectional side view of another example of a distal end of a tubular member of an exhaled breath sampling apparatus.

[0023] FIG. 4E illustrates an exploded, partial-cross-sectional side view of another example of a distal end of a tubular member of an exhaled breath sampling apparatus.

[0024] FIG. 5 illustrates a partial-cross-sectional side view of another example of an exhaled breath sampling apparatus.

[0025] FIG. 6A illustrates an example of a modified connector used in an existing nasal hood so as to permit connection of an exhaled breath sampling apparatus.

[0026] FIG. 6B illustrates the connector component of FIG. 6A.

[0027] FIG. 7 illustrates an alternative example of an exhaled breath sampling apparatus connected to an existing nasal mask.

[0028] FIG. 8 illustrates a perspective view of an alternative example of an exhaled breath sampling apparatus.

[0029] FIG. 9A illustrates a perspective view of an alternative example of an exhaled breath sampling apparatus paired with an existing dental product.

[0030] FIG. 9B illustrates a top cross-sectional view of the alternative example of the exhaled breath sampling apparatus in FIG. 9A.

[0031] FIG. 9C illustrates a perspective view of an alternative example of an exhaled breath sampling apparatus paired with an existing dental product.

[0032] FIG. 9D illustrates a top cross-sectional view of the alternative example of the exhaled breath sampling apparatus in FIG. 9C.

[0033] FIG. 10 illustrates an example of a method of monitoring systemic biomarkers according to the instant application.

DETAILED DESCRIPTION

Overview

[0034] This disclosure is directed to a method and apparatus that may be used in monitoring the presence of and/or concentration of a systemic biomarker, such as ETCO_2 or exhaled CO_2 , in the exhaled breath of a patient, in order to assess the physiological status and/or determine the adequacy of ventilation during a procedure that may involve sedation or GA. The embodiments are described with specificity in order to meet statutory requirements. However, the description itself is not intended to limit the scope of this patent. Rather, the inventors have contemplated that the claimed invention might also be embodied in other ways, to include different elements or combinations of elements similar to the ones described in this document, in conjunction with other present or future technologies.

[0035] The sampling apparatus described herein may be structured to be inserted into a patient's mouth and/or connect to another device to sample exhaled breath from a patient's nose and/or mouth. Accordingly, the sampling apparatus may include a tubular member (also called "a sampling line") and a connector attached to the tubular member. The tubular member permits the flow of exhaled breath to go from the patient to a monitoring device, where a systemic biomarker, such as ETCO_2 exhaled by the patient, is monitored for the safety of the patient. Systemic biomarkers may include, for example, ETCO_2 , nitric oxide, moisture, humidity, temperature, acids, ketones, or other gases, elements, or characteristics found in or associated with exhaled human breath. A biomarker that may be particularly useful is CO_2 , since the average indoor CO_2 levels range from 400-2000 ppm, whereas exhaled CO_2 levels range around 38,000 ppm.

[0036] The tubular member may be manufactured such that at least a portion thereof is manipulable and has plastic material properties so as to be deformable continuously and permanently in any direction without rupture. This manipulable feature provides the operator of the apparatus, e.g., the anesthesiologist, dentist, or other medical personnel, the ability to alter the shape and orientation of the apparatus to better position apparatus where it may more consistently monitor the systemic biomarker, such as ETCO_2 .

[0037] Other advantages of the sampling apparatus relate to its versatility including, but not limited to, being connectable to or integral with, a nasal mask, a nasal hood, an oral airway, and a dental Isolite® system. Furthermore, in embodiments described below, the sampling apparatus

samples exhaled air from both the nose and mouth. An additional advantage is that in embodiments, a length of the sampling apparatus may be quickly and easily adjustable to accommodate the different sizes of patients.

[0038] Various embodiments allow for different means of connection between the components of the sampling apparatus itself, between the sampling apparatus and the systemic biomarker sampling device, and the sampling apparatus and the procedural apparatus with which the sampling apparatus may be coupled.

[0039] Sometimes, using the current methods of practice monitoring ETCO_2 during a procedure, issues and problems related to reliability, and potentially dangerous situations occur. Moreover, patients may even alternate breathing through the nose and the mouth. In such an instance, a nasal sampling line alone will not reliably sample and/or detect exhaled air coming from the mouth. The sampling apparatus of the instant application helps to eliminate or minimize the occurrence of such situations. Namely, the sampling apparatus helps to avoid kinking or occlusions of the sampling line (which may be crafted from, for example, intravenous catheter or extension tubing). Further, the sampling apparatus may eliminate the situation where sampling line is taped to the patient's facial skin. In some instances, hypodermic needles are broken during current procedures and used to puncture the nasal mask so as to insert tubing therein and sample the CO_2 . In such situations, the patient may be subject to a possible cut or abrasion from the broken end of the needle. Accordingly, the embodiments of the sampling apparatus of the instant application, as detailed herein, may provide several advantages over the current methods of monitoring CO_2 .

[0040] Multiple embodiments of an apparatus that may be used to achieve the desired effects of the instant application, including the ability to reliably sample and detect a systemic biomarker, such as CO_2 , are described herein below with respect to FIGS. 1A-9B. Note, throughout the specification the terms "proximal" and "distal" appear several times. Unless otherwise specified, "proximal" refers to the side of the sampling apparatus closer to the end that connects to the systemic biomarker sampling device 150 (FIGS. 1A and 1C), such as an ETCO_2 monitor, and "distal" refers to the side of the apparatus closer to the opposite end of the sampling apparatus which receives the exhaled breath from the patient.

First and Second Illustrative Embodiments

[0041] Inasmuch as the features of FIGS. 1A and 1C are substantially similar, the components of each figure are herein below discussed simultaneously, with the exception of any specific feature that is unique to either one of the figures. Accordingly, substantially similar components are described as, for example, "connector 102A, 102C," which indicates that the connector on each of the figures may be generically described, insofar as they are similar unless explicitly stated otherwise.

[0042] Thus, FIGS. 1A-1D illustrate an example sampling apparatus 100A, 100C that may include a tubular member 102A, 102C having a plurality of openings 105 (fenestrations) on the distal end, via which exhaled breath may be sampled from a patient. It is noted that for the sake of simplicity in the drawings, only FIGS. 1A and 1C show an embodiment including a plurality of openings 105 in the distal end of the device. Nevertheless, it is contemplated that

any of the embodiments shown or discussed in this application may include either a single opening or more than one opening. Although it may be possible to use a device of the instant application that only has one opening **105**, there may be advantages to having a plurality of openings **105**, which may not be achievable with a single opening.

[0043] The tubular member **102A**, **102C** may be a piece of tubing, for example, of medical grade tubing. A connector **104A**, **104C** may be attached to a proximal end of the tubular member **102A**, **102C**. The connector **104A**, **104C** may connect to an extension tube (not shown) leading to a systemic biomarker sampling device **150**, or may directly connect to the sampling device. The means of connection implemented by the connector **104A**, **104C** may vary according to user preference, method of manufacture, or common connections available such as a LuerLok® type of connection, for example. See some additional examples of types of connections considered in FIGS. **3A-4E**. When in use, a pump or other means may create a suction force through the tubular member **102A**, **102C** to sample the patient's breath through the tubular member **102A**, **102C** at the sampling device, whereby the sampling device may monitor a level of a biomarker, such as ETCO_2 , within the breath.

[0044] Additionally, the apparatus **100A**, **100C** may include a cap **106A**, **106C** having one or more corresponding openings therethrough and may be disposed to align with the one or more openings **105** on the distal end of the tubular member **102A**, **102C**. The cap **106C**, as shown in FIG. **1C**, may have a soft, gradual, rounded edge on the distal end thereof, and may be tapered in the longitudinal direction thereof such that the cross-sectional area of the proximal end of the cap **106C** is larger than the cross-sectional area of the distal end of the cap **106C**. The tapered and rounded features of cap **106C** may serve multiple purposes, including, but not limited to comfort of the patient on which the apparatus is used and convenience of the operator, respectively. For example, the soft, rounded edges on the distal end of the cap may prevent harm or annoyance to a patient when placed in a patient's mouth or near the patient's face, when compared with a tube having a rough edge. Further, as discussed in greater detail below, the tapered shape may act as a connector in embodiments, as it creates a wider proximal area on the cap than the distal area of the cap. The wider surface area surrounding the tubular member may act as a back-stopping surface to prevent accidental removal of the tubular member (described in greater detail herein below with respect to FIG. **7**). Alternatively, the tubular member **102A**, **102C** may not have a cap, and instead the distal end of the tubular member may be shaped in a tapered manner itself or may be left as originally manufactured (not shown). In the case where no cap is used, the risk of having the cap come off and enter the patient's body is eliminated.

[0045] In the embodiments shown in FIGS. **1A** and **1C**, the respective distal ends thereof are bent such that the distal end is oriented transversely to a main direction of extension of the majority of the tubular member **102A**, **102C**. Note, however, the tubular members **102A**, **102C** may be temporarily pre-shaped during manufacturing to be straight or to include a curved or hooked shape, for example, which may ease the placement of the tubular member **102A**, **102C** within a patient's mouth at the time of use in a manner that is out of the way of the work being done in the patient's mouth.

[0046] Additionally and/or alternatively, the tubular member **102A**, **102C** may include a manipulable characteristic or component, so that at least a portion of the tubular member **102A**, **102C** is shapeable and yet substantially rigid so as to maintain a manipulated shape upon a direct application of a threshold level of force on the portion of the tubular member **102A**, **102C**. The threshold force, which may be applied by an operator to alter the shape of the portion of the tubular member **102A**, **102C**, is that force sufficient to overcome the inherent resistance force from a property of rigidity associated with the chosen material that is used to manufacture the manipulable characteristic of the tubular member **102A**, **102C**. The term "substantially rigid" is intended to convey the meaning that, while the orientation of the tubular member **102A**, **102C** may be altered under a deliberate act of a threshold force by an operator, the rigidity of the tubular member **102A**, **102C** is such that it is not so limp or flimsy as to bend and flex into a different orientation under the mere presence of a gravitational force, for example, when lifted or shifted from a resting state.

[0047] As an example of the manipulable characteristic or component, in FIG. **1A**, the material of the tubular member **102A** may have properties such that a shape of the tubular member **102A** itself is manipulable due to the material forming the tubular member **102A**. Materials that may be used for the manipulable material may include, for example, ductile or malleable metals such as aluminum, pliable plastics, rubber, and some ceramics, or a combination thereof.

[0048] In an alternative example embodiment, instead of, or in addition to, the material of the tubular member itself being manipulable, a distinct manipulable member **108** may be molded, manufactured, embedded, inserted, or otherwise attached to either an inside or an outside of the wall of the tubular member **102C**, or disposed within the wall of the tubular member **102C**, as shown in FIG. **1C**. For example, the manipulable member **108** may be disposed in the wall of the tubular member **102C** adjacent lumen **110**. Similar to having a manipulable material, as described with respect to FIG. **1A**, the manipulable member **108** enables the operator to adjust the size, shape, position, and/or direction of extension of at least the distal end of the tubular member **102C**, so as to be able to place the tubular member **102C** within, on, or around the mouth of a patient.

[0049] In embodiments, the manipulable member **108** may include a wire, rod, strip, bar, or another section of metal, plastic, ceramic, rubber, or other suitable material. The material of the manipulable member **108** may be such that the manipulable member **108** is pliable and, when the apparatus **100C** is used to sample and/or detect a biomarker during a procedure, the manipulable member **108** may be manipulated to form a curved distal end, such as a quarter round, or a hook shape, if the operator desires. Additionally, the length of the manipulable member **108** may be such that the manipulable member **108** extends:

[0050] 1) throughout the entire length of the tubular member **102C**;

[0051] 2) at least along the distal end of the tubular member **102C** (see for example FIGS. **2A-2D**); or

[0052] 3) for a portion less than the entire length of the tubular member **102C** and located away from the ends thereof, such as at a middle portion between the distal and proximal ends (not shown).

[0053] An advantage of the manipulable member **108** in the distal end of the tubular member **102A**, **102C** is that the

operator may place the sampling apparatus **100A**, **100C** between a patient's teeth and cheek so that the mouth cavity is free of obstructions during the procedure. Thusly, the distal end of the tubular member **102A**, **102C** is positioned to suction the patient's breath and monitor a predetermined biomarker in the breath via the intake into lumen **110**.

[0054] Inasmuch as the manipulable member **108** is adjacent the first lumen **110**, the manipulable member **108** may be disposed in a second lumen in the wall of lumen **110** so as to extend parallel with lumen **110**, as shown more clearly in FIG. 1D. As indicated above, alternatively, the manipulable member **108** may be attached directly to an inner surface of the lumen **110** or an outer surface of the tubular member **102C**; or the manipulable member **108** may simply be embedded in the wall of the lumen **110**, as it appears in FIG. 1D.

[0055] In comparison, FIG. 1B shows a cross-sectional view of the tubular member **102A** in FIG. 1A as a solitary lumen having a substantially uniform wall thickness, whereas FIG. 1D shows a cross-sectional view of tubular member **102C** with lumen **110** as a first lumen, or a solitary lumen, and manipulable member **108** embedded in the wall or inserted into a second lumen large enough to secure the manipulable member **108**.

Third-Sixth Illustrative Embodiments

[0056] In FIGS. 2A-2D, various alternative embodiments of the sampling apparatus **200A-200D** are shown. Inasmuch as several of the features found in the various embodiments of FIGS. 2A-2D are similar with respect to each other, as well as with respect to some features in FIGS. 1A-1D, the similar features are described briefly together. Features in individual FIGS. 2A-2D that are unique to the respective embodiment or distinct from other depicted embodiments, however, may be described explicitly and separately below for clarity.

[0057] Generally, each apparatus (**200A-200D**) may include:

- [0058] a first tubular member (**202A-202D**),
- [0059] a joint member (**204A-204D**),
- [0060] a cap (**206A-206D**),
- [0061] a manipulable member (**208A-208D**),
- [0062] a second tubular member (**210A-210D**),
- [0063] a connector (**212A-212D**),
- [0064] a sampling return line (**214A-214D**),
- [0065] length measurement indicator marks (shown on FIGS. 2D, 3A, and 3B-4E).

First Tubular Member

[0066] Inasmuch as the first tubular members **202A-202D** shown in FIGS. 2A-2D may be similar to the tubular members **102A**, **102C** in FIGS. 1A, 1C, the details of the first tubular members **202A-202D** are not reiterated again here. It is noted, however, that in order to accommodate different sizes of patients, the first tubular members **202A-202D** may be detachable from the respective joint members **204A-204D** to be able to adjust the length thereof. The adjustability of the tubular members is discussed in greater detail herein below.

Joint Member

[0067] In embodiments, a sampling apparatus may include a joint member **204A**, as shown in FIG. 2A, which has a

T-shape. Specifically, the first tubular member **202A** extends from one side arm of the T-shape joint member **204A**, and the second tubular member **210A** extends from the other opposing side arm of the T-shape joint member **204A** so as to extend collinearly with the first tubular member **202A**. The sampling return line **214A**, therefore, extends from the stem portion of the T-shaped joint member **204A**, which is transverse to the arms of the T-shape.

[0068] In embodiments, a sampling apparatus may include a joint member **204B**, as shown in FIG. 2B, where the joint member **204B** may have a tubular shape so as to connect the first tubular member **202B** collinearly with the sampling return line **214B**. The joint member **204B** may further include a hole in which the second tubular member **210B** is adjoined, whereby the suction on the sampling return line **214B** draws exhaled breath from both the first and second tubular members **202B** and **210B**.

[0069] In other embodiments, a sampling apparatus may include a joint member **204C**, as shown in FIG. 2C, where the joint member **204C** may be a joint that is formed at the time of manufacture, as an integral, Y-shaped union of the first and second tubular members **202C** and **210C** and the sampling return line **214C**. In other words, the joint member **204C** may not be a separate component, to which ends of the first and second tubular members **202C** and **210C** and the sampling return line **214C** are secured, as is depicted in FIGS. 2A and 2B. Rather, instead, the merging of the first and second tubular members **202C** and **210C** and the sampling return line **214C** may be a single component formed either entirely together or as a composite united at the time of manufacture.

[0070] Further still, in other embodiments, such as the embodiment shown in FIG. 2D, the joint member **204D** is a Y-shaped component into which the ends of the first and second tubular members **202D** and **210D** and the sampling return line **214D** are secured to one of the three branches of the Y-shaped joint member **204D**.

Cap

[0071] Inasmuch as the features of the cap **206A-206D** shown in FIGS. 2A-2D may be similar to the cap **106A**, **106C** in FIGS. 1A, 1C as depicted, the details of the cap **206A-206D** are not reiterated again here. It is noted, however, that when a cap is implemented, the risk of harm to a patient may be reduced when the cap is completely affixed to the tubular member so that there is little or no chance of the cap coming off into the patient during use. For example, the cap could be glued on or otherwise formed to be permanently attached to the tubular member. Alternatively, as previously indicated, a cap may not always be implemented in every embodiment.

Manipulable Member

[0072] Manipulable members **208A-208D** may be disposed, respectively, within the first tubular members **202A-202D**, in a manner similar to that shown in FIG. 1C, and as described above. Thus, the details of the manipulable members **208A-208D** are not reiterated again here. Note, while the manipulable members **208A-208D** are depicted as not extending throughout the entire length of the respective tubular members **202A-202D** and therefore differ from the manipulable member **108** shown in FIG. 1C, it is contemplated that within the depicted embodiments, the manipu-

lable members **208A-208D** may, alternatively, extend throughout an entirety of the respective tubular members **202A-202D**.

[0073] Furthermore, although explicitly depicted as a distinct element for the sake of clarity, the manipulable members **208A-208D** may be integral elements of the first tubular members, for example, as the actual material of the tubular members.

[0074] Additionally, in FIG. 2D, the apparatus **200D** may also include a second manipulable member **218D**, having characteristics like those of the first manipulable member **208D**. As such, the details of the second manipulable member **218D** are not reiterated here again. It is noted, however, that the ability to adjust the manipulable member **218D** facilitates positioning the second tubular member **210D** in a particular location, for example in a nasal mask as described with respect to FIG. 7, as may be necessary during use.

Second Tubular Member

[0075] Additionally, each of the apparatuses **200A-200D**, respectively, may include a second tubular member **210A-210D**, which may be coupled to the respective first tubular member **202A-202D** via the respective joint member **204A-204D**. In practice, the first tubular members **202A-202D** may be used to sample breath exhaled via the patient's mouth, and the second tubular members **210A-210D** may be used to sample breath exhaled via the patient's nose. Specific examples of how the first and second tubular members sample breath from mouth and nose, respectively, is discussed herein below with respect to FIGS. 6A-7.

Connector

[0076] In the embodiments depicted in FIGS. 2A, 2B, and 2C, the respective second tubular members **210A-210C** may have disposed at the distal ends thereof connectors **212A-212C**, respectively, which may be similar to the connectors **104A, 104C** in FIGS. 1A, 1C. Since the second tubular members **210A-210C** may sample the exhaled breath from a patient's nose, the connectors **212A-212C** may be configured to connect to a corresponding connection piece on a nasal mask or hood (see FIGS. 6A and 6B discussed herein below). Further, inasmuch as the connectors **212A-212C** are illustrated simply a generic box, it is contemplated that the connectors **212A-212C** may be of any suitable type to form a secure connection to the nasal mask or hood, including the manners of connection described herein below with respect to the joint members/caps in FIGS. 3A-4E. For example, the connectors **212A-212C** may be threaded, possibly like a Luer-Lok® connection, or may be structured to form a compression fit, an interference fit, a friction fit, or any other connection that permits a gas flow.

[0077] In the embodiment depicted in FIG. 2D, the connector **212D** may appear similar to caps **206A-206D**, however, connector **212D** may function as the connection point between the apparatus **200D** and a nasal mask like the one shown in FIG. 7, and therefore, is considered a connector.

Sampling Return Line

[0078] FIGS. 2A-2D also depict a sampling return line **214A-214D**. The sampling return line **214A-214D** may extend from the respective joint member **204A-204D** to a systemic biomarker monitor device (not shown). Moreover,

the suction that draws exhaled breath from the first tubular member **202A-202D** to the monitor device may also draw exhaled breath from the second tubular member **210A-210D** by way of the joint member **204A-204D**, which joins the first and second tubular members to the respective sampling return line **214A-214D**. Thusly, exhaled breath may be sampled directly from a patient's mouth and nose in order to provide a more accurate assessment of the vital statistics of a patient under anesthesia.

Length Measurement Indicator Marks

[0079] Although not illustrated on the embodiments of FIGS. 2A-2C, the length measurement indicator marks **220D** shown on each of the first and second tubular members **202D** and **210D** may be incorporated on any of the embodiments of FIGS. 2A-2C, as well. Length measurement indicator marks **220D** are shown as disposed along a portion of the length of the first and second tubular members **202D** and **210D**. In view of the different sizes and shapes of people who may need to undergo a procedure in which the apparatus of the instant application may be used, length measurement indicator marks **220D** provide a guideline for an operator to be able adjust the length of either one or both of the first and second tubular members **202D** and **210D**, depending on the measured or estimated size of the mouth and distance to nasal mask of the specific patient. For example, it is possible that the original manufactured size of the apparatus may be too long for the size of the patient's mouth. In this situation, if longer first and second tubular members **202D** and **210D** are used, the extended length may cause the tubular members to get in the way of the operator during the procedure. Accordingly, the operator may desire to shorten the length of the first tubular member (if using an apparatus like the embodiments of FIGS. 2A-2C, for example), or one or both of the first tubular member **202D** and the second tubular member **210D** (if using the embodiment of apparatus **200D**), to minimize any amount of excess tubing around the patient's face.

[0080] The length measurement indicator marks **220D** may be marked in increments of millimeters, centimeters, decimeters, inches, or any other unit of length measurement. Further, the length measurement indicator marks **220D** may be marked only on portion of the tubular members **202D, 210D**, as shown in FIG. 2D, or along an entire length thereof. Alternatively, the length measurement indicator marks **220D** may be disposed, for example, along either the proximal end the tubular members **202D, 210D** (as shown) or the distal end the tubular members **202D, 210D**, or both. Thus, an operator may measure the interior length of the distance from the back of a patient's mouth on the cheek side to the front of the patient's mouth, for example, and may shorten the total length of the apparatus **200D** accordingly. Depending on the embodiment used for the apparatus, shortening the length of the tubular member(s) may be accomplished by many ways, including cutting, bending, breaking, snapping, sliding, etc.

[0081] In order to minimize the excess tubing, the following steps may be followed. A side of the patient's cheek or the length along the patient's teeth in the mouth may be measured. The first tubular member **202D** from the connector **204D**. Then, using the length measurement indicator marks **220D**, the operator may shorten the first tubular member **202D** to adjust the length thereof for the smaller size patient. By shortening the first tubular member **202D**,

the operator may be able to avoid having excess tubing potentially getting in the way of the work being done on the patient. With regard to the second tubular member 210D, since the second tubular member 210D may be inserted into a hole in a nasal mask, for example, like the one shown in FIG. 7, the operator may measure the distance between the joint member 204D and the hole in the nasal mask on the patient's face. Then, the operator may similarly shorten the second tubular member 210D, if necessary to accommodate a smaller distance as well.

Illustrative Embodiments of Connections at Joint Members and Caps

[0082] Due to the potential need to shorten the tubular members of the apparatus depending on the size of the patient, a manner of easily, effectively, and safely disconnecting and reconnecting the tubular members to either or both of the connectors and caps may be desirable. Inasmuch as a removable cap may pose a health risk to the patient, it may be preferable to not have the cap be removable. However, it is contemplated that the cap may be fixable such that, after adjusting a length of the tubular members, the cap may be replaced and fixed to the tubular member via a fastening means such as adhesive, means shown in the figures, or other means so as to ensure that the cap does not inadvertently get inside the patient.

[0083] FIGS. 3A-3E depict different embodiments of potential connection types that may be used to connect proximal ends of a tubular member (302A-302E) to a connector (304A-304E) of an apparatus (300A-300E) of the instant application. Notably, FIGS. 4A-4E are placed adjacent to the respective FIGS. 3A-3E to depict corresponding connection types between the distal ends of a tubular member (402A-402E) and a cap (404A-404E). Therefore, the descriptions of the connections between the joint members 304A-304E and the tubular members 302A-302E, and the connections between the tubular member 402A-402E and the cap 404A-404E may be substantially similar and are therefore discussed together.

[0084] For the sake of simplicity and clarity in the drawings, of the embodiments in FIGS. 3A-4E, only the embodiment in FIG. 4A is actually depicted with the tubular member 402A having a manipulable member 406A. Regardless, it is understood that one or both ends of the tubular members illustrated in FIGS. 3A-3E and 4B-4E may incorporate a manipulable member. Additionally, it is noted that in an embodiment where a tubular member of an apparatus may be removable from both the joint member on the proximal end and the cap on the distal end, the type of connections used to join the adjacent parts may be different from each other and need not be the same type.

[0085] Specifically, FIGS. 3A and 4A depict an exploded view of a generic tubular member 302A, 402A aligned with a generic joint member 304A and cap 404A, respectively. In FIG. 3A, the tubular member 302A has thereon length measurement indicator marks 306A, while (as mentioned above), FIG. 4A depicts a manipulable member 406A. Additionally, the joint member 304A and cap 404A each are labeled with a reference to an opening 308A and 408A, respectively.

[0086] For convenience, a list of corresponding reference numbers with respect to the common components is provided here. Namely, FIGS. 3B-3E and 4B-4E include a tubular member 302B-302E, 402B-402E, which have

thereon length measurement indicator marks 306B-306E, 406B-406E. FIGS. 3B-3E further include a joint member 304B-304E on the proximal end of the tubular member 302B-302E, respectively, and the joint member 304B-304E is depicted as having attached thereto a secondary tubular member 312B-312E, which may serve as a nasal sampling tubular member. Also depicted in FIGS. 3B-3E and 4B-4E is a connection component 310B-310E and 410B-410E, respectively. The connection components 310B-310E, 410B-410E are discussed in more detail below, however, inasmuch as the manner of connection depicted between the joint members 304B-304E and the respective tubular members 302B-302E is substantially the same as that between the tubular members 402B-402E and respective caps 404B-404E, the connection components 310B-310E, 410B-410E are explained once for simplicity with respect to the components as they are referenced in FIGS. 3B-3E. Any significant differences between the connections formed by the connection components 310B-310E and the connection components 410B-410E are explained accordingly.

[0087] In an embodiment according to FIG. 3B, the connection component 310B may include a flange extending radially, inwardly from an inside wall edge of the distal end of the joint member 304B. Likewise, in FIG. 4B the connection component 410B may include a flange extending radially, inwardly from an inside wall edge of the proximal end of the cap 404B. At least a portion of the length of the outer surface of the tubular member 302B may be shaped to have a side profile that appears like a series of alternating annular ridges and valleys (or a wave-shaped formation, ribs, etc.). In order to maintain the tubular member 302B securely within the respective joint member 304B, the diameter D_{1a} of the opening 308B is less than a diameter D_{2a} of the "ridges," and greater than, or approximately equal to, the diameter D_{2b} of the "valleys." Moreover, the diameter D_{2b} of the interior of the joint member 304B behind the flange (connection component 310B) is greater than the diameter D_{1a} of the opening 308B, so as to accommodate the ridges of the tubular member 302B. Furthermore, a thickness (or width) of the flange 310B approximates the length of the valleys, which is the distance between ridges, so that the flange securely holds the tubular member 302B. The connection formed by connection component 310B. As such, when an end of the tubular member 302B, 402B is inserted into the joint member 304B or cap 404B, the tubular member 302B, 402B flexes slightly so that the ridges push past the flange of the connection component 310B, 410B, and the flange surrounds a valley held in between two ridges, thereby securing the tubular member 302B, 402B. Additionally, the operator may use the length measurement indicator marks 306B to determine how much of the tubular member 302B, 402B may be shortened, if needed.

[0088] In FIGS. 3C and 4C, a compression fit is illustrated as the connection component 310C, 410C. In particular, the diameter D_3 of the interior of the joint member 304C may be less than the outer diameter D_4 of the tubular member 302C. As such, when an end of the tubular member 302C is pressed into the joint member 304C, the tubular member 302C may be secured by compression in the joint member 304C. Further, connection component 310C may also include a tapered edge 310C1 at the entry to the joint member 304C, so as to ease the insertion process between the tubular member 302C and the joint member 304C. The embodiment of the connection component 410C with tapered edge 410C1

between tubular member 402C and cap 404C of FIG. 4C may connect similarly as is depicted and described above with respect to FIG. 3C.

[0089] In FIGS. 3D and 4D, an interference fit is implemented as the manner of connection between the tubular members 302D, 402D and the respective joint member 304D and cap 404D. Interference may be created between at least one or more (as a series) of the connection components 310D, 410D and the interior wall of the tubular member 302D and the cap 304D, respectively. Note, that while the connection components 310D are depicted in FIG. 3D as disposed on an exterior side of the joint member 304D, the connection components 410D are depicted in FIG. 4D as disposed on an exterior side of the tubular member 402D, having measurement indicator marks disposed therebetween. Regardless, the connection components 310D, 410D function similarly. In particular, connection component 310D may include one or more annular, frustoconical-shaped flanges on an exterior surface of the distal end of the joint member 304D. An outer diameter of the frustoconical-shaped flange(s) (connection component 310D) may be larger than the outer diameter D_5 of the joint member 304D and smaller than the diameter D_6 of outer surface of the tubular member 302D, such that, when the tubular member 302D is pressed against the joint member 304D, the frustoconical-shaped flanges 310D interfere with the inner wall of the tubular member 302D, flexing against the wall so as to secure the tubular member 302D to the joint member 304D. The embodiment of the connection component 410D between tubular member 402D and cap 404D of FIG. 4D may connect similarly as is depicted and described above with respect to FIG. 3D. Moreover, the cap 404D may include a tapered edge at the opening 408D to ease insertion of the frustoconical flange(s) 410D.

[0090] In example embodiments, as pictured in FIGS. 3E and 4E, the connection components 310E, 410E may include a threaded surface to make a connection between the tubular member 302E, 402E and the respective joint member 304E and cap 404E. For example, in the embodiment of FIG. 3E, the distal end of the joint member 304E may have a threaded surface, with the diameter D_7 of the threads on the joint member 304E being larger than the inner diameter of the tubular member 302E and smaller than the diameter D_8 of the outer surface of the tubular member 302E. While the interior surface of the tubular member 302E may be threaded to assist in securing the joint member 304E, it need not be threaded, as the threads 310E may be sufficiently sharp and rigid to bite into the material of the tubular member 302E when the tubular member 302E is rotated over the joint member 304E. Alternatively, as shown in FIG. 4E, instead of having threads on the outer surface of the connecting element, the inner surface of the cap 404E is threaded. The smallest diameter of the threaded surface may be smaller than the outer diameter of the distal end of the tubular member 402E, so that the threads inside the cap 404E bite into the outer surface of the tubular member 402E when the cap 404E is rotated about the tubular member 402E, thereby securing the cap 404E to the tubular member 402E.

[0091] Accordingly, as depicted in FIGS. 3E and 4E, a joint member and/or a cap may have internal or external threads, whereby the tubular member may be secured after sizing.

Illustrative Alternative Embodiment of an Adjustable Sampling Apparatus

[0092] FIG. 5 depicts a partial cross-sectional view of an alternative embodiment of an adjustable sampling apparatus 500 that may include a first tubular member 502 having a distinct proximal portion 502A and a distinct distal portion 502B. The partial cross-section is of the end of the proximal portion 502A so as to clearly depict the slidable aspect of this embodiment.

[0093] The proximal portion 502A may extend from the joint member 504. The distal portion 502B may be slidably insertable within the proximal portion 502A. A cap 506 may be attached to the distal portion 502B, and a manipulable element 508 may be an integral part of, disposed on, or disposed within the distal portion 502B. (The manipulable element 508 is only depicted as a visible “component” within the distal portion 502B as a representation of the ability to manipulate the distal portion 502B, and is not intended to exclude an embodiment of the material of the tubular member itself being the manipulable element 508.) As in other embodiments, a second tubular member 510 may be attached to the joint member 504, and the second tubular member 510 may have attached thereto a connector 512. The connector 512 may connect to a nasal hood or mask (not shown). Further, the sampling return line 514 may connect to the joint member 504, as well. The first tubular member 502 may also have thereon length measurement indicator marks 516, which are used to visualize the amount of adjustment of the length of the apparatus 500.

[0094] With regard to the manner of adjusting the length of the embodiment of FIG. 5, FIG. 5 depicts a first sliding component 518 and a second sliding component 520. The first sliding component 518 may include a flange extending radially, inwardly from an inside wall edge of the proximal portion 502A of the first tubular member 502. The second sliding component 520 may include a flange extending radially, outwardly from an outside wall edge of the distal portion 502B of the first tubular member 502. A desired length position between the proximal portion 502A and the distal portion 502B may be maintained by a frictional interference force between the inner wall surface of the proximal portion 502A and the outer peripheral surface of the flange of the second sliding component 520 on the distal portion 502B.

[0095] Inasmuch as the distal portion 502B may be slidable within the proximal portion 502A, a distal surface of the flange of the second sliding component 520 opposes the proximal surface of the first sliding component 518, such that the first and second sliding components 518, 520, respectively are in abutment with each other in a fully extended position so as to prevent removal of the distal portion 502B entirely from the proximal portion 502A. Further, the second sliding component 520 is free to slide from the position of abutment in a direction toward the proximal side of the apparatus 500 so as to shorten a length of the apparatus 500. Sliding may be achieved by pressing or pulling the proximal portion 502A and distal portion 502B with respect to each other, where the pressing or pulling force is a level of force greater than the level of frictional force between the inner wall surface of the proximal portion 502A and the outer peripheral surface of the flange of the second sliding component 520. Additionally, in view of the ability to slide the distal portion 502B within the proximal portion 502A, a material of at least the proximal

portion **502A** may be transparent or translucent so as to permit an operator to view the interior of the proximal portion **502A** and see the end of the distal portion **502B** within the proximal portion **502A** against the length measurement indicator marks **516**, thereby facilitating a length adjustment.

Illustrative Example of an Embodiment of a Sampling Apparatus in Connection with a Nasal Hood

[0096] An example of a nasal hood to which the sampling apparatus of the instant application may be coupled is the Porter Double Mask Scavenger Breathing Circuit (“nasal hood”) marketed by Porter Instrument Division of Parker Hannifin. FIG. 6A depicts the nasal hood **600** that may include a modified connector **602a**, a standard connector **602b**, and a nose port **604**. As depicted, the nasal hood **600** may further include a line-in **600a** via which gas may be administered to a patient through the nose port **604** when in position over a patient’s nose, and a line-out **600b** via which exhaled breath from a patient’s nose may be suctioned out. (See the arrows indicating flow in and out of the nasal hood **600** on the modified connector **602a**.)

[0097] Also depicted in FIG. 6A is a portion of an example sampling apparatus **606**, which may connect to the modified connector **602a** to sample the exhaled breath from the patient’s nose as the breath passes from the line-out **600b** through the modified connector **602a** (explained in more detail with respect to FIG. 6B). The exhaled breath may be sampled via the sampling return line that leads to a systemic biomarker sampling device **650**. Note that the depicted embodiment of the example sampling apparatus **606** may resemble the embodiment illustrated in FIG. 2C, (i.e., the integral Y-shaped joint member **204C** with connector **212C** resemble the portion of the example sampling apparatus **606**). Any such resemblance is coincidental and it is contemplated that any of the aforementioned embodiments of sampling apparatuses may couple with the modified connector **602a**, including, for example, the embodiments of FIGS. 1A, 1C, and 2A-2D. If the embodiment of FIGS. 1A or 1C is coupled to the modified connector **602a**, it is contemplated that the line out **600b** may be connected also to a systemic biomarker sampling device (such as device **650**) in order to sample exhaled breath from the mouth and nose. Furthermore, while the modified connector **602a** is illustrated with a threaded port (discussed further with respect to FIG. 6B) that corresponds to the threaded connector (for example, a LuerLok® connector) on the example sampling apparatus **606**, it is contemplated that the port may be modified to securely engage a cap such as the connector **212D** in the embodiment of FIG. 2D.

[0098] The modified connector **602a** is illustrated in more detail in FIG. 6B. In particular, the modified connector **602a** may include a line-in tube **608** and a line-out tube **610**, which adjoin the line-in **600a** and the line-out **600b** on nasal hood **600**, respectively. A coupler **612** holds the line-in tube **608** and the line-out tube **610** together in a fixed position. At a base of the coupler **612**, a sample joint tube **614** extends through the coupler **612** to the line-out tube **610**. The end of the sample joint tube **614** includes a threaded exterior surface **616** in order to connect the example sampling apparatus **606**. As noted above, however, the sample joint tube **614** may be configured with a secure connection means other than a threaded surface. That is, the coupler **612** and the line-out tube **610** each have a co-aligned hole **618** in which the sample joint tube **614** is disposed so as to form an

additional passageway out of the line-out tube **610** for sampling the breath (note the dashed-arrow line passing from the line-out **610** to the sample joint tube **614**).

[0099] Thus, with the Porter Double Mask Scavenger Breathing Circuit, an operator may replace the standard connector **602b** with a modified connector **602a** according to this application, and thereby connect a sampling apparatus. The modified connector **602a** provides an operator with the ability to sample the systemic biomarkers in the exhaled breath from both the nose and the mouth simultaneously.

Illustrative Example of an Embodiment of a Sampling Apparatus in Connection with a Nasal Mask

[0100] Another example of a nasal mask to which the sampling apparatus of the instant application may be coupled is the Safe Sedate® **700** (“nasal mask”) depicted in FIG. 7. In embodiments, the nasal mask **700** may include a nose port **702**, which has one or more exhaust holes **704**. As illustrated, the nasal mask **700** may be strapped to a patient’s face so that the mouth is clearly accessible. FIG. 7 further depicts an example of a sampling apparatus **200D** (FIG. 2D) being connected to the nasal mask **700**. In particular, the sampling apparatus **200D** may include a first tubular member **202D** and a second tubular member **210D**, and the sampling apparatus **200D** may draw exhaled breath to a systemic biomarker sampling device (such as device **750**). The first tubular member **202D** may be manipulated to have a shape and size so that the first tubular member **202D** is inserted out of the way in the patient’s mouth. Specifically, the first tubular member **202D** may form a hook shape such that the distal end thereof may be placed around the back of the teeth in the patient’s mouth, and the proximal end may extend along a side of the teeth next to the cheek. Further, the second tubular member **210D** may be sized and positioned so as to be able to insert the connector (“cap”) on the distal end of the second tubular member **210D** into an exhaust hole **704** of the nasal mask **700**. As stated above with respect to the cap in FIGS. 1A and 1C, the cross-sectional area of the proximal end of the cap may be larger than the cross-sectional area of the distal end of the cap. Further, the cross-sectional area (i.e., diameter) of the exhaust hole **704** may be smaller than the cross-sectional area of the distal end of the cap. Inasmuch as the material of the nasal mask and/or the material of the cap has elastic properties, an operator may force the cap on the distal end of the second tubular member **210D** through the exhaust hole **704**. Due to the flexing of the material under force, once the proximal side of the cap has squeezed through the narrow area of the hole **704**, the material is released from force and resumes its original shape. Thus, after inserting the cap through the exhaust hole, the wider surface area of the cap surrounding the tubular member may act as a backstopping surface against an inside surface of the nasal mask near the edge of the hole **704**, and may prevent accidental removal of the tubular member.

[0101] Thus, the embodiment of sampling apparatus **200D** in FIG. 2D is well-suited for connection to the Safe Sedate® nasal mask **700**. However, it is contemplated that nasal mask **700** may be modified to include a different means of connection, such as a threaded port, to accommodate a different embodiment of the sampling apparatus.

Illustrative Example of an Embodiment of a Sampling Apparatus in Connection with an Oral Airway

[0102] In yet another embodiment of how a sampling apparatus may be coupled with a product to sample a

patient's exhaled breath, FIG. 8 shows an oral airway **800** having a tube portion **802** (that sits in the patient's mouth) modified with a threaded end **804**. The threaded end **804** may be configured to connect to a sampling apparatus **806** via a connector **808**, which may be similar to a LuerLok® connection, for example, or may be any other type of connection between the sampling apparatus and the oral airway **800**. Thus, the oral airway **800** may be inserted into a patient's mouth, and the exhaled breath may be sampled in a systemic biomarker sampling device (such as device **850**) via the sampling apparatus **806**.

Illustrative Example of an Embodiment of a Sampling Apparatus in Connection with an Isolite System

[0103] In yet another manner of how a sampling apparatus may be coupled with a product to sample a patient's exhaled breath, FIGS. 9A and 9B depict a perspective view and a top view of an Isolite® system **900** ("system") that has been modified to accommodate the addition of an example sampling apparatus **100A**, **100C**, as depicted in FIGS. 1A, 1C. Alternatively, FIGS. 9C and 9D illustrate integrated embodiments, as discussed in detail below.

[0104] Using an integral bite block **902** for the patient to bite down onto with one side of the patient's teeth, the system **900** is a device used in dental practice to provide light and/or suction to a patient's mouth during a procedure. In FIGS. 9A and 9B, the system **900** is depicted as modified to include a hole **904** through the bite block **902**. The tubular member of the example sampling apparatus **100A**, **100C** is disposed through the hole **904** so that the distal end of the tubular member may be located behind the system **900** in the back of the patient's mouth when the system **900** is in place in a patient's mouth. Accordingly, the sampling apparatus **100A**, **100C** is out of the way of the dental work.

[0105] It is noted that the hole **904** was placed in the bite block **902** for convenience and simplicity in the drawings, as well as convenient and simple placement in manufacturing. However, it is contemplated that the hole **904** may be placed through or within any other portion of the system so as to quickly, conveniently, and safely sample systemic biometrics at sampling device **950**. For example, the system **900** may include a sampling line that is embedded within a portion of the main body of the system **900**, as shown in FIGS. 9C and 9D.

[0106] In the embodiment shown in FIGS. 9C and 9D, the system **910** may have a sampling return line **912** extending from a portion of the bite block **902** in a position such that the sampling return line **912** extends through hole **904** into a rib **914** in the main body of the system **910**. The rib **914** may include holes **916** (fenestrations) through the surface of the system **910**, spread along the length of the rib **914** so as to be able to sample breath from the patient.

Illustrative Method of Preparing to Sample a Patient's Exhaled Breath during a Procedure

[0107] In embodiments of the instant application, the steps as shown in FIG. 10 may be performed as a method **1000** to prepare to sample a patient's exhaled breath during a procedure. Step **1002** indicates that the operator may prepare the sampling apparatus for use. Specifically, and in no particular order, the preparation in step **1002** may further include a step **1004** of connecting the sampling return line of the sampling apparatus to the systemic biomarker sampling device. In step **1006**, the operator may couple the sampling apparatus to a procedural device. In step **1008**, the shape of the sampling apparatus may be adjusted to accommodate the

size of the patient, and likewise, in step **1010**, the length of the sampling apparatus may also be adjusted. Steps **1008** and **1010** may further include measuring the patient and accordingly adjusting the sampling apparatus, which may include one or more of bending, cutting, breaking, snapping, sliding, or otherwise adjusting the length or shape of the tubular member(s). When the sampling apparatus is ready, the operator may perform step **1012** of placing the sampling apparatus on the patient. Step **1012** may further include a step **1014** of positioning the sampling apparatus in the patient's mouth. Further, if applicable, the operator may also perform step **1016** which is to attach the sampling apparatus to a nasal mask or hood.

Conclusion

[0108] Although several embodiments have been described in language specific to structural features and/or methodological acts, it is to be understood that the claims are not necessarily limited to the specific features or acts described. Rather, the specific features and acts are disclosed as illustrative forms of implementing the claimed subject matter.

What is claimed is:

1. A connector device, comprising:

- a line coupler including a first coupling portion and a second coupling portion;
- a line-in tube segment disposed in the first coupling portion of the line coupler;
- a line-out tube segment disposed in the second coupling portion of the line coupler; and
- a sample tube segment disposed in a base area of the line coupler, the sample tube segment intersecting the line-out tube segment to create a flow path from the line-out tube segment into the sample tube segment.

2. The connector device according to claim 1, wherein the line coupler secures the line-in tube segment and the line-out tube segment in fixed positions relative to each other.

3. The connector device according to claim 1, wherein the sample tube segment has a threaded portion on an end thereof, the end extending in a direction away from the line coupler.

4. The connector device according to claim 4, wherein the threaded portion of the sample tube segment is threaded to accommodate a luer taper thread configuration.

5. The connector device according to claim 1, wherein the line-out tube segment includes a hole in a sidewall thereof aligned with the sample tube segment.

6. The connector device according to claim 1, wherein the first coupling portion is disposed parallel with the second coupling portion.

7. The connector device according to claim 1, wherein the sample tube segment extends in a direction transverse to a direction of extension of the line-out tube segment.

8. A connector device comprising:

- a line coupler including a first coupling portion and a second coupling portion; and
- a sample tube segment disposed in a base area of the line coupler, the sample tube segment intersecting the second coupling portion to create a flow path from the second coupling portion into the sample tube segment.

9. The connector device according to claim 8, wherein the first coupling portion is shaped to secure a first tube, and the second coupling portion is shaped to secure a second tube.

10. The connector device according to claim 8, wherein the first coupling portion includes a pair of oppositely extending tubular protrusions sized to slip within a line-in tube to form a continuous flow path into a nasal hood apparatus.

11. The connector device according to claim 8, wherein the second coupling portion includes a pair of oppositely extending tubular protrusions sized to slip within a line-out tube to form a continuous flow path away from a nasal hood apparatus.

12. The connector device according to claim 8, wherein the first coupling portion includes a pair of oppositely extending tubular protrusions sized to slip over an outer circumference of a line-in tube to form a continuous flow path into a nasal hood apparatus.

13. The connector device according to claim 8, wherein the second coupling portion includes a pair of oppositely extending tubular protrusions sized to slip over an outer circumference of a line-out tube to form a continuous flow path away from a nasal hood apparatus.

14. The connector device according to claim 8, wherein the sample tube segment includes a threaded outer surface to connect to a sample line for sampling ETCO_2 .

15. A coupling device comprising:

a line-out port including:

a body,

a first opening at a first end of the body, the first opening configured to couple to a line-out tube of a nasal hood,

a second opening through a mid-section thereof, and a third opening at a second end of the body, the third opening configured to couple to secondary line-out tubing; and

a sample line port disposed in fluid communication with the second opening of the line-out port.

16. The coupling device according to claim 15, wherein the sample line port includes a protrusion having an opening therethrough to engage a connection port on a sample tube via which ETCO_2 is monitored.

17. The coupling device according to claim 16, wherein the protrusion is tubular and includes a threaded portion to engage the connection port.

18. The coupling device according to claim 15, wherein the first opening of the line-out port and the third opening of the line-out port are colinear and are tubular and sized to engage via a compression fit within the line-out tube of the nasal hood and the secondary line-out tubing, respectively.

19. The coupling device according to claim 15, further comprising a line-in port coupled to the line-out port, the line-in port including:

a first opening configured to couple to a line-in tube of the nasal hood, and

a second opening configured to couple to secondary line-in tubing.

20. The coupling device according to claim 19, wherein the first opening of the line-in port and the second opening of the line-in port are colinear and are tubular and sized to engage via a compression fit within the line-in tube of the nasal hood and the secondary line-in tubing, respectively.

* * * * *

专利名称(译)	采集系统生物标志物的方法		
公开(公告)号	US20190282161A1	公开(公告)日	2019-09-19
申请号	US16/433904	申请日	2019-06-06
[标]发明人	JOHNSON CASEY THOMAS DORAN BAUER GREG		
发明人	JOHNSON, CASEY THOMAS, DORAN BAUER, GREG		
IPC分类号	A61B5/00 A61B5/083 A61B5/097		
CPC分类号	A61B5/097 A61B5/0836 A61B5/4821		
外部链接	Espacenet USPTO		

摘要(译)

一种方法，包括准备使用的采样装置的步骤。采样装置包括管状构件，管状构件在其远端上具有开口。管状构件的远端的取向是可成形的。远端基本上是刚性的，以便在管状构件的远端上直接施加阈值水平的力之后保持操纵的形状。管状构件还包括设置在管状构件的近端上的接头构件。接头构件配置成将管状构件连接到全身生物标记物取样装置。

