



US010131412B2

(12) **United States Patent**
Hulbert

(10) **Patent No.:** **US 10,131,412 B2**
(45) **Date of Patent:** **Nov. 20, 2018**

(54) **ASCENT AND BUOY SYSTEM FOR DIVERS**

A61B 2560/0242 (2013.01); *B63B 2730/00*
(2013.01); *G08B 21/02* (2013.01)

(71) Applicant: **Christopher B. Hulbert**, Winnetka, IL
(US)

(58) **Field of Classification Search**

CPC . *B63C 11/26*; *B63C 11/2236*; *B63C 11/2245*;
A61B 5/14542; *A61B 5/08*; *A61B*
5/02438; *B63B 22/06*; *B63B 22/18*; *B63B*
2730/00

(72) Inventor: **Christopher B. Hulbert**, Winnetka, IL
(US)

(*) Notice: Subject to any disclaimer, the term of this
patent is extended or adjusted under 35
U.S.C. 154(b) by 0 days.

USPC 405/185, 186
See application file for complete search history.

(21) Appl. No.: **15/489,463**

(56) **References Cited**

(22) Filed: **Apr. 17, 2017**

U.S. PATENT DOCUMENTS

(65) **Prior Publication Data**

US 2018/0001980 A1 Jan. 4, 2018

5,156,055 A 10/1992 Hollis et al.
5,889,730 A 3/1999 May
(Continued)

Related U.S. Application Data

FOREIGN PATENT DOCUMENTS

(60) Provisional application No. 62/458,229, filed on Feb.
13, 2017.

GB 2304444 A * 3/1997 *B63C 11/02*

OTHER PUBLICATIONS

(51) **Int. Cl.**

B63C 11/22 (2006.01)
B63C 11/08 (2006.01)
A61B 5/024 (2006.01)
B63C 11/26 (2006.01)
B63B 22/06 (2006.01)
B63B 22/18 (2006.01)
A61B 5/00 (2006.01)

“Fitbit Surge Fitness Super Watch”—Product Manual, Version 1.2
(circa 2014), 48 pages.
“Fitbit Charge 2”—Product Manual, Version 1.0 (2016), 42 pages.

Primary Examiner — Anthony D Wiest

(Continued)


(52) **U.S. Cl.**

CPC *B63C 11/26* (2013.01); *A61B 5/0205*
(2013.01); *A61B 5/02416* (2013.01); *A61B*
5/02438 (2013.01); *A61B 5/0816* (2013.01);
A61B 5/14551 (2013.01); *A61B 5/742*
(2013.01); *A61B 5/746* (2013.01); *B63B 22/06*
(2013.01); *B63B 22/18* (2013.01); *B63C*
11/2236 (2013.01); *B63C 11/2245* (2013.01);
G08B 5/002 (2013.01); *G08B 21/0453*
(2013.01); *G08B 21/088* (2013.01); *G08B*
25/016 (2013.01); *A61B 2503/10* (2013.01);

(57) **ABSTRACT**

An apparatus for divers is disclosed that includes both a
buoy and an ascent device. The system also includes a
biological sensor for detecting when a diver is in distress.
Upon the biological sensor detecting an anomalous condi-
tion, the system inflates a bladder, such as that found in a
diver's Buoyancy Control Device, to urge the diver toward
the water surface. The system also releases a buoy, allowing
the buoy to float to the water surface and alert others of the
diver in distress. In an example embodiment, the buoy
detects its position upon reaching the surface and issues an
alarm.

12 Claims, 14 Drawing Sheets



(51) **Int. Cl.**

<i>A61B 5/0205</i>	(2006.01)
<i>A61B 5/08</i>	(2006.01)
<i>A61B 5/1455</i>	(2006.01)
<i>G08B 5/00</i>	(2006.01)
<i>G08B 21/04</i>	(2006.01)
<i>G08B 21/08</i>	(2006.01)
<i>G08B 25/01</i>	(2006.01)
<i>G08B 21/02</i>	(2006.01)

(56) **References Cited**

U.S. PATENT DOCUMENTS

6,592,298	B2	7/2003	Beltrani	
7,272,075	B2	9/2007	Pope	
7,303,453	B1	12/2007	Bourke	
7,310,549	B1	12/2007	Angelini et al.	
7,797,124	B2	9/2010	Hollis et al.	
8,417,351	B2	4/2013	Kilger	
9,339,237	B2	5/2016	Frix et al.	
9,339,242	B2	5/2016	Bailey et al.	
9,404,600	B2	8/2016	Kainuma et al.	
2012/0128425	A1 *	5/2012	Walck	B63C 11/02 405/186
2013/0259579	A1 *	10/2013	Bonzon	B63C 11/2245 405/186
2014/0167984	A1	6/2014	Holopainen et al.	
2015/0216454	A1	8/2015	Kasahara et al.	

* cited by examiner




FIG. 1




FIG. 2




FIG. 3




FIG. 4




FIG. 5




FIG. 6




FIG. 7




FIG. 8




FIG. 9




FIG. 10




FIG. 11




FIG. 12




FIG. 13A




FIG. 13B




FIG. 14A




FIG. 14B




FIG. 14C




FIG. 15




FIG. 16




FIG. 17




FIG. 18




FIG. 19




FIG. 20




FIG. 21




FIG. 22




FIG. 23




FIG. 24




FIG. 25




FIG. 26




FIG. 27

ASCENT AND BUOY SYSTEM FOR DIVERS**CLAIM FOR PRIORITY TO RELATED APPLICATION**

This application claims priority to U.S. Provisional Application No. 62/458,229, which was filed on Feb. 13, 2017 and entitled "Underwater Safety Device."

BACKGROUND**Technical Field**

The present system relates to the field of underwater diving and, more particularly, to safety devices used while diving.

Background Art

Underwater diving typically involves a diver breathing from a source of compressed gas. A typical scuba tank for a recreational driver holds gas (e.g., air) at a relatively high pressure (such as 3,000 pounds per square-inch (psi)). The tank is often held by a buoyancy control device (BCD), also referred to as a buoyancy compensator or stabilizer. During use, the BCD is strapped onto the back of a scuba diver.

In a typical single-hose, open-circuit, two-stage scuba system, a first regulator stage reduces the gas pressure in the tank to a low pressure of, for example, 120 to 150 psi. A hose typically supplies gas at the low pressure to a valve on the BCD. The valve allows a diver to inject gas from the tank into one or more bladders in the BCD or to release air from the BCD into the water. In this way, the diver can control her buoyancy, often striving for neutral buoyancy during a dive and positive buoyancy (i.e., a supernatant condition) while ascending toward, or swimming on, the water surface.

Gas at the low pressure is also supplied by a hose to a second stage of the regulator, which is held by a diver's mouth. The second stage of a demand-valve regulator delivers breathable gas (e.g., air) at approximately ambient pressure to the diver's mouth or full-face mask. The ambient pressure, of course, depends of the water depth of the diver.

Another example of underwater diving equipment includes "Snuba" (a combination of the words, snorkel and scuba), which allows underwater diving with air supplied from the water surface. Instead of coming from a tank strapped to a diver's back, air is supplied to the second stage of the regulator from long hose connected to a compressed air tank at the water surface, held by a flotation device.

Upon occasion, an underwater diver encounters difficulty and should promptly ascend toward the water surface and/or summon help. For example, nitrogen narcosis (also sometimes referred to as "the martini effect") can arise from breathing nitrogen at an elevated pressure (i.e., at substantial depth). It can impair a diver's judgment, coordination, and ability to focus mentally.

If, through inattention or the effects of nitrogen narcosis, a diver breathing air descends too deeply in the water, the diver can suffer from oxygen poisoning (as a result of breathing oxygen at too high a partial pressure).

For deeper dives, a diver may use a "non-air" gas mixture. A commercial scuba diver going to depths of 300 or more feet may use, e.g., 10 different bottles, with different combinations of gasses being supplied to the diver at different depths. If the diver's computerized valve assembly malfunctions (e.g., sea water seeps into the computer housing and degrades the performance of the valve controller), the diver must be able promptly to adjust the tank valves manually, a sometimes difficult task.

Divers at remote dive locations may sometimes have their tanks filled locally, near the dive site. On such occasions, a compressor, powered by a gasoline engine, may be used to pump air into the dive tanks. If the compressor operator is not careful, exhaust gas from the gasoline engine, including carbon monoxide, may be pulled in by the air compressor and pumped into a tank. Carbon monoxide is colorless, tasteless, odorless, and toxic.

Decompression sickness (also known as the bends or Caisson Disease) can affect a diver who surfaces too quickly. Upon descending in the water, the pressure around the diver increases, causing nitrogen to be absorbed into her body tissue. To release the nitrogen slowly from her body, a diver generally should ascend slowly and sometimes carry out decompression, or safety, stops. This allows the nitrogen to seep out of the body tissue slowly. If a diver ascends too quickly, however, there can be a build-up of nitrogen bubbles in the diver's body, adversely affecting the diver. A diver who is injured or otherwise under stress may encounter difficulty in ascending at a proper rate or following a desirable dive profile (including safety stops).

Of course, a diver may, at any time, experience an adverse health issue, such as a stroke or heart attack, requiring prompt medical attention. A muscle cramp (such as a debilitating stomach cramp) can pose a risk to a diver.

SUMMARY

The present disclosure describes implementations that relate to a safety system for underwater divers. In one example implementation, the present disclosure describes a sensor and alarm. The sensor detects an anomalous condition and issues an alarm, such as, for example, an audible alarm or a flashing light or both. Upon determining that a major anomaly exists and that rescue measures are enabled, the system inflates a bladder, such as those on a diver's BCD, bringing her toward the water surface.

In another example implementation, upon determining that a major anomaly exists and that rescue measures are enabled, the system releases a buoy, allowing it to float to the water surface. The buoy issues an alarm for others on the surface.

In still another example implementation, the buoy is tethered to the diver. The tether allows a rescue diver to follow the tether to the diver in distress. In another example implementation, the tether enables data transmission, so that the diver may talk, or otherwise communicate with, others on the surface.

The foregoing summary is illustrative only and is not intended to be limiting. In addition to the illustrative aspects, implementations, and operations described above, further aspects, implementations, and operations will become apparent by reference to the figures and the following detailed description.

BRIEF DESCRIPTION OF THE FIGURES

FIG. 1 illustrates a configuration of a safety system, in accordance with an example implementation.

FIG. 2 illustrates an example block diagram of the diving system shown in FIG. 1, in accordance with an example implementation.

FIG. 3 illustrates an example of a controller, in accordance with an example implementation.

FIG. 4 illustrates another example of a controller, in accordance with an example implementation.

FIG. 5 illustrates an example of block diagram of sensors, a controller, and a rescue subsystem, in accordance with an example implementation.

FIG. 6 illustrates an example of oximeter, in accordance with an example implementation.

FIG. 7 illustrates an example of sensors on a controller, in accordance with an example implementation.

FIG. 8 illustrates an example of a gas pressure sensor, in accordance with an example implementation.

FIG. 9 illustrates an example of a controller using LEDs as a display, in accordance with an example implementation.

FIG. 10 illustrates an example of diver wearing a full-face mask, in accordance with an example implementation.

FIG. 11 illustrates an example of an activated alarm, in accordance with an example implementation.

FIG. 12 illustrates an example of a BCD and BCD control valve, in accordance with an example implementation.

FIG. 13A illustrates an example of a diver carrying a buoy, along with personal sonar system, in accordance with an example implementation.

FIG. 13B illustrates an example of a controller, in communication a sonar system, displaying the direction of a dive boat, in accordance with an example implementation.

FIG. 14A illustrates a cross-sectional view of an example of a BCD control valve in a position that blocks supply air from both the BCD port and vent port, in accordance with an example implementation.

FIG. 14B illustrates a cross-sectional view of an example of a BCD control valve in a position that allows supply air to flow to the BCD port but not to the vent port, in accordance with an example implementation.

FIG. 14C illustrates a cross-sectional view of an example of a BCD control valve in a position that allows air to flow from the BCD port to the vent port, in accordance with an example implementation.

FIG. 15 illustrates an example of a diagram of a BCD control valve in communication with the low pressure port of the first stage of a regulator, in accordance with an example implementation.

FIG. 16 illustrates an example of a diver wearing a weight belt with a releasable buckle, in accordance with an example implementation.

FIG. 17 illustrates an example of the releasable buckle shown in FIG. 16, in accordance with an example implementation.

FIG. 18 illustrates an example of a naturally supernatant buoy, in accordance with an example implementation.

FIG. 19 illustrates an example of an inflatable buoy, in accordance with an example implementation.

FIG. 20 illustrates an example of a naturally supernatant buoy and tether, in accordance with an example implementation.

FIG. 21 illustrates an example of a BCD and naturally supernatant buoy, in accordance with an example implementation.

FIG. 22 illustrates an example of a BCD, inflatable buoy, and buoy fill valve, in accordance with an example implementation.

FIG. 23 illustrates an example of a tank, inflatable buoy and buoy fill valve, in accordance with an example implementation.

FIG. 24 illustrates an example diagram of a buoy fill valve in communication with the low pressure port of the first stage of a regulator, in accordance with an example implementation.

FIG. 25 illustrates an example of a floating, naturally supernatant buoy, in accordance with an example implementation.

FIG. 26 illustrates an example of a floating, inflated, tethered buoy, in accordance with an example implementation.

FIG. 27 illustrates an example of a process used by configuration of the safety system of FIG. 23, in accordance with an example implementation.

DETAILED DESCRIPTION

Generally

The following detailed description describes various aspects, implementations, and operations of the disclosed system with reference to the accompanying figures. The illustrative aspects, implementations, and operations described herein are not meant to be limiting. It is contemplated that certain aspects of the disclosed system can be arranged and combined in a wide variety of different configurations.

Unless context suggests otherwise, the features illustrated in each of the figures may be used in combination with one another. Thus, the features should be generally viewed as component aspects of one or more overall implementations, with the understanding that not all illustrated features are necessary for each implementation.

Any enumeration of elements, blocks, or steps in this disclosure or in any associated claim is for purposes of clarity. Thus, such enumeration should not be interpreted to require or imply that these elements, blocks, or steps adhere to a particular arrangement or are carried out in a particular order.

By the terms, “substantially,” “approximately,” or “generally,” it is meant that the recited characteristic, parameter, or value need not be achieved exactly, but that deviations or variations, including for example, tolerances, measurement error, measurement accuracy limitations, and other factors known to those of ordinary skill in the pertinent art may occur in amounts that do not preclude the effect the feature was intended to provide.

The appended figures illustrate example embodiments of a safety system 100, including examples of its subsystems. As shown in FIGS. 1 and 2, an underwater diver 102 employing the safety system 100 is wearing one or more sensors 104, a controller 106, an alarm system 108, and a rescue system 110. In the example embodiment shown in FIG. 1, the controller 106 is worn on the body of the diver 102.

The rescue system 110 includes a BCD subsystem 111, which includes a BCD 112 configured to be strapped onto the back of the diver 102 and to hold a tank 114 of compressed gas. A regulator 116 includes a first, or primary, stage atop the tank 114 and a second, or secondary, stage 120 held by diver's mouth.

Detecting and Reporting Pertinent Conditions: Sensors 104

In an example embodiment, the sensors 104 include one or more biological sensors (e.g., sensors or bio-sensors configured to detect the functioning or activity of the diver 102). The controller 106 is in communication with such body-worn, biological sensors. Each such sensor is configured to measure at least one biological parameter of the diver 102 and transmit a biological signal correlated to the biological parameter to the controller 106.

In example embodiments, the sensors 104 measure and report one or more parameters related to the diver's well-being, including, for example, blood oxygen level, blood gas

saturation level, pulse rate, blood pressure, respiration rate, and/or other vital signs, and provide data regarding the monitored parameters to the controller **106**. Biological sensors are disclosed, for example, in U.S. Pat. No. 9,339,242 (“Systems, methods, components, and software of monitoring and notification of vital sign changes”); U.S. Pat. No. 9,339,237 (“Continuous transdermal monitoring system and method”) and U.S. Pat. No. 8,417,351 (“Peripheral oximimulatur apparatus and methods”); U.S. Pat. No. 7,310,549 (“Dive computer with heart rate monitor”).

In an example embodiment, the sensors **104** also include equipment sensors. Such sensors help measure, for example, tank gas pressure or the water depth of the diver **102**.

One, some, or all of the equipment sensors include a battery power supply and communicate with the controller **106**. In example embodiments, communications between the controller **106** and sensors **104** are wired or wireless or a combination of wired and wireless communications.

Examples of various controller embodiments are shown in FIGS. 3-5, 7 and 9. The controller **106** monitors data from sensors **104** regarding salient conditions of the diver’s body and/or her equipment and provides information to the diver **102** on a display. The module holding the controller **106** may itself house a variety of sensors, with information from such sensors commonly including for example, the depth of the diver, the time the diver has been submerged and at what depth, and rate of the diver’s ascent. An example of a dive computer with wireless communication capabilities is disclosed in U.S. Pat. No. 7,797,124 (“Dive computer with free dive mode and wireless data transmission”).

In another example embodiment, optical communications are employed for data transmission. Optical communications may allow a high data communication rate. In other embodiments, acoustic, or audio, transmissions are used additionally or alternatively for communication. Acoustic signals are similar to sonar signals. Acoustic transmissions are generally reliable and travel relatively efficiently in water. The audio signal may or may not be audible to human ears.

In other example embodiments, radio communications are employed for wireless communication between the controller **106** and sensors **104**. A radio signal may be a relatively low-frequency electromagnetic signal. A low frequency radio signal typically does not propagate far underwater, but available electronic packages allow transmissions to propagate between, e.g., a diver’s pressure gauge and a wrist-mounted dive computer and from one diver to another, nearby diver.

In the example embodiment of FIG. 3, the sensors **104** and controller **106** communicate wirelessly. In the example embodiment of FIG. 4, the sensors **104** and a controller **132** communicate via a wire **134**. In another example embodiment, a combination of wire and wireless communications are used. Wireless communications reduce the risk of a diver tangling or breaking a wire. Wired communications can be less expensive to manufacture and can use less battery power to operate. Electrical connections may also be used for power transmission. In some example embodiments, a receiver that another diver has may be able to receive the wireless signal provided by the controller **106**. This signal may include data from the diver’s body-worn sensors(s), a Caution alarm signal, a Warning alarm signal, and/or a rescue deployment signal.

The controller **106** determines whether a measured parameter value is anomalous (e.g., consistent with a potentially serious condition). If a parameter value is a minor anomaly, the controller **106** issues a Caution alarm signal. If

a parameter value is a major anomaly (e.g., consistent with a more serious and time-critical condition), the controller issues a Warning alarm signal. If a parameter value is a critical anomaly (e.g., consistent with an imminent, potentially catastrophic condition), the controller issues an Emergency alarm signal.

The controller **106** communicates with both the alarm system **108** and rescue system **110**. In an example embodiment, the alarm system **108** includes an audible alarm **122** and/or a light alarm **124**, which activate upon receiving either a Caution or Warning alarm signal from the controller **106**.

The rescue system **110** includes a BCD inflation system **126** and a buoy subsystem **128**, with the buoy subsystem **128** including a deployable buoy **130**. If rescue deployment is enabled in the controller **106** and if a Warning alarm signal is not turned off by the diver **102** or another diver within a time interval after initiation, the controller **106** will issue a rescue deployment signal. The BCD **112** inflates in response to a BCD rescue deployment signal from the controller **106**, and the buoy is released in response to a buoy rescue deployment signal from the controller **106**.

In example embodiments, biological sensors of the system **100** include a pulse sensor **136**, blood oxygen sensor/oximeter **138**, and respiration sensor **140**, as well as a battery **142**. See FIG. 5. In an example embodiment, the sensors **104** also include equipment sensors including a tank gas pressure sensor **144**. In example embodiments, the biological sensors include a combined pulse rate detector and oximeter, which is located on the diver’s wrist, ear, or fingertip, or elsewhere on the diver. The pulse oximeter **146** is shown on the ear of the diver **102** in FIG. 6. The pulse oximeter **146** reports the level of blood oxygen saturation by measuring relative absorbance of red and infrared light in oxygenated and deoxygenated hemoglobin in the blood. The sensor thus determines the extent to which the diver **102** is undergoing hypoxemia. The pulse oximeter **146** reports pulse rate by analyzing periodic change of the relative absorbance data. Nitrogen gas (or other inert gas) saturation is determined based on reported oxygen saturation and/or on dive profile data including breathing gas composition, depth, and time.

FIG. 7 shows a side of the controller **106** adjacent the wrist of the diver **102** in FIG. 1. The controller housing includes an oximeter **138** having a source of red light **148** and detector **150** to sense reflection of red light. From such sensor data, the controller **106** determines the blood oxygen content of the diver **102**.

In another example embodiment, the sensors **104** include a heartbeat monitor held adjacent the chest of the diver **102** with chest strap. In an example embodiment shown in FIG. 8, a pressure sensor **144**, a type of equipment sensor, detects the pressure of gas in the tank **114**. The gas pressure sensor **144** is located at the primary (high pressure) stage **118** of the regulator **116** and reports the pressure of the gas in the tank **114** by generating a wireless equipment signal that is received by the controller **106**. An example of a pressure transducer with wireless communication is disclosed in U.S. patent application Ser. No. 14/108,015 (“Pressure valve transmitter with redundant pressure valve indicator”).

In an example embodiment, changes in tank pressure over time are also used to determine a real-time respiration rate. The pressure sensor **144** transmits an equipment signal to the controller **106** to report pressure data. It may include a battery power supply to allow wireless operation. A rate of incremental decrease in gas pressure in the tank **114** corresponds to the diver’s respiration rate. In another example embodiment, a pressure sensor detects the movement of air

in the second stage **120** of the regulator **116**, both from the second stage **120** into the diver **102** and from the diver **102** to the exhaust ports of second stage **120**, to determine the diver's respiration rate.

A gas composition sensor may determine and report the makeup of the gas being delivered to the diver **102**. The sensor is located in the second (delivery) stage **120** of the regulator **116** and engages in wired or wireless communication with the controller **106** (including a wrist module display or other user interface). The sensor in the second stage **120** receives data from the controller **106** and reports to the diver **102** information regarding the acceptable, or toxic, makeup of the gas being supplied to the diver **102**.

The system **100** may include other types of sensors to detect parameter values consistent with other serious diver conditions. For example, a parameter value corresponding to stopped heart (i.e., no pulse) or a weak or low-rate heartbeat (i.e., a weak or low pulse) is consistent with a heart attack. A parameter value corresponding to blood with a low-oxygen content is consistent with a diver who with a respiration issue (e.g., drowning or carbon monoxide poisoning). Parameter values consistent with diver at substantial depth that fails to ascend when her tank pressure runs very low is consistent with a diver who is unable to focus mentally (and who may run out of breathable gas (e.g., air) before she can safely return to the surface). It is contemplated that the system **100** can use a wide range of biological and equipment sensors configured to be in communication with the controller **106**.

The controller **106** generates an alarm signal upon receiving a signal from a biological and/or equipment sensor that corresponds to a parameter value and determining that the parameter value is anomalous. For example, if the controller **106** receives sensor signals consistent with the diver's respiration rate being too low or the gas pressure in the tank **114** being too low, the controller may then responsively issue signals to initiate Caution alarms, Warning alarms, and/or the deployment of one or both rescue measures.

Receiving Sensor Data: Controller **106**

Upon receiving data from one or more sensors **104** (that is, upon receiving a biological signal or equipment signal relating to the value of a particular parameter), the controller **106** determines if the parameter value is anomalous (that is, whether the parameter is outside a range appropriate for the parameter). If a parameter value is anomalous (that is, an anomaly exists), the controller **106** runs a diagnostic test to confirm that that anomaly is not the result of a fault within the system **100**. If no fault is detected, the controller **106** moves to an alarm condition.

When in an alarm condition, the controller **106** issues an alarm signal. The controller **106** issues a Caution alarm signal upon detecting a minor parameter value anomaly, a Warning alarm signal upon detecting a major parameter value anomaly, and an Emergency alarm signal upon detecting a critical parameter value anomaly.

In an example embodiment, the controller **106** is configured to compare parameter values derived from the data provided by the sensors **104** to threshold values in a lookup table stored in memory. A parameter value is anomalous if it is either above or below threshold values appropriate for the parameter. The controller **106** has stored in its memory a variety of different threshold values, both for different types of parameters (e.g., pulse rate and respiration rate) and also for different alert levels. The threshold level(s) may be default level(s) programmed in a memory of the controller **106** and/or user-definable threshold level(s).

The determination of whether a parameter value exceeds a threshold (and, thus, whether the controller **106** moves to an Alarm condition) is not limited to an arithmetic comparison of a measured parameter value with a static parameter value in memory. Such a determination may include, for example: an evaluation of other factors such as, for example, the rate of change of a parameter value, how long the anomaly has existed, age of the diver, a comparison of the measured parameter value with a value that is adjusted during a dive to account for the length of the dive, the water depth, the water temperature, etc.

In one example embodiment, the controller **106** issues a Caution alarm signal upon detecting a parameter value above (or below) a first threshold (i.e., outside a first range), where the parameter value is consistent with a less serious (e.g., less dangerous and less time-critical) diver condition. That is, with a minor anomaly in a parameter value, the diver **102** is not at substantial risk if she does not receive prompt assistance. In an example embodiment, a modestly depressed pulse and respiration rate is determined to be minor anomaly and results the controller **106** issuing a Caution alarm signal.

In one example embodiment, the controller issues a Warning alarm signal upon detecting a parameter value above (or below) a second threshold (i.e., outside a second range), where the parameter value is consistent with a more serious (e.g., more dangerous and more time-critical) diver condition. That is, with a major anomaly in a parameter value, the diver **102** is at substantial risk if she does not receive prompt assistance. In an example embodiment, a substantially depressed pulse and respiration rate is determined to be a major anomaly and results in the controller **106** issuing a Warning alarm signal.

In some emergency situations, a diver should rise to the surface of the water and obtain assistance immediately, despite the risk associated with an immediate ascent. In one example embodiment, the controller issues an Emergency alarm signal upon detecting a parameter value above (or below) a third threshold (i.e., outside a third range), where the parameter value is consistent with an extraordinarily serious and time-critical diver condition. That is, with an emergency anomaly in a parameter value, the diver **102** is at imminent risk of a catastrophic result if she does not receive prompt assistance. In an example embodiment, parameter values consistent with the diver breathing in water instead of gas (e.g., air) is determined to be an emergency anomaly and results in the controller **106** issuing an Emergency alarm signal.

Referring to FIGS. 3-5, 9, and 11, the controller **106** communicates with the sensors **104** and also includes a user interface **152** and a battery **154**. In various examples, the user interface **152** includes a display **156**. The display **156** and a processor within the controller **106** can share the same housing. In the wrist module embodiment shown in FIG. 4, for example, biological data are shown on the display **156**, which is an integral part of the controller **106**. In another example embodiment, a screen that displays the measurements is physically apart from the housing that encloses the controller processor.

The user or diver-interface **152** also includes user or diver-operable controls **159**, including manually operable buttons **160**. The buttons **160** may be physical buttons or touch-screen buttons or a combination of both. A physical button (such as the Off button **162**) is generally regarded as reliable and intuitive to operate. A touch screen button (such

as the Full On button **164** shown in FIG. 3) has fewer moving parts and is easier to configure in different languages, sizes, and colors.

In another example embodiment, the controller **106** has no alphanumeric display. Rather, as illustrated in the example of FIG. 9, the user interface **152** has red, yellow and green light emitting diodes (LEDs) **164**, **166**, and **168** that illuminate to indicate whether parameters measured by the various sensors are within Warning (red), Caution (yellow), or Normal (green) ranges. A simple display made with LEDs may be less expensive to manufacture and also more readily understood by a diver under stress or suffering from nitrogen narcosis.

Referring to FIG. 10, in another example embodiment, the user interface **152** includes a microphone for accepting audible commands issued by a diver wearing a full-face mask **170**. The controller **106** is configured respond to microphone signals as an alternative to, or in addition to, inputs made by pressing buttons. A further, example of a user interface **152** includes a headset for delivering an audio signal to the diver **102**. Such an audio signal assists the diver in hearing pertinent information, including any alarm, from the controller **106**. The headset may incorporate a bone conduction transducer, headphone, or speaker. In an example embodiment shown in FIG. 10, a bone conduction transducer **172** contacts the diver near her ear and creates sound by conducting vibrations to the diver's skull. An example of a bone conduction transducer is disclosed in U.S. Pat. No. 5,889,730 ("Underwater audio communication system using bone conducted sound").

Issuing Alarms: Alarm System **108**

The display **156** provides information to the diver **102** regarding the parameters measured by the sensors **104**. The display **156** can provide information regarding parameter values that are within nominally safe ranges (such as in FIG. 4) or parameter values that is anomalous and indicate a serious diver condition (such as in FIG. 11).

Upon receiving sensor data indicating that a diving parameter value is anomalous, the controller **106** conducts a diagnostic test to detect a possible fault condition within the controller **106** or the sensor(s) **104**. For example, if the controller **106** detects that a battery voltage is outside an acceptable range or there is an unexpected, internal short (or open) circuit, the controller **106** enters a Fault mode.

In the Fault mode, the controller **106** indicates that a fault has been detected, for example, by flashing the word, "Fault," on the display **156** shown in FIG. 4, or by flashing simultaneously all of the LEDs **164**, **166**, **168** shown FIG. 9. This indicates the system **100** cannot be relied upon. In an example embodiment, the system **100** deploys no rescue measures when in Fault mode.

Upon sensing an anomaly (i.e., upon detecting a parameter value outside an acceptable range), the controller **106** assumes an alarm condition and issues an alarm signal. An alarm condition may be triggered, for example, by: an oxygen saturation level below a threshold value (e.g., below 90% saturation); a respiration level below a threshold value (e.g., below 6 breaths per minute); and/or an unsafe pulse rate (e.g. (a) less than 30 beats per minutes, or (b) more than 230 beats per minute minus the age of the diver).

In another example embodiment, the controller **106** assumes an alarm condition and thus issues an alarm signal if, for example, a diver breathing air at 40 meters or more of depth needs to begin ascending if she is to have enough air for a safe ascent; however, instead of ascending, she swims deeper. Such behavior may indicate the diver has become

disoriented and needs help. In another example embodiment, an alarm condition exists if a diver descends below a predetermined depth.

In an example embodiment, the controller **106** issues a Caution alarm signal upon sensing a minor parameter value anomaly. The Caution alarm signal causes the display **156** to show a yellow "Caution" screen, and/or sound a low-pitch, audible Caution alarm (e.g., buzzer), and/or slowly flash a light (e.g., LED or strobe light). The controller **106** issues a Warning alarm signal upon sensing a major parameter value anomaly. The Warning alarm signal causes the display **156** to show a red "Warning" screen, and/or sound a high-pitch, audible Warning alarm, and/or quickly flash a light.

In one embodiment, the controller **106** in an alarm condition causes audio and/or visual alarms to pulse on and off at rates between 0.5 and 5 hertz. Such an intermittent alarm signal saves energy in the system battery(ies), by allowing reduced duty cycle. The intermittent alarm also makes the alarm(s) easier for divers to discern over any generally constant background noises or light.

In another example embodiment, the controller **106** also includes a vibration motor, which is activated upon the controller **106** entering the alarm condition. The vibration motor vibrates at different speeds in response to either a Caution alarm signal or Warning alarm signal. Such an arrangement helps to alert a distracted diver to a potentially adverse condition indicated by an anomalous parameter value.

The controller **106** may also issue a limited-range radio-wave alarm signal and/or activate light and/or acoustic alarms for other divers in the area. In an example embodiment, an alarm signal is received by a controller worn by another diver in the vicinity (e.g., a "diving buddy"), alerting her that a nearby diver may need assistance. A flashing light or pulsing audio alarm worn by a stricken diver **102** (activated by the alarm signal from the controller **106**) may similarly alert a nearby diver. If the alarm is detected by a nearby diver, she can assess the condition of the diver **102** whose controller initiated the alarms and take any required, remedial action. The diver or diving buddy may activate a diver-operable stop input, such as the Off button **162**, to deactivate the alarm(s) and/or prevent the deployment of one or both rescue measures.

After activation, the controller **106** continues to stay in the alarm condition as long as the alarm has not been manually deactivated with the diver-operable stop input (e.g., Off button **162**) and the parameter value or values that triggered the alarm condition remain anomalous (i.e., the condition that triggered the alarm condition is persists). If the controller **106** is in a Caution alarm condition (and not the more serious, Warning alarm condition), the alarm stays activated (e.g., the audible alarm and/or light stay on), but the system **100** does not deploy any rescue measures unless the controller **106** detects a major anomaly in a parameter value (or receives a manual input instructing the controller **106** to deploy one or both rescue measures).

If the controller **106** persists in the Warning alarm condition for a time interval, and one or more parameter values remains a major anomaly (i.e., time critical and posing substantial risk to the diver **102**), and the diver-operable stop input (e.g., the Off button **162**) has not activated, then the system **100** deploys one or more rescue measures. In one example embodiment, the time interval is a predetermine period of time, such 5 to 15 seconds. In another example embodiment, the time interval is determined based upon the severity of the major anomaly. (In an example embodiment, the time interval for an Emergency alarm condition is zero

11

to five seconds.) Upon the expiration of the time interval (if any), the controller **106** issues a rescue deployment signal. In an example embodiment, the rescue deployment signal may include an ascent control signal and/or a buoy release signal and/or a weight release signal.

Rescue Measures Generally

Referring in particular to the example embodiments shown in FIGS. **1**, **2**, **5**, **12**, **21**, the rescue system **110** includes the BCD subsystem **111** and buoy subsystem **128**. The example BCD subsystem **111** includes the BCD **112** and a BCD inflation system **126**. The BCD inflation system **126** includes a BCD valve **174**, BCD actuator **176**, and battery **178**. The buoy subsystem **128** includes the deployable buoy **130**. The BCD **112** is inflated and/or the deployable buoy **130** is released upon the controller **106** issuing a rescue deployment signal.

In an example embodiment, the controller **106** has (excluding the Fault mode) seven primary modes of operation, as described below.

Off. When in the Off mode, the system **100** activates no alarm, nor does it deploy any rescue measure, unless and until it receives an input to change to a different mode. In an example embodiment, the user interface **146** includes the “Off” button **162**. When pushed by, for example, the diver **102** or a nearby diver, the alarm signal is turned off and the rescue subsystem **110** remains off until activated again with the user interface **152**.

Full On (also referred to as Open Water mode). The controller **106** generally issues alarms and rescue deployment signals, as described below. See FIG. **3**.

Alarm Only (also referred to as Cave or Wreck Diving mode). The controller **106** issues Caution or Warning alarm signals, as appropriate, upon detecting an anomaly; however, the system **100** does not deploy any rescue measure (BCD inflation or buoy release).

Caution Alarm Off. The controller **106** does not issue any Caution alarm signal (which may be preferred by a diver when she is aware of a minor anomaly and does not want the distraction of a visual or audio Caution alarm). The controller **106** will still issue a Warning alarm signal and deploy rescue measures upon detecting a major anomaly.

All Alarms Off. The controller **106** does not issue any alarm signal. The system **100** will still deploy rescue measures upon detecting a major anomaly in a parameter value.

Diver-Elected Ascent. The diver **102** may activate the user interface **152** to inflate the BCD **112**, regardless of whether or not an anomaly has been detected or an alarm signal has issued. The rescue system **110** will bring the diver **102** to the water surface at a controlled rate (or, if the diver **102** so instructs the controller **106** via the user interface **152**, at an unconstrained, emergency ascent rate).

Diver-Elected Buoy Release. The diver **102** may activate the user interface **152** to release the buoy **130**, regardless of whether or not any anomaly has been detected or any alarm signal has issued.

When the controller **106** receives data from a sensor **104** indicating a major anomaly in a parameter value, the controller **106** determines its current mode of operation. If in an appropriate mode, the diagnostic check conducted by the controller **106** and/or sensors **104**. If no fault is detected and (assuming a non-emergency alarm condition) the major anomaly persists for an interval of time following the initiation of a Warning alarm signal, the controller **106** sends

12

a rescue deployment signal, either via a wire or wirelessly. The deployment signal results in a gas being sent to a balloon or other bladder, to help the diver ascend to the surface, and/or a buoy being released. In example embodiments, the deployment signal is received by the BCD valve **174** and/or BCD actuator **176**.

In the example embodiment shown in FIG. **1**, the controller **106** is on the wrist of the diver **102**, physically separate from either the BCD **112** or buoy **130**. Accordingly, the diver **102** need only maintain and work with one (e.g., wrist-mounted) computing module and user interface, rather than separate computing modules on the BCD **112** or buoy **130**. With such an example embodiment, the diver **102** needs to check the battery charge level for only one computer module, rather than multiple computer modules, before a dive. Particularly in stressful circumstances, a diver having to contend with only one dive computer and interface (rather than multiple computers and interfaces) can reduce the chance of diver error and, thus, reduce the risk of an adverse outcome.

Sonar Component **180**

Referring to FIG. **13A**, an example embodiment of the system **100** also includes a personal sonar component **180** to detect nearby obstructions, such as a cave or wreck ceiling. An example of a sonar system is disclosed in U.S. Pat. No. 7,272,075 (“Personal sonar system”). If the sonar component **180** detects an obstruction above the diver, the controller **106** switches to “Cave/Wreck” modes, resulting in the rescue subsystem **110** being disabled until the sonar component **180** no longer detects an obstacle above the diver **102**.

In some instances, the diver **102** initiates a dive from a dive boat. After spending time underwater, she wishes to return to the boat, but does not know the location or the boat relative to her position. She then typically swims to the surface and attempts to locate the boat visually. If she wishes to continue diving, she determines a compass heading for the boat and then, upon continuing her underwater dive, attempts to follow the compass heading she determined at the surface.

In another example embodiment, the boat includes a signal generator, power amplifier, and electro-acoustic transmitter/transducer **181** configured to transmit pulses of sound (“pings”). In various, example embodiments, a series of pings are transmitted on an ongoing basis, either at regular time intervals or in response to receiving a ping sent by the sonar component **180** on the diver **102**.

In an example embodiment, the personal sonar component **180** carried by the diver **102** has an array of sensors oriented in different directions, each of which detects pings. A comparator within the sonar component **180** determines which sensor(s) in the array received the highest energy ping and, accordingly infers the direction from which the pings emanated. The sonar component **180** then relays such information to the controller **106**, which indicates, on the display **156**, the direction the diver **102** should swim if she wishes to return to the boat. In the example embodiment of FIG. **13B**, the display **156** shows an arrow pointing toward the boat. In another example embodiment, the display **156** identifies the compass heading the diver **102** should follow to reach the boat.

BCD Inflation Generally

Typically, the BCD **114** allows the diver **102** manually to operate a valve **182** manually and divert gas from the tank **112**, via a supply hose **183** connected to the first stage **118** of the regulator **116**, into one or more bladders **184** within

the BCD 112. See FIGS. 12, 14 and 15. In some instances, a dedicated tank is used for BCD inflation, but this is less common.

Moving gas from the tank 114 to the bladder 184 of the BCD 114 (generally at a lower pressure than the gas is stored in the tank 112) results in the combination of the tank 114, diver 102, and BCD 112, as a whole, having an increased volume, but the same mass. As such, the combination as a whole is less dense and more buoyant.

In an example embodiment, the BCD valve 174 of the system 100 is a waterproof, electrically operated, normally-closed solenoid valve. A power supply (e.g., the battery 178) provides power to the BCD valve 174, which includes an actuator, or solenoid 186, to move an internal member 188 within the valve body 190. In the example embodiment shown in FIG. 14, the internal member 188 is an axially moveable spool. In another, alternative example embodiment, the actuator of the BCD valve 174 is a stepper motor, rather than a solenoid, to move the internal member 188 between the positions shown in FIG. 14.

According to an example embodiment, applying electrical power to the solenoid 186 opens the BCD valve 174, and removing power closes the BCD valve 174. The power supply (e.g., the battery 178) may be located at the BCD valve 174 and operate in response to a wirelessly transmitted signal from the controller 106. In an alternative, example embodiment, a power conduit electrically connects the BCD valve 174 to a remote power supply. The BCD valve 174 may be located at the first stage (on an intermediate or low-pressure port). In an alternative example embodiment shown in FIG. 12, the BCD valve 174 is downstream, on the low-pressure supply hose 183.

Upon receiving a rescue deployment signal from the controller 106, the solenoid 186 of the BCD valve 174 moves the internal member 188 from the position shown in FIG. 14A (where pressurized gas from the supply hose 183 is blocked) to the position shown in FIG. 14B (where pressurized gas flows from the supply hose 183 into the bladder 184 of the BCD 112. When the controller 106 determines that the gas in the bladder 184 should be vented to the environment, the solenoid 186 moves the internal member 188 to the position shown in FIG. 14C.

Controlled Ascent

A depth sensor associated with the controller 106 senses the ambient water pressure over time, allowing the controller 106 to monitor its ascent rate. The depth sensor may be located in the wrist module portion of the controller 106 or elsewhere. An example of a dive computer configured to determine ascent rate is disclosed in U.S. Pat. No. 5,156,055 ("Ascent rate meter for scuba divers").

Upon determining that the rescue measure of BCD inflation should be deployed, the controller 106 issues a rescue deployment signal. In an example embodiment, one type of rescue deployment signal is an ascent control signal. The ascent control signal controls the operation of the BCD valve 174, instructing it to move the internal member 188 with the valve body 190 to the positions shown in FIG. 14.

Absent a time-critical emergency, the gas volume in the BCD 112 is controlled (i.e., gas is added to, or allowed to escape from, the BCD 112) to keep the ascent speed at a safe speed, such as, for example, 30 feet per second. Absent an emergency condition, where the controller 106 determines the diver 102 should be brought to the surface immediately, the controller 106 determines when the diver 102 is ascending too quickly (e.g., faster than approximately 30 feet per minute), too slowly (e.g., substantially slower than approxi-

mately 25 feet per minute) or is the ascent rate is within a safe range (e.g., approximately 25 to 30 feet per second).

At one or more points during her ascent, it may be appropriate for the diver 102 to stay at a particular depth in the water (e.g., 15 feet) for a "safety" or "decompression" stop, as a precaution against the bends. In one example embodiment, the controller 106 determines whether one or more safety stops are required and, if so, regulates the BCD valve 184 accordingly. For such a stop, the controller 106 regulates the BCD valve 184 such that the diver 102 ascends at 30 feet per second, slows and then stops ascending at an appropriate depth (e.g., 15 feet) and stays at this depth for an appropriate time (e.g., three minutes). Thereafter, with the stop completed, the controller 106 again provides an ascent control signal to the BCD valve 174 to allow more gas into the BCD 112 and allow the diver 102 to continue her ascent (either to the water surface or to another decompression stop).

As generally shown in FIG. 14, the BCD valve 174 has, within the valve body 190, an inlet port 192, outlet port 194, and the vent port 196. The internal member 188 is configured to move between first, second, and third positions. In the first position, the internal member 188 blocks the inlet port 192 (so gas from the tank 114 does not enter the BCD 112). In the second position, the internal member 188 defines a passageway between the inlet and outlet ports 192, 194, such that pressurized gas from the tank 114 flows through the inlet port 192, through the passageway, through the outlet port 194, and into the bladder 184 of the BCD 112. In the third position, the internal member 188 blocks the inlet port 194 and defines a passageway between the outlet and vent ports 194, 196, such that gas in the bladder 184 flows through the outlet port 194, through the passageway, through the vent port 196, and into the environment (e.g., the water surrounding the diver 102). Because the volume of gas in the bladder 184 generally expands as water depth decreases, it may be necessary, as the diver 102 ascends, to bleed gas from the BCD 112 via the vent port 196.

The solenoid 186 receives the rescue deployment signal provided by the controller 106. The rescue deployment signal includes an ascent control signal and, in response to the signal, the solenoid 186 responsively moves the internal member 188 to the second position when the rate of ascent is below a minimum threshold, moves the internal member 188 to the third position when the rate of ascent is above a maximum threshold, and moves the internal member 188 to the first position when the rate of ascent is within the minimum and maximum thresholds. In one example embodiment, the internal member 188 moves to the second position (adding gas to the BCD 112) when the ascent rate is substantially below 30 feet per minute, moves to the first position (blocking the inlet and outlet ports 192, 194) when the ascent rate is approximately between 25 and 30 feet per minutes, and moves to the third position (allowing gas to vent from the BCD 112) when the ascent rate is substantially above 30 feet per minute.

In an example embodiment, the BCD valve 174 that supplies gas to the BCD 112 is a three-way solenoid valve that allows a closed connection (FIG. 14A), an open, regulator-to-BCD connection (FIG. 14B), and an open, BCD-to-environment connection (FIG. 14C). In one particular example embodiment, to supply gas to the BCD bladder 184, the BCD valve 174 is connected with a DC power supply in normal polarity to actuate the solenoid 186 and move the BCD valve 174 to the open, regulator-to-BCD position. See FIG. 14B. To vent, or bleed, gas from the BCD 112, the solenoid 186 may be connected with the DC power

15

supply source in reversed polarity to actuate the solenoid **186** and move the BCD valve **174** to the open BCD-to-environment position, where it can release gas from the BCD **112** via, e.g., the vent, or bleed, port **196**. See FIG. **14C**. The solenoid **186** may include a three-way switch, or multiple switches, to move between the normal-off-reversed polarity conditions.

Even if no anomaly exists, the diver **102** may activate the user interface **152** of the controller **106** to activate the BCD valve **174**. This will cause a controlled flow of gas from the tank **114** into and, as necessary, out of, the BCD bladder **184** for a controlled ascent to the surface. Such an event may occur not because of sensor data indicating an anomalous parameter value, but only because the diver **102** wishes the system **100** to control her ascent, including her safety, or decompression, stops.

Thus, the controller **106** may determine a dive profile for the diver **102**; determining when she should surface, as well as how many decompression stops are indicated, at what depths, and for how long. The ascent control signal provided by the controller **106** to the BCD valve **174** adjusts the position of the internal member **188** so that the diver **102** generally follows the dive profile, including depression stops. The preferred rate of ascent during a decompression stop is typically zero (rather than, for example, 30 to 60 feet per second). Thus, in an example scenario, for a diver at 100 feet, the controller **106** may instruct the BCD valve **174** to inflate, and deflate, the BCD **112** to achieve an ascent rate of approximately 30 feet per minute until the diver **102** approaches 15 feet. Then, the controller **106** adjusts the rate of ascent so that the diver **102** stays at 15 feet of depth for three minutes (for a typical safety, or decompression, stop) and the again instructs the BCD valve **174** to allow additional gas into the BCD **112** and cause the diver **102** to ascend safely the remaining 15 feet.

Unconstrained Ascent

As indicated above, in some emergency situations (e.g., where the anomalous parameter value(s) are extraordinarily serious), a diver should rise to the surface immediately. In such a case, upon the controller **106** issuing the Emergency alarm signal, the ascent rate limit is bypassed, and the diver **102** is brought to the surface at a faster speed.

Upon receiving the Emergency alarm signal from the controller **106**, the solenoid **186** moves the internal member **188** to the position shown in FIG. **14B**. That is, the BCD valve **174** is left in the open, regulator-to-BCD position for an emergency, unconstrained ascent. Most modern BCDs contain over-pressure safety bleed valves, which mitigate the risk of over-pressurizing the BCD **112**.

In an example embodiment, the diver **102** also has the option to employ the user or diver interface **152** to enter an unambiguous instruction for an unconstrained ascent. If the controller **106** has been configured to accept such an instruction, it will send an emergency, unconstrained ascent control signal to the BCD valve **174**, keeping the BCD valve **174** in the open position at least until the diver **102** reaches the water surface.

Weight Belt Ditching

Particularly if a diver is wearing a wet suit or dry suit, she may also wear a weight belt, so as to help her more easily achieve a desired buoyancy during a dive. To further assist the ascent of a diver in an emergency (e.g., when the, the controller **106** detects a persistent, major anomaly), another example embodiment also includes a weight belt **198**, buckle **200**, and buckle actuator **202**, as shown in FIGS. **16-17**.

16

In addition to sending a BCD rescue deployment signal to the BCD actuator **176** to inflate the BCD **112** of a stricken diver, the controller **106** (in some but not all embodiments) also sends a weight release rescue deployment signal (another type of rescue deployment signal) to the buckle actuator **202** associated with the diver's weight belt buckle **200**. Upon receiving the signal, the buckle actuator **202** disengages the ends of the weight belt **198**, allowing the weight belt **198** to fall away from the diver **102**.

Personal Buoy for Emergency Notification

Buoy Subsystem **128**

The system **100** may be configured to enable communication with others. In some example embodiments, the communication is one-way. If the system **100** senses an anomaly in a biological and/or equipment parameter value, the system **100** provides an alarm to the distressed diver and/or other divers and/or other people at the surface. In one example embodiment, an alarm signal actuates a flashing light and audio speaker, as well as advising a controller worn by a nearby diver that an anomalous parameter value has been detected. Under some environmental conditions, the light and audible alarms can be detected by other divers, and the light alarm can be seen by others on the surface. In another example embodiment, one type of alarm issues for a minor anomaly (e.g., a slower-flashing light and a lower-pitched audible alarm) and another type of alarm issues for a major anomaly (e.g., a faster-flashing light and a higher-pitched audible alarm).

Referring to FIG. **5**, in other example embodiments, the system **100** also communicates to others with the buoy subsystem **128**. The buoy subsystem **128** includes the deployable buoy **130**, which has a communication module **206**, and a buoy actuator **208**. The communication module **206** includes a speaker assembly **210**, one or more lights **212**, a radio module **214**, and a battery **216**.

In one example embodiment, the buoy **130** is a naturally supernatant (i.e., naturally buoyant), such as the buoy **218** shown in FIGS. **21** and **25**. In another example, the buoy **130** is inflatable, such as the buoy **220** shown in FIGS. **19** and **26**. The buoy **130** ascends toward the water surface when released. An inflatable buoy **220** is less bulky for a diver **102** to carry. A naturally supernatant buoy **218** does not require an inflation mechanism and, with a larger floatation balloon, is capable of lifting a heavier load in the water.

If the controller **106** is in an appropriate mode of operation and issues a rescue deployment signal, the buoy actuator **208** releases the buoy **130**, allowing it to ascend. Once on the surface, the speaker assembly **210** and light **212** alert others on the surface. The audio and light alarms may signify that an underwater diver in the vicinity of the buoy **130** may require attention.

For example, upon breaking the surface, they buoy **130** may alert a rescue diver on the surface, allowing her to reach more quickly the approximate location of a stricken diver. By moving toward the location of the buoy before the stricken diver arrives at the surface, the time delay in reaching the stricken diver may be reduced.

The radio module **214** is configured to transmit and/or receive radio waves. The radio module **214** includes a buoy controller **224**, antenna **226**, and radio (transmitter and/or transceiver) **228**. After being released from the diver **102**, the radio **228** broadcasts a "Mayday," SOS, or other signal, via the antenna **226**, to indicate distress. In another example embodiment, the buoy controller **224** includes a GPS receiver, in communication with the radio transmitter, for

determining the GPS coordinates of the buoy **214**. The radio **228** then broadcasts the GPS coordinates as part of the distress signal.

In another example embodiment, the diver **102** may wish to alert, or otherwise communicate with, others at the surface, while remaining submerged. For example, a diver may wish to stay with another injured diver, while still summoning help. In this case, the diver **102** may activate the user interface **152** of the controller **106** to deploy the buoy **130**, even when the system **100** has detected no anomaly associated with the diver **102** wearing the system **100**.

During at least the initial portion of a dive, the buoy **130** is coupled to the buoy release mechanism or actuator **208**. Upon receiving a rescue deployment signal from the controller **106**, the buoy actuator **208** may, according to example embodiments, be pneumatically or electromagnetically activated.

Naturally Supernatant Buoy **218**

Referring to the supernatant buoy **218** shown in FIGS. **20**, **21** and **25**, the buoy actuator is a solenoid **228**. A spring locking pin **229** retains the buoy **218** the pin is retracted by the solenoid **228**.

In one example embodiment, the buoy controller **224** and battery **216** control the activation of the solenoid **228**, in addition to controlling the radio module **214**, speaker **210**, and light **212**. In another example embodiment, the buoy **130** also includes a separate activation controller **230** and battery **231** to control the activation of the solenoid **228**. The separate activation controller **230** and battery **231** are within a housing **232** near the buoy **218**.

When a controller (either the buoy controller **224** or activation controller **230**) receives a rescue deployment signal from the system controller **106**, the solenoid **228** activates. The buoy **218** then separates from the housing **232** at the plane indicated by the reference number **234** in FIG. **20**, and the buoy **218** is allowed to ascend toward the surface.

In an example embodiment, the naturally supernatant buoy **218** is generally rigid and, in large part, constructed of a material less dense than water (such as, for example, polystyrene or rubber). In an example embodiment shown in FIG. **21**, the solenoid **228** holds the supernatant buoy onto to the BCD **112**.

Inflatable Buoy **220**

In an example embodiment, the inflatable buoy **220** includes the communication module **206** and an inflatable buoy portion, also referred to as a balloon **244**. In one example embodiment, the buoy **220** is configured, when deflated, to be rolled up or packed so that the communication module **206** (antenna, light, and/or speaker) are wrapped within the inflatable portion **244** of buoy **220**.

In the example embodiments shown in FIGS. **19**, **24**, and **26**, the communication module **206** is a rigid structure attached to the balloon **244**. The uninflated balloon **244** is pressed in a generally rigid, tubular housing **246**. A cap **248** is press fit onto an end of the housing **246**, and a valve assembly **250** is in communication with the housing **246** via a fill stem **252**. The balloon **244** may be constructed from, for example, a urethane plastic or polyethylene material. The housing **246** and cap **248** generally protect the inflatable buoy **220** (communication module **206** and balloon **244**) against physical damage.

Referring to the example embodiment of FIG. **24**, the valve assembly **250** includes a buoy fill valve **254**, fill controller **256**, and battery **258**. The fill valve **254** is a waterproof, electrically-operated, normally-closed solenoid valve, powered by the battery **258**, resting between the

supply hose **183** and fill stem **252**. The buoy fill valve **254** may be similar in general design to the BCD valve **174**, albeit with only inlet and outlet ports.

The fill controller **256**, also powered by the battery **258**, receives a buoy rescue deployment signal from the controller **106** of the system **100** and responsively moves an internal member of the valve **254** to form a passageway between the low-pressure supply hose **183** and the fill stem **252**, allowing pressurized gas from the hose **183** to flow into the fill stem **252** and enter the balloon **244**.

Referring to the example embodiments of FIGS. **19**, **22**, **23**, **24**, and **26**, upon receiving an emergency deployment signal, the valve **250** opens and allows gas from the tank **114** to inflate the balloon **244** and cause the buoy **220** to ascend. As shown in FIG. **19**, a retainer mechanism (e.g., a collapsible seal **253**, slip fit on the fill stem **252**) keeps the balloon **244** in communication with the fill stem **252** until the balloon **244** is sufficiently inflated. As the balloon **244** inflates, it releases from the fill stem **252**, and the collapsible seal **256** prevents escape of gas (e.g., air) from the balloon **244**.

In an example embodiment shown in FIG. **22**, the fill tube **252** is attached to the BCD **112**. In another example embodiment shown in FIG. **23**, the fill tube **252** is attached to the tank **114**. A short line **238**, such as, e.g. a nylon rope, connects the supernatant buoy **218** to the tank **114**. The tendency of the housing **246**, cap **248**, and balloon **244** to float generally keeps the communication module **206** oriented upward, toward the water surface.

In an example embodiment, the cap **248** is a press-fit seal, comprised of rubber or other compliant material. The communication module **206** of the buoy **220** presses against the cap **248** of the housing **246**, pushing it off and clearing the way for the buoy **220** to ascend toward the surface. After a period of time, the air-fill controller **256** provides a signal to close the valve **254** and discontinue supplying gas to the fill balloon **244**.

In another example embodiment, housing **246** further includes the retention assembly **260** having a rubber retention plug **262** and shutoff switch **264**. The plug **262** retains the uninflated balloon **244** in the tubular housing **246** until the balloon **244** begins to inflate. Upon being inflated, the buoy **220** floats upward, out of the housing **246**. When the retention plug **262** pulls from the housing **246** as a result of the balloon **244** inflating, the switch **264** closes, signaling (either via a wire or wirelessly) to the fill controller **256** close the valve **254** and discontinue allowing gas to flow to the fill stem **252**. In an example embodiment, a sensor **266** detects that the contacts **268**, **270** are in contact and sends a short-range RF signal to the controller **256**, instructing it to close.

In another example embodiment, the buoy **220** includes a check valve matingly engaging a fill stem valve. A sensor module receives a buoy rescue deployment signal from the system controller **106**, triggering the release of a clasp coupling the check valve and fill valve **254**. The release of the clasp allows the buoy **220** to disconnect from the fill valve **254** and float toward the surface.

Buoy Tether **272**

In some example embodiments, no tether is used. See FIGS. **21** and **25**. Absent water current or other disruptions, the buoy **130**, once released, typically reaches the water surface in the general location of the still-submerged diver **102**.

In other example embodiments, however, the buoy subsystem **128** includes a tether **272** connected between the diver **102** and the buoy **130**, such shown in FIGS. **20** and **26**.

In the example embodiment shown in FIG. 20, the tether 272 is initially wrapped around a spool 274 within the housing 232 of the buoy 130. As the communication module 206 floats to the water surface, the tether 272 unwraps from the spool 274, and one end is brought to the surface by the buoy 130.

Referring to FIG. 26, when connected between a floating buoy 130 and diver 102, the tether 272 also helps maintain the floating buoy 130 in the vicinity of the submerged diver in distress. Should a rescue diver at the surface see the buoy 130 wish to descend to the diver in distress, the rescue diver can use the tether 272 as a guide to lead her to the stricken diver, even when visibility is poor (e.g., in murky water or at night).

Diver to Surface Communication

In one example embodiment, the tether 272 is a nonconductive line. In other example embodiments, however, the tether 272 comprises a wire, optical transmission cable, etc., for facilitating electronic communication with a submerged diver 102 and another person on the surface. For voice communication, the diver 102 wears an earphone/microphone assembly with a full-face mask 170, as shown in FIG. 10. The conductive tether 272 is interconnected to the radio 214 in the communication module 206 of the buoy 130. Using the tether 272 and radio 214, the diver 102 can talk, and listen, to people above the surface of water.

For example, a diver may be unable to come to the surface, or may simply prefer not to do so, while still wishing to communicate with others on the surface. In such a case, the diver may use the user interface 152 to release the buoy 130 with a conductive tether 272.

Safety Process

As described above, according to an example embodiment, the controller 106 is in communication with one or more sensors 104 (including in at least some embodiments, biological sensors), the alarm system 108, the user or diver-operable controls 159 (such as the Off button 162), the BCD control valve 174, and the buoy actuator 208. The BCD control valve 174 is connected to a supply of compressed gas (such as the tank 114), the BCD bladder 184, and a vent port 196.

The controller 106 receives biological sensor data from one of the biological sensors. Referring to FIG. 27, the controller 106 determines, at Step 300, whether data from a sensor 104 indicates an anomalous parameter value. At Step 302, the controller 106 conducts a diagnostic check to determine whether any apparently anomalous parameter value results from a fault within the system 100. If an anomaly in a parameter value is detected and does not appear to be the result of a fault within the system 100, the controller 106, at Step 304, issues an alarm signal. The controller 106 issues a Caution alarm signal for a minor diver condition and a Warning alarm signal for a major (more serious) diver condition. An audible alarm 122 and/or light alarm 124 activate in response to the alarm signal.

Upon determining, at Step 306, that the parameter value correlates to a major anomaly (i.e., the sensor data are consistent with a serious diver condition), the controller 106 determines, at Step 308, whether the stop input has been operated for a time interval after issuing the alarm signal. If not, the controller 106 determines, at Steps 310 and 312, whether it is in a mode allowing the rescue measure of BCD inflation or the rescue measure of a buoy release or buoy. If a buoy release is allowed, the controller 106 issues, at Step 314, a buoy release signal, allowing the buoy 130 to ascend to the water surface.

If BCD inflation is allowed, the controller 106 determines, at Steps 316 and 318, whether the major anomaly is consistent with a non-extraordinary event or extraordinary event. If the anomaly corresponds to a non-extraordinary event (albeit a major anomaly), the controller 106 issues a BCD valve actuation signal at Step 320. This action causes the BCD valve 174 to open and allow pressurized gas to enter the bladder 184 of the BCD 112.

The controller 106 further determines its rate of ascent in the water and responsively varies the valve actuation signal, whereby the valve activation signal instructs the BCD valve 184 to put the inlet port 192 in communication with the outlet port 194 when the rate of ascent is below a minimum threshold, to close when the rate of ascent is within minimum and maximum thresholds; and to block the inlet port 192 and put the outlet port 196 in communication with and the vent port 196 when the rate of ascent is above a maximum threshold.

If the major anomaly is consistent with an emergency diver condition (such that the diver requires immediate help, despite the potential risks of ascending rapidly), the controller 106, at Step 322, opens the BCD valve 174. In such an emergency condition, the controller 106 does not keep the diver below a threshold rate of ascent.

The steps of FIG. 27 generally followed by an example embodiment of the system 100 need not necessarily be taken in the order presented, nor must every step necessarily be taken. For example, the step of conducting diagnostic test may be done continually (rather than once, as shown in FIG. 27) or may not be performed at all, particularly for a robust system.

In an example embodiment, the controller 106 includes a non-transitory, computer readable medium storing instructions. The controller 106 also includes at least one processor in communication with the computer-readable medium. When the processor(s) executes the stored instructions, the controller, a type of computing device, performs the operations attributed to the controller 106 in the above description.

Conclusion

The system 100 combines different monitoring solutions into one system. A diver can wear a single device that monitors both body parameters and system parameters. It can provide one or more alarms to summon help or bring an unconscious diver to the surface. More than one sensor can be placed around a diver's body and on the equipment, with the sensors 104 communicating with the controller 106, which can be central or distributed.

The system 100 may include one or more processors and data storage units, which together may be part of the controller 106. The system 100 may also include additional sensor(s), power source(s), mechanical components, and electrical components. The system 100 is shown for illustrative purposes, and may include more or fewer components. The various components of system 100 may be connected in any functioning manner, including wired or wireless connections. In some example embodiments, components of the system 100 may be distributed among multiple physical entities rather than a single physical entity.

The processor(s) of the controller 106 and/or sensors 104 may operate as one or more general-purpose hardware processors or special purpose hardware processors (e.g., digital signal processors, application specific integrated circuits, etc.). The processor(s) may be configured to execute computer-readable program instructions, and manipulate data, both of which are stored in the data storage. The processor(s) may also, directly or indirectly, interact with

21

other components of the system **100**, such as sensor(s), power source(s), mechanical components, and/or electrical components. The controller **106** may include one or more electrical circuits, units of digital logic, computer chips, and/or microprocessors configured to (possibly among other tasks), interface between any combination of the sensor(s), the power source(s), the electrical components, and the control system **100**.

Further, in an example embodiment, the controller **106** includes a user (or diver) interface **152** between the system **100** and a diver **102** and/or other divers. The system **100** may perform operations for diving in addition to those described in this disclosure. Operations of the controller **106** may be carried out by one or more the processor(s) in one or more physical locations. During operation, the controller **106** may communicate with other systems carried by the diver **102** or by other divers or by equipment below, on, or above the water surface.

Further, the system **100** may include sensor(s) configured to receive information indicative of the state of the system **100**, including sensor(s) that may monitor the state of the various components of the system **100**. The data provided by the sensor(s) **104** may enable the system **100** to determine errors in operation as well as monitor overall operation of components of the system **100**.

The arrangements described herein are for purposes of example only. As such, those skilled in the art will appreciate that other arrangements and other elements (e.g., interfaces, operations, orders, and groupings of operations, etc.) can be used instead, and some elements may be omitted altogether according to the desired results. Further, many of the elements that are described are functional entities that may be implemented as discrete or distributed components or in conjunction with other components, in any suitable combination and location.

While various aspects and implementations have been disclosed herein, other aspects and implementations will be apparent to those skilled in the art. The various aspects and implementations disclosed herein are for purposes of illustration and are not intended to be limiting, with the true scope being indicated by the following claims, along with the full scope of equivalents to which such claims are entitled. Also, the terminology used herein is for the purpose of describing particular implementations only, and is not intended to be limiting.

I claim:

1. An apparatus for a diver comprising:

a sensor configured to measure a biological parameter of the diver and transmit a sensor signal correlated to a biological parameter value;

a controller in communication with the sensor and configured to:

receive the sensor signal, and

determine that the biological parameter value correlated to the sensor signal is anomalous and responsively issue a rescue deployment signal; and

a buoyancy control bladder;

a buoyancy valve assembly having

an inlet port connectable to a source of pressurized gas, and

an outlet port connected to the bladder,

22

the buoyancy valve assembly configured to receive the rescue deployment signal and responsively supply pressurized gas from the inlet port to the outlet port, whereby gas enters the bladder and the apparatus becomes more buoyant in water and ascends;

a buoy connectable to the diver; and

a buoy release actuator configured to receive the rescue deployment signal and responsively disengage the buoy from the diver.

2. An apparatus as claimed in claim 1 wherein the buoy is supernatant and includes an alarm.

3. An apparatus as claimed in claim 1 wherein the buoy is inflatable and includes an alarm and wherein the buoy release actuator includes a buoy valve having an inlet port connectable to a source of pressurized gas and an outlet port connected to the buoy, the buoy valve configured to receive the rescue deployment signal and responsively provide pressurized gas from the inlet and to the outlet port.

4. An apparatus as claims in claim 3 further comprising a tether connecting the diver and buoy.

5. An apparatus as claimed in claim 4 wherein the tether is a communication cable.

6. An apparatus as claimed in claim 1 further comprising a diver-activatable input device configured to provide a stop signal upon activation, the diver activatable input device being in communication with the controller, and wherein the controller is further configured to:

issue a warning alarm and begin measuring a time interval in response to determining that the biological parameter value correlated to the sensor signal is anomalous;

detect a stop signal during the time interval; and

issue a rescue deployment signal only if the controller does not detect a stop signal from the diver-activatable input device during the time interval.

7. An apparatus as claimed in claim 6 wherein the warning alarm is an audible alarm, whereby the alarm may alert the diver to activate the diver-activatable input device and stop the controller from issuing the rescue deployment signal.

8. An apparatus as claimed in claim 7 wherein:

the controller is further configured to determine a rate of ascent for the apparatus and responsively issue an ascent control signal; and

the buoyancy valve assembly includes a vent port and is further configured to receive the ascent control signal and responsively release gas from the vent port, whereby a rate of ascent of the apparatus is controlled.

9. An apparatus as claimed in claim 8 wherein apparatus includes a wearable housing and the sensor and controller are both within the housing.

10. An apparatus as claimed in claim 9 wherein the biological parameter is a pulse of the diver.

11. An apparatus as claimed in claim 9 wherein the biological parameter is a blood oxygen content level of the diver.

12. An apparatus as claimed in claim 9 wherein the biological parameter is a blood carbon monoxide content level of the diver.

* * * * *

专利名称(译)	潜水员的上升和浮标系统		
公开(公告)号	US10131412	公开(公告)日	2018-11-20
申请号	US15/489463	申请日	2017-04-17
[标]发明人	HULBERT CHRISTOPHER B		
发明人	HULBERT, CHRISTOPHER B.		
IPC分类号	B63C11/22 G08B21/04 G08B21/08 G08B25/01 A61B5/0205 A61B5/00 A61B5/08 A61B5/1455 G08B5/00 B63C11/08 A61B5/024 B63C11/26 B63B22/06 B63B22/18 G08B21/02		
CPC分类号	B63C11/2245 B63C11/2236 G08B21/0453 G08B21/088 G08B25/016 B63C11/26 A61B5/0205 A61B5/02416 A61B5/02438 A61B5/0816 A61B5/14551 A61B5/742 A61B5/746 B63B22/06 B63B22/18 G08B5/002 A61B2503/10 A61B2560/0242 B63B2730/00 G08B21/02 B63C2011/021		
优先权	62/458229 2017-02-13 US		
其他公开文献	US20180001980A1		
外部链接	Espacenet		

摘要(译)

公开了一种用于潜水员的装置，其包括浮标和上升装置。该系统还包括用于检测潜水员何时遇险的生物传感器。在生物传感器检测到异常情况时，系统使膀胱膨胀，例如在潜水员的浮力控制装置中发现的膀胱，以促使潜水员朝向水面。该系统还释放了一个浮标，允许浮标漂浮到水面并提醒其他遇险潜水员。在示例性实施例中，浮标在到达表面时检测其位置并发出警报。

