



US009974612B2

(12) **United States Patent**  
**Pinter et al.**

(10) **Patent No.:** **US 9,974,612 B2**  
(45) **Date of Patent:** **\*May 22, 2018**

(54) **ENHANCED DIAGNOSTICS FOR A TELEPRESENCE ROBOT**

(58) **Field of Classification Search**  
CPC . G06F 19/3418; G06F 19/322; G05D 1/0011;  
G05D 1/0038; G05D 2201/0206;  
(Continued)

(71) Applicant: **INTOUCH TECHNOLOGIES, INC.**,  
Goleta, CA (US)

(56) **References Cited**

(72) Inventors: **Marco Pinter**, Santa Barbara, CA (US);  
**Timothy C. Wright**, Santa Barbara, CA (US);  
**H. Neal Reynolds**, Severna Park, MD (US);  
**Fuji Lai**, Goleta, CA (US);  
**Yulun Wang**, Goleta, CA (US)

U.S. PATENT DOCUMENTS

3,821,995 A 7/1974 Aghnides  
4,107,689 A 8/1978 Jellinek  
(Continued)

(73) Assignee: **INTOUCH TECHNOLOGIES, INC.**,  
Goleta, CA (US)

FOREIGN PATENT DOCUMENTS

(\* ) Notice: Subject to any disclaimer, the term of this  
patent is extended or adjusted under 35  
U.S.C. 154(b) by 0 days. days.

AU 1216200 A 5/2000  
CA 2289697 A1 11/1998  
(Continued)

This patent is subject to a terminal disclaimer.

OTHER PUBLICATIONS

Harmo et al., "Moving Eye—Interactive Telepresence over Internet  
with a Ball Shaped Mobile Robot", Automation Technology Laboratory,  
Helsinki University of Technology, 2000, 6 pages.

(21) Appl. No.: **14/091,292**

(Continued)

(22) Filed: **Feb. 13, 2014**

*Primary Examiner* — Yuen H Wong

(65) **Prior Publication Data**

US 2014/0155755 A1 Jun. 5, 2014

(57) **ABSTRACT**


**Related U.S. Application Data**

(63) Continuation of application No. 14/108,036, filed on  
Dec. 16, 2013, which is a continuation-in-part of  
(Continued)

A telepresence device may autonomously check patients. The telepresence device may determine the frequency of checking based on whether the patient has a risk factor. The telepresence device may include an image sensor, a thermal camera, a depth sensor, one or more systems for interacting with patients, or the like. The telepresence device may be configured to evaluate the patient's condition using the one or more sensors. The telepresence device may measure physiological characteristics using Eulerian video magnification, may detect pallor, fluid level, or fluid color, may detect thermal asymmetry, may determine a psychological state from body position or movement, or the like. The telepresence device may determine whether the patient is experiencing a potentially harmful condition, such as sepsis or stroke, and may trigger an alarm if so. To overcome alarm  
(Continued)

(51) **Int. Cl.**  
**A61B 5/00** (2006.01)  
**A61B 19/00** (2006.01)  
(Continued)

(52) **U.S. Cl.**  
CPC ..... **A61B 19/2203** (2013.01); **A61B 5/0008**  
(2013.01); **A61B 5/0013** (2013.01);  
(Continued)



fatigue, the telepresence device may annoy a care provider until the care provider responds to an alarm.

**4 Claims, 12 Drawing Sheets**

**Related U.S. Application Data**

application No. 13/111,208, filed on May 19, 2011, and a continuation-in-part of application No. 13/830,334, filed on Mar. 14, 2013.

(60) Provisional application No. 61/729,964, filed on Nov. 26, 2012.

(51) **Int. Cl.**

- H04N 7/14* (2006.01)
- B25J 9/16* (2006.01)
- B25J 11/00* (2006.01)
- G05D 1/00* (2006.01)
- G06F 19/00* (2018.01)
- A61B 5/01* (2006.01)
- A61B 5/0205* (2006.01)
- A61B 5/11* (2006.01)
- A61B 5/16* (2006.01)
- A61B 34/30* (2016.01)
- A61B 5/024* (2006.01)

(52) **U.S. Cl.**

- CPC ..... *A61B 5/0022* (2013.01); *A61B 5/0075* (2013.01); *A61B 5/0077* (2013.01); *A61B 5/015* (2013.01); *A61B 5/02055* (2013.01); *A61B 5/1128* (2013.01); *A61B 5/165* (2013.01); *A61B 5/4064* (2013.01); *A61B 5/4809* (2013.01); *A61B 5/7264* (2013.01); *A61B 5/7275* (2013.01); *A61B 5/741* (2013.01); *A61B 5/742* (2013.01); *A61B 5/746* (2013.01); *A61B 34/30* (2016.02); *B25J 9/1689* (2013.01); *B25J 11/009* (2013.01); *G05D 1/0038* (2013.01); *G06F 19/3418* (2013.01); *H04N 7/148* (2013.01); *A61B 5/024* (2013.01); *G05D 2201/0206* (2013.01)

(58) **Field of Classification Search**

- CPC ..... *A61B 5/0008*; *A61B 5/742*; *A61B 5/741*; *A61B 5/7275*; *A61B 5/7264*; *A61B 5/4809*; *A61B 5/4064*; *A61B 5/1128*; *A61B 5/024*; *A61B 5/02055*; *A61B 5/015*; *A61B 5/0077*; *A61B 5/0075*; *A61B 5/0022*; *A61B 5/0013*; *A61B 19/2203*; *A61B 34/30*; *A61B 5/165*; *A61B 5/746*; *H04N 7/148*; *B25J 9/16*; *B25J 9/1689*; *B25J 11/009*

See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

4,213,182 A 7/1980 Eichelberger et al.  
 4,413,693 A 11/1983 Derby  
 4,471,354 A 9/1984 Smith  
 4,519,466 A 5/1985 Shiraishi  
 4,553,309 A 11/1985 Hess et al.  
 4,572,594 A 2/1986 Schwartz  
 4,625,274 A 11/1986 Schroeder  
 4,638,445 A 1/1987 Mattaboni  
 4,652,204 A 3/1987 Arnett  
 4,669,168 A 6/1987 Tamura et al.  
 4,679,152 A 7/1987 Perdue

4,697,278 A 9/1987 Fleischer  
 4,697,472 A 10/1987 Hiyane  
 4,709,265 A 11/1987 Silverman et al.  
 4,733,737 A 3/1988 Falamak  
 4,751,658 A 6/1988 Kadonoff et al.  
 4,766,581 A 8/1988 Korn et al.  
 4,777,416 A 10/1988 George, II et al.  
 4,797,557 A 1/1989 Ohman  
 4,803,625 A 2/1989 Fu et al.  
 4,847,764 A 7/1989 Halvorson  
 4,875,172 A 10/1989 Kanayama  
 4,878,501 A 11/1989 Shue  
 4,942,512 A 7/1990 Kohno  
 4,942,538 A 7/1990 Yuan et al.  
 4,953,159 A 8/1990 Hayden et al.  
 4,974,607 A 12/1990 Miwa  
 4,977,971 A 12/1990 Crane, III et al.  
 5,006,988 A 4/1991 Borenstein et al.  
 5,040,116 A 8/1991 Evans, Jr. et al.  
 5,051,906 A 9/1991 Evans, Jr. et al.  
 5,073,749 A 12/1991 Kanayama  
 5,084,828 A 1/1992 Kaufman et al.  
 5,130,794 A 7/1992 Ritchey  
 5,148,591 A 9/1992 Pryor  
 5,153,833 A 10/1992 Gordon et al.  
 5,155,684 A 10/1992 Burke et al.  
 5,157,491 A 10/1992 Kassatly  
 5,182,641 A 1/1993 Diner et al.  
 5,186,270 A 2/1993 West  
 5,193,143 A 3/1993 Kaemmerer et al.  
 5,217,453 A 6/1993 Wilk  
 5,220,263 A 6/1993 Onishi et al.  
 5,224,157 A 6/1993 Yamada et al.  
 5,230,023 A 7/1993 Nakano  
 5,231,693 A 7/1993 Backes et al.  
 5,236,432 A 8/1993 Matsen, III et al.  
 5,262,944 A 11/1993 Weisner et al.  
 5,305,427 A 4/1994 Nagata  
 5,315,287 A 5/1994 Sol  
 5,319,611 A 6/1994 Korba  
 5,341,242 A 8/1994 Gilboa et al.  
 5,341,459 A 8/1994 Backes  
 5,341,854 A 8/1994 Zezulka et al.  
 5,347,306 A 9/1994 Nitta  
 5,347,457 A 9/1994 Tanaka et al.  
 5,350,033 A 9/1994 Kraft  
 5,366,896 A 11/1994 Margrey et al.  
 5,374,879 A 12/1994 Pin et al.  
 5,375,195 A 12/1994 Johnston  
 5,400,068 A 3/1995 Ishida et al.  
 5,413,693 A 5/1995 Redepenning  
 5,417,210 A 5/1995 Funda et al.  
 5,419,008 A 5/1995 West  
 5,436,542 A 7/1995 Petelin et al.  
 5,441,042 A 8/1995 Putman  
 5,441,047 A 8/1995 David et al.  
 5,442,728 A 8/1995 Kaufman et al.  
 5,462,051 A 10/1995 Oka et al.  
 5,486,853 A 1/1996 Baxter et al.  
 5,510,832 A 4/1996 Garcia  
 5,511,147 A 4/1996 Abdel-Malek  
 5,528,289 A 6/1996 Cortjens et al.  
 5,539,741 A 7/1996 Barraclough et al.  
 5,544,649 A 8/1996 David et al.  
 5,550,577 A 8/1996 Verbiest et al.  
 5,553,609 A 9/1996 Chen et al.  
 5,563,998 A 10/1996 Yaksich et al.  
 5,572,229 A 11/1996 Fisher  
 5,572,999 A 11/1996 Funda et al.  
 5,594,859 A 1/1997 Palmer et al.  
 5,600,573 A 2/1997 Hendricks et al.  
 5,617,539 A 4/1997 Ludwig et al.  
 5,619,341 A 4/1997 Auyeung et al.  
 5,623,679 A 4/1997 Rivette et al.  
 5,630,566 A 5/1997 Case  
 5,636,218 A 6/1997 Ishikawa et al.  
 5,652,849 A 7/1997 Conway et al.  
 5,657,246 A 8/1997 Hogan et al.  
 5,659,779 A 8/1997 Laird et al.

(56)

## References Cited

## U.S. PATENT DOCUMENTS

5,673,082	A	9/1997	Wells et al.	6,321,137	B1	11/2001	De Smet
5,675,229	A	10/1997	Thorne	6,324,184	B1	11/2001	Hou et al.
5,682,199	A	10/1997	Lankford	6,324,443	B1	11/2001	Kurakake et al.
5,684,695	A	11/1997	Bauer	6,325,756	B1	12/2001	Webb et al.
5,701,904	A	12/1997	Simmons et al.	6,327,516	B1	12/2001	Zenke
5,734,805	A	3/1998	Isensee et al.	6,330,486	B1	12/2001	Padula
5,739,657	A	4/1998	Takayama et al.	6,330,493	B1	12/2001	Takahashi et al.
5,748,629	A	5/1998	Caldara et al.	6,346,950	B1	2/2002	Jouppi
5,749,058	A	5/1998	Hashimoto	6,346,962	B1	2/2002	Goodridge
5,749,362	A	5/1998	Funda et al.	6,369,847	B1	4/2002	James et al.
5,754,631	A	5/1998	Cave	6,373,855	B1	4/2002	Downing et al.
5,758,079	A	5/1998	Ludwig et al.	6,381,515	B1	4/2002	Inoue et al.
5,762,458	A	6/1998	Wang et al.	6,389,329	B1	5/2002	Colens
5,764,731	A	6/1998	Yablon	6,400,378	B1	6/2002	Snook
5,767,897	A	6/1998	Howell	6,408,230	B2	6/2002	Wada
5,786,846	A	7/1998	Hiroaki	6,411,055	B1	6/2002	Fujita et al.
5,787,545	A	8/1998	Colens	6,430,471	B1	8/2002	Kintou et al.
5,793,365	A	8/1998	Tang et al.	6,430,475	B2	8/2002	Okamoto et al.
5,801,755	A	9/1998	Echerer	6,438,457	B1	8/2002	Yokoo et al.
5,802,494	A	9/1998	Kuno	6,445,964	B1	9/2002	White et al.
5,836,872	A	11/1998	Kenet et al.	6,449,762	B1	9/2002	McElvain
5,838,575	A	11/1998	Lion	6,452,915	B1	9/2002	Jorgensen
5,844,599	A	12/1998	Hildin	6,457,043	B1	9/2002	Kwak et al.
5,857,534	A	1/1999	DeVault et al.	6,459,955	B1	10/2002	Bartsch et al.
5,867,494	A	2/1999	Krishnaswamy et al.	6,463,352	B1	10/2002	Tadokoro et al.
5,867,653	A	2/1999	Aras et al.	6,463,361	B1	10/2002	Wang et al.
5,871,451	A	2/1999	Unger et al.	6,466,844	B1	10/2002	Ikeda et al.
5,872,922	A	2/1999	Hogan et al.	6,468,265	B1	10/2002	Evans et al.
5,876,325	A	3/1999	Mizuno et al.	6,470,235	B2	10/2002	Kasuga et al.
5,911,036	A	6/1999	Wright et al.	6,474,434	B1	11/2002	Bech
5,917,958	A	6/1999	Nunally et al.	6,480,762	B1	11/2002	Uchikubo et al.
5,927,423	A	7/1999	Wada et al.	6,491,701	B2	12/2002	Tierney et al.
5,949,758	A	9/1999	Kober	6,496,099	B2	12/2002	Wang et al.
5,954,692	A	9/1999	Smith et al.	6,496,755	B2	12/2002	Wallach et al.
5,959,423	A	9/1999	Nakanishi et al.	6,501,740	B1	12/2002	Sun et al.
5,961,446	A	10/1999	Beller et al.	6,507,773	B2	1/2003	Parker et al.
5,966,130	A	10/1999	Benman, Jr.	6,522,906	B1	2/2003	Salisbury, Jr. et al.
5,973,724	A	10/1999	Riddle	6,523,629	B1	2/2003	Buttz et al.
5,974,446	A	10/1999	Sonnenreich et al.	6,526,332	B2	2/2003	Sakamoto et al.
5,983,263	A	11/1999	Rothrock et al.	6,529,620	B2	3/2003	Thompson
5,995,119	A	11/1999	Cosatto et al.	6,529,765	B1	3/2003	Franck et al.
5,995,884	A	11/1999	Allen et al.	6,529,802	B1	3/2003	Kawakita et al.
5,999,977	A	12/1999	Riddle	6,532,404	B2	3/2003	Colens
6,006,946	A	12/1999	Williams et al.	6,535,182	B2	3/2003	Stanton
6,031,845	A	2/2000	Walding	6,535,793	B2	3/2003	Allard
6,036,812	A	3/2000	Williams et al.	6,540,039	B1	4/2003	Yu et al.
6,047,259	A	4/2000	Campbell et al.	6,543,899	B2	4/2003	Covannon et al.
6,091,219	A	7/2000	Maruo et al.	6,549,215	B2	4/2003	Jouppi
6,113,343	A	9/2000	Goldenberg et al.	6,563,533	B1	5/2003	Colby
6,133,944	A	10/2000	Braun et al.	6,567,038	B1	5/2003	Granot et al.
6,135,228	A	10/2000	Asada et al.	6,580,246	B2	6/2003	Jacobs
6,148,100	A	11/2000	Anderson et al.	6,581,798	B2	6/2003	Liff et al.
6,160,582	A	12/2000	Hill	6,584,376	B1	6/2003	Van Kommer
6,170,929	B1	1/2001	Wilson et al.	6,587,750	B2	7/2003	Gerbi et al.
6,175,779	B1	1/2001	Barrett	6,590,604	B1	7/2003	Tucker et al.
6,189,034	B1	2/2001	Riddle	6,594,269	B1	7/2003	Polcyn
6,201,984	B1	3/2001	Funda et al.	6,594,552	B1	7/2003	Nowlin et al.
6,211,903	B1	4/2001	Bullister	6,597,392	B1	7/2003	Jenkins et al.
6,219,587	B1	4/2001	Ahlin et al.	6,602,469	B1	8/2003	Maus et al.
6,232,735	B1	5/2001	Baba et al.	6,604,019	B2	8/2003	Ahlin et al.
6,233,504	B1	5/2001	Das et al.	6,604,021	B2	8/2003	Imai et al.
6,233,735	B1	5/2001	Ebihara	6,611,120	B2	8/2003	Song et al.
6,250,928	B1	6/2001	Poggio et al.	6,643,496	B1	11/2003	Shimoyama et al.
6,256,556	B1	7/2001	Zenke	6,646,677	B2	11/2003	Noro et al.
6,259,806	B1	7/2001	Green	6,650,748	B1	11/2003	Edwards et al.
6,259,956	B1	7/2001	Myers et al.	6,666,374	B1	12/2003	Green et al.
6,266,162	B1	7/2001	Okamura et al.	6,667,592	B2	12/2003	Jacobs et al.
6,266,577	B1	7/2001	Popp et al.	6,674,259	B1	1/2004	Norman et al.
6,289,263	B1	9/2001	Mukherjee	6,684,129	B2	1/2004	Salisbury, Jr. et al.
6,292,713	B1	9/2001	Jouppi et al.	6,691,000	B2	2/2004	Nagai et al.
6,292,714	B1	9/2001	Okabayashi	6,693,585	B1	2/2004	MacLeod
6,304,050	B1	10/2001	Skaar et al.	6,710,797	B1	3/2004	McNelley et al.
6,314,631	B1	11/2001	Pryor	6,724,823	B2	4/2004	Rovati et al.
6,317,652	B1	11/2001	Osada	6,728,599	B2	4/2004	Wang et al.
6,317,953	B1	11/2001	Pryor	6,763,282	B2	7/2004	Glenn et al.
				6,764,373	B1	7/2004	Osawa et al.
				6,769,771	B2	8/2004	Trumbull
				6,781,606	B2	8/2004	Jouppi
				6,784,916	B2	8/2004	Smith

(56)

## References Cited

## U.S. PATENT DOCUMENTS

6,785,589 B2	8/2004	Eggenberger et al.	7,219,364 B2	5/2007	Bolle et al.
6,791,550 B2	9/2004	Goldhor et al.	7,222,000 B2	5/2007	Wang et al.
6,798,753 B1	9/2004	Doganata et al.	7,227,334 B2	6/2007	Yang et al.
6,799,065 B1	9/2004	Niemeyer	7,256,708 B2	8/2007	Rosenfeld et al.
6,799,088 B2	9/2004	Wang et al.	7,262,573 B2	8/2007	Wang et al.
6,804,580 B1	10/2004	Stoddard et al.	7,283,153 B2	10/2007	Provost et al.
6,804,656 B1*	10/2004	Rosenfeld .....	7,289,883 B2	10/2007	Wang et al.
		G06F 19/322	7,292,257 B2	11/2007	Kang et al.
		600/300	7,292,912 B2	11/2007	Wang et al.
6,810,411 B1	10/2004	Coughlin et al.	7,305,114 B2	12/2007	Wolff et al.
6,816,192 B1	11/2004	Nishikawa	7,317,685 B1	1/2008	Flott et al.
6,816,754 B2	11/2004	Mukai et al.	7,321,807 B2	1/2008	Laski
6,836,703 B2	12/2004	Wang et al.	7,332,890 B2	2/2008	Cohen et al.
6,839,612 B2	1/2005	Sanchez et al.	7,333,642 B2	2/2008	Green
6,840,904 B2	1/2005	Goldberg	7,346,429 B2	3/2008	Goldenberg et al.
6,845,297 B2	1/2005	Allard	7,352,153 B2	4/2008	Yan
6,852,107 B2	2/2005	Wang et al.	7,363,121 B1	4/2008	Chen et al.
6,853,878 B2	2/2005	Hirayama et al.	7,382,399 B1	6/2008	McCall et al.
6,853,880 B2	2/2005	Sakagami et al.	7,386,730 B2	6/2008	Uchikubo
6,871,117 B2	3/2005	Wang et al.	7,391,432 B2	6/2008	Terada
6,879,879 B2	4/2005	Jouppi et al.	7,400,578 B2	7/2008	Guthrie et al.
6,888,333 B2	5/2005	Laby	7,404,140 B2	7/2008	O'rourke
6,892,112 B2	5/2005	Wang et al.	7,421,470 B2	9/2008	Ludwig et al.
6,893,267 B1	5/2005	Yueh	7,430,209 B2	9/2008	Porter
6,895,305 B2	5/2005	Lathan et al.	7,432,949 B2	10/2008	Remy et al.
6,898,484 B2	5/2005	Lemelson et al.	7,433,921 B2	10/2008	Ludwig et al.
6,914,622 B1	7/2005	Smith et al.	7,441,953 B2	10/2008	Banks
6,925,357 B2	8/2005	Wang et al.	7,467,211 B1	12/2008	Herman et al.
6,951,535 B2	10/2005	Ghodoussi et al.	7,483,867 B2	1/2009	Ansari et al.
6,952,470 B1	10/2005	Tioe et al.	7,492,731 B2	2/2009	Hagendorf
6,957,712 B2	10/2005	Song et al.	7,510,428 B2	3/2009	Obata et al.
6,958,706 B2	10/2005	Chaco et al.	7,523,069 B1	4/2009	Friedl et al.
6,965,394 B2	11/2005	Gutta et al.	7,525,281 B2	4/2009	Koyanagi et al.
6,990,112 B1	1/2006	Brent et al.	7,535,486 B2	5/2009	Motomura et al.
6,995,664 B1	2/2006	Darling	7,557,758 B2	7/2009	Rofougaran
7,007,235 B1	2/2006	Hussein et al.	7,587,260 B2	9/2009	Bruemmer et al.
7,011,538 B2	3/2006	Chang	7,587,512 B2	9/2009	Ta et al.
7,015,934 B2	3/2006	Toyama et al.	7,590,060 B2	9/2009	Miceli
RE39,080 E	4/2006	Johnston	7,593,030 B2	9/2009	Wang et al.
7,030,757 B2	4/2006	Matsuhira et al.	7,599,290 B2	10/2009	Dos Remedios et al.
7,053,578 B2	5/2006	Diehl et al.	7,624,166 B2	11/2009	Foote et al.
7,055,210 B2	6/2006	Keppler et al.	7,630,314 B2	12/2009	Dos Remedios et al.
7,058,689 B2	6/2006	Parker et al.	7,631,833 B1	12/2009	Ghaleb et al.
7,092,001 B2	8/2006	Schulz	7,643,051 B2	1/2010	Sandberg et al.
7,096,090 B1	8/2006	Zweig	7,647,320 B2	1/2010	Mok et al.
7,115,102 B2	10/2006	Abbruscato	7,657,560 B1	2/2010	Dirienzo
7,117,067 B2	10/2006	McLurkin et al.	7,680,038 B1	3/2010	Gourlay
7,123,285 B2	10/2006	Smith et al.	7,693,757 B2	4/2010	Zimmerman
7,123,974 B1	10/2006	Hamilton	7,698,432 B2	4/2010	Short et al.
7,123,991 B2	10/2006	Graf et al.	7,703,113 B2	4/2010	Dawson
7,127,325 B2	10/2006	Nagata et al.	7,719,229 B2	5/2010	Kaneko et al.
7,129,970 B2	10/2006	James et al.	7,737,993 B2	6/2010	Kaasila et al.
7,133,062 B2	11/2006	Castles et al.	7,739,383 B1	6/2010	Short et al.
7,142,945 B2	11/2006	Wang et al.	7,756,614 B2	7/2010	Jouppi
7,142,947 B2	11/2006	Wang et al.	7,761,185 B2	7/2010	Wang et al.
7,151,982 B2	12/2006	Liff et al.	7,769,492 B2	8/2010	Wang et al.
7,154,526 B2	12/2006	Foote et al.	7,769,705 B1	8/2010	Luechtefeld
7,155,306 B2	12/2006	Haitin et al.	7,774,158 B2	8/2010	Domingues et al.
7,156,809 B2	1/2007	Quy	7,813,836 B2	10/2010	Wang et al.
7,158,859 B2	1/2007	Wang et al.	7,831,575 B2	11/2010	Trossell et al.
7,158,860 B2	1/2007	Wang et al.	7,835,775 B2	11/2010	Sawayama et al.
7,158,861 B2	1/2007	Wang et al.	7,860,680 B2	12/2010	Arms et al.
7,161,322 B2	1/2007	Wang et al.	7,861,366 B2	1/2011	Hahm et al.
7,162,338 B2	1/2007	Goncalves et al.	7,885,822 B2	2/2011	Akers et al.
7,164,969 B2	1/2007	Wang et al.	7,890,382 B2	2/2011	Robb et al.
7,164,970 B2	1/2007	Wang et al.	7,912,583 B2	3/2011	Gutmann et al.
7,167,448 B2	1/2007	Wookey et al.	RE42,288 E	4/2011	Degioanni
7,171,286 B2	1/2007	Wang et al.	7,924,323 B2	4/2011	Walker et al.
7,174,238 B1	2/2007	Zweig	7,949,616 B2	5/2011	Levy et al.
7,181,455 B2	2/2007	Wookey et al.	7,956,894 B2	6/2011	Akers et al.
7,184,559 B2	2/2007	Jouppi	7,957,837 B2	6/2011	Ziegler et al.
7,188,000 B2	3/2007	Chiappetta et al.	7,982,763 B2	7/2011	King
7,199,790 B2	4/2007	Rosenberg et al.	7,982,769 B2	7/2011	Jenkins et al.
7,202,851 B2	4/2007	Cunningham et al.	7,987,069 B2	7/2011	Rodgers et al.
7,206,627 B2	4/2007	Abovitz et al.	8,077,963 B2	12/2011	Wang et al.
7,215,786 B2	5/2007	Nakadal et al.	8,116,910 B2	2/2012	Walters et al.
			8,126,960 B2	2/2012	Obradovich et al.
			8,170,241 B2	5/2012	Roe et al.
			8,179,418 B2	5/2012	Wright et al.

(56)

## References Cited

## U.S. PATENT DOCUMENTS

8,180,486	B2	5/2012	Saito et al.	2003/0030397	A1	2/2003	Simmons
8,209,051	B2	6/2012	Wang et al.	2003/0048481	A1	3/2003	Kobayashi et al.
8,212,533	B2	7/2012	Ota	2003/0050733	A1	3/2003	Wang et al.
8,265,793	B2	9/2012	Cross et al.	2003/0050734	A1	3/2003	Lapham
8,287,522	B2	10/2012	Moses et al.	2003/0060808	A1	3/2003	Wilk
8,292,807	B2	10/2012	Perkins et al.	2003/0063600	A1	4/2003	Noma et al.
8,340,654	B2	12/2012	Bratton et al.	2003/0069752	A1	4/2003	Ledain et al.
8,340,819	B2	12/2012	Mangaser et al.	2003/0080901	A1	5/2003	Piotrowski
8,348,675	B2	1/2013	Dohrmann	2003/0100892	A1	5/2003	Morley et al.
8,374,171	B2	2/2013	Cho et al.	2003/0104806	A1	6/2003	Ruef et al.
8,400,491	B1	3/2013	Panpaliya et al.	2003/0112823	A1	6/2003	Collins et al.
8,401,275	B2	3/2013	Wang et al.	2003/0114962	A1	6/2003	Niemeyer et al.
8,423,284	B2	4/2013	O'Shea	2003/0120714	A1	6/2003	Wolff et al.
8,451,731	B1	5/2013	Lee et al.	2003/0126361	A1	7/2003	Slater et al.
8,463,435	B2	6/2013	Herzog et al.	2003/0135097	A1	7/2003	Wiederhold et al.
8,503,340	B1	8/2013	Xu	2003/0135203	A1	7/2003	Wang et al.
8,515,577	B2	8/2013	Wang et al.	2003/0144579	A1	7/2003	Buss
8,527,094	B2	9/2013	Kumar et al.	2003/0144649	A1	7/2003	Ghodoussi et al.
8,532,860	B2	9/2013	Daly	2003/0151658	A1	8/2003	Smith
8,610,786	B2	12/2013	Ortiz	2003/0152145	A1	8/2003	Kawakita
8,612,051	B2	12/2013	Norman et al.	2003/0171710	A1	9/2003	Bassuk et al.
8,639,797	B1	1/2014	Pan et al.	2003/0174285	A1	9/2003	Trumbull
8,670,017	B2	3/2014	Stuart et al.	2003/0180697	A1	9/2003	Kim et al.
8,726,454	B2	5/2014	Gilbert, Jr. et al.	2003/0195662	A1	10/2003	Wang et al.
8,836,751	B2	9/2014	Ballantyne et al.	2003/0199000	A1	10/2003	Valkirs et al.
8,849,679	B2	9/2014	Wang et al.	2003/0206242	A1	11/2003	Choi
8,849,680	B2	9/2014	Wright et al.	2003/0212472	A1	11/2003	McKee
8,861,750	B2	10/2014	Roe et al.	2003/0216833	A1	11/2003	Mukai et al.
8,897,920	B2	11/2014	Wang et al.	2003/0216834	A1	11/2003	Allard
8,902,278	B2	12/2014	Pinter et al.	2003/0220541	A1	11/2003	Salisbury, Jr. et al.
2001/0002448	A1	5/2001	Wilson et al.	2003/0220715	A1	11/2003	Kneifel, II et al.
2001/0010053	A1	7/2001	Ben-Shachar et al.	2003/0231244	A1	12/2003	Bonilla et al.
2001/0020200	A1	9/2001	Das et al.	2003/0232649	A1	12/2003	Gizis et al.
2001/0034475	A1	10/2001	Flach et al.	2003/0236590	A1	12/2003	Park et al.
2001/0034544	A1	10/2001	Mo	2004/0001197	A1	1/2004	Ko et al.
2001/0037163	A1	11/2001	Allard	2004/0001676	A1	1/2004	Colgan et al.
2001/0048464	A1	12/2001	Barnett	2004/0008138	A1	1/2004	Hockley, Jr. et al.
2001/0051881	A1	12/2001	Filler	2004/0010344	A1	1/2004	Hiratsuka et al.
2001/0054071	A1	12/2001	Loeb	2004/0012362	A1	1/2004	Tsurumi
2001/0055373	A1	12/2001	Yamashita	2004/0013295	A1	1/2004	Sabe et al.
2002/0015296	A1	2/2002	Howell et al.	2004/0017475	A1	1/2004	Akers et al.
2002/0027597	A1	3/2002	Sachau	2004/0019406	A1	1/2004	Wang et al.
2002/0027652	A1	3/2002	Paromtchik et al.	2004/0024490	A1	2/2004	McLurkin et al.
2002/0033880	A1	3/2002	Sul et al.	2004/0041904	A1	3/2004	Lapalme et al.
2002/0038168	A1	3/2002	Kasuga et al.	2004/0065073	A1	4/2004	Nash
2002/0044201	A1	4/2002	Alexander et al.	2004/0068657	A1	4/2004	Alexander et al.
2002/0049517	A1	4/2002	Ruffner	2004/0078219	A1	4/2004	Kaylor et al.
2002/0055917	A1	5/2002	Muraca	2004/0080610	A1	4/2004	James et al.
2002/0057279	A1	5/2002	Jouppi	2004/0088077	A1	5/2004	Jouppi et al.
2002/0058929	A1	5/2002	Green	2004/0088078	A1	5/2004	Jouppi et al.
2002/0059587	A1	5/2002	Cofano et al.	2004/0093409	A1	5/2004	Thompson et al.
2002/0063726	A1	5/2002	Jouppi	2004/0095516	A1	5/2004	Rohlicek
2002/0073429	A1	6/2002	Beane et al.	2004/0098167	A1	5/2004	Yi et al.
2002/0082498	A1	6/2002	Wendt et al.	2004/0102167	A1	5/2004	Shim et al.
2002/0085030	A1	7/2002	Ghani	2004/0107254	A1	6/2004	Ludwig et al.
2002/0095238	A1	7/2002	Ahlin et al.	2004/0107255	A1	6/2004	Ludwig et al.
2002/0095239	A1	7/2002	Wallach et al.	2004/0117065	A1	6/2004	Wang et al.
2002/0098879	A1	7/2002	Rheey	2004/0117067	A1	6/2004	Jouppi
2002/0104094	A1	8/2002	Alexander et al.	2004/0123158	A1	6/2004	Roskind
2002/0106998	A1	8/2002	Presley et al.	2004/0135879	A1	7/2004	Stacy et al.
2002/0109770	A1	8/2002	Terada	2004/0138547	A1	7/2004	Wang et al.
2002/0109775	A1	8/2002	White et al.	2004/0143421	A1	7/2004	Wang et al.
2002/0111988	A1	8/2002	Sato	2004/0148638	A1	7/2004	Weisman et al.
2002/0120362	A1	8/2002	Lathan et al.	2004/0150725	A1	8/2004	Taguchi
2002/0128985	A1	9/2002	Greenwald	2004/0153211	A1	8/2004	Kamoto et al.
2002/0130950	A1	9/2002	James et al.	2004/0157612	A1	8/2004	Kim
2002/0133062	A1	9/2002	Arling et al.	2004/0162637	A1	8/2004	Wang et al.
2002/0141595	A1	10/2002	Alexander	2004/0167666	A1	8/2004	Wang et al.
2002/0143923	A1	10/2002	Alexander	2004/0167668	A1	8/2004	Wang et al.
2002/0177925	A1	11/2002	Onishi et al.	2004/0168148	A1	8/2004	Goncalves et al.
2002/0183894	A1	12/2002	Wang et al.	2004/0170300	A1	9/2004	Jouppi
2002/0184674	A1	12/2002	Xi et al.	2004/0172301	A1	9/2004	Mihai et al.
2002/0186243	A1	12/2002	Ellis et al.	2004/0172306	A1	9/2004	Wohl et al.
2003/0016726	A1	1/2003	Pavlidis	2004/0174129	A1	9/2004	Wang et al.
2003/0021107	A1	1/2003	Howell et al.	2004/0175684	A1	9/2004	Kaasa et al.
				2004/0179714	A1	9/2004	Jouppi
				2004/0186623	A1	9/2004	Dooley et al.
				2004/0189700	A1	9/2004	Mandavilli et al.
				2004/0201602	A1	10/2004	Mody et al.

(56)

## References Cited

## U.S. PATENT DOCUMENTS

2004/0205664	A1	10/2004	Prendergast	2006/0066609	A1	3/2006	Iodice et al.
2004/0215490	A1	10/2004	Duchon et al.	2006/0071797	A1	4/2006	Rosenfeld et al.
2004/0218099	A1	11/2004	Washington	2006/0074525	A1	4/2006	Close et al.
2004/0222638	A1	11/2004	Bednyak	2006/0074719	A1	4/2006	Horner
2004/0224676	A1	11/2004	Iseki	2006/0082642	A1	4/2006	Wang et al.
2004/0230340	A1	11/2004	Fukuchi et al.	2006/0087746	A1	4/2006	Lipow
2004/0240981	A1	12/2004	Dothan et al.	2006/0095158	A1	5/2006	Lee et al.
2004/0241981	A1	12/2004	Doris et al.	2006/0095170	A1	5/2006	Yang et al.
2004/0260790	A1	12/2004	Balloni et al.	2006/0098573	A1	5/2006	Beer et al.
2005/0003330	A1	1/2005	Asgarinejad et al.	2006/0103659	A1	5/2006	Karandikar et al.
2005/0004708	A1	1/2005	Goldenberg et al.	2006/0104279	A1	5/2006	Fellman et al.
2005/0007445	A1	1/2005	Foote et al.	2006/0106493	A1	5/2006	Niemeyer et al.
2005/0013149	A1	1/2005	Trossell	2006/0122482	A1	6/2006	Mariotti et al.
2005/0021182	A1	1/2005	Wang et al.	2006/0125356	A1	6/2006	MEEK, Jr. et al.
2005/0021183	A1	1/2005	Wang et al.	2006/0142983	A1	6/2006	Sorensen et al.
2005/0021187	A1	1/2005	Wang et al.	2006/0149418	A1	7/2006	Anvari
2005/0021309	A1	1/2005	Alexander et al.	2006/0161136	A1	7/2006	Anderson et al.
2005/0024485	A1	2/2005	Castles et al.	2006/0161303	A1	7/2006	Wang et al.
2005/0027567	A1	2/2005	Taha	2006/0164546	A1	7/2006	Adachi
2005/0027794	A1	2/2005	Decker	2006/0171515	A1	8/2006	Hintermeister et al.
2005/0028221	A1	2/2005	Liu et al.	2006/0173708	A1	8/2006	Vining et al.
2005/0035862	A1	2/2005	Wildman et al.	2006/0173712	A1	8/2006	Joubert
2005/0038416	A1	2/2005	Wang et al.	2006/0178559	A1	8/2006	Kumar et al.
2005/0038564	A1	2/2005	Burick	2006/0178776	A1	8/2006	Feingold et al.
2005/0049898	A1	3/2005	Hirakawa	2006/0178777	A1	8/2006	Park et al.
2005/0052527	A1	3/2005	Remy et al.	2006/0184274	A1	8/2006	Sakai et al.
2005/0060211	A1	3/2005	Xiao et al.	2006/0189393	A1	8/2006	Edery
2005/0065435	A1	3/2005	Rauch et al.	2006/0195569	A1	8/2006	Barker
2005/0065438	A1	3/2005	Miller	2006/0224781	A1	10/2006	Tsao et al.
2005/0065659	A1	3/2005	Tanaka et al.	2006/0247045	A1	11/2006	Jeong et al.
2005/0065813	A1	3/2005	Mishelevich et al.	2006/0259193	A1	11/2006	Wang et al.
2005/0071046	A1	3/2005	Miyazaki et al.	2006/0268704	A1	11/2006	Ansari et al.
2005/0073575	A1	4/2005	Thacher et al.	2006/0271238	A1	11/2006	Choi et al.
2005/0078816	A1	4/2005	Sekiguchi et al.	2006/0271400	A1	11/2006	Clements et al.
2005/0083011	A1	4/2005	Yang et al.	2006/0293788	A1	12/2006	Pogodin
2005/0099493	A1	5/2005	Chew	2007/0021871	A1	1/2007	Wang et al.
2005/0104964	A1	5/2005	Bovytrin et al.	2007/0025711	A1	2/2007	Marcus
2005/0110867	A1	5/2005	Schulz	2007/0046237	A1	3/2007	Lakshmanan et al.
2005/0122390	A1	6/2005	Wang et al.	2007/0050937	A1	3/2007	Song et al.
2005/0125083	A1	6/2005	Kiko	2007/0064092	A1	3/2007	Sandberg et al.
2005/0125098	A1	6/2005	Wang et al.	2007/0078566	A1	4/2007	Wang et al.
2005/0149364	A1	7/2005	Ombrellaro	2007/0093279	A1	4/2007	Janik
2005/0152447	A1	7/2005	Jouppi et al.	2007/0112700	A1	5/2007	Den et al.
2005/0152565	A1	7/2005	Jouppi et al.	2007/0116152	A1	5/2007	Thesling
2005/0154265	A1	7/2005	Miro et al.	2007/0117516	A1	5/2007	Saidi et al.
2005/0168568	A1	8/2005	Jouppi	2007/0120965	A1	5/2007	Sandberg et al.
2005/0182322	A1	8/2005	Grispo	2007/0122783	A1	5/2007	Habashi
2005/0192721	A1	9/2005	Jouppi	2007/0133407	A1	6/2007	Choi et al.
2005/0204438	A1	9/2005	Wang et al.	2007/0135967	A1	6/2007	Jung et al.
2005/0212478	A1	9/2005	Takenaka	2007/0142964	A1	6/2007	Abramson
2005/0219356	A1	10/2005	Smith et al.	2007/0170886	A1	7/2007	Plishner
2005/0225634	A1	10/2005	Brunetti et al.	2007/0176060	A1	8/2007	White et al.
2005/0231156	A1	10/2005	Yan	2007/0192910	A1	8/2007	Vu et al.
2005/0231586	A1	10/2005	Rodman et al.	2007/0197896	A1	8/2007	Moll et al.
2005/0232647	A1	10/2005	Takenaka	2007/0198128	A1	8/2007	Ziegler et al.
2005/0234592	A1	10/2005	McGee et al.	2007/0198130	A1	8/2007	Wang et al.
2005/0264649	A1	12/2005	Chang et al.	2007/0199108	A1	8/2007	Angle et al.
2005/0267826	A1	12/2005	Levy et al.	2007/0216347	A1	9/2007	Kaneko et al.
2005/0283414	A1	12/2005	Fernandes et al.	2007/0226949	A1	10/2007	Hahm et al.
2005/0286759	A1	12/2005	Zitnick et al.	2007/0250212	A1	10/2007	Halloran et al.
2006/0007943	A1	1/2006	Fellman	2007/0255115	A1	11/2007	Anglin et al.
2006/0010028	A1	1/2006	Sorensen	2007/0255706	A1	11/2007	Iketani et al.
2006/0013263	A1	1/2006	Fellman	2007/0262884	A1	11/2007	Goncalves et al.
2006/0013469	A1	1/2006	Wang et al.	2007/0273751	A1	11/2007	Sachau
2006/0013488	A1	1/2006	Inoue	2007/0290040	A1	12/2007	Wurman et al.
2006/0014388	A1	1/2006	Lur et al.	2007/0291109	A1	12/2007	Wang et al.
2006/0020694	A1	1/2006	Nag et al.	2007/0291128	A1	12/2007	Wang et al.
2006/0029065	A1	2/2006	Fellman	2008/0009969	A1	1/2008	Bruemmer et al.
2006/0047365	A1	3/2006	Ghodoussi et al.	2008/0011904	A1	1/2008	Cepollina et al.
2006/0048286	A1	3/2006	Donato	2008/0027591	A1	1/2008	Lenser et al.
2006/0052676	A1	3/2006	Wang et al.	2008/0033641	A1	2/2008	Medalia
2006/0052684	A1	3/2006	Takahashi et al.	2008/0045804	A1	2/2008	Williams
2006/0056655	A1	3/2006	Wen et al.	2008/0051985	A1	2/2008	D'Andrea et al.
2006/0056837	A1	3/2006	Vapaakoski	2008/0056933	A1	3/2008	Moore et al.
2006/0064212	A1	3/2006	Thorne	2008/0065268	A1	3/2008	Wang et al.
				2008/0082211	A1	4/2008	Wang et al.
				2008/0086241	A1	4/2008	Phillips et al.
				2008/0091340	A1	4/2008	Milstein et al.
				2008/0126132	A1	5/2008	Warner et al.

(56)

## References Cited

## U.S. PATENT DOCUMENTS

2008/0133052 A1 6/2008 Jones et al.  
 2008/0161969 A1 7/2008 Lee et al.  
 2008/0174570 A1 7/2008 Jobs et al.  
 2008/0201016 A1 8/2008 Finlay  
 2008/0201017 A1 8/2008 Wang et al.  
 2008/0215987 A1 9/2008 Alexander et al.  
 2008/0229531 A1 9/2008 Takida  
 2008/0232763 A1 9/2008 Brady  
 2008/0255703 A1 10/2008 Wang et al.  
 2008/0263451 A1 10/2008 Portele et al.  
 2008/0263628 A1 10/2008 Norman et al.  
 2008/0267069 A1 10/2008 Thielman et al.  
 2008/0269949 A1 10/2008 Norman et al.  
 2008/0281467 A1 11/2008 Pinter  
 2008/0306375 A1 12/2008 Sayler et al.  
 2009/0030552 A1 1/2009 Nakadai et al.  
 2009/0044334 A1 2/2009 Parsell et al.  
 2009/0049640 A1 2/2009 Lee et al.  
 2009/0055023 A1 2/2009 Walters et al.  
 2009/0070135 A1 3/2009 Parida et al.  
 2009/0086013 A1 4/2009 Thapa  
 2009/0102919 A1 4/2009 Zamierowski et al.  
 2009/0105882 A1 4/2009 Wang et al.  
 2009/0106679 A1 4/2009 Anzures et al.  
 2009/0122699 A1 5/2009 Alperovitch et al.  
 2009/0125147 A1 5/2009 Wang et al.  
 2009/0144425 A1 6/2009 Marr et al.  
 2009/0146882 A1 6/2009 Halivaara et al.  
 2009/0164255 A1 6/2009 Menschik et al.  
 2009/0164657 A1 6/2009 Li et al.  
 2009/0171170 A1 7/2009 Li et al.  
 2009/0177323 A1 7/2009 Ziegler et al.  
 2009/0177641 A1 7/2009 Raghavan  
 2009/0237317 A1 9/2009 Rofougaran  
 2009/0240371 A1 9/2009 Wang et al.  
 2009/0248200 A1 10/2009 Root  
 2009/0259339 A1 10/2009 Wright et al.  
 2010/0010672 A1 1/2010 Wang et al.  
 2010/0010673 A1 1/2010 Wang et al.  
 2010/0017046 A1 1/2010 Cheung et al.  
 2010/0019715 A1 1/2010 Roe et al.  
 2010/0026239 A1 2/2010 Li et al.  
 2010/0030578 A1 2/2010 Siddique et al.  
 2010/0051596 A1 3/2010 Diedrick et al.  
 2010/0063636 A1 3/2010 Matsumoto et al.  
 2010/0063848 A1 3/2010 Kremer et al.  
 2010/0066804 A1 3/2010 Shoemake et al.  
 2010/0070079 A1 3/2010 Mangaser et al.  
 2010/0073490 A1 3/2010 Wang et al.  
 2010/0076600 A1 3/2010 Cross et al.  
 2010/0085874 A1 4/2010 Noy et al.  
 2010/0088232 A1 4/2010 Gale  
 2010/0115418 A1 5/2010 Wang et al.  
 2010/0116566 A1 5/2010 Ohm et al.  
 2010/0128104 A1 5/2010 Fabregat et al.  
 2010/0131103 A1 5/2010 Herzog et al.  
 2010/0145479 A1 6/2010 Griffiths  
 2010/0157825 A1 6/2010 Anderlind et al.  
 2010/0171826 A1 7/2010 Hamilton et al.  
 2010/0191375 A1 7/2010 Wright et al.  
 2010/0228249 A1 9/2010 Mohr et al.  
 2010/0268383 A1 10/2010 Wang et al.  
 2010/0278086 A1 11/2010 Pochiraju et al.  
 2010/0286905 A1 11/2010 Goncalves et al.  
 2010/0301679 A1 12/2010 Murray et al.  
 2010/0323783 A1 12/2010 Nonaka et al.  
 2011/0022705 A1 1/2011 Yellamraju et al.  
 2011/0050841 A1 3/2011 Wang et al.  
 2011/0071675 A1 3/2011 Wells et al.  
 2011/0071702 A1 3/2011 Wang et al.  
 2011/0072114 A1 3/2011 Hoffert et al.  
 2011/0153198 A1 6/2011 Korkas et al.  
 2011/0172822 A1 7/2011 Ziegler et al.  
 2011/0187875 A1 8/2011 Sanchez et al.  
 2011/0190930 A1 8/2011 Hanrahan et al.

2011/0193949 A1 8/2011 Nambakam et al.  
 2011/0195701 A1 8/2011 Cook et al.  
 2011/0213210 A1 9/2011 Temby et al.  
 2011/0218674 A1 9/2011 Stuart et al.  
 2011/0245973 A1 10/2011 Wang et al.  
 2011/0280551 A1 11/2011 Sammon  
 2011/0288417 A1\* 11/2011 Pinter ..... A61B 5/0033  
 600/473  
 2011/0292193 A1 12/2011 Wang et al.  
 2011/0301759 A1 12/2011 Wang et al.  
 2011/0306400 A1 12/2011 Nguyen  
 2012/0023506 A1 1/2012 Maeckel et al.  
 2012/0036484 A1 2/2012 Zhang et al.  
 2012/0059946 A1 3/2012 Wang  
 2012/0072023 A1 3/2012 Ota  
 2012/0072024 A1 3/2012 Wang et al.  
 2012/0092157 A1 4/2012 Tran  
 2012/0095352 A1 4/2012 Tran  
 2012/0113856 A1 5/2012 Krishnaswamy  
 2012/0191246 A1 7/2012 Roe et al.  
 2012/0191464 A1 7/2012 Stuart et al.  
 2012/0203731 A1 8/2012 Nelson et al.  
 2012/0291809 A1 11/2012 Kuhe et al.  
 2013/0250938 A1 9/2013 Anandakumar et al.  
 2014/0047022 A1 2/2014 Chan et al.  
 2014/0085543 A1 3/2014 Hartley et al.  
 2014/0135990 A1 5/2014 Stuart et al.  
 2014/0139616 A1 5/2014 Pinter et al.  
 2014/0207286 A1 7/2014 Wang et al.

## FOREIGN PATENT DOCUMENTS

CN 1404695 A 3/2003  
 CN 1554193 A 12/2004  
 CN 1554985 A 12/2004  
 CN 1561923 A 1/2005  
 CN 1743144 A 3/2006  
 CN 101049017 A 10/2007  
 CN 101106939 A 1/2008  
 CN 101151614 A 3/2008  
 CN 100407729 C 7/2008  
 CN 101390098 A 3/2009  
 CN 101507260 A 8/2009  
 CN 101730894 A 6/2010  
 CN 101866396 A 10/2010  
 CN 101978365 A 2/2011  
 CN 102203759 A 9/2011  
 CN 101106939 B 11/2011  
 EP 466492 A2 1/1992  
 EP 488673 A2 6/1992  
 EP 981905 B1 1/2002  
 EP 1262142 A2 12/2002  
 EP 1304872 A1 4/2003  
 EP 1536660 A2 6/2005  
 EP 1573406 A2 9/2005  
 EP 1594660 A2 11/2005  
 EP 1763243 A2 3/2007  
 EP 1791464 A2 6/2007  
 EP 1800476 A2 6/2007  
 EP 1819108 A2 8/2007  
 EP 1856644 A2 11/2007  
 EP 1536660 A3 4/2008  
 EP 1928310 A2 6/2008  
 EP 1232610 B1 1/2009  
 EP 2027716 A2 2/2009  
 EP 2145274 A1 1/2010  
 EP 2214111 A2 8/2010  
 EP 2263158 A2 12/2010  
 EP 2300930 A1 3/2011  
 EP 2342651 A1 7/2011  
 GB 2431261 A 4/2007  
 JP 07-194609 A 8/1995  
 JP 7-213753 A 8/1995  
 JP 7-248823 A 9/1995  
 JP 7-257422 A 10/1995  
 JP 8-84328 A 3/1996  
 JP 08-166822 A 6/1996  
 JP 8-320727 A 12/1996  
 JP 9-267276 A 10/1997

(56)

## References Cited

## FOREIGN PATENT DOCUMENTS

JP	10-79097	A	3/1998
JP	10-288689	A	10/1998
JP	11-220706	A	8/1999
JP	2000-32319	A	1/2000
JP	2000-49800	A	2/2000
JP	2000-79587	A	3/2000
JP	2000-196876	A	7/2000
JP	2001-125641	A	5/2001
JP	2001-147718	A	5/2001
JP	2001-179663	A	7/2001
JP	2001-188124	A	7/2001
JP	2001-198865	A	7/2001
JP	2001-198868	A	7/2001
JP	2001-199356	A	7/2001
JP	2002-00574	A	1/2002
JP	2002-46088	A	2/2002
JP	2002-101333	A	4/2002
JP	2002-112970	A	4/2002
JP	2002-235423	A	8/2002
JP	2002-305743	A	10/2002
JP	2002-321180	A	11/2002
JP	2002-355779	A	12/2002
JP	2004-181229	A	7/2004
JP	2004-524824	T	8/2004
JP	2004-261941	A	9/2004
JP	2004-289379	A	10/2004
JP	2005-28066	A	2/2005
JP	2005-59170	A	3/2005
JP	2005-111083	A	4/2005
JP	2006-035381	A	2/2006
JP	2006-508806	A	3/2006
JP	2006-109094	A	4/2006
JP	2006-224294	A	8/2006
JP	2006-246438	A	9/2006
JP	2007-7040	A	1/2007
JP	2007-81646	A	3/2007
JP	2007-232208	A	9/2007
JP	2007-316966	A	12/2007
JP	2009-125133	A	6/2009
JP	2010-64154	A	3/2010
JP	2010-532109	A	9/2010
JP	2010-246954	A	11/2010
KR	10-2006-0037979	A	5/2006
KR	10-2009-0012542	A	2/2009
KR	10-2010-0019479	A	2/2010
KR	10-2010-0139037	A	12/2010
WO	1993/006690	A1	4/1993
WO	1997/042761	A1	11/1997
WO	1998/51078	A1	11/1998
WO	1999/67067	A1	12/1999
WO	2000/025516	A1	5/2000
WO	2000/033726	A1	6/2000
WO	2001/031861	A1	5/2001
WO	2003/077745	A1	9/2003
WO	2004/008738	A1	1/2004
WO	2004/012018	A2	2/2004
WO	2004/075456	A2	9/2004
WO	2006/012797	A1	2/2006
WO	2006/044847	A2	4/2006
WO	2006/078611	A2	7/2006
WO	2007/041295	A2	4/2007
WO	2007/041038	A3	6/2007
WO	2008/100272	A2	8/2008
WO	2008/100272	A3	10/2008
WO	2009/117274	A2	9/2009
WO	2009/128997	A1	10/2009
WO	2009/145958	A2	12/2009
WO	2010/006205	A1	1/2010
WO	2010/006211	A1	1/2010
WO	2010/033666	A1	3/2010
WO	2010/047881	A1	4/2010
WO	2010/062798	A1	6/2010
WO	2010/065257	A1	6/2010
WO	2010/120407	A1	10/2010
WO	2011/028589	A2	3/2011

WO	2011/028589	A3	4/2011
WO	2011/097130	A2	8/2011
WO	2011/097132	A2	8/2011
WO	2011/109336	A2	9/2011
WO	2011/097132	A3	12/2011
WO	2011/149902	A2	12/2011

## OTHER PUBLICATIONS

- Haule et al., "Control Scheme for Delayed Teleoperation Tasks", Communications, Computers and Signal Processing, Proceedings of IEEE Pacific Rim Conference, May 17-19, 1995, pp. 157-160.
- Hees, William P., "Communications Design for a Remote Presence Robot", CSCI E-131B, Final Project, Jan. 14, 2002, 12 pages.
- Herias et al., "Flexible Virtual and Remote Laboratory for Teaching Robotics", FORMATEX 2006, Proceedings of Advance in Control Education Madrid, Spain, Jun. 2006, pp. 1959-1963.
- Holmberg et al., "Development of a Holonomic Mobile Robot for Mobile Manipulation Tasks", FSR'99 International Conference on Field and Service Robotics, Pittsburgh, PA, Aug. 1999, 6 pages.
- Ishiguro et al., "Integrating a Perceptual Information Infrastructure with Robotic Avatars: A Framework for Tele-Existence", Intelligent Robots and Systems, Proceedings of 1999 IEEE/RSJ International Conference, vol. 2, 1999, pp. 1032-1038.
- Ishihara et al., "Intelligent Microrobot DDS (Drug Delivery System) Measured and Controlled by Ultrasonics", Proceedings of IEEE/RSJ International Workshop on Intelligent Robots and Systems, vol. 2, Nov. 3-5, 1991, pp. 1145-1150.
- ITU, "Call Completion Supplementary Services for H.323", ITU-T, Telecommunication Standardization Sector of ITU, H.450.9, Series H: Audiovisual and Multimedia Systems, Nov. 2000, 63 pages.
- ITU, "Call Intrusion Supplementary Service for H.323", ITU-T, Telecommunication Standardization Sector of ITU, H.450.11, Series H: Audiovisual and Multimedia Systems, Mar. 2001, 59 pages.
- ITU, "Packet-Based Multimedia Communications Systems", ITU-T, Telecommunication Standardization Sector of ITU, H.323, Series H: Audiovisual and Multimedia Systems, Feb. 1998, 128 pages.
- ITU, "A Far End Camera Control Protocol for Videoconferences Using H.224", Transmission of Non-Telephone Signals, ITU-T, Telecommunication Standardization Sector of ITU, H.281, Nov. 1994, 12 pages.
- Ivanova, Natali, "Internet Based Interface for Control of a Mobile Robot", First Degree Programme in Mathematics and Computer Science, Master's thesis, Department of Numerical Analysis and Computer Science, 2003, 59 pages.
- Jacobs et al., "Applying Telemedicine to Outpatient Physical Therapy", AMIA, Annual Symposium Proceedings, 2002, 1 page.
- Jenkins et al., "Telehealth Advancing Nursing Practice", Nursing Outlook, vol. 49, No. 2, Mar. 2001, pp. 100-105.
- Johanson, Mathias, "Supporting Video-Mediated Communication over the Internet", Thesis for the degree of Doctor of Philosophy, Department of Computer Engineering, Chalmers University of Technology, Gothenburg, Sweden, 2003, 222 pages.
- Jouppi et al., "BiReality: Mutually-Immersive Telepresence", Multimedia '04, Proceedings of the 12th Annual ACM International Conference on Multimedia, Oct. 10-16, 2004, pp. 860-867.
- Jouppi et al., "First Steps Towards Mutually-Immersive Mobile Telepresence", CSCW '02, Proceedings of the ACM conference on Computer Supported Cooperative Work, Nov. 16-20, 2002, pp. 354-363.
- Kanehiro et al., "Virtual Humanoid Robot Platform to Develop Controllers of Real Humanoid Robots without Porting", Proceedings of IEEE/RSJ International Conference on Intelligent Robots and Systems, vol. 2, Oct. 29-Nov. 3, 2001, pp. 1093-1099.
- Kaplan et al., "An Internet Accessible Telepresence", Multimedia Systems Journal, vol. 5, 1996, 7 pages.
- Keller et al., "An Interface for Raven", The National Aviary's Teleconferencing Robot, Interaction and Visual Interface Design, School of Design, Carnegie Mellon University, 2001, 8 pages.

(56)

## References Cited

## OTHER PUBLICATIONS

- Khatib et al., "Robots in Human Environments", Robotics Laboratory, Department of Computer Science, Stanford University, 1999, 15 pages.
- Knight et al., "Active Visual Alignment of a Mobile Stereo Camera Platform", Robotics and Automation, Proceedings of ICRA '00, IEEE International Conference, vol. 4, Apr. 24-28, 2000, pp. 3203-3208.
- Kurlowicz et al., "The Mini Mental State Examination (MMSE)", The Hartford Institute for Geriatric Nursing, Journal of Psychiatric Research, No. 3, Jan. 1999, 2 pages.
- Kuzuoka et al., "Can the GestureCam be a Surrogate?", Proceedings of the Fourth European Conference on Computer-Supported Cooperative Work, Sep. 10-14, 1995, pp. 181-196.
- Lane, Earl, "Automated Aides", available online at <<http://www.cs.cum.edu/nursebot/web/press/nd4380.htm>>, Retrieved on Nov. 23, 2010, Oct. 17, 2000, 4 pages.
- Lee et al., "A Novel Method of Surgical Instruction: International Telementoring", World Journal of Urology, vol. 16, No. 6, Dec. 1998, pp. 367-370.
- Lemaire, Edward, "Using Communication Technology to Enhance Rehabilitation Services", Terry Fox Mobile Clinic, The Rehabilitation Centre, Ottawa, Canada, Version 2.0, 1998-2001, 104 pages.
- Lim et al., "Control to Realize Human-Like Walking of a Biped Humanoid Robot", Systems, Man and Cybernetics, IEEE International Conference, vol. 5, 2000, pp. 3271-3276.
- Linebarger et al., "Concurrency Control Mechanisms for Closely Coupled Collaboration in Multithreaded Virtual Environments", Department of Computer Science and Engineering; Lehigh University, vol. 13, 2004, 40 pages.
- Sachs et al., "Virtual Visit™: Improving Communication for Those Who Need it Most", Studies in Health Technology and Informatics, vol. 94, Medicine Meets Virtual Reality 11, 2003, pp. 302-308.
- Long, William F., "Robot Navigation Technology", available online at <<http://www.atp.nist.gov/eao/sp950-1/helpmate.htm>>, retrieved on Nov. 23, 2010, Mar. 1999, 3 pages.
- Luna, Nancy, "Robot a New Face on Geriatric Care", ocregister.com, Aug. 6, 2003, 3 pages.
- Mack, Michael J., "Minimally Invasive and Robotic Surgery", The Journal of the American Medical Association, vol. 285, No. 5, Feb. 7, 2001, pp. 568-572.
- Mair, G. M., "Telepresence—The Technology and its Economic and Social Implications", Technology and Society, Technology and Society at a Time of Sweeping Change, Proceedings of International Symposium, Jun. 20-21, 1997, pp. 118-124.
- Martin, Anya, "Brighter Days Ahead", Assisted Living Today, vol. 9, Nov./Dec. 2002, pp. 19-22.
- McCardle et al., "The Challenge of Utilizing New Technology in Design Education", Loughborough University, IDATER, 2000, pp. 122-127.
- Meng et al., "E-Service Robot in Home Healthcare", Proceedings of the 2000 IEEE/RSJ, International Conference on Intelligent Robots and Systems, 2000, pp. 832-837.
- Metz, Cade, "HP Labs", available online at <<http://www.pcmag.com/article2/0,2817,1130820,00.asp>>, Jul. 1, 2003, 4 pages.
- Michaud, Anne, "Introducing 'Nursebot'", available online at <[http://www.cs.cmu.edu/~nursebot/web/press/globe\\_3\\_01/index.html](http://www.cs.cmu.edu/~nursebot/web/press/globe_3_01/index.html)>, retrieved on May 5, 2008, Sep. 11, 2001, 4 pages.
- Microsoft Corporation, Inc., "Microsoft NetMeeting 3 Features", available online at <<http://technet.microsoft.com/en-us/library/cc723477.aspx>>, retrieved on Jun. 26, 2012, 2012, 6 pages.
- Montemerlo, Mike, "Telepresence: Experiments in Next Generation Internet", available Online at <<http://www.ri.cmu.edu/creative/archives.htm>>, retrieved on May 25, 2008, Oct. 20, 1998, 3 pages.
- Murphy, Robin R., "Introduction to AI Robotics", A Bradford Book, The Massachusetts Institute of Technology Press, 2000, 487 pages.
- Nakajima et al., "A Multimedia Teleteaching System using an Electronic Whiteboard for Two-Way Communication of Motion Videos and Chalkboards", Robot and Human Communication, Proceedings of 2nd IEEE International Workshop, 1993, pp. 436-441.
- Nakazato et al., "Group-Based Interface for Content-Based Image Retrieval", Proceedings of the Working Conference on Advanced Visual Interfaces, 2002, pp. 187-194.
- Nakazato et al., "Group-Oriented User Interface for Digital Image Management", Journal of Visual Languages and Computing, vol. 14, No. 4, Aug. 2003, pp. 45-46.
- NERSC, "Berkeley Lab's RAGE Telepresence Robot Captures R&D100 Award", Available online at <<https://www.nersc.gov/news-publications/news/nersc-center-news/2002/berkeley-lab-s-rage-telepresence-robot-captures-r-and-d100-award/>>, Retrieved on Jan. 22, 2014, Jul. 2, 2002, 2 pages.
- "Nomad XR4000 Hardware Manual", Release 1.0, Nomadic Technologies, Inc., Mar. 1999, 34 pages.
- North, Michael, "Telemedicine: Sample Script and Specifications for a Demonstration of Simple Medical Diagnosis and Treatment Using Live Two-Way Video on a Computer Network", Greenstar Corporation, 1998, 5 pages.
- Ogata et al., "Development of Emotional Communication Robot: WAMOEBA-2R—Experimental evaluation of the Emotional Communication between Robots and Humans", Proceedings of the 2000 IEEE/RSJ International Conference on Intelligent Robots and Systems, vol. 1, 2000, pp. 175-180.
- Ogata et al., "Emotional Communication Robot: WAMOEBA-2R—Emotion Model and Evaluation Experiments", Proceedings of the International Conference on Humanoid Robots, 2000, pp. 1-16.
- "Robart I, II, III", Spawar, Systems Center Pacific, Available online at <<http://www.nosc.mil/robots/land/robart/robart.html>>, retrieved on Nov. 22, 2010, 1998, 8 pages.
- "Using your Infrared Cell Phone Camera", Available on <<http://www.catsdomain.com/xray/about.htm>>, retrieved on Jan. 23, 2014, Courtesy of Internet Wayback Machine, Jan. 30, 2010, 4 pages.
- Appeal from the U.S. District Court for the Central District of California in case No. 11-cv-9185, Judge Percy Anderson, Joint Appendix, vol. I of IV, Jun. 24, 2013, pp. A1-A6357.
- Appeal from the U.S. District Court for the Central District of California in case No. 11-cv-9185, Judge Percy Anderson, Joint Appendix, vol. II of IV, Jun. 24, 2013, pp. A6849-A10634.
- Appeal from the U.S. District Court for the Central District of California in case No. 11-cv-9185, Judge Percy Anderson, Joint Appendix, vol. III of IV, Jun. 24, 2013, pp. A10654-A15517.
- Appeal from the U.S. District Court for the Central District of California in case No. 11-cv-9185, Judge Percy Anderson, Joint Appendix, vol. IV of IV, Jun. 24, 2013, pp. A15677-A18127.
- Reply Brief for Defendant-Appellee VGo Communications, Inc., Appeal from the U.S. District Court for the Central District of California, in Case No. 2:11-cv-9185, Judge Percy Anderson, May 28, 2013, 75 pages.
- Civil Minutes-General: Case No. CV 11-9185PA (AJWx), *InTouch Tech., Inc. v. VGo Commons, Inc.*, U.S. District Court for the Central District of California, Judge Percy Anderson, Sep. 10, 2012, 7 pages.
- Defendant-Counterclaimant VGo Communications, Inc.'s Supplemental Invalidity Contentions Pursuant to the Feb. 27, 2012 Civil Minute Order, U.S. District Court for the Central District of California, Case No. CV11-9185 PA, May 14, 2012, 228 pages.
- Opening Brief for Plaintiff-Appellant InTouch Technologies, Inc., Appeal from the U.S. District Court for the Central District of California in Case No. 11-cv-9185, Judge Percy Anderson, Apr. 12, 2013, 187 pages.
- Reply Brief for Plaintiff-Appellant InTouch Technologies, Inc., Appeal from the U.S. District Court for the Central District of California in Case No. 11-cv-9185, Judge Percy Anderson, Jun. 14, 2013, 39 pages.
- Active Media, Inc., "Saphira Software Manual", Real World, Saphira Version 5.3, 1997, 105 pages.
- Apple Inc., "iPhone", iPhone Series, XP002696350, Sep. 21, 2012, pp. 1-29.

(56)

## References Cited

## OTHER PUBLICATIONS

- Blaer et al., "TopBot: Automated Network Topology Detection With a Mobile Robot", IEEE, Proceedings of the 2003 International Conference on Robotics and Automation, Taipei, Taiwan, Sep. 14-19, 2003, pp. 1582-1587.
- Bradner, S., "The Internet Standards Process—Revision 3", Network Working Group, Request for Comments: 2026, BCP: 9, Obsoletes: 1602, Category: Best Current Practice, Oct. 1996, pp. 1-36.
- Christensen et al., "BeeSoft User's Guide and Reference", Robots for the Real World™, Real World Interface, Inc., Sep. 26, 1997, 203 pages.
- Chu et al., "Detection of Target Mobile Signal Strength", Technical Development, Motorola Inc., Jan. 1999, pp. 205-206.
- Dario et al., "A Robot Workstation for Diagnosis and Physical Therapy", IEEE Catalog No. 88TH0234-5, Centro "E. Piaggio" University of Pisa, Italy, 1989, pp. 67-72.
- Gostai "Gostai Jazz: Robotic Telepresence", available online at <<http://www.gostai.com>>, 4 pages.
- Leifer et al., "VIPRR: A Virtually in Person Rehabilitation Robot", Proceedings of 1997 International Conference on Rehabilitation Robotics, Apr. 14-15, 1997, 4 pages.
- Minsky, Marvin, "Telepresence", OMNI Magazine, Jun. 1980, 6 pages.
- Noritsugu et al., "Application of Rubber Artificial Muscle Manipulator as a Rehabilitation Robot", Mechatronics, IEEE/ASME Transactions, vol. 2, No. 4, Dec. 1997, pp. 259-267.
- Osborn et al., "Quality of Life Technology Center", QoLT Research Overview: A National Science Foundation Engineering Research Center, Carnegie Mellon University of Pittsburgh, 2 pages.
- Reynolds et al., "Review of Robotic Telemedicine Utilization in Intensive Care Units (ICUs)", 11th Annual ATA Symposium, Tampa, Florida, 2011, 1 page.
- Tipsuwan et al., "Gain Adaptation of Networked Mobile Robot to Compensate QoS Deterioration", vol. 4, 28th Annual Conference of the Industrial Electronics Society, Nov. 5-8, 2002, pp. 3146-3151.
- Tsui et al., "Exploring Use Cases for Telepresence Robots", 6th ACM/IEEE International Conference on Human-Robot Interaction (HRI), Mar. 2011, 7 pages.
- UMASS Lowell Robotics Lab, "Robotics Lab @UMASS Lowell", Department of Computer Science, Brochure, 2011, 2 pages.
- Video Middleware Cookbook, "H.350 Directory Services for Multimedia", 4 pages.
- International Search Report received for International Patent Application No. PCT/US2005/037347, dated Apr. 17, 2006, 2 pages.
- International Preliminary Report on Patentability received for International Patent Application No. PCT/US2005/037347, dated Apr. 17, 2007, 7 pages.
- International Search Report and Written Opinion received for International Patent Application No. PCT/US2006/037076, dated May 11, 2007, 6 pages.
- International Preliminary Report on Patentability received for International Patent Application No. PCT/US2006/037076, dated Apr. 1, 2008, 6 pages.
- International Search Report and Written Opinion received for International Patent Application No. PCT/US2007/14099, dated Jul. 30, 2008, 2 pages.
- International Preliminary Report on Patentability received for International Patent Application No. PCT/US2007/14099, dated Dec. 16, 2008, 5 pages.
- Oh et al., "Autonomous Battery Recharging for Indoor Mobile Robots", Proceedings of Australian Conference on Robotics and Automation, 2000, pp. 1-6.
- Ojha, Anand K., "An application of Virtual Reality in Rehabilitation", Proceedings of the 1994 IEEE Southeastcon Creative Technology Transfer, A Global Affair, Apr. 1994, pp. 4-6.
- Paulos et al., "A World Wide Web Telerobotic Remote Environment Browser", available online at <<http://www.w3.org/Conferences/WWW4/Papers/326/>>, retrieved on Nov. 23, 2010, 1995, 15 pages.
- Paulos et al., "Designing Personal Tele-Embodiment", Proceedings of IEEE International Conference on Robotics and Automation, vol. 4, May 16-20, 1998, pp. 3173-3178.
- Paulos et al., "PRoP: Personal Roving Presence", ACM:CHI Proceedings of CHI, 1998, 8 pages.
- Paulos et al., "Ubiquitous Tele-Embodiment: Applications and Implications", International Journal of Human Computer Studies, vol. 46, No. 6, Jun. 1997, pp. 861-877.
- Paulos et al., "Video of PRoP 2 at Richmond Field Station", www.prop.org, Printout of Home Page of Website and Two-page Transcript of the Audio Portion of said PRoP Video, May 2001, 2 pages.
- Paulos, Eric J., "Personal Tele-Embodiment", Dissertation, Doctor of Philosophy in Computer Science in the Graduate Division of the University of California at Berkeley, 2001, 282 pages.
- PictureTel Corporation, "Introducing PictureTel Live200 for Windows NT", 1997, 63 pages.
- Pin et al., "A New Family of Omnidirectional and Holonomic Wheeled Platforms for Mobile Robots", IEEE Transactions on Robotics and Automation, vol. 10, No. 4, Aug. 1994, pp. 480-489.
- Piquepaille, Roland, "How New Technologies are Modifying Our Way of Life", Roland Piquepaille's Technology Trends, This Blog and its RSS Feed Are Moving, Oct. 31, 2004, 2 pages.
- Radvision, "Making Sense of Bandwidth the NetSense Way", Network Congestion in Unmanaged Networks Bandwidth Estimation and Adaptation Techniques, Radvision's Netsense Technology, 2010, 7 pages.
- Roach, Adam, "Automatic Call Back Service in SIP", Internet Engineering Task Force, Internet Draft, Category: Informational, Mar. 2000, 8 pages.
- Rovetta et al., "A New Telerobotic Application: Remote Laparoscopic Surgery Using Satellites and Optical Fiber Networks for Data Exchange", International Journal of Robotics Research, vol. 15, No. 3, Jun. 1, 1996, pp. 267-279.
- Roy et al., "Towards Personal Service Robots for the Elderly", Workshop on Interactive Robots and Entertainment (WIRE 2000), vol. 25, Apr. 30-May 1, 2000, 7 pages.
- Salemi et al., "MILO: Personal Robot Platform", IEEE/RSJ International Conference on Intelligent Robots and Systems, Aug. 2005, pp. 4089-4094.
- Sandt et al., "Perceptions for a Transport Robot in Public Environments", Proceedings of the IEEE/RSJ International Conference on Intelligent Robots and Systems, vol. 1, Sep. 7-11, 1997, pp. 360-365.
- Sawyer, Robert J., "Inventing the Future: 2000 Years of Discovery", Available online at <<http://www.sfwriter.com/priif.htm>>, retrieved on May 25, 2008, Jan. 2, 2000, 2 pages.
- Schaeffer et al., "Care-O-Bot™: The Concept of a System for Assisting Elderly or Disabled Persons in Home Environments", Proceedings of the 24th Annual Conference of the IEEE Industrial Electronics Society, vol. 4, 1998, pp. 2476-2481.
- Schultz et al., "Web Interfaces for Mobile Robots in Public Places", IEEE Robotics and Automation Magazine, vol. 7, No. 1, Mar. 2000, pp. 48-56.
- Shimoga et al., "Touch and Force Reflection for Telepresence Surgery", Proceedings of the 16th Annual International Conference of the IEEE Engineering in Medicine and Biology Society, Nov. 1994, pp. 1049-1050.
- Sieglwart et al., "Interacting Mobile Robots on the Web", Proceedings of the IEEE International Conference on Robotics and Automation, May 1999, pp. 10-15.
- Simmons et al., "Xavier: An Autonomous Mobile Robot on the Web", IEEE Robotics and Automation Magazine, 1999, pp. 43-48.
- Stephenson, Gary, "Dr. Robot Tested at Hopkins", Johns Hopkins Medical institutions, available online at <<http://www.hopkinsmedicine.org/press/2003/august/030805.htm>>, Aug. 5, 2003, 2 pages.
- Stoianovici et al., "Robotic Tools for Minimally Invasive Urologic Surgery", Complications of Urologic Laparoscopic Surgery: Recognition, Management and Prevention, Dec. 2002, 17 pages.
- Suplee, Carl, "Mastering the Robot", available online at <<http://www.cs.cmu.edu-nursebot/web/press/wash/index.html>>, retrieved on Nov. 23, 2010, Sep. 17, 2000, 5 pages.

(56)

## References Cited

## OTHER PUBLICATIONS

- Tahboub et al., "Dynamics Analysis and Control of a Holonomic Vehicle With Continuously Variable Transmission", *Journal of Dynamic Systems, Measurement and Control ASME*, vol. 124, Mar. 2002, pp. 118-126.
- Telepresence Research, Inc., "Telepresence Mobile Robot System", available online at <<http://www.telepresence.com/telepresence-research/TELEROBOT/>>, retrieved on Nov. 23, 2010, Feb. 20, 1995, 3 pages.
- Tendick et al., "Human-Machine Interfaces for Minimally Invasive Surgery", *Proceedings of the 19th Annual International Conference of the IEEE Engineering in Medicine and Biology Society*, vol. 6, Oct. 30-Nov. 2, 1997, pp. 2771-2776.
- Theodosiou et al., "MuLVAT: A Video Annotation Tool Based on XML-Dictionaries and Shot Clustering", *19th International Conference, Artificial Neural Networks—ICANN*, Sep. 14-17, 2009, pp. 913-922.
- Thrun et al., "Probabilistic Algorithms and the Interactive Museum Tour-Guide Robot Minerva", *Journal of Robotics Research*, vol. 19, 2000, pp. 1-35.
- Time, Lists, "Office Coworker Robot", *Best Inventions of 2001*, Available online at <[http://content.time.com/time/specials/packages/article/0,28804,1936165\\_1936255\\_1936640,00.html](http://content.time.com/time/specials/packages/article/0,28804,1936165_1936255_1936640,00.html)>, Nov. 19, 2001, 2 pages.
- Tyrrell et al., "Teleconsultation in Psychology: The Use of Videolinks for Interviewing and Assessing Elderly Patients", *British Geriatrics Society, Age and Ageing*, vol. 30, No. 3, May 2001, pp. 191-195.
- Tzafestas et al., "VR-based Teleoperation of a Mobile Robotic Assistant: Progress Report", *Technical Report DEMO 2000/13*, Institute of Informatics and Telecommunications, National Center for Scientific Research "Demokritos", Athens, Greece, Nov. 2000, pp. 1-23.
- Urquhart, Kim, "InTouch's Robotic Companion 'Beams Up' Healthcare Experts", *Medical Device Daily, The Daily Medical Technology Newspaper*, vol. 7, No. 39, Feb. 27, 2003, pp. 1-4.
- Weaver et al., "Monitoring and Controlling Using the Internet and Java", *Proceedings of the 25th Annual Conference of the IEEE Industrial Electronics Society*, vol. 3, 1999, pp. 1152-1158.
- Weiss et al., "Telework and Video-Mediated Communication: Importance of Real-Time, Interactive Communication for Workers with Disabilities", Available online at <[http://www.telbotics.com/research\\_3.htm](http://www.telbotics.com/research_3.htm)>, retrieved on Nov. 23, 2010, 1999, 3 pages.
- Weiss, et al., "PEBBLES: A Personal Technology for Meeting Education, Social and Emotional Needs of Hospitalised Children", *Personal and Ubiquitous Computing*, vol. 5, No. 3, Aug. 2001, pp. 157-168.
- West et al., "Design of Ball Wheel Mechanisms for Omnidirectional Vehicles with Full Mobility and Invariant Kinematics", *Journal of Mechanical Design, ASME*, vol. 119, Jun. 1997, pp. 153-161.
- Yamasaki et al., "Applying Personal Robots and Active Interface to Video Conference Systems", *6th International Conference on Human Computer Interaction*, vol. B, 1995, pp. 243-248.
- Yamauchi, Brian, "PackBot: A Versatile Platform for Military Robotics", *Proceedings of SPIE for Military Robotics*, 2004, pp. 228-237.
- Yong et al., "Robot Task Execution with Telepresence Using Virtual Reality Technology", *International Conference on Mechatronic Technology*, Nov. 30-Dec. 2, 1998, pp. 1-8.
- Zambroski, James, "CMU, Pitt Developing 'Nursebot'", available online at <<http://www.cs.cmu.edu/~nursebot/web/press/tribunereview.html>>, retrieved on Jun. 26, 2012, Oct. 27, 2000, 3 pages.
- Zamrazil, Kristie, "Telemedicine in Texas: Public Policy Concerns", *Focus Report, House Research Organization, Texas House of Representatives*, No. 76-22, May 5, 2000, pp. 1-16.
- Zipperer, Lorri, "Robotic Dispensing System", *ISMP Medication Safety Alert*, vol. 4, No. 17, Aug. 25, 1999, pp. 1-2.
- Zorn, Benjamin G., "Ubiquitous Telepresence", *Department of Computer Science, University of Colorado*, Mar. 18, 1996, 13 pages.
- "Defendant VGo Communications, Inc.'s Invalidity Contentions Pursuant to the Feb. 27, 2012 Civil Minute Order", U.S. District Court for the Central District of California, in Case No. CV11-9185 PA, May 2, 2012, 143 pages.
- "Magne Charge", *Smart Power for Electric Vehicles, General Motors Corporation*, Serial No. 75189637, Registration No. 2114006, Filing Date: Oct. 29, 1996, Aug. 26, 1997, 2 pages.
- "More Online Robots: Robots that Manipulate", available online at <[http://ford.ieor.berkeley.edu/ir/robots\\_a2.html](http://ford.ieor.berkeley.edu/ir/robots_a2.html)>, retrieved on Nov. 23, 2010, Aug. 2001, 2 pages.
- "PictureTel Adds New Features and Functionality to its Award-Winning Live200 Desktop Videoconferencing System", *PR Newswire Association, LLC, Gale, Cengage Learning*, Jun. 13, 1997, 4 pages.
- Office Action received for Chinese Patent Application No. 200680044698.0 dated Nov. 4, 2010. (9 pages of Official Copy and 17 pages of English Translation).
- Wang et al., "A Healthcare Tele-robotic System with a Master Remote Station with an Arbitrator", U.S. Appl. No. 60/449,762, filed Feb. 24, 2003, 28 pages.
- Activmedia Robotics LLC, "Pioneer 2/PeopleBot™", *Operations Manual, Version 9*, Oct. 2001, 78 pages.
- Adams, Chris, "Simulation of Adaptive Behavior (SAB'02)—From Animals to Animats 7", *Mobile Robotics Research Group, The Seventh International Conference*, available online at: <<http://www.dai.ed.ac.uk/groups/mrg/MRG.html>>, retrieved on Jan. 22, 2014, Aug. 4-11, 2002, 1 page.
- Ando et al., "A Multimedia Self-Service Terminal with Conferencing Functions", *Proceedings of 4th IEEE International Workshop on Robot and Human Communication, RO-MAN'95*, Jul. 5-7, 1995, pp. 357-362.
- Android Amusement Corp., "Renting Robots from Android Amusement Corp!", *What Marketing Secret, (Advertisement)*, 1982, 1 page.
- Applebome, "Planning Domesticated Robots for Tomorrow's Household", *New York Times*, available online at <<http://www.theoldrobots.com/images17/dc17.JPG>>, Mar. 4, 1982, 1 page.
- Bar-Cohen et al., "Virtual Reality Robotic Telesurgery Simulations Using MEMICA Haptic System", *Proceedings of SPIE's 8th Annual International Symposium on Smart Structures and Materials*, Mar. 5-8, 2001, 8 pages.
- Barrett, Rick, "Video Conferencing Business Soars as Companies Cut Travel; Some Travel Cuts are Permanent", available online at <[http://www.ivci.com/international\\_videoconferencing\\_news\\_videoconferencing\\_news\\_19.html](http://www.ivci.com/international_videoconferencing_news_videoconferencing_news_19.html)>, May 13, 2002, 2 pages.
- Bartholomew, "Pharmacy Apothecary of England", *BnF-Teaching Kit—Childhood in the Middle Ages*, available online at <<http://classes.bnf.fr/ema/grands/034.htm>>, retrieved on Jul. 26, 2012, 2 pages.
- Bauer et al., "Remote Telesurgical Mentoring: Feasibility and Efficacy", *IEEE, Proceedings of the 33rd Hawaii International Conference on System Sciences*, 2000, pp. 1-9.
- Bauer, Jeffrey C., "Service Robots in Health Care: The Evolution of Mechanical Solutions to Human Resource Problems", *BonSecours Health System, Inc., Technology Ealy Warning System*, Jun. 2003, pp. 1-10.
- Bischoff, Rainer, "Design Concept and Realization of the Humanoid Service Robot HERMES", In A. Zelinsky (ed.): *Field and Service Robotics*, Springer, London, 1998, pp. 485-492.
- Blackwell, Gerry, "Video: A Wireless LAN Killer App?", Available online at <<http://www.wi-fiplanet.com/columns/article.php/1010261/Video-A-Wireless-LAN-Killer>>, retrieved on Nov. 22, 2010, Apr. 16, 2002, 4 pages.
- Breslow et al., "Effect of a Multiple-Site Intensive Care Unit Telemedicine Program on Clinical and Economic Outcome an Alternative Paradigm for Intensivist Staffing", *Critical Care Med.*, vol. 32, No. 1, Jan. 2004, pp. 31-38.

(56)

## References Cited

## OTHER PUBLICATIONS

- Brooks, Rodney A., "A Robust Layered Control System for a Mobile Robot", IEEE, *Journal of Robotics and Automation*, vol. 2, No. 1, Mar. 1986, pp. 14-23.
- Brooks, Rodney Allen, "Flesh and Machines: How Robots Will Change Us", available online at <<http://dl.acm.org/citation.cfm?id=560264&prelayout=flat%2520of%2520of>>, retrieved on Nov. 23, 2010, Feb. 2002, 3 pages.
- Celi et al., "The eICU: It's Not Just Telemedicine", *Critical Care Medicine*, vol. 29, No. 8 (Supplement), Aug. 2001, pp. 183-189.
- Cheetham et al., "Interface Development for a Child's Video Conferencing Robot", Centre for Learning Technologies, Ryerson University, 2000, 4 pages.
- Cleary et al., "State of the Art in Surgical Robotics: Clinical Applications and Technology Challenges", *Computer Aided Surgery*, Nov. 2001, pp. 1-26.
- CNN, "Floating 'Droids' to Roam Space Corridors of the Future", available online at <<http://edition.cnn.com/2000/TECH/space/01/12/psa/>> retrieved on Nov. 11, 2010., Jan. 12, 2000, 3 pages.
- CNN.com, "Paging Dr. Robot: Machine Helps Doctors with Patients", available online at <<http://edition.cnn.com/2003/TECH/ptech/09/29/doctor.robot.ap/index.html>>, retrieved on Sep. 30, 2003, 3 pages.
- Crowley, Susan L., "Hello to Our Future", *AARP Bulletin*, available online at <[http://www.cs.cmu.edu/~nursebot/web/press/aarp\\_99\\_14/millennium.html](http://www.cs.cmu.edu/~nursebot/web/press/aarp_99_14/millennium.html)>, Jan. 2000, retrieved on Nov. 23, 2010, 12 pages.
- Dalton, Barnaby, "Techniques for Web Telerobotics", Ph. D Thesis for degree of Doctor of Philosophy, University of Western Australia, available online at <<http://telerobot.mech.uwa.edu.au/information.html>>, 2001, 243 pages.
- Davies, Brian, "Robotics in Minimally Invasive Surgery", *Mechatronics in Medicine Lab*, Dept. Mechanical Engineering, Imperial College, London SW7 2BX, The Institution of Electrical Engineers, IEE, Savoy Place, London WC2R 0BL, UK, 1995, pp. 1-2.
- Davis, Erik, "Telefriend, Meet iRobot, The Smartest Webcam on Wheels", *Wired Magazine*, Issue 8.09, available online at <[http://www.wired.com/wired/archive/8.09/irobot.html?pg=1&topic=&topic\\_set=>](http://www.wired.com/wired/archive/8.09/irobot.html?pg=1&topic=&topic_set=>)>, retrieved on Jul. 7, 2012, Sep. 2000, 3 pages.
- Dean et al., "1992 AAAI Robot Exhibition and Competition", *Articles*, *AI Magazine*, vol. 14, No. 1, 1993, 15 pages.
- Digiorgio, James, "Is Your Emergency Department of the Leading Edge?", *Chicago Hospital News*, vol. 2, No. 12, Feb. 2005, 3 pages.
- Dudenhoefter et al., "Command and Control Architectures for Autonomous Micro-Robotic Forces", FY00 Project Report, Idaho National Engineering and Environmental Laboratory, Human Systems Engineering and Sciences Department, Idaho Falls, Apr. 2001, 43 pages.
- Elhajj et al., "Real-Time Haptic Feedback in Internet-Based Telerobotic Operation", *IEEE International Conference on Electro/Information Technology*, Jun. 2000, 10 pages.
- Elhajj et al., "Supermedia in Internet-Based Telerobotic Operations", *Lecture Notes in Computer Science*, vol. 2216, 2001, pp. 359-372.
- Elhajj et al., "Synchronization and Control of Supermedia Transmission via the Internet", *Proceedings of 2001 International Symposium on Intelligent Multimedia Video and Speech Processing*, Hong Kong, May 2-4, 2001, pp. 320-323.
- Ellison et al., "Telerounding and Patient Satisfaction after Surgery", *American College of Surgeons*, Elsevier, Inc., vol. 199, No. 4, Oct. 2004, pp. 523-530.
- Evans et al., "HelpMate: The Trackless Robotic Courier", *PYXIS*, available online at <<http://www.pyxis.com/>>, 3 pages.
- Fels et al., "Developing a Video-Mediated Communication System for Hospitalized Children", *Telemedicine Journal*, vol. 5, No. 2, 1999, 30 pages.
- Fetterman, David M., "Videoconferencing Over the Internet", *Qualitative Health Journal*, vol. 7, No. 1, May 1966. pp. 154-163.
- Fiorini et al., "Health Care Robotics: A Progress Report", *IEEE International Conference on Robotics and Automation*, vol. 2, Apr. 20-25, 1997, pp. 1271-1276.
- Fong, Terrence, "Collaborative Control: A Robot-Centric Model for Vehicle Teleoperation", *The Robotics Institute Carnegie Mellon University*, Nov. 2001, 197 pages.
- Gaidioz et al., "Synchronizing Network Probes to Avoid Measurement Intrusiveness with the Network Weather Service", *High-Performance Distributed Computing*, *Proceedings of the Ninth International Symposium*, 2000, pp. 147-154.
- Garner et al., "The Application of Telepresence in Medicine", *BT Technology Journal*, vol. 15, No. 4, Oct. 1, 1997, pp. 181-187.
- Ghiassi et al., "A Generic Web-based Teleoperations Architecture: Details and Experience", *Proceedings of SPIE, Telemicroscopy and Telepresence Technologies VI*, vol. 3840, No. 234, Sep. 19, 1999, 14 pages.
- Goldberg et al., "Collaborative Teleoperation via the Internet", *IEEE International Conference on Robotics and Automation (ICRA)*, vol. 2, San Francisco, California, 2000, pp. 2019-2024.
- Goldberg et al., "Desktop Teleoperation via the World Wide Web", *Proceedings of IEEE International Conference on Robotics and Automation*, vol. 1, May 21-27, 1995, pp. 654-659.
- Goldenberg et al., "Telemedicine in Otolaryngology", *American Journal of Otolaryngology*, vol. 23, No. 1, Jan. 2002, pp. 35-43.
- Goldman, Lea, "Machine Dreams", available online at <<http://www.forbes.com/global/2002/0527/043.html>>, retrieved on Nov. 23, 2010., May 27, 2002, 5 pages.
- Gump, Michael D., "Robot Technology Improves VA Pharmacies", *U.S. Medicine Informational Central*, Jul. 2001, 3 pages.
- Hameed et al., "A Review of Telemedicine", *Journal of Telemedicine and Telecare*, vol. 5, Supplement 1, 1999, pp. 103-106.
- Han et al., "Construction of an Omnidirectional Mobile Robot Platform Based on Active Dual-Wheel Caster Mechanisms and Development of a Control Simulator", *Journal of Intelligent and Robotic Systems*, Kluwer Academic Publishers, vol. 29, Nov. 2000, pp. 257-275.
- Handley et al., "SDP: Session Description Protocol", RFC 2327, available Online at <<http://www.faqs.org/rfcs/rfc2327.html>>, retrieved on Nov. 23, 2010, Apr. 1998, 22 pages.
- Hanebeck et al., "ROMAN: A Mobile Robotic Assistant for Indoor Service Applications", *Proceedings of the IEEE/RSJ International Conference on Intelligent Robots and Systems*, vol. 2, 1997, pp. 518-525.
- Nomadic Technologies, Inc., "Nomad Scout User's Manual", Software Version 2.7, Part No. DOC00004, Jul. 12, 1999, pp. 1-59.
- ACM Digital Library Record, *Autonomous Robots*, vol. 11, No. 1, Table of Content, available at <<http://dl.acm.org/citation.cfm?id=591550&picked=prox&cfid=360891374&cftoken=35225929>>, Jul. 2001, 2 pages.
- Brenner, Pablo, "A Technical Tutorial on the IEEE 802.11 Protocol", *BreezeCOM Wireless Communications*, Jul. 18, 1996, pp. 1-24.
- Library of Congress, "008-Fixed-Length Data Elements (NR)", *MARC 21 Format for Classification Data*, available at <<http://www.loc.gov/marc/classification/cd008.html>>, retrieved on Jul. 22, 2014, pp. 1-14.
- Paulos et al., "Personal Tele-Embodiment", Chapter 9 in Goldberg et al., Ed., "Beyond Webcams", MIT Press, Jan. 4, 2002, pp. 155-167.
- Paulos et al., "Social Tele-Embodiment: Understanding Presence", *Autonomous Robots*, vol. 11, No. 1, Kluwer Academic Publishers, Jul. 2001, pp. 87-95.
- Paulos, Eric John, "Personal Tele-Embodiment", *Introductory and Cover Pages from 2001 Dissertation Including Contents table*, together with E-mails Relating thereto from UC Berkeley Libraries, as Shelved at UC Berkeley Engineering Library (Northern Regional Library Facility), May 8, 2002, 25 pages (including 4 pages of e-mails).
- Paulos, Eric John, "Personal Tele-Embodiment", *OskiCat Catalog Record*, *UCB Library Catalog*, Results page and MARC Display, retrieved on Jun. 14, 2014, 3 Pages.

(56)

**References Cited**

## OTHER PUBLICATIONS

“Appeal from the U.S. District Court for the Central District of California in No. 11-CV-9185, Judge Percy Anderson”, May 9, 2014, pp. 1-48.

“Google translation of: Innovations Report”, From research project to television star: Care-O-bot in ZDF series, available online at <<http://www.innovations-report.de/specials/printa.php?id=5157>>, Sep. 28, 2001.

“MPEG File Format Summary”, downloaded from: <<http://www.fileformat.info/format/mpeg/egff.htm>>, Feb. 1, 2001, 8 pages.

“MPEG-4: a Powerful Standard for Use in Web and Television Environments”, by Rob Koenen (KPN Research), downloaded from <<http://www.w3.org/Architecture/1998/06/Workshop/paper26>>, Jul. 1, 1998, 4 pages.

CMU Course 16x62, “Robot user’s manual”, (describing the Nomad Scout), Carnegie Mellon University, Feb. 1, 2001, 11 pages.

Panusopone et al., “Performance comparison of MPEG-4 and H.263+ for streaming video applications”, Circuits Systems Signal Processing, vol. 20, No. 3, 2001, pp. 293-309.

Schraft et al., “Care-O-bot™: The Concept of a System for Assisting Elderly or Disabled Persons in Home Environments”, IEEE Proceedings of the 24th Annual Conference of the Industrial Electronics Society, IECON '98, Aug. 31-Sep. 4, 1998, pp. 2476-2481.

Fulbright et al., “SWAMI: An Autonomous Mobile Robot for Inspection of Nuclear Waste of Storage Facilities”, Autonomous Robots, vol. 2, 1995, pp. 225-235.

Screenshot Showing Google Date for Lemaire Telehealth Manual, Screenshot Retrieved on Dec. 18, 2014, 1 page.

Nomadic Technologies, Inc., “Nomad Scout Language Reference Manual”, Software Version: 2.7, Part No. DOC00002, Jul. 12, 1999, 47 pages.

\* cited by examiner

100




FIG. 1

FIG. 2




FIG. 3A







FIG. 3B












FIG. 7










FIG. 10



FIG. 11




FIG. 12

## ENHANCED DIAGNOSTICS FOR A TELEPRESENCE ROBOT

### RELATED APPLICATIONS

This application is a continuation of U.S. patent application Ser. No. 14/108,036 filed Dec. 16, 2013 and entitled "Enhanced Diagnostics for a Telepresence Robot," which claims priority to U.S. Patent Application Ser. No. 61/729,964 filed Nov. 26, 2012 and entitled "Enhanced Diagnostics Using Multiple Sensors with Coordinated Sensor Spaces" and which is a continuation-in-part of U.S. patent application Ser. No. 13/111,208, filed May 19, 2011 and entitled "Mobile Videoconferencing Robot System with Autonomy and Image Analysis" and a continuation-in-part of U.S. patent application Ser. No. 13/830,334 filed Mar. 14, 2013 and entitled "Enhanced Video Interaction for a User Interface of a Telepresence Network," all of which are hereby incorporated by reference herein in their entirety.

### STATEMENT REGARDING FEDERALLY SPONSORED RESEARCH OR DEVELOPMENT

This invention was made with government support under grant number R43 MD006709 awarded by the National Institutes of Health.

### TECHNICAL FIELD

This disclosure relates to enhanced diagnostics for a telepresence device. More specifically, this disclosure relates to systems and methods for improving patient diagnosis by a telepresence device configured to autonomously check patients.

### BRIEF DESCRIPTION OF THE DRAWINGS

Non-limiting and non-exhaustive embodiments of the disclosure are described herein, including various embodiments of the disclosure illustrated in the figures listed below.

FIG. 1 is a schematic diagram of a telepresence network comprising a plurality of telepresence devices.

FIG. 2 is a schematic diagram of a computer configured to provide enhanced diagnostics by a telepresence device.

FIGS. 3A,B are exemplary screen displays that may be displayed to a user of a control device.

FIG. 4 is an exemplary screen display comprising a telepresence device location map.

FIG. 5 is an exemplary depiction of a healthcare facility map.

FIG. 6 is a perspective view of a telepresence device performing one or more diagnostic activities on a patient using an image sensor.

FIG. 7 is a perspective view of the telepresence device performing one or more diagnostic activities on a fluid bag using the image sensor.

FIG. 8 is a perspective view of a telepresence device performing one or more diagnostic activities on a patient using a thermal camera.

FIG. 9 is a perspective view of a telepresence device performing one or more diagnostic activities on a patient using a depth sensor.

FIG. 10 is a perspective view of a telepresence device evaluating whether a patient is currently in their bed.

FIG. 11 is a perspective view of a telepresence device performing an interactive test with a patient.

FIG. 12 is a perspective view of a telepresence device informing a care provider in-person of the existence of an alarm.

The described features, structures, and/or characteristics of the systems and methods described herein may be combined in any suitable manner in one or more alternative embodiments, and may differ from the illustrated embodiments.

### DETAILED DESCRIPTION OF PREFERRED EMBODIMENTS

In certain industries, a shortage of skilled employees may result in poor outcomes, particularly during night shifts when skilled employees are less likely to be working. For example, the difficulties with filling night shifts may be especially pervasive in hospitals, such as hospitals in underserved urban communities, in high-crime neighborhoods, and/or in rural areas where specialists are unavailable and local caregivers do not recognize the need for remote specialists. Less skilled employees may be used to fill the shortage, but they often require additional supervision and may perform more poorly than their high-skill counterparts, which may result in higher mortality rates in hospitals, for example. Hospitals may require that patients at risk for specific diseases be checked at predetermined intervals, but low-skilled employees may be less consistent in how they check patients and may neglect to check patients until the end of their shifts, which may be too late. Accordingly, there is a strong need to address the problems of availability, quality, and reliability of nighttime healthcare in disadvantaged communities.

A telepresence device may be part of a telepresence network that allows users remote from the telepresence device to interact with an environment where the telepresence device is located. When no remote users are interacting with the telepresence device, it may act autonomously. For example, the telepresence device may automatically perform rounds and check on patients with a predetermined frequency (e.g., at predetermined intervals). The telepresence device may be configured to capture video and/or environmental measurements, which may be relayed to one or more users and/or stored for later viewing. The telepresence device may also, or instead, detect the existence of problems based on the captured video and/or environmental measurements and may alert one or more users of the problem. A control device may allow the one or more users to interact with the telepresence device, such as by sending and/or receiving captured video and/or audio, sending commands to the telepresence device, and the like. The telepresence device may be more reliable in complying with strict patient monitoring schedules and may provide a consistent level of care with each visit.

Each telepresence network may include one or more facilities that each include at least one corresponding telepresence device local to the facility. Exemplary facilities may include manufacturing plants, research and development facilities, testing facilities, hospitals, rehabilitation facilities, long-term care facilities, and the like. Types of telepresence devices include, but are not limited to, remote telepresence devices, mobile telepresence units, and/or control stations. For example, a remote telepresence device may include a telepresence robot configured to move within a medical facility and provide a means for a remote practitioner to perform remote consultations.

Exemplary, non-limiting uses for telepresence devices may include healthcare and industrial applications. For

example, healthcare facilities may include telemedicine technologies, such as telepresence devices in a telepresence network, that allow remote healthcare practitioners to provide services to patients and/or other healthcare practitioners in remote locations. A remote medical professional may be a neurologist practicing in a relatively large hospital who may, via a telepresence device, provide services and consultations to patients and/or other medical professionals in hospitals located in rural areas that otherwise may not have a neurologist on staff.

The control device may include a general purpose and/or special purpose computer systems and/or one or more computer networks. In an embodiment, the control device and the telepresence device may each include at least one camera, at least one display device, at least one speaker, and at least one microphone to allow for two-way video/audio communication. One or more input devices may allow the user of the control device to remotely control movement of the telepresence device. Additional discussion of remotely controlling movement of a telepresence device is contained in U.S. Pat. No. 6,845,297, titled "Method and System for Remote Control of Mobile Robot," filed on Jan. 9, 2003, and European Patent No. 1279081, titled "Method and System for Remote Control of Mobile Robot," filed on May 1, 2001, which applications are hereby incorporated by reference in their entireties.

The control device, the telepresence device, and/or the telepresence network may be configured to store session content data, such video and/or audio recordings, telemetry data (e.g., physiological data), notes, time stamps, and/or the like. In an embodiment, the telepresence network may include a server configured to store the session content data. Additional discussion of data storage for telepresence devices and automatic use of stored data is contained in U.S. patent application Ser. No. 12/362,454, titled "DOCUMENTATION THROUGH A REMOTE PRESENCE ROBOT," filed on Jan. 29, 2009, which application is hereby incorporated by reference in its entirety.

Reference throughout this specification to "one embodiment" or "an embodiment" means that a particular feature, structure, or characteristic described in connection with the embodiment is included in at least one embodiment. Thus, the appearances of the phrases "in one embodiment" and "in an embodiment" in various places throughout this specification are not necessarily all referring to the same embodiment. In particular, an "embodiment" may be a system, an article of manufacture (such as a computer-readable storage medium), a method, and/or a product of a process.

The phrases "connected to" and "in communication with" refer to any form of interaction between two or more entities, including mechanical, electrical, magnetic, and electromagnetic interaction. Two components may be connected to each other even though they are not in direct contact with each other and even though there may be intermediary devices between the two components.

The embodiments of the disclosure may be understood by reference to the drawings, wherein like elements are designated by like numerals throughout. In the following description, numerous specific details are provided for a thorough understanding of the embodiments described herein. However, those of skill in the art will recognize that one or more of the specific details may be omitted, or other methods, components, or materials may be used. In some cases, operations and/or components are not shown or described in detail.

Furthermore, the described features, operations, or characteristics may be combined in any suitable manner in one

or more embodiments. The order of the steps or actions of the methods described in connection with the embodiments disclosed may be varied. Thus, any order in the drawings or Detailed Description is for illustrative purposes only and is not meant to imply a required order, unless otherwise specified.

Embodiments may include various steps, which may be embodied in machine-executable instructions to be executed by a computer system. The computer system may comprise one or more general-purpose or special-purpose computers (or other electronic devices). Alternatively, the computer system may comprise hardware components that include specific logic for performing the steps or comprise a combination of hardware, software, and/or firmware. Without limitation, a computer system may comprise a workstation, desktop computer, laptop computer, disconnectable mobile computer, server, mainframe, cluster, so-called "network computer" or "thin client," tablet, smartphone, multimedia device, electronic reader, personal digital assistant or other hand-held computing device, "smart" consumer electronics device or appliance, or a combination thereof. A server may include a physical server, a server cluster, a distributed server, a virtual server, a cloud server, a computer providing resources to one or more clients, a combination of one or more of the aforementioned, and/or the like. Some or all of the functions, steps, and/or operations discussed herein may be performed by one or more clients and/or one or more servers. Those of skill in the art will realize possible divisions of operations between the one or more servers and the one or more clients.

Each computer system includes at least a processor and a memory; computer systems may also include various input devices and/or output devices. The processor may include one or more general-purpose central processing units (CPUs), graphic processing units (GPUs), or Digital Signal Processors (DSPs), such as Intel®, AMD®, ARM®, Nvidia®, ATI®, TI®, or other "off-the-shelf" microprocessors. The processor may include a special-purpose processing device, such as an ASIC, PAL, PLA, PLD, Field Programmable Gate Array (FPGA), or other customized or programmable device. The memory may include static RAM, dynamic RAM, flash memory, ROM, CD-ROM, disk, tape, magnetic, optical, or other computer storage medium. The input device(s) may include a keyboard, mouse, touch screen, light or other pen, tablet, microphone, sensor, or other hardware with accompanying firmware and/or software. The output device(s) may include a monitor or other display, printer, speech or text synthesizer, switch, signal line, or other hardware with accompanying firmware and/or software.

The computers may be capable of using a floppy drive, tape drive, optical drive, magneto-optical drive, memory card reader, or other means to read a storage medium. A suitable storage medium includes a magnetic, optical, or other computer-readable storage device having a specific physical configuration. Suitable storage devices include floppy disks, hard disks, tape, CD-ROMs, DVDs, PROMs, random access memory, flash memory, and other computer system storage devices. The physical configuration represents data and instructions which cause the computer system to operate in a specific and predefined manner as described herein.

Embodiments may also be provided as a computer program product, including a non-transitory machine-readable storage medium having stored thereon instructions that may be used to program a computer system (or other electronic device) to perform processes described herein. The non-

transitory machine-readable storage medium may include, but is not limited to, hard drives, floppy diskettes, optical disks, CD-ROMs, DVD-ROMs, ROMs, RAMs, EPROMs, EEPROMs, magnetic or optical cards, tapes, solid-state memory devices, or other types of media/machine-readable media suitable for storing electronic instructions.

Suitable networks for configuration and/or use as described herein include one or more local area networks, wide area networks, metropolitan area networks, and/or “Internet” or IP networks, such as the World Wide Web, a private Internet, a secure Internet, a value-added network, a virtual private network, an extranet, an intranet, or even standalone machines which communicate with other machines by physical transport of media (a so-called “sneakernet”). In particular, a suitable network may be formed from parts or entirety of two or more other networks, including networks using disparate hardware and network communication technologies. One suitable network includes a server and several clients; other suitable networks may contain other combinations of servers, clients, and/or peer-to-peer nodes, and a given computer may function both as a client and as a server. Each network includes at least two computer systems, such as the server and/or clients.

The network may include communications or networking software, such as the software available from Novell, Microsoft, Artisoft, and other vendors, and may operate using TCP/IP, SPX, IPX, and other protocols over twisted pair, coaxial, or optical fiber cables, telephone lines, satellites, microwave relays, modulated AC power lines, physical media transfer, and/or other data transmission “wires” or wireless protocols known to those of skill in the art. The network may encompass smaller networks and/or be connectable to other networks through a gateway or similar mechanism.

Suitable software to assist in implementing the invention is readily provided by those of skill in the pertinent art(s) using the teachings presented here and programming languages and tools, such as Java, Pascal, C++, C, PHP, JavaScript, Python, C#, Perl, SQL, Ruby, Shell, Visual Basic, Assembly, Action Script, Objective C, Lisp, Scala, Tel Haskell, Scheme, database languages, APIs, SDKs, assembly, firmware, microcode, and/or other languages and tools. Suitable signal formats may be embodied in analog or digital form, with or without error detection and/or correction bits, packet headers, network addresses in a specific format, and/or other supporting data readily provided by those of skill in the pertinent art(s).

Several aspects of the embodiments described will be illustrated as software modules or components. As used herein, a software module or component may include any type of computer instruction or computer-executable code located within a memory device. A software module may, for instance, comprise one or more physical or logical blocks of computer instructions, which may be organized as a routine, a program, a script, an object, a component, a data structure, etc., that perform one or more tasks or implements particular abstract data types.

In certain embodiments, a particular software module may comprise disparate instructions stored in different locations of a memory device, different memory devices, or different computers, which together implement the described functionality of the module. Indeed, a module may comprise a single instruction or many instructions, and may be distributed over several different code segments, among different programs, and across several memory devices. Some embodiments may be practiced in a distributed computing environment where tasks are performed by a remote

processing device linked through a communications network. In a distributed computing environment, software modules may be located in local and/or remote memory storage devices. In addition, data being tied or rendered together in a database record may be resident in the same memory device, or across several memory devices, and may be linked together in fields of a record in a database across a network.

Much of the infrastructure that may be used according to the present invention is already available, such as general-purpose computers, computer programming tools and techniques, computer networks and networking technologies, and digital storage media.

FIG. 1 is a schematic diagram of a telepresence network 100 comprising a plurality of telepresence devices 130. A plurality of control devices 120, such as laptops, tablets, smart phones, and the like, may be configured to transmit video, audio, and/or commands to the telepresence devices 130 and receive video, audio, and/or measurement data from the telepresence devices 130. The control devices 120 may directly couple to the telepresence devices 130, and/or a server 110 may couple the control devices to the telepresence devices 130. In an embodiment, the server 110 may establish a connection between a control device 120 and a telepresence device 130, and the control device 120 and telepresence device 130 may communicate directly after the connection has been established. A connection between a control device 120 and a telepresence device 130 may be referred to as a session. The server 110 may comprise and/or be coupled to a hard drive 112. The hard drive 112 may be configured to store a history for one or more control devices 120 and/or telepresence devices 130. The history may include session data, commands, measurement data, recorded video and/or audio, annotations, bookmarks, and the like. The control devices 120 may be able to retrieve the history from the hard drive 112 via the server 110. It should be understood that any processing required to be performed by the telepresence device 130, the control device 120, and/or the server 110 may be shared and/or distributed among the telepresence device 130, the control device 120, and/or the server 110 in any manner without departing from the scope of this disclosure. Accordingly, if the application states that the telepresence device 130 performs an action that requires execution by a processor, embodiments are contemplated where that action may be performed wholly or partially by the server 110 and/or the control device 120 even if not explicitly recited.

FIG. 2 is a schematic diagram of a computer 200 configured to provide enhanced diagnostics by a telepresence device. The computer 200 may include a processor 230 coupled to a volatile memory 240, a network interface 250, and a computer-readable storage medium 210 by a bus 220. In some embodiments, the computer-readable storage medium 210 may comprise the volatile memory 240. The computer-readable storage medium 210 may include a plurality of modules configured to perform specific functions. For example, an auto-round module 211 may be configured to cause the telepresence device to navigate to patients with a predetermined frequency to perform one or more tests; a video test module 212 may be configured to evaluate a characteristic of a patient based on video of the patient captured by an image sensor (e.g., using Eulerian video magnification); a thermographic test module 213 may be configured to evaluate a characteristic of the patient based on a thermographic image of the patient captured by a thermal camera; an actigraphy module 214 may be configured to determine a position of the patient and/or motion of

the patient using data from a depth sensor and to determine a psychological state of the patient from the position and/or motion; a telemetry gathering module **215** may be configured to acquire telemetry data from a patient monitor, for example, using optical character recognition, by requesting the data from the patient monitor over a wireless network, by requesting the data from an electronic medical record system, and/or the like; an interactive test module **216** may be configured to perform a test requiring the patient to respond orally to one or more prompts and/or to perform one or more actions; a test evaluation module **217** may be configured to receive results from one or more tests and determine the existence of an adverse condition based on the results; an alert module **218** may be configured to notify one or more care providers of the adverse condition and to ensure a care provider responds to the alert; and a storage module **219** may be configured to store selected video, audio, and/or data. Alternatively, the computer **200** may contain more or fewer modules and/or a different computer may contain some of the modules.

FIGS. **3A,B** are exemplary screen displays **300**, **350** that may be displayed to a user of a control device. The user may be attempting to connect to a telepresence device. A plurality of options **310**, **360** may be displayed to the user including available endpoints to which the user may connect. The user may select the telepresence directly and/or select a healthcare facility or patient of interest. An optimal telepresence device may be automatically connected to if a healthcare facility or patient of interest is selected. The user may also be able to select an alarms option **315**, **365** that allows a user to view telepresence devices that have triggered an alarm or healthcare facilities with patients for whom an alarm has been triggered. The alarms and/or additional patient data may allow the user to connect to telepresence devices near and/or interacting with patients most urgently needing attention. Once the user has connected to the telepresence device, the user may interact with a patient using audio, video, and/or data capabilities of the telepresence device. The user may develop a treatment plan and issue corresponding orders to local care providers and/or modify existing orders.

FIG. **4** is an exemplary screen display **400** comprising a telepresence device location map **420**. The locations of various telepresence devices **421**, **422** may be illustrated as figures on the map **420**. A Quick Nav bar **410** may allow the user to see telepresence devices available in a region of interest. The user may be able to connect to one of the telepresence devices **421**, **422** by selecting the desired telepresence device from the map **420**. A telepresence device **425** issuing an alarm may include a distinctive indication that an alarm is occurring. The distinctive indication may be configured to draw the attention of the user and may include a unique color, a flashing icon, text, a pop-up window, and/or the like. The user may select the alarming telepresence device **425** to connect to that telepresence device **425** and resolve the alarm.

FIG. **5** is an exemplary depiction **500** of a healthcare facility map **560**. The healthcare facility map **560** and/or a digital representation of the map **560** may be used by a telepresence device **510** to autonomously navigate to a plurality of patients in turn to check the patients and evaluate whether each patient is experiencing a potentially harmful condition. The telepresence device **510** may perform one or more diagnostic activities to evaluate each patient. Diagnostic activities may include diagnostic tests, which may or may not require interaction by the patient, and may include gathering telemetry data from a source external to the telepresence device **510** (e.g., a patient monitor, an elec-

tronic medical records (EMR) system, etc.). The diagnostic activities may be specified in advance by a care provider and/or may be determined based on a previous diagnosis and/or previous results of diagnostic activities. The results of the one or more diagnostic activities may be processed by the telepresence device **510** and/or a computer system external to the telepresence device **510** (e.g., the server **110**) to determine whether a potentially harmful condition exists with the patient.

In response to determining that a potentially harmful condition exists, the telepresence device **510** and/or the computer system may perform one or more actions responsive to the potentially harmful condition. The one or more actions may include archiving the results of the one or more diagnostic activities, alerting a local care provider, alerting a remote care provider, and/or the like. The action may be selected based on the severity of the potentially harmful condition, the probability the patient is experiencing the potentially harmful condition, and/or the like. Alternatively, or in addition, a user may have specified in advance what actions should be taken for particular results of the one or more diagnostic activities. If the action includes alerting a remote care provider, the telepresence device **510** may also prepare to receive a connection from the alerted remote care provider.

The telepresence device **510** may be able to receive medical data (e.g., a medical record of a patient) from a patient monitor, an EMR system, a telepresence network server (e.g., the server **110**) and/or the like. The telepresence device **510** may also be able to transmit medical data measured by the telepresence device **510**, for example, to the EMR system for storage. The telepresence device **510** may transmit the medical data over a secure, wireless connection (e.g., a WiFi network) to the hospital's EMR and/or other databases, in some embodiments. Alternatively, or in addition, the telepresence device **510** may include local storage for persistent storage of the medical data measured by the telepresence device **510**. The medical data may include instructions to the telepresence device **510** including diagnostic activities to perform, thresholds for evaluating the results of the diagnostic activities, a frequency of performing the diagnostic activities and/or checking the patient, actions to perform in response to the determinations of the evaluation of the results of the diagnostic activities, and/or the like. Alternatively, or in addition, the telepresence device **510** may determine diagnostic activities, evaluation thresholds, frequency of checking each patient, response actions, and/or the like by parsing the previous diagnoses and results of diagnostic activities indicated in the medical data.

The telepresence device **510** and/or the computer system may determine an order and/or a frequency for visiting the plurality of patients. For example, the telepresence device **510** may receive indications of a plurality of patients that it should routinely check and/or may include indications of patients that should be added or removed from the plurality of patients that the telepresence device **510** routinely checks. Any time there is a change in which patients are monitored by the telepresence device **510**, the telepresence device **510** may redetermine the order and/or frequency for visiting the monitored patients. The frequency with which each patient needs to be checked may be specified by a care provider and/or included in medical data for each patient. Alternatively, or in addition, the telepresence device **510** and/or the computer system may determine a risk level for each patient and visit the higher risk patients more frequently than lower risk patients. The risk may be specified in the medical data, for example, as a numerical risk level, and/or the risk may

be computed based on parsing of the medical data. The medical data may be parsed to detect risk factors (e.g., diagnoses requiring more frequency checking, physiological measurements correlated with higher risk, etc.).

In an embodiment, the telepresence device **510** may query the EMR system to ascertain whether a patient has been diagnosed (e.g., by a care provider, the telepresence device **510**, and/or the like) with a urinary tract infection (UTI) or sepsis and may check the patient more frequently for sepsis if the patient has a UTI and/or an existing sepsis diagnosis due to the higher risk for sepsis. Because it can be important to achieve certain metrics (e.g., venous pressure, hemoglobin levels, etc.) in a short time frame when treating sepsis, the telepresence device **510** may also, or instead, monitor sepsis patients at a predetermined frequency (e.g., at predetermined intervals) to ensure that they are meeting the desired goals and/or that care providers know when a patient characteristic is outside a desired range. Alternatively, or in addition, a care provider may manually identify patients having a higher risk of sepsis (e.g., in an online database that can be queried by the telepresence device **510**).

The exemplary depiction **500** of the healthcare facility map **560** includes a previously travelled route **540** and a route **530** currently being travelled by the telepresence device **510**. In the illustrated embodiment, the telepresence device **510** does not simply visit the rooms in an order determined based on spatial proximity to each other. Rather, the telepresence device **510** may weight the relative spatial proximity in addition to weighting patient monitoring frequency, which may have been determined based on risk. The telepresence device **510** may attempt to take advantage of spatial proximity of patients while also ensuring that higher risk patients aren't neglected for lower risk patients that are more proximate. In some embodiments, movement of the telepresence device **510** may be controlled by a central server (e.g., the server **110**), which may receive real-time telemetry data from a plurality of patients and dynamically adjust the order of patient monitoring, and/or the telepresence device **510** may be configured to receive real-time telemetry data and dynamically adjust its route.

FIG. **6** is a perspective view of a telepresence device **610** performing one or more diagnostic activities on a patient **650** using an image sensor **611**. The telepresence device **610** may include the image sensor **611** (e.g., a video camera) and a display device **615**, which is showing an image captured by the image sensor **611** in the illustrated embodiment. In many embodiments, the image captured by the image sensor may not be displayed on the display device **615** but is included here for illustrative purposes. Instead, the image may be processed internally by the telepresence device **610**, provided to a remote care provider, archived, etc. The telepresence device **610** may use the image sensor **611** to measure one or more patient characteristics, such as a physiological characteristic, of the patient **650**. For example, the telepresence device **610** may use Eulerian video magnification to detect small changes in color and/or small movements in the captured video and amplify the detected changes and/or movements. The telepresence device **610** may then extract heart rate from detected changes in skin color (e.g., by determining the frequency of skin reddening corresponding to heart beats) and/or respiration rate from detected movements of the patient's chest (e.g., by determining the frequency of chest movements).

Alternatively, or in addition, the telepresence device **610** may determine a measurement of a physiological characteristic by receiving telemetry data from a patient monitor **630**. In one embodiment, the telepresence device **610** may use

optical character recognition to read telemetry data displayed by the patient monitor **630**. In another embodiment, the telepresence device **610** may use a wireless network to request the telemetry data from the patient monitor **630** and/or to request the telemetry data from a computer system coupled to the patient monitor **630** (e.g., an EMR system).

The telepresence device **610** may also, or instead, detect the patient's pallor using the image sensor **611**. Referring also to FIG. **7**, the telepresence device **610** may be configured to determine the fluid level, the fluid color, and/or the like of a fluid bag **730** of a patient **750** using the image sensor **611**. For example, the telepresence device **610** may detect when intravenously supplied saline, medication, and/or the like is running low, and/or the telepresence device **610** may detect the color and/or fluid level of a urine bag (e.g., to detect perfusion). If a potentially harmful condition is determined to exist from the one or more diagnostic activities, an alarm may be triggered. In an embodiment, the patient monitor **630** and/or fluid bag **730** may be identified using scale-invariant feature transform (SIFT), speeded up robust features (SURF), and/or oriented features from accelerated segment test and rotated binary robust independent elementary features (ORB). The boundaries of the patient's face may be determined using Haar feature detectors. A level of the fluid bag **730** may be determined by finding the most salient line using Hough line detection. Color thresholds may be determined by averaging the color within the boundary of the fluid bag **730** or facial area and calculating the RGB distance of that color to a desired norm. The system may perform white balancing with a known white feature in the room prior to performing a test requiring color measurement since white balance may materially impact color detection.

The measurements of the patient characteristics may complement the telemetry data received from the patient monitor **630**, and/or the measurements may back up or replace the telemetry data. For example, pallor, fluid level, fluid color, temperature symmetry (as discussed below with regard to FIG. **8**) and/or the like may be combined with telemetry data to evaluate whether a potentially harmful condition exists. Alternatively, or in addition, the telemetry data may correspond to the one or more patient characteristic measured by the telepresence device **610**. The telepresence device **610** may measure the one or more patient characteristics to confirm accuracy of the telemetry data, and/or the telepresence device **610** may measure the one or more patient characteristics once it has attempted to acquire the telemetry data and has been unable to do so (e.g., the telepresence device **610** detects that the patient **650**, **750** is not connected to a patient monitor, requests telemetry data and does not receive a response, determines the patient is in room with little or no telemetry or unlikely to have telemetry, such as a room in a Medical/Surgical ward, and/or the like).

If a potentially harmful condition is detected, an action responsive to the potentially harmful condition may be performed as previously discussed. The action may include providing medical data acquired by the image sensor **611** to a local and/or remote care provider. For example, images and/or video of fluid levels, fluid color, pallor, etc. may be made available to the care provider (e.g., by uploading over a wireless network to a central server), and/or an indication of why the fluid level, fluid color, pallor, etc. caused an alarm to be triggered may be provided. For some alarms, such as when a patient potentially has sepsis, a care provider may want to watch for visual cues of respiratory distress when making a diagnosis. Accordingly, the telepresence device

610 may record a video clip of the patient's respiration once the alarm has been triggered and while waiting for the care provider to respond. The video clip may be made immediately available to the care provider once the care provider has responded. For other potentially harmful conditions, video clips of other activities by the patient and/or other regions of the patient's body may be captured instead.

FIG. 8 is a perspective view of a telepresence device 810 performing one or more diagnostic activities on a patient 850 using a thermal camera 812. The telepresence device 810 may include a display device 815, which is showing a thermographic image captured by the thermal camera 812 in the illustrated embodiment. In many embodiments, the thermographic image may not be displayed on the display device 815 but is included here for illustrative purposes. Instead, the image may be processed internally by the telepresence device 810, provided to a remote care provider, archived, etc. The telepresence device 810 may estimate a temperature of the patient 850 from the thermographic image, for example, if the temperature cannot be determined from telemetry data. The telepresence device 810 may use Haar feature detectors to detect the boundaries of the face and compute an average temperature within those boundaries. The telepresence device 810 may determine an overall or core temperature and/or may determine whether the patient's limbs/extremities are warmer or colder than is desirable relative to the overall or core temperature. The telepresence device 810 may determine the location of limbs using a depth sensor (not shown) and associated skeletal mapping software. The temperature of the limb may then be determined by computing an average temperature of an area in close proximity to the center point of the detected limb. The patient may be prompted to remove part of a blanket to facilitate this measurement. Alternatively, or in addition, the telepresence device 810 may determine whether the temperature of the patient 850 is asymmetric (e.g., whether limbs on one side of the body are warmer or colder than the other side). The telepresence device 810 may also determine whether torso temperature is asymmetric. To do so, the telepresence device 810 may perform skeletal mapping to calculate a center line of the patient's body and may compare temperatures to the left and right of the center line (e.g., points 2, 4, 6, or 8 inches to each side of the center line).

Patient thermal data may be particularly helpful in detecting certain potentially harmful conditions, such as sepsis or infection, that can lead to mortality if not detected early enough. In general, patient thermal data may be used to detect high fever by observing overall temperature, to assess local hot spots suggestive of inflammation or infection, to detect asymmetric body temperature abnormalities, to detect symmetric body temperature abnormalities (e.g., warm shock vs. cold shock), and/or the like. For example, sepsis may be associated with a gradually rising temperature and/or high overall temperature, thermal asymmetry, a gradually rising heart rate, and respiratory distress. For patients at risk for sepsis and/or who begin to show signs, the telepresence device 810 may check the patient on a strict schedule. Because some indications of sepsis include gradual trends, the telepresence device 810 may store (e.g., locally, on an EMR system, etc.) one or more pieces of patient data (e.g., thermal data, telemetry data, etc.) for later review by the telepresence device 810 and/or a care provider. Similarly, patient data may be stored during management and/or treatment of sepsis to detect progress and/or to detect, manage, and/or treat one or more other predetermined conditions.

To detect sepsis, the telepresence device 810 may attempt to measure patient characteristics facially indicative of sep-

sis and evaluate measurements of patient characteristics relative to historical measurements to detect trends indicative of sepsis. In an embodiment, the telepresence device 810 may monitor for an overall temperature over 100 degrees Fahrenheit, a temperature rise of over 2% or 2 degrees Fahrenheit in two hours, a heart rate rise of over 20%, and/or the like. If an individual characteristic and/or plurality of characteristics are indicative of sepsis, the telepresence device 810 may take responsive action including triggering an alarm, paging a designated specialist, preparing for connection by an off-site specialist, physically locating a local care provider (as discussed below with regard to FIG. 12), and/or the like. The telepresence device 810 and/or a central server (not shown) may perform responsive actions according to a prioritize ordering. The telepresence device 810 may query a database to determine if a local qualified care provider is available, in which case the local qualified care provider may be paged. Otherwise, if a local qualified care provider is not available, a remote qualified care provider who is on-call may be paged, and the telepresence device 810 may prepare for a remote connection. Heart rate and respiration rate may be measured directly by the telepresence device 810 (e.g., using Eulerian video magnification) and/or may be determined by receiving telemetry data. In some embodiments, the telepresence device 810 may trigger a sepsis alarm only if there are a combination of multiple indications, such as one or more indications from a networked telemetry device along with one or more indications from the telepresence device's own imaging systems.

FIG. 9 is a perspective view of a telepresence device 910 performing one or more diagnostic activities on a patient 950 using a depth sensor 913. The telepresence device 910 may include one or more image sensors 911 (e.g., a video camera) used by the depth sensor 913 to determine depth. Alternatively, or in addition, the one or more image sensors 911 used by the telepresence device 910 may be distinct from image sensors used by the telepresence device 910 to perform visual assessments. The telepresence device 910 may also include a display device 915, which is showing a stick model of the patient 950 as determined by the depth sensor in the illustrated embodiment. In many embodiments, the internal depth model may not be displayed on the display device 915 but is included here for illustrative purposes. Instead, the model may be processed internally by the telepresence device 910, provided to a remote care provider, archived, etc. The position of the patient 950 and/or the patient's limbs and motion by the patient 950 may be determined using the depth sensor (e.g., via an off-the-shelf skeletal mapping software program configured to process the 3D point cloud data from the depth sensor). The depth sensor 913 may be used in combination with a thermal camera 912 to detect the existence of thermal asymmetries. For example, the depth sensor 913 may determine the location of one or more limbs, and the temperature of the limb may be determined from temperature data corresponding to the location of the limb.

The telepresence device 910 may be able to determine whether the patient is sleeping based on gross motor activity of one or more of the patient's body parts (e.g., the telepresence device 910 may perform actigraphy using the depth sensor 913). Monitoring multiple body parts may improve the accuracy of the determination of whether the patient is sleeping. In an embodiment, the system may detect motion of limbs using skeletal mapping with the depth sensor, may detect motion of the head using Haar feature detectors, and may identify a sleeping state versus wakefulness through preconfigured thresholds of movement of the limbs and face.

The telepresence device **910** and/or local care providers may be able to shift interactive tests and/or diagnostics to times when the patient **950** is awake based on the assessment by the telepresence device **910** of whether the patient **950** is asleep. For example, a local care provider may subscribe to be notified by the telepresence device **910** when the patient **950** wakes up. Once the patient **950** is awake, any delayed tests may be performed. Because patients will need to be woken up less frequently, the stress, fatigue, and “ICU psychosis” that may result from frequent waking can be avoided. Sleep may be one of several psychological states detectable by the telepresence device **910**. The telepresence device **910** may also or instead be configured to detect agitation and/or distress in the patient based on the position and/or motion of the patient’s limbs (e.g., using a modification of the thresholds for detecting a sleeping state). An alarm may be triggered by the telepresence device **910** if agitation or distress is detected without any other indications of a potentially harmful condition and/or if agitation and/or distress are detected in combination with one or more patient characteristics indicative of a potentially harmful condition.

FIG. **10** is a perspective view of a telepresence device **1010** evaluating whether a patient **1050** is currently in their bed **1060** or, for example, has fallen out. The telepresence device **1010** may include one or more image sensors **1011** (e.g., a video camera), a thermal camera **1012**, a depth sensor **1013**, which may leverage the one or more image sensors **1011** to determine depth, and/or the like. The telepresence device **1010** may also include a display device **1015**, which is indicating that the patient **1050** has been detected in the bed **1060** in the illustrated embodiment. In many embodiments, the determination of whether the patient **1050** is in the bed **1060** may not be displayed on the display device **1015** but is included here for illustrative purposes. Instead, sensor data may be processed internally by the telepresence device **1010**, provided to a remote care provider, archived, etc. The telepresence device **1010** may use a combination of information from the one or more image sensors **1011**, the thermal camera **1012**, the depth sensor **1013**, and/or the like to detect whether the patient **1050** is in their bed **1060**. For example, the telepresence device **1010** may detect the edges of the bed **1060** using the depth sensor **1013** and/or the one or more image sensors **1011** and may determine the location of the patient **1050** using the thermal camera **1012** and/or the depth sensor **1013**. If the patient location is inside the detected edges, the telepresence device **1010** may conclude the patient **1050** is in the bed **1060**. If the patient location is not inside the detected edges and/or only partially inside the detected edges, the telepresence device **1010** may conclude the patient **1050** is out of the bed **1060** and/or has fallen. The telepresence device **1010** may take a responsive action, such as triggering an alarm if the patient **1050** is out of the bed **1060**.

FIG. **11** is a perspective view of a telepresence device **1110** performing an interactive test with a patient **1150**. The telepresence device **1110** may display instructions to the patient **1150** using a display device **1115** and/or may speak instructions using one or more speakers (not shown). The interactive test may require the patient **1150** to correctly perform an action. The telepresence device **1110** may determine the performance of the patient **1150** using one or more image sensors **1111**, a depth sensor **1113** in combination with skeletal mapping software, which may leverage the one or more image sensors **1111**, speech recognition, telemetry data, and/or the like. The telepresence device **1110** may evaluate the performance of the patient **1150** and determine whether a potentially harmful condition exists and/or a responsive action should be taken.

For example, the telepresence device **1110** may evaluate whether the patient **1150** has suffered a stroke using the National Institute of Health Stroke Scale (NIHSS). The telepresence device **1110** may explain the NIHSS using audio and/or graphics, video, text, etc. Instructions for each test in the NIHSS may be displayed on the display device **1115** and/or played using the one or more speakers. To determine responsiveness (NIHSS #1A), the telepresence device **1110** may provide an audio and/or video stimulus to the patient **1150** and use the depth sensor **1113** to detect the patient’s response to the stimulus. The telepresence device **1110** may present a prompt, such as an audio questions or an image (e.g., pictures, text, etc.), to the patient **1150** and use speech recognition to evaluate responses to determine consciousness, detect aphasia, detect dysarthria, and/or the like (NIHSS #1B, 9, and 10). Allowances may be made for false positives and/or false negatives that may result from errors in speech recognition. Alternatively, or in addition, responses may be recorded for evaluation by a care provider. Facial recognition (e.g., using Haar-like feature analysis and/or the like via the image sensor **1111**) may be used to detect facial symmetry and/or expression to determine the patient’s ability to close her eyes and/or facial palsy (NIHSS #1C and 4). Eye tracking and/or movements detected by the depth sensor **1113** may be used to determine patient responsiveness to commands (e.g., video and/or audio commands), determine gaze palsy, determine hemianopia, and/or the like (NIHSS #1C, 2, and 3).

Arm drift, leg drift, and limb ataxia may be detected using the depth sensor **1113**, and the display device **1115** may provide instructions and/or a countdown timer to the patient **1150** during the test (NIHSS #5, 6, and 7). For example, the telepresence device **1110** may play synthesized speech stating, “Could you please sit up and hold your arms directly in front of you while you see the timer on my screen? Thank you.” The telepresence device **1110** may then evaluate whether the patient is able to maintain their limbs in an elevated position for a predetermined amount of time. In some embodiments, the telepresence device **1110** may be equipped to provide a tactile stimulus necessary to detect sensory loss and/or extinction and may use speech recognition to determine whether the patient properly perceives the tactile stimulus (NIHSS #8, 11). The telepresence device **1110** may compute a score on the NIHSS to evaluate the patient’s performance and determine whether the patient **1150** has suffered a stroke. Alternatively, or in addition, the telepresence device **1110** may be unable to perform one or more tests and may determine a score without the one or more unperformed tests and/or may request that care provider perform the one or more unperformed tests. The results of the tests, which may include video recording of the test, may be made instantly available to local and/or remote care providers. An alarm may be triggered if certain stroke scale factors or a combination of factors fall outside of certain thresholds. Recorded video, audio, and/or still images for some or all tests may be stored locally and/or on a remote storage device by the telepresence device **1110** for later review by a care provider and/or for quality assessment.

The telepresence device **1110** may directly ask the patient **1150** to assess her own condition. For example, the telepresence device **1110** may ask the patient “How are you breathing?”; “On a scale of 0 to 10, how much pain are you feeling right now?”; and/or the like. To help avoid falling incidents, which frequently occur when patients attempt to use the bathroom, the telepresence device **1110** may ask patients whether they need to use the bathroom. Prompting the patients may be necessary because of embarrassment and/or a lack of lucidity on the part of the patients. The telepresence device **1110** may use speech recognition to determine the response of the patient **1150**. The responses may be archived in audio and/or text form, and/or the

telepresence device 1110 may perform a responsive action if it determines one is necessary, for example, by sending an alert to the nursing station that the patient requires assistance in walking to the bathroom. Additionally, the telepresence device 1110 may be able to request that the patient 1150 remove blankets from a part of their body in order to analyze it thermally since blankets may decrease accuracy of thermal imaging.

Delirium may be associated with increased risk of mortality due to overdosing. Thus, the telepresence device 1110 may perform one or more interactive tests to detect delirium and/or the level of sedation (e.g., using the Richmond Agitation Sedation Scale). If the patient 1150 is in danger of overdosing, the telepresence device 1110 may take a responsive action, such as sending a recommendation to one or more care providers to stop or reduce medication to the patient 1150, noting that a change in medication may be needed in the patient's health record or another documentation system, triggering an alarm, and/or the like. The telepresence device 1110 may determine a frequency of sedation and/or delirium testing based on a risk for overdose and/or an amount of medication previously received and/or currently being received.

FIG. 12 is a perspective view of a telepresence device 1210 informing a care provider 1250 in-person of the existence of an alarm. Care providers may suffer alarm fatigue and may not respond to alarms, for example, under the belief the alarms are not true emergencies. When an alarm has been triggered for a patient, the telepresence device 1210 may locate a care provider 1250 by navigating to a nurses' station as identified on an internal map and identifying a care provider 1250 through Haar feature face detection at a predetermined depth behind the counter. The telepresence device 1210 may alert the identified care provider 1250 that the patient is experiencing an alarm. In some embodiments, the telepresence device 1210 may only travel to the care provider 1250 if the alarm indicates the patient is experiencing a high-priority condition and/or if a predetermined amount of time has transpired without the arrival of a care provider 1250.

The telepresence device 1210 may have triggered the alarm (e.g., after performing one or more diagnostic activities) and/or may determine that an alarm has already been triggered (e.g., by receiving an indication from a patient monitor, an EMR system, and/or the like). Similarly, the telepresence device 1210 may locate the care provider 1250 (e.g., using a vision system 1211), and/or the telepresence device 1210 may be informed of the nearest care provider 1250 by a hospital computer system, which may localize staff through RFID tags in the care providers' badges. The telepresence device 1210 may alert the care provider 1250 by displaying a message on a display device 1215, by playing an alert sound, by playing an audio message comprising synthesized and/or prerecorded speech, and/or the like. The telepresence device 1210 may be configured to increase volume and/or become increasingly annoying until the care provider responds.

A telepresence device may be configured to determine diagnostic activities, responsive actions, and/or frequency of monitoring based on a patient's medical condition, past diagnostic results, etc., for example, as indicated by patient data received by the telepresence device. Alternatively, or in addition, care providers may be able to create custom protocols for monitoring specific patients and/or specific medical conditions, such as a custom protocol for a patient who just underwent a revascularization procedure. Custom protocols may be saved as presets that can be reused. The care provider may be able to include in the custom protocol some or all of the diagnostic activities and/or responsive actions that the telepresence device and/or a ward's telemetry system is able to perform, such as those previously

discussed. The care provider may select a predetermined and/or custom frequency of monitoring. The care provider may be able specify predetermined and/or custom thresholds for diagnostic activities. The custom protocol may include threshold for single measurements and/or trending thresholds as determined from a local storage device, an EMR system, and/or the like.

The responsive actions may include alerting a care provider. The protocol may specify which care providers are alerted and how they are alerted. The protocol may specify whether a nurse or doctor should be contacted, which specialty should be contacted, whether a local or remote care provider should be contacted, and/or the like. For example, a custom protocol may specify that a cardiologist should be contacted for a blood flow anomaly and a neurologist should be contacted for motor response deficiencies. The protocol may specify that a text message should be sent, a page should be sent, an alarm should be triggered, an in-person notification should be delivered, and/or the like. Other responsive actions, such as archiving patient data, preparing to receive a remote connection, etc., may be performed as well or instead. The archived patient data may be available for later review by the telepresence device, a local and/or remote care provider, and/or the like. Table 1 is an exemplary partial list of drop-down options available for custom protocols and includes diagnostic activities and responses that a telepresence device may perform in an embodiment:

Existing Telemetry (or thermal or Eulerian)	
V1	Heart rate
V2	Breathing rate
V3	Gross Temperature
	Patient Q&A (speech recognition)
Q1	Magnitude of pain [specify region]: respond 1 to 10
Q2	Stroke scale #5, #6, and #7 (via 3D point cloud/skeletal mapping)
Q3	Stroke scale #1b, #9, and #10 (via speech recognition)
Q4	Stroke scale #2 and #3 (via gaze tracking)
	Thermal & Intelligent Imaging
T1	Extremity temperature
T2	Asymmetry of temperature
T3	Fluid Color
	Actions: Notifications/Warnings/Archiving
A1	Notify RN immediately
A2	Notify remote intensivist on call
A3	Notify RN when round complete
A4	Archive image/data
A5	Notify remote cardiologist
A6	Notify remote neurologist
	Frequency of Monitoring
F1	q-15-min x ___ hours
F2	q-30-min x ___ hours
...	
F8	q-8-hrs x ___ hours

Table 2 includes examples of custom protocols that may have been specified by a care provider (e.g., using a preset, for one-time use for a specific patient, etc.) and/or performed by a telepresence device:

Patient #	Freq.	Optional custom name or reminder	Sensor 1	Test 1	Responses	
15432	F4	Monitor for chest pain/increase	Q1 [chest]	>5 or increase	A1	A2
18723	F7	Warmth of extremity after revascularization	T1 [Arm-Left-Upper]	2 deg drop from baseline	A3	A6
17892	F4	Warmth of extremity with IAPD present	T1 [Leg-Right]	>48 C.	A2	A4
14998	F2	Breathing pattern with COPD exacerbation	V2	>40	A1	A2
17894	F4	Urine output monitoring for perfusion	T3 [Urine-Bag]	color<>RGB_urine_norm	A1	A2
18023	F7	Neuro- motor/ataxia	Q2	score not in NIHSS_norm	A6	A1
19001	F7	Neuro- LOC/language	Q3	score not in NIHSS_norm	A6	A1
18987	F6	Neuro- gaze/visual	Q4	score not in NIHSS_norm	A6	A1

The telepresence device may continue to perform each custom protocol at the designated frequency until that custom protocol is removed, until it is detected that the patient has been discharged, and/or the like.

According to various embodiments, a telepresence and/or control device may be configured with all or some of the features and embodiments described herein. For example, a telepresence and/or control device may include any number of the features and embodiments described herein as selectively displayed and/or selectively functional options. An explicit enumeration of all possible permutations of the various embodiments is not included herein; however, it will be apparent to one of skill in the art that any of the variously described embodiments may be selectively utilized, if not at the same time, in a single telepresence and/or control device.

It will be understood by those having skill in the art that many changes may be made to the details of the above-described embodiments without departing from the underlying principles of the disclosure. The scope of the present disclosure should, therefore, be determined only by the following claims.

The invention claimed is:

1. A non-transitory computer-readable storage medium including computer-readable instruction code that, when executed, causes a telepresence device to perform operations for autonomously checking a plurality of patients, the operations comprising:

receiving, by a processor, indications of each of the plurality of patients; receiving, by the processor, medical data, via a communications network, for at least one of the plurality of patients;

determining, by the processor, a frequency of checking each of the plurality of patients with the telepresence device based on the received medical data, wherein checking each of the plurality of patients with the telepresence device includes autonomously moving a camera of the telepresence device to capture a series of images of each of the plurality of patients;

responsive to an instruction from the processor, autonomously moving the camera of the telepresence device to capture a first series of images of at least one of the plurality of patients at a first time;

determining, by the processor, a heart rate of the at least one of the plurality of patients by analyzing the first series of images to detect changes in skin color of the at least one patient captured in the first series of image; and

autonomously moving the camera of the telepresence device to capture at least a second series of images of the at least one of the plurality of patients at a second time after a period of time defined by the determined frequency of checking has elapsed.

2. The non-transitory computer-readable storage medium of claim 1, wherein the method further comprises detecting one or more risk factors in the received medical data, and wherein determining the frequency comprises determining the frequency based on the one or more risk factors.

3. The non-transitory computer-readable storage medium of claim 2, wherein detecting one or more risk factors comprises receiving an indication of a diagnosis requiring more frequent checking.

4. The non-transitory computer-readable storage medium of claim 1, wherein the medical data includes an indication of the frequency.

\* \* \* \* \*

专利名称(译)	增强的远程呈现机器人诊断功能		
公开(公告)号	<a href="#">US9974612</a>	公开(公告)日	2018-05-22
申请号	US14/091292	申请日	2014-02-13
[标]申请(专利权)人(译)	英塔茨科技公司		
申请(专利权)人(译)	INTOUCH TECHNOLOGIES , INC.		
当前申请(专利权)人(译)	INTOUCH TECHNOLOGIES , INC.		
[标]发明人	PINTER MARCO WRIGHT TIMOTHY C REYNOLDS H NEAL LAI FUJI WANG YULUN		
发明人	PINTER, MARCO WRIGHT, TIMOTHY C. REYNOLDS, H. NEAL LAI, FUJI WANG, YULUN		
IPC分类号	A61B5/00 A61B34/30 H04N7/14 B25J9/16 B25J11/00 G05D1/00 G06F19/00 A61B5/01 A61B5/16 A61B5/11 A61B5/0205 A61B5/024		
CPC分类号	A61B5/0008 A61B34/30 A61B5/0022 A61B5/0075 A61B5/0077 A61B5/015 A61B5/02055 A61B5/1128 A61B5/165 A61B5/4064 A61B5/4809 A61B5/7264 A61B5/7275 A61B5/741 A61B5/742 A61B5/746 B25J9/1689 B25J11/009 G05D1/0038 H04N7/148 G16H40/67 A61B5/0013 A61B5/024 G05D2201 /0206 G06F19/3418 G16H10/60 G16H50/20 A61B34/10		
优先权	61/729964 2012-11-26 US		
其他公开文献	US20140155755A1		
外部链接	<a href="#">Espacenet</a> <a href="#">USPTO</a>		

摘要(译)

远程呈现设备可以自主检查患者。远程呈现设备可以基于患者是否具有风险因素来确定检查的频率。远程呈现设备可以包括图像传感器，热摄影机，深度传感器，用于与患者交互的一个或多个系统等。远程呈现设备可以被配置为使用一个或多个传感器来评估患者的状况。远程呈现设备可以使用欧拉视频放大来测量生理特征，可以检测苍白，液体水平或流体颜色，可以检测热不对称性，可以根据身体位置或运动来确定心理状态等。远程呈现设备可以确定患者是否正在经历潜在的有害状况，例如脓毒症或中风，并且如果是的话可以触发警报。为了克服警报疲劳，远程呈现设备可能会烦扰护理提供者，直到护理提供者响应警报。

