



US 20200060885A1

(19) **United States**

(12) **Patent Application Publication**
Arizti et al.

(10) **Pub. No.: US 2020/0060885 A1**

(43) **Pub. Date: Feb. 27, 2020**

(54) **SENSOR DEVICES AND SYSTEMS FOR MONITORING THE BASIC NEEDS OF AN INFANT**

(60) Provisional application No. 62/723,179, filed on Aug. 27, 2018.

Publication Classification

(71) Applicant: **The Procter & Gamble Company**, Cincinnati, OH (US)

(51) **Int. Cl.**
A61F 13/42 (2006.01)
A61B 5/00 (2006.01)

(72) Inventors: **Blanca Arizti**, Schmittgen (DE); **Mark Reidy**, Geneva (CH)

(52) **U.S. Cl.**
CPC *A61F 13/42* (2013.01); *A61B 5/0077* (2013.01); *A61B 5/01* (2013.01); *A61B 2562/0219* (2013.01); *A61B 2503/04* (2013.01); *A61B 5/7275* (2013.01)

(21) Appl. No.: **16/452,693**


(22) Filed: **Jun. 26, 2019**

Related U.S. Application Data

(57) **ABSTRACT**

(63) Continuation of application No. 16/402,348, filed on May 3, 2019.

Sensor devices and systems for monitoring the basic needs of an infant comprising feeding, sleeping, and/or voiding (urinating and/or defecating) are described herein.






Fig. 1




Fig. 2




Fig. 5




Fig. 6




Fig. 7




Fig. 8




Fig. 9




Fig. 10




Fig. 11




Fig. 12




Fig. 13




Fig. 14




Fig. 15




Fig. 16




Fig. 17

SENSOR DEVICES AND SYSTEMS FOR MONITORING THE BASIC NEEDS OF AN INFANT

FIELD OF THE DISCLOSURE

[0001] The present disclosure relates to sensor devices and systems for monitoring the basic needs of an infant comprising feeding, sleeping, and/or voiding (urinating and/or defecating).

BACKGROUND

[0002] Smart devices and systems for monitoring the care of infants and ageing adults are becoming more commonplace. Examples of such devices includes wetness sensors associated with diapers and adult incontinence products that can sense when urination occurs and then alert a caregiver that a product change is in order. Visual and audio monitoring devices are also employed for determining the location, activity of, and needs of an infant or adult patient.

[0003] Feeding is a critical function for continued health and life. However, tracking feeding typically involves feedback from the individual feeding, at least some caregiver input, and/or employment of sophisticated equipment. There is a need to easily and automatically sense feeding characteristics (e.g., time and/or intake volume) of an individual that is unable to provide useable feedback to a caregiver and without a caregiver having to track, monitor, and/or record the feeding characteristics.

[0004] Separate and apart from the need for an improved system for understanding feeding characteristics, there is also a need for improved systems and methods for monitoring multiple aspects of an infant's or patient's wellbeing. Known systems tend to be bulky, incorporate electronic components within mass produced disposable articles, and/or are complicated to use in busy lives. Various forms of the present disclosure address one or more of these identified needs.

SUMMARY

[0005] Forms of the present disclosure provide a system for monitoring the basic needs of an infant (or patient), including feeding, sleeping, and/or voiding. The system includes a data gathering module that includes a sensor device for temporary association with an absorbent article or clothing worn by the infant (or patient); a data processing module; and a communication module. The sensor device includes a sensor housing and a plurality of electronic components disposed on and/or within the sensor housing. The data processing unit is configured to receive sensor data from the sensor device and communicate information related to the sensor data to a communication module. The communication module includes a software application that enables information related to feeding, sleeping, and/or voiding to be displayed to a caregiver via a computer platform based on data comprising the sensor data. The information related to voiding can include a urination event, a bowel movement event, or simply a diaper change. The information related to feeding is derived from the sensor device, and can relate to breast feeding, bottle feeding, or both. The data gathering module can also comprise a camera to capture images of an infant or patient wearing a disposable absorbent article to which the sensor device is attached. An optional camera may comprise additional functionality,

including environmental sensing and data processing (e.g., communicating data from the sensor device to a router for subsequent transmission of data via the internet). Systems of the present disclosure may employ multiple cameras. For example, cameras can be placed into several rooms of a house, with the video feeds from one or more of the cameras being communicated to a caregiver. The cameras may be able to detect the presence of a monitored individual through the location of the sensor device and/or via motion detection. In this scenario, only one of the cameras may be communicating data to a caregiver at any one time.

[0006] Systems of the present disclosure can further include a plurality of absorbent articles to which the sensor device can be attached to and detached from. In this form, the sensor becomes a multi-use sensor enabling a cost effective smart product that includes disposable components and a non-disposable component.

[0007] Forms of the present disclosure provide methods for monitoring the basic needs of an infant (or patient). The methods include the steps of providing a sensor device with instructions of how and where to attach the sensor device to a disposable absorbent article, providing a software application operable on a computer device that can display information based on data generated by the sensor device when the disposable absorbent article containing the sensor device is placed onto an infant/patient, and providing data processing for manipulating the data generated by the sensor device to transform or interpret the data generated by the sensor device to consumer understandable information related to feeding, sleeping, and/or voiding.

BRIEF DESCRIPTION OF THE DRAWINGS

[0008] The above-mentioned and other features and advantages of the present disclosure, and the manner of attaining them, will become more apparent and the disclosure itself will be better understood by reference to the following description of example forms of the disclosure taken in conjunction with the accompanying drawings, wherein:

[0009] FIG. 1 is a schematic illustrating modules associated with systems of the present disclosure;

[0010] FIG. 2 is a schematic showing operational aspects of the sensor devices and systems of the present disclosure;

[0011] FIG. 3 is a plan view of an example absorbent article in the form of a taped diaper, garment-facing surface facing the viewer, in a flat laid-out state;

[0012] FIG. 4 is a plan view of the example absorbent article of FIG. 3, wearer-facing surface facing the viewer, in a flat laid-out state;

[0013] FIG. 5 is a front perspective view of the absorbent article of FIGS. 3 and 4 in a fastened position;

[0014] FIG. 6 is a front perspective view of an absorbent article in the form of a pant;

[0015] FIG. 7 is a rear perspective view of the absorbent article of FIG. 6;

[0016] FIG. 8 is a plan view of the absorbent article of FIG. 6, laid flat, with a garment-facing surface facing the viewer;

[0017] FIG. 9 is a cross-sectional view of the absorbent article taken about line IX-IX of FIG. 8;

[0018] FIG. 10 is a cross-sectional view of the absorbent article taken about line X-X of FIG. 8;

[0019] FIG. 11 is a plan view of an example absorbent core or an absorbent article;

[0020] FIG. 12 is a cross-sectional view, taken about line XII-XII, of the absorbent core of FIG. 11;

[0021] FIG. 13 is a cross-sectional view, taken about line XIII-XIII, of the absorbent core of FIG. 11;

[0022] FIG. 14 is a partial view of an exemplary sensor device of the present disclosure;

[0023] FIG. 15 is a caregiver-facing side of a sensor device of the present disclosure;

[0024] FIG. 16 is a disposable article-facing side of the sensor device of FIG. 15; and

[0025] FIG. 17 is an exemplary kit of the present disclosure, comprising a plurality of disposable absorbent articles, two sensor devices, a camera, and two camera docking stations.

DETAILED DESCRIPTION

[0026] Various non-limiting aspects of the present disclosure will now be described to provide an overall understanding of the principles of the structure, function, manufacture, and/or use of the subject matter disclosed herein. In the following detailed description, reference is made to the accompanying figures, which form a part hereof. In the figures, similar symbols may identify similar elements, unless context dictates otherwise. It will be readily understood that the aspects of the present disclosure, as generally described herein, and illustrated in the figures, can be arranged, substituted, combined, separated, and designed in a wide variety of different configurations, all of which are explicitly contemplated herein.

[0027] With reference to FIG. 1, exemplary systems S1 of the present disclosure generally include three elements: a data gathering module 100, a data processing module 102, and a communication module 103. The data gathering module includes a sensor device that can be associated with a disposable absorbent article or article of clothing worn by an infant or patient. Besides a sensor device worn with a disposable absorbent article, the data gathering module can comprise other sensor devices or equipment in proximity to the person wearing the sensor device. For example, the data gathering module may comprise a camera; an environmental sensor for sensing smoke, carbon monoxide, temperature, relative humidity; a motion sensor, an audio recorder, and the like. The data processing module can comprise data transmission, data storage, data interpretation, and/or data manipulation to transform the data from the data gathering module into consumer understandable information related to the wellbeing of an individual, including, for example, feeding, sleeping, and/or voiding. And the communication module comprises a software application for communicating (e.g., displaying) the consumer understandable information.

[0028] FIG. 2 is an exemplary schematic illustrating how sensor devices and systems of the present disclosure can operate. Two example operation modes are shown; one where the sensor device 200 is worn by an infant/patient that is located within a dwelling or care center 202 with wireless communication (e.g., Bluetooth low energy, 15.4, ad hoc mesh networks, and the like) conducted between sensor device 200 and a hub 202. And another where the infant/patient is located remotely (e.g., in a car or stroller) with wireless communication conducted between sensor device 200 and a smart device 204 (e.g., phone). Data and information from sensor device 200 is communicated via a router 203 or smart device 204 to a system frontend 206 for

transforming the data and information to consumer usable information provided via a software application.

[0029] FIG. 2 shows additional optional aspects of systems of the present disclosure. Hub 202 may comprise a camera and other sensors for additional data gathering. Video streams and/or images can be communicated from the optional camera 205 to video data manager 208. It should be understood that while FIG. 2 shows separate data management systems for sensor device data located on Cloud A and for video/image data located on Cloud B, all of the data could be communicated with a single data management system.

[0030] Data management system Cloud A may contain one or more relationship models 210 to enable a primary account holder (e.g., mom or dad) to provide access to some or all of the data to secondary care providers (e.g., grandparent, nanny, daycare employee). By way of example only, the primary account holder receives video/image data, but does not provide access of the same to secondary care providers.

[0031] FIG. 2 shows optional online customer support 212. Customer support 212 can include a variety of functionality ranging from sensor device operational assistance to replenishment of disposable absorbent articles via an integrated eCommerce site.

[0032] FIG. 2 further shows alternative login portals 214 and 216. Login portal 214 is a standalone access for confirming the identity of an account holder that is seeking access to the data and information flowing from the sensor device and systems comprising the same. Login portal 216 represents an alternative access point through an existing network account—for example, a Google or Facebook account.

[0033] Descriptions of exemplary disposable absorbent articles to which the sensor device can be associated with is provided below, followed by a description of the system modules, a description of exemplary sensor device forms, and optional additional aspects of systems of the present disclosure.

[0034] I. Disposable Absorbent Articles

[0035] An exemplary disposable absorbent article 10 according to the present disclosure, shown in the form of a taped diaper, is represented in FIGS. 3-5. FIG. 3 is a plan view of the example absorbent article 10, garment-facing surface 2 facing the viewer in a flat, laid-out state (i.e., no elastic contraction). FIG. 4 is a plan view of the example absorbent article 10 of FIG. 3, wearer-facing surface 4 facing the viewer in a flat, laid-out state. FIG. 5 is a front perspective view of the absorbent article 10 of FIGS. 3 and 4 in a fastened configuration. The absorbent article 10 of FIGS. 3-5 is shown for illustration purposes only as the present disclosure may be used for making a wide variety of diapers, including adult incontinence products, pants, or other absorbent articles, such as sanitary napkins and absorbent pads, for example.

[0036] The absorbent article 10 may comprise a front waist region 12, a crotch region 14, and a back waist region 16. The crotch region 14 may extend intermediate the front waist region 12 and the back waist region 16. The front waist region 12, the crotch region 14, and the back waist region 16 may each be 1/3 of the length of the absorbent article 10. The absorbent article 10 may comprise a front end edge 18, a back end edge 20 opposite to the front end edge 18, and

longitudinally extending, transversely opposed side edges **22** and **24** defined by the chassis **52**.

[0037] The absorbent article **10** may comprise a liquid permeable topsheet **26**, a liquid impermeable backsheet **28**, and an absorbent core **30** positioned at least partially intermediate the topsheet **26** and the backsheet **28**. The absorbent article **10** may also comprise one or more pairs of barrier leg cuffs **32** with or without elastics **33**, one or more pairs of leg elastics **34**, one or more elastic waistbands **36**, and/or one or more acquisition materials **38**. The acquisition material or materials **38** may be positioned intermediate the topsheet **26** and the absorbent core **30**. An outer cover material **40**, such as a nonwoven material, may cover a garment-facing side of the backsheet **28**. The absorbent article **10** may comprise back ears **42** in the back waist region **16**. The back ears **42** may comprise fasteners **46** and may extend from the back waist region **16** of the absorbent article **10** and attach (using the fasteners **46**) to the landing zone area or landing zone material **44** on a garment-facing portion of the front waist region **12** of the absorbent article **10**. The absorbent article **10** may also have front ears **47** in the front waist region **12**. The absorbent article **10** may have a central lateral (or transverse) axis **48** and a central longitudinal axis **50**. The central lateral axis **48** extends perpendicular to the central longitudinal axis **50**.

[0038] In other instances, the absorbent article may be in the form of a pant having permanent or refastenable side seams. Suitable refastenable seams are disclosed in U.S. Pat. Appl. Pub. No. 2014/0005020 and U.S. Pat. No. 9,421,137. Referring to FIGS. **6-10**, an example absorbent article **10** in the form of a pant is illustrated. FIG. **6** is a front perspective view of the absorbent article **10**. FIG. **7** is a rear perspective view of the absorbent article **10**. FIG. **8** is a plan view of the absorbent article **10**, laid flat, with the garment-facing surface facing the viewer. Elements of FIG. **6-10** having the same reference number as described above with respect to FIGS. **3-5** may be the same element (e.g., absorbent core **30**). FIG. **9** is an example cross-sectional view of the absorbent article taken about line IX-IX of FIG. **8**. FIG. **10** is an example cross-sectional view of the absorbent article taken about line X-X of FIG. **8**. FIGS. **9** and **10** illustrate example forms of front and back belts **54, 56**. The absorbent article **10** may have a front waist region **12**, a crotch region **14**, and a back waist region **16**. Each of the regions **12, 14**, and **16** may be 1/3 of the length of the absorbent article **10**. The absorbent article **10** may have a chassis **52** (sometimes referred to as a central chassis or central panel) comprising a topsheet **26**, a backsheet **28**, and an absorbent core **30** disposed at least partially intermediate the topsheet **26** and the backsheet **28**, and an optional acquisition material **38**, similar to that as described above with respect to FIGS. **3-5**. The absorbent article **10** may comprise a front belt **54** in the front waist region **12** and a back belt **56** in the back waist region **16**. The chassis **52** may be joined to a wearer-facing surface **4** of the front and back belts **54, 56** or to a garment-facing surface **2** of the belts **54, 56**. Side edges **23** and **25** of the front belt **54** may be joined to side edges **27** and **29**, respectively, of the back belt **56** to form two side seams **58**. The side seams **58** may be any suitable seams known to those of skill in the art, such as butt seams or overlap seams, for example. When the side seams **58** are permanently formed or refastenably closed, the absorbent article **10** in the form of a pant has two leg openings **60** and a waist opening circumference **62**. The side seams **58** may

be permanently joined using adhesives or bonds, for example, or may be refastenably closed using hook and loop fasteners, for example.

A. Belts

[0039] Referring to FIGS. **9** and **10**, the front and back belts **54** and **56** may comprise front and back inner belt layers **66** and **67** and front and back outer belt layers **64** and **65** having an elastomeric material (e.g., strands **68** or a film (which may be apertured)) disposed at least partially therebetween. The elastic elements **68** or the film may be relaxed (including being cut) to reduce elastic strain over the absorbent core **30** or, may alternatively, run continuously across the absorbent core **30**. The elastic elements **68** may have uniform or variable spacing therebetween in any portion of the belts. The elastic elements **68** may also be pre-strained the same amount or different amounts. The front and/or back belts **54** and **56** may have one or more elastic element free zones **70** where the chassis **52** overlaps the belts **54, 56**. In other instances, at least some of the elastic elements **68** may extend continuously across the chassis **52**.

[0040] The front and back inner belt layers **66, 67** and the front and back outer belt layers **64, 65** may be joined using adhesives, heat bonds, pressure bonds or thermoplastic bonds. Various suitable belt layer configurations can be found in U.S. Pat. Appl. Pub. No. 2013/0211363.

[0041] Front and back belt end edges **55** and **57** may extend longitudinally beyond the front and back chassis end edges **19** and **21** (as shown in FIG. **8**) or they may be co-terminus. The front and back belt side edges **23, 25, 27**, and **29** may extend laterally beyond the chassis side edges **22** and **24**. The front and back belts **54** and **56** may be continuous (i.e., having at least one layer that is continuous) from belt side edge to belt side edge (e.g., the transverse distances from **23** to **25** and from **27** to **29**). Alternatively, the front and back belts **54** and **56** may be discontinuous from belt side edge to belt side edge (e.g., the transverse distances from **23** to **25** and **27** to **29**), such that they are discrete.

[0042] As disclosed in U.S. Pat. No. 7,901,393, the longitudinal length (along the central longitudinal axis **50**) of the back belt **56** may be greater than the longitudinal length of the front belt **54**, and this may be particularly useful for increased buttocks coverage when the back belt **56** has a greater longitudinal length versus the front belt **54** adjacent to or immediately adjacent to the side seams **58**.

[0043] The front outer belt layer **64** and the back outer belt layer **65** may be separated from each other, such that the layers are discrete or, alternatively, these layers may be continuous, such that a layer runs continuously from the front belt end edge **55** to the back belt end edge **57**. This may also be true for the front and back inner belt layers **66** and **67**—that is, they may also be longitudinally discrete or continuous. Further, the front and back outer belt layers **64** and **65** may be longitudinally continuous while the front and back inner belt layers **66** and **67** are longitudinally discrete, such that a gap is formed between them—a gap between the front and back inner and outer belt layers **64, 65, 66**, and **67** is shown in FIG. **9** and a gap between the front and back inner belt layers **66** and **67** is shown in FIG. **10**.

[0044] The front and back belts **54** and **56** may include slits, holes, and/or perforations providing increased breathability, softness, and a garment-like texture. Underwear-like

appearance can be enhanced by substantially aligning the waist and leg edges at the side seams **58** (see FIGS. **6** and **7**).

[0045] The front and back belts **54** and **56** may comprise graphics (see e.g., **78** of FIG. **3**). The graphics may extend substantially around the entire circumference of the absorbent article **10** and may be disposed across side seams **58** and/or across proximal front and back belt seams **15** and **17**; or, alternatively, adjacent to the seams **58**, **15**, and **17** in the manner described in U.S. Pat. No. 9,498,389 to create a more underwear-like article. The graphics may also be discontinuous.

[0046] Alternatively, instead of attaching belts **54** and **56** to the chassis **52** to form a pant, discrete side panels may be attached to side edges of the chassis **22** and **24**. Suitable forms of pants comprising discrete side panels are disclosed in U.S. Pat. Nos. 6,645,190; 8,747,379; 8,372,052; 8,361,048; 6,761,711; 6,817,994; 8,007,485; 7,862,550; 6,969,377; 7,497,851; 6,849,067; 6,893,426; 6,953,452; 6,840,928; 8,579,876; 7,682,349; 7,156,833; and 7,201,744.

B. Topsheet

[0047] The topsheet **26** is the part of the absorbent article **10** that is in contact with the wearer's skin. The topsheet **26** may be joined to portions of the backsheet **28**, the absorbent core **30**, the barrier leg cuffs **32**, and/or any other layers as is known to those of ordinary skill in the art. The topsheet **26** may be compliant, soft-feeling, and non-irritating to the wearer's skin. Further, at least a portion of, or all of, the topsheet may be liquid permeable, permitting liquid bodily exudates to readily penetrate through its thickness. A suitable topsheet may be manufactured from a wide range of materials, such as porous foams, reticulated foams, apertured plastic films, woven materials, nonwoven materials, woven or nonwoven materials of natural fibers (e.g., wood or cotton fibers), synthetic fibers or filaments (e.g., polyester or polypropylene or bicomponent PE/PP fibers or mixtures thereof), or a combination of natural and synthetic fibers. The topsheet may have one or more layers. The topsheet may be apertured (FIG. **4**, element **31**), may have any suitable three-dimensional features, and/or may have a plurality of embossments (e.g., a bond pattern). The topsheet may be apertured by overbonding a material and then rupturing the overbonds through ring rolling, such as disclosed in U.S. Pat. No. 5,628,097, to Benson et al., issued on May 13, 1997 and disclosed in U.S. Pat. Appl. Publication No. US 2016/0136014 to Arora et al. Any portion of the topsheet may be coated with a skin care composition, an antibacterial agent, a surfactant, and/or other beneficial agents. The topsheet may be hydrophilic or hydrophobic or may have hydrophilic and/or hydrophobic portions or layers. If the topsheet is hydrophobic, typically apertures will be present so that bodily exudates may pass through the topsheet.

C. Backsheet

[0048] The backsheet **28** is generally that portion of the absorbent article **10** positioned proximate to the garment-facing surface of the absorbent core **30**. The backsheet **28** may be joined to portions of the topsheet **26**, the outer cover material **40**, the absorbent core **30**, and/or any other layers of the absorbent article by any attachment methods known to those of skill in the art. The backsheet **28** prevents, or at

least inhibits, the bodily exudates absorbed and contained in the absorbent core **10** from soiling articles such as bedsheets, undergarments, and/or clothing. The backsheet is typically liquid impermeable, or at least substantially liquid impermeable. The backsheet may, for example, be or comprise a thin plastic film, such as a thermoplastic film having a thickness of about 0.012 mm to about 0.051 mm. Other suitable backsheets may include breathable materials which permit vapors to escape from the absorbent article, while still preventing, or at least inhibiting, bodily exudates from passing through the backsheet.

D. Outer Cover Material

[0049] The outer cover material (sometimes referred to as a backsheet nonwoven) **40** may comprise one or more nonwoven materials joined to the backsheet **28** and that covers the backsheet **28**. The outer cover material **40** forms at least a portion of the garment-facing surface **2** of the absorbent article **10** and effectively "covers" the backsheet **28** so that film is not present on the garment-facing surface **2**. The outer cover material **40** may comprise a bond pattern, apertures, and/or three-dimensional features.

E. Absorbent Core

[0050] As used herein, the term "absorbent core" **30** refers to the component of the absorbent article **10** having the most absorbent capacity and that comprises an absorbent material. Referring to FIGS. **11-13**, in some instances, absorbent material **72** may be positioned within a core bag or a core wrap **74**. The absorbent material may be profiled or not profiled, depending on the specific absorbent article. The absorbent core **30** may comprise, consist essentially of, or consist of, a core wrap, absorbent material **72**, and glue enclosed within the core wrap. The absorbent material may comprise superabsorbent polymers, a mixture of superabsorbent polymers and air felt, only air felt, and/or a high internal phase emulsion foam. In some instances, the absorbent material may comprise at least 80%, at least 85%, at least 90%, at least 95%, at least 99%, or up to 100% superabsorbent polymers, by weight of the absorbent material. In such instances, the absorbent material may be free of air felt, or at least mostly free of air felt. The absorbent core periphery, which may be the periphery of the core wrap, may define any suitable shape, such as rectangular "T," "Y," "hour-glass," or "dog-bone" shaped, for example. An absorbent core periphery having a generally "dog bone" or "hour-glass" shape may taper along its width towards the crotch region **14** of the absorbent article **10**.

[0051] Referring to FIGS. **11-13**, the absorbent core **30** may have areas having little or no absorbent material **72**, where a wearer-facing surface of the core bag **74** may be joined to a garment-facing surface of the core bag **74**. These areas having little or no absorbent material may be referred to as "channels" **76**. These channels can embody any suitable shapes and any suitable number of channels may be provided. In other instances, the absorbent core may be embossed to create the impression of channels. The absorbent core in FIGS. **11-13** is merely an example absorbent core. Many other absorbent cores with or without channels are also within the scope of the present disclosure.

F. Barrier Leg Cuffs/Leg Elastics

[0052] Referring to FIGS. **3** and **4**, for example, the absorbent article **10** may comprise one or more pairs of

barrier leg cuffs **32** and one or more pairs of leg elastics **34**. The barrier leg cuffs **32** may be positioned laterally inboard of leg elastics **34**. Each barrier leg cuff **32** may be formed by a piece of material which is bonded to the absorbent article **10** so it can extend upwards from a wearer-facing surface **4** of the absorbent article **10** and provide improved containment of body exudates approximately at the junction of the torso and legs of the wearer. The barrier leg cuffs **32** are delimited by a proximal edge joined directly or indirectly to the topsheet and/or the backsheet and a free terminal edge, which is intended to contact and form a seal with the wearer's skin. The barrier leg cuffs **32** may extend at least partially between the front end edge **18** and the back end edge **20** of the absorbent article **10** on opposite sides of the central longitudinal axis **50** and may be at least present in the crotch region **14**. The barrier leg cuffs **32** may each comprise one or more elastics **33** (e.g., elastic strands or strips) near or at the free terminal edge. These elastics **33** cause the barrier leg cuffs **32** to help form a seal around the legs and torso of a wearer. The leg elastics **34** extend at least partially between the front end edge **18** and the back end edge **20**. The leg elastics **34** essentially cause portions of the absorbent article **10** proximate to the chassis side edges **22**, **24** to help form a seal around the legs of the wearer. The leg elastics **34** may extend at least within the crotch region **14**.

G. Elastic Waistband

[0053] Referring to FIGS. **3** and **4**, the absorbent article **10** may comprise one or more elastic waistbands **36**. The elastic waistbands **36** may be positioned on the garment-facing surface **2** or the wearer-facing surface **4**. As an example, a first elastic waistband **36** may be present in the front waist region **12** near the front belt end edge **18** and a second elastic waistband **36** may be present in the back waist region **16** near the back end edge **20**. The elastic waistbands **36** may aid in sealing the absorbent article **10** around a waist of a wearer and at least inhibiting bodily exudates from escaping the absorbent article **10** through the waist opening circumference. In some instances, an elastic waistband may fully surround the waist opening circumference of an absorbent article.

H. Acquisition Materials

[0054] Referring to FIGS. **3**, **4**, **9**, and **10**, one or more acquisition materials **38** may be present at least partially intermediate the topsheet **26** and the absorbent core **30**. The acquisition materials **38** are typically hydrophilic materials that provide significant wicking of bodily exudates. These materials may dewater the topsheet **26** and quickly move bodily exudates into the absorbent core **30**. The acquisition materials **38** may comprise one or more nonwoven materials, foams, cellulosic materials, cross-linked cellulosic materials, air laid cellulosic nonwoven materials, spunlace materials, or combinations thereof, for example. In some instances, portions of the acquisition materials **38** may extend through portions of the topsheet **26**, portions of the topsheet **26** may extend through portions of the acquisition materials **38**, and/or the topsheet **26** may be nested with the acquisition materials **38**. Typically, an acquisition material **38** may have a width and length that are smaller than the width and length of the topsheet **26**. The acquisition material may be a secondary topsheet in the feminine pad context. The acquisition material may have one or more channels as

described above with reference to the absorbent core **30** (including the embossed version). The channels in the acquisition material may align or not align with channels in the absorbent core **30**. In an example, a first acquisition material may comprise a nonwoven material and as second acquisition material may comprise a cross-linked cellulosic material.

I. Landing Zone

[0055] Referring to FIGS. **3** and **4**, the absorbent article **10** may have a landing zone area **44** that is formed in a portion of the garment-facing surface **2** of the outer cover material **40**. The landing zone area **44** may be in the back waist region **16** if the absorbent article **10** fastens from front to back or may be in the front waist region **12** if the absorbent article **10** fastens back to front. In some instances, the landing zone **44** may be or may comprise one or more discrete nonwoven materials that are attached to a portion of the outer cover material **40** in the front waist region **12** or the back waist region **16** depending upon whether the absorbent article fastens in the front or the back. In essence, the landing zone **44** is configured to receive the fasteners **46** and may comprise, for example, a plurality of loops configured to be engaged with, a plurality of hooks on the fasteners **46**, or vice versa.

[0056] Absorbent article **10** may optionally employ a second landing zone area **95**, as shown on FIG. **3**, for sensor device attachment. Landing zone area **95** may comprise a discrete strip of material that is affixed to garment-facing surface **2**. For example, a discrete fibrous strip of material may be used to engage hooks on an article-facing surface of the sensor device. Landing zone area **95** may comprise alternative engagement features, such as, for example, a pocket for partially or completely receiving the sensor device. It should be understood that the sensor device may be attachable directly to outer cover material **40** without the need for an additional strip of material or other landing zone component.

J. Wetness Indicator/Graphics

[0057] Referring to FIG. **3**, the absorbent articles **10** of the present disclosure may comprise graphics **78** and/or wetness indicators **80** that are visible from the garment-facing surface **2**. The graphics **78** may be printed on the landing zone **40**, the backsheet **28**, and/or at other locations. The wetness indicators **80** are typically applied to the absorbent core facing side of the backsheet **28**, so that they can be contacted by bodily exudates within the absorbent core **30** and thereafter change in visual appearance (for example, change color via pH sensitive materials). In some instances, the wetness indicators **80** may form portions of the graphics **78**. For example, a wetness indicator may appear or disappear and create/remove a character within some graphics. In other instances, the wetness indicators **80** may coordinate (e.g., same design, same pattern, same color) or not coordinate with the graphics **78**.

[0058] Graphic **82** is an optional target graphic for aiding a consumer in attaching a sensor device to absorbent article **10**. Fig. **3** shows graphic **82** is proximate to but spaced apart from wetness indicator **80**, but it can alternatively be adjacent to and/or overlap with indicator **80** depending on the size and configuration of a chosen sensor device.

K. Front and Back Ears

[0059] Referring to FIGS. 3 and 4, as referenced above, the absorbent article 10 may have front and/or back ears 47, 42 in a taped diaper context. Only one set of ears may be required in most taped diapers. The single set of ears may comprise fasteners 46 configured to engage the landing zone or landing zone area 44. If two sets of ears are provided, in most instances, only one set of the ears may have fasteners 46, with the other set being free of fasteners. The ears, or portions thereof, may be elastic or may have elastic panels. In an example, an elastic film or elastic strands may be positioned intermediate a first nonwoven material and a second nonwoven material. The elastic film may or may not be apertured. The ears may be shaped. The ears may be integral (e.g., extension of the outer cover material 40, the backsheet 28, and/or the topsheet 26) or may be discrete components attached to a chassis 52 of the absorbent article on a wearer-facing surface 4, on the garment-facing surface 2, or intermediate the two surfaces 4, 2.

[0060] II. Data Gathering Module

[0061] The data gathering module comprises the sensor device. The sensor device can be a single-use device, or a multi-use device that is attachable to and detachable from a disposable absorbent article (such as absorbent article 10 shown in FIGS. 3-8) or article of clothing worn by an individual. When the sensor device is a single-use device it may come already associated with a purchased absorbent article or it may be attachable by a wearer or caregiver.

[0062] The sensor device includes a sensor housing that generally protects sensors and other electronic components disposed therein, as well as inhibiting unwanted contact of the same with an infant, patient, or caregiver. The housing can be made from a variety of materials, both flexible and rigid, examples of which include thermoplastic polymers, thermoplastic elastomers, silicone, Tecaform, Tecanant, and combinations thereof. Other materials can also be employed for the housing so long as it is generally regarded as safe for human contact and does not cause irritation or other unwanted health effects. Inclusion of a bittering agent or other approaches may optionally be used to discourage placement of the sensor device in one's mouth or otherwise tampering with the sensor device.

[0063] The sensor device may be attachable to skin (via hydrogel or bio-adhesive material, for example), to a disposable article such as an absorbent article defined herein, and/or to clothing worn by an individual. Various attachment mechanisms may be employed for attaching the sensor device to an article of clothing or an absorbent article. For example, hook and loop fastening mechanisms, magnets, adhesives, thermal bonds, and male and female mating fasteners such as snaps and buttons. Receiving features, such as pockets, recesses, and voids may also be employed that essentially hold the sensor device with or without attachment features. In yet another form, an auxiliary article may be used to integrate the sensor device with an absorbent article. The auxiliary article may be in the form of a pant-like reusable garment designed to fit over an absorbent article. Such auxiliary articles may include inexpensive, stretchable materials including, for example, rayon, nylon, polyester, polyolefins, spandex, cotton, wool, and combinations thereof.

[0064] In one form, the sensor device is adapted for attachment to the outer cover of an absorbent article. Hook and loop features can be used with this attachment approach.

For example, a strip of hook material can be affixed to one surface of the sensor housing, where the hooks can engage directly with material used for the outer cover or with an added strip of material, such as landing zone 95 shown in FIG. 3.

[0065] The sensor housing comprises a plurality of electronic component disposed on and/or within the housing. Typically, the electronic components include at least one sensor, a transmitter, and a power source (e.g., a disposable battery or a rechargeable battery). The number and type of sensors employed by the sensor device are chosen based on the application of the systems and methods disclosed herein. Exemplary sensors include, but are not limited to, optical sensors, color sensors, wetness sensors, BM (bowel movement) sensors, motion sensors, temperature sensors, chemical sensors, strain gauges, and combinations thereof. A VOC (volatile organic compound) sensor is one suitable type of a BM sensor. And a triaxial accelerometer (typically measuring linear movement/motion) is one suitable type of motion sensor. Alternative or additional motion sensors can be used, including, for example, inertial measurement units (IMUs), gyroscopes for measuring angular movements, and magnetometer for measuring magnetic fields. The VOC sensors can be of MOS-type (metal oxide). BM sensors can be capable of acting as an electronic nose to detect chemical signatures of organic materials associated with body exudates, including, for example, skatole, mercaptans, amines, volatile fatty acids, acetone, methyl acetate, and methanol. BM sensors may also include leverage an optical or color sensor to detect the presence of feces in the article. Along these lines, multiple optical or color sensors can be used to detect both urine and feces, based either on their inherent colors or based on use of an indicator that changes color in the presence of urine and/or feces. For example, the following enzymes associated with body exudates can trigger an optical change in an included indicator that can be sensed by an optical or color sensor: urease, trypsin, chemotrypsin, LAP, lipase, amilase, and urease.

[0066] Wetness sensors for detecting the presence of urine or other bodily fluid can include optical sensors, color sensors, and electrical sensors that comprise a resistance, capacitance, inductance or continuity sensitive indicator. A resistance sensitive indicator can be provided, for example, by providing two electrical conductors disposed at a given spatial distance relative to each other.

[0067] FIGS. 14 and 15 illustrate aspects of one exemplary sensor device 300 comprising a plurality of sensors and other electronic components. FIG. 14 shows the sensor device in a manufactured form before its final configuration and encasing with a sensor housing 310 (shown in FIG. 15). With reference to FIG. 14, multiple electrically-connected printed circuit boards 312, 313, 314, and 315 are employed. Printed circuit board 312 comprises an optical sensor 320, an absorbent article-facing light source 322, a power management component 324, a flash memory component 326, an optical sensor frontend 328, a processor and transmitter component 330, and an antenna 332. Printed circuit board 313 comprises a motion sensor (e.g., accelerometer) 334 and a power source (e.g., coin cell battery) 336. Printed circuit board 314 comprises a BM sensor (e.g., VOC sensor) 338, a temperature and relative humidity sensor 340, a second optical sensor 342, and a second absorbent article-facing light source 344. And printed circuit board 315 comprises a consumer-engageable button 346 for activating or otherwise

operating sensor device 300, and a caregiver-facing light source 348 to indicate an operational aspect of sensor device 300. Button 346 or similar engageable feature can be used for multiple tasks. For example, button 346 can be initially activated for “waking” the sensor up from a power-save mode and/or manually activated by a caregiver upon changing an absorbent article if a wearer of the article has had a bowel movement. Acknowledgement of a bowel movement via action of button 346 or similar engageable feature can be communicated by the sensor device to a communication module for tracking timing, frequency, or other aspects of a wearer’s bowel movement history. One skilled in the art would appreciate that a single circuit board can be employed in a sensor device, as well as other numbers of circuit boards beyond what is shown in FIG. 14.

[0068] FIG. 14 includes two arrows showing how exemplary sensor device 300 is manipulated, with circuit boards 313 and 315 being folded over onto circuit board 312 before sensor housing 310 is added as shown in FIG. 15. The caregiver-facing surface 350 is shown in FIG. 15, wherein button 346 is and light source 348 are visible.

[0069] FIG. 16 shows article-facing surface 360 of sensor device 300. Note that internal components are not shown in FIG. 16 like they were in FIG. 15. Instead, FIG. 16 illustrates windows 362 in sensor housing 310 to permit the pairs of light sources 322, 344 and optical sensors 320, 342 to operate properly, particularly when sensor housing 310 is opaque. Article-facing surface 360 also includes a port 364 for BM sensor 338, and a port 366 for temperature a relative humidity sensor 340 to operate properly. Lastly, exemplary sensor device 300 includes a patch of hook material 370 for engaging fibrous material on a disposable absorbent article.

[0070] Many prior art systems that included more than one sensor type would employ individual sensor housings for each of the sensor types. This can be disadvantageous, as it can require attachment and detachment of multiple items from an article, which is cumbersome and can increase errors. Thus, integrating multiple sensors into a single sensor housing can be highly desirable. However, the overall size or footprint of such a sensor housing can become large as functionality increases. And while a relatively large sensor device and accompanying sensor housing is okay for attachment to an article of clothing like a onesie, the available area for attachment to a small size disposable absorbent article (e.g., newborn size, or size 1 or 2 diaper) is quite limited. In some forms of the present disclosure, the sensor device comprises a transmitter, a battery, and three, four, five or more sensors within a single sensor housing that is attachable within an absorbent article area of 25 cm² or 20 cm² or less. This area or sensor “footprint” can be determined a number of different ways, including attaching the sensor to an absorbent article, drawing a line around the perimeter of the sensor with a marker, removing the sensor, and then conducting image analysis to determine the area within the drawn line. In these or other forms of the present disclosure, center-to-center distances between adjacent electronic components within the sensor housing is no more than 2.0 cm, 1.5 cm, 1.0 cm, 0.8 cm, or 0.5 cm. In yet other forms, the distance between attachment points of adjacent electronic components to a printed circuit board or other substrate can be no more than 20 mm, 10 mm, 8 mm, 5 mm, 4 mm, 3 mm, or 2 mm. While it can be advantageous to employ as many different electronic components within a given area/volume to increase sensor device functionality, at least some of the

sensor devices of the present disclosure are removable from an absorbent article. And if removable, the sensor device must comply with safety regulations including small part regulations for products marketed for use with infants and minors. Choking is one of the concerns with products in this marketing space. United States 16 Code of Federal Regulation (“CFR”) 1501.4 defines a cylinder test apparatus, and products must be able to fit entirely within this test cylinder to comply with regulations. Some sensor devices described herein have multiple monitoring capabilities, but are sized and configured so as not to fit entirely within the cylinder test apparatus. For safety and convenient handling of the sensor device, it may be useful that the sensor device in applications with infants has a length of at least 3 cm, 4 cm, 5 cm, 6 cm, 7 cm, 8 cm, or more, and normally less than 15 cm and a width of at 1 cm, 2 cm, 3 cm, or 4 cm, and normally less than 8 cm. Exemplary sensor device thicknesses are those from about 0.2 cm to about 1.5 cm. For applications with toddlers or adults, the dimensions of the sensor device may be the same or larger.

[0071] In one form, the sensor device comprises a power source in the form of a battery, a transmitter, multiple optical sensors (e.g., a color sensor), multiple light sources (e.g., an LED), an accelerometer, and optionally a VOC sensor. The sensor device is attached to an absorbent article comprising a wetness indicator, as described above, such that the light source can direct light onto the wetness indicator. The wetness indicator changes appearance (e.g., changes color) when a wearer urinates into the absorbent article. The optical sensor measures the reflected light from the wetness indicator to sense when a urination event occurs. Multiple pairs of absorbent article-facing light sources and optical sensors can be employed to sense changes of a wetness indicator at different points along the indicator to confirm a urination event has occurred, or predict the volume of urine and/or number of urination events that occurred. A signal from the optical sensor can then be transmitted to the data processing module. The accelerometer is employed to track data associated with sleep and awake times. The awake data can include awake feeding motion data and awake non-feeding motion, and the inventors have discovered how to distinguish the two. The accelerometer is capable of sensing breastfeeding times and provide feeding information for one’s right breast and left breast. And the optional VOC sensor can sense a bowel movement and communicate a signal indicating the same via the transmitter.

[0072] The data gathering module may also contain secondary devices that while not necessarily intimately associated with an infant or patient, can obtain data and information regarding the status of the infant/patient and/or their environment, and/or impact their environment. By way of example only, the data gathering module may contain a camera, a light source, an audio device (comprising a speaker and/or microphone), a carbon monoxide sensor, a smoke detector, humidity device, and temperature device.

[0073] III. Data Processing Module

[0074] The data processing module can comprise data transmission, data storage, data interpretation, data filtering, and/or data manipulation to transform the data from the data gathering module into consumer understandable information related to the wellbeing of an individual, including, for example, feeding, sleeping, and/or voiding. The data processing module can include algorithms to parse/filter the received data. Data processing can be accomplished by one

or more devices and in the same or different locations. For example, the sensor device may optionally employ a memory device to temporarily store data. One reason for temporary storage of data is when communication between the sensor device and a remote data processing module component and/or the information communication module is unavailable.

[0075] The sensor device may also optionally employ a data processor for processing raw data from one or more sensors associated with the sensor device prior to transmitting data/information based on the raw data. This can reduce the volume of data/information transmitted from the sensor device, and thereby reduce the amount of power required and accompanying electromagnetic radiation emission.

[0076] IV. Information Communication Module

[0077] The communication module comprises a software application operable on a computer device to display information related to the data obtained by the data gathering module, including data transformed via the data processing module. The computer device may be a smart phone, as is shown in FIG. 2, but other computer devices, such as a laptop, tablet, digital assistant (ALEXA and GOOGLE HOME, for example) can be used to communicate information to one or more caregivers.

[0078] V. Systems and Kits

[0079] Sensor devices and systems including the same can form a part of consumer purchasable kit. One exemplary kit includes two or more sensor devices as described herein, a camera, a plurality of absorbent articles that can accept the sensor devices, and access to a software application for viewing data and information flowing from the sensor device and any other secondary data gathering device(s). A subscription can also be offered to consumers that provides delivery of additional absorbent articles, sensor devices, and/or continued access and operation of the software application. For example, a subscription can include an automatic delivery of a number of absorbent articles every two weeks along with a code or other mechanism for continued operation of the software application. The subscription can work with an affirmative action request by a consumer or as an automatic delivery order that delivers products on a set re-occurring schedule until the schedule reaches a predetermined endpoint, or is altered or discontinued by the consumer. Similar to the subscription example above, packages of absorbent articles can be sold in brick and mortar locations wherein the packages contain a code for operation of the software application to view data and information received from a sensor device according to the present disclosure.

[0080] FIG. 17 shows an exemplary kit 400 comprising a plurality of absorbent articles 402, two sensor devices 404, a camera 406, and two camera docking stations 408.

[0081] Sensor devices by themselves may also be offered for sale, which would include information on how to associate the sensor device with a disposable absorbent article.

[0082] While the discussion has focused on infants and patients, systems of the present invention are also applicable for elderly care. The sensors associated with such systems may be capable of association with an elderly's skin, durable undergarments, disposable absorbent articles, bed materials, bed pads, and/or clothing articles.

[0083] This application is a continuation of U.S. application Ser. No. 16/402,348, filed on May 3, 2019, which claims the benefit of U.S. Provisional Application Nos. 62/723,179,

filed on Aug. 27, 2018 and 62/666,989, filed on May 4, 2018, the entireties of which are all incorporated by reference herein.

[0084] The dimensions and values disclosed herein are not to be understood as being strictly limited to the exact numerical values recited. Instead, unless otherwise specified, each such dimension is intended to mean both the recited value and a functionally equivalent range surrounding that value. For example, a dimension disclosed as "40 mm" is intended to mean "about 40 mm."

[0085] Every document cited herein, including any cross referenced or related patent or application and any patent application or patent to which this application claims priority or benefit thereof, is hereby incorporated herein by reference in its entirety unless expressly excluded or otherwise limited. The citation of any document is not an admission that it is prior art with respect to any disclosure disclosed or claimed herein or that it alone, or in any combination with any other reference or references, teaches, suggests or discloses any such disclosure. Further, to the extent that any meaning or definition of a term in this document conflicts with any meaning or definition of the same term in a document incorporated by reference, the meaning or definition assigned to that term in this document shall govern.

[0086] While particular forms of the present disclosure have been illustrated and described, it would be obvious to those skilled in the art that various other changes and modifications can be made without departing from the spirit and scope of the disclosure. It should be understood that other forms may include more or less of each element shown in a given figure. Further, some of the illustrated elements may be combined or omitted. Yet further, an exemplary form may include elements that are not illustrated in the figures. The various aspects and forms disclosed herein are for purposes of illustration and are not intended to be limiting, with the true scope and spirit being indicated by the following claims.

1. A system for monitoring the basic needs of an infant, the system comprising:

- a. a data gathering module comprising:
 - i. a multi-use sensor device configured for attachment to and detachment from a disposable absorbent article, and comprising a urination event sensor, a bowel movement event sensor, a transmitter, a data processor for processing raw data from the urination event sensor or the bowel movement event sensor prior to transmitting data or information based on the raw data, and a non-volatile memory device capable of storing data from the urination event sensor, the bowel movement event sensor, and/or the data processor; and
 - ii. a secondary device that is not intimately associated with the infant but that is capable of obtaining status of an environment in which the infant is located; and
- b. a communication module comprising a software application that is operable on a computer device to display information related to data obtained by the data gathering module to a caregiver.

2. The system of claim 1, wherein the multi-use sensor device comprises a volatile organic compound sensor.

3. The system of claim 1, wherein the multi-use sensor device comprises a temperature sensor.

4. The system of claim 1, wherein the multi-use sensor device comprises a sensor capable of detecting at least one of the following: skatole, mercaptans, amines, volatile fatty acids, acetone, methyl acetate, and methanol.

5. The system of claim 1, wherein the multi-use sensor device comprises a motion sensor.

6. The system of claim 1, wherein the multi-use sensor device comprises a rechargeable battery.

7. The system of claim 1, wherein the secondary device comprises at least one of a temperature device, a humidity device, and a light source.

8. The system of claim 1, wherein the secondary device comprises an audio device.

9. The system of claim 1, wherein the secondary device comprises a camera.

10. The system of claim 1, wherein the secondary device comprises a smoke detector.

11. The system of claim 1, wherein the secondary device comprises a carbon monoxide sensor.

12. The system of claim 1, further comprising a plurality of disposable absorbent articles and wherein the multi-use sensor device comprises attachment hooks that are configured to engage nonwoven material used for an outer cover of the disposable absorbent articles.

13. The system of claim 1, further comprising a plurality of disposable absorbent articles each of which comprising a backsheet comprising a film that is liquid impermeable but that is breathable in that it allows vapors to escape from the absorbent articles.

14. A system for monitoring the basic needs of an infant, the system comprising:

a. a data gathering module comprising:

i. a multi-use sensor device configured for attachment to and detachment from a disposable absorbent article, and comprising a volatile organic compound sensor, a temperature sensor, a transmitter, and a non-volatile memory device capable of storing data from the volatile organic compound sensor and/or the temperature sensor prior to transmission of data; and

ii. a secondary device that is not associated with the infant but that is capable of obtaining status of an environment in which the infant is located; and

b. a communication module comprising a software application that is operable on a computer device to display information related to data obtained by the data gathering module to a caregiver.

15. The system of claim 14, wherein the multi-use sensor device comprises a rechargeable battery.

16. The system of claim 14, wherein the multi-use sensor device comprises an antenna.

17. The system of claim 14, further comprising a plurality of disposable absorbent articles each of which comprising a backsheet comprising a film that is liquid impermeable but that is breathable in that it allows vapors to escape from the absorbent articles.

18. (canceled)

19. (canceled)

20. (canceled)

* * * * *

专利名称(译)	用于监测婴儿基本需求的传感器设备和系统		
公开(公告)号	US20200060885A1	公开(公告)日	2020-02-27
申请号	US16/452693	申请日	2019-06-26
[标]申请(专利权)人(译)	宝洁公司		
申请(专利权)人(译)	宝洁公司		
当前申请(专利权)人(译)	宝洁公司		
[标]发明人	ARIZTI BLANCA		
发明人	ARIZTI, BLANCA REIDY, MARK		
IPC分类号	A61F13/42 A61B5/00		
CPC分类号	A61B5/0077 A61B5/7275 A61B2562/0219 A61B5/4809 A61B5/01 A61B5/11 A61F13/42 A61F2013/427 A61B2503/04 A61B5/002 A61F2013/424 A61B5/0022 A61B5/1118 A61B5/207 A61B5/6808 A61B5/68 A61B5/74 G16H40/67 G06Q10/087 G08B21/18 G08B21/20		
优先权	62/723179 2018-08-27 US		
外部链接	Espacenet USPTO		

摘要(译)

本文描述了用于监视婴儿的基本需求的传感器装置和系统，包括喂养，睡觉和/或排尿（排尿和/或排便）。

